

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent	12391326
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Savoie; Felix et al.

---

### Vehicle with a windshield assembly

---

#### Abstract

A vehicle comprising: a frame; a driver seat connected to the frame; a handlebar disposed forward of the driver seat, the handlebar rotatable about a steering column axis; a storage rack connected to the frame, the storage rack being disposed forward of the handlebar; a windshield support connected to the frame, the windshield support being disposed forward of the handlebar and rearward of the rack; and a windshield connected to the windshield support, the handlebar rotating relative to the windshield. A method of mounting the windshield to the vehicle, the method comprising: selecting the windshield support from first and second windshield supports, the second windshield support being taller than the first windshield support; connecting the selected windshield support to the frame of the vehicle forward of the driver seat and between the handlebar and the front storage rack; and connecting the windshield to the selected windshield support.

---

<b>Inventors:</b>	<b>Savoie; Felix (Sherbrooke, CA), Larrouy; Remi (Sherbrooke, CA)</b>
<b>Applicant:</b>	<b>BOMBARDIER RECREATIONAL PRODUCTS INC. (Valcourt, CA)</b>
<b>Family ID:</b>	<b>1000008763205</b>
<b>Assignee:</b>	<b>BOMBARDIER RECREATIONAL PRODUCTS INC. (Valcourt, CA)</b>
<b>Appl. No.:</b>	<b>18/490215</b>
<b>Filed:</b>	<b>October 19, 2023</b>

#### Prior Publication Data

<b>Document Identifier</b>	<b>Publication Date</b>
US 20240140550 A1	May. 02, 2024

#### Related U.S. Application Data

us-provisional-application US 63420135 20221028

---

## Publication Classification

**Int. Cl.:** B62J17/04 (20060101); B62J7/06 (20060101); B62K5/01 (20130101)

**U.S. Cl.:**

**CPC** B62J17/04 (20130101); B62J7/06 (20130101); B62K5/01 (20130101);

## Field of Classification Search

**CPC:** B62J (17/04); B62J (7/06); B62J (17/02); B62K (5/01)

---

## References Cited

### U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4606571	12/1985	Fujita	296/89	B62J 17/04
2002/0074820	12/2001	Gagne	296/78.1	B60J 1/04
2009/0146447	12/2008	Baretta	296/96.21	B60J 1/04
2014/0136076	12/2013	Novak	701/99	B62J 17/02
2021/0107584	12/2020	Sawada	N/A	B62J 17/04
2022/0055709	12/2021	Tamura	N/A	B62J 50/225
2023/0339560	12/2022	Tsai	N/A	B62J 17/04

### FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
3700761	12/1986	DE	N/A
102020126146	12/2023	DE	B62J 17/04
1958858	12/2007	EP	B62J 17/02
2923927	12/2014	EP	B62J 17/04
2362189	12/2010	ES	B62J 17/04
2592414	12/2015	ES	B62J 17/04
202000025822	12/2021	IT	N/A
H0752857	12/1994	JP	N/A
2023035571	12/2022	JP	B29C 45/14631
200404701	12/2003	TW	N/A
200918397	12/2008	TW	B62J 17/04
WO-2021105967	12/2020	WO	B62K 11/14

---

*Primary Examiner:* Brown; Drew J

*Attorney, Agent or Firm:* BCF LLP

---

## Background/Summary

REFERENCE TO RELATED APPLICATION (1) The present application claims priority to U.S. Provisional Patent Application No. 63/420,135, filed Oct. 28, 2022, the entirety of which is incorporated herein by reference.

## TECHNOLOGICAL FIELD

(1) The present technology relates to vehicles with a windshield assembly.

## BACKGROUND

(2) Recreational vehicles such as personal watercrafts (PWCs), all-terrain vehicles (ATVs), side-by-side off-road vehicles (SSVs), snowmobiles and the like are used for both utility and recreational purposes. Some such vehicles have a windshield which is connected to a frame of the vehicle and is independent of a handlebar. However, fixing the windshield to a part of the body of the vehicle may result in a reduction of space of storage and/or accessories.

(3) Therefore, there is a desire for windshield assemblies for recreational vehicles that are independent of the handlebar and do not result in a significant reduction of storage space.

## SUMMARY

(4) It is an object of the present technology to ameliorate at least some of the inconveniences present in the prior art.

(5) In one aspect, the present technology provides vehicle comprising: a frame; a driver seat connected to the frame; a handlebar disposed forward of the driver seat, the handlebar rotatable about a steering column axis; a storage rack connected to the frame, the storage rack being disposed forward of the handlebar; a windshield support connected to the frame, the windshield support being disposed forward of the handlebar and rearward of the rack; and a windshield connected to the windshield support, the handlebar rotating relative to the windshield.

(6) In some implementations, the windshield support extends upwardly from the frame.

(7) In some implementations, the windshield support comprises: a central portion which is connected to the frame and extends upwardly from the frame, a left wing portion extending forwardly from a left side of the central portion and connected to the windshield at a left region of the windshield; and a right wing portion extending forwardly from a right side of the central portion and connected to the windshield at a right region of the windshield.

(8) In some implementations, each of the left wing portion and the right wing portion has a distal surface which abuts the windshield and extends upwardly along the respective left and right regions of the windshield.

(9) In some implementations, each of the left wing portion and the right wing portion have one or more wing openings formed therein.

(10) In some implementations, the windshield defines windshield apertures, each of the windshield apertures being configured to receive a fastener therethrough for engagement with a corresponding windshield support aperture in the windshield support.

(11) In some implementations, the windshield apertures comprise a lower set of windshield apertures and an upper set of windshield apertures.

(12) In some implementations, the windshield apertures are configured such that the windshield can be connected to the windshield support at a first height from the frame or at a second height from the frame, the first and second heights being different.

(13) In some implementations, the vehicle further comprises a cover connected to the windshield on a forward side of the windshield, the cover covering at least some of the windshield apertures.

(14) In some implementations, the windshield support is connected to and supported by a panel which is connected to the frame.

(15) In some implementations, the windshield support is a primary windshield support, the vehicle further comprising a secondary windshield support connected to the frame, and the primary windshield support is connected to and supported by the secondary windshield support.

(16) In some implementations, the secondary windshield support comprises a storage compartment.

(17) In some implementations, the storage compartment has a front wall and a door, the door being rearward of the front wall, and the primary windshield support is mounted to the front wall of the storage compartment.

- (18) In some implementations, the vehicle further comprises a left wind deflector and a right wind deflector connected to a left side and a right side, respectively, of the storage compartment.
- (19) In some implementations, the vehicle further comprises a left wind deflector and a right wind deflector connected to the frame at a left side and a right side, respectively, of the windshield.
- (20) In some implementations, a lower edge of the windshield is lower than an upper edge of the left wind deflector and an upper edge of the right wind deflector.
- (21) In some implementations, a lower edge of the left wind deflector and a lower edge the right wind deflector windshield is lower than a lower edge of the windshield.
- (22) In some implementations, the vehicle further comprises a cargo box attached to the storage rack, the cargo box being forward of the windshield and having a lid.
- (23) In some implementations, the vehicle is an all-terrain vehicle; the driver seat is a straddle-type seat; and the vehicle comprises: a motor supported by the frame; and four wheels connected to the frame, at least two of the four wheels being operatively connected to and driven by the motor.
- (24) From another aspect, there is provided a method of mounting a windshield to a vehicle, the method comprising: selecting a windshield support from a first windshield support and a second windshield support, the second windshield support being taller than the first windshield support; connecting the selected windshield support to a frame of the vehicle at a position forward of a driver seat of the vehicle and between a handlebar of the vehicle and a front storage rack of the vehicle; and connecting the windshield to the selected windshield support.
- (25) In some implementations, connecting the windshield to the selected windshield support comprises: inserting a pair of fasteners through one of a first pair of windshield apertures and a second pair of windshield apertures defined in the windshield; and inserting the pair of fasteners in a pair of windshield support apertures defined in the selected windshield support; the windshield is at a first height relative to the frame when the pair of fasteners is inserted through the first pair of windshield apertures; the windshield is at a second height relative to the frame when the pair of fasteners is inserted through the second pair of windshield apertures; and the second height is greater than the first height.
- (26) For purposes of the present application, terms related to spatial orientation when referring to a vehicle and components in relation to the vehicle, such as “forwardly”, “rearwardly”, “left”, “right”, “top”, “bottom”, “upper”, “lower” “above” and “below”, are as they would be understood by a driver of the vehicle sitting thereon in an upright driving position, with the vehicle steered straight-ahead.
- (27) Implementations of the present technology each have at least one of the above-mentioned object and/or aspects, but do not necessarily have all of them. It should be understood that some aspects of the present technology that have resulted from attempting to attain the above-mentioned object may not satisfy this object and/or may satisfy other objects not specifically recited herein.
- (28) Additional and/or alternative features, aspects, and advantages of implementations of the present technology will become apparent from the following description, the accompanying drawings, and the appended claims.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

- (1) For a better understanding of the present technology, as well as other aspects and further features thereof, reference is made to the following description which is to be used in conjunction with the accompanying drawings, where:
- (2) FIG. 1 is a perspective view taken from a top, back, left side of a straddle-seat all-terrain vehicle (ATV), with a windshield assembly secured thereto;
- (3) FIG. 2 is a left side elevation view of the vehicle of FIG. 1;

- (4) FIG. 3 is a front elevation view of a portion of the vehicle of FIG. 1;
- (5) FIG. 4 is a back elevation view of the portion of the vehicle of FIG. 3;
- (6) FIG. 5 is a perspective view taken from a top, back, left side of the portion of the vehicle of FIG. 4;
- (7) FIG. 6 is a perspective view taken from a top, back, left side of the portion of the vehicle of FIG. 4 with a lid of a storage compartment open;
- (8) FIG. 7 is a perspective view taken from a top, back, left side of the portion of the vehicle of FIG. 4 with a partially exploded view of the windshield assembly;
- (9) FIG. 8 is a left elevation view of the portion of the vehicle of FIG. 4;
- (10) FIG. 9 is a left elevation view of the portion of the vehicle of FIG. 4, with the windshield assembly separated from the vehicle;
- (11) FIG. 10 is an exploded view of the windshield assembly of FIG. 1 taken from a top, back, left side;
- (12) FIG. 11 is an exploded view of the windshield assembly of FIG. 1 taken from a top, front, left side;
- (13) FIG. 12 is an exploded top plan view of the windshield assembly of FIG. 1;
- (14) FIG. 13 is a top plan view of the portion of the vehicle of FIG. 3;
- (15) FIG. 14 is a top plan view of the portion of the vehicle of FIG. 3, and including a cargo box with a lid;
- (16) FIG. 15 is a right elevation view of the portion of the vehicle and cargo box of FIG. 14; and
- (17) FIG. 16 is a perspective view taken from a top, front, right side of the portion of the vehicle and cargo box of FIG. 14 with the lid of the cargo box open.

#### DETAILED DESCRIPTION

(18) In the following description, an implementation of a windshield assembly **200** for a vehicle **10** will be described. The windshield assembly **200** that will be described herein is for a straddle-seat all-terrain vehicle **10** (hereinafter ATV) and is of a fixed-type, meaning that it is of a type wherein the windshield is independent of a handlebar of the ATV and does not move with the handlebar. It is contemplated that aspects of the windshield assembly **200** of the present technology could be used in other types of vehicles, such as three-wheeled vehicles, personal watercrafts (PWCs), motorcycles, and the like.

(19) Before describing the windshield assembly **200** in detail, the ATV **10** will be generally described. Referring to FIGS. 1 to 3, the ATV **10** has a front end **12** and a rear end **14** defined consistently with a forward travel direction of the ATV **10**. A longitudinal center plane **16** (FIG. 3) extends vertically and longitudinally through the lateral center of the ATV **10**. The ATV **10** has a frame **20**.

(20) A motor **22** (schematically shown in FIG. 2) is connected to the frame for powering the ATV **10**. The ATV **10** has two front wheels **24** and two back wheels **24** (omitted in FIG. 3). The wheels **24** are operatively connected to the motor **22** via a transmission (not shown). In the present implementation, the motor **22** is an internal combustion engine and the transmission is a continuously variable transmission, but other types of motors and transmissions are contemplated. Each of the wheels **24** is provided with low-pressure balloon tires adapted for off-road conditions and traversing rugged terrain. It is contemplated that other implementations of the ATV **10** could have only three wheels **24**. The two front wheels **24** are suspended from the frame **20** by left and right front suspension assemblies **30** while the two rear wheels **24** are suspended from the frame **20** by left and right rear suspension assemblies **30**.

(21) As best seen in FIGS. 1 and 2, the ATV **10** further includes a straddle seat **40** connected to the frame **20** for accommodating a driver of the ATV **10**. Driver footrests **50** are provided on either side of the driver seat **40** and are disposed vertically lower than the driver seat **40** to support the driver's feet. A steering assembly **80** is rotationally connected to the frame **20** to enable a driver to steer the ATV **10**. The steering assembly **80** includes a handlebar **82** connected to a steering column

assembly for actuating steering linkages operatively connected to the left and right front wheels **24**. The handlebar **82** is disposed forwardly of the driver seat **40**. The handlebar **82** is rotatable about a steering column axis **84** (FIG. 2). Other steering input devices, such as a steering wheel, could be used in different vehicles.

(22) A throttle operator **86** (FIGS. 1 and 2), in the form of a thumb-actuated throttle lever, is mounted to the handlebar **82**. Other types of throttle operators, such as a finger-actuated throttle lever and a twist grip, are also contemplated. A gear shifter located near the handlebar **82** is connected to the transmission and enables a driver to select one of a plurality of gear configurations for operation of the ATV **10**. In the illustrated implementation of the ATV **10**, the gear configurations include park, neutral, reverse, low, and high. It is contemplated that the sequence and/or number of gear configurations could be different than as shown herein. A display cluster **88**, including a number of gauges and buttons, is disposed forwardly of the steering assembly **80** (FIGS. 4 to 7).

(23) As best seen in FIG. 1, a plurality of body panels are provided on the vehicle **10** to conceal the internal components of the vehicle **10**, such as but not limited to cowlings **90** to cover the motor **22**, fenders **92** disposed over each of the wheels **24**, side panels **94** extending over lateral sides of the ATV **10**, and a front panel **96** extending over a top side of the ATV **10** forward of the handlebar **82**.

(24) A front rack **98** is provided, which is connected to the frame **20**, and mounted above the front panel **96**. The front rack **98** is disposed forward of the handlebar **82**. In certain implementations, the front rack **98** may be used to support a cargo box **200**, which will be described later with reference to FIGS. 14 to 16.

(25) A storage compartment **100** is provided forward of the handlebar **82** and rearward of the front rack **98**. As best seen in FIG. 5, the storage compartment **100** is forward of the display cluster **88**, in a dashboard region of the ATV **10**. The storage compartment **100** comprises walls **102** defining a storage chamber **104** (FIG. 6) and a lid **106** which can be opened to access the storage chamber **104**. At least one of the walls **102** is a forwardly facing wall **108**.

(26) The ATV **10** further includes other components such as an air intake system, an exhaust system, headlights, and the like. As it is believed that these components would be readily recognized by one of ordinary skill in the art, further explanation and description of these components will not be provided herein.

(27) The windshield assembly **200** will now be described in more detail with reference to FIGS. 4 to 13.

(28) The windshield assembly **200** comprises a windshield **202** connected to a windshield support **204**. The windshield support **204** is connected to the frame **20** of the ATV **10** via the storage compartment **100**. The windshield support **204** is disposed forward of the handlebar **82** and rearward of the front rack **98**. The windshield support **204** thus connected is independent of the handlebar **82**.

(29) The windshield support **204** is mounted to the storage compartment **100** which is itself connected to the frame **20**. More specifically, the windshield support **204** is mounted to the forwardly facing wall **108** of the storage compartment **100**. In other implementations (not shown), the windshield support **204** may be connected directly to the front panel **96**, or to the frame **20**.

(30) The windshield support **204** is configured to space the windshield **202** at a given height from the front panel **96** and at a given longitudinal distance from the handlebar **82**. In this respect, and as best seen in FIGS. 11 and 12, the windshield support **204** comprises a central portion **206** which is connected to the forwardly facing wall **108** of the storage compartment **100** and which extends upwardly from the front panel **96**; a left wing portion **208** which extends forwardly from a left side **210** of the central portion **206**; and a right wing portion **212** which extends forwardly from a right side **214** of the central portion **206**. The left wing portion **208** terminates in a left distal end **216**. The left distal end **216** is connected to the windshield **202** at a left region **218** of the windshield **202**. The right wing portion **212** terminates in a right distal end **220**. The right distal end **220** is

connected to the windshield **202** at a right region **222** of the windshield **202**. The left distal end **216** and the right distal end **220** each extend generally vertically along the back of the respective left and right regions of the windshield, **218**, **222**.

(31) The left wing portion **208** has a left wing opening **224** formed therein and the right wing portion **212** has a right wing opening **226** formed therein. In other implementations, there are no openings in the left and right wing portions **224**, **226**. In other implementations, there is more than one opening in the left and right wing portions **224**, **226**.

(32) The windshield **202** has windshield apertures **228** extending therethrough, each windshield aperture **228** extending between a front side **230** and a back side **232** of the windshield **202**. The windshield apertures **228** are defined in the windshield **202** as pairs. For each pair of the windshield apertures **228**, one of the pair is defined in the left region **218** of the windshield **202** and the other of the pair is defined in the right region **222** of the windshield **202**. On each of the left and right regions **218**, **222** of the windshield **202**, the windshield apertures **228** are grouped as a lower set **238** of the windshield apertures **228** and an upper set **240** of the windshield apertures **228**. The pairs of windshield apertures **228** in the upper set **240** are more widely laterally spaced from each other than the pairs of windshield apertures **228** in the lower set **238**. The windshield apertures **228** of each pair are positioned one above each other. As illustrated, there are three pairs of windshield apertures **228** in the lower set **238** and three pairs of windshield apertures **228** in the upper set **240**. The multiple aperture pairs in each of the lower set **238** and the upper set **240** permit a height of the windshield **202** relative to the frame **20** to be adjusted, in a manner that will be described below.

(33) An upper cover pair **240a** of the windshield apertures **228** in the upper set **240**, and a lower cover pair **238a** of the windshield apertures **228** in the lower set **238** are used to attach a cover **234** to hide at least some of the windshield apertures **228**. In this respect, there is provided a left cover **234a** which is sized and shaped to extend over the windshield apertures **228** on the left region **218** of the windshield, and a right cover **234b** which is sized and shaped to extend over the windshield apertures **228** on the right region **222** of the windshield **202**. Each of the left cover **234a** and the right cover **234b** has an upper projection **235a** and a lower projection **235b** which are received into the respective apertures of the upper cover pair **240a** of the windshield apertures **228** in the upper set **240**, and the lower cover pair **238b** of the windshield apertures **228** in the lower set **238**. The covers **234** are removably connectable to the front side **230** of the windshield **202**. In certain implementations, one or both of the left cover **234a** and the right cover **234b** may be omitted.

(34) With continued reference to FIG. **11**, the windshield support apertures **236** comprise a lower pair **242** and an upper pair **244**. One windshield support aperture **236** of the lower pair **242** is defined within the distal end **216** of the left wing portion **208**, and the other windshield support aperture **236** of the lower pair **242** is defined within the distal end **220** of the right wing portion **212**. Similarly, one windshield support aperture **236** of the upper pair **244** is defined within the distal end **216** of the left wing portion **208**, and the other windshield support aperture **236** of the upper pair **244** is defined within the distal end **220** of the right wing portion **212**. The upper pair **244** of the windshield support apertures **236** are positioned upwardly, on the respective distal ends **216**, **220** of the windshield support apertures **236**, of the lower pair **242**.

(35) The windshield **202** is connected to the windshield support **204** by aligning one pair of the lower set **238** of the windshield apertures **228** with the lower pair **242** of the windshield support apertures **236**, and one pair of the upper set **240** of windshield apertures **228** with the upper pair **244** of the windshield support apertures **236**, and extending a fastener **246** through each aligned aperture of the windshield **202** and the windshield support **204**. The windshield assembly **100** is provided with four fasteners **246** for connecting the windshield **202** and the windshield support **204**. Each windshield aperture **228** and windshield support aperture **236** is configured to receive the fasteners **246**. Connection of the windshield **202** to the windshield support **204** is thus achieved by the fasteners **246** extending at least partially into, and between, respective windshield and windshield support apertures **228**, **236**. The fasteners **246** may comprise grommets, pegs or any

other configuration permitting removal and installation from the windshield and windshield support apertures **228**, **236**. This can permit convenient repositioning of the windshield **202**.

(36) As mentioned above, there are multiple windshield apertures **228** in each of the lower set **238** and the upper set **240**, permitting an adjustment of the height of the windshield **202** relative to the frame **20** and the windshield support **204**. More specifically, the three pairs of windshield apertures **228** in the lower and upper sets **238**, **240** can permit the windshield to be positioned at three different heights: lowest, highest and medium heights relative to the windshield support **204**.

(37) When the windshield **202** is connected to the windshield support **204** using the lowermost pair of the windshield apertures **228** of each of the lower set **238** and the upper set **240**, the height of the windshield **202** is at a highest height relative to the windshield support **204**. When the windshield **202** is connected to the windshield support **204** using the uppermost pair of the windshield apertures **228** of each of the lower set **238** and the upper set **240**, the height of the windshield **202** is at a lowest height relative to the windshield support **204**. When the windshield **202** is connected to the windshield support **204** using the middle pair of the windshield apertures **228** of each of the lower set **238** and the upper set **240**, the height of the windshield **202** is at a height between the lowest and highest heights relative to the windshield support **204**. In other implementations, the windshield **202** can be provided with more than three windshield **202** height options or less than three windshield **202** height options.

(38) Further height options of the windshield **202** can be obtained using windshield supports **204** having different sizes of the windshield support **204**. For example, windshield supports **204** having the central portion **206** with different heights can be provided as a kit. In some implementations, the kit includes three different windshield supports **204** each having a different height, thus providing an option of nine different heights of the windshield (three height adjustments per windshield support **204**).

(39) Further height options of the windshield **202** can be obtained using windshields **202** of different lengths. For example, windshields **202** having different lengths can be provided as a kit together with other components of the windshield assembly **200**.

(40) The windshield assembly **200** further comprises a left wind deflector **248** and a right wind deflector **250** connected to a left side and a right side, respectively, of the storage compartment **100**. Each of the left wind deflector **248** and the right wind deflector **250** has a lower edge **252** and an upper edge **254** (FIGS. 3 and 4). The lower edge **252** of the left wind deflector **248** and the right wind deflector **250** is lower than a lower edge **256** of the windshield **202** (FIG. 3). This can protect the driver from oncoming flow of air when the ATV **10** is in motion. The left wind deflector **248** and a right wind deflector **250** may deflect any wind that passes under the windshield **202**. The lower edge **256** of the windshield **202** is lower than the respective upper edges **254** of the left wind deflector **248** and the right wind deflector **250** (FIG. 5).

(41) In other implementations, the left wind deflector **248** and the right wind deflector **250** are connected to the windshield **202**. The left wind deflector **248**, the right wind deflector **250** and the windshield **202** may be one piece. In yet other implementations, the left wind deflector **248** and the right wind deflector **250** may be omitted.

(42) Referring now to FIGS. 14 to 16, in some implementations, the ATV includes a cargo box **260** attached to the front rack **98**. The cargo box **260** is disposed forward of the windshield **202** and the windshield support **204**. The cargo box **260** includes a container portion **262** defining a cargo chamber **264** and a lid **266** connected to the container portion **262** and moveable between closed and open positions. As best seen in FIG. 16, the lid **266** is connected to the container portion **262** such that the lid **266** opens rearwardly so that a user can access the cargo chamber **264** from the front end **12** of the ATV. The cargo box **260** can be implemented in any suitable manner.

(43) By virtue of the positioning of the windshield support **204** forward of the handlebar **82** and rearward of the front rack **98**, the lid **266** of the cargo box **260** can be opened without interfering with the windshield **202**.



(44) With reference to FIGS. 1 to 13, an illustrative scenario describing the installation and use of the windshield assembly **200** with the ATV **10** is provided below.

(45) Initially, the windshield assembly **200** is separate from the ATV **10**. When a user desires to install the windshield assembly **200** on the ATV **10**, the user first selects the windshield support **204** with a desired height from a first windshield support and a second windshield support, the second windshield support being taller than the first windshield support.

(46) Next, the user connects the selected windshield support to the frame **20** of the ATV **10** at a position forward of the seat **40** and between the handlebar **82** of the ATV **10** and the front rack **98** of the ATV **10**.

(47) Then, the user connects the windshield **202** to the selected windshield support **204**. Connecting the windshield **202** to the selected windshield support **204** comprises inserting a pair of the fasteners **246** through a pair of the windshield apertures **228** in the lower set **238** and a pair of windshield apertures **228** in the upper set **240** such that they protrude outwardly from the back side **232** of the windshield. The pair of the windshield apertures **228** are selected from a plurality of windshield apertures **228** in each of the lower set **238** and the upper set **240** according to the desired height of the windshield **202**. The protruding portions of the fasteners **246** are inserted into the windshield support apertures **236**. It will be appreciated that the windshield **202** is at a first height relative to the frame **20** when the fasteners **246** are inserted through one pair of the windshield apertures **228** in the lower and upper sets **238, 240** and at another different height when the fasteners **246** are inserted through another pair of the windshield apertures **228** in the lower and upper sets **238, 240** upper sets **238, 240**.

(48) Next, the covers **234a, 234b** are attached, one on each of the left region **218** and the right region **222**, at the front side **230** of the windshield **202** by inserting the upper and lower projections **235a, 235b** into the upper cover pair **240a** of the windshield apertures **228** in the upper set **240**, and the lower cover pair **238a** of the windshield apertures **228** in the lower set **238**.

(49) Finally, the left and right wind deflectors **248, 250** are attached to the storage compartment **100**. It will be appreciated that the left and right wind deflectors **248, 250**, when present, can be attached to the storage compartment **100** at any stage, such as before the connection of the windshield **202** to the selected windshield support **204**.

(50) In other implementations, the windshield assembly **200** can be installed on the ATV **10** as follows.

(51) Initially, the windshield assembly **200** is separate from the ATV **10**. When a user desires to install the windshield assembly **200** on the ATV **10**, the user first selects the windshield **202** with a desired length from a first windshield and a second windshield, the second windshield being longer than the first windshield.

(52) Next, the user connects the selected windshield **202** to the windshield support **204**. Connecting the selected windshield **202** to the windshield support **204** comprises inserting a pair of the fasteners **246** through a pair of the windshield apertures **228** in the lower set **238** and a pair of windshield apertures **228** in the upper set **240** such that they protrude outwardly from the back side **232** of the windshield. The pair of the windshield apertures **228** are selected from a plurality of windshield apertures **228** in each of the lower set **238** and the upper set **240** according to the desired height of the windshield **202**. The protruding portions of the fasteners **246** are inserted into the windshield support apertures **236**. It will be appreciated that the windshield **202** is at a first height relative to the frame **20** when the fasteners **246** are inserted through one pair of the windshield apertures **228** in the lower and upper sets **238, 240** and at another different height when the fasteners **246** are inserted through another pair of the windshield apertures **228** in the lower and upper sets **238, 240** upper sets **238, 240**.

(53) The windshield support **204** with the windshield **202** attached thereto is connected to the frame **20** of the ATV **10** at a position forward of the seat **40** and between the handlebar **82** of the ATV **10** and the front rack **98** of the ATV **10**.

(54) Next, the covers **234a**, **234b** are attached, one on each of the left region **218** and the right region **222**, at the front side **230** of the selected windshield **202** by inserting the upper and lower projections **235a**, **235b** into the upper cover pair **240a** of the windshield apertures **228** in the upper set **240**, and the lower cover pair **238a** of the windshield apertures **228** in the lower set **238**. It will be appreciated that the covers **234a**, **234b** may be attached to the selected windshield **202** before the windshield support **204** is connected to the frame **20** of the ATV **10**.

(55) Finally, the left and right wind deflectors **248**, **250** are attached to the storage compartment **100**. It will be appreciated that the left and right wind deflectors **248**, **250**, when present, can be attached to the storage compartment **100** at any stage, such as before the connection of the windshield **202** to the selected windshield support **204**.

(56) Modifications and improvements to the above-described implementations of the present technology may become apparent to those skilled in the art. The foregoing description is intended to be exemplary rather than limiting. The scope of the present technology is therefore intended to be limited solely by the scope of the appended claims.

## Claims

1. A vehicle comprising: a frame; a driver seat connected to the frame; a handlebar disposed forward of the driver seat, the handlebar rotatable about a steering column axis; a storage rack connected to the frame, the storage rack being disposed forward of the handlebar; a primary windshield support connected to the frame, the primary windshield support being disposed forward of the handlebar and rearward of the rack; a secondary windshield support connected to the frame, the primary windshield support being connected to and supported by the secondary windshield support; the secondary windshield support comprising a storage compartment, the storage compartment has a front wall and a door, the door being rearward of the front wall, and the primary windshield support being mounted to the front wall of the storage compartment; and a windshield connected to the primary windshield support, the handlebar rotating relative to the windshield.
2. The vehicle of claim 1, wherein the primary windshield support extends upwardly from the frame.
3. The vehicle of claim 1, wherein the primary windshield support comprises: a central portion which is connected to the frame and extends upwardly from the frame, a left wing portion extending forwardly from a left side of the central portion and connected to the windshield at a left region of the windshield; and a right wing portion extending forwardly from a right side of the central portion and connected to the windshield at a right region of the windshield.
4. The vehicle of claim 3, wherein each of the left wing portion and the right wing portion has a distal surface which abuts the windshield and extends upwardly along the respective left and right regions of the windshield.
5. The vehicle of claim 3, wherein each of the left wing portion and the right wing portion have one or more wing openings formed therein.
6. The vehicle of claim 1, wherein the windshield defines windshield apertures, each of the windshield apertures being configured to receive a fastener therethrough for engagement with a corresponding windshield support aperture in the primary windshield support.
7. The vehicle of claim 6, wherein the windshield apertures comprise a lower set of windshield apertures and an upper set of windshield apertures.
8. The vehicle of claim 6, wherein the windshield apertures are configured such that the windshield can be connected to the primary windshield support at a first height from the frame or at a second height from the frame, the first and second heights being different.
9. The vehicle of claim 6, further comprising a cover connected to the windshield on a forward side of the windshield, the cover covering at least some of the windshield apertures.
10. The vehicle of claim 1, wherein the primary windshield support is connected to and supported

by a panel which is connected to the frame.

11. The vehicle of claim 1, further comprising a left wind deflector and a right wind deflector connected to a left side and a right side, respectively, of the storage compartment.

12. The vehicle of claim 11, wherein a lower edge of the windshield is lower than an upper edge of the left wind deflector and an upper edge of the right wind deflector; and a lower edge of the left wind deflector and a lower edge of the right wind deflector windshield is lower than a lower edge of the windshield.

13. The vehicle of claim 1, wherein: the vehicle is an all-terrain vehicle; the driver seat is a straddle-type seat; and the vehicle comprises: a motor supported by the frame; and four wheels connected to the frame, at least two of the four wheels being operatively connected to and driven by the motor.

14. A method of mounting a windshield to a vehicle, the method comprising: selecting a windshield support from a first windshield support and a second windshield support, the second windshield support being taller than the first windshield support; connecting the selected windshield support to a frame of the vehicle at a position forward of a driver seat of the vehicle and between a handlebar of the vehicle and a front storage rack of the vehicle; connecting the windshield to the selected windshield support.

15. The method of claim 14, wherein: connecting the windshield to the selected windshield support comprises: inserting a pair of fasteners through one of a first pair of windshield apertures and a second pair of windshield apertures defined in the windshield; and inserting the pair of fasteners in a pair of windshield support apertures defined in the selected windshield support; the windshield is at a first height relative to the frame when the pair of fasteners is inserted through the first pair of windshield apertures; the windshield is at a second height relative to the frame when the pair of fasteners is inserted through the second pair of windshield apertures; and the second height is greater than the first height.

---