

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12393959
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Kiani; Abbas et al.

System and method for offering network slice as a service

Abstract

A method includes defining a first specification for a first network slice, determining a first equilibrium value for a first time period for the first network slice offering, receiving a first bid price for the first network slice for the first time period from a first customer, comparing the first equilibrium value to the first bid price; and providing services using the network slice to the customer during the time period in accordance with the first specification and the bid price if the bid price meets or exceeds the equilibrium value.

Inventors:	Kiani; Abbas (Aberdeen, NJ), Hashemi; Seyed (Johns Creek, GA)
Applicant:	AT&T Intellectual Property I, L.P. (Atlanta, GA)
Family ID:	1000008765075
Assignee:	AT&T Intellectual Property I, L.P. (Atlanta, GA)
Appl. No.:	18/609487
Filed:	March 19, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240221015 A1	Jul. 04, 2024

Related U.S. Application Data

division parent-doc US 18187450 20230321 US 11961101 child-doc US 18609487
division parent-doc US 16802342 20200226 US 11636503 20230425 child-doc US 18187450

Publication Classification

Int. Cl.: G06Q30/00 (20230101); G06N20/00 (20190101); G06Q30/0201 (20230101); G06Q30/08 (20120101); H04L12/00 (20060101); H04L12/46 (20060101); H04L41/00 (20220101); H04L41/0895 (20220101); H04L41/12 (20220101); H04L41/40 (20220101)

U.S. Cl.:

CPC G06Q30/0206 (20130101); G06N20/00 (20190101); G06Q30/08 (20130101); H04L12/4641 (20130101); H04L41/0895 (20220501); H04L41/12 (20130101); H04L41/40 (20220501);

Field of Classification Search

CPC: G06Q (30/00); G06Q (10/00-50/00); G06N (20/00); H04L (41/0895); H04L (41/40); H04L (12/4641); H04L (41/12)

USPC: 705/7.35

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2011/0276447	12/2010	Paul et al.	N/A	N/A
2015/0032563	12/2014	Moser	705/26.3	G06Q 30/08
2017/0039633	12/2016	Yenisetty et al.	N/A	N/A
2017/0180213	12/2016	Li et al.	N/A	N/A
2018/0220008	12/2017	Reith	N/A	H04L 47/821
2018/0220358	12/2017	Reith	N/A	H04W 48/02
2018/0248815	12/2017	Cui	N/A	H04L 43/04
2018/0317133	12/2017	Sciancalepore	N/A	H04W 24/02
2020/0106680	12/2019	Chen	N/A	H04L 41/20
2020/0195495	12/2019	Parker et al.	N/A	N/A
2020/0226675	12/2019	Mitra	N/A	G06N 3/084
2020/0257566	12/2019	Ganguli et al.	N/A	N/A
2020/0260218	12/2019	Karimli et al.	N/A	N/A
2021/0112428	12/2020	Young et al.	N/A	N/A
2021/0360401	12/2020	Marinho et al.	N/A	N/A
2021/0392501	12/2020	Buyukdura	N/A	N/A
2021/0392572	12/2020	Thantharate et al.	N/A	N/A
2023/0217362	12/2022	Sharma et al.	N/A	N/A
2023/0230117	12/2022	Kiani et al.	N/A	N/A

Primary Examiner: Iqbal; Mustafa

Attorney, Agent or Firm: Guntin & Gust, PLC

Background/Summary

CROSS REFERENCE TO RELATED APPLICATION(S) (1) This application is a divisional of U.S. patent application Ser. No. 18/187,450, filed on Mar. 21, 2023, which is a divisional of U.S. patent application Ser. No. 16/802,342, filed on Feb. 26, 2020 (now U.S. Pat. No. 11,636,503). All sections of the aforementioned application(s) and/or patent(s) are incorporated herein by reference in their entirety.

TECHNICAL FIELD

(1) This disclosure is directed to systems and methods for specifying network slice as a service offering.

BACKGROUND

(2) In 5G networks, Network Slice as a Service (NSaaS) may be used for enterprises that require isolated radio resource allocation in on-premise deployments. In NSaaS, the enterprise customer, e.g., a factory or campus, has the control or ownership of its network slices including the radio resources. Using software defined networks by a network service provider goes a long way towards having the capability for enterprises to spin up the resources for each customer as they are needed. (3) However, this begs the question as to how and under what terms the network provider should make those resources available. Enterprise customers want ready access to network slice instances (NSIs) but typically would not want to pay for unused network capacity. Network providers need to be able to economically and efficiently provide NSIs and include the granularity of any particular NSI in its pricing models by taking into consideration its enterprise customers' location and availability of resources at different network domains, e.g., access, edge, and core. In fact, the traditional charging and policy capabilities are not suitable or flexible for the paradigm of NSaaS where NSIs must be offered in a sizable manner and with adjustable values.

SUMMARY

(4) The present disclosure is directed to a method including defining a first specification for a first network slice, determining a first equilibrium value for a first time period for the first network slice, receiving a first bid price for the first network slice for the first time period from a first customer, comparing the first equilibrium value to the first bid price, and providing services using the network slice to the customer during the time period in accordance with the first specification and the bid price if the bid price meets or exceeds the equilibrium value. The first specification may include a network topology and performance requirements. The equilibrium value may be calculated based on the minimum cost to provide the service using the network slice or alternatively, the equilibrium value may be calculated based on a location that the network slice will be instantiated or may be based on market supply and demand in a particular location and for the first time period.

(5) In an aspect, the method may further including determining a second equilibrium value for a second time period for the first network slice; receiving a second bid price for the second time period for the first network slice, comparing the second equilibrium value and the second bid price, and providing service using the network slice to the customer if the second bid price meets or exceeds the second equilibrium value. The first bid price may be calculated based on a historical price for the network slice for a similar time period. In an aspect, the first bid price may be calculated by a machine learning algorithm.

(6) The disclosure is also directed to a method including defining a first specification for a first network slice, analyzing historical pricing for the first network slice, generating a first bid price for the first network slice for a first time period, and if the first bid price is accepted, receiving the service using the first network slice in accordance with the first specification. The first bid may be accepted if the first bid meets or exceeds an equilibrium value. The method may further include if the first bid is not accepted, then increasing the first bid to a second bid and receiving service using the network slice in accordance with the first specification if the second bid price is accepted. The analyzing step may include a machine learning algorithm to determine a target equilibrium value

and the first bid price is set equal to or greater than the target equilibrium value.

(7) The disclosure is also directed to a system including a software defined network (SDN) controller, a software defined network managed by the SDN controller and wherein the software defined network has a first virtual network function (VNF) topology, a second VNF topology and a third VNF topology and wherein each of the first VNF topology, the second VNF topology and the third VNF topology has a set of performance requirements associated therewith, an input-output interface, a processor coupled to the input-output interface wherein the processor is further coupled to a memory, the memory having stored thereon executable instructions that when executed by the processor cause the processor to effectuate operations including defining a network slice specification using at least one of the first VNF topology, the second VNF topology or the third VNF technology and the associated performance requirements, determining a first equilibrium value for a network slice configured in accordance with the network slice specification, receiving a first bid price for the network slice, comparing the first bid price to the equilibrium value and providing service using the network slice in accordance with the network slice specification based on the comparing step. The first VNF topology may include an access cloud architecture and includes an SDN radio receiving unit in communication with a base station, an SDN access evolved packet core (EPC), and a first transport layer between the SDN radio receiving unit and the SDN access EPC. The second VNF topology may include an edge cloud architecture and includes an edge SDN EPC and there is a second transport layer between the first VNF topology and the second VNF topology. The third VNF topology may include a core cloud architecture and includes a core SDN EPC and there is a third transport layer between the second VNF topology and the third VNF topology. The operations may further include determining a second equilibrium value for a second time period for the network slice, receiving a second bid price for the second time period for the first network slice, comparing the second equilibrium value and the second bid price, and providing the network slice to the customer if the second bid price meets or exceeds the second equilibrium value. The system may further include an historical database accessible by the customer and the first bid price is calculated using data from the historical database. The first bid price may be calculated using a machine learning algorithm in which the machine learning algorithm may include linear regression analysis.

(8) This summary is provided to introduce a selection of concepts in a simplified form that are further described below in the Detailed Description. This Summary is not intended to identify key features or essential features of the claimed subject matter, nor is it intended to be used to limit the scope of the claimed subject matter. Furthermore, the claimed subject matter is not limited to limitations that solve any or all disadvantages noted in any part of this disclosure.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) Reference will now be made to the accompanying drawings, which are not necessarily drawn to scale.
- (2) FIG. 1 illustrates an exemplary 5G system topology for implementing network slice as a service.
- (3) FIG. 2 illustrates an exemplary matrix of network slice types and associated performance requirements for those network slice types.
- (4) FIG. 3 illustrates an exemplary flow diagram of the specification and auction process from the network provider side in accordance with the present disclosure.
- (5) FIG. 4 illustrates an exemplary flow diagram of the specification and bid process from the customer side in accordance with the present disclosure.
- (6) FIG. 5 illustrates a schematic of an exemplary network device.

(7) FIG. 6 illustrates an exemplary communication system that provides wireless telecommunication services over wireless communication networks.

(8) FIG. 7 is a representation of an exemplary network.

(9) FIG. 8 is a representation of an exemplary hardware platform for a network.

DETAILED DESCRIPTION

(10) System Overview. This disclosure is directed to a novel system and method for a resource and topology aware NSI valuation approach to render NSIs to the customers. The disclosure includes a new model for service provider NSI specifications by providing a model that can be extended and implemented by service providers as a service catalog for network slice services. In conjunction with that model, the disclosure includes a time-slotted NSI valuation approach wherein the service provider is able to set and reset the economic value for each type of NSI for a particular time frame. In an example, the values may be set and reset at the beginning of a given time frame such as 15 minutes.

(11) For the NSI specification, delivery and pricing models to operate efficiently, the disclosure provides processes on both the provider side and the customer side that may be implemented. For the purposes of this disclosure, unless otherwise specified, the term “provider” will mean a network service provider or a network service reseller that is offering NSaaS to its customers. The term “customer” will mean the purchasers of NSaaS by enterprise customers for its own consumption or that of its organization, cooperative customers purchasing and using NSaaS for its members, or network resellers who are purchasing and reselling NSaaS to its own customers.

(12) Provider Side: On the network service provider side, the service provider may offer customers a set of NSIs. Such NSIs may be provisioned as different types of NSIs, each with a different KPI for the amount of expected or maximum traffic. For example, one type of NSI may have a specification which includes a maximum latency of “x” milliseconds for a maximum allowed traffic of “y” bits, while a second type of NSI may have a specification which includes a longer maximum latency of “2x” milliseconds but for a higher maximum allowed traffic of “2y” bits.

(13) The various types of NSIs may also follow different topologies and different resource-based requirements. To manage the fluctuations in consumer demands while taking into consideration of the limitations of available resources, the service provider may consider a flexible NSI valuation method in which the resources are valued according to the demands. In such a case, the service provider may update the value for each type of NSI at the beginning of a time frame wherein the value depends on available resources and demands.

(14) Customer Side: The NSI customers may submit their NSI requirements and demand bids for the offered NSIs stating their maximum willingness to pay for their desired NSI type. The maximum willingness to pay can be decided by consulting an NSI value history. In an aspect, customers may submit their bids at any time even if the service provider begins an auction at a predefined time interval. Demand bids may be submitted based on the required NSI type. At the time of the auction, bids above a certain threshold value are accepted and NSaaS is provided, while bids below the threshold are rejected and no NSaaS is provided.

(15) Resource and Topology Aware Auction: The service provider may initiate an auction at predetermined time intervals. To do so, the service provider may decide the threshold value of the NSIs, which may depend on the number of served bids for each type of NSI. The service provider may also determine the assignments of the VNF among the various cloud locations based on demand or anticipated demand. This may result in a local valuation approach in which the value of a specific type of NSI varies from one location to another based on the available radio resources and traffic characteristics of supply and demand. In an aspect, all the served bids in one AP location may pay an identical value, e.g., equilibrium value per instance of an NSI type. In another aspect, for a given type of NSI at each AP location, only those bids whose respective willingness to pay are greater than or equal to the equilibrium value may be served with their desired NSIs.

(16) This NSI value may be derived based on the available resources, the required resources to

instantiate and run each type of NSI based on service catalog specifications, submitted demand bids including desired type of NSI, maximum willingness to pay, the AP location of customer, the cost of running each type of NSI (e.g., electricity cost, operational expense costs, etc.) In considering the foregoing, the service provider may determine an equilibrium value for each type of NSI at each AP location and then instantiate or de-allocate the VMs at different cloud locations. In this manner, the service provider may be able to maximize the total value for each network slice instance while at the same time ensuring that the value of each network slice instance is greater than the cost to provide it. For the purposes of this disclosure and the appended claims, the term equilibrium value will be used to designate the minimum acceptance price per the NSI per the time period in a particular location, regardless of how the equilibrium value is calculated. This means that the bid price must meet or exceed the equilibrium value for the requested NSI to be provided to the customer.

(17) Operating Environment. The system and method provided herein allows for the provision of network slice instances that meet the requirements of a customer in an auction environment. Network slicing is an end-to-end concept where the user or operator of a network slice views the network slice as a separate logical network having similar properties of a dedicated network (e.g. separate management and optimization), but in fact is realized using a common infrastructure (processing, transport, radio) which is shared with other network slices. Physical network resources are separated from the logical network using the principles of Network Function Virtualization (NFV) and Software Defined Networking (SDN).

(18) With reference to FIG. 1, there is shown a system **10** having three types of topology-based NSIs. The radio access network, known as NG-RAN in 5G terminology, comprises a set of radio base stations connected to the 5G core network and to each other. The NG-RAN often includes a centralized unit (CU) **18**, distributed units (DU) **15** and a radio receiver unit (RU) **11** which may be deployed in various configurations depending on the various needs of customers. A single base station may be in communication with and provide service to multiple RUs **11**. The topology based NSIs may be partitioned along virtual network functions with the partitions being an access cloud (AC) topology **12**, edge cloud (EC) topology **16** and core cloud (CC) topology **20**. Within each type of topology, there may be associated functionality. For example, the access cloud topology **12** may include the RU functionality **11**, fronthaul transport **13**, DU functionality **16** and an access Evolved Packet Core (EPC) functionality **14**. This topology may provide customers some or all of the NSI functionality required and thus may be designated as an NSI specification.

(19) Other customers may need additional NSI functionality and use the AV topology **12** as a front end to the edge cloud topology **16**. The edge cloud topology **16** may include mid-haul transport **17**, CU functions **18**, and edge-based access to EPC functionality **19**. Finally, other customers may specify an NSI core cloud topology **20** that may include access to the core network through backhaul transport **21** to the core EPC **22**.

(20) As such, customers may access EPC functions deployed at the access cloud **12**, edge cloud **16** and/or the core cloud **20**. Moreover, within each topology-based type of NSI (i.e., AC, EC, and CC), there may be different resource-based types of NSI, which may, for example, be classified as Large, XLarge, and 2Xlarge. For example, Large AC and XLarge AC NSIs may be differentiated based on the allocated resources in which the CPU cores to be allocated to different network functions or the allocated bandwidth between different transport links.

(21) There is also shown an SDN controller **23** which may include separate control planes and data planes to set up and control the network virtualization functions. The SDN controller may include functionality to instantiate virtual network functions, allocate virtual network functions to particular network slices, balance the load across physical resources, and act as a network orchestrator. The SDN controller **23** may interface with the various functionalities performed by each network layer to coherently manage each network slice request. As such, the SDN controller **23** enables an efficient and flexible network slice creation that can be configured and reconfigured during its life-

cycle. Operationally, the SDN controller **23** may control end-to-end service management which includes mapping of the various network slices instances expressed in terms of requirements with suitable network functions capable of satisfying the service constraints. The SDN controller **23** may provide for the virtualization of the physical network resources in order to simplify the resources management operations performed to allocate network functions. Finally, the SDN controller **23** may manage the life-cycle of the network slices, including performance monitoring to dynamically reconfigure each slice to accommodate possible SLA requirements modifications. It will be understood that while the SDN controller **23** is shown as a single component, the SDN controller **23** may be composed of multiple components and/or service orchestrators.

(22) There is also shown an historical database **24** which may, for example, include one or more of historical pricing per NSI specification and performance criteria, equilibrium values, winning or losing bids as a function of location, time periods, maintenance, special events, emergencies and other factors which may affect access to and pricing of NSI assets. While shown as part of the network **10**, it will be understood that the historical database **24** may be operated by or on behalf of a service provider or by or on behalf of a customer or by a third party or, alternatively the historical database **24** may be configured to be accessed by either a service provider, customer or third party.

(23) FIG. **2** is an exemplary matrix which may provide a catalog of network slices to be made available by a service provider to its customers. Along the left column is a set of network slice specifications, which may, for example, include a set of service level agreement (SLA) performance requirements. As an example only, those slices shown are AC Large, AC XLarge, AC 2XLarge, EC Large, EC XLarge, and EC 2Xlarge, CC Large, CC Xlarge, and CC 2Xlarge. Across the top of the matrix are the particular specifications that may be offered by the service provider. It will be understood that these categories are exemplary only and other categories of specifications may be possible and are included within the scope of the present disclosure and appended claims.

(24) These specifications may include the maximum number of subscribers, the maximum throughput per subscriber, the maximum number of traffic flows per subscriber, guaranteed end-to-end latency, guaranteed RAN latency, and guaranteed latencies for each stage—front haul, mid-haul and back haul—as appropriate per the network slices. Note that some combinations are not available options, such as back haul latency for AC and EC network slices in view of the type of topology specified.

(25) Methods of Use. With reference to FIG. **3**, there is shown an exemplary method **220** from the perspective of a service provider. At **221**, the set of network slice instances for the next time period are defined. These NSI specifications may, for example, be based on topology requirements and performance requirements. At **222**, the equilibrium value for each NSI for the next time slot is determined. The equilibrium value may, for example, be the minimum cost for the service provider to supply the NSI during that time period. While the equilibrium value may be based on the cost of providing the NSI which may include the cost of electricity, capital equipment, and the like, it may be possible that other factors may affect the equilibrium value. For example, the equilibrium value may include market concepts such as supply and demand, location, historical bids, and the like. The equilibrium value may even be less than the cost of providing a network slice instance for a particular time period which may occur, for example, when a service provider is offering special deals to its customers or potential customers. At **223**, the service provider may receive bids from one or more customers for one or more of the NSIs specified. At **224**, the service provider may compare the customer bids with the equilibrium value. At **225**, it is determined whether any of the individual bids exceed the equilibrium value. If any bids do exceed the equilibrium value, then service is provided at **227** for those customers whose bid did exceed the equilibrium value. If any of the bids do not exceed the equilibrium value, then service is denied at **226** for those customers whose bid did not exceed the equilibrium value. Regardless, a new time period may begin at **228** during which the auction/bid process may continue or restart as the case may be.

(26) With reference to FIG. **4**, there is shown an exemplary flow diagram **320** from the perspective

of the customer. At **321**, the customer defines the specifications it desires for NSI consumption. At **322**, the customer may generate a bid based on its specifications and the bid history. The bid history may include equilibrium values or winning bids and may be available in an historical database maintained by either the service provider or by the customer. At **323**, it is determined whether the customer's bid exceeds the equilibrium value. If so, service is received by the customer at **325**. If at **323** it is determined that the bid did not exceed the equilibrium value, the customer is given the option to increase its bid at **324**. If so, the process continues at **323** to determine if the new bid exceeds the equilibrium value. If the customer decides not to increase its bid at **324**, the customer may simply wait for a new auction at **328** at the beginning of the new time period.

(27) Whenever a bid exceeds the equilibrium value and the customer receives service, the price of the service may match the bid, may match the equilibrium value, or may fall somewhere in between the two. For example, the customer may have a service contract with the service provider that includes a set price, volume discounts or some other pricing arrangements that sets the price somewhere between the equilibrium value and the bid value. In an aspect, the service contract may specify the bid price of the customer as the maximum price the customer will ever pay for a particular time slot and a particular NSI.

(28) In an aspect, there may be bid optimization processes which calculate the expected equilibrium value and generate bids accordingly. For example, the bid optimization process may determine based on trial and error method what the equilibrium value may be for a given location, a given NSI specification and a given time slot and maintain a historical record of such equilibrium values. The bid optimization process may determine what other customers were paying for similar NSIs based on similar specifications during a similar time period. For example, there may be an historical record of the equilibrium value for a specific NSI type and associated performance requirements for a particular Thursday afternoon and the bid optimization process may consider whether the time period at issue, for example, a Wednesday afternoon or other Thursday afternoons in future weeks are similar to that Thursday afternoon in terms of pricing. The bid optimization process may include an algorithm that successively will bid from low to high for each time period until service is provided. In an aspect, the customer may place bids with two or more service providers in the hope of achieving the lower of two equilibrium values for any given time period.

(29) In an aspect, the bid optimization process may include a machine learning algorithm. Such a machine learning algorithm may be implemented on either the customer side or the service provider side. For example, a customer may implement a machine learning algorithm such as predictive linear regression analysis to predict the equilibrium value and to generate bids accordingly. Use of such an algorithm may predict a present or future equilibrium value based on changes in input variables, such as the time of day, location, and/or increased or decreased demand caused by special events or emergencies. The algorithm may also generate a bid based on the predicted equilibrium value and automatically increase the bid if the bid does not initially exceed the equilibrium value. Moreover, the algorithm may consider overall budget and reduce the NSI specification in order to generate a more cost conservative bid if the predicted equilibrium value is deemed too high for a given time period in light of the anticipated usage and urgency of that usage. For example, if the predicted equilibrium value is deemed to be too high, the algorithm may relax the latency requirements in the network slice to allow for the services to be provisioned on physical assets at a different locale which may have a cheaper equilibrium value for that time period and therefore a lower bid price may be accepted.

(30) On the service provider side, the machine learning algorithm may determine that the best way to maximize revenue is to lower the equilibrium value in certain time periods and focus not on the individual profit of an NSI for a particular time period, but rather on the aggregate revenue and determine equilibrium values accordingly. As such, the auction/bid process may thus create a dynamic marketplace implemented on specially programmed computer servers that advance the state of the art in network technology.

(31) The auction/bid process may enable the market to determine the appropriate pricing for any NSI specification for any locale and for any time period by ensuring that the service provider is not losing money, either on individual network slice instances or in the aggregate, while at the same time ensuring that the customers are not overpaying for service.

(32) In an aspect, an aggregator may participate in both the purchasing side of the auction and the selling side of an auction. For example, an aggregator may have service contracts with one or more service providers and resell NSIs to its own customers. The aggregator may wait for individual bids from its customers and then bid for service from the service providers or may choose to proactively purchase NSIs from the service providers and set its own equilibrium value based on that purchase price and its anticipated profit margin.

(33) In view of the foregoing, this disclosure provides a practical application that builds a centralized system to provide for the specification, provisioning, and pricing of network slice instances based on specifications of the customer. There is an equilibrium value set by the service providers which is the minimum price that service will be provided to customers, while the bid process provides the possible upside of increased margins should the market demand manifest itself in higher bids. At the same time, the disclosure provides protection for customers by ensuring that the customers will not be surprised by service costs and are able to purchase services based only what they need for a given time period. The practical application includes generating a dynamic market for the provision of network slice instances and removes a barrier to offering network slice as a service to network customers. As such, the disclosure provides a new and novel method for offering and pricing of a new service offering that advances the state of the telecommunications industry.

(34) While the disclosure has been described in relation to a generic network, it will be understood that the systems and methods disclosed herein may be deployed in both edge and central clouds to support current and future 5G real time use cases. Moreover, the architecture may also be used by carrier or third-party vendors.

(35) Network Description. FIG. 5 is a block diagram of network device **300** that may be connected to the network described in FIG. 1 or which may be a component of such a network. Network device **300** may comprise hardware or a combination of hardware and software. The functionality to facilitate telecommunications via a telecommunications network may reside in one or combination of network devices **300**. Network device **300** depicted in FIG. 5 may represent or perform functionality of an appropriate network device **300**, or combination of network devices **300**, such as, for example, a component or various components of a cellular broadcast system wireless network, a processor, a server, a gateway, a node, a mobile switching center (MSC), a short message service center (SMSC), an automatic location function server (ALFS), a gateway mobile location center (GMLC), a radio access network (RAN), a serving mobile location center (SMLC), or the like, or any appropriate combination thereof. It is emphasized that the block diagram depicted in FIG. 5 is exemplary and not intended to imply a limitation to a specific implementation or configuration. Thus, network device **300** may be implemented in a single device or multiple devices (e.g., single server or multiple servers, single gateway or multiple gateways, single controller or multiple controllers). Multiple network entities may be distributed or centrally located. Multiple network entities may communicate wirelessly, via hard wire, or any appropriate combination thereof.

(36) Network device **300** may comprise a processor **302** and a memory **304** coupled to processor **302**. Memory **304** may contain executable instructions that, when executed by processor **302**, cause processor **302** to effectuate operations associated with mapping wireless signal strength. As evident from the description herein, network device **300** is not to be construed as software per se.

(37) In addition to processor **302** and memory **304**, network device **300** may include an input/output system **306**. Processor **302**, memory **304**, and input/output system **306** may be coupled together (coupling not shown in FIG. 5) to allow communications between them. Each portion of

network device **300** may comprise circuitry for performing functions associated with each respective portion. Thus, each portion may comprise hardware, or a combination of hardware and software. Accordingly, each portion of network device **300** is not to be construed as software per se. Input/output system **306** may be capable of receiving or providing information from or to a communications device or other network entities configured for telecommunications. For example, input/output system **306** may include a wireless communication (e.g., 3G/4G/GPS) card. Input/output system **306** may be capable of receiving or sending video information, audio information, control information, image information, data, or any combination thereof. Input/output system **306** may be capable of transferring information with network device **300**. In various configurations, input/output system **306** may receive or provide information via any appropriate means, such as, for example, optical means (e.g., infrared), electromagnetic means (e.g., RF, Wi-Fi, Bluetooth® ZigBee®), acoustic means (e.g., speaker, microphone, ultrasonic receiver, ultrasonic transmitter), or a combination thereof. In an example configuration, input/output system **306** may comprise a Wi-Fi finder, a two-way GPS chipset or equivalent, or the like, or a combination thereof.

(38) Input/output system **306** of network device **300** also may contain a communication connection **308** that allows network device **300** to communicate with other devices, network entities, or the like. Communication connection **308** may comprise communication media. Communication media typically embody computer-readable instructions, data structures, program modules or other data in a modulated data signal such as a carrier wave or other transport mechanism and includes any information delivery media. By way of example, and not limitation, communication media may include wired media such as a wired network or direct-wired connection, or wireless media such as acoustic, RF, infrared, or other wireless media. The term computer-readable media as used herein includes both storage media and communication media. Input/output system **306** also may include an input device **310** such as keyboard, mouse, pen, voice input device, or touch input device. Input/output system **306** may also include an output device **312**, such as a display, speakers, or a printer.

(39) Processor **302** may be capable of performing functions associated with telecommunications, such as functions for processing broadcast messages, as described herein. For example, processor **302** may be capable of, in conjunction with any other portion of network device **300**, determining a type of broadcast message and acting according to the broadcast message type or content, as described herein.

(40) Memory **304** of network device **300** may comprise a storage medium having a concrete, tangible, physical structure. As is known, a signal does not have a concrete, tangible, physical structure. Memory **304**, as well as any computer-readable storage medium described herein, is not to be construed as a signal. Memory **304**, as well as any computer-readable storage medium described herein, is not to be construed as a transient signal. Memory **304**, as well as any computer-readable storage medium described herein, is not to be construed as a propagating signal. Memory **304**, as well as any computer-readable storage medium described herein, is to be construed as an article of manufacture.

(41) Memory **304** may store any information utilized in conjunction with telecommunications. Depending upon the exact configuration or type of processor, memory **304** may include a volatile storage **314** (such as some types of RAM), a nonvolatile storage **316** (such as ROM, flash memory), or a combination thereof. Memory **304** may include additional storage (e.g., a removable storage **318** or a non-removable storage **320**) including, for example, tape, flash memory, smart cards, CD-ROM, DVD, or other optical storage, magnetic cassettes, magnetic tape, magnetic disk storage or other magnetic storage devices, USB-compatible memory, or any other medium that can be used to store information and that can be accessed by network device **300**. Memory **304** may comprise executable instructions that, when executed by processor **302**, cause processor **302** to effectuate operations to map signal strengths in an area of interest.

(42) FIG. 6 depicts an exemplary diagrammatic representation of a machine in the form of a computer system **500** within which a set of instructions, when executed, may cause the machine to perform any one or more of the methods described above. One or more instances of the machine can operate, for example, as processor **302**, server **112**, mobile device **101**, in **102**, MME **103**, and other devices of FIG. 1 and FIG. 2. In some embodiments, the machine may be connected (e.g., using a network **502**) to other machines. In a networked deployment, the machine may operate in the capacity of a server or a client user machine in a server-client user network environment, or as a peer machine in a peer-to-peer (or distributed) network environment.

(43) The machine may comprise a server computer, a client user computer, a personal computer (PC), a tablet, a smart phone, a laptop computer, a desktop computer, a control system, a network router, switch or bridge, internet of things (IOT) device (e.g., thermostat, sensor, or other machine-to-machine device), or any machine capable of executing a set of instructions (sequential or otherwise) that specify actions to be taken by that machine. It will be understood that a communication device of the subject disclosure includes broadly any electronic device that provides voice, video or data communication. Further, while a single machine is illustrated, the term “machine” shall also be taken to include any collection of machines that individually or jointly execute a set (or multiple sets) of instructions to perform any one or more of the methods discussed herein.

(44) Computer system **500** may include a processor (or controller) **504** (e.g., a central processing unit (CPU)), a graphics processing unit (GPU, or both), a main memory **506** and a static memory **508**, which communicate with each other via a bus **510**. The computer system **500** may further include a display unit **512** (e.g., a liquid crystal display (LCD), a flat panel, or a solid-state display). Computer system **500** may include an input device **514** (e.g., a keyboard), a cursor control device **516** (e.g., a mouse), a disk drive unit **518**, a signal generation device **520** (e.g., a speaker or remote control) and a network interface device **522**. In distributed environments, the embodiments described in the subject disclosure can be adapted to utilize multiple display units **512** controlled by two or more computer systems **500**. In this configuration, presentations described by the subject disclosure may in part be shown in a first of display units **512**, while the remaining portion is presented in a second of display units **512**.

(45) The disk drive unit **518** may include a tangible computer-readable storage medium **524** on which is stored one or more sets of instructions (e.g., software **526**) embodying any one or more of the methods or functions described herein, including those methods illustrated above. Instructions **526** may also reside, completely or at least partially, within main memory **506**, static memory **508**, or within processor **504** during execution thereof by the computer system **500**. Main memory **506** and processor **504** also may constitute tangible computer-readable storage media.

(46) FIG. 7 is a representation of an exemplary network **600**. Network **600** (e.g., network **111**) may comprise an SDN—that is, network **600** may include one or more virtualized functions implemented on general purpose hardware, such as in lieu of having dedicated hardware for every network function. That is, general purpose hardware of network **600** may be configured to run virtual network elements to support communication services, such as mobility services, including consumer services and enterprise services. These services may be provided or measured in sessions.

(47) A virtual network functions (VNFs) **602** may be able to support a limited number of sessions. Each VNF **602** may have a VNF type that indicates its functionality or role. For example, FIG. 7 illustrates a gateway VNF **602a** and a policy and charging rules function (PCRF) VNF **602b**. Additionally or alternatively, VNFs **602** may include other types of VNFs. Each VNF **602** may use one or more virtual machines (VMs) **604** to operate. Each VM **604** may have a VM type that indicates its functionality or role. For example, FIG. 7 illustrates a management control module (MCM) VM **604a**, an advanced services module (ASM) VM **604b**, and a DEP VM **604c**. Additionally or alternatively, VMs **604** may include other types of VMs. Each VM **604** may

consume various network resources from a hardware platform **606**, such as a resource **608**, a virtual central processing unit (vCPU) **608a**, memory **608b**, or a network interface card (NIC) **608c**.

Additionally or alternatively, hardware platform **606** may include other types of resources **608**.

(48) While FIG. 7 illustrates resources **608** as collectively contained in hardware platform **606**, the configuration of hardware platform **606** may isolate, for example, certain memory **608c** from other memory **608c**. FIG. 8 provides an exemplary implementation of hardware platform **606**.

(49) Hardware platform **606** may comprise one or more chassis **610**. Chassis **610** may refer to the physical housing or platform for multiple servers or other network equipment. In an aspect, chassis **610** may also refer to the underlying network equipment. Chassis **610** may include one or more servers **612**. Server **612** may comprise general purpose computer hardware or a computer. In an aspect, chassis **610** may comprise a metal rack, and servers **612** of chassis **610** may comprise blade servers that are physically mounted in or on chassis **610**.

(50) Each server **612** may include one or more network resources **608**, as illustrated. Servers **612** may be communicatively coupled together (not shown) in any combination or arrangement. For example, all servers **612** within a given chassis **610** may be communicatively coupled. As another example, servers **612** in different chassis **610** may be communicatively coupled. Additionally, or alternatively, chassis **610** may be communicatively coupled together (not shown) in any combination or arrangement.

(51) The characteristics of each chassis **610** and each server **612** may differ. For example, FIG. 8 illustrates that the number of servers **612** within two chassis **610** may vary. Additionally, or alternatively, the type or number of resources **610** within each server **612** may vary. In an aspect, chassis **610** may be used to group servers **612** with the same resource characteristics. In another aspect, servers **612** within the same chassis **610** may have different resource characteristics.

(52) Given hardware platform **606**, the number of sessions that may be instantiated may vary depending upon how efficiently resources **608** are assigned to different VMs **604**. For example, assignment of VMs **604** to particular resources **608** may be constrained by one or more rules. For example, a first rule may require that resources **608** assigned to a particular VM **604** be on the same server **612** or set of servers **612**. For example, if VM **604** uses eight vCPUs **608a**, 1 GB of memory **608b**, and 2 NICs **608c**, the rules may require that all of these resources **608** be sourced from the same server **612**. Additionally, or alternatively, VM **604** may require splitting resources **608** among multiple servers **612**, but such splitting may need to conform with certain restrictions. For example, resources **608** for VM **604** may be able to be split between two servers **612**. Default rules may apply. For example, a default rule may require that all resources **608** for a given VM **604** must come from the same server **612**.

(53) An affinity rule may restrict assignment of resources **608** for a particular VM **604** (or a particular type of VM **604**). For example, an affinity rule may require that certain VMs **604** be instantiated on (that is, consume resources from) the same server **612** or chassis **610**. For example, if VNF **602** uses six MCM VMs **604a**, an affinity rule may dictate that those six MCM VMs **604a** be instantiated on the same server **612** (or chassis **610**). As another example, if VNF **602** uses MCM VMs **604a**, ASM VMs **604b**, and a third type of VMs **604**, an affinity rule may dictate that at least the MCM VMs **604a** and the ASM VMs **604b** be instantiated on the same server **612** (or chassis **610**). Affinity rules may restrict assignment of resources **608** based on the identity or type of resource **608**, VNF **602**, VM **604**, chassis **610**, server **612**, or any combination thereof.

(54) An anti-affinity rule may restrict assignment of resources **608** for a particular VM **604** (or a particular type of VM **604**). In contrast to an affinity rule—which may require that certain VMs **604** be instantiated on the same server **612** or chassis **610**—an anti-affinity rule requires that certain VMs **604** be instantiated on different servers **612** (or different chassis **610**). For example, an anti-affinity rule may require that MCM VM **604a** be instantiated on a particular server **612** that does not contain any ASM VMs **604b**. As another example, an anti-affinity rule may require that MCM VMs **604a** for a first VNF **602** be instantiated on a different server **612** (or chassis **610**) than MCM

VMs **604a** for a second VNF **602**. Anti-affinity rules may restrict assignment of resources **608** based on the identity or type of resource **608**, VNF **602**, VM **604**, chassis **610**, server **612**, or any combination thereof.

(55) Within these constraints, resources **608** of hardware platform **606** may be assigned to be used to instantiate VMs **604**, which in turn may be used to instantiate VNFs **602**, which in turn may be used to establish sessions. The different combinations for how such resources **608** may be assigned may vary in complexity and efficiency. For example, different assignments may have different limits of the number of sessions that can be established given a particular hardware platform **606**.

(56) For example, consider a session that may require gateway VNF **602a** and PCRF VNF **602b**. Gateway VNF **602a** may require five VMs **604** instantiated on the same server **612**, and PCRF VNF **602b** may require two VMs **604** instantiated on the same server **612**. (Assume, for this example, that no affinity or anti-affinity rules restrict whether VMs **604** for PCRF VNF **602b** may or must be instantiated on the same or different server **612** than VMs **604** for gateway VNF **602a**.) In this example, each of two servers **612** may have sufficient resources **608** to support 10 VMs **604**. To implement sessions using these two servers **612**, first server **612** may be instantiated with 10 VMs **604** to support two instantiations of gateway VNF **602a**, and second server **612** may be instantiated with 9 VMs: five VMs **604** to support one instantiation of gateway VNF **602a** and four VMs **604** to support two instantiations of PCRF VNF **602b**. This may leave the remaining resources **608** that could have supported the tenth VM **604** on second server **612** unused (and unusable for an instantiation of either a gateway VNF **602a** or a PCRF VNF **602b**). Alternatively, first server **612** may be instantiated with 10 VMs **604** for two instantiations of gateway VNF **602a** and second server **612** may be instantiated with 10 VMs **604** for five instantiations of PCRF VNF **602b**, using all available resources **608** to maximize the number of VMs **604** instantiated.

(57) Consider, further, how many sessions each gateway VNF **602a** and each PCRF VNF **602b** may support. This may factor into which assignment of resources **608** is more efficient. For example, consider if each gateway VNF **602a** supports two million sessions, and if each PCRF VNF **602b** supports three million sessions. For the first configuration—three total gateway VNFs **602a** (which satisfy the gateway requirement for six million sessions) and two total PCRF VNFs **602b** (which satisfy the PCRF requirement for six million sessions)—would support a total of six million sessions. For the second configuration—two total gateway VNFs **602a** (which satisfy the gateway requirement for four million sessions) and five total PCRF VNFs **602b** (which satisfy the PCRF requirement for 15 million sessions)—would support a total of four million sessions. Thus, while the first configuration may seem less efficient looking only at the number of available resources **608** used (as resources **608** for the tenth possible VM **604** are unused), the second configuration is actually more efficient from the perspective of being the configuration that can support more the greater number of sessions.

(58) To solve the problem of determining a capacity (or, number of sessions) that can be supported by a given hardware platform **605**, a given requirement for VNFs **602** to support a session, a capacity for the number of sessions each VNF **602** (e.g., of a certain type) can support, a given requirement for VMs **604** for each VNF **602** (e.g., of a certain type), a give requirement for resources **608** to support each VM **604** (e.g., of a certain type), rules dictating the assignment of resources **608** to one or more VMs **604** (e.g., affinity and anti-affinity rules), the chassis **610** and servers **612** of hardware platform **606**, and the individual resources **608** of each chassis **610** or server **612** (e.g., of a certain type), an integer programming problem may be formulated.

(59) As described herein, a telecommunications system wherein management and control utilizing a software designed network (SDN) and a simple IP are based, at least in part, on user equipment, may provide a wireless management and control framework that enables common wireless management and control, such as mobility management, radio resource management, QoS, load balancing, etc., across many wireless technologies, e.g. LTE, Wi-Fi, and future 5G access technologies; decoupling the mobility control from data planes to let them evolve and scale

independently; reducing network state maintained in the network based on user equipment types to reduce network cost and allow massive scale; shortening cycle time and improving network upgradability; flexibility in creating end-to-end services based on types of user equipment and applications, thus improve customer experience; or improving user equipment power efficiency and battery life—especially for simple M2M devices—through enhanced wireless management.

(60) While examples of a telecommunications system have been described in connection with various computing devices/processors, the underlying concepts may be applied to any computing device, processor, or system capable of facilitating a telecommunications system. The various techniques described herein may be implemented in connection with hardware or software or, where appropriate, with a combination of both. Thus, the methods and devices may take the form of program code (i.e., instructions) embodied in concrete, tangible, storage media having a concrete, tangible, physical structure. Examples of tangible storage media include floppy diskettes, CD-ROMs, DVDs, hard drives, or any other tangible machine-readable storage medium (computer-readable storage medium). Thus, a computer-readable storage medium is not a signal. A computer-readable storage medium is not a transient signal. Further, a computer-readable storage medium is not a propagating signal. A computer-readable storage medium as described herein is an article of manufacture. When the program code is loaded into and executed by a machine, such as a computer, the machine becomes a device for telecommunications. In the case of program code execution on programmable computers, the computing device will generally include a processor, a storage medium readable by the processor (including volatile or nonvolatile memory or storage elements), at least one input device, and at least one output device. The program(s) can be implemented in assembly or machine language, if desired. The language can be a compiled or interpreted language and may be combined with hardware implementations.

(61) The methods and devices associated with a telecommunications system as described herein also may be practiced via communications embodied in the form of program code that is transmitted over some transmission medium, such as over electrical wiring or cabling, through fiber optics, or via any other form of transmission, wherein, when the program code is received and loaded into and executed by a machine, such as an EPROM, a gate array, a programmable logic device (PLD), a client computer, or the like, the machine becomes an device for implementing telecommunications as described herein. When implemented on a general-purpose processor, the program code combines with the processor to provide a unique device that operates to invoke the functionality of a telecommunications system.

(62) While a telecommunications system has been described in connection with the various examples of the various figures, it is to be understood that other similar implementations may be used, or modifications and additions may be made to the described examples of a telecommunications system without deviating therefrom. For example, one skilled in the art will recognize that a telecommunications system as described in the instant application may apply to any environment, whether wired or wireless, and may be applied to any number of such devices connected via a communications network and interacting across the network. Therefore, a telecommunications system as described herein should not be limited to any single example, but rather should be construed in breadth and scope in accordance with the appended claims.

(63) In describing preferred methods, systems, or apparatuses of the subject matter of the present disclosure as illustrated in the Figures, specific terminology is employed for the sake of clarity. The claimed subject matter, however, is not intended to be limited to the specific terminology so selected, and it is to be understood that each specific element includes all technical equivalents that operate in a similar manner to accomplish a similar purpose. In addition, the use of the word “or” is generally used inclusively unless otherwise provided herein.

(64) This written description uses examples to enable any person skilled in the art to practice the claimed subject matter, including making and using any devices or systems and performing any incorporated methods. The patentable scope of the disclosed subject matter is defined by the claims

and may include other examples that occur to those skilled in the art (e.g., skipping steps, combining steps, or adding steps between exemplary methods disclosed herein). Such other examples are intended to be within the scope of the claims if they have structural elements that do not differ from the literal language of the claims, or if they include equivalent structural elements with insubstantial differences from the literal languages of the claims.

Claims

1. A method comprising: defining, by a processor, a specification for a network slice; analyzing, by the processor, historical pricing for the network slice, wherein the analyzing is performed via a machine learning algorithm, and wherein the machine learning algorithm utilizes variables including one or more of: a time of day, a location, an increased demand, or a decreased demand; generating, by the processor, a first bid price for the network slice for a time period, wherein the first bid price is generated based at least in part upon a maximum specified latency expressed as milliseconds and a maximum specified allowed traffic expressed as bits; and if the first bid price is accepted, receiving service using the network slice via one or more allocated virtual network functions in accordance with the specification.
2. The method of claim 1, wherein the first bid price is accepted if the first bid price meets or exceeds an equilibrium value.
3. The method of claim 1, wherein the method further comprises, if the first bid price is not accepted, increasing, by the processor, the first bid price to a second bid price.
4. The method of claim 3, wherein the method further comprises, if the second bid price is accepted, receiving service using the network slice in accordance with the specification.
5. The method of claim 1, wherein the method further comprises utilizing the machine learning algorithm to determine a target equilibrium value.
6. The method of claim 5, wherein the first bid price is set equal to or greater than the target equilibrium value.
7. The method of claim 1, wherein the method further comprises obtaining the historical pricing.
8. The method of claim 7, wherein the historical pricing is obtained from an historical database.
9. The method of claim 8, wherein the historical pricing comprises winning bids.
10. The method of claim 1, wherein the specification comprises one or more of guaranteed end-to-end latency and guaranteed RAN latency.
11. The method of claim 1, wherein the network slice is in a wireless communications system, and wherein the wireless communications system comprises a 5G cellular system.
12. A system comprising: a processor coupled to a memory, the memory having stored thereon executable instructions that when executed by the processor cause the processor to effectuate operations comprising: defining a specification for a network slice, the specification comprising one or more of guaranteed end-to-end latency and guaranteed RAN latency; analyzing, via a machine learning algorithm, historical pricing for the network slice; generating a first bid price for the network slice for a time period, wherein the first bid price is generated based at least in part upon a maximum specified latency expressed as milliseconds and a maximum specified allowed traffic expressed as bits; and if the first bid price is accepted, receiving service using the network slice via one or more allocated virtual network functions in accordance with the specification, wherein the first bid price is accepted if the first bid price meets or exceeds an equilibrium value, and wherein the equilibrium value is based upon supply and demand.
13. The system of claim 12, wherein the machine learning algorithm comprises linear regression analysis.
14. The system of claim 13, wherein the machine learning algorithm utilizes variables including one or more of a time of day, a location, an increased demand, a decreased demand.
15. The system of claim 14, wherein demand is affected by special events or emergencies.

16. The system of claim 12, wherein the network slice is in a wireless communications system, and wherein the wireless communications system comprises a 5G cellular system.
17. A non-transitory computer-readable storage medium comprising executable instructions that when executed by a processor cause the processor to effectuate operations comprising: obtaining historical pricing for a network slice in a wireless communications system, wherein the historical pricing is obtained from a database, and wherein the database comprises winning or losing bids as a function of location; analyzing the historical pricing for the network slice, wherein the network slice has associated therewith a defined specification, and wherein the analyzing is performed via a machine learning algorithm; generating a first bid price for the network slice for a time period, wherein the first bid price is generated based at least in part upon a maximum specified latency expressed as milliseconds and a maximum specified allowed traffic expressed as bits; if the first bid price is accepted, receiving wireless service using the network slice via one or more allocated virtual network functions in accordance with the defined specification; if the first bid price is not accepted, increasing the first bid price to a second bid price; and if the second bid price is accepted, receiving wireless service using the network slice via one or more allocated virtual network functions in accordance with the defined specification.
18. The non-transitory computer-readable storage medium of claim 17, wherein the wireless communications system comprises a 5G cellular system.
19. The non-transitory computer-readable storage medium of claim 17, wherein the defined specification comprises a guaranteed end-to-end latency.
20. The non-transitory computer-readable storage medium of claim 17, wherein the defined specification comprises a guaranteed RAN latency.
-