

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250259798

Kind Code

A1

Publication Date

August 14, 2025

Inventor(s)

NISHIKIORI; Yuichi et al.

VACUUM CAPACITOR

Abstract

A vacuum capacitor is provided with a vacuum container accommodating a fixed electrode and movable electrode to ensure capacitance, and a vacuum expansion container communicating with the vacuum container in series. The vacuum container is provided with a movable support part supporting the movable electrode, a movable conductor supporting the movable support part to enable reciprocation in the axial direction of the vacuum container, a fixed conductor supporting the fixed electrode, and a main bellows interposed between the movable support part and the movable conductor. The vacuum expansion container is provided with a movable part arranged coaxially with the movable support part, and an adjustment bellows interposed between the movable part and the inner end surface of the vacuum expansion container. The movable support part and movable part are connected by an insulating connection rod arranged coaxially with the fixed electrode and movable electrode.

Inventors: NISHIKIORI; Yuichi (Shinagawa-ku, JP), SHIMOKAWA; Takuya (Shinagawa-ku, JP), TANIMIZU; Yoshiyuki (Shinagawa-ku, JP), TANIMIZU; Toru (Shinagawa-ku, JP)

Applicant: MEIDENSHA CORPORATION (Shinagawa-ku, Tokyo, JP)

Family ID: 89615996

Appl. No.: 19/115177

Filed (or PCT Filed): August 29, 2023

PCT No.: PCT/JP2023/031138

Foreign Application Priority Data

JP 2022-153213

Sep. 27, 2022

Publication Classification

Int. Cl.: H01G5/014 (20060101); H01G5/14 (20060101)

U.S. Cl.:

CPC H01G5/014 (20130101); H01G5/14 (20130101);

Background/Summary

TECHNICAL FIELD

[0001] The present invention relates to a vacuum capacitor used, for example, for adjusting the impedance of high-frequency apparatus such as high-frequency power supplies and high-power transmission circuits in semiconductor facilities.

BACKGROUND TECHNOLOGY

[0002] Various vacuum capacitors have traditionally been used in high-frequency apparatus such as high-frequency power supplies and high-power transmission circuits in general semiconductor facilities for impedance adjustment. Recently, the operation speed of apparatus related to high-frequency apparatus has become faster, and there is also a growing demand for vacuum capacitors to reduce operating force in order to support high-speed operation.

[0003] FIG. 2 is a schematic sectional diagram showing one example of a general vacuum capacitor. A vacuum container 1 is formed in a cylindrical shape by a flange pipe 3 at one end and a flange pipe 4 at the other end of an insulating ceramic tube 2, and one of the both ends is sealed with a metal fixed conductor 5 and the other end is sealed with a metal movable conductor 6.

[0004] A fixed electrode 7 is composed of a plurality of thin cylindrical electrode members having different diameters which are arranged at regular intervals on the same axis, and is provided on the vacuum container 1 inner side of the fixed conductor 5. Similar to the fixed electrode 7, a movable electrode 8 is composed of a plurality of thin cylindrical electrode members having different diameters which are arranged at regular intervals on the same axis. The individual electrode members of the movable electrode 8 are inserted and removed in a state of intersecting with those of the fixed electrode 7, ensuring minute gaps with the fixed electrode 7 to obtain capacitance. This movable electrode 8 is provided on a movable support part 9 made of copper material, which can adjust the degree of insertion and removal with respect to the fixed electrode 7 in an axial direction Y of the vacuum container 1.

[0005] A hollow movable rod 10 is provided extending from the back side of the movable electrode 8 of the movable support part 9 in the axial direction Y of the vacuum container 1 so as to protrude from the movable conductor 6. The movable rod 10 slidably guides and supports the movable support part 9 in the axial direction Y of the vacuum container 1 via a bearing member 11 fixed to the movable conductor 6, with a gap between the outer peripheral surface of the movable rod 10 and the bearing member 11.

[0006] A male screw portion 12b at one end of an operating rod 12 is screwed into a female screw portion 10a on the inner wall at one end of the movable rod 10, and an operating rod head 12a at the other end is connected to a driving source of a vacuum capacitor, such as a motor. In addition, the operating rod 12 is supported by an operating rod support part 13, which is composed of a screw receiving portion 13a and a thrust bearing 13b that protrude from the movable conductor 6 provided to the vacuum container 1 and cover the bearing member 11, so as to be freely rotatable while receiving a main retraction force F1.

[0007] The operating rod 12 guides and moves the movable rod 10 in the axial direction Y of the

vacuum container **1**, using the bearing member **11**, and the capacitance of the vacuum capacitor is obtained by the facing area of the fixed electrode **7** and the movable electrode **8**.

[0008] A main bellows **14** has a bellows shape and is made of a thin and flexible metal. The main bellows **14** is configured to allow the movable electrode **8**, movable support part **9** and movable rod **10** to move in the axial direction Y while maintaining airtightness of a vacuum chamber **15** enclosed by the fixed electrode **7**, movable electrode **8** and main bellows **14** in the vacuum container **1**. One end of the main bellows **14** is joined to the inner wall of the movable conductor **6**, and the other end is joined to the movable support part **9**. An atmospheric chamber **16** having the atmospheric pressure is formed on the movable rod **10** side of the main bellows **14** within the vacuum container **1**.

[0009] The main bellows **14** has a vacuum pressure $F1v$ that is always pulling in the direction of the vacuum container, which is determined by the diameter of the main bellows **14**. Furthermore, in the operation range in 100% in total of 50% expansion and 50% contraction based on the initial length of the manufacture, plural expansion and contraction operation life is obtained from the allowable stress during expansion and contraction, and an expansion and contraction force $F1b$ in accordance with the spring constant associated with expansion and contraction is set. A main retraction force $F1$ is the total force of the vacuum pressure $F1v$, the expansion and contraction force $F1b$, and the sliding friction of the main bellows **14**.

[0010] In the vacuum capacitor mentioned above, when the driving source such as a motor rotates the operating rod **12** to move the moving rod **10** in the axial direction Y of the vacuum container **1**, the area of intersection between the fixed electrode **7** and the movable electrode **8** changes, and consequently, the capacitance is controlled to adjust the impedance.

PRIOR ART REFERENCE(S)

Patent Document(s)

[0011] Patent Document 1: Japanese Patent Application Publication No. 2007-116025 [0012]

Patent Document 2: U.S. Pat. No. 9,805,873

SUMMARY OF THE INVENTION

[0013] Of the main retraction force $F1$ of the main bellows **14** relative to the movable rod **10**, the force of the vacuum pressure $F1v$ is constant and large. Furthermore, the expansion and contraction force $F1b$ changes depending on the operating position (capacitance value). Since the main retraction force $F1$ is large and fluctuates, it becomes difficult to perform high-speed control and fine adjustment of the capacitance.

[0014] The present invention is made in consideration of such a situation, and an object of the present invention is to perform high-speed control and fine adjustment of capacitance by reducing the operating force of the electrodes that ensure the capacitance.

[0015] Therefore, the present invention, in one aspect thereof, is a vacuum capacitor including: a vacuum container which accommodates a pair of electrodes which are capable of ensuring capacitance; and a vacuum expansion container which communicates with the vacuum container in series, wherein the vacuum container includes: a movable support part which supports one electrode of the pair of electrodes; one conductor which supports the movable support part to enable reciprocation in an axial direction of the vacuum container; an other conductor which supports an other electrode of the pair of electrodes; and a main bellows which is interposed between the movable support part and the one conductor, wherein the vacuum expansion container includes: a movable part arranged coaxially with the movable support part; and an adjustment bellows which is interposed between the movable part and an inner surface of an end portion of the vacuum expansion container, and wherein the movable support part and the movable part are connected by an insulating connection rod arranged coaxially with the pair of electrodes.

[0016] In the vacuum capacitor in one aspect of the present invention, an operating rod which operates the movable support part or the movable part is provided on an atmospheric side.

[0017] In the vacuum capacitor in one aspect of the present invention, the adjustment bellows has a

vacuum pressure equal to or less than that of the main bellows.

[0018] In the vacuum capacitor in one aspect of the present invention, the main bellows and the adjustment bellows have a same spring constant and an expansion and contraction rate.

[0019] In the vacuum capacitor in one aspect of the present invention, the main bellows and the adjustment bellows each are set to have an operation range of a 50% expansion and 50% contraction relative to an initial length at a time of manufacture.

[0020] In the vacuum capacitor in one aspect of the present invention, the other conductor is formed with a through hole through which the insulating connection rod is inserted, and the vacuum container and the vacuum expansion container communicate with each other via the through hole.

[0021] According to the present invention, the operating force of the electrodes that ensure the capacitance can be reduced, thereby performing high-speed control and fine adjustment of the capacitance.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0022] FIG. 1 is a schematic sectional diagram of a vacuum capacitor in a first embodiment of the present invention.

[0023] FIG. 2 is a schematic sectional diagram of a conventional vacuum capacitor.

MODE FOR IMPLEMENTING THE INVENTION

[0024] In the following, an embodiment of the present invention will be explained by referring to the drawings.

[0025] A vacuum capacitor in a first embodiment that is one aspect of the present invention in FIG. 1 is provided with a vacuum container **1a** which accommodates a fixed electrode **7** (other electrode) and a movable electrode **8** (one electrode), which are a pair of electrodes that are capable of ensuring capacitance, and a vacuum expansion container **52** that communicates with the vacuum container **1a** in series.

[0026] The vacuum container **1a** is composed of and sealed by a ceramic tube **2**, flange tubes **3** and **4**, a fixed conductor **51** and a movable conductor **6**.

[0027] The ceramic tube **2** is arranged coaxially with the fixed electrode **7** and the movable electrode **8** inside the vacuum container **1a**.

[0028] The flange tube **3** is interposed between one end of the ceramic tube **2** and the fixed conductor **51** (other conductor) on the same axis mentioned above.

[0029] The flange tube **4** is interposed between the other end of the ceramic tube **2** and the movable conductor **6** (one conductor) on the same axis mentioned above.

[0030] The fixed electrode **7** is provided to the fixed conductor **51** in the inside of the vacuum container **1a** and is composed of a plurality of electrode members which have thin plate and substantially cylindrical shapes, have different diameters, and are arranged coaxially at regular intervals.

[0031] The movable electrode **8** is provided to a movable support part **91**, which can reciprocate in an axial direction Y of the vacuum container **1a**, and is composed of electrode members which have thin plate and substantially cylindrical shapes, have different diameters, and are arranged coaxially at regular intervals such that an arbitrary capacitance can be ensured between the movable electrode **8** and the fixed electrode **7**.

[0032] A movable rod **10** that reciprocates in the axial direction Y by an operating rod **12** is provided in the center of the back side of the movable support part **91** which is a side opposite to the side of the movable electrode **8**. The movable rod **10** is surrounded by a main bellows **50** which is interposed between the movable conductor **6** and the movable support part **91**, and is supported

coaxially with the flange tube **4** by a bearing member **11** in the movable conductor **6**.

[0033] The operating rod **12** includes, on one side thereof, a male screw portion **12b** which is screwed into a female screw portion **10a** of the movable rod **10**, and, on the other side thereof, an operating rod head **12a** which is connected to a driving source of the vacuum capacitor, such as a motor, and is rotatably supported by an operating rod support part **13** in the movable conductor **6**.

[0034] The operating rod support part **13** is composed of a screw receiving portion **13a** provided to the movable conductor **6** to cover the bearing member **11** on the atmospheric side of the movable conductor **6**, and a thrust bearing **13b** which reduces the rotational torque of the operating rod **12** at the screw receiving portion **13a**. With this operating rod support part **13**, by the rotation of the operating rod **12** by a driving source such as a motor, the movable rod **10** moves in the axial direction Y while being guided by the bearing member **11**. Consequently, the facing area of the movable electrode **8** and the fixed electrode **7** becomes variable, and a desired capacitance can be obtained.

[0035] The main bellows **50** has a bellows shape and is made of a copper alloy or copper-plated flexible thin metal, and is expandable and contractible in the axial direction Y of the vacuum container **1a**. The main bellows **50** is arranged coaxially with the flange tube **4**, and one end of the main bellows **50** is joined to the inner wall of the movable conductor **6**, and the other end is joined to the movable support part **91** to surround the movable rod **10**, so as to airtightly maintain the vacuum chamber **15** with the fixed electrode **7** and movable electrode **8**. In addition, an atmospheric chamber **16** under the atmospheric pressure state is formed on the movable rod **10** side of the main bellows **50** in the vacuum container **1a**.

[0036] A through hole **51a** is formed in the center of the fixed conductor **51**, through which an insulating connection rod **55** connected to the movable support part **91** is inserted. One end of the insulating connection rod **55** is fixed to a fixed seat **91a** in the center of the movable electrode **8** side of the movable support part **91**, while the other end is fixed to a fixed seat **54a** of the movable part **54** through the through hole **51a** of the fixed conductor **51**.

[0037] On the atmospheric side of the fixed conductor **51**, a vacuum expansion container **52** having a cylindrical shape with a bottom and a smaller diameter than the ceramic tube **2** and the flange tubes **3** and **4** is disposed.

[0038] The vacuum expansion container **52** is provided with a movable part **54** connected to the insulating connection rod **55** introduced through the through hole **51a** of the fixed conductor **51**, and an adjustment bellows **53** interposed between the movable part **54** and the inner bottom surface of the vacuum expansion container **52**.

[0039] The adjustment bellows **53** is interposed between the movable part **54** and the inner surface of an end portion of the vacuum expansion container **52**. In particular, the adjustment bellows **53** is set to have a spring constant, which is the same as that of the main bellows **50**, and a vacuum pressure equal to or less than that of the main bellows **50**, and the vacuum chamber **15a**, which is formed by the fixed conductor **51**, movable part **54** and adjustment bellows **53**, is airtightly maintained and the movable part **54** and insulating connection rod **55** are provided in the vacuum expansion container **52** so as to be movable in the axial direction Y. Inside the adjustment bellows **53**, the atmospheric chamber **16a** under the atmospheric pressure state is formed by a suction and exhaust hole **52a** at the bottom of the vacuum expansion container **52**. An adjusting retraction force **F3** of the adjustment bellows **53** is the total of a vacuum pressure **F3v** and an expansion and contraction force **F3b** of the adjustment bellows **53**.

[0040] As described above, the main bellows **50**, the insulating connection rod **55** and the adjustment bellows **53** are arranged in series in the axial direction Y, and an operating rod, which is omitted from the illustration, is further provided on the atmospheric side of the main bellows **50** or the adjustment bellows **53**.

[0041] According to the vacuum capacitor in the present embodiment, by the rotation of the operating rod **12** by a driving source such as a motor in the atmosphere, the movable rod **10** and the

movable support part **91** move in the axial direction **Y**, and the main bellows **50** expands and contracts, and the facing area between the fixed electrode **7** and the movable electrode **8** varies. Consequently, the capacitance by the fixed electrode **7** and the movable electrode **8** can be controlled, and the impedance is adjusted as desired. Linked with this, the insulating connection rod **55** expands and contracts the adjustment bellows **53** via the movable part **54** in the vacuum chamber **15a** through the through hole **51a** of the fixed conductor **51**, and the main retraction force **F2** and the adjustment retraction force **F3** become forces in opposite directions that cancel each other out, such that a total retraction force **F4** becomes only sliding friction.

[0042] As described above, the total retraction force **F4** is reduced by the cancellation of the main retraction force **F2** of the main bellows **50** and the adjustment retraction force **F3** of the adjustment bellows **53**. The insulating connection rod **55**, which is arranged between the main bellows **50** of the vacuum chamber **15** and the adjustment bellows **53** of the vacuum chamber **15a**, is insulated in a vacuum and the creep distance is reduced, and it can be applied as a compressive force with high allowable stress, thereby reducing the cross-section and diameter of the insulating connection rod **55**.

[0043] In addition, since the operating rod **12** is arranged on the atmospheric chamber **16** side of the main bellows **50** on the same axis as the main bellows **50**, the insulating connection rod **55** and the adjustment bellows **53**, a drive source such as a motor connected to the operating rod **12** can be disposed in the atmosphere, and thereby maintenance and inspection become easier.

[0044] Moreover, if the vacuum pressure **F3v** of the adjustment bellows **53** is equal to the vacuum pressure **F2v** of the main bellows **50**, the vacuum pressures **F3v** and **F2v** cancel each other out, and if the vacuum pressure **F3v** is equal to or less than the vacuum pressure **F2v**, the total retraction force **F4** corresponding to the reduction in vacuum pressure based on the conditions of a driving source such as a motor is generated.

[0045] Then, the expansion and contraction force **F2b** of the main bellows **50** and the expansion and contraction force **F3b** of the adjustment bellows **53** have the same spring constant and expansion and contraction rate, and the expansion and contraction force **F3b** of the adjustment bellows **53** becomes a force in the opposite direction to the expansion and contraction force **F2b** of the main bellows **50**. Therefore, by connecting the main bellows **50** and the adjustment bellows **53** via the insulating connection rod **55**, the expansion and contraction forces **F2b** and **F3b** cancel each other out, and the total retraction force **F4** can be reduced.

[0046] In addition, by setting each of the main bellows **50** and the adjustment bellows **53** to have an operating range in 100% in total of 50% expansion and 50% contraction relative to the initial length at the time of manufacture, the expansion and contraction force **F2b** of the main bellows **50** is the same as the expansion and contraction force **F3b** of the adjustment bellows **53**, and they become forces acting in opposite directions to each other. Therefore, the expansion and contraction forces **F2b** and **F3b** cancel each other out by the connection mentioned above, and the total retraction force **F4** can be reduced.

[0047] Further, the vacuum chamber **15** of the vacuum container **1a** communicates with the vacuum chamber **15a** of the vacuum expansion container **52** by connecting the vacuum container **1a** and the vacuum expansion container **52** via the fixed conductor **51** formed with the through hole **51a** through which the insulating connection rod **55** is inserted. Consequently, vacuum brazing and vacuum maintenance are combined into a single process, and thereby a plurality of manufacturing and assembly process for a sealed container becomes unnecessary.

[0048] Then, the insulating connection rod **55** is thinly constructed for pressure resistance and is introduced into the vacuum expansion container **52** on the same axis as the fixed electrode **7** and the movable electrode **8**. Consequently, the insulating connection rod **55** can be joined to the adjustment bellows **53** inside the vacuum expansion container **52** without affecting the facing area (capacitance) of the fixed electrode **7** and the movable electrode **8**.

[0049] In addition, since by the through hole **51a** through which the insulating connection rod **55** is

inserted, the insulating connection rod **55** is in a non-sliding state, as a result of which the movable mechanism of the vacuum capacitor can be achieved with only the bearing member **11**, and the misalignment that occurs in the case of a multi-point sliding guide structure is suppressed, and core adjustment is no longer necessary.

[0050] As the above, according to the present embodiment, the total retraction force **F4** can be a stable force and is easily finely adjusted, such that high-speed control can be performed by providing a driving source, such as a motor, in the atmosphere.

[0051] In the first embodiment in FIG. **1**, the operating rod **12** is provided on the atmosphere chamber **16** side of the main bellows **50**, but it may also be provided on the atmosphere chamber **16a** side of the adjustment bellows **53**.

Claims

1.-6. (canceled)

7. A vacuum capacitor comprising: a vacuum container which accommodates a pair of electrodes which are capable of ensuring capacitance; and a vacuum expansion container which communicates with the vacuum container in series, wherein the vacuum container includes: a movable support part which supports one electrode of the pair of electrodes; one conductor which supports the movable support part to enable reciprocation in an axial direction of the vacuum container; an other conductor which supports an other electrode of the pair of electrodes; and a main bellows which is interposed between the movable support part and the one conductor, wherein the vacuum expansion container includes: a movable part arranged coaxially with the movable support part; and an adjustment bellows which is interposed between the movable part and an inner surface of an end portion of the vacuum expansion container, wherein the movable support part and the movable part are connected by an insulating connection rod arranged coaxially with the pair of electrodes, wherein the other conductor is formed with a through hole through which the insulating connection rod is inserted, and wherein the vacuum container and the vacuum expansion container communicate with each other via the through hole.

8. The vacuum capacitor according to claim 7, wherein an operating rod which operates the movable support part or the movable part is provided on an atmospheric side.

9. The vacuum capacitor according to claim 7, wherein the adjustment bellows has a vacuum pressure equal to or less than that of the main bellows.

10. The vacuum capacitor according to claim 7, wherein the main bellows and the adjustment bellows have a same spring constant and an expansion and contraction rate.

11. The vacuum capacitor according to claim 7, wherein the main bellows and the adjustment bellows each have a 50% expansion and 50% contraction relative to an initial length at a time of manufacture.
