

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent	12391276
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Sharma; Deva-Datta et al.

---

### Digital map truth maintenance

---

#### Abstract

The described technology is generally directed towards digital map truth maintenance. Map inputs shared among multiple users of a shared overlay map service can have a range of credibility, from not credible to highly credible. The disclosed digital map truth maintenance technologies can be used to enhance credibility of shared map inputs. Credibility values can be calculated for map inputs, based on any of multiple factors. Map inputs having sufficiently high credibility, such as a credibility value determined to be above a threshold value, can be shared among multiple mobile devices.

---

<b>Inventors:</b>	Sharma; Deva-Datta (San Ramon, CA), Oetting; John (Zionsville, PA)
<b>Applicant:</b>	AT&T Intellectual Property I, L.P. (Atlanta, GA)
<b>Family ID:</b>	1000008766249
<b>Assignee:</b>	AT&T Intellectual Property I, L.P. (Atlanta, GA)
<b>Appl. No.:</b>	18/059596
<b>Filed:</b>	November 29, 2022

#### Prior Publication Data

<b>Document Identifier</b>	<b>Publication Date</b>
US 20230107956 A1	Apr. 06, 2023

#### Related U.S. Application Data

division parent-doc US 16876430 20200518 US 11535275 child-doc US 18059596

---

#### Publication Classification

**Int. Cl.:** G01C21/36 (20060101); B60W60/00 (20200101); G01C21/00 (20060101); H04L67/12 (20220101)

**U.S. Cl.:**

**CPC** B60W60/0011 (20200201); B60W60/0025 (20200201); G01C21/3605 (20130101); G01C21/367 (20130101); G01C21/3804 (20200801); G01C21/3833 (20200801); H04L67/12 (20130101)

## Field of Classification Search

**CPC:** G01C (21/3885); G01C (21/3804); G01C (21/367); G01C (21/3893); G01C (21/3856); G01C (21/3833); G01C (21/3841); G01C (21/3605); H04L (67/12); H04W (4/30); H04W (4/40); B60W (60/0025); B60W (60/0011); H01L (67/12)

**USPC:** 701/23; 701/423; 701/532

---

## References Cited

### U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
7849031	12/2009	Stehle et al.	N/A	N/A
8717387	12/2013	Brewington	N/A	N/A
9204257	12/2014	Mendelson	N/A	N/A
9679487	12/2016	Hayward	N/A	N/A
9792575	12/2016	Khasis	N/A	N/A
9805601	12/2016	Fields et al.	N/A	N/A
9953535	12/2017	Canavor et al.	N/A	N/A
9961507	12/2017	Mendelson	N/A	N/A
10156848	12/2017	Konrardy et al.	N/A	N/A
10194273	12/2018	Xie	N/A	H04W 64/00
10354217	12/2018	Khasis	N/A	N/A
10543741	12/2019	Biderman et al.	N/A	N/A
10578450	12/2019	LeBeau	N/A	G06F 16/638
10611475	12/2019	Durand	N/A	N/A
10794710	12/2019	Liu et al.	N/A	N/A
11042827	12/2020	Khasis	N/A	N/A
11493354	12/2021	Sharma	N/A	G01C 21/3415
11641665	12/2022	Helms	370/329	H04L 67/535
11774263	12/2022	Sharma	701/423	H04L 67/12
12014254	12/2023	Bryce	N/A	G06Q 40/03
2003/0014187	12/2002	Chun et al.	N/A	N/A
2005/0099322	12/2004	Wainfan et al.	N/A	N/A
2007/0293958	12/2006	Stehle et al.	N/A	N/A
2011/0106592	12/2010	Stehle et al.	N/A	N/A
2011/0208417	12/2010	Fink et al.	N/A	N/A
2013/0030698	12/2012	Yamagishi et al.	N/A	N/A

2013/0090801	12/2012	Backes	701/23	B61L 23/28
2014/0149032	12/2013	Barrett et al.	N/A	N/A
2014/0244110	12/2013	Tharaldson et al.	N/A	N/A
2015/0032366	12/2014	Man et al.	N/A	N/A
2015/0073697	12/2014	Barrett et al.	N/A	N/A
2015/0081201	12/2014	Rubin	701/301	G01C 21/26
2015/0153175	12/2014	Skaaksrud	701/23	G05D 1/81
2015/0338234	12/2014	Seastrom	701/409	G01C 21/3679
2016/0012465	12/2015	Sharp	705/14.17	G06Q 20/321
2016/0012723	12/2015	Biderman et al.	N/A	N/A
2017/0098372	12/2016	Eilertsen	N/A	N/A
2017/0262790	12/2016	Khasis	N/A	N/A
2017/0284817	12/2016	Greenspan et al.	N/A	N/A
2017/0323249	12/2016	Khasis	N/A	N/A
2018/0017401	12/2017	Fletcher	N/A	N/A
2018/0310129	12/2017	Xie	N/A	H04W 4/026
2019/0004525	12/2018	Bills et al.	N/A	N/A
2019/0325376	12/2018	Khasis	N/A	N/A
2019/0332114	12/2018	Moroniti et al.	N/A	N/A
2019/0383624	12/2018	Magzimof et al.	N/A	N/A
2020/0166361	12/2019	Voznesensky et al.	N/A	N/A
2020/0372792	12/2019	Li et al.	N/A	N/A
2021/0004363	12/2020	Bailly et al.	N/A	N/A
2021/0035449	12/2020	Merfels	N/A	G08G 1/0112
2021/0285788	12/2020	Sharma et al.	N/A	N/A
2021/0312375	12/2020	Khasis	N/A	N/A
2021/0354724	12/2020	Sharma et al.	N/A	N/A

## FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
106612369	12/2016	CN	G01C 21/367
108335197	12/2017	CN	G06Q 40/02
109154969	12/2018	CN	G06F 16/337
109447780	12/2018	CN	N/A
109754135	12/2018	CN	N/A
110689423	12/2019	CN	G06Q 40/025
110796440	12/2019	CN	N/A
110957024	12/2019	CN	N/A

## OTHER PUBLICATIONS

Blukis, Valts, et al. “Learning to map natural language instructions to physical quadcopter control using simulated flight.” arXiv preprint arXiv: 1910.09664 (2019). (Year: 2019). cited by examiner

Alagha, Ahmed, et al. “Target localization using multi-agent deep reinforcement learning with proximal policy optimization.” Future Generation Computer Systems 136 (2022): 342-357. (Year: 2022). cited by examiner

Deng, Wan-Yu, et al. "Domain adaption via feature selection on explicit feature map." IEEE transactions on neural networks and learning systems 30.4 (2018): 1180-1190. (Year: 2018). cited by examiner

Chen, Songchao, et al. "Digital mapping of GlobalSoilMap soil properties at a broad scale: A review." Geoderma 409 (2022): 115567. (Year: 2022). cited by examiner

Alshehri, Abdullah, et al. "Residual neural networks for origin-destination trip matrix estimation from traffic sensor information." Sustainability 15.13 : 9881. (Year: 2023). cited by examiner

Mayalu Jr, Alfred Kulua. "Beyond LiDAR for Unmanned Aerial Event-Based Localization in GPS Denied Environments.". (Year: 2021). cited by examiner

Ballardini, Augusto Luis, et al. "Vehicle localization using 3D building models and point cloud matching." Sensors 21.16 (2021): 5356. (Year: 2021). cited by examiner

Kumar, D. Lokesh Sai, et al. "Road Extraction From Remote Sensing Images Using U-Net." 2024 International Conference on Advances in Modern Age Technologies for Health and Engineering Science (AMATHE). IEEE,. (Year: 2024). cited by examiner

Non-Final Office Action received for U.S. Appl. No. 16/846,883 dated Mar. 14, 2022, 64 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 16/815,333 dated Mar. 25, 2022, 55 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 16/876,430 dated Mar. 28, 2022, 32 pages. cited by applicant

"Comparison of satellite navigation software", [https://en.wikipedia.org/wiki/Comparison\\_of\\_satellite\\_navigationsoftware](https://en.wikipedia.org/wiki/Comparison_of_satellite_navigationsoftware), 2020, 4 pages. cited by applicant

"Reason maintenance", [https://en.wikipedia.org/wiki/Reason\\_maintenance](https://en.wikipedia.org/wiki/Reason_maintenance), 2020, 3 pages. cited by applicant

"Digital Map Market worth \$29.4 billion by 2024", <https://www.marketsandmarkets.com/PressReleases/digital-map.asp>, 2020, 6 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 16/876,430 dated Aug. 24, 2022, 33 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 16/846,883 dated Jul. 1, 2022, 64 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 16/815,333 dated Aug. 24, 2022, 68 pages. cited by applicant

---

*Primary Examiner:* Nguyen; Cuong H

*Attorney, Agent or Firm:* Guntin & Gust, PLC

---

## **Background/Summary**

(1) The subject patent application is a divisional of, and claims priority to, U.S. patent application Ser. No. 16/876,430, filed May 18, 2020, and entitled "DIGITAL MAP TRUTH MAINTENANCE," the entirety of which priority application is hereby incorporated by reference herein.

### **TECHNICAL FIELD**

(1) The subject application is related to digital navigational map technologies and communications, such as wireless communications, to interact with digital navigational maps, including fifth generation (5G) and subsequent generation cellular communication systems.

## BACKGROUND

(2) Digital navigational maps coupled with mobile device location technologies have revolutionized the way we navigate. Today's mobile devices can wirelessly access digital maps that represent virtually any location in the world. Furthermore, devices can plot current device locations on maps. Users can enter starting points and destinations to calculate navigation routes. Digital navigational maps can also show certain real-time information, such as traffic information and locations of car accidents.

(3) However, further improvements in digital navigational maps remain to be developed. For instance, the business landscape for digital navigational maps is presently limited to a few major providers, such as GOOGLE® and APPLE®. These companies have proprietary digital navigational map systems which do not easily share information across platforms. The ability to share map information directly among map users is also limited and cumbersome. In most use cases, direct sharing of map information requires human involvement, such as the manual specification of a map location to be shared and a set of recipients.

(4) A present difficulty in sharing map information is expected to present difficulties for unmanned ground vehicles (UGV), such as driverless cars and delivery robots, in particular. Proprietary systems can and likely will be developed to allow fleets of UGVs to communicate with one another, and such communications can comprise map information. However, additional efficiency and control, as well as meaningful public safety and convenience gains, can be realized from automated cross-platform sharing of map information among different fleets of UGVs.

(5) The above-described background relating to digital navigational mapping technology is merely intended to provide a contextual overview of some current issues, and is not intended to be exhaustive. Other contextual information may become further apparent upon review of the following detailed description.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

(1) Non-limiting and non-exhaustive embodiments of the subject disclosure are described with reference to the following figures, wherein like reference numerals refer to like parts throughout the various views unless otherwise specified.

(2) FIG. 1 illustrates an example wireless communication system, in accordance with various aspects and embodiments of the subject disclosure.

(3) FIG. 2 illustrates an example map authority that hosts a shared overlay map service and a truth maintenance module, along with example subscriber devices that use the shared overlay map service, in accordance with various aspects and embodiments of the subject disclosure.

(4) FIG. 3A illustrates an example shared overlay map for use by a shared overlay map service, in accordance with various aspects and embodiments of the subject disclosure.

(5) FIG. 3B illustrates an example map overlay that can be applied to the shared overlay map of FIG. 3A, in accordance with various aspects and embodiments of the subject disclosure.

(6) FIG. 3C illustrates an example combination of the map overlay illustrated in FIG. 3B with a digital navigational map at a mobile subscriber device, in accordance with various aspects and embodiments of the subject disclosure.

(7) FIG. 4 illustrates an unmanned ground vehicle (UGV), as one example implementation of a mobile subscriber device, in accordance with various aspects and embodiments of the subject disclosure.

(8) FIG. 5 illustrates an example map authority server, in accordance with various aspects and embodiments of the subject disclosure.

(9) FIG. 6 illustrates an example shared overlay map and additional example map overlays, in

accordance with various aspects and embodiments of the subject disclosure.

(10) FIG. 7 is a flow diagram representing example operations of a server comprising a truth maintenance module for map inputs, in accordance with various aspects and embodiments of the subject disclosure.

(11) FIG. 8 is a flow diagram representing another example set of operations of a server comprising a truth maintenance module for map inputs, in accordance with various aspects and embodiments of the subject disclosure.

(12) FIG. 9 is a flow diagram representing another example set of operations of a server comprising a truth maintenance module for map inputs, in accordance with various aspects and embodiments of the subject disclosure.

(13) FIG. 10 is a block diagram of an example computer that can be operable to execute processes and methods in accordance with various aspects and embodiments of the subject disclosure.

#### DETAILED DESCRIPTION

(14) One or more embodiments are now described with reference to the drawings, wherein like reference numerals are used to refer to like elements throughout. In the following description, for purposes of explanation, numerous specific details are set forth in order to provide a thorough understanding of the various embodiments. It is evident, however, that the various embodiments can be practiced without these specific details, and without applying to any particular networked environment or standard.

(15) One or more aspects of the technology described herein are generally directed towards digital map truth maintenance. Map inputs shared among multiple users of a shared overlay map service can have a range of credibility, from not credible to highly credible. The disclosed digital map truth maintenance technologies can be used to enhance credibility of shared map inputs. Credibility values can be calculated for map inputs, based on any of multiple factors. Map inputs having sufficiently high credibility, such as a credibility value determined to be above a threshold value, can be shared among multiple mobile devices.

(16) As used in this disclosure, in some embodiments, the terms “component,” “system” and the like are intended to refer to, or comprise, a computer-related entity or an entity related to an operational apparatus with one or more specific functionalities, wherein the entity can be either hardware, a combination of hardware and software, software, or software in execution. As an example, a component can be, but is not limited to being, a process running on a processor, a processor, an object, an executable, a thread of execution, computer-executable instructions, a program, and/or a computer. By way of illustration and not limitation, both an application running on a server and the server can be a component.

(17) One or more components can reside within a process and/or thread of execution and a component can be localized on one computer and/or distributed between two or more computers. In addition, these components can execute from various computer readable media having various data structures stored thereon. The components can communicate via local and/or remote processes such as in accordance with a signal having one or more data packets (e.g., data from one component interacting with another component in a local system, distributed system, and/or across a network such as the internet with other systems via the signal). As another example, a component can be an apparatus with specific functionality provided by mechanical parts operated by electric or electronic circuitry, which is operated by a software application or firmware application executed by a processor, wherein the processor can be internal or external to the apparatus and executes at least a part of the software or firmware application. As yet another example, a component can be an apparatus that provides specific functionality through electronic components without mechanical parts, the electronic components can comprise a processor therein to execute software or firmware that confers at least in part the functionality of the electronic components. While various components have been illustrated as separate components, it will be appreciated that multiple components can be implemented as a single component, or a single component can be implemented

as multiple components, without departing from example embodiments.

(18) The term “facilitate” as used herein is in the context of a system, device or component “facilitating” one or more actions or operations, in respect of the nature of complex computing environments in which multiple components and/or multiple devices can be involved in some computing operations. Non-limiting examples of actions that may or may not involve multiple components and/or multiple devices comprise transmitting or receiving data, establishing a connection between devices, determining intermediate results toward obtaining a result, etc. In this regard, a computing device or component can facilitate an operation by playing any part in accomplishing the operation. When operations of a component are described herein, it is thus to be understood that where the operations are described as facilitated by the component, the operations can be optionally completed with the cooperation of one or more other computing devices or components, such as, but not limited to, sensors, antennae, audio and/or visual output devices, other devices, etc.

(19) Further, the various embodiments can be implemented as a method, apparatus or article of manufacture using standard programming and/or engineering techniques to produce software, firmware, hardware or any combination thereof to control a computer to implement the disclosed subject matter. The term “article of manufacture” as used herein is intended to encompass a computer program accessible from any computer-readable (or machine-readable) device or computer-readable (or machine-readable) storage/communications media. For example, computer readable storage media can comprise, but are not limited to, magnetic storage devices (e.g., hard disk, floppy disk, magnetic strips), optical disks (e.g., compact disk (CD), digital versatile disk (DVD)), smart cards, and flash memory devices (e.g., card, stick, key drive). Of course, those skilled in the art will recognize many modifications can be made to this configuration without departing from the scope or spirit of the various embodiments.

(20) Moreover, terms such as “mobile device equipment,” “mobile station,” “mobile,” “subscriber station,” “access terminal,” “terminal,” “handset,” “communication device,” “mobile device” (and/or terms representing similar terminology) can refer to a wireless device utilized by a subscriber or mobile device of a wireless communication service to receive or convey data, control, voice, video, sound, gaming or substantially any data-stream or signaling-stream. The foregoing terms are utilized interchangeably herein and with reference to the related drawings. Likewise, the terms “access point (AP),” “Base Station (BS),” BS transceiver, BS device, cell site, cell site device, “gNode B (gNB),” “evolved Node B (eNode B),” “home Node B (HNB)” and the like, are utilized interchangeably in the application, and refer to a wireless network component or appliance that transmits and/or receives data, control, voice, video, sound, gaming or substantially any data-stream or signaling-stream from one or more subscriber stations. Data and signaling streams can be packetized or frame-based flows.

(21) Furthermore, the terms “device,” “communication device,” “mobile device,” “subscriber,” “customer entity,” “consumer,” “customer entity,” “entity” and the like are employed interchangeably throughout, unless context warrants particular distinctions among the terms. It should be appreciated that such terms can refer to human entities or automated components supported through artificial intelligence (e.g., a capacity to make inference based on complex mathematical formalisms), which can provide simulated vision, sound recognition and so forth.

(22) Embodiments described herein can be exploited in substantially any wireless communication technology, comprising, but not limited to, wireless fidelity (Wi-Fi), global system for mobile communications (GSM), universal mobile telecommunications system (UMTS), worldwide interoperability for microwave access (WiMAX), enhanced general packet radio service (enhanced GPRS), third generation partnership project (3GPP) long term evolution (LTE), third generation partnership project 2 (3GPP2) ultra-mobile broadband (UMB), fifth generation core (5G Core), fifth generation option 3x (5G Option 3x), high speed packet access (HSPA), Z-Wave, Zigbee and other 802. XX wireless technologies and/or legacy telecommunication technologies.

(23) FIG. 1 illustrates a non-limiting example of a wireless communication system **100** which can be used in connection with at least some embodiments of the subject disclosure. In one or more embodiments, system **100** can comprise one or more user equipment UEs **102.sub.1**, **102.sub.2**, referred to collectively as UEs **102**, a network node **104**, and communication service provider network(s) **106**.

(24) In an example embodiment, mobile subscriber devices, such as UGVs, described herein, can be implemented as UEs **102**. Alternatively, mobile subscriber devices can access a wireless communication system **100** through UEs **102**. A map authority, also described herein, can be implemented as a server within communication service provider network(s) **106**. Alternatively, the map authority described herein can be accessible via communication service provider network(s) **106**, e.g., the map authority can be implemented as an Internet service accessible via a network connection between communication service provider network(s) **106** and the Internet.

(25) The non-limiting term “user equipment” can refer to any type of device that can communicate with a network node **104** in a cellular or mobile communication system **100**. UEs **102** can have one or more antenna panels having vertical and horizontal elements. Examples of UEs **102** comprise target devices, device to device (D2D) UEs, machine type UEs or UEs capable of machine to machine (M2M) communications, personal digital assistants (PDAs), tablets, mobile terminals, smart phones, laptop mounted equipment (LME), universal serial bus (USB) dongles enabled for mobile communications, computers having mobile capabilities, mobile devices such as cellular phones, laptops having laptop embedded equipment (LEE, such as a mobile broadband adapter), tablet computers having mobile broadband adapters, wearable devices, virtual reality (VR) devices, heads-up display (HUD) devices, smart cars, machine-type communication (MTC) devices, augmented reality head mounted displays, and the like. UEs **102** can also comprise IOT devices that communicate wirelessly.

(26) In various embodiments, system **100** comprises communication service provider network(s) **106** serviced by one or more wireless communication network providers. Communication service provider network(s) **106** can comprise a “core network”. In example embodiments, UEs **102** can be communicatively coupled to the communication service provider network(s) **106** via network node **104**. The network node **104** (e.g., network node device) can communicate with UEs **102**, thus providing connectivity between the UEs **102** and the wider cellular network. The UEs **102** can send transmission type recommendation data to the network node **104**. The transmission type recommendation data can comprise a recommendation to transmit data via a closed loop MIMO mode and/or a rank-1 precoder mode.

(27) A network node **104** can have a cabinet and other protected enclosures, computing devices, an antenna mast, and multiple antennas for performing various transmission operations (e.g., MIMO operations) and for directing/steering signal beams. Network node **104** can comprise one or more base station devices which implement features of the network node **104**. Network nodes can serve several cells, also called sectors, depending on the configuration and type of antenna. In example embodiments, UEs **102** can send and/or receive communication data via a wireless link to the network node **104**. The dashed arrow lines from the network node **104** to the UEs **102** represent downlink (DL) communications and the solid arrow lines from the UEs **102** to the network node **104** represents an uplink (UL) communications.

(28) Communication service provider networks **106** can facilitate providing wireless communication services to UEs **102** via the network node **104** and/or various additional network devices (not shown) included in the one or more communication service provider networks **106**. The one or more communication service provider networks **106** can comprise various types of disparate networks, including but not limited to: cellular networks, femto networks, picocell networks, microcell networks, internet protocol (IP) networks Wi-Fi service networks, broadband service network, enterprise networks, cloud based networks, millimeter wave networks and the like. For example, in at least one implementation, system **100** can be or comprise a large scale



wireless communication network that spans various geographic areas. According to this implementation, the one or more communication service provider networks **106** can be or comprise the wireless communication network and/or various additional devices and components of the wireless communication network (e.g., additional network devices and cell, additional UEs, network server devices, etc.).

(29) The network node **104** can be connected to the one or more communication service provider networks **106** via one or more backhaul links **108**. For example, the one or more backhaul links **108** can comprise wired link components, such as a T1/E1 phone line, a digital subscriber line (DSL) (e.g., either synchronous or asynchronous), an asymmetric DSL (ADSL), an optical fiber backbone, a coaxial cable, and the like. The one or more backhaul links **108** can also comprise wireless link components, such as but not limited to, line-of-sight (LOS) or non-LOS links which can comprise terrestrial air-interfaces or deep space links (e.g., satellite communication links for navigation). In an embodiment, network node **104** can be part of an integrated access and backhaul network. This may allow easier deployment of a dense network of self-backhauled 5G cells in a more integrated manner by building upon many of the control and data channels/procedures defined for providing access to UEs.

(30) Wireless communication system **100** can employ various cellular systems, technologies, and modulation modes to facilitate wireless radio communications between devices (e.g., the UE **102** and the network node **104**). While example embodiments might be described for 5G new radio (NR) systems, the embodiments can be applicable to any radio access technology (RAT) or multi-RAT system where the UE operates using multiple carriers e.g., LTE FDD/TDD, GSM/GERAN, CDMA2000 etc.

(31) For example, system **100** can operate in accordance with global system for mobile communications (GSM), universal mobile telecommunications service (UMTS), long term evolution (LTE), LTE frequency division duplexing (LTE FDD, LTE time division duplexing (TDD), high speed packet access (HSPA), code division multiple access (CDMA), wideband CDMA (WCDMA), CDMA2000, time division multiple access (TDMA), frequency division multiple access (FDMA), multi-carrier code division multiple access (MC-CDMA), single-carrier code division multiple access (SC-CDMA), single-carrier FDMA (SC-FDMA), orthogonal frequency division multiplexing (OFDM), discrete Fourier transform spread OFDM (DFT-spread OFDM) single carrier FDMA (SC-FDMA), Filter bank based multi-carrier (FBMC), zero tail DFT-spread-OFDM (ZT DFT-s-OFDM), generalized frequency division multiplexing (GFDM), fixed mobile convergence (FMC), universal fixed mobile convergence (UFMC), unique word OFDM (UW-OFDM), unique word DFT-spread OFDM (UW DFT-Spread-OFDM), cyclic prefix OFDM CP-OFDM, resource-block-filtered OFDM, Wi Fi, WLAN, WiMax, and the like. However, various features and functionalities of system **100** are particularly described wherein the devices (e.g., the UEs **102** and the network device **104**) of system **100** are configured to communicate wireless signals using one or more multi carrier modulation schemes, wherein data symbols can be transmitted simultaneously over multiple frequency subcarriers (e.g., OFDM, CP-OFDM, DFT-spread OFDM, UFMC, FBMC, etc.). The embodiments are applicable to single carrier as well as to multicarrier (MC) or carrier aggregation (CA) operation of the UE. The term carrier aggregation (CA) is also called (e.g., interchangeably called) “multi-carrier system”, “multi-cell operation”, “multi-carrier operation”, “multi-carrier” transmission and/or reception. Note that some embodiments are also applicable for Multi RAB (radio bearers) on some carriers (that is data plus speech is simultaneously scheduled).

(32) In various embodiments, system **100** can be configured to provide and employ 5G or subsequent generation wireless networking features and functionalities. 5G wireless communication networks are expected to fulfill the demand of exponentially increasing data traffic and to allow people and machines to enjoy gigabit data rates with virtually zero (e.g., single digit millisecond) latency. Compared to 4G, 5G supports more diverse traffic scenarios. For example, in

addition to the various types of data communication between conventional UEs (e.g., phones, smartphones, tablets, PCs, televisions, internet enabled televisions, AR/VR head mounted displays (HMDs), etc.) supported by 4G networks, 5G networks can be employed to support data communication between smart cars in association with driverless car environments, as well as machine type communications (MTCs). Considering the drastic different communication needs of these different traffic scenarios, the ability to dynamically configure waveform parameters based on traffic scenarios while retaining the benefits of multi carrier modulation schemes (e.g., OFDM and related schemes) can provide a significant contribution to the high speed/capacity and low latency demands of 5G networks. With waveforms that split the bandwidth into several sub-bands, different types of services can be accommodated in different sub-bands with the most suitable waveform and numerology, leading to an improved spectrum utilization for 5G networks.

(33) To meet the demand for data centric applications, features of proposed 5G networks can comprise: increased peak bit rate (e.g., 20 Gbps), larger data volume per unit area (e.g., high system spectral efficiency—for example about 3.5 times that of spectral efficiency of long term evolution (LTE) systems), high capacity that allows more device connectivity both concurrently and instantaneously, lower battery/power consumption (which reduces energy and consumption costs), better connectivity regardless of the geographic region in which a user is located, a larger numbers of devices, lower infrastructural development costs, and higher reliability of the communications. Thus, 5G networks can allow for: data rates of several tens of megabits per second should be supported for tens of thousands of users, 1 gigabit per second to be offered simultaneously to tens of workers on the same office floor, for example; several hundreds of thousands of simultaneous connections to be supported for massive sensor deployments; improved coverage, enhanced signaling efficiency; reduced latency compared to LTE.

(34) The upcoming 5G access network can utilize higher frequencies (e.g., >6 GHz) to aid in increasing capacity. Currently, much of the millimeter wave (mmWave) spectrum, the band of spectrum between 30 GHz and 300 GHz is underutilized. The millimeter waves have shorter wavelengths that range from 10 millimeters to 1 millimeter, and these mmWave signals experience severe path loss, penetration loss, and fading. However, the shorter wavelength at mmWave frequencies also allows more antennas to be packed in the same physical dimension, which allows for large-scale spatial multiplexing and highly directional beamforming.

(35) Performance can be improved if both the transmitter and the receiver are equipped with multiple antennas. Multi-antenna techniques can significantly increase the data rates and reliability of a wireless communication system. The use of multiple input multiple output (MIMO) techniques, which was introduced in the 3GPP and has been in use (including with LTE), is a multi-antenna technique that can improve the spectral efficiency of transmissions, thereby significantly boosting the overall data carrying capacity of wireless systems. The use of MIMO techniques can improve mmWave communications and has been widely recognized a potentially important component for access networks operating in higher frequencies. MIMO can be used for achieving diversity gain, spatial multiplexing gain and beamforming gain. For these reasons, MIMO systems are an important part of the 3rd and 4th generation wireless systems and are planned for use in 5G systems.

(36) FIG. 2 illustrates an example map authority that hosts a shared overlay map service and a truth maintenance module, along with example subscriber devices that use the shared overlay map service, in accordance with various aspects and embodiments of the subject disclosure. FIG. 2 includes a map authority **200** comprising a shared overlay map service **210** and a truth maintenance module **215**. The techniques disclosed herein can employ truth maintenance module **215** in conjunction with a shared overlay map service **210**, however, the shared overlay map service **210** is not necessary for operation of the truth maintenance module **215**, and in some embodiments, truth maintenance module **215** can be employed, e.g., in connection with other digital map technologies.

(37) The illustrated subscriber devices **221**, **222**, **223**, **224**, and **260** comprise multiple example

mobile subscriber devices (MSDs) **221**, **222**, **223**, and **224**, and a server **260**. The server **260** provides an example subscriber device which is not necessarily mobile. In an embodiment, any of the MSDs **221**, **222**, **223**, and **224** can be in the form of an unmanned ground vehicle (UGV), such as illustrated in FIG. 4, however, in other embodiments, MSDs **221**, **222**, **223**, and **224** can comprise any mobile device equipped to use wireless communications and digital navigational maps. The server **260** can comprise, e.g., a government operated server that controls restricted areas for certain subscriber devices, such as UGVs. Embodiments of this disclosure allow rapid, flexible, and immediately effective deployment of different types of restriction zones to different types of subscriber devices, regardless of which specific navigation systems are employed at the subscriber devices.

(38) In an example embodiment, the MSDs **221**, **222**, **223**, and **224**, and the server **260** can communicate with the shared overlay map service **210** via a wireless communication system **100** such as illustrated in FIG. 1. The MSDs **221**, **222**, **223**, and **224**, and the server **260** can send and receive map inputs, also referred to herein as active/smart overlays (ASOs), to and from the shared overlay map service **210**. For example, any of the MSDs, e.g., MSD **221**, can generate and send an ASO **212** to the shared overlay map service **210**. The shared overlay map service **210** can receive the ASO **212**, use the truth maintenance module **215** to check credibility of the ASO **212**, and, when the ASO **212** is sufficiently credible, the shared overlay map service **210** can promulgate the ASO **212** to the multiple subscriber devices **221**, **222**, **223**, **224**, and **260**. ASOs can also be referred to herein as map overlay information. In general, any of the MSDs **221**, **222**, **223**, and **224**, and the server **260** can send ASOs to the shared overlay map service **210**, and the shared overlay map service **210** can promulgate received ASOs to some or all of the MSDs **221**, **222**, **223**, **224**, and the server **260**.

(39) The example MSDs **221**, **222**, **223**, and **224** can each comprise a digital navigational map (DNM). In the illustrated example, some of the MSDs, namely, MSDs **221** and **222**, comprise a first digital navigational map DNM.sub.1 **231**, while others of the MSDs, namely, MSDs **223** and **224**, comprise a second digital navigational map DNM.sub.2 **232**. Furthermore, the example MSDs **221**, **222**, **223**, and **224** can each comprise an ASO manager **250**.

(40) The ASO managers **250** can be configured to generate and send ASO updates to the shared overlay map service **210**. The ASO managers **250** can furthermore be configured to receive ASOs, such as ASO **212**, from the shared overlay map service **210**, and the ASO managers **250** can be configured to associate received ASOs with the DNM, i.e., with either DNM.sub.1 **231** or DNM.sub.2 **232** depending on which of the DNMs is used by an MSD. The illustrated configuration allows sharing of ASOs while also permitting individual MSDs to use different DNMs, as well as using different navigation system software or other applications that interact with the different DNMs **231** and **232**.

(41) In general, the truth maintenance module **215** can be configured to filter map inputs such as ASO **212** based on credibility thereof, approving credible map inputs for promulgation to subscriber devices **221**, **222**, **223**, **224**, and **260**, while blocking promulgation of non-credible or irrelevant map inputs.

(42) DNMs such as Apple Maps®, Google Maps® and OpenStreetMap® are useful for individuals and UGVs alike. DNMs are also embedded in various devices, such as devices made by TomTom® and Garmin®. DNM users can update some DNMs by adding features and annotations that can be of interest to other users. However, such updates are presently limited to the specific vendor maps employed by the user's device. For example, users of Waze® can share updates with other users of Waze®, but not with users of other DNMs. The shared overlay maps described herein allow for sharing map updates across different DNM platforms.

(43) User generated DNM annotations are preferably reliable and credible. Without restrictions on who can post annotations/updates to DNMs, and mechanisms to validate user DNM updates or assign different priority and confidence values to user updates, relevant user updates can potentially

become lost in the noise of spurious user updates. For example, a user update such as “bush fire at intersection of Hwy 5 and Hwy 580,” if shared by a fire department, should have both a high priority and confidence. A user update such as “see smoke in the direction of Hwy 5 while driving on Hwy 580 towards Hwy 5” by an anonymous individual is of less priority and confidence.

(44) DNMs are used by various types of users, e.g., humans using special navigational devices such as TomTom®, self-driving cars, and UGVs (e.g., service robots). Using shared overlay maps, DNMs can be modified in real-time by users with annotations/content that can help other users. For example, a user might put an annotation/content about an oil spill at some location on a map, and the annotation can be pushed out to other users. Support for user generated annotations is a powerful capability; however, to be truly useful the resulting map should also be credible.

(45) The truth maintenance module **215** can be configured to enhance credibility of user map inputs. A variety of techniques can be applied, individually or in combination. These techniques can include, for example: identifying a credibility of a user posting a map input, identifying a credibility of the map input itself, and identifying a credibility of a location and time at which the map input is reported.

(46) Furthermore, the truth maintenance module **215** can be configured to remove map inputs after they are no longer relevant. For example, an annotation of an “oil spill” at location X can be removed after the spill condition has been cleared. Also, the truth maintenance module **215** can be configured to identify and consolidate duplicate map inputs. For example, a map input “fire hydrant broken at location X” and “water spill near location X” likely refer to a same event and are preferably reduced to one map input.

(47) In some embodiments, the truth maintenance module **215** can incorporate truth maintenance system (TMS) technologies. TMS technologies can use algorithms to restore consistency of a knowledge representation. Example truth maintenance systems include single-context truth maintenance systems, multi-context truth maintenance systems, and multi-agent truth maintenance systems. In single context systems, consistency is maintained among all facts in memory. In multi-context systems, consistency can be maintained among subsets of facts in memory. In multi-agent truth maintenance systems, truth maintenance can be performed across multiple memories.

(48) For the purpose of this disclosure, a knowledge representation maintained by the truth maintenance module **215** can be, e.g., a set of map properties (roads, buildings, bridges, etc.) and map inputs for a given map region. The truth maintenance module **215** can maintain consistency between previous credible knowledge and new credible knowledge through revision. If new credible knowledge contradicts the previous credible knowledge, then the knowledge representation can optionally be updated with the new credible knowledge.

(49) The truth maintenance module **215** can maintain records in the form of a dependency network. Nodes in the dependency network can include entries in the knowledge representation. Arcs of the dependency network can include inference steps through which nodes were derived. Premises are fundamental beliefs which are assumed to be true. Premises do not need justifications, and form the basis from which justifications for other nodes can be derived.

(50) The truth maintenance module **215** can evaluate credibility of a given map input using information such as identity of a user (or device) who is posting the map input, location and time of map input generation, and correlation between the user and the map input, in particular whether the user has a qualification relevant to the map input. An example configuration of the truth maintenance module **215** is illustrated in FIG. 5.

(51) FIG. 3A illustrates an example shared overlay map for use by a shared overlay map service, in accordance with various aspects and embodiments of the subject disclosure. The example shared overlay map **300** can include a coordinate system to define locations within the shared overlay map **300**, and features such as example feature **302** with defined locations within the shared overlay map **300**.

(52) FIG. 3A includes an example Cartesian (x, y) type coordinate system, however, it will be

appreciated that other coordinate systems can be used, such as polar coordinates, spherical coordinates, volumetric (x, y, z) coordinates, etc. In an embodiment, a shared overlay map service such as shared overlay map service **210** illustrated in FIG. 2 can include a shared overlay map **300** as a reference map, for use in connection with processing ASO updates **212**.

(53) In an example embodiment, the shared overlay map **300** can represent a city, and the illustrated features **302** can represent city blocks and city streets. In another example embodiment, the illustrated shared overlay map **300** can represent an indoor environment, e.g., inside a physical structure, and features **302** can represent, for example, hallways and rooms. The shared overlay map **300** can generally represent any terrain, and features **302** can represent any features.

(54) FIG. 3B illustrates an example map overlay (also referred to herein as a map input) that can be applied to the shared overlay map of FIG. 3A, in accordance with various aspects and embodiments of the subject disclosure. The example map overlay is implemented as ASO **310**. The ASO **310** provides an example restriction zone map overlay to indicate a restriction zone **312** where mobile subscriber devices, e.g., MSDs **221**, **222**, **223**, and **224**, are not permitted to travel. The ASO **310** is one example of a map overlay, and a wide variety of other map overlays can be generated according to the teachings provided herein. Further example map overlays are illustrated in FIG. 6.

(55) In FIG. 3B, the ASO **310** can include location information, e.g., the illustrated x.sub.1, y.sub.1 coordinate. The x.sub.1, y.sub.1 coordinate can reference, e.g., a coordinate of a location on the shared overlay map **300**. The ASO **310** location information thereby includes location information to position the ASO **310** on the shared overlay map **300**. Further location information, or else dimension information, such as the illustrated width and height dimensions (w<sub>2</sub>, h<sub>2</sub>) of the restriction zone **312** and the illustrated width and height dimensions (w<sub>1</sub>, h<sub>1</sub>) of the unrestricted zone, can be used to position further portions of the ASO **310** on the shared overlay map **300**.

(56) FIG. 3B furthermore illustrates metadata **314** which can be linked to the ASO **310** in some embodiments. The metadata **314** can optionally include any data desired to accompany the ASO **310**. For example, the metadata **314** can include a time at which the ASO **310** was generated at a subscriber device, an identification of the subscriber device that generated the ASO **310**, a location of the subscriber device at the time the subscriber device generated the ASO **310**, and/or a wide variety of other information, such as photos and videos of the location where the ASO **310** was generated and sensor values of any sensors at the subscriber device when the ASO **310** was generated.

(57) FIG. 3C illustrates an example combination of the map overlay illustrated in FIG. 3B with a digital navigational map at a mobile subscriber device, in accordance with various aspects and embodiments of the subject disclosure. FIG. 3C illustrates a DNM with ASO **320**, wherein the map overlay ASO **310** of FIG. 3B is positioned on a DNM at a subscriber device.

(58) In an example scenario according to FIG. 3C, a first subscriber device can generate the ASO **310** illustrated in FIG. 3B. The first subscriber device can upload the ASO **310** to a map authority including a shared overlay map **300** such as illustrated in FIG. 3A. The map authority can then promulgate the ASO **310** to multiple subscriber devices, each of the multiple subscriber devices including a DNM. At least one of the multiple subscriber devices can position the received ASO **310** on its DNM, in order to produce a DNM with ASO **320** such as illustrated in FIG. 3C. The coordinate x<sub>1</sub>, y<sub>1</sub> can be translated as necessary, e.g., by an ASO manager **250**, to correctly position the received ASO **310** on a subscriber device DNM. The subscriber device including the DNM with ASO **320** can then use the DNM with ASO **320** according to its own navigational procedures. For example, the subscriber device can avoid navigating into the restriction zone **312** and instead remain inside the boundaries of the unrestricted zone.

(59) A map overlay such as ASO **310** can be generated by a governmental authority such as a city transportation authority. In such a scenario, the governmental authority is a highly credible user and the truth maintenance module **215** can assign the ASO **310** a high credibility value. As a result, the credibility value for ASO **310** can exceed any threshold credibility value used to filter low-

credibility map inputs. The truth maintenance module **215** can approve promulgation of the ASO **310** by the shared overlay map service **210** to subscriber devices. In other circumstances, credibility may be more difficult to determine and may not be approved for promulgation, as will be described further herein.

(60) FIG. **4** illustrates an unmanned ground vehicle (UGV), as one example implementation of a mobile subscriber device, in accordance with various aspects and embodiments of the subject disclosure. FIG. **4** includes example UGV **400**, which can include, for example, a computer **410** and various sensors **456** inside a housing that rides on wheels. The computer **410** can communicate with remote devices, such as remote servers that host a navigation service **435** and a map authority **200**, via a wireless communication system **100** such as illustrated in FIG. **1**. The UGV **400** is one example implementation of an MSD such as MSD **221**, introduced in FIG. **2**.

(61) The example computer **410** can be communicatively coupled with sensor(s) **456**, and the computer **410** can comprise a navigation system **430**, a DNM **431**, and an ASO manager **450**. The ASO manager **450** can comprise an ASO generator **454**, and a DNM updater **452**.

(62) In an example operation of UGV **400**, a sensor of sensor(s) **456** can detect an input, for example, a route blocking obstruction which prevents UGV **400** from navigating on its calculated route. The sensor can send the input to the ASO generator **454**. The ASO generator **454** can generate a map overlay in the form of ASO **472**, and the ASO manager **450** can upload the ASO **472** to the map authority **200**. The map authority **200** can perform any modifications to ASO **472**, thereby generating ASO **474**, and the map authority **200** can promulgate the ASO **474** to multiple subscriber devices, such as UGVs. The ASO **474** can be received by UGV **400**, that is, the same UGV **400** that originally generated ASO **472**, as well as other subscriber devices.

(63) The received ASO **474** can be processed by DNM updater **452**. The DNM updater can update DNM **431** to include the received ASO **474**. The navigation system **430** can then use the updated DNM **431**, including ASO **474**, in connection with route calculations for UGV **400**. The navigation system **430** can for example communicate with navigation service **435**, by sending and receiving navigation data **482**. The navigation system **430** can be configured to recalculate routes for the UGV **400** in view of the received ASO **474**.

(64) In an alternative embodiment, UGV **400** can be equipped with limited local processing power, and some or all UGV **400** processing can be done remotely. A remote system, e.g., navigation service **435**, can provide any of the UGV **400** processing functions illustrated in FIG. **4**, including the communications with the map authority **200**, and the navigation service **435** can send navigation commands wirelessly to the UGV **400**.

(65) Sensor(s) **456** can optionally comprise, for example, machine vision sensors, such as cameras, lasers, sonar, radar and/or LIDAR, acoustic sensors such as a microphone, wireless signal sensors such as antennae to measure wireless signal strengths, including cellular radio signals and Wi-Fi, location sensors such as global positioning system (GPS) units, accelerometers, pressure sensors, or any other sensors.

(66) In some embodiments, a sensor input can be inserted directly into information for a generated ASO **472**. For example, ASO generator **454** can include a wireless signal strength measurement, or a detected location of the UGV **400**, in an ASO **472**, along with shared overlay map **300** location information or other metadata **314**. In other embodiments, computer **410** can include software to process sensor inputs to determine appropriate map overlay information to include in an ASO **472**. For example, a multifactor analysis, based in part on machine vision sensor inputs and/or other sensor inputs, can be performed at computer **410** to conclude that a route blockage exists which prevents the UGV **400** from traveling an intended route. ASO generator **454** can place a route blockage determination, optionally along with supporting sensor inputs, in an ASO **472** to be sent to the map authority **200**.

(67) Map inputs generated by robotic subscriber devices, such as UGV **400**, can optionally be processed separately by the truth maintenance module **215**, that is, by different truth maintenance

processing functions than used for human generated map inputs. A UGV map input such as ASO **472** can generally be treated as highly credible, however, there is also a high probability that the map input may be duplicative or irrelevant. Truth maintenance module **215A** can optionally include robot map input processing for assigning credibility values to robot generated map inputs.

(68) In some embodiments, a subscriber device such as UGV **400** can furthermore be configured to send and receive monitoring data **476**. The monitoring data **476** can include monitoring requests from the map authority **200**, and monitoring responses (responses to monitoring requests) generated at UGV **400**. For example, the map authority **200** may send a monitoring request for a photograph of a particular location. The ASO manager **450** can be configured to take the requested photograph and send it to map authority **200** as monitoring data **476**. Monitoring requests and responses are described further in connection with FIG. 5.

(69) FIG. 5 illustrates an example map authority server, in accordance with various aspects and embodiments of the subject disclosure. The illustrated example map authority server **500** can include a shared overlay map service **502** and a truth maintenance module **515**. In an embodiment, the map authority server **500** can implement a map authority **200** such as illustrated in FIG. 2, the shared overlay map service **502** can implement a shared overlay map service **210** such as illustrated in FIG. 2, and the truth maintenance module **515** can implement a truth maintenance module **215** such as illustrated in FIG. 2.

(70) The map authority server **500** can communicate with subscriber devices **570** and subscriber device **550** via a wireless communication system **100** such as illustrated in FIG. 1. The subscriber devices **570** and **550** can include, e.g., UGVs such as example UGV **400** illustrated in FIG. 4. Otherwise, subscriber devices **570** and **550** can be implemented by any mobile devices, including mobile telephones, tablets, self-driving cars, and other mobile devices. In some embodiments, subscriber devices **570** and **550** can also include one or more stationary devices, e.g., a stationary server **260** such as illustrated in FIG. 2.

(71) The example shared overlay map service **502** can include a shared overlay map **510**, a shared overlay map (SOM) application programming interface (API) **520**, an ASO validator **522**, an ASO store **524**, and a subscriber group determination unit **526**. The shared overlay map **510** can implement at shared overlay map **300** such as illustrated in FIG. 3A. The various components of the shared overlay map service **502** are described below in connection with example operations of the shared overlay map service **502**.

(72) The example truth maintenance module **515** can include a credibility module **530**, a credibility machine learning (ML) module **531**, a normalizer **532**, and a map input monitor **533**. The credibility module **530** can retrieve user identity information from user identity data **540**. The various components of the truth maintenance module **515** are described below in connection with example operations of the truth maintenance module **515**.

(73) In an example operation sequence, an incoming ASO **572** can be received at SOM API **520** from a subscriber device **550**. The SOM API **520** can expose a network API supporting automated accesses to the shared overlay map service **502** by subscriber devices **570** and **550**. The SOM API **520** can pass the received ASO **572** to ASO validator **522**. The ASO validator **522** can process the ASO **572** to ensure ASO **572** complies with shared overlay map service **502** requirements. The ASO validator **522** can pass ASO **572** to the truth maintenance module **515**, and the truth maintenance module **515** can return a credibility determination **535**. In an embodiment, the credibility determination **535** can comprise a YES/NO determination of whether the ASO **572** is credible or not. The shared overlay map service **502** can be configured to further process and promulgate credible ASOs, while deferring or declining promulgation of non-credible ASOs. Other example requirements that can be enforced by ASO validator **522** include timeliness requirements, data structure requirements, data completeness requirements, subscriber device identification requirements, or other requirements as may be appropriate for particular embodiments.

(74) The ASO validator **522** can optionally modify the ASO **572**. The ASO validator **522** can use

the shared overlay map **510** in connection with processing the ASO **572**, for example, to refine or otherwise modify location information included in ASO **572**, or to check redundancy of ASO **572** with other ASOs in the ASO store **524**. Once the ASO **572** is validated, the ASO validator **522** can store the ASO **572** along with other ASOs in the ASO store **524**.

(75) The subscriber group determination unit **526** can determine a subscriber group, namely, a group of the subscriber devices **570**, to receive the ASO **572**. In some embodiments, the subscriber devices **570** can be divided into different groups, and an ASO originating from any subscriber device within a particular subscriber group can be promulgated to the other subscriber devices of the same particular subscriber group.

(76) In other embodiments, the subscriber group determination unit **526** can determine an appropriate group of subscriber devices **570** for each ASO **572**. The group of subscriber devices **570** can be determined based on relevance of the ASO **572** to the subscriber devices **570**. For example, an ASO including a UGV restriction zone may be relevant to only UGV type subscriber devices, and so the subscriber group determination unit **526** can send such a restriction zone ASO to only UGV subscriber devices. Subscriber device type and subscriber device ASO preferences can optionally be gathered by shared overlay map service **502** during a subscriber device enrollment process, and subscriber device information can be provided to subscriber group determination unit **526** for use in determining a group of subscriber devices **570** for each new ASO **572**.

(77) The subscriber group determination unit **526** can pass subscriber device group information to SOM API **520**, and the SOM API **520** can send ASO **572** to the group of subscriber devices **570**.

(78) The operations of the truth maintenance module **515** can include determining and supplying credibility determination **535** with regard to ASO **572**. In an example, ASO **572** can include a report from subscriber device **550** of a smoke cloud indicating a possible fire at a location. The ASO **572** can initially be received at the credibility module **530**, and the credibility module **530** can be configured to assign the credibility determination **535** to the ASO **572** and return the credibility determination **535** to the shared overlay map service **502**.

(79) The credibility module **530** can calculate the credibility determination **535** based on one or more credibility factors, including, e.g., a location and time of the subscriber device **550** when the ASO **572** was generated; a user identity associated with a user of the subscriber device **550**, a profile of the user identity of a user of the subscriber device **550**, a credibility score associated with the user identity of the user of the subscriber device **550**, a nature of the event described in ASP **570**, and any correlation between the nature of the event and the profile of the user identity.

(80) In an embodiment, the credibility module **530** can retrieve a user identity **537** corresponding to the ASO **572**, e.g., where the user identity **537** is that of a user associated with subscriber device **550**. In the illustrated embodiment, the credibility module obtains the user identity **537** from an external source, e.g., a communication service provider database. In our example, different credibility values can be associated with different user identities. Furthermore, higher credibility values can be assigned to ASOs when a user identity **537** includes a credential related to the content of the ASO **572**, e.g., where user identity **537** indicates that the user is a fire department employee, and lower credibility values can be assigned to ASOs when a user identity **537** does not include a credential related to the content of the ASO **572**.

(81) The credibility module **530** can operate in conjunction with the normalizer **532**. In an embodiment, the ASO **572** can be furthermore processed by the normalizer **532**. The normalizer **532** can be configured to account for multiple events in a geographical area. For example, functions of the normalizer **532** can include: resolving conflicts between two or more reported events; consolidating multiple reports of a same event; and assigning a confidence factor to ASO **572** based on a number of confirming reports as well as similarity of the confirming reports.

(82) In some embodiments, the normalizer **532** can be configured to generate a new, high credibility ASO based on multiple received ASOs such as ASO **572**. The high credibility ASO can



be provided to the shared overlay map service **502**, e.g., in lieu of credibility determination **535**, and the shared overlay map service **502** can promulgate the high credibility ASO to subscriber devices **570** in lieu of one or more individual ASOs, such as ASO **572**.

(83) In some embodiments, the truth maintenance module **515** and/or the normalizer **532** can be configured to employ a map input monitor **533** to gather further information about ASOs. The map input monitor **533** can be configured to send and receive monitoring requests/responses **539** to selected devices of subscriber devices **570**, namely, to devices in the vicinity of an event described in an ASO **572**. The monitoring requests can request validation and/or status of a reported event, and the monitoring responses can provide such validation and/or status information.

(84) In some embodiments, the truth maintenance module **515** can be configured to employ a credibility machine learning (ML) module **531**. The credibility ML module **531** can use credibility information from normalizer **532** and credibility module **530** to improve future credibility determinations, e.g., by updating credibility data associated with different user identities, based on previous credibility determinations.

(85) FIG. **6** illustrates an example shared overlay map and additional example map overlays, in accordance with various aspects and embodiments of the subject disclosure. The shared overlay map **600** can include an implementation of the shared overlay map **510** illustrated in FIG. **5**, or the shared overlay map **300** illustrated in FIG. **3**. Several example map overlays are illustrated on the shared overlay map **600**. The illustrated map overlays can be generated using data from ASOs or navigation advisories described herein. This disclosure provides example map overlays, and further map overlays can be generated with the benefit of this disclosure, and credibility of received map overlays can be evaluated according the techniques described herein.

(86) Some map overlays can comprise location updates, such as location updates **602** and location updates **612**. In an embodiment, subscriber devices such as UGVs can send ASOs comprising location updates indicating current locations of the subscriber devices. A first UGV can send location updates **602**, while a second UGV can send location updates **612**. The location updates **602** and **612** can optionally be sent periodically, or else, as a function of UGV displacement since a previous location update. The location updates **602** and **612** are illustrated in FIG. **6** as a time series of updates, with older location updates progressively fading away. In an implementation, a map authority can optionally store location histories of location updates **602** and **612**, and can optionally promulgate a limited amount of location history information to subscriber devices, in addition to current subscriber device locations. Location history can be useful for example to allow UGV subscriber devices to determine speed and direction of travel of other UGVs.

(87) Information such as location updates **602** and **612**, especially from robots such as UGVs, is an example of highly credible information which can receive a high credibility score. Location information is generally easy to determine by a subscriber device and is not prone to human judgement or interpretation error.

(88) Some map overlays can include wireless coverage information, such as wireless coverage area **604** and wireless coverage area **606**. Wireless coverage areas can potentially overlap. Map inputs comprising wireless coverage information can include, for example, wireless signal identification information and measured wireless signal strength at different locations within the shared overlay map **600**. In an embodiment, wireless coverage area **604** can comprise a region associated with a first wireless signal, and wireless coverage area **606** can comprise a region associated with a second wireless signal. Alternatively, wireless coverage area **604** can comprise a region of strong wireless signal strength, while wireless coverage area **606** can comprise a region of limited or no wireless signal strength. The measured wireless signals can comprise, e.g., cellular radio signals, Wi-Fi signals, or other wireless signals. Some UGVs make heavy, near continuous use of wireless communications, and so wireless coverage information can affect navigation route decisions. Like location updates, wireless coverage information can be assigned high credibility values in some embodiments.

(89) Some map overlays can comprise route blockage information, for example, route blockage **610** and route blockage **608**. Route blockage information can comprise an indication that travel is blocked at a location on the shared overlay map **600**. Route blockage information can optionally specify a portion of a road or sidewalk and/or a direction of travel which is blocked. Furthermore, route blockage information can comprise any information, such as sensor values, pertaining to the route blockage. For example, a route can be blocked due to long term blockage such as construction, or due to short term blockage such as a safety operation, e.g., a car accident response. Route blockage information is generally less credible when received from a UGV subscriber, while it may be more credible when received from a human user, especially if the user location is at the route blockage or displays a location history leading to the route blockage, such as location updates **602** leading to route blockage **608**. If received from a police officer or transportation official, route blockage information can be highly credible

(90) In addition to the example map overlays described herein, some embodiments can be configured to support map overlay annotations. Map overlay annotations can comprise a lightweight annotation to an ASO, to provide some further relevant information for the map overlay. Map overlay annotations can be handled similarly to the map overlays themselves, i.e., generated at a subscriber device, sent to a shared overlay map service, and then promulgated to multiple other subscriber devices.

(91) The map overlays illustrated in FIG. 6, e.g., the location updates **612**, can be generated by mobile subscriber devices, sent to a shared overlay map service, evaluated by a truth maintenance module, and, if credible, promulgated by the shared overlay map service to a plurality of mobile subscriber devices. Other map overlays, e.g., the restriction zone map overlay illustrated in FIG. 3B, can be generated by a stationary server, such as server **260**, sent to a shared overlay map service, optionally evaluated by a truth maintenance module, and, if credible, promulgated by the shared overlay map service to a plurality of mobile subscriber devices.

(92) FIG. 7 is a flow diagram representing example operations of a server comprising a truth maintenance module for map inputs, in accordance with various aspects and embodiments of the subject disclosure. The illustrated blocks can represent actions performed in a method, functional components of a computing device, or instructions implemented in a machine-readable storage medium executable by a processor. While the operations are illustrated in an example sequence, the operations can be eliminated, combined, or re-ordered in some embodiments.

(93) The operations illustrated in FIG. 7 can be performed, for example, by a map authority server **500** comprising a truth maintenance module **515**, as illustrated in FIG. 5. In some embodiments, the map authority server **500** can comprise an indoor shared overlay map service for a physical structure, such as an office building, a sports arena, or a warehouse, and the mobile subscriber devices can comprise mobile subscriber devices inside the physical structure. For multistory buildings and buildings with underground spaces such as parking garages and the like, the technologies provided herein can be implemented in three dimensions (3D). An example computing device that can provide the map authority server for an indoor shared overlay map service is a multi-access edge computer (MEC) in a wireless communication system **100** such as illustrated in FIG. 1.

(94) In other embodiments, map authority server **500** can comprise an outdoor shared overlay map service for an outdoor area such as a city. The mobile subscriber devices can comprise mobile subscriber devices inside the city. An example computing device that can provide the map authority server for a city shared overlay map service is a RAN intelligent controller (RIC) in a wireless communication system **100** such as illustrated in FIG. 1.

(95) Example operations include operation **702**, which represents receiving, by a device comprising a processor, e.g., by server **500**, a map input such as ASO **572** from a mobile device such as subscriber device **550**, the map input comprising a map location and description information associated with the map location. At **704**, the device **500** can determine a map input credibility

value, such as credibility determination **535**, for the map input, e.g., by processing ASO **572** at the truth maintenance module **515**. The map input credibility value can be determined based on an identity, such as user identity **537**, which is associated with the mobile device **550**. At **706**, in response to the map input credibility value being determined to be above a threshold value, the device **500** can send the map input, e.g., the ASO **572**, to multiple mobile devices **570**.

(96) In an embodiment, the truth maintenance module **515** can calculate the credibility value by combining credibility values associated with different credibility factors. If the combined credibility value is above a threshold, then the map input (ASO **572**) is sufficiently credible to promulgate. If not, then the ASO **572** can be withheld from promulgation.

(97) The credibility value can be determined based on any of the factors described herein or otherwise. For example, a credibility value can be determined based on proximity of a location of the mobile device **550** with the map location included in the ASO **572**. Credibility value can be determined based on a time difference between a first time, e.g., a time included in the description information of ASO **572**, and a second time, e.g., a time associated with a transmission of the ASO **572** to the map authority server **500**. Credibility value can be determined based on whether the identity associated with the mobile device **550** (e.g., as may be indicated in ASO **572**) matches an identity, e.g., user identity **537**, which is accessible by the map authority server **500**. Credibility value can be determined based on an output of a comparison of the map input with profile information associated with an identity such as user identity **537**, for example, credibility can be higher when profile information matches content of the ASO **572**.

(98) Credibility value can also optionally be determined based on an identity credibility value assigned to the identity, e.g., user identity **537**, accessible by the device **500**. At **708**, the credibility ML module **532** at device **500** can furthermore update the identity credibility value assigned to the identity **537** in user identity data **540**, based on the map input credibility value applied to ASO **572**.

(99) At **710**, the device **500** can compare the map input/ASO **572** with other map inputs, and the device **500** can determine a representative map input to send to the multiple mobile devices **570**. Operation **710** can be performed by normalizer **532**. Normalizer **532** can thereby eliminate duplicate ASOs and improve accuracy of the representative ASO based on consensus of multiple incoming ASOs.

(100) At **712**, the device **500** can send a monitoring request **539** to at least one mobile device of mobile devices **570**, and the device **500** can receive a monitoring response **539** from the at least one mobile device. For example, map input monitor **533** can send a monitoring request **539** to at least one mobile device of subscriber devices **570**, the monitoring request comprising a request for an update of the map input **572**. The map input monitor **533** can subsequently receive from the at least one mobile device, in response to the monitoring request, the update of the map input **572**. The map input monitor **533** can modify the map input **572** in response to receiving the update of the map input. The modified map input, e.g., an updated version of ASO **572**, can be sent to the multiple mobile devices **570**.

(101) FIG. **8** is a flow diagram representing another example set of operations of a server comprising a truth maintenance module for map inputs, in accordance with various aspects and embodiments of the subject disclosure. The illustrated blocks can represent actions performed in a method, functional components of a computing device, or instructions implemented in a machine-readable storage medium executable by a processor. While the operations are illustrated in an example sequence, the operations can be eliminated, combined, or re-ordered in some embodiments.

(102) The operations illustrated in FIG. **8** can be performed, for example, by a map authority server **500** comprising a truth maintenance module **515**, as illustrated in FIG. **5**. Example operations include operation **802**, which represents receiving map inputs such as ASO **572** from first mobile devices such as subscriber device **550**, wherein the map inputs **572** comprise map locations and description information associated with the map locations.

(103) At operation **804**, truth maintenance module **515** can assign credibility values to map inputs. For example, the credibility module **530** can assign credibility values to the map inputs such as ASO **572**, based on credibility values associated with user identities stored in user identity data **540**, or other data associated with the map inputs. In some embodiments, map inputs having sufficiently high credibility values, e.g., having credibility values that have been determined to exceed a threshold credibility value, can be passed to the normalizer **532** for consolidation.

(104) At operations **806-812**, truth maintenance module **515** can consolidate map inputs. At **806**, the normalizer **532** can identify a group of the map inputs that comprises proximal map locations. For example, the normalizer **532** can identify a group of ASOs, including ASO **572** and other received ASOs, which comprise proximal map locations. The group of map inputs can optionally furthermore comprise matching or otherwise similar description information. At **808**, the normalizer **532** can furthermore optionally remove a conflicting map input from the group of the map inputs. The conflicting map input can comprise, e.g., conflicting description information that conflicts with description information of other map inputs in the group. At **810**, the normalizer **532** can determine a representative map input which is representative of the group of the map inputs. For example, the representative map input can comprise a representative map location based on the proximal map locations of the group of the map inputs, and the representative map input can comprise representative description information based on description information in the group of the map inputs. At **812**, the normalizer **532** can assign a confidence value to the representative map input, wherein the confidence value is based on the credibility values of the group of the map inputs. For example, the representative map input can comprise an average or mean confidence value of the group of the map inputs, optionally increased in view of the knowledge of multiple agreeing map inputs.

(105) At operation **814**, the server **500** can send the representative map input to second mobile devices, e.g., to subscriber devices **570**. In the illustrated embodiment, the representative map input can be provided to the shared overlay map service **502** in lieu of, or in addition to, credibility determination **535**, and the representative map input can be distributed to multiple mobile devices **570** by the shared overlay map service **502**.

(106) FIG. **9** is a flow diagram representing another example set of operations of a server comprising a truth maintenance module for map inputs, in accordance with various aspects and embodiments of the subject disclosure. The illustrated blocks can represent actions performed in a method, functional components of a computing device, or instructions implemented in a machine-readable storage medium executable by a processor. While the operations are illustrated in an example sequence, the operations can be eliminated, combined, or re-ordered in some embodiments.

(107) The operations illustrated in FIG. **9** can be performed, for example, by a map authority server **500** comprising a truth maintenance module **515**, as illustrated in FIG. **5**. At operation **902**, the server **500** can receive a map input, such as ASO **572**, from a first mobile device, e.g., from subscriber device **550**. The map input can comprise a map location and description information associated with the map location. At operation **904**, the truth maintenance module **515** can determine a map input credibility value for the map input, e.g., credibility determination **535** can be determined for ASO **572**. At **906**, the server **500** can send the map input, namely ASO **572**, to a group of mobile devices such as subscriber devices **570**. The group of mobile devices can, although need not necessarily, comprise UE devices, UGVs, or any other mobile devices.

(108) Operations **908-914** pertain to the further use of monitoring requests. At **908**, the server **500** can send a monitoring request **539** to a second mobile device, e.g., to one or more of subscriber devices **570**. The monitoring request **539** can comprise a request for an update of the map input, i.e., an update of ASO **572** which was sent to subscriber devices **570** at operation **906**. At **910**, the server **500** can receive, from the second mobile device in response to the monitoring request **539**, a monitoring response (also labeled **539** in FIG. **5**) comprising the update of the map input. At **912**,

the server **500** can modify the map input, namely the ASO **572**, in response to receiving the update of the map input, resulting in a modified map input. At **914**, the server **500** can send the modified map input (a modified ASO **572**) to the group of mobile devices, i.e., to subscriber devices **570**. The modified ASO can include information to cancel or delete the original ASO **572**, or information to modify any of the data included in the original ASO **572**.

(109) At **916**, the server **500** can update, based on the update of the map input, an identity credibility value of an identity associated with the first mobile device. For example, the server **500** can update, based on the update of the map input included in monitoring response **539**, an identity credibility value of an identity stored in user identity data **540**, wherein the identity is associated with the subscriber device **550** that initially supplied the ASO **572**.

(110) FIG. **10** is a block diagram of an example computer that can be operable to execute processes and methods in accordance with various aspects and embodiments of the subject disclosure. The example computer can be adapted to implement, for example, a mobile subscriber device **221**, a server **260**, a computer **410**, a map authority server **500**, or other computing devices described herein.

(111) FIG. **10** and the following discussion are intended to provide a brief, general description of a suitable computing environment **1000** in which the various embodiments of the embodiment described herein can be implemented. While the embodiments have been described above in the general context of computer-executable instructions that can run on one or more computers, those skilled in the art will recognize that the embodiments can be also implemented in combination with other program modules and/or as a combination of hardware and software.

(112) Generally, program modules include routines, programs, components, data structures, etc., that perform particular tasks or implement particular abstract data types. Moreover, those skilled in the art will appreciate that the methods can be practiced with other computer system configurations, including single-processor or multiprocessor computer systems, minicomputers, mainframe computers, IoT devices, distributed computing systems, as well as personal computers, hand-held computing devices, microprocessor-based or programmable consumer electronics, and the like, each of which can be operatively coupled to one or more associated devices.

(113) The illustrated embodiments of the embodiments herein can be also practiced in distributed computing environments where certain tasks are performed by remote processing devices that are linked through a communications network. In a distributed computing environment, program modules can be located in both local and remote memory storage devices.

(114) Computing devices typically include a variety of media, which can include computer-readable storage media, machine-readable storage media, and/or communications media, which two terms are used herein differently from one another as follows. Computer-readable storage media or machine-readable storage media can be any available storage media that can be accessed by the computer and includes both volatile and nonvolatile media, removable and non-removable media. By way of example, and not limitation, computer-readable storage media or machine-readable storage media can be implemented in connection with any method or technology for storage of information such as computer-readable or machine-readable instructions, program modules, structured data or unstructured data.

(115) Computer-readable storage media can include, but are not limited to, random access memory (RAM), read only memory (ROM), electrically erasable programmable read only memory (EEPROM), flash memory or other memory technology, compact disk read only memory (CD-ROM), digital versatile disk (DVD), Blu-ray disc (BD) or other optical disk storage, magnetic cassettes, magnetic tape, magnetic disk storage or other magnetic storage devices, solid state drives or other solid state storage devices, or other tangible and/or non-transitory media which can be used to store desired information. In this regard, the terms “tangible” or “non-transitory” herein as applied to storage, memory or computer-readable media, are to be understood to exclude only propagating transitory signals per se as modifiers and do not relinquish rights to all standard

storage, memory or computer-readable media that are not only propagating transitory signals per se.

(116) Computer-readable storage media can be accessed by one or more local or remote computing devices, e.g., via access requests, queries or other data retrieval protocols, for a variety of operations with respect to the information stored by the medium.

(117) Communications media typically embody computer-readable instructions, data structures, program modules or other structured or unstructured data in a data signal such as a modulated data signal, e.g., a carrier wave or other transport mechanism, and includes any information delivery or transport media. The term “modulated data signal” or signals refers to a signal that has one or more of its characteristics set or changed in such a manner as to encode information in one or more signals. By way of example, and not limitation, communication media include wired media, such as a wired network or direct-wired connection, and wireless media such as acoustic, RF, infrared and other wireless media.

(118) With reference again to FIG. 10, the example environment **1000** for implementing various embodiments of the aspects described herein includes a computer **1002**, the computer **1002** including a processing unit **1004**, a system memory **1006** and a system bus **1008**. The system bus **1008** couples system components including, but not limited to, the system memory **1006** to the processing unit **1004**. The processing unit **1004** can be any of various commercially available processors. Dual microprocessors and other multi-processor architectures can also be employed as the processing unit **1004**.

(119) The system bus **1008** can be any of several types of bus structure that can further interconnect to a memory bus (with or without a memory controller), a peripheral bus, and a local bus using any of a variety of commercially available bus architectures. The system memory **1006** includes ROM **1010** and RAM **1012**. A basic input/output system (BIOS) can be stored in a non-volatile memory such as ROM, erasable programmable read only memory (EPROM), EEPROM, which BIOS contains the basic routines that help to transfer information between elements within the computer **1002**, such as during startup. The RAM **1012** can also include a high-speed RAM such as static RAM for caching data.

(120) The computer **1002** further includes an internal hard disk drive (HDD) **1014** (e.g., EIDE, SATA), one or more external storage devices **1016** (e.g., a magnetic floppy disk drive (FDD) **1016**, a memory stick or flash drive reader, a memory card reader, etc.) and an optical disk drive **1020** (e.g., which can read or write from a CD-ROM disc, a DVD, a BD, etc.). While the internal HDD **1014** is illustrated as located within the computer **1002**, the internal HDD **1014** can also be configured for external use in a suitable chassis (not shown). Additionally, while not shown in environment **1000**, a solid state drive (SSD) could be used in addition to, or in place of, an HDD **1014**. The HDD **1014**, external storage device(s) **1016** and optical disk drive **1020** can be connected to the system bus **1008** by an HDD interface **1024**, an external storage interface **1026** and an optical drive interface **1028**, respectively. The interface **1024** for external drive implementations can include at least one or both of Universal Serial Bus (USB) and Institute of Electrical and Electronics Engineers (IEEE) 1394 interface technologies. Other external drive connection technologies are within contemplation of the embodiments described herein.

(121) The drives and their associated computer-readable storage media provide nonvolatile storage of data, data structures, computer-executable instructions, and so forth. For the computer **1002**, the drives and storage media accommodate the storage of any data in a suitable digital format.

Although the description of computer-readable storage media above refers to respective types of storage devices, it should be appreciated by those skilled in the art that other types of storage media which are readable by a computer, whether presently existing or developed in the future, could also be used in the example operating environment, and further, that any such storage media can contain computer-executable instructions for performing the methods described herein.

(122) A number of program modules can be stored in the drives and RAM **1012**, including an

operating system **1030**, one or more application programs **1032**, other program modules **1034** and program data **1036**. All or portions of the operating system, applications, modules, and/or data can also be cached in the RAM **1012**. The systems and methods described herein can be implemented utilizing various commercially available operating systems or combinations of operating systems. (123) Computer **1002** can optionally comprise emulation technologies. For example, a hypervisor (not shown) or other intermediary can emulate a hardware environment for operating system **1030**, and the emulated hardware can optionally be different from the hardware illustrated in FIG. **10**. In such an embodiment, operating system **1030** can comprise one virtual machine (VM) of multiple VMs hosted at computer **1002**. Furthermore, operating system **1030** can provide runtime environments, such as the Java runtime environment or the .NET framework, for applications **1032**. Runtime environments are consistent execution environments that allow applications **1032** to run on any operating system that includes the runtime environment. Similarly, operating system **1030** can support containers, and applications **1032** can be in the form of containers, which are lightweight, standalone, executable packages of software that include, e.g., code, runtime, system tools, system libraries and settings for an application.

(124) Further, computer **1002** can be enabled with a security module, such as a trusted processing module (TPM). For instance, with a TPM, boot components hash next in time boot components, and wait for a match of results to secured values, before loading a next boot component. This process can take place at any layer in the code execution stack of computer **1002**, e.g., applied at the application execution level or at the operating system (OS) kernel level, thereby enabling security at any level of code execution.

(125) A user can enter commands and information into the computer **1002** through one or more wired/wireless input devices, e.g., a keyboard **1038**, a touch screen **1040**, and a pointing device, such as a mouse **1042**. Other input devices (not shown) can include a microphone, an infrared (IR) remote control, a radio frequency (RF) remote control, or other remote control, a joystick, a virtual reality controller and/or virtual reality headset, a game pad, a stylus pen, an image input device, e.g., camera(s), a gesture sensor input device, a vision movement sensor input device, an emotion or facial detection device, a biometric input device, e.g., fingerprint or iris scanner, or the like. These and other input devices are often connected to the processing unit **1004** through an input device interface **1044** that can be coupled to the system bus **1008**, but can be connected by other interfaces, such as a parallel port, an IEEE 1394 serial port, a game port, a USB port, an IR interface, a BLUETOOTH® interface, etc.

(126) A monitor **1046** or other type of display device can be also connected to the system bus **1008** via an interface, such as a video adapter **1048**. In addition to the monitor **1046**, a computer typically includes other peripheral output devices (not shown), such as speakers, printers, etc.

(127) The computer **1002** can operate in a networked environment using logical connections via wired and/or wireless communications to one or more remote computers, such as a remote computer(s) **1050**. The remote computer(s) **1050** can be a workstation, a server computer, a router, a personal computer, portable computer, microprocessor-based entertainment appliance, a peer device or other common network node, and typically includes many or all of the elements described relative to the computer **1002**, although, for purposes of brevity, only a memory/storage device **1052** is illustrated. The logical connections depicted include wired/wireless connectivity to a local area network (LAN) **1054** and/or larger networks, e.g., a wide area network (WAN) **1056**. Such LAN and WAN networking environments are commonplace in offices and companies, and facilitate enterprise-wide computer networks, such as intranets, all of which can connect to a global communications network, e.g., the internet.

(128) When used in a LAN networking environment, the computer **1002** can be connected to the local network **1054** through a wired and/or wireless communication network interface or adapter **1058**. The adapter **1058** can facilitate wired or wireless communication to the LAN **1054**, which can also include a wireless access point (AP) disposed thereon for communicating with the adapter

**1058** in a wireless mode.

(129) When used in a WAN networking environment, the computer **1002** can include a modem **1060** or can be connected to a communications server on the WAN **1056** via other means for establishing communications over the WAN **1056**, such as by way of the internet. The modem **1060**, which can be internal or external and a wired or wireless device, can be connected to the system bus **1008** via the input device interface **1044**. In a networked environment, program modules depicted relative to the computer **1002** or portions thereof, can be stored in the remote memory/storage device **1052**. It will be appreciated that the network connections shown are example and other means of establishing a communications link between the computers can be used.

(130) When used in either a LAN or WAN networking environment, the computer **1002** can access cloud storage systems or other network-based storage systems in addition to, or in place of, external storage devices **1016** as described above. Generally, a connection between the computer **1002** and a cloud storage system can be established over a LAN **1054** or WAN **1056** e.g., by the adapter **1058** or modem **1060**, respectively. Upon connecting the computer **1002** to an associated cloud storage system, the external storage interface **1026** can, with the aid of the adapter **1058** and/or modem **1060**, manage storage provided by the cloud storage system as it would other types of external storage. For instance, the external storage interface **1026** can be configured to provide access to cloud storage sources as if those sources were physically connected to the computer **1002**.

(131) The computer **1002** can be operable to communicate with any wireless devices or entities operatively disposed in wireless communication, e.g., a printer, scanner, desktop and/or portable computer, portable data assistant, communications satellite, any piece of equipment or location associated with a wirelessly detectable tag (e.g., a kiosk, news stand, store shelf, etc.), and telephone. This can include Wireless Fidelity (Wi-Fi) and BLUETOOTH® wireless technologies. Thus, the communication can be a predefined structure as with a conventional network or simply an ad hoc communication between at least two devices.

(132) The above description includes non-limiting examples of the various embodiments. It is, of course, not possible to describe every conceivable combination of components or methodologies for purposes of describing the disclosed subject matter, and one skilled in the art can recognize that further combinations and permutations of the various embodiments are possible. The disclosed subject matter is intended to embrace all such alterations, modifications, and variations that fall within the spirit and scope of the appended claims.

(133) With regard to the various functions performed by the above described components, devices, circuits, systems, etc., the terms (including a reference to a “means”) used to describe such components are intended to also include, unless otherwise indicated, any structure(s) which performs the specified function of the described component (e.g., a functional equivalent), even if not structurally equivalent to the disclosed structure. In addition, while a particular feature of the disclosed subject matter may have been disclosed with respect to only one of several implementations, such feature may be combined with one or more other features of the other implementations as may be desired and advantageous for any given or particular application.

(134) The terms “exemplary” and/or “demonstrative” as used herein are intended to mean serving as an example, instance, or illustration. For the avoidance of doubt, the subject matter disclosed herein is not limited by such examples. In addition, any aspect or design described herein as “exemplary” and/or “demonstrative” is not necessarily to be construed as preferred or advantageous over other aspects or designs, nor is it meant to preclude equivalent structures and techniques known to one skilled in the art. Furthermore, to the extent that the terms “includes,” “has,” “contains,” and other similar words are used in either the detailed description or the claims, such terms are intended to be inclusive—in a manner similar to the term “comprising” as an open transition word—without precluding any additional or other elements.

(135) The term “or” as used herein is intended to mean an inclusive “or” rather than an exclusive



“or.” For example, the phrase “A or B” is intended to include instances of A, B, and both A and B. Additionally, the articles “a” and “an” as used in this application and the appended claims should generally be construed to mean “one or more” unless either otherwise specified or clear from the context to be directed to a singular form.

(136) The term “set” as employed herein excludes the empty set, i.e., the set with no elements therein. Thus, a “set” in the subject disclosure includes one or more elements or entities. Likewise, the term “group” as utilized herein refers to a collection of one or more entities.

(137) The terms “first,” “second,” “third,” and so forth, as used in the claims, unless otherwise clear by context, is for clarity only and doesn't otherwise indicate or imply any order in time. For instance, “a first determination,” “a second determination,” and “a third determination,” does not indicate or imply that the first determination is to be made before the second determination, or vice versa, etc.

(138) The description of illustrated embodiments of the subject disclosure as provided herein, including what is described in the Abstract, is not intended to be exhaustive or to limit the disclosed embodiments to the precise forms disclosed. While specific embodiments and examples are described herein for illustrative purposes, various modifications are possible that are considered within the scope of such embodiments and examples, as one skilled in the art can recognize. In this regard, while the subject matter has been described herein in connection with various embodiments and corresponding drawings, where applicable, it is to be understood that other similar embodiments can be used or modifications and additions can be made to the described embodiments for performing the same, similar, alternative, or substitute function of the disclosed subject matter without deviating therefrom. Therefore, the disclosed subject matter should not be limited to any single embodiment described herein, but rather should be construed in breadth and scope in accordance with the appended claims below.

## Claims

1. A device, comprising: a processor; and a memory that stores executable instructions that, when executed by the processor, facilitate performance of operations, comprising: receiving a map input from each mobile device from a first group of mobile devices resulting in a group of map inputs, wherein each map input from the group of map inputs comprise a map location and a description information associated with the map location; identifying a first portion of the group of the map inputs that comprises proximal map locations; determining a representative map input based on a credibility value associated with each of the first portion of the group of the map inputs received from a respective mobile device from the first group of mobile devices resulting in a group of credibility values, wherein the credibility value associated with each of the first portion of the group of map inputs is based on a user identity associated with the respective mobile device from the first group of mobile devices; and sending the representative map input to a second group of mobile devices other than the first group of mobile devices.
2. The device of claim 1, wherein the operations further comprise removing a conflicting map input from the first portion of the group of the map inputs, and wherein the conflicting map input comprises conflicting description information that conflicts with description information of other map inputs of the first portion of the group of the map inputs other than the conflicting map input.
3. The device of claim 1, wherein the first portion of the group of the map inputs comprises matching description information.
4. The device of claim 1, wherein the representative map input comprises a representative map location based on the proximal map locations of the first portion of the group of the map inputs, and representative description information based on description information in the first portion of the first group of the map inputs.
5. The device of claim 1, wherein the operations further comprise assigning a credibility value from

the group of credibility values to each of the first portion of the group of map inputs, and wherein the each of the first portion of the group of the map inputs comprises inputs with a credibility value from the group of credibility values that have been determined to exceed a threshold credibility value.

6. The device of claim 5, wherein the operations further comprise assigning a confidence value to the representative map input, and wherein the confidence value is based on each credibility value from the group of credibility values associated with each of the first portion of the group of the map inputs.

7. A method, comprising: receiving, by a processing system comprising a processor, a map input from each mobile device from a first group of mobile devices resulting in a group of map inputs, wherein each map input from the group of map inputs comprise a map location and a description information associated with the map location; identifying, by the processing system, a first portion of the group of the map inputs that comprises proximal map locations; determining, by the processing system, a map input credibility value for each of the first portion of the group of the map inputs resulting in a group of map input credibility values, wherein each map input credibility value from the group of map input credibility values is based on a user identity associated with a respective mobile device from the first group of mobile devices; in response to the group of map input credibility values being determined to comprise at least one map input credibility value above a threshold value, determining, by the processing system, a representative map input based on the first portion of the group of the map inputs; and sending, by the processing system, the representative map input to a second group of mobile devices.

8. The method of claim 7, wherein each of the group of map input credibility values are determined based on a proximity of location of each of the first group of mobile devices with a map location included in the first portion of the group of map inputs.

9. The method of claim 7, wherein each map input credibility value from the group of map input credibility values are determined based on a transmission time associated with each respective map input from the first portion of the group of map inputs.

10. The method of claim 7, wherein each map input credibility value from the group of map input credibility values are determined based on time differences between first times included in the description information associated with each respective map input from the first portion of the group of map inputs and second times associated with transmissions of the respective map input from the first portion of the group of map inputs from a respective mobile device from the first group of mobile devices.

11. The method of claim 7, further comprising assigning, by the system, a representative credibility value to the representative map input, wherein the representative credibility value is based on the first portion of the group of map input credibility values.

12. The method of claim 11, wherein the threshold value is a first threshold value, and wherein sending the representative map input to the second group of mobile devices is in response to the representative credibility value being determined to be above a second threshold value.

13. The method of claim 7, wherein the representative map input is based on a consensus of the first portion of the group of the map inputs.

14. The method of claim 7, further comprising sending, by the processing system, a monitoring request to at least one of the first group of mobile devices, wherein the monitoring request comprises a request for an updated map input.

15. A non-transitory machine-readable medium, comprising executable instructions that, when executed by a processor, facilitate performance of operations, comprising: receiving a map input from each mobile device of a first group of mobile devices resulting in a group of map inputs, wherein each map input from the group of map inputs comprise a map location and a description information associated with the map location; identifying a first portion of the group of the map inputs that comprises matching description information; determining a representative map input

which is representative of the first portion of the group of the map inputs based on a credibility value associated with each of the first portion of the group of map inputs received from a respective mobile device from the first group of mobile devices resulting in a group of credibility values, wherein each credibility value of the group of credibility values is based on a user identity associated with the respective mobile device from the first group of mobile devices; and sending the representative map input to a second group of mobile devices.

16. The non-transitory machine-readable medium of claim 15, wherein the operations further comprise removing a conflicting map input from the first portion of the group of the map inputs.

17. The non-transitory machine-readable medium of claim 15, wherein the representative map input comprises a representative map location based on a map location of the first portion of the group of the map inputs.

18. The non-transitory machine-readable medium of claim 15, wherein the operations further comprise assigning a credibility value from the group of credibility values to each of the first portion of the group of map inputs, and wherein the first portion of the group of the map inputs comprises credibility values that have been determined to exceed a threshold credibility value.

19. The non-transitory machine-readable medium of claim 15, wherein the operations further comprise assigning a confidence value to the representative map input, and wherein the confidence value is based on the group of credibility values associated with the first portion of the group of the map inputs.

20. The non-transitory machine-readable medium of claim 15, wherein the operations further comprise sending, to at least one mobile device of the first group of mobile devices, a request for an updated map input.

---