

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12395582
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	An; Jungchul et al.

Electronic device including waterproof structure

Abstract

According to various embodiments, an electronic device may include: a first housing including a first support member, a second housing including a second support member and foldably coupled to the first housing through a hinge device, a display panel supported by the first housing and the second housing, a support plate disposed under the display panel, a first reinforced plate at least partially disposed under the support plate to correspond to the first support member, a second reinforced plate at least partially disposed under the support plate to correspond to the second support member, a first waterproof structure disposed between the first housing and the first reinforced plate to define at least one first waterproof space, and a second waterproof structure disposed between the second housing and the second reinforced plate to define at least one second waterproof space.

Inventors: An; Jungchul (Suwon-si, KR), Kim; Seonghoon (Suwon-si, KR), Shin; Hyunho (Suwon-si, KR), Hong; Hyunju (Suwon-si, KR)

Applicant: SAMSUNG ELECTRONICS CO., LTD. (Suwon-si, KR)

Family ID: 1000008765991

Assignee: Samsung Electronics Co., Ltd. (Suwon-si, KR)

Appl. No.: 17/885945

Filed: August 11, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230051260 A1	Feb. 16, 2023

Foreign Application Priority Data

KR	10-2021-0105015	Aug. 10, 2021
----	-----------------	---------------

Related U.S. Application Data

continuation parent-doc WO PCT/KR2022/011556 20220804 PENDING child-doc US 17885945

Publication Classification

Int. Cl.: H04M1/02 (20060101); G06F1/16 (20060101); H04M1/18 (20060101)

U.S. Cl.:

CPC H04M1/18 (20130101); G06F1/1616 (20130101); G06F1/1652 (20130101); G06F1/1656 (20130101); H04M1/0216 (20130101); H04M1/0268 (20130101);

Field of Classification Search

CPC: H04M (1/18); H04M (1/0216); H04M (1/0268); H04M (1/02); H04M (1/0277); G06F (1/1616); G06F (1/1652); G06F (1/1656); G06F (1/1637); G06F (3/041); G06F (1/1658); G06F (1/1681); G06F (3/0412); H05K (5/06); H05K (5/061)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2005/0225952	12/2004	Takagi	361/749	H04M 1/18
2011/0110022	12/2010	Kumagai	361/679.01	H04M 1/18
2015/0282364	12/2014	Moon et al.	N/A	N/A
2018/0006064	12/2017	Miyaguchi	N/A	N/A
2018/0076412	12/2017	Kim et al.	N/A	N/A
2018/0241861	12/2017	Kim et al.	N/A	N/A
2018/0249588	12/2017	Choi et al.	N/A	N/A
2018/0335679	12/2017	Hashimoto et al.	N/A	N/A
2019/0181194	12/2018	Wu et al.	N/A	N/A
2020/0162596	12/2019	Kim	N/A	G06F 1/1683
2020/0236826	12/2019	Baek	N/A	H01F 27/366
2020/0319672	12/2019	Kim et al.	N/A	N/A
2021/0029841	12/2020	Kim et al.	N/A	N/A
2021/0116964	12/2020	Moon et al.	N/A	N/A
2021/0176872	12/2020	Woo et al.	N/A	N/A
2022/0164002	12/2021	An et al.	N/A	N/A
2023/0047246	12/2022	An	N/A	H05K 5/06
2023/0180413	12/2022	An	345/905	G06F 1/1652
2023/0262914	12/2022	Kang	361/807	G06F 1/1681

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
3151524	12/2016	EP	N/A
3771186	12/2020	EP	N/A
2020522730	12/2019	JP	N/A
2021107929	12/2020	JP	N/A
10-2018-0029190	12/2017	KR	N/A
10-2018-0096178	12/2017	KR	N/A
10-2020-0062827	12/2019	KR	N/A
10-2020-0108754	12/2019	KR	N/A
10-2021-0012930	12/2020	KR	N/A
10-2021-0047753	12/2020	KR	N/A
10-2021-0070880	12/2020	KR	N/A
2020/171449	12/2019	WO	N/A

OTHER PUBLICATIONS

Extended European Search Report dated Oct. 4, 2024 issued in European Patent Application No. 22856105.6. cited by applicant

Korean Notice of Allowance issued Jun. 27, 2024 in corresponding Korean Patent Application No. 10-2021-0105015. cited by applicant

Search Report and Written Opinion dated Aug. 10, 2022 issued in International Patent Application No. PCT/KR2022/011556. cited by applicant

Primary Examiner: Perez; Angelica

Attorney, Agent or Firm: Nixon & Vanderhye P.C.

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of International Application No. PCT/KR2022/011556 designating the United States, filed on Aug. 4, 2022, in the Korean Intellectual Property Receiving Office and claiming priority to Korean Patent Application No. 10-2021-0105015, filed on Aug. 10, 2021, in the Korean Intellectual Property Office, the disclosures of which are incorporated by reference herein in their entireties.

BACKGROUND

Field

(1) The disclosure relates to an electronic device including a waterproof structure.

Description of Related Art

(2) Electronic devices are becoming slim and are being enhanced to differentiate functional elements of thereof while the rigidity and design aspects are developed. The electronic devices may require a sealed waterproof and/or dustproof structure for preventing/reducing electronic components arranged inside the electronic devices from being damaged by water and/or foreign materials.

(3) An electronic device may include a first housing, a second housing foldably coupled to the first housing through a hinge device (e.g., a hinge module), and a flexible display disposed to be supported by the first housing and the second housing. When the first housing and the second housing are folded with respect to each other, an area of the flexible display, corresponding to the hinge device, may be bent.

(4) An electronic device may include a waterproof member (e.g., waterproof tape) disposed between the first housing and the flexible display and disposed between the second housing and the flexible display. The electronic device may include a waterproof structure in which a part of an area corresponding to the first housing and/or an area corresponding to the second housing is sealed through the waterproof member. These areas may include areas in which permeation of water should be necessarily prevented, in a folding structure of the electronic device, in which water is easily introduced into a folding area.

(5) However, a waterproof structure in which a waterproof member is disposed between a housing and a flexible display may become a cause of a damage (e.g., tearing) of the flexible display by a strong adhesive force of the waterproof member when the flexible display is to be separated from housings for maintenance of the electronic device. In addition, when the waterproof member is directly applied to a rear surface of the flexible display, the waterproof member may be visible from the outside of the flexible display, or a problem of deterioration in a surface quality may occur. In addition, when a digitizer is applied under a display panel of the flexible display, the waterproof member may be disposed between the digitizer and the housing, but this may cause deterioration in a waterproof function due to a pattern step (e.g., a coil pattern) of the digitizer.

SUMMARY

(6) Embodiments of the disclosure may provide an electronic device including a waterproof function which can prevent and/or reduce a flexible display from being damaged and thus can assist in maintenance.

(7) Embodiments of the disclosure may provide an electronic device including a waterproof structure which can assist in enhancing a surface quality.

(8) Embodiments of the disclosure may provide an electronic device including a waterproof structure which can assist in enhancing a waterproof performance.

(9) However, a problem addressed by the disclosure is not limited to the problems mentioned above, and may be variously expanded without departing from the idea and the scope of the disclosure.

(10) According to various example embodiments, an electronic device may include: a first housing including a first support member, a second housing including a second support member and foldably coupled to the first housing through a hinge device, a display panel supported by the first housing and the second housing, a support plate disposed under the display panel, a first reinforced plate at least partially disposed under the support plate to correspond to the first support member, a second reinforced plate at least partially disposed under the support plate to correspond to the second support member, a first waterproof structure disposed between the first housing and the first reinforced plate to define at least one first waterproof space, and a second waterproof structure disposed between the second housing and the second reinforced plate to define at least one second waterproof space.

(11) According to various example embodiments, an electronic device may include: a first housing including a first support member, a second housing including a second support member and foldably coupled to the first housing through a hinge device, a display panel supported by the first housing and the second housing, a support plate disposed under the display panel, a first digitizer disposed under the support plate to correspond to the first support member, and including a first flexible printed circuit board (FPCB) connection portion, a second digitizer disposed under the support plate to correspond to the second support member, and including a second FPCB connection portion, a first reinforced plate disposed under the first digitizer to correspond to the first support member, a second reinforced plate disposed under the second digitizer to correspond to the second support member, a first waterproof structure disposed between the first housing and the first reinforced plate to define at least one first waterproof space, and a second waterproof structure disposed between the second housing and the second reinforced plate to define at least one second waterproof space, wherein the first FPCB connection portion is disposed, when seen

from above the flexible display, at a position overlapping with the at least one first waterproof space, and the second FPCB connection portion is disposed, when seen from above the flexible display, at a position overlapping with the at least one second waterproof space.

(12) An electronic device according to various example embodiments of the disclosure may include reinforced plates arranged under a flexible display, and include a waterproof structure in which at least one waterproof member is disposed between a reinforced plate and a housing, and thus, during maintenance, a phenomenon in which the flexible display is damaged by an adhesive force of the waterproof member can be reduced, a surface quality of the flexible display can be enhanced, and a deterioration in a waterproof function can be reduced even when a digitizer is disposed.

(13) Various other effects directly or indirectly identified through the disclosure can be provided.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) With regard to description of drawings, the same or similar reference numerals may be used for the same or similar elements. Further, the above and other aspects, features and advantages of certain embodiments of the present disclosure will be more apparent from the following detailed description, taken in conjunction with the accompanying drawings, in which:

(2) FIGS. 1A and 1B are diagrams illustrating a front view and a rear view, respectively, of an unfolded state of an electronic device according to various embodiments;

(3) FIGS. 2A and 2B are diagrams illustrating a front view and a rear view, respectively, of a folded state of an electronic device according to various embodiments;

(4) FIG. 3 is an exploded perspective view illustrating an electronic device according to various embodiments;

(5) FIG. 4 is an exploded perspective view illustrating a first display according to various embodiments;

(6) FIG. 5 is a diagram illustrating an example configuration of reinforced plates according to various embodiments;

(7) FIG. 6 is a diagram illustrating a rear surface structure of a flexible display according to various embodiments;

(8) FIG. 7 is a diagram illustrating an example configuration of an electronic device, in an unfolded state while a flexible display is omitted, according to various embodiments;

(9) FIG. 8A is a cross-sectional view illustrating an electronic device including a flexible display, taken along line 8a-8a in FIG. 6 according to various embodiments;

(10) FIG. 8B is a cross-sectional view of a part of an electronic device, illustrating a state in which an FPCB connection portion is disposed through area 8b in FIG. 6 and area 8b in FIG. 7, according to various embodiments;

(11) FIG. 8C is a perspective view of a part of a second housing, illustrating a state in which a fourth waterproof member is applied in area 8c in FIG. 7, according to various embodiments;

(12) FIG. 8D is a cross-sectional view illustrating an electronic device including a flexible display, taken along the line 8d-8d in FIG. 6, according to various embodiments;

(13) FIG. 9 is an enlarged view illustrating area 9 in FIG. 6, according to various embodiments;

(14) FIG. 10 is a cross-sectional view illustrating an electronic device according to various embodiments;

(15) FIG. 11A is a cross-sectional view illustrating an electronic device according to various embodiments;

(16) FIG. 11B is a diagram illustrating an example configuration of reinforced plates applied to FIG. 11A, according to various embodiments; and

(17) FIG. 12 is a cross-sectional view illustrating an electronic device according to various

embodiments.

DETAILED DESCRIPTION

(18) FIGS. 1A and 1B are diagrams illustrating a front view and a rear view, respectively, of an unfolded state of an electronic device according to various embodiments. FIGS. 2A and 2B are diagrams illustrating a front view and a rear view, respectively, of a folded state of an electronic device according to various embodiments.

(19) Referring to FIGS. 1A, 1B, 2A and 2B (which may be referred to as FIGS. 1A to 2B), an electronic device **200** may include a pair of housings **210** and **220** (e.g., a foldable housing structure) rotatably coupled to each other with reference to folding axis A through a hinge device (e.g., a hinge device **320** of FIG. 3) (e.g., a hinge module) so as to be folded with respect to each other, a first display **230** (e.g., a flexible display, a foldable display, or a main display) disposed through the pair of housings **210** and **220**, and/or a second display **300** (e.g., a sub display) disposed through the second housing **220**. According to an embodiment, at least a part of the hinge device (e.g., the hinge device **320** of FIG. 3) may be disposed so as not to be seen from the outside through the first housing **210** and the second housing **220**, and may be disposed so as not to be seen from the outside through the hinge housing **310** covering a foldable portion. According to an embodiment, the hinge device **320** may include a hinge module including a gear assembly including multiple gears and multiple hinge cams which are coupled to hinge shafts rotating through the gear assembly and perform a cam interlocking operation, and hinge plates for connecting the hinge model to the first housing **210** and the second housing **220**. In the disclosure, a surface in which the first display **230** is disposed may be defined as a front surface of the electronic device **200**, and a surface opposite to the front surface may be defined as a rear surface of the electronic device **200**. In addition, a surface surrounding a space between the front surface and the rear surface may be defined as a side surface of the electronic device **200**.

(20) According to various embodiments, the pair of housings **210** and **220** may include a first housing **210** and a second housing **220** foldably arranged with respect to each other through the hinge device (e.g., the hinge device **320** of FIG. 3). According to an embodiment, the shape and the coupling of the pair of housings **210** and **220** are not limited to those illustrated in FIGS. 1A to 2B, and the pair of housings **210** and **220** may be implemented by a combination and/or coupling of other shapes or components. According to an embodiment, the first housing **210** and the second housing **220** may be arranged on opposite sides with reference to the folding axis A, and may have shapes that are entirely symmetric to each other with respect to the folding axis A. According to an embodiment, the first housing **210** and the second housing **220** may be asymmetrically folded with reference to the folding axis A. According to an embodiment, the angle or the distance between the first housing **210** and the second housing **220** may vary depending on whether the electronic device **200** is in an unfolded state, a folded state, or an intermediate state.

(21) According to various embodiments, the first housing **210** may include, in the unfolded state of the electronic device **200**, a first surface **211** connected to the hinge device (e.g., the hinge device **320** of FIG. 3) and disposed to be oriented to the front surface of the electronic device **200**, a second surface **212** oriented in a direction opposite to the first surface **211**, and/or a first side member **213** surrounding at least a part of a first space between the first surface **211** and the second surface **212**. According to an embodiment, the second housing **220** may include, in the unfolded state of the electronic device **200**, a third surface **221** connected to the hinge device (e.g., the hinge device **320** of FIG. 3) and disposed to be oriented to the front surface of the electronic device **200**, a fourth surface **222** oriented in a direction opposite to the third surface **221**, and/or a second side member **223** surrounding at least a part of a second space between the third surface **221** and the fourth surface **222**. According to an embodiment, the first surface **211** and the third surface **221** may be oriented in substantially the same direction in the unfolded state, and the first surface **211** and the third surface **221** may at least partially face each other in the folded state. According to an embodiment, the electronic device **200** may include a recess **201** formed to receive the first display

230 through structural coupling of the first housing **210** and the second housing **220**. According to an embodiment, the recess **201** may have substantially the same shape as the first display **230**. According to an embodiment, the first housing **210** may include a first protection frame **213a** (e.g., a first decoration member) which is, when seen from above the first display **230**, coupled to the first side member **213**, disposed to overlap with an edge of the first display **230**, so as to cover the edge of the first display **230** to allow the same not to be seen from the outside. According to an embodiment, the first protection frame **213a** may be integrally formed with the first side member **213**. According to an embodiment, the second housing **220** may include a second protection frame **223a** (e.g., a second decoration member) which is, when seen from above the first display **230**, coupled to the second side member **223**, disposed to overlap with an edge of the first display **230**, so as to cover the edge of the first display **230** to allow the same not to be seen from the outside. According to an embodiment, the second protection frame **223a** may be integrally formed with the first side member **223**. In an embodiment, the first protection frame **213a** and the second protection frame **223a** may be omitted.

(22) According to various embodiments, the hinge housing **310** (e.g., a hinge cover) may be disposed between the first housing **210** and the second housing **220**, and may be disposed to cover a part (e.g., at least one hinge module) of the hinge device (e.g., the hinge device **320** of FIG. 3) disposed on the hinge housing **310**. According to an embodiment, the hinge housing **310** may be hidden or exposed from or to the outside by a part of the first housing **210** and the second housing **220** according to the unfolded state, the folded state, or the intermediate state of the electronic device **200**. For example, when the electronic device **200** is in the unfolded state, at least a part of the hinge housing **310** may be covered by the first housing **210** and the second housing **220** and not be substantially exposed. According to an embodiment, when the electronic device **200** is in the folded state, at least a part of the hinge housing **310** may be exposed to the outside between the first housing **210** and the second housing **220**. According to an embodiment, in the intermediate state in which the first housing **210** and the second housing **220** are folded with each other by a predetermined angle (folded with a certain angle), the hinge housing **310** may be at least partially exposed to the outside of the electronic device **200** between the first housing **210** and the second housing **220**. For example, an area in which the hinge housing **310** is exposed to the outside, may be smaller than that in a case in which the electronic device **200** is completely folded. According to an embodiment, the hinge housing **310** may include a curved surface.

(23) According to various embodiments, when the electronic device **200** is in the unfolded state (e.g., the states shown in FIGS. 1A and 1B), the first housing **210** and the second housing **220** may meet at an about 180-degree angle, and a first area **230a**, a second area **230b**, and a folding area **230c** of the first display **230** may form the same plane and arranged to be oriented in substantially the same direction (e.g., a z-axis direction). In an embodiment, when the electronic device **200** is in the unfolded state, the first housing **210** may rotate by an about 360-degree angle with respect to the second housing **220**, and may be outwardly folded (an out-folding scheme) so that the second surface **212** and the fourth surface **222** face each other.

(24) According to various embodiments, when the electronic device **200** is in the folded state (e.g., the states shown in FIGS. 2A and 2B), the first surface **211** of the first housing **210** and the third surface **221** of the second housing **220** may be arranged to face each other. In this case, the first area **230a** and the second area **230b** of the first display **230** may form a narrow angle (e.g., a range between 0 degrees to about 10 degrees) through the folding area **230c**, and may be arranged to face each other. According to an embodiment, at least a part of the folding area **230c** may be deformed into a curved shape having a predetermined curvature. According to an embodiment, when the electronic device **200** is in the intermediate state, the first housing **210** and the second housing **220** may be arranged at a predetermined angle (a certain angle). In this case, the first area **230a** and the second area **230b** of the first display **230** may form an angle that is greater than that in the folded state and smaller than that in the unfolded state, and the curvature of the folding area **230c** may be

lower than in the folded state, and may be higher than that in the unfolded state. In an embodiment, the first housing **210** and the second housing **220** may form an angle which allows stopping at a designated folding angle between the folded state and the unfolded state (a free stop function), through the hinge device (e.g., the hinge device **320** of FIG. 3). In an embodiment, the first housing **210** and the second housing **220** may continuously operate while being pressed in an unfolding direction or a folding direction with reference to a designated inflection angle, through the hinge device (e.g., the hinge device **320** of FIG. 3).

(25) According to various embodiments, the electronic device **200** may include at least one of at least one display **230** and **300** disposed on the first housing **210** and/or the second housing **220**, an input device **215**, sound output devices **227** and **228**, sensor modules **217a**, **217b**, and **226**, camera modules **216a**, **216b**, and **225**, a key input device **219**, an indicator (not shown), or a connector port **229**. In an embodiment, the electronic device **200** may omit at least one of the elements, or may additionally include at least one another element.

(26) According to various embodiments, the at least one display **230** and **300** may include a first display **230** (e.g., a flexible display) disposed to be supported by the third surface **221** of the second housing **220** from the first surface **211** of the first housing **210** through the hinge device (e.g., the hinge device **320** of FIG. 3), and a second display **300** disposed to be at least partially seen from the outside through the fourth surface **222** in a space in the second housing **220**. In an embodiment, the second display **300** may be disposed to be seen from the outside through the second surface **212** in a space in the first housing **210**. According to an embodiment, the first display **230** may be mainly used in the unfolded state of the electronic device **200**, and the second display **300** may be mainly used in the folded state of the electronic device **200**. According to an embodiment, the electronic device **200** may control, in the intermediate state, the first display **230** and/or the second display **300** to be used, based on a folding angle between the first housing **210** and the second housing **220**.

(27) According to various embodiments, the first display **230** may be disposed in a receiving space formed by the pair of housings **210** and **220**. For example, the first display **230** may be disposed in a recess **201** formed by the pair of housings **210** and **220**, and may be disposed to occupy substantially the most of the front surface of the electronic device **200** in the unfolded state. According to an embodiment, the first display **230** may include a flexible display having at least one area which can be deformed into a plane or a curved surface. According to an embodiment, the first display **230** may include the first area **230a** facing the first housing **210** and the second area **230b** facing the second housing **220**. According to an embodiment, the first display **230** may include the folding area **230c** including a part of the first area **230a** and a part of the second area **230b** with respect to the folding axis A. According to an embodiment, at least a part of the folding area **230c** may include an area corresponding to the hinge device (e.g., the hinge device **320** of FIG. 3). According to an embodiment, a division of an area of the first display **230** merely corresponds to an example physical division by the pair of housings **210** and **220** and the hinge device (e.g., the hinge device **320** of FIG. 3), and the first display **230** may be substantially displayed as one seamless full screen through the pair of the housings **210** and **220** and the hinge device (e.g., the hinge device **320** of FIG. 3). According to an embodiment, the first area **230a** and the second area **230b** may have shapes that are entirely symmetric or partially asymmetric to each other with respect to the folding area **230c**.

(28) According to various embodiments, the electronic device **200** may include a first rear cover **240** disposed on the second surface **212** of the first housing **210** and a second rear cover **250** disposed on the fourth surface **222** of the second housing **220**. In an embodiment, at least a part of the first rear cover **240** may be integrally formed with the first side member **213**. In an embodiment, at least a part of the second rear cover **250** may be integrally formed with the second side member **223**. According to an embodiment, at least one of the first rear cover **240** and the second rear cover **250** may be substantially formed of a transparent plate (e.g., a polymer plate or

glass plate including various coding layers) or an opaque plate. According to an embodiment, the first rear cover **240** may be formed of, for example, an opaque plate such as coded or colored glass, ceramic, polymer, metal (e.g., aluminum, stainless steel (STS), or magnesium), or a combination of at least two of the materials above. According to an embodiment, the second rear cover **250** may be substantially formed of, for example, a transparent plate such as glass or polymer. Accordingly, the second display **300** may be disposed to be seen from the outside through the second rear cover **250** in a space in the second housing **220**.

(29) According to various embodiments, the input device **215** may include a microphone. In an embodiment, the input device **215** may include multiple microphones arranged to detect the direction of sound. According to an embodiment, the sound output devices **227** and **228** may include speakers. According to an embodiment, the sound output devices **227** and **228** may include a call receiver **227** disposed through the fourth surface **222** of the second housing **220** and an external speaker **228** disposed through at least a part of the second side member **223** of the second housing **220**. In an embodiment, the input device **215**, the sound output devices **227** and **228**, and the connector **229** may be disposed in spaces of the first housing **210** and/or the second housing **220**, and may be exposed to an external environment through at least one hole formed through the first housing **210** and/or the second housing **220**. In an embodiment, holes formed through the first housing **210** and/or the second housing **220** may be commonly used for the input device **215** and the sound output devices **227** and **228**. In an embodiment, the sound output devices **227** and **228** may include a speaker (e.g., a piezo speaker) operating without including a hole formed through the first housing **210** and/or the second housing **220**.

(30) According to various embodiments, the camera modules **216a**, **216b**, and **225** may include a first camera module **216a** disposed on the first surface **211** of the first housing **210**, a second camera module **216b** disposed on the second surface **212** of the first housing **210**, and/or a third camera module **225** disposed on the fourth surface **222** of the second housing **220**. According to an embodiment, the electronic device **200** may include a flash **218** disposed around the second camera module **216b**. According to an embodiment, the flash **218** may include, for example, a light-emitting diode or a xenon lamp. According to an embodiment, the camera modules **216a**, **216b**, and **225** may include one or multiple lenses, an image sensor, and/or an image signal processor. In an embodiment, at least one of the camera modules **216a**, **216b**, and **225** may include two or more lenses (e.g., wide-angle and telephoto lenses) and image sensors, and may be arranged together on one surface of the first housing **210** and/or the second housing **220**.

(31) According to various embodiments, the sensor modules **217a**, **217b**, and **226** may generate a data value or an electrical signal corresponding to an internal operational state or an external environmental state of the electronic device **200**. According to an embodiment, the sensor modules **217a**, **217b**, and **226** may include a first sensor module **217a** disposed on the first surface **211** of the first housing **210**, a second sensor module **217b** disposed on the second surface **212** of the first housing **210**, and/or a third sensor module **226** disposed on the fourth surface **222** of the second housing **220**. In an embodiment, the sensor modules **217a**, **217b**, and **226** may include at least one of a gesture sensor, a grip sensor, a color sensor, an infrared (IR) sensor, an illuminance sensor, an ultrasonic sensor, an iris recognition sensor, or a distance detection sensor (e.g., a time of flight (TOF) sensor or a light detection and ranging (LiDAR)).

(32) According to various embodiments, the electronic device **200** may further include an unillustrated sensor module, for example, at least one of an atmospheric sensor, a magnetic sensor, a biometric sensor, a temperature sensor, a humidity sensor, or a fingerprint recognition sensor. In an embodiment, the fingerprint recognition sensor may be disposed through at least one of the first side member **213** of the first housing **210** and/or the second side member **223** of the second housing **220**.

(33) According to various embodiments, the key input device **219** may be disposed to be exposed to the outside through the first side member **213** of the first housing **210**. In an embodiment, the

key input device **219** may be disposed to be exposed to the outside through the second side member **223** of the second housing **220**. In an embodiment, the electronic device **200** may not include some or all of the key input device **219**, and the unincluded key input device **219** may be implemented in another shape such as a soft key on the least one display **230** and **300**. In an embodiment, the key input device **219** may be implemented using a pressure sensor included in the at least one display **230** and **300**.

(34) According to various embodiments, the connector port **229** may include a connector (e.g., a USB connector or an IF module (an interface connector port module)) for transmitting or receiving data and/or power to and/or from an external electronic device. In an embodiment, the connector port **229** may perform a function of transmitting or receiving an audio signal to or from the external electronic device together, or may further include a separate connector port (e.g., an ear jack hole) for performing a function of transmitting or receiving an audio signal to or from the external electronic device.

(35) According to various embodiments, at least one camera modules **216a** and **225** of the camera modules **216a**, **216b**, and **225**, at least one sensor module **217a** and **226** of the sensor modules **217a**, **217b**, and **226**, and/or an indicator may be arranged to be exposed through the at least one display **230** and **300**. For example, the at least one camera modules **216a** and **225**, the at least one sensor module **217a** and **226**, and/or the indicator may be arranged under an activated area (a display area) of the at least one display **230** and **300** in a space in the at least one housing **210** and **220**, and may be arranged to come into contact with an external environment through a transparent area or an opening that is perforated to a cover member (e.g., a window layer (not shown) of the first display **230** and/or the second rear cover **250**). According to an embodiment, an area in which the at least one display **230** and **300** and the at least one camera module **216a** and **225** face each other may be formed as a transmission area having a predetermined transmission ratio, as a part of an area in which a content is displayed. According to an embodiment, the transmission area may be formed to have a transmission ratio in the range of about 5% to about 20%. The transmission area may include an area overlapping with an effective area (e.g., an angle of view area) of the at least one camera module **216a** and **225**, wherein an image is formed on the image sensor in the effective area, and light for generating an image passes through the effective area. For example, the transmission area of the display **230** and **300** may include an area in which the density of a pixel is lower than that in a surrounding area. For example, the transmission area may be replaced with an opening. For example, the at least one camera module **216a** and **225** may include an under-display camera (UDC) or an under-panel camera (UPC). In an embodiment, some camera modules or sensor modules **271a** and **226** may be arranged to perform functions thereof without being visually exposed through the display. For example, an area facing the sensor module **217a** and **226** and/or the camera module **216a** and **225** arranged under the display **230** and **300** (e.g., a display panel) corresponds to an under-display camera (UDC) structure, and a perforated opening is not necessarily required.

(36) FIG. 3 is an exploded perspective view illustrating an electronic device **200** according to various embodiments.

(37) Referring to FIG. 3, the electronic device **200** may include a first display **230** (e.g., a flexible display), a second display **300**, a hinge device **320**, a pair of support members **261** and **262**, at least one substrate **270** (e.g., a printed circuit board (PCB)), a first housing **210**, a second housing **220**, a first rear cover **240**, and/or a second rear cover **250**.

(38) According to various embodiments, the first display **230** may include a display panel **430** (e.g., a flexible display panel), a support plate **450** disposed under the display panel **430**, and a pair of reinforced plates **461** and **462** arranged under the support plate **450**. According to an embodiment, the display panel **430** may include a first panel area **430a** corresponding to a first area (e.g., the first area **230a** of FIG. 1A) of the first display **230**, a second panel area **430b** extending from the first panel area **430a** and corresponding to a second area (e.g., the second area **230b** of FIG. 1A) of the

first display **230**, and a third panel area **430c** for connecting the first panel area **430a** and the second panel area **430b** and corresponding to a folding area (e.g., the folding area **230c** of FIG. **1A**) of the first display **230**. According to an embodiment, the support plate **450** may be disposed between the display panel **430** and the pair of support members **261** and **262** and may be formed to have a material and a shape for providing a planar support structure for the first panel area **430a** and the second panel area **430b** and a bendable structure for assisting in the flexibility of the third panel area **430c**. According to an embodiment, the support plate **450** may be formed of a conductive material (e.g., metal) or a non-conductive material (e.g., polymer or fiber reinforced plastic (FRP)). According to an embodiment, the pair of reinforced plates **461** and **462** may include, between the support plate **450** and the pair of support members **261** and **262**, a first reinforced plate **461** disposed to correspond to at least a part of the first panel **430a** and the third panel area **430c**, and a second reinforced plate **462** disposed to correspond to at least a part of the second panel area **430b** and the third panel area **430c**. According to an embodiment, the pair of reinforced plates **461** and **462** may be formed of metal materials (e.g., SUS), and may thus assist in reinforcing of the rigidity and a ground connection structure for the first display **230**.

(39) According to various embodiments, the second display **300** may be disposed in a space between the second housing **220** and the second rear cover **250**. According to an embodiment, the second display **300** may be disposed in a space between the second housing **220** and the second rear cover **250** so as to allow the second display **300** to be seen from the outside through substantially the entire area of the second rear cover **250**.

(40) According to various embodiments, at least a part of the first support member **261** may be bendably coupled to the second support member **262** through the hinge device **320**. According to an embodiment, the electronic device **200** may include at least one wire member **263** (e.g., a flexible printed circuit board (FPCB)) disposed from at least a part of the first support member **261** to a part of the second support member **262** by crossing the hinge device **320**. According to an embodiment, the first support member **261** may be disposed by extending from the first side member **213** or structurally coupled to the first side member **213**. According to an embodiment, the electronic device **200** may include a first space (e.g., a first space **2101** of FIG. **1A**) provided through the first support member **261** and the first rear cover **240**. According to an embodiment, the first housing **210** (e.g., a first housing structure) may be configured by coupling of the first side member **213**, the first support member **261**, and the first rear cover **240**. According to an embodiment, the second support member **262** may be disposed by extending from the second side member **223** or structurally coupled to the second side member **223**. According to an embodiment, the electronic device **200** may include a second space (e.g., a second space **2201** of FIG. **1A**) provided through the second support member **262** and the second rear cover **250**. According to an embodiment, the second housing **220** (e.g., a second housing structure) may be configured through coupling of the second side member **223**, the second support member **262**, and the second rear cover **250**. According to an embodiment, at least a part of the hinge device **320** and/or the at least one wire member **263** may be disposed to be supported through at least a part of the pair of support members **261** and **262**. According to an embodiment, the at least one wire member **263** may be disposed in a direction (e.g., an x-axis direction) crossing the first support member **261** and the second support member **262**. According to an embodiment, the at least one wire member **263** may be disposed in a direction (e.g., an x-axis direction) substantially perpendicular to a folding axis (e.g., a y-axis or the folding axis A of FIG. **1A**).

(41) According to various embodiments, the at least one substrate **270** may include a first substrate **271** disposed in the first space **2101** and a second substrate **272** disposed in the second space **2201**. According to an embodiment, the first substrate **271** and the second substrate **272** may include multiple electronic components arranged to implement various functions of the electronic device **200**. According to an embodiment, the first substrate **271** and the second substrate **272** may be electrically connected to each other through the at least one wire member **263**.

(42) According to various embodiments, the electronic device **200** may include at least one battery **291** and **292**. According to an embodiment, the at least one battery **291** and **292** may include a first battery **291** disposed in the first space **2101** of the first housing **210** and electrically connected to the first substrate **271**, and a second battery disposed in the second space **2201** of the second housing **220** and electrically connected to the second substrate **272**. According to an embodiment, the first support member **261** and the second support member **262** may further include at least one swelling hole for the first battery **291** and the second battery **292**.

(43) According to various embodiments, the first housing **210** may include a first rotation support surface **214**, and the second housing **220** may include a second rotation support surface **224** corresponding to the first rotation support surface **214**. According to an embodiment, the first rotation support surface **214** and the second rotation support surface **224** may include a curved surface (seamlessly connected) corresponding to an external surface of a curved shape of the hinge housing **310**. According to an embodiment, when the electronic device **200** is in the unfolded state, the first rotation support surface **214** and the second rotation support surface **224** may hide the hinge housing **310** not to expose the hinge housing **310** through the rear surface of the electronic device **200** or to expose only a part thereof. According to an embodiment, when the electronic device **200** in the folded state, the first rotation support surface **214** and the second rotation support surface **224** may be at least partially expose the hinge housing **310** through the rear surface of the electronic device **200** as the curved shape of the hinge housing **310** rotates along an external surface.

(44) According to various embodiments, the electronic device **200** may include at least one antenna **276** disposed in the first space **2201**. According to an embodiment, the at least one antenna **276** may be disposed on the first battery **291** and the first rear cover **240** in the first space **2201**. According to an embodiment, the at least one antenna **276** may include, for example, a near-field communication (NFC) antenna, a wireless charging antenna, and/or a magnetic secure transmission (MST) antenna. According to an embodiment, the at least one antenna **276** may perform, for example, short-distance communication with an external device, or wirelessly transmit or receive power required for charging. In an embodiment, an antenna structure may be formed by at least a part of the first side member **213** or the second side member **223** and/or a part or a combination of the first support member **261** and the second support member **262**.

(45) According to various embodiments, the electronic device **200** may further include at least one electronic component assembly **274** and **275** and/or additional support members **263** and **273** disposed in the first space **2101** and/or the second space **2201**. For example, the at least one electronic component assembly may include an interface connector port assembly **274** or the speaker assembly **275**.

(46) According to various embodiments, the electronic device **100** may include a first waterproof structure WP1 disposed between the first reinforced plate **461** and the first support member **261** and a second waterproof structure WP2 disposed between the second reinforced plate **462** and the second support member **262**.

(47) According to an embodiment, the first waterproof structure WP1 may include a first waterproof member **481** disposed to have at least one first waterproof space **4811**, **4812**, and **4813** formed between the first reinforced plate **461** and the first support member **261**. According to an embodiment, the second waterproof structure WP2 may include a second waterproof member **482**, a third waterproof member **483**, and a fourth waterproof member **484** disposed to have at least one second waterproof space **4821** formed between the second reinforced plate **462** and the second support member **262**. According to an embodiment, the fourth waterproof member **484** may be disposed in a space between the second waterproof member **482** and the third waterproof member **483** spaced apart from each other, to connect the second waterproof member and the third waterproof member to each other.

(48) According to various embodiments, the at least one first waterproof space **4811** corresponds to

a wire structure for connecting an electronic component (e.g., a first digitizer **471** of FIG. **4**) disposed between the first reinforced plate **461** and the first support member **262** to the first space **2101** through the first waterproof member **481**, and may be disposed to receive a through-path of an FPCB connection portion (e.g., a first FPCB connection portion **4711** of FIG. **6**). According to an embodiment, the at least one second waterproof space **4821** corresponds to a wire structure for connecting an electronic component (e.g., a second digitizer **472** of FIG. **4**) disposed between the second reinforced plate **462** and the second support member **262** to the second space **2201** through the second waterproof member **482**, the third waterproof member **483**, and the fourth waterproof member **484**, and may be disposed to receive a through-path of an FPCB connection (e.g., a second FPCB connection **4721** of FIG. **6**). According to an embodiment, the at least one first waterproof space **4812** and **4813** may receive an area corresponding to at least one electronic component (e.g., a camera module or a sensor module) disposed to be supported by the first support member **261**. According to an embodiment, the at least one second waterproof space **4821** may receive at least a part of a bending portion (e.g., a bending portion **432** of FIG. **4**) bent over a rear surface of the first display **230**. For example, the at least one second waterproof space **4821** may be disposed to extend from a display panel (e.g., a display panel **430** of FIG. **4**) of the first display **230** and surround at least a part of the bending portion **432** bent over the rear surface. Accordingly, multiple electrical elements (not shown) and a control circuit (e.g., a control circuit **4321a** of FIG. **4**) disposed on the bending portion **432** may be disposed in the at least one second waterproof space **4821**, so as to be protected from water and/or a foreign material from the outside.

(49) According to various embodiments, the electronic device **200** may include waterproof tape **241** disposed between the first rear cover **240** and the first housing **210**. According to an embodiment, the electronic device **200** may include a bonding member **251** disposed between the second rear cover **250** and the second housing **220**. In an embodiment, the bonding member **251** may be disposed between the second display **300** and the second housing **220**. In an embodiment, the waterproof tape **241** may be replaced with the bonding member **251**, and the bonding member **251** may be replaced with the waterproof tape **241**.

(50) In the electronic device **200** according to an example embodiment of the disclosure, the at least one waterproof member **481**, **482**, **483**, and **484** may include at least one waterproof structure WP1 and WP2 disposed between the first support member **261** of the first housing **210** and the first reinforced plate **461** and/or between the second support member **262** of the second housing **220** and the second reinforced plate **462**, so that a phenomenon in which the first display is damaged when the first display **230** is separated from the housings **210** and **220** for maintenance of the electronic device **200** can be reduced through a waterproof member, and the at least one waterproof member **481**, **482**, **483**, and **484** is disposed to avoid the rear surface of the first display **230**, and thus, external visibility can be enhanced and a surface quality can be secured.

(51) FIG. **4** is an exploded perspective view illustrating a first display according to various embodiments. Hereinafter, a first display may be referred to as a “flexible display”.

(52) A flexible display (e.g., the first display **230** of FIG. **3**) according to various example embodiments of the disclosure may include an unbreakable (UB)-type OLED display (e.g., a curved display). However, the flexible display is not limited thereto and the flexible display **230** may include an oncell touch active matrix organic light-emitting diode (AMOLED) (OCTA) flat type display.

(53) Referring to FIG. **4**, the flexible display **230** may include a window layer **410**, and a polarizer (POL) **420** (e.g., a polarization film), a display panel **430**, a polymer layer **440**, a support plate **450**, and reinforced plates **461** and **462**, which are sequentially arranged on a rear surface (e.g., -z axis direction) of the window layer **410**. In an embodiment, the flexible display **230** may also include a digitizer **470** disposed between the support plate **450** and the reinforced plates **461** and **462**. In an embodiment, the digitizer **470** may be disposed between the polymer layer **440** and the support plate **450**.

(54) According to various embodiments, the window layer **410** may include a glass layer.

According to an embodiment, the window layer **410** may include an ultra-thin glass (UTG). In an embodiment, the window layer **410** may also include polymer. In this case, the window layer **410** may also include polyethylene terephthalate (PET) or polyimide (PI). In an embodiment, the window layer **410** may have multiple layers formed to include a glass layer and polymer.

(55) According to various embodiments, the window layer **410**, the polarization layer **420**, the display panel **430**, the polymer layer **440**, and the support plate **450** may be arranged to cross at least a part of a first surface (e.g., the first surface **211** of FIG. 1A) of a first housing (e.g., the first housing **210** of FIG. 1A) and a third surface (e.g., the third surface **221** of FIG. 1A) of a second housing (e.g., the second housing **220** of FIG. 1A). According to an embodiment, the reinforced plates **461** and **462** may include a first reinforced plate **461** corresponding to the first housing (e.g., the first housing **210** of FIG. 1A) and a second reinforced plate **462** corresponding to the second housing (e.g., the second housing **220** of FIG. 1A). According to an embodiment, the reinforced plates **461** and **462** may provide rigidity for the flexible display **230**, and may be used as a ground for preventing/reducing malfunction of the flexible display **230**. According to an embodiment, the reinforced plates **461** and **462** may be formed of a metal material. According to an embodiment, the reinforced plates **461** and **462** may be formed of SUS or AL. According to an embodiment, the window layer **410**, the polarization layer **420**, the display panel **430**, the polymer layer **440**, the support plate **450**, and the reinforced plates **461** and **462** may be attached to each other through adhesives P1, P2, or P3 (or adhesive agents). For example, the adhesives P1, P2, and P3 may include at least one of an optical clear adhesive (OCA), a pressure sensitive adhesive (PSA), a heat sensitive adhesive, a normal adhesive, or double-sided tape.

(56) According to various embodiments, the display panel **430** may include multiple pixels and a wire structure (e.g., an electrode pattern). According to an embodiment, the polarization layer **420** may allow light generated from a light source of the display panel **430** and vibrating in a predetermined direction to selectively pass therethrough. According to an embodiment, the display panel **430** and the polarization layer **420** may be integrally formed. According to an embodiment, the flexible display **230** may also include a touch panel (not shown).

(57) According to various embodiments, the polymer layer **440** may be disposed under the display panel **430** to provide a dark background for securing visibility of the display panel **430** and to be formed of a buffer material for buffering. In an embodiment, for waterproofing of the flexible display **230**, the polymer layer **440** may be removed, or may be disposed under the support plate **450**.

(58) According to various embodiments, the support plate **450** may provide a curved characteristic to the flexible display **230**. For example, the support plate **450** may be formed of a non-metal sheet type material such as fiber reinforced plastic (FRP) (e.g., carbon fiber reinforced plastic (CFRP) or glass fiber reinforced plastic (GFRP)) having a rigid characteristic to support the display panel **430**. According to an embodiment, the support plate **450** may include a first plane portion **451** corresponding to the first housing (e.g., the first housing **210** of FIG. 1A), a second plane portion **452** corresponding to the second housing (e.g., the second housing **220** of FIG. 1A), and a bending portion **453** (e.g., a flexible portion or a bending portion) for connecting the first plane portion **451** and the second plane portion **452**. According to an embodiment, the bending portion **453** may include multiple openings **4531** arranged to be spaced apart from each other by a designated space. According to an embodiment, a bendability characteristic of the bending portion **453** may be determined through at least one of sizes, shapes, or arrangement densities of some of the multiple openings **4531**. In an embodiment, the support plate **450** may be formed of a metal material such as steel use stainless (SUS) (e.g., stainless steel (STS)), Cu, Al, or metal CLAD (e.g., a laminate member obtained by alternately arranging SUS and Al). In this case, the multiple openings may be formed through the entire area of the support plate **450** so that a detection operation of the digitizer **470** disposed under the support plate **450** is derived. According to an embodiment, the support plate

450 may assist in reinforcing rigidity of an electronic device (e.g., the electronic device **200** of FIG. **1A**) and shield surrounding noise, and may be used to dissipate heat discharged from a surrounding heat discharging component.

(59) According to various embodiments, the display **230** may be disposed under the support plate **450**, and may include a digitizer **470** as a detection member for receiving an input of an electronic pen (e.g., a stylus). According to an embodiment, the digitizer **470** may include coil members arranged on a dielectric substrate (e.g., a dielectric film or a dielectric sheet) to detect an electromagnetic induction-type resonance frequency applied from the electronic pen. According to an embodiment, the digitizer **470** may include a first digitizer **471** corresponding to the first housing (e.g., the first housing **210** of FIG. **1A**) and a second digitizer **472** corresponding to the second housing (e.g., the second housing **220** of FIG. **1A**). According to an embodiment, the first digitizer **471** and the second digitizer **472** may be electrically connected to substrates (e.g., the substrates **271** and **272** of FIG. **3**) of an electronic device (e.g., the electronic device **200** of FIG. **3**) through FPCB connection portions (e.g., the first FPCB connection portion **4711** and the second FPCB connection portion **4721** of FIG. **6**), respectively, so as to operate as a single digitizer. In an embodiment, the first digitizer **471** and the second digitizer **472** may individually operate.

(60) According to various embodiments, the flexible display **230** may include at least one functional member (not shown) disposed between the polymer layer **440** and the support plate **450**, or disposed under the support plate **450**. According to an embodiment, the functional member may include a graphite sheet for heat dissipation, an added display, a force touch FPCB, a fingerprint sensor FPCB, a communication antenna radiator, or conductive/non-conductive tape. According to an embodiment, when the functional member is not bendable, the functional member may be individually disposed on the first housing (e.g., the first housing **210** of FIG. **1A**) and the second housing (e.g., the second housing **220** of FIG. **1A**). According to an embodiment, when the functional member is bendable, the functional member may be disposed from the first housing (e.g., the first housing **210** of FIG. **1A**) to at least a part of the second housing (e.g., the second housing **220** of FIG. **1A**) through the hinge device (e.g., the hinge device **320** of FIG. **3**).

(61) According to various embodiments, the flexible display **230** may include a bending portion **432** disposed in which the bending portion **432** is bent over at least partial area of a rear surface (e.g., -z axis direction) of the flexible display **230** from the display panel **430**. According to an embodiment, the bending portion **432** may include an extension portion **4321** extending from the display panel **430** and including a control circuit **4321a**, and a flexible substrate **4322** electrically connected to the extension portion **4321** and including multiple electrical elements. According to an embodiment, the control circuit **4321a** may include a display driver IC (DDI) or a touch display driver IC (TDDI) mounted on the extension portion **4321** having an electrical wire structure. According to an embodiment, the bending portion **432** may include a chip on panel or chip on plastic (COP) structure in which the control circuit **4321a** is directly disposed on the extension portion **4321**. In an embodiment, the bending portion **432** may also include a chip on film (COF) structure in which the control circuit **4321a** is mounted on a separate connection film (not shown) for connecting the extension portion **4321** and the flexible substrate **4322**. According to an embodiment, the flexible display **230** may include multiple electrical elements (not shown) arranged on the flexible substrate **4322**. According to an embodiment, the flexible display **230** may include an FPCB connection portion **4323** extending from the flexible substrate **4322** and electrically connected to a substrate (e.g., the second substrate **272** of FIG. **3**) of an electronic device (e.g., the electronic device **200** of FIG. **3**). According to an embodiment, the multiple electrical elements may include a touch IC, a display flash memory, an ESD prevention diode, a pressure sensor, a fingerprint sensor, or a passive element such as a Decap. In an embodiment, when the bending portion **432** is disposed in an area facing the first housing (e.g., the first housing **210** of FIG. **1A**) of the flexible display **230**, the FPCB connection portion **4323** may also be electrically connected to another substrate (e.g., the second substrate **271** of FIG. **3**) of an electronic

device (e.g., the electronic device **200** of FIG. 3).

(62) According to various example embodiments of the disclosure, an electronic device (e.g., the electronic device **200** of FIG. 3) may include a wire structure of an FPCB connection portion (e.g., the FPCB connections **4711** and **4712** of FIG. 6) withdrawn from the digitizer **470** disposed on a rear surface of the flexible display **230**, and a waterproof structure provided to protect, from water and/or a foreign material from the outside, areas corresponding to at least one electronic component (e.g., a camera module or a sensor module) disposed through the support members **461** and **462** and at least a part (e.g., the extension portion **4321**) of the bending portion **432** bent over the rear surface of the flexible display **230** and including the control circuit **4321a** and the multiple electrical elements.

(63) Hereinafter, a detailed description of a waterproof structure provided to an electronic device is made.

(64) FIG. 5 is a diagram illustrating an example configuration of reinforced plates according to various embodiments. FIG. 6 is a diagram illustrating a rear surface structure of a flexible display according to various embodiments.

(65) FIGS. 5 and 6 illustrate configurations of a flexible display **230** and reinforced plates **461** and **462** seen when an electronic device (e.g., the electronic device **200** of FIG. 1B) is seen in a rear direction (e.g., when the electronic device is seen in the state shown in FIG. 1B).

(66) Referring to FIGS. 5 and 6, an electronic device (e.g., the electronic device **200** of FIG. 3) may include a first reinforced plate **461** corresponding to a first housing (e.g., the first housing **210** of FIG. 1A) and a second reinforced plate **462** corresponding to a second housing (e.g., the second housing **220** of FIG. 1A). According to an embodiment, a first digitizer (e.g., the first digitizer **471** of FIG. 4) may be disposed between a support plate (e.g., the support plate **450** of FIG. 4) and the first reinforced plate **461**, and a first FPCB connection portion **4711** of the first digitizer **471** may be electrically connected to a substrate (e.g., the first subplate **271** of FIG. 3) disposed in a first space (e.g., the first space **2101** of FIG. 1A) of a first housing (e.g., the first housing **210** of FIG. 1A) through the first reinforced plate **461**. Accordingly, the first reinforced plate **461** may include a first through-hole **4611** through which the first FPCB connection portion **4711** is to extend.

According to an embodiment, a second digitizer (e.g., the second digitizer **472** of FIG. 4) may be also disposed between the support plate (e.g., the support plate **450** of FIG. 4) and the second reinforced plate **462**, and a second connection portion **4721** of the second digitizer **472** may be electrically connected to a substrate (e.g., the second substrate **272** of FIG. 3) disposed in a second space (e.g., the second space **2201** of FIG. 1A) of a second housing (e.g., the second housing **220** of FIG. 1A), through the second reinforced plate **462**. Accordingly, the second reinforced plate **462** may include a second through-hole **4621** through which the second FPCB connection portion **4721** is to extend. According to an embodiment, the first reinforced plate **461** may include at least one hole **4612** for one or more electronic components (e.g., a camera module or a sensor module) arranged to be supported by a first support member (e.g., the first support member **261** of FIG. 3). For example, the at least one electronic component may be disposed to correspond to at least one hole **4612** to detect an external environment through the flexible display **230**.

(67) According to various embodiments, the electronic device (e.g., the electronic device **200** of FIG. 3) may include a first waterproof structure WP1 disposed between the first reinforced plate **461** and the first support member (e.g., the first support member **261** of FIG. 3) of the first housing (e.g., the first housing **210** of FIG. 3) and a second waterproof structure WP2 disposed between the second reinforced plate **462** and the second support member (e.g., the second support member **262** of FIG. 3) of the second housing (e.g., the second housing **220** of FIG. 3). According to an embodiment, the first waterproof structure WP1 may include at least one first waterproof space **4811**, **4812**, and **4813** formed through the first waterproof member **481**. According to an embodiment, the first waterproof member **481** may include at least one of tape, an adhesive, waterproof dispensing, silicone, waterproof rubber, and urethane. According to an embodiment, the

at least one first waterproof space **4811**, **4812**, and **4813** may include a closed loop-shaped waterproof space **4811**, a closed loop-shaped waterproof space **4812** spaced apart from the waterproof space **4811**, and a closed loop-shaped waterproof space **4813** spaced apart from the waterproof space **4812**. According to an embodiment, the first through-hole **4611** may be disposed at a position at least partially overlapping with the waterproof space **4811** when seen from above the first reinforced plate **461**. According to an embodiment, the at least one hole **4612** may be disposed at a position at least partially overlapping with the waterproof space **4812** when seen from above the first reinforced plate **461**. The waterproof space **4813** may be disposed a position overlapping with the at least one electronic component (e.g., a sensor module).

(68) According to various embodiments, the second waterproof structure WP2 may include a closed loop-shaped fourth waterproof space **4821** formed through a second waterproof member **482**, a third waterproof member **483**, and a fourth waterproof member **484**. According to an embodiment, the second through-hole **4621** may be disposed at a position at least partially overlapping with the fourth waterproof space **4821** when seen from above the second reinforced plate **462**. According to an embodiment, the fourth waterproof space **4821** may be formed between the second reinforced plate **462** and the second support member **262** and through the second waterproof member **482** disposed to surround at least a part of the bending portion **432**, the third waterproof member **483** disposed between the extension portion **4321** and the second support member **262**, and the fourth waterproof member **484** for connecting the second waterproof member **482** and the third waterproof member **483**. According to an embodiment, the second waterproof member **482** and the third waterproof member **483** may include at least one of tape, an adhesive, waterproof dispensing, silicone, waterproof rubber, and urethane. According to an embodiment, when the second waterproof member **482** and the third waterproof member **483** are integrally formed, water or a foreign material may be introduced into a gap formed due to a height difference (a step) between the bending portion **432** and the second reinforced plate **462**. According to an embodiment, the second waterproof member **482** may be attached in a state in which the second waterproof member **482** is separated to be spaced apart from the third waterproof member **483** by a designated space at the stepped portion, wherein the stepped portion including the corresponding space may be connected through the fourth waterproof member **484** without a gap. According to an embodiment, the fourth waterproof member **484** may include a semisolid or liquid material, and include a cured in place gasket (CIPG) (e.g., a waterproof filling member) having a characteristic of naturally solidifying or solidifying by an external condition (e.g., heat, ultraviolet rays, moisture, or pressure).

(69) According to various embodiments, the second through-hole **4621** may be disposed at a position at least partially overlapping with the fourth waterproof space **4821** when seen from above the second reinforced plate **462**. According to an embodiment, the flexible display **230** may include a third FPCB connection portion **4323** extending from a flexible substrate **4322** of the bending portion **432**.

(70) According to an embodiment, the third FPCB connection portion **4323** may be electrically connected to a substrate (e.g., the second substrate **272** of FIG. 3) disposed in a second space (e.g., the second space **2201** of FIG. 1A) through the second support member **262**. According to an embodiment, an area in which the third FPCB connection portion **4323** is disposed may be also disposed in an area at least partially overlapping with the fourth space **4821** when seen from above the second reinforced plate **262**. Accordingly, the second through-hole **4621** and the third FPCB connection portion **4323** may be positioned in the closed loop-shaped fourth waterproof space **4821** to prevent and/or reduce water and a foreign material from being introduced.

(71) FIG. 7 is a diagram illustrating an example configuration of an electronic device, which indicates an unfolded state while a flexible display is omitted, according to various embodiments.

(72) FIG. 7 illustrates configurations of housings **210** and **220** seen when an electronic device (e.g., the electronic device **200** of FIG. 1A) is seen in a front surface direction (e.g., when the electronic

device is seen in the state shown in FIG. 1A).

(73) Referring to FIGS. 5, 6 and 7 (which may be referred to as FIGS. 5 to 7), an electronic device **200** may include a first housing **210**, and a second housing **220** foldably connected to the first housing **210** through a hinge device (e.g., the hinge device **320** of FIG. 3). According to an embodiment, the first housing **210** may include a first side member **213** for forming at least a part of a side surface of the electronic device **210**, and a first support member **261** extending from the first side member **213** to a first space **2101**. According to an embodiment, the second housing **220** may include a second side member **223** for forming at least a part of a side surface of the electronic device, and a second support member **262** extending from the second side member **223** to a second space **2201**. According to an embodiment, the first support member **261** and the second support member **262** may be substantially formed as a flat surface to support the flexible display **230** of FIG. 6. According to an embodiment, when the flexible display **230** is coupled to be supported by the first housing **210** and the second housing **220**, the first reinforced plate **461** may be disposed to face at least a part of the first support member **261**, and the second reinforced plate **462** may be disposed to face at least a part of the second support member **262**.

(74) According to various embodiments, the first support member **261** may include a first member through-hole **2611** connected to the first space **2201** from an external surface. According to an embodiment, when the flexible display **230** is disposed, the first FPCB connection portion **4711** of the first digitizer **471** withdrawn from the first through-hole **4611** of the first reinforced plate **461** may be electrically connected to a first substrate (e.g., the first substrate **271** of FIG. 3) disposed in the first space **2101** of the first housing **210**, through the first member through-hole **2611** formed through the first support member **261**. According to an embodiment, when the flexible display **230** is disposed, the second FPCB connection portion **4721** of the second digitizer **472** withdrawn from the second through-hole **4621** of the second reinforced plate **462** may be electrically connected to a second substrate (e.g., the second substrate **272** of FIG. 3) disposed in the second space **2201** of the second housing **220**, through the second member through-hole **4621** formed through the second support member **262**. According to an embodiment, the third FPCB connection portion **4323** disposed to be bent over a rear surface of the flexible display **230** and connected to the flexible substrate **4322** may be electrically connected to a second substrate (e.g., the second substrate **272** of FIG. 3) disposed in the second space **4821** of the second housing **220**, through the third member through-hole **2622** formed through the second support member **261**. According to an embodiment, at least one electronic component (e.g., a camera module or a sensor module) disposed in the first space **2101** may be disposed to be oriented in a direction of a flexible display through a module receiving hole **2612** formed through the first support member **261**.

(75) According to various embodiments, a penetration structure of the first FPCB connection portion **4711** through the first through-hole **4611** of the first reinforced plate **461** and the first member through-hole **2611** of the first support member **261** may be disposed to be included in the first waterproof space **4811** formed by the first waterproof structure WP1 when seen from above the first support member **261**, so as to be protected from water and/or a foreign material from the outside. According to an embodiment, a penetration structure of the second FPCB connection portion **4721** through the second through-hole **4621** of the second reinforced plate **462** and the second member through-hole **2621** of the second support member **262** may be disposed to be included in the fourth waterproof space **4821** formed by the second waterproof structure WP2 when seen from above the second support member **262**, so as to be protected from water and/or a foreign material from the outside. According to an embodiment, a penetration structure of the third FPCB connection portion **4323**, extending through the third member through-hole **2622** of the second support member **262** and extending from the bending portion **432** of a display panel (e.g., the display panel **430** of FIG. 4), may be disposed to be included in the fourth waterproof space **4821** formed by the second waterproof structure WP2 when seen from above the second support member **262**, so as to be protected from water from the outside. According to an embodiment, the module

receive hole **2612** formed through the first support member **261** may be disposed to be included in the second waterproof space **4812** formed by the first waterproof structure **WP1** when seen from above the first support member **261**, so that the at least one electronic component can be protected from water from the outside.

(76) According to various embodiments, the first digitizer **471** and the second digitizer **472** may include a shield layer (e.g., a magnetic metal powder (MMP)) disposed on a rear surface, so as to shield an electromagnetic signal. According to an embodiment, the first digitizer **471** and the second digitizer **472** may omit a shield layer in an area in which the first FPCB connection portion **4711** and the second FPCB connection portion **4721** are withdrawn. Accordingly, when seen from above the first reinforced plate **461**, the first support member **261** may include a first shield layer **471a** (e.g., a shield member or an MMP) disposed at a position corresponding to the first through-hole **4611**. Accordingly, the first member through-hole **2611** may be disposed at a position not overlapping with the first through-hole **4611**. According to an embodiment, when seen from above the second reinforced plate **462**, the second support member **262** may include a second shield layer **472a** (e.g., a shield member or an MMP) disposed at a position corresponding to the second through-hole **4621**. Accordingly, the second member through-hole **2621** may be disposed at a position not overlapping with the second through-hole **4621**.

(77) FIG. **8A** is a cross-sectional view illustrating an electronic device including a flexible display, taken along line **8a-8a** in FIG. **6** according to various embodiments.

(78) Referring to FIG. **8A**, an electronic device **100** may include a first housing **210** including a first side member **213**, a second housing including a second side member **223**, and a flexible display **230** disposed to be supported by the first housing **210** and the second housing **220**. According to an embodiment, the flexible display **230** may be disposed to be supported by a first support member **261** extending from the first side member **213** and a second support member **262** extending from the second side member **223**. According to an embodiment, the first housing **210** may include a first protection frame **213a** (e.g., a first decoration member) which is, when seen from above the flexible display **230**, coupled to the first side member **213** and disposed to overlap with an edge of the flexible display **230**, so as to cover the edge of the flexible display **230** to allow the same not to be seen from the outside. According to an embodiment, the first protection frame **213a** may be also integrally formed with the first side member **213**. According to an embodiment, the second housing **220** may include a second protection frame **223a** (e.g., a second decoration member) which is, when seen from above the flexible display **230**, coupled to the second side member **223** and disposed to overlap with an edge of the flexible display **230**, so as to cover the edge of the flexible display **230** to allow the same not to be seen from the outside. According to an embodiment, the second protection frame **223a** may be also integrally formed with the first side member **223**. In an embodiment, the first protection frame **213a** and the second protection frame **223a** may be omitted. In an embodiment, in order to receive a slip phenomenon occurring upon an operation of folding or unfolding the electronic device **200**, the flexible display **230** may be disposed to maintain a gap of a designated interval between the side members **213** and **223** and the protection frames **213a** and **223a**, respectively.

(79) According to various embodiments, the flexible display **230** may include a window layer **410**, and a polarization layer **420**, a display panel **430**, a polymer layer **440**, a support plate **450**, a pair of digitizers **471** and **472**, and a pair of reinforced plates **461** and **462**, which are sequentially arranged under the window layer **410**. According to an embodiment, the support plate **450** may include multiple openings **4531** formed in a folding area to provide bendability to the flexible display **230**. According to an embodiment, the flexible display **230** may further include a shield member **4532** disposed in the middle of an adhesive layer **P** for attaching the digitizer **470** to the support plate **450**, to shield the multiple openings **4531**. According to an embodiment, the shield member may include thermoplastic polyurethane (TPU) attached to the support plate. According to an embodiment, the pair of digitizers **471** and **472** may include a first digitizer **471** disposed at a

position corresponding to the first housing **210**, and a second digitizer **472** disposed at a position corresponding to the second housing **220**. According to an embodiment, the pair of reinforced plates **461** and **462** may include a first reinforced plate **461** disposed at a position corresponding to the first housing **210**, and a second reinforced plate **462** disposed at a position corresponding to the second housing **220**. According to an embodiment, the electronic device **200** may include a first metal sheet layer **4712** disposed between the first digitizer **471** and the first reinforced plate **461**, and a second metal sheet layer **4722** disposed between the second digitizer **472** and the second reinforced plate **262**. According to an embodiment, the first metal sheet layer **4712** and the second metal sheet layer **4722** may assign directivity to an electromagnetic induction signal generated from the digitizers **471** and **472**, and may be formed of a metal material capable of preventing/reducing an eddy current. According to an embodiment, each of the first metal sheet layer **4712** and the second metal sheet layer **4722** may include a Cu sheet.

(80) According to various embodiments, the flexible display **230** may include a bending portion **432** extending toward an outer side from the display panel **430** and disposed to be bent over a rear surface (e.g., a surface of the second reinforced plate **462**) of the flexible display **230**. According to an embodiment, the flexible display **230** may further include a bending portion protection layer **4324** (e.g., a bending protection layer (BPL)) which is laminated on an outer surface of the bending portion **432** and is for protecting at least a part of the bending portion **432**. According to an embodiment, the bending portion **432** may include an extension portion **4321** extending from the display panel **430** and including a control circuit **4321a**, and a flexible substrate **4322** connected to the extension portion **4321** and including multiple electrical elements. According to an embodiment, the bending portion **432** may be bent over the rear surface of the flexible display **230** and attached to the second reinforced plate **462**. According to an embodiment, a ground of the flexible substrate **4322** may be electrically connected to the second reinforced plate **462** to assist in preventing/reducing malfunction (e.g., a flicker phenomenon) of the flexible display **230**.

According to an embodiment, the extension portion **4321** of the bending portion **432** may be attached to the second reinforced plate **462** on the rear surface of the flexible display **230** through a first adhesive member **T1**. According to an embodiment, the flexible substrate **4322** may be attached to the second reinforced plate **462** through the second adhesive member **T2**. For example, the first adhesive member **T1** corresponds to a tape member having a designated thickness and may also perform a role of a spacer having a thickness for compensating a height difference between the extension portion **4321** and the flexible substrate **4322** and maintain a bent state of the bending portion **432**. According to an embodiment, the first adhesive member **T1** and/or the second adhesive member **T2** may be at least partially exposed to the outside and may thus include a waterproof member (e.g., waterproof tape). According to an embodiment, the first adhesive member **T1** may include PET, PI, or a material obtained by combining closed-type foam and PET. According to an embodiment, the second adhesive member **T2** may include conductive tape for electrically connecting the ground of the flexible substrate **4322** to the second reinforced plate **462**. In an embodiment, the second adhesive member **T2** may also have a compensation function for compensating a height difference between the extension portion **4321** and the flexible substrate **4322**.

(81) According to various embodiments, the control circuit **4321a** disposed on the extension portion **4321** may be protected by a cover member **485** attached to cover at least a part of the flexible substrate **4322** to at least a part of the extension portion **4321**. According to an embodiment, the control circuit **4321a** may be disposed between the flexible substrate **4322** and the third adhesive member **T3** disposed between the cover member **485** and the extension portion **4321**, so as to be sealed. In an embodiment, when the size of the control circuit **4321a** is small and the distance between the control circuit **4321a** and the bending portion protection layer **4324** is far, the third adhesive member **T3** may be omitted. In this case, a part of the cover member **485** may be bent and then directly attached to the extension portion **4321**. According to an embodiment, the

third adhesive member **T3** may include a waterproof member (e.g., waterproof tape). According to an embodiment, the third adhesive member **T3** may be disposed between the bending portion protection layer **4324** and the control circuit **4321a**. According to an embodiment, at least a part of the cover member **485** may directly come into contact with water and/or a foreign material from the outside and may be thus formed of a material, wherein the material itself has a waterproof structure. For example, the cover member **485** may include a conductive non-woven fabric which has pieces of conductive fiber tissue, which are irregularly arranged, and prevents and/or reduces water from being introduced from the outside.

(82) According to various embodiments, the electronic device **200** may include a first waterproof structure **WP1** including a first waterproof member **481** disposed between the first reinforced plate **461** and the first support member **261**. According to an embodiment, the first waterproof member **481** may provide a first waterproof space **4811**, a second waterproof space **4812**, and a third waterproof space (e.g., the third waterproof space **4813** of FIG. 7) between the first reinforced plate **461** and the first support member **261**. According to an embodiment, the first waterproof space **4811** may receive a through-path for a first FPCB connection portion (e.g., the first FPCB connection portion **4711** of FIG. 6) of the first digitizer **471**. According to an embodiment, the second waterproof space **4812** may receive a module receiving hole **2612** formed through the first support member **261**, so as to connect a camera module (e.g., the camera module **261a** of FIG. 1A) disposed in a first space (e.g., the first space **2101** of FIG. 7) of the first housing **210** to the display panel **430**. According to an embodiment, the third waterproof space (e.g., the third waterproof space **4813** of FIG. 7) may receive at least one electronic component (e.g., a sensor module) disposed through the first housing **210**. According to an embodiment, the first reinforced plate **461** extending to a position that is substantially the same as or similar to that of the edge of the first support member **261**, so as to include a hole (e.g., a camera hole) corresponding to the module receiving hole **2612**.

(83) According to various embodiments, the electronic device **200** may include a second waterproof structure **WP2** including a second waterproof member **482**, a third waterproof member **483**, and a fourth waterproof member (e.g., the fourth waterproof member **484** of FIG. 7) arranged between the second reinforced plate **462** and the second support member **262**. According to an embodiment, the second waterproof structure **WP2** may provide a fourth waterproof space **4821** between the second waterproof plate **462** and the second support member **262**. According to an embodiment, the second waterproof member **482** may be disposed on the second reinforced plate **462** to surround at least a part of the bending portion **432**, the third waterproof member **483** may be disposed on the cover member **485**, and the fourth waterproof member **484** may be disposed in a stepped space between the second waterproof member **482** and the third waterproof member **483** spaced apart from each other, to connect the second waterproof member and the third waterproof member. According to an embodiment, the fourth waterproof space **4821** may receive a through-path for a second FPCB connection portion (e.g., the second FPCB connection portion **4721** of FIG. 6) of the second digitizer **472**. According to an embodiment, the fourth waterproof space **4821** may include a through-path for a third FPCB connection portion (e.g., the third FPCB connection portion **4323** of FIG. 6) extending from the flexible substrate **4322**. Accordingly, the control circuit **4321a** and the multiple electrical elements may be formed between the second reinforced plate **462** and the second support member **262** through the second waterproof member **482**, the third waterproof member **483**, and the fourth waterproof member **484**, may be disposed in the fourth waterproof space **4821** having a closed-loop shape, which has overcome a discontinuous interval caused by a stepped structure, and thus can be protected from water and/or a foreign material introduced from the outside.

(84) The waterproof structures **WP1** and **WP2** according to various example embodiments of the disclosure may have an arrangement structure in which the multiple waterproof members **481**, **482**, **483**, and **484** are attached to the reinforced plates **461** and **462** rather than on the rear surface of the

display panel **430**, and thus, a damage (e.g., tearing due to an adhesive force) of the display panel **430** during the maintenance of the electronic device **200** can be reduced and visibility can be enhanced. In addition, the multiple waterproof members **481**, **482**, **483**, and **484** are not directly attached to the digitizers **471** and **472**, and thus, deterioration in a waterproof function by a coil pattern can be reduced. In addition, the digitizers **471** and **472** and/or an electrical connection (e.g., through-paths of the FPCB connection portions **4711**, **4721**, and **4723**) of the display panel **430** may be provided in the waterproof spaces **4811** and **4821**, and thus, exposure to water from the outside and/or contamination due to a foreign material can be reduced.

(85) FIG. **8B** is a cross-sectional view of a part of an electronic device, which illustrates a state in which an FPCB connection portion is disposed through area **8b** in FIG. **6** and area **8b** in FIG. **7**, according to various embodiments.

(86) Referring to FIG. **8B**, an electronic device (e.g., the electronic device **300** of FIG. **3**) may include a first waterproof member **481** disposed between a first support member **261** of a first housing **210** and a first reinforced plate **461** disposed under a first digitizer **471**. According to an embodiment, the first waterproof member **481** may include a first waterproof space **4811** formed between the first support member **261** and the first reinforced plate **461**. According to an embodiment, the first digitizer **471** may include a through-hole **4711a** formed on a first metal sheet layer **4712** disposed between the first digitizer **471** and the first reinforced plate **461**, and a first FPCB connection portion **4711** formed on the first reinforced plate **461** and withdrawn through a first through-hole **4611** received in the first waterproof space **4811**. According to an embodiment, one end of the first FPCB connection portion **4711** may be electrically connected to the first digitizer **471** through a solder **S**, and the other end may extend through a first member through-hole **2611** formed through the first support member **261**, and then electrically connected to a first substrate **271** disposed in a first space (e.g., the first space **2101** of FIG. **1A**) of the first housing **210**. In an embodiment, at least a part of the first FPCB connection portion **4711** may be attached to a surface of the reinforced plate **461** through a fourth adhesive member **T4** in the first waterproof space **4811**. Accordingly, a cable through-path for connecting the first digitizer **471** and the first substrate **271** may be disposed in the first waterproof space **4811** formed through the first waterproof member **481**, and can thus prevent and/or reduce water and/or a foreign material from being introduced from the outside. Although not shown, a second digitizer (e.g., the second digitizer **472** of FIG. **8**) may also electrically connected to a second substrate (e.g., the second substrate **272** of FIG. **3**) disposed in a second space (e.g., the second space **2201** of FIG. **1A**) of a second housing (e.g., the second housing **220** of FIG. **1A**) in substantially the same scheme as the first digitizer, through a fourth waterproof space (e.g., the fourth waterproof space **4821** of FIG. **8A**) formed through a second waterproof structure (e.g., the second waterproof structure **WP2** of FIG. **8A**).

(87) FIG. **8C** is a perspective view of a part of a second housing, illustrating a state in which in which a fourth waterproof member is applied in the **8c** area in FIG. **7**, according to various embodiments.

(88) Referring to FIG. **8C**, a second housing **220** may include a filling member injection hole **2623** (e.g., a through-hole) formed through the second support member **262** in a position facing a second reinforced plate (e.g., the second reinforced plate **462** of FIG. **6**) and corresponding to a space between a second waterproof member (e.g., the second waterproof member **482** of FIG. **7**) and a third waterproof member (e.g., the third waterproof member **483** of FIG. **7**) spaced apart from each other. For example, a filling member injection hole **2623** may be formed at a position corresponding to a space between a second waterproof member **482** attached to the second reinforced plate **462** and a third waterproof member (e.g., the third waterproof member **484** of FIG. **7**) attached to a cover member (e.g., the cover member **485** of FIG. **8A**), the second waterproof member and the third waterproof member being spaced apart from each other. According to an embodiment, the fourth waterproof member **484** may be injected through the filling member

injection hole **2623** from a second space **2201** of the second housing **220** in a state in which the second water member **482** and the third waterproof member **483** are attached (e.g., when the flexible display **230** is attached to the second housing **220**). According to an embodiment, after a needle **610** of a dispenser **600** is partially inserted into the filling member injection hole **263**, the fourth waterproof member **484** may be applied in a liquid or a semisolid form through the needle **610**, and then solidifies. In this case, the solidifying fourth waterproof member **484** may connect the second waterproof member **482** and the third waterproof member **483**, becomes rigid, and then is fixed in the second support member **262** and the space between the second waterproof member **482** and the third waterproof member **483** spaced apart from each other, and can thus assist in forming a sealed fourth waterproof space (e.g., the fourth waterproof space **4821** of FIG. 7).

(89) FIG. 8D is a cross-sectional view illustrating an electronic device including a flexible display, taken along the line **8d-8d** in FIG. 6, according to various embodiments.

(90) In describing an electronic device **200** of FIG. 8D, the same reference numerals are assigned to elements that are substantially the same as or similar to those of the electronic device **200** of FIG. 8A, and a detailed description thereof may not be repeated.

(91) Referring to FIG. 8D, the electronic device **200** may include at least one magnet **M1** and **M2** arranged in the first housing **210** and the second housing **220**. According to an embodiment, the at least one magnet **M1** and **M2** may include a first magnet **M1** disposed in the first housing **210** and a second magnet **M2** disposed in the second housing **220**. According to an embodiment, when the electronic device **200** is in a folded state, the first magnet **M1** and the second magnet **M2** may be disposed at a corresponding position at which the first magnet **M1** and the second magnet **M2** can react to magnetic forces with respect to each other, and can thus assist in maintaining the folded state through the magnetic forces (e.g., human power).

(92) According to various embodiments, the electronic device **200** may include a first shield member **491** for performing shielding so that the magnetic force of the first magnet **M1** disposed in the first housing **210** does not influence the first digitizer **471** and/or the display panel **430**, and a second shield member **492** for performing shielding so that the magnetic force of the second magnet **M2** disposed in the second housing **220** does not influence the second digitizer **472** and/or the display panel **430**. According to an embodiment, the first shield member **491** overlaps with the first waterproof member **481** disposed on the first reinforced plate **461**, a waterproof function may not be performed due to generation of a step. Accordingly, the first shield member **491** may be disposed between the first digitizer **471** and the first support member **261** in an area in which at least a part of the first metal sheet layer and the first reinforced plate **461** are excluded, in order to avoid the first waterproof member **481** and receive the thickness of the first shield member **491**. According to an embodiment, the second shield member **492** may be disposed through a laminate structure in which the bending portion **432** is disposed, in an area corresponding to the second housing **220**. According to an embodiment, the second shield member **492** may be disposed between the second digitizer **472** and the first adhesive member **T1** for attaching the extension unit **4321** to the second reinforced plate **462**, in an area in which the second reinforced plate **462** and the second metal sheet layer **4722** are omitted. For example, the thickness of the second shield member **492** may be formed with a thickness identical to a thickness obtained by summing thicknesses of the second reinforced plate **462** and the second metal sheet layer **4722**.

(93) FIG. 9 is an enlarged view illustrating area **9** in FIG. 6, according to various embodiments.

(94) Referring to FIG. 9, a second waterproof space **4812** formed through a first waterproof member **481** may be disposed near an edge **481a** (e.g., an edge) of the first waterproof member **481** to correspond to a module receiving hole (e.g., the module receiving hole **2612** of FIG. 7) of a first support member (e.g., the first support member **261** of FIG. 7). This is because, in a case where at least one electronic component disposed through the module receiving hole **2612** corresponds to a camera module and/or a sensor module, it is advantageous to configure a large screen when the second waterproof space **4812** is disposed closer to the edge of the flexible display **230**. In this

case, the distance from the second waterproof space **4812** to the edge **481a** of the first waterproof member **481** may become narrow, which makes implementation of a waterproof function difficult. (95) According to an example embodiment of the disclosure, the first waterproof member **481** may include a protrusion **481b** having an extended distance D obtained through protrusion by a designated distance ΔD from the edge **481a**. According to an embodiment, the protrusion **481b** may be formed as a shape corresponding to the shape of the second waterproof space **4812**, so that the first waterproof member **481** may induce the distance D from the second waterproof space **4812** to the edge **481a** to be uniform, and can thus assist in stably implementing the waterproof function. According to an embodiment, when the second waterproof space **4812** has a circular shape, the protrusion **481b** may be formed to have a curved shape having a curvature, which corresponds to the circular shape.

(96) FIG. **10** is a cross-sectional view illustrating an electronic device according to various embodiments.

(97) In describing an electronic device **200** of FIG. **10**, the same reference numerals are assigned to elements that are substantially the same as or similar to those of the electronic device **200** of FIG. **8A**, and a detailed description thereof may not be repeated.

(98) Referring to FIG. **10**, the electronic device **200** may be configured by excluding a digitizer (e.g., the digitizer **470** of FIG. **8A**) and conductive sheet layers (e.g., the conductive sheet layers **4712** and **4722** of FIG. **8A**). In this case, the first reinforced plate **461** may be attached to the support plate **450** through the adhesive member P. According to an embodiment, the second reinforced plate **462** may be also attached to the support plate **450** through the adhesive member P. According to an embodiment, the electronic device **200** may include a first waterproof structure WP1 disposed between the first reinforced plate **461** and the first support member **261** of the first housing **210**, and a second waterproof structure WP2 disposed between the second reinforced plate **462** and the second support member **262** of the second housing **220**. According to an embodiment, a configuration of arranging the first waterproof structure WP1 and the second waterproof structure WP2 may be substantially identical to that in FIG. **8A**.

(99) FIG. **11A** is a cross-sectional view illustrating an electronic device according to various embodiments. FIG. **11B** is a diagram illustrating an example configuration of reinforced plates applied to FIG. **11A**, according to various embodiments.

(100) In describing an electronic device **200** of FIG. **11A**, the same reference numerals are assigned to elements that are substantially the same as or similar to those of the electronic device **200** of FIG. **10**, and a detailed description thereof may not be repeated.

(101) Referring to FIGS. **11A** and **11B**, in the electronic device **200** of FIG. **10**, the bending portion **432** of the display panel **430** disposed in an area corresponding to the second housing **220** may be disposed to be laminated on the second reinforced plate **462**. In this case, the flexible substrate **4322** and the second adhesive member T2, each of which has a relatively greater thickness, may make the thickness of the electronic device **200** to be greater in the z-axis direction, which may become a cause of adverse contribution to slimming of the size of the electronic device **200**.

(102) According to an example embodiment of the disclosure, the first reinforced plate **461** may include a third through-hole **4623** formed in an area corresponding to the second adhesive member T2. According to an embodiment, the third through-hole **4623** may have a shape and a size which allow at least a part of the second adhesive member T2 to extend therethrough. Accordingly, the second adhesive member T2 may come into contact with the support plate **450** after extending through the third through-hole **4623**, and thus, the entire lamination height of the bending portion **432** may be lowered. In this case, for ground connection of the flexible substrate **4322**, the support plate **450** may be formed of a conductive material (e.g., a metal material). In an embodiment, the third through-hole **4623** may have a size and a shape which allow at least a part of the flexible substrate **4322** and the second adhesive member T2 to be received therein.

(103) FIG. **12** is a cross-sectional view illustrating an electronic device according to various

embodiments.

(104) In describing an electronic device **200** of FIG. **12**, the same reference numerals are assigned to elements that are substantially the same as or similar to those of the electronic device **200** of FIG. **8A**, and a detailed description thereof may not be repeated.

(105) Referring to FIG. **12**, the electronic device **200** may be configured by excluding a digitizer (e.g., the digitizer **470** of FIG. **8A**), conductive sheet layers (e.g., the conductive sheet layers **4712** and **4722** of FIG. **8A**), and reinforced plates (e.g., the reinforced plates **461** and **462** of FIG. **8A**). According to an embodiment, the electronic device **200** may include a first waterproof space **4811** provided through the first waterproof member **481** disposed between the first support member **261** of the first housing **210** and the support plate **450**, a second waterproof space (e.g., the second waterproof space **4812** of FIG. **7**), or a third waterproof space (e.g., the third waterproof space **4813** of FIG. **7**). According to an embodiment, the electronic device **200** may include a fourth waterproof space **4821** provided through the second waterproof member **482** disposed between the support plate **450** and the second support member **262** of the second housing **220**, the third waterproof member **483**, and a fourth waterproof member (e.g., the fourth waterproof member **484** of FIG. **7**). In this case, the support plate **450** may be formed of a conductive material (e.g., a metal material) to come into ground contact with the flexible substrate **4322** disposed on the bending portion **432** of the display panel **430**.

(106) In an embodiment, when the electronic device **200** includes at least one digitizer (e.g., the digitizers **471** and **472** of FIG. **8A**), the at least one digitizer (e.g., the digitizers **471** and **472** of FIG. **8A**) may be disposed in the waterproof space under the support plate **450**. In an embodiment, the waterproof members **481**, **482**, **483**, and **484** may be arranged between the support members **261** and **262** and the at least one digitizer **471** and **472**. In an embodiment, the at least one digitizer **471** and **472** may be disposed between the polymer layer **440** and the support plate **450**.

(107) According to various example embodiments, an electronic device (e.g., the electronic device **200** of FIG. **3**) may include: a first housing (e.g., the first housing **210** of FIG. **3**) including a first support (e.g., a first support member **261** of FIG. **3**), a second housing (e.g., the second housing **220** of FIG. **3**) including a second support (e.g., the second support member **262** of FIG. **3**) and foldably coupled to the first housing through a hinge (e.g., the hinge device **320** of FIG. **3**), a display panel (e.g., the display panel **430** of FIG. **4**) supported by the first housing and the second housing, a support plate (e.g., the support plate **450** of FIG. **3**) disposed under the display panel, a first reinforced plate (e.g., the first reinforced plate **461** of FIG. **3**) at least partially disposed under the support plate and corresponding to the first support, a second reinforced plate (e.g., the second reinforced plate **462** of FIG. **3**) at least partially disposed under the support plate and corresponding to the second support, a first waterproof structure comprising a waterproof material (e.g., the first waterproof structure WP1 of FIG. **7**) disposed between the first housing and the first reinforced plate to define at least one first waterproof space (e.g., the first waterproof space **4811**, the second waterproof space **4812**, or the third waterproof space **4813** of FIG. **7**), and a second waterproof structure comprising a waterproof material (e.g., the second waterproof structure WP2 of FIG. **7**) disposed between the second housing and the second reinforced plate to define at least one second waterproof space (e.g., the fourth waterproof space **4821** of FIG. **7**).

(108) According to various example embodiments, the first reinforced plate and the second reinforced plate may comprise a metal material.

(109) According to various example embodiments, at least one digitizer disposed under the support plate may be included.

(110) According to various example embodiments, the at least one digitizer may include a first digitizer disposed between the support plate and the first reinforced plate corresponding to the first support, and including a first flexible printed circuit board (FPCB) connection portion, and a second digitizer disposed between the support plate and the second reinforced plate corresponding to the second support, and including a second FPCB connection portion.

(111) According to various example embodiments, the first reinforced plate may include a first through-hole formed through an area overlapping with the at least one first waterproof space when seen from above the flexible display, the first support may include a first support through-hole formed through an area overlapping with the at least one first waterproof space when seen from above the flexible display, and the first FPCB connection portion may be electrically connected to a first substrate disposed in a first space of the first housing through the first through-hole and the first support through-hole.

(112) According to various example embodiments, the second reinforced plate may include a second through-hole formed through an area overlapping the at least one second waterproof space when seen from above the flexible display, the second support may include a second support through-hole formed through an area overlapping the at least one second waterproof space when seen from above the flexible display, and the second FPCB connection portion may be electrically connected to a second substrate disposed in a second space of the second housing through the second through-hole and the second support through-hole.

(113) According to various example embodiments, the first substrate and the second substrate may be electrically connected through at least one wire disposed to cross from the first space to the second space.

(114) According to various example embodiments, a first metal sheet layer disposed between the first digitizer and the first reinforced plate, and a second metal sheet layer disposed between the second digitizer and the second reinforced plate may be further included.

(115) According to various example embodiments, the first waterproof structure may include a first waterproof portion disposed between the first support and the first reinforced plate.

(116) According to various example embodiments, the at least one waterproof space may be disposed near an edge of the first waterproof portion, and the first waterproof portion may include a protrusion extending to allow an edge corresponding to the at least one first waterproof space to protrude over a surrounding edge.

(117) According to various example embodiments, the first waterproof portion may include at least one of tape, an adhesive, waterproof dispensing, silicone, waterproof rubber, or urethane.

(118) According to various example embodiments, the flexible display may include a window layer, a display panel disposed under the window layer, an extension portion extending from the display panel and including a control circuit, a bending portion connected to the extension portion and including a flexible substrate including an FPCB connection portion, and a cover disposed to cover at least a part of the flexible substrate and the extension portion, wherein the bending portion is disposed so that the bending portion is bent over a rear surface of the flexible display and is attached to the second reinforced plate, and the FPCB connection portion is disposed, when seen from above the flexible display, at a position overlapping with the at least one second waterproof space.

(119) According to various example embodiments, the second support may include a second support through-hole formed, when seen from above the flexible display, in an area corresponding to the FPCB connection portion, and the FPCB connection portion may be electrically connected to a substrate disposed in a second space of the second housing through the second support through-hole.

(120) According to various example embodiments, the second reinforced plate may include a through-hole formed at a position corresponding to the flexible substrate, and the flexible substrate may be attached to the support plate through an adhesive at least partially extending through the through-hole.

(121) According to various example embodiments, the adhesive may include conductive tape.

(122) According to various example embodiments, the second waterproof structure may include a first waterproof portion disposed to surround at least a part of the bending portion on the second reinforced plate, a second waterproof portion disposed on the cover at a position spaced apart from

the first waterproof portion, and a third waterproof portion configured to connect the first waterproof portion and the second waterproof portion in a space between the first waterproof portion and the second waterproof portion spaced apart from each other, wherein the at least one second waterproof space is provided through the first waterproof portion, the second waterproof portion, and the third waterproof portion.

(123) According to various example embodiments, the first waterproof portion and the second waterproof portion may include at least one of tape, an adhesive, waterproof dispensing, silicone, waterproof rubber, or urethane, and the third waterproof portion includes cured in place gaskets (CIPGs) including a semisolid or a liquid material having a characteristic of naturally solidifying or solidifying by an external condition.

(124) According to various example embodiments, an electronic device (e.g., the electronic device **200** of FIG. 3) may include: a first housing (e.g., the first housing **210** of FIG. 3) including a first support (e.g., the first support member **261** of FIG. 3), a second housing (e.g., the second housing **220** of FIG. 3) including a second support (e.g., the second support member **262** of FIG. 3) and foldably coupled to the first housing through a hinge (e.g., the hinge device **320** of FIG. 3), a display panel (e.g., the display panel **430** of FIG. 4) supported by the first housing and the second housing, a support plate (e.g., the support plate **450** of FIG. 3) disposed under the display panel, a first digitizer (e.g., the first digitizer **471** of FIG. 8A) disposed under the support plate and corresponding to the first support, and including a first flexible printed circuit board (FPCB) connection portion (e.g., the first FPCB connection portion **4711** of FIG. 6), a second digitizer (e.g., the second digitizer **472** of FIG. 8A) disposed under the support plate and corresponding to the second support, and including a second FPCB connection portion (e.g., the second FPCB connection portion **4721** of FIG. 6), a first reinforced plate (e.g., the first reinforced plate **461** of FIG. 3) disposed under the first digitizer corresponding to the first support, a second reinforced plate (e.g., the second reinforced plate **462** of FIG. 3) disposed under the second digitizer corresponding to the second support, a first waterproof structure comprising a waterproof material (e.g., the first waterproof structure **WP1** of FIG. 7) disposed between the first housing and the first reinforced plate to define at least one first waterproof space (e.g., the first waterproof space **4811**, the second waterproof space **4812**, or the third waterproof space **4813** of FIG. 7), and a second waterproof structure comprising a waterproof material (e.g., the second waterproof structure **WP2** of FIG. 7) disposed between the second housing and the second reinforced plate to define at least one second waterproof space (e.g., the fourth waterproof space **4821** of FIG. 7), wherein the first FPCB connection portion is disposed, when seen from above the flexible display, at a position overlapping with the at least one first waterproof space, and the second FPCB connection portion is disposed, when seen from above the flexible display, at a position overlapping with the at least one second waterproof space.

(125) According to various example embodiments, the first reinforced plate may include a first through-hole formed through an area overlapping with the at least one first waterproof space when seen from above the flexible display, the first support may include a first support through-hole formed through an area overlapping with the at least one first waterproof space when seen from above the flexible display, and the first FPCB connection portion may be electrically connected to a first substrate disposed in a first space of the first housing through the first through-hole and the first support through-hole.

(126) According to various example embodiments, the second reinforced plate may include a second through-hole formed through an area overlapping with the at least one second waterproof space when seen from above the flexible display, the second support may include a second support through-hole formed through an area overlapping with the at least one second waterproof space when seen from above the flexible display, and the second FPCB connection portion may be electrically connected to a second substrate disposed in a second space of the second housing through the second through-hole and the second support through-hole.

(127) While the disclosure has been illustrated and described with reference to various example embodiments, it will be understood that the various example embodiments are intended to be illustrative, not limiting. It will be further understood by those skilled in the art that various changes in form and detail may be made without departing from the true spirit and full scope of the disclosure, including the appended claims and their equivalents. It will also be understood that any of the embodiment(s) described herein may be used in conjunction with any other embodiment(s) described herein.

Claims

1. An electronic device comprising: a first housing comprising a first support member; a second housing comprising a second support member and foldably coupled to the first housing through a hinge device; a display panel supported by the first housing and the second housing; a support plate disposed under the display panel; a first reinforced plate at least partially disposed under the support plate to correspond to the first support member; a second reinforced plate at least partially disposed under the support plate to correspond to the second support member; a first waterproof structure disposed between the first housing and the first reinforced plate to define at least one first waterproof space; a second waterproof structure disposed between the second housing and the second reinforced plate to define at least one second waterproof space; and a bending portion comprising an extension portion extending from the display panel and a flexible substrate connected to the extension portion, the flexible substrate comprising a flexible printed circuit board (FPCB) connection portion, wherein the bending portion is disposed so that the bending portion is bent and is attached to the second reinforced plate, and wherein the FPCB connection portion is disposed at a position overlapping with the at least one second waterproof space when the display panel is viewed from above.
2. The electronic device of claim 1, wherein the first reinforced plate and the second reinforced plate comprise a metal material.
3. The electronic device of claim 1, further comprising at least one digitizer disposed under the support plate.
4. The electronic device of claim 3, wherein the at least one digitizer comprises: a first digitizer disposed between the support plate and the first reinforced plate corresponding to the first support member, and comprising a first flexible printed circuit board (FPCB) connection portion; and a second digitizer disposed between the support plate and the second reinforced plate corresponding to the second support member, and comprising a second FPCB connection portion.
5. The electronic device of claim 4, wherein the first reinforced plate comprises a first through-hole formed through an area overlapping with the at least one first waterproof space when seen from above the display panel, wherein the first support member comprises a first member through-hole formed through an area overlapping with the at least one first waterproof space when seen from above the display panel, and wherein the first FPCB connection portion is electrically connected to a first substrate disposed in a first space of the first housing through the first through-hole and the first member through-hole.
6. The electronic device of claim 5, wherein the second reinforced plate comprises a second through-hole formed through an area overlapping the at least one second waterproof space when seen from above the display panel, wherein the second support member comprises a second member through-hole formed through an area overlapping the at least one second waterproof space when seen from above the display panel, and wherein the second FPCB connection portion is electrically connected to a second substrate disposed in a second space of the second housing through the second through-hole and the second member through-hole.
7. The electronic device of claim 6, wherein the first substrate and the second substrate are electrically connected through at least one wire member disposed to cross from the first space to

the second space.

8. The electronic device of claim 4, further comprising: a first metal sheet layer disposed between the first digitizer and the first reinforced plate; and a second metal sheet layer disposed between the second digitizer and the second reinforced plate.

9. The electronic device of claim 1, wherein the first waterproof structure comprises a first waterproof member disposed between the first support and the first reinforced plate.

10. The electronic device of claim 9, wherein the at least one first waterproof space is disposed near an edge of the first waterproof member, and wherein the first waterproof member comprises a protrusion extending to allow an edge corresponding to the at least one first waterproof space to protrude over a surrounding edge.

11. The electronic device of claim 9, wherein the first waterproof member comprises at least one of tape, an adhesive, waterproof dispensing, silicone, waterproof rubber, or urethane.

12. The electronic device of claim 1, further comprising: a window layer disposed on the display panel; and a cover member disposed to cover at least a part of the flexible substrate and the extension portion, wherein the extension portion comprises a control circuit, the control circuit being disposed between the cover member and the extension.

13. The electronic device of claim 12, wherein the second support member comprises a member through-hole formed, when seen from above the flexible display, in an area corresponding to the FPCB connection portion, and wherein the FPCB connection portion is electrically connected to a substrate disposed in a second space of the second housing through the member through-hole.

14. The electronic device of claim 12, wherein the second reinforced plate comprises a through-hole formed at a position corresponding to the flexible substrate, and wherein the flexible substrate is attached to the support plate through an adhesive member at least partially extending through the through-hole.

15. The electronic device of claim 14, wherein the adhesive member comprises conductive tape.

16. The electronic device of claim 12, wherein the second waterproof structure comprises: a first waterproof member disposed to surround at least a part of the bending portion on the second reinforced plate; a second waterproof member disposed on the cover member at a position spaced apart from the first waterproof member; and a third waterproof member configured to connect the first waterproof member and the second waterproof member in a space between the first waterproof member and the second waterproof member spaced apart from each other, and wherein the at least one second waterproof space is provided through the first waterproof member, the second waterproof member, and the third waterproof member.

17. The electronic device of claim 16, wherein the first waterproof member and the second waterproof member comprise at least one of tape, an adhesive, waterproof dispensing, silicone, waterproof rubber, or urethane, and wherein the third waterproof member comprises cured in place gaskets (CIPGs) comprising a semisolid or a liquid material having a characteristic of naturally solidifying or solidifying by an external condition.

18. An electronic device comprising: a first housing comprising a first support member; a second housing comprising a second support member and foldably coupled to the first housing through a hinge; a display panel supported by the first housing and the second housing; a support plate disposed under the display panel; a first digitizer disposed under the support plate and corresponding to the first support member, and comprising a first flexible printed circuit board (FPCB) connection portion; a second digitizer disposed under the support plate and corresponding to the second support member, and comprising a second FPCB connection portion; a first reinforced plate disposed under the first digitizer corresponding to the first support member; a second reinforced plate disposed under the second digitizer corresponding to the second support member; a first waterproof structure disposed between the first housing and the first reinforced plate to define at least one first waterproof space; and a second waterproof structure disposed between the second housing and the second reinforced plate to define at least one second

waterproof space, wherein the first FPCB connection portion is disposed, when seen from above the flexible display, at a position overlapping with the at least one first waterproof space, and wherein the second FPCB connection portion is disposed, when seen from above the flexible display, at a position overlapping with the at least one second waterproof space.

19. The electronic device of claim 18, wherein the first reinforced plate comprises a first through-hole formed through an area overlapping with the at least one first waterproof space when seen from above the flexible display, wherein the first support member comprises a first member through-hole formed through an area overlapping with the at least one first waterproof space when seen from above the flexible display, and wherein the first FPCB connection portion is electrically connected to a first substrate disposed in a first space of the first housing through the first through-hole and the first member through-hole.

20. The electronic device of claim 18, wherein the second reinforced plate comprises a second through-hole formed through an area overlapping with the at least one second waterproof space when seen from above the flexible display, wherein the second support member comprises a second member through-hole formed through an area overlapping with the at least one second waterproof space when seen from above the flexible display, and wherein the second FPCB connection portion is electrically connected to a second substrate disposed in a second space of the second housing through the second through-hole and the second member through-hole.
