

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12391107
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Müller; Roland et al.

Battery guide pins for a battery receiving space of a materials handling vehicle, and materials handling vehicles incorporating the same

Abstract

A materials handling vehicle including a battery receiving space, and a removable battery assembly, wherein: the battery receiving space includes opposing pairs of battery guide pins, each opposing pair arranged on opposite sides of the battery receiving space, and each opposing pair includes a latching pin and a guiding pin; the removable battery assembly includes a battery locking mechanism; the battery locking mechanism includes spring-loaded locking pins that are spring-biased in extended positions and are movable from the extended positions to respective retracted positions; the latching pin of each opposing pair of battery guide pins includes a recess forming a battery latch that is positioned to receive a leading portion of one of the spring-loaded locking pins in the extended position.

Inventors: Müller; Roland (Feldkirchen, DE), Ma; Martin (Jiangsu, CN), Yang; Jack (Jiangsu, CN), Chen; Andy (Jiangsu, CN), Xia; Bruce (Jiangsu, CN), Sun; Luying (Jiangsu, CN)

Applicant: CROWN EQUIPMENT CORPORATION (New Bremen, OH)

Family ID: 1000008764248

Assignee: CROWN EQUIPMENT CORPORATION (New Bremen, OH)

Appl. No.: 17/814585

Filed: July 25, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230129896 A1	Apr. 27, 2023

Related U.S. Application Data

Publication Classification

Int. Cl.: **B60K1/04** (20190101); **B60L50/64** (20190101); **B60L53/80** (20190101); **H01M50/249** (20210101)

U.S. Cl.:

CPC **B60K1/04** (20130101); **B60L50/64** (20190201); **B60L53/80** (20190201); **H01M50/249** (20210101); H01M2220/20 (20130101)

Field of Classification Search

CPC: B60K (1/04); H01M (50/249); H01M (50/244); H01M (50/256); H01M (50/262); H01M (2220/20); B66F (9/0753); B66F (9/07536); B66F (9/0754)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5626979	12/1996	Mitsui	429/97	H01M 50/244
6004690	12/1998	Van Lerberghe	N/A	N/A
7117966	12/2005	Kohda	180/68.5	B60L 53/80
8347995	12/2012	Fernandez- Mateo	N/A	N/A
8413947	12/2012	Chiang	N/A	N/A
9327586	12/2015	Miyashiro	N/A	B62J 43/20
9827840	12/2016	Wen	N/A	H01M 50/249
11233291	12/2021	Confer	N/A	H01M 50/264
11813956	12/2022	Decuzzi	N/A	B66D 1/60
2005/0191543	12/2004	Harrington	N/A	N/A
2007/0052389	12/2006	Kooij	N/A	N/A
2010/0275564	12/2009	Baetica et al.	N/A	N/A
2018/0130983	12/2017	Tessier	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
101100184	12/2007	CN	N/A
101200269	12/2007	CN	N/A
102358156	12/2011	CN	N/A
102398876	12/2011	CN	N/A
211255144	12/2013	CN	N/A
105523506	12/2015	CN	N/A

205873810	12/2016	CN	N/A
108112339	12/2017	CN	N/A
208819918	12/2018	CN	N/A
211578809	12/2019	CN	N/A
113120809	12/2020	CN	B60K 1/04
213738432	12/2020	CN	N/A
113471613	12/2020	CN	N/A
215662918	12/2021	CN	N/A
19956623	12/2000	DE	B60K 1/04
102007034747	12/2008	DE	N/A
202014004558	12/2013	DE	N/A
2018989	12/2009	EP	N/A
2261167	12/2009	EP	B60L 11/1822
2674389	12/2016	EP	N/A
3309001	12/2017	EP	N/A
3719862	12/2019	EP	N/A
2629787	12/1996	JP	N/A
H11208287	12/1997	JP	N/A
2002003194	12/2001	JP	N/A
2003327394	12/2002	JP	N/A
5478853	12/2013	JP	N/A
201820679	12/2017	JP	N/A
20130130921	12/2012	KR	N/A

OTHER PUBLICATIONS

International Search Report and Written Opinion dated Dec. 30, 2022 issued in International application No. PCT/CN2022/083994 filed Mar. 30, 2022. cited by applicant
Extended European Search Report issued Oct. 9, 2023 in European Application No. 22203046.2 filed Oct. 21, 2022. cited by applicant
International Search Report and Written Opinion issued in International application No. PCT/CN2021/125869 dated Jun. 7, 2022. cited by applicant
Extended European Search Report issued on Aug. 21, 2024 in related European Patent Application No. 24176256.6 filed Oct. 21, 2022. cited by applicant

Primary Examiner: Clemmons; Steve

Attorney, Agent or Firm: Dinsmore & Shohl LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a bypass continuation in part application of International Patent Application Ser. No. PCT/CN2021/125869 filed Oct. 22, 2021, and a bypass continuation application of International Patent Application Ser. No. PCT/CN2021/083994 filed Mar. 30, 2022, the entire disclosures of which are hereby incorporated herein by reference.

BACKGROUND

(1) Although the concepts of the present disclosure are described herein with primary reference to

electric pallet trucks where the drive motor of the pallet truck is integrated with the hub of the pallet truck's single drive wheel, it is contemplated that particular concepts of the present disclosure will enjoy applicability to pallet trucks with other types of motor configurations, or to other types of battery-powered materials handling vehicles including, for example, forklift trucks, tuggers, etc.

SUMMARY

(2) In accordance with the present disclosure, an object of the invention can be seen in providing an improved materials handling vehicle as well as an improved removable battery assembly.

(3) An aspect relates to a materials handling vehicle. The materials handling vehicle may comprise a materials handling mechanism and a drive mechanism. The materials handling vehicle may comprise a battery receiving space and a removable battery assembly.

(4) The materials handling vehicle may be configured to move along an inventory transit surface and engage goods in a warehouse environment. The materials handling mechanism may be configured to engage goods in a warehouse environment and may cooperate with the drive mechanism, under power from the removable battery assembly, to move goods along an inventory transit surface in the warehouse environment. The removable battery assembly may comprise a battery body and a battery locking mechanism. The removable battery assembly and the battery receiving space may cooperate to define a battery insertion and removal axis. The removable battery assembly may be inserted into and removed from the battery receiving space along the battery insertion and removal axis. The battery body may define a longitudinal battery insertion and removal axis along which the removable battery assembly can be inserted into and removed from a battery receiving space of a materials handling vehicle.

(5) The battery locking mechanism may comprise a spring-loaded battery handle and a spring-loaded locking pin. The spring-loaded locking pin may comprise a leading portion that may be configured to engage a battery latch positioned in a battery receiving space of a materials handling vehicle. The battery receiving space may comprise a battery latch positioned to receive a leading portion of the spring-loaded locking pin, with the spring-loaded locking pin in an extended position, and/or the removable battery assembly seated in the battery receiving space. The spring-loaded battery handle may comprise a planar handle cam surface and the spring-loaded locking pin may comprise a planar pin cam surface that may be parallel to the handle cam surface. The spring-loaded battery handle and the spring-loaded locking pin may be configured such that the handle cam surface engages the pin cam surface with movement of the battery handle, relative to the battery body, along the battery insertion and removal axis. The spring-loaded battery handle and the handle cam surface may be constrained to linear movement along the battery insertion and removal axis. The battery body may constrain the spring-loaded battery handle and the handle cam surface to linear movement along the battery insertion and removal axis. The spring-loaded locking pin and the pin cam surface may be constrained to linear movement along a latch engagement and disengagement axis that may be perpendicular to the battery insertion and removal axis. The battery body may constrain the spring-loaded locking pin and the pin cam surface to linear movement along the latch engagement and disengagement axis. The spring-loaded battery handle may be spring-biased in a locked position and may be movable relative to the battery body from the locked position to an unlocked position in a handle lifting direction along the battery insertion and removal axis. The spring-loaded locking pin may be spring-biased in an extended position and may be movable to a retracted position in response to movement of the battery handle from the locked position to an unlocked position, with the handle cam surface engaging the pin cam surface. The spring-loaded locking pin may be spring-biased in an extended position and may be movable relative to the battery body from the extended position to a retracted position along the latch engagement and disengagement axis in response to movement of the battery handle, relative to the battery body, in the handle lifting direction with the handle cam surface engaged with the pin cam surface.

(6) The battery locking mechanism may comprise a pair of spring-loaded locking pins. The battery

receiving space may comprise a corresponding pair of battery latches positioned on opposite sides of the battery receiving space, to receive a leading portion of a corresponding one of the pair of spring-loaded locking pins with the removable battery assembly seated in the battery receiving space.

(7) The spring-loaded battery handle may comprise a grip portion and a pair of spaced apart arm portions extending in the handle lifting direction, along the battery insertion and removal axis, from inside the battery body to opposite ends of the grip portion, outside of the battery body (210). Each arm portion may comprise a planar handle cam surface and each spring-loaded locking pin may comprise a corresponding planar pin cam surface that may be parallel to the handle cam surface.

(8) The planar handle cam surface and corresponding planar pin cam surface of one of the arm portions may be configured as a mirror image of the planar handle cam surface and corresponding planar pin cam surface of the other of the arm portions. The pair of spring-loaded locking pins may comprise locking pin extensions that may extend along the latch engagement and disengagement axis in opposite directions.

(9) The planar handle cam surface and the planar pin cam surface may define equal alternate exterior angles, relative to a cam surface traversal extending in the handle lifting direction, along the battery insertion and removal axis.

(10) The spring-loaded battery handle may comprise a locking pin passage formed in the planar handle cam surface. The spring-loaded locking pin may comprise a locking pin extension extending from the planar pin cam surface through the locking pin passage formed in the planar handle cam surface.

(11) The removable battery assembly may further comprise a handle spring in direct contact with the spring-loaded battery handle to bias the battery handle toward the locked position, a locking pin spring in direct contact with the spring-loaded locking pin to bias the spring-loaded locking pin toward the extended position, or both.

(12) The removable battery assembly may further comprise a handle spring in direct contact with the spring-loaded battery handle to bias the battery handle toward the locked position. The battery body may comprise a handle-facing, spring-receiving cavity for the handle spring. The spring-loaded battery handle may comprise a spring-engaging finger extending from the battery handle in the handle lifting direction, along the battery insertion and removal axis, into the handle-facing spring-receiving cavity, along a longitudinal axis of the spring-receiving cavity.

(13) The removable battery assembly may further comprise a locking pin spring in direct contact with the spring-loaded locking pin to bias the spring-loaded locking pin toward the extended position. The battery body may comprise a pin-facing, spring-receiving cavity. The spring-loaded locking pin may comprise a spring-engaging finger extending from the spring-loaded locking pin perpendicular to the battery insertion and removal axis, into the pin-facing, spring-receiving cavity, along a longitudinal axis of the spring-receiving cavity.

(14) The battery body of the removable battery assembly may comprise a plurality of rechargeable battery cells, a front case, and a rear case. The front and rear cases may cooperate to contain a plurality of rechargeable battery cells therein. The front and rear cases may cooperate to contain portions of the spring-loaded battery handle comprising the handle cam surface and portions of the spring-loaded locking pin comprising the pin cam surface.

(15) Either the front case or the rear case of the battery body may exclusively constrain the spring-loaded battery handle and the handle cam surface to linear movement along the battery insertion and removal axis.

(16) The battery body may contain portions of the spring-loaded battery handle comprising the handle cam surface and portions of the spring-loaded locking pin comprising the pin cam surface. The battery body may comprise one or more handle passages and one or more locking pin passages. An arm portion of the spring-loaded battery handle may pass through the handle passage to a grip portion of the battery handle outside of the battery body. A locking pin extension of the

spring-loaded locking pin passes through the locking pin passage to an exterior of the battery body.

(17) The spring-loaded battery handle and the spring-loaded locking pin may engage at the handle cam surface and the pin cam surface such that movement of the battery handle from the locked position to the unlocked position through the handle passage in the handle lifting direction causes movement of the locking pin extension of the spring-loaded locking pin through the locking pin passage from the extended position to the retracted position along the latch engagement and disengagement axis.

(18) The grip portion of the battery handle may be flush with a top surface of the battery body in the locked position and may extend above the top surface of the battery body in the unlocked position.

(19) The battery body may comprise a handle grip recess formed below the grip portion of the spring-loaded battery handle. The handle grip recess may extend at least approximately 6.5 mm along the battery insertion and removal axis.

(20) The spring-loaded battery handle may comprise handle-side limiting surfaces independent of the planar handle cam surface of the battery handle. The handle-side limiting surfaces may be inclined relative to the handle lifting direction. The battery body may comprise body-side limiting surfaces that may be positioned parallel to corresponding handle-side limiting surfaces of the spring-loaded battery handle, to engage the corresponding handle-side limiting surfaces of the battery handle in the locked position.

(21) The battery body may comprise a body-side limiting surface that may be inclined relative to the handle lifting direction and dedicated for engagement of the handle cam surface in the unlocked position.

(22) The removable battery assembly may comprise a leading face and an electrical socket on the leading face of the removable battery assembly. The battery receiving space may comprise an electrical connector that may complement the electrical socket of the removable battery assembly. The spring-loaded locking pin may be positioned at a point along a longitudinal dimension of the battery body that may result in locking pin engagement with the battery latch simultaneously with engagement of the electrical socket on the leading face of the removable battery assembly with the electrical connector in the battery receiving space, as the removable battery assembly may be inserted into the battery receiving space, with the spring-loaded battery handle in the locked position.

(23) The electrical socket may be recessed on the leading face of the removable battery assembly.

(24) The leading face of the removable battery assembly may rest on a bottom surface of the battery receiving space with the spring-loaded locking pin engaged with the battery latch, and the electrical socket engaged with the electrical connector.

(25) The removable battery assembly may comprise a leading face and an electrical socket on the leading face of the removable battery assembly. The battery receiving space may comprise an electrical connector that may complement the electrical socket of the removable battery assembly. The electrical socket, the electrical connector, the battery body, and the battery receiving space may be configured to define a standoff gap extending along the battery insertion and removal axis between opposing surfaces of the electrical socket and the electrical connector, with the leading face of the removable battery assembly resting on a bottom surface of the battery receiving space.

(26) The electrical connector in the battery receiving space may comprise a connector housing comprising an outer wall that is tapered to a reduced-size footprint as it extends away from the bottom surface of the battery receiving space. The electrical socket on the leading face of the removable battery assembly may comprise a socket housing comprising an inner wall that is tapered to an increased-size footprint as it extends away from the leading face of the removable battery assembly, the inner wall that may be tapered to complement and contact the taper of the outer wall of the connector housing with the leading face of the removable battery assembly resting on the bottom surface of the battery receiving space, and with the standoff gap between opposing

surfaces of the electrical socket and the electrical connector.

(27) The battery receiving space may comprise opposing pairs of battery guide pins, each opposing pair may be arranged on opposite sides of the battery receiving space, and each opposing pair may comprise a latching pin and a guiding pin. The battery body may comprise lateral battery faces, each may comprise a longitudinal guide structure that may be oriented along the battery insertion and removal axis and is sized to accommodate the opposing pairs of guide pins as the removable battery assembly is inserted into and removed from the battery receiving space. The latching pin of each opposing pair of battery guide pins may comprise a recess forming the battery latch that may be positioned to receive a leading portion of one of the spring-loaded locking pins in the extended position, with the removable battery assembly seated in the battery receiving space.

(28) The battery receiving space may comprise a latching pin and a guiding pin arranged on one side of the battery receiving space. The battery body may comprise a lateral battery face comprising a longitudinal guide structure that may be oriented along the battery insertion and removal axis and may be sized to accommodate the latching pin and the guiding pin as the removable battery assembly is inserted into and removed from the battery receiving space. The latching pin may comprise a recess forming the battery latch.

(29) The battery receiving space may comprise latching pins arranged on opposite sides of the battery receiving space. The battery body may comprise lateral battery faces, each comprising a longitudinal guide structure that may be oriented along the battery insertion and removal axis and may be sized to accommodate one of the latching pins as the removable battery assembly is inserted into and removed from the battery receiving space. Each latching pin may comprise a recess forming the battery latch.

(30) A further aspect relates to a removable battery assembly. The removable battery assembly may comprise a battery body and a battery locking mechanism.

(31) The battery body may define a longitudinal battery insertion and removal axis along which the removable battery assembly can be inserted into and removed from a battery receiving space of a materials handling vehicle.

(32) The battery locking mechanism may comprise a spring-loaded battery handle and a spring-loaded locking pin. The spring-loaded locking pin may comprise a leading portion that may be configured to engage a battery latch positioned in a battery receiving space of a materials handling vehicle. The spring-loaded battery handle may comprise a planar handle cam surface and the spring-loaded locking pin may comprise a planar pin cam surface that may be parallel to the handle cam surface. The spring-loaded battery handle and the spring-loaded locking pin may be configured such that the handle cam surface engages the pin cam surface with movement of the battery handle, relative to the battery body, along the battery insertion and removal axis. The battery body may constrain the spring-loaded battery handle and the handle cam surface to linear movement along the battery insertion and removal axis. The battery body may constrain the spring-loaded locking pin and the pin cam surface to linear movement along a latch engagement and disengagement axis that may be perpendicular to the battery insertion and removal axis. The spring-loaded battery handle may be spring-biased in a locked position and is movable relative to the battery body from the locked position to an unlocked position in a handle lifting direction along the battery insertion and removal axis. The spring-loaded locking pin may be spring-biased in an extended position and may be movable relative to the battery body from the extended position to a retracted position along the latch engagement and disengagement axis in response to movement of the battery handle, relative to the battery body, in the handle lifting direction with the handle cam surface engaged with the pin cam surface.

(33) The battery locking mechanism may comprise a pair of spring-loaded locking pins. The battery receiving space may comprise a corresponding pair of battery latches positioned on opposite sides of the battery receiving space, to receive a leading portion of a corresponding one of the pair of spring-loaded locking pins with the removable battery assembly seated in the battery

receiving space.

(34) The spring-loaded battery handle may comprise a grip portion and a pair of spaced apart arm portions extending in the handle lifting direction, along the battery insertion and removal axis, from inside the battery body to opposite ends of the grip portion, outside of the battery body (210). Each arm portion may comprise a planar handle cam surface and each spring-loaded locking pin may comprise a corresponding planar pin cam surface that may be parallel to the handle cam surface.

(35) The planar handle cam surface and corresponding planar pin cam surface of one of the arm portions may be configured as a mirror image of the planar handle cam surface and corresponding planar pin cam surface of the other of the arm portions. The pair of spring-loaded locking pins may comprise locking pin extensions that may extend along the latch engagement and disengagement axis in opposite directions.

(36) The planar handle cam surface and the planar pin cam surface may define equal alternate exterior angles, relative to a cam surface traversal extending in the handle lifting direction, along the battery insertion and removal axis.

(37) The spring-loaded battery handle may comprise a locking pin passage formed in the planar handle cam surface. The spring-loaded locking pin may comprise a locking pin extension extending from the planar pin cam surface through the locking pin passage formed in the planar handle cam surface.

(38) The removable battery assembly may further comprise a handle spring in direct contact with the spring-loaded battery handle to bias the battery handle toward the locked position, a locking pin spring in direct contact with the spring-loaded locking pin to bias the spring-loaded locking pin toward the extended position, or both.

(39) The removable battery assembly may further comprise a handle spring in direct contact with the spring-loaded battery handle to bias the battery handle toward the locked position. The battery body may comprise a handle-facing, spring-receiving cavity for the handle spring. The spring-loaded battery handle may comprise a spring-engaging finger extending from the battery handle in the handle lifting direction, along the battery insertion and removal axis, into the handle-facing spring-receiving cavity, along a longitudinal axis of the spring-receiving cavity.

(40) The removable battery assembly may further comprise a locking pin spring in direct contact with the spring-loaded locking pin to bias the spring-loaded locking pin toward the extended position. The battery body may comprise a pin-facing, spring-receiving cavity. The spring-loaded locking pin may comprise a spring-engaging finger extending from the spring-loaded locking pin perpendicular to the battery insertion and removal axis, into the pin-facing, spring-receiving cavity, along a longitudinal axis of the spring-receiving cavity.

(41) The battery body of the removable battery assembly may comprise a plurality of rechargeable battery cells, a front case, and a rear case. The front and rear cases may cooperate to contain a plurality of rechargeable battery cells therein. The front and rear cases may cooperate to contain portions of the spring-loaded battery handle comprising the handle cam surface and portions of the spring-loaded locking pin comprising the pin cam surface.

(42) Either the front case or the rear case of the battery body may exclusively constrain the spring-loaded battery handle and the handle cam surface to linear movement along the battery insertion and removal axis.

(43) The battery body may contain portions of the spring-loaded battery handle comprising the handle cam surface and portions of the spring-loaded locking pin comprising the pin cam surface. The battery body may comprise one or more handle passages and one or more locking pin passages. An arm portion of the spring-loaded battery handle may pass through the handle passage to a grip portion of the battery handle outside of the battery body. A locking pin extension of the spring-loaded locking pin passes through the locking pin passage to an exterior of the battery body.

(44) The spring-loaded battery handle and the spring-loaded locking pin may engage at the handle cam surface and the pin cam surface such that movement of the battery handle from the locked

position to the unlocked position through the handle passage in the handle lifting direction causes movement of the locking pin extension of the spring-loaded locking pin through the locking pin passage from the extended position to the retracted position along the latch engagement and disengagement axis.

(45) The grip portion of the battery handle may be flush with a top surface of the battery body in the locked position and may extend above the top surface of the battery body in the unlocked position.

(46) The battery body may comprise a handle grip recess formed below the grip portion of the spring-loaded battery handle. The handle grip recess may extend at least approximately 6.5 mm along the battery insertion and removal axis.

(47) The spring-loaded battery handle may comprise handle-side limiting surfaces independent of the planar handle cam surface of the battery handle. The handle-side limiting surfaces may be inclined relative to the handle lifting direction. The battery body may comprise body-side limiting surfaces that may be positioned parallel to corresponding handle-side limiting surfaces of the spring-loaded battery handle, to engage the corresponding handle-side limiting surfaces of the battery handle in the locked position.

(48) The battery body may comprise a body-side limiting surface that may be inclined relative to the handle lifting direction and dedicated for engagement of the handle cam surface in the unlocked position.

(49) The removable battery assembly may comprise a leading face and an electrical socket on the leading face of the removable battery assembly. The battery receiving space may comprise an electrical connector that may complement the electrical socket of the removable battery assembly. The spring-loaded locking pin may be positioned at a point along a longitudinal dimension of the battery body that may result in locking pin engagement with the battery latch simultaneously with engagement of the electrical socket on the leading face of the removable battery assembly with the electrical connector in the battery receiving space, as the removable battery assembly may be inserted into the battery receiving space, with the spring-loaded battery handle in the locked position.

(50) The electrical socket may be recessed on the leading face of the removable battery assembly.

(51) The leading face of the removable battery assembly may rest on a bottom surface of the battery receiving space with the spring-loaded locking pin engaged with the battery latch, and the electrical socket engaged with the electrical connector.

(52) The removable battery assembly may comprise a leading face and an electrical socket on the leading face of the removable battery assembly. The battery receiving space may comprise an electrical connector that may complement the electrical socket of the removable battery assembly. The electrical socket, the electrical connector, the battery body, and the battery receiving space may be configured to define a standoff gap extending along the battery insertion and removal axis between opposing surfaces of the electrical socket and the electrical connector, with the leading face of the removable battery assembly resting on a bottom surface of the battery receiving space.

(53) The electrical connector in the battery receiving space may comprise a connector housing comprising an outer wall that is tapered to a reduced-size footprint as it extends away from the bottom surface of the battery receiving space. The electrical socket on the leading face of the removable battery assembly may comprise a socket housing comprising an inner wall that is tapered to an increased-size footprint as it extends away from the leading face of the removable battery assembly, the inner wall that may be tapered to complement and contact the taper of the outer wall of the connector housing with the leading face of the removable battery assembly resting on the bottom surface of the battery receiving space, and with the standoff gap between opposing surfaces of the electrical socket and the electrical connector.

(54) The battery receiving space may comprise opposing pairs of battery guide pins, each opposing pair may be arranged on opposite sides of the battery receiving space, and each opposing pair may

comprise a latching pin and a guiding pin. The battery body may comprise lateral battery faces, each may comprise a longitudinal guide structure that may be oriented along the battery insertion and removal axis and is sized to accommodate the opposing pairs of guide pins as the removable battery assembly is inserted into and removed from the battery receiving space. The latching pin of each opposing pair of battery guide pins may comprise a recess forming the battery latch that may be positioned to receive a leading portion of one of the spring-loaded locking pins in the extended position, with the removable battery assembly seated in the battery receiving space.

(55) The battery receiving space may comprise a latching pin and a guiding pin arranged on one side of the battery receiving space. The battery body may comprise a lateral battery face comprising a longitudinal guide structure that may be oriented along the battery insertion and removal axis and may be sized to accommodate the latching pin and the guiding pin as the removable battery assembly is inserted into and removed from the battery receiving space. The latching pin may comprise a recess forming the battery latch.

(56) The battery receiving space may comprise latching pins arranged on opposite sides of the battery receiving space. The battery body may comprise lateral battery faces, each comprising a longitudinal guide structure that may be oriented along the battery insertion and removal axis and may be sized to accommodate one of the latching pins as the removable battery assembly is inserted into and removed from the battery receiving space. Each latching pin may comprise a recess forming the battery latch.

(57) In a further aspect, a materials handling vehicle includes a battery receiving space, and a removable battery assembly, wherein: the removable battery assembly includes a battery body and a battery locking mechanism; the battery locking mechanism includes a spring-loaded battery handle and a spring-loaded locking pin; the battery receiving space includes a battery latch positioned to receive a leading portion of the spring-loaded locking pin with the removable battery assembly seated in the battery receiving space; the spring-loaded battery handle includes a planar handle cam surface and the spring-loaded locking pin includes a planar pin cam surface; the spring-loaded battery handle and the spring-loaded locking pin are configured such that the handle cam surface engages the pin cam surface with movement of the battery handle, relative to the battery body; the spring-loaded battery handle is spring-biased in a locked position; and the spring-loaded locking pin is spring-biased in an extended position and is movable to a retracted position in response to movement of the battery handle from the locked position to an unlocked position, with the handle cam surface engaging the pin cam surface.

(58) A further aspect relates to a materials handling vehicle. The materials handling vehicle may comprise a materials handling mechanism and a drive mechanism. The materials handling vehicle may comprise a battery receiving space and a removable battery assembly.

(59) The materials handling vehicle may be configured to move along an inventory transit surface and engage goods in a warehouse environment. The materials handling mechanism may be configured to engage goods in a warehouse environment and may cooperate with the drive mechanism, under power from the removable battery assembly, to move goods along an inventory transit surface in the warehouse environment.

(60) The removable battery assembly and the battery receiving space may cooperate to define a battery insertion and removal axis. The removable battery assembly may be inserted into and removed from the battery receiving space along the battery insertion and removal axis. The battery receiving space may comprise opposing pairs of battery guide pins, each opposing pair may be arranged on opposite sides of the battery receiving space, and each opposing pair may comprise a latching pin and a guiding pin. The battery receiving space may comprise a battery guide pin that may be arranged on each opposite side of the battery receiving space. Each opposing pair of battery guide pins may comprise the battery guide pin. The battery guide pin may be the guiding pin or vice versa. The battery guide pin may be the latching pin or vice versa.

(61) The removable battery assembly may comprise a battery body. The removable battery

assembly may comprise a battery locking mechanism. The battery body may comprise lateral battery faces, each comprising a longitudinal guide structure. The longitudinal guide structure may be sized to accommodate a pair of guide pins as the removable battery assembly is inserted into and removed from a battery receiving space comprising opposing pairs of guide pins. The longitudinal guide structure may be oriented along the battery insertion and removal axis. The longitudinal guide structure may be sized to accommodate the battery guide pins or the battery guide pin that may be arranged on each opposite side of the battery receiving space as the removable battery assembly is inserted into and removed from the battery receiving space.

(62) The battery locking mechanism may comprise spring-loaded locking pins that may be spring-biased in extended positions and may be movable relative to the battery body from the extended positions to respective retracted positions along a latch engagement and disengagement axis. The latching pin of each opposing pair of battery guide pins may comprise a recess forming a battery latch that may be positioned to receive a leading portion of one of the spring-loaded locking pins in the extended position, with the removable battery assembly seated in the battery receiving space.

(63) The latching pin of each opposing pair of battery guide pins may comprise a chamfered engagement face. The spring-loaded locking pins of the battery locking mechanism each may comprise a complementary chamfered engagement face that may be oriented to face the chamfered engagement face of one of the latching pins as the removable battery assembly is inserted into the battery receiving space.

(64) The chamfered engagement face of each latching pin may lead to the recess forming the battery latch of each latching pin.

(65) The latching pin and the guiding pin of each opposing pair of battery guide pins may be positioned along a common guide pin axis, parallel to the battery insertion and removal axis.

(66) The latching pin and the guiding pin of each opposing pair of battery guide pins are separated by a guide pin spacing that may be less than half of a longitudinal dimension of the lateral battery faces, and may be at least about 47.5 mm.

(67) The longitudinal guide structure of the lateral battery faces may be configured as guide channels. The battery guide pins or the battery guide pin that may be arranged on each opposite side of the battery receiving space may extend into the guide channels with the removable battery assembly seated in the battery receiving space.

(68) The longitudinal guide structure of one of the lateral battery faces may be shorter than the longitudinal guide structure of the other lateral battery face, to create free space along one of the lateral battery faces.

(69) The removable battery assembly may further comprise a pair of guide pin stabilizers on each of the lateral battery faces. Each pair of guide pin stabilizers may form a restricted-width guide pin gap along the longitudinal guide structure on each of the lateral battery faces. The restricted-width guide pin gap may be formed for receiving a corresponding one of the battery guide pins. The corresponding one of the battery guide pins may be the battery guide pin that may be arranged on each opposite side of the battery receiving space. The battery guide pins may comprise each battery guide pin that may be arranged on each opposite side of the battery receiving space.

(70) A fastener may extend through each pair of guide pin stabilizers. The fastener may threadably engage the lateral battery face of the battery body.

(71) Each pair of guide pin stabilizers may be formed from a deformable and/or resilient material. Each pair of guide pin stabilizers may be formed as a unitary structure, in particular as a unitary, one piece polyurethane structure. Each pair of guide pin stabilizers may be configured to deform in a lateral direction perpendicular to the battery insertion and removal axis when a battery guide pin enters the restricted-width guide pin gap.

(72) Each pair of guide pin stabilizers may comprise an alignment feature that may be received within a corresponding slot formed in one of the lateral battery faces, to prevent rotation of each pair of guide pin stabilizers relative to the lateral battery faces.

(73) The guiding pin of each opposing pair of battery guide pins or the guide pin stabilizers may reside at a guiding pin parking position along the longitudinal guide structure on each of the lateral battery faces, with the removable battery assembly seated in the battery receiving space. The restricted-width guide pin gap formed by each pair of guide pin stabilizers may at least partially overlap the guiding pin parking position along the longitudinal guide structure on each of the lateral battery faces. The battery guide pins may have respective diameters that are greater than a width of the restricted-width guide pin gap.

(74) The guide pin stabilizers may be configured to yield in a lateral yielding direction and to maintain a degree of lateral resilience, when a guiding pin enters the restricted-width guide pin gap. The guide pin stabilizers may be configured to yield in a lateral yielding direction perpendicular to the battery insertion and removal axis, and to maintain a degree of lateral resilience, when a guiding pin enters the restricted-width guide pin gap. The guide pin stabilizers may be configured to at least partially yield in a lateral yielding direction perpendicular to the battery insertion and removal axis, and to maintain a degree of lateral resilience, when a guide pin enters the restricted-width guide pin gap.

(75) The longitudinal guide structure of the lateral battery faces may be configured as guide channels. Each guide pin stabilizer may comprise a stabilizer shank that may be anchored in the battery body and a stabilizer cap that may extend partially into or partially over one of the guide channels to reduce an effective width of the guide channel. Each pair of guide pin stabilizers may extend partially into or partially over one of the guide channels to reduce an effective width of the guide channel.

(76) Each pair of guide pin stabilizers may comprise a truncated portion. Each pair of guide pin stabilizers may have a Shore A hardness between 50 Shore A and 90 Shore A. Each pair of guide pin stabilizers may have a Shore A hardness between 60 Shore A and 80 Shore A.

(77) The battery locking mechanism may comprise a spring-loaded battery handle. The spring-loaded battery handle may comprise a planar handle cam surface and the spring-loaded locking pin may comprise a planar pin cam surface that may be parallel to the handle cam surface. The spring-loaded battery handle and the spring-loaded locking pin may be configured such that the handle cam surface engages the pin cam surface with movement of the battery handle, relative to the battery body, along the battery insertion and removal axis.

(78) The battery body may constrain the spring-loaded battery handle and the handle cam surface to linear movement along the battery insertion and removal axis. The battery body may constrain the spring-loaded locking pin and the pin cam surface to linear movement along a latch engagement and disengagement axis that may be perpendicular to the battery insertion and removal axis. The spring-loaded battery handle may be spring-biased in a locked position and may be movable relative to the battery body from the locked position to an unlocked position in a handle lifting direction along the battery insertion and removal axis. The spring-loaded locking pin may be spring-biased in the extended position and is movable relative to the battery body from the extended position to a retracted position along the latch engagement and disengagement axis in response to movement of the battery handle, relative to the battery body, in the handle lifting direction with the handle cam surface engaged with the pin cam surface.

(79) The removable battery assembly may comprise a leading face and an electrical socket on the leading face of the removable battery assembly. The battery receiving space may comprise an electrical connector that complements the electrical socket of the removable battery assembly. The spring-loaded locking pins may be positioned at points along a longitudinal dimension of the battery body that results in locking pin engagement with the latching pins simultaneously with engagement of the electrical socket on the leading face of the removable battery assembly with the electrical connector in the battery receiving space, as the removable battery assembly is inserted into the battery receiving space, with the spring-loaded battery handle in the locked position.

(80) The leading face of the removable battery assembly may rest on a bottom surface of the

battery receiving space with the spring-loaded locking pins engaged with the latching pins, and the electrical socket engaged with the electrical connector.

(81) A further aspect relates to a removable battery assembly. The removable battery assembly may comprise a battery body. The removable battery assembly may comprise a battery locking mechanism. The removable battery assembly may be configured according to the previous aspect.

(82) The battery body may comprise lateral battery faces, each comprising a longitudinal guide structure that may be sized to accommodate a pair of guide pins as the removable battery assembly is inserted into and removed from a battery receiving space comprising opposing pairs of guide pins.

(83) The removable battery assembly may further comprise a pair of guide pin stabilizers on each of the lateral battery faces. The pair of guide pin stabilizers may be configured according to the previous aspect. Each pair of guide pin stabilizers may form a restricted-width guide pin gap along the longitudinal guide structure on each of the lateral battery faces and may be configured to yield in a lateral yielding direction and to maintain a degree of lateral resilience, when a guiding pin enters the restricted-width guide pin gap.

(84) The removable battery assembly and the battery receiving space may cooperate to define a battery insertion and removal axis. The removable battery assembly may be inserted into and removed from the battery receiving space along the battery insertion and removal axis.

(85) The longitudinal guide structure may be oriented along the battery insertion and removal axis. The longitudinal guide structure may be sized to accommodate the opposing pairs of guide pins as the removable battery assembly is inserted into and removed from the battery receiving space.

(86) The battery locking mechanism may comprise spring-loaded locking pins that may be spring-biased in extended positions and may be movable relative to the battery body from the extended positions to respective retracted positions along a latch engagement and disengagement axis. A latching pin of each opposing pair of guide pins may comprise a recess forming a battery latch that may be positioned to receive a leading portion of one of the spring-loaded locking pins in the extended position, with the removable battery assembly seated in the battery receiving space.

(87) The latching pin of each opposing pair of guide pins may comprise a chamfered engagement face. The spring-loaded locking pins of the battery locking mechanism each may comprise a complementary chamfered engagement face that may be oriented to face the chamfered engagement face of one of the latching pins as the removable battery assembly is inserted into the battery receiving space.

(88) The chamfered engagement face of each latching pin may lead to the recess forming the battery latch of each latching pin.

(89) The latching pin and the guiding pin of each opposing pair of guide pins may be positioned along a common guide pin axis, parallel to the battery insertion and removal axis.

(90) The latching pin and the guiding pin of each opposing pair of guide pins are separated by a guide pin spacing that may be less than half of a longitudinal dimension of the lateral battery faces, and may be at least about 47.5 mm.

(91) The longitudinal guide structure of the lateral battery faces may be configured as guide channels. The opposing pairs of guide pins may extend into the guide channels with the removable battery assembly seated in the battery receiving space.

(92) The longitudinal guide structure of one of the lateral battery faces may be shorter than the longitudinal guide structure of the other lateral battery face, to create free space along one of the lateral battery faces.

(93) The removable battery assembly may further comprise a pair of guide pin stabilizers on each of the lateral battery faces. Each pair of guide pin stabilizers may form a restricted-width guide pin gap along the longitudinal guide structure on each of the lateral battery faces.

(94) The guiding pin of each opposing pair of guide pins may reside at a guiding pin parking position along the longitudinal guide structure on each of the lateral battery faces, with the

removable battery assembly seated in the battery receiving space. The restricted-width guide pin gap formed by each pair of guide pin stabilizers may at least partially overlap the guiding pin parking position along the longitudinal guide structure on each of the lateral battery faces.

(95) The guide pin stabilizers may be configured to yield in a lateral yielding direction and to maintain a degree of lateral resilience, when a guiding pin enters the restricted-width guide pin gap. The guide pin stabilizers may be configured to yield in a lateral yielding direction perpendicular to the battery insertion and removal axis, and to maintain a degree of lateral resilience, when a guiding pin enters the restricted-width guide pin gap.

(96) The longitudinal guide structure of the lateral battery faces may be configured as guide channels. The opposing pairs of guide pins may extend into the guide channels with the removable battery assembly seated in the battery receiving space.

(97) The longitudinal guide structure of one of the lateral battery faces may be shorter than the longitudinal guide structure of the other lateral battery face, to create free space along one of the lateral battery faces.

(98) The removable battery assembly may further comprise a pair of guide pin stabilizers on each of the lateral battery faces. Each pair of guide pin stabilizers may form a restricted-width guide pin gap along the longitudinal guide structure on each of the lateral battery faces.

(99) The guiding pin of each opposing pair of guide pins may reside at a guiding pin parking position along the longitudinal guide structure on each of the lateral battery faces, with the removable battery assembly seated in the battery receiving space. The restricted-width guide pin gap formed by each pair of guide pin stabilizers may at least partially overlap the guiding pin parking position along the longitudinal guide structure on each of the lateral battery faces.

(100) The guide pin stabilizers may be configured to yield in a lateral yielding direction and to maintain a degree of lateral resilience, when a guiding pin enters the restricted-width guide pin gap. The guide pin stabilizers may be configured to yield in a lateral yielding direction perpendicular to the battery insertion and removal axis, and to maintain a degree of lateral resilience, when a guiding pin enters the restricted-width guide pin gap.

(101) The longitudinal guide structure of the lateral battery faces may be configured as guide channels. Each guide pin stabilizer may comprise a stabilizer shank that may be anchored in the battery body and a stabilizer cap that may extend partially into or partially over one of the guide channels to reduce an effective width of the guide channel.

(102) The battery locking mechanism may comprise a spring-loaded battery handle. The spring-loaded battery handle may comprise a planar handle cam surface and the spring-loaded locking pin may comprise a planar pin cam surface that may be parallel to the handle cam surface. The spring-loaded battery handle and the spring-loaded locking pin may be configured such that the handle cam surface engages the pin cam surface with movement of the battery handle, relative to the battery body, along the battery insertion and removal axis.

(103) The battery body may constrain the spring-loaded battery handle and the handle cam surface to linear movement along the battery insertion and removal axis. The battery body may constrain the spring-loaded locking pin and the pin cam surface to linear movement along a latch engagement and disengagement axis that may be perpendicular to the battery insertion and removal axis. The spring-loaded battery handle may be spring-biased in a locked position and may be movable relative to the battery body from the locked position to an unlocked position in a handle lifting direction along the battery insertion and removal axis. The spring-loaded locking pin may be spring-biased in the extended position and is movable relative to the battery body from the extended position to a retracted position along the latch engagement and disengagement axis in response to movement of the battery handle, relative to the battery body, in the handle lifting direction with the handle cam surface engaged with the pin cam surface.

(104) The removable battery assembly may comprise a leading face and an electrical socket on the leading face of the removable battery assembly. The battery receiving space may comprise an

electrical connector that complements the electrical socket of the removable battery assembly. The spring-loaded locking pins may be positioned at points along a longitudinal dimension of the battery body that results in locking pin engagement with the latching pins simultaneously with engagement of the electrical socket on the leading face of the removable battery assembly with the electrical connector in the battery receiving space, as the removable battery assembly is inserted into the battery receiving space, with the spring-loaded battery handle in the locked position.

(105) The leading face of the removable battery assembly may rest on a bottom surface of the battery receiving space with the spring-loaded locking pins engaged with the latching pins, and the electrical socket engaged with the electrical connector.

(106) In a further aspect, a materials handling vehicle includes a battery receiving space, and a removable battery assembly, wherein: the battery receiving space includes opposing pairs of battery guide pins, each opposing pair arranged on opposite sides of the battery receiving space, and each opposing pair includes a latching pin and a guiding pin; the removable battery assembly includes a battery locking mechanism; the battery locking mechanism includes spring-loaded locking pins that are spring-biased in extended positions and are movable from the extended positions to respective retracted positions; the latching pin of each opposing pair of battery guide pins includes a recess forming a battery latch that is positioned to receive a leading portion of one of the spring-loaded locking pins in the extended position.

(107) A further aspect relates to a materials handling vehicle. The materials handling vehicle may comprise a materials handling mechanism and a drive mechanism. The materials handling vehicle may comprise a battery receiving space and a removable battery assembly.

(108) The materials handling vehicle may be configured to move along an inventory transit surface and engage goods in a warehouse environment. The materials handling mechanism may be configured to engage goods in a warehouse environment and may cooperate with the drive mechanism, under power from the removable battery assembly, to move goods along an inventory transit surface in the warehouse environment.

(109) The removable battery assembly and the battery receiving space may cooperate to define a battery insertion and removal axis. The removable battery assembly may be inserted into and removed from the battery receiving space along the battery insertion and removal axis. The removable battery assembly may comprise lateral battery faces, each comprising a longitudinal guide structure that may be oriented along the battery insertion and removal axis. The removable battery assembly may comprise a battery body and a battery locking mechanism. The battery body may define a longitudinal battery insertion and removal axis along which the removable battery assembly can be inserted into and removed from a battery receiving space of a materials handling vehicle. The battery body may comprise lateral battery faces. Each lateral battery face may comprise a longitudinal guide structure that may be oriented along the battery insertion and removal axis.

(110) The battery receiving space may comprise opposing guide blocks, each arranged on opposite sides of the battery receiving space, and each comprising a securement portion and a replaceable portion. The replaceable portion of each guide block may comprise a friction-inducing surface and a guiding surface. Each friction-inducing surface may extend along the battery insertion and removal axis, parallel to and facing an opposing one of the lateral battery faces, with the removable battery assembly seated in the battery receiving space. Each guiding surface may extend along the battery insertion and removal axis, perpendicular to the lateral battery faces and/or facing an opposing surface of the longitudinal guide structure, with the removable battery assembly seated in the battery receiving space.

(111) The friction-inducing and guiding surfaces of each replaceable portion of each guide block may face an opposing surface of the removable battery assembly or the longitudinal guide structure without interference from the securement portions of each guide block, with the removable battery assembly seated in the battery receiving space.

(112) The friction-inducing surface of each replaceable portion of each guide block may extend discontinuously in a direction along the battery insertion and removal axis and may face the opposing lateral battery face in a perpendicular direction, with the removable battery assembly seated in the battery receiving space. The guiding surface of each replaceable portion of each guide block may extend continuously in the direction and may face the opposing surface of the longitudinal guide structure in a perpendicular direction, with the removable battery assembly seated in the battery receiving space.

(113) The longitudinal guide structure of the lateral battery face may be configured as a stepped guide channel comprising a one-sided channel portion that may transition to a two-sided channel portion at a channel shoulder. The replaceable portion of each guide block may comprise a chamfered leading portion, the chamfered leading portion may face the channel shoulder in the longitudinal guide structure. The one and two-sided channel portions of the longitudinal guide structure may extend along the battery insertion and removal axis.

(114) The replaceable portion of each guide block may comprise a lower surface hardness and higher surface friction, relative to the securement portion.

(115) The friction-inducing surfaces of each replaceable portion of each guide block may be raised, relative to the securement portions and remaining portions of the replaceable portions of each guide block, in the direction of the opposing the lateral battery faces.

(116) The friction-inducing surfaces of each replaceable portion of each guide block may comprise a series of friction-inducing ridges oriented across the battery insertion and removal axis.

(117) The securement portion of each guide block may be secured to the materials handling vehicle. The replaceable portion of each guide block may be seated within the securement portion, and may be removable from the securement portion without destruction of the securement portion.

(118) The securement portion of each guide block may be configured as a bracket from which the replaceable portion of each guide block may extend to define the friction-inducing and guiding surfaces.

(119) The longitudinal guide structure of the lateral battery face may be configured as a stepped guide channel comprising a one-sided channel portion that may transition to a two-sided channel portion at a channel shoulder. The replaceable portion of each guide block may comprise a chamfered leading portion, the chamfered leading portion facing the channel shoulder in the longitudinal guide structure.

(120) Each longitudinal guide structure of the lateral battery faces may comprise a one-sided channel portion that may comprise the opposing surface facing the guiding surface of the guide block, with the removable battery assembly seated in the battery receiving space.

(121) The one-sided and two-sided channel portions of the longitudinal guide structure may extend in a direction along the battery insertion and removal axis. Each friction-inducing surface may face an opposing one of the lateral battery faces in a perpendicular direction, with the removable battery assembly seated in the battery receiving space. Each guiding surface may face an opposing surface of the longitudinal guide structure in a perpendicular direction, with the removable battery assembly seated in the battery receiving space. The replaceable portion of each guide block may comprise a chamfered leading portion that may face a channel shoulder of the longitudinal guide structure, in the direction.

(122) The removable battery assembly or the locking mechanism may further comprise a pair of spring-loaded locking pins, each disposed in one of the two-sided channel portions of the longitudinal guide structure.

(123) The battery receiving space may comprise a pair of battery latches positioned on opposite sides of the battery receiving space, to receive a leading portion of a corresponding one of the pair of spring-loaded locking pins with the removable battery assembly seated in the battery receiving space.

(124) Each opposing guide block may be positioned along the battery insertion and removal axis to

engage the channel shoulder of one of the longitudinal guide structures with the removable battery assembly seated in the battery receiving space and the leading portions of the pair of spring-loaded locking pins received within the pair of battery latches.

(125) A further aspect relates to a removable battery assembly. The removable battery assembly may comprise a battery body. The removable battery assembly may comprise a battery locking mechanism.

(126) The battery body may define a longitudinal battery insertion and removal axis along which the removable battery assembly can be inserted into and removed from a battery receiving space of a materials handling vehicle. The battery body may comprise lateral battery faces. Each lateral battery face may comprise a longitudinal guide structure that may be oriented along the battery insertion and removal axis. The longitudinal guide structures of the lateral battery faces may be configured as a stepped guide channel comprising a one-sided channel portion that may transition to a two-sided channel portion at a channel shoulder. The one and two-sided channel portions of the longitudinal guide structure may extend along the battery insertion and removal axis. The locking mechanism may comprise a pair of spring-loaded locking pins, each disposed in one of the two-sided channel portions of the longitudinal guide structure.

(127) The battery receiving space may comprise opposing guide blocks, each arranged on opposite sides of the battery receiving space, and each comprising a securement portion and a replaceable portion. The replaceable portion of each guide block may comprise a friction-inducing surface and a guiding surface. Each friction-inducing surface may extend along the battery insertion and removal axis, parallel to and facing an opposing one of the lateral battery faces, with the removable battery assembly seated in the battery receiving space. Each guiding surface may extend along the battery insertion and removal axis, perpendicular to the lateral battery faces and/or facing an opposing surface of the longitudinal guide structure, with the removable battery assembly seated in the battery receiving space.

(128) The friction-inducing and guiding surfaces of each replaceable portion of each guide block may face an opposing surface of the removable battery assembly or the longitudinal guide structure without interference from the securement portions of each guide block, with the removable battery assembly seated in the battery receiving space.

(129) The friction-inducing surface of each replaceable portion of each guide block may extend discontinuously in a direction along the battery insertion and removal axis and may face the opposing lateral battery face in a perpendicular direction, with the removable battery assembly seated in the battery receiving space. The guiding surface of each replaceable portion of each guide block may extend continuously in the direction and may face the opposing surface of the longitudinal guide structure in a perpendicular direction, with the removable battery assembly seated in the battery receiving space.

(130) The replaceable portion of each guide block may comprise a chamfered leading portion, the chamfered leading portion may face the channel shoulder in the longitudinal guide structure. The one and two-sided channel portions of the longitudinal guide structure may extend along the battery insertion and removal axis.

(131) The replaceable portion of each guide block may comprise a lower surface hardness and higher surface friction, relative to the securement portion.

(132) The friction-inducing surfaces of each replaceable portion of each guide block may be raised, relative to the securement portions and remaining portions of the replaceable portions of each guide block, in the direction of the opposing the lateral battery faces.

(133) The friction-inducing surfaces of each replaceable portion of each guide block may comprise a series of friction-inducing ridges oriented across the battery insertion and removal axis.

(134) The securement portion of each guide block may be secured to the materials handling vehicle. The replaceable portion of each guide block may be seated within the securement portion, and may be removable from the securement portion without destruction of the securement portion.

(135) The securement portion of each guide block may be configured as a bracket from which the replaceable portion of each guide block may extend to define the friction-inducing and guiding surfaces.

(136) Each longitudinal guide structure of the lateral battery faces may comprise a one-sided channel portion that may comprise the opposing surface facing the guiding surface of the guide block, with the removable battery assembly seated in the battery receiving space.

(137) The longitudinal guide structure of the lateral battery face may be configured as a stepped guide channel comprising a one-sided channel portion that may transition to a two-sided channel portion at a channel shoulder. The one-sided channel portion of the longitudinal guide structure may comprise the opposing surface facing the guiding surface of the guide block, with the removable battery assembly seated in the battery receiving space.

(138) The one-sided and two-sided channel portions of the longitudinal guide structure may extend in a direction along the battery insertion and removal axis. Each friction-inducing surface may face an opposing one of the lateral battery faces in a perpendicular direction, with the removable battery assembly seated in the battery receiving space. Each guiding surface may face an opposing surface of the longitudinal guide structure in a perpendicular direction, with the removable battery assembly seated in the battery receiving space. The replaceable portion of each guide block may comprise a chamfered leading portion that may face a channel shoulder of the longitudinal guide structure, in the direction.

(139) The removable battery assembly or the locking mechanism may further comprise a pair of spring-loaded locking pins, each disposed in one of the two-sided channel portions of the longitudinal guide structure.

(140) The battery receiving space may comprise a pair of battery latches positioned on opposite sides of the battery receiving space, to receive a leading portion of a corresponding one of the pair of spring-loaded locking pins with the removable battery assembly seated in the battery receiving space.

(141) Each opposing guide block may be positioned along the battery insertion and removal axis to engage the channel shoulder of one of the longitudinal guide structures with the removable battery assembly seated in the battery receiving space and the leading portions of the pair of spring-loaded locking pins received within the pair of battery latches.

(142) In a further aspect, a materials handling vehicle includes a battery receiving space, and a removable battery assembly, wherein: the removable battery assembly includes lateral battery faces, each including a longitudinal guide structure; the battery receiving space includes opposing guide blocks, each arranged on opposite sides of the battery receiving space, and each including a securement portion and a replaceable portion; the replaceable portion of each guide block including a friction-inducing surface and a guiding surface; each friction-inducing surface facing an opposing one of the lateral battery faces; and each guiding surface facing an opposing surface of the longitudinal guide structure, with the removable battery assembly seated in the battery receiving space.

(143) A further aspect relates to a materials handling vehicle. The materials handling vehicle may comprise a materials handling mechanism and a drive mechanism. The materials handling vehicle may comprise a battery receiving space and a removable battery assembly.

(144) The materials handling vehicle may be configured to move along an inventory transit surface and engage goods in a warehouse environment. The materials handling mechanism may be configured to engage goods in a warehouse environment and cooperates with the drive mechanism, under power from the removable battery assembly, to move goods along an inventory transit surface in the warehouse environment.

(145) The removable battery assembly may comprise a battery body. The battery body may define a longitudinal battery insertion and removal axis along which the battery assembly can be inserted into and removed from a battery receiving space of a materials handling vehicle. The removable

battery assembly and the battery receiving space may cooperate to define a battery insertion and removal axis. The removable battery assembly may be inserted into and removed from the battery receiving space along the battery insertion and removal axis. The removable battery assembly may comprise lateral battery faces, each comprising a longitudinal guide structure that may be oriented along the battery insertion and removal axis.

(146) The battery receiving space may comprise opposing retention blocks, each arranged on opposite sides of the battery receiving space, and each comprising a retention lever comprising a fixed end and a distal end. The longitudinal guide structure of each lateral battery face may comprise a lever-receiving detent that is configured to receive the distal end of one of the retention levers, with the removable battery assembly seated in the battery receiving space.

(147) Each retention lever may be configured to lie in a state of flexion when received in the lever-receiving detent of the longitudinal guide structure.

(148) Each retention block may comprise a planar guiding surface facing an opposing surface of the longitudinal guide structure. The planar guiding surface of the retention block may comprise a retention lever recess. Each retention lever may be configured for increased flexion as it moves progressively towards the retention lever recess.

(149) Each retention block may comprise a planar guiding surface facing an opposing surface of the longitudinal guide structure. The planar guiding surface of the retention block may comprise a retention lever recess. The fixed end of each retention lever may be positioned in the retention lever recess to avoid contact with the opposing surface of the longitudinal guide structure.

(150) The distal end of each retention lever may comprise a terminal lobe. The lever-receiving detent and the terminal lobe may define mating rounded profiles.

(151) Each retention block may comprise a metal backing plate and a plastic retention lever plate.

(152) The removable battery assembly may comprise a leading face and an electrical socket on the leading face of the removable battery assembly. The battery receiving space may comprise an electrical connector that complements the electrical socket of the removable battery assembly. Each retention lever may be positioned such that each of the lever-receiving detents receives a distal end of one of the retention levers simultaneously with engagement of the electrical socket on the leading face of the removable battery assembly with the electrical connector in the battery receiving space, as the removable battery assembly is inserted into the battery receiving space.

(153) Each longitudinal guide structure of the lateral battery faces may comprise a one-sided channel portion that comprises the opposing surface facing the guiding surface of the retention block, with the removable battery assembly seated in the battery receiving space. The one-sided channel portion of the longitudinal guide structure may comprise a lever-receiving detent that is configured to receive the distal end of a retention lever, with the removable battery assembly seated in the battery receiving space.

(154) The one-sided channel portion may terminate in a channel shoulder of the longitudinal guide structure. Each guide block may comprise a chamfered leading portion that faces the channel shoulder of the longitudinal guide structure, with the removable battery assembly seated in the battery receiving space.

(155) A further aspect relates to a removable battery assembly. The removable battery assembly may comprise a battery body.

(156) The battery body may define a longitudinal battery insertion and removal axis along which the battery assembly can be inserted into and removed from a battery receiving space of a materials handling vehicle. The removable battery assembly may comprise lateral battery faces, each comprising a longitudinal guide structure that may be oriented along the battery insertion and removal axis. The longitudinal guide structure of each lateral battery face may comprise a one-sided channel portion that may terminate in a channel shoulder of the longitudinal guide structure. The one-sided channel portion of the longitudinal guide structure may comprise a lever-receiving detent that may be configured to receive the distal end of retention levers, with the removable

battery assembly seated in the battery receiving space.

(157) The battery receiving space may comprise opposing retention blocks, each arranged on opposite sides of the battery receiving space, and each comprising a retention lever comprising a fixed end and a distal end. The longitudinal guide structure of each lateral battery face may comprise a lever-receiving detent that is configured to receive the distal end of one of the retention levers, with the removable battery assembly seated in the battery receiving space.

(158) Each retention lever may be configured to lie in a state of flexion when received in the lever-receiving detent of the longitudinal guide structure.

(159) Each retention block may comprise a planar guiding surface facing an opposing surface of the longitudinal guide structure. The planar guiding surface of the retention block may comprise a retention lever recess. Each retention lever may be configured for increased flexion as it moves progressively towards the retention lever recess.

(160) Each retention block may comprise a planar guiding surface facing an opposing surface of the longitudinal guide structure. The planar guiding surface of the retention block may comprise a retention lever recess. The fixed end of each retention lever may be positioned in the retention lever recess to avoid contact with the opposing surface of the longitudinal guide structure.

(161) The distal end of each retention lever may comprise a terminal lobe. The lever-receiving detent and the terminal lobe may define mating rounded profiles.

(162) Each retention block may comprise a metal backing plate and a plastic retention lever plate.

(163) The removable battery assembly may comprise a leading face and an electrical socket on the leading face of the removable battery assembly. The battery receiving space may comprise an electrical connector that complements the electrical socket of the removable battery assembly. Each retention lever may be positioned such that each of the lever-receiving detents receives a distal end of one of the retention levers simultaneously with engagement of the electrical socket on the leading face of the removable battery assembly with the electrical connector in the battery receiving space, as the removable battery assembly is inserted into the battery receiving space.

(164) Each longitudinal guide structure of the lateral battery faces may comprise a one-sided channel portion that comprises the opposing surface facing the guiding surface of the retention block, with the removable battery assembly seated in the battery receiving space. The one-sided channel portion of the longitudinal guide structure may comprise a lever-receiving detent that is configured to receive the distal end of a retention lever, with the removable battery assembly seated in the battery receiving space.

(165) The one-sided channel portion may terminate in a channel shoulder of the longitudinal guide structure. Each guide block may comprise a chamfered leading portion that faces the channel shoulder of the longitudinal guide structure, with the removable battery assembly seated in the battery receiving space.

(166) In a further aspect, a materials handling vehicle includes a battery receiving space, and a removable battery assembly, wherein: the removable battery assembly includes lateral battery faces, each including a longitudinal guide structure; the battery receiving space includes opposing retention blocks, each arranged on opposite sides of the battery receiving space, and each comprising a retention lever including a fixed end and a distal end; and the longitudinal guide structure of each lateral battery face includes a lever-receiving detent that is configured to receive the distal end of one of the retention levers.

(167) A further aspect relates to a materials handling vehicle. The materials handling vehicle may comprise a materials handling mechanism, a drive mechanism, a battery receiving space, and a removable battery assembly.

(168) The materials handling mechanism may be configured to engage goods in a warehouse environment and may cooperate with the drive mechanism, under power from the removable battery assembly, to move goods along an inventory transit surface in the warehouse environment.

(169) The removable battery assembly and the battery receiving space may cooperate to define a

battery insertion and removal axis along which the removable battery assembly may be inserted into and removed from the battery receiving space. The removable battery assembly may comprise a battery body, a leading face, an electrical socket on the leading face of the removable battery assembly, and a battery locking mechanism. The battery receiving space may comprise an electrical connector that may complement the electrical socket of the removable battery assembly, and a battery latch that may engage the battery locking mechanism simultaneously with engagement of the electrical socket on the leading face of the removable battery assembly with the electrical connector in the battery receiving space, as the removable battery assembly is inserted into the battery receiving space. The leading face of the removable battery assembly may rest on a bottom surface of the battery receiving space with the battery locking mechanism engaged with the battery latch, and/or with the electrical socket engaged with the electrical connector. The electrical socket, the electrical connector, the battery body, and the battery receiving space may be configured to define a standoff gap extending along the battery insertion and removal axis between opposing surfaces of the electrical socket and the electrical connector, with the leading face of the removable battery assembly resting on the bottom surface of the battery receiving space.

(170) The electrical connector in the battery receiving space may comprise a connector housing comprising an outer wall that may be tapered to a reduced-size footprint as it extends away from the bottom surface of the battery receiving space. The electrical socket on the leading face of the removable battery assembly may comprise a socket housing comprising an inner wall that may be tapered to an increased-size footprint as it extends away from the leading face of the removable battery assembly. The inner wall that may be tapered to complement and contact the taper of the outer wall of the connector housing with the leading face of the removable battery assembly resting on the bottom surface of the battery receiving space, and with the standoff gap between opposing surfaces of the electrical socket and the electrical connector.

(171) The opposing surfaces of the electrical socket and the electrical connector may be horizontally oriented opposing surfaces that may be perpendicular to the battery insertion and removal axis and may be spaced apart by the standoff gap.

(172) The standoff gap, or a gap larger than the standoff gap, may be maintained between substantially all horizontally oriented opposing surfaces of the electrical socket and the electrical connector.

(173) The standoff gap **(414)** may be at least about 0.2 mm. The standoff gap may be between about 0.2 mm and about 1.7 mm.

(174) The battery-side electrical socket may be recessed in the leading face of the battery assembly with a socket housing. The vehicle-side electrical connector may project upwardly from the bottom surface of the battery receiving space with a connector housing. The battery-side electrical socket may comprise a rim portion that may be enclosed by the socket housing and may extend generally parallel to the leading face of the battery assembly. The vehicle-side electrical connector may comprise a shoulder portion that may be enclosed by the connector housing and may extend generally parallel to the bottom surface of the battery receiving space.

(175) The rim portion of the battery-side electrical socket may extend parallel to the shoulder portion of the vehicle-side electrical connector, with the removable battery assembly seated in the battery receiving space, and is spaced from the shoulder portion by the standoff gap.

(176) The battery-side electrical socket may be recessed in the leading face of the battery assembly with a socket housing. The vehicle-side electrical connector may project upwardly from the bottom surface of the battery receiving space with a connector housing.

(177) The connector housing may comprise an outer wall that may be tapered to a reduced-size footprint as it extends away from the bottom surface of the battery receiving space. The socket housing may comprise an inner wall that may be tapered to an increased-size footprint as it extends away from the leading face of the removable battery assembly.

(178) The battery-side electrical socket may comprise a rim portion that may be enclosed by the

socket housing and may extend generally parallel to the leading face of the battery assembly. The vehicle-side electrical connector may comprise a shoulder portion that may be enclosed by the connector housing and may extend generally parallel to the bottom surface of the battery receiving space.

(179) The rim portion of the battery-side electrical socket may extend parallel to the shoulder portion of the vehicle-side electrical connector, with the removable battery assembly seated in the battery receiving space, and may be spaced from the shoulder portion by the standoff gap.

(180) The electrical connector in the battery receiving space may comprise a connector housing comprising an outer wall that may be tapered to a reduced-size footprint as it extends away from the bottom surface of the battery receiving space.

(181) The electrical socket on the leading face of the removable battery assembly may comprise a socket housing comprising an inner wall that may be tapered to an increased-size footprint as it extends away from the leading face of the removable battery assembly.

(182) The electrical connector in the battery receiving space may comprise a connector housing comprising an outer wall that may be tapered to a reduced-size footprint as it extends away from the bottom surface of the battery receiving space. The electrical socket on the leading face of the removable battery assembly may comprise a socket housing comprising an inner wall that may be tapered to an increased-size footprint as it extends away from the leading face of the removable battery assembly; and the inner wall of the electrical socket may be tapered to complement and contact the taper of the outer wall of the connector housing with the leading face of the removable battery assembly resting on the bottom surface of the battery receiving space.

(183) The electrical socket may comprise a set of electrically conductive pin receptacles and the electrical connector may comprise a set of complementary electrically conductive connector pins. An outermost portion of the standoff gap may surround the set of electrically conductive pin receptacles and the set of complementary electrically conductive connector pins, with the leading face of the removable battery assembly resting on the bottom surface of the battery receiving space and a set of electrically conductive pin receptacles engaging the set of complementary electrically conductive connector pins.

(184) The socket housing of the electrical socket and the connector housing of the electrical connector may cooperate to enclose the set of electrically conductive pin receptacles and the set of complementary electrically conductive connector pins to form a barrier between the outermost portion of the standoff gap and the engaged sets of pin receptacles and connector pins, with the leading face of the removable battery assembly resting on the bottom surface of the battery receiving space.

(185) The electrical connector in the battery receiving space comprises a connector housing comprising an outer wall that may be tapered to a reduced-size footprint as it extends away from the bottom surface of the battery receiving space. The electrical socket on the leading face of the removable battery assembly may comprise a socket housing comprising an inner wall that may be tapered to an increased-size footprint as it extends away from the leading face of the removable battery assembly. The inner wall of the electrical socket may be tapered to complement and contact the taper of the outer wall of the connector housing with the leading face of the removable battery assembly resting on the bottom surface of the battery receiving space. The inner wall of the electrical socket may contact the outer wall of the connector housing at a tapered contact boundary surrounding the outermost portion of the standoff gap.

(186) The set of electrically conductive pin receptacles and the set of complementary electrically conductive connector pins form an eight pin configuration comprising: positive and negative battery terminals B+/B-; a CANH signal pin for a CAN Bus High Signal; a CANL signal pin for a CAN Bus Low Signal; a SIG1 signal pin for a battery discharge start signal; a SIG2 signal pin for a battery charge start signal; a SIG3 signal pin for a discharge select signal; and/or a SIG4 signal pin for an Auxiliary Signal.

(187) In a further aspect, a materials handling vehicle includes a battery receiving space, and a removable battery assembly, wherein: the removable battery assembly includes a battery body, a leading face, and an electrical socket on the leading face of the removable battery assembly; the battery receiving space includes an electrical connector; the leading face of the removable battery assembly rests on a bottom surface of the battery receiving space with the electrical socket engaged with the electrical connector; and the electrical socket, the electrical connector, the battery body, and the battery receiving space are configured to define a standoff gap between opposing surfaces of the electrical socket and the electrical connector, with the leading face of the removable battery assembly resting on the bottom surface of the battery receiving space.

(188) Embodiments and features from one aspect may be embodiments and features from another aspect. Additional features and advantages may be gleaned by the person skilled in the art from the following description of exemplary embodiments with respect to the appended figures. The embodiments as shown and described are exemplary embodiments only and shall not be construed as limiting the invention, which is defined by the appended claims.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The following detailed description of specific embodiments of the present disclosure can be best understood when read in conjunction with the following drawings, where like structure is indicated with like reference numerals and in which:

(2) FIG. 1 schematically depicts a perspective view of a materials handling vehicle, according to one or more embodiments shown and described herein;

(3) FIG. 2 schematically depicts a removable battery assembly of the materials handling vehicle of FIG. 1, according to one or more embodiments shown and described herein;

(4) FIG. 3 schematically depicts an exploded perspective view of the removable battery assembly of FIG. 2, according to one or more embodiments shown and described herein;

(5) FIG. 4 schematically depicts another exploded perspective view of the removable battery assembly of FIG. 2, according to one or more embodiments shown and described herein;

(6) FIG. 5 schematically depicts an enlarged cross-section view of cam surfaces of the removable battery assembly of FIG. 2, according to one or more embodiments shown and described herein;

(7) FIG. 6 schematically depicts a perspective view of a spring-loaded battery handle of the removable battery assembly of FIG. 2, according to one or more embodiments shown and described herein;

(8) FIG. 7 schematically depicts a perspective view of a spring-loaded locking pin of the removable battery assembly of FIG. 2, according to one or more embodiments shown and described herein;

(9) FIG. 8 schematically depicts a partial cross-section view of the removable battery assembly of FIG. 2, according to one or more embodiments shown and described herein;

(10) FIG. 9 schematically depicts an enlarged partial cross-section view of the removable battery assembly of FIG. 2 in a locked position, according to one or more embodiments shown and described herein;

(11) FIG. 10 schematically depicts an enlarged partial cross-section view of the removable battery assembly of FIG. 2 in an unlocked position, according to one or more embodiments shown and described herein;

(12) FIG. 11 schematically depicts an embodiment of a removable battery assembly including a pair of guide pin stabilizers, according to one or more embodiments shown and described herein;

(13) FIG. 12 schematically depicts a perspective view of the removable battery assembly of FIG. 11 being inserted into a battery receiving space, according to one or more embodiments shown and described herein;

(14) FIG. 13 schematically depicts another perspective view of the removable battery assembly of FIG. 11 being inserted into the battery receiving space, according to one or more embodiments shown and described herein;

(15) FIG. 14 schematically depicts a side view of the removable battery assembly of FIG. 11 received within the battery receiving space, according to one or more embodiments shown and described herein;

(16) FIG. 15 schematically depicts an embodiment of a removable battery assembly including a pair of guide pin stabilizers, according to one or more embodiments shown and described herein;

(17) FIG. 16 schematically depicts an enlarged view of the removable battery assembly of FIG. 15 including the pair of guide pin stabilizers, according to one or more embodiments shown and described herein;

(18) FIG. 17 schematically depicts a partial cross-section view of the removable battery assembly of FIG. 15 taken along line 17-17, according to one or more embodiments shown and described herein;

(19) FIG. 18 schematically depicts a side view of the removable battery assembly of FIG. 15 received within the battery receiving space, according to one or more embodiments shown and described herein;

(20) FIG. 19 schematically depicts a perspective view of another embodiment of a removable battery assembly being inserted into the battery receiving space including a guide block, according to one or more embodiments shown and described herein;

(21) FIG. 20 schematically depicts a perspective view of the guide block of FIG. 19, according to one or more embodiments shown and described herein;

(22) FIG. 21 schematically depicts an exploded perspective view of the guide block of FIG. 19, according to one or more embodiments shown and described herein;

(23) FIG. 22 schematically depicts a perspective view of the battery receiving space including a pair of retention blocks, according to one or more embodiments shown and described herein;

(24) FIG. 23 schematically depicts a side view of one of the retention blocks engaging the removable battery assembly, according to one or more embodiments shown and described herein;

(25) FIG. 24 schematically depicts an enlarged side view of the retention block of FIG. 22, according to one or more embodiments shown and described herein;

(26) FIG. 25 schematically depicts a cross-section view of an electrical socket of the removable battery assembly mating with an electrical connector of the battery receiving space, according to one or more embodiments shown and described herein;

(27) FIG. 26 schematically depicts an enlarged cross-section view of the electrical socket of FIG. 21 mating with the electrical connector of FIG. 25, according to one or more embodiments shown and described herein;

(28) FIG. 27 schematically depicts an enlarged front view of the electrical socket of FIG. 21 mating with the electrical connector of FIG. 25, according to one or more embodiments shown and described herein;

(29) FIG. 28 schematically depicts a perspective view of the electrical connector of FIG. 25, according to one or more embodiments shown and described herein;

(30) FIG. 29 schematically depicts another perspective view of the electrical connector of FIG. 25, according to one or more embodiments shown and described herein;

(31) FIG. 30 schematically depicts a plurality of display screens to be displayed on a battery display of the removable battery assembly, according to one or more embodiments shown and described herein; and

(32) FIG. 31 schematically depicts a circuit schematic illustrating complementary socket/connector pin assignments for the battery coupling of a battery powered materials handling vehicle, according to one or more embodiments shown and described herein.

DETAILED DESCRIPTION

(33) Referring initially to FIG. 1, a materials handling vehicle **100** is shown. The materials handling vehicle **100** includes a materials handling mechanism **110**, a drive mechanism **120**, a battery receiving space **130**, and a removable battery assembly **200**. The materials handling mechanism **110** is configured to engage goods in a warehouse environment and cooperates with the drive mechanism **120**, under power from the removable battery assembly **200**, to move goods along an inventory transit surface in the warehouse environment.

(34) For the purposes of defining and describing the concepts and scope of the present disclosure, it is noted that a “warehouse” encompasses any indoor or outdoor industrial facility in which materials handling vehicles transport goods including, but not limited to, indoor or outdoor industrial facilities that are intended primarily for the storage of goods, such as those where multi-level racks are arranged in aisles, and manufacturing facilities where goods are transported about the facility by materials handling vehicles for use in one or more manufacturing processes.

(35) The drive mechanism **120** is merely illustrated schematically in FIG. 1, and it is noted that a variety of conventional and yet-to-be developed drive mechanisms will be suitable for operation with materials handling vehicles of the present disclosure. For example, and not by way of limitation, in the context of a pallet truck, the drive mechanism **120** may comprise an electric motor that is integrated with the steerable wheel of the pallet truck, as is disclosed in U.S. Pat. No. 6,343,907, and other similar patent literature.

(36) The removable battery assembly **200** and the battery receiving space **130** cooperate to define a battery insertion and removal axis **140** along which the removable battery assembly **200** is inserted into and removed from the battery receiving space **130**. It is noted that the present description and claims refer to movement of various components “along” respective axes. This movement “along” an axis encompasses movement that is directly co-linear with the associated axis and movement that is displaced from but parallel to the associated axis.

(37) Referring now to FIGS. 2-4, the removable battery assembly **200** comprises a battery body **210** and a battery locking mechanism **220**. The battery body **210** of the removable battery assembly **200** comprises a plurality of rechargeable battery cells **211**, a front case **210A**, and a rear case **210B**. The front and rear cases **210A**, **210B** cooperate to contain the plurality of rechargeable battery cells **211** therein. As described in more detail herein, the front and rear cases **210A**, **210B** cooperate to contain portions of the battery locking mechanism **220**. The removable battery assembly **200** comprises a leading face **201** provided at a lower end of the front and rear cases **210A**, **210B**.

(38) It should be appreciated that only one of the front and rear cases **210A**, **210B** will need to be designed with particular attention to the tolerances required for proper constraintment of the linear movement of the locking mechanism parts, as described herein. In addition, battery assembly is optimized by allowing for the complete installation of the battery locking mechanism **220** in one of front and rear cases **210A**, **210B** prior to assembly of the front and rear cases **210A**, **210B** with appropriate securing hardware, adhesive, and/or other bonding technology. The battery body **210** may comprise unitarily integrated hardware, multi-component hardware, or a combination thereof, for constraining the battery locking mechanism **220** and individual components thereof to linear movement.

(39) As shown in FIG. 25, the removable battery assembly **200** comprises an electrical socket **300** on the leading face **201** of the removable battery assembly **200**. The battery receiving space **130** comprises an electrical connector **400** that complements the electrical socket **300** of the removable battery assembly **200**. The leading face **201** is the side of the removable battery assembly **200** facing the battery receiving space **130** as the removable battery assembly **200** is inserted into the battery receiving space **130** in a direction opposite the handle lifting direction **255** along the battery insertion and removal axis **140**.

(40) As shown in FIG. 6, the battery locking mechanism **220** comprises a spring-loaded battery handle **230** including a grip portion **231** and one or more arm portions **237A**, **237B** extending in a

handle lifting direction **255**. As shown, the spring-loaded battery handle **230** includes a pair of spaced-apart arm portions provided at opposite ends of the grip portion **231**. The spring-loaded battery handle **230** comprises a planar handle cam surface **232A**, **232B** provided at an end of at least one of the spaced apart arm portions. In embodiments, each arm portion **237A**, **237B** comprises a planar handle cam surface **232A**, **232B**. The spring-loaded battery handle **230** comprises a locking pin passage **234A**, **234B** formed in the planar handle cam surface **232A**, **232B**. In embodiments, the spring-loaded battery handle **230** includes a locking pin passage **234A**, **234B** formed in each of the planar handle cam surfaces **232A**, **232B**. The spring-loaded battery handle **230** may comprise one or more handle-side limiting surfaces **236A**, **236B** independent of the planar handle cam surface **232A**, **232B** of the battery handle **230**. As shown, each spaced-apart arm portion includes a handle-side limiting surface **236A**, **236B**. The handle-side limiting surfaces **236A**, **236B** are inclined relative to the handle lifting direction **255**. The battery handle **230** may additionally comprise one or more handle-side limiting surfaces **236A'**, **236B'** that are oriented perpendicular to the handle lifting direction **255**. The spring-loaded battery handle **230** further may comprise one or more spring-engaging fingers **239A**, **239B** extending from the handle-side limiting surfaces **236A'**, **236B'** of the battery handle **230** in the handle lifting direction **255**, along the battery insertion and removal axis **140**. As shown, the spring-loaded battery handle **230** comprises a pair of spring-engaging fingers **239A**, **239B**. The spring-loaded battery handle **230** may be unitary elements, as would be the case for a molded structure, or may be formed of multiple components.

(41) As shown in FIG. 7, the battery locking mechanism **220** comprises one or more spring-loaded locking pins **240A**, **240B**. As described in more detail herein, the battery locking mechanism **220** may comprise a pair of spring-loaded locking pins **240A**, **240B** each having identical structure and being a mirror image of one another. Referring to FIG. 7 which illustrates a single spring-loaded locking pin **240A** and FIG. 8 which illustrates the pair of spring-loaded locking pins **240A**, **240B**, the structure of the spring-loaded locking pins **240A**, **240B** is discussed in more detail. The spring-loaded locking pins **240A**, **240B** comprise a planar pin cam surface **250A**, **250B** that is parallel to the planar handle cam surface **232A**, **232B**. The planar handle cam surface **232A**, **232B** and corresponding planar pin cam surface **250A**, **250B** of one of the arm portions **237A**, **237B** is configured as a mirror image of the planar handle cam surface **232A**, **232B** and corresponding planar pin cam surface **250A**, **250B** of the other of the arm portions **237A**, **237B**. The spring-loaded locking pin **237A**, **237B** comprises a locking pin extension **242A**, **242B** that extends along a latch engagement and disengagement axis **152A**, **152B**. The spring-loaded locking pin **240A**, **240B** comprises a locking pin extension **242A**, **242B** extending from the planar pin cam surface **250A**, **250B** and through the locking pin passage **234A**, **234B** formed in the planar handle cam surface **232A**, **232B**. The spring-loaded locking pins **240A**, **240B** of the battery locking mechanism **220** may each comprise a complementary chamfered engagement face **244A**, **244B**. The spring-loaded locking pin **240A**, **240B** may comprise a spring-engaging finger **249A**, **249B** extending in a direction opposite the locking pin extension **242A**, **242B** and perpendicular to the battery insertion and removal axis **140**. The spring-loaded locking pin **240A**, **240B** may be a unitary element, as would be the case for a molded structure, or may be formed of multiple components.

(42) As used herein. “planar” surfaces may include non-planar portions. This is shown, for example in FIGS. 6 and 7, where the planar pin cam surface **250A**, **250B** and the planar handle cam surface **232A**, **232B** terminate with rounded shoulder portions.

(43) As shown in FIG. 5, the planar handle cam surface **232A** of the spring-loaded battery handle **230** and the planar pin cam surface **250A** of the spring-loaded locking pin **240** are shown. An exterior angle $\theta_{sub.1}$ is defined between the planar handle cam surface **232A** and a cam surface traversal **T** extending in the handle lifting direction **255** along the battery insertion and removal axis **140**. The cam surface traversal **T** is perpendicular to the latch engagement and disengagement axis **152A**. Additionally, an exterior angle $\theta_{sub.2}$ is defined between the planar pin cam surface **250A**

and the cam surface traversal T. As such, the exterior angles $\theta_{sub.1}$, $\theta_{sub.2}$ are equal and alternate of one another relative to the cam surface traversal T.

(44) As described in more detail herein, the battery locking mechanism **220** is positionable between a locked position, shown in FIG. **8**, an intermediate position, shown in FIG. **9**, and an unlocked position, shown in FIG. **10**. It should be appreciated that when the battery locking mechanism **220** is in the locked position, the removable battery assembly **200** is locked within the battery receiving space **130**. Alternatively, when the battery locking mechanism **220** is in the unlocked position, the removable battery assembly **200** is permitted to be removed from the battery receiving space **130**.

(45) The battery receiving space **130** comprises one or more battery latches **150A**, **150B**.

(46) As shown, the battery receiving space **130** may comprise a pair of battery latches **150A**, **150B** positioned to receive a corresponding leading portion **245A**, **245B** of the spring-loaded locking pins **240A**, **240B** when the spring-loaded locking pins **240A**, **240B** are in an extended position and the removable battery assembly **200** is seated in the battery receiving space **130**.

(47) In embodiments, the battery receiving space **130** may comprise opposing pairs of battery guide pins **132A**, **132B**, each opposing pair arranged on opposite sides of the battery receiving space **130**. Each opposing pair of guide pins **132A**, **132B** comprises a latching pin **132A'**, **132B'** and a guiding pin **132A''**, **132B''**. The latching pin **132A'**, **132B'** and the guiding pin **132A''**, **132B''** of each opposing pair of battery guide pins **132A**, **132B** are positioned along a common guide pin axis, parallel to the battery insertion and removal axis **140**. The latching pin **132A'**, **132B'** of each opposing pair of battery guide pins **132A**, **132B** comprises a recess forming the battery latch **150A**, **150B** that is positioned to receive the leading portion **245A**, **245B** of one of the spring-loaded locking pins **237A**, **237B** when in the extended position, with the removable battery assembly **200** seated in the battery receiving space **130**. As used herein, the term “pin” can take a variety of forms, and need only be seated in the battery receiving space **130** while presenting structure that can extend into longitudinal guide structures **204A**, **204B** of the battery body **210**, as discussed herein. It is also noted that a “pin” may be a monolithic element or may comprise multiple components.

(48) Although, in the illustrated embodiment, the latching pin **132A'**, **132B'** is positioned closer to an open end of the battery receiving space **130**, it is contemplated that the guiding pin **132A''**, **132B''** may alternatively be positioned closer to an open end of the battery receiving space **130**. As shown in FIG. **14**, the latching pin **132A'**, **132B'** and the guiding pin **132A''**, **132B''** of each opposing pair of battery guide pins **132A**, **132B** are separated by a guide pin spacing S. Although this guide pin spacing may vary across different embodiments, in some cases it will be advantageous to ensure that the guide pin spacing S is less than half of a longitudinal dimension L, shown in FIG. **12**, of the lateral battery faces **202A**, **202B**, and is at least about 47.5 mm. The aforementioned upper limit on the guide pin spacing S helps ensure that the battery assembly **200** will not stick during insertion and removal, while the aforementioned minimum spacing helps ensure that the guide pins **132A**, **132B** will provide sufficient resistance to inadvertent battery tilting during insertion and removal.

(49) Although a wide variety of battery dimensions are contemplated within the scope of the present disclosure, in embodiments, battery dimensions will range from between about 400 mm and about 450 mm (height), between about 80 mm and about 120 mm (depth), and between about 200 mm and about 230 mm (width). In embodiments, battery dimensions will range from between about 415 mm and about 416 mm (height), between about 101 mm and about 102 mm (depth), and between about 211 mm and about 212 mm (width). The dimensions of the guide pins **132A**, **132B** and the longitudinal guide structure **204A**, **204B** can be taken to scale relative to the aforementioned battery dimensions. To ensure proper insertion and removal of the removable battery assembly **200** to and from the battery receiving space **130**, as discussed in more detail herein, a minimum amount of clearance should be maintained between the periphery of the guide pins **132A**, **132B** and inside walls of the longitudinal guide structure **204A**, **204B**. In many cases, a

clearance of between about 0.5 mm and about 5 mm will suffice. In many cases, a clearance of between about 1 mm and about 1.5 mm will suffice.

(50) Referring again to FIGS. **8-10**, the latching pin **132A'**, **132B'** of each opposing pair of battery guide pins **132A**, **132B** may comprise a chamfered engagement face **136A**, **136B**. The chamfered engagement face **136A**, **136B** of each latching pin **132A'**, **132B'** leads to the recess forming the battery latch **150A**, **150B** of each latching pin **132A'**, **132B'**. Each complementary chamfered engagement face **244A**, **244B** of the spring-loaded locking pins **240A**, **240B** is oriented to face the chamfered engagement face **136A**, **136B** of one of the latching pins **132A'**, **132B'** as the removable battery assembly **200** is inserted into the battery receiving space **130**.

(51) As shown in FIGS. **12** and **13**, the battery body **210** comprises lateral battery faces **202A**, **202B**, each comprising a longitudinal guide structure **204A**, **204B** that is oriented along the battery insertion and removal axis **140**. The longitudinal guide structure **204A**, **204B** is sized to accommodate the opposing pairs of guide pins **132A**, **132B**, including the latching pin **132A'**, **132B'** and the guiding pin **132A''**, **132B''**, as the removable battery assembly **200** is inserted into and removed from the battery receiving space **130**. The longitudinal guide structure **204A**, **204B** of the lateral battery faces **202A**, **202B** is configured as guide channels. In embodiments, the longitudinal guide structure **204A** of one of the lateral battery faces **202A** is shorter than the longitudinal guide structure **204B** of the other lateral battery face **202B**, to create free space along one of the lateral battery faces **202B**. As is illustrated in FIGS. **11** and **12**, this free space can be used to create room for hardware that forms part of the battery receiving space **130** of the materials handling vehicle **100**.

(52) Referring again to FIG. **8**, the battery body **210** may comprise one or more handle passages **217A**, **217B** and one or more locking pin passages **219A**, **219B**. The battery body **210** may also comprise a handle grip recess **225**. As shown, the handle grip recess **225** is formed below the grip portion **231** of the spring-loaded battery handle **230** and may extend at least approximately 6.5 mm along the battery insertion and removal axis **140**. In this manner, the aforementioned handle grip recess **225** provides sufficient freedom of movement to allow a user to grasp the grip portion **231** of the spring-loaded battery handle **230** with one or two hands and initiate a battery removal operation.

(53) The battery body **210** further may comprise one or more body-side limiting surfaces **216A**, **216B** that are positioned parallel to corresponding handle-side limiting surfaces **236A**, **236B** of the spring-loaded battery handle **230**, to engage the corresponding handle-side limiting surfaces **236A**, **236B** of the spring-loaded battery handle **230** when the battery locking assembly **220** is in the locked position. The battery body **210** may further comprise one or more body-side limiting surfaces **216A'**, **216B'** that are inclined relative to the handle lifting direction **255** and dedicated for engagement of a corresponding one of the handle cam surfaces **232A**, **232B** when the battery locking assembly **220** is in the unlocked position.

(54) In the illustrated embodiment, for example, each body-side limiting surface **216A'**, **216B'** is inclined at an angle of approximately 45 degrees, relative to the handle lifting direction **255**. In this manner, the absolute surface area of the body-side limiting surface **216A'**, **216B'** is increased, as compared to cases where the body-side limiting surface **216A'**, **216B'** would be perpendicular to the handle lifting direction **255**, to increase stopping power in the battery locking mechanism **220**, and to reduce wear. However, it should be appreciated that variations of the illustrated 45 degree limiting surface angle are contemplated.

(55) The battery body **210** may additionally comprise one or more body-side limiting surfaces **216A''**, **216B''** that are oriented perpendicular to the handle lifting direction **255**, and may be positioned for engagement with a corresponding one of the handle-side limiting surfaces **236A'**, **236B'** when the battery locking assembly **220** is in the locked position. This perpendicular orientation helps optimize the movement limiting capacity of the battery locking mechanism **220**.

(56) The battery body **210** further may comprise one or more handle-facing, spring-receiving

cavities **212A**, **212B**. A handle spring **238A**, **238B** may be positioned within each handle-facing, spring-receiving cavity **212A**, **212B**. Corresponding spring-engaging fingers **239A**, **239B** of the battery handle **230** extend into the handle-facing, spring-receiving cavity **212A**, **212B** along a longitudinal axis of the handle-facing, spring-receiving cavity **212A**, **212B**. In this manner, the handle-facing, spring-receiving cavity **212A**, **212B** and the spring-engaging finger **239A**, **239B** of the battery handle **230** cooperate to help maintain the orientation of the spring-loaded battery handle **230** along the battery insertion and removal axis **140** as the battery handle **230** moves between a lowered or locked position, when the battery locking assembly **220** is in the locked position, and a raised or unlocked position, when the battery locking assembly **220** is in the unlocked position.

(57) The battery body **210** may comprise one or more pin-facing, spring-receiving cavities **213A**, **213B**. A locking pin spring **248A**, **248B** may be positioned within each spring-receiving cavity **213A**, **213B**. Corresponding spring-engaging fingers **249A**, **249B** of the spring-loaded locking pins **240A**, **240B** extend into the pin-facing, spring-receiving cavities **213A**, **213B** along a longitudinal axis of the pin-facing, spring-receiving cavities **213A**, **213B**. In this manner, the pin-facing, spring-receiving cavity **213A**, **213B** and the spring-engaging finger **249A**, **249B** of each spring-loaded locking pin **240A**, **240B** cooperate to help maintain the orientation of the spring-loaded locking pin **240A**, **240B** perpendicular to the battery insertion and removal axis **140** as the spring-loaded battery handle **230** moves between the locked position and the unlocked position.

(58) As shown in FIG. 9, when the battery locking mechanism **220** is in the locked position, the grip portion **231** of the battery handle **230** may be flush with a top surface **218** of the battery body **210**. Alternatively, as shown in FIGS. 9 and 10, when the battery locking mechanism is in the intermediate position or the unlocked position, respectively, the grip portion **231** extends above a top surface **218** of the battery body **210**. In this manner, the grip portion **231** is accessible from an exterior of the battery body **210** to be gripped by a user to move the spring-loaded battery handle **230** toward the unlocked position and remove the removable battery assembly **200** from the battery receiving space **130**. It is noted that the spring-loaded battery handle **230** may be considered to be “flush” with the top surface **218** of the battery body **210** when within an acceptable degree of tolerance, e.g., within approximately 0.2 mm to about 0.5 mm.

(59) The spring-loaded battery handle **230** and the spring-loaded locking pin **240A**, **240B** are configured such that the handle cam surface **232A**, **232B** engages the pin cam surface **250A**, **250B** with movement of the battery handle **230**, relative to the battery body **210**, along the battery insertion and removal axis **140**. More particularly, the spring-loaded battery handle **230** and the spring-loaded locking pin **240A**, **240B** engage at the handle cam surface **232A**, **232B** and the pin cam surface **250A**, **250B** such that movement of the battery handle **230** from the locked position to the unlocked position through the handle passage **217A**, **217B** in the handle lifting direction **255** causes movement of the locking pin extension **242A**, **242B** of the spring-loaded locking pin **240A**, **240B** through the locking pin passage **234A**, **234B** from an extended position, when the battery locking assembly **220** is in the locked position, to a retracted position, when the battery locking assembly **220** is in the unlocked position, along the latch engagement and disengagement axis **152A**, **152B**. As discussed herein, the battery body **210** constrains the spring-loaded battery handle **230** and the handle cam surface **232A**, **232B** to linear movement along the battery insertion and removal axis **140**. Additionally, the battery body **210** constrains the spring-loaded locking pin **240A**, **240B** and thus the pin cam surface **250A**, **250B** to linear movement along a latch engagement and disengagement axis **152A**, **152B** that is perpendicular to the battery insertion and removal axis **140**. In embodiments, either the front case **210A** or the rear case **210B** of the battery body **210** exclusively constrains the spring-loaded battery handle **230** and the handle cam surfaces **232A**, **232B** to linear movement along the battery insertion and removal axis **140**.

(60) As described herein, the spring-loaded battery handle **230** is spring-biased in the locked position by the handle springs **238A**, **238B** and is movable relative to the battery body **210** from the

locked position to an unlocked position in the handle lifting direction **255** along the battery insertion and removal axis **140**. Additionally, the spring-loaded locking pins **240A**, **240B** are also spring-biased by the locking pin springs **248A**, **248B** in the extended position and are movable relative to the battery body **210** from the extended position to the retracted position along the latch engagement and disengagement axis **152A**, **152B** in response to movement of the battery handle **230**, relative to the battery body **210**, in the handle lifting direction **255** with the handle cam surface **232A**, **232B** engaged with the pin cam surface **250A**, **250B**. However, it should be appreciated that the removable battery assembly **200** may include one of a handle spring **238A**, **238B** in direct contact with the spring-loaded battery handle **230** to bias the battery handle **230** toward the locked position, a locking pin spring **248A**, **248B** in direct contact with the spring-loaded locking pin **240A**, **240B** to bias the spring-loaded locking pin **240A**, **240B** toward the extended position, or both the handle spring **238A**, **238B** and the locking pin spring **248A**, **248B**.

(61) This movement of the spring-loaded battery handle **230** in the handle lifting direction **255** forces movement of the spring-loaded locking pin **240A**, **240B** along the latch engagement and disengagement axis **140** because the respective planar handle cam surfaces **232A**, **232B** and the planar pin cam surfaces **250A**, **250B** are relatively low friction surfaces, which are slideably engaged, and which are constrained by the battery body **210** to move linearly along their respective axes of movement. In this manner, the pair of locking pins **240A**, **240B** will move simultaneously, in opposite directions, along the latch engagement and disengagement axis **152A**, **152B**, as the spring-loaded battery handle **230** moves between the locked position and the unlocked position.

(62) It should be appreciated that the spring-loaded locking pin **240A**, **240B** is positioned at a point along a longitudinal dimension **L**, shown in FIG. **12**, of the battery body **210** that results in locking pin engagement with the battery latch **150A**, **150B** simultaneously with engagement of an electrical socket **300**, shown in FIG. **25**, on the leading face **201** of the removable battery assembly **200** with an electrical connector **400** in the battery receiving space **130**, as the removable battery assembly **200** is inserted into the battery receiving space **130**, with the spring-loaded battery handle **230** in the locked position. The leading face **201** of the removable battery assembly **200** rests on a bottom surface **134** of the battery receiving space **130** with the spring-loaded locking pin **240A**, **240B** engaged with the battery latch **150A**, **150B**, and the electrical socket **300** engaged with the electrical connector **400**. With the battery assembly and the battery receiving space **130** so designed, locking is not enabled until the electrical connections on the vehicle are properly seated in the electrical socket **300**.

(63) Referring now to FIGS. **11-14**, in embodiments, the removable battery assembly **200** further comprises a pair of guide pin stabilizers **205A**, **205A'**, **205B**, **205B'** on each of the lateral battery faces **202A**, **202B**. Each guide pin stabilizer **205A**, **205A'**, **205B**, **205B'** comprises a stabilizer shank **206A** that is anchored in the battery body **210** and a stabilizer cap **208A**, **208B** that extends partially into or partially over one of the guide channels of the longitudinal guide structure **204A**, **204B** to reduce an effective width of the guide channel.

(64) As shown in FIG. **14**, each pair of guide pin stabilizers **205A**, **205A'**, **205B**, **205B'** forms a restricted-width guide pin gap **G** along the longitudinal guide structure **204A**, **204B** on each of the lateral battery faces **202A**, **202B**. The guiding pin **132A''**, **132B''** of each opposing pair of guide pins **132A**, **132B** resides at a guiding pin parking position **P** along the longitudinal guide structure **204A**, **204B** on each of the lateral battery faces **202A**, **202B**, with the removable battery assembly **200** seated in the battery receiving space **130**. The restricted-width guide pin gap **G** formed by each pair of guide pin stabilizers **205A**, **205A'**, **205B**, **205B'** at least partially overlaps the guiding pin parking position **P** along the longitudinal guide structure **204A**, **204B** on each of the lateral battery faces **202A**, **202B**. The guiding pins **132A''**, **132B''** have a diameter greater than a width of the restricted-width guide pin gap **G**. The guide pin stabilizers **205A**, **205A'**, **205B**, **205B'** are configured to yield in a lateral yielding direction **Y** perpendicular to the battery insertion and removal axis **140**, and to maintain a degree of lateral resilience, when a guiding pin **132A''**, **132B''**

enters the restricted-width guide pin gap G. FIG. 14 illustrates the lateral yielding direction Y for each guide pin stabilizer 205A, 205A', on one side of the battery body 210, e.g., on the lateral battery face 202A.

(65) To facilitate the aforementioned resilient yielding action, each guide pin stabilizer 205A, 205A', 205B, 205B' should define a degree of structural flexibility and rigidity. In the embodiment illustrated in FIGS. 11 to 14, the aforementioned yielding action may be provided primarily where the shank 206A, 206B meets the cap 208A, 208B. To this end, each guide pin stabilizer 205A, 205A', 205B, 205B' may be formed as a unitary, one piece polyurethane structure with a shank 206A, 206B that is relatively thin, when compared to the lateral dimensions of the cap 208A, 208B. To reduce wear, the guide pin cap 208A, 208B, which would otherwise define a circular footprint, may comprise a truncated portion 209A, 209B, as shown in FIG. 14.

(66) Referring now to FIGS. 15-18, in embodiments, the removable battery assembly 200 further comprises a pair of guide pin stabilizers 505A, 505A' on each of the lateral battery faces 202A, 202B, as opposed to the guide pin stabilizers 205A, 205A', 205B, 205B' discussed herein. Although only a pair of guide pin stabilizers 505A, 505A' are illustrated on the lateral battery face 202A, it should be appreciated that a pair of guide pin stabilizers are also provided on the other lateral battery face 202B. Each guide pin stabilizer 505A, 505A' can be secured to the battery body 210 with a fastener 506A and extends partially into or partially over one of the guide channels of the longitudinal guide structure 204A, 204B to reduce an effective width of the guide channel.

(67) As shown in FIG. 18, each pair of guide pin stabilizers 505A, 505A' forms a restricted-width guide pin gap G along the longitudinal guide structure 204A, 204B on each of the lateral battery faces 202A, 202B. The guiding pin 132A'', 132B'' of each opposing pair of guide pins 132A, 132B resides at a guiding pin parking position P along the longitudinal guide structure 204A, 204B on each of the lateral battery faces 202A, 202B, with the removable battery assembly 200 seated in the battery receiving space 130. The restricted-width guide pin gap G formed by each pair of guide pin stabilizers 505A, 505A' at least partially overlaps the guiding pin parking position P along the longitudinal guide structure 204A, 204B on each of the lateral battery faces 202A, 202B. To reduce wear, the guide pin stabilizers 505A, 505A' which would otherwise define a circular footprint, may comprise the truncated portion 509A, as shown in FIG. 18. The guide pin stabilizers 505A, 505A', or at least a portion of the guide pin stabilizers 505A, 505A', are configured to yield in a lateral yielding direction Y perpendicular to the battery insertion and removal axis 140, and to maintain a degree of lateral resilience, when a guiding pin 132A'', 132B'' enters the restricted-width guide pin gap G. FIG. 18 illustrates the lateral yielding direction Y for each guide pin stabilizer 505A, 505A', on one side of the battery body 210, e.g., on the lateral battery face 202A. In this embodiment, "yield" may be used herein to refer to a partial compression of the guide pin stabilizers 505A, 505A' such that a truncated portion 509A of the guide pin stabilizers 505A, 505A' compresses by partially deforming in the lateral yielding direction Y as the guiding pin 132A'', 132B'' enters the restricted-width guide pin gap G.

(68) To facilitate the aforementioned resilient yielding action, each guide pin stabilizer 505A, 505A' should define a degree of structural flexibility and rigidity, most advantageously at the truncated portion 509A of the guide pin stabilizers 505A, 505A'. To this end, each guide pin stabilizer 505A, 505A' may be formed as a unitary polyurethane structure. More particularly, the guide pin stabilizers 505A, 505A' may be formed from any suitable deformable, resilient material having a Shore A hardness between 50 Shore A and 90 Shore A. The guide pin stabilizers 505A, 505A' deform as pressure or a force is applied to one side of the guide pin stabilizers 505A, 505A' such as, for example, a force in the lateral yielding direction Y perpendicular to the battery insertion and removal axis 140 by contact with the guiding pin 132A'', 132B''. In embodiments, the guide pin stabilizers 505A, 505A' may have a Shore A hardness between 50 Shore A and 70 Shore A. In other embodiments, the guide pin stabilizers 505A, 505A' may have a Shore A hardness between 60 Shore A and 80 Shore A. In still further embodiments, the guide pin stabilizers 505A,

505A' may have a Shore A hardness between 70 Shore A and 90 Shore A.

(69) As shown in FIG. 16, the longitudinal guide structure **204A** of the lateral battery face **202A** comprises raised tracks **503A** that receive the guide pin stabilizers **505A**, **505A'**. Although not shown, it should be appreciated that the lateral battery face **202B** similarly comprises raised tracks that receive the other pair of guide pin stabilizers. The raised tracks **503A** define a slot **503A'** for receiving an alignment feature **508A'** extending from the guide pin stabilizers **505A**, **505A'**. As shown in FIG. 16, the alignment feature **508A'** of each guide pin stabilizer **505A**, **505A'** is received within a corresponding slot **503A'** to facilitate installation of the guide pin stabilizers **505A**, **505A'** in the proper orientation, and to help prevent the guide pin stabilizers **505A**, **505A'** from rotating relative to the lateral battery face **202A**.

(70) As shown in FIG. 17, a cross-section view of the guide pin stabilizer **505A'** is shown illustrating the fastener **506A** extending through the guide pin stabilizers **505A'** and received within a channel **502A'** formed in the battery face **202A**. The fastener **506A** may be a rigid member extending through the guide pin stabilizer **505A'** and including external threads configured to threadedly engage with internal threads formed in the channel **502A'**. The fastener **506A** is formed from a material having a hardness greater than a hardness of the guide pin stabilizer **505A'**. In use, the guide pin stabilizers **505A**, **505A'** may be positioned to be received within the raised tracks **503A** and the slot **503A'** and, subsequently, the fastener **506A** engages the battery face **202A** to secure the guide pin stabilizers **505A**, **505A'**. The alignment feature **508A'** of the guide pin stabilizers **505A**, **505A'** prevents rotation of the guide pin stabilizers **505A**, **505A'** as the fastener **506A** rotates to engage the battery face **202A**. In other embodiments, the guide pin stabilizers **505A**, **505A'** may be secured to the battery face **202A** using an adhesive or other suitable fastening member other than a mechanical fastener such as the fastener **506A**.

(71) Referring now to FIGS. 19-22, in embodiments, the battery receiving space **130** comprises opposing guide blocks **160A**, **160B**, each arranged on opposite sides of the battery receiving space **130**. Each opposing guide block **160A**, **160B** is positioned along the battery insertion and removal axis **140** to engage the channel shoulder **2043A**, **2043B** of one of the longitudinal guide structures **204A**, **204B** with the removable battery assembly **200** seated in the battery receiving space **130** and the leading portions **245A**, **245B** of the pair of spring-loaded locking pins **237A**, **237B** received within the pair of battery latches **150A**, **150B**.

(72) Each opposing guide block **160A**, **160B** comprises a securement portion **162A**, **162B** and a replaceable portion **164A**, **164B**. The securement portion **162A**, **162B** of each guide block **160A**, **160B** is secured to the materials handling vehicle **100**. The replaceable portion **164A**, **164B** of each guide block **160A**, **160B** is seated within the securement portion **162A**, **162B**, and is removable from the securement portion **162A**, **162B** without destruction of the securement portion **162A**, **162B**. The securement portion **162A**, **162B** of each guide block **160A**, **160B** is configured as a bracket from which the replaceable portion **164A**, **164B** of each guide block **160A**, **160B** extends to define friction-inducing surfaces **166A**, **166B** and guiding surfaces **168A**, **168B**, as discussed herein. In this manner, the replaceable portion **164A**, **164B** of each guide block **160A**, **160B** can be removed and replaced many times over the lifetime of the materials handling vehicle **100**. In particular embodiments, the replaceable portion **164A**, **164B** may be fabricated from, a machined polyurethane block and may be fastened to the securement portion **162A**, **162B**, or press fit into a space formed by the securement portion **162A**, **162B**. The securement portion **162A**, **162B** may be fabricated from stamped steel or other metal, and can be secured to the materials handling vehicle **100** in a variety of ways. e.g., by welding it to an interior housing **135** of the battery receiving space **130**, or by using fasteners to secure it to the interior housing, or another component of the materials handling vehicle.

(73) The replaceable portion **164A**, **164B** of each guide block **160A**, **160B** comprises a lower surface hardness and higher surface friction, relative to the securement portion **162A**, **162B**. As noted above, the replaceable portion **164A**, **164B** of each guide block **160A**, **160B** comprises a

friction-inducing surface **166A**, **166B** and a guiding surface **168A**, **168B**. The friction-inducing surface **166A**, **166B** and the guiding surface **168A**, **168B** of each replaceable portion **164A**, **164B** of each guide block **160A**, **160B** face an opposing surface **207A**, **207B** of the removable battery assembly **200** or the longitudinal guide structure **204A**, **204B** without interference from the securement portions **162A**, **162B** of each guide block **160A**, **160B**, with the removable battery assembly **200** seated in the battery receiving space **130**. The replaceable portion **164A**, **164B** of each guide block **160A**, **160B** may comprise a chamfered leading portion **165A**, **165B**.

(74) Each friction-inducing surface **166A**, **166B** extends along the battery insertion and removal axis **140**, parallel to and facing an opposing one of the lateral battery faces **202A**, **202B**, with the removable battery assembly **200** seated in the battery receiving space **130**. More particularly, the friction-inducing surface **166A**, **166B** of each replaceable portion **164A**, **164B** of each guide block **160A**, **160B** extends discontinuously in a direction Z along the battery insertion and removal axis **140** and faces the opposing lateral battery face **202A**, **202B** in a perpendicular direction X, with the removable battery assembly **200** seated in the battery receiving space **130**. The friction-inducing surfaces **166A**, **166B** of each replaceable portion **164A**, **164B** of each guide block **160A**, **160B** are raised, relative to the securement portions **162A**, **162B** and remaining portions of the replaceable portions **164A**, **164B** of each guide block **160A**, **160B**, in the direction of the opposing lateral battery faces **202A**, **202B**. The friction-inducing surfaces **166A**, **166B** of each replaceable portion **164A**, **164B** of each guide block **160A**, **160B** comprise a series of friction-inducing ridges oriented across the battery insertion and removal axis **140**.

(75) Each guiding surface **168A**, **168B** extends along the battery insertion and removal axis **140**, perpendicular to the lateral battery faces **202A**, **202B** and facing an opposing surface **207A**, **207B** of the longitudinal guide structure **204A**, **204B**, with the removable battery assembly **200** seated in the battery receiving space **130**. More particularly, the guiding surface **168A**, **168B** of each replaceable portion **164A**, **164B** of each guide block **160A**, **160B** extends continuously in the direction Z and faces the opposing surface **207A**, **207B** of the longitudinal guide structure **204A**, **204B** in a perpendicular direction Y, with the removable battery assembly **200** seated in the battery receiving space **130**.

(76) The aforementioned discontinuities in the friction-inducing surfaces **166A**, **166B** of the guide blocks **160A**, **160B** create surfaces that will more readily resist overly rapid insertion of the removable battery assembly **200** into the battery receiving space **130**. Conversely, the aforementioned continuity in the guiding surfaces of the guide blocks **160A**, **160B** create surfaces that will more readily guide movement of the removable battery assembly **200** as it is inserted/removed, without undue resistance.

(77) As shown in FIG. **19**, in embodiments, the longitudinal guide structure **204A** of the lateral battery face **202A** may be configured as a stepped guide channel comprising a one-sided channel portion **2041A** that transitions to a two-sided channel portion **2042A** at a channel shoulder **2043A**. The chamfered leading portion **165A** faces the channel shoulder **2043A** in the longitudinal guide structure **204A**. Although not shown, a stepped guide channel may be formed on both lateral battery faces **202A**, **202B**.

(78) By configuring the replaceable portion of each guide block **160A**, **160B** in this manner, the replaceable portions **164A**, **164B** of each guide block **160A**, **160B** functionally optimize the sliding contact that occurs between the battery assembly **200** and the battery receiving space **130** as the battery assembly **200** is inserted into and removed from the battery receiving space **130**, while extending the life of the removable battery assembly **200** and minimizing wear to the components of the battery receiving space **130**. During insertion in particular, the guide blocks **160A**, **160B** help limit excessively rapid insertion of the removable battery assembly **200** into the battery receiving space **130**.

(79) Referring now to FIGS. **22-24**, in embodiments, the battery receiving space **130** comprises opposing retention blocks **260A**, **260B**. Each retention block **260A**, **260B** is arranged on opposite

sides of the battery receiving space **130**. Each retention block **260A**, **260B** may comprise a metal backing plate **261A**, **261B** and a plastic retention lever plate **263A**, **263B**. Although each retention block **260A**, **260B** illustrated in FIG. **22** is presented as a two-piece assembly comprising a backing plate **261A**, **261B** fabricated from a relatively high strength and rigid metal, and a separate lever plate **263A**, **263B** fabricated from a material that is flexible enough to facilitate the formation of a functional retention lever, as described herein, it is contemplated that the suitable plastics and other relatively flexible materials with sufficient strength may be used to fabricate a monolithic retention block.

(80) Each retention block **260A**, **260B** comprises a retention lever **262A**, **262B** comprising a fixed end **264A**, **264B** and a distal end **266A**, **266B**. The distal end **266A**, **266B** of each retention lever **262A**, **262B** comprises a terminal lobe **267A**, **267B**.

(81) In embodiments, each longitudinal guide structure **204A**, **204B** of the lateral battery faces **202A**, **202B** comprises a one-sided channel portion **2041A**, **2041B** that comprises the opposing surface **207A**, **207B** facing the guiding surface **268A**, **268B** of the retention block **260A**, **260B**, with the removable battery assembly **200** seated in the battery receiving space **130**. As shown in FIG. **23**, the one-sided channel portion **2041A**, **2041B** terminates in a channel shoulder **2043A**, **2043B** of the longitudinal guide structure **204A**, **204B**. Each guide block **160A**, **160B** may comprise a chamfered leading portion **165A**, **165B** that faces the channel shoulder **2043A**, **2043B** of the longitudinal guide structure **204A**, **204B**, with the removable battery assembly **200** seated in the battery receiving space **130**.

(82) In embodiments, the longitudinal guide structure **204A**, **204B** of each lateral battery face **202A**, **202B** comprises a lever-receiving detent **270A** that is configured to receive the distal end **266A**, **266B** of one of the retention levers **262A**, **262B**, with the removable battery assembly **200** seated in the battery receiving space **130**. Each retention lever **262A**, **262B** is configured to lie in a state of flexion when received in the lever-receiving detent **270A** of the longitudinal guide structure **204A**, **204B**. More particularly, each retention lever **262A**, **262B** is positioned such that each of the lever-receiving detents **270A** receives a distal end **266A**, **266B** of one of the retention levers **262A**, **262B** simultaneously with engagement of the electrical socket **300** on the leading face **201** of the removable battery assembly **200** with the electrical connector **400** in the battery receiving space **130**, as the removable battery assembly **200** is inserted into the battery receiving space **130**. In embodiments, the lever-receiving detent **270A** and the terminal lobe **267A**, **267B** define mating rounded profiles.

(83) Each retention block **260A**, **260B** comprises a planar guiding surface **268A**, **268B** facing an opposing surface **207A**, **207B** of the longitudinal guide structure **204A**, **204B**. The planar guiding surface **268A**, **268B** of the retention block **260A**, **260B** comprises a retention lever recess **265A**, **265B**. The fixed end **264A**, **264B** of each retention lever **262A**, **262B** is positioned in the retention lever recess **265A**, **265B** to avoid contact with the opposing surface **207A**, **207B** of the longitudinal guide structure **204A**, **204B**. Accordingly, each retention lever **262A**, **262B** is configured for increased flexion as it moves progressively towards the retention lever recess **265A**, **265B**.

(84) Although the retention lever recess illustrated in FIG. **22** is defined by upper and lower arcuate surfaces, it is contemplated that the retention levers **262A**, **262B**, and the associated retention lever recesses **265A**, **265B**, according to the present disclosure may be formed in a variety of ways including, for example, by utilizing planar surfaces to form the retention levers **262A**, **262B** and the retention lever recesses **265A**, **265B**.

(85) Referring to FIGS. **25-29**, as is noted above, the removable battery assembly **200** and the battery receiving space **130** cooperate to define a battery insertion and removal axis **140** along which the removable battery assembly **200** is inserted into and removed from the battery receiving space **130**. The removable battery assembly **200** comprises a battery body **210**, a leading face **201**, an electrical socket **300** on the leading face **201** of the removable battery assembly **200**, and a battery locking mechanism **220**.

(86) The battery receiving space **130** comprises an electrical connector **400** that complements the electrical socket **300** of the removable battery assembly **200**, and a battery latch **150A**, **150B** that engages the battery locking mechanism **220** simultaneously with engagement of the electrical socket **300** on the leading face **201** of the removable battery assembly **200** with the electrical connector **400** in the battery receiving space **130**, as the removable battery assembly **200** is inserted into the battery receiving space **130**.

(87) The leading face **201** of the removable battery assembly **200** rests on a bottom surface **134** of the battery receiving space **130** with the battery locking mechanism **22** engaged with the battery latch **150A**, **150B**, and with the electrical socket **300** engaged with the electrical connector **400**. The electrical socket **300** may be recessed on the leading face **201** of the removable battery assembly **200**.

(88) The electrical socket **300**, the electrical connector **400**, the battery body **210**, and the battery receiving space **130** are configured to define a standoff gap **414** extending along the battery insertion and removal axis **140** between opposing surfaces **416**, **418** of the electrical socket **300** and the electrical connector **400**, with the leading face **201** of the removable battery assembly **200** resting on the bottom surface **134** of the battery receiving space **130**. A reliable electrical connection can be maintained between the electrical socket **300** and the electrical connector **400**, even after repeated insertion and removal of the battery assembly **200**, by maintaining this standoff gap **414**, and by ensuring that the leading face **201** of the removable battery assembly **200** rests on the bottom surface **134** of the battery receiving space **130**, under the weight of the battery assembly **200**. This is possible because the relatively sturdy and physically substantial leading face **201** of the removable battery assembly **200** and bottom surface **134** of the battery receiving space **130** oppose further engagement of the mating connector components under the weight of the battery, instead of components of the less substantial electrical socket **300** and the electrical connector **400**.

(89) The aforementioned reliable electrical connection across the electrical socket **300** and the electrical connector **400** is particularly significant in the context of materials handling vehicles where significant data is transferred back and forth across the connection. This data may include, for example, general CAN bus data that is transmitted between a “smart” battery controller and one or more of the vehicle controllers, data representing vehicle or battery errors, command data, and, display data, for embodiments where the battery assembly **200** includes a battery display. Each of these types of data transmission require a stable and reliable electrical connection across the electrical socket **300** and the electrical connector **400** for proper vehicle operation.

(90) In some embodiments, to enhance the aforementioned insertion and removal operations, the electrical connector **400** in the battery receiving space **130** may comprise a connector housing **410** comprising an outer wall **412** that is tapered to a reduced-size footprint as it extends away from the bottom surface **134** of the battery receiving space **130**. Similarly, the electrical socket **300** on the leading face **201** of the removable battery assembly **200** comprises a socket housing **310** comprising an inner wall **312** that is tapered to an increased-size footprint as it extends away from the leading face **201** of the removable battery assembly. The inner wall **312** that is tapered to complement and contact the taper of the outer wall **412** of the connector housing **410** with the leading face **201** of the removable battery assembly **200** resting on the bottom surface **134** of the battery receiving space **130**, and with the standoff gap **414** between opposing surfaces **416**, **418** of the electrical socket **300** and the electrical connector **400**.

(91) The opposing surfaces **416**, **418** of the electrical socket **300** and the electrical connector **400** are horizontally oriented opposing surfaces that are perpendicular to the battery insertion and removal axis **140** and are spaced apart by the standoff gap **414**. Preferably, either the standoff gap **414**, or a gap larger than the standoff gap **414**, is maintained between substantially all horizontally oriented opposing surfaces of the electrical socket **300** and the electrical connector **400**. In some embodiments, it may be preferable to ensure that the standoff gap **414** is at least about 0.2 mm. In more particular embodiments, the standoff gap **414** is between about 0.2 mm and about 1.7 mm.

(92) The battery-side electrical socket **300** can be recessed in the leading face **201** of the battery assembly **200** with a socket housing **310**. In this manner, the battery assembly **200** may be removed from the battery receiving space **130** and placed, leading face **201** down, on a warehouse floor or other surface, without causing damage to, or receiving interference from, the electrical socket **300**. The vehicle-side electrical connector **400** can be configured to complement the battery-side electrical socket **300** by projecting upwardly from the bottom surface **134** of the battery receiving space **130** with a connector housing **410**.

(93) The battery-side electrical socket **300** may comprise a rim portion **315** that is enclosed by the socket housing **310** and extends generally parallel to the leading face **201** of the battery assembly. Similarly, the vehicle-side electrical connector **400** may comprise a shoulder portion **415** that is enclosed by the connector housing **410** and extends generally parallel to the bottom surface **134** of the battery receiving space **130**. The rim portion **315** of the battery-side electrical socket extends parallel to the shoulder portion **415** of the vehicle-side electrical connector **400**, with the removable battery assembly **200** seated in the battery receiving space **130**, and is spaced from the shoulder portion **415** by the standoff gap **414**.

(94) The electrical socket **300** may comprise a set of electrically conductive pin receptacles **320** and the electrical connector **400** may comprise a set of complementary electrically conductive connector pins **420**, or vice-versa. An outermost portion of the standoff gap **414** can be configured to surround the set of electrically conductive pin receptacles **320** and the set of complementary electrically conductive connector pins **420**, with the leading face **201** of the removable battery assembly **200** resting on the bottom surface **134** of the battery receiving space **130**, and with the a set of electrically conductive pin receptacles **320** engaging the set of complementary electrically conductive connector pins **420**.

(95) The socket housing **310** of the electrical socket **300** and the connector housing **410** of the electrical connector cooperate to enclose the set of electrically conductive pin receptacles **320** and the set of complementary electrically conductive connector pins **420** to form a protective barrier between the outermost portion of the standoff gap **414** and the engaged sets of pin receptacles and connector pins, with the leading face **201** of the removable battery assembly **200** resting on the bottom surface **134** of the battery receiving space **130**.

(96) FIG. **30** depicts a plurality of display screens that may be displayed on an on board battery display **280** of the removable battery assembly **200**. Battery errors such as, for example, communication errors, input/output errors, and/or battery errors, may be detected, as discussed in more detail herein, and an associated error message may be displayed on the battery display **280** to alert an operator. Further, a status of the charge of the intelligent battery may be shown on the battery display **280** when coupled to or removed from the materials handling vehicle **100**. As such, the battery display **280** may be configured to show one or more operation status display screens **282**, one or more charging status display screens **284**, one or more standalone battery screens **286**, and/or one or more error display screens associated with each status. Operation status may illustrate a vehicle start-up display, such as a logo, a vehicle standby display including battery charge and vehicle run life, or a blinking display when the battery charge is under a threshold, such as 10%, such that a low energy icon may blink to indicate need to charge the battery. Charging status may illustrate a logo icon upon charging initiation and a charging icon that may blink upon the battery being charged. An error status may illustrate vehicle and battery error event codes detected.

(97) As a result, the battery display **280** may thus provide a joint display of battery information and vehicle information on the removable battery assembly **200** when the removable battery assembly **200** is connected to the vehicle **100**. A joint display is advantageous when using a battery that may be reused across a plurality of vehicles to show joint battery and vehicle information at a single location on the removable battery assembly **200** when the removable battery assembly **200** is connected to a specific vehicle.

(98) FIG. **31** is a circuit schematic illustrating complementary socket/connector pin assignments for

the battery coupling **350** of a battery powered materials handling vehicle **100** comprising a removable battery assembly **200**, according to embodiments of the present disclosure. In some embodiments, the set of electrically conductive pin receptacles **320** and the set of complementary electrically conductive connector pins **420** may be presented in the form of an eight pin configuration comprising, for example: positive and negative battery terminals B+/B-, a CANH signal pin for a CAN Bus High Signal, a CANL signal pin for a CAN Bus Low Signal, a SIG1 signal pin for a battery discharge start signal, a SIG2 signal pin for a battery charge start signal, a SIG3 signal pin for a discharge select signal, and a SIG4 signal pin for an Auxiliary Signal.

(99) In this manner, a discharge select signal can be initiated across the SIG3 signal pin by accessing, for example, a key switch, keypad, or RFID reader on the vehicle.

(100) Referring further to the schematic of FIG. **31**, it is noted that an emergency stop switch may be present and configured to stop providing power upon, for example, detection of one or more vehicle or battery errors as communicated between the CAN bus and the battery assembly **200**. It is further contemplated that the battery assembly **200** may receive a charging signal when connected to an AC charger and may be configured to check the charger CAN communication to detect any errors such that the battery may prevent charging should an error be detected until the error is corrected. If no error is detected, the battery may then be ready for charging. The battery may send out a charging request current to the charger via the CAN bus connection. The charger would receive the charging request current and transit the requested charging current to the battery. When the battery state of charge (SOC) reaches 100%, the battery may set the charging request current to zero to send out to the charger via the CAN bus to stop charging the battery.

(101) In the embodiment of FIG. **31**, a key switch feature is shown along with an on-board charger discharging scheme in which an on-board charger is configured to charge the battery assembly **200** as described above. In another embodiment of an external charger discharging scheme, the on-board charger may not be present, the SIG2 signal pin may be disconnected, and the battery assembly **200** may operate to be charged by an external charger.

(102) In yet another embodiment, a keypad and/or RFID component feature may be included as part of the circuit diagram for selection rather than the key switch feature. Similar to the embodiment of FIG. **31** showing an on-board charger discharging scheme, the keypad and/or RFID component feature may replace the key switch feature between the SIG1 signal pin and the negative battery terminal of the materials handling vehicle. In an embodiment with the keypad and/or RFID component feature and for an external charger discharging scheme, the on-board charger may not be present, the SIG2 signal pin may be disconnected, and the battery assembly **200** may operate to be charged by an external charger.

(103) The removable battery assembly **200** comprises an on board battery display **280** and battery controller **290**, both of which reside with the removable battery assembly **200** and communicate with the vehicle side electronics via the battery coupling **350**, which comprises the battery-side electrical socket **300** of the battery assembly **200** and the vehicle-side electrical connector **400**. The battery controller **290** of the battery assembly **200** is configured to exchange information with a vehicle controller **170** across the battery coupling, which includes the multi-pin configuration described above.

(104) The battery controller **290** may include a printed/protection circuit board (PCB) including a battery management system (BMS) as an intelligent battery feature. The BMS may provide battery information to the battery as well as to the vehicle when the battery is electrically coupled to the vehicle to safely manage the battery and prolong battery life. The vehicle controller **170** may provide vehicle information (speed, vehicle running hours such as over the life of the vehicle, vehicle errors, etc.) to the battery display **280**, which is communicatively coupled to the PCB when the battery **200** is coupled to the vehicle **100** via the battery coupling **350**. Such errors may include errors indicated by a vehicle safety standard, as indicated via the vehicle controller **170**, such as communication errors, input/output errors, and/or battery errors. The vehicle errors may be

associated with vehicle fault codes such as warning errors that warn of an error without affecting vehicle operation and alarm errors that result in the vehicle controller **170** taking an action based on the error. The vehicle controller **170** may transmit vehicle information to the BMS via the CAN bus, and the BMS may transmit this information to the battery display via an internal circuit of the BMS.

(105) Battery errors, such as those discussed herein with reference to FIG. **30**, may be transmitted to the vehicle controller **170** for the vehicle controller **170** to take an action, e.g., limiting vehicle speed based on a battery error, to avoid further influence of the battery error on vehicle operation. The vehicle controller **170** may also report these errors for display on the battery display **280**. The vehicle controller **170** may further detect a CAN communication error from the battery **200** and send out an associated error message to the battery **200** for display on the battery display **280**.

(106) It should be appreciated that the display of vehicle and battery information on a battery display **280** is enabled by the reliable electrical coupling that occurs across the battery coupling **350**, which coupling ensures reliable transmission of vehicle information to the battery display **280**. Components of the battery assembly **200**, including components of the battery-side electrical socket **300**, and portions of the battery body **210**, and the battery receiving space **130**, as described above are designed to include tapered engagement surfaces that become progressively more engaged under weight of the battery assembly **200**.

(107) It is noted that recitations herein of a component of the present disclosure being “configured” in a particular way, to embody a particular property, or to function in a particular manner, are structural recitations, as opposed to recitations of intended use. More specifically, the references herein to the manner in which a component is “configured” denotes an existing physical condition of the component and, as such, is to be taken as a definite recitation of the structural characteristics of the component.

(108) For the purposes of describing and defining the present invention it is noted that the terms “about” and “approximately” are utilized herein to represent the inherent degree of uncertainty that may be attributed to any quantitative comparison, value, measurement, or other representation. The terms “about” and “approximately” are also utilized herein to represent the degree by which a quantitative representation may vary from a stated reference without resulting in a change in the basic function of the subject matter at issue.

(109) Having described the subject matter of the present disclosure in detail and by reference to specific embodiments thereof, it is noted that the various details disclosed herein should not be taken to imply that these details relate to elements that are essential components of the various embodiments described herein, even in cases where a particular element is illustrated in each of the drawings that accompany the present description. Further, it will be apparent that modifications and variations are possible without departing from the scope of the present disclosure, including, but not limited to, embodiments defined in the appended claims. More specifically, although some aspects of the present disclosure are identified herein as preferred or particularly advantageous, it is contemplated that the present disclosure is not necessarily limited to these aspects.

(110) It is noted that one or more of the following claims utilize the term “wherein” as a transitional phrase. For the purposes of defining the present invention, it is noted that this term is introduced in the claims as an open-ended transitional phrase that is used to introduce a recitation of a series of characteristics of the structure and should be interpreted in like manner as the more commonly used open-ended preamble term “comprising.”

Claims

1. A materials handling vehicle comprising a materials handling mechanism, a drive mechanism, a battery receiving space, and a removable battery assembly, wherein: the materials handling mechanism is configured to engage goods in a warehouse environment and cooperates with the

drive mechanism, under power from the removable battery assembly, to move goods along an inventory transit surface in the warehouse environment; the removable battery assembly and the battery receiving space cooperate to define a battery insertion and removal axis along which the removable battery assembly is inserted into and removed from the battery receiving space; the battery receiving space comprises a battery guide pin arranged on each opposite side of the battery receiving space; the removable battery assembly comprises a battery body comprising lateral battery faces, each comprising a longitudinal guide structure that is oriented along the battery insertion and removal axis and is sized to accommodate the battery guide pins as the removable battery assembly is inserted into and removed from the battery receiving space; and the removable battery assembly further comprises a pair of guide pin stabilizers on each of the lateral battery faces, each pair of guide pin stabilizers forms a restricted-width guide pin gap along a longitudinal guide structure on each of the lateral battery faces for receiving a corresponding one of the battery guide pins, the longitudinal guide structure of the lateral battery faces are configured as guide channels, each guide pin stabilizer reducing an effective width of the guide channel.

2. The materials handling vehicle of claim 1, wherein each pair of guide pin stabilizers is formed from a deformable and resilient material.
3. The materials handling vehicle of claim 1, wherein each pair of guide pin stabilizers is formed as a unitary, one piece polyurethane structure.
4. The materials handling vehicle of claim 1, wherein each pair of guide pin stabilizers is configured to deform in a lateral direction perpendicular to the battery insertion and removal axis when a battery guide pin enters the restricted-width guide pin gap.
5. The materials handling vehicle of claim 1, wherein each pair of guide pin stabilizers has a Shore A hardness between 50 Shore A and 90 Shore A.
6. The materials handling vehicle of claim 1, wherein each pair of guide pin stabilizers has a Shore A hardness between 60 Shore A and 80 Shore A.
7. The materials handling vehicle of claim 1, further comprising a fastener, wherein the fastener extends through each pair of guide pin stabilizers and threadedly engages the lateral battery face of the battery body.
8. The materials handling vehicle of claim 1, wherein each pair of guide pin stabilizers comprises an alignment feature received within a corresponding slot formed in one of the lateral battery faces, to prevent rotation of each pair of guide pin stabilizers relative to the lateral battery faces.
9. The materials handling vehicle of claim 1, wherein: the battery guide pins extend into the guide channels with the removable battery assembly seated in the battery receiving space.
10. The materials handling vehicle of claim 1, wherein: the guide pin stabilizers reside at a guiding pin parking position along the longitudinal guide structure on each of the lateral battery faces, with the removable battery assembly seated in the battery receiving space; and the restricted-width guide pin gap formed by each pair of guide pin stabilizers at least partially overlaps the guiding pin parking position along the longitudinal guide structure on each of the lateral battery faces.
11. The materials handling vehicle of claim 1, wherein the battery guide pins have respective diameters that are greater than a width of the restricted-width guide pin gap.
12. The materials handling vehicle of claim 1, wherein the guide pin stabilizers are configured to at least partially yield in a lateral yielding direction perpendicular to the battery insertion and removal axis, and to maintain a degree of lateral resilience, when a guide pin enters the restricted-width guide pin gap.
13. The materials handling vehicle of claim 1, wherein: each pair of guide pin stabilizers extends partially into or partially over one of the guide channels to reduce the effective width of the guide channel.
14. The materials handling vehicle of claim 1, wherein: each pair of guide pin stabilizers comprises a truncated portion.
15. The materials handling vehicle of claim 1, wherein: the battery receiving space comprises

opposing pairs of battery guide pins, each opposing pair arranged on opposite sides of the battery receiving space, and each opposing pair comprising a latching pin and a guiding pin; the removable battery assembly comprises a battery body and a battery locking mechanism; the battery locking mechanism comprises spring-loaded locking pins that are spring-biased in extended positions and are movable relative to the battery body from the extended positions to respective retracted positions along a latch engagement and disengagement axis; the latching pin of each opposing pair of battery guide pins comprises a recess forming a battery latch that is positioned to receive a leading portion of one of the spring-loaded locking pins in the extended position, with the removable battery assembly seated in the battery receiving space.

16. A materials handling vehicle comprising a materials handling mechanism, a drive mechanism, a battery receiving space, and a removable battery assembly, wherein: the materials handling mechanism is configured to engage goods in a warehouse environment and cooperates with the drive mechanism, under power from the removable battery assembly, to move goods along an inventory transit surface in the warehouse environment; the removable battery assembly and the battery receiving space cooperate to define a battery insertion and removal axis along which the removable battery assembly is inserted into and removed from the battery receiving space; the battery receiving space comprises opposing pairs of battery guide pins, each opposing pair arranged on opposite sides of the battery receiving space, and each opposing pair comprising a latching pin and a guiding pin; the removable battery assembly comprises a battery body and a battery locking mechanism; the battery body comprises lateral battery faces, each comprising a longitudinal guide structure that is oriented along the battery insertion and removal axis and is sized to accommodate the opposing pairs of battery guide pins as the removable battery assembly is inserted into and removed from the battery receiving space; the battery locking mechanism comprises spring-loaded locking pins that are spring-biased in extended positions and are movable relative to the battery body from the extended positions to respective retracted positions along a latch engagement and disengagement axis; and the latching pin of each opposing pair of battery guide pins comprises a recess forming a battery latch that is positioned to receive a leading portion of one of the spring-loaded locking pins in the extended position, with the removable battery assembly seated in the battery receiving space.

17. The materials handling vehicle of claim 16, wherein: the latching pin of each opposing pair of battery guide pins comprises a chamfered engagement face; and the spring-loaded locking pins of the battery locking mechanism each comprise a complementary chamfered engagement face that is oriented to face the chamfered engagement face of one of the latching pins as the removable battery assembly is inserted into the battery receiving space.

18. The materials handling vehicle of claim 17, wherein the chamfered engagement face of each latching pin leads to the recess forming the battery latch of each latching pin.

19. The materials handling vehicle of claim 16, wherein the latching pin and the guiding pin of each opposing pair of battery guide pins are positioned along a common guide pin axis, parallel to the battery insertion and removal axis.

20. The materials handling vehicle of claim 16, wherein the latching pin and the guiding pin of each opposing pair of battery guide pins are separated by a guide pin spacing that is less than half of a longitudinal dimension of the lateral battery faces, and is at least about 47.5 mm.

21. The materials handling vehicle of claim 16, wherein: the longitudinal guide structure of the lateral battery faces is configured as guide channels; and the opposing pairs of battery guide pins extend into the guide channels with the removable battery assembly seated in the battery receiving space.

22. The materials handling vehicle of claim 16, wherein the longitudinal guide structure of one of the lateral battery faces is shorter than the longitudinal guide structure of the other lateral battery face, to create free space along one of the lateral battery faces.

23. The materials handling vehicle of claim 16, wherein: the removable battery assembly further

comprises a pair of guide pin stabilizers on each of the lateral battery faces; each pair of guide pin stabilizers forms a restricted-width guide pin gap along the longitudinal guide structure on each of the lateral battery faces.

24. The materials handling vehicle of claim 23, wherein: the guiding pin of each opposing pair of battery guide pins resides at a guiding pin parking position along the longitudinal guide structure on each of the lateral battery faces, with the removable battery assembly seated in the battery receiving space; the restricted-width guide pin gap formed by each pair of guide pin stabilizers at least partially overlaps the guiding pin parking position along the longitudinal guide structure on each of the lateral battery faces.

25. The materials handling vehicle of claim 23, wherein the guide pin stabilizers are configured to yield in a lateral yielding direction perpendicular to the battery insertion and removal axis, and to maintain a degree of lateral resilience, when a guiding pin enters the restricted-width guide pin gap.

26. The materials handling vehicle of claim 23, wherein: the longitudinal guide structure of the lateral battery faces are configured as guide channels; and each guide pin stabilizer comprises a stabilizer shank that is anchored in the battery body and a stabilizer cap that extends partially into or partially over one of the guide channels to reduce an effective width of the guide channel.

27. The materials handling vehicle of claim 16, wherein: the battery locking mechanism comprises a spring-loaded battery handle; the spring-loaded battery handle comprises a planar handle cam surface and the spring-loaded locking pin comprises a planar pin cam surface that is parallel to the handle cam surface; and the spring-loaded battery handle and the spring-loaded locking pin are configured such that the handle cam surface engages the pin cam surface with movement of the battery handle, relative to the battery body, along the battery insertion and removal axis.

28. The materials handling vehicle of claim 27, wherein: the battery body constrains the spring-loaded battery handle and the handle cam surface to linear movement along the battery insertion and removal axis; the battery body constrains the spring-loaded locking pin and the pin cam surface to linear movement along a latch engagement and disengagement axis that is perpendicular to the battery insertion and removal axis; the spring-loaded battery handle is spring-biased in a locked position and is movable relative to the battery body from the locked position to an unlocked position in a handle lifting direction along the battery insertion and removal axis; and the spring-loaded locking pin is spring-biased in the extended position and is movable relative to the battery body from the extended position to a retracted position along the latch engagement and disengagement axis in response to movement of the battery handle, relative to the battery body, in the handle lifting direction with the handle cam surface engaged with the pin cam surface.

29. The materials handling vehicle of claim 16, wherein: the removable battery assembly comprises a leading face and an electrical socket on the leading face of the removable battery assembly; the battery receiving space comprises an electrical connector that complements the electrical socket of the removable battery assembly; and the spring-loaded locking pins are positioned at points along a longitudinal dimension of the battery body that results in locking pin engagement with the latching pins simultaneously with engagement of the electrical socket on the leading face of the removable battery assembly with the electrical connector in the battery receiving space, as the removable battery assembly is inserted into the battery receiving space, with the spring-loaded battery handle in the locked position.

30. The materials handling vehicle of claim 29, wherein the leading face of the removable battery assembly rests on a bottom surface of the battery receiving space with the spring-loaded locking pins engaged with the latching pins, and the electrical socket engaged with the electrical connector.

31. The materials handling vehicle of claim 16, wherein: the latching pin and the guiding pin of each opposing pair of battery guide pins are positioned along a common guide pin axis, parallel to the battery insertion and removal axis; the longitudinal guide structure of the lateral battery faces are configured as guide channels; and the opposing pairs of battery guide pins extend into the guide channels with the removable battery assembly seated in the battery receiving space.

32. The materials handling vehicle of claim 16, wherein: the longitudinal guide structure of the lateral battery faces are configured as guide channels; the opposing pairs of battery guide pins extend into the guide channels with the removable battery assembly seated in the battery receiving space; the removable battery assembly further comprises a pair of guide pin stabilizers on each of the lateral battery faces; and each pair of guide pin stabilizers forms a restricted-width guide pin gap along the guide channel on each of the lateral battery faces.

33. A materials handling vehicle configured to move along an inventory transit surface and engage goods in a warehouse environment, the materials handling vehicle comprising a battery receiving space, and a removable battery assembly, wherein: the removable battery assembly and the battery receiving space cooperate to define a battery insertion and removal axis; the battery receiving space comprises opposing pairs of battery guide pins, each opposing pair arranged on opposite sides of the battery receiving space, and each opposing pair comprising a latching pin and a guiding pin; the removable battery assembly comprises a battery body and a battery locking mechanism; the battery body comprises lateral battery faces, each comprising a longitudinal guide structure that is oriented along the battery insertion and removal axis; the battery locking mechanism comprises spring-loaded locking pins that are spring-biased in extended positions and are movable relative to the battery body from the extended positions to respective retracted positions along a latch engagement and disengagement axis; and the latching pin of each opposing pair of battery guide pins comprises a recess forming a battery latch that is positioned to receive a leading portion of one of the spring-loaded locking pins in the extended position, with the removable battery assembly seated in the battery receiving space.
