

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent
Kind Code
Date of Patent
Inventor(s)

12392730
B1
August 19, 2025
Brighton; Mark et al.

Systems and techniques for vehicle inspection and condition analysis

Abstract

Systems and techniques for inspecting vehicles, such as cars or trucks. Some embodiments provide a method for inspecting a vehicle using a vehicle inspection system. The vehicle inspection system may include a vehicle exterior inspection system having a plurality of exterior sensor arrays, the plurality of exterior sensor arrays including respective sets of sensors oriented in different directions. The vehicle inspection system may include a vehicle undercarriage inspection system having an undercarriage sensor array including cameras configured to capture images at different angles, and a sensor configured to output vehicle position/motion data. In some embodiments, the method includes: moving the vehicle and/or vehicle inspection system; triggering capture, by the exterior sensor arrays and undercarriage sensor array, of sensor data about the vehicle; capturing the sensor data; stopping capture of the sensor data; stopping movement of the vehicle and/or vehicle inspection system; and generating a vehicle condition report.

Inventors: Brighton; Mark (Buffalo, NY), Donnelly; Margaret (Buffalo, NY), Forte, III; Livio (Lloyd Harbor, NY), Giegerich; William (Buffalo, NY), Pollina; Frank (Pendleton, NY), Schneider; Philip (Amherst, NY), Shetty; Prajwal Shubhodaya (Buffalo, NY)

Applicant: ACV Auctions Inc. (Buffalo, NY)

Family ID: 1000008408429

Assignee: ACV Auctions Inc. (Buffalo, NY)

Appl. No.: 19/009882

Filed: January 03, 2025

Related U.S. Application Data

us-provisional-application US 63689539 20240830

Publication Classification

Int. Cl.: G06V10/12 (20220101); G01N21/88 (20060101); G06T7/00 (20170101); G07C5/08 (20060101)

U.S. Cl.:

CPC G01N21/8851 (20130101); G06T7/0002 (20130101); G06V10/12 (20220101); G07C5/0808 (20130101); G06T2207/30248 (20130101); G06V2201/08 (20220101)

Field of Classification Search

CPC: G06V (2201/08); G06V (10/12); G07C (5/006); G07C (5/0808); G06T (7/0002); G01N (21/8851)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6369849	12/2001	Rzyski	N/A	N/A
6661516	12/2002	Dietsch et al.	N/A	N/A
6856344	12/2004	Franz	N/A	N/A
7349007	12/2007	Millar	348/148	H04N 7/18
7359042	12/2007	Ovadia	N/A	N/A
8006559	12/2010	Mian et al.	N/A	N/A
8155384	12/2011	Chew	N/A	N/A
8230362	12/2011	Couch	N/A	N/A
8305442	12/2011	Millar	N/A	N/A
8358343	12/2012	Millar	N/A	N/A
8594979	12/2012	Icove et al.	N/A	N/A
8817098	12/2013	Millar	N/A	N/A
9244133	12/2015	Icove et al.	N/A	N/A
9599537	12/2016	DeAscanis et al.	N/A	N/A
9648256	12/2016	Ramsey et al.	N/A	N/A
9649990	12/2016	Hoellmann et al.	N/A	N/A
10346969	12/2018	Raghu et al.	N/A	N/A
10410182	12/2018	Tang et al.	N/A	N/A
10497108	12/2018	Knuffman et al.	N/A	N/A
10825097	12/2019	Knuffman et al.	N/A	N/A
10893213	12/2020	Magnuszewski et al.	N/A	N/A
11196965	12/2020	Hansen	N/A	G06T 5/20
11770493	12/2022	Carolus et al.	N/A	N/A
12140501	12/2023	Hever et al.	N/A	N/A
2003/0185340	12/2002	Frantz	N/A	N/A
2004/0057042	12/2003	Ovadia	N/A	N/A
2004/0165750	12/2003	Chew	382/105	G08B 13/19697
2004/0199785	12/2003	Pederson	N/A	N/A

2006/0170768	12/2005	Riley	N/A	N/A
2006/0262190	12/2005	Millar	N/A	N/A
2007/0030349	12/2006	Riley	348/143	H04N 7/181
2007/0040911	12/2006	Riley	N/A	N/A
2007/0273760	12/2006	Morrison et al.	N/A	N/A
2008/0136625	12/2007	Chew	N/A	N/A
2008/0292211	12/2007	Frantz	N/A	N/A
2009/0033744	12/2008	Frantz	N/A	N/A
2011/0098056	12/2010	Rhoads et al.	N/A	N/A
2014/0036082	12/2013	Hoellmann et al.	N/A	N/A
2014/0313334	12/2013	Slotky	N/A	N/A
2015/0331113	12/2014	Stettner et al.	N/A	N/A
2016/0090132	12/2015	Ramsey et al.	N/A	N/A
2017/0180611	12/2016	Arcaini et al.	N/A	N/A
2018/0035606	12/2017	Burdoucci	N/A	N/A
2019/0204184	12/2018	Neumann	N/A	G01M 17/00
2019/0304099	12/2018	Hever et al.	N/A	N/A
2019/0304100	12/2018	Hever et al.	N/A	N/A
2020/0175352	12/2019	Cha et al.	N/A	N/A
2020/0322545	12/2019	Magnuszewski et al.	N/A	N/A
2020/0322546	12/2019	Carolus et al.	N/A	N/A
2021/0018426	12/2020	Amer et al.	N/A	N/A
2021/0090242	12/2020	Hever et al.	N/A	N/A
2021/0174117	12/2020	Hever et al.	N/A	N/A
2021/0358115	12/2020	Hever et al.	N/A	N/A
2021/0390720	12/2020	Dmitriev	N/A	N/A
2022/0051391	12/2021	Bogomolny et al.	N/A	N/A
2022/0097463	12/2021	Shklyar et al.	N/A	N/A
2022/0101512	12/2021	Grossman et al.	N/A	N/A
2023/0342937	12/2022	Hever et al.	N/A	N/A
2023/0388442	12/2022	Carolus et al.	N/A	N/A
2024/0351705	12/2023	Ferry et al.	N/A	N/A
2024/0404041	12/2023	Hever et al.	N/A	N/A
2025/0063131	12/2024	Carolus et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2011-255033	12/2010	JP	N/A
10-1630596	12/2015	KR	N/A
WO 2004/061771	12/2003	WO	N/A
WO 2006/059998	12/2005	WO	N/A
WO 2006/091874	12/2005	WO	N/A
WO 2012/103999	12/2011	WO	N/A
WO 2013/178460	12/2012	WO	N/A
WO 2020/250220	12/2019	WO	N/A

OTHER PUBLICATIONS

Frederick Chong Chuen Kiong, "Vehicle Undercarriage Scanning System", Oct. 27, 2005 (Year: 2005). cited by examiner
Al-in-One, "UnderCarriage Photography" Jun. 7, 2023 <https://www.youtube.com/watch?v=dSejeRA5e0> (Year: 2023). cited by examiner
International Search Report and Written Opinion for International Application No. PCT/US2020/026417 mailed Jul. 31, 2020. cited by applicant
Extended European Search Report for European Application No. 20784941.5 dated Nov. 22, 2022. cited by applicant
Dickson et al., Mosaic generation for under vehicle inspection. Proceedings of the Sixth IEEE Workshop on Applications of Computer Vision (WACV 2002). Dec. 2002, 6 pages. cited by applicant
Kasch et al., Design and Operational Assessment of a Railroad Track Robot for Railcar Undercarriage Condition Inspection. Designs. Jul. 10, 2024;8(4):70. 31 pages. cited by applicant
Ross et al., VUIR: A Vehicle Undercarriage Inspection Robot. Recent Advances in Robotics and Automation. Berlin, Heidelberg: Springer Berlin Heidelberg. 2013, pp. 183-192. cited by applicant
Ruiz et al., Use of an automatic under-vehicle inspection system as a tool to streamline vehicle screening at ports of entry and security checkpoints. 2012 European Intelligence and Security Informatics Conference. Aug. 22, 2012:329-33. cited by applicant
U.S. Appl. No. 18/935,278, filed Nov. 1, 2024, Carolus et al. cited by applicant
U.S. Appl. No. 19/009,893, filed Jan. 3, 2025, Brighton et al. cited by applicant
U.S. Appl. No. 19/009,900, filed Jan. 3, 2025, Brighton et al. cited by applicant
PCT/US2020/026417, Jul. 31, 2020, International Search Report and Written Opinion. cited by applicant
20784941.5, Nov. 22, 2022, Extended European Search Report. cited by applicant

Primary Examiner: Smith; Maurice C

Attorney, Agent or Firm: Wolf, Greenfield & Sacks, P.C.

Background/Summary

RELATED APPLICATIONS (1) This application claims priority under 35 U.S.C. § 119(e) to U.S. Provisional Application No. 63/689,539, filed on Aug. 30, 2024, entitled "SYSTEMS AND TECHNIQUES FOR VEHICLE INSPECTION AND CONDITION ANALYSIS", which is herein incorporated by reference in its entirety.

FIELD

(1) This disclosure relates to vehicle inspection systems.

BACKGROUND

(2) Vehicles are often bought and sold multiple times throughout their lifetimes. Vehicles can be bought and sold in person, online in a virtual sales environment, and/or at auctions, which may take place in person or online over the Internet. Because of the large volume of vehicles sold at auctions, it is often not possible for buyers to inspect vehicles in person, let alone have the vehicles inspected by qualified mechanics. Buyers often rely on auction houses or third-party inspection services to provide information about the vehicle upon which purchasing decisions may be made. Such information about a vehicle may be provided, in electronic form, as a part of a vehicle condition report. The value of a vehicle condition report depends on the accuracy and completeness of the data it contains. Vehicle condition reports contain information about many different parts of

vehicles, and it is difficult to obtain this information accurately and efficiently when inspecting a vehicle.

SUMMARY

(3) Some embodiments provide for a vehicle inspection system for inspecting a vehicle, the system comprising: a vehicle exterior inspection system comprising: a first support member; a first sensor array coupled to the first support member and comprising a first set of cameras positioned to capture images of wheels of the vehicle being imaged; a second sensor array coupled to the first support member and comprising a second set of cameras positioned to capture images of a side of the vehicle being imaged; and a third sensor array coupled to the first support member and comprising a third set of cameras positioned to capture images of a roof of the vehicle being imaged; and a vehicle undercarriage inspection system comprising: a base having a width and a depth respectively extending along first and second directions orthogonal to one another, the width extending from a first end of the base to a second end of the base, the base supporting a fourth sensor array configured to capture images of an undercarriage of the vehicle, wherein the fourth sensor array comprises: a first camera positioned at a first side of the base, and oriented towards the first side of the base; a second camera positioned at a second side of the base, and oriented towards the second side of the base; and a third camera positioned between the first and second cameras, wherein the vehicle inspection system is configured to: capture a first plurality of images of the vehicle using the first, second and third sets of cameras of the vehicle exterior inspection system; and capture a second plurality of images of the undercarriage of the vehicle using the fourth sensor array of the vehicle undercarriage inspection system.

(4) In some embodiments, the vehicle inspection system further comprises a computer hardware processor configured to: when the vehicle is moved relative to the vehicle exterior inspection system and the vehicle undercarriage inspection system: triggering the capture of the first plurality of images of the vehicle using the first, second and third sets of cameras of the vehicle exterior inspection system, receiving the first plurality of images, and/or processing the first plurality of images; and triggering the capture of a second plurality of images of the undercarriage of the vehicle using the fourth sensor array of the vehicle undercarriage inspection system, receiving the second plurality of images, and/or processing the second plurality of images.

(5) In some embodiments, the vehicle inspection system is configured to trigger the capture the first and second plurality of images based on a position of the vehicle.

(6) In some embodiments, the vehicle undercarriage inspection system further comprises: a sensor configured to output data indicative of the position and/or motion of the vehicle relative to the vehicle inspection system, wherein the capturing of the first plurality of images is performed in response to determining the vehicle is at a first position and/or first distance relative to the vehicle inspection system, based on the data indicative of the position and/or motion of the vehicle.

(7) In some embodiments, the capturing of the second plurality of images is performed in response to determining the vehicle is at a second position and/or distance relative to the vehicle inspection system, different from the first position, based on the data indicative of the position and/or motion of the vehicle.

(8) In some embodiments, the second position is closer to the vehicle inspection system than the first position, and/or the first distance is smaller than the second distance.

(9) In some embodiments, the computer hardware processor is further configured to perform: stopping the capturing of the first plurality of images in response to determining the vehicle is at a third position and/or distance relative to the vehicle inspection system, different from the first and second positions and/or distances, based on the data indicative of the position and/or motion of the vehicle; and stopping the capturing of the second plurality of images in response to determining the vehicle is at a fourth position and/or distance relative to the vehicle inspection system, different from the first, second and third positions and/or distances, based on the data indicative of the position and/or motion of the vehicle.

(10) In some embodiments, the vehicle exterior inspection system further comprises: a second support member; a fourth sensor array coupled to the second support member and comprising a fourth set of cameras positioned to capture images of wheels of the vehicle being imaged; a fifth sensor array coupled to the second support member and comprising a fifth set of cameras positioned to capture images of a side of the vehicle being imaged; and a sixth sensor array coupled to the second support member and comprising a sixth set of cameras positioned to capture images of a roof of the vehicle being imaged.

(11) In some embodiments, the vehicle exterior inspection system is portable and is collapsible between a deployed and a stowed configuration, and is configured to image the vehicle when in the deployed configuration, and the vehicle undercarriage inspection system weighs less than 10 pounds, and further comprises a handle attached to the base for lifting the vehicle undercarriage inspection system.

(12) In some embodiments, one or more of the first, second, third and fourth sensor arrays comprise one or more of: a microphone, an infrared camera, a thermal camera, a magnetometer, a time of flight sensor, a light source, and/or an air quality sensor.

(13) In some embodiments, the first, second, and third sensor arrays are configured such that a combined FOV of the first, second and third sets of cameras spans at least 150 inches in height, 300 inches in length and 120 inches in width.

(14) Some embodiments provide for a vehicle inspection system for analyzing condition of a vehicle, the system comprising: a vehicle exterior inspection system comprising: a first support member; a first sensor array coupled to the first support member and comprising a first set of cameras positioned to capture images of wheels of the vehicle being imaged; a second sensor array coupled to the first support member and comprising a second set of cameras positioned to capture images of a side of the vehicle being imaged; and a third sensor array coupled to the first support member and comprising a third set of cameras positioned to capture images of a roof of the vehicle being imaged; a vehicle undercarriage inspection system comprising: a base having a width and a depth respectively extending along first and second directions orthogonal to one another, the width extending from a first end of the base to a second end of the base, the base supporting a fourth sensor array configured to capture images of an undercarriage of the vehicle, wherein the fourth sensor array comprises: a first camera positioned at a first side of the base, and oriented towards the first side of the base; a second camera positioned at a second side of the base, and oriented towards the second side of the base; and a third camera positioned between the first and second cameras; and a computer hardware processor configured to perform: obtaining a first plurality of images of the vehicle captured using the first, second and third sets of cameras of the vehicle exterior inspection system; obtaining a second plurality of images of the undercarriage of the vehicle captured using the fourth sensor array of the vehicle undercarriage inspection system; processing images of the first and second pluralities of images, using at least one trained machine learning (ML) model, to determine whether the vehicle has one or more defects; and generating a vehicle condition report based on results of the processing of the images of the first plurality of images and the second plurality of images.

(15) In some embodiments, the computer hardware processor is further configured to perform: generating a composite image of the undercarriage of the vehicle by combining images of the second plurality of images, wherein the composite image is processed using the at least one machine learning model to determine whether the vehicle has the one or more defects.

(16) In some embodiments, the one or more defects include: scratches to an exterior of the vehicle; cracked windows, mirrors, or windshields, chipped paint, dents to the exterior of the vehicle, misaligned body panels, missing vehicle parts, non-standard replacement parts, non-standard paint, aftermarket vehicle accessories, rust/corrosion on the vehicle, damaged wheels, damaged tires, bald tires, tire sidewall bubbles, broken tire valves, wheel misalignment, mismatched tires, brake rotor discoloration, brake rotor damage, brake rotor wear, a missing catalytic converter and/or

suspension modifications.

(17) In some embodiments, the computer hardware processor is further configured to perform: generating a 3D model of the of the vehicle based on the first and second pluralities of images; generating a visualization of the 3D model; and providing access to the visualization to one or more users.

(18) In some embodiments, the computer hardware processor is further configured to perform: before processing the images of the first plurality of images, identifying a subset of the first plurality of images based on a pose of the vehicle in images of the plurality of images, wherein processing the images of the first plurality of images comprises processing the subset of images.

(19) In some embodiments, the vehicle undercarriage imaging system further comprises a sensor configured to output data indicative of the position and/or motion of the vehicle relative to the vehicle undercarriage inspection system; and generating the composite image is performed based on the data indicative of the position and/or motion of the vehicle.

(20) In some embodiments, one or more of the first, second, third and fourth sensor arrays comprise one or more of: a microphone, an infrared camera, a thermal camera, a magnetometer, a time of flight sensor, a light source, and/or an air quality sensor.

(21) In some embodiments, obtaining the first plurality of images comprises capturing the first plurality of images of the vehicle using the first, second and third sets of cameras of the vehicle exterior inspection system; and obtaining the second plurality of images comprises capturing the second plurality of images of the undercarriage of the vehicle using the fourth sensor array of the vehicle undercarriage inspection system.

(22) Some embodiments provide for a vehicle inspection system, for inspecting a vehicle, the vehicle inspection system comprising: a vehicle exterior inspection system comprising: a first support member comprising a first portion and a second portion angled relative to the first portion; and a first plurality of sensor arrays coupled to the first support member, the first plurality of sensor arrays comprising: a first sensor array comprising a first set of cameras oriented in multiple first directions, the first sensor array being coupled to the first support member at a position at which the first set of cameras has one or more wheels of a vehicle in its field of view (FOV) when the first sensor array is being used to image the vehicle; a second sensor array comprising a second set of cameras oriented in multiple second directions, the second sensor array being coupled to the first support member at a position at which the second set of cameras has a first side of the vehicle in its FOV when the second sensor array is being used to image the vehicle; and a third sensor array comprising a third set of cameras oriented in multiple third directions, the third sensor array being coupled to the first support member at a position at which the third set of cameras has a roof of the vehicle in its FOV when the third sensor array is being used to image the vehicle; and a vehicle undercarriage inspection system, comprising: a base having a width and a depth respectively extending along first and second directions orthogonal to one another, the width extending from a first end of the base to a second end of the base; and a fourth sensor array coupled to the base, the fourth sensor array comprising a set of cameras oriented in multiple directions, the set of cameras including: a first camera oriented in part towards the first end of the base; a second camera oriented in part towards the second end of the base; and a third camera positioned between the first and second cameras.

(23) Some embodiments provide for a method for inspecting a vehicle using a vehicle inspection system, the vehicle inspection system comprising a vehicle exterior inspection system comprising a support member and a plurality of exterior sensor arrays coupled to the support member, the plurality of exterior sensor arrays comprising respective sets of sensors oriented in different directions, and a vehicle undercarriage inspection system comprising an undercarriage sensor array comprising first, second and third cameras configured to capture images at different angles relative to the vehicle undercarriage, and a sensor configured to output data indicative of position and/or motion of the vehicle relative to the vehicle inspection system, the method comprising: moving the

vehicle and the vehicle inspection system relative to one another; triggering capture, by the plurality of exterior sensor arrays and undercarriage sensor array, of sensor data about the vehicle; capturing the sensor data about the vehicle using the plurality of exterior sensor arrays and undercarriage sensor array of the vehicle inspection system; stopping capture of the sensor data about the vehicle; stopping movement of the vehicle and the vehicle inspection system relative to one another; and generating a vehicle condition report based on the sensor data collected using the plurality of exterior sensor arrays and the undercarriage sensor array.

(24) In some embodiments, the generating comprises generating the vehicle condition report using the vehicle inspection system.

(25) In some embodiments, the generating comprises: providing to a computer hardware processor, separate from the vehicle inspection system, at least some of the sensor data collected using the plurality of exterior sensor arrays and the undercarriage sensor array.

(26) In some embodiments, the triggering is performed by the vehicle inspection system based on the data indicative of the position and/or motion of the vehicle.

(27) In some embodiments, the triggering comprises: triggering capture of the sensor data by the plurality of exterior sensor arrays when the vehicle is determined to be at a first position and/or distance relative to the vehicle inspection system based on the data indicative of the position and/or motion of the vehicle.

(28) In some embodiments, the triggering comprises: triggering capture of the sensor data by the undercarriage sensor array when the vehicle is determined to be at a second position and/or a second distance relative to the vehicle inspection system, different from the first position, based on the data indicative of the position and/or motion of the vehicle.

(29) In some embodiments, the second position is closer to the vehicle inspection system than the first position, and/or the second distance is smaller than the first distance.

(30) In some embodiments, the stopping is performed by the vehicle inspection system based on the data indicative of the position and/or motion of the vehicle.

(31) In some embodiments, the method further comprises: before the moving, placing a mobile vehicle diagnostic device (MVDD) of the vehicle inspection system at an engine of the vehicle, wherein the triggering comprises triggering a sensor array of the MVDD of the vehicle inspection system to capture the sensor data about the engine of the vehicle and the capturing comprises using the MVDD to capture the sensor data about the engine of the vehicle.

(32) Some embodiments provide for a method for inspecting a vehicle using a vehicle inspection system, the vehicle inspection system comprising a vehicle exterior inspection system comprising a support member and a plurality of exterior sensor arrays coupled to the support member, the plurality of exterior sensor arrays comprising respective sets of sensors oriented in different directions, and a vehicle undercarriage inspection system comprising an undercarriage sensor array comprising first, second and third cameras configured to capture images at different angles relative to the vehicle undercarriage, and a sensor configured to output data indicative of position and/or motion of the vehicle relative to the vehicle undercarriage inspection system, the method comprising: moving the vehicle and the vehicle inspection system relative to one another; triggering capture, by the plurality of exterior sensor arrays and undercarriage sensor array, of sensor data about the vehicle; capturing the sensor data about the vehicle using the plurality of exterior sensor arrays and undercarriage sensor array of the vehicle inspection system; stopping capture of the sensor data about the vehicle; stopping movement of the vehicle and the vehicle inspection system relative to one another; and processing the sensor data, using a computer hardware processor, to identify one or more vehicle defects.

(33) In some embodiments, the triggering comprises: triggering capture of the sensor data by the plurality of exterior sensor arrays is performed when the vehicle is determined to be at a first position and/or distance relative to the vehicle inspection system based on the data indicative of the position and/or motion of the vehicle.

(34) In some embodiments, the triggering comprises: triggering capture of the sensor data by the undercarriage sensor array is performed when the vehicle is determined to be at a second position and/or distance relative to the vehicle inspection system, different from the first position, based on the data indicative of the position and/or motion of the vehicle.

(35) In some embodiments, the stopping is performed by the vehicle inspection system based the data indicative of the position and/or motion of the vehicle.

(36) In some embodiments, the method further comprises: before the moving, placing a mobile vehicle diagnostic device (MVDD) of the vehicle inspection system at an engine of the vehicle, wherein the triggering comprises triggering a sensor array of the MVDD of the vehicle inspection system to capture the sensor data about the engine of the vehicle and the capturing comprises using the MVDD to capture the sensor data about the engine of the vehicle.

(37) Some embodiments provide for a method for inspecting a vehicle using a vehicle inspection system, the vehicle inspection system comprising a vehicle exterior inspection system comprising a support member and a plurality of exterior sensor arrays coupled to the support member, the plurality of exterior sensor arrays comprising respective sets of sensors oriented in different directions, and a vehicle undercarriage inspection system comprising an undercarriage sensor array comprising first, second and third cameras configured to capture images at different angles relative to the vehicle undercarriage, and a sensor configured to output data indicative of position and/or motion of the vehicle relative to the vehicle inspection system, the method comprising: positioning the vehicle, the vehicle exterior inspections system and the vehicle undercarriage inspection system relative to one another; triggering the vehicle inspection system to collect alignment data of the vehicle relative to the vehicle inspection system; obtaining an indication of an alignment of the vehicle relative to the vehicle inspection system based on the alignment data; based on the indication of the alignment of the vehicle, adjusting one or more of the exterior sensor arrays or the undercarriage sensor array; moving the vehicle and the vehicle inspection system relative to one another; capturing sensor data about the vehicle using the plurality of exterior sensor arrays and undercarriage sensor array of the vehicle inspection system; and processing the sensor data, using a computer hardware processor, to identify one or more vehicle defects.

(38) In some embodiments, the alignment data is captured by the sensor of the vehicle undercarriage inspection system configured to output the data indicative of the position and/or motion of the vehicle.

(39) In some embodiments, the moving comprises driving the vehicle past the vehicle undercarriage inspection system and vehicle exterior inspection system. In some embodiments, the moving comprises moving the vehicle exterior and vehicle undercarriage inspection systems about the vehicle.

(40) In some embodiments, the method further comprises: before the moving, placing a mobile vehicle diagnostic device (MVDD) of the vehicle inspection system at an engine of the vehicle, wherein the triggering comprises triggering a sensor array of the MVDD of the vehicle inspection system to capture the sensor data about the engine of the vehicle and the capturing comprises using the MVDD to capture the sensor data about the engine of the vehicle.

(41) In some embodiments, the method further comprises: receiving an indication the capturing was unsuccessful; and recapturing second sensor data about the vehicle using the plurality of exterior sensor arrays and undercarriage sensor array of the vehicle inspection system.

(42) Some embodiments provide for a system for vehicle inspection, the system comprising: a first support member comprising a first portion and a second portion angled relative to the first portion; a first plurality of sensor arrays coupled to the first support member, the first plurality of sensor arrays comprising: a first sensor array comprising a first set of cameras oriented in multiple first directions, the first sensor array being coupled to the first support member at a position at which the first set of cameras has one or more wheels of a vehicle in its field of view (FOV) when the first sensor array is being used to image the vehicle; a second sensor array comprising a second set of

cameras oriented in multiple second directions, the second sensor array being coupled to the first support member at a position at which the second set of cameras has a first side of the vehicle in its FOV when the second sensor array is being used to image the vehicle; and a third sensor array comprising a third set of cameras oriented in multiple third directions, the third sensor array being coupled to the first support member at a position at which the third set of cameras has a roof of the vehicle in its FOV when the third sensor array is being used to image the vehicle; and a processor configured to control the first plurality of sensor arrays to capture images of the vehicle.

(43) In some embodiments, the first sensor array is positioned below the second and third sensor arrays on the first support member. In some embodiments, the second sensor array is positioned below the third sensor array on the first support member. In some embodiments, the first and second sensor arrays are positioned on the first portion of the first support member, and the third sensor array is positioned on the second portion of the first support member.

(44) In some embodiments, the first sensor array further comprises: a microphone, an infrared camera, a thermal camera, a magnetometer, a light source and/or an air quality sensor.

(45) In some embodiments, the system further comprises: a second support member comprising a third portion, and a fourth portion angled relative to the third portion; and a second plurality of sensor arrays coupled to the second support member, the second plurality of sensor arrays comprising: a fourth sensor array comprising a fourth set of cameras oriented in multiple fourth directions, the fourth sensor array being coupled to the second support member at a position at which the fourth set of cameras has one or more wheels of a vehicle in its FOV when the fourth sensor array is being used to image the vehicle; a fifth sensor array comprising a fifth set of cameras oriented in multiple fifth directions, the fifth sensor array being coupled to the second support member at a position at which the fifth set of cameras has a second side of the vehicle in its field of view when the fifth sensor array is being used to image the vehicle; and a sixth sensor array comprising a sixth set of cameras oriented in multiple sixth directions, the sixth sensor array being coupled to the second support member at a position at which the sixth set of cameras has the roof of the vehicle in its field of view when the sixth sensor array is being used to image the vehicle, wherein the processor is further configured to control the second plurality of sensor arrays capture images of the vehicle.

(46) In some embodiments, the first plurality of sensor arrays is configured such that a combined FOV of the first, second and third sets of cameras spans at least 150 inches in height, 300 inches in length and 120 inches in width.

(47) In some embodiments, during imaging the vehicle and the first support member move relative to one another along a first direction; the first set of cameras comprises: a first camera oriented in part towards the first direction; a second camera oriented in part opposite the first direction; and a third camera oriented substantially perpendicular to the first direction; the first camera has a rocker panel and wheels of the vehicle in its field of view when being used to image the vehicle; the second camera has the rocker panel and rear of the vehicle in its field of view when being used to image the vehicle; and the third camera has one or more wheels of the vehicle in its field of view when being used to image the vehicle.

(48) In some embodiments, during imaging the vehicle and the first support member move relative to one another along a first direction; the second set of cameras comprises: a first camera oriented in part towards the first direction; a second camera oriented in part opposite the first direction; and a third camera oriented substantially perpendicular to the first direction; the first camera has the side and front of the vehicle in its field of view when being used to image the vehicle; the second camera has the side and rear of the vehicle in its field of view when being used to image the vehicle; and the third camera has the side of the vehicle in its field of view when being used to image the vehicle.

(49) In some embodiments, during imaging the vehicle and the first support member move relative to one another along a first direction; the third set of cameras comprises: a first camera oriented in

part towards the first direction; a second camera oriented in part opposite the first direction; and a third camera oriented substantially perpendicular to the first direction; the first camera has the roof, front, and hood of the vehicle in its field of view when being used to image the vehicle; the second camera has the roof and rear of the vehicle in its field of view when being used to image the vehicle; and the third camera has the hood and the roof of the vehicle in its field of view when being used to image the vehicle.

(50) In some embodiments, the first support member is portable and is collapsible between a deployed and a stowed configuration, and the vehicle inspection system is configured to image the vehicle when the first support member is in the deployed configuration.

(51) In some embodiments, the processor is configured to control the first plurality of sensor arrays to image the vehicle as the vehicle is driven past the first support member. In some embodiments, the processor is configured to control the first support member to move about the vehicle, and the processor is configured to control the first plurality of sensor arrays to image the vehicle as the first support member moves about the vehicle.

(52) In some embodiments, the processor is further configured to process the images of the vehicle using at least one trained machine learning (ML) model, to determine whether the vehicle has one or more defects, wherein the one or more defects include: scratches to an exterior of the vehicle, cracked windows, mirrors, or windshields, chipped paint, dents to the exterior of the vehicle, misaligned body panels, missing vehicle parts, non-standard replacement parts, non-standard paint, aftermarket vehicle accessories, rust/corrosion on the vehicle, damaged wheels, damaged tires, bald tires, tire sidewall bubbles, broken tire valves, wheel misalignment, mismatched tires, brake rotor discoloration, brake rotor damage, brake rotor wear, and/or suspension modifications.

(53) In some embodiments, the system further comprises a vehicle undercarriage inspection system comprising a fourth sensor array configured to capture signals related to the undercarriage of the vehicle.

(54) Some embodiments provide for a system for vehicle inspection, the system comprising: a support member; a first plurality of sensor arrays coupled to the first support member, the first plurality of sensor arrays comprising: a first sensor array comprising a first set of cameras oriented in multiple first directions and a first microphone; a second sensor array comprising a second set of cameras oriented in multiple second directions and a second microphone; and a third sensor array comprising a third set of cameras oriented in multiple third directions, and a third microphone; and a processor configured to control the first plurality of sensor arrays to capture images and audio recordings of the vehicle.

(55) In some embodiments, during imaging the vehicle and support member move relative to one another along a first direction; and the first, second and third sets of cameras respectively comprise: a first camera oriented in part towards the first direction; a second camera oriented in part opposite the first direction; and a third camera oriented substantially perpendicular to the first direction.

(56) In some embodiments, the processor is further configured to process the images and/or audio of the vehicle using at least one trained machine learning (ML) model, to determine whether the vehicle has one or more defects, wherein the one or more defects include: scratches to an exterior of the vehicle; cracked windows, mirrors, or windshields; chipped paint; dents to the exterior of the vehicle; misaligned body panels; missing vehicle parts, non-standard replacement parts, non-standard paint; aftermarket vehicle accessories; rust/corrosion on the vehicle; damaged wheels; damaged tires; bald tires; tire sidewall bubbles; broken tire valves; wheel misalignment; mismatched tires; brake rotor discoloration; brake rotor damage; brake rotor wear; suspension modifications; engine damage; an exhaust leak; and/or transmission whine.

(57) Some embodiments provide for a system for vehicle inspection, the system comprising: a support member; a first plurality of sensor arrays coupled to the first support member, the first plurality of sensor arrays configured to capture signals about a vehicle as the vehicle and support member move relative to one another along a first direction, and comprising: a first sensor array

comprising a first set of cameras, the first sensor array coupled to the first support member at a position at which the first set of cameras has a first side of the vehicle in its FOV when the first sensor array is being used to image the vehicle, the first set of cameras comprising: a first camera oriented in part towards the first direction; a second camera oriented in part opposite the first direction; and a third camera oriented substantially perpendicular to the first direction; and a second sensor array comprising a second set of cameras, the first sensor array coupled to the first support member at a position at which the second set of cameras has a roof of the vehicle in its FOV when the second sensor array is being used to image the vehicle, the second set of cameras comprising: a fourth camera oriented in part towards the first direction; a fifth camera oriented in part opposite the first direction; and a sixth camera oriented substantially perpendicular to the first direction; and a processor configured to control the first plurality of sensor arrays to capture images of the vehicle.

(58) In some embodiments, the first camera has the side and front of the vehicle in its FOV when being used to image the vehicle; the second camera has the side and rear of the vehicle in its FOV when being used to image the vehicle; the third camera has the side of the vehicle in its FOV when being used to image the vehicle; the fourth camera has the roof, front, and hood of the vehicle in its FOV when being used to image the vehicle; the fifth camera has the roof and rear of the vehicle in its FOV when being used to image the vehicle; and the sixth camera has the hood and the roof of the vehicle in its FOV when being used to image the vehicle.

(59) Some embodiments provide for a method for analyzing condition of a vehicle from images of the vehicle collected by a vehicle inspection system, the vehicle inspection system comprising a plurality of sensor arrays comprising first, second and third sensor arrays comprising respective first, second, and third sets of cameras, the method comprising: using at least one computer hardware processor to perform: obtaining a plurality of images using the vehicle inspection system, the plurality of images including first, second, and third sets of images captured, respectively, by the first, second, and third sets of cameras; identifying a subset of the plurality of images for subsequent processing to identify whether the vehicle has one or more defects, wherein the identifying is performed based on a pose of the vehicle in images of the plurality of images; processing the subset of the plurality of images, using at least one trained machine learning (ML) model, to determine whether the vehicle has the one or more defects; and generating a vehicle condition report based on results of the processing, the vehicle condition report including an indication of the one or more defects in the plurality of images.

(60) In some embodiments, the obtaining comprises controlling the plurality of sensor arrays of the vehicle inspection system to capture the plurality of images of the vehicle.

(61) In some embodiments, the controlling comprises: controlling the first set of cameras to capture images of one or more wheels of the vehicle; controlling the second set of cameras to capture images of a first side of the vehicle; and controlling the third set of cameras to capture images of a roof of the vehicle.

(62) In some embodiments, the method further comprises: generating a 3D model of the vehicle using at least some of the plurality of images; generating a visualization of the 3D model; and providing access to the visualization to one or more users.

(63) In some embodiments, the 3D model is generated using photogrammetry, neural radiance fields, or Gaussian splatting.

(64) In some embodiments, the method further comprises: identifying, from among the plurality of images, an image containing personally identifiable information (PII); identifying a region of the image containing the PII; and distorting the region of the image containing the PII, wherein the vehicle condition report includes the image.

(65) In some embodiments, the one or more defects include: scratches to an exterior of the vehicle, cracked windows, mirrors, or windshields, chipped paint, dents to the exterior of the vehicle, misaligned body panels, missing vehicle parts, non-standard replacement parts, non-standard paint,

aftermarket vehicle accessories, rust/corrosion on the vehicle, damaged wheels, damaged tires, bald tires, tire sidewall bubbles, broken tire valves, wheel misalignment, mismatched tires, brake rotor discoloration, brake rotor damage, brake rotor wear, and/or suspension modifications.

(66) In some embodiments, the vehicle inspection system further comprises a vehicle undercarriage inspection system; and the plurality of images includes a fourth set of images of an undercarriage of the vehicle captured by the vehicle undercarriage inspection system.

(67) In some embodiments, identifying the subset of the plurality of images for subsequent processing comprises: determining a degree of matching between the pose of the vehicle in images of the plurality of images and vehicle poses of a reference set of vehicle poses; and for each vehicle pose of the reference set of vehicle poses, identifying an image in the plurality of images having at least a threshold degree of matching and including the identified image in the subset of the plurality of images.

(68) In some embodiments, determining the degree of matching between the pose of the vehicle in the images of the plurality of images and vehicle poses of the reference set of vehicle poses comprises: determining a distance between a center of a bounding box of the vehicle in an image and the center of the image.

(69) In some embodiments, the set of vehicle poses includes poses associated with the cameras of the first, second and third sets of cameras.

(70) Some embodiments provide for a vehicle inspection system comprising: a plurality of sensor arrays comprising first, second and third sensor arrays comprising respective first, second, and third sets of cameras; and a computer hardware processor configured to perform: obtaining a plurality of images, the plurality of images including first, second, and third sets of images captured, respectively, by the first, second, and third sets of cameras; identifying a subset of the plurality of images for subsequent processing to identify whether the vehicle has one or more defects, wherein the identifying is performed based on a pose of the vehicle in images of the plurality of images; processing the subset of the plurality of images, using at least one trained machine learning (ML) model, to determine whether the vehicle has the one or more defects; and generating a vehicle condition report based on results of the processing, the vehicle condition report including an indication of the one or more defects in the plurality of images.

(71) In some embodiments, the obtaining comprises controlling the plurality of sensor arrays of the vehicle inspection system to capture the plurality of images of the vehicle.

(72) In some embodiments, the controlling comprises: controlling the first set of cameras to capture images of one or more wheels of the vehicle; controlling the second set of cameras to capture images of a first side of the vehicle; and controlling the third set of cameras to capture images of a roof of the vehicle.

(73) In some embodiments, the vehicle inspection system further comprises: generating, using photogrammetry, neural radiance fields or Gaussian splatting, a 3D model of the vehicle using at least some of the plurality of images; generating a visualization of the 3D model; and providing access to the visualization to one or more users.

(74) In some embodiments, the one or more defects include: scratches to an exterior of the vehicle, cracked windows, mirrors, or windshields, chipped paint, dents to the exterior of the vehicle, misaligned body panels, missing vehicle parts, non-standard replacement parts, non-standard paint; aftermarket vehicle accessories, rust/corrosion on the vehicle, damaged wheels, damaged tires, bald tires, tire sidewall bubbles, broken tire valves, wheel misalignment, mismatched tires, brake rotor discoloration, brake rotor damage, brake rotor wear, and/or suspension modifications.

(75) Some embodiments provide for at least one non-transitory computer-readable storage medium storing processor-executable instructions that, when executed by at least one computer hardware processor, causes the at least one computer hardware processor to perform a method for analyzing conditions of a vehicle from images of the vehicle collected by a vehicle inspection system, the vehicle inspection system comprising a plurality of sensor arrays comprising first, second and third

sensor arrays comprising respective first, second, and third sets of cameras, the method comprising: obtaining a plurality of images, the plurality of images including first, second, and third sets of images captured, respectively, by the first, second, and third sets of cameras; identifying a subset of the plurality of images for subsequent processing to identify whether the vehicle has one or more defects, wherein the identifying is performed based on a pose of the vehicle in images of the plurality of images; processing the subset of the plurality of images, using at least one trained machine learning (ML) model, to determine whether the vehicle has the one or more defects; and generating a vehicle condition report based on results of the processing, the vehicle condition report including an indication of the one or more defects in the plurality of images.

(76) In some embodiments, the obtaining comprises controlling the plurality of sensor arrays of the vehicle inspection system to capture the plurality of images of the vehicle.

(77) In some embodiments, the controlling comprises: controlling the first set of cameras to capture images of one or more wheels of the vehicle; controlling the second set of cameras to capture images of a first side of the vehicle; and controlling the third set of cameras to capture images of a roof of the vehicle.

(78) In some embodiments, the one or more defects include: scratches to an exterior of the vehicle, cracked windows, mirrors, or windshields, chipped paint, dents to the exterior of the vehicle, misaligned body panels, missing vehicle parts, non-standard replacement parts, non-standard paint, aftermarket vehicle accessories, rust/corrosion on the vehicle, damaged wheels, damaged tires, bald tires, tire sidewall bubbles, broken tire valves, wheel misalignment, mismatched tires, brake rotor discoloration, brake rotor damage, brake rotor wear, and/or suspension modifications.

(79) Some embodiments provide a method for a vehicle using a vehicle inspection system, the vehicle inspection system comprising a support member and a plurality of sensor arrays coupled to the support member, the plurality of sensor arrays comprising respective sets of sensors oriented in different directions, the method comprising: moving the vehicle and the support member of the vehicle inspection system relative to one another; triggering capture of sensor data about the vehicle by the plurality of sensor arrays of the vehicle inspection system; capturing the sensor data about the vehicle using the plurality of sensor arrays of the vehicle inspection system; stopping capture of the sensor data about the vehicle; stopping movement of the vehicle and the support member relative to one another; providing, to a computer hardware processor, the sensor data collected using the plurality of sensor arrays; and receiving, from the computer hardware processor, a vehicle condition report generated using the sensor data.

(80) In some embodiments, the plurality of sensor arrays comprise first, second and third sensor arrays, the first sensor array comprising a first set of cameras oriented in multiple first directions, the second sensor array comprising a second set of cameras oriented in multiple second directions, the third sensor array comprising a third set of cameras oriented in multiple third directions, and wherein capturing the data related to the vehicle using the plurality of sensor arrays comprises, capturing images of the vehicle using the first, second and third sets of cameras.

(81) In some embodiments, obtaining an image of a front of the vehicle using a camera of the vehicle inspection system.

(82) In some embodiments, the method further comprises, obtaining a plurality of images of an interior of the vehicle using a camera of the vehicle inspection system; and providing the plurality of images to the computer hardware processor.

(83) In some embodiments, the method further comprises: before the moving, placing a mobile vehicle diagnostic device (MVDD) of the vehicle inspection system at an engine of the vehicle, wherein the triggering comprises triggering a sensor array of the MVDD of the vehicle inspection system to capture sensor data about the engine of the vehicle.

(84) In some embodiments, the method further comprises: before the moving, positioning a vehicle undercarriage imaging system of the vehicle inspection system relative to the vehicle and the support member of the vehicle inspection system, wherein the triggering comprises triggering a

sensor array of the vehicle undercarriage imaging system to capture sensor data about an undercarriage of the vehicle.

(85) In some embodiments, the method further comprises: obtaining a plurality of images of an interior of the vehicle using a camera of the vehicle inspection system, wherein the providing further comprises providing the plurality of images of the interior of the vehicle to the computer hardware processor.

(86) In some embodiments, the triggering is performed by the vehicle inspection system when the vehicle is detected at a first position by one or more sensors of the plurality of sensor arrays.

(87) In some embodiments, the stopping capture is performed by the vehicle inspection system when the vehicle is detected at a second position, different from the first position, by the one or more sensors of the plurality of sensor arrays.

(88) In some embodiments, the method further comprises: before receiving the vehicle condition report, receiving from the computer hardware processor an indication the capturing was unsuccessful; recapturing second sensor data about the vehicle using the plurality of sensor arrays of the vehicle inspection system; and providing, to the computer hardware processor, the second sensor data collected using the plurality of sensor arrays.

(89) In some embodiments, the method further comprises: before the moving, positioning the support member relative to the vehicle.

(90) In some embodiments, the moving comprises driving the vehicle past the support member. In some embodiments, the moving comprises moving the support member about the vehicle.

(91) Some embodiments provide for a method for inspecting a vehicle using a vehicle inspection system, the vehicle inspection system comprising a support member, and a plurality of sensor arrays coupled to the support member, the plurality of sensor arrays comprising respective sets of sensors oriented in different directions, the method comprising: positioning the vehicle and the support member of the vehicle inspection system relative to one another; triggering the vehicle inspection system to collect alignment data of the vehicle relative to the vehicle inspection system; providing, to a computer hardware processor, the alignment data; receiving, from the computer hardware processor, an indication of an alignment of the vehicle relative to the vehicle inspection system; repositioning the support member relative to the vehicle based on the indication of the alignment; moving the vehicle and the support member of the vehicle inspection system relative to one another; capturing sensor data about the vehicle using the plurality of sensor arrays of the vehicle inspection system; providing, to a computer hardware processor, the sensor data collected using the plurality of sensor arrays; and receiving, from the computer hardware processor, a vehicle condition report.

(92) In some embodiments, the method further comprises: before the moving, positioning a vehicle undercarriage imaging system of the vehicle inspection system relative to the vehicle and the support member of the vehicle inspection system; and performing a registration process between the support member and the vehicle undercarriage imaging system, wherein the triggering comprises triggering the vehicle inspection system to collect alignment data of the support member and the vehicle undercarriage inspection system relative to the vehicle.

(93) In some embodiments, the method further comprises: before the moving, placing a mobile vehicle diagnostic device (MVDD) of the vehicle inspection system at an engine of the vehicle, the MVDD comprising a sensor array. In some embodiments, the moving comprises driving the vehicle past the support member.

(94) Some embodiments provide for a method for inspecting a vehicle using a vehicle inspection system, the vehicle inspection system comprising a support member, and a plurality of sensor arrays coupled to the support member, the plurality of sensor arrays comprising respective sets of sensors oriented in different directions, the method comprising: moving the vehicle and the support member of the vehicle inspection system relative to one another; capturing sensor data about the vehicle using the plurality of sensor arrays of the vehicle inspection system; stopping movement of

the vehicle and the support member relative to one another; providing, to a computer hardware processor, the sensor data collected using the plurality of sensor arrays; receiving, from the computer hardware processor, a vehicle condition report indicating one or more defects present on the vehicle; providing, to the computer hardware processor, a request for sensor data related to the one or more defects present on the vehicle; and receiving, from the computer hardware processor, a plurality of sensor data related to the one or more defects present on the vehicle.

(95) In some embodiments, the sets of sensors oriented in different directions of the plurality of sensor arrays are respective sets of cameras; and the plurality of sensor data related to the one or more defects comprises a plurality of images of the one or more defects taken from different angles by cameras of the respective sets of cameras of the plurality of sensor arrays.

(96) In some embodiments, the method further comprises: analyzing the vehicle to confirm a presence of the one or more defects; providing, to the computer hardware processor, an indication of the presence of the one or more defects; and receiving, from the computer hardware processor, an updated vehicle condition report.

(97) Some embodiments provide for a vehicle undercarriage inspection system, comprising: a base having a width and a depth respectively extending along first and second directions orthogonal to one another, the width extending from a first end of the base to a second end of the base; a sensor array coupled to the base, the sensor array comprising a set of cameras oriented in multiple directions, the set of cameras including: a first camera oriented in part towards the first end of the base; a second camera oriented in part towards the second end of the base; and a third camera positioned between the first and second cameras; and a processor configured to control the sensor array to capture a plurality of images of an undercarriage of a vehicle with the set of cameras.

(98) In some embodiments, the sensor array further comprises: a microphone, an infrared camera, a thermal camera, a magnetometer, a time of flight sensor, a light source, and/or an air quality sensor.

(99) In some embodiments, the processor is further configured to: generate a composite image of the vehicle undercarriage from images of the plurality of images of the vehicle undercarriage captured using the set of cameras.

(100) In some embodiments, the processor is further configured to: process the composite image, using at least one trained machine learning (ML) model, to determine whether the vehicle has one or more defects, or provide the composite image to another computing device for processing with the at least one trained ML model to determine whether the vehicle has one or more defects.

(101) In some embodiments, the one or more defects include: damage to one or more vehicle parts, presence of rust, presence of one or more aftermarket vehicle modifications, altered vehicle suspension, and/or a missing catalytic converter.

(102) In some embodiments, the sensor array further comprises: a first time of flight (TOF) sensor oriented in part toward the first end of the base; and a second TOF sensor oriented in part the second end of the base, wherein the processor is configured to: determine a position and/or motion of the vehicle relative to the vehicle undercarriage inspection system based on signals collected by the first and second TOF sensors; and generate a composite image of the vehicle undercarriage from images of the plurality of images of the vehicle undercarriage captured using the set of cameras and based on the position and/or motion of the vehicle relative to the vehicle undercarriage inspection system.

(103) In some embodiments, the vehicle undercarriage inspection system further comprises a cover coupled to the base, wherein the cover is configured to withstand 16,000 pounds of force. In some embodiments, the cover comprises internal ribbing configured to reinforce the cover to withstand the 16,000 pounds of force.

(104) In some embodiments, the first, second and third cameras are configured such that their combined field of view (FOV) is 200 cm in width with a minimum pixel density of 15 pixels/cm.

(105) In some embodiments, the vehicle undercarriage inspection system weighs less than 10 pounds; and the vehicle undercarriage inspection system further comprises a handle attached to the

base for lifting the vehicle undercarriage inspection system.

(106) In some embodiments, the processor is configured to: generate a 3D reconstruction of the vehicle undercarriage using the images of the vehicle undercarriage captured using the set of cameras.

(107) In some embodiments, the vehicle undercarriage inspection further comprises: a substrate supporting a plurality of electronic components, the plurality of electronic components comprising: the processor; respective camera controllers for the first, second and third cameras; and a power supply.

(108) Some embodiments provide for a vehicle undercarriage inspection system, comprising: a base having a width and a depth respectively extending along first and second directions orthogonal to one another, the width extending from a first end of the base to a second end of the base; a sensor array coupled to the base, the sensor array comprising: a set of cameras oriented in multiple directions; and a first time of flight (TOF) sensor configured to detect a position and/or motion of the vehicle; and a processor configured to: control the sensor array to capture a plurality of images of an undercarriage of a vehicle with the set of cameras; and control the TOF sensor to capture one or more signals indicative of the position and/or motion of the vehicle.

(109) In some embodiments, the vehicle undercarriage inspection system further comprises: a second time of flight sensor configured to detect a position and/or motion of the vehicle, wherein: the first time of flight sensor is oriented in part towards the first end of the base; the second time of flight sensor is oriented in part towards the second end of the base; and the first and second time of flight sensors are configured to collect signals indicative of a distance to one or more wheels of the vehicle.

(110) In some embodiments, the first TOF sensor is oriented to collect signals indicative of a distance between the undercarriage of the vehicle and the vehicle undercarriage inspection system.

(111) In some embodiments, wherein the processor is configured to generate a composite image of the undercarriage of the vehicle by combining images of the plurality of images based on the signals indicative of the position and/or motion of the vehicle.

(112) Some embodiments provide for a method for inspecting an undercarriage of a vehicle using a vehicle undercarriage inspection system, the vehicle undercarriage inspection system comprising a sensor array comprising first, second and third cameras configured to capture images at different angles relative to the vehicle undercarriage, and a time of flight (TOF) sensor configured to output signals indicative of distance of one or more parts of the vehicle relative to the vehicle undercarriage inspection system, the method comprising using a computer hardware processor to perform: obtaining, using the TOF sensor, at least one first signal indicative of a distance between the vehicle and the TOF sensor; in response to determining, using the at least one signal, that the vehicle is within a threshold distance of the TOF sensor, triggering the sensor array to capture one or more images of the vehicle undercarriage; capturing the one or more images of the vehicle undercarriage using the sensor array; and processing images of the one or more images using a trained machine learning model to determine whether the vehicle has one or more defects.

(113) In some embodiments, the method further comprises: obtaining, using the TOF sensor, at least one second signal indicative of the distance between the vehicle and the TOF sensor; and in response to determining the vehicle is in a second position relative to the vehicle undercarriage inspection system based on the at least one second signal, triggering the sensor array to stop capture of the images of the vehicle undercarriage.

(114) In some embodiments, the method further comprises: determining, using the at least one signal, that the vehicle is within the threshold distance of the TOF sensor.

(115) In some embodiments, the one or more images of the vehicle undercarriage comprise a plurality of images, and wherein the processing comprises: generating a composite image of the undercarriage of the vehicle by combining the images of the plurality of images based on the signals related to position of the vehicle obtained from the TOF sensor.

(116) Some embodiments provide for a method for analyzing condition of an undercarriage of a vehicle using a vehicle undercarriage inspection system, the vehicle undercarriage inspection system comprising a sensor array, the sensor array comprising first, second, and third cameras, the method comprising using a computer hardware processor to perform: obtaining, using the sensor array of the vehicle undercarriage inspection system, sensor data about the undercarriage of the vehicle captured as the vehicle and vehicle undercarriage inspection system move relative to each other, the sensor data including: first, second and third sets of images captured by the first, second and third cameras, respectively; and data indicative of a position and/or motion of the vehicle relative to the vehicle undercarriage inspection system; generating a composite image of the undercarriage of the vehicle by combining images of the first, second and third sets of images based on the data indicative of a position and/or motion of the vehicle relative to the vehicle undercarriage inspection system; determining whether the vehicle has one or more defects by processing the composite image, using a first trained machine learning (ML) model; and generating a vehicle condition report based on results of the processing.

(117) In some embodiments, the first, second and third sets of images respectively comprise consecutive images of the undercarriage of the vehicle taken by the first, second and third cameras.

(118) In some embodiments, the method further comprises: determining pixel shift distances between adjacent images of the consecutive images of the first, second and third sets of images, wherein generating the composite image is performed based on the pixel shift distances and the data indicative of position and/or motion of the vehicle.

(119) In some embodiments, the vehicle undercarriage imaging system further comprises a sensor configured to output data indicative of a position and/or motion of the vehicle relative to the vehicle undercarriage inspection system.

(120) In some embodiments, the method further comprises: determining pixel shift distances between adjacent images of the consecutive images of the first, second and third sets of images; and aligning the first, second and third sets of images using the respective pixel shift distances for the first, second and third sets of images, wherein the generating comprises combining temporally aligned images of the first, second and third sets of images.

(121) In some embodiments, aligning the first, second and third sets of images comprises: determining a difference between the pixel shift distances of the second and third sets of images and the pixel shift distances of the first set of images; and determining an alignment of the first, second and third sets of images which minimizes the difference between the pixel shift distances of the second and third sets of images and the pixel shift distances of the first set of images.

(122) In some embodiments, the method further comprises: determining pixel shift distances between adjacent images of the consecutive images of the first, second and third sets of images; and determining, based on the pixel shift distances, respective first, second and third subsets of images from the first, second and third sets of images, the first, second and third subsets of images comprising images in which the vehicle is moving relative to the vehicle undercarriage inspection system, wherein generating the composite image of the undercarriage of the vehicle by combining images of the first, second and third subsets of images.

(123) In some embodiments, the one or more defects include: damage to one or more vehicle parts, presence of rust, presence of one or more aftermarket vehicle modifications, altered vehicle suspension, and/or a missing catalytic converter.

(124) In some embodiments, the method further comprises: generating a 3D model of the undercarriage of the vehicle based on the first, second and third sets of images and the data indicative of the position and/or motion of the vehicle relative to the vehicle undercarriage inspection system; generating a visualization of the 3D model; and providing access to the visualization to one or more users.

(125) In some embodiments, the method further comprises: obtaining air quality data from an air quality sensor of the vehicle undercarriage inspection system; obtaining magnetic field data from a

magnetometer of the vehicle undercarriage inspection system; and/or obtaining audio data from a microphone of the vehicle undercarriage inspection system, wherein determining whether the vehicle has the one or more defects comprises processing the air quality data, magnetic field data and/or the audio data using a second trained machine learning model.

(126) Some embodiments provide for a vehicle undercarriage inspection system for analyzing a condition of an undercarriage of a vehicle, the system comprising: a sensor array comprising: a first, second and third camera; and a time-of-flight sensor configured to output data indicative of a position and/or motion of the vehicle relative to the vehicle undercarriage inspection system; and a computer hardware processor configured to perform: obtaining, from the sensor array, sensor data about the undercarriage of the vehicle captured as the vehicle and vehicle undercarriage inspection system move relative to each other, the sensor data including: first, second and third sets of images taken respectively by the first, second and third cameras; and data, captured by the time-of-flight sensor indicative of a position and/or motion of the vehicle relative to the vehicle undercarriage inspection system; generating a composite image of the undercarriage of the vehicle by combining images of the first, second and third sets of images based on the data indicative of position and/or motion of the vehicle relative to the vehicle undercarriage inspection system; determining whether the vehicle has one or more defects by processing the composite image, using a first trained machine learning (ML) model; and generating a vehicle condition report based on results of the processing.

(127) In some embodiments, the first, second and third sets of images respectively comprise consecutive images of the undercarriage of the vehicle taken by the first, second and third cameras.

(128) In some embodiments, the computer hardware processor is further configured to perform: determining pixel shift distances between adjacent images of the consecutive images of the first, second and third sets of images, wherein generating the composite image is performed based on the pixel shift distances and the data indicative of position and/or motion of the vehicle.

(129) In some embodiments, the computer hardware processor is further configured to perform: determining pixel shift distances between adjacent images of the consecutive images of the first, second and third sets of images; and aligning the first, second and third sets of images using the respective pixel shift distances for the first, second and third sets of images, wherein the generating the composite image comprises combining aligned images of the first, second and third sets of images.

(130) In some embodiments, wherein the one or more defects include: damage to one or more vehicle parts, presence of rust, presence of one or more aftermarket vehicle modifications, altered vehicle suspension, and/or a missing catalytic converter.

(131) Some embodiments provide for at least one non-transitory computer-readable storage medium storing processor executable instructions that, when executed by at least one computer hardware processor, cause the at least one computer hardware processor to perform a method for analyzing conditions of an undercarriage of a vehicle using a vehicle undercarriage inspection system, the vehicle undercarriage inspection system comprising a sensor array, the sensor array comprising first, second and third cameras, the method comprising: obtaining, using the sensor array of the vehicle undercarriage inspection system, sensor data about the undercarriage of the vehicle captured as the vehicle and vehicle undercarriage inspection system move relative to each other, the sensor data including: first, second and third sets of images captured by the first, second and third cameras, respectively; and data indicative of a position and/or motion of the vehicle relative to the vehicle undercarriage inspection system; generating a composite image of the undercarriage of the vehicle by combining images of the first, second and third sets of images based on the data indicative of a position and/or motion of the vehicle relative to the vehicle undercarriage inspection system; determining whether the vehicle has one or more defects by processing the composite image, using a first trained machine learning (ML) model; and generating a vehicle condition report based on results of the processing.

(132) In some embodiments, wherein the first, second and third sets of images respectively comprise consecutive images of the undercarriage of the vehicle taken by the first, second and third cameras.

(133) In some embodiments, the method further comprises: determining pixel shift distances between adjacent images of the consecutive images of the first, second and third sets of images, the generating the composite image is performed based on the pixel shift distances.

(134) In some embodiments, the method further comprises: determining pixel shift distances between adjacent images of the consecutive images of the first, second and third sets of images; and aligning the first, second and third sets of images using the respective pixel shift distances for the first, second and third sets of images, wherein the generating the composite image comprises combining aligned images of the first, second and third sets of images.

(135) In some embodiments, the one or more defects include: damage to one or more vehicle parts, presence of rust, presence of one or more aftermarket vehicle modifications, altered vehicle suspension, and/or a missing catalytic converter.

(136) Some embodiments provide for a method for inspecting an undercarriage of a vehicle using a vehicle undercarriage inspection system, the vehicle undercarriage inspection system comprising a sensor array comprising first, second and third cameras configured to capture images at different angles relative to the vehicle undercarriage, and a sensor configured to output data indicative of position and/or motion of the vehicle relative to the vehicle undercarriage inspection system, the method comprising: positioning the vehicle undercarriage inspection system relative to the vehicle; moving the vehicle and the vehicle undercarriage inspection system relative to one another; triggering capture of data about the vehicle undercarriage by the sensor array of the vehicle undercarriage inspection system; capturing the data about the vehicle undercarriage using the sensor array of the vehicle undercarriage inspection system, the data about the vehicle including a plurality of images of the undercarriage of the vehicle captured by the first, second, and third cameras at the different angles relative to the vehicle undercarriage; stopping capture of the data about the vehicle undercarriage; and generating, based on at least some of the plurality of images, a composite image of the vehicle undercarriage.

(137) In some embodiments, the generating is performed using the vehicle inspection system.

(138) In some embodiments, the generating comprises: providing, from the vehicle undercarriage inspection system to a computer hardware processor, separate from the vehicle undercarriage inspection system the at least some of the plurality of images for use in generating the composite image of the vehicle undercarriage.

(139) In some embodiments, the capturing comprises capturing respective first, second and third set of images using the first, second and third cameras of the sensor array.

(140) In some embodiments, the triggering comprises triggering the capture based on the data indicative of the position and/or motion of the vehicle.

(141) In some embodiments, the stopping capture is performed based on the data indicative of the position and/or motion of the vehicle.

(142) In some embodiments, the moving comprises driving the vehicle over the vehicle undercarriage inspection system.

(143) In some embodiments, the method further comprises: before the moving, positioning a vehicle exterior inspection system relative to the vehicle, the vehicle exterior inspection system comprising a support member and a plurality of sensor arrays coupled to the support member, the plurality of sensor arrays comprising respective sets of sensors oriented in different directions, wherein: the triggering comprises triggering the plurality of sensor arrays to capture sensor data about an exterior of the vehicle; and the capturing further comprises capturing the sensor data about an exterior of the vehicle using the plurality of sensor arrays.

(144) Some embodiments provide for a method for inspecting an undercarriage of a vehicle using a vehicle undercarriage inspection system, the vehicle undercarriage inspection system comprising a

sensor array comprising first, second and third cameras configured to capture images at different angles relative to the vehicle undercarriage, and a sensor configured to output data indicative of position and/or motion of the vehicle relative to the vehicle undercarriage inspection system, the method comprising: positioning the vehicle undercarriage inspection system relative to the vehicle; triggering the vehicle undercarriage inspection system to collect alignment data of the vehicle relative to the vehicle undercarriage inspection system; generating, based on the alignment data, an indication of an alignment of the vehicle relative to the vehicle inspection system; repositioning the vehicle relative to the vehicle undercarriage inspection system based on the indication of the alignment of the vehicle relative to the vehicle inspection system; moving the vehicle and the vehicle undercarriage inspection system relative to one another; capturing sensor data about the vehicle undercarriage using the sensor array of the vehicle undercarriage inspection system, the data about the vehicle including a plurality of images of the undercarriage of the vehicle; and generating, based on at least some of the plurality of images, a composite image of the vehicle undercarriage.

(145) In some embodiments, the alignment data is captured by the sensor configured to output data indicative of the position and/or motion of the vehicle.

(146) In some embodiments, the capturing is triggered based on the data indicative of the position and/or motion of the vehicle. In some embodiments, the capturing is stopped based on the data indicative of the position and/or motion of the vehicle.

(147) In some embodiments, the moving comprises driving the vehicle over the vehicle undercarriage inspection system. In some embodiments, the moving comprises moving the vehicle undercarriage inspection system beneath the vehicle.

(148) In some embodiments, the generating is performed by the vehicle undercarriage inspection system.

(149) Some embodiments provide for a method for inspecting an undercarriage of a vehicle using a vehicle undercarriage inspection system, the vehicle undercarriage inspection system comprising a sensor array comprising first, second and third cameras configured to capture images at different angles relative to the vehicle undercarriage, and a sensor configured to output data indicative of position and/or motion of the vehicle relative to the vehicle undercarriage inspection system, the method comprising: moving the vehicle and the vehicle undercarriage inspection system relative to one another; capturing sensor data about the vehicle undercarriage using the sensor array of the vehicle undercarriage inspection system; providing, to a computer hardware processor, the data about the vehicle undercarriage; receiving, from the computer hardware processor, a vehicle condition report indicating one or more defects present on the vehicle; providing, to the computer hardware processor, a request for sensor data related to the one or more defects present on the vehicle; and receiving, from the computer hardware processor, a plurality of sensor data related to the one or more defects present on the vehicle.

(150) In some embodiments, the plurality of sensor data related to the one or more defects comprises a plurality of images of the one or more defects taken from different angles by the first, second and third cameras of the sensor array.

(151) In some embodiments, the method further comprises: analyzing the vehicle to confirm a presence of the one or more defects; providing, to the computer hardware processor, an indication of the presence of the one or more defects; and receiving, from the computer hardware processor, an updated vehicle condition report.

(152) In some embodiments, the capturing is triggered by the vehicle undercarriage inspection based on the data indicative of the position and/or motion. In some embodiments, the capturing is stopped by the vehicle inspection system based on the data indicative of the position and/or motion.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1A depicts an example environment in which a vehicle inspection system may be deployed, according to some embodiments of the technology described herein.
- (2) FIG. 1B is a diagram illustrating components of a vehicle inspection system, according to some embodiments of the technology described herein.
- (3) FIG. 1C illustrates an example of an environment **130** in which multiple vehicle inspection systems may be deployed, according to some embodiments of the technology described herein.
- (4) FIG. 1D illustrates an example vehicle examination process **190** for use with a digital vehicle auction platform, according to some embodiments of the technology described herein.
- (5) FIG. 2 illustrates an example vehicle condition report, according to some embodiments of the technology described herein.
- (6) FIGS. 3A-3F illustrate steps in an example vehicle inspection process, according to some embodiments of the technology described herein.
- (7) FIG. 4A illustrates example image data which may be captured by a vehicle inspection system, according to some embodiments of the technology described herein.
- (8) FIG. 4B is an example of images of a vehicle interior which may be captured during a vehicle inspection process, according to some embodiments of the technology described herein.
- (9) FIG. 5A illustrates one or more trained machine learning models **500** for processing images of a vehicle to evaluate the vehicle's condition, according to some embodiments of the technology described herein.
- (10) FIG. 5B illustrates one or more trained machine learning models **510** for processing images and data of a vehicle to evaluate the vehicle's condition, according to some embodiments of the technology described herein.
- (11) FIG. 5C illustrates one or more trained machine learning models **523** for processing images of the interior of a vehicle to evaluate the vehicle's condition, according to some embodiments of the technology described herein.
- (12) FIG. 5D illustrates one or more trained machine learning models **530** for processing data of a vehicle to evaluate the vehicle's condition, according to some embodiments of the technology described herein.
- (13) FIG. 6A is a flowchart of an illustrative process **600** for inspecting a vehicle using a vehicle inspection system, according to some embodiments of the technology described herein.
- (14) FIG. 6B is a flowchart of an illustrative process **610** for preparing and using a vehicle inspection system to perform a vehicle inspection, according to some embodiments of the technology described herein.
- (15) FIG. 6C is a flowchart of an illustrative process **620** for using a vehicle inspection system to determine one or more vehicle defects, according to some embodiments of the technology described herein.
- (16) FIG. 7 is a view of an example vehicle undercarriage inspection system, according to some embodiments of the technology described herein.
- (17) FIG. 8A illustrates an example set of cameras part of a vehicle undercarriage inspection system, according to some embodiments of the technology described herein.
- (18) FIG. 8B is a view of an example mounting bracket of a vehicle undercarriage inspection system, according to some embodiments of the technology described herein.
- (19) FIG. 8C illustrates an example camera mounting bracket, according to some embodiments of the technology described herein.
- (20) FIG. 8D illustrates a camera indirectly mounted to a camera mounting bracket via an angled wedge, according to some embodiments of the technology described herein.
- (21) FIG. 8E illustrates example internal components of a vehicle undercarriage inspection system, according to some embodiments of the technology described herein.

(22) FIG. **9A** is a diagram illustrating the components of a vehicle undercarriage inspection system, according to some embodiments of the technology described herein.

(23) FIG. **9B** is a diagram illustrating components of a vehicle undercarriage inspection system, according to some embodiments of the technology described herein.

(24) FIG. **10** illustrates an example process **1000** for generating a composite image of a vehicle undercarriage, according to some embodiments of the technology described herein.

(25) FIG. **11A** is an example data flow for generating a composite image of a vehicle undercarriage, according to some embodiments of the technology described herein.

(26) FIG. **11B** illustrates an example process for determining pixel shift distances between adjacent images of an images set, according to some embodiments of the technology described herein.

(27) FIGS. **11C-D** illustrate an example of aligning image sets, according to some embodiments of the technology described herein.

(28) FIG. **11E** is an example of a plot of pixel shift distance values which may be used in cropping images sets, according to some embodiments of the technology described herein.

(29) FIG. **11F** is an example composite image of a vehicle generated based on vehicle speed estimated from pixel shift distances without TOF sensor data, according to some embodiments of the technology described herein.

(30) FIG. **11G** is an example composite image of a vehicle generated based on vehicle speed estimated from pixel shift distances and TOF sensor data, according to some embodiments of the technology described herein.

(31) FIG. **12** is an example of displaying images of a vehicle undercarriage, according to some embodiments of the technology described herein.

(32) FIG. **13A** illustrates one or more trained machine learning models **1300** for processing images of an undercarriage of a vehicle to evaluate the vehicle condition, according to some embodiments of the technology described herein.

(33) FIG. **13B** illustrates one or more trained machine learning models **1320** for processing images and data of a vehicle undercarriage to evaluate the vehicle condition, according to some embodiments of the technology described herein.

(34) FIG. **13C** illustrates one or more trained machine learning models **1340** for processing data of a vehicle undercarriage to evaluate the vehicle condition, according to some embodiments of the technology described herein.

(35) FIG. **14** is a flowchart of an illustrative process **1400** for performing a vehicle inspection using a vehicle undercarriage inspection system to identify vehicle defects, according to some embodiments of the technology described herein.

(36) FIG. **15** is a flowchart of an illustrative process **1500** for analyzing vehicle condition using a vehicle undercarriage inspection system, according to some embodiments of the technology described herein.

(37) FIG. **16A** is a flowchart of an illustrative process **1600** for inspecting an undercarriage of a vehicle using a vehicle undercarriage inspection system, according to some embodiments of the technology described herein.

(38) FIG. **16B** is a flowchart of an illustrative process **1610** for preparing and using a vehicle undercarriage inspection system to perform a vehicle inspection, according to some embodiments of the technology described herein.

(39) FIG. **16C** is a flowchart of an illustrative process **1620** for using a vehicle undercarriage inspection system to analyze vehicle conditions, according to some embodiments of the technology described herein.

(40) FIG. **17A** illustrates an example vehicle exterior inspection system with two support members, according to some embodiments of the technology described herein.

(41) FIG. **17B** illustrates an example vehicle exterior inspection system with four support members, according to some embodiments of the technology described herein.

(42) FIG. 17C illustrates an example vehicle inspection system with rotating support members, according to some embodiments.

(43) FIG. 17D illustrates an example vehicle inspection system with a moving sensor array, according to some embodiments of the technology described herein.

(44) FIG. 17E illustrates an example vehicle exterior inspection system with a frame and a moving and rotating sensor array, according to some embodiments of the technology described herein.

(45) FIG. 17F illustrates an example vehicle exterior inspection system with a frame and a moving sensor array, according to some embodiments of the technology described herein.

(46) FIG. 17G illustrates an example vehicle exterior inspection system with a pivoting frame, according to some embodiments of the technology described herein.

(47) FIG. 17H illustrates an example vehicle exterior inspection system with a turntable, according to some embodiments of the technology described herein.

(48) FIGS. 18A-C illustrate an example support member of a vehicle exterior inspection system, according to some embodiments of the technology described herein.

(49) FIG. 18D illustrates an example vehicle exterior imaging system, according to some embodiments of the technology described herein.

(50) FIG. 19 shows an example of fields of view of camera sets of a vehicle exterior inspection system, according to some embodiments of the technology described herein.

(51) FIG. 20 illustrates an example of images captured by a vehicle exterior inspection system, according to some embodiments of the technology described herein.

(52) FIG. 21A is a diagram illustrating the components of a vehicle exterior inspection system, according to some embodiments of the technology described herein.

(53) FIG. 21B is a diagram illustrating the components of processor(s) of a vehicle exterior inspection system, according to some embodiments of the technology described herein.

(54) FIGS. 22A-E show example techniques for determining a subset of images captured by a vehicle exterior inspection system for analysis, according to some embodiments.

(55) FIG. 23A illustrates one or more trained machine learning models **2300** for processing images of the exterior of a vehicle to evaluate the vehicle condition, according to some embodiments of the technology described herein.

(56) FIG. 23B illustrates one or more trained machine learning models **2310** for processing images and data from the exterior of a vehicle to evaluate the vehicle condition, according to some embodiments of the technology described herein.

(57) FIG. 23C illustrates one or more trained machine learning models **2320** for processing sensor data about an exterior of a vehicle to evaluate the vehicle condition, according to some embodiments of the technology described herein.

(58) FIG. 23D shows example inputs and performance of a wheel and tire machine learning model, according to some embodiments of the technology described herein.

(59) FIG. 23E shows example inputs and performance of a tire depth machine learning model, according to some embodiments of the technology described herein.

(60) FIG. 24A illustrates an image of a vehicle with defect tags, according to some embodiments of the technology described herein.

(61) FIG. 24B is an example of is an example of additional information which may be provided in response to a user selecting a tag, according to some embodiments of the technology described herein.

(62) FIG. 25 is an example process for removing personally identifiable information (PII) from an image, according to some embodiments of the technology described herein.

(63) FIG. 26 is an example process for generating a 3D model of a vehicle, according to some embodiments of the technology described herein.

(64) FIG. 27 is a flowchart of an illustrative process **2700** for analyzing vehicle condition using a vehicle exterior inspection system, according to some embodiments of the technology described

herein.

(65) FIG. 28A is a flowchart of an illustrative process **2800** for inspecting a vehicle using a vehicle exterior inspection system, according to some embodiments of the technology described herein.

(66) FIG. 28B is a flowchart of an illustrative process **2810** for preparing and using a vehicle exterior inspection system to perform a vehicle inspection, according to some embodiments of the technology described herein.

(67) FIG. 28C is a flowchart of an illustrative process **2820** for using a vehicle exterior inspection system to analyze vehicle conditions, according to some embodiments of the technology described herein.

(68) FIG. 29 illustrates a block diagram of an illustrative computing system that may be used in implementing some embodiments of the technology described herein.

DETAILED DESCRIPTION

(69) Every year, a large number of vehicles (e.g., cars, trucks, boats, etc.) is bought and sold across numerous locations such as dealerships and auction houses. In addition to the millions of new vehicles sold each year, annual sales of used cars and trucks are in the tens of millions in the U.S. alone. Used vehicle transactions involve cars of many different brands and trims, manufactured across a wide range of years (i.e., decades), in a variety of conditions ranging from almost new to having numerous defects, and possibly with post-sale modifications. Given the range of vehicle types and conditions transacted, vehicle inspections are especially important to collect accurate and complete data to inform the transactions taking place, but the sheer number of vehicles to be inspected poses a challenge not only in getting such inspections completed in a timely fashion, but also having them be sufficiently thorough and accurate so that their results are reliable.

(70) Indeed, vehicle inspectors have to collect a vast amount and variety of data about vehicles including data about a vehicle's exterior, interior, undercarriage, drivetrain, exhaust system, engine, transmission, electrical systems, and other components, to generate a complete vehicle condition report. Collecting all this information for one vehicle is time consuming not only because there is a lot of data that must be collected, but also because a vehicle inspector cannot collect different types of data simultaneously. This limits the inspector's abilities and would require additional inspectors or extended inspection times for meeting the needs of auction houses, which have many (e.g., hundreds, thousands, or tens of thousands) of vehicles to analyze.

(71) An additional challenge is that vehicle inspections be performed in a consistent and principled manner across the many types of vehicles being inspected and that the inspection results be provided in a consistent way. Differences in inspectors and how they approach inspectors as well as the different types and conditions of vehicles being inspected, leads to variations in the data collected about the vehicles, which in turn analyzing such data a complex task that cannot be performed in a uniform or standardized manner across all inspected vehicles. For example, if different inspectors take different types of images of vehicle exteriors (e.g., different resolution, different angles, different lighting conditions), analyzing images taken in different conditions in the same automated way can lead to errors (e.g., missed defects or incorrectly identified defects). What is desirable, but has not yet been achieved by conventional vehicle inspection methods, is the ability to generate vehicle condition reports that contain similar types of information about vehicles (in terms of the type, the quality, and the accuracy of the data being collected), regardless of the inspector performing the inspection or the vehicle that is being inspected.

(72) Of course, the state of the art is not entirely manual inspections because inspectors do have access to a variety of different vehicle inspection tools that can help them to perform the inspections. For example, an inspector may use their mobile phone to take pictures or videos of a car and upload the captured images for inclusion in the vehicle condition report or for further analysis (e.g., to identify dents, chipped paint, rust, etc.). As another example, an inspector may use a device equipped with a microphone to record the sounds generated by a vehicle (e.g., its engine, transmission, exhaust system, etc.) during operation for inclusion in the vehicle condition reports or

for further analysis (e.g., to identify engine defects, transmission defects, exhaust system defects, etc.). As yet another example, an inspector may use an OBD/OBDII scanner to access on-board diagnostic (OBD) codes that provide information about the vehicle's condition.

(73) However, although such tools can be very helpful, they don't fully address a number of the above-described challenges and therefore conventional inspection techniques relying on such tools can be improved upon. First, even if an inspector has access to a variety of technologies (e.g., cameras, microphones, OBD scanners, etc.), an inspector cannot use all these tools at once and instead will use them serially, one after the other, which can take time and does not address the need to perform inspections efficiently given the number of vehicles to be inspected. Relatedly, because the tools are not used simultaneously, not only do inspections take longer but there is not a way to take advantage of multi-sensor fusion techniques by jointly analyzing data collected by different sensors (e.g., audio and image sensors, different audio sensors, different cameras, regular, infrared, and multi-spectral camera, etc.). Second, different inspectors may deploy such technological tools differently (e.g., inspectors may take images at different angles and/or lighting conditions, inspectors may record audio by placing the microphones in different positions relative to the car, etc.), which leads to variations in the quality and accuracy of data collected.

(74) To address the above-described problems with conventional inspection techniques, including conventional inspection techniques that rely on various technologies, the inventors have developed a new vehicle inspection system. The new vehicle inspection system increases the speed of inspection (e.g., from an average of 30 minutes of which about 10-15 minutes is devoted to imaging down to an average of less than 3 minutes, with about 20-40 seconds for imaging), allowing for a greater number of vehicles to be inspected more quickly. The new vehicle inspection system captures sensor data in a standardized way by providing consistent sensor positions and orientations relative to the vehicle in a consistent environment (e.g., consistent lighting conditions). To this end, the new vehicle inspection system includes numerous sensors of different types positioned over a wide range of angles and perspectives relative to the vehicle being inspected. Moreover, the new vehicle inspection system is able to capture data simultaneously using multiple sensors including multiple sensors of the same type (e.g., multiple cameras, multiple audio sensors, etc.) and sensors of different types (e.g., optical cameras, infrared cameras, multi-spectral cameras, audio sensors, vibration sensors, magnetometers, time-of-flight sensors, etc.), which enables data collected by multiple sensors concurrently (e.g., simultaneously) to be analyzed jointly for assessing the condition of the vehicle being inspected (e.g., by identifying one or more defects using data collected by multiple different sensors). All this provides for a vehicle inspection system that improves over conventional vehicle inspection technology by providing for more time-efficient, accurate and high quality inspections and subsequent analysis.

(75) The new vehicle inspection system developed by the inventors may be deployed in a variety of locations such as a vehicle auction location, a dealership, an inspection site, a rental car locations, a parking lot, and/or any other suitable location. The vehicle inspection system developed by the inventors may be portable such that its components may be moved to different positions at a location (e.g., moved to different parking lots at a dealership having multiple parking lots) or between locations (e.g., moved from one dealership to another or from one auction site to another).

(76) In some embodiments, the vehicle inspection system may include one or multiple components. For example, the vehicle inspection system may include a vehicle exterior inspection system, a vehicle undercarriage inspection system, or both the vehicle exterior inspection system and the vehicle undercarriage inspection system. One or both of the vehicle undercarriage inspection system and the vehicle exterior inspection systems may be portable. Each of the vehicle inspection system components may include one or more sensors. For example, in some embodiments, the vehicle undercarriage inspection system may have a sensor array having one or more of: a camera, a microphone, an infrared camera, a thermal camera, a magnetometer, a time of flight sensor, a light source, and/or an air quality sensor. As another example, the vehicle exterior inspection

system may have multiple sensor arrays each having multiple cameras (of the same or different types) thereon. The sensor arrays may also include acoustic sensors, light sources, and/or any other suitable sensors).

(77) In some embodiments, the vehicle inspection system may further include one or more processors which may be part of one or more computing devices. The processor(s) may be configured to control operation of the sensors part of the vehicle inspection system. For example, the processor(s) may be configured to trigger collection of data by one or more of the sensors and may control the sensors to collect data in a synchronized manner, for example, concurrently (so there is overlap in the time periods the sensors are operating) or even simultaneously (so that two or more sensors are controlled to gather sensor data at the same time). The processor(s) may further offload the captured data from the sensor(s), pre-process and/or analyze the data, and/or forward the data to one or more other computing devices (e.g., computing devices external to the vehicle inspection system, for example, one or more computing devices on the cloud) for pre-processing and/or analysis. The processor(s) may be part of a computing device or devices co-located or integrated with the vehicle inspection system (e.g., a laptop, a desktop, a smartphone, a tablet, a raspberry pi, a controller, etc.).

(78) In some embodiments, a vehicle may be moved relative to the vehicle inspection system and the vehicle inspection system may capture data about the vehicle using its sensor suite. The sensors may be automatically triggered to capture data about the vehicle based on the relative position of the vehicle and the sensors. For example, a car may be driven through (or automatically moved through on a moving belt relative to) the vehicle inspection system and sensors in the vehicle exterior inspection system and the vehicle undercarriage inspection system may be triggered to start and stop capturing data about the vehicle based on the position of the vehicle relative to the sensors. In some embodiments, the vehicle inspection system may include one or more sensors (e.g., a ranging sensor such as a radar, a time of flight sensor, a lidar, etc.) configured to measure the distance (e.g., range) to and/or the position of the vehicle relative to the system or a component thereof (e.g., one or more sensors) and use the data collected by such as a sensor or sensors to trigger the starting and stopping of capture of sensor data by other sensors (e.g., cameras).

(79) As can be appreciated from the foregoing, in some embodiments, the vehicle inspection system may operate to inspect the vehicle autonomously. For example, the vehicle inspection system may control movement of the vehicle (e.g., by moving a belt or other movable platform, like a turntable), so that the vehicle moves relative to the vehicle inspection system. As the car is then moved to certain positions relative to the sensors, the vehicle inspection system may trigger those sensors (e.g., cameras, acoustic sensors, magnetometers, etc.) to start capturing data about the vehicle and, later, stop capture when the car is moved out of position. Of course, fully automated inspection is not required and, in some embodiments, an inspector may co-operate with the system to perform the inspection. For example, the inspector may drive a car through the inspection system and/or reposition the car relative to the inspection system when the alignment is not suitable for one or more sensors. As another example, the inspector may reposition a component of the inspection system (e.g., the vehicle undercarriage inspection system) so that it is better aligned with the vehicle.

(80) As described above, in some embodiments, a vehicle inspection system includes a vehicle undercarriage inspection system. In some embodiments, a vehicle undercarriage inspection system includes a sensor array, configured to capture sensor data about an undercarriage of a vehicle. In some embodiments, a sensor array of a vehicle undercarriage inspection system includes one or more of each of: a camera, a microphone, an infrared camera, a thermal camera, a magnetometer, a time of flight sensor, a light source, and/or an air quality sensor. In some embodiments, sensors of a vehicle undercarriage inspection system may be angled in different directions to capture data from different parts of the vehicle undercarriage. In some embodiments, a vehicle undercarriage inspection system may record data using a sensor array as a vehicle is driven over and/or around

the vehicle undercarriage inspection system. In some embodiments, a vehicle undercarriage inspection system records data using a sensor array as the vehicle undercarriage inspection system moves beneath and/or around a vehicle. In some embodiments, a vehicle undercarriage inspection system may automatically record data from the undercarriage of the vehicle based on the position and/or motion of the vehicle. In some embodiments, a vehicle undercarriage inspection system may be controlled by a user to record data from the undercarriage of the vehicle.

(81) In some embodiments, a composite image of a vehicle may be generated based on data captured by a vehicle undercarriage inspection system. In some embodiments, a composite image may be generated by combining images captured by one or more cameras of a vehicle undercarriage inspection system as the vehicle moves relative to the vehicle undercarriage inspection system. In some embodiments, a composite image may be generated by combining images captured by one or more cameras of a vehicle undercarriage inspection system based on a speed of the vehicle in the images. In some embodiments, the speed of the vehicle in the images may be determined based on a pixel shift distance between consecutive images. In some embodiments, the speed of the vehicle in the images may be determined based on data received from a sensor configured to output data related to the position and/or motion of the vehicle relative to the vehicle undercarriage inspection system, for example a time of flight (TOF) sensor.

(82) In some embodiments, data recorded by a sensor array of a vehicle undercarriage inspection system may be processed using one or more machine learning models. In some examples, a composite image of a vehicle undercarriage may be analyzed using the one or more machine learning models. In some embodiments, the data may be analyzed using the one or more machine learning models to determine the presence of one or more defects in a vehicle. In some embodiments, the one or more defects include one or more of: damage to one or more vehicle parts, presence of rust, presence of one or more aftermarket vehicle modifications, altered vehicle suspension, and/or a missing catalytic converter, among other defects. In some embodiments, the data may be analyzed using the one or more machine learning models to determine one or more characteristics of a vehicle. In some examples, the vehicle characteristics include a vehicle drivetrain type, a vehicle battery type, a vehicle make, a vehicle model, a vehicle trim level, and vehicle component types, among other vehicle characteristics.

(83) Accordingly, some embodiments provide for a vehicle undercarriage inspection system, comprising: (A) a base having a width and a depth respectively extending along first and second directions orthogonal to one another, the width extending from a first end of the base to a second end of the base; (B) a sensor array coupled to the base, the sensor array comprising a set of cameras oriented in multiple directions, the set of cameras including: a first camera oriented in part towards the first end of the base; a second camera oriented in part towards the second end of the base; and a third camera positioned between the first and second cameras; and (C) a processor configured to control the sensor array to capture a plurality of images of an undercarriage of a vehicle with the set of cameras.

(84) In some embodiments, the sensor array may further comprise: a microphone, an infrared camera, a thermal camera, a magnetometer, a time of flight sensor, a light source, and/or an air quality sensor.

(85) In some embodiments, the processor is further configured to generate a composite image of the vehicle undercarriage from images of the plurality of images of the vehicle undercarriage captured using the set of cameras. Additionally, the processor may be further configured to: process the composite image, using at least one trained machine learning (ML) model, to determine whether the vehicle has one or more defects (e.g., damage to one or more vehicle parts, presence of rust, presence of one or more aftermarket vehicle modifications, altered vehicle suspension, and/or a missing catalytic converter), or provide the composite image to another computing device for processing with the at least one trained ML model to determine whether the vehicle has one or more defects, or generate a 3D reconstruction of the vehicle undercarriage using the images of the

vehicle undercarriage captured using the set of cameras.

(86) In some embodiments, the sensor array further comprises: a first time of flight (TOF) sensor oriented in part toward the first end of the base; and a second TOF sensor oriented in part the second end of the base, wherein the processor is configured to: determine a position and/or motion of the vehicle relative to the vehicle undercarriage inspection system based on signals collected by the first and second TOF sensors; and generate a composite image of the vehicle undercarriage from images of the plurality of images of the vehicle undercarriage captured using the set of cameras and based on the position and/or motion of the vehicle relative to the vehicle undercarriage inspection system.

(87) In some embodiments, the first, second and third cameras are configured such that their combined field of view (FOV) is 200 cm in width with a minimum pixel density of 15 pixels/cm.

(88) In some embodiments, the vehicle undercarriage inspection system may weigh less than 10 pounds (e.g., between 3 and 10 lbs.) and include a handle attached to the base for lifting the vehicle undercarriage inspection system.

(89) In some embodiments, the vehicle undercarriage inspection system further comprises: a substrate supporting a plurality of electronic components, the plurality of electronic components comprising: the processor; respective camera controllers for the first, second and third cameras; and a power supply.

(90) In some embodiments, the vehicle undercarriage inspection system further comprises a cover coupled to the base, wherein the cover is configured to withstand up to 16,000 pounds of force. The cover may include internal ribbing configured to reinforce the cover to withstand the 16,000 pounds of force.

(91) In some embodiments, a vehicle undercarriage inspection system may comprise: (A) a base having a width and a depth respectively extending along first and second directions orthogonal to one another, the width extending from a first end of the base to a second end of the base; (B) a sensor array coupled to the base, the sensor array comprising: a set of cameras oriented in multiple directions; and a first time of flight (TOF) sensor configured to detect a position and/or motion of the vehicle; and (C) a processor configured to:

(92) control the sensor array to capture a plurality of images of an undercarriage of a vehicle with the set of cameras; and control the TOF sensor to capture one or more signals indicative of the position and/or motion of the vehicle.

(93) Examples of analyses of vehicle data, and machine learning models for processing vehicle data are discussed in U.S. Pat. No. 11,631,289, entitled "Vehicle Audio Capture and Diagnostics," filed Jan. 22, 2020, U.S. Pat. No. 10,893,213, entitled "Vehicle Undercarriage Imaging System," filed Apr. 2, 2019, U.S. Pat. No. 18,778,247, entitled "Methods and Systems for Identifying Potential Vehicle Defects," filed Jul. 19, 2024, and U.S. patent application Ser. No. 18/483,935, entitled: "Machine Learning and Magnetic Field Sensing Techniques for Vehicle Inspection and Condition Analysis," filed Oct. 10, 2023, each of which is incorporated by reference herein in its entirety.

(94) As described above, in some embodiments, a vehicle inspection system includes a vehicle exterior inspection system. In some embodiments, a vehicle exterior inspection system may include a support member which supports components for vehicle inspection. In some embodiments, a vehicle exterior inspection system may include one or more sensor arrays, coupled to the support member, for capturing data related to a vehicle. In some examples, a sensor array of a vehicle exterior inspection system may include one or more of: a camera, a microphone, an infrared camera, a thermal camera, a magnetometer, a time of flight sensor, a light source, and/or an air quality sensor. In some embodiments, sensors of a vehicle exterior inspection system may be positioned to capture data related to specific portions of a vehicle. For example, sensors and/or sensor arrays may be positioned to capture data from the front, rear, roof, hood, sides, and wheels of a vehicle, among other vehicle portions. In some embodiments, a support member of a vehicle

exterior inspection system may support multiple sensor arrays to capture data from different vehicle portions. In some embodiments, a support member of a vehicle inspection system may include one or more angled portions to support a sensor and/or sensor array to capture data of a particular portion of a vehicle, for example the top of a support member may be angled such that a sensor array positioned at the top of the support member may capture data from the roof of the vehicle. In some embodiments, a vehicle exterior inspection system may automatically record data from the undercarriage of the vehicle based on the position and/or motion of the vehicle. In some embodiments, a vehicle exterior inspection system may be controlled by a user to record data from the undercarriage of the vehicle.

(95) In some embodiments, data subsets may be determined from the data collected by a vehicle exterior inspection system. For example, a subset of images may be determined from images captured by one or more cameras of the vehicle exterior inspection system. In some embodiments, the subset of images may be determined based on the pose of the vehicle within the images. For example, an image is selected for the subset of images when the vehicle is in a desired position within the image. In some embodiments, a desired position of the vehicle may be when the vehicle is centered within the image. In some embodiments a desired position of the vehicle is when a specific component of the vehicle is centered within the image, for example a wheel of the vehicle. In some embodiments, a desired position of the vehicle is when the vehicle and/or a component of the vehicle is in a desired location within the image, for example, the hood is at a side of the image. In some embodiments, a subset of images may be determined by comparing images to a set of desired vehicle poses. In some embodiments a subset of data is processed.

(96) In some embodiments, data recorded by sensor array(s) of a vehicle exterior inspection system may be processed using one or more machine learning models. In some embodiments, the data may be analyzed using the one or more machine learning models to determine the presence of one or more defects in a vehicle. In some embodiments, the one or more defects include one or more of: scratches to an exterior of the vehicle; cracked windows, mirrors, or windshields, chipped paint, dents to the exterior of the vehicle, misaligned body panels, missing vehicle parts, non-standard replacement parts, non-standard paint, aftermarket vehicle accessories, rust/corrosion on the vehicle, damaged wheels, damaged tires, bald tires, tire sidewall bubbles, broken tire valves, wheel misalignment, mismatched tires, brake rotor discoloration, brake rotor damage, brake rotor wear, a missing catalytic converter and/or suspension modifications. In some embodiments, the data may be analyzed using the one or more machine learning models to determine one or more characteristics of a vehicle. In some examples, the vehicle characteristics include a vehicle drivetrain type, a vehicle battery type, a vehicle make, a vehicle model, a vehicle trim level, and vehicle component types, among other vehicle characteristics.

(97) In some embodiments, an air quality sensor may be configured to detect levels of one or more of: CO.sub.2, CO, NO.sub.x, and/or SO.sub.2. CO.sub.2 may be indicative of combustion efficiency wherein higher CO.sub.2 concentration equals greater vehicle efficiency. Low concentrations are linked to problems within the engine (e.g., air/fuel imbalance or misfires). CO may be indicative of improper combustion, catalytic converter issues, and exhaust leaks (in the early stages of the exhaust). Ideally, all CO should be converted to CO.sub.2 upon exiting through the exhaust tailpipe. NO.sub.x may be indicative of catalytic converter problems accompanied by possible exhaust leaks, fuel system issues, and exhaust gas recirculation (EGR) obstruction/malfunction. Ideally, NO.sub.x should be converted to N.sub.2 upon exhaust. High levels of SO.sub.2 may be indicative of poor fuel quality.

(98) Examples of analyses of vehicle data and machine learning models for processing vehicle data are discussed in U.S. Pat. No. 11,631,289, entitled "Vehicle Audio Capture and Diagnostics," filed Jan. 22, 2020, U.S. Pat. No. 10,893,213, entitled "Vehicle Undercarriage Imaging System," filed Apr. 2, 2019, U.S. Pat. No. 18,778,247, entitled "Methods and Systems for Identifying Potential Vehicle Defects," filed Jul. 19, 2024, and U.S. patent application Ser. No. 18/483,935, entitled:

“Machine Learning and Magnetic Field Sensing Techniques for Vehicle Inspection and Condition Analysis,” filed Oct. 10, 2023, each of which is incorporated by reference herein in its entirety.

(99) In some embodiments, a vehicle inspection system may include a mobile vehicle diagnostic device (MVDD), containing one or more types of sensors, for gathering vehicle data during a vehicle inspection. An example of an MVDD is described in US Patent Publication number US 2023/0204461A1, entitled “Multi-Sensor Devices and Systems for Evaluating Vehicle Conditions,” filed Dec. 22, 2022, the entire contents of which are incorporated by reference herein in its entirety. In some embodiments, a MVDD may be positioned, by an inspector in accordance with a vehicle inspection, near or inside a vehicle to collect data about the vehicle. In some embodiments a MVDD may record audio signals, vibration signals, and/or metadata containing one or more properties of the particular vehicle. In some embodiments, data recorded by a MVDD may be analyzed to detect presence or absence of one or more defects in the particular vehicle (e.g., by detecting the presence or absence of engine noise, transmission noise, start-up engine rattle, and/or any other type of defect the presence of which may be reflected in the gathered data). In some embodiments, data recorded by a MVDD may be processed using one or more machine learning models to determine the presence of defects in the vehicle. For example, a ML model may analyze data from a MVDD to determine one or more of presence or absence of abnormal internal engine noise (e.g., ticking, knocking, hesitation), rough running engine, abnormal timing chain noise (e.g., rattling of a stretched chain), abnormal engine accessory noise (e.g., power steering pump whines, serpentine belt squeals, bearing damage, turbocharger or supercharger noise, and noise emanating from any other anomalous components that are not internal to the engine block), and/or abnormal exhaust noise (e.g., noise generated due to a cracked or damaged exhaust system near the engine), among other defects.

(100) In some embodiments, a vehicle inspection system may include a device which records on-board diagnostic (OBD) codes from a vehicle. In some embodiments, a vehicle inspection system may include a device which records OBDII codes from a vehicle. In some embodiments, the data obtained from a device which records OBD and/or OBDII codes may be analyzed by one or more machine learning models, to determine defects and/or characteristics of a vehicle. In some embodiments, the data obtained from a device which records OBD and/or OBDII codes may be analyzed by one or more machine learning models together with data from one or more other sensors of a vehicle inspection system, to determine defects and/or characteristics of a vehicle.

(101) In some embodiments, a vehicle inspection system may include a camera for obtaining images of a vehicle. In some embodiments, the camera may be a camera of a mobile device such as a smartphone or a tablet. In some embodiments, the camera may be a digital camera. In some embodiments the camera may be a 360° camera. In some embodiments, a camera may be used to obtain images of the front, rear, VIN plate, and/or engine bay of a vehicle. In some embodiments, the camera may be used to capture images of the interior of a vehicle. In some embodiments, the data obtained from a camera may be analyzed by one or more machine learning models, to determine defects and/or characteristics of a vehicle. In some embodiments, the data obtained from camera may be analyzed by one or more machine learning models together with data from one or more other sensors of a vehicle inspection system, to determine defects and/or characteristics of a vehicle.

(102) In some embodiments, a vehicle inspection system may include a paint meter for measuring the thickness at one or more portions of the vehicle. In some embodiments, the data obtained from paint meter may be analyzed by one or more machine learning models, to determine defects and/or characteristics of a vehicle. In some embodiments, the data obtained from a paint meter may be analyzed by one or more machine learning models together with data from one or more other sensors of a vehicle inspection system, to determine defects and/or characteristics of a vehicle.

(103) In some embodiments, a vehicle inspection system may include any combination of a vehicle undercarriage inspection system, a vehicle exterior inspection system, a MVDD, a device for

recording OBD codes, a paint meter, and a camera. For example, a vehicle inspection system may include all six components, any five of the components, any four of the components, any three of the components, any two of the components, or any one of the components.

(104) In some embodiments a vehicle inspection system may include one or more computer hardware processors for performing vehicle inspections and/or processing vehicle inspection data. In some embodiments, the one or more processors may control the components of a vehicle inspection system to collect data. For example, by triggering the sensors to begin and/or stop collection of data. In some embodiments, the one or more processors may control the vehicle inspection system based on data received from one or more sensors, for example, by triggering recording of data when a vehicle is determined to be at a specific position based on data from a TOF sensor. In some embodiments, the one or more processors may perform analyses of vehicle inspection data, for example, generating composite images, data subsets, processing with ML models, determining the presence of one or more vehicle defects, and/or generating vehicle condition reports. In some examples, the one or more processors of a vehicle inspection system may be included in one or more components of the vehicle inspection system, for example in a vehicle undercarriage inspection system, a vehicle exterior inspection system, a mobile device, or a computer used with the vehicle inspection system. In some embodiments, the components of a vehicle connection system may be connected to enable transmission and reception of data between each other, for example using a wired or wireless connection. In some embodiments, components of vehicle inspection system such as mobile devices and/or processors may be connected via Bluetooth and/or Wi-Fi connections. In some embodiments, a vehicle inspection process requires connecting components via Bluetooth and/or Wi-Fi. In some embodiments, the one or more processors of a vehicle inspection system may be remote from the vehicle inspection system and may transmit and/or receive data to/from the components of the vehicle inspection system. In such embodiments, the components of the vehicle inspection system may be connected to the one or more processors via a communication network (e.g., Internet, local area network (LAN), wide area network (WAN), wireless network, wired network, and/or any suitable combination thereof). In some embodiments, the one or more processors of the vehicle inspection system may be distributed between the components of the vehicle inspection system and a remote location.

(105) In some embodiments, the one or more processors of a vehicle inspection system may use one or more ML models to analyze data recorded by the sensors of the vehicle inspection system. In some examples, the data may be processed to determine one or more characteristics and/or defects of the vehicle, as described herein. In some embodiments, machine learning models may analyze data recorded by a single sensor, type of sensor, and/or sensor array of the vehicle inspection system. For example, a ML model configured to determine the presence of damage to the exterior of the vehicle may only process images captured by cameras of the vehicle exterior inspection system. In some embodiments, a ML model may analyze data recorded by multiple sensors, or types of sensors. For example, a ML model configured to determine the presence of a catalytic converter may analyze a composite image of a vehicle undercarriage and magnetometer data from the vehicle.

(106) In some embodiments, a vehicle inspection system is configured to generate a vehicle condition report. In some embodiments, the vehicle condition report is generated based on data collected from sensors of the vehicle inspection system. In some embodiment, the vehicle condition report is generated based on processing of data (e.g., using one or more machine learning models) collected by the sensors of the vehicle inspection system. In some embodiments, the vehicle condition report includes information related to vehicle characteristics, for example, a make, model, year, mileage, trim level, Vehicle Identification Number (VIN), color, vehicle options, vehicle packages, and vehicle maintenance history, among other characteristics. In some embodiments, the vehicle condition report may include one or more defects and/or characteristics determined based on data collected by the vehicle inspection system. In some embodiments, the

vehicle condition report may include data collected by the vehicle inspection system, for example, a composite image of the vehicle undercarriage, images of the exterior of the vehicle, and audio recordings of the, among other data. In some embodiments, the vehicle condition report may be in an electronic format. In some embodiments, the vehicle condition report may be presented on a user interface of the vehicle inspection system, such as a on a display of a mobile device and/or computer associated with the vehicle inspection system. In some embodiments the vehicle condition report may be generated using one or more ML models.

(107) In some embodiments, the electronic vehicle condition report may be provided via at least one communication network, to a remote device of an inspector of the vehicle. The inspector may review the determined characteristics and or for correctness and may, for example, confirm its correctness (e.g., via a GUI) or change its value. In some embodiments, the electronic vehicle condition report may be provided, via at least one communication network, to one or more reviewers. The reviewer(s) may review accuracy of the vehicle condition report to determine the likelihood of a claim dispute. In some embodiments, upon reviewing and approving the electronic vehicle condition report, an online vehicle auction to auction the vehicle may be initiated, manually or automatically.

(108) Accordingly, in some embodiments, an exterior vehicle inspection system comprises: (A) a first support member comprising a first portion and a second portion angled relative to the first portion; (B) a first plurality of sensor arrays coupled to the first support member, the first plurality of sensor arrays comprising: a first sensor array comprising a first set of cameras oriented in multiple first directions, the first sensor array being coupled to the first support member at a position at which the first set of cameras has one or more wheels of a vehicle in its field of view (FOV) when the first sensor array is being used to image the vehicle; a second sensor array comprising a second set of cameras oriented in multiple second directions, the second sensor array being coupled to the first support member at a position at which the second set of cameras has a first side of the vehicle in its FOV when the second sensor array is being used to image the vehicle; and a third sensor array comprising a third set of cameras oriented in multiple third directions, the third sensor array being coupled to the first support member at a position at which the third set of cameras has a roof of the vehicle in its FOV when the third sensor array is being used to image the vehicle; and (C) a processor configured to control the first plurality of sensor arrays to capture images of the vehicle.

(109) In some embodiments, the first sensor array is positioned below the second and third sensor arrays on the first support member. The second sensor array may be positioned below the third sensor array on the first support member. The first and second sensor arrays may be positioned on the first portion of the first support member, and the third sensor array may be positioned on the second portion of the first support member.

(110) In some embodiments, the first sensor array further comprises: a microphone, an infrared camera, a thermal camera, a magnetometer, a light source and/or an air quality sensor. In some embodiments, the exterior vehicle inspection system comprises: a second support member comprising a third portion, and a fourth portion angled relative to the third portion; a second plurality of sensor arrays coupled to the second support member, the second plurality of sensor arrays comprising: a fourth sensor array comprising a fourth set of cameras oriented in multiple fourth directions, the fourth sensor array being coupled to the second support member at a position at which the fourth set of cameras has one or more wheels of a vehicle in its FOV when the fourth sensor array is being used to image the vehicle; a fifth sensor array comprising a fifth set of cameras oriented in multiple fifth directions, the fifth sensor array being coupled to the second support member at a position at which the fifth set of cameras has a second side of the vehicle in its field of view when the fifth sensor array is being used to image the vehicle; and a sixth sensor array comprising a sixth set of cameras oriented in multiple sixth directions, the sixth sensor array being coupled to the second support member at a position at which the sixth set of cameras has the roof

of the vehicle in its field of view when the sixth sensor array is being used to image the vehicle, wherein the processor is further configured to control the second plurality of sensor arrays capture images of the vehicle.

(111) In some embodiments, the first plurality of sensor arrays is configured such that the combined FOV of the first, second and third sets of cameras spans at least 150 inches in height, 300 inches in length and 120 inches in width.

(112) In some embodiments, during imaging the vehicle and support structure move relative to one another along a first direction; the first set of cameras comprises: a first camera oriented in part towards the first direction; a second camera oriented in part opposite the first direction; and a third camera oriented substantially perpendicular to the first direction; the first camera has a rocker panel and wheels of the vehicle in its field of view when being used to image the vehicle; the second camera has the rocker panel and rear of the vehicle in its field of view when being used to image the vehicle; and the third camera has one or more wheels of the vehicle in its field of view when being used to image the vehicle.

(113) In some embodiments, during imaging the vehicle and support structure move relative to one another along a first direction, and the second set of cameras comprises: a first camera oriented in part towards the first direction; a second camera oriented in part opposite the first direction; and a third camera oriented substantially perpendicular to the first direction; the first camera has the side and front of the vehicle in its field of view when being used to image the vehicle; the second camera has the side and rear of the vehicle in its field of view when being used to image the vehicle; and the third camera has the side of the vehicle in its field of view when being used to image the vehicle.

(114) In some embodiments, during imaging the vehicle and support structure move relative to one another along a first direction, the third set of cameras comprises: a first camera oriented in part towards the first direction; a second camera oriented in part opposite the first direction; and a third camera oriented substantially perpendicular to the first direction; the first camera has the roof, front, and hood of the vehicle in its field of view when being used to image the vehicle; the second camera has the roof and rear of the vehicle in its field of view when being used to image the vehicle; and the third camera has the hood and the roof of the vehicle in its field of view when being used to image the vehicle.

(115) In some embodiments, the first support member is portable and is collapsible between a deployed and a stowed configuration, and the vehicle inspection system is configured to image the vehicle when the first support member is in the deployed configuration.

(116) In some embodiments, the processor is configured to control the first plurality of sensor arrays to image the vehicle as the vehicle is driven past the first support member.

(117) In some embodiments, the processor is configured to control the first support member to move about the vehicle, and the processor is configured to control the first plurality of sensor arrays to image the vehicle as the first support member moves about the vehicle.

(118) In some embodiments, the processor is further configured to process the images of the vehicle using at least one trained machine learning (ML) model, to determine whether the vehicle has the one or more defects, wherein the one or more defects include: scratches to an exterior of the vehicle, cracked windows, mirrors, or windshields, chipped paint, dents to the exterior of the vehicle, misaligned body panels, missing vehicle parts, non-standard replacement parts, non-standard paint, aftermarket vehicle accessories, rust/corrosion on the vehicle, damaged wheels, damaged tires, bald tires, tire sidewall bubbles, broken tire valves, wheel misalignment, mismatched tires, brake rotor discoloration, brake rotor damage, brake rotor wear, and/or suspension modifications.

(119) Some embodiments are directed to a system for vehicle inspection, the system comprising: a support member; a first plurality of sensor arrays coupled to the first support member, the first plurality of sensor arrays comprising: a first sensor array comprising a first set of cameras oriented

in multiple first directions and a first microphone; a second sensor array comprising a second set of cameras oriented in multiple second directions and a second microphone; and a third sensor array comprising a third set of cameras oriented in multiple third directions, and a third microphone; and a processor configured to control the first plurality of sensor arrays to capture images and audio recordings of the vehicle.

(120) In some embodiments, during imaging the vehicle and support member move relative to one another along a first direction, and the first, second and third sets of cameras respectively comprise: a first camera oriented in part towards the first direction; a second camera oriented in part opposite the first direction; and a third camera oriented substantially perpendicular to the first direction.

(121) In some embodiments, the processor is further configured to process the images and/or audio of the vehicle using at least one trained machine learning (ML) model, to determine whether the vehicle has the one or more defects, wherein the one or more defects include: scratches to an exterior of the vehicle; cracked windows, mirrors, or windshields; chipped paint; dents to the exterior of the vehicle; misaligned body panels; missing vehicle parts, non-standard replacement parts, non-standard paint; aftermarket vehicle accessories; rust/corrosion on the vehicle; damaged wheels; damaged tires; bald tires; tire sidewall bubbles; broken tire valves; wheel misalignment; mismatched tires; brake rotor discoloration; brake rotor damage; brake rotor wear; suspension modifications; engine damage; an exhaust leak; and/or transmission whine.

(122) Some embodiments provide for a system for vehicle inspection, the system comprising: a support member; a first plurality of sensor arrays coupled to the first support member, the first plurality of sensor arrays configured to capture signals about a vehicle as the vehicle and support member move relative to one another along a first direction, and comprising: a first sensor array comprising a first set of cameras, the first sensor array coupled to the first support member at a position at which the first set of cameras has a first side of the vehicle in its FOV when the first sensor array is being used to image the vehicle, the first set of cameras comprising: a first camera oriented in part towards the first direction; a second camera oriented in part opposite the first direction; and a third camera oriented substantially perpendicular to the first direction; and a second sensor array comprising a second set of cameras, the first sensor array coupled to the first support member at a position at which the second set of cameras has a roof of the vehicle in its FOV when the second sensor array is being used to image the vehicle, the second set of cameras comprising: a fourth camera oriented in part towards the first direction; a fifth camera oriented in part opposite the first direction; and a sixth camera oriented substantially perpendicular to the first direction; and a processor configured to control the first plurality of sensor arrays to capture images of the vehicle.

(123) In some embodiments, the first camera has the side and front of the vehicle in its FOV when being used to image the vehicle; the second camera has the side and rear of the vehicle in its FOV when being used to image the vehicle; the third camera has the side of the vehicle in its FOV when being used to image the vehicle; the fourth camera has the roof, front, and hood of the vehicle in its FOV when being used to image the vehicle; the fifth camera has the roof and rear of the vehicle in its FOV when being used to image the vehicle; and the sixth camera has the hood and the roof of the vehicle in its FOV when being used to image the vehicle.

(124) As described above, in some embodiments, a vehicle inspection system may include both an exterior vehicle inspection system and a vehicle undercarriage inspection system. Accordingly, some embodiments provide for a vehicle inspection system for inspecting a vehicle, the system comprising: (A) a vehicle exterior inspection system comprising: a first support member; a first sensor array coupled to the first support member and comprising a first set of cameras positioned to capture images of wheels of the vehicle being imaged; a second sensor array coupled to the first support member and comprising a second set of cameras positioned to capture images of a side of the vehicle being imaged; and a third sensor array coupled to the first support member and comprising a third set of cameras positioned to capture images of a roof of the vehicle being

imaged; (B) a vehicle undercarriage inspection system comprising: a base having a width and a depth respectively extending along first and second directions orthogonal to one another, the width extending from a first end of the base to a second end of the base, the base supporting a fourth sensor array configured to capture images of an undercarriage of the vehicle, wherein the fourth sensor array comprises: a first camera positioned at a first side of the base, and oriented towards the first side of the base; a second camera positioned at a second side of the base, and oriented towards the second side of the base; and a third camera positioned between the first and second cameras, wherein the vehicle inspection system is configured to: capture a first plurality of images of the vehicle using the first, second and third sets of cameras of the vehicle exterior inspection system; and capture a second plurality of images of the undercarriage of the vehicle using the fourth sensor array of the vehicle undercarriage inspection system.

(125) In some embodiments, the vehicle inspection system further comprises a computer hardware processor configured to: when the vehicle is moved relative to the vehicle exterior inspection system and the vehicle undercarriage inspection system, triggering the capture of the first plurality of images of the vehicle using the first, second and third sets of cameras of the vehicle exterior inspection system, receiving the first plurality of images, and/or processing the first plurality of images; and triggering the capture of a second plurality of images of the undercarriage of the vehicle using the fourth sensor array of the vehicle undercarriage inspection system, receiving the second plurality of images, and/or processing the second plurality of images.

(126) In some embodiments, the vehicle inspection system is configured to trigger the capture the first and second plurality of images based on a position of the vehicle.

(127) In some embodiments, the vehicle undercarriage inspection system further comprises: a sensor configured to output data indicative of the position and/or motion of the vehicle relative to the vehicle inspection system, wherein the capturing of the first plurality of images is performed in response to determining the vehicle is at a first position and/or first distance relative to the vehicle inspection system, based on the data indicative of the position and/or motion of the vehicle.

(128) In some embodiments, capturing of the second plurality of images is performed in response to determining the vehicle is at a second position and/or distance relative to the vehicle inspection system, different from the first position, based on the data indicative of the position and/or motion of the vehicle. The second position of the vehicle may be closer to the vehicle inspection system than the first position, and/or the first distance is smaller than the second distance.

(129) In some embodiments, the computer hardware processor is further configured to perform: stopping the capturing of the first plurality of images in response to determining the vehicle is at a third position and/or distance relative to the vehicle inspection system, different from the first and second positions and/or distances, based on the data indicative of the position and/or motion of the vehicle; and stopping the capturing of the second plurality of images in response to determining the vehicle is at a fourth position and/or distance relative to the vehicle inspection system, different from the first, second and third positions and/or distances, based on the data indicative of the position and/or motion of the vehicle.

(130) In some embodiments, the vehicle exterior inspection system further comprises: a second support member; a fourth sensor array coupled to the second support member and comprising a fourth set of cameras positioned to capture images of wheels of the vehicle being imaged; a fifth sensor array coupled to the second support member and comprising a fifth set of cameras positioned to capture images of a side of the vehicle being imaged; and a sixth sensor array coupled to the second support member and comprising a sixth set of cameras positioned to capture images of a roof of the vehicle being imaged.

(131) In some embodiments, the vehicle exterior inspection system is portable and is collapsible between a deployed and a stowed configuration, and is configured to image the vehicle when in the deployed configuration; and the vehicle undercarriage inspection system weighs less than 10 pounds, and further comprises a handle attached to the base for lifting the vehicle undercarriage

inspection system.

(132) In some embodiments, one or more of the first, second, third and fourth sensor arrays comprise one or more of: a microphone, an infrared camera, a thermal camera, a magnetometer, a time of flight sensor, a light source, and/or an air quality sensor.

(133) In some embodiments, the first, second, and third sensor arrays are configured such that the combined FOV of the first, second and third sets of cameras spans at least 150 inches in height, 300 inches in length and 120 inches in width.

(134) Some embodiments provide for a vehicle inspection system for analyzing the condition of a vehicle, the system comprising: (A) a vehicle exterior inspection system comprising: a first support member; a first sensor array coupled to the first support member and comprising a first set of cameras positioned to capture images of wheels of the vehicle being imaged; a second sensor array coupled to the first support member and comprising a second set of cameras positioned to capture images of a side of the vehicle being imaged; and a third sensor array coupled to the first support member and comprising a third set of cameras positioned to capture images of a roof of the vehicle being imaged; and (B) a vehicle undercarriage inspection system comprising: a base having a width and a depth respectively extending along first and second directions orthogonal to one another, the width extending from a first end of the base to a second end of the base, the base supporting a fourth sensor array configured to capture images of an undercarriage of the vehicle, wherein the fourth sensor array comprises: a first camera positioned at a first side of the base, and oriented towards the first side of the base; a second camera positioned at a second side of the base, and oriented towards the second side of the base; and a third camera positioned between the first and second cameras; and (C) a computer hardware processor configured to perform: obtaining a first plurality of images of the vehicle captured using the first, second and third sets of cameras of the vehicle exterior inspection system; and obtaining a second plurality of images of the undercarriage of the vehicle captured using the fourth sensor array of the vehicle undercarriage inspection system; processing images of the first and second pluralities of images, using at least one trained machine learning (ML) model, to determine whether the vehicle has one or more defects; and generating a vehicle condition report based on results of the processing of the images and the composite image.

(135) In some embodiments, the computer hardware processor is further configured to perform: generating a composite image of the undercarriage of the vehicle by combining images of the second plurality of images, wherein the composite image is processed using the at least one machine learning model to determine whether the vehicle has the one or more defects. The one or more defects include: scratches to an exterior of the vehicle; cracked windows, mirrors, or windshields, chipped paint, dents to the exterior of the vehicle, misaligned body panels, missing vehicle parts, non-standard replacement parts, non-standard paint, aftermarket vehicle accessories, rust/corrosion on the vehicle, damaged wheels, damaged tires, bald tires, tire sidewall bubbles, broken tire valves, wheel misalignment, mismatched tires, brake rotor discoloration, brake rotor damage, brake rotor wear, a missing catalytic converter and/or suspension modifications.

(136) In some embodiments, the computer hardware processor is further configured to perform: generating a 3D model of the of the vehicle based on the first and second pluralities of images; generating a visualization of the 3D model; and providing access to the visualization to one or more users.

(137) In some embodiments, the computer hardware processor is further configured to perform: before processing the images of the first plurality of images, identifying a subset of the first plurality of images based on a pose of the vehicle in images of the plurality of images, wherein processing the images of the first plurality of images comprises processing the subset of images.

(138) In some embodiments, the vehicle undercarriage imaging system further comprises a sensor configured to output data indicative of the position and/or motion of the vehicle relative to the vehicle undercarriage inspection system; and the computer hardware processor is further configured to perform: determining, based on the data indicative of the position and/or motion of

the vehicle, a speed of the vehicle relative to the vehicle undercarriage inspection system, wherein the composite image is generated based on the vehicle speed.

(139) In some embodiments, one or more of the first, second, third and fourth sensor arrays comprise one or more of: a microphone, an infrared camera, a thermal camera, a magnetometer, a time of flight sensor, a light source, and/or an air quality sensor.

(140) In some embodiments, obtaining the first plurality of images comprises capturing the first plurality of images of the vehicle using the first, second and third sets of cameras of the vehicle exterior inspection system; and obtaining the second plurality of images comprises capturing the second plurality of images of the undercarriage of the vehicle using the fourth sensor array of the vehicle undercarriage inspection system.

(141) Some embodiments provide for a vehicle inspection system, for inspecting a vehicle, the vehicle inspection system comprising: (A) a vehicle exterior inspection system comprising: a first support member comprising a first portion and a second portion angled relative to the first portion; a first plurality of sensor arrays coupled to the first support member, the first plurality of sensor arrays comprising: a first sensor array comprising a first set of cameras oriented in multiple first directions, the first sensor array being coupled to the first support member at a position at which the first set of cameras has one or more wheels of a vehicle in its field of view (FOV) when the first sensor array is being used to image the vehicle; a second sensor array comprising a second set of cameras oriented in multiple second directions, the second sensor array being coupled to the first support member at a position at which the second set of cameras has a first side of the vehicle in its FOV when the second sensor array is being used to image the vehicle; and a third sensor array comprising a third set of cameras oriented in multiple third directions, the third sensor array being coupled to the first support member at a position at which the third set of cameras has a roof of the vehicle in its FOV when the third sensor array is being used to image the vehicle; and (B) a vehicle undercarriage inspection system, comprising: a base having a width and a depth respectively extending along first and second directions orthogonal to one another, the width extending from a first end of the base to a second end of the base; a fourth sensor array coupled to the base, the fourth sensor array comprising a set of cameras oriented in multiple directions, the set of cameras including: a first camera oriented in part towards the first end of the base; a second camera oriented in part towards the second end of the base; and a third camera positioned between the first and second cameras.

(142) It should be appreciated that the techniques described herein may be implemented in any of numerous ways, as the techniques are not limited to any particular manner of implementation. Examples of details of implementation are provided herein solely for illustrative purposes. Furthermore, the techniques disclosed herein may be used individually or in any suitable combination, as aspects of the technology described herein are not limited to the use of any particular technique or combination of techniques.

(143) FIG. 1A depicts an example environment to which a vehicle inspection system is deployed, according to some embodiments. The environment **100** includes vehicle inspection system **110**, vehicle **102** and vehicle inspector **101**.

(144) The vehicle inspection system **110** includes vehicle undercarriage inspection system **111**, vehicle exterior inspection system **112**, and other sensors **113**. The other sensors **113** include a camera **114**, a MVDD **115**, and mobile device **116**. In some embodiments, the other sensors may include further sensors such as a device to record OBD codes from vehicle **102**. As described herein, the vehicle inspection system **110** may include any number and/or combination of sensors **111-116**.

(145) The vehicle undercarriage inspection system **111** is positioned between the two support members of the vehicle exterior inspection system **112**. In some embodiments, the vehicle undercarriage inspection system is configured to obtain data from the undercarriage of the vehicle as the vehicle drives over the vehicle undercarriage inspection system **111**. In some embodiments,

the vehicle undercarriage inspection system **111** includes a sensor array, which includes one or more sensors for recording data from the undercarriage of the vehicle. In some embodiments, data collected by the vehicle undercarriage inspection system **111** may be used to generate a composite image of the undercarriage of the vehicle, and/or in determining one or more characteristics and/or defects of the vehicle. Example vehicle undercarriage inspection systems are further described herein with reference to FIGS. 7-16C.

(146) The vehicle exterior inspection system **112** includes two support members which collect data about the exterior of the vehicle, as the vehicle **102** drives past the support members of the vehicle exterior inspection system. In some embodiments, the vehicle exterior inspection system **112**. In some embodiments, the support members of the vehicle exterior inspection system **112** include one or more sensor arrays which record data about the exterior of the vehicle as the vehicle drives past the support members of the vehicle exterior inspection system **112**. In some embodiments, the sensors and/or sensor arrays of the vehicle exterior inspection system **112** may be positioned to record different portions of the vehicle **102**. In some embodiments, the sensors and/or sensor arrays of the vehicle exterior inspection system **112** may be angled at different directions to capture data from different portions of the exterior of the vehicle. In some embodiments, data collected by the vehicle exterior inspection system **112** may be used in determining one or more characteristics and/or defects of the vehicle **102**. Example vehicle exterior inspection systems are further described herein with reference to FIGS. 17A-29C.

(147) In some embodiments, vehicle inspector **101** may use camera **114** to capture images of the vehicle **102**. In some embodiments, the camera **114** may be used to capture images of the front of the vehicle, and/or the rear of the vehicle. In some embodiments, the camera **114** may be used to capture images of the interior of the vehicle **102**. In some embodiments, images captured by the camera **114** may be used in determining one or more characteristics and/or defects of the vehicle **102**.

(148) In some embodiments, vehicle inspector **101** may place MVDD at the engine of the vehicle, to capture data related to the engine of the vehicle **102**. In some embodiments, the MVDD may capture data related to the engine of the vehicle **102** when the vehicle **102** is being driven. In some embodiments, the MVDD may capture data related to the engine of the vehicle **102** when the vehicle **102** is driven over the vehicle undercarriage inspection system **111** and/or past the support members of the vehicle exterior inspection system. In some embodiments, the data related to the engine of the vehicle **102** may be used in determining one or more defects and/or characteristics of the vehicle **102**.

(149) In some embodiments, vehicle inspector **101** may use mobile device **116** to capture images of the vehicle **102**. In some embodiments, the mobile device **116** may be used to capture images of the front of the vehicle, and/or the rear of the vehicle. In some embodiments, the mobile device **116** may be used to capture images of the interior of the vehicle **102**. In some embodiments, the mobile device **116** may be used to capture other data related to the vehicle **102**, for example audio data and/or magnetic field data. In some embodiments, data captured by the mobile device **116** may be used in determining one or more characteristics and/or defects of the vehicle **102**.

(150) In some embodiments, vehicle inspector **101** may control the capturing of data by the vehicle inspection system using mobile device **116**. In some embodiments, the mobile device **116** may be connected to one or more components of the vehicle inspection system **110**. In some embodiments, the mobile device **116** may provide an application which allows for the controlling of components of the vehicle inspection system **110**.

(151) In some embodiments, one or more components of the vehicle inspection system **110** may include a processor. In some embodiments the processor(s) of the vehicle inspection system **110** may be used in controlling the capturing of data related to the vehicle **102**. In some embodiments, the processor(s) may control automatic capturing of data related to the vehicle **102**. In some embodiments, the processor(s) of the vehicle inspection system **110** may allow the vehicle

inspector **101** to control the capturing of data related to the vehicle **102**. In some embodiments, the processor(s) of the vehicle inspection system **110** may allow for capturing of data related to the vehicle **102** which is automatic in part, and in part controlled by the vehicle inspector **101**.

(152) In some embodiments, the processor(s) of the vehicle inspection system **110** may process and/or analyze data captured using the vehicle inspection system. In some embodiments, the processor(s) of the vehicle inspection system **110** may determine one or more characteristics and/or defects of the vehicle **102**, based on the captured data. In some embodiments, the processor(s) of the vehicle inspection system may generate a vehicle condition report for vehicle **102**. In some embodiments, the processor(s) of the vehicle inspection system may display a vehicle condition report for review by vehicle inspector **101**. In some embodiments, a vehicle condition report may be displayed on mobile device **116**. In some embodiments, the processor(s) of the vehicle inspection system **110** may provide a user interface for displaying of vehicle data and/or controlling of components of the vehicle inspection system.

(153) FIG. **1B** is a diagram illustrating the processor(s) of a vehicle inspection system, according to some embodiments. In FIG. **1B**, vehicle inspection system **110** includes vehicle undercarriage inspection system **111**, vehicle exterior inspection system **112**, additional sensors **113**, and processor(s) **120**. Processor(s) **120** may be part of one or more computing device(s) (laptops, desktops, single-board computing devices such as a Raspberry Pi, a tablet, a smartphone, a rackmount computer, etc.). The processor(s) **120** may be programmed to perform one or more tasks by executing processor-executable instructions. Processor-executable instructions may be organized into one or more software modules as shown in FIG. **1B**. These are shown inside the processor-executable instructions box to indicate that they can be used to program the processor(s) **120**.

(154) As described herein, in some embodiments, the processor(s) **120** may be implemented as a part of the components of the vehicle inspection system **110**, for example as a part of the vehicle undercarriage inspection system **111**, the vehicle exterior inspection system **112**, and/or the additional sensors **113**. In some embodiments, the processor(s) **120** may be implemented separately from the vehicle undercarriage inspection system **111**, vehicle exterior inspection system **112**, and additional sensors **113**, for example as part of a computer connected to the vehicle inspection system **110**. In some examples, the processor(s) **120** may be implemented remotely from the vehicle inspection system **110**, and may be connected to the vehicle undercarriage inspection system **111**, vehicle exterior inspection system **112**, and/or additional sensors **113** via a communication network. Thus, the processors **120** may include one or more processors and each such processor may be part of vehicle inspection system **110** or remote from vehicle inspection system **110**. In some embodiments, when processor(s) **120** include multiple processors, one or more processors may be co-located with vehicle inspection system **110** (e.g., integrated with or proximate to vehicle undercarriage inspection system and/or vehicle exterior inspection system) and one or more other processors may be located remotely from vehicle inspection system **110** (e.g., as part of a cloud computing infrastructure).

(155) The processor(s) **120** may transmit data to and/or receive data from the vehicle undercarriage inspection system **111**, vehicle exterior inspection system **112**, and additional sensors **113**. In some embodiments, the processor(s) **120** may transmit control signals to the vehicle undercarriage inspection system **111**, vehicle exterior inspection system **112**, and additional sensors **113**. In some embodiments, the control signals may trigger the vehicle undercarriage inspection system **111**, vehicle exterior inspection system **112**, and additional sensors **113** to begin and/or stop capturing of data related to a vehicle. In some embodiments, the processor(s) **120** may generate control signals based on sensor data received from the vehicle undercarriage inspection system **111**, vehicle exterior inspection system **112**, and additional sensors **113**, for example data related to the position and/or motion of the vehicle. In some embodiments, the processors may generate control signals automatically when the vehicle is determined to be in one or more specific locations. In some

embodiments, the processor(s) may transmit control signals to sensors of the vehicle undercarriage inspection system **111**, vehicle exterior inspection system **112**, and additional sensors **113**, individually based on the position and/or motion of the vehicle. In some embodiments, the processor(s) may transmit control signals to the vehicle undercarriage inspection system **111**, vehicle exterior inspection system **112**, and additional sensors **113** based on input of a user. (156) The processor(s) **120** may be programmed to perform one or more tasks by computer executable instructions in one or more software modules. Such software modules may include, as shown in FIG. **1B**, data processing and analysis module(s) **121**, alignment verification module(s) **122**, data formatting module(s) **123**, 3D model generation module **124**, condition report generation module **125**, user interface generation module **126**, system control module **127**, and one or more database(s) **129** storing machine learning models **128**.

(157) The data processing and analysis modules **121** may perform one or more operations on data received from the vehicle undercarriage inspection system **111**, vehicle exterior inspection system **112**, and/or additional sensors **113**. In some embodiments, the processing and analysis modules **121** may filter data, structure data and/or preprocess data for additional processing and analysis. In some embodiments, the data processing and analysis modules **121** may determine one or more vehicle characteristics from the data received from the vehicle undercarriage inspection system **111**, vehicle exterior inspection system **112**, and/or additional sensors **113**. In some embodiments, the data processing and analysis modules **121** may use one or more machine learning models, such as ML models **128** to determine the one or more vehicle characteristics. In some embodiments, the data processing and analysis modules **121** may determine one or more vehicle defects from the data received from the vehicle undercarriage inspection system **111**, vehicle exterior inspection system **112**, and/or additional sensors **113**. In some embodiments, the data processing and analysis modules may determine the one or more defects using one or more ML models, such as ML models **128**.

(158) The alignment verification module **122** may determine whether the vehicle is properly aligned with the vehicle inspection system **110** for inspection. In some embodiments, the alignment verification module may analyze data received from one or more sensors of the vehicle inspection system, for example cameras and/or TOF sensors. In some embodiments, the alignment verification module **122** determines an alignment of the vehicle relative to one or more components of the vehicle inspection system, for example the vehicle undercarriage inspection system **111** and/or the vehicle exterior inspection system **112**. In some embodiments, the alignment verification module **122** may determine an alignment of the vehicle and provide an indication of the alignment of the vehicle to one or more components of the vehicle inspection system, such as a mobile device or other component with a display. In some embodiments, the alignment of the vehicle may be a binary value, for example, aligned or not aligned. In some embodiments, when the alignment verification module **122** determines the vehicle is not aligned with the vehicle inspection system, the alignment verification module may provide an indication of an adjustment to be made to the vehicle, for example move vehicle left.

(159) The data formatting module(s) **123** may perform one or more operations on the data received from the vehicle undercarriage inspection system **111**, vehicle exterior inspection system **112**, and/or additional sensors **113**. In some embodiments, the data formatting modules **123** may format data such that it may be further used by other modules of the processor(s) **120**. In some embodiments, the data formatting module may generate a composite image of a vehicle undercarriage based on data received from the vehicle undercarriage inspection system **111**, for example by combining images captured by cameras of the vehicle undercarriage inspection system **111**. In some embodiments the composite image may be generated based on additional data received from the vehicle undercarriage inspection system **111**, for example data indicative of the position and/or motion of the vehicle such as data captured by a TOF sensor. In some embodiments, the data formatting modules **123** may determine subsets of data for analysis. In some

embodiments, the data formatting modules **123** may determine subsets of data for analysis by determining whether the data matches one or more criteria and in response to determining the data matches one or more criteria, including the data in a subset of data for analysis. In some embodiments, the data may be selected based on a level of noise in the data, the signal strength in the data, and/or a position of the vehicle within the data. In some embodiments, the data formatting modules may remove personally identifiable information from data, for example images received from the vehicle undercarriage inspection system **111**, vehicle exterior inspection system **112**, and/or additional sensors **113**. In some embodiments, the data formatting modules **123** may provide data to other modules for analysis, for example data processing and analysis modules **121**, alignment verification modules **122**, 3D model generation modules **124**, condition report generation module **125**, user interface generation module **126**, and/or system control module.

(160) In some embodiments, the 3D model generation module **124** may generate a 3D model of a vehicle based on data received from the vehicle undercarriage inspection system **111**, vehicle exterior inspection system **112**, and/or additional sensors **113**. In some embodiments, the 3D model generation module **124** may generate a 3D model of the exterior of the vehicle based on data received from the vehicle exterior inspection system **112**. In some embodiments, the 3D model generation module may generate a 3D model of the undercarriage of the vehicle based on data received from the vehicle undercarriage inspection system **111**. In some embodiments, the 3D model may be generated using one or more ML models, such as ML models **128**. In some embodiments, the 3D model is generated using photogrammetry. In some embodiments, the 3D model is generated using neural radiance fields. In some embodiments, the 3D model is generated using Gaussian splatting.

(161) The vehicle condition report generation module **125** may generate a vehicle condition report based on data received from the vehicle undercarriage inspection system **111**, vehicle exterior inspection system **112**, and/or additional sensors **113**. In some embodiments, the vehicle condition report generation module **125** may generate a vehicle condition report based on one or more characteristics and/or defects of the vehicle determined using the data processing and analysis modules **121**. In some embodiments, the condition report generation module **125** may generate a vehicle condition report that includes data related to a vehicle, for example images of the vehicle, and/or audio recordings of the vehicle. In some embodiments, the vehicle condition report generation module **125** may generate a vehicle condition report using data received from the data formatting modules **123**, for example, images with PII removed, a subset of images and/or other data, and/or a composite image of the vehicle undercarriage. In some embodiments, the condition report generation module may include a 3D model of the vehicle generated using the 3D model generation model **124**. In some embodiments, the condition report generation module may generate a vehicle condition report using data obtained from a user interface of the vehicle inspection system.

(162) User interface generation module **126** may provide a user interface of the vehicle inspection system on one or more displays connected to the vehicle inspection system. In some embodiments the user interface generation module **126** may provide a user interface on a mobile device of the vehicle inspection system, a computer connected to one or more components of the vehicle inspection system, and/or a device remote from the vehicle inspection system. In some embodiments, the user interface generation module **126** may generate a user interface which displays information related to a vehicle, for example, alignment data, a 3D model of a vehicle, and/or a vehicle condition report. In some embodiments, the user interface generation module **126** may provide vehicle data to a user responsive to a request for additional data, for example, the module **126** may provide additional images of a region of the vehicle responsive to a request for images of the region.

(163) The system control module **127** may generate and provide control signals to the vehicle undercarriage inspection system **111**, vehicle exterior inspection system **112**, and/or additional

sensors **113**. In some embodiments, the control signals may include signals to trigger the starting and/or stopping of recording data by sensors of the vehicle inspection system. In some embodiment, the control signals may be generated based on data obtained from the vehicle undercarriage inspection system **111**, vehicle exterior inspection system **112**, and/or additional sensors **113**, for example data indicative of the position and/or motion of the vehicle. In some embodiments, the system control module **127** may generate control signals based on inputs received from a user of the vehicle inspection system **110**.

(164) Databases **129** store ML models **128**. In some embodiments, the databases **129** are implemented as a part of one or more components of the vehicle inspection system **110**, for example as physical storage. In some embodiments, the databases **129** are accessible by components of the vehicle inspection system, for example as cloud storage.

(165) ML models **128** may be used by modules of the vehicle inspection system to analyze data and/or process obtained from the vehicle undercarriage inspection system **111**, vehicle exterior inspection system **112**, and/or additional sensors **113**. In some embodiments, the ML models **128** may be used in determining one or more vehicle defects and/or characteristics. Machine learning models for determining vehicle characteristics and/or defects are described in U.S. Pat. No. 11,631,289, entitled “Vehicle Audio Capture and Diagnostics,” filed Jan. 22, 2020, U.S. Pat. No. 10,893,213, entitled “Vehicle Undercarriage Imaging System,” filed Apr. 2, 2019, U.S. Pat. No. 18,778,247, entitled “Methods and Systems for Identifying Potential Vehicle Defects,” filed Jul. 19, 2024, and U.S. patent application Ser. No. 18/483,935, entitled: “Machine Learning and Magnetic Field Sensing Techniques for Vehicle Inspection and Condition Analysis,” filed Oct. 10, 2023, each of which is incorporated by reference herein in its entirety. In some embodiments, the ML models may be used by the alignment verification modules **122**, data formatting modules **123**, 3D model generation modules **124**, and/or condition report generation modules **125**.

(166) FIG. **1C** illustrates an example of an environment **130** to which multiple vehicle inspection systems are deployed, according to some embodiments. The inspections may be used to collect information about one or more vehicles and analyze the collected information to determine whether any one of the vehicles has or is likely to have one or more potential defects. The collected information may be collected by inspectors in connection with one or vehicle inspections, such as vehicle inspections **140**, **150**, **160** and **170**.

(167) In the illustrated example of FIG. **1C**, the environment may include any suitable number of mobile devices for collecting data about any suitable number of vehicles as aspects of the technology described herein are not limited by the number of devices that are part of the vehicle inspection system or the number of vehicles that such devices may be used to examine. As shown in the example of FIG. **1C**, four vehicle inspections are being performed, **140**, **150**, **160** and **170**, however greater or fewer inspections may be performed in such environments.

(168) As shown in FIG. **1C**, each inspection is performed using different devices. Inspection **140** is performed on vehicle **141** by inspector **142**, using vehicle exterior inspection system **143**, vehicle undercarriage inspection system **144**, mobile device **145** and MVDD **146**. Vehicle inspection **150** is performed on vehicle **151** by inspector **152** using vehicle undercarriage inspection system **153** and mobile device **154**. Vehicle inspection **160** is performed on vehicle **161** by inspector **162** using vehicle exterior inspection system **163** and mobile device **164**. Vehicle inspection **170** is performed on vehicle **171** by inspector **172** using mobile device **173**.

(169) During vehicle inspections **140**, **150**, **160**, and **170** the data collected may be provided through network **180** to a remote computer **182** and/or server(s) **181** where the data may be stored and/or processed by trained machine learning models. In some embodiments, the vehicle information includes data gathered at least in part during inspection of the vehicle using a vehicle inspection system, as described herein. For example, the vehicle information may include audio recordings acquired by recording sounds of various vehicle components while the vehicle is in operation. As another example, the vehicle information may include a photo and/or video acquired

during the vehicle inspection of the interior and/or exterior of the vehicle. As yet another example, the vehicle information may include on-board diagnostic codes data, such as on-board diagnostics II (OBDII) codes and/or a live data stream from the vehicles on-board diagnostic system. In some embodiments, the data may be used to generate a vehicle condition report, as described herein.

(170) In some embodiments, the data collected during vehicle inspections, and/or results of analysis by ML models (e.g., identified defects and/or characteristics, and/or likelihoods of defects and/or characteristics) may be provided to reviewer **183** on remote computer **182**. The reviewer **183** may review the data to determine the accuracy of the results of the analysis by the ML models and whether one or more defects and/or characteristics are present on the vehicle. In some embodiments, reviewer **183** may update the data associated with a vehicle inspection, and/or may make changes to a vehicle condition report based on their review.

(171) FIG. **1D** illustrates an example vehicle examination process **190** for use with a digital vehicle auction platform, according to some embodiments. As shown in FIG. **1D**, vehicle examination **190** may involve a user uploading a vehicle listing for sale **191**. In some embodiments, a vehicle sale profile may be uploaded to a server, on which the platform is hosted, for display as an available vehicle for sale. The user may perform said uploading via a software application installed on a user's device. That software application may be an application for connecting with a digital vehicle auction platform and/or an Internet browser providing web-based access to the digital vehicle auction platform.

(172) Once uploaded, a vehicle condition inspector **192** may conduct an examination of the vehicle. That examination may involve the inspector to physically inspect the vehicle. The examination process may involve having the inspector use a vehicle inspection system to collect data about the vehicle, as described herein. The inspector may have a mobile device as part of the vehicle inspection system and may use that device to interact with the vehicle inspection system. The mobile device may have a software application executing thereon that may instruct the inspector to take the vehicle through a series of stages (e.g., starting the engine, revving the engine, idling the engine, moving the vehicle, turning off the engine, a series of any of the preceding stages sequenced in any suitable way and repeating any one stage any suitable number of times) while the vehicle inspection gathers sensor data during at least some of those stages. As described herein, the collected data may be analyzed (e.g., using one or more trained ML models described herein) and the results of the analysis may be included in a vehicle condition report that serves aggregation of data regarding the vehicle's current condition. When the vehicle is presented to potential buyers on the digital platform, the vehicle condition report may be presented to parties potentially interested in bidding on the vehicle.

(173) In some embodiments, the vehicle's condition report may include a review of the vehicle's characteristics, defects, damage, and/or faults. The vehicle condition report may include multiple (e.g., at least 10, 20, 30, etc.) photos of the exterior, interior, undercarriage, engine bay, and/or any other suitable component. Additionally or alternatively, the vehicle condition report may include the VIN number, odometer reading, engine fuel type, cosmetic issues observed by a user, mechanical issues observed by a user, and any of the other types of information about a vehicle described herein. In some embodiments, the vehicle condition report may include signals acquired of the vehicle during the vehicle examination, as described herein including with reference to FIG. **2**.

(174) As described herein, in some embodiments, the vehicle examination includes acquiring sensor signals using vehicle inspection system. Following the vehicle examination, the vehicle condition inspector generates a vehicle condition report associated with the vehicle for which a vehicle sale profile has been created. The vehicle condition report may include the signals and/or metadata acquired during the vehicle examination.

(175) In some embodiments, the vehicle examination may occur prior to the uploading of a vehicle sale profile **191**. Accordingly, in some embodiments, the vehicle condition report **193** may be

generated along with the vehicle sale profile. In some embodiments, the vehicle condition report may be generated prior to the vehicle sale profile. However, once the vehicle sale profile is created it may be matched with the vehicle condition report based on the VIN or other available identification information.

(176) However, in generating the vehicle condition report, user observations as to potential vehicle conditions may not be reliable. For example, engine defects may be very subtle issues which may only be discernible by automobile experts, if observable by physical observation at all.

Accordingly, a vehicle defect may go unnoticed or even misclassified resulting in inaccurate vehicle condition report. In such an instance, an unknowing buyer may purchase the anomalous vehicle and upon finding such an undisclosed issue, may be eligible to file for an arbitration. More accurate vehicle condition reports may reduce the occurrence of undisclosed vehicle defects and by extension arbitrations.

(177) Accordingly, to decrease the risk of undisclosed vehicle defects, the signals acquired during the vehicle examination by a plurality of sensors of the vehicle inspection device may be processed by one or trained machine learning models to detect the presence or absence of potential vehicle defects. After the generated of the vehicle condition report, the acquired signals may be processed by trained machine learning model(s) **194** to produce one or more outputs **195**, which may be indicative of one or more defects present in the vehicle (as determined based on the sensor data and/or metadata processed). In some embodiments, the output(s) **195** may be compared to threshold(s) **196** to determine if the output(s) **195** are indicative of the presence or absence of a one or more potential vehicle defects.

(178) In some embodiments, comparing output(s) **195** to threshold(s) **196** may be implemented using class-wise thresholds such that if a predicted vehicle defect exceeds its class threshold the vehicle is subsequently flagged with the corresponding defect. In some embodiments, the thresholds may be tuned to favor very precise predictions at the expense of recall to decrease the likelihood of falsely labeling a vehicle as having a vehicle defect when it is in fact clean. For example, different classes of defects (e.g., internal engine noise, after market vehicle parts, rough running engine, timing chain noise, etc.) may be associated with different threshold confidences such that different degrees of confidence may be required for different types of defects in order to flag them as potential defects in the report.

(179) After determining whether the output(s) **195** are indicative of the presence or absence of a potential vehicle defect, the vehicle condition report may be flagged for the presence of the potential vehicle defect. In some embodiments, if the processing by the trained machine learning model(s) identifies potential defects which were not listed in the vehicle condition report **193**, then the vehicle condition report may be flagged for additional review by the vehicle condition inspector **192**, including conducting a second vehicle examination. Such a second vehicle examination may include collecting additional data about the vehicle using vehicle inspection system, for example, by collecting additional sensor data and subsequently analyzing it using one or multiple trained ML models.

(180) In some embodiments, where a potential defect was listed in the vehicle condition report, but the analysis by the trained machine learning models identified that the listed vehicle condition was absent from the data, the vehicle condition report may also be flagged for an additional review by the vehicle condition inspector **192**, including conducting a second vehicle examination. In some embodiments, the output of the trained machine learning model(s) may be used to update the vehicle condition report to indicate either the presence and/or the absence of a vehicle defect without requiring an additional review by the vehicle condition inspector.

(181) FIG. 2 illustrates an example vehicle condition report, according to some embodiments. In some embodiments, vehicle report **200** may include basic vehicle data **210**, vehicle data **221**, and detected defect list **222**. Vehicle data **221** may include data recorded during a vehicle inspection, for example audio data, magnetometer data, air quality data, position data, metadata, and/or

vibration data. In some embodiments, vehicle data may include additional data recorded by a vehicle inspection system, as described herein. In some embodiments, the vehicle data is selectable to be viewed in detail by a user of a vehicle inspection system.

(182) As shown in the example of FIG. 2, basic vehicle data **210** may include vehicle model **211**, vehicle make **212**, vehicle year **213**, vehicle type **214**, trim type **215**, engine type **216**, VIN **217**, an odometer reading **218**, and one or more images **220** of the vehicle and/or any of its components (e.g., undercarriage, panels, doors, hood, engine block, rear, etc.) may be included in vehicle condition report **200**.

(183) The vehicle report of FIG. 2 is illustrative and that, in other examples, one or more other types of information may be included in the vehicle report in addition to or instead of the information shown in FIG. 2, as aspects of the technology described herein are not limited in this respect. For example, a vehicle condition report may include vehicle RPM data from the OBDII port and/or data from one or more other sensors (e.g., thermal, humidity, VOC, etc.). As another example, any list part of list **222** may be displayed with a corresponding numeric value (e.g., a probability, a confidence value, a likelihood) indicating a degree of confidence in the vehicle actually having that defect. Such numeric values may be generated by the trained ML models described herein, for example.

(184) FIGS. 3A-3F illustrate steps in an example vehicle inspection process, according to some embodiments.

(185) In FIG. 3A, components of a vehicle inspection system are shown. The vehicle inspection system includes vehicle undercarriage inspection system **310** and support members **320A** and **320B** of a vehicle exterior inspection system. The vehicle inspection may be performed by inspector **301** on vehicle **300**.

(186) Support members **320A** and **B** contain sensor arrays including cameras **321-323A** and **321-323B**, respectively. As shown the sensor arrays include three cameras, each angled in different directions. In FIG. 3A, cameras **321A** and **321B** have fields of view (FOV) s **324A** and **324B**, respectively, facing vehicle **300**. Cameras **322A** and **B** have FOVs **325A** and **325B**, respectively, which face the opposite support member. Cameras **323A** and **323B** have FOVs **326A** and **326B**, respectively, which face away from vehicle **300**.

(187) As shown, the support members of the vehicle exterior inspection system have sensor arrays including three cameras, however, the vehicle exterior inspection system may include a greater number of sensor arrays and/or cameras, as described herein.

(188) In some embodiments, a registration process may be performed between the components of a vehicle inspection system, before performing an inspection. In some embodiments, the registration process includes communicatively connecting the components, for example through wired and/or wireless connections. In some embodiments the registration process requires registering the positions of the components, for example using sensors of the system. In some embodiments the registration process involves capturing images and/or data from the components including the position of one or more markers and/or fiducials on the components.

(189) In some embodiments, the alignment of the components of the vehicle inspection system may be verified and/or adjusted before performing an inspection.

(190) In FIG. 3B, the inspector **301** places a MVDD **330** at the engine of the vehicle **300**. The MVDD may collect audio and vibration signals of the engine of the vehicle, as described herein. In FIG. 3C, the inspector **301** connects a vehicle diagnostic device **340** to the vehicle **300**. In some embodiments the vehicle diagnostic device **340** is configured to record metadata from the vehicle **300**. In some embodiments, the vehicle diagnostic device **340** is configured to record OBD and/or OBDII signals from the vehicle **300**.

(191) In FIG. 3D, the inspector **301** drives the vehicle **300**. The inspector drives the vehicle over vehicle undercarriage inspection system **310**. In some embodiments, the vehicle undercarriage inspection device may be configured to automatically start and stop recording of data related to the

undercarriage of the vehicle as the vehicle passes over.

(192) In FIG. 3D, The inspector **301** drives the vehicle through the fields of view of the cameras of the vehicle exterior inspection system. The vehicle begins in fields of view **324A** and **324B** in which cameras **321A** and **321B** capture images of the vehicle **300**. The vehicle then passes into fields of view **325A** and **325B** in which cameras **322A** and **322B** capture images of the vehicle. Finally the vehicle passes into fields of view **326A** and **326B** in which cameras **323A** and **323B** capture images of the vehicle.

(193) In sum embodiments, the cameras of the vehicle exterior inspection device are configured to automatically start and stop capturing of images of the vehicle as the vehicle passes into and out of their respective fields of view.

(194) In FIG. 3E, the vehicle **300** has passed through all fields of view of the cameras of the vehicle exterior inspection system, and has passed over the vehicle undercarriage inspection system **310**. And both systems have completed capturing data of the vehicle.

(195) In FIG. 3F, The inspector **301** moves around vehicle **300** to capture additional images of the vehicle using camera **350**. In some embodiments, the inspector **301** uses camera **350** to capture images of the front, rear, VIN plate, and/or engine bay of a vehicle. In some embodiments, the inspector **301** captures images of the interior of the vehicle using camera **350**.

(196) After completion of the vehicle inspection process as detailed in FIGS. 3A through 3F, the data collected using the sensors of the vehicle inspection system may be analyzed using one or more processors to determine characteristics and/or defects of the vehicle as described herein.

(197) In some embodiments, the data may be analyzed, for example by one or more ML models to determine if it is of sufficient quality for analysis. In some examples, it may be determined the inspection process was unsuccessful and needs to be reperformed. In some embodiments, the user is notified the inspection process was unsuccessful via a user interface of the vehicle inspection system.

(198) The vehicle inspection process of FIGS. 3A-3F allows for data to be collected from a vehicle efficiently, from multiple sources, during a single pass of the vehicle through the vehicle inspection system. This vehicle inspection process is more efficient than conventional inspection processes and allows for faster vehicle inspections to be performed.

(199) FIG. 4A illustrates example image data which may be captured by a vehicle inspection system, according to some embodiments. In the example of FIG. 4A, the vehicle inspection system includes a vehicle exterior inspection system and a vehicle undercarriage inspection system. The vehicle exterior inspection system includes 2 support members **420A** and **420B**. Each support member **420A** and **420B** includes three camera sets, **421A-423A** and **421B-423B**, respectively. Each camera set may include multiple cameras oriented in different directions as described herein. Each camera set may be configured to capture images of different portions of the vehicle during a vehicle inspection process.

(200) The top camera sets **421-A** and **421B** are configured to capture images of the roof of the vehicle **424**. The middle two camera sets, **422A** and **422B**, are configured to capture images of multiple components of the vehicle **425**. The middle two camera sets **422A** and **422B** are configured to capture images of the front corners, rear corners, front laterals, rear laterals, sides, and trim badges of both sides of the vehicle. In addition, the middle two camera sets **422A** and **422B** are configured to capture images of the back front and hood of the vehicle. Finally, the bottom two camera sets **423A** and **423B** are configured to capture images of the laterals, front wheels, rear wheels and rocker panels of the vehicle on both sides of the vehicle, as shown by reference **426**.

(201) The vehicle undercarriage inspection system **410** is additionally configured to capture images of the undercarriage of the vehicle, as represented by reference **412**. The vehicle undercarriage inspection system **410** may include a set of cameras configured to capture different frames of the vehicle undercarriage, including the left, rearm right and front of the undercarriage, as represented

by reference **412**. The vehicle undercarriage inspection system may capture additional frames of the vehicle undercarriage for use in analyses.

(202) FIG. **4B** is an example of images of a vehicle interior which may be captured during a vehicle inspection process, according to some embodiments. The images **430** of FIG. **4B** may be captured, for example, as described with reference to FIG. **3F**. The images of the vehicle interior may include images of the driver side front seat, passenger side front seat, driver side rear seat, passenger side rear seat, center console, odometer, gauge cluster, trunk, and/or the user manual and keys of the vehicle. The vehicle interior images may be analyzed as described herein. In some embodiments, the images **430** may be analyzed to determine one or more defects and/or characteristics of the interior of the vehicle such as damaged seats, damaged floor, damaged headliner, damaged panels interior color, odometer reading, and/or warning lights, among other defects and/or characteristics.

(203) FIG. **5A** illustrates one or more trained machine learning models **500** for processing images of a vehicle to evaluate the vehicle's condition, according to some embodiments. As shown in FIG. **5A**, trained machine learning model **500** includes trained machine learning model **503** for processing the vehicle images **501** to obtain outputs **505**.

(204) In some embodiments, the images **501** may be captured as a part of a vehicle inspection, performed using a vehicle inspection system. For example, as described with reference to FIGS. **3A-F**. In some embodiments, the images **501** may include the views of the vehicle described with reference to FIGS. **4A-4B**.

(205) In some embodiments, the images **502** of the vehicle may be a series of images acquired of different views of the vehicle or may be a single image constructed from processing a series of images as described herein. In some embodiments, the vehicle images **502** include images and/or a composite image of the undercarriage of the vehicle. In some embodiments, the vehicle images **502** include an image and/or images of the exterior of the vehicle. In some embodiments, the images **502** may be collected from a vehicle inspection system, as described herein. The images **502** may include multiple color channels and may be formatted in any suitable image format. For example, the image may be a Joint Photographic Expert Group (JPEG) image or a Portable Network Graphics (PNG) image, where each pixel has a corresponding value indicating the red, blue, and green color components.

(206) In some embodiments, trained machine learning model **503** for processing the images of the vehicle may include preprocessing to generate input images for trained machine learning model **504**. Preprocessing to generate input images may modify at least one characteristic of the images of the vehicle, prior to the image being processed by the trained machine learning model **504**.

(207) Trained machine learning model **504** may be any suitable machine learning model for image analysis. In some embodiments, trained machine learning model **504** is a 2D convolutional neural network. In some embodiments, ML model **504** is structured as a deep convolutional neural network (DCNN). In some embodiments, ML model **504** is structured as a YOLO architecture neural network. In some embodiments, ML model **504** is a transformer-based model. In some embodiments, ML model **504** is a diffusion model. In some embodiments the machine learning model **504** is configured as an EfficientNet convolutional neural network.

(208) Outputs **505** may include a list of vehicle defects and the respective likelihood of the defect being present in the vehicle. As shown in FIG. **5A** outputs **505** include the likelihood of a first vehicle defect **506**, the likelihood of a vehicle image defect **507**, and a likelihood of an nth vehicle defect **508**. For example, when n=8 there may be 8 output classes (e.g., types of vehicle defects) including 7 defect classes and one affirmative quality class. In some embodiments, the outputs **505** include likelihood of particular vehicle characteristics being present. Examples of vehicle characteristics and defects are described herein. In some embodiments, the outputs include likelihoods of image defects, for example incorrect cropping, insufficient detail, dirty lens, haze or glare, incorrect trim, and/or poor lighting, among other image defects.

(209) FIG. 5B illustrates one or more trained machine learning models **510** for processing images and data of a vehicle to evaluate the vehicle's condition, according to some embodiments. As shown in FIG. 5B, trained machine learning model **510** includes trained machine learning model **514** for processing the vehicle data **511** to obtain outputs **516**.

(210) In some embodiments, the data **511** may be captured as a part of a vehicle inspection, performed using a vehicle inspection system. For example, as described with reference to FIGS. 3A-F. In some embodiments, the images **512** of the data **511** may include the views of the vehicle described with reference to FIGS. 4A-4B.

(211) In some embodiments, the vehicle data may include images **512** of and sensor data **513** about a vehicle. In some embodiments, the images **512** of the vehicle may be a series of images acquired of different views of the vehicle or may be a single image constructed from processing a series of images as described herein. In some embodiments, the images **512** may be formatted as described with reference to images **502** of FIG. 5A.

(212) In some embodiments, the sensor data **513** may include data collected by one or more sensors of a vehicle inspection system, as described herein. For example, the sensor data **513** may include data collected by a microphone, an infrared camera, a thermal camera, a magnetometer, a time of flight sensor, a MVDD, a device configured to collect vehicle metadata, and/or an air quality sensor.

(213) In some embodiments, trained machine learning model **514** for processing the vehicle data may include preprocessing to generate input data for trained machine learning model **515**. Preprocessing to generate input data may modify at least one characteristic of the vehicle data, prior to the data being processed by the trained machine learning model **515**.

(214) In some embodiments, the trained machine learning models **514** may process vehicle images **512** and sensor data **513** separately. In some embodiments, the trained machine learning models **514** may process vehicle images **512** and sensor data **513** together. In some embodiments, the trained machine learning models **514** may process vehicle images **512** and sensor data **513** together in part and separately in part.

(215) Trained machine learning model **515** may be any suitable machine learning model for image and/or sensor data analysis. In some embodiments, trained machine learning model **515** is a 2D convolutional neural network. In some embodiments, ML model **515** is structured as a deep convolutional neural network (DCNN). In some embodiments, ML model **515** is structured as a YOLO architecture neural network. In some embodiments, ML model **515** is a transformer-based model. In some embodiments, ML model **515** is a diffusion model. In some embodiments the machine learning model **515** is configured as an EfficientNet convolutional neural network.

(216) Outputs **516** may include a list of vehicle defects and the respective likelihood of the defect being present in the vehicle. As shown in FIG. 5B outputs **516** include the likelihood of a first vehicle defect **517**, the likelihood of a vehicle image defect **518**, and a likelihood of an nth vehicle defect **519**. For example, when n=8 there may be 8 output classes (e.g., types of vehicle defects) including 7 defect classes and one affirmative quality class. In some embodiments, the outputs **516** include likelihood of particular vehicle characteristics being present. Examples of vehicle characteristics and defects are described herein. In some embodiments, the outputs include likelihoods of image and/or data defects, for example incorrect cropping, insufficient detail, dirty lens, haze or glare, incorrect trim, insufficient magnitude, too noisy, and/or poor lighting, among other defects.

(217) FIG. 5C illustrates one or more trained machine learning models **523** for processing images of the interior of a vehicle to evaluate the vehicle's condition, according to some embodiments. As shown in FIG. 5C, trained machine learning model **520** includes trained machine learning model **523** for processing the vehicle interior images **522** to obtain outputs **525**.

(218) In some embodiments, the vehicle interior images **522** may be captured as a part of a vehicle inspection, performed using a vehicle inspection system. For example, as described with reference

to FIGS. 3A-F. In some embodiments, the vehicle interior images 522 may include the views of the interior of the vehicle described with reference to FIG. 4B.

(219) In some embodiments, trained machine learning model 523 for processing the vehicle interior images may include preprocessing to generate input data for trained machine learning model 524. Preprocessing to generate input data may modify at least one characteristic of the vehicle interior images, prior to the data being processed by the trained machine learning model 524.

(220) Trained machine learning model 523 may be any suitable machine learning model for image analysis. In some embodiments, trained machine learning model 523 is a 2D convolutional neural network. In some embodiments, ML model 523 is structured as a deep convolutional neural network (DCNN). In some embodiments, ML model 523 is structured as a YOLO architecture neural network. In some embodiments, ML model 523 is a transformer-based model. In some embodiments, ML model 523 is a diffusion model. In some embodiments the machine learning model 523 is configured as an EfficientNet convolutional neural network, which takes interior images as inputs and is configured to output prediction labels for identified damage and/or defects.

(221) Outputs 525 may include a list of vehicle defects and the respective likelihood of the defect being present in the vehicle. As shown in FIG. 5C outputs 525 include the likelihood of a first vehicle defect 526, the likelihood of a vehicle image defect 527, and a likelihood of an nth vehicle defect 528. For example, when n=8 there may be 8 output classes (e.g., types of vehicle defects) including 7 defect classes and one affirmative quality class. In some embodiments, the outputs 525 include likelihood of particular vehicle characteristics being present. Examples of vehicle characteristics and defects are described herein. In some embodiments, the outputs include likelihoods of image defects, as described herein.

(222) FIG. 5D illustrates one or more trained machine learning models 530 for processing data of a vehicle to evaluate the vehicle's condition, according to some embodiments. As shown in FIG. 5D, trained machine learning model 530 includes trained machine learning model 533 for processing the vehicle data 531 to obtain outputs 535.

(223) In some embodiments, the data 531 may be captured as a part of a vehicle inspection, performed using a vehicle inspection system. For example, as described with reference to FIGS. 3A-F.

(224) In some embodiments, the vehicle data may sensor data 532 about a vehicle. In some embodiments, the sensor data 532 may include data collected by one or more sensors of a vehicle inspection system, as described herein. For example, the sensor data 532 may include data collected by a microphone, an infrared camera, a thermal camera, a magnetometer, a time of flight sensor, a MVDD, a device configured to collect vehicle metadata, and/or an air quality sensor.

(225) In some embodiments, trained machine learning model 533 for processing the vehicle data may include preprocessing to generate input data for trained machine learning model 534. Preprocessing to generate input data may modify at least one characteristic of the vehicle data, prior to the data being processed by the trained machine learning model 534.

(226) In some embodiments, the trained machine learning models 533 may process vehicle sensor data from different vehicle sensors separately. In some embodiments, the trained machine learning models 533 may process the sensor data from different vehicle sensors together. In some embodiments, the trained machine learning models 533 may process sensor data from different sensors together in part and separately in part.

(227) Trained machine learning model 534 may be any suitable machine learning model for sensor data analysis. In some embodiments, trained machine learning model 534 is a 2D convolutional neural network. In some embodiments, ML model 534 is structured as a deep convolutional neural network (DCNN). In some embodiments, ML model 534 is a transformer-based model.

(228) Outputs 535 may include a list of vehicle defects and the respective likelihood of the defect being present in the vehicle. As shown in FIG. 5D outputs 535 include the likelihood of a first vehicle defect 536, the likelihood of a vehicle image defect 537, and a likelihood of an nth vehicle

defect **538**. For example, when $n=8$ there may be 8 output classes (e.g., types of vehicle defects) including 7 defect classes and one affirmative quality class. In some embodiments, the outputs **535** include likelihood of particular vehicle characteristics being present. Examples of vehicle characteristics and defects are described herein. In some embodiments, the outputs include likelihoods data defects, for example incorrect cropping, insufficient detail, incorrect trim, insufficient magnitude, and/or too noisy, among other defects.

(229) FIG. **6A** is a flowchart of an illustrative process **600** for inspecting a vehicle using a vehicle inspection system, according to some embodiments. In some embodiments, the vehicle inspection system is configured such as those described herein with reference to FIGS. **1A-4B**. In some embodiments, the vehicle inspection system used in performing process **600** includes a vehicle exterior inspection system with a support member and exterior sensor arrays coupled to the support member. The exterior sensor arrays having respective sets of sensors oriented in different directions. The vehicle inspection system may also include a vehicle undercarriage inspection system with an undercarriage sensor array including first, second and third cameras which capture images at different angles relative to the vehicle undercarriage, and a sensor configured to output data indicative of the position and/or motion of the vehicle relative to the vehicle inspection system. Some steps of process **600** may be performed by a vehicle inspector. Some steps of process **600** may be performed by one or more components of the vehicle inspection system.

(230) Process **600** starts at step **601** by moving the vehicle and the vehicle inspection system relative to one another. In some embodiments, the vehicle may be driven past components of a vehicle inspection system, such as described with reference to FIGS. **3A-F**. The vehicle may be driven by an inspector or by another individual. In some embodiments, one or more components of a vehicle inspection system may move relative to the vehicle. For example, a vehicle undercarriage inspection system may move beneath and/or around a vehicle, and/or a vehicle exterior inspection system may move relative to the vehicle such as described with reference to FIGS. **17C-H**.

(231) Next, step **602** is performed by triggering capture, by the plurality of exterior sensor arrays and undercarriage sensor array, of sensor data about the vehicle. In some embodiments, the triggering is performed automatically by the vehicle inspection system. In some embodiments the triggering is performed automatically based on signals obtained from one or more sensors of a vehicle inspection system, such as TOF sensors, and/or cameras. In some embodiments, the triggering is performed when the vehicle is determined to be at one or more positions relative to the vehicle inspection system based on sensor data. In some embodiments, different components may be triggered at different times, for example a vehicle exterior inspection system may be triggered to capture data when the vehicle is determined to be at a first position and the vehicle undercarriage inspection system is triggered to capture data when the vehicle is determined to be at a second position. In some embodiments individual sensors may be triggered at different times, for example sensors having different orientations may be triggered based on the position of the vehicle.

(232) In some embodiments, the triggering is performed manually by an inspector by providing one or more inputs to a vehicle inspection system, such as through a user interface or other inputs as described herein.

(233) Next, step **603** is performed by capturing the sensor data about the vehicle using the plurality of exterior sensor arrays and undercarriage sensor array of the vehicle inspection system.

(234) Next, step **604** is performed by stopping capture of the sensor data about the vehicle. In some embodiments, the stopping is performed automatically by the vehicle inspection system. In some embodiments the stopping is performed automatically based on signals obtained from one or more sensors of a vehicle inspection system, such as TOF sensors, and/or cameras. In some embodiments, the stopping is performed when the vehicle is determined to be at one or more positions relative to the vehicle inspection system based on sensor data. In some embodiments, different components may be stopped at different times, for example a vehicle exterior inspection system may be stopped from capturing data when the vehicle is determined to be at a first position

and the vehicle undercarriage inspection system may be stopped from capturing data when the vehicle is determined to be at a second position. In some embodiments individual sensors may be stopped at different times, for example sensors having different orientations may be stopped based on the position of the vehicle.

(235) In some embodiments, the stopping is performed manually by an inspector by providing one or more inputs to a vehicle inspection system, such as through a user interface or other inputs as described herein.

(236) Next, step **605** is performed by stopping movement of the vehicle and the vehicle inspection system relative to one another. In some embodiments, step **605** is performed by an inspector or other individual by stopping the vehicle. In some embodiments, step **605** is performed by an inspector by providing an input to the vehicle inspection system to stop moving. In some embodiments, step **605** is performed automatically by a vehicle inspection system.

(237) Next, step **606** is performed by generating a vehicle condition report based on the sensor data collected using the plurality of exterior sensor arrays and the undercarriage sensor array. In some embodiments, step **606** is performed by an inspector who reviews the collected data. In some embodiments, step **606** is performed by one or more components of the vehicle inspection system, such as processors. In some embodiments, the condition report includes data related to the vehicle, for example as described with reference to FIG. 2. In some embodiments, data of a vehicle condition report may be determined using one or more machine learning models, such as those described herein with reference to FIGS. 5A-D, 13A-C, and/or 23A-E. In some embodiments, the vehicle condition report may be displayed and/or otherwise provided for a vehicle inspector for review.

(238) Following the conclusion of process **600**, the inspector may proceed to conduct a further vehicle inspection. Accordingly, in some embodiments, the inspector may use the vehicle condition report and/or targeted professional inspection instructions to determine particular techniques to use during the further vehicle inspection (e.g., to check for the potential vehicle defects).

(239) Additionally, or alternatively, the inspector may be a potential buyer who may use the vehicle condition report to make more informed pricing offers or to perform an inspection of the vehicle for themselves (e.g., to determine the presence of the potential vehicle defects). Additionally, or alternatively, the inspector may be a potential seller who may use the output to anticipate potential customer complaints. Additionally, or alternatively, the inspector may be the vehicle owner who may use the output to anticipate component failures and repairs.

(240) FIG. 6B is a flowchart of an illustrative process **610** for preparing and using a vehicle inspection system to perform a vehicle inspection, according to some embodiments. In some embodiments, the vehicle inspection system is configured such as those described herein with reference to FIGS. 1A-4B. In some embodiments, the vehicle inspection system used in performing process **610** includes a vehicle exterior inspection system with a support member and exterior sensor arrays coupled to the support member. The exterior sensor arrays having respective sets of sensors oriented in different directions. The vehicle inspection system may also include a vehicle undercarriage inspection system with an undercarriage sensor array including first, second and third cameras which capture images at different angles relative to the vehicle undercarriage, and a sensor configured to output data indicative of the position and/or motion of the vehicle relative to the vehicle inspection system. Some steps of process **610** may be performed by a vehicle inspector. Some steps of process **610** may be performed by one or more components of the vehicle inspection system.

(241) Process **610** begins at step **611**, by positioning the vehicle, the vehicle exterior inspection system and the vehicle undercarriage inspection system relative to one another. In some embodiments, the system components may be positioned as described with reference to FIGS. 3A-F, with a vehicle undercarriage inspection system positioned between support members of a vehicle exterior inspection system, in front of a vehicle. In some embodiments, vehicle exterior inspection

systems may be configured as described with reference to FIGS. 17A-H, in combination with vehicle undercarriage inspection systems as described herein. In some embodiments, an inspector may perform step **611**. In some embodiments step **611** may be performed automatically by components of the vehicle inspection system. In some embodiments step **611** may be performed in part by an inspector and in part by components of the vehicle inspection system.

(242) Next, step **612** is performed by triggering the vehicle inspection system to collect alignment data of the vehicle relative to the vehicle inspection system. In some embodiments, the triggering is performed automatically by the vehicle inspection system. In some embodiments the triggering is performed automatically based on signals obtained from one or more sensors of a vehicle inspection system, such as TOF sensors, and/or cameras. In some embodiments, the triggering is performed when the vehicle is determined to be at one or more positions relative to the vehicle inspection system based on sensor data.

(243) In some embodiments, the triggering is performed manually by an inspector by providing one or more inputs to a vehicle inspection system, such as through a user interface or other inputs as described herein.

(244) In some embodiments, the alignment data includes data from one or more TOF sensors of the vehicle inspection system, as described herein. For example, the alignment data may include data collected by TOF sensors of a vehicle undercarriage imaging system as described with reference to FIGS. 7-9B. In some embodiments, the alignment data includes data from one or more cameras of the vehicle inspection system.

(245) Next, step **613** is performed by obtaining an indication of an alignment of the vehicle relative to the vehicle inspection system based on the alignment data. In some embodiments, the indication of alignment may be determined by the vehicle inspection system. In some embodiments, the indication of alignment may be determined by an alignment verification module, such as modules **122**, **932** and/or **2132**. In some embodiments, the indication of alignment may be provided on a display of a vehicle inspection system, as described in herein. Next, step **614** is performed by adjusting one or more of the exterior sensor arrays or the undercarriage sensor array, based on the indication of the alignment of the vehicle. In some embodiments, step **614** may be performed by an inspector or another individual. In some embodiments step **614** may be performed automatically by one or more components of a vehicle inspection system. In some embodiments step **614** may be performed in part by an inspector or other individual and in part automatically by one or more components of a vehicle inspection system. In some embodiments, the indication of alignment includes a direction for readjustment, and step **614** may be performed based on the direction for readjustment.

(246) In some embodiments, steps **611-614** may be iterated until the vehicle is determined to be properly aligned.

(247) Next, step **615** is performed by moving the vehicle and the vehicle inspection system relative to one another. In some embodiments, the vehicle may be driven past components of a vehicle inspection system, such as described with reference to FIGS. 3A-F. The vehicle may be driven by an inspector or by another individual. In some embodiments, one or more components of a vehicle inspection system may move relative to the vehicle. For example, a vehicle undercarriage inspection system may move beneath and/or around a vehicle, and/or a vehicle exterior inspection system may move relative to the vehicle such as described with reference to FIGS. 17C-H.

(248) Next, step **616** is performed by capturing sensor data about the vehicle using the plurality of exterior sensor arrays and undercarriage sensor array of the vehicle inspection system.

(249) Next step **617** is performed by processing the sensor data, using a computer hardware processor, to identify one or more vehicle defects. In some embodiments, the one or more defects include vehicle defects, as described herein. In some embodiments, step **617** may be performed by one or more components of a vehicle inspection system, for example data processing and analysis modules, such as **121**, **931**, and/or **2131**, as described herein. In some embodiments, the sensor data

may undergo formatting for processing, as described herein. For example, subsets of data may be selected for processing, such as described with reference to FIGS. 22A-E. Additionally, or alternatively, for example, a composite image may be generated for processing, using images and/or sensor data obtained from the undercarriage inspection system, such as described with reference to FIGS. 10-11G. In some embodiments, the processing may be performed using one or more trained machine learning models to identify vehicle defects, for example ML models such as those described herein with reference to FIGS. 5A-D, 13A-C, and/or 23A-E.

(250) In some embodiments, the vehicle defects may be displayed and/or otherwise provided for a vehicle inspector for review. In some embodiments, the vehicle defects may be provided as a part of a vehicle condition report. In some embodiments, the vehicle defects may be formatted as likelihoods of the vehicle having the defects. In some embodiments, the vehicle defects may be formatted as probabilities of the vehicle having the defects. In some embodiments the vehicle defects may be confidence scores of the vehicle having the defects.

(251) Following the conclusion of process 610, the inspector may proceed to conduct a further vehicle inspection. Accordingly, in some embodiments, the inspector may use the identified defects and/or targeted professional inspection instructions to determine particular techniques to use during the further vehicle inspection to check for the potential vehicle defects. Additionally, or alternatively, the targeted professional inspection instructions may alert the inspector of features indicative of the potential vehicle defects.

(252) Additionally, or alternatively, the inspector may be a potential buyer who may use the defects to make more informed pricing offers or to check for themselves the presence of the potential vehicle defects. Additionally, or alternatively, the inspector may be a potential seller who may use the output to anticipate potential customer complaints. Additionally, or alternatively, the inspector may be the vehicle owner who may use the output to anticipate component failures and repairs.

(253) FIG. 6C is a flowchart of an illustrative process 620 for using a vehicle inspection system to determine one or more vehicle defects, according to some embodiments. In some embodiments, the vehicle inspection system is configured such as those described herein with reference to FIGS. 1A-4B. In some embodiments, the vehicle inspection system used in performing process 610 includes a vehicle exterior inspection system with a support member and exterior sensor arrays coupled to the support member. The exterior sensor arrays having respective sets of sensors oriented in different directions. The vehicle inspection system may also include a vehicle undercarriage inspection system with an undercarriage sensor array including first, second and third cameras which capture images at different angles relative to the vehicle undercarriage, and a sensor configured to output data indicative of the position and/or motion of the vehicle relative to the vehicle inspection system. Some steps of process 620 may be performed by a vehicle inspector. Some steps of process 620 may be performed by one or more components of the vehicle inspection system.

(254) Process 620 begins at step 621 by moving the vehicle and the vehicle inspection system relative to one another. In some embodiments, the vehicle may be driven past components of a vehicle inspection system, such as described with reference to FIGS. 3A-F. The vehicle may be driven by an inspector or by another individual. In some embodiments, one or more components of a vehicle inspection system may move relative to the vehicle. For example, a vehicle undercarriage inspection system may move beneath and/or around a vehicle, and/or a vehicle exterior inspection system may move relative to the vehicle such as described with reference to FIGS. 17C-H.

(255) Next, step 621 is performed by triggering capture, by the plurality of exterior sensor arrays and undercarriage sensor array, of sensor data about the vehicle. In some embodiments, the triggering is performed automatically by the vehicle inspection system. In some embodiments the triggering is performed automatically based on signals obtained from one or more sensors of a vehicle inspection system, such as TOF sensors, and/or cameras. In some embodiments, the triggering is performed when the vehicle is determined to be at one or more positions relative to the vehicle inspection system based on sensor data. In some embodiments, different components may

be triggered at different times, for example a vehicle exterior inspection system may be triggered to capture data when the vehicle is determined to be at a first position and the vehicle undercarriage inspection system is triggered to capture data when the vehicle is determined to be at a second position. In some embodiments individual sensors may be triggered at different times, for example sensors having different orientations may be triggered based on the position of the vehicle.

(256) In some embodiments, the triggering is performed manually by an inspector by providing one or more inputs to a vehicle inspection system, such as through a user interface or other inputs as described herein.

(257) Next, step **623** is performed by capturing the sensor data about the vehicle using the plurality of exterior sensor arrays and undercarriage sensor array of the vehicle inspection system.

(258) Next, step **624** is performed by stopping capture of the sensor data about the vehicle. In some embodiments, the stopping is performed automatically by the vehicle inspection system. In some embodiments the stopping is performed automatically based on signals obtained from one or more sensors of a vehicle inspection system, such as TOF sensors, and/or cameras. In some embodiments, the stopping is performed when the vehicle is determined to be at one or more positions relative to the vehicle inspection system based on sensor data. In some embodiments, different components may be stopped at different times, for example a vehicle exterior inspection system may be stopped from capturing data when the vehicle is determined to be at a first position and the vehicle undercarriage inspection system may be stopped from capturing data when the vehicle is determined to be at a second position. In some embodiments individual sensors may be stopped at different times, for example sensors having different orientations may be stopped based on the position of the vehicle.

(259) In some embodiments, the stopping is performed manually by an inspector by providing one or more inputs to a vehicle inspection system, such as through a user interface or other inputs as described herein.

(260) Next, step **625** is performed by stopping movement of the vehicle and the vehicle inspection system relative to one another. In some embodiments, step **605** is performed by an inspector or other individual by stopping the vehicle. In some embodiments, step **605** is performed by an inspector by providing an input to the vehicle inspection system to stop moving. In some embodiments, step **605** is performed automatically by a vehicle inspection system.

(261) Next, step **626** is performed by processing the sensor data, using a computer hardware processor, to identify one or more vehicle defects. In some embodiments, step **626** may be performed by one or more components of a vehicle inspection system, for example data processing and analysis modules, such as **121**, **931**, and/or **2131**, as described herein. In some embodiments, the sensor data may undergo formatting for processing, as described herein. For example, subsets of data may be selected for processing, such as described with reference to FIGS. **22A-E**.

Additionally, or alternatively, for example, a composite image may be generated for processing, using images and/or sensor data obtained from the undercarriage inspection system, such as described with reference to FIGS. **10-11G**. In some embodiments, the processing may be performed using one or more trained machine learning models to identify vehicle defects, for example ML models such as those described herein with reference to FIGS. **5A-D**, **13A-C**, and/or **23A-E**.

(262) In some embodiments, the vehicle defects may be displayed and/or otherwise provided for a vehicle inspector for review. In some embodiments, the vehicle defects may be provided as a part of a vehicle condition report. In some embodiments, the vehicle defects may be formatted as likelihoods of the vehicle having the defects. In some embodiments, the vehicle defects may be formatted as probabilities of the vehicle having the defects. In some embodiments the vehicle defects may be confidence scores of the vehicle having the defects.

(263) Following the conclusion of process **620**, the inspector may proceed to conduct a further vehicle inspection. Accordingly, in some embodiments, the inspector may use the identified defects

and/or targeted professional inspection instructions to determine particular techniques to use during the further vehicle inspection to check for the potential vehicle defects. Additionally, or alternatively, the targeted professional inspection instructions may alert the inspector of features indicative of the potential vehicle defects.

(264) Additionally, or alternatively, the inspector may be a potential buyer who may use the defects to make more informed pricing offers or to check for themselves the presence of the potential vehicle defects. Additionally, or alternatively, the inspector may be a potential seller who may use the output to anticipate potential customer complaints. Additionally, or alternatively, the inspector may be the vehicle owner who may use the output to anticipate component failures and repairs.

(265) FIG. 7 is a view of a vehicle undercarriage inspection system, according to some embodiments. The vehicle undercarriage inspection system **700** includes a base and multiple sensors for capturing data related to a vehicle undercarriage. In some embodiments, vehicle undercarriage inspection system **700** may be used as a part of a vehicle inspection system for example vehicle inspection system **110** as described with reference to FIG. 1A. In some embodiments, vehicle undercarriage inspection system **700** maybe used alone to capture data from the undercarriage of a vehicle.

(266) Vehicle under system **700** includes cover **710**. Cover **710** may be configured to allow the vehicle undercarriage inspection system **700** to be accidentally ran over by a car. For example, the materials, shape, and/or structure of the cover **710** may allow for the cover to withstand being run over by a car. In some embodiments, the cover **710** may be made from one or more materials, including PEEK, ABS, PC, PTFE, HDPE, and/or Nylon. In some embodiments, the cover **710** includes internal structures such as support members, trusses and/or ribs, which allow the cover to withstand forces from vehicles. In some embodiments, the cover **710** is shaped di dissipate forces from vehicles. In some embodiments, the cover **710** may withstand up to 5,000 lbs. of force, up to 10,000 lbs. of force, up to 15,000 lbs. of force, up to 16,000 lbs. of force, up to 20,000 lbs. of force, and/or up to 50,000 lbs. of force.

(267) The cover includes handle **712**. Handle **712** may be used for positioning and/or transporting vehicle undercarriage inspection system **700**. In some embodiments, the vehicle undercarriage inspection system **700** may be transported between inspection locations, and/or repositioned during vehicle inspections. In some embodiments, the vehicle undercarriage inspection system **700** is light weight, allowing for easy transportation and/or positioning of the system. In some embodiments, the vehicle undercarriage inspection system may weigh less than 50 lbs., less than 40 lbs., less than 30 lbs., less than 20 lbs., less than 10 lbs., and/or less than 5 lbs.

(268) The vehicle undercarriage inspection system **700** includes various sensors and features for collecting data related to a vehicle undercarriage. In some embodiments, the sensors and features of the vehicle undercarriage inspection system **700** may be configured as a sensor array, as described herein. The vehicle undercarriage inspection system **700** includes cameras **720A-C**, TOF sensors **722A-B**, microphones **724A-C**, and light source **723**. In some embodiments, the vehicle undercarriage inspection system **700** may contain additional sensors, for example additional cameras, TOF sensors, microphones. In some embodiments, the vehicle undercarriage inspection system may include an infrared camera, a thermal camera, a magnetometer, and/or an air quality sensor. In some embodiments, data collected by the sensors of the vehicle undercarriage inspection system **700** may be analyzed and/or used in generating a vehicle condition report, as described herein.

(269) In some embodiments the sensors of the vehicle undercarriage inspection system **700** may be controlled to capture data from the undercarriage of a vehicle as the vehicle and undercarriage inspection system move relative to each other. In some embodiments, the vehicle may move relative to the vehicle undercarriage inspection system **700** (e.g., by driving over the vehicle undercarriage inspection system). In some embodiments, the vehicle undercarriage inspection system may move relative to the vehicle (e.g., moving underneath and/or around the vehicle on

tracks or wheels).

(270) The vehicle undercarriage inspection system **700** includes cameras **720A**, **720B** and **720C**. The cameras may capture images of the vehicle undercarriage as the vehicle and vehicle undercarriage inspection system **700** move relative to each other. In some embodiments, the cameras may be oriented at different angles. In some embodiments, camera **720A** may be oriented in part towards the right side of the vehicle undercarriage inspection system **700** in FIG. 7. In some embodiments, camera **720B** may be oriented substantially vertically in FIG. 7. In some embodiments, camera **720C** may be oriented in part towards the left side of the vehicle undercarriage inspection system **700**. In some embodiments, the images captured by cameras **720A-C** may be used in generating a composite image of the undercarriage of the vehicle, as described herein.

(271) Cameras of vehicle undercarriage imaging systems, as described herein, may be configured with specific attributes. For example, cameras may have a horizontal FOV (along the width of the vehicle) of 150-250 cm at 20 cm of clearance, a resolution of 8-12 pixels/cm at 20 cm of clearance, a sampling rate of 50-75 Hz, and/or a shutter speed of 200-500 us. In some embodiments, camera parameters are selected to minimize motion blur, for example to have a maximum blur at specified vehicle speeds, such as a maximum blur of 4 pixels at 6 miles per hour.

(272) The vehicle undercarriage inspection system **700** includes time of flight sensors **722A** and **722B**. In some embodiments, the vehicle undercarriage inspection system **700** may additionally include a third time of flight sensor opposite time of flight sensor **722A**, on the right side of the vehicle undercarriage inspection system **700** in FIG. 7. In some embodiments, the time of flight sensors may be configured to detect signals related to the position, and/or motion of the vehicle. For example, the time of flight sensors may detect signals indicative of the distance between the time of flight centers and one or more parts of the vehicle. Time of flight sensor **722A** may be configured to determine the distance between the vehicle inspection system **701** or more wheels of the vehicle. In some embodiments, time of flight sensor **722** a may be used to determine the alignment of the vehicle relative to the vehicle undercarriage inspection system **700**. Time of flight sensor **722 B** may be configured to determine the distance between the undercarriage of the vehicle and the vehicle undercarriage inspection system **700**. In some embodiments, data from time of flight sensor **722B** may be used in generating a composite image of the vehicle undercarriage, as described herein.

(273) In embodiments, data from time of flight sensors of the vehicle undercarriage inspection system may be used to trigger one or more sensors of the vehicle undercarriage inspection system to start and/or stop capturing of data. In some embodiments, data from time of flight sensors may be used to start and or stop capturing of data by one or more sensors of a vehicle inspection system. In some embodiments, data from time of flight sensors may be used to determine when the vehicle is at one or more positions relative to the vehicle undercarriage inspection system and/or a vehicle inspection system, and in response to determining the vehicle is at the one or more positions, trigger one or more sensors to start and/or stop capturing data.

(274) Vehicle undercarriage inspection system **700** additionally includes microphones **724A**, **724B** and **724C**. The microphones may be configured to record audio from the undercarriage of the vehicle. As shown in FIG. 7, the microphones are distributed along a width of the vehicle undercarriage inspection system **700**. Accordingly, the microphones may capture audio from different portions of the undercarriage of the vehicle. For example microphone **724A** may capture audio from parts of the vehicle passing over the left portion of the vehicle undercarriage inspection system **700** in FIG. 7, microphone **724 B** may capture audio from parts of the vehicle passing over the center of the vehicle undercarriage inspection system **700** in FIG. 7, and microphone **724 C** may capture audio from parts of the vehicle passing over the right portion of the vehicle undercarriage inspection system **700** in FIG. 7.

(275) The vehicle undercarriage inspection system **700** additionally includes light source **723**.

Light source **723** may be configured to illuminate the undercarriage of the vehicle during a vehicle inspection, such that the cameras **720A**, **720B** and **720 C** may capture images of the undercarriage of the vehicle. In some embodiments, the light source **723** include multiple individual light sources. For example, light source **723** may include multiple LED's. In some embodiments, individual light sources of light source **723** may be angled in different directions to illuminate different portions of the undercarriage of the vehicle. For example, one or more individual light sources of light source **723** may be angled towards the right side of vehicle undercarriage inspection system **700**, one or more individual light sources of light source **723** may be angled towards the left side of the vehicle undercarriage inspection system **700**, one or more individual light sources of light source **723** maybe angled towards the front of vehicle undercarriage inspection system **700**, and one or more individual light sources of light source **723** may be angled towards the rear of the vehicle undercarriage inspection system **700**. In some embodiments, light source **723** may be controlled based on the position of the vehicle relative to the vehicle undercarriage inspection system **700**, as described herein.

(276) In some embodiments, the parameters of light sources of vehicle undercarriage imaging systems may be selected to improve imaging quality. For example, constant current LEDs may be used to eliminate flicker.

(277) In some embodiments, vehicle undercarriage inspection system **700** may comprise one or more processors for controlling sensors, and/or analyzing data recorded by sensors, as described herein. In some embodiments, vehicle undercarriage inspection system **700** may provide data recorded by sensors to a processor separate from vehicle undercarriage inspection system **700** to analyze the data, as described herein. In some embodiments, vehicle undercarriage inspection system **700** may receive data, such as control data, from a processor separate from vehicle undercarriage inspection system **700**, as described herein.

(278) In some embodiments, vehicle undercarriage inspection system **700** may include one or more features for facilitating movement and/or placement. For example vehicle undercarriage inspection system may include one or more of wheels, adjustable feet, and/or pads.

(279) FIG. **8A** illustrates an example camera set of a vehicle undercarriage inspection system, according to some embodiments. In some embodiments, the camera set may be included in a vehicle undercarriage inspection system such as **700** of FIG. **7**. In some embodiments, the camera set may be a part of a vehicle inspection system, as described herein. The camera set **810** includes four cameras **814A-D** and associated components for positioning the cameras within a vehicle undercarriage inspection system.

(280) The cameras **814A-D** may be positioned within a vehicle undercarriage inspection system using components shown in FIG. **8A**. These components include support member **811**, camera mounting brackets **813A-D**, and mounting brackets **812A-B**. In some embodiments, cameras of a vehicle undercarriage inspection system may be positioned within the vehicle undercarriage inspection system using different components than those shown in FIG. **8A**.

(281) The support member **811** allows for mounting of cameras **814A-C** with respective camera mounting brackets **813A-C**. In some embodiments, the camera mounting brackets may be secured to the support member using fasteners, a friction fit, and/or alignment of features between the mounting brackets and the support member. In some embodiments, the support member **811** may comprise one or more features which facilitate the mounting of the camera mounting brackets, such as holes and/or rails.

(282) The support member **811** may be secured within a vehicle undercarriage inspection system using mounting brackets **812A** and **812B**. The mounting brackets **812A** and **812B** may support the support member **811** at the ends of the support member. In some embodiments, the mounting brackets secure the support member to the base of a vehicle undercarriage inspection system.

(283) The cameras **814A-D** are mounted to the support member by respective camera mounting brackets **813A-D**. In some embodiments, the cameras may be secured to the camera mounting

brackets via fasteners, adhesives, and/or other suitable mounting techniques. Some of the camera mounting brackets may be angled such that the cameras mounted to them are oriented at an angle. For example, camera mounting bracket **813A** is angled such that camera **814A** is angled to the left side of FIG. **8A**, and camera mounting bracket **813D** is angled such that camera **814D** is angled towards the right side of FIG. **8A**. Camera mounting brackets **813B** and **813C** are not angled and the respective cameras **814B** and **814C** are therefore oriented towards the top of FIG. **8A**. In some embodiments, additional cameras may be oriented at different angles, for example three of the cameras may be oriented at different angles, or all of the cameras may be oriented at different angles. In some embodiments, fewer cameras may be oriented at different angles, on camera or none of the cameras may be oriented at different angles.

(284) The different orientations of the cameras allow for the camera set **810** to capture images of the undercarriage of a vehicle at different angles. This may allow for capturing of images of a greater amount of a vehicle undercarriage than in vehicle undercarriage inspection systems with cameras which are not angled. The different angles of the cameras, and/or number of cameras in the set may allow for cameras to “look around” components of the vehicle undercarriage. For example, if a camera of the camera set is obscured by a low hanging part of the vehicle undercarriage, images of the undercarriage may be captured by the other cameras of the camera set.

(285) The different orientations of the cameras **814A-D** are represented by the respective camera fields of view (FOVs) **815A-D**. The FOVs represent the area in which cameras may capture images of the vehicle undercarriage. As shown, the FOVs **815A** and **815D**, respectively, of cameras **814A** and **814D** are angled towards the left side of FIG. **8A** and the right side of FIG. **8A**, respectively. This is due to the orienting of cameras **814A** and **814D** by the respective camera mounting brackets **813A** and **D**, as described herein. As shown, the FOVs of the cameras overlap in some areas, and therefore images components of the vehicle undercarriage may be captured by multiple cameras.

(286) FIG. **8B** is a view of an example mounting bracket of a vehicle undercarriage inspection system, according to some embodiments. The mounting bracket **860** of FIG. **8B** may be used in a vehicle undercarriage inspection system as described herein, for example as described with reference to FIG. **8A**. The mounting bracket **860**, supports support member **861**. Support member **861** may support one or more cameras, as described herein. Cameras may be mounted to support member **861** using camera mounting brackets, as described herein, such as camera mounting bracket **865**.

(287) Mounting bracket **860** may allow for the support member **861** to be positioned at different angles. As shown in FIG. **8B**, the angle of the support member **861** can be adjusted between an angle of 25° and 90° relative to a vertical direction in FIG. **8B**. The angle may be adjusted using angle adjustment mechanism **863**, which may interact with holes in a side of the mounting bracket. The mounting bracket **860** additionally includes bottom portion for securing to a base or other component of a vehicle undercarriage inspection system.

(288) FIG. **8C** illustrates an example camera mounting bracket, according to some embodiments. The camera mounting bracket **865** is coupled to a support member **866**. The camera mounting bracket **865** maybe coupled to the support member via the holes in the camera mounting bracket **865** and the rail of the support member **866**. A camera maybe mounted to camera mounting bracket **865** directly or indirectly. As shown, a camera is indirectly mounted to mounting bracket **865** via camera mounting plate **867**. In some embodiments, a camera may be mounted to a camera mounting plate using fasteners and/or adhesives as described herein. In some embodiments, a camera mounting plate may be mounted to a camera mounting bracket through fasteners and/or adhesives.

(289) FIG. **8D** illustrates a camera indirectly mounted to a camera mounting bracket via an angled wedge, according to some embodiments. As shown, camera **868** is mounted to a camera mounting plate which in turn is mounted via angled wedge **869** to a camera mounting bracket. The angled wedge may allow for the camera to be oriented in different angles, as described herein. As shown,

the angled wedge orients the camera at a 30° angle relative to the support member in FIG. 8D, an angled wedge may have any suitable angle for orienting cameras for capturing images of vehicle undercarriages. For example, an angled wedge may have any angle between 5° and 90°.

(290) FIG. 8E illustrates example internal components of a vehicle undercarriage inspection system, according to some embodiments. The vehicle undercarriage inspection system **870** of FIG. 8E is an example vehicle undercarriage inspection system and other systems may have the same, similar, or different components and/or arrangements.

(291) Vehicle undercarriage inspection system **870** includes base **875** which components may be mounted to. The components may be mounted to base **875** via any suitable method, for example adhesives and/or fasteners.

(292) Vehicle undercarriage inspection system **870** includes light support member, which provides support for light sources **872**. As shown there are 7 light sources, however the vehicle undercarriage inspection system may include greater or fewer light sources. As shown, two of the light sources are angled towards the sides of the base **875**. These light sources may allow different portions of the vehicle undercarriage to be illuminated, which cannot be without such angling. As shown, the light support member **871** is mounted to the base with standoffs, however other mounting techniques may be used.

(293) The vehicle undercarriage inspection system **870** additionally includes fans **873A** and **873B** which may be used to manage the temperature of the components of the vehicle undercarriage inspection system.

(294) The vehicle undercarriage inspection system **870** additionally includes TOF sensors **874A** and **874B**, which are oriented towards the ends of the vehicle undercarriage inspection system. TOF sensors may capture data related to the position and/or motion of the vehicle. In some embodiments, TOF sensors **874A** and **B** may capture data related to the wheels of the vehicle. In some embodiments, data captured by the TOF sensors **874A-B** may be used to determine an alignment of the vehicle relative to the vehicle undercarriage inspection system and/or a vehicle inspection system, as described herein. In some embodiments, data from the TOF sensors **874A-B** may be used to trigger starting and/or stopping of data collection by sensors of the vehicle undercarriage inspection system and/or a vehicle inspection system.

(295) Vehicle undercarriage inspection system **870** additionally includes cameras **876**, which may capture images of the vehicle undercarriage, as described herein. In some embodiments, the cameras **876** may include greater or fewer cameras, as described herein. In some embodiments, the cameras **876** may be oriented at different angles, as described herein. In some embodiments, the cameras may include a lens cover and/or filter, as shown on the central camera in FIG. 8E. In some embodiments, the cameras may include microphones.

(296) The vehicle inspection system additionally includes air quality sensor **883**, which may capture data related to the air quality at the undercarriage of the vehicle. This data may be used to determine vehicle defects such as exhaust and/or fluid leaks. In some embodiments, air quality sensor **883** is configured as a Volatile Organic Compound (VOC) sensor. In some embodiments, air quality sensor **883** may be configured to detect levels of CO.sub.2, CO, nitrogen oxides NO.sub.x, and/or SO.sub.2.

(297) The vehicle undercarriage inspection system additionally includes power supply **877**. Power supply **877** may be a battery or other suitable power supply. In some embodiments the power supply may be charged via a power source plugged into power assembly **879**. Power assembly additional includes a power switch for powering on and off the vehicle undercarriage inspection system **870**.

(298) The vehicle undercarriage inspection system **870** additionally includes signal port **878** which may connect (e.g., via a cable) to a computer and/or a communication network. The signal port may connect to network switch **881**. In some embodiments the network switch **881** is configured as an Ethernet switch. In some embodiments, vehicle undercarriage inspection system **870** may

connect to a computer and/or network through a wireless connection. In some embodiments, the vehicle undercarriage inspection system **870** may connect via wireless connections using router **880**.

(299) The components of the vehicle undercarriage inspection system **870** may be controlled (e.g., turned on, turned off, triggered to begin and/or stop recording of data, etc.) by the processors **882A-C**. In some embodiments, the vehicle undercarriage inspection system may perform analyses of data captured by the sensors of the vehicle undercarriage inspection system and/or a vehicle inspection system, using processors **882A-C**. In some embodiments, the vehicle undercarriage inspection system may include a greater or lesser number of processors. Example functions of processors of a vehicle undercarriage inspection system are discussed with regard to FIGS. **9A-B**.

(300) FIG. **9A** is a diagram illustrating the components of a vehicle undercarriage inspection system, according to some embodiments. Vehicle undercarriage inspection system **900** includes a sensor array **910**, system components **920**, and processor(s) **930**. The vehicle undercarriage system **900** is an example vehicle undercarriage inspection system and may be configured as described herein, for example, as described with reference to FIGS. **7-8E**. In some embodiments, the sensor array **910**, system components **920** and processors **930** may be implemented in a single device and/or location. In some embodiments, the sensor array **910**, system components **920** and processors **930** may be implemented in separate devices and/or locations. In some embodiments, the sensor array **910**, system components **920**, and processors **930** may be implemented in part in a single device and/or location and in part in separate and/or remote devices and/or locations.

(301) Sensor array **910** includes multiple sensors which may be included in vehicle undercarriage inspection system **900**. These sensors include cameras **911**, TOF sensors **913**, magnetometers **914**, air quality sensors **915** and microphones **916**. In some embodiments, sensor array **910** may include additional sensors, as described herein. In some examples, a sensor array may include fewer sensors than those shown in sensor array **910**. The sensor array additionally includes components which may facilitate the recording of data from the undercarriage of the vehicle, for example, light source **912**.

(302) Cameras **911** may capture images of the undercarriage of a vehicle. The images may be captured as the vehicle and vehicle undercarriage inspection system move relative to one another. In some embodiments, the cameras **911** may be configured as a camera set, as described herein. In some embodiments the cameras **911** may include different types of cameras, for example, optical cameras, thermal cameras, and/or IR cameras. In some embodiments, the cameras may be oriented at different angles, as described herein. In some embodiments, the images captured by cameras **911** may be used to generate a composite image of the vehicle undercarriage, as described herein. In some embodiments, the images captured by the cameras **911** may be analyzed to determine one or vehicle characteristics and/or defects, as described herein.

(303) Light source **912** may be used to illuminate the vehicle undercarriage to facilitate capturing of images of the undercarriage. In some embodiments, the light source **912** may include one or more individual light sources which supply light to the vehicle undercarriage, as described herein. In some embodiments, the individual light sources of light source **912** may be oriented at different angles, as described herein.

(304) TOF sensors **913** may capture data indicative of the position and/or motion of the vehicle relative to the vehicle undercarriage inspection system **900**. In some embodiments, the TOF sensors **913** may capture data indicative of the position and/or motion of the vehicle relative to a vehicle inspection system, as described herein. In some examples, the TOF sensors **913** may include multiple TOF sensors. In some embodiments, the TOF sensors **913** may be oriented in different directions. In some embodiments the TOF sensors **913** may be oriented in different directions, for example towards different ends of a vehicle undercarriage inspection system, and/or substantially vertically towards a vehicle undercarriage, as described herein. In some embodiments, data collected by TOF sensors **913** may be used in determining vehicle alignment with the vehicle

undercarriage inspection system. For example, a vehicle undercarriage inspection system may use TOF sensors oriented towards ends of the vehicle undercarriage inspection system to determine alignment. In some embodiments, the data collected by TOF sensors **913** may be used in controlling one or more components of the vehicle undercarriage inspection system **900** and/or a vehicle inspection system.

(305) Magnetometers **914** may capture magnetic field signals from a vehicle undercarriage. In some embodiments, the magnetic field signals are used to determine characteristics and/or defects of a vehicle, for example, a vehicle trim, drivetrain, make, model, presence of a catalytic converter, alternator performance, battery type, battery performance, and/or drivetrain performance, among other defects and/or characteristics as described herein. Techniques for analyzing vehicles using magnetometers are discussed in U.S. patent application Ser. No. 18/483,935, entitled: "Machine Learning and Magnetic Field Sensing Techniques for Vehicle Inspection and Condition Analysis," filed Oct. 10, 2023, which is incorporated by reference herein in its entirety.

(306) Air quality sensors **915** may record air quality data of the vehicle undercarriage. In some embodiments, the air quality sensors are VOC sensors. In some examples, data recorded by the air quality sensors **915** may be used to determine one or more defects such as fluid leaks, exhaust performance, and/or exhaust leaks.

(307) Microphones **916** may be used to record audio data from the undercarriage of a vehicle. The audio data may be used in determining one or more defects and/or characteristics of a vehicle, for example exhaust leaks, engine knocking, engine defects, and/or transmission whine, among other defects and/or characteristics, as described herein.

(308) Vehicle undercarriage inspection system additionally includes system components **920**. In some embodiments, the vehicle undercarriage inspection system may include greater or fewer components than those included in system components **920**.

(309) System components **920** include circuitry **921**, power supply **922**, heat management **923** and inputs **924**. In some embodiments, the system components may include greater or fewer components than those shown.

(310) Circuitry **921** may include circuit boards, wiring, and/or other electrical components for interconnecting components of the vehicle undercarriage inspection system, including components of the sensor array **910** and system components **920**.

(311) Power supply **922** may provide power to components of the vehicle undercarriage inspection system, including components of the sensor array **910** and system components **920**. Power supply **922** may be configured as a battery and/or any suitable power supply.

(312) Heat management components **923** may function to reduce the temperature of the vehicle undercarriage inspection system. In some embodiments, the heat management components **923** may be active and/or passive components. In some embodiments, the heat management components may include fans and/or heat sinks.

(313) Inputs **924** may allow for signals and/or other inputs to be provided to the vehicle undercarriage inspection system. In some embodiments, the inputs **924** may include one or more electrical ports and/or connectors, buttons, switches, antennas, routers, and/or other components, as described herein.

(314) Sensor array **910** and system components may send data to and/or receive data from processors **930**. For example data from sensors of the sensor array and components of system components **920** may be provided to processors **930**, and processors **930** may provide control signals to the sensor arrays and/or system components **920**.

(315) FIG. 9B is a diagram illustrating the components of processor(s) of a vehicle undercarriage inspection system, according to some embodiments. In FIG. 9B, vehicle undercarriage inspection system **900** includes sensor array **910**, system components **920**, and processor(s) **930**. As described herein, in some embodiments, the processors **930** may be implemented as a part of the components of the vehicle undercarriage inspection system **900**. In some embodiments, the processor(s) **930**

may be implemented separate from the vehicle undercarriage inspection system **900**, for example as a device connected to the vehicle undercarriage inspection system **900** at the location of the vehicle inspection system and/or in a remote location. In some embodiments, the processors **930** may be implemented in part separately from and in part as a portion of the vehicle undercarriage inspection system **900**.

(316) The processor(s) **930** include data processing and analysis modules **931**, alignment verification modules **932**, composite image generation module **933**, 3D model generation module **934**, condition report generation module **935**, user interface generation module **936**, system control module **937**, and database **939** storing machine learning models **938**.

(317) The data processing and analysis modules **931** may perform one or more operations on data received from the sensor array **910**. In some embodiments, the processing and analysis modules **931** may filter data, structure data and/or preprocess data for additional processing and analysis. In some embodiments, the data processing and analysis modules **931** may determine one or more vehicle characteristics from the data received from the sensor array **910**. In some embodiments, the data processing and analysis modules **931** may use one or more machine learning models, such as ML models **938** to determine the one or more vehicle characteristics. In some embodiments, the data processing and analysis modules **931** may determine one or more vehicle defects from the data received from sensor array **910**. In some embodiments, the data processing and analysis modules may determine the one or more defects using one or more ML models, such as ML models **938**.

(318) The alignment verification module **932** may determine whether the vehicle is properly aligned with the vehicle undercarriage inspection system for an inspection. In some embodiments, the alignment verification module may determine whether the vehicle is aligned with a vehicle inspection system. In some embodiments, the alignment verification module may analyze data received from one or more sensors of the vehicle inspection system, for example cameras and/or TOF sensors. In some embodiments, the alignment verification module determines the alignment of the vehicle using TOF sensors. In some embodiments, the alignment may be determined based on one or more TOF sensors facing a vehicle, and comparing a detected position of the vehicle to a desired position. In some embodiments, the alignment may be determined based on data from TOF sensors facing different ends of the vehicle undercarriage inspection system. In some embodiments, the alignment verification may determine a difference between the position of the vehicle at the different ends of the vehicle undercarriage inspection system, and determine whether the difference is greater than a threshold alignment difference. In some embodiments, the alignment verification module **932** may determine an alignment of the vehicle and provide an indication of the alignment of the vehicle to one or more components of the vehicle inspection system, such as a mobile device or other component with a display. In some embodiments, the alignment of the vehicle may be a binary value, for example, aligned or not aligned. In some embodiments, when the alignment verification module **932** determines the vehicle is not aligned with the vehicle inspection system, the alignment verification module may provide an indication of an adjustment to be made to the vehicle, for example move vehicle left.

(319) The composite image generation module **933** may generate a composite image of the undercarriage of the vehicle based on data obtained from the sensor array. In some embodiments, the composite image may be generated using images obtained from the cameras of the sensor array. In some embodiments, the composite image may be generated based on data obtained from a TOF sensor. Examples of composite image generation are described with reference to FIGS. **10-11G**.

(320) In some embodiments, the 3D model generation module **934** may generate a 3D model of a vehicle based on data received from the sensor array. In some embodiments, the 3D model may be generated using one or more ML models, such as ML models **938**. In some embodiments, the 3D model is generated using photogrammetry. In some embodiments, the 3D model is generated using neural radiance fields. In some embodiments, the 3D model is generated using Gaussian splatting.

(321) The vehicle condition report generation module **935** may generate a vehicle condition report based on data received the sensor array. In some embodiments, the vehicle condition report generation module **935** may generate a vehicle condition report based on one or more characteristics and/or defects of the vehicle determined using the data processing and analysis modules **931**. In some embodiments, the condition report generation module **935** may generate a vehicle condition report that includes data related to a vehicle, for example images of the vehicle, and/or audio recordings of the vehicle. In some embodiments, a vehicle condition report may include a composite image of the vehicle undercarriage. In some embodiments, the condition report generation module may include a 3D model of the vehicle in a vehicle condition report. In some embodiments, the condition report generation module may generate a vehicle condition report using data obtained from a user interface of the vehicle undercarriage inspection system.

(322) User interface generation module **936** may provide a user interface of the vehicle undercarriage inspection system on one or more displays connected to the vehicle undercarriage inspection system. In some embodiments the user interface generation module **936** may provide a user interface on a mobile device connected to the vehicle undercarriage inspection system, a computer connected to one or more components of the vehicle undercarriage inspection system, and/or a device remote from the vehicle undercarriage inspection system. In some embodiments, the user interface generation module **936** may generate a user interface which displays information related to a vehicle, for example, alignment data, a 3D model of a vehicle, and/or a vehicle condition report. In some embodiments, the user interface generation module **936** may provide vehicle data to a user responsive to a request for additional data, for example, the module **936** may provide additional images of a region of the vehicle responsive to a request for images of the region.

(323) The system control module **927** may generate and provide control signals to the components of vehicle undercarriage inspection system **900**. In some embodiments, the control signals may include signals to trigger the starting and/or stopping of recording data by sensors of the sensor array **910**. In some embodiment, the control signals may be generated based on data obtained from the sensor array, for example data indicative of the position and/or motion of the vehicle. In some embodiments, the system control module **937** may generate control signals based on inputs received from a user of the vehicle undercarriage inspection system **900**.

(324) Databases **939** store ML models **938**. In some embodiments, the databases **939** are implemented as a part of one or more components of the vehicle undercarriage inspection system **900**, for example as physical storage. In some embodiments, the databases **939** are accessible by components of the vehicle inspection system, for example as cloud storage.

(325) ML models **938** may be used by modules of the vehicle undercarriage inspection system to analyze data and/or process obtained from the sensor array **910**. In some embodiments, the ML models **938** may be used in determining one or more vehicle defects and/or characteristics. Machine learning models for determining vehicle characteristics and/or defects are describe in U.S. Pat. No. 11,631,289, entitled “Vehicle Audio Capture and Diagnostics,” filed Jan. 22, 2020, U.S. Pat. No. 10,893,213, entitled “Vehicle Undercarriage Imaging System,” filed Apr. 2, 2019, U.S. Pat. No. 18,778,247, entitled “Methods and Systems for Identifying Potential Vehicle Defects,” filed Jul. 19, 2024, and U.S. patent application Ser. No. 18/483,935, entitled: “Machine Learning and Magnetic Field Sensing Techniques for Vehicle Inspection and Condition Analysis,” filed Oct. 10, 2023, each of which is incorporated by reference herein in its entirety. In some embodiments, the ML models may be used by the alignment verification modules **932**, composite image generation module **933**, 3D model generation modules **934**, and/or condition report generation modules **935**.

(326) FIG. **10** illustrates an example process **1000** for generating a composite image of a vehicle undercarriage, according to some embodiments. In the example of FIG. **10**, a composite image is generated from images received from cameras **1011A**, **1011B** and **1011C** of a sensor array **1010** of

an example vehicle undercarriage inspection system. The process of FIG. **10** may be used to generate a composite image from images captured from cameras of vehicle undercarriage inspection systems, as described herein.

(327) Each camera captures multiple images of the vehicle undercarriage. Camera **1011A** captures image set **1012**, including images **1012A-C**. Camera **1011B** captures image set **1013**, including images **1013A-C**. Camera **1011C** captures image set **1014**, including images **1014A-C**. The image sets **1012**, **1013** and **1014** may include consecutive images captured as the vehicle and vehicle undercarriage inspection system move relative to one another.

(328) The images captured by the cameras **1011A-C** may be sent to composite image generation module **1020**, where composite image **1021** is produced from the images. As shown, composite image **1021** includes a complete view of the undercarriage of the vehicle. The composite image generation module may generate the composite image **1021** by determining pixel shifts between adjacent photos within an image set. Image sets may then be aligned and cropped. The vehicle speed in images may be determined based on pixel shift distances. Finally the composite image may be generated based on the aligned image sets and vehicle speed. In some embodiments, the composite image may be generated based on data related to the position and/or motion of the vehicle, such as from a TOF sensor. Composite image generation is described in more detail in FIGS. **11A-E**.

(329) FIG. **11A** is an example data flow for generating a composite image of a vehicle undercarriage, according to some embodiments. The process flow **1100** may be performed by one or more processors of a vehicle undercarriage inspection system and/or a vehicle inspection system, as described herein.

(330) Sensor array **1110** may be a sensor array of a vehicle undercarriage inspection system, and provides vehicle undercarriage image sets **1111** to composite image generation module **1120**. In some embodiments, the vehicle undercarriage image sets **1111** may be captured by cameras of a vehicle undercarriage inspection system. In some embodiments, each set of the vehicle undercarriage image sets **1111** may be captured by a respective camera of a vehicle undercarriage imaging system, as described herein. In some embodiments, the vehicle undercarriage image sets may include consecutive images of the undercarriage of the vehicle. In some embodiments, the image sets may be reversed in order, such that the images of the image set are ordered from the front to the rear of the vehicle.

(331) The composite image generation module **1120** includes sub modules for generating the composite image of the undercarriage of the vehicle. These sub modules include pixel shift determination module **1121**, image set alignment module **1122**, image set cropping module **1123**, vehicle speed estimation module **1124**, and composite image generation module **1125**.

(332) Pixel shift determination module **1121** may determine pixel shift distances between adjacent images of the image sets **1111**. The pixel shifts may be caused by the movement of the vehicle and vehicle undercarriage inspection system relative to each other. In some embodiments, pixel shift distance may be determined based on a comparison of adjacent images, for example, by determining a location of an image feature in adjacent images and determining the difference in position. In some embodiments, one of more ML models may be used in determining pixel shift distances. In some embodiments, pixel shift distances may be determined based on the process shown in FIG. **11B**.

(333) FIG. **11B** illustrates an example process for determining pixel shift distances between adjacent images of an images set, according to some embodiments. In some embodiments, the process of FIG. **11B** may be performed on all adjacent images of image sets. In the process of FIG. **11B**, if an image set has n frames, $n-1$ pixel shift values will be determined.

(334) Image **1130** is an example image from a vehicle undercarriage image set. The image **1130** may be cropped to minimize distortion caused by the lens of the camera used to capture the image. In some embodiments, the image may be center cropped. In some embodiments the center $\frac{1}{3}$ sup.rd

of the image may be cropped. As shown, image **1130** is center cropped, and cropped image **1131** is used in further processing.

(335) Cropped images may be provided to preprocessing module **1136**, where one or more transformations may be applied. As shown, two adjacent cropped images from a vehicle undercarriage image set have been preprocessed. The preprocessed images **1132** and **1133** may have had one or more transformations applied. In some embodiments, the preprocessed images may have had one or more of a Contrast Limited Adaptive Histogram Equalization transformation, and/or a Laplacian transformation applied. All images of an image set may be preprocessed using preprocessing module **1136**.

(336) After preprocessing, the phase correlation **1134** may be determined between the adjacent preprocessed images **1132** and **1133**. The phase correlation may be indicative of the offset between the adjacent preprocessed images. The phase correlation may be determined for all adjacent preprocessed images from an image set.

(337) Pixel shift distances **1135** may then be determined from the phase correlations **1134**. The pixel shift distances **1135** may represent the amount the vehicle and vehicle undercarriage inspection system moved relative to each other (in pixels) between adjacent images of an image set. Pixel shift distances may be determined for all adjacent images of received image sets. In some embodiments, pixel shift distances for an image set may be stored in an array.

(338) Returning to FIG. **11A**, the determined pixel shift distances may be passed to image set alignment module **1122**. Although the image sets **1111** may be recorded at the same time programmatically, the images of the image sets may still be out of sync. Image set alignment module **1122** may align the images of the image sets **1111** based on the pixel shift distances. Image sets **1111** may be aligned by matching the pixel shift distance of the image sets. The image sets may be aligned such that the difference between pixel shift distances of the image sets is minimized. In some embodiments, the image sets may be aligned by “locking” the position of an image set and moving the other image sets relative to the locked image set. At each index the other image sets are moved to, the difference between the pixel shift distances may be determined. In some embodiments, the average pixel shift difference may be determined for each index the image sets are moved to. In some embodiments, the image sets may be shifted by a certain amount in one or more directions. In some embodiments, the image sets may be shifted forward in time based on the time of capture and/or backwards in time based on the time of capture. In some embodiments the image sets may be shifted by up to 25% of their length forwards and/or backwards. The image sets may be aligned at the index with the lowest difference in pixel shift distances.

(339) FIGS. **11C-D** illustrate an example of aligning image sets, according to some embodiments. In FIG. **11C**, plot **1140** illustrates the pixel shift distances for two sets of images. The indexes of the images of the image sets are shown on the X-axis. The pixel shift distances for adjacent images are shown on the Y-axis. Line **1141** corresponds to pixel shift distances for a first image set, and line **1142** corresponds to pixel shift distances for a second image set. As shown lines **1141** and **1142** have similar shapes, but line **1142** is shifted to the right of **1141**.

(340) FIG. **11D** shows a plot **1150** of aligned image sets. The indexes of the images of the image sets are shown on the X-axis. The pixel shift distances for adjacent images are shown on the Y-axis. As shown, the lines **1141** and **1142** are aligned, compared to plot **1140** of FIG. **11C**. The lines **1141** and **1142** are aligned such that the pixel shift distance differences between them are minimized. As shown, line **1142** is no longer shifted to the right of line **1141** and the shapes of the lines **1141** and **1142** generally follow each other.

(341) Returning to FIG. **11A**, the aligned image sets may be passed to image set cropping module **1123**. Image set cropping module **1123** may crop image sets such that the image sets include images where the vehicle undercarriage is present. In some embodiments, the image sets may be cropped based on the pixel shift distances of the image sets.

(342) In some embodiments, the pixel shifts for the aligned image sets are iterated over, and the

average values are found for indexes at the left and right of the image set. The left and right of the image set may represent the beginning and end indexes of the image set. The differences between the average pixel shift distance values for the left and right indexes, and the maximum difference gives the starting index for where the vehicle undercarriage becomes visible and the minimum difference represents the ending index for when the vehicle undercarriage is visible.

(343) This process is shown in FIG. 11E. In FIG. 11E includes plot 1160, which displays the right index average values, 1162, left index average values 1163, difference between the left and right index average values 1161, start point 1164 and end point 1165. The start point 1164 corresponds to the maximum difference between the left and right index average values and where the vehicle undercarriage becomes visible. The end point 1165 corresponds to the minimum difference between the left and right index average values and where the vehicle undercarriage is no longer visible.

(344) The image sets may be trimmed such that only images where the vehicle undercarriage is visible are included.

(345) Returning to FIG. 11A, the cropped image sets may then be provided to vehicle speed estimation module. In some embodiments, the vehicle speed represents the speed of the vehicle relative to the vehicle undercarriage inspection system, when the vehicle is moving. In some embodiments the vehicle speed represents the speed of the vehicle undercarriage inspection system relative to the vehicle when the vehicle undercarriage inspection system is moving. The vehicle speed may be estimated based on the pixel shift values of the cropped image sets. In some embodiments, the vehicle speed may be estimated based on the pixel shift values by estimating the speed based on an estimated distance to the vehicle undercarriage. This estimated distance may be used to correlate the pixel shift values to distances and/or to vehicle speeds. In some embodiments, the vehicle speed may be estimated based on pixel shift values and data from one or more TOF sensors facing the undercarriage of the vehicle. The TOF sensor data may represent the distance between the vehicle and the vehicle undercarriage inspection system. The TOF sensor data may be used to more accurately convert the pixel shift values to distances and/or speed, and to reduce errors caused by varying depths of undercarriage components. For example, low hanging undercarriage components may appear to be moving faster than the remainder of the undercarriage due to their close proximity to cameras of the vehicle undercarriage imaging system and high differences in position in adjacent frames.

(346) A TOF sensor may give the distance between the vehicle undercarriage and the vehicle undercarriage inspection system. This distance may be used in determining the speed of the vehicle based on pixel shift distances, for use in stitching images as detailed below:

(347) For smooth image stitching, the number of pixels shifted c' should be determined for a fixed distance from camera d' of the undercarriage instead of varying heights.

$$c'.sub.i = s.sub.i * p / (l(d') * f)$$

(348) Where $s.sub.i$ is the speed in meters per second at image index i , p is the height of the center crop window used in phase correlation, f is the frames per second of the video.

(349) For a given distance from the camera d in meters, $l(d)$ is the length of the cropped window in meters.

$$l(d) = 2 * d * \tan(v/2)$$

(350) where v is the field of view of the camera for the cropped window measured using a flat charuco board at a fixed distance from the camera.

(351) Vehicle speed $s.sub.i$ is given by the following formula

$$s.sub.i = f * l(d.sub.i) * c.sub.i / p$$

(352) Where $d.sub.i$ is the distance from the camera in meters given by a TOF sensor, interpolated to match the camera's framerate, $c.sub.i$ is the number of pixels shifted given by phase correlation.

(353) The vehicle speed may be determined for each image of the cropped image sets. These images may then be used to generate a composite image. The composite image generation module

may generate a composite image by creating slices of the images of the image sets and combining the slices together to form a composite image. In some embodiments, the size of the slices may be determined based on the vehicle speed. In some embodiments the slices are taken along a width of the vehicle undercarriage. In some embodiments, the slices are blended together. In some embodiments the slices are blended using a soft feathering technique. The composite image may be displayed, and/or processed as described herein.

(354) FIGS. **11F** and **11G** illustrate the improved composite image quality from using the vehicle speed as recorded by a TOF sensor in combining images.

(355) FIG. **11F** is an example composite image of a vehicle generated based on vehicle speed estimated from pixel shift distances, according to some embodiments. As described herein, the depth of undercarriage parts can impact the speed estimated based on pixel shifts alone, with lower parts being estimated as moving faster and higher parts being estimated as moving slower, due to different proximities to the cameras of the vehicle undercarriage imaging system. As shown in image **1170**, in region **1171**, the image is visibly stretched which is likely due to this portion of the undercarriage being closer to the cameras than other portions. In section **1172**, the image is visibly compressed, which is likely due to this portion of the vehicle undercarriage being further from the camera than other portions.

(356) FIG. **11G** is an example composite image of a vehicle generated based on vehicle speed estimated from pixel shift distances and TOF sensor data, according to some embodiments. The composite image **1180** is of the same vehicle as composite image **1170** of FIG. **11F**. As can be seen, there is no compression or extension of portions of image **1180**, as there is in image **1170**. This is due to the more accurate vehicle speed which may be determined by using TOF sensor data, as described herein.

(357) FIG. **12** is an example of displaying images of a vehicle undercarriage, according to some embodiments. In some embodiments, the images of FIG. **12** may be displayed on a display of and/or connected to a vehicle undercarriage inspection system and/or a vehicle inspection system, as described herein.

(358) Shown in FIG. **12** is a vehicle undercarriage composite image **1200**, which may be generated as described herein. Composite image **1200** includes box **1210** around the bell housing of the vehicle. In some embodiments, the box may be applied to the image during processing to identify a defect in the undercarriage, for example a cracked bell housing. In some embodiments, the box may be generated by a user of the display. The box **1210** may be selectable to obtain additional views of the components of the undercarriage within the box. In some embodiments, a user may select any portion of the composite image to obtain additional views of the portion. In some embodiments, portions of the composite image identified as having defects may be selected to obtain additional views. In some embodiments, the user may review the additional views and provide inputs related to the views, for example confirming whether a defect is present.

(359) Additional views **1220** show the components within box **1210**. The views **1220** may be captured by one or more cameras of a vehicle undercarriage imaging system. In some embodiments, the additional views **1220** may be captured from different angles, providing views of the components within the box **1210** from different angles. These views allow for a more thorough analysis of the vehicle undercarriage components than is possible based on a composite image alone.

(360) FIG. **13A** illustrates one or more trained machine learning models **1300** for processing images of an undercarriage of a vehicle to evaluate the vehicle condition, according to some embodiments. As shown in FIG. **13A**, trained machine learning model **1300** includes trained machine learning model **1310** for processing the vehicle undercarriage images **1311** to obtain outputs **1315**.

(361) In some embodiments, the images **1311** may be captured as a part of a vehicle inspection, performed using a vehicle undercarriage inspection system. For example, as described with

reference to FIGS. 3A-F, and 7-9B. In some embodiments, the images may be a composite image of the vehicle undercarriage, which may be generated as described herein, for example as described with reference to FIGS. 10-11G.

(362) In some embodiments, trained machine learning model **1312** for processing the images of the vehicle may include preprocessing to generate input images for trained machine learning model **1314**. Preprocessing to generate input images may modify at least one characteristic of the images of the vehicle, prior to the image being processed by the trained machine learning model **1314**. Preprocessing may be performed by preprocessing module **1313**. In some embodiments, the undercarriage image processed by the model may have a resolution of 650×224. The resolution of the undercarriage image may be upsampled (e.g., the number of pixels may be increased) or downsampled (e.g., the number of pixels may be reduced) such that the smaller dimension of the image is a same dimension as an input to the convolutional neural network architecture. For example, if the convolutional neural network is engineered for 224×224 inputs, the undercarriage image may be input as an image having 224 pixels for the width, and 650 pixels for the height to match the average aspect ratio of the images. In some embodiments, the images are resized using bilinear interpolation.

(363) Trained machine learning model **1314** may be any suitable machine learning model for image analysis. In some embodiments, trained machine learning model **1314** is a 2D convolutional neural network. In some embodiments, ML model **1314** is structured as a deep convolutional neural network (DCNN). In some embodiments, ML model **1314** is structured as a YOLO architecture neural network. In some embodiments, ML model **1314** is a transformer-based model. In some embodiments, ML model **1314** is a diffusion model. In some embodiments the machine learning model **1314** is configured as an EfficientNet convolutional neural network.

(364) Outputs **1315** may include a list of vehicle defects and the respective likelihood of the defect being present in the vehicle. As shown in FIG. 13A outputs **1315** include the likelihood of a first vehicle defect **1316**, the likelihood of a vehicle image defect **1317**, and a likelihood of an nth vehicle defect **1318**. For example, when n=8 there may be 8 output classes (e.g., types of vehicle defects) including 7 defect classes and one affirmative quality class. In some embodiments, the outputs **1315** include likelihood of particular vehicle characteristics being present. Examples of vehicle characteristics and defects are described herein. In some embodiments, the outputs include likelihoods of image defects, for example incorrect cropping, insufficient detail, dirty lens, haze or glare, incorrect trim, and/or poor lighting, among other image defects.

(365) FIG. 13B illustrates one or more trained machine learning models **1320** for processing images and data of a vehicle undercarriage to evaluate the vehicle condition, according to some embodiments. As shown in FIG. 13B, trained machine learning model **1320** includes trained machine learning model **1324** for processing the vehicle data **1321** to obtain outputs **1327**.

(366) In some embodiments, the data **1321** may be captured as a part of a vehicle inspection, performed using a vehicle undercarriage inspection system. For example, as described with reference to FIGS. 3A-F, and 7-9B. In some embodiments, the images **1322** of the data **1321** may include a composite image of the vehicle undercarriage, which may be generated as described herein, for example as described with reference to FIGS. 10-11G.

(367) In some embodiments, the sensor data **1323** may include data collected by one or more sensors of a vehicle undercarriage inspection system, as described herein. For example, as described with respect to FIGS. 7-9B.

(368) In some embodiments, trained machine learning model **1324** for processing the vehicle data may include preprocessing to generate input data for trained machine learning model **1326**. Preprocessing to generate input data may modify at least one characteristic of the vehicle data, prior to the data being processed by the trained machine learning model **1326**.

(369) In some embodiments, the trained machine learning models **1324** may process vehicle images **1322** and sensor data **1323** separately. In some embodiments, the trained machine learning

models **1324** may process vehicle images **1322** and sensor data **1323** together. In some embodiments, the trained machine learning models **1324** may process vehicle images **1322** and sensor data **1323** together in part and separately in part.

(370) Trained machine learning model **1326** may be any suitable machine learning model for image and/or sensor data analysis. In some embodiments, trained machine learning model **1326** is a 2D convolutional neural network. In some embodiments, ML model **1326** is structured as a deep convolutional neural network (DCNN). In some embodiments, ML model **1326** is structured as a YOLO architecture neural network. In some embodiments, ML model **1326** is a transformer-based model. In some embodiments, ML model **1326** is a diffusion model. In some embodiments the machine learning model **1326** is configured as an EfficientNet convolutional neural network.

(371) Outputs **1327** may include a list of vehicle defects and the respective likelihood of the defect being present in the vehicle. As shown in FIG. **13B** outputs **1327** include the likelihood of a first vehicle defect **1328**, the likelihood of a vehicle image defect **1329**, and a likelihood of an nth vehicle defect **1330**. For example, when n=8 there may be 8 output classes (e.g., types of vehicle defects) including 7 defect classes and one affirmative quality class. In some embodiments, the outputs **1327** include likelihood of particular vehicle characteristics being present. Examples of vehicle characteristics and defects are described herein. In some embodiments, the outputs include likelihoods of image and/or data defects, for example incorrect cropping, insufficient detail, dirty lens, haze or glare, incorrect trim, insufficient magnitude, too noisy, and/or poor lighting, among other defects.

(372) FIG. **13C** illustrates one or more trained machine learning models **1340** for processing data of a vehicle undercarriage to evaluate the vehicle condition, according to some embodiments. As shown in FIG. **13C**, trained machine learning model **1343** includes trained machine learning model **1344** for processing the vehicle data **1342** to obtain outputs **1345**.

(373) In some embodiments, the data **1342** may be captured as a part of a vehicle undercarriage inspection, performed using a vehicle undercarriage inspection system. For example, as described with reference to FIGS. **7-9B**.

(374) In some embodiments, the vehicle data may sensor data **1342** about the undercarriage of a vehicle. In some embodiments, the sensor data **1342** may include data collected by one or more sensors of a vehicle undercarriage inspection system, as described herein.

(375) In some embodiments, trained machine learning model **1343** for processing the vehicle data may include preprocessing to generate input data for trained machine learning model **1344**.

Preprocessing to generate input data may modify at least one characteristic of the vehicle undercarriage data, prior to the data being processed by the trained machine learning model **1344**.

(376) In some embodiments, the trained machine learning models **1343** may process vehicle undercarriage sensor data from different vehicle undercarriage sensors separately. In some embodiments, the trained machine learning models **1343** may process the sensor data from different vehicle sensors together. In some embodiments, the trained machine learning models **1343** may process sensor data from different sensors together in part and separately in part.

(377) Trained machine learning model **1344** may be any suitable machine learning model for sensor data analysis. In some embodiments, trained machine learning model **1344** is a 2D convolutional neural network. In some embodiments, ML model **1344** is structured as a deep convolutional neural network (DCNN). In some embodiments, ML model **1344** is a transformer-based model.

(378) Outputs **1345** may include a list of vehicle defects and the respective likelihood of the defect being present in the vehicle. As shown in FIG. **13C** outputs **1345** include the likelihood of a first vehicle defect **1346**, the likelihood of a vehicle image defect **1347**, and a likelihood of an nth vehicle defect **1348**. For example, when n=8 there may be 8 output classes (e.g., types of vehicle defects) including 7 defect classes and one affirmative quality class. In some embodiments, the outputs **1345** include likelihood of particular vehicle characteristics being present. Examples of

vehicle characteristics and defects are described herein. In some embodiments, the outputs include likelihoods data defects, for example incorrect cropping, insufficient detail, incorrect trim, insufficient magnitude, and/or too noisy, among other defects.

(379) FIG. **14** is a flowchart of an illustrative process **1400** for performing a vehicle inspection using a vehicle undercarriage inspection system to determine vehicle defects, according to some embodiments. In some embodiments the vehicle undercarriage inspection system used in performing the process **1400** includes a sensor array with first, second and third cameras configured to capture images at different angles relative to the vehicle undercarriage, and a time of flight (TOF) sensor configured to output signals indicative of the distance of one or more parts of the vehicle relative to the vehicle undercarriage inspection system. In some embodiments, the vehicle undercarriage inspection system may be configured as described herein, for example as described with reference to FIGS. **7-9B**. In some embodiments, the process **1400** may be performed by one or more processors of a vehicle undercarriage inspection system, as described herein, for example processors **930** as described with reference to FIGS. **9A-9B**.

(380) Process **1400** begins at step **1401** by obtaining, using the TOF sensor, at least one first signal indicative of a distance between the vehicle and the TOF sensor. In some embodiments, signals may be obtained from multiple TOF sensors, for example 2 TOF sensors, 3 TOF sensors, 4 TOF sensors or greater than 4 TOF sensors. In some embodiments, the TOF sensor may be oriented facing the vehicle. In some embodiments, the TOF sensor may be oriented towards an end of a vehicle undercarriage inspection system and configured to capture signals indicative of the position and/or movement of one or more wheels of the vehicle, such as TOF sensor **722A** of FIG. **7**. In some embodiments, the TOF sensor may be oriented facing the undercarriage of the vehicle, such as sensor **722B** of FIG. **7**.

(381) Next, step **1402** is performed by in response to determining, using the at least one signal, that the vehicle is within a threshold distance of the TOF sensor, triggering the sensor array to capture one or more images of the vehicle undercarriage. In some embodiments, all sensors of the sensor array may be triggered to capture data from the vehicle undercarriage based on the at least one signal. In some embodiments, different sensors of the sensor arrays may be triggered at different times based on the at least one signal, for example cameras of the sensor array may be triggered first, followed by microphones of the sensor array. In some embodiments, step **1402** is performed by a system control module of a processor, for example module **937**.

(382) Next, step **1403** is performed by capturing the one or more images of the vehicle undercarriage using the sensor array. The one or more images may be captured using cameras of the sensor array.

(383) Next, step **1404** is performed by processing images of the plurality of images using a machine learning model to determine whether the vehicle has one or more defects. In some embodiments, the one or more defects include vehicle defects, as described herein. In some embodiments, step **1404** may be performed by a data processing and analysis module, such as **931**, as described herein. In some embodiments, the sensor data may undergo formatting for processing, as described herein. For example, a composite image may be generated for processing, using images and/or sensor data obtained from the undercarriage inspection system, such as described with reference to FIGS. **10-11G**. In some embodiments, the processing may be performed using one or more trained machine learning models to identify vehicle defects, for example ML models such as those described herein with reference to FIGS. **13A-C**.

(384) In some embodiments, the vehicle defects may be displayed and/or otherwise provided for a vehicle inspector for review. In some embodiments, the vehicle defects may be provided as a part of a vehicle condition report. In some embodiments, the vehicle defects may be formatted as likelihoods of the vehicle having the defects. In some embodiments, the vehicle defects may be formatted as probabilities of the vehicle having the defects. In some embodiments the vehicle defects may be confidence scores of the vehicle having the defects.

(385) Following the conclusion of process **1400**, the inspector may proceed to conduct a further vehicle inspection. Accordingly, in some embodiments, the inspector may use the identified defects and/or targeted professional inspection instructions to determine particular techniques to use during the further vehicle inspection to check for the potential vehicle defects. Additionally, or alternatively, the targeted professional inspection instructions may alert the inspector of features indicative of the potential vehicle defects.

(386) Additionally, or alternatively, the inspector may be a potential buyer who may use the defects to make more informed pricing offers or to check for themselves the presence of the potential vehicle defects. Additionally, or alternatively, the inspector may be a potential seller who may use the output to anticipate potential customer complaints. Additionally, or alternatively, the inspector may be the vehicle owner who may use the output to anticipate component failures and repairs.

(387) FIG. **15** is a flowchart of an illustrative process **1500** for analyzing vehicle condition using a vehicle undercarriage inspection system, according to some embodiments. In some embodiments, the vehicle undercarriage inspection system used in performing process **1500** includes a sensor array with first, second, and third cameras. In some embodiments, the vehicle undercarriage inspection system used in performing process **1500** may be configured as described herein, for example as described with reference to FIGS. **7-9B**. In some embodiments, process **1500** may be performed by one or more processors of a vehicle undercarriage inspection system, for example processors **930** as described with reference to FIGS. **9A-B**.

(388) Process **1500** begins at step **1501** by obtaining, using the sensor array of the vehicle undercarriage inspection system, sensor data about the undercarriage of the vehicle captured as the vehicle and vehicle undercarriage inspection system move relative to each other, the sensor data including: first, second and third sets of images captured by the first, second and third cameras, respectively, and data indicative of a position and/or motion of the vehicle relative to the vehicle undercarriage inspection system.

(389) In some embodiments, the vehicle may be driven over and/or around a vehicle undercarriage inspection system. In some embodiments a vehicle undercarriage inspection system may move beneath and/or around the vehicle.

(390) In some embodiments, the data indicative of the position and/or motion of the vehicle may be determined from the sets of images captured by the first, second and third cameras. In some embodiments, the data indicative of the position and/or motion of the vehicle may be captured from a TOF sensor.

(391) Next, step **1502** is performed by generating a composite image of the undercarriage of the vehicle by combining images of the first, second and third sets of images based on the data indicative of a position and/or motion of the vehicle relative to the vehicle undercarriage inspection system. In some embodiments, the composite image is generated in part by determining pixel shift distances between images in each of the sets of images, aligning the sets of images, cropping the aligned sets of images, estimating the speed of the vehicle in images of the sets of images, and combining the images of the sets of images based on the vehicle speed, as described with reference to FIGS. **10-11G**. In some embodiments, the vehicle speed may be determined based on pixel shift distances. In some embodiments, the vehicle may be determined based on pixel shift distances and data obtained from a TOF sensor.

(392) Next, step **1503** is performed by determining whether the vehicle has one or more defects by processing the composite image, using a first trained machine learning (ML) model. In some embodiments, the one or more defects include vehicle defects, as described herein. In some embodiments, step **1503** may be performed by a data processing and analysis module, such **931**, as described herein. In some embodiments, the processing may be performed using one or more trained machine learning models to identify vehicle defects, for example ML models such as those described herein with reference to FIGS. **13A-C**.

(393) Next, step **1504** is performed by generating a vehicle condition report based on results of the

processing. In some embodiments, step **1504** is performed by a vehicle report generation module, such as **935** as described with reference to FIG. **9B**. In some embodiments, the condition report includes data related to the vehicle such as vehicle characteristics and/or defects, for example as described with reference to FIG. **2**. In some embodiments, data of a vehicle condition report may be determined using one or more machine learning models, such as those described herein with reference to FIGS. **13A-C**. In some embodiments, the vehicle condition report may be displayed and/or otherwise provided for a vehicle inspector for review.

(394) Following the conclusion of process **1500**, the inspector may proceed to conduct a further vehicle inspection. Accordingly, in some embodiments, the inspector may use the vehicle condition report and/or targeted professional inspection instructions to determine particular techniques to use during the further vehicle inspection (e.g., to check for the potential vehicle defects).

(395) Additionally, or alternatively, the inspector may be a potential buyer who may use the vehicle condition report to make more informed pricing offers or to perform an inspection of the vehicle for themselves (e.g., to determine the presence of the potential vehicle defects). Additionally, or alternatively, the inspector may be a potential seller who may use the output to anticipate potential customer complaints. Additionally, or alternatively, the inspector may be the vehicle owner who may use the output to anticipate component failures and repairs.

(396) FIG. **16A** is a flowchart of an illustrative process **1600** for inspecting an undercarriage of a vehicle using a vehicle undercarriage inspection system, according to some embodiments. In some embodiments, the vehicle undercarriage inspection system used in performing process **1600** includes a sensor array with first, second and third cameras configured to capture images at different angles relative to the vehicle undercarriage, and a sensor configured to output data indicative of the position and/or motion of the vehicle relative to the vehicle undercarriage inspection system. In some embodiments, the vehicle undercarriage inspection system is configured as described with reference to FIGS. **7-9B**. Some steps of process **1600** may be performed by an inspector and some steps may be performed by one or more components of the vehicle undercarriage inspection system.

(397) Process **1600** begins with step **1601** by positioning the vehicle undercarriage inspection system relative to the vehicle. In some embodiments, vehicle undercarriage inspection system may be positioned as described with reference to FIGS. **3A-F**, with the vehicle undercarriage inspection system positioned in front of a vehicle. In some embodiments, an inspector may perform step **1601**. In some embodiments step **1601** may be performed automatically by the vehicle undercarriage inspection system. In some embodiments step **1601** may be performed in part by an inspector and in part by the vehicle undercarriage inspection system.

(398) Next, step **1602** is performed by moving the vehicle and the vehicle undercarriage inspection system relative to one another. In some embodiments, the vehicle may be driven over the vehicle undercarriage inspection system, such as described with reference to FIGS. **3A-F**. The vehicle may be driven by an inspector or by another individual. In some embodiments, the vehicle undercarriage inspection system may move relative to the vehicle. For example, the vehicle undercarriage inspection system may move beneath and/or around the vehicle.

(399) Next, step **1603** is performed by triggering capture of data about the vehicle undercarriage by the sensor array of the vehicle undercarriage inspection system. In some embodiments, the triggering is performed automatically by the vehicle undercarriage inspection system. In some embodiments the triggering is performed automatically based on signals obtained from one or more sensors of the vehicle undercarriage inspection system, such as TOF sensors, and/or cameras. In some embodiments, the triggering is performed when the vehicle is determined to be at one or more positions relative to the vehicle inspection undercarriage system based on sensor data. In some embodiments different sensors of the vehicle undercarriage inspection system may be triggered at different times, for example sensors having different orientations may be triggered based on the position of the vehicle. In some embodiments, the triggering is performed in response

to one or more inputs received from an inspector, such as through a user interface or other inputs as described herein.

(400) Next, step **1604** is performed by capturing the data about the vehicle undercarriage using the sensor array of the vehicle undercarriage inspection system, the data about the vehicle including a plurality of images of the undercarriage of the vehicle captured by the first, second, and third cameras at the different angles relative to the vehicle undercarriage.

(401) Next, step **1605** is performed by stopping capture of the data about the vehicle undercarriage. In some embodiments, the stopping is performed automatically by the vehicle undercarriage inspection system. In some embodiments the stopping is performed automatically based on signals obtained from one or more sensors of a vehicle undercarriage inspection system, such as TOF sensors, and/or cameras. In some embodiments, the stopping is performed when the vehicle is determined to be at one or more positions relative to the vehicle undercarriage inspection system based on sensor data. In some embodiments individual sensors may be stopped at different times, for example sensors having different orientations may be stopped based on the position of the vehicle. In some embodiments, the stopping is performed in response to inputs received from an inspector, such as through a user interface or other inputs as described herein.

(402) Next, step **1606** is performed by generating, based on at least some of the plurality of images, a composite image of the vehicle undercarriage. In some embodiments, the composite image is generated in part by determining pixel shift distances between images of the plurality of images, aligning images of the plurality of images, cropping the aligned images, estimating the speed of the vehicle in the images, and combining the images based on the vehicle speed, as described with reference to FIGS. **10-11G**. In some embodiments, the vehicle speed may be determined based on pixel shift distances. In some embodiments, the vehicle may be determined based on pixel shift distances and data obtained from a TOF sensor. In some embodiments, the composite image may be displayed and/or otherwise provided for a vehicle inspector for review.

(403) Following the conclusion of process **1600**, the inspector may proceed to conduct a further vehicle inspection. Accordingly, in some embodiments, the inspector may use the composite image and/or targeted professional inspection instructions to determine particular techniques to use during the further vehicle inspection (e.g., to check for the potential vehicle defects).

(404) Additionally, or alternatively, the inspector may be a potential buyer who may use the composite image to make more informed pricing offers or to perform an inspection of the vehicle for themselves (e.g., to determine the presence of the potential vehicle defects). Additionally, or alternatively, the inspector may be a potential seller who may use the output to anticipate potential customer complaints. Additionally, or alternatively, the inspector may be the vehicle owner who may use the output to anticipate component failures and repairs.

(405) FIG. **16B** is a flowchart of an illustrative process **1610** for preparing and using a vehicle undercarriage inspection system to perform a vehicle inspection, according to some embodiments. In some embodiments, the vehicle undercarriage inspection system used in performing process **1610** includes a sensor array with first, second and third cameras configured to capture images at different angles relative to the vehicle undercarriage, and a sensor configured to output data indicative of the position and/or motion of the vehicle relative to the vehicle undercarriage inspection system. In some embodiments, the vehicle undercarriage inspection system is configured as described with reference to FIGS. **7-9B**. Some steps of process **1610** may be performed by an inspector and some steps may be performed by one or more components of the vehicle undercarriage inspection system.

(406) Process **1610** begins with step **1611** by positioning the vehicle undercarriage inspection system relative to the vehicle. In some embodiments, vehicle undercarriage inspection system may be positioned as described with reference to FIGS. **3A-F**, with the vehicle undercarriage inspection system positioned in front of a vehicle. In some embodiments, an inspector may perform step **1611**. In some embodiments step **1611** may be performed automatically by the vehicle undercarriage

inspection system. In some embodiments step **1611** may be performed in part by an inspector and in part by the vehicle undercarriage inspection system.

(407) Next, step **1612** is performed by triggering the vehicle undercarriage inspection system to collect alignment data of the vehicle relative to the vehicle undercarriage inspection system. In some embodiments, the triggering is performed automatically by the vehicle undercarriage inspection system. In some embodiments the triggering is performed automatically based on signals obtained from one or more sensors of the undercarriage inspection system, such as TOF sensors, and/or cameras. In some embodiments, the triggering is performed when the vehicle is determined to be at one or more positions relative to the vehicle undercarriage inspection system based on sensor data.

(408) In some embodiments, the triggering is performed manually by an inspector by providing one or more inputs to a vehicle undercarriage inspection system, such as through a user interface or other inputs as described herein.

(409) In some embodiments, the alignment data includes data from one or more TOF sensors of the vehicle undercarriage inspection system, as described herein. For example, the alignment data may include data collected by TOF sensors of the vehicle undercarriage imaging system as described with reference to FIGS. 7-9B. In some embodiments, the alignment data includes data from one or more cameras of the vehicle undercarriage inspection system.

(410) Next, step **1613** is performed by obtaining, based on the alignment data, an indication of an alignment of the vehicle relative to the vehicle inspection system. In some embodiments, the indication of alignment may be determined by the vehicle undercarriage inspection system. In some embodiments, the indication of alignment may be determined by an alignment verification module, such as module **932** as described with reference to FIG. 9B. In some embodiments, the indication of alignment may be provided on a display of the vehicle undercarriage inspection system, as described in herein.

(411) Next, step **1614** is performed by repositioning the vehicle relative to the vehicle undercarriage inspection system based on the indication of the alignment of the vehicle relative to the vehicle inspection system. In some embodiments, step **1614** may be performed by an inspector or another individual. In some embodiments step **1614** may be performed automatically by the vehicle undercarriage inspection system. In some embodiments step **1614** may be performed in part by an inspector or other individual and in part automatically the vehicle undercarriage inspection system. In some embodiments, the indication of alignment includes a direction for repositioning, and step **1614** may be performed based on the direction for repositioning.

(412) In some embodiments, steps **1611-1614** may be iterated until the vehicle is determined to be properly aligned.

(413) Next, step **1615** is performed by moving the vehicle and the vehicle undercarriage inspection system relative to one another. In some embodiments, the vehicle may be driven over the vehicle undercarriage inspection system, such as described with reference to FIGS. 3A-F. The vehicle may be driven by an inspector or by another individual. In some embodiments, the vehicle undercarriage inspection system may move relative to the vehicle. For example, the vehicle undercarriage inspection system may move beneath and/or around the vehicle.

(414) Next, step **1616** is performed by capturing sensor data about the vehicle undercarriage using the sensor array of the vehicle undercarriage inspection system, the data about the vehicle including a plurality of images of the undercarriage of the vehicle.

(415) Next, step **1617** is performed by generating, based on at least some of the plurality of images, a composite image of the vehicle undercarriage. In some embodiments, the composite image is generated in part by determining pixel shift distances between images of the plurality of images, aligning images of the plurality of images, cropping the aligned images, estimating the speed of the vehicle in the images, and combining the images based on the vehicle speed, as described with reference to FIGS. 10-11G. In some embodiments, the vehicle speed may be determined based on

pixel shift distances. In some embodiments, the vehicle may be determined based on pixel shift distances and data obtained from a TOF sensor. In some embodiments, the composite image may be displayed and/or otherwise provided for a vehicle inspector for review.

(416) Following the conclusion of process **1610**, the inspector may proceed to conduct a further vehicle inspection. Accordingly, in some embodiments, the inspector may use the composite image and/or targeted professional inspection instructions to determine particular techniques to use during the further vehicle inspection (e.g., to check for the potential vehicle defects).

(417) Additionally, or alternatively, the inspector may be a potential buyer who may use the composite image to make more informed pricing offers or to perform an inspection of the vehicle for themselves (e.g., to determine the presence of the potential vehicle defects). Additionally, or alternatively, the inspector may be a potential seller who may use the output to anticipate potential customer complaints. Additionally, or alternatively, the inspector may be the vehicle owner who may use the output to anticipate component failures and repairs.

(418) FIG. **16C** is a flowchart of an illustrative process **1620** for using a vehicle undercarriage inspection system to analyze vehicle conditions, according to some embodiments. In some embodiments, the vehicle undercarriage inspection system used in performing process **1620** includes a sensor array with first, second and third cameras configured to capture images at different angles relative to the vehicle undercarriage, and a sensor configured to output data indicative of the position and/or motion of the vehicle relative to the vehicle undercarriage inspection system. In some embodiments, the vehicle undercarriage inspection system is configured as described with reference to FIGS. **7-9B**. Some steps of process **1620** may be performed by an inspector and some steps may be performed by one or more components of the vehicle undercarriage inspection system.

(419) Process **1620** begins at step **1621** by moving the vehicle and the vehicle undercarriage inspection system relative to one another. In some embodiments, the vehicle may be driven over the vehicle undercarriage inspection system, such as described with reference to FIGS. **3A-F**. The vehicle may be driven by an inspector or by another individual. In some embodiments, the vehicle undercarriage inspection system may move relative to the vehicle. For example, the vehicle undercarriage inspection system may move beneath and/or around the vehicle.

(420) Next, step **1622** is performed by capturing sensor data about the vehicle undercarriage using the sensor array of the vehicle undercarriage inspection system.

(421) Next step **1623** is performed by providing, to a computer hardware processor, the data about the vehicle undercarriage. In some embodiments, the computer hardware processor is a component of the vehicle undercarriage inspection system. In some embodiments the computer hardware processor is a processor remote from the vehicle undercarriage inspection system. In some embodiments, the data may be formatted and/or processed before it is provided to the computer hardware processor. For example, the data may be processed as described with reference to the components of processor **930**, as discussed with reference to FIG. **9B**. In some embodiments, the data about the vehicle undercarriage includes a composite image of the vehicle undercarriage, as described herein with reference to FIGS. **10-11G**.

(422) Next, step **1623** is performed by receiving, from the computer hardware processor, a vehicle condition report indicating one or more defects present on the vehicle. In some embodiments, the condition report includes data related to the vehicle, for example as described with reference to FIG. **2**. In some embodiments, data of a vehicle condition report may be determined using one or more machine learning models, such as those described herein with reference to FIGS. **13A-C**. In some embodiments, the vehicle condition report may be displayed and/or otherwise provided for a vehicle inspector for review.

(423) Next step **1625** is performed by providing, to the computer hardware processor, a request for sensor data related to the one or more defects present on the vehicle. In some embodiments, step **1625** may be performed by an inspector, such as by providing one or more inputs to the vehicle

undercarriage inspection system, such as through a user interface of the vehicle undercarriage inspection system, as described herein. In some embodiments, the vehicle condition report may include one or more selectable inputs related to the defects. In some embodiments, the request may be provided by selecting a region of a vehicle undercarriage composite image, such as described with reference to FIG. 12.

(424) Next, step **1626** is performed by receiving, from the computer hardware processor, a plurality of sensor data related to the one or more defects present on the vehicle. In some embodiments, the plurality of sensor data includes the sensor data used in determining the one or more defects are present. In some embodiments, the plurality of sensor data is provided in one or more visual displays, such as charts, plots, images and/or other visual displays. In some embodiments the plurality of sensor data includes a plurality of images of the defect, such as described with reference to FIG. 12. In some embodiments, the plurality of sensor data may be displayed and/or otherwise provided for a vehicle inspector for review.

(425) Following the conclusion of process **1620**, the inspector may proceed to conduct a further vehicle inspection. Accordingly, in some embodiments, the inspector may use the sensor data related to the one or more defects and/or targeted professional inspection instructions to determine particular techniques to use during the further vehicle inspection (e.g., to check for the potential vehicle defects).

(426) Additionally, or alternatively, the inspector may be a potential buyer who may use sensor data related to the one or more defects to make more informed pricing offers or to perform an inspection of the vehicle for themselves (e.g., to determine the presence of the potential vehicle defects). Additionally, or alternatively, the inspector may be a potential seller who may use the output to anticipate potential customer complaints. Additionally, or alternatively, the inspector may be the vehicle owner who may use the output to anticipate component failures and repairs.

(427) FIGS. 17A-H illustrate example vehicle exterior inspection systems, according to some embodiments.

(428) FIG. 17A illustrates an example vehicle exterior inspection system with two support members, according to some embodiments. Vehicle inspection system **1700** includes support members **1701A** and **1701B**. The support members include sensor arrays **1702**, which may be oriented at different angles, as described herein. The sensor arrays may include multiple sensors for recording data about vehicle **1703**. Data may be recorded about vehicle **1703** as the vehicle drives past support members **1701A** and **1701B**.

(429) FIG. 17B illustrates an example vehicle exterior inspection system with four support members, according to some embodiments. Vehicle inspection system **1704** includes support members **1705A-D**. The support members include sensor arrays **1706**, which may be oriented at different angles, as described herein. As shown, the support members **1705A-D** are positioned at different angles relative to each other. The sensor arrays **1706** may include multiple sensors for recording data about vehicle **1707**. Data may be recorded about vehicle **1707** as the vehicle drives past support members **1705A-D**.

(430) FIG. 17C illustrates an example vehicle inspection system with rotating support members, according to some embodiments. Vehicle inspection system **1708** includes 2 support members, **1709 A** and **1709 B**. The two support members **1709 A** and **1709 B** contain multiple sensor arrays **1711**. The sensor arrays **1711** may include multiple sensors, as described herein. The support members **1709 A** and **1709 B** may be configured to rotate as vehicle **1712** drives between these support members, in order to capture data from multiple angles relative to the vehicle. The support members **1709 A** and **1709 B** may rotate as shown by respective arrows **1710 A** and **1710 B**. Data may be recorded about vehicle **1712** as the vehicle drives past support members **1709 A** and **1709 B**.

(431) FIG. 17D illustrates an example vehicle inspection system with a moving sensor array, according to some embodiments. As shown, vehicle inspection system **1713** includes frame

members **1714 A** and **1714 B**. The frame members support sensor array component **1715**. Sensor array component **1715** includes multiple sensor arrays **1716**. Sensor arrays **1716** may include multiple sensors, as described herein. As shown vehicle **1718** is parked between frame members **1714 A** and **1714 B**. The sensor array component **1715** may move along frame members **1714 A** and **1714 B** to capture data from multiple portions of the exterior of the vehicle **1718**. The sensor array component may move along arrow **1717** to capture the data about the vehicle **1718**.

(432) FIG. **17E** illustrates an example vehicle exterior inspection system with a frame and a moving and rotating sensor array, according to some embodiments. Vehicle inspection system **1719** includes frame **1720**. Vehicle **1728** is parked within frame **1720**. Sensor array **1724** is attached to a rotating component **1723**, and rotating component **1723** is attached to sliding component **1721**. The sensor array may be moved around the vehicle **1728** to capture data from multiple portions of the vehicle, as described herein. Sliding component **1721** may move the rotating component **1723** along directions **1726** and **1727**. Rotating component **1723** may rotate as shown by arrow **1725** as it is moved by the sliding component **1721** to capture data from different portions of the vehicle **1728**.

(433) FIG. **17F** illustrates an example vehicle exterior inspection system with a frame and a moving sensor array, according to some embodiments. Vehicle exterior inspection system **1729** includes frame **1730**. Frame **1730** includes 4 pillars which support sensor array **1731**. Sensor array **1731** may include multiple sensors to capture data about vehicle **1733**, as described herein. Sensor array **1731** may move along direction **1732** to capture data about vehicle **1733**. As shown, sensor array **1731** is shaped as a ring which may encompass vehicle **1733** as it is moved along direction **1732**. Accordingly, sensor array **1731** may capture data from multiple angles of vehicle **1733**.

(434) FIG. **17G** Illustrates an example vehicle exterior inspection system with a pivoting frame, according to some embodiments. Vehicle exterior inspection system **1734** includes frame **1735**. Frame **1735** may pivot between position **1736** and **1737** to capture data about vehicle **1739**, from multiple angles. Frame **1735** may move as shown by arrows **1738**. Frame **1735** may support one or more sensor arrays to capture data about vehicle **1739**, as described herein. In some embodiments frame **1735** may move as vehicle **1739** is driven beneath frame **1735**. In some embodiments, frame **1735** may move well vehicles **1739** is parked beneath frame **1735**.

(435) FIG. **17H** Illustrates an example vehicle exterior inspection system with a turntable, according to some embodiments. Vehicle exterior inspection system **1740** includes sensor array **1741** which may include multiple sensors to capture data about vehicle **1744**, as described herein. Vehicle **1744** is positioned on turntable **1742** which may rotate such that the sensor array **1741** may capture data from multiple angles of vehicle **1744**.

(436) FIGS. **18A-C** illustrate an example support member of a vehicle exterior inspection system, according to some embodiments. Support member **1800** includes sensor arrays **1820A-D**, and **1821**. Sensor arrays **1820A-D** include three cameras, each camera oriented in a different direction, and may include additional sensors as described herein. In some embodiments, the sensor arrays are shaped as a trapezoid, with a camera oriented three sides of the trapezoid. In some embodiments, sensor arrays **1820A-D** include light sources. Sensor array **1821** may include sensors such as microphones, air quality sensors, and/or TOF sensors, among other sensors as described herein. In some embodiments, sensor array **1821** includes a light source. Support member **1800** includes multiple portions, including angled portion **1811** and vertical portion **1810**. In some embodiments, the support member **1800** may be used in conjunction with a second support member to capture data from a vehicle. In some embodiments, the support member **1800** may capture data from a vehicle as the vehicle is driven past support member **1800**.

(437) Sensor array **1820A** is positioned on angled portion **1811**. Angled portion **1811** may be angled relative to vertical portion **1810** such that the sensors of sensor array **1820A** may capture data from the roof of a vehicle. Vertical portion **1810** may be oriented substantially vertically, as shown in FIGS. **18A-C**. Sensor array **1820B** is positioned on vertical portion **1810** and may be

configured to capture data about the sides of a vehicle. Sensor array **1820C** is positioned on vertical portion **1810** and may be configured to capture data from lower portions of a vehicle, such as wheels, tires and/or rocker panels. Sensor array **1820D** is positioned at the bottom of vertical portion **1810** and may be configured to capture images of lower portions of a vehicle including wheels, tires and/or rocker panels. In some embodiments, sensor array **1820D** is angled to capture data from a vehicle. Sensor array **1821** is positioned on the vertical portion **1810** and may be configured to capture signals from a side of a vehicle.

(438) Support member **1800** additionally includes base **1812**, which allows the support member **1800** to stand.

(439) Support member **1800** additionally includes housing **1830** which may include one or more components of the vehicle exterior imaging system. For example, housing **1830** may include components such as circuitry, processors, heat management components, inputs, a power supply, routers, and/or networking components, among other components as described herein. As shown, housing **1830** is attached to vertical portion **1810**.

(440) In some embodiments, support member **1800** is collapsible between a stowed and a deployed configuration. For example, one or more components such as vertical portion **1810** base, **1812**, and angled portion **1811** may be telescoping and/or may have hinges or other features for folding or collapsing. As shown, in FIGS. **18A-C** support member **1800** is in the deployed configuration.

(441) FIG. **18D** illustrates an example vehicle exterior imaging system, according to some embodiments. The vehicle exterior imaging system includes two support members, **1800** and **1840**. FIG. **18D** includes example dimensions in inches for the positioning of various components. For example, support member **1800** has a height of 126.13 in, and is positioned 105.6 in from support member **1840**.

(442) Sensor array **1820C** is positioned at a height of 15.5 in, but may be adjusted to any suitable height, for example between 0 and 50 in. Sensor array **1821** is positioned at a height of 37.75 in but may be adjusted to any suitable height for example between 0 and 80 in. Sensor array **1820B** is positioned at a height of 60 in but may be adjusted to any suitable height, for example between 20 and 100 in. Sensor array **1820A** is positioned at a height of 118.11 in but may be adjusted to any suitable height, for example between 100 and 125 in.

(443) The dimensions are shown by way of example only and may vary to be greater or smaller due to desired positioning and adjustability.

(444) In addition, example angles are shown in FIG. **18D**. For example, angled portion **1841** is angled at 135° from vertical portion **1842**. In addition, sensor array **1843** is positioned at an angle of 120°. The angles are shown by way of example only and may vary to be greater or smaller by 5%, 10%, 20% or greater than 20%. In some embodiments, one or more angles of the vehicle exterior imaging system may be adjustable.

(445) In some embodiments, a vehicle exterior imaging system, such as those described with reference to FIGS. **17A-18D** may be configured to image many sizes of vehicles.

(446) In some embodiments, a vehicle exterior imaging system may be capable of imaging vehicles having lengths between a minimum and maximum length. In some embodiments, the minimum length may be 60 inches, 80 inches, 100 inches, 120 inches, 150 inches, or any length between 60 and 150 inches. In some embodiments, the maximum length may be 200 inches, 220 inches, 240 inches, 260 inches, 280 inches, 290 inches, 300 inches, 320 inches, 350 inches, or any length between 200 and 350 inches.

(447) In some embodiments, a vehicle exterior imaging system may be capable of imaging vehicles having heights between a minimum and maximum height. In some embodiments, the minimum height may be 35 inches, 40 inches, 45 inches, 50 inches, 55 inches, or any height between 35 and 55 inches. In some embodiments, the maximum height may be 90 inches, 95 inches, 100 inches, 105 inches, 110 inches, 115 inches, 120 inches, 125 inches, 150 inches, or any height between 90 and 150 inches.

(448) In some embodiments, a vehicle exterior imaging system may be capable of imaging vehicles having widths between a minimum and maximum width. In some embodiments, the minimum width may be 45 inches, 55 inches, 60 inches, 65 inches, 70 inches, or any width between 45 and 70 inches. In some embodiments, the maximum width may be 85 inches, 90 inches, 95 inches, 100 inches, 105 inches, 110 inches, 115 inches, 120 inches, 150 inches, or any width between 85 and 150 inches.

(449) In some embodiments, a vehicle exterior imaging system may be capable of imaging vehicles having wheelbases between a minimum and maximum lengths. In some embodiments, the minimum wheelbase length may be 60 inches, 70 inches, 80 inches, 90 inches, 100 inches, or any length between 60 and 100 inches. In some embodiments, the maximum length may be 160 inches, 170 inches, 180 inches, 190 inches, 200 inches, 210 inches, 220 inches, 250 inches, or any length between 160 and 250 inches.

(450) In some embodiments, the minimum a maximum lengths, widths, heights and wheelbase lengths are determined based on a pixel density of a FOV of the cameras at that dimension.

(451) In some embodiments, vehicle exterior inspection systems, as described herein are configured to capture complete exterior images of vehicles which are smaller than “oversized vehicles” according to U.S. National Size Specifications for Vehicles on Road.

(452) In some embodiments, imaging of different sized vehicles is accomplished in part by the FOVs of cameras of vehicle exterior inspection systems. In some embodiments, cameras of a vehicle exterior inspection system have FOVs of up to 175° in any direction, up to 170° in any direction, up to 160° in any direction, up to 155° in any direction, up to 150° in any direction, up to 145° in any direction, up to 140° in any direction, up to 130° in any direction or up to 100° in any direction. In some embodiments, cameras of vehicle exterior inspection systems have different FOVs depending on their positions. For example, a camera configured to capture images of the side of a vehicle may have a horizontal FOV of 170° and a vertical FOV of 160°.

(453) FIG. **19** shows an example of fields of view of camera sets of a vehicle exterior inspection system, according to some embodiments. Shown is support member **1910** which is capturing data from vehicle **1913**.

(454) Support member **1910** includes three sensor arrays **1911A-C**, however, may include greater or fewer sensor arrays, as described herein. As shown, sensor array **1911A** is positioned on an angled portion of the support member and is overlooking the roof of the vehicle **1913**. Sensor array **1911B** is positioned at about eye level. Finally, sensor array **1911C** is positioned low and is angled upwards towards the vehicle **1913**.

(455) Each sensor array **1911A-C** includes a camera set with three cameras, oriented at different angles. The cameras of the camera set may have a camera angled in part into the page of FIG. **19**, in part to the left of FIG. **19**, and in part out of the page of FIG. **19**. The orientation of the cameras of the camera sets of sensor arrays **1911A-C** allow for images to be captured of different portions of the vehicle.

(456) FIG. **19** includes the FOVs **1912A-C**, respectively of cameras of camera sets of sensor arrays **1911A-C**. FOV **1912A** is of a camera of sensor array **1911A** and is shown outlined in dashes. FOV **1912A** includes the top portion of the vehicle and extends from above the roof of the vehicle to the hood of the vehicle. FOV **1912B** is of a camera of sensor array **1911B** and is shown outlined in dots. FOV **1912B** is of the middle of the vehicle and extends from part of the wheels to the roof of the vehicle. FOV **1912C** is of a camera of sensor array **1911C** and is shown outlined in dots and dashes. FOV **1912C** is of the lower part of the vehicle and extends from above the wheels of the vehicle to below the wheels of the vehicle.

(457) As shown the FOVs overlap, therefore images of vehicle components may be captured by multiple cameras of the sensor arrays **1911A-C**.

(458) FIG. **20** illustrates an example of images captured by a vehicle exterior inspection system, according to some embodiments. FIG. **20** shows sensor array, including a camera set, at three

different points in time, as vehicle **2025** moves past the vehicle inspection system. The sensor array illustrated in FIG. **20** may be a sensor array as described herein, and/or may be included in a vehicle exterior inspection system, as described herein. The sensor array shown in FIG. **20** may be positioned on a vertical portion of a support member, such as sensor array **1911** of FIGS. **19** and/or **1820B** of FIGS. **18A-D**.

(459) FIG. **20** includes sensor array **2010A**, which represents a sensor array of a vehicle exterior inspection system, at a first point in time, as a vehicle approaches the vehicle exterior inspection system. As shown, sensor array **2010A** includes a camera set with cameras **2011A**, **2012A** and **2013A**. The camera set may capture image set **2014A**, which includes two images. This is because the vehicle is within the FOV of two cameras, **2012A** and **2013A**. The leftmost image of image set **2014A** shows the side of the vehicle, including the hood and front wheel, as the vehicle is alongside the vehicle exterior imaging system and is captured by camera **2012A**. The rightmost image shows a view of the driver side of the vehicle from the front of the vehicle and was captured by camera **2013A**. The vehicle **2015** is not within the FOV of camera **2011A**, as the vehicle approaches the vehicle exterior imaging system at the first timepoint.

(460) FIG. **20** includes sensor array **2010B**, which represents a sensor array of a vehicle exterior inspection system, at a second point in time, as a vehicle **2015** is alongside the vehicle exterior inspection system. As shown, sensor array **2010B** includes a camera set with cameras **2011B**, **2012B** and **2013B**. The camera set may capture image set **2014B**, which includes three images. This is because the vehicle is within the FOV of all three cameras, **2011B**, **2012B** and **2013B**. The leftmost image of image set **2014B** shows the front, driver's side of the vehicle, including the hood and front wheel, as the vehicle moves alongside the vehicle exterior imaging system and is captured by camera **2011B**. The center image of image set **2014B** shows the side of the vehicle **2015** as the vehicle is alongside the vehicle exterior inspection system and is captured by camera **2012B**. The rightmost image shows a view of the rear driver side of the vehicle from captured from the center of the vehicle and is captured by camera **2013B**.

(461) FIG. **20** includes sensor array **2010C**, which represents a sensor array of a vehicle exterior inspection system, at a third point in time, as a vehicle moves past the vehicle exterior inspection system. As shown, sensor array **2010C** includes a camera set with cameras **2011C**, **2012C** and **2013C**. The camera set may capture image set **2014C**, which includes two images. This is because the vehicle is within the FOV of two cameras, **2011C** and **2012C**. The leftmost image of image set **2014C** shows the driver's side of the vehicle, captured from the rear of the vehicle as the vehicle moves past the vehicle exterior imaging system and is captured by camera **2011C**. The rightmost image shows a view of the rear driver side of the vehicle, including the rear wheel and trunk, and was captured by camera **2012C**. The vehicle **2015** is not within the FOV of camera **2013C**, as the vehicle moves past the vehicle exterior imaging system at the third timepoint.

(462) FIG. **21A** is a diagram illustrating the components of a vehicle exterior inspection system, according to some embodiments. Vehicle exterior inspection system **2100** includes subsystems **2110A** and **2110B**, system components **2120**, and processor(s) **2130**. The vehicle exterior inspection system **2100** is an example vehicle exterior inspection system and may be configured as described herein, for example, as described with reference to FIGS. **17A-20**. In some embodiments, subsystems **2110A** and **2110B**, system components **2120** and processors **2130** may be implemented in a single device and/or location. In some embodiments, the subsystems **2110A-B**, system components **2120** and processors **2130** may be implemented in separate devices and/or locations. In some embodiments, the subsystems **2110A-B**, system components **2120**, and processors **2130** may be implemented in part in a single device and/or location and in part in separate and/or remote devices and/or locations.

(463) Subsystems **2110A** and **2110B** may be portions of a vehicle exterior inspection system, such as support members or other portions which may support one or more sensor arrays, as described herein. In some embodiments, a vehicle exterior inspection system may include one or more

subsystems for capturing data about a vehicle. As shown, the vehicle exterior inspection system **2100** includes two subsystems **2110A** and **2110B**, each of which includes respective sensor arrays **2111A** and **2111B**. In some embodiments, subsystems may include any suitable number of sensor arrays, for example, 1, 2, 3, 4, 5 or greater than 5 sensor arrays.

(464) Components of a sensor array of sensor arrays **2111A** are shown in FIG. **21A**. These components include cameras **2112A**, light source **2113A**, magnetometers **2115A**, air quality sensors **2116A**, time of flight sensors **2114A**, and microphones **2117A**. In some embodiments, a sensor array may include greater or fewer sensor than those shown in FIG. **21A**, as described herein.

(465) Cameras **2112A** may capture images of the exterior of a vehicle. The images may be captured as the vehicle and vehicle exterior inspection system move relative to one another. In some embodiments, the cameras **2112A** may be configured as a camera set, as described herein. In some embodiments the cameras **2112A** may include different types of cameras, for example, optical cameras, thermal cameras, and/or IR cameras. In some embodiments, the cameras **2112A** may be oriented at different angles, as described herein. In some embodiments, the images captured by the cameras **2112A** may be analyzed to determine one or vehicle characteristics and/or defects, as described herein.

(466) Light source **2113A** may be used to illuminate the vehicle exterior to facilitate capturing of images of the vehicle. In some embodiments, the light source **2113A** may include one or more individual light sources which supply light to the vehicle exterior, as described herein. In some embodiments, the individual light sources of light source **2113A** may be oriented at different angles, as described herein.

(467) TOF sensors **2114A** may capture data indicative of the position and/or motion of the vehicle relative to the vehicle exterior inspection system **2100**. In some embodiments, the TOF sensors **2114A** may capture data indicative of the position and/or motion of the vehicle relative to a vehicle inspection system, as described herein. In some examples, the TOF sensors **2114A** may include multiple TOF sensors. In some embodiments, the TOF sensors **2114A** may be oriented in different directions. In some embodiments, data collected by TOF sensors **2114A** may be used in determining vehicle alignment with the vehicle exterior inspection system. In some embodiments, the data collected by TOF sensors **2114A** may be used in controlling one or more components of the vehicle exterior inspection system **2100** and/or a vehicle inspection system.

(468) Magnetometers **2115A** may capture magnetic field signals from a vehicle. In some embodiments, the magnetic field signals are used to determine characteristics and/or defects of a vehicle, for example, a vehicle trim, drivetrain, make, model, presence of a catalytic converter, alternator performance, battery type, battery performance, and/or drivetrain performance, among other defects and/or characteristics as described herein. Techniques for analyzing vehicles using magnetometers are discussed in U.S. patent application Ser. No. 18/483,935, entitled: "Machine Learning and Magnetic Field Sensing Techniques for Vehicle Inspection and Condition Analysis," filed Oct. 10, 2023, which is incorporated by reference herein in its entirety.

(469) Air quality sensors **2116A** may record air quality data of the vehicle. In some embodiments, the air quality sensors are VOC sensors. In some examples, data recorded by the air quality sensors **2116A** may be used to determine one or more defects such as fluid leaks, exhaust performance, and/or exhaust leaks.

(470) Microphones **2117A** may be used to record audio data from the undercarriage of a vehicle. The audio data may be used in determining one or more defects and/or characteristics of a vehicle, for example exhaust leaks, engine knocking, engine defects, and/or transmission whine, among other defects and/or characteristics, as described herein.

(471) Vehicle exterior inspection system **2100** additionally includes system components **2120**. In some embodiments, the vehicle exterior inspection system may include greater or fewer components than those included in system components **2120**. In some embodiments, one or more components of system components **2120** may be included in one or more subsystems of a vehicle

exterior inspection system, for example subsystem **2110A** and/or subsystem **2110B**.

(472) As shown, system components **2120** include circuitry **2121**, power supply **2122**, heat management **2123** and inputs **2124**. In some embodiments, the system components may include greater or fewer components than those shown.

(473) Circuitry **2121** may include circuit boards, wiring, and/or other electrical components for interconnecting components of the vehicle exterior inspection system, including components of subsystems **2110A-B** and/or system components **2120**.

(474) Power supply **2122** may provide power to components of the vehicle exterior inspection system **2100**, including components of the subsystems **2110A-B** and system components **2120**. Power supply **2122** may be configured as a battery and/or any suitable power supply.

(475) Heat management components **2123** may function to reduce the temperature of the vehicle exterior inspection system. In some embodiments, the heat management components **2123** may be active and/or passive components. In some embodiments, the heat management components may include fans and/or heat sinks.

(476) Inputs **2124** may allow for signals and/or other inputs to be provided to the vehicle exterior inspection system **2100**. In some embodiments, the inputs **2124** may include one or more electrical ports and/or connectors, buttons, switches, antennas, routers, and/or other components, as described herein.

(477) Subsystems **2110A-B** and system components **2120** may send data to and/or receive data from processors **2130**. For example, data from sensor arrays of the subsystems and components of system components **2120** may be provided to processors **2130**, and processors **2130** may provide control signals to the subsystems **2110A-B** and/or system components **2120**.

(478) FIG. **21B** is a diagram illustrating the components of processor(s) of a vehicle exterior inspection system, according to some embodiments. In FIG. **21B**, vehicle exterior inspection system **2100** includes subsystem(s) **2110**, system components **2120**, and processor(s) **2130**. As described herein, in some embodiments, the processors **2130** may be implemented as a part of the components of the vehicle exterior inspection system **2100**. In some embodiments, the processor(s) **2130** may be implemented separate from the vehicle exterior inspection system **2100**, for example as a device connected to the vehicle exterior inspection system **2100** at the location of the vehicle inspection system and/or in a remote location. In some embodiments, the processors **2130** may be implemented in part separately from and in part as a portion of the vehicle exterior inspection system **2100**.

(479) The processor(s) **2130** include data processing and analysis modules **2131**, alignment verification modules **2132**, PII removal module **2133**, 3D model generation module **2134**, condition report generation module **2135**, user interface generation module **2136**, system control module **2137**, and database **2139** storing machine learning models **2138**.

(480) The data processing and analysis modules **2131** may perform one or more operations on data received from the subsystems **2110**. In some embodiments, the processing and analysis modules **2131** may filter data, structure data and/or preprocess data for additional processing and analysis. In some embodiments, the data processing and analysis modules **2131** may determine one or more vehicle characteristics from the data received from the subsystems **2110**. In some embodiments, the data processing and analysis modules **2131** may use one or more machine learning models, such as ML models **2138** to determine the one or more vehicle characteristics. In some embodiments, the data processing and analysis modules **2131** may determine one or more vehicle defects from the data received from subsystem(s) **2110**. In some embodiments, the data processing and analysis modules may determine the one or more defects using one or more ML models, such as ML models **2138**.

(481) In some embodiments, the data processing and analysis modules **2131** may determine subsets of data for analysis from data received from subsystems **2110**. For example, a subset of images may be determined from images received from the subsystems **2110**. In some examples, a subset of

images may be determined based on the location of the vehicle and/or parts of the vehicle within the images, as described herein.

(482) The alignment verification module **2132** may determine whether the vehicle is properly aligned with the vehicle exterior inspection system for an inspection. In some embodiments, the alignment verification module may determine whether the vehicle is aligned with a vehicle inspection system. In some embodiments, the alignment verification module may analyze data received from one or more sensors of the vehicle undercarriage system, for example cameras and/or TOF sensors. In some embodiments, the alignment verification module determines the alignment of the vehicle using TOF sensors. In some embodiments, the alignment may be determined based on one or more TOF sensors facing a vehicle and comparing a detected position of the vehicle to a desired position. In some embodiments, the alignment verification module **2132** may determine an alignment of the vehicle and provide an indication of the alignment of the vehicle to one or more components of the vehicle exterior inspection system, such as a mobile device or other component with a display. In some embodiments, the alignment of the vehicle may be a binary value, for example, aligned or not aligned. In some embodiments, when the alignment verification module **2132** determines the vehicle is not aligned with the vehicle exterior inspection system, the alignment verification module may provide an indication of an adjustment to be made to the vehicle, for example move vehicle left.

(483) The PII removal module **2133** may remove personally identifiable information from one or more images and/or data received from subsystems **2110**. In some embodiments, PII may include names of individuals, images of individuals and/or other data about individuals which may be captured by sensors of subsystems **2110**. In some embodiments, PII removal module may analyze data received from subsystems **2110** to determine the presence of PII. In some embodiments the PII may be obscured, replaced, eliminated or otherwise removed from the data.

(484) In some embodiments, the 3D model generation module **2134** may generate a 3D model of a vehicle based on data received from the subsystems **2110**. In some embodiments, the 3D model may be generated using one or more ML models, such as ML models **2138**. In some embodiments, the 3D model is generated using photogrammetry. In some embodiments, the 3D model is generated using neural radiance fields. In some embodiments, the 3D model is generated using Gaussian splatting.

(485) The vehicle condition report generation module **2135** may generate a vehicle condition report based on data received the subsystems **2110**. In some embodiments, the vehicle condition report generation module **2135** may generate a vehicle condition report based on one or more characteristics and/or defects of the vehicle determined using the data processing and analysis modules **2131**. In some embodiments, the condition report generation module **2135** may generate a vehicle condition report that includes data related to a vehicle, for example images of the vehicle, and/or audio recordings of the vehicle. In some embodiments, the condition report generation module may include a 3D model of the vehicle in a vehicle condition report. In some embodiments, the condition report generation module may generate a vehicle condition report using data obtained from a user interface of the vehicle exterior inspection system.

(486) User interface generation module **2136** may provide a user interface of the vehicle exterior inspection system on one or more displays connected to the vehicle exterior inspection system. In some embodiments the user interface generation module **2136** may provide a user interface on a mobile device connected to the vehicle exterior inspection system, a computer connected to one or more components of the vehicle exterior inspection system, and/or a device remote from the vehicle exterior inspection system. In some embodiments, the user interface generation module **2136** may generate a user interface which displays information related to a vehicle, for example, alignment data, a 3D model of a vehicle, and/or a vehicle condition report. In some embodiments, the user interface generation module **2136** may provide vehicle data to a user responsive to a request for additional data, for example, the module **2136** may provide additional images of a

region of the vehicle responsive to a request for images of the region.

(487) The system control module **2127** may generate and provide control signals to the components of vehicle exterior inspection system **2100**, including subsystems **2110** and system components **2120**. In some embodiments, the control signals may include signals to trigger the starting and/or stopping of recording data by sensors of the subsystems **2110**. In some embodiment, the control signals may be generated based on data obtained from the sensors of the subsystems, for example data indicative of the position and/or motion of the vehicle. In some embodiments, the system control module **2137** may generate control signals based on inputs received from a user of the vehicle exterior inspection system **2100**.

(488) Databases **2139** store ML models **2138**. In some embodiments, the databases **2139** are implemented as a part of one or more components of the vehicle exterior inspection system **2100**, for example as physical storage. In some embodiments, the databases **2139** are accessible by components of the vehicle inspection system, for example as cloud storage.

(489) ML models **2138** may be used by modules of the vehicle exterior inspection system to analyze data and/or process obtained from the subsystems **2110**. In some embodiments, the ML models **2138** may be used in determining one or more vehicle defects and/or characteristics. Machine learning models for determining vehicle characteristics and/or defects are describe in U.S. Pat. No. 11,631,289, entitled “Vehicle Audio Capture and Diagnostics,” filed Jan. 22, 2020, U.S. Pat. No. 10,893,213, entitled “Vehicle Undercarriage Imaging System,” filed Apr. 2, 2019, U.S. Pat. No. 18,778,247, entitled “Methods and Systems for Identifying Potential Vehicle Defects,” filed Jul. 19, 2024, and U.S. patent application Ser. No. 18/483,935, entitled: “Machine Learning and Magnetic Field Sensing Techniques for Vehicle Inspection and Condition Analysis,” filed Oct. 10, 2023, each of which is incorporated by reference herein in its entirety. In some embodiments, the ML models may be used by the alignment verification modules **2132**, 3D model generation modules **2134**, and/or condition report generation modules **2135**.

(490) FIGS. **22A-E** show example techniques for determining a subset of images captured by a vehicle exterior inspection system for analysis, according to some embodiments.

(491) FIG. **22A** illustrates an example process flow for determining a subset of images for analysis, according to some embodiments. The process flow of FIG. **22A** may determine a subset of images **2216** from vehicle image sets **2211** received from sensor arrays **2210**. Sensor arrays **2210** may be one or more sensor arrays of a vehicle exterior inspection system, as described herein. In some embodiments, sensor arrays **2210** may include camera sets with cameras oriented at different angles, as described herein. In some embodiments, vehicle image sets **2211** may include images captured from different cameras and/or at different angles relative to the vehicle.

(492) The image sets **2211** may be provided to data processing and analysis module **2217**. Data processing and analysis module **2217** may be included in one or more processors of a vehicle exterior inspection system, as described herein. Within data processing and analysis module is vehicle pose determination module **2212**, which may determine a pose of the vehicle within the images of image sets **2211**.

(493) The vehicle pose determination module **2212** may determine the pose of the vehicle using one or more techniques. In some embodiments may determine the pose of the vehicle by segmenting the vehicle out from the images of image sets **2211**. In some examples, the vehicle may be segmented out by determining a bounding box for the vehicle within images and applying a segmentation algorithm to segment out the vehicle from the bounding box. In some embodiments, the bounding box may be determined by a machine learning model which is configured to detect a vehicle within images. For example, in some embodiments, the machine learning model may be a text-prompted object detector, a transformer-based object detector, a neural network configured to identify vehicles within images, among other suitable machine learning models. In some embodiments, the vehicle may be segmented from bounding boxes by creating a mask for the vehicle and segmenting the vehicle out of the image based on the mask. In some embodiments, the

mask may be generated using one or more machine learning models for example a neural network trained to generate object masks and/or a transformer-based model which generates object masks, among other suitable machine learning models. The vehicle pose for an image is the position within the image that the segmented-out vehicle is/was positioned and the orientation of the segmented out vehicle.

(494) In some embodiments, the vehicle pose may be determined based on a position of a bounding box of the vehicle within an image. For example, the center of a bounding box. In some embodiments, a bounding box may be determined by a machine learning model which is configured to detect a vehicle within images. For example, in some embodiments, the machine learning model may be a text-prompted object detector, a transformer-based object detector, a neural network configured to identify vehicles within images, among other suitable machine learning models. In some embodiments, multiple vehicles are present within an image and the largest bounding box is selected as the pose of the vehicle. In some embodiments, multiple vehicles are present within an image and a bounding box is selected based on an optical flow algorithm using data from previously analyzed images.

(495) In some embodiments, the pose of the vehicle may be determined by determining a pose of a particular part of the vehicle within an image, for example a wheel or window of the vehicle. In some embodiments, the pose of a part of a vehicle may be determined using the same techniques used to determine the pose of the vehicle.

(496) Once the pose of the vehicle is determined using pose determination module **2212**, the pose may be determined to one or more poses of a set of vehicle poses **2214**. The vehicle pose set **2214** may include desired poses of the vehicle and/or poses of the vehicle to be used for analysis. In some embodiments, the poses of the pose set **2214** may include poses of the vehicle where specific vehicle parts are visible for analysis. In some embodiments, the poses of the pose set may include one or more poses for particular cameras of a vehicle exterior inspection system. For example, each camera of a vehicle exterior image system may have one or more associated poses in pose set **2214**. Poses associated with particular cameras may reflect the pose of the vehicle when the vehicle is at a particular position with respect to that camera.

(497) In some embodiments, poses of pose set **2214** may be determined based on images of a vehicle. For example, by generating masks representing the location of the vehicle within the images of the vehicle, determining an average orientation of the vehicle from the masks and using the average orientation as the vehicle pose.

(498) FIG. **22B** illustrates an example process for determining a desired vehicle pose, according to some embodiments. In FIG. **22B**, a vehicle image set **2221** is obtained including multiple images of a vehicle type. As shown, the same model of vehicle is included in all images of the image set **2221**. In addition, the images of set **2221** are taken from about the same angle, such that the images include a view of the vehicle from the front driver's side of the vehicle. Image masks **2222** may be determined using the images of image set **2221**. Image masks **2222** may be determined, as described herein, and the images may be modified such that the image mask is shown as white, and the remainder of the image is shown as black. After image masks **2222** are determined, an average vehicle orientation **2223** may be determined by averaging the image masks. The average vehicle orientation **2223** may be used as a desired vehicle pose of a set of vehicle poses, such as **2214**. The process of FIG. **22B** may be used to determine one or more poses of a set of vehicle poses.

(499) Returning to FIG. **22A**, in some embodiments, poses of the set of poses **2214** may correspond to locations of the vehicle and/or a vehicle part within an image.

(500) The poses determined by vehicle pose determination module **2212** may then be compared to the vehicle poses of vehicle pose set **2214** at **2213**. In some embodiments the pose of an image may be determined by determining a matching level such as an Intersection over Union (IoU) matching level, or a distance between the poses. If the vehicle pose of an image of the image sets **2211** is within a threshold level of matching to a vehicle pose of the vehicle pose set **2214**, the associated

image may be included in subset of images **2216**. If the vehicle pose of an image of the image sets **2211** is not within a threshold level of matching to a vehicle pose of the vehicle pose set **2214**, the associate image may not be used for analysis, shown by block **2215**. In some embodiments, only the image having a vehicle having the highest level of matching to a particular pose of pose set **2214** is included in the subset of images **2216**. In some embodiments, multiple images having a level of matching greater than a threshold are included in the subset of images **2216**.

(501) FIG. **22C** shows an example of determining a level of matching between a pose of a vehicle and a desired pose, according to some embodiments. As shown, the pose of the vehicle in image **2231** is compared to desired pose **2230**. In some embodiments, pose **2230** may be generated as described herein and included in a set of poses. As shown in plot **2232**, IoU matching has been determined for multiple frames of a video, which correspond to images of a set of images. In some embodiments, the frames may all be captured by the same camera of a vehicle exterior inspection system. As shown frame **16** has the highest IoU matching and corresponds to image **2231**. Image **2231** may therefore be included in a subset of images for analysis, as described herein.

(502) Returning to FIG. **22A**, in some embodiments, the pose of the set of poses **2214** may be compared to the poses determined for the images of the sets of images by determining a distance between the poses. In some embodiments the Euclidean distance between poses may be determined and/or any other suitable distance.

(503) FIG. **22D** illustrates an example of determining the distance between poses, according to some embodiments. In FIG. **22D**, the desired pose is the center of the image **2240**, which may correspond to the center of the FOV of the camera used to obtain the image. The pose of the vehicle within the image is the center of the bounding box **2242** surrounding vehicle **2241**. The bounding box **2242** may be determined as described herein. Line **2243** represents the Euclidean distance between the desired pose and the center of bounding box **2242**. In some embodiments, an image may be selected for inclusion in a subset for analysis when the distance **2243** is below a threshold. In some embodiments, the image with the smallest distance **2243** is selected for inclusion in an image subset.

(504) In some embodiments, positions other than the center of the image may be used as a desired pose. For example, for lateral images of a vehicle (images taken of a vehicle between a corner of the vehicle and parallel to a side of the vehicle), a distance may be determined between the bounding box of a vehicle and the edge of a FOV of the camera associated with the image. In some embodiments, an image may be selected for inclusion in a subset for analysis when the distance between the bounding box and the edge of the FOV is below a threshold. In some embodiments, the image with the smallest distance between the bounding box and the edge of the FOV is selected for inclusion in an image subset. Different vehicle poses may be selected for lateral frames to give the appearance that the camera is rotating around the car due to the distortion caused by the lens.

(505) In some embodiments, the position of a part of a vehicle may be used as the pose of the vehicle and compared to a desired pose in a set of posed. As shown in FIG. **22E** a bounding box of a wheel of the vehicle is used as the pose of the vehicle and this is compared to a desired pose at the center of the frame of the image. In the left frame **2251**, bounding box **2253** surrounds the front driver's side wheel of the vehicle. Distance **2252** is determined between the desired pose at the center of the image. In some embodiments, an image may be selected for inclusion in a subset for analysis when the distance **2252** is below a threshold. In some embodiments, the image with the smallest distance **2252** is selected for inclusion in an image subset.

(506) Determining vehicle poses based on vehicle parts may be difficult to perform due to the presence of multiple of the same vehicle part within images. For example, in image **2251**, two wheel bounding boxes are shown, **2253** and **2254**. Therefore, in some embodiments, bounding boxes may need to be determined for use as the vehicle pose. In some embodiments, the bounding boxes may be determined based on the size of the boxes, proximity of the boxes to the desired pose, and/or whether a complete vehicle part is contained within the box, for use as the vehicle

pose.

(507) Image **2255** is a second image of the vehicle taken after image **2251** as the vehicle moves past a vehicle exterior inspection system. Image **2255** includes bounding boxes **2256** and **2257** of the front wheels of the vehicle, and bounding box **2259** of the rear driver's side wheel of the vehicle. As shown bounding box **2259** is used as the pose of the vehicle and may be determined as described herein. distance **2258** represents the distance between the bounding box **2259** and the desired pose of the vehicle at the center of the image. In some embodiments, an image may be selected for inclusion in a subset for analysis when the distance **2258** is below a threshold. In some embodiments, the image with the smallest distance **2258** is selected for inclusion in an image subset.

(508) In some embodiments, images of the front and rear driver's side wheels may be desired. Therefore, multiple images must be selected for inclusion in a subset of images, at least some of which include a view of the front wheel and at least some of which include a view of the rear wheel. In some embodiments, this may be accomplished by using "peak" detection algorithm to find the two predominant peaks in the Euclidean distance measure of images of the driver's side of the vehicle. These peaks correspond to the two detected front and rear wheels of the car, and the associated images may be included in a subset, as described herein.

(509) In some embodiments, the process of FIG. **22A** may be performed in real time or near real time, as images of vehicles are captured. This produces a subset of images corresponding to the desired views of the vehicle as an inspection is occurring. In some embodiments, the process of FIG. **22A** may be performed after a vehicle inspection has been performed. In some embodiments, images in a subset of images, such as **2216**, may be analyzed and/or processed as described herein. In some embodiments, images in a subset of images, such as **2216**, may be included in a vehicle condition report, as described herein.

(510) FIG. **23A** illustrates one or more trained machine learning models **2300** for processing images of the exterior of a vehicle to evaluate the vehicle condition, according to some embodiments. As shown in FIG. **23A**, trained machine learning model **2300** includes trained machine learning model **2303** for processing the vehicle images sets **2301** to obtain outputs **2305**.

(511) In some embodiments, the image sets **2301** may be captured as a part of a vehicle inspection, performed using a vehicle exterior inspection system. For example, as described with reference to FIGS. **17A-20**. In some embodiments, the images **2301** may include the views of the vehicle described with reference to FIG. **4A**. In some embodiments, the image sets may be one or more subsets of images, as described herein, for example with reference to FIG. **22A-E**.

(512) In some embodiments, the images **2302** of the vehicle may be a series of images acquired of different views of the vehicle or may be a single image constructed from processing a series of images as described herein. In some embodiments, the images **2302** may be collected from a vehicle exterior inspection system, as described herein. In some embodiments, the images **2302** may be collected from a vehicle inspection system, as described herein. The images **2302** may include multiple color channels and may be formatted in any suitable image format. For example, the image may be a Joint Photographic Expert Group (JPEG) image or a Portable Network Graphics (PNG) image, where each pixel has a corresponding value indicating the red, blue, and green color components.

(513) In some embodiments, trained machine learning model **2303** for processing the images of the vehicle may include preprocessing to generate input images for trained machine learning model **2304**. Preprocessing to generate input images may modify at least one characteristic of the images of the vehicle, prior to the image being processed by the trained machine learning model **2304**.

(514) Trained machine learning model **2304** may be any suitable machine learning model for image analysis. In some embodiments, trained machine learning model **2304** is a 2D convolutional neural network. In some embodiments, ML model **2304** is structured as a deep convolutional neural network (DCNN). In some embodiments, ML model **2304** is structured as a YOLO architecture

neural network. In some embodiments, ML model **2304** is a transformer-based model. In some embodiments, ML model **2304** is a diffusion model. In some embodiments the machine learning model **2304** is configured as an EfficientNet convolutional neural network.

(515) Outputs **2305** may include a list of vehicle defects and the respective likelihood of the defect being present in the vehicle. As shown in FIG. **23A** outputs **2305** include the likelihood of a first vehicle defect **2306**, the likelihood of a vehicle image defect **2307**, and a likelihood of an nth vehicle defect **2308**. For example, when n=8 there may be 8 output classes (e.g., types of vehicle defects) including 7 defect classes and one affirmative quality class. In some embodiments, the outputs **2305** include likelihood of particular vehicle characteristics being present. Examples of vehicle characteristics and defects are described herein. In some embodiments, the outputs include likelihoods of image defects, for example incorrect cropping, insufficient detail, dirty lens, haze or glare, incorrect trim, and/or poor lighting, among other image defects.

(516) FIG. **23B** illustrates one or more trained machine learning models **2310** for processing images and data from the exterior of a vehicle to evaluate the vehicle condition, according to some embodiments. As shown in FIG. **23B**, trained machine learning model **2310** includes trained machine learning model **2314** for processing the vehicle data **2311** to obtain outputs **2316**.

(517) In some embodiments, the data **2311** may be captured as a part of a vehicle inspection, performed using a vehicle exterior inspection system. For example, as described with reference to FIGS. **17A-20**. In some embodiments, the images **2312** of the data **2311** may include the views of the vehicle described with reference to FIG. **4A**.

(518) In some embodiments, the vehicle data may include images **2312** of and sensor data **2313** about a vehicle. In some embodiments, the images **2312** of the vehicle may be a series of images acquired of different views of the exterior of the vehicle. In some embodiments, the images **2312** may be formatted as described with reference to images **2302** of FIG. **23A**. In some embodiments, the images **2312** may be a subset of images determined as described with reference to FIGS. **22A-E**.

(519) In some embodiments, the sensor data **2313** may include data collected by one or more sensors of a vehicle exterior inspection system, as described herein. For example, the sensor data **2313** may include data collected by a microphone, an infrared camera, a thermal camera, a magnetometer, a time of flight sensor, and/or an air quality sensor.

(520) In some embodiments, trained machine learning model **2314** for processing the vehicle data may include preprocessing to generate input data for trained machine learning model **2315**. Preprocessing to generate input data may modify at least one characteristic of the vehicle data, prior to the data being processed by the trained machine learning model **2315**.

(521) In some embodiments, the trained machine learning models **2314** may process vehicle images **2312** and sensor data **2313** separately. In some embodiments, the trained machine learning models **2314** may process vehicle images **2312** and sensor data **2313** together. In some embodiments, the trained machine learning models **2314** may process vehicle images **2312** and sensor data **2313** together in part and separately in part.

(522) Trained machine learning model **2315** may be any suitable machine learning model for image and/or sensor data analysis. In some embodiments, trained machine learning model **2315** is a 2D convolutional neural network. In some embodiments, ML model **2315** is structured as a deep convolutional neural network (DCNN). In some embodiments, ML model **2315** is structured as a YOLO architecture neural network. In some embodiments, ML model **2315** is a transformer-based model. In some embodiments, ML model **2315** is a diffusion model. In some embodiments the machine learning model **2315** is configured as an EfficientNet convolutional neural network.

(523) Outputs **2316** may include a list of vehicle defects and the respective likelihood of the defect being present in the vehicle. As shown in FIG. **23B** outputs **2316** include the likelihood of a first vehicle defect **2317**, the likelihood of a vehicle image defect **2318**, and a likelihood of an nth vehicle defect **2319**. For example, when n=8 there may be 8 output classes (e.g., types of vehicle

defects) including 7 defect classes and one affirmative quality class. In some embodiments, the outputs **2316** include likelihood of particular vehicle characteristics being present. Examples of vehicle characteristics and defects are described herein. In some embodiments, the outputs include likelihoods of image and/or data defects, for example incorrect cropping, insufficient detail, dirty lens, haze or glare, incorrect trim, insufficient magnitude, too noisy, and/or poor lighting, among other defects.

(524) FIG. **23C** illustrates one or more trained machine learning models **2320** for processing sensor data about an exterior of a vehicle to evaluate the vehicle condition, according to some embodiments. As shown in FIG. **23C**, trained machine learning model **2320** includes trained machine learning model **2323** for processing the vehicle data **2321** to obtain outputs **2325**.

(525) In some embodiments, the data **2321** may be captured as a part of a vehicle inspection, performed using a vehicle exterior inspection system. For example, as described with reference to FIGS. **17A-20**.

(526) In some embodiments, the vehicle data may sensor data **2322** about a vehicle. In some embodiments, the sensor data **2322** may include data collected by one or more sensors of a vehicle exterior inspection system, as described herein. For example, the sensor data **2322** may include data collected by a microphone, an infrared camera, a thermal camera, a magnetometer, a time of flight sensor, and/or an air quality sensor.

(527) In some embodiments, trained machine learning model **2323** for processing the vehicle data may include preprocessing to generate input data for trained machine learning model **2324**. Preprocessing to generate input data may modify at least one characteristic of the vehicle data, prior to the data being processed by the trained machine learning model **2324**.

(528) In some embodiments, the trained machine learning models **2323** may process vehicle sensor data from different vehicle sensors separately. In some embodiments, the trained machine learning models **2323** may process the sensor data from different vehicle sensors together. In some embodiments, the trained machine learning models **2323** may process sensor data from different sensors together in part and separately in part.

(529) Trained machine learning model **2324** may be any suitable machine learning model for sensor data analysis. In some embodiments, trained machine learning model **2324** is a 2D convolutional neural network. In some embodiments, ML model **2324** is structured as a deep convolutional neural network (DCNN). In some embodiments, ML model **2324** is a transformer-based model.

(530) Outputs **2325** may include a list of vehicle defects and the respective likelihood of the defect being present in the vehicle. As shown in FIG. **23D** outputs **2325** include the likelihood of a first vehicle defect **2326**, the likelihood of a vehicle image defect **2327**, and a likelihood of an nth vehicle defect **2328**. For example, when n=8 there may be 8 output classes (e.g., types of vehicle defects) including 7 defect classes and one affirmative quality class. In some embodiments, the outputs **2325** include likelihood of particular vehicle characteristics being present. Examples of vehicle characteristics and defects are described herein. In some embodiments, the outputs **2325** include likelihoods data defects, for example incorrect cropping, insufficient detail, incorrect trim, insufficient magnitude, and/or too noisy, among other defects.

(531) FIG. **23D** shows example inputs and performance of a wheel and tire machine learning model, according to some embodiments. In some embodiments, the wheel and tire machine learning model may be a machine learning model configured to analyze images of wheels and tires of a vehicle, captured by a vehicle exterior inspection system. In some embodiments, the wheel and tire machine learning model may be configured as described with reference to FIG. **23A**. In some embodiments, the wheel and tire machine learning model may be configured as one or more machine learning models.

(532) As shown the wheel and tire machine learning model is configured to determine multiple defects associated with the wheels and/or tires of a vehicle. The defects include uneven tread wear,

damaged wheels, oversized tires, mismatched tires, rotted and cracked tires, and aftermarket wheels. The ROC curves for these defects are shown in FIG. 23D. As shown the ROC scores for the defects are 0.76 for uneven tread wear, 0.84 for damaged wheels, 0.94 for oversized tires, 0.78 for mismatched tires, 0.76 for rotted and cracked tires, and 0.95 for aftermarket wheels, indicating the model performs well at discriminating defective vehicles from non-defective vehicles.

(533) FIG. 23E shows example inputs and performance of a tire depth machine learning model, according to some embodiments. In some embodiments, the tire depth machine learning model may be a machine learning model configured to analyze images of wheels and tires of a vehicle, captured by a vehicle exterior inspection system. In some embodiments, the tire depth machine learning model may be configured as described with reference to FIG. 23A. In some embodiments, the tire depth machine learning model may be configured as one or more machine learning models.

(534) As shown the tire depth machine learning model is configured to determine whether the tread depth of the tires of a vehicle is an acceptable depth. In some embodiments, an acceptable depth may be greater than 1/10", greater than 1/8", greater than 1/6", greater than 1/4" and/or greater than 1/3". The ROC curve for the tread depth machine learning model is shown in FIG. 23E. As shown the ROC score for the tread depth machine learning model is 0.87, indicating the model performs well at discriminating vehicles having unacceptable tread depths.

(535) In some embodiments, additional ML models may be provided for analysis of wheel and tires of vehicles. For example, a ML model may be configured to predict whether the vehicle has proper wheel alignment based on images of the sides of wheels, for example by predicting a camber angle for the wheel and comparing the camber angle to an acceptable range of camber angles.

(536) FIG. 24A illustrates an image of a vehicle with defect tags, according to some embodiments. FIG. 24A includes image 2400 showing the driver's side of a vehicle. Image 2400 may be captured by a vehicle exterior imaging system, as described herein. The tags on image 2400 may be applied by one or more machine learning models, such as those described herein with reference to FIGS. 23A-E. In some embodiments, image 2400 may be included in a vehicle condition report, as described herein. In some embodiments, image 2400 may be provided on a user interface, as described herein.

(537) Image 2400 includes tags indicating the location of different defects on the vehicle 2401. Tag 2410 indicates the presence of a scratch on the bumper and includes an outline and label. Tag 2411 indicates a body crack near the driver's side window and includes a label. Tag 2412 indicates the presence of rust at the bottom corner of the cabin and includes an outline and a label. Tag 2413 indicates a dent on the rear portion of the vehicle and includes an outline and a label. Tag 2414 indicates a dent on the rear portion of the vehicle and includes an outline and a label. Tag 2415 indicates a scratch rear wheel well of the vehicle and includes an outline and a label. Tag 2416 indicates a dent on the rear portion of the vehicle and includes an outline and a label. Tag 2417 indicates a scratch on the rear portion of the vehicle and includes an outline and a label. Tag 2418 indicates rust on the rear portion of the vehicle and includes an outline and a label. Tag 2419 indicates rust on the rear portion of the vehicle and includes an outline and a label.

(538) The tags on image 2400 may be selectable by a user to obtain additional information related to the defects of the vehicle, for example on a user interface. In some embodiments, the user may select a defect to review the defect and may update the tag to provide additional information, add a comment, change the tag, delete the tag, or perform another action related to the tag.

(539) FIG. 24B is an example of is an example of additional information which may be provided in response to a user selecting a tag, according to some embodiments. As shown, image 2420 of vehicle 2421, has tag 2422 indicating a dent. The tag may be generated and/or applied as described herein.

(540) A user may select tag 2422 to obtain additional information related to the dent. As shown, the additional information provide is images 2423 of the dent from different angles. The images may be captured from different cameras of a vehicle exterior inspection system such as cameras oriented

at different angles, as described herein.

(541) In some embodiments, a user may select any portion of image **2420** to obtain additional information about that portion of the image, such as additional images of a portion of the vehicle.

(542) FIG. **25** is an example process for removing personally identifiable information (PII) from an image, according to some embodiments. Process **2500** is for removing the PII from image **2510**. Image **2510** may be captured from a camera of a vehicle exterior inspection system, as described herein. The process of FIG. **25** may be performed by a PII removal module of a vehicle exterior inspection system, as described herein.

(543) The process **2500** begins by identifying the PII present in image **2510**. In image PII is present within circles **2511**, which includes the head of a driver, and **2512**, which includes the hands of the driver. The PII may be identified by generating a mask **2520** indicative of the location(s) of the PII within the image. The mask **2520** may be generated using one or more machine learning models for example a neural network trained to generate object masks and/or a transformer-based model which generates object masks, among other suitable machine learning models. The mask may then be dilated to increase its size, shown as dilated mask **2521**. The dilation ensures that all identified PII and any surrounding PII not included in mask **2520** is within the dilated mask **2521**.

(544) The PII may then be removed from image **2510** through an inpainting process, to generate inpainted image **2530**. In the inpainted image the PII is removed, as shown in circles **2531** and **2532**, where there is no longer a driver or evidence of the driver. In some embodiments, a machine learning-based inpainting model may be used to generate inpainted image **2530**, for example a transformer-based ML model, a large mask inpainting model, and/or a diffusion model (e.g., Stable Diffusion Inpainting, Stable Diffusion (SDXL) Inpainting, Kandinsky Inpainting, etc.), among other suitable ML models. In some embodiments, the PII may be removed through other processes, such as blurring areas identified as having PII, or covering areas identified as having PII.

(545) In some embodiments, inpainted image **2530** may be presented on a user interface of a vehicle exterior inspection system, as described herein. In some embodiments, inpainted image **2530** may be included in a vehicle condition report, as described herein.

(546) FIG. **26** is an example process for generating a 3D model of a vehicle, according to some embodiments. In FIG. **26**, vehicle image sets **2610** are processed to generate 3D model **2630**. Image sets **2610** may be captured by cameras of a vehicle exterior inspection system as described herein. In some embodiments, the image sets **2610** may be subsets of images determined from larger image sets, as described herein.

(547) 3D model **2630** may be generated by 3D model generation module **2620**. The 3D model **2630** may be generated by determining a surface of the vehicle and applying images of the image sets **2610** to the surface. In some embodiments, the 3D model **2630** is generated using photogrammetry. In some embodiments, the 3D model **2630** is generated using neural radiance fields. In some embodiments, the 3D model **2630** is generated using Gaussian splatting.

(548) In some embodiments, 3D model **2630** may be presented on a user interface of a vehicle exterior inspection system, as described herein. In some embodiments, 3D model **2630** may be included in a vehicle condition report, as described herein.

(549) FIG. **27** is a flowchart of an illustrative process **2700** for analyzing vehicle condition using a vehicle exterior inspection system, according to some embodiments. In some embodiments, the vehicle exterior inspection system used in performing process **2700** includes a plurality of sensor arrays including first, second and third sensor arrays having respective first, second, and third sets of cameras. In some embodiments, the vehicle exterior inspection system used in performing process **2700** may be configured as described herein, for example as described with reference to FIGS. **17A-12B**. In some embodiments, process **2700** may be performed by one or more processors of a vehicle undercarriage inspection system, for example processors **2130** as described with reference to FIGS. **21A-B**.

(550) Process **2700** begins at step **2701** by obtaining a plurality of images using the vehicle

inspection system, the plurality of images including first, second, and third sets of images captured, respectively, by the first, second, and third sets of cameras. In some embodiments, step **2701** may be performed as the vehicle and vehicle exterior inspection system move relative to each other. In some embodiments the vehicle may drive through and/or past the vehicle exterior inspection system, as described herein. In some embodiments the vehicle exterior inspection system may move around the vehicle, as described herein. In some embodiments, the vehicle may move through and/or past the vehicle exterior inspection system as the vehicle exterior inspection system moves around the vehicle.

(551) Next, step **2702** is performed by identifying a subset of the plurality of images for subsequent processing to identify whether the vehicle has one or more defects, wherein the identifying is performed based on a pose of the vehicle in images of the plurality of images. In some embodiments, the pose of the vehicle is determined based on the position of the vehicle within an image. In some embodiments, the pose of the vehicle is determined based on the position of one or more parts of the vehicle within an image. In some embodiments the pose of the vehicle is determined based on the position of a bounding box of the vehicle and/or a part of the vehicle within an image. In some embodiments, the subset of images is determined by comparing a pose of the vehicle within an image to a set of desired vehicle poses, such as described with reference to FIGS. **22A-E**. In some embodiments, the subset of images may be determined based on one or more other attributes of the images including a level of noise and/or blur in the image, a lighting of the image, a contrast of the image, a focus of the image, and/or other attributes of the image.

(552) Next, step **2703** is performed by processing the subset of the plurality of images, using at least one trained machine learning (ML) model, to determine whether the vehicle has the one or more defects. In some embodiments the one or more defects may include defects as described herein. In some embodiments, step **2703** may be performed by one or more components of a vehicle exterior inspection system, for example data processing and analysis module **2131**, as described in reference to FIG. **21B**. In some embodiments, the at least one trained machine learning may include ML models such as those described herein with reference to **23A-E**.

(553) Next, step **2704** is performed by generating a vehicle condition report based on results of the processing, the vehicle condition report including an indication of the one or more defects in the plurality of images. In some embodiments, step **2704** is performed by a condition report generation module such as **2135**, as described with reference to FIG. **21B**. In some embodiments, the condition report includes data related to the vehicle, for example as described with reference to FIG. **2**. In some embodiments, data of a vehicle condition report may be determined using one or more machine learning models, such as those described herein with reference to **23A-E**. In some embodiments, the vehicle condition report may be displayed and/or otherwise provided for a vehicle inspector for review.

(554) Following the conclusion of process **2700**, the inspector may proceed to conduct a further vehicle inspection. Accordingly, in some embodiments, the inspector may use the vehicle condition report and/or targeted professional inspection instructions to determine particular techniques to use during the further vehicle inspection (e.g., to check for the potential vehicle defects).

(555) Additionally, or alternatively, the inspector may be a potential buyer who may use the vehicle condition report to make more informed pricing offers or to perform an inspection of the vehicle for themselves (e.g., to determine the presence of the potential vehicle defects). Additionally, or alternatively, the inspector may be a potential seller who may use the output to anticipate potential customer complaints. Additionally, or alternatively, the inspector may be the vehicle owner who may use the output to anticipate component failures and repairs.

(556) FIG. **28A** is a flowchart of an illustrative process **2800** for inspecting a vehicle using a vehicle exterior inspection system, according to some embodiments. In some embodiments, the vehicle exterior inspection system used in performing process **2800** includes a support member and a plurality of sensor arrays coupled to the support member, the plurality of sensor arrays having

respective sets of sensors oriented in different directions. In some embodiments, the vehicle exterior inspection system may be configured as described herein, for example as described with reference to FIGS. 17A-21B. Some steps of process **2800** may be performed by an inspector and some steps may be performed by one or more components of the vehicle exterior inspection system.

(557) Process **2800** begins with step **2801** by moving the vehicle and the support member of the vehicle inspection system relative to one another. In some embodiments the vehicle may drive through and/or past the vehicle exterior inspection system, as described herein. In some embodiments the vehicle may be driven by an inspector or by another individual. In some embodiments the vehicle exterior inspection system may move around the vehicle, such as described herein with reference to FIGS. 17C-H. In some embodiments, the vehicle may move through and/or past the vehicle exterior inspection system as the vehicle exterior inspection system moves around the vehicle.

(558) Next, step **2802** is performed by triggering capture of sensor data about the vehicle by the plurality of sensor arrays of the vehicle exterior inspection system. In some embodiments, the triggering is performed automatically by the vehicle exterior inspection system. In some embodiments the triggering is performed automatically based on signals obtained from one or more sensors of and/or connected to the vehicle exterior inspection system, such as TOF sensors, and/or cameras. In some embodiments, the triggering is performed when the vehicle is determined to be at one or more positions relative to the vehicle exterior inspection undercarriage system based on sensor data. In some embodiments different sensors of the vehicle exterior inspection system may be triggered at different times, for example sensors having different orientations may be triggered based on the position of the vehicle. In some embodiments, the triggering is performed in response to one or more inputs received from an inspector, such as through a user interface of the vehicle exterior inspection system or other inputs as described herein.

(559) Next, step **2803** is performed by capturing the sensor data about the vehicle using the plurality of sensor arrays of the vehicle inspection system.

(560) Next, step **2804** is performed by stopping capture of the sensor data about the vehicle. In some embodiments, the stopping is performed automatically by the vehicle exterior inspection system. In some embodiments the stopping is performed automatically based on signals obtained from one or more sensors of the vehicle exterior inspection system, such as TOF sensors, and/or cameras. In some embodiments, the stopping is performed when the vehicle is determined to be at one or more positions relative to the vehicle exterior inspection system based on sensor data. In some embodiments individual sensors may be stopped at different times, for example sensors having different orientations may be stopped based on the position of the vehicle. In some embodiments, the stopping is performed in response to inputs received from an inspector, such as through a user interface of the vehicle exterior inspection system or other inputs as described herein.

(561) Next, step **2805** is performed by stopping movement of the vehicle and the support member relative to one another. In some embodiments, step **2805** is performed by an inspector or other individual by stopping the vehicle. In some embodiments, step **2805** is performed by an inspector by providing an input to the vehicle inspection system to stop moving. In some embodiments, step **2805** is performed automatically by the vehicle exterior inspection system.

(562) Next, step **2806** is performed by providing, to a computer hardware processor, the sensor data collected using the plurality of sensor arrays. In some embodiments, the computer hardware processor is a component of the vehicle exterior inspection system. In some embodiments the computer hardware processor is a processor remote from the vehicle exterior inspection system. In some embodiments, the data may be formatted and/or processed before it is provided to the computer hardware processor. For example, the data may be processed as described with reference to the components of processor **2130**, as discussed with reference to FIG. 21B. In some

embodiments, the data about the vehicle includes a subset of images which may be determined as described with reference to FIGS. 22A-E.

(563) Next, step **2807** is performed by receiving, from the computer hardware processor, a vehicle condition report generated using the sensor data. In some embodiments, the condition report includes data related to the vehicle, for example as described with reference to FIG. 2. In some embodiments the vehicle condition report includes data related to one or more defects of the vehicle and/or one or more characteristics of the vehicle, as described herein. In some embodiments, data of a vehicle condition report may be determined using one or more machine learning models, such as those described herein with reference to 23A-E. In some embodiments, the vehicle condition report may be displayed and/or otherwise provided for a vehicle inspector for review.

(564) Following the conclusion of process **2800**, the inspector may proceed to conduct a further vehicle inspection. Accordingly, in some embodiments, the inspector may use the vehicle condition report and/or targeted professional inspection instructions to determine particular techniques to use during the further vehicle inspection (e.g., to check for the potential vehicle defects).

(565) Additionally, or alternatively, the inspector may be a potential buyer who may use the vehicle condition report to make more informed pricing offers or to perform an inspection of the vehicle for themselves (e.g., to determine the presence of the potential vehicle defects). Additionally, or alternatively, the inspector may be a potential seller who may use the output to anticipate potential customer complaints. Additionally, or alternatively, the inspector may be the vehicle owner who may use the output to anticipate component failures and repairs.

(566) FIG. 28B is a flowchart of an illustrative process **2810** for preparing and using a vehicle exterior inspection system to perform a vehicle inspection, according to some embodiments. In some embodiments, the vehicle exterior inspection system used in performing process **2810** includes a support member and a plurality of sensor arrays coupled to the support member, the plurality of sensor arrays having respective sets of sensors oriented in different directions. In some embodiments, the vehicle exterior inspection system may be configured as described herein, for example as described with reference to FIGS. 17A-21B. Some steps of process **2810** may be performed by an inspector and some steps may be performed by one or more components of the vehicle exterior inspection system.

(567) Process **2810** begins with step **2811** by positioning the vehicle and the support member of the vehicle inspection system relative to one another. In some embodiments, vehicle exterior inspection system may be positioned as described with reference to FIGS. 3A-F, with the support member positioned in front of and facing the side of a vehicle. In some embodiments, the vehicle exterior inspections system may be positioned as described with reference to FIGS. 17A-H. In some embodiments, an inspector may perform step **2811**. In some embodiments step **2811** may be performed automatically by the vehicle exterior inspection system. In some embodiments step **2811** may be performed in part by an inspector and in part by the vehicle exterior inspection system.

(568) Next, step **2812** is performed by triggering the vehicle exterior inspection system to collect alignment data of the vehicle relative to the vehicle inspection system. In some embodiments, the triggering is performed automatically by the vehicle exterior inspection system. In some embodiments the triggering is performed automatically based on signals obtained from one or more sensors of the vehicle exterior inspection system, such as TOF sensors, and/or cameras. In some embodiments, the triggering is performed when the vehicle is determined to be at one or more positions relative to the vehicle exterior inspection system based on sensor data.

(569) In some embodiments, the triggering is performed manually by an inspector by providing one or more inputs to a vehicle exterior inspection system, such as through a user interface or other inputs as described herein.

(570) Next, step **2813** is performed by providing, to a computer hardware processor, the alignment data. In some embodiments, the computer hardware processor is a component of the vehicle

exterior inspection system. In some embodiments the computer hardware processor is a processor remote from the vehicle exterior inspection system. In some embodiments, the data may be formatted and/or processed before it is provided to the computer hardware processor.

(571) Next, step **2814** is performed by receiving, from the computer hardware processor, an indication of an alignment of the vehicle relative to the vehicle inspection system. In some embodiments, the indication of alignment may be provided on a display of a vehicle exterior inspection system, as described in herein.

(572) Next, step **2815** is performed by repositioning the support member relative to the vehicle based on the indication of the alignment. In some embodiments, step **2815** may be performed by an inspector or another individual. In some embodiments step **2815** may be performed automatically by the vehicle exterior inspection system. In some embodiments step **2815** may be performed in part by an inspector or other individual and in part automatically the vehicle exterior inspection system. In some embodiments, the indication of alignment includes a direction for repositioning, and step **2815** may be performed based on the direction for repositioning.

(573) Next, step **2816** is performed by moving the vehicle and the support member of the vehicle inspection system relative to one another. In some embodiments the vehicle may drive through and/or past the vehicle exterior inspection system, as described herein. In some embodiments the vehicle may be driven by an inspector or by another individual. In some embodiments the vehicle exterior inspection system may move around the vehicle, such as described herein with reference to FIGS. 17C-H. In some embodiments, the vehicle may move through and/or past the vehicle exterior inspection system as the vehicle exterior inspection system moves around the vehicle.

(574) Next, step **2817** is performed by capturing sensor data about the vehicle using the plurality of sensor arrays of the vehicle inspection system.

(575) Next, step **2818** is performed by providing, to the computer hardware processor, the sensor data collected using the plurality of sensor arrays. In some embodiments, the computer hardware processor is a component of the vehicle exterior inspection system. In some embodiments the computer hardware processor is a processor remote from the vehicle exterior inspection system. In some embodiments, the data may be formatted and/or processed before it is provided to the computer hardware processor. For example, the data may be processed as described with reference to the components of processor **2130**, as discussed with reference to FIG. 21B. In some embodiments, the data about the vehicle includes a subset of data, such as images, which may be determined as described with reference to FIGS. 22A-E.

(576) Next, step **2819** is performed by receiving, from the computer hardware processor, a vehicle condition report. In some embodiments, the condition report includes data related to the vehicle, for example as described with reference to FIG. 2. In some embodiments the vehicle condition report includes data related to one or more defects of the vehicle and/or one or more characteristics of the vehicle, as described herein. In some embodiments, data of a vehicle condition report may be determined using one or more machine learning models, such as those described herein with reference to 23A-E. In some embodiments, the vehicle condition report may be displayed and/or otherwise provided for a vehicle inspector for review.

(577) Following the conclusion of process **2810**, the inspector may proceed to conduct a further vehicle inspection. Accordingly, in some embodiments, the inspector may use the vehicle condition report and/or targeted professional inspection instructions to determine particular techniques to use during the further vehicle inspection (e.g., to check for the potential vehicle defects).

(578) Additionally, or alternatively, the inspector may be a potential buyer who may use the vehicle condition report to make more informed pricing offers or to perform an inspection of the vehicle for themselves (e.g., to determine the presence of the potential vehicle defects). Additionally, or alternatively, the inspector may be a potential seller who may use the output to anticipate potential customer complaints. Additionally, or alternatively, the inspector may be the vehicle owner who may use the output to anticipate component failures and repairs.

(579) FIG. 28C is a flowchart of an illustrative process **2820** for using a vehicle exterior inspection system to analyze vehicle conditions, according to some embodiments. In some embodiments, the vehicle exterior inspection system used in performing process **2820** includes a support member and a plurality of sensor arrays coupled to the support member, the plurality of sensor arrays having respective sets of sensors oriented in different directions. In some embodiments, the vehicle exterior inspection system may be configured as described herein, for example as described with reference to FIGS. 17A-21B. Some steps of process **2820** may be performed by an inspector and some steps may be performed by one or more components of the vehicle exterior inspection system.

(580) Process **2820** begins with step **2821** by moving the vehicle and the support member of the vehicle inspection system relative to one another. In some embodiments the vehicle may drive through and/or past the vehicle exterior inspection system, as described herein. In some embodiments the vehicle may be driven by an inspector or by another individual. In some embodiments the vehicle exterior inspection system may move around the vehicle, such as described herein with reference to FIGS. 17C-H. In some embodiments, the vehicle may move through and/or past the vehicle exterior inspection system as the vehicle exterior inspection system moves around the vehicle.

(581) Next, step **2822** is performed by capturing sensor data about the vehicle using the plurality of sensor arrays of the vehicle exterior inspection system.

(582) Next, step **2823** is performed by stopping movement of the vehicle and the support member relative to one another. In some embodiments, step **2823** is performed by an inspector or other individual by stopping the vehicle. In some embodiments, step **2823** is performed by an inspector by providing an input to the vehicle inspection system to stop moving. In some embodiments, step **2823** is performed automatically by the vehicle exterior inspection system.

(583) Next, step **2824** is performed by providing, to a computer hardware processor, the sensor data collected using the plurality of sensor arrays. In some embodiments, the computer hardware processor is a component of the vehicle exterior inspection system. In some embodiments the computer hardware processor is a processor remote from the vehicle exterior inspection system. In some embodiments, the data may be formatted and/or processed before it is provided to the computer hardware processor. For example, the data may be processed as described with reference to the components of processor **2130**, as discussed with reference to FIG. 21B. In some embodiments, the data about the vehicle includes a subset of data, such as images, which may be determined as described with reference to FIGS. 22A-E.

(584) Next, step **2825** is performed by receiving, from the computer hardware processor, a vehicle condition report indicating one or more defects present on the vehicle. In some embodiments, the condition report includes data related to the vehicle, for example as described with reference to FIG. 2. In some embodiments the vehicle condition report includes data related to one or more defects of the vehicle and/or one or more characteristics of the vehicle, as described herein. In some embodiments, data of a vehicle condition report may be determined using one or more machine learning models, such as those described herein with reference to 23A-E. In some embodiments, the vehicle condition report may be displayed and/or otherwise provided for a vehicle inspector for review.

(585) Next, step **2826** is performed by providing, to the computer hardware processor, a request for sensor data related to the one or more defects present on the vehicle. In some embodiments, step **2826** may be performed by an inspector, such as by providing one or more inputs to the vehicle exterior inspection system, such as through a user interface of the vehicle exterior inspection system, as described herein. In some embodiments, the vehicle condition report may include one or more selectable inputs related to the defects. In some embodiments, the request may be provided by selecting a region of an image, such as described with reference to FIGS. 24A-B.

(586) Next, step **2827** is performed by receiving, from the computer hardware processor, a plurality

of sensor data related to the one or more defects present on the vehicle. In some embodiments, the plurality of sensor data includes the sensor data used in determining the one or more defects are present. In some embodiments, the plurality of sensor data is provided in one or more visual displays, such as charts, plots, images and/or other visual displays. In some embodiments the plurality of sensor data includes a plurality of images of the defect, such as described with reference to FIG. 24B. In some embodiments, the plurality of sensor data may be displayed and/or otherwise provided for a vehicle inspector for review.

(587) Following the conclusion of process **2820**, the inspector may proceed to conduct a further vehicle inspection. Accordingly, in some embodiments, the inspector may use the sensor data related to the one or more defects and/or targeted professional inspection instructions to determine particular techniques to use during the further vehicle inspection (e.g., to check for the potential vehicle defects).

(588) Additionally, or alternatively, the inspector may be a potential buyer who may use sensor data related to the one or more defects to make more informed pricing offers or to perform an inspection of the vehicle for themselves (e.g., to determine the presence of the potential vehicle defects). Additionally, or alternatively, the inspector may be a potential seller who may use the output to anticipate potential customer complaints. Additionally, or alternatively, the inspector may be the vehicle owner who may use the output to anticipate component failures and repairs.

(589) FIG. 29 illustrates a block diagram of an illustrative computing system that may be used in implementing some embodiments of the technology described herein. An illustrative implementation of a computer system **2900** that may be used in connection with any of the embodiments of the disclosure provided herein is shown in FIG. 29. For example, any of the computing devices described herein (e.g., **116, 120, 145, 154, 164, 173, 182, 930, 2130**) may be implemented as computer system **2900**. The computer system **2900** may include one or more computer hardware processors **2904** and one or more articles of manufacture that comprise non-transitory computer-readable storage media, for example, one or more volatile storage device **2906** (e.g., random access memory or any other suitable type of memory) and/or one or more non-volatile storage devices **2902** (e.g., a hard disk, a flash memory, etc.). The hardware processor **2902** (s) may control writing data to and reading data from the volatile storage device(s) **2906** and the non-volatile storage device(s) **2902** in any suitable manner. To perform any of the functionality described herein, including with respect to any process described herein, the hardware processor(s) **2904** may execute one or more processor-executable instructions stored in one or more non-transitory computer-readable storage media (e.g., the volatile storage device(s) **2906** and/or non-volatile storage device(s) **2902**), which may serve as non-transitory computer-readable storage media storing processor-executable instructions for execution by the hardware processor(s) **2904**.

(590) Having thus described several aspects of at least one embodiment of the technology described herein, it is to be appreciated that various alterations, modifications, and improvements will readily occur to those skilled in the art.

(591) Such alterations, modifications, and improvements are intended to be part of this disclosure, and are intended to be within the spirit and scope of disclosure. Further, though advantages of the technology described herein are indicated, not every embodiment of the technology described herein will include every described advantage. Some embodiments may not implement any features described as advantageous herein and in some instances one or more of the described features may be implemented to achieve further embodiments. Accordingly, the foregoing description and drawings are by way of example only.

(592) The above-described embodiments of the technology described herein may be implemented in any of numerous ways. For example, the embodiments may be implemented using hardware, software, or a combination thereof. When implemented in software, the software code may be executed on any suitable processor or collection of processors, whether provided in a single computer or distributed among multiple computers. Such processors may be implemented as

integrated circuits, with one or more processors in an integrated circuit component, including commercially available integrated circuit components known in the art by names such as CPU chips, GPU chips, microprocessor, microcontroller, or co-processor. Alternatively, a processor may be implemented in custom circuitry, such as an ASIC, or semicustom circuitry resulting from configuring a programmable logic device. As yet a further alternative, a processor may be a portion of a larger circuit or semiconductor device, whether commercially available, semi-custom or custom. As a specific example, some commercially available microprocessors have multiple cores such that one or a subset of those cores may constitute a processor. However, a processor may be implemented using circuitry in any suitable format.

(593) Further, a computer may be embodied in any of a number of forms, such as a rack-mounted computer, a desktop computer, a laptop computer, or a tablet computer. Additionally, a computer may be embedded in a device not generally regarded as a computer but with suitable processing capabilities, including a Personal Digital Assistant (PDA), a smart phone, tablet, or any other suitable portable or fixed electronic device.

(594) Also, a computer may have one or more input and output devices. These devices may be used, among other things, to present a user interface. Examples of output devices that may be used to provide a user interface include printers or display screens for visual presentation of output and speakers or other sound generating devices for audible presentation of output. Examples of input devices that may be used for a user interface include keyboards, and pointing devices, such as mice, touch pads, and digitizing tablets. As another example, a computer may receive input information through speech recognition or in other audible format.

(595) Such computers may be interconnected by one or more networks in any suitable form, including as a local area network or a wide area network, such as an enterprise network or the Internet. Such networks may be based on any suitable technology and may operate according to any suitable protocol and may include wireless networks, wired networks, fiber optic networks, or any suitable combination thereof.

(596) Also, the various methods or processes outlined herein may be coded as software that is executable on one or more processors that employ any one of a variety of operating systems or platforms. Additionally, such software may be written using any of a number of suitable programming languages and/or programming or scripting tools, and also may be compiled as executable machine language code or intermediate code that is executed on a framework or virtual machine.

(597) In this respect, aspects of the technology described herein may be embodied as a computer readable storage medium (or multiple computer readable media) (e.g., a computer memory, one or more floppy discs, compact discs (CD), optical discs, digital video disks (DVD), magnetic tapes, flash memories, circuit configurations in Field Programmable Gate Arrays or other semiconductor devices, or other tangible computer storage medium) encoded with one or more programs that, when executed on one or more computers or other processors, perform methods that implement the various embodiments described above. As is apparent from the foregoing examples, a computer readable storage medium may retain information for a sufficient time to provide computer-executable instructions in a non-transitory form. Such a computer readable storage medium or media may be transportable, such that the program or programs stored thereon may be loaded onto one or more different computers or other processors to implement various aspects of the technology as described above. As used herein, the term “computer-readable storage medium” encompasses only a non-transitory computer readable medium that may be considered to be a manufacture (i.e., article of manufacture) or a machine. Alternatively or additionally, aspects of the technology described herein may be embodied as a computer readable medium other than a computer-readable storage medium, such as a propagating signal.

(598) The terms “program” or “software” are used herein in a generic sense to refer to any type of computer code or set of processor-executable instructions that may be employed to program a

computer or other processor to implement various aspects of the technology as described above. Additionally, one or more computer programs that when executed perform methods of the technology described herein need not reside on a single computer or processor, but may be distributed in a modular fashion amongst a number of different computers or processors to implement various aspects of the technology described herein.

(599) Processor-executable instructions may be in many forms, such as program modules, executed by one or more computers or other devices. Generally, program modules include routines, programs, objects, components, data structures, etc. that perform particular tasks or implement particular abstract data types. Typically, the functionality of the program modules may be combined or distributed.

(600) Also, data structures may be stored in one or more non-transitory computer-readable storage media in any suitable form. For simplicity of illustration, data structures may be shown to have fields that are related through location in the data structure. Such relationships may likewise be achieved by assigning storage for the fields with locations in a non-transitory computer-readable medium that convey relationship between the fields. However, any suitable mechanism may be used to establish relationships among information in fields of a data structure, including through the use of pointers, tags or other mechanisms that establish relationships among data elements.

(601) Various aspects of the technology described herein may be used alone, in combination, or in a variety of arrangements not specifically described in the embodiments described in the foregoing and is therefore not limited in its application to the details and arrangement of components set forth in the foregoing description or illustrated in the drawings. For example, aspects described in one embodiment may be combined in any manner with aspects described in other embodiments.

(602) Also, the technology described herein may be embodied as a method, of which examples are provided herein. The acts performed as part of any of the methods may be ordered in any suitable way. Accordingly, embodiments may be constructed in which acts are performed in an order different than illustrated, which may include performing some acts simultaneously, even though shown as sequential acts in illustrative embodiments.

(603) As used herein in the specification and in the claims, the phrase “at least one,” in reference to a list of one or more elements, should be understood to mean at least one element selected from any one or more of the elements in the list of elements, but not necessarily including at least one of each and every element specifically listed within the list of elements and not excluding any combinations of elements in the list of elements. This definition also allows that elements may optionally be present other than the elements specifically identified within the list of elements to which the phrase “at least one” refers, whether related or unrelated to those elements specifically identified. Thus, for example, “at least one of A and B” (or, equivalently, “at least one of A or B,” or, equivalently “at least one of A and/or B”) can refer, in one embodiment, to at least one, optionally including more than one, A, with no B present (and optionally including elements other than B); in another embodiment, to at least one, optionally including more than one, B, with no A present (and optionally including elements other than A); in yet another embodiment, to at least one, optionally including more than one, A, and at least one, optionally including more than one, B (and optionally including other elements); etc.

(604) The phrase “and/or,” as used herein in the specification and in the claims, should be understood to mean “either or both” of the elements so conjoined, i.e., elements that are conjunctively present in some cases and disjunctively present in other cases. Multiple elements listed with “and/or” should be construed in the same fashion, i.e., “one or more” of the elements so conjoined. Other elements may optionally be present other than the elements specifically identified by the “and/or” clause, whether related or unrelated to those elements specifically identified. Thus, as a non-limiting example, a reference to “A and/or B,” when used in conjunction with open-ended language such as “comprising” can refer, in one embodiment, to A only (optionally including elements other than B); in another embodiment, to B only (optionally including elements other than

A); in yet another embodiment, to both A and B (optionally including other elements); etc.

(605) Use of ordinal terms such as “first,” “second,” “third,” etc., in the claims to modify a claim element does not by itself connote any priority, precedence, or order of one claim element over another or the temporal order in which acts of a method are performed. Such terms are used merely as labels to distinguish one claim element having a certain name from another element having a same name (but for use of the ordinal term). The phraseology and terminology used herein is for the purpose of description and should not be regarded as limiting. The use of “including,” “comprising,” “having,” “containing,” “involving,” and variations thereof, is meant to encompass the items listed thereafter and additional items.

(606) Unless otherwise specified, the terms “approximately,” “substantially,” and “about” may be used to mean within $\pm 10\%$ of a target value in some embodiments. The terms “approximately,” “substantially” and “about” may include the target value.

(607) Having described several embodiments of the techniques described herein in detail, various modifications, and improvements will readily occur to those skilled in the art. Such modifications and improvements are intended to be within the spirit and scope of the disclosure. Accordingly, the foregoing description is by way of example only, and is not intended as limiting. The techniques are limited only as defined by the following claims and the equivalents thereto.

(608) Various aspects are described in this disclosure, which include, but are not limited to, the following aspects:

(609) 1. A vehicle inspection system for inspecting a vehicle, the system comprising: a vehicle exterior inspection system comprising: a first support member; a first sensor array coupled to the first support member and comprising a first set of cameras positioned to capture images of wheels of the vehicle being imaged; a second sensor array coupled to the first support member and comprising a second set of cameras positioned to capture images of a side of the vehicle being imaged; and a third sensor array coupled to the first support member and comprising a third set of cameras positioned to capture images of a roof of the vehicle being imaged; a vehicle undercarriage inspection system comprising: a base having a width and a depth respectively extending along first and second directions orthogonal to one another, the width extending from a first end of the base to a second end of the base, the base supporting a fourth sensor array configured to capture images of an undercarriage of the vehicle, wherein the fourth sensor array comprises: a first camera positioned at a first side of the base, and oriented towards the first side of the base; a second camera positioned at a second side of the base, and oriented towards the second side of the base; and a third camera positioned between the first and second cameras, wherein the vehicle inspection system is configured to: capture a first plurality of images of the vehicle using the first, second and third sets of cameras of the vehicle exterior inspection system; and capture a second plurality of images of the undercarriage of the vehicle using the fourth sensor array of the vehicle undercarriage inspection system.

(610) 2. The vehicle inspection system of aspect 1, further comprising: a computer hardware processor configured to: when the vehicle is moved relative to the vehicle exterior inspection system and the vehicle undercarriage inspection system: triggering the capture of the first plurality of images of the vehicle using the first, second and third sets of cameras of the vehicle exterior inspection system, receiving the first plurality of images, and/or processing the first plurality of images; and triggering the capture of a second plurality of images of the undercarriage of the vehicle using the fourth sensor array of the vehicle undercarriage inspection system, receiving the second plurality of images, and/or processing the second plurality of images.

(611) 3. The vehicle inspection system of any of aspects 1-2, wherein: the vehicle inspection system is configured to trigger the capture the first and second plurality of images based on a position of the vehicle.

(612) 4. The vehicle inspection system of any of aspects 1-3, wherein the vehicle undercarriage inspection system further comprises: a sensor configured to output data indicative of the position

and/or motion of the vehicle relative to the vehicle inspection system, wherein the capturing of the first plurality of images is performed in response to determining the vehicle is at a first position and/or first distance relative to the vehicle inspection system, based on the data indicative of the position and/or motion of the vehicle.

(613) 5. The vehicle inspection system of any of aspects 1-4, wherein: the capturing of the second plurality of images is performed in response to determining the vehicle is at a second position and/or distance relative to the vehicle inspection system, different from the first position, based on the data indicative of the position and/or motion of the vehicle.

(614) 6. The vehicle inspection system of any of aspects 1-5, wherein: the second position is closer to the vehicle inspection system than the first position, and/or the first distance is smaller than the second distance.

(615) 7. The vehicle inspection system of any of aspects 1-5, wherein: the computer hardware processor is further configured to perform: stopping the capturing of the first plurality of images in response to determining the vehicle is at a third position and/or distance relative to the vehicle inspection system, different from the first and second positions and/or distances, based on the data indicative of the position and/or motion of the vehicle; and stopping the capturing of the second plurality of images in response to determining the vehicle is at a fourth position and/or distance relative to the vehicle inspection system, different from the first, second and third positions and/or distances, based on the data indicative of the position and/or motion of the vehicle.

(616) 8. The vehicle inspection system of any of aspects 1-7, wherein the vehicle exterior inspection system further comprises: a second support member; a fourth sensor array coupled to the second support member and comprising a fourth set of cameras positioned to capture images of wheels of the vehicle being imaged; a fifth sensor array coupled to the second support member and comprising a fifth set of cameras positioned to capture images of a side of the vehicle being imaged; and a sixth sensor array coupled to the second support member and comprising a sixth set of cameras positioned to capture images of a roof of the vehicle being imaged.

(617) 9. The vehicle inspection system of any of aspects 1-8, wherein: the vehicle exterior inspection system is portable and is collapsible between a deployed and a stowed configuration, and is configured to image the vehicle when in the deployed configuration; and wherein the vehicle undercarriage inspection system weighs less than 10 pounds, and further comprises a handle attached to the base for lifting the vehicle undercarriage inspection system.

(618) 10. The vehicle inspection system of any of aspects 1-9, wherein one or more of the first, second, third and fourth sensor arrays comprise one or more of: a microphone, an infrared camera, a thermal camera, a magnetometer, a time of flight sensor, a light source, and/or an air quality sensor.

(619) 11. The vehicle inspection system of any of aspects 1-10, wherein first, second, and third sensor arrays are configured such that the combined FOV of the first, second and third sets of cameras spans at least 150 inches in height, 300 inches in length and 120 inches in width.

(620) 12. A vehicle inspection system for analyzing the condition of a vehicle, the system comprising: a vehicle exterior inspection system comprising: a first support member; a first sensor array coupled to the first support member and comprising a first set of cameras positioned to capture images of wheels of the vehicle being imaged; a second sensor array coupled to the first support member and comprising a second set of cameras positioned to capture images of a side of the vehicle being imaged; and a third sensor array coupled to the first support member and comprising a third set of cameras positioned to capture images of a roof of the vehicle being imaged; a vehicle undercarriage inspection system comprising: a base having a width and a depth respectively extending along first and second directions orthogonal to one another, the width extending from a first end of the base to a second end of the base, the base supporting a fourth sensor array configured to capture images of an undercarriage of the vehicle, wherein the fourth sensor array comprises: a first camera positioned at a first side of the base, and oriented towards the

first side of the base; a second camera positioned at a second side of the base, and oriented towards the second side of the base; and a third camera positioned between the first and second cameras; and a computer hardware processor configured to perform: obtaining a first plurality of images of the vehicle captured using the first, second and third sets of cameras of the vehicle exterior inspection system; and obtaining a second plurality of images of the undercarriage of the vehicle captured using the fourth sensor array of the vehicle undercarriage inspection system; processing images of the first and second pluralities of images, using at least one trained machine learning (ML) model, to determine whether the vehicle has one or more defects; and generating a vehicle condition report based on results of the processing of the images of the first plurality of images and the composite image.

(621) 13. The vehicle inspection system of aspect 12, wherein the computer hardware processor is further configured to perform: generating a composite image of the undercarriage of the vehicle by combining images of the second plurality of images, wherein the composite image is processed using the at least one machine learning model to determine whether the vehicle has the one or more defects.

(622) 14. The vehicle inspection system of any of aspects 12-13, wherein the one or more defects include: scratches to an exterior of the vehicle; cracked windows, mirrors, or windshields, chipped paint, dents to the exterior of the vehicle, misaligned body panels, missing vehicle parts, non-standard replacement parts, non-standard paint, aftermarket vehicle accessories, rust/corrosion on the vehicle, damaged wheels, damaged tires, bald tires, tire sidewall bubbles, broken tire valves, wheel misalignment, mismatched tires, brake rotor discoloration, brake rotor damage, brake rotor wear, a missing catalytic converter and/or suspension modifications.

(623) 15. The vehicle inspection system of any of aspects 12-14, wherein the computer hardware processor is further configured to perform: generating a 3D model of the of the vehicle based on the first and second pluralities of images; generating a visualization of the 3D model; and providing access to the visualization to one or more users.

(624) 16. The vehicle inspection system of any of aspects 12-15, wherein the computer hardware processor is further configured to perform: before processing the images of the first plurality of images, identifying a subset of the first plurality of images based on a pose of the vehicle in images of the plurality of images, wherein processing the images of the first plurality of images comprises processing the subset of images.

(625) 17. The vehicle inspection system of any of aspects 12-16, wherein: the vehicle undercarriage imaging system further comprises a sensor configured to output data indicative of the position and/or motion of the vehicle relative to the vehicle undercarriage inspection system; and the computer hardware processor is further configured to perform: determining, based on the data indicative of the position and/or motion of the vehicle, a speed of the vehicle relative to the vehicle undercarriage inspection system, wherein the composite image is generated based on the vehicle speed.

(626) 18. The vehicle inspection system of any of aspects 12-17, wherein one or more of the first, second, third and fourth sensor arrays comprise one or more of: a microphone, an infrared camera, a thermal camera, a magnetometer, a time of flight sensor, a light source, and/or an air quality sensor.

(627) 19. The vehicle inspection system of any of aspects 12-18, wherein: obtaining the first plurality of images comprises capturing the first plurality of images of the vehicle using the first, second and third sets of cameras of the vehicle exterior inspection system; and obtaining the second plurality of images comprises capturing the second plurality of images of the undercarriage of the vehicle using the fourth sensor array of the vehicle undercarriage inspection system.

(628) 20. A vehicle inspection system, for inspecting a vehicle, the vehicle inspection system comprising: a vehicle exterior inspection system comprising: a first support member comprising a first portion and a second portion angled relative to the first portion; a first plurality of sensor

arrays coupled to the first support member, the first plurality of sensor arrays comprising: a first sensor array comprising a first set of cameras oriented in multiple first directions, the first sensor array being coupled to the first support member at a position at which the first set of cameras has one or more wheels of a vehicle in its field of view (FOV) when the first sensor array is being used to image the vehicle; a second sensor array comprising a second set of cameras oriented in multiple second directions, the second sensor array being coupled to the first support member at a position at which the second set of cameras has a first side of the vehicle in its FOV when the second sensor array is being used to image the vehicle; and a third sensor array comprising a third set of cameras oriented in multiple third directions, the third sensor array being coupled to the first support member at a position at which the third set of cameras has a roof of the vehicle in its FOV when the third sensor array is being used to image the vehicle; and a vehicle undercarriage inspection system, comprising: a base having a width and a depth respectively extending along first and second directions orthogonal to one another, the width extending from a first end of the base to a second end of the base; a fourth sensor array coupled to the base, the fourth sensor array comprising a set of cameras oriented in multiple directions, the set of cameras including: a first camera oriented in part towards the first end of the base; a second camera oriented in part towards the second end of the base; and a third camera positioned between the first and second cameras.

(629) 21. A method for inspecting a vehicle using a vehicle inspection system, the vehicle inspection system comprising a vehicle exterior inspection system comprising a support member and a plurality of exterior sensor arrays coupled to the support member, the plurality of exterior sensor arrays comprising respective sets of sensors oriented in different directions, and a vehicle undercarriage inspection system comprising an undercarriage sensor array comprising first, second and third cameras configured to capture images at different angles relative to the vehicle undercarriage, and a sensor configured to output data indicative of the position and/or motion of the vehicle relative to the vehicle inspection system, the method comprising: moving the vehicle and the vehicle inspection system relative to one another; triggering capture, by the plurality of exterior sensor arrays and undercarriage sensor array, of sensor data about the vehicle; capturing the sensor data about the vehicle using the plurality of exterior sensor arrays and undercarriage sensor array of the vehicle inspection system; stopping capture of the sensor data about the vehicle; stopping movement of the vehicle and the vehicle inspection system relative to one another; generating a vehicle condition report based on the sensor data collected using the plurality of exterior sensor arrays and the undercarriage sensor array.

(630) 22. The method of aspect 21, wherein the generating comprises generating the vehicle condition report using the vehicle inspection system.

(631) 23. The method of any of aspects 21-22, wherein the generating comprises: providing to a computer hardware processor, separate from the vehicle inspection system, at least some of the sensor data collected using the plurality of exterior sensor arrays and the undercarriage sensor array.

(632) 24. The method of any of aspects 21-23, wherein the triggering is performed by the vehicle inspection system based on the data indicative of the position and/or motion of the vehicle.

(633) 25. The method of any of aspects 21-24, wherein the triggering comprises: triggering capture of the sensor data by the plurality of exterior sensor arrays when the vehicle is determined to be at a first position and/or distance relative to the vehicle inspection system based on the data indicative of the position and/or motion of the vehicle.

(634) 26. The method of aspect 25, wherein the triggering comprises: triggering capture of the sensor data by the undercarriage sensor array when the vehicle is determined to be at a second position and/or distance relative to the vehicle inspection system, different from the first position, based on the data indicative of the position and/or motion of the vehicle.

(635) 27. The method of any of aspects 25-26, wherein the second position is closer to the vehicle inspection system than the first position, and/or the second distance is smaller than the first

distance.

(636) 28. The method of any of aspects 25-27, wherein the stopping is performed by the vehicle inspection system based on the data indicative of the position and/or motion of the vehicle.

(637) 29. The method of any of aspects 21-28, further comprising: before the moving: placing a mobile vehicle diagnostic device (MVDD) of the vehicle inspection system at an engine of the vehicle, wherein the triggering comprises triggering a sensor array of the MVDD of the vehicle inspection system to capture the sensor data about the engine of the vehicle and the capturing comprises using the MVDD to capture the sensor data about the engine of the vehicle.

(638) 30. A method for inspecting a vehicle using a vehicle inspection system, the vehicle inspection system comprising a vehicle exterior inspection system comprising a support member and a plurality of exterior sensor arrays coupled to the support member, the plurality of exterior sensor arrays comprising respective sets of sensors oriented in different directions, and a vehicle undercarriage inspection system comprising an undercarriage sensor array comprising first, second and third cameras configured to capture images at different angles relative to the vehicle undercarriage, and a sensor configured to output data indicative of the position and/or motion of the vehicle relative to the vehicle undercarriage inspection system, the method comprising: moving the vehicle and the vehicle inspection system relative to one another; triggering capture, by the plurality of exterior sensor arrays and undercarriage sensor array, of sensor data about the vehicle; capturing the sensor data about the vehicle using the plurality of exterior sensor arrays and undercarriage sensor array of the vehicle inspection system; stopping capture of the sensor data about the vehicle; stopping movement of the vehicle and the vehicle inspection system relative to one another; processing the sensor data, using a computer hardware processor, to identify one or more vehicle defects.

(639) 31. The method of aspect 30, wherein the triggering comprises: triggering capture of the sensor data by the plurality of exterior sensor arrays is performed when the vehicle is determined to be at a first position and/or distance relative to the vehicle inspection system based on the data indicative of the position and/or motion of the vehicle.

(640) 32. The method of aspect 31, wherein the triggering comprises: triggering capture of the sensor data by the undercarriage sensor array is performed when the vehicle is determined to be at a second position and/or distance relative to the vehicle inspection system, different from the first position, based on the data indicative of the position and/or motion of the vehicle.

(641) 33. The method of any of aspects 30-32, wherein the stopping is performed by the vehicle inspection system based the data indicative of the position and/or motion of the vehicle.

(642) 34. The method of any of aspects 30-33, further comprising: before the moving: placing a mobile vehicle diagnostic device (MVDD) of the vehicle inspection system at an engine of the vehicle, wherein the triggering comprises triggering a sensor array of the MVDD of the vehicle inspection system to capture the sensor data about the engine of the vehicle and the capturing comprises using the MVDD to capture the sensor data about the engine of the vehicle.

(643) 35. A method for inspecting a vehicle using a vehicle inspection system, the vehicle inspection system comprising a vehicle exterior inspection system comprising a support member and a plurality of exterior sensor arrays coupled to the support member, the plurality of exterior sensor arrays comprising respective sets of sensors oriented in different directions, and a vehicle undercarriage inspection system comprising an undercarriage sensor array comprising first, second and third cameras configured to capture images at different angles relative to the vehicle undercarriage, and a sensor configured to output data indicative of the position and/or motion of the vehicle relative to the vehicle inspection system, the method comprising: positioning the vehicle, the vehicle exterior inspections system and the vehicle undercarriage inspection system relative to one another; triggering the vehicle inspection system to collect alignment data of the vehicle relative to the vehicle inspection system; obtaining an indication of an alignment of the vehicle relative to the vehicle inspection system based on the alignment data; based on the indication of the

alignment of the vehicle, adjusting one or more of the exterior sensor arrays or the undercarriage sensor array; moving the vehicle and the vehicle inspection system relative to one another; capturing sensor data about the vehicle using the plurality of exterior sensor arrays and undercarriage sensor array of the vehicle inspection system; and processing the sensor data, using a computer hardware processor, to identify one or more vehicle defects.

(644) 36. The method of aspect 35, wherein the alignment data is captured by the sensor of the vehicle undercarriage inspection system configured to output the data indicative of the position and/or motion of the vehicle.

(645) 37. The method of any of aspects 35-36, wherein the moving comprises driving the vehicle past the vehicle undercarriage inspection system and vehicle exterior inspection system.

(646) 38. The method of any of aspects 35-37, wherein the moving comprises moving the vehicle exterior and vehicle undercarriage inspection systems about the vehicle.

(647) 39. The method of any of aspects 35-38, further comprising: before the moving: placing a mobile vehicle diagnostic device (MVDD) of the vehicle inspection system at an engine of the vehicle, wherein the triggering comprises triggering a sensor array of the MVDD of the vehicle inspection system to capture the sensor data about the engine of the vehicle and the capturing comprises using the MVDD to capture the sensor data about the engine of the vehicle.

(648) 40. The method of any of aspects 35-39, further comprising: before the processing: receiving an indication the capturing was unsuccessful; and recapturing second sensor data about the vehicle using the plurality of exterior sensor arrays and undercarriage sensor array of the vehicle inspection system.

(649) 41. A system for vehicle inspection, the system comprising: a first support member comprising a first portion and a second portion angled relative to the first portion; a first plurality of sensor arrays coupled to the first support member, the first plurality of sensor arrays comprising: a first sensor array comprising a first set of cameras oriented in multiple first directions, the first sensor array being coupled to the first support member at a position at which the first set of cameras has one or more wheels of a vehicle in its field of view (FOV) when the first sensor array is being used to image the vehicle; a second sensor array comprising a second set of cameras oriented in multiple second directions, the second sensor array being coupled to the first support member at a position at which the second set of cameras has a first side of the vehicle in its FOV when the second sensor array is being used to image the vehicle; and a third sensor array comprising a third set of cameras oriented in multiple third directions, the third sensor array being coupled to the first support member at a position at which the third set of cameras has a roof of the vehicle in its FOV when the third sensor array is being used to image the vehicle; and a processor configured to control the first plurality of sensor arrays to capture images of the vehicle.

(650) 42. The system of aspect 41, wherein the first sensor array is positioned below the second and third sensor arrays on the first support member.

(651) 43. The system of aspect 42, wherein the second sensor array is positioned below the third sensor array on the first support member.

(652) 44. The system of any of aspects 41-43, wherein the first and second sensor arrays are positioned on the first portion of the first support member, and the third sensor array is positioned on the second portion of the first support member.

(653) 45. The system of any of aspects 41-44, wherein the first sensor array further comprises: a microphone, an infrared camera, a thermal camera, a magnetometer, a light source and/or an air quality sensor.

(654) 46. The system of any of aspects 41-45, further comprising: a second support member comprising a third portion, and a fourth portion angled relative to the third portion; a second plurality of sensor arrays coupled to the second support member, the second plurality of sensor arrays comprising: a fourth sensor array comprising a fourth set of cameras oriented in multiple fourth directions, the fourth sensor array being coupled to the second support member at a position

at which the fourth set of cameras has one or more wheels of a vehicle in its FOV when the fourth sensor array is being used to image the vehicle; a fifth sensor array comprising a fifth set of cameras oriented in multiple fifth directions, the fifth sensor array being coupled to the second support member at a position at which the fifth set of cameras has a second side of the vehicle in its field of view when the fifth sensor array is being used to image the vehicle; and a sixth sensor array comprising a sixth set of cameras oriented in multiple sixth directions, the sixth sensor array being coupled to the second support member at a position at which the sixth set of cameras has the roof of the vehicle in its field of view when the sixth sensor array is being used to image the vehicle, wherein the processor is further configured to control the second plurality of sensor arrays capture images of the vehicle.

(655) 47. The system of any of aspects 41-46, wherein the first plurality of sensor arrays is configured such that the combined FOV of the first, second and third sets of cameras spans at least 150 inches in height, 300 inches in length and 120 inches in width.

(656) 48. The system of any of aspects 41-47, wherein: during imaging the vehicle and support structure move relative to one another along a first direction; the first set of cameras comprises: a first camera oriented in part towards the first direction; a second camera oriented in part opposite the first direction; and a third camera oriented substantially perpendicular to the first direction; the first camera has a rocker panel and wheels of the vehicle in its field of view when being used to image the vehicle; the second camera has the rocker panel and rear of the vehicle in its field of view when being used to image the vehicle; and the third camera has one or more wheels of the vehicle in its field of view when being used to image the vehicle.

(657) 49. The system of any of aspects 41-48, wherein: during imaging the vehicle and support structure move relative to one another along a first direction; the second set of cameras comprises: a first camera oriented in part towards the first direction; a second camera oriented in part opposite the first direction; and a third camera oriented substantially perpendicular to the first direction; the first camera has the side and front of the vehicle in its field of view when being used to image the vehicle; the second camera has the side and rear of the vehicle in its field of view when being used to image the vehicle; and the third camera has the side of the vehicle in its field of view when being used to image the vehicle.

(658) 50. The system of any of aspects 41-49, wherein: during imaging the vehicle and support structure move relative to one another along a first direction; the third set of cameras comprises: a first camera oriented in part towards the first direction; a second camera oriented in part opposite the first direction; and a third camera oriented substantially perpendicular to the first direction; the first camera has the roof, front, and hood of the vehicle in its field of view when being used to image the vehicle; the second camera has the roof and rear of the vehicle in its field of view when being used to image the vehicle; and the third camera has the hood and the roof of the vehicle in its field of view when being used to image the vehicle.

(659) 51. The system of any of aspects 41-50, wherein: the first support member is portable and is collapsible between a deployed and a stowed configuration; and wherein the vehicle inspection system is configured to image the vehicle when the first support member is in the deployed configuration.

(660) 52. The system of any of aspects 41-51, wherein: the processor is configured to control the first plurality of sensor arrays to image the vehicle as the vehicle is driven past the first support member.

(661) 53. The system of any of aspects 41-52, wherein: the processor is configured to control the first support member to move about the vehicle, and wherein the processor is configured to control the first plurality of sensor arrays to image the vehicle as the first support member moves about the vehicle.

(662) 54. The system of any of aspects 41-53, wherein: the processor is further configured to process the images of the vehicle using at least one trained machine learning (ML) model, to

determine whether the vehicle has the one or more defects, wherein the one or more defects include: scratches to an exterior of the vehicle, cracked windows, mirrors, or windshields, chipped paint, dents to the exterior of the vehicle, misaligned body panels, missing vehicle parts, non-standard replacement parts, non-standard paint, aftermarket vehicle accessories, rust/corrosion on the vehicle, damaged wheels, damaged tires, bald tires, tire sidewall bubbles, broken tire valves, wheel misalignment, mismatched tires, brake rotor discoloration, brake rotor damage, brake rotor wear, and/or suspension modifications.

(663) 55. The system of any of aspects 41-54, further comprising a vehicle undercarriage inspection system comprising a fourth sensor array configured to capture signals related to the undercarriage of the vehicle.

(664) 56. A system for vehicle inspection, the system comprising: a support member; a first plurality of sensor arrays coupled to the first support member, the first plurality of sensor arrays comprising: a first sensor array comprising a first set of cameras oriented in multiple first directions and a first microphone; a second sensor array comprising a second set of cameras oriented in multiple second directions and a second microphone; and a third sensor array comprising a third set of cameras oriented in multiple third directions, and a third microphone; and a processor configured to control the first plurality of sensor arrays to capture images and audio recordings of the vehicle.

(665) 57. The system of aspect 56, wherein: during imaging the vehicle and support member move relative to one another along a first direction; and the first, second and third sets of cameras respectively comprise: a first camera oriented in part towards the first direction; a second camera oriented in part opposite the first direction; and a third camera oriented substantially perpendicular to the first direction.

(666) 58. The system of any of aspects 56-57, wherein: the processor is further configured to process the images and/or audio of the vehicle using at least one trained machine learning (ML) model, to determine whether the vehicle has the one or more defects; wherein the one or more defects include: scratches to an exterior of the vehicle; cracked windows, mirrors, or windshields; chipped paint; dents to the exterior of the vehicle; misaligned body panels; missing vehicle parts, non-standard replacement parts, non-standard paint; aftermarket vehicle accessories; rust/corrosion on the vehicle; damaged wheels; damaged tires; bald tires; tire sidewall bubbles; broken tire valves; wheel misalignment; mismatched tires; brake rotor discoloration; brake rotor damage; brake rotor wear; suspension modifications; engine damage; an exhaust leak; and/or transmission whine.

(667) 59. A system for vehicle inspection, the system comprising: a support member; a first plurality of sensor arrays coupled to the first support member, the first plurality of sensor arrays configured to capture signals about a vehicle as the vehicle and support member move relative to one another along a first direction, and comprising: a first sensor array comprising a first set of cameras, the first sensor array coupled to the first support member at a position at which the first set of cameras has a first side of the vehicle in its FOV when the first sensor array is being used to image the vehicle, the first set of cameras comprising: a first camera oriented in part towards the first direction; a second camera oriented in part opposite the first direction; and a third camera oriented substantially perpendicular to the first direction; and a second sensor array comprising a second set of cameras, the first sensor array coupled to the first support member at a position at which the second set of cameras has a roof of the vehicle in its FOV when the second sensor array is being used to image the vehicle, the second set of cameras comprising: a fourth camera oriented in part towards the first direction; a fifth camera oriented in part opposite the first direction; and a sixth camera oriented substantially perpendicular to the first direction; and a processor configured to control the first plurality of sensor arrays to capture images of the vehicle.

(668) 60. The system of aspect 59, wherein: the first camera has the side and front of the vehicle in its FOV when being used to image the vehicle; the second camera has the side and rear of the vehicle in its FOV when being used to image the vehicle; the third camera has the side of the

vehicle in its FOV when being used to image the vehicle; the fourth camera has the roof, front, and hood of the vehicle in its FOV when being used to image the vehicle; the fifth camera has the roof and rear of the vehicle in its FOV when being used to image the vehicle; and the sixth camera has the hood and the roof of the vehicle in its FOV when being used to image the vehicle.

(669) 61. A method for analyzing condition of a vehicle from images of the vehicle collected by a vehicle inspection system, the vehicle inspection system comprising a plurality of sensor arrays comprising first, second and third sensor arrays comprising respective first, second, and third sets of cameras, the method comprising: using at least one computer hardware processor to perform: obtaining a plurality of images using the vehicle inspection system, the plurality of images including first, second, and third sets of images captured, respectively, by the first, second, and third sets of cameras; identifying a subset of the plurality of images for subsequent processing to identify whether the vehicle has one or more defects, wherein the identifying is performed based on a pose of the vehicle in images of the plurality of images; processing the subset of the plurality of images, using at least one trained machine learning (ML) model, to determine whether the vehicle has the one or more defects; and generating a vehicle condition report based on results of the processing, the vehicle condition report including an indication of the one or more defects in the plurality of images.

(670) 62. The method of aspect 61, wherein the obtaining comprises controlling the plurality of sensor arrays of the vehicle inspection system to capture the plurality of images of the vehicle.

(671) 63. The method of aspect 62, wherein the controlling comprises: controlling the first set of cameras to capture images of one or more wheels of the vehicle; controlling the second set of cameras to capture images of a first side of the vehicle; and controlling the third set of cameras to capture images of a roof of the vehicle.

(672) 64. The method of any of aspects 61-63, further comprising: generating a 3D model of the vehicle using at least some of the plurality of images; generating a visualization of the 3D model; and providing access to the visualization to one or more users.

(673) 65. The method of aspect 64, wherein the 3D model is generated using photogrammetry, neural radiance fields, or Gaussian splatting.

(674) 66. The method of any of aspects 61-65, further comprising: identifying, from among the plurality of images, an image containing personally identifiable information (PII); identifying a region of the image containing the PII; and distorting the region of the image containing the PII, wherein the vehicle condition report includes the image.

(675) 67. The method of any of aspects 61-66, wherein the one or more defects include: scratches to an exterior of the vehicle, cracked windows, mirrors, or windshields, chipped paint, dents to the exterior of the vehicle, misaligned body panels, missing vehicle parts, non-standard replacement parts, non-standard paint, aftermarket vehicle accessories, rust/corrosion on the vehicle, damaged wheels, damaged tires, bald tires, tire sidewall bubbles, broken tire valves, wheel misalignment, mismatched tires, brake rotor discoloration, brake rotor damage, brake rotor wear, and/or suspension modifications.

(676) 68. The method of any of aspects 61-67, wherein: the vehicle inspection system further comprises a vehicle undercarriage inspection system; and the plurality of images includes a fourth set of images of an undercarriage of the vehicle captured by the vehicle undercarriage inspection system.

(677) 69. The method of any of aspects 61-68, wherein identifying the subset of the plurality of images for subsequent processing comprises: determining a degree of matching between the pose of the vehicle in images of the plurality of images and vehicle poses of a reference set of vehicle poses; and for each vehicle pose of the reference set of vehicle poses, identifying an image in the plurality of images having at least a threshold degree of matching and including the identified image in the subset of the plurality of images.

(678) 70. The method of aspect 69, wherein determining the degree of matching between the pose

of the vehicle in the images of the plurality of images and vehicle poses of the reference set of vehicle poses comprises: determining a distance between a center of a bounding box of the vehicle in an image and the center of the image.

(679) 71. The method of any of aspects 69-70, wherein the set of vehicle poses includes poses associated with the cameras of the first, second and third sets of cameras.

(680) 72. A vehicle inspection system comprising: a plurality of sensor arrays comprising first, second and third sensor arrays comprising respective first, second, and third sets of cameras; and a computer hardware processor configured to perform: obtaining a plurality of images, the plurality of images including first, second, and third sets of images captured, respectively, by the first, second, and third sets of cameras; identifying a subset of the plurality of images for subsequent processing to identify whether the vehicle has one or more defects, wherein the identifying is performed based on a pose of the vehicle in images of the plurality of images; processing the subset of the plurality of images, using at least one trained machine learning (ML) model, to determine whether the vehicle has the one or more defects; and generating a vehicle condition report based on results of the processing, the vehicle condition report including an indication of the one or more defects in the plurality of images.

(681) 73. The vehicle inspection system of aspect 72, wherein the obtaining comprises controlling the plurality of sensor arrays of the vehicle inspection system to capture the plurality of images of the vehicle.

(682) 74. The vehicle inspection system of aspect 73, wherein the controlling comprises: controlling the first set of cameras to capture images of one or more wheels of the vehicle; controlling the second set of cameras to capture images of a first side of the vehicle; and controlling the third set of cameras to capture images of a roof of the vehicle.

(683) 75. The vehicle inspection system of any of aspects 72-74, further comprising: generating, using photogrammetry, neural radiance fields or Gaussian splatting, a 3D model of the vehicle using at least some of the plurality of images; generating a visualization of the 3D model; and providing access to the visualization to one or more users.

(684) 76. The vehicle inspection system of any of aspects 72-75, wherein the one or more defects include: scratches to an exterior of the vehicle, cracked windows, mirrors, or windshields, chipped paint, dents to the exterior of the vehicle, misaligned body panels, missing vehicle parts, non-standard replacement parts, non-standard paint; aftermarket vehicle accessories, rust/corrosion on the vehicle, damaged wheels, damaged tires, bald tires, tire sidewall bubbles, broken tire valves, wheel misalignment, mismatched tires, brake rotor discoloration, brake rotor damage, brake rotor wear, and/or suspension modifications.

(685) 77. At least one non-transitory computer-readable storage medium storing processor-executable instructions that, when executed by at least one computer hardware processor, causes the at least one computer hardware processor to perform a method for analyzing conditions of a vehicle from images of the vehicle collected by a vehicle inspection system, the vehicle inspection system comprising a plurality of sensor arrays comprising first, second and third sensor arrays comprising respective first, second, and third sets of cameras, the method comprising: obtaining a plurality of images, the plurality of images including first, second, and third sets of images captured, respectively, by the first, second, and third sets of cameras; identifying a subset of the plurality of images for subsequent processing to identify whether the vehicle has one or more defects, wherein the identifying is performed based on a pose of the vehicle in images of the plurality of images; processing the subset of the plurality of images, using at least one trained machine learning (ML) model, to determine whether the vehicle has the one or more defects; and generating a vehicle condition report based on results of the processing, the vehicle condition report including an indication of the one or more defects in the plurality of images.

(686) 78. The at least one non-transitory computer-readable storage medium of aspect 77, wherein the obtaining comprises controlling the plurality of sensor arrays of the vehicle inspection system

to capture the plurality of images of the vehicle.

(687) 79. The at least one non-transitory computer-readable storage medium of aspect 78, wherein the controlling comprises: controlling the first set of cameras to capture images of one or more wheels of the vehicle; controlling the second set of cameras to capture images of a first side of the vehicle; and controlling the third set of cameras to capture images of a roof of the vehicle.

(688) 80. The at least one non-transitory computer-readable storage medium of any of aspects 77-79, wherein the one or more defects include: scratches to an exterior of the vehicle, cracked windows, mirrors, or windshields, chipped paint, dents to the exterior of the vehicle, misaligned body panels, missing vehicle parts, non-standard replacement parts, non-standard paint, aftermarket vehicle accessories, rust/corrosion on the vehicle, damaged wheels, damaged tires, bald tires, tire sidewall bubbles, broken tire valves, wheel misalignment, mismatched tires, brake rotor discoloration, brake rotor damage, brake rotor wear, and/or suspension modifications.

(689) 81. A method for inspecting a vehicle using a vehicle inspection system, the vehicle inspection system comprising a support member and a plurality of sensor arrays coupled to the support member, the plurality of sensor arrays comprising respective sets of sensors oriented in different directions, the method comprising: moving the vehicle and the support member of the vehicle inspection system relative to one another; triggering capture of sensor data about the vehicle by the plurality of sensor arrays of the vehicle inspection system; capturing the sensor data about the vehicle using the plurality of sensor arrays of the vehicle inspection system; stopping capture of the sensor data about the vehicle; stopping movement of the vehicle and the support member relative to one another; providing, to a computer hardware processor, the sensor data collected using the plurality of sensor arrays; and receiving, from the computer hardware processor, a vehicle condition report generated using the sensor data.

(690) 82. The method of aspect 81, wherein the plurality of sensor arrays comprise first, second and third sensor arrays, the first sensor array comprising a first set of cameras oriented in multiple first directions, the second sensor array comprising a second set of cameras oriented in multiple second directions, the third sensor array comprising a third set of cameras oriented in multiple third directions, and wherein capturing the data related to the vehicle using the plurality of sensor arrays comprises, capturing images of the vehicle using the first, second and third sets of cameras.

(691) 83. The method of any of aspects 81-82, further comprising: obtaining an image of a front of the vehicle using a camera of the vehicle inspection system.

(692) 84. The method of any of aspects 81-83, further comprising: obtaining a plurality of images of an interior of the vehicle using a camera of the vehicle inspection system; and providing the plurality of images to the computer hardware processor.

(693) 85. The method of any of aspects 81-84, further comprising: before the moving: placing a mobile vehicle diagnostic device (MVDD) of the vehicle inspection system at an engine of the vehicle, wherein the triggering comprises triggering a sensor array of the MVDD of the vehicle inspection system to capture sensor data about the engine of the vehicle.

(694) 86. The method of any of aspects 81-85, further comprising: before the moving: positioning a vehicle undercarriage imaging system of the vehicle inspection system relative to the vehicle and the support member of the vehicle inspection system, wherein the triggering comprises triggering a sensor array of the vehicle undercarriage imaging system to capture sensor data about an undercarriage of the vehicle.

(695) 87. The method of any of aspects 81-86, further comprising: obtaining a plurality of images of an interior of the vehicle using a camera of the vehicle inspection system, wherein the providing further comprises providing the plurality of images of the interior of the vehicle to the computer hardware processor.

(696) 88. The method of any of aspects 81-87, wherein the triggering is performed by the vehicle inspection system when the vehicle is detected at a first position by one or more sensors of the plurality of sensor arrays.

(697) 89. The method of aspect 88, wherein the stopping capture is performed by the vehicle inspection system when the vehicle is detected at a second position, different from the first position, by the one or more sensors of the plurality of sensor arrays.

(698) 90. The method of any of aspects 81-89, further comprising: before receiving the vehicle condition report, receiving from the computer hardware processor an indication the capturing was unsuccessful; recapturing second sensor data about the vehicle using the plurality of sensor arrays of the vehicle inspection system; and providing, to the computer hardware processor, the second sensor data collected using the plurality of sensor arrays.

(699) 91. The method of any of aspects 81-90, further comprising: before the moving, positioning the support member relative to the vehicle.

(700) 92. The method of any of aspects 81-91, wherein the moving comprises driving the vehicle past the support member.

(701) 93. The method of any of aspects 81-92, wherein the moving comprises moving the support member about the vehicle.

(702) 94. A method for inspecting a vehicle using a vehicle inspection system, the vehicle inspection system comprising a support member, and a plurality of sensor arrays coupled to the support member, the plurality of sensor arrays comprising respective sets of sensors oriented in different directions, the method comprising: positioning the vehicle and the support member of the vehicle inspection system relative to one another; triggering the vehicle inspection system to collect alignment data of the vehicle relative to the vehicle inspection system; providing, to a computer hardware processor, the alignment data; receiving, from the computer hardware processor, an indication of an alignment of the vehicle relative to the vehicle inspection system; repositioning the support member relative to the vehicle based on the indication of the alignment; moving the vehicle and the support member of the vehicle inspection system relative to one another; capturing sensor data about the vehicle using the plurality of sensor arrays of the vehicle inspection system; providing, to a computer hardware processor, the sensor data collected using the plurality of sensor arrays; and receiving, from the computer hardware processor, a vehicle condition report.

(703) 95. The method of aspect 94, further comprising: before the moving: positioning a vehicle undercarriage imaging system of the vehicle inspection system relative to the vehicle and the support member of the vehicle inspection system; and performing a registration process between the support member and the vehicle undercarriage imaging system, wherein the triggering comprises triggering the vehicle inspection system to collect alignment data of the support member and the vehicle undercarriage inspection system relative to the vehicle.

(704) 96. The method of any of aspects 94-95, further comprising: before the moving: placing a mobile vehicle diagnostic device (MVDD) of the vehicle inspection system at an engine of the vehicle, the MVDD comprising a sensor array.

(705) 97. The method of any of aspects 94-96, wherein the moving comprises driving the vehicle past the support member.

(706) 98. A method for inspecting a vehicle using a vehicle inspection system, the vehicle inspection system comprising a support member, and a plurality of sensor arrays coupled to the support member, the plurality of sensor arrays comprising respective sets of sensors oriented in different directions, the method comprising: moving the vehicle and the support member of the vehicle inspection system relative to one another; capturing sensor data about the vehicle using the plurality of sensor arrays of the vehicle inspection system; stopping movement of the vehicle and the support member relative to one another; providing, to a computer hardware processor, the sensor data collected using the plurality of sensor arrays; receiving, from the computer hardware processor, a vehicle condition report indicating one or more defects present on the vehicle; providing, to the computer hardware processor, a request for sensor data related to the one or more defects present on the vehicle; and receiving, from the computer hardware processor, a plurality of sensor data related to the one or more defects present on the vehicle.

(707) 99. The method of aspect 98, wherein: the sets of sensors oriented in different directions of the plurality of sensor arrays are respective sets of cameras; and the plurality of sensor data related to the one or more defects comprises a plurality of images of the one or more defects taken from different angles by cameras of the respective sets of cameras of the plurality of sensor arrays.

(708) 100. The method of aspect 99, further comprising: analyzing the vehicle to confirm a presence of the one or more defects; providing, to the computer hardware processor, an indication of the presence of the one or more defects; and receiving, from the computer hardware processor, an updated vehicle condition report.

(709) 101. A vehicle undercarriage inspection system, comprising: a base having a width and a depth respectively extending along first and second directions orthogonal to one another, the width extending from a first end of the base to a second end of the base; a sensor array coupled to the base, the sensor array comprising a set of cameras oriented in multiple directions, the set of cameras including: a first camera oriented in part towards the first end of the base; a second camera oriented in part towards the second end of the base; and a third camera positioned between the first and second cameras; and a processor configured to control the sensor array to capture a plurality of images of an undercarriage of a vehicle with the set of cameras.

(710) 102. The vehicle undercarriage inspection system of aspect 101, wherein the sensor array further comprises: a microphone, an infrared camera, a thermal camera, a magnetometer, a time of flight sensor, a light source, and/or an air quality sensor.

(711) 103. The vehicle undercarriage inspection system of any of aspects 101-102, wherein the processor is further configured to: generate a composite image of the vehicle undercarriage from images of the plurality of images of the vehicle undercarriage captured using the set of cameras.

(712) 104. The vehicle undercarriage inspection system of aspect 103, wherein the processor is further configured to: process the composite image, using at least one trained machine learning (ML) model, to determine whether the vehicle has one or more defects, or provide the composite image to another computing device for processing with the at least one trained ML model to determine whether the vehicle has one or more defects.

(713) 105. The vehicle undercarriage inspection system of aspect 104, wherein the one or more defects include: damage to one or more vehicle parts, presence of rust, presence of one or more aftermarket vehicle modifications, altered vehicle suspension, and/or a missing catalytic converter.

(714) 106. The vehicle undercarriage inspection system of any of aspects 101-105, wherein: the sensor array further comprises: a first time of flight (TOF) sensor oriented in part toward the first end of the base; and a second TOF sensor oriented in part the second end of the base, wherein the processor is configured to: determine a position and/or motion of the vehicle relative to the vehicle undercarriage inspection system based on signals collected by the first and second TOF sensors; and generate a composite image of the vehicle undercarriage from images of the plurality of images of the vehicle undercarriage captured using the set of cameras and based on the position and/or motion of the vehicle relative to the vehicle undercarriage inspection system.

(715) 107. The vehicle undercarriage inspection system of any of aspects 101-106, further comprising: a cover coupled to the base, wherein the cover is configured to withstand 16,000 pounds of force.

(716) 108. The vehicle undercarriage inspection system of aspect 107, wherein: the cover comprises internal ribbing configured to reinforce the cover to withstand the 16,000 pounds of force.

(717) 109. The vehicle undercarriage inspection system of any of aspects 101-108, wherein first, second and third cameras are configured such that their combined field of view (FOV) is 200 cm in width with a minimum pixel density of 15 pixels/cm.

(718) 110. The vehicle undercarriage inspection system of any of aspects 101-109, wherein: the vehicle undercarriage inspection system weighs less than 10 pounds; and the vehicle undercarriage inspection system further comprises a handle attached to the base for lifting the vehicle

undercarriage inspection system.

(719) 111. The vehicle undercarriage inspection system of any of aspects 101-110, wherein the processor is configured to: generate a 3D reconstruction of the vehicle undercarriage using the images of the vehicle undercarriage captured using the set of cameras.

(720) 112. The vehicle undercarriage inspection system of any of aspects 101-111, further comprising: a substrate supporting a plurality of electronic components, the plurality of electronic components comprising: the processor; respective camera controllers for the first, second and third cameras; and a power supply.

(721) 113. A vehicle undercarriage inspection system, comprising: a base having a width and a depth respectively extending along first and second directions orthogonal to one another, the width extending from a first end of the base to a second end of the base; a sensor array coupled to the base, the sensor array comprising: a set of cameras oriented in multiple directions; and a first time of flight (TOF) sensor configured to detect a position and/or motion of the vehicle; and a processor configured to: control the sensor array to capture a plurality of images of an undercarriage of a vehicle with the set of cameras; and control the TOF sensor to capture one or more signals indicative of the position and/or motion of the vehicle.

(722) 114. The vehicle undercarriage inspection system of aspect 113, further comprising: a second time of flight sensor configured to detect a position and/or motion of the vehicle, wherein: the first time of flight sensor is oriented in part towards the first end of the base; the second time of flight sensor is oriented in part towards the second end of the base; and the first and second time of flight sensors are configured to collect signals indicative of a distance to one or more wheels of the vehicle.

(723) 115. The vehicle undercarriage inspection system of any of aspects 113-114, wherein the first TOF sensor is oriented to collect signals indicative of a distance between the undercarriage of the vehicle and the vehicle undercarriage inspection system.

(724) 116. The vehicle undercarriage inspection system of any of aspects 113-115, wherein the processor is configured to generate a composite image of the undercarriage of the vehicle by combining images of the plurality of images based on the signals indicative of the position and/or motion of the vehicle.

(725) 117. A method for inspecting an undercarriage of a vehicle using a vehicle undercarriage inspection system, the vehicle undercarriage inspection system comprising a sensor array comprising first, second and third cameras configured to capture images at different angles relative to the vehicle undercarriage, and a time of flight (TOF) sensor configured to output signals indicative of the distance of one or more parts of the vehicle relative to the vehicle undercarriage inspection system, the method comprising: using a computer hardware processor to perform: obtaining, using the TOF sensor, at least one first signal indicative of a distance between the vehicle and the TOF sensor; in response to determining, using the at least one signal, that the vehicle is within a threshold distance of the TOF sensor, triggering the sensor array to capture one or more images of the vehicle undercarriage; capturing the one or more images of the vehicle undercarriage using the sensor array; and processing images of the plurality of images using a machine learning model to determine whether the vehicle has one or more defects.

(726) 118. The method of aspect 117, further comprising: obtaining, using the TOF sensor, at least one second signal indicative of the distance between the vehicle and the TOF sensor; in response to determining the vehicle is in a second position relative to the vehicle undercarriage inspection system based on the at least one second signal, triggering the sensor array to stop capture of the images of the vehicle undercarriage.

(727) 119. The method of any of aspects 117-118, further comprising: determining, using the at least one signal, that the vehicle is within the threshold distance of the TOF sensor.

(728) 120. The method of any of aspects 117-119, wherein the processing comprises: generating a composite image of the undercarriage of the vehicle by combining the images of the plurality of

images based on the signals related to the position of the vehicle obtained from the TOF sensor.

(729) 121. A method for analyzing the condition of an undercarriage of a vehicle using a vehicle undercarriage inspection system, the vehicle undercarriage inspection system comprising a sensor array, the sensor array comprising first, second, and third cameras, the method comprising: using a computer hardware processor to perform: obtaining, using the sensor array of the vehicle undercarriage inspection system, sensor data about the undercarriage of the vehicle captured as the vehicle and vehicle undercarriage inspection system move relative to each other, the sensor data including: first, second and third sets of images captured by the first, second and third cameras, respectively; and data indicative of the speed of the vehicle relative to the vehicle undercarriage inspection system; generating a composite image of the undercarriage of the vehicle by combining images of the first, second and third sets of images based on the speed of the vehicle; determining whether the vehicle has one or more defects by processing the composite image, using a first trained machine learning (ML) model; and generating a vehicle condition report based on results of the processing.

(730) 122. The method of aspect 121, wherein the first, second and third sets of images respectively comprise consecutive images of the undercarriage of the vehicle taken by the first, second and third cameras.

(731) 123. The method of aspect 122, further comprising: determining pixel shift distances between adjacent images of the consecutive images of the first, second and third sets of images, wherein determining the speed of the vehicle comprises determining the speed of the vehicle based on the pixel shift distances.

(732) 124. The method of aspect 123, wherein the vehicle undercarriage imaging system further comprises a sensor configured to output data indicative of a position and/or motion of the vehicle relative to the vehicle undercarriage inspection system, and the determining the speed of the vehicle is performed based on the pixel shift distances and the data indicative of the position and/or motion of the vehicle relative to the vehicle undercarriage inspection system.

(733) 125. The method of any of aspects 122-124, further comprising: determining pixel shift distances between adjacent images of the consecutive images of the first, second and third sets of images; and aligning the first, second and third sets of images using the respective pixel shift distances for the first, second and third sets of images, wherein the generating comprises combining temporally aligned images of the first, second and third sets of images.

(734) 126. The method of aspect 125, wherein aligning the first, second and third sets of images comprises: determining a difference between the pixel shift distances of the second and third sets of images and the pixel shift distances of the first set of images; and determining an alignment of the first, second and third sets of images which minimizes the difference between the pixel shift distances of the second and third sets of images and the pixel shift distances of the first set of images.

(735) 127. The method of any of aspects 122-126, further comprising: determining pixel shift distances between adjacent images of the consecutive images of the first, second and third sets of images; and determining, based on the pixel shift distances, respective first, second and third subsets of images from the first, second and third sets of images, the first, second and third subsets of images comprising images in which the vehicle is moving relative to the vehicle undercarriage inspection system, wherein generating the composite image of the undercarriage of the vehicle by combining images of the first, second and third subsets of images.

(736) 128. The method of any of aspects 121-127, wherein the one or more defects include: damage to one or more vehicle parts, presence of rust, presence of one or more aftermarket vehicle modifications, altered vehicle suspension, and/or a missing catalytic converter.

(737) 129. The method of any of aspects 121-128, further comprising: generating a 3D model of the undercarriage of the vehicle based on the first, second and third sets of images and the data indicative of the speed of the vehicle relative to the vehicle undercarriage inspection system;

generating a visualization of the 3D model; and providing access to the visualization to one or more users.

(738) 130. The method of any of aspects 121-129, further comprising: obtaining air quality data from an air quality sensor of the vehicle undercarriage inspection system; obtaining magnetic field data from a magnetometer of the vehicle undercarriage inspection system; and/or obtaining audio data from a microphone of the vehicle undercarriage inspection system, wherein determining whether the vehicle has the one or more defects comprises processing the air quality data, magnetic field data and/or the audio data using a second trained machine learning model.

(739) 131. A vehicle undercarriage inspection system for analyzing a condition of an undercarriage of a vehicle, the system comprising: a sensor array comprising: a first, second and third camera; a time-of-flight sensor configured to output data indicative of a position and/or motion of the vehicle relative to the vehicle undercarriage inspection system; and a computer hardware processor configured to perform: obtaining, from the sensor array, sensor data about the undercarriage of the vehicle captured as the vehicle and vehicle undercarriage inspection system move relative to each other, the sensor data including: first, second and third sets of images taken respectively by the first, second and third cameras; and data, captured by the time-of-flight sensor indicative of a position and/or motion of the vehicle relative to the vehicle undercarriage inspection system; generating a composite image of the undercarriage of the vehicle by combining images of the first, second and third sets of images based on the data indicative of position and/or motion of the vehicle relative to the vehicle undercarriage inspection system; determining whether the vehicle has one or more defects by processing the composite image, using a first trained machine learning (ML) model; and generating a vehicle condition report based on results of the processing.

(740) 132. The vehicle undercarriage inspection system of aspect 131, wherein the first, second and third sets of images respectively comprise consecutive images of the undercarriage of the vehicle taken by the first, second and third cameras.

(741) 133. The vehicle undercarriage inspection system of aspect 132, wherein the computer hardware processor is further configured to perform: determining pixel shift distances between adjacent images of the consecutive images of the first, second and third sets of images, wherein generating the composite image is performed based on the pixel shift distances and the data indicative of position and/or motion of the vehicle.

(742) 134. The vehicle undercarriage inspection system of any of aspects 132-133, wherein the computer hardware processor is further configured to perform: determining pixel shift distances between adjacent images of the consecutive images of the first, second and third sets of images; and aligning the first, second and third sets of images using the respective pixel shift distances for the first, second and third sets of images, wherein the generating the composite image comprises combining aligned images of the first, second and third sets of images.

(743) 135. The vehicle undercarriage inspection system of any of aspects 131-134, wherein the one or more defects include: damage to one or more vehicle parts, presence of rust, presence of one or more aftermarket vehicle modifications, altered vehicle suspension, and/or a missing catalytic converter.

(744) 136. At least one non-transitory computer-readable storage medium storing processor-executable instructions that, when executed by at least one computer hardware processor, cause the at least one computer hardware processor to perform a method for analyzing conditions of an undercarriage of a vehicle using a vehicle undercarriage inspection system, the vehicle undercarriage inspection system comprising a sensor array, the sensor array comprising first, second and third cameras, the method comprising: obtaining, using the sensor array of the vehicle undercarriage inspection system, sensor data about the undercarriage of the vehicle captured as the vehicle and vehicle undercarriage inspection system move relative to each other, the sensor data including: first, second and third sets of images captured by the first, second and third cameras, respectively; and data indicative of the speed of the vehicle relative to the vehicle undercarriage

inspection system; generating a composite image of the undercarriage of the vehicle by combining images of the first, second and third sets of images based on the speed of the vehicle; determining whether the vehicle has one or more defects by processing the composite image, using a first trained machine learning (ML) model; and generating a vehicle condition report based on results of the processing.

(745) 137. The at least one non-transitory computer-readable storage medium of aspect 136, wherein the first, second and third sets of images respectively comprise consecutive images of the undercarriage of the vehicle taken by the first, second and third cameras.

(746) 138. The at least one non-transitory computer-readable storage medium of aspect 137, wherein the method further comprises: determining pixel shift distances between adjacent images of the consecutive images of the first, second and third sets of images, wherein the generating the composite image is performed based on the pixel shift distances.

(747) 139. The at least one non-transitory computer-readable storage medium of any of aspects 137-138, wherein the method further comprises: determining pixel shift distances between adjacent images of the consecutive images of the first, second and third sets of images; and aligning the first, second and third sets of images using the respective pixel shift distances for the first, second and third sets of images, wherein the generating the composite image comprises combining aligned images of the first, second and third sets of images.

(748) 140. The at least one non-transitory computer-readable storage medium of any of aspects 136-139, wherein the one or more defects include: damage to one or more vehicle parts, presence of rust, presence of one or more aftermarket vehicle modifications, altered vehicle suspension, and/or a missing catalytic converter.

(749) 141. A method for inspecting an undercarriage of a vehicle using a vehicle undercarriage inspection system, the vehicle undercarriage inspection system comprising a sensor array comprising first, second and third cameras configured to capture images at different angles relative to the vehicle undercarriage, and a sensor configured to output data indicative of the position and/or motion of the vehicle relative to the vehicle undercarriage inspection system, the method comprising: positioning the vehicle undercarriage inspection system relative to the vehicle; moving the vehicle and the vehicle undercarriage inspection system relative to one another; triggering capture of data about the vehicle undercarriage by the sensor array of the vehicle undercarriage inspection system; capturing the data about the vehicle undercarriage using the sensor array of the vehicle undercarriage inspection system, the data about the vehicle including a plurality of images of the undercarriage of the vehicle captured by the first, second, and third cameras at the different angles relative to the vehicle undercarriage; stopping capture of the data about the vehicle undercarriage; generating, based on at least some of the plurality of images, a composite image of the vehicle undercarriage.

(750) 142. The method of aspect 141, wherein the generating is performed using the vehicle inspection system.

(751) 143. The method of any of aspects 141-142, wherein the generating comprises: providing, from the vehicle undercarriage inspection system to a computer hardware processor, separate from the vehicle undercarriage inspection system the at least some of the plurality of images for use in generating the composite image of the vehicle undercarriage.

(752) 144. The method of any of aspects 141-143, wherein the capturing comprises capturing respective first, second and third set of images using the first, second and third cameras of the sensor array.

(753) 145. The method of any of aspects 141-144, wherein the triggering comprises triggering the capture based on the data indicative of the position and/or motion of the vehicle.

(754) 146. The method of aspect 145, wherein the stopping capture is performed based on the data indicative of the position and/or motion of the vehicle.

(755) 147. The method of any of aspects 141-146, wherein the moving comprises driving the

vehicle over the vehicle undercarriage inspection system.

(756) 148. The method of any of aspects 141-146, further comprising: before the moving: positioning a vehicle exterior inspection system relative to the vehicle, the vehicle exterior inspection system comprising a support member and a plurality of sensor arrays coupled to the support member, the plurality of sensor arrays comprising respective sets of sensors oriented in different directions, wherein: the triggering comprises triggering the plurality of sensor arrays to capture sensor data about an exterior of the vehicle; the capturing further comprises capturing the sensor data about an exterior of the vehicle using the plurality of sensor arrays.

(757) 149. A method for inspecting an undercarriage of a vehicle using a vehicle undercarriage inspection system, the vehicle undercarriage inspection system comprising a sensor array comprising first, second and third cameras configured to capture images at different angles relative to the vehicle undercarriage, and a sensor configured to output data indicative of the position and/or motion of the vehicle relative to the vehicle undercarriage inspection system, the method comprising: positioning the vehicle undercarriage inspection system relative to the vehicle; triggering the vehicle undercarriage inspection system to collect alignment data of the vehicle relative to the vehicle undercarriage inspection system; generating, based on the alignment data, an indication of an alignment of the vehicle relative to the vehicle inspection system; repositioning the vehicle relative to the vehicle undercarriage inspection system based on the indication of the alignment of the vehicle relative to the vehicle inspection system; moving the vehicle and the vehicle undercarriage inspection system relative to one another; capturing sensor data about the vehicle undercarriage using the sensor array of the vehicle undercarriage inspection system, the data about the vehicle including a plurality of images of the undercarriage of the vehicle; generating, based on at least some of the plurality of images, a composite image of the vehicle undercarriage.

(758) 150. The method of aspect 149, wherein the alignment data is captured by the sensor configured to output data indicative of the position and/or motion of the vehicle.

(759) 151. The method of any of aspects 149-150, wherein the capturing is triggered based on the data indicative of the position and/or motion of the vehicle.

(760) 152. The method of aspect 151, wherein the capturing is stopped based on the data indicative of the position and/or motion of the vehicle.

(761) 153. The method of any of aspects 149-152, wherein the moving comprises driving the vehicle over the vehicle undercarriage inspection system.

(762) 154. The method of any of aspects 149-153, wherein the moving comprises moving the vehicle undercarriage inspection system beneath the vehicle.

(763) 155. The method of any of aspects 149-154, wherein the generating is performed by the vehicle undercarriage inspection system.

(764) 156. A method for inspecting an undercarriage of a vehicle using a vehicle undercarriage inspection system, the vehicle undercarriage inspection system comprising a sensor array comprising first, second and third cameras configured to capture images at different angles relative to the vehicle undercarriage, and a sensor configured to output data indicative of the position and/or motion of the vehicle relative to the vehicle undercarriage inspection system, the method comprising: moving the vehicle and the vehicle undercarriage inspection system relative to one another; capturing sensor data about the vehicle undercarriage using the sensor array of the vehicle undercarriage inspection system; providing, to a computer hardware processor, the data about the vehicle undercarriage; receiving, from the computer hardware processor, a vehicle condition report indicating one or more defects present on the vehicle; providing, to the computer hardware processor, a request for sensor data related to the one or more defects present on the vehicle; and receiving, from the computer hardware processor, a plurality of sensor data related to the one or more defects present on the vehicle.

(765) 157. The method of aspect 156, wherein: the plurality of sensor data related to the one or

more defects comprises a plurality of images of the one or more defects taken from different angles by the first, second and third cameras of the sensor array.

(766) 158. The method of aspect 157, further comprising: analyzing the vehicle to confirm a presence of the one or more defects; providing, to the computer hardware processor, an indication of the presence of the one or more defects; and receiving, from the computer hardware processor, an updated vehicle condition report.

(767) 159. The method of any of aspects 156-158, wherein the triggering is performed by the vehicle undercarriage inspection based on the data indicative of the position and/or motion.

(768) 160. The method of aspect 159, wherein the stopping capture is performed by the vehicle inspection system based on the data indicative of the position and/or motion.

Claims

1. A method for inspecting a vehicle using a vehicle inspection system, the vehicle inspection system comprising a vehicle exterior inspection system comprising a support member and a plurality of exterior sensor arrays coupled to the support member, the plurality of exterior sensor arrays comprising respective sets of sensors oriented in different directions, and a vehicle undercarriage inspection system comprising an undercarriage sensor array comprising first, second and third cameras configured to capture images at different angles relative to the vehicle undercarriage, and a sensor configured to output data indicative of the position and/or motion of the vehicle relative to the vehicle inspection system, the method comprising: moving the vehicle and the vehicle inspection system relative to one another; triggering capture, by the plurality of exterior sensor arrays and undercarriage sensor array, of sensor data about the vehicle; capturing the sensor data about the vehicle using the plurality of exterior sensor arrays and undercarriage sensor array of the vehicle inspection system; stopping capture of the sensor data about the vehicle; stopping movement of the vehicle and the vehicle inspection system relative to one another; generating a vehicle condition report based on the sensor data collected using the plurality of exterior sensor arrays and the undercarriage sensor array.

2. The method of claim 1, wherein the generating comprises generating the vehicle condition report using the vehicle inspection system.

3. The method of claim 1, wherein the generating comprises: providing to a computer hardware processor, separate from the vehicle inspection system, at least some of the sensor data collected using the plurality of exterior sensor arrays and the undercarriage sensor array.

4. The method of claim 1, wherein the triggering is performed by the vehicle inspection system based on the data indicative of the position and/or motion of the vehicle.

5. The method of claim 1, wherein the triggering comprises: triggering capture of the sensor data by the plurality of exterior sensor arrays when the vehicle is determined to be at a first position and/or distance relative to the vehicle inspection system based on the data indicative of the position and/or motion of the vehicle.

6. The method of claim 5, wherein the triggering comprises: triggering capture of the sensor data by the undercarriage sensor array when the vehicle is determined to be at a second position and/or distance relative to the vehicle inspection system, different from the first position, based on the data indicative of the position and/or motion of the vehicle.

7. The method of claim 6, wherein the second position is closer to the vehicle inspection system than the first position, and/or the second distance is smaller than the first distance.

8. The method of claim 5, wherein the stopping is performed by the vehicle inspection system based on the data indicative of the position and/or motion of the vehicle.

9. The method of claim 1, further comprising: before the moving: placing a mobile vehicle diagnostic device (MVDD) of the vehicle inspection system at an engine of the vehicle, wherein the triggering comprises triggering a sensor array of the MVDD of the vehicle inspection system to

capture the sensor data about the engine of the vehicle and the capturing comprises using the MVDD to capture the sensor data about the engine of the vehicle.

10. A method for inspecting a vehicle using a vehicle inspection system, the vehicle inspection system comprising a vehicle exterior inspection system comprising a support member and a plurality of exterior sensor arrays coupled to the support member, the plurality of exterior sensor arrays comprising respective sets of sensors oriented in different directions, and a vehicle undercarriage inspection system comprising an undercarriage sensor array comprising first, second and third cameras configured to capture images at different angles relative to the vehicle undercarriage, and a sensor configured to output data indicative of the position and/or motion of the vehicle relative to the vehicle undercarriage inspection system, the method comprising: moving the vehicle and the vehicle inspection system relative to one another; triggering capture, by the plurality of exterior sensor arrays and undercarriage sensor array, of sensor data about the vehicle; capturing the sensor data about the vehicle using the plurality of exterior sensor arrays and undercarriage sensor array of the vehicle inspection system; stopping capture of the sensor data about the vehicle; stopping movement of the vehicle and the vehicle inspection system relative to one another; processing the sensor data, using a computer hardware processor, to identify one or more vehicle defects.

11. The method of claim 10, wherein the triggering comprises: triggering capture of the sensor data by the plurality of exterior sensor arrays is performed when the vehicle is determined to be at a first position and/or distance relative to the vehicle inspection system based on the data indicative of the position and/or motion of the vehicle.

12. The method of claim 11, wherein the triggering comprises: triggering capture of the sensor data by the undercarriage sensor array is performed when the vehicle is determined to be at a second position and/or distance relative to the vehicle inspection system, different from the first position, based on the data indicative of the position and/or motion of the vehicle.

13. The method of claim 10, wherein the stopping is performed by the vehicle inspection system based the data indicative of the position and/or motion of the vehicle.

14. The method of claim 10, further comprising: before the moving: placing a mobile vehicle diagnostic device (MVDD) of the vehicle inspection system at an engine of the vehicle, wherein the triggering comprises triggering a sensor array of the MVDD of the vehicle inspection system to capture the sensor data about the engine of the vehicle and the capturing comprises using the MVDD to capture the sensor data about the engine of the vehicle.

15. A method for inspecting a vehicle using a vehicle inspection system, the vehicle inspection system comprising a vehicle exterior inspection system comprising a support member and a plurality of exterior sensor arrays coupled to the support member, the plurality of exterior sensor arrays comprising respective sets of sensors oriented in different directions, and a vehicle undercarriage inspection system comprising an undercarriage sensor array comprising first, second and third cameras configured to capture images at different angles relative to the vehicle undercarriage, and a sensor configured to output data indicative of the position and/or motion of the vehicle relative to the vehicle inspection system, the method comprising: positioning the vehicle, the vehicle exterior inspections system and the vehicle undercarriage inspection system relative to one another; triggering the vehicle inspection system to collect alignment data of the vehicle relative to the vehicle inspection system; obtaining an indication of an alignment of the vehicle relative to the vehicle inspection system based on the alignment data; based on the indication of the alignment of the vehicle, adjusting one or more of the exterior sensor arrays or the undercarriage sensor array; moving the vehicle and the vehicle inspection system relative to one another; capturing sensor data about the vehicle using the plurality of exterior sensor arrays and undercarriage sensor array of the vehicle inspection system; and processing the sensor data, using a computer hardware processor, to identify one or more vehicle defects.

16. The method of claim 15, wherein the alignment data is captured by the sensor of the vehicle

undercarriage inspection system configured to output the data indicative of the position and/or motion of the vehicle.

17. The method of claim 15, wherein the moving comprises driving the vehicle past the vehicle undercarriage inspection system and vehicle exterior inspection system.

18. The method of claim 15, wherein the moving comprises moving the vehicle exterior and vehicle undercarriage inspection systems about the vehicle.

19. The method of claim 15, further comprising: before the moving: placing a mobile vehicle diagnostic device (MVDD) of the vehicle inspection system at an engine of the vehicle, wherein the triggering comprises triggering a sensor array of the MVDD of the vehicle inspection system to capture the sensor data about the engine of the vehicle and the capturing comprises using the MVDD to capture the sensor data about the engine of the vehicle.

20. The method of claim 15, further comprising: before the processing: receiving an indication the capturing was unsuccessful; and recapturing second sensor data about the vehicle using the plurality of exterior sensor arrays and undercarriage sensor array of the vehicle inspection system.
