



US012383282B2

(12) **United States Patent**
Anderson

(10) **Patent No.:** **US 12,383,282 B2**
(45) **Date of Patent:** **Aug. 12, 2025**

(54) **DEPTH CONTROLLABLE AND MEASURABLE MEDICAL DRIVER DEVICES AND METHODS OF USE**

2090/036 (2016.02); A61B 2090/062 (2016.02); A61B 2090/066 (2016.02); A61B 2217/007 (2013.01)

(71) Applicant: **Quartus Engineering, Inc.**, San Diego, CA (US)

(58) **Field of Classification Search**
CPC A61B 17/1622; A61B 17/1624; A61B 17/1633
See application file for complete search history.

(72) Inventor: **Wayne Anderson**, Las Vegas, NV (US)

(73) Assignee: **Quartus Engineering, Inc.**, San Diego, CA (US)

(56) **References Cited**

U.S. PATENT DOCUMENTS

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

1,308,798 A 7/1919 Masland
1,831,813 A 11/1931 Levedahl
(Continued)

(21) Appl. No.: **18/828,790**

FOREIGN PATENT DOCUMENTS

(22) Filed: **Sep. 9, 2024**

CN 1688258 A 10/2005
CN 2774405 Y 4/2006
(Continued)

(65) **Prior Publication Data**

US 2024/0423645 A1 Dec. 26, 2024

OTHER PUBLICATIONS

Related U.S. Application Data

http://www.motion-control-info.com/encoder_design_guide.html. Web. Aug. 20, 2009. 8 pages.

(63) Continuation of application No. 18/073,640, filed on Dec. 2, 2022, now Pat. No. 12,108,957, which is a continuation of application No. 16/667,639, filed on Oct. 29, 2019, now Pat. No. 11,517,324, which is a continuation of application No. 15/389,186, filed on Dec. 22, 2016, now Pat. No. 10,456,146, which is a
(Continued)

(Continued)

Primary Examiner — Olivia C Chang

(74) *Attorney, Agent, or Firm* — Snell & Wilmer, L.L.P.; April Wurster

(51) **Int. Cl.**

A61B 17/16 (2006.01)

A61B 17/17 (2006.01)

A61B 90/00 (2016.01)

(52) **U.S. Cl.**


CPC A61B 17/1624 (2013.01); A61B 17/1633 (2013.01); A61B 17/17 (2013.01); A61B 90/06 (2016.02); A61B 17/162 (2013.01); A61B

(57)

ABSTRACT

Disclosed are devices and methods for creating a bore in bone. The devices and methods described involve driving a rotating bit in an axial direction such that both rotation and linear movement are controlled and measurable. The instrument is useful for a surgeon to control and simultaneously measure the travel of the tool into the bone and prevent injury to surrounding structures.

18 Claims, 6 Drawing Sheets



Related U.S. Application Data

continuation of application No. 14/473,299, filed on Aug. 29, 2014, now Pat. No. 9,526,511, which is a continuation of application No. 12/474,749, filed on May 29, 2009, now Pat. No. 8,821,493.

- (60) Provisional application No. 61/076,105, filed on Jun. 26, 2008.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,488,992	A	11/1949	Taylor	5,810,821	A	9/1998	Vandewalle
2,557,429	A	6/1951	Hawley	5,810,828	A	9/1998	Lightman et al.
2,869,403	A	1/1959	Bent	5,833,404	A	11/1998	Johnson et al.
2,883,891	A	4/1959	Shutlers et al.	5,856,922	A	1/1999	Jehanno
2,909,949	A	10/1959	Winslow	5,875,920	A	3/1999	Parent
3,083,593	A	4/1963	Cotter	5,890,897	A	4/1999	Kruger et al.
3,397,600	A	8/1968	Wells	5,894,095	A	4/1999	DeMali
3,526,158	A	9/1970	Adams et al.	5,895,389	A	4/1999	Schenk et al.
3,546,976	A	12/1970	Clapp et al.	5,941,706	A	8/1999	Ura
3,750,671	A	8/1973	Hedrick	5,961,257	A	10/1999	Bettini et al.
3,775,021	A	11/1973	Langebach	5,980,248	A	11/1999	Kusakabe et al.
3,854,836	A	12/1974	Weissman	5,993,453	A	11/1999	Bullara et al.
3,867,932	A	2/1975	Huene	5,993,454	A	11/1999	Longo
4,005,527	A	2/1977	Wilson et al.	5,997,541	A	12/1999	Schenk
4,111,208	A	9/1978	Leuenberger	6,001,115	A	12/1999	Ahola et al.
4,157,231	A	6/1979	Phillips	6,022,352	A	2/2000	Vandewalle
4,209,069	A	6/1980	Smith	6,022,356	A	2/2000	Noyes et al.
4,242,017	A	12/1980	De Fazio	6,033,409	A	3/2000	Allotta
4,288,182	A	9/1981	Vandenkieboom et al.	6,096,042	A	8/2000	Herbert
4,329,092	A	5/1982	Ponitzsch et al.	6,096,051	A	8/2000	Kortenbach et al.
4,341,206	A	7/1982	Perrett et al.	6,110,174	A	8/2000	Nichter
4,351,467	A	9/1982	White	6,146,385	A	11/2000	Torrie et al.
4,358,228	A	11/1982	Stark	6,171,312	B1	1/2001	Beaty
4,440,529	A	4/1984	Henslee et al.	6,209,886	B1	4/2001	Estes et al.
4,461,015	A	7/1984	Kulhavy	6,238,400	B1	5/2001	Bays
4,487,270	A	12/1984	Huber	6,277,135	B1	8/2001	Wang
4,534,420	A	8/1985	Goldelius	6,302,406	B1	10/2001	Ventura
4,594,030	A	6/1986	Weigel, Jr.	6,337,142	B2	1/2002	Harder et al.
4,601,518	A	7/1986	Laneus	6,342,057	B1	1/2002	Brace et al.
4,620,539	A	11/1986	Andrews et al.	6,378,626	B1	4/2002	Wallace
4,644,335	A	2/1987	Wen	6,379,364	B1	4/2002	Brace et al.
4,688,970	A	8/1987	Eckman	6,391,016	B2	5/2002	Bays
4,710,075	A	12/1987	Davison	6,416,517	B2	7/2002	Harder et al.
4,723,911	A	2/1988	Kurtz	6,436,103	B1	8/2002	Suddaby
4,728,876	A	3/1988	Mongeon et al.	6,473,962	B1	11/2002	Beduhn
4,736,742	A	4/1988	Alexson et al.	6,484,814	B2	11/2002	Bongers-Ambrosius
4,749,314	A	6/1988	LeBlond	6,514,018	B2	2/2003	Martinez et al.
4,752,161	A	6/1988	Hill	6,527,778	B2	3/2003	Athanasίου et al.
4,852,434	A	8/1989	Bald	6,536,536	B1	3/2003	Gass et al.
4,854,786	A	8/1989	Alexander et al.	6,547,562	B2	4/2003	Kumar
4,854,873	A	8/1989	Linden	6,565,293	B2	5/2003	Desmoulins
4,961,674	A	10/1990	Wang et al.	6,605,092	B2	8/2003	Grumberg et al.
5,014,793	A	5/1991	Germanton et al.	6,610,067	B2	8/2003	Tallarida et al.
5,071,293	A	12/1991	Wells	6,635,060	B2	10/2003	Hanson et al.
5,405,348	A	4/1995	Anspach, Jr. et al.	6,645,227	B2	11/2003	Fallin et al.
5,409,493	A	4/1995	Greenberg	6,665,948	B1 *	12/2003	Kozin A61B 90/06 175/45
5,411,503	A	5/1995	Hollstien et al.	6,702,531	B2	3/2004	Linderholm
5,454,811	A	10/1995	Huebner	6,702,818	B2	3/2004	Kupferschmid et al.
5,482,411	A	1/1996	McGlasson	6,758,642	B2	7/2004	Linderholm et al.
5,533,842	A	7/1996	Johnson et al.	6,776,562	B2	8/2004	Morrison et al.
5,538,423	A	7/1996	Coss et al.	6,783,532	B2	8/2004	Steiner et al.
5,554,154	A	9/1996	Rosenberg	6,786,683	B2	9/2004	Schaer et al.
5,569,254	A	10/1996	Carlson et al.	6,849,071	B2	2/2005	Whitman et al.
5,575,793	A	11/1996	Carls et al.	6,872,036	B2	3/2005	Linderholm
5,599,142	A	2/1997	Fujimoto et al.	6,874,980	B1	4/2005	Noelle et al.
5,613,810	A	3/1997	Bureller	6,925,725	B2	8/2005	Herrmann et al.
5,653,712	A	8/1997	Stern	6,951,562	B2	10/2005	Zwirnmann
5,658,292	A	8/1997	Axelsson, Jr.	6,974,481	B1	12/2005	Carson
5,667,509	A	9/1997	Westin	7,004,943	B2	2/2006	Ferrante et al.
5,669,915	A	9/1997	Caspar et al.	7,011,661	B2	3/2006	Riedel et al.
5,697,158	A	12/1997	Klinzing et al.	7,021,933	B2	4/2006	Caldwell
5,725,530	A	3/1998	Popken	7,033,363	B2	4/2006	Powell
5,755,537	A	5/1998	Lubbering	7,048,477	B2	5/2006	Abrams
5,755,721	A	5/1998	Hearn	7,066,940	B2	6/2006	Riedel et al.
				7,073,989	B2	7/2006	Erickson et al.
				7,081,119	B2	7/2006	Stihl
				7,094,242	B2	8/2006	Ralph et al.
				7,108,459	B1	9/2006	Mueller
				7,111,411	B2	9/2006	Knopfle et al.
				7,121,773	B2	10/2006	Mikiya et al.
				7,150,751	B2	12/2006	Lechot
				7,163,542	B2	1/2007	Ryan
				7,179,259	B1	2/2007	Gibbs
				7,188,431	B2	3/2007	Herrmann et al.
				7,210,881	B2	5/2007	Greenberg
				7,226,450	B2	6/2007	Athanasίου et al.
				7,235,940	B2	6/2007	Bosch et al.
				7,258,692	B2	8/2007	Thelen et al.

(56)

References Cited**U.S. PATENT DOCUMENTS**

7,303,363	B2	12/2007	Krause et al.
7,331,406	B2	2/2008	Wottreng, Jr. et al.
7,497,860	B2	3/2009	Carusillo et al.
D593,389	S	6/2009	Clayton
7,578,642	B2	8/2009	Fritsche et al.
7,641,000	B2	1/2010	Albert
7,670,328	B2	3/2010	Miller
7,681,659	B2	3/2010	Zhang et al.
8,167,518	B2	5/2012	Mathis et al.
8,394,099	B2	3/2013	Patwardhan
8,444,647	B2	5/2013	Walen et al.
8,511,945	B2	8/2013	Apkarian et al.
8,529,567	B2	9/2013	Garcia et al.
8,562,635	B2	10/2013	Tanner et al.
8,821,493	B2	9/2014	Anderson
8,894,654	B2	11/2014	Anderson
9,204,885	B2	12/2015	McGinley et al.
9,526,511	B2	12/2016	Anderson
9,877,734	B2	1/2018	Anderson
10,245,043	B2	4/2019	Xie
10,736,643	B2	8/2020	Anderson et al.
11,517,324	B2	12/2022	Anderson
11,839,385	B2	12/2023	Anderson et al.
2001/0016744	A1	8/2001	Kupferschmid et al.
2001/0047219	A1	11/2001	Oden
2002/0038124	A1	3/2002	Lee
2003/0049082	A1	3/2003	Morrison et al.
2003/0143042	A1	7/2003	Doyle et al.
2003/0229354	A1	12/2003	Schmieding et al.
2003/0233098	A1	12/2003	Markworth
2004/0049128	A1*	3/2004	Miller A61B 10/0275 600/566
2004/0059317	A1	3/2004	Hermann
2004/0146367	A1	7/2004	Gerhardt et al.
2004/0179829	A1	9/2004	Phillips et al.
2004/0179910	A1	9/2004	Theising et al.
2004/0193173	A1	9/2004	Knopfle et al.
2004/0215395	A1	10/2004	Strasser et al.
2004/0265082	A1	12/2004	Abrams
2005/0116673	A1	6/2005	Carl et al.
2005/0131415	A1*	6/2005	Hearn B25B 23/147 606/80
2005/0169717	A1	8/2005	Field
2005/0171504	A1	8/2005	Miller
2005/0171553	A1	8/2005	Schwarz et al.
2005/0192585	A1	9/2005	Simmons
2005/0261693	A1	11/2005	Miller et al.
2006/0085005	A1	4/2006	Kenealy et al.
2006/0096767	A1	5/2006	Miller
2006/0104731	A1	5/2006	Etter et al.
2006/0106363	A1	5/2006	Aravena et al.
2006/0217729	A1	9/2006	Eskridge et al.
2006/0224161	A1	10/2006	Bhattacharyya
2006/0241628	A1	10/2006	Parak
2006/0269372	A1	11/2006	Goshima
2007/0135803	A1	6/2007	Belson
2007/0217879	A1	9/2007	Larsson

2008/0027449	A1	1/2008	Gundlapalli et al.
2008/0077149	A1	3/2008	Hoegerle
2008/0119860	A1	5/2008	McCarthy
2008/0245159	A1	10/2008	Garshelis et al.
2008/0269755	A1	10/2008	Malackowski et al.
2009/0093830	A1	4/2009	Miller
2009/0162158	A1	6/2009	Glodowski et al.
2009/0196696	A1	8/2009	Otsuka et al.
2009/0245956	A1	10/2009	Apkarian et al.
2009/0297284	A1	12/2009	Brown et al.
2009/0326537	A1	12/2009	Anderson
2010/0114288	A1	5/2010	Haller et al.
2010/0160924	A1	6/2010	Soliman
2011/0245833	A1	10/2011	Anderson
2011/0301611	A1	12/2011	Garcia et al.
2012/0059378	A1	3/2012	Farrell
2012/0123418	A1	5/2012	Giurgi et al.
2013/0096561	A1	4/2013	Miller et al.
2013/0110117	A1	5/2013	Soliman
2013/0165937	A1	6/2013	Patwardhan
2014/0371752	A1	12/2014	Anderson
2015/0080966	A1	3/2015	Anderson
2015/0257808	A1	9/2015	Sweeney
2017/0231644	A1	8/2017	Anderson
2018/0140308	A1	5/2018	Anderson
2019/0013830	A1	1/2019	Hoglund et al.
2019/0029697	A1	1/2019	Anderson et al.
2019/0247057	A1	8/2019	Anderson
2020/0060694	A1	2/2020	Anderson

FOREIGN PATENT DOCUMENTS

EP	2392269	A1	12/2011
JP	59-196105	A	11/1984
JP	2000516109	A	12/2000
WO	1997024991	A1	7/1997
WO	1998018390	A1	5/1998
WO	2003101322	A1	12/2003
WO	2004019785	A2	3/2004
WO	2009158115	A1	12/2009
WO	2015006296	A1	1/2015

OTHER PUBLICATIONS

U.S. Notice of Allowance in U.S. Appl. No. 18/073,640 dated Jun. 21, 2024.

AU: Examination Report dated Aug. 21, 2024 in Australian Patent Application No. 2023208149 (4 pages).

AU: Examination Report dated Oct. 11, 2024 in Australian Patent Application No. 2023208149 (3 pages).

Mínguez, "The Work-Energy Theorem and the First Law of Thermodynamics," International Journal of Mechanical Engineering Education. 33(1):77-82 (2005) DOI:10.7227/IJME.33.1.8.

U.S. Non-Final Office Action in U.S. Appl. No. 18/828,756 dated Nov. 1, 2024 (32 pages).

U.S. Notice of Allowance in U.S. Appl. No. 18/828,756 dated Feb. 20, 2025 (12 pages).

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7A




FIG. 7B

DEPTH CONTROLLABLE AND MEASURABLE MEDICAL DRIVER DEVICES AND METHODS OF USE

CROSS REFERENCE TO RELATED APPLICATIONS

This application is a continuation of U.S. application Ser. No. 18/073,640, filed Dec. 2, 2022, which is a continuation of Ser. No. 16/667,639, filed Oct. 29, 2019, now U.S. Pat. No. 11,517,324, which is a continuation of U.S. application Ser. No. 15/389,186, filed Dec. 22, 2016, now U.S. Pat. No. 10,456,146, which is a continuation of U.S. application Ser. No. 14/473,299, filed Aug. 29, 2014, now U.S. Pat. No. 9,526,511, which is a continuation of U.S. application Ser. No. 12/474,749, filed May 29, 2009, now U.S. Pat. No. 8,821,493, which claims the benefit of priority of U.S. Provisional Patent Application Ser. No. 61/076,105, filed Jun. 26, 2008. The filing dates and subject matter of each of the above-noted applications is incorporated by reference in their entirety by reference thereto.

BACKGROUND

Orthopedic surgery can require bone drilling for the repair of fractures or insertion of implants or other devices. The resulting holes are needed to accept screws, implants and other devices to exert pressure, fixation or reduction of the bone. During any procedure where a drill or other driver is used to advance a tool into and through bone, the operator must consciously and carefully limit the penetration to the desired depth. If the operator allows the tool to penetrate further, the patient can suffer injury to distal structures such as nerve, brain, spinal cord, artery, vein, muscle, fascia, bone or joint space structures. These types of injuries can lead to severe patient morbidity and even death. The devices inserted to a drilled bore often must fit within a narrow length range that can vary sometimes by no more than a millimeter or less.

Once the drilling of a bone is safely complete, it is often prudent to obtain the depth of the bore made by the drilling tool. Many procedures require knowledge of the depth of tool penetration, such as in the placement of internal fixation devices, screws and other implantable hardware. Selecting an appropriate length of the screw or other implant necessary for the procedure depends upon such knowledge of the bore's depth. Conventional techniques used in the art are often inconvenient, time consuming and unreliable often requiring trial and error and multiple exposures to radiographs before the proper implant insertion is achieved.

A common way to obtain the depth of the bore formed by a drilling tool is to use a depth gauge. Often surgeons must interrupt the drilling procedure in order to palpate or measure with a depth gauge whether or not the desired depth has been achieved. In many instances a surgeon will take a radiograph during a drilling procedure to confirm the appropriate depth of penetration has been achieved or take a radiograph while the depth gauge is in place to ensure the information the gauge provides is accurate. Depth gauges used in the art can be inaccurate resulting in a surgeon placing a screw of an inappropriate length not often identified until a confirming radiograph is taken. Each radiograph taken increases the radiation exposure of the surgeon, staff and patient in the operating suite. Depth gauges known in the art can also break and require the surgeon to retrieve it from the bore. Inconvenient and inaccurate depth measurement devices and methods known in the art can result in

improperly sized screws that must be removed and replaced with new properly sized screws. Wasted hardware, increased disruptions and delays in orthopedic procedures ultimately increase the expense of a procedure as well as exposing the surgeon, staff and the patient to unnecessary radiation. The cost of the additional time, the wasted hardware and the radiation exposure are quite significant.

SUMMARY

All the techniques known in the art to drill holes in bone are technically demanding and require separate measuring steps that interrupt the actual drilling of the bone adding time, cost and need for additional confirming radiographs to complete such procedures. There remains a need for safer, controlled drilling methods and devices. There is also a need for an instrument that simultaneously controls and measures the depth of penetration of the instrument during procedures such as placement of internal fixation devices, screws, and other implantable hardware.

In an embodiment, disclosed is a medical drilling device having a housing including a hand-held portion near a proximal end of the housing; an engagement portion near a distal end of the housing; and an actuator. The device also includes an axial drive shaft extending through a region of the housing between the proximal and distal ends; a first drive element coupled to a region of the axial drive shaft; a rotational drive shaft extending through a region of the housing between the proximal and distal ends; a second drive element coupled to a region of the rotational drive shaft; a coupler interchangeably connected to a working tool and the rotational drive shaft, the coupler extends beyond the engagement portion of the housing; a transducer; and an electronics package. In another embodiment, the medical drilling device further includes a drill guide assembly including a drill guide; a forward surface guide and a rear surface guide. The drill guide surrounds the working tool and a distal region of the forward surface guide couples to the drill guide and a proximal region of the forward surface guide couples to the rear surface guide, and the rear surface guide couples to the axial drive shaft.

Also disclosed are methods for creating a bore in bone. In an embodiment the method includes providing a device comprising a housing having a hand-held portion near a proximal end and an engagement portion near a distal end; an axial drive shaft extending through a region of the housing between the proximal and distal ends; a first drive element coupled to a region of the axial drive shaft; a rotational drive shaft extending through a region of the housing between the proximal and distal ends; a second drive element coupled to a region of the rotational drive shaft; a transducer and an electronics package. The method also includes coupling a distal end of the rotational drive shaft to a working tool that is interchangeably connected to the rotational drive shaft by way of a coupler that can extend beyond the engagement portion of the housing. The method also includes dissecting tissue to create an exposed surface of a bone; contacting the engagement portion of the device to the exposed surface of bone; zeroing the transducer; actuating the second drive element to engage and rotate the rotational drive shaft; actuating the first drive element to engage the axial drive shaft to travel axially; creating a bore in the bone with the working tool; reading a display of metering information provided instantaneously from the transducer, the metering information comprising a measure of depth of the working tool into the bore; and removing the working tool from the bore.

3

Other features and advantages will be apparent from the following description of various embodiments, which illustrate, by way of example, the principles of the disclosed devices and methods.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view of one embodiment of a drilling device.

FIG. 2 is a perspective view of the distal end of the embodiment of the device shown in FIG. 1 demonstrating coupler extension.

FIG. 3 is a perspective view of the distal end of an embodiment of the device having an attachable/detachable guide with irrigation nozzles.

FIG. 4 is a perspective view of the distal end of the device shown in FIG. 2 in which the coupler is extended outside of the body tube.

FIG. 5 is a perspective view of an embodiment of a rotary encoder shown in FIG. 1.

FIG. 6 is a perspective, exploded view of another embodiment of a drilling device.

FIGS. 7A-7B are perspective views of the drilling device of FIG. 6.

DETAILED DESCRIPTION

This disclosure relates to a surgical instrument for preparing a bore in animal tissue. Specifically, the disclosure relates to a surgical instrument that drives a rotating tool in which both rotation and linear, axial movement are controlled and measurable. The instrument has both a rotational drive and an axial drive, each of which are controllable by the surgeon. The instrument is useful for enabling a surgeon to control and simultaneously measure the travel of the tool and prevent injury to surrounding structures. Controlling the rotational speed of the drive can be important to reduce the risk of heating surrounding tissue and bone, for example to the point of causing localized burns. Controlling the axial motion can also be important in the prevention of penetrating injuries, for example, to structures distal of the target such as nerve, brain, spinal cord, artery, vein, muscle, fascia, bone or joint space structures.

FIG. 1 illustrates a perspective view of one embodiment of an instrument 10. The instrument 10 can include a body 20 that houses a drive shaft 40 and two drive motors 30, 60. Drive motor 30 can be a fixed axial drive motor. Drive motor 30 powers the drive shaft 40, which in turn axially moves the second motor 60. The second drive motor 60 can be a slidable, rotational drive motor. The drive shaft 40 can include a jack screw, ball screw or lead screw and the like. The second drive motor 60 can be fixed against rotational movement and provide for the eventual rotational movement of the working tool 110 located near the distal end of the body 20, described in more detail below. Although the embodiments shown herein use motors, powered by a battery 160, it should be appreciated that other power systems are to be considered, for example pneumatic motors powered by a nitrogen gas source, electrical motors and the like.

The working tool 110 can be, for example a drill bit, Kirshner wire, trochar, burr, reamer, screw driver or other tools. The tool 110 can be made of materials such as titanium metal or stainless steel. A tool made of metal material can be sterilized and reused. Alternatively, the tools 110 can be made of polymeric material that can be discarded after each use. The material can be chosen to provide the necessary strength to allow the proper tool action.

4

The body 20 of the instrument 10 is shown as a hollow tube having a pistol grip although other configurations are considered herein, for example a straight-bodied instrument. As shown in FIG. 1, the body 20 includes an engagement end 120 near the distal end of the body 20. Proximally the body 20 includes an end piece 150. The end piece 150 can be removed to gain access to the proximal region of the body 20 in order to clean or remove the modular portions of the instrument 10 near the proximal portion such as the drive shaft 40 and the drive motor 30.

A coupler 90 can be housed within the body 20 of the instrument 10 near the distal engagement end 120. The coupler 90 can be rotatably driven and is configured to connect the working tool 110 to the instrument 10. The coupler 90 can be a chuck device such as a common three-jaw chuck in which the jaws grasp the upper portion of the tool 110 and hold it firmly in place. The coupler 90 can be actuated to open or close the jaws by a rotation mechanism or a key or other techniques known in the art. The coupler 90 could also be a quick release type of chuck or coupler.

The coupler 90 can be housed within the body 20 or it can extend beyond the distal engagement end 120 of the body 20 to be accessed external to the body 20 of the instrument 10 (see FIGS. 2 and 4). This accessibility of the coupler 90 externally from the body 20 of the instrument 10 allows for the operator to make reliable connections between the working tool 110 and the coupler 90. The exterior access can also allow for shorter, safer driven tools than if the coupler 90 was internal to the instrument body 20. Additionally, the exterior access can provide for ease of cleaning of this part of the instrument 10.

The drive motor 30 can be housed inside the body 20 and turned on by a drive motor actuator 32. In one embodiment, the drive motor actuator 32 can be a depressible trigger on the handle of the body 20. In an embodiment the speed of the drive motor 30 can be proportional to the degree of actuation of the trigger 32, for example depression of the trigger.

The drive shaft 40 can be a jack screw, ball screw, lead screw and the like and is controlled by the drive motor 30. The drive shaft 40 converts rotary movement of the drive motor 30 to linear movement. The drive shaft 40 can be made to move either in a forward direction or reverse direction that is substantially parallel to the axis of the instrument 10 or tool 110. The direction the drive shaft 40 moves can be determined, for example by the position of a switch 34 changed from the forward or reverse direction.

The drive shaft 40 can translate the torque of the drive motor 30 into thrust of the drive shaft 40. The operator can change the thrust of the drive motor 30, for example, by letting up or pressing down on the trigger 32. The operator can also change the thrust of the instrument by pushing down or letting up on the axial pressure being applied to the instrument. In an embodiment, tissue resistance as compared to axial pressure on the instrument applied by the operator can cause/allow the relative position of the handle of the instrument to feel as if it were backing out of the work as the tool is axially extended from the instrument. This can require the operator to apply additional axial pressure to drive the tool through the tissue. The torque as related to the rotating tool 110 can also change during use of the instrument. This change provides feedback to the operator who in turn can make appropriate adjustments to the axial and rotational movements as needed. In an embodiment, the torque can be changeable, programmable and measurable.

In addition to having control over the speed of rotation, the axial motion of the drive shaft 40 can be controlled and

measured. The movement and position of the drive shaft **40** can be measured and displayed such as, for example, by a transducer **39** providing information for display such as by a removable electronics package **36** (described in more detail below). The measurement can be zeroed by the operator prior to use, for example, by depressing the axial measurement selector/reset button **38**. This allows the operator to zero the measurement according to the length of the selected tool **110**.

The instrument **10** provides the surgeon with instantaneously metered axial motion as the tool **110** penetrates the tissue. The axial motion can be metered by a transducer **39**, such as an incremental rotary encoder or absolute rotary encoder (see for example BEI Optical encoder; www.motion-control-info.com/encoder_design_guide.html). The rotation of the jack screw, ball screw or lead screw can be measured and a multiplication performed to determine the distance traveled. This distance can be compared to a set point or zero point. Then, the position of the tool from the distal end of the instrument can be calculated. This calculation relates to depth as determined by the position of the distal end of the instrument with respect to the target tissue (e.g. bone).

In one embodiment, the distal end of the tool **110** is aligned with the distal end of the body **20** and the instrument zeroed. This can be performed manually by the surgeon or electronically with set points and a feedback system (i.e. interface with the coupler). The alignment of the distal end of the tool **110** and the distal end of the body **20** can be such that the two are flush with one another or the distal end of the tool **110** can be some distance beyond the distal end of the body **20**, for example

3-7 mm. The tool **110** can be positioned flush against the bone prior to drilling. As the tool **110** advances into the bone, the instrument **10** can be pushed flush against the bone. Alternatively, a drill guide **170** can be used such that the bulk of the instrument is focused into a smaller area of contact, see for example FIG. **3**. The drill guide **170** can also fit into a fixation plate for use by the surgeon. The drill guide **170** can fit into the fixation plate by directly pressing or screwing it into one or more of the holes on the fixation plate. The controlled depth medical drilling device can then be connected to the drill guide **170** and the tool **110** aligned with the distal end of the drill guide **170** and fixation plate complex and the instrument zeroed. Once the cut is started and the tool **110** is flush with the bone, the surgeon can use the axial drive to further advance the tool through the bone.

Instantaneous metering of the bore as the tool **110** penetrates the tissue provides an advantage when selecting implants for insertion. For example, the length of the drilling hole and subsequently the length of the implant needed are simultaneously metered upon creating the bore. This eliminates the need for an additional step of measuring with a separate device the depth of the bore created. For example, depth gauges known in the art can frequently provide false measurements. Consequently, surgeons can select the wrong size implant for insertion requiring them to remove it and reinsert a different sized implant. Depth gauges known in the art are also prone to breakage, which can lead to additional time usage and patient morbidity. Controlling and metering the depth of the bore as it is being created prevents repeated trials of implant fixation and eliminates the trial-and-error process of selecting the correct implant for the procedure and improves patient safety. The instrument **10** also saves operating time and the need for additional procedures like repeated radiographs in determining implant size. Because estimates of operating room costs for the personnel alone

can be as high as \$25 per minute even small savings of time in an operating room can result in large savings of money.

Use of the device and method described herein provides an added benefit of reducing the number of radiographs needed in the operating room. Intra-operative radiographs and radiation exposure are one of the major occupational risks to surgeons and operating room staff. Radiation exposure of this type has been shown to lead to radiation dermatitis, cataracts, skin cancers, leukemia and other cancers. By using a device and method such as that described herein the number of radiographs needed per procedure is reduced as is the life-time exposure of surgeons and staff to x rays. This reduced radiation exposure ultimately lowers chronic radiation exposure and the risk of radiation-related illnesses in surgeons and their staff.

As mentioned above, the drive motor **60** can be a slidable, rotational drive motor. The drive motor **60** can be housed in the body **20** and connected to the drive shaft **40** by way of a detachable coupler **50**. As best shown in FIG. **4**, the drive motor **60** can extend up to the distal end of the body **20** and allow for actuation of a release **52** on the coupler **50**. When the release **52** is depressed, the operator can disconnect the drive motor **60** from the drive shaft **40** and remove it from the body **20** of the instrument **10**. The drive motor **60**, the drive shaft **80**, the coupler **90** and the tool **110** can be modular and can be completely separated from the body **20** of the instrument **10**. This allows for interchanging parts as well as cleaning and sterilizing the elements of the instrument **10**.

The drive motor **60** can be turned on by actuator **62**. In one embodiment, the actuator **62** can be a depressible trigger on the handle of the body **20**. In an embodiment the speed of the drive motor **60** can be proportional to the degree of actuation of the trigger **62**, for example depression of the trigger. The drive shaft **60** can be a slidable, rotational drive motor that can be made to rotate either in a clockwise or counterclockwise direction as determined by the position of the forward/reverse switch **34**, as described above.

In an embodiment, the instrument can include a meter that measures the rotational speed (see for example the speed device described in U.S. Pat. No. 4,723,911), acceleration, deceleration or torque. The meter can provide the surgeon information pertaining to the passage through different layers of tissue. For example, movement of the drill bit through cortical bone into medullary bone, medullary bone to cortical bone, or from cortical bone to soft tissue. The device provides rotation and gradual advancement providing the surgeon with a feel for the type of tissue being passed therethrough, whether it is dense cortical bone or spongy medullary bone.

In one embodiment, the axial motion can be measured using a transducer or rotary encoder **39**. The encoder **39** can measure rotation and convert that information into axial motion. In an embodiment, the rotary encoder **39** includes a bearing housing assembly **201**, a light source **202**, a code disc **203**, a mask **204**, a photodetector assembly **205**, an electronics board **206** that rotate around shaft **208** (see FIG. **5**). In an embodiment, the rotary encoder is an incremental rotary encoder with dual channels in quadrature with an additional data track to provide an internal position reference for setting a "zero point". The rotary encoder **39** can interface with the drive motor **30** and the drive shaft **40**. The rotary encoder **39** can provide instantaneous information on the position of the drive shaft **40** regarding the depth of axial movement of the working tool into a bore. This information can be fed to the removable electronics package **36** that can perform count multiplication to determine the tool position.

This rotary encoder **39** can be removable from the body **20** for cleaning and/or repair. The rotary encoder **39** can be mechanical, magnetic, electrical or optical.

In another embodiment, time can be added to the values measured by the rotary encoder. Measuring time can allow for velocity and acceleration to be computed by the removable electronics package **36**. The information measured can be displayed by the removable electronics package **36** and provide the surgeon with information pertaining to the passage of the tool through different layers of tissue. For example, movement of the drill bit through cortical bone into medullary bone, medullary bone to cortical bone or from cortical bone to soft tissue. In another embodiment a torque sensor could be applied to the drive motor **60** and provide the surgeon with information pertaining to the passage of the tool through varied layers of tissue.

In addition to automatically measuring depth of penetration during use, the surgeon can control the depth of penetration of the device. In an embodiment, the depth of penetration of the device can incorporate electronics adapted to control the depth of axial movement of the tool **110** into the bore. In an embodiment, the maximum depth of the bore that is to be created by the device can be programmed in advance of drilling with electronics. In an embodiment, the surgeon can feed distally a portion of the working tool **110**, for example 30 mm if working on a tibia or femur or 12 mm if working on a radius. The surgeon would then drill through the bone as with an axially static drill. Upon reaching that pre-programmed depth, if the distal cortex had not yet been breached, the axial drive can be used to penetrate the bone further. In another embodiment, the electronics could contain a preset maximum distance that would limit the distal travel of the tool **110**. For example, a stop and go signal (i.e. single click of the trigger) or a double stop and go (i.e. double click of the trigger) could release the depth stop and allow further travel. Any of a variety of schedules could be programmed into the electronics to control distal advancement of the tool. For example, using a schedule similar to a snooze alarm system of a typical clock radio could be useful. Each time the tool **110** is advanced after the initial stop the electronics could be programmed to allow only a further distal travel of for example 3 mm or 6 mm or other incremental distance.

Identifying the desired depth of penetration for pre-programmed embodiments can be determined as is known in the art. For example, knowing the age and size of a patient or the typical size of the target tissue from pre-op radiographs and CT scans provide useful information for knowing the desired depth of penetration. A surgeon can also estimate to approximately 70-80%, depending on the bone, that would result in travel through the proximal cortex, the medullary bone and close to or into the distal cortex. Once within the distal cortex, where a great amount of control is needed, the axial drive of the instrument can be used to slowly proceed until a pop is felt or a change in speed can be heard in the drill. This can be augmented by acceleration or torque measurements. For example, as the drill bit penetrates to the very last layers of the distal cortex it can begin to accelerate with a burst of acceleration as it breeches the distal cortex completely, this could also be sensed as a change in torque. The instrument can provide its own auditory output to accentuate the sometimes subtle auditory changes caused by the drill bit. Upon reaching the predetermined target depth, axial movement can slow or stop while rotational movement can continue. The surgeon can

override any pre-programmed limitations by actuation/triggers on the device without changing hand positions to continue.

The drive motor **60** can be held rotationally still by the anti-rotation conducting flanges **70**. In an embodiment, the flanges **70** slide within channels in the body **20**. In an embodiment, each channel can have an opposite polarity such that they conduct electricity from a power source, such as a rechargeable battery **160** in the handle of the body **20**, to the drive motor **60**. In another embodiment, the power can be separate from the conducting flanges. The anti-rotation conduction flanges can also be spiral shaped and travel through spiral grooves to add stability. The anti-rotation conduction flanges can also be excluded from the device and the rotational drive motor fixed to the axial drive shaft. This would result in the drive motor to turn with the axial drive shaft.

A drive shaft **80** can be connected to and driven by the drive motor **60**. The drive shaft **80** can be also connected to the coupler **90** that holds the tool **110**. The coupler **90** is stabilized within the body **20** by bearings **100**. The bearings **100** can be axially slidable and stabilizing.

In an embodiment, the instrument can include an irrigation system. The irrigation system can include one or more irrigation nozzles **130**, an irrigation port **140**, and an irrigation actuator **142**. The irrigation actuator **142** can be a depressible trigger on the handle of the body **20**. The actuator **142** can turn on the flow of irrigation through the nozzles **130** to be delivered to the surgical field. The irrigation nozzles **130** can be located at or near the engagement end **120** of the body **20**. The irrigation nozzles **130** can be connected through the irrigation port **140** to a sterile fluid bag and sterile tubing (not shown). The irrigation fluid can be delivered to the irrigation port **140** via a sterile fluid bag and sterile tubing. An external fluid pump or gravity can be used to pressurize the irrigation system. The irrigation system can be kept outside the sterile surgical field except, for example, for the sterile tubing connected to the instrument. Such an arrangement can contribute to the engagement end **120** and the tool **110** remaining relatively free from bulk or other awkward equipment enabling more accurate placement and easy use of the instrument **10** in the surgical field.

The irrigation nozzles **130** allow for the surgical field to be kept cool while the instrument is in use. In one embodiment, the irrigation nozzles **130** spray fluid from the tip of the instrument. In another embodiment, the irrigation nozzles **130** can be routed internally through the tool **110** and sprayed from channels near the distal end of the tool. The irrigation nozzles **130** reduce the risk of tissue damage at the site of use such as bone burning and bone death. The irrigation nozzles **130** also can reduce the risk of hardware failure, the need for re-operation, infection, limb loss and death. The instrument can also include a means for suction at or near the surgical field. Suction means can be applied through the nozzles **130** of the irrigation system or can be applied through additional channels.

With respect to FIG. 3, one embodiment of the instrument **10** can include an attachable/detachable guide **170** with or without irrigation nozzles **130**. The guide **170** can provide for a smaller diameter at its distal end with which to engage the surgical field compared to the distal end of the body. The electronics package **36** can be zeroed as described above to include the additional axial length of the guide **170**.

In use, the drive shaft **40** axially drives the drive motor **60**, which rotates the drive shaft **80**, which rotates that coupler **90** which rotates the tool **110**. The drive shaft **40** is driven in

an axial direction by the drive motor **30**. In turn, the tool **110** rotates and is also axially translated along the longitudinal axis of the tool. Both the rotational movement and axial displacement of the tool **110** can be controlled in a gradual and steady manner.

FIG. **6** illustrates another embodiment of an instrument **200** that allows a surgeon to instantaneously control and measure the depth of the bore. As with the previous embodiments, this embodiment of the device eliminates the extra, unreliable, time-consuming and hazardous steps of using a depth gauge with or without a confirming radiograph. The instrument **200** includes a body **210** that houses two drive motors **230**, **260**, a rear and forward surface guide **300**, **302** and a drill guide **370**. Although the embodiments shown herein use motors, it should be appreciated that other power systems are to be considered, for example pneumatic motors powered by a nitrogen gas source, electrical motors and the like.

Drive motor **230** can be an axial drive motor and spindle **231**. Drive motor **230** and spindle **231** is seated in the rear of the body **210** and is attached to drive lug **240**. The drive motor spindle **231** can function like a jackscrew, a ball screw, a lead screw or the like. The axial drive motor **230** powers the drive lug **240** in an axial direction, which in turn drives the rear surface guide **300**, the forward surface guide **302** and the drill guide **370** all in an axial direction.

The second drive motor **260** can be a rotational drive motor and spindle **261**. The second drive motor **260** is seated in the front of the body **210**. The second drive motor **260** rotationally drives the coupler or chuck **290** and eventually the tool **310**. The coupler or chuck **290** can be a chuck device such as a common three-jaw chuck in which the jaws grasp the upper portion of the tool **310** and hold it firmly in place. The coupler or chuck **290** can be actuated to open or close the jaws by a rotation mechanism or a key or other techniques known in the art. The coupler or chuck **290** can be a quick release type of chuck or coupler. The coupler or chuck **290** can connect to a working tool **310**. A coupler or chuck extension **280** can also be included.

The working tool **310** can be, for example a drill bit, Kirshner wire, trochar, burr, reamer, screwdriver or other tools. The working tool **310** can be made of materials such as titanium metal or stainless steel. A tool **310** made of metal material can be sterilized and reused or discarded after each use. Alternatively, the tools **310** can be made of polymeric material that can be sterilized and reused or discarded after each use. The material can be chosen to provide the necessary strength to allow the proper tool action. The working tool **310** fits through the distal end of the forward surface guide **302** extending through the drill guide **370** to engage the work.

The depth the tool **310** travels into the work can be measured by a mechanical, magnetic, electrical or optical rotary encoder, or the like. The rotary encoder can be an incremental rotary encoder or an absolute rotary encoder. The depth the tool **310** travels into the work can also be measured by a synchro, a resolver, a rotary variable differential transformer (RVDT) or a rotary potentiometer, or the like. As mentioned above, information regarding use of the instrument can be relayed in real-time to a display **236** with removable electronics package that can be found in the body **210** of the instrument **200** providing instantaneous information such as bore depth during drilling. The display **236** can include an LED or other display using, for example, electrical filaments, plasma, gas or the like.

The rear surface guide **300** attaches to the drive lug **240** at its proximal end and the forward surface guide **302** at its

distal end. There can be one or more o-rings **250** between the two surface guides **300**, **302**. In another embodiment the surface guides **300**, **302** can be a single unit. The surface guides **300**, **302** shown in the drawings have two "arms" or supports that extend axially. But it should be appreciated that the surface guides **300**, **302** can have one, two, three or more arms that provide additional support to bear the load. The forward surface guide **302** can engage the outside of the coupler or chuck **290**. In an embodiment the coupler or chuck **290** includes a sleeve and/or stabilizing flanges. In another embodiment, the coupler or chuck **290** can function without a sleeve or stabilizing flanges. In that embodiment the forward surface guide **302** can have a bushing or other device to engage the coupler or chuck **290** directly and still allow the coupler or chuck **290** to spin freely.

The drill guide **370** connects to the distal end of the forward surface guide **302**. The drill guide **370** can engage bone, fracture plates or other implants. A drill guide that screws into a fracture plate can provide for directional guidance for the drill bit. The drill guide **370** can be screwed into a fracture plate such that the drill guide **370** can receive a drill bit and can attach to the instrument **200** via the drill guide. The fracture plate can connect to the drill guide **370**, the drill guide **370** can connect to the instrument **200** resulting in one interconnected complex for drilling a bore. In one embodiment the drill guide **370** screws into a fracture plate and the instrument **200** can then be attached to the drill guide **370** by connecting the forward surface guide **302** to the drill guide **370**.

A body insert **220** can fit inside the top of the body **210** such that it covers the drive motors **230** and **260**. The drive lug **240** and the rear surface guide **300** sit in the body **210** above the body insert **220**. The top of the body **210** also can accept a body cover **214**. The rear surface guide **300** fits between the body **210** and the body cover **214** such that it is free to move within the body **210** and extend beyond the body **210** and the body cover **214**. The axial drive motor **230** and spindle **231** and the drive lug **240** determine the movement of the rear surface guide **300**. The body **210** also can include a trigger housing **212** having, for example, a forward two-stage trigger **232** and a reverse trigger **234**.

In an embodiment the forward two-stage trigger **232** can actuate both drive motors **230**, **260**. The first stage can engage the rotational drive motor **260**. The second stage can engage the axial drive motor **230**. The speed of the rotational drive motor **260** can be proportional to the degree of actuation of the first stage of the trigger **232**, for example depression of the trigger. The speed of the axial drive motor **230** can be proportional to the degree of actuation of the second stage of the trigger **232**. In an embodiment, the further the trigger is pulled while in the first stage and the rotational drive motor **260** is engaged, the faster the tool spins until it is at full speed. The tool spins at full speed just before it enters the second stage and the axial drive motor **230** is engaged and the surface guide begins to move axially.

When the first stage of the two-stage trigger **232** is actuated, the rotational drive motor **260** and spindle **261**, the coupler or chuck **290** and the tool **310** spin in a forward direction. When the second stage of the two-stage trigger **232** is actuated, the rotational drive motor **260** and spindle **261**, the coupler or chuck **290** and the tool **310** are spinning at maximal speed in a forward direction and the axial drive motor **230** and spindle **231** begins to spin proportional to the degree of actuation of the second stage of the two-stage trigger **232**. The action of the axial drive motor **230** and spindle **231** cause the drive lug **240**, the rear surface guide **300**, the forward surface guide **302** and the drill guide **370**

to move in an axial, proximal direction or towards the body **210** of the instrument **200** and away from the target tissue. The axial movement in the proximal direction towards the body **210** of the instrument **200** reveals the tool **310** allowing it to engage with and bore into the work as the operator applies pressure to the instrument **200** and keeps it engaged with the work.

The reverse trigger **234** can cause both of the drive motors **230**, **260** to reverse their direction. When the reverse trigger **234** is engaged while the two-stage trigger **232** is actuated during the first stage, the rotational drive motor **260** and spindle **261**, the coupler or chuck **290** and the tool **310** spin in a reverse direction. When the second stage of the two-stage trigger **232** is actuated, and the reverse trigger **234** is still engaged, the rotational drive motor **260** and spindle **261**, the coupler or chuck **290** and the tool **310** are spinning at maximal speed in a reverse direction and the axial drive motor **230** and spindle **231** begins to spin proportional to the degree of actuation of the second stage of the two-stage trigger **232**. The action of the axial drive motor **230** and spindle **231** cause the drive lug **240**, the rear surface guide **300**, the forward surface guide **302** and the drill guide **370** to move in an axial direction away from the body **210** of the instrument **200**. The axial movement away from the body **210** of the instrument **200** pushes the instrument body **210** away from the work and draws the tool **310** out of the work. In another embodiment the motors **230**, **260** can have independent reverse functions and can be controlled independently via independent actuators or triggers.

Distal to the trigger housing **212** there can be an oscillation select switch **262**. When the oscillation select switch **262** is in the off position, the instrument **200** can function as described above. When the oscillation select switch **262** is in the on position, the rotational drive motor **260** can oscillate in the appropriate direction when the triggers are actuated and the axial drive motor's **230** function is not affected. If the forward trigger is actuated, the instrument **200** oscillates in the forward direction, i.e. the rotational drive motor oscillates forward but the axial drive motor moves smoothly in the forward direction as before. If the reverse and forward triggers are actuated, the instrument **200** oscillates in the reverse direction, i.e. the rotational drive motor oscillates in reverse but the axial drive motor moves smoothly in the reverse direction as before. The oscillation select switch affects the function of the rotational motor not the axial drive motor. When selected it causes the rotational motor to oscillate.

In an embodiment the rotation drive motor **260** can have a torque sensor applied (not shown). When the tool passes cortical bone into medullary bone or from cortical bone into soft tissue the measured torque will drop dramatically. The information can be relayed to the display **236** and integrated with the function of the motor drivers and their actuators. For example, in an embodiment, when the tool **310** is moving axially in a forward direction and passes from cortical bone to medullary bone or from cortical bone to soft tissue the reduced torque will interrupt the axial motion. The axial drive can then be reengaged by releasing pressure on the forward two-stage trigger and reapplying pressure.

The body **210** can accept an irrigation tube **340**. Automated irrigation is generally a desired option for surgeons as it effectively reduces drill bit temperature, bone temperature and the risk of bone burning. The forward surface guide **302** can have one or more irrigation nozzles **330**. The body **210** can accept an irrigation actuator (not shown), for example a depressible trigger on the handle of the body **210**. The irrigation actuator can be part of the electronics package

contained in the display **236**. The actuator can turn on the flow of irrigation from the irrigation tube **340** through the nozzles **330** to be delivered to the surgical field. The irrigation nozzles **330** can be connected through the irrigation tube **340** to a sterile fluid bag and sterile tubing (not shown). The irrigation fluid can be delivered to the irrigation port **340** via a sterile fluid bag and sterile tubing. An external fluid pump or gravity can be used to pressurize the irrigation system. The irrigation system can be kept outside the sterile surgical field except, for example, for the sterile tubing connected to the instrument. Such an arrangement can contribute to the engagement end and the tool **310** remaining relatively free from bulk or other awkward equipment enabling more accurate placement and easy use of the instrument **200** in the surgical field. In another embodiment the irrigation system can be adapted to supply fluid to the working tool **310** whereas irrigation can travel into the tool **310** and exit through distal ports in the tool **310** and into the work. In another embodiment the irrigation system, or another system of tubes, can be adapted to supply suction to the work area.

The body **210** can accept a battery cover **362** that encloses a battery **360** and is capped on the bottom by a battery case cover **364**. The body **210** can accept battery release buttons **366**. The body **210** of the instrument **200** together with the battery cover **362**, battery case cover **364**, body cover **214** and trigger housing **212** is shown as a pistol grip although other configurations are considered herein. For example a straight-bodied instrument or other configuration can be used.

Below is an exemplary method of use for the device or devices described herein. In one embodiment, the surgeon can dissect tissue down to the bone and create a field large enough to put the drill bit or a drill guide or an attachable drill guide against the bone. Screws can be placed across fractures without any other implants or a plate can be fixed across the fracture by bone screws. The screws can lock into the plate and bone. When a plate is to be used, the surgeon can create a field large enough to place the plate. Alternatively, the plate can be inserted through a small incision such that the surgeon slides it along the surface of the bone in combination of blunt dissection of the tissue along the way (i.e. subcutaneous plate). The screws can be placed, for example using a radiograph to find the holes in the plate, through small incisions through the skin with dissection down to the bone. The surrounding tissue can be protected using retractors, a drill guide through which the drill bit is inserted, attachable guides placed on the instrument and the like. If a drill guide is used, the length of the guide is accounted for in the depth measurement. If an attachable guide is used, the depth is automatically or manually zeroed. If a plate is used the thickness of the plate can be automatically or manually accounted for in the zeroing.

The working end of the instrument, with or without a guide, can be placed next to the exposed and dissected bone and the instrument zeroed. Alternatively, the surgeon can extend a few millimeters of the drill bit to engage the bone and drill a counter-sink or pilot hole prior to zeroing the device. Where a fixation plate is used, the plate can be placed next to the bone and the drill end placed snug to the plate. Alternatively, some plates have drill guides that screw into them such that the drill is directed at the proper angle. The instrument disclosed herein can be made such that it attached to or freely engages these types of drill guides. Additionally, drill bit guides can have small spikes to hold their position on the bone. The guide can have spikes to perform this function.

13

The surgeon then can apply pressure axially and engage first the rotational drive to the desired speed. The surgeon proceeds to engage the axial drive either continuously or incrementally, depending upon the bone density and preference of the user. The drilling can continue through the cortical bone, through the medullary bone, into and through the distal cortical bone. Once through the distal cortical bone as determined by pre-set depth control means, axial resistance, auditory feedback from the rotational speed of the drill and/or auditory feedback from acceleration or torque sensors, the axial movement is stopped. The surgeon can then remove the drill by reversing the axial drive or by pulling back on the instrument. The rotational drive can be left engaged and in the forward direction to facilitate clearing the hole created. The surgeon can then read the depth on the display and select the proper screw for implantation. The screw can be implanted using a manual screw driver or the like.

Now with respect to FIGS. 7A-7B, in use the instrument **200** can be set against exposed bone or, if used, the fracture fixation plate. The appropriate zero depth position can be determined automatically. Once the operator activates the trigger **232**, the drill guide **370** retracts in the proximal direction (arrow P) and the working tool **310** extends through the drill guide **370**. The working tool **310** engages the work and bores into the work as the operator applies pressure to the instrument **200** and keeps it engaged with the work. The working tool **310** can drill into the bone by the amount the drill guide **370** retracts. The drill guide **370** retraction can be measured instantaneously and shown on the display **236** at the back of the instrument **200**. The automatic determination of the zero-position whether set against bone or against a fracture fixation plate will depend upon proprietary algorithms related to the way the drill guide **370** sets against the bone or the plate and the thickness of the plate. These variables can be unique to each plating system and set of drill guides. The depth of the travel of working tool **310** into the work is measured and shown on the display **236** simultaneously and instantaneously as the working tool **310** moves axially in a distal direction and penetrates the work.

Once the desired depth of penetration is reached, the reverse trigger **234** can be actuated to cause both of the drive motors **230**, **260** to reverse their direction. The action of the axial drive motor **230** causes the drive lug **240**, the rear surface guide **300**, the forward surface guide **302** and the drill guide **370** to move in an axial direction away from the body **210** of the instrument in a distal direction such that the axial movement pushes the instrument body **210** away from the work and draws the tool **310** out of the work.

While this specification contains many specifics, these should not be construed as limitations on the scope of the claims or of what can be claimed, but rather as descriptions of features specific to particular embodiments. Certain features that are described in this specification in the context of separate embodiments can also be implemented in combination in a single embodiment. Conversely, various features that are described in the context of a single embodiment can also be implemented in multiple embodiments separately or in any suitable sub-combination. Moreover, although features can be described above as acting in certain combinations and even initially claimed as such, one or more features from a claimed combination can in some cases be excised from the combination, and the claimed combination can be directed to a sub-combination or a variation of a sub-combination. Similarly, while operations are depicted in the drawings in a particular order, this should not be understood

14

as requiring that such operations be performed in the particular order shown or in sequential order, or that all illustrated operations be performed, to achieve desirable results.

Although embodiments of various methods and devices are described herein in detail with reference to certain versions, it should be appreciated that other versions, embodiments, methods of use, and combinations thereof are also possible. Therefore the spirit and scope of the appended claims should not be limited to the description of the embodiments contained herein.

What is claimed is:

1. A medical drilling device comprising: a housing; a working tool near a distal end of the housing; a rotational drive motor operatively coupled to the working tool disposed in the housing; an actuator operatively coupled to the rotational drive motor disposed in the housing; and a first sensor interfaced with the working tool the first sensor disposed in the housing; wherein the first sensor is configured for outputting a first signal representative of advancement of the working tool relative to the distal end of the housing.

2. The medical device of claim 1, wherein the first sensor is configured to instantaneously measure a distance of advancement of the working tool.

3. The medical device of claim 1, further comprising a second sensor configured for outputting a second signal representative of passage of the working tool through varied layers of tissue having differences in material strength.

4. The medical device of claim 3, wherein the second sensor is configured to prevent further axial penetration of the working tool when the second signal indicates passage of the working tool beyond a distal cortex while rotational movement of the working tool is allowed.

5. The medical device of claim 1, wherein a distal end of the working tool is aligned with the distal end of the housing such that the distal end of the working tool and distal end of the housing are flush with one another.

6. The medical device of claim 1, further comprising a drive rod extending through the housing and engaged with the rotational drive motor, wherein the first sensor comprises a transducer configured to rotate around the drive shaft.

7. The medical device of claim 1, wherein the rotational drive motor is held rotationally still by anti-rotation conducting flanges.

8. The medical device of claim 7, wherein the flanges are configured to slide within channels in the housing.

9. The medical device of claim 1, further comprising an irrigation system configured to cool a surgical field while the medical device is in use.

10. The medical device of claim 1, further comprising an irrigation system wherein the irrigation system includes one or more irrigation nozzles, an irrigation port, and an irrigation actuator.

11. A medical drilling device comprising:

a housing;

a working tool near a distal end of the housing;

a rotational drive motor operatively coupled to the working tool disposed in the housing;

an actuator operatively coupled to the rotational drive motor disposed in the housing; and a first sensor interfaced with the working tool, the first sensor comprising a transducer, wherein the transducer comprises a bearing housing assembly, a light source, a code disc, a mask, a photodetector assembly, and an electronics board.

12. A medical drilling device comprising:

a housing;

15

a working tool near a distal end of the housing;
 a rotational drive motor operatively coupled to the working tool disposed in the housing;
 a first sensor interfaced with the working tool, the first sensor comprising a transducer within the housing; and
 a drill guide assembly is configured to move towards the distal end of the housing while the working tool is configured to remain fixed axially along the longitudinal axis to reveal a portion of the working tool beyond the distal end of the drill guide assembly to engage the bone.

13. The medical device of claim **12**, wherein the first sensor is configured to instantaneously measure a distance of advancement of the working tool beyond a distal end of a drill guide assembly.

14. A medical drilling device comprising:

a housing;
 a working tool near a distal end of the housing;
 a rotational drive motor operatively coupled to the working tool disposed in the housing;
 a drive shaft within the housing and engaged with the rotational drive motor;
 a first sensor configured to output a first signal representative of advancement of the working tool; and

16

a second sensor configured to output a second signal representative of passage of the working tool through varied layers of tissue having differences in material strength the second sensor configured to prevent further axial penetration of the working tool when the second signal indicates passage of the working tool beyond a distal cortex.

15. The medical device of claim **14**, wherein the rotational drive motor is connected to the drive shaft by way of a detachable coupler.

16. The medical device of claim **14**, wherein the rotational drive motor is connected with the drive shaft when a release button is in a first position and wherein the rotational drive motor is disconnected from the drive shaft when the release button is in a second position.

17. The medical device of claim **14**, further comprising a coupler operatively coupled to the working tool, wherein the coupler is stabilized within the housing by bearings, the bearings axially slidable and stabilizing.

18. The medical device of claim **14**, wherein the coupler is configured to be rotatably driven.

* * * * *