



US012395429B2

(12) **United States Patent**
Jha et al.

(10) **Patent No.:** **US 12,395,429 B2**
(45) **Date of Patent:** ***Aug. 19, 2025**

(54) **MEDICAL DEVICE COMMUNICATION METHOD**

(71) Applicant: **ICU Medical, Inc.**, San Clemente, CA (US)

(72) Inventors: **Prakash Kumar Arvind Jha**, San Diego, CA (US); **James Cudney**, Santee, CA (US); **Benjamin Herr**, Kelso, WA (US); **Mark I. Lee**, Poway, CA (US); **Matteo D. Picinich**, Temecula, CA (US)

(73) Assignee: **ICU Medical, Inc.**, San Clemente, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **18/743,658**

(22) Filed: **Jun. 14, 2024**

(65) **Prior Publication Data**

US 2025/0016093 A1 Jan. 9, 2025

Related U.S. Application Data

(63) Continuation of application No. 18/045,061, filed on Oct. 7, 2022, now Pat. No. 12,047,292, which is a (Continued)

(51) **Int. Cl.**
H04L 45/74 (2022.01)
G16H 20/17 (2018.01)
(Continued)

(52) **U.S. Cl.**
CPC **H04L 45/74** (2013.01); **G16H 20/17** (2018.01); **G16H 40/63** (2018.01); **G16H 40/67** (2018.01);
(Continued)

(58) **Field of Classification Search**

CPC H04L 69/32; H04L 69/165; H04L 69/162; H04L 69/16; H04L 45/74; H04L 45/302; G16H 40/67; G16H 40/63; G16H 20/17
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,024,864 A 5/1977 Davies et al.
4,055,175 A 10/1977 Clemens et al.
(Continued)

FOREIGN PATENT DOCUMENTS

AU 2004226440 10/2004
AU 2004305087 7/2005
(Continued)

OTHER PUBLICATIONS

Sethia et al., "Security Framework for Portable NFC Mobile Based Health Record System", Oct. 2016, IEEE 12th International Conference on Wireless and Mobile Computing, Networking and Communications, pp. 1-8.

(Continued)


Primary Examiner — Gbemileke J Onamuti

(74) *Attorney, Agent, or Firm* — Knobbe, Martens, Olson & Bear, LLP

(57) **ABSTRACT**

A medical device communication method that may be implemented within a variety of medical devices including but not limited to infusion pumps. The method may be implemented with a protocol stack for at least intra-device communication. Embodiments provide connection-oriented, connectionless-oriented, broadcast and multicast data exchange with priority handling of data, fragmentation, and reassembly of data, unique static and dynamic address assignment and hot swap capability for connected peripherals or subsystems.

17 Claims, 19 Drawing Sheets



Related U.S. Application Data

continuation of application No. 17/074,268, filed on Oct. 19, 2020, now Pat. No. 11,470,000, which is a continuation of application No. 16/446,381, filed on Jun. 19, 2019, now Pat. No. 10,812,380, which is a continuation of application No. 15/581,442, filed on Apr. 28, 2017, now Pat. No. 10,333,843, which is a continuation of application No. 14/198,807, filed on Mar. 6, 2014, now Pat. No. 9,641,432.

- (60) Provisional application No. 61/773,647, filed on Mar. 6, 2013.

(51) **Int. Cl.**

G16H 40/63 (2018.01)

G16H 40/67 (2018.01)

H04L 45/302 (2022.01)

H04L 69/16 (2022.01)

H04L 69/165 (2022.01)

H04L 69/32 (2022.01)

(52) **U.S. Cl.**

CPC **H04L 45/302** (2013.01); **H04L 69/16** (2013.01); **H04L 69/162** (2013.01); **H04L 69/165** (2013.01); **H04L 69/32** (2013.01)

(58) **Field of Classification Search**

USPC 370/392
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,151,845	A	5/1979	Clemens	4,803,625	A	2/1989	Fu et al.
4,213,454	A	7/1980	Shim	4,835,372	A	5/1989	Gombrich et al.
4,240,438	A	12/1980	Updike et al.	4,838,275	A	6/1989	Lee
4,280,494	A	7/1981	Cosgrove et al.	4,838,856	A	6/1989	Mulreany et al.
4,308,866	A	1/1982	Jeliffe	4,838,857	A	6/1989	Strowe et al.
4,370,983	A	2/1983	Lichtenstein et al.	4,854,324	A	8/1989	Hirschman et al.
4,373,527	A	2/1983	Fischell	4,857,716	A	8/1989	Gombrich et al.
4,392,849	A	7/1983	Petre et al.	4,858,154	A	8/1989	Anderson et al.
4,395,259	A	7/1983	Prestele et al.	4,898,578	A	2/1990	Rubalcaba, Jr.
4,457,751	A	7/1984	Rodler	4,908,017	A	3/1990	Howson et al.
4,464,170	A	8/1984	Clemens	4,933,873	A	6/1990	Kaufman et al.
4,469,481	A	9/1984	Kobayashi	4,943,279	A	7/1990	Samiotes et al.
4,475,901	A	10/1984	Kraegen et al.	4,946,439	A	8/1990	Eggers
4,494,950	A	1/1985	Fischell	4,953,745	A	9/1990	Rowlett
4,498,843	A	2/1985	Schneider et al.	4,978,335	A	12/1990	Arthur, III
4,515,584	A	5/1985	Abe et al.	5,000,739	A	3/1991	Kulisz et al.
4,526,568	A	7/1985	Clemens et al.	5,010,473	A	4/1991	Jacobs
4,529,401	A	7/1985	Leslie et al.	5,014,698	A	5/1991	Cohen
4,543,955	A	10/1985	Schroeppel	5,016,172	A	5/1991	Dessertine
4,551,133	A	11/1985	Zegers de Beyl et al.	5,026,084	A	6/1991	Paisfield
4,553,958	A	11/1985	LeCocq	5,034,004	A	7/1991	Crankshaw
4,559,037	A	12/1985	Franetzki et al.	5,041,086	A	8/1991	Koenig et al.
4,613,937	A	9/1986	Batty	5,058,161	A	10/1991	Weiss
4,624,661	A	11/1986	Arimond	5,078,683	A	1/1992	Sancoff et al.
4,633,878	A	1/1987	Bombardieri	5,084,828	A	1/1992	Kaufman et al.
4,634,426	A	1/1987	Kamen	5,088,981	A	2/1992	Howson et al.
4,634,427	A	1/1987	Hannula et al.	5,097,505	A	3/1992	Weiss
4,674,652	A	6/1987	Aten et al.	5,100,380	A	3/1992	Epstein et al.
4,676,776	A	6/1987	Howson et al.	5,102,392	A	4/1992	Sakai et al.
4,679,562	A	7/1987	Luksha	5,104,374	A	4/1992	Bishko et al.
4,685,903	A	8/1987	Cable et al.	5,109,850	A	5/1992	Blanco et al.
4,695,954	A	9/1987	Rose	5,131,816	A	7/1992	Brown
4,696,671	A	9/1987	Epstein et al.	5,142,484	A	8/1992	Kaufman et al.
4,714,462	A	12/1987	DiDomenico	5,153,827	A	10/1992	Coutre et al.
4,722,734	A	2/1988	Kolin	5,157,640	A	10/1992	Backner
4,730,849	A	3/1988	Siegel	5,161,222	A	11/1992	Montejo et al.
4,731,051	A	3/1988	Fischell	5,177,993	A	1/1993	Beckman et al.
4,741,732	A	5/1988	Crankshaw et al.	5,181,910	A	1/1993	Scanlon
4,756,706	A	7/1988	Kerns et al.	5,190,522	A	3/1993	Wocicki et al.
4,776,842	A	10/1988	Franetzki et al.	5,199,439	A	4/1993	Zimmerman et al.
4,785,969	A	11/1988	McLaughlin	5,200,891	A	4/1993	Kehr et al.
				5,216,597	A	6/1993	Beckers
				5,221,268	A	6/1993	Barton et al.
				5,230,061	A	7/1993	Welch
				5,243,982	A	9/1993	Möstl et al.
				5,244,463	A	9/1993	Cordner, Jr. et al.
				5,249,260	A	9/1993	Nigawara et al.
				5,254,096	A	10/1993	Rondelet et al.
				5,256,156	A	10/1993	Kern et al.
				5,256,157	A	10/1993	Samiotes et al.
				5,261,702	A	11/1993	Mayfield
				5,317,506	A	5/1994	Coutre et al.
				5,319,355	A	6/1994	Russek
				5,319,363	A	6/1994	Welch et al.
				5,330,634	A	7/1994	Wong et al.
				5,338,157	A	8/1994	Blomquist
				5,341,476	A	8/1994	Lowell
				5,364,346	A	11/1994	Schrezenmeir
				5,366,346	A	11/1994	Danby
				5,368,562	A	11/1994	Blomquist et al.
				5,373,454	A	12/1994	Kanda et al.
				5,376,070	A	12/1994	Purvis et al.
				5,378,231	A	1/1995	Johnson et al.
				5,389,071	A	2/1995	Kawahara et al.
				5,389,078	A	2/1995	Zalesky et al.
				5,417,222	A	5/1995	Dempsey et al.
				5,423,748	A	6/1995	Uhala
				5,429,602	A	7/1995	Hauser
				5,431,627	A	7/1995	Pastrone et al.
				5,432,777	A	7/1995	Le Boudec et al.
				5,445,621	A	8/1995	Poli et al.
				5,447,164	A	9/1995	Shaya et al.
				5,455,851	A	10/1995	Chaco et al.
				5,461,365	A	10/1995	Schlager et al.
				5,464,392	A	11/1995	Epstein et al.
				5,465,082	A	11/1995	Chaco
				5,485,408	A	1/1996	Blomquist
				5,486,286	A	1/1996	Peterson et al.
				5,493,430	A	2/1996	Lu et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

5,496,273	A	3/1996	Pastrone et al.	5,935,106	A	8/1999	Olsen
5,505,828	A	4/1996	Wong et al.	5,941,846	A	8/1999	Duffy et al.
5,507,288	A	4/1996	Bocker et al.	5,956,501	A	9/1999	Brown
5,507,786	A	4/1996	Morgan et al.	5,957,885	A	9/1999	Bollish et al.
5,508,499	A	4/1996	Ferrario	5,960,085	A	9/1999	de la Huerga
5,515,713	A	5/1996	Saugues et al.	5,961,448	A	10/1999	Swenson et al.
5,520,637	A	5/1996	Pager et al.	5,967,559	A	10/1999	Abramowitz
5,522,798	A	6/1996	Johnson et al.	5,971,594	A	10/1999	Sahai et al.
5,547,470	A	8/1996	Johnson et al.	5,975,081	A	11/1999	Hood et al.
5,554,013	A	9/1996	Owens et al.	5,990,838	A	11/1999	Burns et al.
5,562,615	A	10/1996	Nassif	5,997,476	A	12/1999	Brown
5,577,169	A	11/1996	Prezioso	6,000,828	A	12/1999	Leet
5,582,323	A	12/1996	Kurtenbach	6,003,006	A	12/1999	Colella et al.
5,582,593	A	12/1996	Hultman	6,012,034	A	1/2000	Hamparian et al.
5,594,786	A	1/1997	Chaco et al.	6,017,318	A	1/2000	Gauthier et al.
5,598,519	A	1/1997	Narayanan	6,021,392	A	2/2000	Lester et al.
5,620,608	A	4/1997	Rosa et al.	6,024,539	A	2/2000	Blomquist
5,630,710	A	5/1997	Tune et al.	6,024,699	A	2/2000	Surwit et al.
5,636,044	A	6/1997	Yuan et al.	6,032,155	A	2/2000	de la Huerga
5,643,212	A	7/1997	Coutre et al.	6,032,676	A	3/2000	Moore
5,651,775	A	7/1997	Walker et al.	6,039,251	A	3/2000	Holowko et al.
5,658,131	A	8/1997	Aoki et al.	6,070,761	A	6/2000	Bloom et al.
5,658,250	A	8/1997	Blomquist et al.	6,073,106	A	6/2000	Rozen et al.
5,665,065	A	9/1997	Colman et al.	6,104,295	A	8/2000	Gaisser et al.
5,669,877	A	9/1997	Blomquist	6,112,182	A	8/2000	Akers et al.
5,672,154	A	9/1997	Sillén et al.	6,112,323	A	8/2000	Meizlik et al.
5,681,285	A	10/1997	Ford et al.	RE36,871	E	9/2000	Epstein et al.
5,685,844	A	11/1997	Marttila	6,115,365	A	9/2000	Newberg
5,687,717	A	11/1997	Halpern et al.	6,115,390	A	9/2000	Chuah
5,689,229	A	11/1997	Chaco et al.	6,122,536	A	9/2000	Sun et al.
5,697,899	A	12/1997	Hillman et al.	6,126,637	A	10/2000	Kriesel et al.
5,699,509	A	12/1997	Gary et al.	6,135,949	A	10/2000	Russo et al.
5,708,714	A	1/1998	Lopez et al.	6,150,942	A	11/2000	O'Brien
5,713,350	A	2/1998	Yokota et al.	6,151,643	A	11/2000	Cheng et al.
5,713,856	A	2/1998	Eggers et al.	6,157,914	A	12/2000	Seto et al.
5,718,562	A	2/1998	Lawless et al.	6,159,147	A	12/2000	Lichter et al.
5,719,761	A	2/1998	Gatti et al.	6,167,567	A	12/2000	Chiles et al.
5,733,259	A	3/1998	Valcke et al.	6,182,667	B1	2/2001	Hanks et al.
5,738,102	A	4/1998	Lemelson	6,189,105	B1	2/2001	Lopes
5,744,027	A	4/1998	Connell et al.	6,195,589	B1	2/2001	Ketcham
5,752,621	A	5/1998	Passamante	6,208,974	B1	3/2001	Campbell et al.
5,754,111	A	5/1998	Garcia	6,222,323	B1	4/2001	Yamashita et al.
5,764,034	A	6/1998	Bowman et al.	6,223,440	B1	5/2001	Rashman
5,764,159	A	6/1998	Neffel et al.	6,226,277	B1	5/2001	Chuah
5,772,635	A	6/1998	Dastur et al.	6,227,371	B1	5/2001	Song
5,774,865	A	6/1998	Glynn	6,234,176	B1	5/2001	Domae et al.
5,778,256	A	7/1998	Darbee	6,241,704	B1	6/2001	Peterson et al.
5,778,345	A	7/1998	McCartney	6,248,067	B1	6/2001	Causey, III et al.
5,781,442	A	7/1998	Engleson et al.	6,249,705	B1	6/2001	Snell
5,782,805	A	7/1998	Meinzer et al.	6,257,265	B1	7/2001	Brunner et al.
5,788,669	A	8/1998	Peterson	6,259,355	B1	7/2001	Chaco et al.
5,797,515	A	8/1998	Liff et al.	6,269,340	B1	7/2001	Ford et al.
5,800,387	A	9/1998	Duffy et al.	6,270,455	B1	8/2001	Brown
5,814,015	A	9/1998	Gargano et al.	6,271,813	B1	8/2001	Palalau
5,822,544	A	10/1998	Chaco et al.	6,277,072	B1	8/2001	Bardy
5,822,715	A	10/1998	Worthington et al.	6,280,380	B1	8/2001	Bardy
5,827,179	A	10/1998	Lichter et al.	6,283,761	B1	9/2001	Joao
5,832,448	A	11/1998	Brown	6,285,665	B1	9/2001	Chuah
5,836,910	A	11/1998	Duffy et al.	6,292,860	B1	9/2001	Cochcroft, Jr.
5,850,344	A	12/1998	Conkright	6,312,378	B1	11/2001	Bardy
5,867,821	A	2/1999	Ballantyne et al.	6,327,254	B1	12/2001	Chuah
5,870,733	A	2/1999	Bass et al.	6,330,008	B1	12/2001	Razdow et al.
5,871,465	A	2/1999	Vasko	6,339,718	B1	1/2002	Zatezalo et al.
5,873,731	A	2/1999	Predergast	6,346,886	B1	2/2002	de la Huerga
5,885,245	A	3/1999	Lynch et al.	6,363,282	B1	3/2002	Nichols et al.
5,897,493	A	4/1999	Brown	6,371,719	B1	4/2002	Hildebrandt
5,897,498	A	4/1999	Canfield, II et al.	6,377,548	B1	4/2002	Chuah
5,910,252	A	6/1999	Truitt et al.	6,388,951	B1	5/2002	Matsumoto et al.
5,912,818	A	6/1999	McGrady et al.	6,406,426	B1	6/2002	Reuss et al.
5,915,240	A	6/1999	Karpf	6,408,330	B1	6/2002	Huerga
5,920,054	A	7/1999	Uber, III	6,418,334	B1	7/2002	Unger et al.
5,920,263	A	7/1999	Huttenhoff et al.	6,427,088	B1	7/2002	Bowman et al.
5,924,074	A	7/1999	Evans	6,428,483	B1	8/2002	Carlebach
5,931,764	A	8/1999	Freeman et al.	6,442,432	B2	8/2002	Lee
5,935,099	A	8/1999	Peterson et al.	6,469,991	B1	10/2002	Chuah
				6,475,180	B2	11/2002	Peterson et al.
				6,482,158	B2	11/2002	Mault
				6,485,418	B2	11/2002	Yasushi et al.
				6,494,694	B2	12/2002	Lawless et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

6,494,831	B1	12/2002	Koritzinsky	6,923,763	B1	8/2005	Kovatchev et al.
6,497,680	B1	12/2002	Holst et al.	6,924,781	B1	8/2005	Gelbman
6,514,460	B1	2/2003	Fendrock	6,928,338	B1	8/2005	Buchser et al.
6,517,482	B1	2/2003	Eiden et al.	6,928,490	B1	8/2005	Buchholz et al.
6,519,569	B1	2/2003	White et al.	6,936,029	B2	8/2005	Mann et al.
6,520,930	B2	2/2003	Critchlow et al.	6,945,954	B2	9/2005	Hochman et al.
6,540,672	B1	4/2003	Simonsen et al.	6,948,492	B2	9/2005	Wemeling et al.
6,542,902	B2	4/2003	Dulong et al.	6,958,677	B1	10/2005	Carter
6,544,212	B2	4/2003	Galley et al.	6,958,691	B1	10/2005	Anderson et al.
6,544,228	B1	4/2003	Heitmeier	6,958,705	B2	10/2005	Lebel et al.
6,546,350	B1	4/2003	Hartmann et al.	6,961,448	B2	11/2005	Nichols et al.
6,551,276	B1	4/2003	Mann et al.	6,969,352	B2	11/2005	Chiang et al.
6,554,798	B1	4/2003	Mann et al.	6,969,865	B2	11/2005	Duchon et al.
6,558,320	B1	5/2003	Causey et al.	6,974,437	B2	12/2005	Lebel et al.
6,558,351	B1	5/2003	Steil et al.	6,979,326	B2	12/2005	Mann et al.
6,565,509	B1	5/2003	Say et al.	6,980,958	B1	12/2005	Surwit et al.
6,567,416	B1	5/2003	Chuah	6,985,870	B2	1/2006	Martucci et al.
6,571,294	B2	5/2003	Simmon et al.	6,986,347	B2	1/2006	Hickle
6,572,542	B1	6/2003	Houben et al.	6,997,880	B2	2/2006	Carlebach et al.
6,572,545	B2	6/2003	Knobbe et al.	6,997,920	B2	2/2006	Mann et al.
6,578,002	B1	6/2003	Derzay et al.	6,998,984	B1	2/2006	Zittrain
6,581,117	B1	6/2003	Klein et al.	7,016,752	B1	3/2006	Ruben et al.
6,587,034	B1	7/2003	Heiman et al.	7,017,293	B2	3/2006	Riley
6,589,229	B1	7/2003	Connelly et al.	7,025,743	B2	4/2006	Mann et al.
6,599,281	B1	7/2003	Struys et al.	7,029,455	B2	4/2006	Flaherty
6,602,191	B2	8/2003	Quy	7,038,584	B2	5/2006	Carter
6,605,072	B2	8/2003	Struys et al.	7,060,031	B2	6/2006	Webb et al.
6,628,809	B1	9/2003	Rowe et al.	7,060,059	B2	6/2006	Keith et al.
6,631,353	B1	10/2003	Davis et al.	7,069,552	B2	6/2006	Lindberg et al.
6,640,246	B1	10/2003	Gardy, Jr. et al.	7,072,725	B2	7/2006	Bristol et al.
6,641,533	B2	11/2003	Causey, III et al.	7,079,035	B2	7/2006	Bock et al.
6,647,299	B2	11/2003	Bourget	7,092,943	B2	8/2006	Roesse et al.
6,652,455	B1	11/2003	Kocher	7,096,072	B2	8/2006	Engleson et al.
6,653,937	B2	11/2003	Nelson et al.	7,099,809	B2	8/2006	Dori
6,659,947	B1	12/2003	Carter et al.	7,103,419	B2	9/2006	Engleson et al.
6,669,630	B1	12/2003	Joliat et al.	7,103,578	B2	9/2006	Beck et al.
6,671,563	B1	12/2003	Engleson et al.	7,107,106	B2	9/2006	Engleson et al.
6,673,033	B1	1/2004	Sciulli et al.	7,108,680	B2	9/2006	Rohr et al.
6,674,403	B2	1/2004	Gray et al.	7,109,878	B2	9/2006	Mann et al.
6,681,003	B2	1/2004	Linder et al.	7,114,002	B1	9/2006	Okumura et al.
6,689,091	B2	2/2004	Bui et al.	7,117,041	B2	10/2006	Engleson et al.
6,692,241	B2	2/2004	Watanabe et al.	7,136,645	B2	11/2006	Hanson et al.
6,694,191	B2	2/2004	Starkweather et al.	7,137,964	B2	11/2006	Flaherty
6,694,334	B2	2/2004	DuLong et al.	7,142,190	B2	11/2006	Martinez
6,721,286	B1	4/2004	Williams et al.	7,150,741	B2	12/2006	Erickson et al.
6,721,582	B2	4/2004	Trepagnier et al.	7,153,289	B2	12/2006	Vasko
6,725,200	B1	4/2004	Rost	7,154,397	B2	12/2006	Zerhusen et al.
6,731,989	B2	5/2004	Engleson et al.	7,156,807	B2	1/2007	Carter et al.
6,740,072	B2	5/2004	Starkweather et al.	7,158,030	B2	1/2007	Chung
6,751,651	B2	6/2004	Crockett	7,161,484	B2	1/2007	Tsoukalis et al.
6,752,787	B1	6/2004	Causey, III et al.	7,167,755	B2	1/2007	Seeberger et al.
6,753,830	B2	6/2004	Gelbman	7,167,920	B2	1/2007	Traversat
6,758,810	B2	7/2004	Lebel et al.	7,171,277	B2	1/2007	Engleson et al.
6,773,396	B2	8/2004	Flach et al.	7,171,492	B1	1/2007	Borella et al.
6,774,786	B1	8/2004	Havekost et al.	7,181,493	B2	2/2007	English et al.
6,775,577	B2	8/2004	Cmkovich et al.	7,185,288	B2	2/2007	McKeever
6,780,156	B2	8/2004	Haueter et al.	7,193,514	B2	3/2007	Ritson
6,790,198	B1	9/2004	White et al.	7,197,025	B2	3/2007	Chuah
6,792,470	B2	9/2004	Hakenberg et al.	7,201,734	B2	4/2007	Hickle
6,796,956	B2	9/2004	Hartlaub et al.	7,204,823	B2	4/2007	Estes et al.
6,799,149	B2	9/2004	Hartlaub	7,213,009	B2	5/2007	Pestotnik
6,809,653	B1	10/2004	Mann et al.	7,216,802	B1	5/2007	de la Hueraga
6,811,534	B2	11/2004	Bowman, IV et al.	7,220,240	B2	5/2007	Struys et al.
6,816,605	B2	11/2004	Rowe et al.	7,224,979	B2	5/2007	Singhal et al.
6,839,753	B2	1/2005	Biondi et al.	7,229,430	B2	6/2007	Hickle et al.
6,852,104	B2	2/2005	Blomquist	7,230,529	B2	6/2007	Ketcherside
6,859,134	B1	2/2005	Heiman et al.	7,236,936	B2	6/2007	White et al.
6,871,211	B2	3/2005	Labounty et al.	7,238,164	B2	7/2007	Childers et al.
6,873,268	B2	3/2005	Lebel et al.	7,247,154	B2	7/2007	Hickle
6,876,303	B2	4/2005	Reeder et al.	7,248,239	B2	7/2007	Dowling
6,885,881	B2	4/2005	Leonhardt	7,250,856	B2	7/2007	Havekost et al.
6,891,525	B2	5/2005	Ogoro	7,255,683	B2	8/2007	Vanderveen et al.
6,892,278	B2	5/2005	Ebergen	7,256,888	B2	8/2007	Staehr et al.
6,899,695	B2	5/2005	Herrera	7,258,534	B2	8/2007	Fathallah et al.
6,915,170	B2	7/2005	Engleson et al.	7,263,213	B2	8/2007	Rowe
				7,267,664	B2	9/2007	Rizzo
				7,267,665	B2	9/2007	Steil et al.
				7,275,156	B2	9/2007	Balfanz et al.
				7,278,983	B2	10/2007	Ireland et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

7,289,815	B2	10/2007	Gfeller et al.	7,868,754	B2	1/2011	Salvat, Jr.
7,289,948	B1	10/2007	Mohri	7,871,394	B2	1/2011	Halbert et al.
7,293,107	B1	11/2007	Hanson et al.	7,886,231	B2	2/2011	Hopermann et al.
7,295,119	B2	11/2007	Rappaport et al.	7,895,053	B2	2/2011	Holland et al.
7,295,556	B2	11/2007	Roese et al.	7,896,842	B2	3/2011	Palmroos et al.
7,301,451	B2	11/2007	Hastings	7,899,546	B2	3/2011	Sieracki et al.
7,308,300	B2	12/2007	Toews et al.	7,905,710	B2	3/2011	Wang et al.
7,315,825	B2	1/2008	Rosenfeld et al.	7,920,061	B2	4/2011	Klein et al.
7,319,386	B2	1/2008	Collins, Jr. et al.	7,933,780	B2	4/2011	de la Huerga
7,324,000	B2	1/2008	Zittrain et al.	7,938,796	B2	5/2011	Moubayed
7,327,705	B2	2/2008	Fletcher et al.	7,945,452	B2	5/2011	Fathallah et al.
7,343,224	B2	3/2008	DiGianfilippo et al.	7,974,714	B2	7/2011	Hoffberg
7,346,025	B2	3/2008	Bryson	7,976,508	B2	7/2011	Hoag
7,347,836	B2	3/2008	Peterson et al.	7,996,241	B2	8/2011	Zak
7,354,420	B2	4/2008	Steil et al.	8,034,026	B2	10/2011	Grant
7,369,897	B2	5/2008	Boveja et al.	8,038,593	B2	10/2011	Friedman et al.
7,369,948	B1	5/2008	Ferenczi et al.	8,048,040	B2	11/2011	Kiani
7,383,088	B2	6/2008	Spinelli et al.	8,060,576	B2	11/2011	Chan et al.
7,384,410	B2	6/2008	Eggers et al.	8,065,161	B2	11/2011	Howard et al.
7,398,183	B2	7/2008	Holland et al.	8,066,672	B2	11/2011	Mandro
7,398,279	B2	7/2008	Muno, Jr. et al.	8,075,514	B2	12/2011	Butterfield et al.
7,399,277	B2	7/2008	Saidara et al.	8,078,983	B2	12/2011	Davis et al.
7,402,153	B2	7/2008	Steil et al.	8,082,018	B2	12/2011	Duchon et al.
7,420,472	B2	9/2008	Tran	8,082,312	B2	12/2011	Chan et al.
7,432,807	B2	10/2008	Schmitt	8,095,692	B2	1/2012	Mehta et al.
7,436,454	B2	10/2008	Yamaguchi et al.	8,126,730	B2	2/2012	Dicks et al.
7,447,643	B1	11/2008	Olson	8,147,448	B2	4/2012	Sundar et al.
7,454,314	B2	11/2008	Holland et al.	8,149,131	B2	4/2012	Blomquist
7,457,804	B2	11/2008	Uber, III et al.	8,169,914	B2	5/2012	Bajpai
7,464,040	B2	12/2008	Joao	8,171,094	B2	5/2012	Chan et al.
7,469,213	B1	12/2008	Rao	8,172,798	B2	5/2012	Hungerford et al.
7,471,994	B2	12/2008	Ford et al.	8,185,322	B2	5/2012	Schroeder et al.
7,483,756	B2	1/2009	Engleson et al.	8,195,478	B2	6/2012	Petersen et al.
7,489,808	B2	2/2009	Gerder	8,206,350	B2	6/2012	Mann et al.
7,490,021	B2	2/2009	Holland et al.	8,219,413	B2	7/2012	Martinez et al.
7,490,048	B2	2/2009	Joao	8,231,578	B2	7/2012	Fathallah et al.
7,491,187	B2	2/2009	Van Den Berghe et al.	8,234,128	B2	7/2012	Martucci et al.
7,519,905	B2	4/2009	Kougiouris et al.	8,267,892	B2	9/2012	Spencer et al.
7,523,401	B1	4/2009	Aldridge	8,271,106	B2	9/2012	Wehba et al.
7,524,304	B2	4/2009	Genosar	8,287,495	B2	10/2012	Michaud et al.
7,551,078	B2	6/2009	Carlson	8,291,337	B2	10/2012	Gannin et al.
7,559,321	B2	7/2009	Wermeling et al.	8,298,184	B2	10/2012	DiPerna et al.
7,565,197	B2	7/2009	Haulbrich et al.	8,312,272	B1	11/2012	Serenyl et al.
7,572,230	B2	8/2009	Neumann et al.	8,352,290	B2	1/2013	Bartz et al.
7,578,802	B2	8/2009	Hickle	8,359,338	B2	1/2013	Butterfield et al.
7,621,009	B2	11/2009	Elhabashy	8,380,536	B2	2/2013	Howard et al.
D606,533	S	12/2009	De Jong et al.	8,387,112	B1	2/2013	Ranjan et al.
7,636,718	B1	12/2009	Steen et al.	8,394,077	B2	3/2013	Jacobson et al.
7,640,172	B2	12/2009	Kuth	8,398,592	B2	3/2013	Leibner-Druska
7,645,258	B2	1/2010	White et al.	8,403,908	B2	3/2013	Jacobson et al.
7,647,237	B2	1/2010	Malave et al.	8,435,206	B2	5/2013	Evans et al.
7,662,124	B2	2/2010	Duchon et al.	8,449,523	B2	5/2013	Brukalo et al.
7,668,731	B2	2/2010	Martucci et al.	8,452,953	B2	5/2013	Buck et al.
7,671,733	B2	3/2010	McNeal et al.	8,453,645	B2	6/2013	Figueiredo et al.
7,678,071	B2	3/2010	Lebel et al.	8,472,630	B2	6/2013	Konrad et al.
7,687,678	B2	3/2010	Jacobs	8,480,648	B2	7/2013	Burnett et al.
7,697,994	B2	4/2010	VanDanacker et al.	8,486,019	B2	7/2013	White et al.
7,698,239	B2	4/2010	Lieuallen	8,489,427	B2	7/2013	Simpson et al.
7,705,727	B2	4/2010	Pestotnik	8,494,879	B2	7/2013	Davis et al.
7,724,147	B2	5/2010	Brown et al.	8,504,179	B2	8/2013	Blomquist
7,739,126	B1	6/2010	Cave	8,517,990	B2	8/2013	Teel et al.
7,746,218	B2	6/2010	Collins, Jr.	8,518,021	B2	8/2013	Stewart et al.
7,766,873	B2	8/2010	Moberg et al.	8,543,416	B2	9/2013	Palmroos et al.
7,776,029	B2	8/2010	Whitehurst et al.	8,551,038	B2	10/2013	Tsoukalis et al.
7,776,031	B2	8/2010	Hartlaub et al.	8,560,345	B2	10/2013	Wehba et al.
7,785,313	B2	8/2010	Mastrototaro	8,567,681	B2	10/2013	Borges et al.
7,788,369	B2	8/2010	McAllen et al.	8,577,692	B2	11/2013	Silkaitis et al.
7,806,852	B1	10/2010	Jurson	8,579,884	B2	11/2013	Lanier et al.
7,806,886	B2	10/2010	Kanderian, Jr. et al.	8,626,530	B1	1/2014	Tran et al.
7,826,981	B2	11/2010	Goode, Jr. et al.	8,655,676	B2	2/2014	Wehba et al.
7,835,927	B2	11/2010	Schlatterbeck et al.	8,660,860	B2	2/2014	Wehba et al.
7,836,314	B2	11/2010	Chieu	8,662,388	B2	3/2014	Belkin
7,856,276	B2	12/2010	Ripart et al.	8,666,769	B2	3/2014	Butler et al.
7,860,583	B2	12/2010	Condurso et al.	8,667,293	B2	3/2014	Birtwhistle et al.
7,864,771	B2	1/2011	Tavares et al.	8,687,811	B2	4/2014	Nierzwick et al.
				8,700,421	B2	4/2014	Feng et al.
				8,731,960	B2	5/2014	Butler et al.
				8,768,719	B2	7/2014	Wehba et al.
				8,771,251	B2	7/2014	Ruchti et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

8,777,894 B2	7/2014	Butterfield et al.	10,757,219 B2	8/2020	Moskal
8,777,895 B2	7/2014	Hsu et al.	10,765,799 B2	9/2020	Belkin et al.
8,799,012 B2	8/2014	Butler et al.	10,799,632 B2	10/2020	Kohlbrecher
8,876,793 B2	11/2014	Ledford et al.	10,812,380 B2	10/2020	Jha et al.
8,886,316 B1	11/2014	Juels	10,861,592 B2	12/2020	Xavier et al.
8,922,330 B2	12/2014	Moberg et al.	10,898,641 B2	1/2021	Day et al.
8,936,565 B2	1/2015	Chawla	10,950,339 B2	3/2021	Xavier et al.
8,945,043 B2	2/2015	Lee et al.	10,964,428 B2	3/2021	Xavier et al.
8,952,794 B2	2/2015	Blomquist et al.	11,013,861 B2	5/2021	Wehba et al.
8,959,617 B2	2/2015	Newlin et al.	11,037,668 B2	6/2021	Ruchti et al.
8,998,100 B2	4/2015	Halbert et al.	11,052,193 B2	7/2021	Day et al.
9,026,370 B2	5/2015	Rubalcaba et al.	11,139,058 B2	10/2021	Xavier et al.
9,069,887 B2	6/2015	Gupta et al.	11,151,290 B2	10/2021	Karakoyunlu et al.
9,077,544 B2	7/2015	Baker et al.	11,152,108 B2	10/2021	Xavier et al.
9,089,642 B2	7/2015	Murphy et al.	11,152,109 B2	10/2021	Xavier et al.
9,114,217 B2	8/2015	Sur et al.	11,152,110 B2	10/2021	Xavier et al.
9,123,077 B2	9/2015	Silkaitis et al.	11,194,810 B2	12/2021	Butler et al.
9,192,712 B2	11/2015	DeBelser et al.	11,235,100 B2	2/2022	Howard et al.
9,240,002 B2	1/2016	Hume et al.	11,289,183 B2	3/2022	Kohlbrecher
9,292,692 B2	3/2016	Wallrabenstein	11,309,070 B2	4/2022	Xavier et al.
9,302,035 B2	4/2016	Marseille et al.	11,328,804 B2	5/2022	Xavier et al.
9,313,154 B1	4/2016	Son	11,328,805 B2	5/2022	Xavier et al.
9,381,296 B2	7/2016	Arrizza et al.	11,373,753 B2	6/2022	Xavier et al.
9,393,362 B2	7/2016	Cozmi et al.	11,437,132 B2	9/2022	Xavier et al.
9,430,655 B1	8/2016	Stockton et al.	11,470,000 B2	10/2022	Jha et al.
9,438,580 B2	9/2016	Kupper	11,483,402 B2	10/2022	Xavier et al.
9,483,615 B2	11/2016	Roberts	11,483,403 B2	10/2022	Xavier et al.
9,498,583 B2	11/2016	Sur et al.	11,501,877 B2	11/2022	Kohlbrecher et al.
9,539,383 B2	1/2017	Kohlbrecher	11,571,508 B2	2/2023	Jacobson et al.
9,572,923 B2	2/2017	Howard et al.	11,574,721 B2	2/2023	Kohlbrecher
9,594,875 B2	3/2017	Arrizza et al.	11,574,737 B2	2/2023	Dharwad et al.
9,604,000 B2	3/2017	Wehba et al.	11,587,669 B2	2/2023	Xavier et al.
9,641,432 B2	5/2017	Jha et al.	11,590,057 B2	2/2023	Tagliamento et al.
9,649,431 B2	5/2017	Gray et al.	11,594,326 B2	2/2023	Xavier et al.
9,662,436 B2	5/2017	Belkin et al.	11,605,468 B2	3/2023	Jacobson et al.
9,690,909 B2	6/2017	Stewart et al.	11,626,205 B2	4/2023	Arrizza et al.
9,707,341 B2	7/2017	Dumas, III et al.	11,628,246 B2	4/2023	Day et al.
9,717,845 B2	8/2017	Istoc	11,628,254 B2	4/2023	Day et al.
9,724,470 B2	8/2017	Day et al.	11,654,237 B2	5/2023	Wehba et al.
9,764,082 B2	9/2017	Day et al.	11,670,416 B2	6/2023	Xavier et al.
9,886,550 B2	2/2018	Lee et al.	11,763,927 B2	9/2023	Ruchti et al.
9,943,269 B2	4/2018	Muhsin et al.	11,783,935 B2	10/2023	Xavier et al.
9,967,739 B2	5/2018	Proennecke et al.	11,881,297 B2	1/2024	Xavier et al.
9,971,871 B2	5/2018	Arrizza et al.	11,923,076 B2	3/2024	Xavier et al.
9,995,611 B2	6/2018	Ruchti et al.	11,986,623 B2	5/2024	Jacobson et al.
10,022,498 B2	7/2018	Ruchti et al.	11,996,188 B2	5/2024	Arrizza et al.
10,042,986 B2	8/2018	Ruchti et al.	12,002,562 B2	6/2024	Kohlbrecher
10,046,112 B2	8/2018	Oruklu et al.	12,036,390 B2	7/2024	Wehba et al.
10,166,328 B2	1/2019	Oruklu et al.	12,040,068 B2	7/2024	Xavier et al.
10,173,008 B2	1/2019	Simpson et al.	12,042,623 B2	7/2024	Day et al.
10,188,849 B2	1/2019	Fangrow	12,042,631 B2	7/2024	Day et al.
10,233,179 B2	3/2019	Ng et al.	12,046,361 B2	7/2024	Xavier et al.
10,238,799 B2	3/2019	Kohlbrecher	12,047,292 B2	7/2024	Jha et al.
10,238,801 B2	3/2019	Wehba et al.	12,097,351 B2	9/2024	Belkin et al.
10,242,060 B2	3/2019	Butler et al.	2001/0016056 A1	8/2001	Westphal et al.
10,300,194 B2	5/2019	Day et al.	2001/0029178 A1	10/2001	Criss et al.
10,311,972 B2	6/2019	Kohlbrecher et al.	2001/0031944 A1	10/2001	Peterson et al.
10,314,974 B2	6/2019	Day et al.	2001/0032099 A1	10/2001	Joao
10,333,843 B2	6/2019	Jha et al.	2001/0037060 A1	11/2001	Thompson et al.
10,341,866 B1	7/2019	Spencer et al.	2001/0044731 A1	11/2001	Coffman et al.
10,409,995 B1	9/2019	Wasiq	2001/0048027 A1	12/2001	Walsh
10,430,761 B2	10/2019	Hume et al.	2001/0051787 A1	12/2001	Haller et al.
10,434,246 B2	10/2019	Silkaitis et al.	2001/0056358 A1	12/2001	Dulong et al.
10,438,001 B1	10/2019	Hariprasad	2002/0010595 A1	1/2002	Kapp
10,452,842 B2	10/2019	Dhondse	2002/0013551 A1	1/2002	Zaitzu et al.
10,453,157 B2	10/2019	Kamen et al.	2002/0013723 A1	1/2002	Mise
10,463,788 B2	11/2019	Day	2002/0015018 A1	2/2002	Shimazu et al.
10,516,536 B2	12/2019	Rommel	2002/0019584 A1	2/2002	Schulze et al.
10,617,815 B2	4/2020	Day et al.	2002/0021700 A1	2/2002	Hata et al.
10,646,651 B2	5/2020	Day et al.	2002/0026103 A1	2/2002	Norris et al.
10,681,207 B1	6/2020	Johnson et al.	2002/0029776 A1	3/2002	Blomquist
10,692,595 B2	6/2020	Xavier et al.	2002/0032583 A1	3/2002	Joao
10,728,262 B1	7/2020	Vaswani	2002/0040208 A1	4/2002	Flaherty et al.
10,740,436 B2	8/2020	Moskal et al.	2002/0040282 A1	4/2002	Bailey et al.
10,741,280 B2	8/2020	Xavier et al.	2002/0044043 A1	4/2002	Chaco et al.
			2002/0044059 A1	4/2002	Reeder et al.
			2002/0082728 A1	6/2002	Mueller et al.
			2002/0087115 A1	7/2002	Hartlaub
			2002/0087116 A1	7/2002	Hartlaub

(56)

References Cited

U.S. PATENT DOCUMENTS

2002/0095486 A1	7/2002	Bahl	2004/0167464 A1	8/2004	Ireland et al.
2002/0103675 A1	8/2002	Vanelli	2004/0167465 A1	8/2004	Kohler
2002/0123905 A1	9/2002	Goodroe et al.	2004/0167804 A1	8/2004	Simpson
2002/0143580 A1	10/2002	Bristol et al.	2004/0172222 A1	9/2004	Simpson et al.
2002/0152239 A1	10/2002	Bautista-Lloyd et al.	2004/0172283 A1	9/2004	Vanderveen
2002/0154600 A1	10/2002	Ido et al.	2004/0172301 A1	9/2004	Mihai et al.
2002/0173702 A1	11/2002	Lebel et al.	2004/0172302 A1	9/2004	Martucci et al.
2002/0173875 A1	11/2002	Wallace et al.	2004/0176667 A1	9/2004	Mihai et al.
2002/0193679 A1	12/2002	Malave et al.	2004/0176980 A1	9/2004	Bulitta et al.
2002/0194329 A1	12/2002	Alling	2004/0176984 A1	9/2004	White et al.
2003/0009244 A1	1/2003	Engleson	2004/0181314 A1	9/2004	Zaleski
2003/0013959 A1	1/2003	Grunwald et al.	2004/0189708 A1	9/2004	Larcheveque et al.
2003/0014222 A1	1/2003	Klass et al.	2004/0193325 A1	9/2004	Bonderud
2003/0014817 A1	1/2003	Gallant et al.	2004/0193328 A1	9/2004	Butterfield et al.
2003/0025602 A1	2/2003	Medema et al.	2004/0193453 A1	9/2004	Butterfield et al.
2003/0028082 A1	2/2003	Thompson	2004/0204673 A1	10/2004	Flaherty et al.
2003/0036683 A1	2/2003	Kehr et al.	2004/0215278 A1	10/2004	Stegink et al.
2003/0036744 A1	2/2003	Struys et al.	2004/0220517 A1	11/2004	Starkweather et al.
2003/0047126 A1	3/2003	Tomaschko	2004/0225252 A1	11/2004	Gillespie et al.
2003/0047600 A1	3/2003	Nakanishi et al.	2004/0236240 A1	11/2004	Kraus et al.
2003/0050621 A1	3/2003	Lebel et al.	2004/0243438 A1	12/2004	Mintz
2003/0059750 A1	3/2003	Bindler et al.	2004/0254434 A1	12/2004	Goodnow et al.
2003/0060688 A1	3/2003	Ciarniello et al.	2005/0010269 A1	1/2005	Lebel et al.
2003/0069963 A1	4/2003	Jayant et al.	2005/0020886 A1	1/2005	Hutchinson et al.
2003/0079746 A1	5/2003	Hickle	2005/0021006 A1	1/2005	Tonnies
2003/0097529 A1	5/2003	Arimilli et al.	2005/0027560 A1	2/2005	Cook
2003/0104982 A1	6/2003	Wittmann et al.	2005/0027567 A1	2/2005	Taha
2003/0105389 A1	6/2003	Noonan et al.	2005/0038311 A1	2/2005	Kuth
2003/0106553 A1	6/2003	Vanderveen	2005/0038669 A1	2/2005	Sachdeva et al.
2003/0115358 A1	6/2003	Yun	2005/0038680 A1	2/2005	McMahon
2003/0120384 A1	6/2003	Haitin et al.	2005/0040226 A1	2/2005	Al-Sheikh
2003/0125662 A1	7/2003	Bui	2005/0043620 A1	2/2005	Fallows et al.
2003/0130616 A1	7/2003	Steil	2005/0049910 A1	3/2005	Lancaster et al.
2003/0133508 A1	7/2003	Hickle et al.	2005/0055242 A1	3/2005	Bello et al.
2003/0139701 A1	7/2003	White et al.	2005/0055244 A1	3/2005	Mullan et al.
2003/0140928 A1	7/2003	Bui et al.	2005/0065465 A1	3/2005	Lebel et al.
2003/0140929 A1	7/2003	Wilkes et al.	2005/0065817 A1	3/2005	Mihai et al.
2003/0141981 A1	7/2003	Bui et al.	2005/0075544 A1	4/2005	Shapiro et al.
2003/0143746 A1	7/2003	Sage, Jr.	2005/0080801 A1	4/2005	Kothandaraman et al.
2003/0144878 A1	7/2003	Wilkes et al.	2005/0086071 A1	4/2005	Fox, Jr. et al.
2003/0158749 A1	8/2003	Olchanski et al.	2005/0086072 A1	4/2005	Fox
2003/0187338 A1	10/2003	Say et al.	2005/0088704 A1	4/2005	Vaschillo et al.
2003/0200116 A1	10/2003	Forrester	2005/0090808 A1	4/2005	Malave et al.
2003/0204416 A1	10/2003	Acharya	2005/0099624 A1	5/2005	Staehr
2003/0204781 A1	10/2003	Peebles et al.	2005/0102162 A1	5/2005	Blumenfeld
2003/0212364 A1	11/2003	Mann et al.	2005/0102165 A1	5/2005	Oshita et al.
2003/0212379 A1	11/2003	Bylund et al.	2005/0102167 A1	5/2005	Kapoor
2003/0212821 A1	11/2003	Gillies et al.	2005/0102669 A1	5/2005	Marney et al.
2003/0216831 A1	11/2003	Hart et al.	2005/0107923 A1	5/2005	Vanderveen
2003/0217962 A1	11/2003	Childers et al.	2005/0108057 A1	5/2005	Cohen et al.
2004/0008123 A1	1/2004	Carrender et al.	2005/0117529 A1	6/2005	Ramos-Escano
2004/0010786 A1	1/2004	Cool et al.	2005/0119788 A1	6/2005	Engleson et al.
2004/0015132 A1	1/2004	Brown	2005/0119914 A1	6/2005	Batch
2004/0019464 A1	1/2004	Martucci et al.	2005/0131739 A1	6/2005	Rabinowitz et al.
2004/0019607 A1	1/2004	Moubayed et al.	2005/0135306 A1	6/2005	McAllen et al.
2004/0030323 A1	2/2004	Ullestad et al.	2005/0137522 A1	6/2005	Aoki
2004/0039257 A1	2/2004	Hickle	2005/0137573 A1	6/2005	McLaughlin
2004/0057226 A1	3/2004	Berthou et al.	2005/0138428 A1	6/2005	McAllen et al.
2004/0064341 A1	4/2004	Langan et al.	2005/0154769 A1	7/2005	Eckart et al.
2004/0064342 A1	4/2004	Browne et al.	2005/0160057 A1	7/2005	Wefers et al.
2004/0064435 A1	4/2004	Moubayed et al.	2005/0171503 A1	8/2005	Van Den Berghe et al.
2004/0073161 A1	4/2004	Tachibana	2005/0171815 A1	8/2005	Vanderveen
2004/0073811 A1	4/2004	Sanin	2005/0177096 A1	8/2005	Bollich et al.
2004/0077934 A1	4/2004	Massad	2005/0177395 A1	8/2005	Blomquist
2004/0078231 A1	4/2004	Wilkes et al.	2005/0182306 A1	8/2005	Sloan
2004/0078236 A1	4/2004	Stoodley et al.	2005/0182355 A1	8/2005	Bui
2004/0085186 A1	5/2004	Eveland et al.	2005/0187950 A1	8/2005	Parker
2004/0104271 A1	6/2004	Martucci et al.	2005/0192557 A1	9/2005	Brauker et al.
2004/0122530 A1	6/2004	Hansen	2005/0197554 A1	9/2005	Polcha
2004/0128162 A1	7/2004	Schlotterbeck et al.	2005/0197621 A1	9/2005	Poulsen et al.
2004/0128163 A1	7/2004	Goodman et al.	2005/0210037 A1	9/2005	Wefers et al.
2004/0133441 A1	7/2004	Brady et al.	2005/0216479 A1	9/2005	Wefers et al.
2004/0139004 A1	7/2004	Cohen et al.	2005/0216480 A1	9/2005	Wefers et al.
2004/0145480 A1	7/2004	Despotis	2005/0223045 A1	10/2005	Funahashi et al.
2004/0147034 A1	7/2004	Gore et al.	2005/0224083 A1	10/2005	Crass
			2005/0234746 A1	10/2005	Funahashi
			2005/0240305 A1	10/2005	Bogash et al.
			2005/0246416 A1	11/2005	Blomquist
			2005/0251418 A1	11/2005	Fox et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2005/0261660	A1	11/2005	Choi	2007/0100667	A1	5/2007	Bardy
2005/0273059	A1	12/2005	Mernoe et al.	2007/0106126	A1	5/2007	Mannheimer et al.
2005/0273367	A1	12/2005	Nourie et al.	2007/0112298	A1	5/2007	Mueller et al.
2005/0277873	A1	12/2005	Stewart et al.	2007/0116037	A1	5/2007	Moore
2005/0277890	A1	12/2005	Stewart et al.	2007/0118405	A1	5/2007	Campbell et al.
2005/0277911	A1	12/2005	Stewart et al.	2007/0135866	A1	6/2007	Baker et al.
2005/0278194	A1	12/2005	Holland et al.	2007/0136098	A1	6/2007	Smythe et al.
2006/0004772	A1	1/2006	Hagan et al.	2007/0142822	A1	6/2007	Remde
2006/0009727	A1	1/2006	O'Mahony et al.	2007/0156282	A1	7/2007	Dunn
2006/0009734	A1	1/2006	Martin	2007/0156452	A1	7/2007	Batch
2006/0010098	A1	1/2006	Goodnow et al.	2007/0169008	A1	7/2007	Varanasi et al.
2006/0042139	A1	3/2006	Mendes	2007/0179448	A1	8/2007	Lim et al.
2006/0047270	A1	3/2006	Shelton	2007/0186923	A1	8/2007	Poutiatine et al.
2006/0053036	A1	3/2006	Coffman et al.	2007/0191817	A1	8/2007	Martin
2006/0064020	A1	3/2006	Burnes et al.	2007/0191973	A1	8/2007	Holzbauer et al.
2006/0074633	A1	4/2006	Mahesh et al.	2007/0213657	A1	9/2007	Jennewine et al.
2006/0074920	A1	4/2006	Wefers et al.	2007/0213684	A1	9/2007	Hickle et al.
2006/0079831	A1	4/2006	Gilbert	2007/0214003	A1	9/2007	Holland et al.
2006/0089539	A1	4/2006	Miodownik et al.	2007/0215545	A1	9/2007	Bissler et al.
2006/0089854	A1	4/2006	Holland et al.	2007/0229249	A1	10/2007	McNeal et al.
2006/0089855	A1	4/2006	Holland et al.	2007/0232867	A1	10/2007	Hansmann
2006/0100746	A1	5/2006	Leibner-Druska	2007/0233035	A1	10/2007	Wehba et al.
2006/0100907	A1	5/2006	Holland et al.	2007/0233049	A1	10/2007	Wehba et al.
2006/0106649	A1	5/2006	Eggers et al.	2007/0233206	A1	10/2007	Frikart
2006/0111943	A1	5/2006	Wu	2007/0233520	A1	10/2007	Wehba et al.
2006/0116904	A1	6/2006	Brem	2007/0240215	A1	10/2007	Flores
2006/0116907	A1	6/2006	Rhodes et al.	2007/0251835	A1	11/2007	Mehta et al.
2006/0122481	A1	6/2006	Sievenpiper et al.	2007/0253021	A1	11/2007	Mehta et al.
2006/0122867	A1	6/2006	Eggers et al.	2007/0254593	A1	11/2007	Jollota et al.
2006/0129140	A1	6/2006	Todd et al.	2007/0255125	A1	11/2007	Moberg et al.
2006/0129429	A1	6/2006	Moubayed et al.	2007/0257788	A1	11/2007	Carlson
2006/0129434	A1	6/2006	Smitherman et al.	2007/0258395	A1	11/2007	Jollota et al.
2006/0129435	A1	6/2006	Smitherman et al.	2007/0299687	A1	12/2007	Palmer et al.
2006/0136266	A1	6/2006	Tarassenko et al.	2007/0299695	A1	12/2007	Jung et al.
2006/0136271	A1	6/2006	Eggers et al.	2008/0001771	A1	1/2008	Faoro et al.
2006/0143051	A1	6/2006	Eggers et al.	2008/0004904	A1	1/2008	Tran
2006/0173260	A1	8/2006	Gaoni et al.	2008/0009684	A1	1/2008	Corsetti et al.
2006/0173406	A1	8/2006	Hayes et al.	2008/0033361	A1	2/2008	Evans et al.
2006/0173715	A1	8/2006	Wang et al.	2008/0033966	A1	2/2008	Wahl
2006/0173927	A1	8/2006	Beyer et al.	2008/0034323	A1	2/2008	Blomquist
2006/0190302	A1	8/2006	Eggers et al.	2008/0041942	A1	2/2008	Aissa
2006/0195022	A1	8/2006	Trepagnier et al.	2008/0052704	A1	2/2008	Wysocki
2006/0200007	A1	9/2006	Brockway et al.	2008/0065007	A1	3/2008	Peterson et al.
2006/0200369	A1	9/2006	Batch et al.	2008/0065417	A1	3/2008	Jung et al.
2006/0211404	A1	9/2006	Crompt et al.	2008/0071217	A1	3/2008	Moubayed et al.
2006/0224141	A1	10/2006	Rush et al.	2008/0071251	A1	3/2008	Moubayed et al.
2006/0229918	A1	10/2006	Fotsch et al.	2008/0086088	A1	4/2008	Malcolm
2006/0236373	A1	10/2006	Graves et al.	2008/0091466	A1	4/2008	Butler et al.
2006/0247606	A1	11/2006	Batch	2008/0095339	A1	4/2008	Elliott
2006/0253554	A1	11/2006	Uwais	2008/0097289	A1	4/2008	Steil et al.
2006/0258985	A1	11/2006	Russell	2008/0097552	A1	4/2008	Dicks et al.
2006/0259327	A1	11/2006	Hoag	2008/0126969	A1	5/2008	Blomquist
2006/0264895	A1	11/2006	Flanders	2008/0139907	A1	6/2008	Rao et al.
2006/0265246	A1	11/2006	Hoag	2008/0148047	A1	6/2008	Appenzeller et al.
2006/0267753	A1	11/2006	Hussey et al.	2008/0149117	A1	6/2008	Raghuram
2006/0268710	A1	11/2006	Appanna et al.	2008/0154177	A1	6/2008	Moubayed et al.
2006/0270971	A1	11/2006	Gelfand et al.	2008/0172337	A1	7/2008	Banfield et al.
2006/0277206	A1	12/2006	Bailey et al.	2008/0184219	A1	7/2008	Matsumoto
2006/0287885	A1	12/2006	Frick	2008/0188796	A1	8/2008	Steil et al.
2007/0015972	A1	1/2007	Wang et al.	2008/0214919	A1	9/2008	Harmon et al.
2007/0016443	A1	1/2007	Wachman et al.	2008/0246748	A1	10/2008	Cassidy et al.
2007/0021715	A1	1/2007	Kohlbreuner et al.	2008/0256305	A1	10/2008	Kwon
2007/0027506	A1	2/2007	Stender et al.	2008/0259926	A1	10/2008	Tavares et al.
2007/0060796	A1	3/2007	Kim	2008/0262469	A1	10/2008	Bristol et al.
2007/0060870	A1	3/2007	Tolle et al.	2008/0269714	A1	10/2008	Mastrototaro et al.
2007/0060871	A1	3/2007	Istoc	2008/0269723	A1	10/2008	Mastrototaro et al.
2007/0061393	A1	3/2007	Moore	2008/0275384	A1	11/2008	Mastrototaro et al.
2007/0065363	A1	3/2007	Dalal et al.	2008/0300572	A1	12/2008	Rankers et al.
2007/0073419	A1	3/2007	Sesay	2008/0301298	A1	12/2008	Bernardi et al.
2007/0073822	A1	3/2007	Bennett et al.	2008/0320387	A1	12/2008	Sasaki et al.
2007/0078314	A1	4/2007	Grounsell	2008/0320466	A1	12/2008	Dias
2007/0083870	A1	4/2007	Kanakogi	2009/0003554	A1	1/2009	Katis et al.
2007/0088333	A1	4/2007	Levin et al.	2009/0005703	A1	1/2009	Fasciano
2007/0093786	A1	4/2007	Goldsmith et al.	2009/0005728	A1	1/2009	Weinert et al.
2007/0100665	A1	5/2007	Brown	2009/0006061	A1	1/2009	Thukral et al.
				2009/0006129	A1	1/2009	Thukral
				2009/0006133	A1	1/2009	Weinert
				2009/0018495	A1	1/2009	Panduro
				2009/0036750	A1	2/2009	Weinstein et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2009/0051560	A1	2/2009	Manning et al.	2011/0078608	A1	3/2011	Gannon et al.
2009/0054743	A1	2/2009	Stewart	2011/0093284	A1	4/2011	Dicks et al.
2009/0054754	A1	2/2009	McMahon et al.	2011/0099313	A1	4/2011	Bolanowski
2009/0057399	A1	3/2009	Sajkowsky	2011/0106318	A1	5/2011	Ledford et al.
2009/0063187	A1	3/2009	Johnson et al.	2011/0125095	A1	5/2011	Lebel et al.
2009/0069785	A1	3/2009	Miller et al.	2011/0138185	A1	6/2011	Ju et al.
2009/0099867	A1	4/2009	Newman	2011/0166628	A1	7/2011	Jain
2009/0135196	A1	5/2009	Holland et al.	2011/0175728	A1	7/2011	Baker, Jr.
2009/0143662	A1	6/2009	Estes et al.	2011/0178462	A1	7/2011	Moberg et al.
2009/0149743	A1	6/2009	Barron et al.	2011/0185010	A1	7/2011	Shatsky et al.
2009/0150174	A1	6/2009	Buck et al.	2011/0196748	A1	8/2011	Caron et al.
2009/0150439	A1	6/2009	Gejdos et al.	2011/0231216	A1	9/2011	Fyke et al.
2009/0150878	A1	6/2009	Pathak et al.	2011/0252230	A1	10/2011	Segre et al.
2009/0156991	A1	6/2009	Roberts	2011/0257496	A1	10/2011	Terashima et al.
2009/0157695	A1	6/2009	Roberts	2011/0257798	A1	10/2011	Ali et al.
2009/0158274	A1	6/2009	Roberts	2011/0259954	A1	10/2011	Bartz et al.
2009/0177146	A1	7/2009	Nesbitt et al.	2011/0264043	A1	10/2011	Kotnick et al.
2009/0177769	A1	7/2009	Roberts	2011/0264044	A1	10/2011	Bartz et al.
2009/0177992	A1	7/2009	Rubalcaba et al.	2011/0266221	A1	11/2011	Ware et al.
2009/0183147	A1	7/2009	Davis et al.	2011/0270045	A1	11/2011	Lebel et al.
2009/0209938	A1	8/2009	Aalto-Setälä	2011/0275904	A1	11/2011	Lebel et al.
2009/0210250	A1	8/2009	Prax et al.	2011/0286457	A1	11/2011	Ee
2009/0221890	A1	9/2009	Saffer et al.	2011/0289162	A1	11/2011	Furlong
2009/0231249	A1	9/2009	Wang et al.	2011/0289314	A1	11/2011	Whitcomb
2009/0270833	A1	10/2009	DeBelser	2011/0289497	A1	11/2011	Kiaie et al.
2009/0275886	A1	11/2009	Blomquist et al.	2011/0295196	A1	12/2011	Chazot et al.
2009/0275896	A1	11/2009	Kamen et al.	2011/0295341	A1	12/2011	Estes et al.
2009/0284691	A1	11/2009	Marhefka et al.	2011/0296051	A1	12/2011	Vange
2009/0292340	A1	11/2009	Mass et al.	2011/0296411	A1	12/2011	Tang et al.
2009/0306573	A1	12/2009	Gagner et al.	2011/0313789	A1	12/2011	Karmen et al.
2009/0326340	A1	12/2009	Wang	2011/0319813	A1	12/2011	Kamen et al.
2009/0326516	A1	12/2009	Bangera et al.	2011/0320049	A1	12/2011	Chossat et al.
2010/0008377	A1	1/2010	Hasti et al.	2012/0005680	A1	1/2012	Dolby et al.
2010/0022988	A1	1/2010	Wochner	2012/0011253	A1	1/2012	Friedman et al.
2010/0036310	A1	2/2010	Hillman	2012/0016305	A1	1/2012	Jollota
2010/0056992	A1	3/2010	Hayter	2012/0029941	A1	2/2012	Malave et al.
2010/0083060	A1	4/2010	Rahman	2012/0036102	A1	2/2012	Fletcher et al.
2010/0095229	A1	4/2010	Dixon et al.	2012/0036550	A1	2/2012	Rodriguez
2010/0121170	A1	5/2010	Rule	2012/0066501	A1	3/2012	Xiong
2010/0121246	A1	5/2010	Peters et al.	2012/0070045	A1	3/2012	Vesper et al.
2010/0121415	A1	5/2010	Skelton et al.	2012/0079084	A1	3/2012	Forssell et al.
2010/0121654	A1	5/2010	Portnoy et al.	2012/0095437	A1	4/2012	Hemmerling
2010/0121752	A1	5/2010	Banigan et al.	2012/0112903	A1	5/2012	Kaib et al.
2010/0130933	A1	5/2010	Holland et al.	2012/0130198	A1	5/2012	Beaule
2010/0131434	A1	5/2010	Magent et al.	2012/0143116	A1	6/2012	Ware et al.
2010/0138523	A1	6/2010	Umess et al.	2012/0150556	A1	6/2012	Galasso et al.
2010/0146137	A1	6/2010	Wu et al.	2012/0157920	A1	6/2012	Flachbart et al.
2010/0156633	A1	6/2010	Buck et al.	2012/0179135	A1	7/2012	Rinehart et al.
2010/0160854	A1	6/2010	Gauthier	2012/0179136	A1	7/2012	Rinehart et al.
2010/0160860	A1	6/2010	Celentano et al.	2012/0185267	A1	7/2012	Kamen et al.
2010/0174266	A1	7/2010	Estes	2012/0203177	A1	8/2012	Lanier
2010/0191525	A1	7/2010	Rabenko et al.	2012/0245554	A1	9/2012	Kawamura
2010/0198034	A1	8/2010	Thomas et al.	2012/0259978	A1	10/2012	Petersen et al.
2010/0198196	A1	8/2010	Wei	2012/0260012	A1	10/2012	Gao-Saari et al.
2010/0200506	A1	8/2010	Ware et al.	2012/0277716	A1	11/2012	Ali et al.
2010/0209268	A1	8/2010	Davis	2012/0283630	A1	11/2012	Lee et al.
2010/0212675	A1	8/2010	Walling et al.	2012/0284734	A1	11/2012	McQuaid et al.
2010/0217621	A1	8/2010	Schoenberg	2012/0323212	A1	12/2012	Murphy
2010/0234708	A1	9/2010	Buck et al.	2012/0330380	A1	12/2012	Corndorf
2010/0250732	A1	9/2010	Bucknell	2013/0006666	A1	1/2013	Schneider
2010/0271479	A1	10/2010	Heydlauf	2013/0006702	A1	1/2013	Wu
2010/0273738	A1	10/2010	Valcke et al.	2013/0012877	A1	1/2013	Debelser et al.
2010/0274218	A1	10/2010	Yodfat et al.	2013/0012879	A1	1/2013	Debelser et al.
2010/0280486	A1	11/2010	Khair et al.	2013/0012880	A1	1/2013	Blomquist
2010/0292634	A1	11/2010	Kircher	2013/0015980	A1	1/2013	Evans et al.
2010/0298765	A1	11/2010	Budiman et al.	2013/0036403	A1	2/2013	Geist
2010/0318025	A1	12/2010	John	2013/0036412	A1	2/2013	Birtwhistle et al.
2011/0001605	A1	1/2011	Kiani et al.	2013/0066265	A1	3/2013	Grant
2011/0021898	A1	1/2011	Wei et al.	2013/0072872	A1	3/2013	Yodfat et al.
2011/0028885	A1	2/2011	Eggers et al.	2013/0091350	A1	4/2013	Gluck
2011/0040158	A1	2/2011	Katz et al.	2013/0096444	A1	4/2013	Condurso et al.
2011/0060758	A1	3/2011	Schlotterbeck et al.	2013/0096648	A1	4/2013	Benson
2011/0071844	A1	3/2011	Cannon et al.	2013/0102963	A1	4/2013	Marsh et al.
2011/0072379	A1	3/2011	Gannon	2013/0114594	A1	5/2013	Van Zijst
2011/0078253	A1	3/2011	Chan et al.	2013/0116578	A1	5/2013	An
				2013/0133083	A1	5/2013	Kurumai
				2013/0138452	A1	5/2013	Cork et al.
				2013/0144206	A1	6/2013	Lee et al.
				2013/0150824	A1	6/2013	Estes et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2013/0158504 A1	6/2013	Ruchti et al.	2016/0277152 A1	9/2016	Xiang et al.
2013/0167245 A1	6/2013	Birtwhistle et al.	2016/0285876 A1	9/2016	Perez et al.
2013/0173473 A1	7/2013	Birtwhistle et al.	2016/0317742 A1	11/2016	Gannon et al.
2013/0191770 A1	7/2013	Bartz et al.	2016/0350513 A1	12/2016	Jacobson et al.
2013/0204188 A1	8/2013	Kamen et al.	2016/0378618 A1	12/2016	Cmielowski
2013/0218080 A1	8/2013	Peterfreund et al.	2017/0024534 A1	1/2017	Arrizza et al.
2013/0261993 A1	10/2013	Ruchti et al.	2017/0034277 A1	2/2017	Jackson et al.
2013/0274669 A1	10/2013	Stempfle et al.	2017/0063559 A1	3/2017	Wallrabenstein
2013/0275539 A1	10/2013	Gross et al.	2017/0099148 A1	4/2017	Ochmanski et al.
2013/0291116 A1	10/2013	Homer	2017/0104645 A1	4/2017	Wooton et al.
2013/0296823 A1	11/2013	Melker et al.	2017/0111301 A1	4/2017	Robinson
2013/0296984 A1	11/2013	Burnett et al.	2017/0140134 A1	5/2017	Brough et al.
2013/0317753 A1	11/2013	Kamen et al.	2017/0146381 A1	5/2017	Eckel et al.
2013/0346108 A1	12/2013	Kamen et al.	2017/0149567 A1	5/2017	Moskal
2014/0025392 A1	1/2014	Chandrasenan	2017/0149929 A1	5/2017	Moskal
2014/0039446 A1	2/2014	Day	2017/0214762 A1	7/2017	Swain et al.
2014/0108783 A1	4/2014	Suzuki	2017/0246388 A1	8/2017	Kohlbrecher
2014/0142540 A1	5/2014	Imhof	2017/0258401 A1	9/2017	Volpe
2014/0142963 A1	5/2014	Hill et al.	2017/0258986 A1	9/2017	Tsoiukalis
2014/0163517 A1	6/2014	Finan et al.	2017/0262590 A1	9/2017	Karakosta et al.
2014/0172994 A1	6/2014	Raumann et al.	2017/0274140 A1	9/2017	Howard et al.
2014/0180711 A1	6/2014	Kamen et al.	2017/0286637 A1	10/2017	Arrizza et al.
2014/0197950 A1	7/2014	Shupp et al.	2017/0319780 A1	11/2017	Belkin et al.
2014/0215490 A1	7/2014	Mathur et al.	2017/0325091 A1	11/2017	Freeman et al.
2014/0257251 A1	9/2014	Bush et al.	2017/0331804 A1	11/2017	Jellison et al.
2014/0266790 A1	9/2014	Al-Ali et al.	2017/0351841 A1	12/2017	Moskal
2014/0266794 A1	9/2014	Brown et al.	2018/0008772 A1	1/2018	Wehba et al.
2014/0269643 A1	9/2014	Sun	2018/0028742 A1	2/2018	Day et al.
2014/0276571 A1	9/2014	Ludolph	2018/0043094 A1	2/2018	Day et al.
2014/0280522 A1	9/2014	Watte	2018/0063724 A1	3/2018	Zhang et al.
2014/0294177 A1	10/2014	Shastry et al.	2018/0121613 A1	5/2018	Connely, IV et al.
2014/0297329 A1	10/2014	Rock	2018/0122502 A1	5/2018	Jones et al.
2014/0316819 A1	10/2014	Dunsirn et al.	2018/0126067 A1	5/2018	Ledford et al.
2014/0318639 A1	10/2014	Peret et al.	2018/0157821 A1	6/2018	Fan
2014/0350513 A1	11/2014	Oruklu et al.	2018/0181712 A1	6/2018	Ensey et al.
2014/0358077 A1	12/2014	Oruklu et al.	2018/0247712 A1	8/2018	Muhsin et al.
2014/0366878 A1	12/2014	Baron	2018/0272117 A1	9/2018	Fangrow
2014/0371543 A1	12/2014	Steinhauer et al.	2018/0278594 A1	9/2018	Schiffman et al.
2015/0005935 A1	1/2015	Bae et al.	2018/0317826 A1	11/2018	Muhsin et al.
2015/0006907 A1	1/2015	Brouwer et al.	2018/0322948 A1	11/2018	Drost et al.
2015/0045729 A1	2/2015	Denzer et al.	2018/0359085 A1	12/2018	Dervyn
2015/0058044 A1	2/2015	Butler et al.	2019/0006044 A1	1/2019	Brask
2015/0058960 A1	2/2015	Schmoyer et al.	2019/0030329 A1	1/2019	Hannaman et al.
2015/0066531 A1	3/2015	Jacobson et al.	2019/0036688 A1	1/2019	Wasily et al.
2015/0081894 A1	3/2015	Blomquist	2019/0096518 A1	3/2019	Pace
2015/0100038 A1	4/2015	McCann et al.	2019/0132196 A1	5/2019	Trivedi et al.
2015/0100787 A1	4/2015	Westin et al.	2019/0147998 A1	5/2019	Ruchti et al.
2015/0117234 A1	4/2015	Raman et al.	2019/0166501 A1	5/2019	Debates et al.
2015/0134265 A1	5/2015	Kohlbrecher et al.	2019/0172590 A1	6/2019	Vesto et al.
2015/0141955 A1	5/2015	Ruchti et al.	2019/0207965 A1	7/2019	Espinosa
2015/0151051 A1	6/2015	Tsoukalis	2019/0228863 A1	7/2019	Dharwad et al.
2015/0161354 A1	6/2015	Blomquist	2019/0229982 A1	7/2019	Ikuta et al.
2015/0199192 A1	7/2015	Borges et al.	2019/0240405 A1	8/2019	Wehba et al.
2015/0199485 A1	7/2015	Borges et al.	2019/0243829 A1	8/2019	Butler et al.
2015/0207626 A1	7/2015	Neffel et al.	2019/0244689 A1	8/2019	Atkin
2015/0220890 A1	8/2015	Seshadri et al.	2019/0245942 A1	8/2019	Moskal
2015/0230760 A1	8/2015	Schneider	2019/0269852 A1	9/2019	Kohlbrecher
2015/0281128 A1	10/2015	Sindhu	2019/0311803 A1	10/2019	Kohlbrecher et al.
2015/0325064 A1	11/2015	Downey	2019/0348160 A1	11/2019	Heavelyn et al.
2015/0328396 A1	11/2015	Adams et al.	2019/0392929 A1	12/2019	Gassman
2015/0352301 A1	12/2015	Stedman et al.	2020/0023127 A1	1/2020	Simpson et al.
2015/0371004 A1	12/2015	Jones	2020/0027541 A1	1/2020	Xavier et al.
2015/0379237 A1	12/2015	Mills et al.	2020/0027548 A1	1/2020	Xavier et al.
2016/0001003 A1	1/2016	Perazzo et al.	2020/0027550 A1	1/2020	Xavier et al.
2016/0006695 A1	1/2016	Prodoehl et al.	2020/0027551 A1	1/2020	Xavier et al.
2016/0015885 A1	1/2016	Pananen et al.	2020/0035355 A1	1/2020	Xavier et al.
2016/0034655 A1	2/2016	Gray et al.	2020/0054825 A1	2/2020	Kamen et al.
2016/0045661 A1	2/2016	Gray et al.	2020/0118692 A1	4/2020	Booker et al.
2016/0051749 A1	2/2016	Istoc	2020/0153627 A1	5/2020	Wentz
2016/0051751 A1	2/2016	Silkaitis et al.	2020/0206413 A1	7/2020	Silkaitis et al.
2016/0063471 A1	3/2016	Kobres et al.	2020/0220865 A1	7/2020	Finger et al.
2016/0103960 A1	4/2016	Hume et al.	2020/0282139 A1	9/2020	Susi
2016/0158437 A1	6/2016	Biasi et al.	2020/0334497 A1	10/2020	Barrett et al.
2016/0228633 A1	8/2016	Welsch et al.	2020/0335194 A1	10/2020	Jacobson et al.
2016/0241391 A1	8/2016	Fenster	2020/0351376 A1	11/2020	Moskal
			2020/0353167 A1	11/2020	Vivek et al.
			2020/0353168 A1	11/2020	Keenan et al.
			2021/0014259 A1	1/2021	Harris et al.
			2021/0043296 A1	2/2021	Xavier et al.

(56)	References Cited			EP	0 652 528	5/1995
	U.S. PATENT DOCUMENTS			EP	0 672 427	9/1995
				EP	0 683 465	11/1995
				EP	0 880 936	12/1998
2021/0045640	A1	2/2021	Poltorak	EP	1 050 993	11/2000
2021/0085855	A1	3/2021	Belkin et al.	EP	1 157 711	11/2001
2021/0098106	A1	4/2021	Kohlbrecher et al.	EP	1 174 817	1/2002
2021/0098107	A1	4/2021	Xavier et al.	EP	0 664 102	4/2002
2021/0252210	A1	8/2021	Day et al.	EP	1 197 178	4/2002
2021/0358603	A1	11/2021	Xavier et al.	EP	0 830 775	8/2002
2021/0375421	A1	12/2021	Ruchti et al.	EP	1 500 025	4/2003
2021/0375438	A1	12/2021	Xavier et al.	EP	1 487 171	7/2007
2021/0409362	A1	12/2021	Katis et al.	EP	1 933 497	6/2008
2022/0023535	A1	1/2022	Day	EP	2 026 223	2/2009
2022/0037011	A1	2/2022	Fryman	EP	2 113 842	11/2009
2022/0037012	A1	2/2022	Fryman	EP	2 228 004	9/2010
2022/0051777	A1	2/2022	Xavier et al.	EP	2 243 506	10/2010
2022/0062541	A1	3/2022	Kamen et al.	EP	2 410 448	1/2012
2022/0129452	A1	4/2022	Butler et al.	EP	2 742 961	6/2014
2022/0139536	A1	5/2022	Xavier et al.	EP	2 874 087	5/2015
2022/0139537	A1	5/2022	Xavier et al.	ES	2 371 995	1/2012
2022/0139538	A1	5/2022	Xavier et al.	FR	2 717 919	9/1995
2022/0150307	A1	5/2022	Walsh et al.	GB	2 285 135	6/1995
2022/0165404	A1	5/2022	Vivek et al.	JP	04-161139	6/1992
2022/0189605	A1	6/2022	Kelly et al.	JP	07-502678	3/1995
2022/0223283	A1	7/2022	Biasi et al.	JP	11-500643	1/1999
2022/0270736	A1	8/2022	Kohlbrecher	JP	2000-316820	11/2000
2022/0328175	A1	10/2022	Arrizza et al.	JP	2002-531154	9/2002
2022/0331513	A1	10/2022	Howard et al.	JP	2003-016183	1/2003
2022/0344023	A1	10/2022	Xavier et al.	JP	2003-296173	10/2003
2022/0375565	A1	11/2022	Xavier et al.	JP	2003-308586	10/2003
2022/0384059	A1	12/2022	Xavier et al.	JP	2005-021463	1/2005
2023/0009405	A1	1/2023	Xavier et al.	JP	2005-527284	9/2005
2023/0009417	A1	1/2023	Xavier et al.	JP	2005-284846	10/2005
2023/0139360	A1	5/2023	Kohlbrecher et al.	JP	2006-047319	2/2006
2023/0145267	A1	5/2023	Xavier et al.	JP	2006-520949	9/2006
2023/0147762	A1	5/2023	Xavier et al.	JP	2007-518479	7/2007
2023/0166026	A1	6/2023	Jacobson et al.	JP	2007-525256	9/2007
2023/0253108	A1	8/2023	Dharwad et al.	JP	2008-080036	4/2008
2023/0285660	A1	9/2023	Day et al.	JP	2008-516303	5/2008
2023/0298768	A1	9/2023	Jacobson et al.	JP	2008-158622	7/2008
2023/0320935	A1	10/2023	Tagliamento	JP	2008-529675	8/2008
2023/0321350	A1	10/2023	Day et al.	JP	2009-163534	7/2009
2023/0321351	A1	10/2023	Wehba et al.	JP	2010-502361	1/2010
2023/0326570	A1	10/2023	Kohlbrecher	JP	2011-506048	3/2011
2023/0410989	A1	12/2023	Xavier et al.	JP	2012-011204	1/2012
2024/0038358	A1	2/2024	Xavier et al.	JP	2012-070991	4/2012
2024/0047035	A1	2/2024	Ruchti et al.	JP	2012-523895	10/2012
2024/0071609	A1	2/2024	Rohlwing	JP	2014-068283	4/2014
				JP	5647644	1/2015
				TW	200426656	12/2004
				TW	1631966	8/2018

(56)

References Cited

FOREIGN PATENT DOCUMENTS

WO	WO 03/091836	11/2003
WO	WO 03/094092	11/2003
WO	WO 2004/060455	7/2004
WO	WO 2004/070557	8/2004
WO	WO 2004/070562	8/2004
WO	WO 2004/072828	8/2004
WO	WO 2005/036447	4/2005
WO	WO 2005/050526	6/2005
WO	WO 2005/057175	6/2005
WO	WO 2005/066872	7/2005
WO	WO 2007/087443	8/2007
WO	WO 2007/117705	10/2007
WO	WO 2007/127879	11/2007
WO	WO 2007/127880	11/2007
WO	WO 2008/059495	5/2008
WO	WO 2008/064254	5/2008
WO	WO 2008/067245	6/2008
WO	WO 2008/082854	7/2008
WO	WO 2008/088490	7/2008
WO	WO 2008/097316	8/2008
WO	WO 2008/103915	8/2008
WO	WO 2008/124478	10/2008
WO	WO 2008/134146	11/2008
WO	WO 2009/016504	2/2009
WO	WO 2009/023406	2/2009
WO	WO 2009/023407	2/2009
WO	WO 2009/023634	2/2009
WO	WO 2009/036327	3/2009
WO	WO 2009/049252	4/2009
WO	WO 2010/017279	2/2010
WO	WO 2010/033919	3/2010
WO	WO 2010/053703	5/2010
WO	WO 2010/075371	7/2010
WO	WO 2010/099313	9/2010
WO	WO 2010/114929	10/2010
WO	WO 2010/119409	10/2010
WO	WO 2010/124127	10/2010
WO	WO 2010/130992	11/2010
WO	WO 2010/135646	11/2010
WO	WO 2010/135654	11/2010
WO	WO 2010/135686	11/2010
WO	WO 2011/005633	1/2011
WO	WO 2011/022549	2/2011
WO	WO 2012/048833	4/2012
WO	WO 2012/049214	4/2012
WO	WO 2012/049218	4/2012
WO	WO 2012/120078	9/2012
WO	WO 2012/140547	10/2012
WO	WO 2012/164556	12/2012
WO	WO 2012/170942	12/2012
WO	WO 2013/045506	4/2013
WO	WO 2014/100736	6/2014
WO	WO 2014/131729	9/2014
WO	WO 2014/131730	9/2014
WO	WO 2015/047595	4/2015
WO	WO 2015/124569	8/2015
WO	WO 2016/179389	11/2016
WO	WO 2017/176928	10/2017
WO	WO 2017/200989	11/2017
WO	WO 2019/219290	11/2019
WO	WO 00/003344	1/2020
WO	WO 2020/227403	11/2020
WO	WO 2021/201884	10/2021
WO	WO 2022/006014	1/2022
WO	WO 2022/051230	3/2022
WO	WO 2023/159134	8/2023

OTHER PUBLICATIONS

Ahn et al., "Towards Scalable Authentication in Health Services", Eleventh IEEE International Workshops on Enabling Technologies: Infrastructure for Collaborative Enterprises, Jun. 2002, pp. 83-88.

Akridge, Jeannie, "New Pumps Outsmart User Error", Healthcare Purchasing News, Apr. 2011, pp. 10, <<http://web.archive.org/web/20110426122450/http://www.hpnonline.com/inside/2011-04/1104-OR-Pumps.html>>.

20110426122450/<http://www.hpnonline.com/inside/2011-04/1104-OR-Pumps.html>>.

Alur et al., "Formal Specifications and Analysis of the Computer-Assisted Resuscitation Algorithm (CARA) Infusion Pump Control System", International Journal on Software Tools for Technology Transfer, Feb. 2004, vol. 5, No. 4, pp. 308-319.

Aragon, Daleen RN, Ph.D., CCRN, "Evaluation of Nursing Work Effort and Perceptions About Blood Glucose Testing in Tight Glycemic Control", American Journal of Critical Care, Jul. 2006, vol. 15, No. 4, pp. 370-377.

ASHP Advantage, "Improving Medication Safety in Health Systems Through Innovations in Automation Technology", Proceedings of Educational Symposium and Educational Sessions during the 39th ASHP Midyear Clinical Meeting, Dec. 5-9, 2004, Orlando, FL, pp. 28.

Beard et al., "Total Quality Pain Management: History, Background, Resources", Abbott Laboratories, TQPM Survey History, available Feb. 2015 or earlier, pp. 1-3.

Bektas et al., "Bluetooth Communication Employing Antenna Diversity", Proceedings of Eight IEEE International Symposium on Computers and Communication, Jul. 2003, pp. 6.

Bellare et al., "Security Proofs for Identity-Based Identification and Signature Schemes", Lecture Notes in Computer Science, Jan. 2009, vol. 22, No. 1, pp. 18.

Bequette, Ph.D., "A Critical Assessment of Algorithms and Challenges in the Development of a Closed-Loop Artificial Pancreas", Diabetes Technology & Therapeutics, Feb. 28, 2005, vol. 7, No. 1, pp. 28-47.

Bequette, B. Wayne, Ph.D., "Analysis of Algorithms for Intensive Care Unit Blood Glucose Control", Journal of Diabetes Science and Technology, Nov. 2007, vol. 1, No. 6, pp. 813-824.

Block, Alexander, "Secret Sharing and 1-11 Threshold Signatures with BLS", Jul. 2, 2018, <https://blog.dash.org/secret-sharing-and-threshold-signatures-with-bls-954d1587b5f>, in 8 pages.

Braun, "Infusomat® Space and Accessories", Instructions for Use, Nov. 2010, pp. 68. <[http://corp.bbBraun.de/Extranet/Infusionpumpe/Kasutusjuhendid/Vanad/Kasutusjuhend-Infusomat_Space\(vers688J,inglise_k\).pdf](http://corp.bbBraun.de/Extranet/Infusionpumpe/Kasutusjuhendid/Vanad/Kasutusjuhend-Infusomat_Space(vers688J,inglise_k).pdf)>.

Brownlee, Seth, "Product Spotlight: The Plum A+ with Hospira MedNet Infusion System", PP&P Magazine, Dec. 2005, vol. 2, No. 7, pp. 2.

Cannon, MD et al., "Automated Heparin-Delivery System to Control Activated Partial Thromboplastin Time", Circulation, Feb. 16, 1999, vol. 99, pp. 751-756.

Cardinal Health, "Alaris® Syringe Pumps" Technical Service Manual, Copyright 2002-2006, Issue 9, pp. 1-88, <http://www.frankshospitalworkshop.com/equipment/documents/infusion_pumps/service_manuals/Cardinal_Alaris_-_Service_Manual.pdf>.

"CareAware® Infusion Management", Cerner Store, as printed May 12, 2011, pp. 3, <<https://store.cerner.com/items/7>>.

Chen et al., "Enabling Location-Based Services on Wireless LANs", The 11th IEEE International Conference on Networks, ICON 2003, Sep. 28-Oct. 1, 2003, pp. 567-572.

"Computer Dictionary", Microsoft Press, Third Edition, Microsoft Press, 1997, pp. 430 & 506.

"Context-Free Grammar", Wikipedia.org, as last modified Mar. 5, 2010 in 11 pages, <https://en.wikipedia.org/w/index.php?title=Context-free_grammar&oldid=347915989>.

Crawford, Anne J., MSN, RNC, "Building a Successful Quality Pain Service: Using Patient Satisfaction Data and the Clinical Practice Guideline", USA, 1995, pp. 1-6.

Crocker et al., "Augmented BNF for Syntax Specifications: ABNF", Network Working Group, Standards Track, Jan. 2008, pp. 16.

Davidson et al., "A Computer-Directed Intravenous Insulin System Shown to be Safe, Simple, and Effective in 120,618 h of Operation", Diabetes Care, Oct. 2005, vol. 28, No. 10, pp. 2418-2423.

Davies, T., "Cordless Data Acquisition in a Hospital Environment", IEE Colloquium on Cordless Computing—Systems and User Experience, 1993, pp. 4.

Dayhoff et al., "Medical Data Capture and Display: The Importance of Clinicians' Workstation Design", AMIA, Inc., 1994, pp. 541-545.

(56)

References Cited**OTHER PUBLICATIONS**

- Diabetes Close Up, Close Concerns AACE Inpatient Management Conference Report, Consensus Development Conference on Inpatient Diabetes and Metabolic Control, Washington, D.C., Dec. 14-16, 2003, pp. 1-32.
- Doesburg et al., "Improved Usability of a Multi-Infusion Setup Using a Centralized Control Interface: A Task-Based Usability Test", Aug. 11, 2017, PLoS ONE, vol. 12, No. 8, pp. 10.
- "Download", Free On-Line Dictionary of Computing, as archived Jun. 16, 2010 in 1 page, <http://web.archive.org/web/20100616010314/https://foldoc.org/download>.
- East PhD et al., "Digital Electronic Communication Between ICU Ventilators and Computers and Printers", Respiratory Care, Sep. 1992, vol. 37, No. 9, pp. 1113-1122.
- Edworthy, Judy, "Medical Audible Alarms: A Review", Journal of the American Medical Informatics Association, vol. 20, No. 3, 2013, pp. 584-589.
- Einhorn, George W., "Total Quality Pain Management: A Computerized Quality Assessment Tool for Postoperative Pain Management", Abbott Laboratories, Chicago, IL, Mar. 2, 2000, pp. 1-4.
- Eskew et al., "Using Innovative Technologies to Set New Safety Standards for the Infusion of Intravenous Medications", Hospital Pharmacy, 2002, vol. 37, No. 11, pp. 1179-1189.
- Felleiter et al., "Data Processing in Prehospital Emergency Medicine", International Journal of Clinical Monitoring and Computing, Feb. 1995, vol. 12, No. 1, pp. 37-41.
- "File Verification", Wikipedia.org, as last modified Oct. 11, 2011 in 2 pages, <https://en.wikipedia.org/w/index.php?title=File_verification&oldid=455048290>.
- Fogt et al., Development and Evaluation of a Glucose Analyzer for a Glucose-Controlled Insulin Infusion System (Biostator®), Clinical Chemistry, 1978, vol. 24, No. 8, pp. 1366-1372.
- Gabel et al., "Camp: A Common API for Measuring Performance", 21st Large Installations System Administration Conference (LISA '07), 2007, pp. 49-61.
- Gage et al., "Automated Anesthesia Surgery Medical Record System", International Journal of Clinical Monitoring and Computing, Dec. 1990, vol. 7, No. 4, pp. 259-263.
- Galt et al., "Personal Digital Assistant-Based Drug Information Sources: Potential to Improve Medication Safety", Journal of Medical Library Association, Apr. 2005, vol. 93, No. 2, pp. 229-236.
- Gardner, Ph.D et al., "Real Time Data Acquisition: Recommendations for the Medical Information Bus (MIB)", 1992, pp. 813-817.
- "General-Purpose Infusion Pumps", Health Devices, EXRI Institute, Oct. 1, 2002, vol. 31, No. 10, pp. 353-387.
- Givens et al., "Exploring the Internal State of User Interfaces by Combining Computer Vision Techniques with Grammatical Inference", Proceedings of the 2013 International Conference on Software Engineering, San Francisco, CA, May 18-26, 2013, pp. 1165-1168.
- Glaeser, "A Hierarchical Minicomputer System for Continuous Post-Surgical Monitoring", Computers and Biomedical Research, Aug. 31, 1975, pp. 336-361.
- Goldberg et al., "Clinical Results of an Updated Insulin Infusion Protocol in Critically Ill Patients", Diabetes Spectrum, 2005, vol. 18, No. 3, pp. 188-191.
- Gomez et al., "CLAM: Connection-Less, Lightweight, and Multiway Communication Support for Distributed Computing", Computer Science, 1997, vol. 1199, pp. 227-240.
- "GPS Tracker for Medical Equipment", <<http://www.trackingsystem.com/forbusinesses/corporate-trackingsystem/1098-gps-tracker-formedicalequipment.html>>, Mar. 15, 2015, pp. 2.
- Graseby, "Model 3000/500 and Micro 3100/505: Volumetric Infusion Pump", Technical Service Manual, Graseby Medical Ltd., Apr. 2002, Issue A, pp. 160.
- Graseby, "Model 3000/500 and Micro 3100/505: Volumetric Infusion Pump: Illustrated Parts List for Pump Serial Nos. from 3000 to 59,999", Technical Service Manual, Graseby Medical Ltd., Apr. 2002, Issue A, pp. 71.
- Gutwin et al., "Gone But Not Forgotten: Designing for Disconnection in Synchronous Groupware", CSCW 2010, Feb. 6-10, 2010, Savannah, Georgia, USA., pp. 179-188.
- Halpern et al., "Changes in Critical Care Beds and Occupancy in the United States 1985-2000: Differences Attributable to Hospital Size", Critical Care Medical, Aug. 2006, vol. 34, No. 8, pp. 2105-2112.
- Hamann et al., "PUMPSIM: A Software Package for Simulating Computer-Controlled Drug Infusion Pumps", Annual International Conference of the IEEE Engineering in Medicine and Biology Society, 1990, vol. 12, No. 5, pp. 2019-2020.
- Hasegawa et al., "On a Portable Memory Device for Physical Activities and Informations of Maternal Perception", Journal of Perinatal Medicine, 1988, vol. 16, No. 4, pp. 349-356.
- Hawley et al., "Clinical Implementation of an Automated Medical Information Bus in an Intensive Care Unit", Proceedings of the Annual Symposium on Computer Application in Medical Care, Nov. 9, 1988, pp. 621-624.
- Hayes-Roth et al., "Guardian: A Prototype Intelligent Agent for Intensive-Care Monitoring", Artificial Intelligence in Medicine, vol. 4, Dec. 31, 1992, pp. 165-185.
- Hospira, GemStar® Pain Management Infusion System 9-084-PR1-2-2, <www.hospira.com/products/gemstar_painmanagement.aspx>, Jan. 28, 2010, pp. 1-2.
- Huang et al., "Secure Identity-Based Data Sharing and Profile Matching for Mobile Healthcare Social Networks in Cloud Computing", vol. 6, Jul. 2018, pp. 36584-36594.
- Introducing Abbott TQPM (Total Quality Pain Management), Abbott Laboratories, Abbott Park, IL, May 2000, pp. 1-4.
- "Infusion Pump", Wikipedia.org, as last modified Mar. 27, 2014, in 3 pages, <https://web.archive.org/web/20140703024932/https://en.wikipedia.org/wiki/Infusion_pump>.
- Isaka et al., "Control Strategies for Arterial Blood Pressure Regulation", IEEE Transactions on Biomedical Engineering, Apr. 1993, vol. 40, No. 4, pp. 353-363.
- Johnson et al., "Using BCMA Software to Improve Patient Safety in Veterans Administration Medical Centers", Journal of Healthcare Information Management, Dec. 6, 2004, vol. 16, No. 1, pp. 46-51.
- Kent Displays, "Reflex™ Electronic Skins", Product Brief 25127B, 2009, pp. 2.
- Kent Displays, "Reflex Electronic Skins Engineering Evaluation Kit", 25136A, Mar. 10, 2009.
- Lefkowitz et al., "A Trial of the Use of Bar Code Technology to Restructure a Drug Distribution and Administration System", Hospital Pharmacy, Mar. 31, 1991, vol. 26, No. 3, pp. 239-242.
- Lenssen et al., "Bright Color Electronic Paper Technology and Applications", IDS '09 Publication EP1-2 (Phillips Research), 2009, pp. 529-532.
- Leveson, Nancy, "Medical Devices: The Therac-25", Appendix A, University of Washington, 1995, pp. 49.
- Li et al., "Hijacking an Insulin Pump: Security Attacks and Defenses for a Diabetes Therapy System", 2011 IEEE 13th International Conference on e-Health Networking, Applications and Services, 2011, pp. 150-156.
- Linkens, D.A. "Computer Control for Patient Care", Computer Control of Real-Time Processes, IEE Control Engineering Series 41, 1990, Ch. 13, pp. 216-238.
- Mako Hill et al., "The Official Ubuntu Book", Shoeisha Co., Ltd., 1st Edition, Jun. 11, 2007, pp. 115 to 125.
- Marshall, et al., "New Microprocessor-Based Insulin Controller", IEEE Transactions on Biomedical Engineering, Nov. 1983, vol. BME-30, No. 11, pp. 689-695.
- Martino et al., "Automation of a Medical Intensive Care Environment with a Flexible Configuration of Computer Systems", Proceedings of the Annual Symposium on Computer Application in Medical Care, Nov. 5, 1980, vol. 3, pp. 1562-1568.
- Matsunaga et al., "On the Use of Machine Learning to Predict the Time and Resources Consumed by Applications", 2010 10th IEEE/ACM International Conference on Cluster, Cloud and Grid Computing (CCGrid), May 17-20, 2010, pp. 495-504.
- Mauseth et al., "Proposed Clinical Application for Tuning Fuzzy Logic Controller of Artificial Pancreas Utilizing a Personalization Factor", Journal of Diabetes Science and Technology, Jul. 2010, vol. 4, No. 4, pp. 913-922.

(56)

References Cited**OTHER PUBLICATIONS**

- "McKesson Automation and ALARIS Medical Systems Developing Point-of-Care Bar Coding Solution to Improve IV Medication Safety", PR Newswire, NY, Dec. 9, 2002, pp. 4.
- Medfusion™, "Medfusion Syringe Infusion Pump Model 4000", Operator's Manual, Software Version V1.1, Sep. 2011, pp. 154. <http://www.medfusionpump.com/assets/literature/manuals/Operators_Manual_4000_40-5760-51A.pdf>.
- Metnitz et al., "Computer Assisted Data Analysis in Intensive Care: the ICDEV Project-Development of a Scientific Database System for Intensive Care", International Journal of Clinical Monitoring and Computing, Aug. 1995, vol. 12, No. 3, pp. 147-159.
- Michienzi, Kelly, "Managing Drug Library Updates", Pharmacy Purchasing Products, <https://www.pppmag.com/article/1061>, Feb. 2012, vol. 9, pp. 22-23.
- Micrel Medical Devices, "MP Daily +" <<http://web.archive.org/web/20130803235715/http://www.micrelmed.com/index.aspx?productid=9>> as archived Aug. 3, 2013 in 1 page.
- Moghissi, Etie, MD, FACP, FACE, "Hyperglycemia in Hospitalized Patients", A Supplement to ACP Hospitalist, Jun. 15, 2008, pp. 32.
- Murphy, Robert, "The Design of Safety-Critical Medical Infusion Devices", May 30, 2007, Doctor of Philosophy submission, pp. 317.
- Murray, Jr. et al., "Automated Drug Identification System (during surgery)", IEEE Proceedings of Southeastcon '91, Apr. 7-10, 1991, pp. 265.
- Nicholson et al., "Smart' Infusion Apparatus for Computation and Automated Delivery of Loading, Tapering, and Maintenance Infusion Regimens of Lidocaine, Procainamide, and Theophylline", Proceedings of the Seventh Annual Symposium on Computer Applications in Medical Care, Oct. 1983, pp. 212-213.
- Nojournian et al., "Social Secret Sharing in Cloud Computing Using a New Trust Function", 2012 Tenth Annual International Conference on Privacy, Security and Trust, pp. 161-167.
- Nolan et al., "The P1073 Medical Information Bus Standard: Overview and Benefits for Clinical Users", 1990, pp. 216-219.
- Omnilink Systems, Inc., "Portable Medical Equipment Tracking", <<http://www.omnilink.com/portablemedicalequipmenttracking/>>, Mar. 15, 2015, pp. 2.
- O'Shea, Kristen L., "Infusion Management: Working Smarter, Not Harder", Hospital Pharmacy, Apr. 2013, vol. 48, No. 3, pp. S1-S14.
- Package Management in Debian GNU/Linux, Debian GNU/Linux Expert Desktop Use Special, Giutsu-Hyohron Co., Ltd., First Edition, Sep. 25, 2004, pp. 183-185.
- Passos et al., "Distributed Software Platform for Automation and Control of General Anaesthesia", Eighth International Symposium on Parallel and Distributed Computing, ISPDC '09, Jun. 30-Jul. 4, 2009, pp. 8.
- Philips, "IntelliSpace Event Management and IntelliVue Patient Monitoring", Release 10, 2011, <http://incenter.medical.philips.com/doclib/enc/fetch/2000/4504/577242/577243/577247/582646/583147/8359175/Philips_Patient_Monitoring_and_IntelliSpace_Event_Management_Interoperability.pdf%3fnodeid%3d8508574%26vernum%3d-2>, pp. 2.
- Pretty et al., "Hypoglycemia Detection in Critical Care Using Continuous Glucose Monitors: An in Silico Proof of Concept Analysis", Journal of Diabetes Science and Technology, Jan. 2010, vol. 4, No. 1, pp. 15-24.
- Rahmani et al., "Smart e-Health Gateway: Bringing Intelligence to Internet-of-Things Based Ubiquitous Healthcare Systems", 2015 12th Annual IEEE Consumer Communications and Networking Conference (CCNC), Jul. 2015, pp. 826-834.
- Rappoport, Arthur E., "A Hospital Patient and Laboratory machine-Readable Identification System (MRIS) Revisited", Journal of Medical Systems, Apr. 1984, vol. 8, Nos. 1/2, pp. 133-156.
- Ritchie et al., "A Microcomputer Based Controller for Neuromuscular Block During Surgery", Annals of Biomedical Engineering, Jan. 1985, vol. 13, No. 1, pp. 3-15.
- Saager et al., "Computer-Guided Versus Standard Protocol for Insulin Administration in Diabetic Patients Undergoing Cardiac Surgery", Annual Meeting of the American Society of Critical Care Anesthesiologists, Oct. 13, 2006.
- Sanders et al., "The Computer in a Programmable Implantable Medication System (PIMS)", Proceedings of the Annual Symposium on Computer Application in Medical Care, Nov. 2, 1982, pp. 682-685.
- Schilling et al., "Optimizing Outcomes! Error Prevention and Evidence-Based Practice with IV Medications", A Pro-Ce Publication, Hospira, Inc., Feb. 6, 2012, pp. 56.
- Schulze et al., "Advanced Sensors Technology Survey", Final Report, Feb. 10, 1992, pp. 161.
- Scott, et al., "Using Bar-Code Technology to Capture Clinical Intervention Data in a Hospital with a Stand-Alone Pharmacy Computer System", Mar. 15, 1996, American Journal of Health-System Pharmacy, vol. 53, No. 6, pp. 651-654.
- Sebald et al., "Numerical Analysis of a Comprehensive in Silico Subcutaneous Insulin Absorption Compartmental Model", 31st Annual International Conference of the IEEE Engineering in Medicine and Biology Society, Sep. 2-6, 2009, pp. 3901-3904.
- Shabot, M. Michael, "Standardized Acquisition of Bedside Data: The IEEE P1073 Medical Information Bus", International Journal of Clinical Monitoring and Computing, vol. 6, Sep. 27, 1989, pp. 197-204.
- Sheppard, Louis, Ph.D., "Automation of the Infusion of Drugs Using Feedback Control", Journal of Cardiothoracic and Vascular Anesthesia, Feb. 28, 1989, vol. 3, No. 1, pp. 1-3.
- Sheppard, Louis, Ph.D., "Computer Control of the Infusion of Vasoactive Drugs", Annals of Biomedical Engineering, Jul. 1980, vol. 8, No. 4-6, pp. 431-444.
- Sheppard, Louis, Ph.D., "The Application of Computers to the Measurement, Analysis, and Treatment of Patients Following Cardiac Surgical Procedures", The University of Alabama in Birmingham, Oct. 31, 1977, pp. 297-300.
- Sheppard, Louis, Ph.D., "The Computer in the Care of Critically Ill Patients", Proceedings of the IEEE, Sep. 1979, vol. 67, No. 9, pp. 1300-1306.
- "Sigma Spectrum: Operator's Manual", May 15, 2008, pp. 63. <<https://usme.com/content/manuals/sigma-spectrum-operator-manual.pdf>>.
- "Sigma Spectrum: Operator's Manual", Oct. 2009, pp. 72. <<http://static.medonecapital.com/manuals/userManuals/Sigma-Spectrum-Operator-Manual-October-2009.pdf>>.
- Simonsen, Michael Ph.D., POC Testing, New Monitoring Strategies on Fast Growth Paths in European Healthcare Arenas, Biomedical Business & Technology, Jan. 2007, vol. 30, No. 1, pp. 1-36.
- Siv-Lee et al., "Implementation of Wireless 'Intelligent' Pump IV Infusion Technology in a Not-for-Profit Academic Hospital Setting", Hospital Pharmacy, Sep. 2007, vol. 42, No. 9, pp. 832-840. <<http://www.thomasland.com/hpj4209-832.pdf>>.
- Slack, W.V., "Information Technologies for Transforming Health Care", <<https://www.andrew.cmu.edu/course/90-853/medis.dir/otadocs.dir/03ch2.pdf>>, Ch. 2, 1995, pp. 29-78.
- Smith, Joe, "Infusion Pump Informatics", CatalyzeCare: Transforming Healthcare, as printed May 12, 2011, pp. 2.
- Sodders, Lisa, "VA Center Keeps Medicine in Right Hands", The Capital-Journal, Dec. 4, 1999, pp. 1-2.
- "Software Versioning", Wikipedia.org, dated Oct. 16, 2011 in 11 pages, <https://en.wikipedia.org/w/index.php?title=Software_versioning&oldid=455859110>.
- Solapurkar et al., "Building Secure Healthcare Services Using OAuth 2.0 and JSON Web Token in IOT Cloud Scenario", Dec. 2016, 2nd International Conference on Contemporary Computing and Informatics, pp. 99-10.
- Stitt, F.W., "The Problem-Oriented Medical Synopsis: a Patient-Centered Clinical Information System", Proceedings of the Annual Symposium on Computer Application in Medical Care, 1994, pp. 88-92.
- Stokowski, Laura A. RN, MS, "Using Technology to Improve Medication Safety in the Newborn Intensive Care Unit", Advances in Neonatal Care, Dec. 2001, vol. 1, No. 2, pp. 70-83.
- Sutton et al., "The Syntax and Semantics of the PROforma Guideline Modeling Language", Journal of the American Medical Informatics Association, Sep./Oct. 2003, vol. 10, No. 5, pp. 433-443.

(56)

References Cited**OTHER PUBLICATIONS**

Szeinbach et al., "Automated Dispensing Technologies: Effect on Managed Care", *Journal of Managed Care Pharmacy (JMCP)*, Sep./Oct. 1995, vol. 1, No. 2, pp. 121-127.

Szolovits et al., "Guardian Angel: Patient-Centered Health Information Systems", Technical Report MIT/LCS/TR-604, Massachusetts Institute of Technology Laboratory for Computer Science, May 1994, pp. 39.

"TCG TPM v2.0 Provisioning Guidance", Reference, Version 1, Revision 1, Mar. 15, 2017, pp. 1-43.

Van Den Berghe, M.D., Ph.D., et al., "Intensive Insulin Therapy in Critically Ill Patients", *The New England Journal of Medicine*, Nov. 8, 2001, vol. 345, No. 19, pp. 1359-1367.

Van Den Berghe, M.D., Ph.D., et al., "Intensive Insulin Therapy in the Medical ICU", *The New England Journal of Medicine*, Feb. 2, 2006, vol. 354, No. 5, pp. 449-461.

Van Der Maas et al., "Requirements for Medical Modeling Languages", *Journal of the American Medical Informatics Association*, Mar./Apr. 2001, vol. 8, No. 2, pp. 146-162.

Villalobos et al., "Computerized System in Intensive Care medicine", *Medical Informatics*, vol. 11, No. 3, 1986, pp. 269-275.

Wilkins et al., "A Regular Language: The Annotated Case Report Form", PPD Inc., PharmaSUG2011—Paper CD18, 2011, pp. 1-9.

Ying et al., "Regulating Mean Arterial Pressure in Postsurgical Cardiac Patients. A Fuzzy Logic System to Control Administration of Sodium Nitroprusside", *IEEE Engineering in Medicine and Biology Magazine*, vol. 13, No. 5, Nov.-Dec. 1994, pp. 671-677.

Yoo et al., "Code-Based Authentication Scheme for Lightweight Integrity Checking of Smart Vehicles", *IEEE Access*, 2018, vol. 6, pp. 46731-46741.

Yue, Ying Kwan, "A Healthcare Failure Mode and Effect Analysis on the Safety of Secondary Infusions", Thesis, Institute of Biomaterials and Biomedical Engineering, University of Toronto, 2012, pp. 168.

Yurkonis et al., "Computer Simulation of Adaptive Drug Infusion", *IEEE Transactions on Biomedical Engineering*, vol. BME-34, No. 8, Aug. 1987, pp. 633-635.

Zakariah et al., "Combination of Biphasic Transmittance Waveform with Blood Procalcitonin Levels for Diagnosis of Sepsis in Acutely Ill Patients", *Critical Care Medicine*, 2008, vol. 36, No. 5, pp. 1507-1512.

International Search Report and Written Opinion received in PCT Application No. PCT/US2014/021335, dated Jul. 8, 2014 in 13 pages.

International Preliminary Report on Patentability and Written Opinion received in PCT Application No. PCT/US2014/021335, dated Sep. 17, 2015 in 12 pages.

FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9





FIG. 10A



Connection Type	Destination Address	Destination Port	Source Port	CID	File Descriptor
Service	8	50	40	100	55
TCP	5	23	60	72	63
Service	15	68	40	110	87
TCP	4	20	55	103	21

FIG. 10B

Connection Oriented
Data Transfer

Layer Flag [1 bit]	Connection Type [2 bits]	Message Type [4 bits]	CID	Data
0	Connection Oriented	Data	1 Byte	N Bytes

Connectionless Data
Transfer

Layer Flag [1 bit]	Connection Type [2 bits]	Message Type [4 bits]	Source Port	Destination Port	Data
0	Connection Less	Data	1 Byte	1 Byte	N Bytes

Connection
Request

Layer Flag [1 bit]	Connection Type [2 bits]	Message Type [4 bits]	Command [1 Byte]	Source Port	Destination Port
1	Unknown	Connection	Connection Request	1 Byte	1 Byte

Connection
Accept

Layer Flag [1 bit]	Connection Type [2 bits]	Msg. Type [4 bits]	Command [1 Byte]	CID	Destination Port	Source Port
1	Unknown	Connection	Connection Accept	1 Byte	1 Byte	1 Byte

Connection
Acknowledgement

Layer Flag [1 bit]	Connection Type [2 bits]	Message Type [4 bits]	Command [1 Byte]	CID	Source Port
1	Unknown	Connection	Connection Ack.	1 Byte	1 Byte

Connection
Disconnect

Layer Flag [1 bit]	Connection Type [2 bits]	Message Type [4 bits]	Command [1 Byte]	CID	Source Port
1	Unknown	Connection	Connection Disconnect	1 Byte	1 Byte

Connection
Disconnect Ack

Layer Flag [1 bit]	Connection Type [2 bits]	Message Type [4 bits]	Command [1 Byte]	CID	Source Port
1	Unknown	Connection	Connection Disconnect Ack	1 Byte	1 Byte

FIG. 10C

Connection
Reject

Layer Flag [1 bit]	Connection Type [2 bits]	Msg. Type [4 bits]	Command [1 Byte]	Destination Port	Source Port	Reason
1	Unknown	Connection	Connection Reject	1 Byte	1 Byte	1 Byte

CID Info
Request

Layer Flag [1 bit]	Connection Type [2 bits]	Message Type [4 bits]	Command [1 Byte]	CID	Source Port
1	Unknown	CID	CID Info Request	1 Byte	1 Byte

CID Info
Response

Layer Flag [1 bit]	Conn. Type [2 bits]	Msg. Type [4 bits]	Command [1 Byte]	CID	Source Port	Info Length [1 Byte]	CID Info
1	Unknown	CID	CID Info Response	1 Byte	1 Byte	1 Byte	1 Byte

Socket Status
Request

Layer Flag [1 bit]	Conn. Type [2 bits]	Message Type [4 bits]	Command [1 Byte]	CID	Source Port
1	Unknown	Socket	Socket Status Request	1 Byte	1 Byte

Socket Status
Response

Layer Flag [1 bit]	Conn. Type [2 bits]	Msg. Type [4 bits]	Command [1 Byte]	CID	Source Port	Info Length [1 Byte]	Socket Status
1	Unknown	Socket	Socket Status Res	1 Byte	1 Byte	1 Byte	1 Byte

Subscribe To
Service

Layer Flag [1 bit]	Connection Type [2 bits]	Message Type [4 bits]	Command [1 Byte]	Source Port	Destination Port
1	Unknown	Service	Subscription Request	1 Byte	1 Byte

Subscription To
Service Ack

Layer Flag [1 bit]	Connection Type [2 bits]	Msg. Type [4 bits]	Command [1 Byte]	CID	Destination Port	Source Port
1	Unknown	Service	Subscription Ack	1 Byte	1 Byte	1 Byte

Subscription
Reject

FIG. 10D

Layer Flag [1 bit]	Conn. Type [2 bits]	Msg. Type [4 bits]	Command [1 Byte]	Destination Port	Source Port	Reason
1	Unknown	Service	Subscription Reject	1 Byte	1 Byte	1 Byte

Unsubscribe From
Service

Layer Flag [1 bit]	Conn. Type [2 bits]	Msg. Type [4 bits]	Command [1 Byte]	CID	Source Port
1	Unknown	Service	Unsubscribe Request	1 Byte	1 Byte

Unsubscribe From
Service Ack

Layer Flag [1 bit]	Conn. Type [2 bits]	Msg. Type [4 bits]	Command [1 Byte]	CID	Source Port
1	Unknown	Service	Unsubscribe Request Ack	1 Byte	1 Byte

Device Address
Request

Layer Flag [1 bit]	Conn. Type [2 bits]	Msg. Type [4 bits]	Command [1 Byte]	CID	Source Port
1	Unknown	Device Info	Device Address Request	1 Byte	1 Byte

Device Address
Response

Layer Flag [1 bit]	Conn. Type [2 bits]	Msg. Type [4 bits]	Command [1 Byte]	CID	Source Port	Info Length [1 Byte]	Device Address
1	Unknown	Device Info	Device Addr. Resp.	1 Byte	1 Byte	1 Byte	1 Byte


Device Type
Request

Layer Flag [1 bit]	Conn. Type [2 bits]	Msg. Type [4 bits]	Command [1 Byte]	CID	Source Port
1	Unknown	Device Info	Device Type Request	1 Byte	1 Byte

Device Type
Response

Layer Flag [1 bit]	Conn. Type [2 bits]	Msg. Type [4 bits]	Command [1 Byte]	CID	Source Port	Info Length [1 Byte]	Device Name
1	Unknown	Device Info	Device Type Response	1 Byte	1 Byte	1 Byte	1 Byte

FIG. 11A

**Acknowledgement Message**

Layer Flag (1 bit)	Message Type (4 bits)	Msg. Length (3 bits)	Information (6 bits)	Fragment ID (10 bits)
	Message Type 0000 – Ack 0001 – Nak			

Re-transmit

Layer Flag (1 bit)	Message Type (4 bits)	Msg. Length (3 bits)	Information (6 bits)	Fragment ID (10 bits)
	Message Type 0010 – Re TX			

Window Size Request

Layer Flag (1 bit)	Message Type (4 bits)	Msg. Length (3 bits)
	Message Type 0011 – Window Size Request	

FIG. 11B

Window Size Response

Layer Flag (1 bit)	Message Type (4 bits)	Msg. Length (3 bits)	Information (6 bits)	Window Size (10 bits)
-----------------------	--------------------------	-------------------------	-------------------------	--------------------------

Message Type
0100 – Window Size Response

Ping

Layer Flag (1 bit)	Message Type (4 bits)	Msg. Length (3 bits)
-----------------------	--------------------------	-------------------------

Message Type
0101 – Ping

Ping Response

Layer Flag (1 bit)	Message Type (4 bits)	Msg. Length (3 bits)
-----------------------	--------------------------	-------------------------


Message Type
0110 – Ping Response

Intent

Layer Flag (1 bit)	Message Type (4 bits)	Msg. Length (3 bits)
-----------------------	--------------------------	-------------------------

Message Type
0111 – Intent

FIG. 12A



Bus Interface	Device ID	HW Address	Device Type	Device Status	Status Duration	Last Updated
Serial	10	23:ad:33:56	CE	Online	0	112548
CAN	20	44:56:ac:eb	PMC1	Pumping	0	125489
CAN	50	44:56:ef:bd	PMC2	Sleep	100254	095446

Address Request
Message

SOF	Destination Address	Source Address	Message Length	Message Type	Physical Address	CRC
1 Byte	01	00	2	Address Request	1 Byte	2 Bytes

Address Response
Message

SOF	Destination Address	Source Address	Message Length	Message Type	Physical Address	Logical Address	CRC
1 Byte	00	01	3	Address Response	1 Byte	1 Byte	2 Bytes

Disassociation
Message

FIG. 12B

SOF	Destination Address	Source Address	Message Length	Message Type	CRC
1 Byte	01	1 Byte	1	Disconnect Request	2 Bytes

Request Device Type
Message

SOF	Destination Address	Source Address	Message Length	Message Type	CRC
1 Byte	1 Byte	1 Byte	1	Device Type Request	2 Bytes

Device Type Response
Message

SOF	Destination Address	Source Address	Message Length	Message Type	Device Type	CRC
1 Byte	1 Byte	1 Byte	2	Device Type Response	1 Byte	2 Bytes

Device Status Request
Message

SOF	Destination Address	Source Address	Message Length	Message Type	CRC
1 Byte	1 Byte	1 Byte	1	Device Status Req.	2 Bytes

Device Status Response
Message

SOF	Destination Address	Source Address	Message Length	Message Type	Device Status	CRC
1 Byte	1 Byte	1 Byte	2	Device Status Resp.	1 Byte	2 Bytes

Device Status Duration
Message


SOF	Destination Address	Source Address	Message Length	Message Type	Device Status	CRC
1 Byte	1 Byte	1 Byte	2	Status Duration	1 Byte	2 Bytes

Data Re-Transmission Request
Message

SOF	Destination Address	Source Address	Message Length	Message Type	CRC
1 Byte	1 Byte	1 Byte	1	Data ReTransmis.	2 Bytes

FIG. 13A

Network Layering Diagram



1

MEDICAL DEVICE COMMUNICATION METHOD

INCORPORATION BY REFERENCE TO ANY PRIORITY APPLICATIONS

Any and all applications for which a foreign or domestic priority claim is identified in the Application Data Sheet as filed with the present application are hereby incorporated by reference under 37 CFR 1.57.

BACKGROUND OF THE INVENTION

Field of the Invention

One or more embodiments of the invention are related to the field of multiplex communication protocols for medical devices such as, but not limited to, infusion pumps. More particularly, but not by way of limitation, embodiments of the invention enable a medical device communication method for communication between connected peripherals and subsystems that includes connection-oriented, connectionless-oriented, broadcast and multicast data exchange with priority handling of data, fragmentation and reassembly of data, unique static and dynamic address assignment and hot swap capabilities.

Description of the Related Art

Devices that exchange data generally do so using a communication protocol. Communication protocols enable data to be transmitted and received in a controlled manner. Medical devices are example devices that may utilize a communication protocol, for example to exchange data between peripherals or subsystems that generate or utilize data. There are many types of communications protocols that vary in complexity, efficiency and hardware utilization. Current communication protocols utilized within medical devices make use of the operating system and particular bus architecture within the medical device. A problem with this type of architecture is that some implementations may prevent time-multiplexed access of the communication link, thereby starving or otherwise preventing multiple applications from communicating simultaneously. In addition, applications that transfer data using operating system and bus specific software calls must be altered when the operating system or bus architecture changes, specifically to account for differences in operating system calls or with respect to the bus architecture, different data formatting, sequencing and any other protocol specific nuances. In addition, medical devices in general must undergo extensive testing to ensure that they do not fail. Thus, changing bus architectures increases costs associated with applications that make use of the bus architecture, since the application must be retested if the source code for the application is altered.

Known communications protocols are generally targeted at a specific type of communication bus architecture, for example Ethernet, WiFi, Bluetooth, CAN, Serial, I2C, SPI, etc. Known communication protocols in general are not capable of use with more than one type of communication bus since they attempt to provide a solution to a specific communication problem in a coherent manner. Because of the low power requirements, limited processor capabilities and limited memory capacity of medical devices with embedded processors that do specific functions or tasks,

2

such as infusion pumps, existing sophisticated communications protocols are generally not utilized in such medical devices.

In summary, known solutions use communication protocols that are tied to a specific operating system and/or communications bus. Unfortunately, these communication protocols are not agnostic to all communication bus types and do not provide an efficient and lightweight protocol stack for intra-device communication that includes connection-oriented, connectionless-oriented, broadcast and multicast data exchange with priority handling of data, fragmentation, and reassembly of data, unique static and dynamic address assignment for connected subsystems and hot swap capabilities. For at least the limitations described above there is a need for a medical device communication method that provides these features as described and claimed herein.

SUMMARY OF THE INVENTION

Embodiments of the invention enable a medical device communication method for communication between medical peripherals and subsystems that includes connection-oriented, connectionless-oriented, broadcast and multicast data exchange with priority handling of data, fragmentation and reassembly of data, unique static and dynamic address assignment and hot swap capabilities. Example medical devices that may employ an embodiment of the invention include but are not limited to infusion pumps, both present and future. Embodiments of the communication protocol provide an interface that is detached, or otherwise abstracted from the operating system and underlying bus architecture within the medical device, making the behavior and interface of communication protocol consistent across bus architectures and operating systems, which is unknown in the art of infusion pumps for example. Hence, the same application may be utilized on multiple hardware platforms, for example without altering the application itself. Thus, embodiments enable simplified application code, portability thereof and minimize maintenance and testing requirements. Embodiments may utilize any type of physical communication path, for example wireless or hardwired, including but not limited to a data bus. Embodiments for intra-device communications over a data bus generally employ data bus drivers specific to each type of data bus to control reading and writing of data over the bus along with a standard interface to these data bus drivers.

Embodiments may be implemented in separate layers of software configured to execute on one or more computing elements, wherein each layer performs operations to provide data exchange that is generally independent of the other layers. Each layer for example may create, read or update headers associated with data to be exchanged, wherein the headers contain information to support the above-mentioned features. The layers make up what is known as a protocol stack. Embodiments of the protocol stack may include a manager layer, session layer, transport layer, and data link layer or any other architecture as long as the resulting implementation provides the functionality described herein.

Depending on the peripheral or subsystem, data type, priority and desired reliability of data to be exchanged, applications may transmit data using connection-oriented data exchange to provide guaranteed delivery of data or connectionless data exchange for less sensitive data. Embodiments also support one-to-one, as well as one-to-many and many-to-one multicast, and broadcast modes of data exchange between connected peripherals and subsystems. At least one embodiment also supports priority based

data exchange and gives preference to high priority data over low priority data to ensure that high priority messages are delivered first. Additionally, at least one embodiment supports data fragmentation and reassembly data to comply with demands of the particular physical communication technology. Embodiments also provide unique static and dynamic address assignment for connected subsystems and hot swap capabilities, which are unknown for example in current infusion pumps.

Specifically, in the case of connection-oriented communication, at least one embodiment utilizes a Communication ID or "CID", as a token to uniquely identify all active connections within a subsystem and route the data between respective applications. In the case of connectionless communications, at least one embodiment uses port numbers, for example source and destination port numbers, to identify the targeted application. At least one embodiment supports subscription services for recipient applications, which enables multicasting of data to all subscribed applications. Multicasting can be both connection-oriented and connectionless. In connection-oriented communication sessions, at least one embodiment guarantees delivery of data, for example using acknowledgements. Alternatively, connectionless communication sessions do not guarantee delivery of data, but are very efficient. At least one embodiment supports broadcasting of data/messages, wherein the broadcast messages are forwarded to all the subsystems connected to the broadcasting subsystem.

Applications may need to exchange data larger in size than an underlying communication technology or data bus can support. In such cases, at least one embodiment breaks or fragments the data into a smaller size, for example that the data bus can actually transfer. At least one embodiment reassembles data into the original data size at the receiving end. At least one embodiment executes on embedded systems that may have limited resources, including memory, processing power, bus utilization, and power. Hence, embodiments efficiently utilize available resources. Example data exchanges that are large enough to warrant fragmentation of messages include drug library downloads and firmware updates.

With respect to fragmentation, at least one embodiment utilizes window that represents a count of fragments that may be sent before receiving an acknowledgement from receiver. In at least one embodiment, the transmitter requests for window size from the receiver before sending the first fragment. The receiver determines the available memory space to accommodate received packets and responds with the window size, for example as an integral multiple of the maximum frame size that fits into the available memory. The transmitter numbers the fragments in sequence and sends them to receiver. After a window size worth of messages have been sent, the transmitter waits for an acknowledgement of the last fragment. The receiver accumulates all the received fragments and verifies that all the received fragments are in sequence. If there is no missing fragment, the receiver sends the fragment number of last fragment as an acknowledgement, or otherwise sends the fragment numbers of missing fragments as part of negative acknowledgement or NAK.

Since medical devices such as infusion pumps in the future may include hot swappable peripherals or subsystems, at least one embodiment supports unique address assignments to connected devices in order to provide conflict free exchange of data, thus reducing complexity in applications. At least one embodiment supports communication over multiple underlying data transfer technologies

such as serial, CAN, SPI, SDIO, USB, or any other type of physical medium or data bus. At least one embodiment also keeps track of devices connected on each bus and routes data onto the respective bus.

BRIEF DESCRIPTION OF THE DRAWINGS

The above and other aspects, features and advantages of the invention will be more apparent from the following more particular description thereof, presented in conjunction with the following drawings wherein:

FIG. 1 illustrates an architectural view of a system having a user interface controller, and multiple peripherals that communicate with one another using an embodiment of the invention.

FIG. 2 illustrates a hierarchical layered embodiment of the invention implemented as a protocol stack.

FIG. 3 illustrates an embodiment of an address request method implemented within the manager layer.

FIG. 4 illustrates an embodiment of a simple infusion sequence utilizing various messages provided by embodiments of the method.

FIG. 5 illustrates an embodiment of a connection method implemented within the session layer.

FIG. 6 illustrates an embodiment of a data exchange method implemented within the session layer.

FIG. 7 illustrates an embodiment of a disconnection request method implemented within the session layer.

FIG. 8 illustrates a layer flow diagram that shows the flow of data within the various layers implemented in at least one embodiment of the invention.

FIG. 9 illustrates an activity diagram showing routing between various devices.

FIGS. 10A-D illustrate the structure of the messages of the Session Layer.

FIGS. 11A-B illustrate the structure of the messages of the Transport Layer.

FIGS. 12A-B illustrate the structure of the messages of the Data Link/Physical Layer.

FIGS. 13A-B illustrate an exemplary message transfer of a medical function using exemplary values within the messages to demonstrate the system and method according to at least one embodiment of the invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

A medical device communication method will now be described. In the following exemplary description numerous specific details are set forth in order to provide a more thorough understanding of embodiments of the invention. It will be apparent, however, to an artisan of ordinary skill that the present invention may be practiced without incorporating all aspects of the specific details described herein. In other instances, specific features, quantities, or measurements well known to those of ordinary skill in the art have not been described in detail so as not to obscure the invention. Readers should note that although examples of the invention are set forth herein, the claims, and the full scope of any equivalents, are what define the metes and bounds of the invention.

FIG. 1 illustrates an architectural view of a system having user interface controller or "UIC", and multiple peripherals that communicate with one another using an embodiment of the invention. As shown user interface controller UIC communicates with peripherals Pump Motor Control or "PMC", PMC 1 and PMC 2 as well as communication engine or

5

“CE” for various applications including but not limited to drug library, status and diagnostic message handling. For exemplary purposes, UIC has a destination/device ID, e.g., an address of 5 and messages from UIC to the other devices travel over pathways uniquely defined by the tuples defined in the table, for example on a per device and communication ID defined channel. These channels are shown in the table above UIC, namely between UIC and PMC 1, at ports 10 and 20, i.e., the therapeutic and status ports, via Communication ID or “CID” **100** and CID **250** respectively followed by a channel used between UIC and PMC 2 at port 10, the therapeutic port, via Communication ID **100**, along with a channel between UIC and CE at port 40, via Communication ID **175**. The CE, whose address is 7, shows channels in the table above CE to PMC 2 and the UIC, namely devices 2 and 5 via Communication ID’s **250** and **175** respectively. PMC 1 is illustrated as having channels to the UIC, via Communication ID’s **100** and **250**. PMC 2 is illustrated as having channels to the UIC and CE through ports 10 and 20, via Communication ID’s **100** and **250**. PMC 3 and 4 may be hot swapped into the system or otherwise commanded or queried on the fly. Embodiments of the invention are generally configured to utilize minimal memory and processing to enable execution on devices having limited memory and limited processing power, which is generally unknown in the art with respect to sophisticated communications protocols for example. In one or more embodiments, the stack utilizes one kernel thread to execute the Data Link layer and Transport lower layer, whereas remaining layers are part of application process and execute in the context of application. Minimum thread implementation supports blocking access, for example read and write operations block until the operation is completed. Embodiments may also support asynchronous callbacks, and in such cases, the stack may utilize two threads, one for write operations and one for read operation, hence total number of threads utilized is $2*N+1$, where N is the number of applications using the stack.

FIG. 2 illustrates a hierarchical layered embodiment of the invention implemented as a protocol stack. As shown, a data message in the application layer is N bytes long. The application layer may include any functionality independent of the protocol stack that is implemented in the layers beneath the application layer as shown. When the message is transmitted from one application to another, for example to an application executing on a peripheral or subsystem, control information or headers are appended to the message as the message descends layers. The various headers or other appended information are removed as the message rises through the protocol stack to the respective receiving application.

In one or more embodiments, a manager layer may be utilized to implement the first layer in the protocol stack beneath the application. The manager layer may provide standard interfaces to applications across any desired operating system. The layer provides application programmer interfaces or API’s that enables socket-based communications between applications. The manager layer also manages file descriptors and facilitates opening of ports. In at least one embodiment, the manager layer creates and otherwise utilizes a message header having a port number and file descriptor.

A session layer is another layer in the protocol stack and provides or includes API’s to exchange data and control between manager layer and session layer. The session layer may provide guaranteed application-to-application delivery of data and enables connection-oriented and connectionless-oriented modes of communication. This layer also enables

6

one-to-one, one-to-many, many-to-one multicast and broadcasting mode of communication. The layer maintains the translation between CID and an associated socket or virtual port. For connection-oriented communication, the protocol utilizes the CID and otherwise generates and utilizes CID’s. As the connection-oriented data exchange utilizes a handshake between applications for data exchange, the session layer handles the handshake and generates a CID for the communication and informs the other participating session layers of application(s) about the CID. After the handshake, data packets utilize the CID for communication. In case of connectionless communication, no CID is utilized and hence both source and destination port addresses are exchanged in each communication packet or payload. In at least one embodiment, the manager layer creates and otherwise utilizes a message header having control flags and a message type along with a communication identifier. This structure along with an exemplary connection table is shown in FIG. 10A, along with exemplary message types in FIGS. 10B-D. The control flags may be implemented with a layer flag of 1 bit, a connection type of 2 bits and a CID source of 1 bit for example. The session layer utilizes some messages that are associated with the session-session communications and are never passed up the stack to the manager layer in one or more embodiments. These messages are generally used for establishing or closing connections, acknowledgements, etc. If the layer flag is set, for example set to True or 1, the message will be consumed at session layer and will not be forwarded up the stack. The connection type flag indicates the type of connection, for example if connection-oriented, set to 01 or if connectionless, set to 00. An example connectionless protocol is User Datagram Protocol or UDP while an example connection-oriented protocol is Transmission Control Protocol or TCP. The CID source bit is used to identify if the data as being sent from the entity that generated CID for the connection in use or from sub-modules using this CID for communication. The entity that generates CID for communication sets this bit for all the messages generated by it for the respective active connection, while other entities involved in communication reset this flag for messages while using this CID. As the CID is unique within the entity generating CID, there may be duplicate CIDs across other entities. Hence, this layer helps in resolving the source of CID (local or remote) via this flag. The message type field associates messages with categories and lets the session layer know what to expect in the following fields. The message type field is a 4-bit wide field in one or more embodiments. The message type field is used to determine the type of message. Exemplary values include 0000 for data, 0001 for connection, 0010 for CID, 0011 for socket, 0100 for service and 0101 for device information. Any module that provides a service generates a unique CID for communicating with the consumers of the service. Communication ID ‘0’ is reserved for connectionless type of communication in one or more embodiments. Communication ID field is 1 byte wide and is utilized for the data that is passed up the protocol stack. CID can hold any number between 0-255. As state above, CID ‘0’ is for connectionless type communication and is thus not a valid ID for connection-oriented communication. Connection oriented type communications will have a CID in the range of 1-255. Hence, CID ‘0’ is an implicit indication of connectionless communication, any other number between 1-255 suggests connection-oriented. Applications may establish one or more notification filters to select message to receive and process using a desired function. The filtration mechanism may utilize one or more regular expression that specifies the

location, length and content of the matching data in the data portion of the packet. This functionality is implemented in the management layer in one embodiment of the invention. Before the management layer forwards the data to application, it may check if any filters are defined on the data. Depending on the filter, the manager layer filters data and forwards the data to respective callback handlers.

Embodiments of the invention enable a single application to maintain connections with more than one device over one or more physical communication layers or bus implementations. This is accomplished by the use of virtual ports. A single application such as the Therapeutic Manager in the UIC may for example maintain open connections with more than one drug pump PMC or other device as would be asserted during a multi-channel infusion. Similarly, many applications may maintain a connection with one application or device, for example, UIC, CE, and other applications may connect to a particular PMC to gather infusion status information.

The one-to-many and/or many-to-one communication relationship can further be classified into three types, unicast, multicast and broadcast. For example, different applications can gather infusion status from a PMC either by requesting, for example via multicasting, or the PMC can broadcast its status on a known port and interested applications can listen to the port. Listening to a known port can be either anonymous or subscription based. In anonymous mode, broadcasting application continuously transmits on a known port and any application can listen to the port. In subscription based mode, the broadcasting application will not transmit until there is at least one recipient, interested application, which will have to request for service and disconnect when done using the service.

Virtual ports can be implemented by enabling a handshake between participating modules/applications. Applications providing the service generally open a port and connect to the port. For every accepted connection request, CID is generated by the service provider and is passed back to requesting entity in an acknowledgement. Subsequent communication is performed using this CID. In general, the CID is unique to the entity that generated it. A disconnection message is used to stop communication and the CID is then returned to the pool, for example to be reused later. If the service provider runs out of CIDs, it may return a NAK to incoming connection requests with appropriate NAK ID. In case of communication failure, for example module shut down, too much waiting time, too many retries, etc., after waiting for sufficient retries to send a message, one or more embodiments may assume that the communication has stopped and CID is then returned to pool. As the CID are generated by the service provider and are unique within the entity, there can be duplicate CIDs on other sub-entities. To avoid the conflict because of duplicate CIDs, two CID tables may be maintained, one for the CID generated by the system, and the other for the CIDs generated by other systems engaged in communication. The creator of CID sets the "CID Source" flag, hence when other involved applications look at this flag, they perform lookup in appropriate CID table. Each entity may therefor maintain a table shared by the applications running on it. This table is maintained at the session layer and serves as a reference table for routing incoming data packets to respective ports/sockets.

As example scenario is illustrated in the following table, and is also shown in the bottom portion of FIG. 10A for illustration purposes and is not intended to limit the invention as claimed. As shown, the connection type may be set to a value indicative of a connection-oriented type of com-

munication, such as TCP as shown, or a connectionless communication type, such as UDP as shown, or a "Service", for example an application that exists to log data for other applications. The destination address, destination port and communication ID generally uniquely identify a row in above-mentioned table. Destination address is the logical address of a device engaged in a communication. Embodiments may support repeated entries with the same destination address, which indicates multiple active connections with the same destination device. The source port field stores the local port number responsible for handling communication(s) with the CID associated therewith. Depending on CID, received messages are routed to the respective port. Multiple repeated entries in the source port column suggest various applications communicating over same port, which may be indicative of one-to-many communication for example. In one or more embodiments, applications may register or otherwise provide a request to a service provider to receive messages. The destination port is the port number on the destination device engaged in a communication. The communication between a destination port and the local port associated therewith takes place over the respective CID. Hence, CID behaves as a key for this communication. Since the CID is a unique number assigned to distinct communication requests, and which may be implemented with a particular data type of a certain size, there may be an upper limit to the number of active connections that can be handled by the system/application. The upper limit is thus an upper numerical limit of the CID. Once the count of unique CID's exceeds the upper limit, one or more embodiments send a NAK to new incoming connection requests. The File Descriptor (FD) functions similar to file handler or file descriptor in standard operating systems as one skilled in the art will recognize. Communication related operations are performed using this descriptor. Repeating entries of FD suggests multiple connections are being served by one application, many-to-one type of communication. See also FIGS. 10B-D for specific message structures utilized in one or more embodiments of the invention.

Connection Type	Destination Address	Destination Port	Source Port	CID	File Descriptor
Service	8	50	40	100	55
TCP	5	23	60	72	63
Service	15	68	40	110	87
UDP	4	20	55	103	21

The transport layer is another layer in the protocol stack and is responsible for transport layer to transport layer delivery of data. This layer handles flow control, timeouts, acknowledgements and fragmentation and reassembly of data and also resolves the data priority. At least one embodiment of the protocol stack supports two or more priority levels, for example three priority levels, High priority, Medium priority and Low priority and depending on the priority of data, the transport layer puts the data in a respective priority queue. The transport layer may be implemented with two sub-layers namely the transport upper and lower layers. The transport upper layer along with manager and session layers resides in application space, whereas the transport lower layer along with data link layer resides in kernel space. The transport upper layer handles reading and writing to priority queues, fragmentation and reassembly of data and transport-to-transport layer acknowledgements, whereas the transport lower layer may be implemented as a very thin layer and handles reading from priority queues and

communication with one or more other stack layers, for example a lower stack layer. This structure along with an exemplary message types in FIGS. 11A-B.

The transport layer generally ensures that manageable sized datagrams are sent over the underlying bus. Hence, this layer looks at the data coming from upper layers and if the size of data exceeds Maximum Transmission Unit (MTU) size, the layer fragments the incoming data to fit within MTU boundary. Thus, embodiments of the invention may utilize any type of bus of any size, e.g., one bit as per a serial bus, or multiple bits as per a parallel bus of any width. The layer adds appropriate information to the data so that it can be reassembled faithfully at the receiving end. If the incoming data can be sent in three fragments, 'Fragment ID' field is used to number the fragments starting from '1' and the 'Extended flag' bit is not used. All zeros in the 'Fragment ID' field indicates an un-fragmented message and hence is treated as a standalone message. If a message requires more than three fragments to be transmitted, 'Extended Flag' is set, which enables an extra of 8 bits (Extended Fragment ID field is 8 bits) to be used for numbering the fragments. With this flag set, there are total of 10 bits available for numbering which can support 1023 ($2^{10}-1$) fragments. At the receiving end, 'Extended flag' is inspected to determine if 'Extended Fragment ID' is used or not. If the flag is set, the receiver assumes the fragments to arrive in sequence, starting from sequence number 1. But, if the flag is not set, the receiver inspects the 'Fragment ID' field. If the 'Fragment ID' field has zero in it, it indicates an independent message, but if it's a non-zero value, the receiver treats the received message as fragmented data (expects a maximum of three packets). Once all of the fragments are received, the receiver will re-assemble all the fragments into one message. To do this, the receiver aligns all the received messages in ascending order of their fragment ID. Then the receiver verifies that no fragment has been missed in the sequence. If all fragments are received successfully, the receiver removes the 'Transport layer' header information from all the related fragments and concatenates them into one message. If Transport layer has limited memory to re-assemble all the fragments, it forwards the fragments up the stack, as they arrive, which gets reassembled in application buffer.

Congestion control is also provided by the transport layer, which may implement messages dedicated specifically for transport layer to layer communication. These specific messages are consumed at transport layer and not passed up the stack. One such message is the window message, which is exchanged to determine window size for data exchange.

Before sending the first fragment from fragmented data, the transmitter requests a window size from receiver. The receiver looks at the available buffer space in the application buffer and computes the number of fragments it can stage before running out of available memory. It responds to transmitters request with this computed number as window size. Then the transmitter sends window size worth of fragments before expecting an acknowledgement. Once the receiver receives all the messages transmitted in a window, it verifies that all the fragments are in desired sequence and sends acknowledgement for last received fragment in the sequence. If the receiver determines that fragment(s) is missing, it sends a NAK for the missing fragment and the transmitter re-transmits the respective fragment(s). The transmitter may check for window size in middle of communication to keep the data exchange optimized, also, if the

receiver gets low on resources, it can explicitly send a window response and update the transmitter about the window size.

The transport layer is also responsible for the reliable delivery of data. The transport layer has ability to ensure delivery of data to the receiving end. Transport layer has a field for acknowledgement. The receiver may send an acknowledgement for every received data packet with the acknowledgement flag set. In case of fragmented messages, an acknowledgement is sent when the last fragment in a window has been received or last frame in the message has been received or timer expires before all messages have been received.

Embodiments of the transport layer may also implement a "time to live". For example, after transmitting a message, the transmitter initiates a timer and waits for an acknowledgement. If acknowledgement is received, the timer is reset and next packets are transmitted. But if no acknowledgement is received, the transport layer re-transmits the message and again waits for an acknowledgement. The transmitter will retry to send the message certain number of times and if it fails to get an acknowledgement, it will assume that the receiver is not available and will inform upper layers. In case of fragmentation, the transmitter sends window-sized messages and then waits for an acknowledgement on the last fragment sent. If the timer expires, the transmitter will resend the messages again.

The transport layer also may implement fault detection and recovery. For example, the transport layer at the receiver may request the transmitter to re-transmit selected frames through layer-to-layer messages.

The transport layer may also implement priority for messages. For example, the upper layers may pass the message priority down to this layer and this layer adds the priority to the message header. Header has a two bit fields for message priority and hence there are four priority levels possible in one or more embodiments although any number of bits may be used for priority to implement more levels and this applies to all message partitions and bit numbers described herein. Each priority level has its own queue and depending on message priority, transport layer puts them into respective queues to be processed by other layers. As there are four priority levels in a 2-bit embodiment, there may be a maximum of four priority queues and a minimum of one queue, but the number of priority queue depends on the number of priority levels used.

The data link layer is another layer, by way of example and not limitation the bottommost layer, in the communication stack and is responsible for subsystem-to-subsystem delivery of data. This layer completely resides in the kernel space. Data link layer may also be implemented with two sub-layers, for example a Link Layer and Media Access (MAC) layer. The link layer verifies data integrity by calculating/verifying CRC for each outgoing/incoming data frame and also handles any hardware acknowledgements for example. The layer also handles requests for unique logical addresses as well and generates and assigns unique addresses. The MAC layer utilizes driver(s) handling the underlying physical communication channels or bus(es). As the data frames arrive on the buses, the MAC layer copies the received data into a memory pool and passes the pointer to the copied data to Link layer. At least one embodiment supports communication over multiple underlying data transfer technologies or hardware implementations such as serial, CAN, SPI, SDIO, USB, or any other type of communications medium or data bus. This structure along with an exemplary message types in FIGS. 12A-B.

11

In one or more embodiments, the data link layer is responsible for data integrity, for example through the use of CRC checking or any other type data integrity coding or format desired. Embodiments of the data link layer are also responsible for logical address assignment. For example, this layer is responsible for assigning and managing logical addresses of modules in a device. All the modules like Pump Motor Controller, Power Supply Controller, Communication Engine, User Interface Controller, etc., have a unique ID so that they can be uniquely identified in a pump. The protocol stack can support 254 modules as the address field is 1 Byte field and logical addresses 00, 01, and FF are reserved addresses. If modules are identified according to their unique hardware address (MAC addresses), and as the hardware addresses are more than a Byte in size, this would add overhead to the protocol. To avoid this, each module may be assigned a logical address between 1 to 255 and this layer then maintains the assigned addresses. The application layer does not need to know what the hardware address is or what the logical address is in general, which simplifies logical and API calls.

One of the modules is generally assigned with the task of generating unique logical addresses for other modules in the device, no matter if those modules are connected directly to this special module or not. When the device powers on, all the modules power on as programmed. The module responsible for generating address for devices is called the "root" device. The root device is aware of its special role and assigns itself a logical address of 01. As other modules wake up, they assume their logical address as 00. They know that 00 is not a valid address but also know that there exists a module with address 01 who can provide a unique address to them.

Hence, these modules send address requests to a destination with address 01. On receipt of this message, the root module checks its internal table to verify if the requesting hardware already has a logical address assigned. If a logical address is assigned, the root module sends that same logical address in response; else it generates a unique logical address, updates this address in its internal table against the requester's MAC address and sends this address in response. On receipt of an Address Response, the requester module starts communicating with this logical address.

A module in one or more embodiments may not communicate without a valid logical address. If multiple modules try to request for a logical address, there will be collisions. Due to collisions, no requests ever reach the root module, and thus none of the modules receives a logical address. In this scenario, other modules will retry after a random period of time. Depending on the criticality of device, the amount of random time can be varied, i.e. critical devices may wait for lesser period of time before a retry. The amount of wait time may be part of configuration and the devices may wait with reference to their internal clock for example.

If a device does not desire to use the dynamic addressing mechanism, each module may be programmed with a unique address, for example to implement a static versus dynamic address assignment scheme. Embodiments may still utilize a root module that maintains the addresses of the connected modules.

Embodiments of the data link layer may also implement routing. As mentioned, a module may have multiple bus types or topologies and there may be different type of devices connected on various buses. If a Data Link layer receives a packet that is not addressed to it, it first checks if it has multiple bus architectures and if true, it forwards the message to other buses; else it simply discards the packet.

12

This kind of addressing mechanism is well suited for star topology for example. Hence if PMC1 wants to send data to PMC2 but there is no direct data path, then it will re-route it through the root module. In this case, the root module can broadcast the message in the network or perform a lookup in its internal table and just forward the packet on a specific line. Hence, in one or more embodiments that implement routing, each module that supports multiple communication buses may maintain a list of all devices directly connected to the module so that they can efficiently route the packets. As stack supports data routing, it seamlessly bridges multiple heterogeneous data buses, thus making communication, bus topology independent. Few examples of possible bus topologies include Ring, Star, Mesh, and Tree topologies or any other topology that may be utilized to transfer data.

FIG. 3 illustrates an embodiment of an address request method implemented within the manager layer. As shown, when a device is added to the system, for example hot-swapped in, the device boots and requests an address from the root device. The new device waits for a response and if a timeout occurs, requests an address again. Once the root device receives the address request message, it looks up an available device number and generates a logical address for the new device and updates the table. Alternatively, if there are no available numbers left a NAK with appropriate error message may be returned to the new device. The root device returns the new device logical address to the new device in an address response message. Any further requests for the address are handled by lookup via the root device. The new device stores the logical address in a local table for further use. This capability generally does not exist in medical devices or infusion pumps since the configurations are generally assumed to be fixed, using a fixed operating system and fixed bus without regard to potential new devices and new types of devices that may communicate with a root device.

FIG. 4 illustrates an embodiment of a simple infusion sequence utilizing various messages provided by embodiments of the method. Once the address of a new device is obtained, it may communicate with the other components within the system. The figure shows user interface controller UIC having device number 1, initially connecting to a drug infusion pump having device number 3, wherein the logical addresses of the devices, or device numbers are obtained as shown in FIG. 3. The UIC accepts input from a Care Giver that indicates an infusion is to take place. The UIC application calculates the necessary steps to achieve the infusion and sends an infusion header and data message to the drug infusion pump, which acknowledges the message. The UIC then sends an infusion safety data message, which is acknowledged and after the infusion is complete, the UIC sends an infusion stop data message, which is acknowledged. This scenario is a typical scenario that enables any type of drug infusion pump to be added to a system and utilized, for example in a hot swap scenario where an infusion pump may return an error or a different type of drug infusion pump is to be added to the system and utilized for example.

FIG. 5 illustrates an embodiment of a connection method implemented within the session layer. In the scenario shown, the UIC requests a connection in order to communicate with the PMC to command the PMC and/or for example obtain status updates. In this case, PMC acts as a service provider as the PMC is providing status updates on a known port. UIC sends a connection request to PMC on that port, e.g., port 10, shown as a message passing from left to right. After receipt of the connection request, the PMC accepts the request,

generates a unique CID, e.g., 26 for this communication and updates its internal table. The PMC sends the generated CID back to UIC as a part of connection accept message, shown traveling from right to left. On receipt of connection accept message from the PMC, the UIC extracts the CID from the message and updates its internal CID table as shown in the lower left. The UIC then sends an acknowledgement message to the PMC to confirm the successful receipt of CID. If the PMC is not able to process the request from UIC and hence cannot establish communication, the PMC sends a connection reject message to the UIC. On receipt of connection reject message, the UIC may retry to obtain a connection. See also FIGS. 10A-D, 11A-B and 12A-B for an embodiment of the exemplary message structures that may be utilized to form an implementation of various layers, which are described further in detail below.

FIG. 6 illustrates an embodiment of a data exchange method implemented within the session layer. Once the PMC receives acknowledgement from the UIC, the connection process is complete. At this time, both devices may exchange data using the agreed CID. When the session layer of PMC receives any data from the UIC with a valid CID, it performs a lookup in its internal table against the 'Destination ID' and 'CID' to resolve the port number where the packet is to be forwarded.

FIG. 7 illustrates an embodiment of a disconnection request method implemented within the session layer. On completion of data transmission, either of the communicating parties may request for a connection termination. As shown, the UIC initiates the process of connection termination. It sends a disconnect request to PMC with the respective CID. The PMC processes the request and if there is no active communication, the PMC will send an acknowledgement to the UIC and delete the CID entry from its table. On receipt of disconnection acknowledgement from PMC, the UIC also removes the CID entries from its table.

Although the general session layer communication protocol has been described above, a more in-depth description of the Session layer messages follows, according to one or more embodiments of the invention. The message structures utilized in one or more embodiments of the invention as described below are shown in FIGS. 10B-D.

Connection Request Message

For a connection-oriented communication session, when an application opens a socket to communicate over a port on some other device, a handshake is performed before the communication starts. The handshake begins with a connection request type message to the service provider. The "layer flag" is set for this message type. Therefore, the request packet is consumed by the session layer. The connection type may be initially set to "Unknown" suggesting that the data packet is neither connection-oriented nor connection-less. The message type is set to "Connection" as the command is used to establish new connection. The message is a request for establishing new connection; hence "Command" field has "Connection Request" set. The application requesting a connection specifies the destination's port address and also provides its own port address, hence the connection request packet has source and destination port address.

Connect Accept Message

On receipt of a connection request message, if the service provider has enough resource, it responds with a connection accept type of message. The service provider generates a CID for the communication and sends it to the requester as a part of this message. As the connection requesting entity has no information of the generated CID, the service pro-

vider sends source and destination port address as a part of this message to let the other end know about the generated CID.

Connection Acknowledgement Message

On receipt of a connection accept message, the requesting end updates its internal table with the received CID. In response to connection accept message, the requesting end sends an acknowledgement message to indicate the service provider about the receipt of CID and complete the handshake. It is possible that multiple applications on one module request to communicate with one application on another module on the same port number, e.g., many-to-one. To inform the service provider about the particular application that is sending an acknowledgement, "source port" is added to the acknowledgement message.

Connection Disconnect Message

Once the communication is completed, any one of the participating entities may request a connection disconnect for a graceful termination of the connection.

Connection Disconnect Acknowledgement Message

This message is sent as an acknowledgement on receipt of a disconnect message. The message is intended to ensure that a communication is not terminated if an active connection still exists. If a disconnection acknowledgement is not received within a certain time period, a disconnection attempt may be made again.

Connection Reject Message

If the service provider cannot accept any new connections, it sends a connection reject in response to a connection request message. In the connection reject message, it sends the reason for rejecting the request. On receipt of a connection reject message, the requester may retry after some time for example.

CID Info Request Message

Any participant involved in communication can request for status of CID. This message acts as a ping message to verify if the destination port is open and CID is an active CID.

CID Info Response Message

On receipt of a CID Info request, a CID Info Response is transmitted. This message contains the source and destination port addresses involved in communication, window size for transmission, etc., and also indicates if the CID is active or not.

Socket Status Request Message

This message is utilized to request socket related information such as the type of socket, purpose of opening this socket, etc.

Socket Status Response Message

This message is sent in response to Socket Status Request message. The message contains socket related information such as the type of socket, purpose of opening this socket etc.

Subscribe to Service Message

The communication protocol enables applications to provide a service, e.g. a broadcast service. For example, the PMC may have a service running that broadcasts PMC status periodically on a known port. If the UIC requests the PMC status, it may simply subscribe to this service with the PMC and receive the messages. Typically these services are one-way communication.

Subscribe to Service Acknowledgement Message

Once the service provider receives a subscription request, it has to provide a CID to the requester. The CID is delivered through an acknowledgement message.

15

Unsubscribe from Service Message

If a subscribed application no longer desires to be subscribed to a service, it may request to unsubscribe. On receipt of an unsubscribe service message, the service provider removes the entries from its internal CID table and sends an acknowledgement to the requester. If the service provider finds that there is no one subscribed to a service, it may decide to stop the broadcast service until it has at least one subscribed application.

Unsubscribe from Service Acknowledgement Message

On receipt of this message the application requesting to unsubscribe, removes entries of CID from its internal table and releases the involved sockets and ports.

Device Address Request Message

An application may request a logical address for a device using this message.

Device Address Response Message

On receipt of an "Address Request" message, a device sends its address as a part of the response message. Alternatively, a Device Address Response Message may be sent independently at anytime and may not necessarily be tied to a request message.

Device Type Request Message

This message is used to request name of a device. Every connected device has a unique address but may have non-unique names or no names. Device types can be PMC, CE, UIC, etc.

Device Type Response

This message is generally sent in response to "Device Type Request" message and contains the type of the device sending this message. Alternatively, a Device Type Response Message may be sent independently at anytime and may not necessarily be tied to a request message.

Connection-Oriented Data Message

At least one embodiment of the session layer adds just two bytes of header information when sending data between devices. The CID is generated and exchanged during the handshake process prior to data transfer.

Connectionless Data Message

Connectionless data transfer is used when no handshake is required to transfer data. As there is no handshake, there is no CID generated for the communication and hence both source and destination port numbers are utilized to ensure the delivery of data.

FIGS. 11A-B and 12A-B illustrate corresponding message structures for exemplary embodiments of the Transport layer and Data Link layer respectively and are described further below.

FIG. 8 illustrates a layer flow diagram that shows the flow of data within the various layers implemented in at least one embodiment of the invention. Specifically, data flow up the protocol stack for incoming data is shown. The destination application buffer location is not known until the data frame moves up to manager layer. Hence, the fragment is stored in a memory pool until it reaches manager layer and once the target application is resolved, the data is copied from the memory pool into application buffer. In one or more embodiments, memory utilization may be minimized by returning a buffer to memory if the buffer is over a predefined age threshold.

Data Link Layer

Data Link layer controls one or more physical communications links, data buses. The layer filters the messages directed to the specific device and ignores other messages. The layer may compute a CRC on the received packet and verify it with the received CRC. Valid data frames are copied

16

into a memory pool and pointer to these messages are forwarded to the transport layer.

The transport lower layer and data link layer run as an independent service and stores data in the designated priority queue, P1, P2, P3 or P4. The transport upper layer, session and manager layers execute in the application space, and the transport upper layer maintains pointers to the priority queues and Communication ID tables. In one or more embodiments, the memory pool, priority queues and CID tables are in shared memory space.

In one or more embodiments, the data link layer is further divided into two sub-layers, a link layer and a MAC layer. The MAC layer may interface with bus drivers and has a buffer for each underlying bus. As the data arrives on these buses, the data is copied into these buffers and then forwarded to link layer. The buffer may be implemented as a pair of buffers, while one buffer is used for receiving new data, other buffer is used to transfer previously received data.

The link layer copies the data from buffers into the memory pool. The memory pool is a contiguous memory block and each memory block may be implemented as a factor of frame length. As the application consumes data, the data is removed from the memory pool to make room for new data packets. As the application consumes data randomly, there may be memory holes in the memory pool. Hence, the link layer generally maintains a list of available memory locations in the memory pool. When memory is freed from the memory pool, the pointer to available location is added at the end of this list. When a new packet arrives, it is placed at the memory pointed by the first element in this list. If there is no element in the list, memory pool will be considered full and the packets will be dropped. In one or more embodiments of the invention a memory manager may be utilized to control access to memory from the various layers, including concurrent access control of memory from the various layers. Embodiments of the invention may minimize or altogether avoid multiple copying operations by maintaining one copy of data in the memory pool while passing pointers to the memory as the data moves up and down the stack. By controlling access to the memory during access, semaphores may be utilized to ensure data integrity while allowing multiple processes to effectively utilize the data in a concurrent manner. Avoiding multiple copy operations enables minimal memory utilization in embedded environments and minimizes processor utilization as well.

As the transmitter has tendencies to push data on buses, they can soon over-utilize the bus by transmitting too much data. The bus driver at the MAC layer in one or more embodiments may be implemented to handle such scenarios.

Transport Layer

In one or more embodiments, the transport layer may be divided into two sub-layers, a transport upper and a transport lower layer. The transport upper layer resides in application space whereas the transport lower layer resides in kernel space. These two layers together handle transport layer functionalities.

The transport layer is implemented in one or more embodiments to reassemble fragmented data and also to resolve data priority. When a new data packet is received by transport lower layer, a timer may be started for the data. If the data is not consumed before the timer expires, the data may be discarded and the memory freed from the memory pool. This avoids memory starvation if no application exists to consume received data. If the acknowledgement field was set, the transport layer sends a NAK, "timed out in priority queue" error code, for example.

The transport layer header has an acknowledgement flag and if the flag is set, the receiving transport layer will have to send some kind of acknowledgement for the received data fragment. If fragmented data is received, the acknowledgement is sent after receiving window size amount of data or a complete message. This flag is set for a connection-oriented data transfer to ensure delivery of data. This flag may also be set in a connectionless data transfer only if data fragmentation is utilized.

Fragmented Data Packet Handling

In case of fragmented data, before the transmitter starts sending any data fragments, the transport upper layer at the transmitter first requests a window size from the receiver. The window size may be exchanged once during first data transfer or may be obtained before every data transfer. Window size is the number of data fragments that can be sent before an acknowledgement can be expected. When receiver receives a window size request, transport upper layer at receiver's end, computes the amount of free memory in application buffer and sends the response as window size in the 'window size response' message.

In one or more embodiments, the transport upper layer at the transmitter side initializes a data structure for the CID that requested a window size. In this structure, the transport layer stores the CID, last reported window size, last successfully received fragment number and the maximum allowed time period between two fragments, etc. Also, the transport upper layer at the receiver maintains same structure. The transport layer expects that the fragments will be sequentially numbered starting from 1 in one or more embodiments.

As the transmitter receives a window message, it calculates the number of fragments to be transmitted before expecting an acknowledgement. The transmitter starts sending data fragments in sequence starting from fragment number 1 for example.

When the receiver receives first fragment, the transport lower layer starts a timer on the received data frame and places the fragment it into the respective priority queue. The transport upper layer updates the structure and stores the sequence number of the fragment. If the fragment is delivered to the application buffer by upper layers, the upper layers inform the transport upper layer about the success. The transport upper layer updates its structure with the first fragment being delivered. Upper layers do not inform application about the available fragment until all the fragments constituting to a message are received. An application buffer is used for re-assembly of fragments to minimize memory footprint.

If the transport upper layer receives all the fragments for a window successfully, it waits for all the fragments to be delivered to application buffer successfully. Once all the fragments are sent to application buffer, the received fragment number and delivered fragment number match and the transport upper layer sends an acknowledgement for the last fragment in the sequence. The transmitter receives the acknowledgement at the transport upper layer.

Ideally, the transport layer accumulates all fragments, verifies that they are in sequence and merges them into one complete message before sending it up the stack. However, in one or more embodiments, the transport upper layer forwards the frames to the session layer as they are received, but ensures that the fragments are delivered in sequence. This optional implementation may be utilized to lower memory utilization. This is the case since the message does not have to be reconstructed in full within the stack until the full message is received in the application. As the fragment

number in the transport header is 10 bits wide in one or more embodiments, the layer can support a maximum of 1023 fragments (fragment number 0 is reserved and represents a non fragment data frame) before the fragment numbering overflow. As each fragment has a maximum of 248 Bytes payload, hence a total of 253,704 Bytes is required at the receiver end for each active connection to accommodate all the fragments. Any other size of fragment number field may be utilized to increase the overall size as one skilled in the art will recognize.

At the receiver, as the fragments are received, transport upper layer updates the last fragment number in its structure. Before updating, it verifies that the received fragment is in sequence with previously received fragment. If it detects a missing fragment, the layer still forwards the fragments up the stack, but in their respective token puts an offset value. Metadata along with a pointer to the received data fragment is called a token. This offset value is used by manager layer to provide a gap while accommodating other fragments around the missing one, so that the gap can be filled once the missing fragment is received. For example to create an empty space in memory so that when the missing frame is finally received, it will be accommodated in this empty space to complete the final message. Meanwhile, transport upper layer waits for the fragments to arrive and then looks for any missing fragment in the sequence. Once the layer generates a list of all missing fragments, it requests for retransmission of fragments from the transmitter. Once the missing fragments are received, they are forwarded to upper layers so that they can be used for filling the empty spaces in final message.

When retransmission is required, transport upper layer at receiver end, sends retransmission request message with the desired fragment number in it. The receiving end maintains a list of missing fragments and as the missing fragments are received, their entry is removed from this list.

If the transmitter retransmits an already transmitted fragment, the receiver compares the fragment number with last received fragment number and will detect that there has been a retransmission. The layer checks if the retransmission was requested by the receiver explicitly or not. If the retransmission was intentional, the fragment is consumed else the fragment is dropped assuming a false retransmission of data.

Once the transmitter sends one window size worth of fragments, it starts a timer and waits for an acknowledgement on the last fragment in the sequence. The transmitter may send any further fragments only when it receives an acknowledgement. If the acknowledgement is delayed and the timer expires, the transmitter may send a "window size" request message before retransmitting the fragments. A receiver may fail to send an acknowledgement if the receiver is too busy or its buffers are full. Hence, a "window size" message is sent because it serves two purposes, the first being that a response to this message implies that the receiver is ready for accepting messages, and the second being that the new responded window size buffer is available at receiver so that chances of getting an acknowledgement increases.

In case of missing fragments, the receiver sends a retransmission request instead of an acknowledgement. A retransmission request can only be sent if the last fragment in the sequence was either received successfully or was found missing. Hence, the transmitter considers a retransmission request message as an implied acknowledgement and no more waits for an explicit acknowledgement, but may wait on acknowledgement for retransmitted fragment.

Missing fragments can be of three types, the first fragment missing, any fragment(s) missing between first and the last fragment of a complete message, and the last fragment itself missing. If the first fragment is missing and the receiver starts receiving from fragment number 2, it accumulates all the messages till it receives window size messages and explicitly requests for the 1st fragment. The same technique is used for requesting any missing fragment between 1st and last fragment.

Missing the last fragment of a complete message may be a complicated scenario because transmitter never informs the receiver about total number of fragments needed to send a message and hence, there is no way for receiver to know when the message completes. Missing "last" fragments can be of two types, missing the last fragment from a window and missing the last fragment of a message. In the case of missing the last fragment from a window, it is easy to detect. Every time a fragment is received, the receiver starts a timer and waits for next fragment to be received before the timer expires. The transmitter sends the last message for the window and waits for an acknowledgement. If this message is lost, the receiver waits for this last fragment to arrive. The timer at the receiver expires earlier than the timer at the transmitter. As the receiver keeps track of fragment sequences and window size, it realizes that the last fragment was not received on time and hence sends a retransmission request for the last fragment.

A more difficult problem occurs when the last fragment of a message is lost. As the receiver has no idea about how many fragments will constitute a message, it looks for the fragment with 'last fragment' flag set. This fragment indicates the receiver that it was the last fragment from the message. If this fragment is lost, the receiver has no idea when to stop reassembling fragments. To ensure delivery of this last fragment, the transmitter can use following two approaches.

In the first approach, the transmitter knows that the last fragment is approaching. It explicitly reduces the window size to make sure that the last fragment of the message becomes the last fragment of the window as well. As the receiver can detect the last fragment from a window, if the last fragment from a message is lost, the receiver may request retransmission.

In the second approach, the transmitter will send the last fragment with 'last fragment' flag set, followed by few fragments with random payload but with incremental fragment number. If the last fragment of the message is missing, the receiver will detect the missing fragment as there will be gap in sequence numbers and will request for retransmission. When the receiver attempts to arrange the fragments in sequence, it detects the fragment with 'last fragment' flag set and hence discards all fragments following this fragment.

Non-Fragmented Data Packet Handling

For a non-fragmented data frame, it is first received by transport lower layer, which starts a lifetime timer on this frame and puts the frame in appropriate priority queue. The frame is picked from the priority queue by transport upper layer, which forwards it to other layers, for example Session layer.

Session Layer

Session layer major responsibilities are to ensure application-to-application delivery of data and generate unique CID's within a system. The stack works on the principle of service provider and service consumer. The application providing service generates unique CID's for the engaged participants. The CID is unique within the system running the service provider application in one or more embodi-

ments. The CID may be thought of as a key used to hide the information about source and destination ports engaged in communication.

The session layer may be implemented in a lightweight or a very thin layer to a connectionless communication because a connectionless data packet will contain the source and destination port addresses as part of their headers and hence does not utilize a CID.

Packets reaching the session layer may be divided into two categories, namely data and control. Further, the incoming data can be connection-oriented or connectionless and fragmented or non-fragmented.

Connection-Oriented Data Transfer

Connection-oriented data transfer makes use of a connection through a handshake process. After an initial handshake process is complete as is described further below, data exchange occurs. In connection-oriented data transfer, embodiments of the invention utilize a data header with an acknowledgement flag set and connection type set to 01, for example. Data being exchanged may be fragmented or non-fragmented based on the size of the data and the underlying packet size supported by the physical medium.

Fragmented Data

When an application writes to a virtual port, the session layer adds a session layer header to the data and forwards it down the stack. In one or more embodiments, the session layer header is 2 bytes wide. Hence, if fragmentation is needed at the transport layer, the first fragment is set to contain the CID from the session layer while the rest of the fragments may contain only application data. The session layer at the receiving end forwards the first fragment that contains the session layer header, but is unsure as to where to forward other fragments from the sequence as there is no CID information in subsequent headers. Also, if two or more applications on one device want to send data to one device, it is not possible without further information in general at the receiving end to aggregate fragmented data because there is no way to uniquely identify which application is sending what data fragment. To resolve this issue, the transport layer copies session layer header to all the related fragments. As all the fragments will now contain CID, they can be uniquely identified at the receiving end.

The session layer header contains an acknowledgement flag that is utilized in the case of complete messages. As the session layer ensures application-to-application delivery of data, it sets the acknowledgement flag for the receiver to acknowledge successful delivery of data. As the header is copied in each fragment, the session layer will look at the flag and will acknowledge the transmitter every time a fragment is delivered which is not what acknowledgements are generally for, i.e., a complete message acknowledgement.

To avoid this issue, the transport upper layer at the receiver end appends metadata to packets as they are sent up the stack. Metadata along with pointer to received data fragment is called a token and instead of passing data, transport layer passes a token to session layer. In the case of exceptions in behavior of the session layer, metadata provides guidelines for the session layer to follow. For example, the session layer will not send any acknowledgements for data fragments, and when the transport upper layer receives a fragment with a "last fragment" flag set, it updates the metadata so that session layer knows that it needs to send an acknowledgement to the transmitter regarding the receipt of a complete message.

Flow of Control

As the fragments move through the session layer, session layer extracts the CID from the fragments, performs a lookup in the Communication ID table based on CID and the sources logical address obtained from the metadata. The session layer determines the associated file descriptor source and destination ports for the CID. Once the file descriptor is known, it removes all the headers and modifies the metadata to communicate the file descriptor detail to manager layer.

Once the fragment arrives at the manager layer, the manager layer extracts the file descriptor information from metadata and forwards the fragment to respective application. Before the manager layer forwards the message to the application, it determines if the file descriptor is still in use and in the state of accepting data. If conditions are favorable, the message is copied into the application buffer and a "message received" flag in file descriptor is set. If the current operation on the file descriptor is a blocking read, the read function call returns with number of bytes available in application buffer. If the current operation is a non blocking call, the application either checks the flag and if set, reads data from buffer, or the manager layer may make an asynchronous function call on receiving data.

After delivering the data to the application, the manager layer returns the token to session layer. This token contains information about the state of the previously passed message. Depending on the state of token, the session layer performs activities such as sending a session-to-session layer acknowledgement.

If the data is fragmented, session layer further modifies this token and sends it down to transport layer, otherwise the session layer consumes the token. The transport layer determines if the fragments were delivered in sequence they were sent and accordingly controls acknowledgements and window sizes.

Non-Fragmented Data

If a message size is less than the Maximum Transmission Unit (MTU), no fragmentation is required and the complete message is sent in one frame. As the frame moves up the stack, transport upper layer adds very little information to the metadata as complete information for the session layer is already available in the frames header. The session layer reads the header and extracts the data type. If the data type is connection-oriented data, the session layer extracts the CID and performs a lookup in the CID table to determine source and destination ports. The session layer removes all the headers from the datagram, updates the metadata with the destination file descriptor, and forwards it to the manager layer.

Connectionless Data Transfer

As mentioned above, in a connectionless data transfer, the session layer may be implemented in a lightweight or very thin layer. As connectionless data transfer does not utilize a handshake, no CID is generated. Due to the absence of the CID, the protocol header utilizes source and destination port addresses. The session layer reads the destination port address and determines the associated file descriptor and forwards the message to that port. As connectionless data transmission does not guarantee delivery of data, the acknowledgement flag on the frames is set to false.

If a connectionless data frame is larger than the MTU, the transport upper layer fragments the data into manageable sizes without setting the transport layer acknowledgement flag as would be done in connection based communications. During reassembly, if transport layer sees any missing fragments, it discards the complete message. Through a

token, the transport layer informs upper layers to discard previously accumulated fragments in application buffer.

Manager Layer

Manager layer handles file descriptors and forwards packets from lower layers to appropriate file handlers. The manager layer also performs the copying of data from the memory pool into the application buffer. The manager layer knows the size of the application buffer and the application buffer size may be smaller than one frame length.

If the application buffer is large enough, the manager layer copies the complete message into application buffer. If the application buffer is not large enough, the manager layer copies data in a sequential manner. The manager layer fills the application buffer with data and waits for the application to read the data before copying the next portion of data. Once data is successfully delivered to the application, depending on the token, the manager layer informs the session layer regarding success.

Control Flow Up the Stack

The flow of control is now described as data moves up the stack from the lowest layer to the application layer.

Data Link Layer

The data link layer control is described with respect to the two sub-layers that make up the data link layer, namely the link layer and the MAC layer. The MAC layer controls the physical bus drivers.

MAC Layer

As the datagram arrives on the physical bus, the bus driver copies the datagram into a buffer. Once the complete datagram is available in the buffer, the MAC layer calls an API in Link Layer to copy the available data into the memory pool.

The link layer API returns a value to indicate the outcome of the copy operation. The operation may succeed or fail. The returned error code provides the reason for any failure. The MAC layer waits for the API to finish the operation before storing newly available data into the buffer.

Link Layer

As discussed in the sections above, the memory pool may be fragmented due to applications consuming data at random rates, resulting in holes in the memory pool. In one or more embodiments, the link layer maintains a link list, or a doubly link list, or bit map or any other data structure capable of storing available memory locations in the memory pool. When a memory location is made available, a pointer to the memory location is added to the tail of the list. When a new datagram is available, it gets copied at the memory pointed by pointer in the head of the list. Though the received message can be of any size and wherein a maximum size exists, for example 256 bytes, the size of the memory pool is selected to be an integral multiple of the maximum datagram size. This simplifies memory management, as the stack is aware of the size of allocated memory given the pointer to that memory. There may be instances when a datagram is available at the time when memory is made available in the memory pool. In this case, both the copy and the delete processes will try to access the list simultaneously leading to concurrency issues. In one or more embodiments, the memory pool may include non-uniform size buffers for a more flexible buffer implementation at the cost of memory management complexity as one skilled in the art will recognize.

When the MAC layer calls an API to copy the data from hardware buffer to memory pool, the API first checks the list for any available memory location in the pool. If memory is available, the API copies the datagram to the memory location pointed by the head of the list and deletes the

pointer from the list. If no space is available, for example the link list is empty, or error occurs during the copying to memory pool, the API returns respective error code.

After successfully copying the datagram, the API adds the pointer to the datagram in a list with a number of timer ticks remaining before the data should be delivered to application. This API may be reentrant as the MAC layer may be riding over multiple bus architectures and the data may be available in multiple buffers at the same time resulting in calling this API while the layer is still servicing the previous call.

The protocol stack may be implemented with a time limit within which a datagram is to be used by an application, or else the datagram is dropped from the memory pool. To enable this feature, embodiments may implement a global list containing pointers to each datagram with the timer count on each pointer. As the new packets arrive, an API adds the pointer to this packet at the end of this list. The API adds "time to live" value to the current timer count and generates a timer count that represents an expiration time for the packets. When timer count changes, an API looks at the timer count starting from top most element in the list and starts deleting datagram if their timer counts are less than or equal to current timer count.

Once the data is consumed by the application or the data times out, an API is called to remove the datagram from the memory pool and add the pointer to the available memory list. This API may be reentrant as the data may expire at the same time it was consumed by the application. Both processes may attempt to delete the same datagram, therefore semaphores/locks may be utilized to effectively serialize control.

When data gets copied to memory pool, the link layer generates a token for the packet. The token contains the pointer to the datagram and length of the datagram. This token is forwarded to the transport layer through a transport layer API for further processing.

Transport Layer

After the transport lower layer receives a token, the transport lower layer determines if the frame is a transport-layer-to-transport layer message. If the 'layer flag' is set, then these types of messages are layer-to-layer messages and hence are not forwarded to upper layers. If the flag is not set, transport lower layer looks at the priority of the message and places the token into appropriate priority queue.

In one or more embodiments, the transport upper layer receives the token from the priority queue and determines if the 'extended flag' is set or not. If the flag is set, it indicates that a large volume of data is to be expected and informs the API that an extra byte has been used in header for sequencing large number of fragments.

The layer also reads the "Last Fragment" flag. A set 'last fragment' flag indicates to the layer that the current datagram fragment is the last fragment in the sequence of fragments and hence the end of one message. If there is any fragmentation, at least one fragment will have this flag set.

The layer further reads the acknowledgement flag. If the transmitter requests or otherwise is to be sent an acknowledgement for delivery of the datagram to the receiver's transport layer, the layer will set this flag and the receiver will acknowledge the receipt of the packet. If the devices engaged in communication have agreed on a window size for acknowledgements, then the transport layer acknowledges after receiving window size messages else the layer acknowledges each datagram.

The transport upper layer adds more information to the data token and forwards it to session layer. The transport upper layer informs the session layer if the message is a

complete message or not. In case of fragmented message, the transport layer informs the session layer about receiving the last fragment, so that session layer may send an acknowledgement if needed.

Session Layer

From the data pointer in the token, the session layer accesses the frame and extracts session layer header. From the header, session layer first determines if the message is a layer-to-layer message or needs to be forwarded up the stack. If the message is a layer-to-layer type message, then the message is consumed by session layer.

If the layer flag is not set, the frame is forwarded up the stack. The session layer reads the 'Connection Type' field and determines if the message is of unknown connection type or connection-oriented or connectionless. An unknown connection type is generally for the messages exchanged during handshake process, whereas a connectionless message does not need an acknowledgement for delivery, and connection-oriented messages are the ones that use an acknowledgement on successfully delivery.

The session layer further looks into the message type field to determine the type of frame. The frame type is used to determine the purpose of the frame, and only 'Data' type frames are forwarded up the stack and the control type frames are consumed at session layer.

The CID is generated by the application providing a service. Any application that wants to use the service will request a communication ID. CID is unique within one module, for example all of the CID's generated by the UIC are unique within a particular UIC. The CID is generated through a handshake process, where the application using the service sends the details required for uniquely identifying an active connection and receives the CID in response.

The CID specifics and details may be stored in a CID table located in a shared memory region in one or more embodiments, so that the session layers of all the applications may access the CID. In a connectionless data frame, there is no CID information as there is no handshake utilized to establish a connection. Hence connectionless frames contain both source and destination port address in the header.

In a connection-oriented data transfer, there exists a CID in the session layer header. Once the session layer determines the CID from the header, the layer combines the information with the source logical address available in the data token to uniquely identify an entry in CID table. From this table, the session layer determines the source and destination port address and the file descriptors handling the port. The source logical address of the received frame is set by the data link layer along with the file handler information and is forwarded in the data token to the manager layer.

If the received frame is connection-oriented and is a complete message, the session layer maintains a record of the message and forwards the data token to the manager layer. Once the manager layer copies the frame from memory pool into the application buffer, the manager layer notifies the session layer about the successful delivery of data. On receipt of notification, the session layer sends an acknowledgement to the transmitter session layer regarding the successful delivery of data. If the delivery was unsuccessful, as a part of the acknowledgement, the session layer forwards the error message returned from the manager layer to the transmitter.

Manager Layer

The session layer calls an API in manager layer and passes the data token to the manager layer. The manager layer copies the data from memory pool into the application buffer and notifies the session layer regarding the copy. The

manager layer notifies the lower layer about the delivery of message by modifying the data token and sending the data token back to the session layer. Once the data is successfully copied, the manager layer removes the frame pointer from the list of frames monitored by the timer and deletes the frame from the memory pool to make room for new packets.

It may happen that the application buffer is smaller in size than the received data frame, in such cases the manager layer will fill the application buffer with what it can hold and wait for the application to consume it. Once the application consumes the message, the remaining portion of the message is copied and the process is repeated until the complete frame is consumed. Before starting the progress of copying messages in small sizes, the manager layer removes the pointer to the frame from the timer-monitored list because the timer may expire and corrupt the message. Also, the manager layer notifies the lower layer regarding successful delivery of data only when a complete message is sent to the application. At the end of the sequential copy process, the manager layer deletes the frame from the memory pool.

In the case of fragmented data, as the fragments are received by this layer, it copies the fragments into the application buffer and notifies the session layer. The session layer forwards the notification to the transport layer. The transport layer, after receiving notifications for a window size number of messages, sends an acknowledgement to the transmitter about receiving the messages. When the last fragment is successfully delivered to the application, it implies that one complete message was delivered. In such cases, the manager layer notifies the session layer of success, and the session layer sends an acknowledgement message to the transmitter regarding the success, thus providing guaranteed delivery of data.

Data Flow Down the Stack

Assuming that in case of a connection-oriented data transfer, the handshake process has already been done and a valid CID has been already generated, the application copies data into an application buffer and passes a pointer to the API exposed by the manager layer for sending data over virtual ports. The application also specifies the file descriptor that handles the communication and the size of data to be written on the virtual port.

The priority of a message is determined by the priority of the virtual port being used or priority can be set for the message passing through. Hence, through a set of API's, the manager layer informs the session layer about the priority of data, size of data, file descriptor for the communication, pointer to application buffer, and if data is connection-oriented or connectionless. If the data is connectionless, the session layer looks into the file descriptor table and determines the port number associated with the file descriptor. The session layer then adds source and destination port addresses as header to the data. If the transfer is to be connection-oriented, the session layer performs a lookup in the CID table and determines CID associated with the file descriptor and adds this CID as header to the data. The session layer then forwards this pointer to the transport layer and waits for an acknowledgement from the receiver.

The transport upper layer determines the size of the data and determines if fragmentation is required or not. If fragmentation is needed, the transport upper layer breaks the data into manageable sizes and adds information to the header so that the data can be reassembled at the receiver's transport upper layer. If fragmentation is not needed, the transport upper layer still adds some information in one or more embodiments. For example, the transport upper layer copies the data from application buffer into transmitter

memory pool and depending on the priority of data, stores the pointer into appropriate message queues.

The transport lower layer eventually reads the pointer from the priority queue and forwards it to the link layer. The link layer determines the destination logical address and adds it to the data header, computes a CRC on the frame and adds it to the frame before sending it. The MAC layer determines the bus over which the destination is available and sends the data over that bus.

Flow of Data Up the Stack

As the data frame arrives at the underlying bus, the MAC layer determines if the frame is for the subsystem or for some other subsystem. If it is for some other subsystem, the MAC layer drops the data frame. The MAC layer copies valid data frames into a shared memory region and calls an API in the Link layer to inform it about arrival of new data. Throughout the stack, only the pointer to this data is updated to reduce multiple copying of fragments.

The link layer computes the CRC on the received frame and compares the computed CRC with the CRC on the received frame. Frames with invalid CRC's are dropped. Pointers to valid frames are forwarded to the transport lower layer.

The transport lower layer reads the priority of the frame and adds a pointer to the frame to the respective priority queue. The pointer to the frame remains in the queue and waits for appropriate application to consume it. Eventually, the target application's transport upper layer reads the pointer to the frame from the priority queue.

The transport upper layer looks at the headers to determine if the data is fragmented or a complete message. If the data is fragmented, the layer reassembles all the messages from the sequence and then forwards it to the application layer. If the data is not fragmented, it directly forwards the pointer to the frame to the session layer through appropriate API calls.

The session layer looks at the frame headers and determines if the message is of type connectionless or connection-oriented. If the message is connectionless, the session layer looks at the destination port number and determines the file descriptor handling that port. The session layer forwards the pointer to the manager layer with appropriate file descriptor information. If the frame is connection-oriented, the session layer reads the CID and determines the file handler handling that communication. The session layer then forwards the file descriptor information to the manager layer and waits for an acknowledgement from the manager layer. The manager layer sends an acknowledgement indicating whether the data was delivered to the application or not. This information is used by the session layer to acknowledge receipt of data.

The manager layer may be implemented with a lightweight or thin layer and is responsible for copying the data from the memory pool into the application buffer and freeing the memory pool. Once the data gets copied into the application memory, the manager layer informs the application about data being available. The manager layer sends an acknowledgement to the session layer. Thus, to the applications, the manager layer offers synchronous and asynchronous methods for reading and writing to virtual ports.

FIG. 9 illustrates an activity diagram showing routing between various devices. As shown, Device A is connected directly to Device B, which is directly connected to Device C. Device A is not directly connect to Device C. When Device A attempts to send a message to Device C, it sends the message out and Device B reads the message, determines

27

that the message is not for the device and checks to see if there is a path to the device in Device B's destination table. If so, Device B forwards the message to Device C, which processes the data. Hence, embodiments of the invention enable routing and daisy chain or multi-bus configurations that are generally not as flexibly possible in medical devices such as infusion pumps.

An embodiment of the manager layer API is detailed below. The manager layer provides the API to enable socket programming over the protocol stack. The manager layer API calls are utilized by any application that wishes to transfer data using an embodiment of the invention.

pro_socket—creates an unbound socket in a communication domain, and returns a file descriptor that can be used in later function calls that operate on sockets.

int16 **pro_socket** (ConnectionType type, uint8 *pSocket)

Arguments:

type: specifies the type of socket to be created (CONNECTIONTYPE and CONNECTIONLESSTYPE for connection oriented and connection-less data exchange).

pSocket: integer pointer to return newly created socket.

```
typedef enum ConnType
{
    CONNECTIONTYPE=1,
    CONNECTIONLESSTYPE=2,
    RAWTYPE=3
} ConnectionType;
```

On successful completion, the function shall return a SUCCESS; else appropriate error code is returned. The API returns allocated socket in the reference variable pSocket passed as a parameter.

pro_bind—assigns a local address to a socket identified by file descriptor socket.

int16 **pro_bind** (uint8 uint8Socket, const ProSockaddr *pAddress)

```
typedef struct pro_sockaddr
{
    uint8 address;
    uint8 portNo;
    uint8 priority;
    uint8 flags;
    uint32 timeout;
    datafilter *filter;
} ProSockaddr;
```

address: holds logical address of device

portNo: holds port number for connection

priority: holds the priority of the port. All the data passing through this port inherits ports priority

flags: holds configuration flags for changing behavior of socket

TIMEOUT: flag is set, waits for an operation to complete within a given period of time, else returns.

SO_LINGER: set flag indicates that a connection will be terminated only when all the data pending to be sent is sent successfully.

FILTER_DATA: set flag indicates that the data matching supplied filter pattern will only be forwarded to callback function registered to handle it. If flag is reset, data matching the filter will be sent to both, regular socket handler as well as to the registered callback function.

28

timeout: If the TIMEOUT flag is set, timeout value is specified here. A timeout value of 0 returns immediately.

filter: link list of datafilter type structure defining the filter to be applied on received data. More than one element in this link list will have an ORing property. As an example, if an application wants to process data either from PMC, or UIC, or CE or all three, it will create three nodes in this link list one for each PMC, UIC and CE.

Datafilter structure is used to allow applications to select what messages they want to receive, and which function should handle what type of messages. A regular expression pattern is used to create a filter on received data and once a match is found, data is forwarded to registered callback function.

```
typedef struct
{
    char *regEx;
    uint8 index;
    uint8 length;
    void *callback;
    datafilter *filter;
} datafilter;
```

regEx: pointer to regular expression to be used for matching.

index: location to start looking for match in the data section of received message. A '0' in this field indicates that the match will start from the beginning.

length: starting from the provided index, indicates the length of data section to be considered for regular expression matching. If index contains '0' and length contains '0', match will be performed over the entire data section.

callback: function to be called in case of a successful match. If this field is set to null, all the matching data packets will be dropped depending on FILTER_DATA flag.

filter: linklist of any additional filter to be added over existing filter. If this field contains additional filters, on a successful match, callback is made to the function specified in the structure containing this linklist. This link list of filters has anding properties, i.e. a match is successful only if all the regEx specified in all the filters match. As an example, if an application wants to process data containing expressions PMC, UIC and CE, it will instantiate this filter for PMC and have a link list containing filters for UIC and CE respectively.

One or more embodiments support three priority levels for messages namely high, medium and low. The enum defining message priority is as follows.

```
typedef enum ProPriority
{
    HIGHPRIORITYTYPE = 1,
    MEDIUMPRIORITYTYPE = 2,
    LOWPRIORITYTYPE = 3
} MessagePriority;
```

Arguments:

uint8Socket: file descriptor of socket to be bound

pAddress: pointer to ProSockaddr struct containing address to be bound to the socket.

29

Return Value:

Upon successful completion, the function shall return SUCCESS, otherwise appropriate error code.

pro_connect—attempts to connect a socket to the specified address.

int16 pro_connect (uint8 uint8Socket, const ProSockaddr *pAddress)

Arguments:

uint8Socket: socket to be connected to specified address.

pAddress: pointer to structure pro_sockaddr containing peer address.

Return Value:

Upon successful completion, the function shall return SUCCESS; otherwise returns appropriate error code

pro_listen—marks the socket referred to by “socket” as a passive socket, that is, as a socket that will be used to accept incoming connection requests using accept()

int16 pro_listen (uint8 uint8Socket, uint8 uint8Backlog)

Arguments:

uint8Socket: file descriptor of a socket that needs to be put in accepting connections mode.

uint8Backlog: set a limit on number of outstanding connections in the socket’s listen queue. A zero would set the queue length to system defined minimum queue length.

Return Value:

Upon successful completion, the function shall return SUCCESS; otherwise, appropriate error code is returned.

pro_accept—extracts the first connection on the queue of pending connections, creates a new connected socket with same socket type protocol and address family as the specified socket, and returns a new file descriptor for the socket.

int16 pro_accept (uint8 uint8Socket, ProSockaddr *pAddress, uint8 *pClientSocket)

Arguments:

uint8Socket: file descriptor associated with socket.

pAddress: Either a NULL pointer, or a pointer to ProSockaddr struct where the address of connecting socket shall be returned.

pClientSocket: pointer to an unsigned integer for returning file descriptor associated with the newly created socket.

Return Value:

Upon successful completion SUCCESS is returned along with an associated file descriptor for the newly created socket, on failure, returns appropriate error code.

pro_send—initiates transmission of a message from the specified socket to its peer. The pro_send() function sends a message when the socket is connected.

int16 pro_send (uint8 uint8Socket, const void *pBuffer, uint32 intLength, uint32 *pBytesSent)

Arguments:

uint8Socket: socket’s file descriptor

pBuffer: points to buffer containing the message to send.

intLength: length of message in bytes.

pBytesSent: pointer to an integer for returning actual number of bytes sent.

Return Value:

Upon successful completion, the API returns SUCCESS else appropriate error code is returned.

pro_recv—receives a message from a connection-mode or connectionless-mode socket. It is normally used with connected sockets because and does not provide the source address of received data to the application.

30

int16 pro_recv (uint8 uint8Socket, void *pBuffer, uint32 intLength, uint32 *pBytesReceived)

Arguments:

uint8Socket: file descriptor of socket.

pBuffer: pointer to the buffer where message should be stored.

intLength: length in bytes of the message to be received.

pBytesReceived: pointer to an integer for returning number of bytes actually received.

Return Value:

Upon successful completion, SUCCESS is returned along with number of bytes in the reference passed as a parameter, else returns appropriate error code.

pro_close—deallocates the file descriptor and makes the file descriptor available for functions which allocate file descriptors. All outstanding record locks owned by the process on the file associated with the file descriptor are removed. Causes the socket to be destroyed. If the socket is in connection-oriented, and the SO_LINGER option is set for the socket with non-zero linger time, and the socket has un-transmitted data, then pro_close() blocks for up to the current linger interval for all pending data to be transmitted.

int16 pro_close (uint8 uint8Socket)

Arguments:

uint8Socket: file descriptor of socket that needs to be closed.

Return Value:

Upon successful completion, function shall return SUCCESS; otherwise appropriate error code shall be returned.

One skilled in the art will recognize that in addition to the exemplary API illustrated above for the Manager Layer, API’s for the Session, Transport and Data Link Layers may be implemented as desired to communicate the messages shown in FIGS. 10A-D, 11A-B and 12A-B depending on the desired application.

One or more embodiments of the invention may be implemented as a system or method. For example at least one embodiment may include a medical device communication method that includes accepting a request by a programmable device to obtain a device identifier associated with a transmitting device associated with the request, a connection type of connection-oriented or connectionless-oriented, and a receiving device number associated with a receiving device to transmit a message to. The method may also include determining a port number of a port to transmit said message to, for example either via a requesting programmable device or the programmable device that receives the request. Embodiments may also include generating a communication identifier or CID for at least the advantages stated throughout this disclosure. Embodiments may also include accepting a request associated with a medical function, inserting the CID and the medical function into the message, determining if the connection type is connection-oriented or connectionless and transmitting the message to a medical device. This scenario is shown with exemplary values to demonstrate the previous message formatting and transfer in FIGS. 13A and 13B, which are intended to couple with one another on the right side of FIG. 13A and the left side of FIG. 13B.

Embodiments may also include transmitting the message to the receiving device even if the receiving device is not directly connected to the transmitting device. This enables built in routing that allows for devices to pass through messages without requiring a master to control all phases of communication for example.

31

Embodiments may also include accepting a multicast request configured to enable multiple receiving devices to receive the message. Embodiments may further include accepting a priority parameter configured to enable prioritized handling of the message. This enables messages with high priority to be delivered before other lower priority messages and in one or more embodiments may be implemented with a plurality of message data structures such as queues, linked lists or any other data structure or structures. Embodiments may include transmitting messages from a high priority message queue before transmitting data from a low priority message queue. Other embodiments may apply any type of strategy pattern to the delivery process, and may for example change strategies depending on the type of messages that are likely to be received in particular time periods. This enables predictive handling and processing of messages to provide intelligent and robust delivery of medical functions.

Embodiments may also include determining if a size of data to transfer is larger than a predetermined fragmentation value and packing the data in a plurality of messages to facilitate transfer. Embodiments may efficiently utilize memory and for example reduce latency by copying a pointer to the message between a plurality of message layers without copying the message itself. This is the case since the message does not have to be reconstructed in full within the stack until the full message is received in the application. Furthermore, embodiments of the invention may utilize optimized memory management that includes requesting memory from a buffer that includes non-uniform sizes to further increase efficiency of data memory utilization and lower overall required memory. When sending data packets or message that are larger than the maximum size allowed by the underlying hardware, embodiments may include setting a last fragmentation flag in a final message of fragmented message, starting a timer for an acknowledgement and retransmitting the final message if said timer expires. Further increases in efficiency may be achieved by embodiments that include receiving a request to change a window size for receipt of fragmented messages and adjusting memory usage based thereon, for example having lower window sizes for more reliable communication links. Embodiments may also include providing the device identifier to a new medical device that replaces the medical device after hot-swapping the new medical device for the original medical device, i.e., if a failure occurs. This allows embodiments of the invention to provide robust functionality and transparent replacement of hardware without interrupting medical functions or at least minimizing the interruptions. Embodiments may also include providing a pointer to a complete message after receipt of multiple fragmented messages without copying received message data after receipt thereof. This enables incoming data to be inserted into a buffer once and given to the application after the data is received without extraneous copying for example, which reduces memory utilization and programmable device processing required. One or more embodiments of the invention may include accepting an infusion request associated with an infusion related medical function. Any other type of medical function is in keeping with the spirit of the invention.

Embodiments of the system may include a programmable device configured to accept a request to obtain a device identifier associated with a transmitting device associated with the request, a connection type of connection-oriented or connectionless-oriented, a receiving device number associated with a receiving device to transmit a message to.

32

Embodiments of the system may further determine a port number of a port to transmit said message to, generate a communication identifier or CID and accept a request associated with a medical function. The system may also insert the CID and the medical function into the message, determine if the connection type is connection-oriented or connectionless and transmit the message to a medical device. Embodiments of the system may also implement all functionality of the method previously described and may utilize any of the data structures or API's described herein in combination.

While the invention herein disclosed has been described by means of specific embodiments and applications thereof, numerous modifications and variations could be made thereto by those skilled in the art without departing from the scope of the invention set forth in the claims.

What is claimed is:

1. A medical device communication system for connecting a first medical device system with a second medical device system, the medical device communication system comprising a controller configured to:

receive a first message comprising a request for an address from a first medical device system;
determine in a stored table that there is no entry corresponding to the first medical device system;
generate a connection identifier for the first medical device system based on the determination; and
transmit the connection identifier to the first medical device system, wherein the first medical device system is further configured to update its identity with the connection identifier.

2. The communication system of claim 1, wherein the controller is further configured to facilitate transmission of a second message from the first medical device system to an additional hardware, wherein the first medical device system and the additional hardware are not directly connected.

3. The communication system of claim 2, wherein the second message is transferred between a plurality of message layers by copying a pointer and without copying said second message itself.

4. The communication system of claim 2, wherein a session layer communication is made independent of bus topology.

5. The communication system of claim 1, wherein the controller is further configured to transmit the connection identifier to a second medical device system that replaces the first medical device system.

6. The communication system of claim 1, wherein a fragmented message is reassembled into a complete message in an application buffer.

7. The communication system of claim 1, wherein the controller is further configured to:

determine that a size of data to transfer is larger than a predetermined fragmentation value; and
pack said data in a plurality of messages independent of an underlying data bus width.

8. The communication system of claim 1, wherein the controller is further configured to request memory from a buffer comprising non-uniform sizes.

9. The communication system of claim 1, wherein the first medical device system is connected with the controller without altering an application of the first medical device system.

10. The communication system of claim 1, wherein the controller manages connection requests from a plurality of medical device systems.

33

11. A method for connecting hardware components of an medical device system, the method comprising:
 transmitting a first connection identifier to a controller of
 a first medical device system responsive to a first
 message corresponding to a first request for an address 5
 from the first medical device system;
 receiving a second message corresponding to a second
 request for an address from a second medical device
 system;
 determining that the second medical device system has 10
 replaced the first medical device system;
 changing an association of the first connection identifier
 from the first medical device system to the second
 medical device system;
 transmitting the first connection identifier to the second 15
 medical device system, wherein the second medical
 device system is further configured to update its iden-
 tity with the first connection identifier.
 12. The method of claim 11, further comprising facilitat-
 ing transmission of a second message from the first medical

34

device system to an additional hardware, wherein the first
 medical device system and the additional hardware are not
 directly connected.

13. The method of claim 11, further comprising transmit-
 ting messages between hardware components by copying a
 pointer and without copying the messages.

14. The method of claim 11, wherein a session layer
 communication is made independent of bus topology.

15. The method of claim 11, wherein a fragmented
 message is reassembled into a complete message in an
 application buffer.

16. The method of claim 11, further comprising deter-
 mining that a size of data to transfer is larger than a
 predetermined fragmentation value and packing said data in
 a plurality of messages independent of an underlying data
 bus width.

17. The method of claim 11, further comprising request-
 ing memory from a buffer comprising non-uniform sizes.

* * * * *