

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12391277
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Wu; Nan et al.

Autonomous driving system

Abstract

An autonomous driving system includes: at least one sensor (1) configured to collect environment information around a vehicle; a primary decision unit (21) configured to calculate decision information based on the environment information collected by the at least one sensor (1), and transmit the decision information to a controller (3); an alternative decision unit (22) configured to calculate decision information based on the environment information collected by the at least one sensor (1) in response to detecting that the primary decision unit (21) is abnormal, and transmit the decision information to the controller (3); and the controller (3) configured to calculate vehicle control information based on the received decision information, and transmit the vehicle control information to a bottom vehicle controller. In this way, the stability and reliability of the autonomous driving system can be improved and safety of autonomous driving of the vehicle can be guaranteed.

Inventors:	Wu; Nan (Beijing, CN), Zheng; He (Beijing, CN)
Applicant:	BEIJING TUSEN WEILAI TECHNOLOGY CO., LTD (Beijing, CN)
Family ID:	1000008766519
Assignee:	BEIJING TUSEN WEILAI TECHNOLOGY CO., LTD (Beijing, CN)
Appl. No.:	18/316293
Filed:	May 12, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230278583 A1	Sep. 07, 2023

Foreign Application Priority Data

CN	201810015286.9	Jan. 08, 2018
----	----------------	---------------

Related U.S. Application Data

continuation parent-doc US 16923520 20200708 US 11648958 child-doc US 18316293
continuation parent-doc WO PCT/CN2018/105476 20180913 PENDING child-doc US 16923520

Publication Classification

Int. Cl.: **B60W60/00** (20200101); **B60W50/14** (20200101)

U.S. Cl.:

CPC **B60W60/0011** (20200201); **B60W50/14** (20130101); **B60W60/0015** (20200201);
B60W60/0025 (20200201); **B60W60/0053** (20200201); B60W2050/143 (20130101);
B60W2050/146 (20130101); B60W2420/403 (20130101); B60W2420/408 (20240101);
B60W2556/45 (20200201)

Field of Classification Search

CPC: B60W (60/0011); B60W (60/0015); B60W (60/0025); B60W (60/0053); B60W (50/14);
B60W (2556/45); B60W (2420/408); B60W (2050/143); B60W (2050/146); B60W
(2420/403)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2007/0293989	12/2006	Norris	N/A	N/A
2010/0109430	12/2009	DiSaverio et al.	N/A	N/A
2014/0351658	12/2013	D'Ambrosia	N/A	N/A
2015/0012166	12/2014	Hauler et al.	N/A	N/A
2016/0031448	12/2015	Sakai	N/A	N/A
2016/0103450	12/2015	Hogenmueller et al.	N/A	N/A
2017/0277607	12/2016	Samii et al.	N/A	N/A
2018/0283872	12/2017	Robinson	N/A	G01C 21/3833
2020/0331493	12/2019	Wu et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
101549707	12/2008	CN	N/A
103645715	12/2013	CN	N/A
104049530	12/2013	CN	N/A
104267721	12/2014	CN	N/A
104503272	12/2014	CN	N/A
105346483	12/2015	CN	N/A
105785993	12/2015	CN	N/A
106094830	12/2015	CN	N/A

106340197	12/2016	CN	N/A
106354141	12/2016	CN	N/A
106774291	12/2016	CN	N/A
107024927	12/2016	CN	N/A
107161141	12/2016	CN	N/A
107187465	12/2016	CN	N/A
108196547	12/2017	CN	N/A
102014213171	12/2014	DE	N/A
2015203938	12/2014	JP	G05D 1/02

OTHER PUBLICATIONS

European Patent Office, Communication pursuant to Article 94(3) EPC for EP Appl. No. 18898940.4, mailed Aug. 29, 2023, 5 pages. cited by applicant

Nielles, Daniel. European Application No. 18898940, Extended European Search Report Mailed Aug. 23, 2021, pp. 1-9. cited by applicant

No Author Chinese Application 2018100152869 First Office Action Mailed Sep. 17, 2019, pp. 1-16. cited by applicant

No Author Chinese Application 2018100152869 Notice of Grant, Mailed Apr. 17, 2021, pp. 1-4. cited by applicant

Ooka Naoto “Development of automatic driving system on rough road”, Nippondenso Co, Aug. 6, 2002 (Year: 2002). cited by applicant

Lu Jinwen, Driving control system and driving control method, (Jan. 25, 2017), English translation of CN 106354141 A (Year: 2017). cited by applicant

Local Area Network, Jan. 20, 2017, Wikipedia (Year: 2017). cited by applicant

International Search Report and Written Opinion Mailed Nov. 27, 2018 in International Application No. PCT/CN2018/105476. cited by applicant

Primary Examiner: Lang; Michael D

Attorney, Agent or Firm: Perkins Coie LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. patent application Ser. No. 16/923,520, filed on Jul. 8, 2020, which is a continuation of International Patent Application No. PCT/CN2018/105476, filed on Sep. 13, 2018, which claims priority to and the benefit of Chinese Patent Application No. 201810015286.9, filed Jan. 8, 2018. The entire contents of the aforementioned applications are incorporated by reference as part of the disclosure of this application in their entireties.

TECHNICAL FIELD

(1) The present disclosure relates to autonomous driving technology, and more particularly, to an autonomous driving system.

BACKGROUND

(2) Implementation of autonomous driving of a vehicle mainly involves parts such as sensing, decision and control. The sensing part collects environment information around the vehicle using sensors mounted on the vehicle. For example, surrounding obstacles can be sensed using e.g., cameras or laser radars. The decision part is implemented by a decision unit which provides

decision information based on the environment information collected by the cameras. Finally, a controller controls the vehicle to move along a decided path based on the decision information outputted from the decision unit.

(3) However, the current autonomous driving technology is still in an experimental or testing phase, and there are still many technical problems that need to be overcome. For example, vehicles, especially trucks, may cause damages to hardware in the decision unit and the controller in the autonomous driving system due to bumping and shaking while the vehicle is moving, resulting in a problem that the autonomous driving system fails to work. As another example, in order to ensure that the vehicle can move safely, the autonomous driving system needs to have the ability to process a large amount of data quickly and in real time. During the calculation process, the autonomous driving system may crash due to problems such as poor heat dissipation. Therefore, how to ensure the stable and reliable operation of the autonomous driving system has become a technical problem to be solved by those skilled in the art.

SUMMARY

(4) In view of the above problem, the present disclosure provides an autonomous driving system, capable of improving the stability and reliability of the autonomous driving system and guaranteeing safety of autonomous driving of a vehicle.

(5) According to an embodiment of the present disclosure, an autonomous driving system is provided. The autonomous driving system includes at least one sensor, a decision unit and a controller. The decision unit includes a primary decision unit and an alternative decision unit. The at least one sensor is configured to collect environment information around a vehicle. The primary decision unit is configured to calculate decision information based on the environment information collected by the at least one sensor, and transmit the decision information to the controller. The alternative decision unit is configured to calculate decision information based on the environment information collected by the at least one sensor in response to detecting that the primary decision unit is abnormal, and transmit the decision information to the controller. The controller is configured to calculate vehicle control information based on the received decision information, and transmit the vehicle control information to a bottom vehicle controller.

(6) The autonomous driving system according to the embodiment of the present disclosure is provided with two decision units, a primary decision unit and an alternative decision unit. The alternative decision unit monitors the state of the primary decision unit, and upon detecting that the primary decision unit is abnormal, takes over and calculates decision information based on the environment information, so as to guarantee normal operation of the autonomous driving system, such that the entire autonomous driving system will not crash due to failure of the primary decision unit. In this way, the stability and reliability of the autonomous driving system can be improved.

(7) The other features and advantages of the present disclosure will be explained in the following description, and will become apparent partly from the description or be understood by implementing the present disclosure. The objects and other advantages of the present disclosure can be achieved and obtained from the structures specifically illustrated in the written description, claims and figures.

(8) In the following, the solutions according to the present disclosure will be described in detail with reference to the figures and embodiments.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The figures are provided for facilitating further understanding of the present disclosure. The figures constitute a portion of the description and can be used in combination with the embodiments of the present disclosure to interpret, rather than limiting, the present disclosure. It is

apparent to those skilled in the art that the figures described below only illustrate some embodiments of the present disclosure and other figures can be obtained from these figures without applying any inventive skills. In the figures:

- (2) FIG. 1 is a first schematic diagram showing a structure of an autonomous driving system according to an embodiment of the present disclosure;
- (3) FIG. 2 is a second schematic diagram showing a structure of an autonomous driving system according to an embodiment of the present disclosure;
- (4) FIG. 3 is a third schematic diagram showing a structure of an autonomous driving system according to an embodiment of the present disclosure;
- (5) FIG. 4 is a fourth schematic diagram showing a structure of an autonomous driving system according to an embodiment of the present disclosure;
- (6) FIG. 5 is a fifth schematic diagram showing a structure of an autonomous driving system according to an embodiment of the present disclosure;
- (7) FIG. 6 is a sixth schematic diagram showing a structure of an autonomous driving system according to an embodiment of the present disclosure;
- (8) FIG. 7 is a seventh schematic diagram showing a structure of an autonomous driving system according to an embodiment of the present disclosure;
- (9) FIG. 8 is an eighth schematic diagram showing a structure of an autonomous driving system according to an embodiment of the present disclosure;
- (10) FIG. 9 is a ninth schematic diagram showing a structure of an autonomous driving system according to an embodiment of the present disclosure; and
- (11) FIG. 10 is a tenth schematic diagram showing a structure of an autonomous driving system according to an embodiment of the present disclosure.

DETAILED DESCRIPTION OF THE EMBODIMENTS

(12) In the following, the solutions according to the embodiments of the present disclosure will be described clearly and completely with reference to the figures, such that the solutions can be better understood by those skilled in the art. Obviously, the embodiments described below are only some, rather than all, of the embodiments of the present disclosure. All other embodiments that can be obtained by those skilled in the art based on the embodiments described in the present disclosure without any inventive efforts are to be encompassed by the scope of the present disclosure.

(13) The autonomous driving system according to the embodiment of the present disclosure can be applied to autonomous vehicles (such as cars, trucks, public transportation vehicles, buses, sweepers, sprinklers, electric vehicles, etc.), drones, unmanned ships, etc. The present disclosure is not limited to any specific application scenario.

Embodiment 1

(14) FIG. 1 is a schematic diagram of an autonomous driving system according to Embodiment 1 of the present disclosure. Referring to FIG. 1, the autonomous driving system includes at least one sensor 1, a decision unit 2, and a controller 3. The controller 3 is connected to a bottom vehicle controller, which may include a Vehicle Control Unit (VCU), a brake Electronic Control Unit (ECU), a throttle ECU, a steering wheel ECU, etc. The decision unit 2 includes a primary decision unit 21 and an alternative decision unit 22.

(15) The at least one sensor 1 is configured to collect environment information around a vehicle.

(16) In an embodiment of the present disclosure, the at least one sensor 1 may include any one or more types of sensors: a camera, a laser radar, a millimeter wave radar, a positioning sensor, a wind speed sensor, a light sensor, an infrared sensor, etc. Here, the positioning sensor may be a Global Positioning System (GPS), a Global Navigation Satellite System (GNSS) or an Inertial Navigation System (INS). The camera may include a front camera, a side camera, and a rear camera of the vehicle. The environment information collected by the camera may be image data within the field of view of the camera. The environment information collected by the laser radar may be laser point cloud data. The environment information collected by the positioning sensor may be location

information of the vehicle. The environment information collected by the wind speed sensor may be information such as a wind speed and a wind direction. The environment information collected by the light sensor may be light intensity.

(17) The primary decision unit **21** is configured to calculate decision information based on the environment information collected by the at least one sensor, and transmit the decision information to the controller.

(18) In an embodiment of the present disclosure, the primary decision unit **21** determines the perception information (which may include obstacles around the vehicle, distances and directions between the vehicle and the respective obstacles, lane line information, traffic information, etc.) based on the environment information, and then calculate the decision information based on the perception information. Here, the decision information may include a moving path of the vehicle, which includes information on waypoints constituting the path, and each waypoint includes latitude and longitude coordinate information.

(19) The alternative decision unit **22** is configured to calculate decision information based on the environment information collected by the at least one sensor **1** in response to detecting that the primary decision unit **21** is abnormal, and transmit the decision information to the controller **3**.

(20) The controller **3** is configured to calculate vehicle control information based on the received decision information, and transmit the vehicle control information to the bottom vehicle controller.

(21) In an embodiment of the present disclosure, the vehicle control information calculated by the controller **3** may include any one or more of the following parameters: a steering angle of a steering wheel, a torque, throttle information, brake information, lighting control information, horn control information, etc.

(22) In an embodiment of the present disclosure, the decision unit **2**, the controller **3** and the bottom vehicle controller can communicate with each other via a vehicle mounted Controller Area Network (CAN). The decision unit **2**, the controller **3** and the bottom vehicle controller are connected to a CAN bus, and the decision unit **2** and the controller **3** can transmit information via the CAN bus. For example, the decision unit **2** can transmit the decision information onto the CAN bus, and the controller **3** can receive the decision information from the CAN bus. The controller **3** can transmit the vehicle control information onto the CAN bus, and the bottom vehicle controller can receive the vehicle control information from the CAN bus.

(23) The autonomous driving system according to Embodiment 1 of the present disclosure is provided with two decision units, a primary decision unit and an alternative decision unit. The alternative decision unit monitors the state of the primary decision unit, and upon detecting that the primary decision unit is abnormal, takes over and calculates decision information based on the environment information, so as to guarantee normal operation of the autonomous driving system, such that the entire autonomous driving system will not crash due to failure of the primary decision unit. In this way, the stability and reliability of the autonomous driving system can be improved, and safe driving of the vehicle can be guaranteed.

Embodiment 2

(24) FIG. 2 is a schematic diagram of an autonomous driving system according to Embodiment 2 of the present disclosure. Referring to FIG. 2, the autonomous driving system includes at least one sensor **1**, a decision unit **2** and a controller **3**. The decision unit **2** includes a primary decision unit **21** and an alternative decision unit **22**. The controller **3** includes a primary control unit **31**, an alternative control unit **32**, and a verification unit **33**. For details of the at least one sensor **1**, the primary decision unit **21** and the alternative decision unit **22**, reference can be made to Embodiment 1 as described above, and description thereof will be omitted here. The modules included in the controller **3** will be described in detail below.

(25) The primary control unit **31** is configured to calculate first vehicle control information based on the received decision information, and transmit the first vehicle control information to the verification unit **33**.

(26) The alternative control unit **32** is configured to calculate second vehicle control information based on the received decision information, and transmit the second vehicle control information to the verification unit **33**.

(27) The verification unit **33** is configured to select one of the first vehicle control information and the second vehicle control information as the vehicle control information, and transmit the selected vehicle control information to the bottom vehicle controller.

(28) In an embodiment of the present disclosure, each of the primary decision unit **21** and the alternative decision unit **22** transmits its determined decision information onto the CAN bus, and each of the primary control unit **31** and the alternative control unit **32** receives the decision information from the CAN bus.

(29) In an embodiment of the present disclosure, the primary control unit **31** and the alternative control unit **32** may be two hardware devices having the same structures and parameter settings. They calculate the vehicle control information based on the received decision information in the same way. Based on the information on the waypoints in the decision information, the primary control unit **31** and the alternative control unit can determine the vehicle control information for controlling the vehicle to move from a current position to a next waypoint position, including e.g., a steering angle of a steering wheel, a torque, acceleration information, and lighting control information, horn control information, etc.

(30) In an embodiment of the present disclosure, the verification unit **33** selecting one of the first vehicle control information and the second vehicle control information as the vehicle control information may include: determining whether each of the first vehicle control information and the second vehicle control information is abnormal in accordance with a predetermined determination mechanism; when the first vehicle control information and the second vehicle control information are both normal, selecting the first vehicle control information as vehicle control information; when the first vehicle control information and the second vehicle control information are both are abnormal, triggering an alarm; or when one of the first vehicle control information and the second vehicle control information is abnormal, selecting the other as the vehicle control information.

(31) In an embodiment of the present disclosure, the verification unit **33** may be provided in advance with criteria for determining whether various parameters in the vehicle control information are abnormal or not. For example, if a value of the steering angle of the steering wheel is within a predetermined value range, the steering angle parameter is considered to be normal; otherwise it is considered to be abnormal. As another example, if the lighting control information indicates that a left turn signal or a right turn signal is on while the vehicle is in a through lane, it is confirmed that the lighting control information is abnormal. If the lighting control information indicates that a right turn signal is on while the vehicle is in a left turn lane, it is confirmed that the lighting control information is abnormal. If the lighting control information indicates that a left turn signal is on while the vehicle is in a right turn lane, it is confirmed that the lighting control information is abnormal. As yet another example, when the acceleration is greater than 0 while the distance between the vehicle and the vehicle ahead is smaller than or equal to a safe distance, it means that the acceleration information is abnormal. These can be set flexibly by those skilled in the art depending on actual requirements, and the present disclosure is not limited to any of these examples.

(32) The verification unit **33** determining whether each of the first vehicle control information and the second vehicle control information is abnormal in accordance with the predetermined determination mechanism may include: determining whether there is an abnormal parameter in the first vehicle control information (or the second vehicle control information); and if so, determining that the first vehicle control information (or the second vehicle control information) is abnormal, or otherwise determining that the first vehicle control information (or the second vehicle control information) is normal.

(33) In an embodiment of the present disclosure, if the first vehicle control information and the

second vehicle control information are both abnormal, meaning that the primary control unit **31** and the alternative control unit **32** are both abnormal, and it is determined that the autonomous driving system cannot operate normally. Thus, the verification unit **33** can trigger an alarm, including, but not limited to, any one or more of: displaying fault information in a pop-up alarm window on an interactive interface of the autonomous driving system, playing voice alarm information, or transmitting alarm information to a remote server.

(34) With the autonomous driving system according to Embodiment 2 of the present disclosure, on one hand, a redundancy design is provided for the decision unit **2** to improve the stability and reliability of the decision unit **2**; and on the other hand, a redundancy design is provided for the controller **3** to improve the stability and reliability of the controller **3**. Therefore, when compared with Embodiment 1, the stability and reliability of the autonomous driving system can be further improved.

Embodiment 3

(35) FIG. **3** is a schematic diagram of an autonomous driving system according to Embodiment 3 of the present disclosure. Referring to FIG. **3**, the autonomous driving system includes at least one sensor **1**, a decision unit **2**, and a controller **3**. The decision unit **2** includes a primary decision unit **21** and an alternative decision unit **22**. The controller **3** includes a primary control unit **34** and an alternative control unit **35**. For details of the at least one sensor **1**, the primary decision unit **21** and the alternative decision unit **22**, reference can be made to Embodiment 1 as described above, and description thereof will be omitted here. The modules included in the controller **3** will be described in detail below.

(36) The primary control unit **34** is configured to calculate first vehicle control information based on the received decision information, and transmit the first vehicle control information to the bottom vehicle controller.

(37) The alternative control unit **35** is configured to calculate second vehicle control information based on the received decision information in response to detecting that the primary control unit **34** is abnormal, and transmit the second vehicle control information to the bottom vehicle controller.

(38) In an example, the primary control unit **34** can be further configured to: transmit first verification information for verifying whether the primary control unit **34** is abnormal to the alternative control unit **35** periodically. The alternative control unit **35** can be further configured to determine whether the primary control unit **34** is abnormal based on the first verification information.

(39) In another example, the controller can further include a first monitoring unit **36**. As shown in FIG. **4**, the primary control unit **34** can be further configured to transmit first verification information for verifying whether the primary control unit **34** is abnormal to the first monitoring unit **36** periodically. The first monitoring unit **36** can be configured to determine whether the primary control unit **34** is abnormal based on the first verification information, and transmit a determination result to the alternative control unit **35**.

(40) In an example, the first verification information may be a verification code, and a verification mechanism may be set in the primary control unit **34** and the alternative control unit **35** (or the first monitoring unit **36**) in advance. The primary control unit **34** can periodically generate verification codes in accordance with the predetermined verification mechanism, and transmit the verification codes to the alternative control unit **35** (or the first monitoring unit **36**). The alternative control unit **35** (or the first monitoring unit **36**) can verify each received verification code in accordance with the predetermined verification mechanism, and determine that the primary control unit **34** is normal when the verification succeeds, or determine that the primary control unit **34** is abnormal when the verification fails. For example, assuming that the value range of the verification code is 0-255, the primary control unit **34** can determine whether the value of the previous verification code is 255 or not each time before generating the current verification code, and if not, generate the current verification code by incrementing the previous verification code by 1, or otherwise use 0 as the

current verification code (these operations may be performed cyclically). Correspondingly, each time the alternative control unit **35** (or the first monitoring unit **36**) receives the verification code, it can determine whether the previously received verification code is 255 or not. If the previously received verification code is 255, it can then determine whether the currently received verification code is 0 or not, and if so, the verification succeeds, or otherwise the verification fails. If the previously received verification code is not 255, it can then determine whether the currently received verification code is larger than the previous verification code by 1 or not, and if so, the verification succeeds, or otherwise the verification fails.

(41) In another example, the first verification information may alternatively be a heartbeat message. The primary control unit **34** can periodically transmit heartbeat messages to the alternative control unit **35** (or the first monitoring unit **36**). The alternative control unit **35** (or the first monitoring unit **36**) can start a timer each time after receiving a heartbeat message, determine whether the next heartbeat message from the primary control unit **34** is received when the timer reaches a predetermined time length threshold (which is greater than or equal to the time period at which the primary control unit **34** transmits heartbeat messages), and if so, determine that the primary control unit **34** is normal, or otherwise determine that the primary control unit **34** is abnormal.

(42) In some embodiments, in the autonomous driving system described above in connection with FIGS. **1-4**, the primary decision unit **21** may be further configured to transmit second verification information for verifying whether the primary decision unit **21** is normal to the alternative decision unit **22** periodically. The alternative decision unit **22** may be further configured to determine whether the primary decision unit **21** is abnormal based on the second verification information.

(43) In other embodiments, in the autonomous driving system described above in connection with FIGS. **1-4**, the decision unit **2** may further include a second monitoring unit **23**. FIGS. **5-8** show that the decision unit **2** of the autonomous driving system shown in each of FIGS. **1-4** can further include a second monitoring unit **23**, respectively.

(44) The primary decision unit **21** can be further configured to transmit second verification information for verifying whether the primary decision unit **21** is normal to the second monitoring unit **23** periodically. The second monitoring unit **23** can be configured to determine whether the primary decision unit **21** is abnormal based on the second verification information, and transmit a determination result to the alternative decision unit **22**.

(45) In an example, the second verification information may be a verification code, and a verification mechanism may be set in the primary decision unit **21** and the alternative decision unit **22** (or the second monitoring unit **23**) in advance. The primary decision unit **21** can periodically generate verification codes in accordance with the predetermined verification mechanism, and transmit the verification codes to the alternative decision unit **22** (or the second monitoring unit **23**). The alternative decision unit **22** (or the second monitoring unit **23**) can verify each received verification code in accordance with the predetermined verification mechanism, and determine that the primary decision unit **21** is normal when the verification succeeds, or determine that the primary decision unit **21** is abnormal when the verification fails. For example, assuming that the value range of the verification code is 0-255, the primary decision unit **21** can determine whether the value of the previous verification code is 255 or not each time before generating the current verification code, and if not, generate the current verification code by incrementing the previous verification code by 1, or otherwise use 0 as the current verification code (these operations may be performed cyclically). Correspondingly, each time the alternative decision unit **22** (or the second monitoring unit **23**) receives the verification code, it can determine whether the previously received verification code is 255 or not. If the previously received verification code is 255, it can then determine whether the currently received verification code is 0 or not, and if so, the verification succeeds, or otherwise the verification fails. If the previously received verification code is not 255, it can then determine whether the currently received verification code is larger than the previous

verification code by 1 or not, and if so, the verification succeeds, or otherwise the verification fails.

(46) In another example, the second verification information may alternatively be a heartbeat message. The primary decision unit **21** can periodically transmit heartbeat messages to the alternative decision unit **22** (or the second monitoring unit **23**). The alternative decision unit **22** (or the second monitoring unit **23**) can start a timer each time after receiving a heartbeat message, determine whether the next heartbeat message from the primary decision unit **21** is received when the timer reaches a predetermined time length threshold (which is greater than or equal to the time period at which the primary decision unit **21** transmits heartbeat messages), and if so, determine that the primary decision unit **21** is normal, or otherwise determine that the primary decision unit **21** is abnormal.

(47) With the autonomous driving system according to Embodiment 3 of the present disclosure, on one hand, a redundancy design is provided for the decision unit **2** to improve the stability and reliability of the decision unit **2**; and on the other hand, a redundancy design is provided for the controller **3** to improve the stability and reliability of the controller **3**. Therefore, when compared with Embodiment 1, the stability and reliability of the autonomous driving system can be further improved.

(48) In practice, data outputted from each sensor is typically data in one channel. In order to further ensure that each of the primary decision unit **21** and the alternative decision unit **22** can obtain the environment information collected by each sensor timely, thereby facilitating the multiplexing of the sensor data, in an embodiment of the present disclosure, the autonomous driving system shown in FIGS. **1-8** may further include a data exchange controller **4**. FIG. **9** shows that the autonomous driving system shown in FIG. **2** can further include a data exchange controller **4**.

(49) The data exchange controller **4** is configured to receive the environment information collected by the at least one sensor **1** and transmit the environment information to each of the primary decision unit **21** and the alternative decision unit **22**.

(50) In an embodiment of the present disclosure, in order to further improve the data transmission efficiency, a sensor having a large amount of data to transmit, e.g., a camera, a laser radar, etc., can transmit the collected environment information to the data exchange controller **4** via a Local Area Network (LAN). A sensor having a small amount of data to transmit, e.g., a millimeter wave radar, a positioning sensor, etc., can transmit the collected environment information to the alternative decision unit **22** via a vehicle-mounted CAN, and then the alternative decision unit **22** can transmit the environment information to the primary decision unit **21**. For example, the alternative decision unit **22** can transmit the environment information received from the millimeter wave radar and the positioning sensor to a CAN bus, and the primary decision unit **21** can receive the environment information from the CAN bus. As shown in FIG. **10**, a sensor having a large amount of data, e.g., a camera or a laser radar, can communicate the data with the data exchange controller **4** via the LAN, and the data exchange controller **4** can communicate the data with the primary decision unit **21** and the alternative decision unit **22** via the LAN. A sensor having a small amount of data, e.g., a millimeter wave radar or a positioning sensor, can communicate the data via the CAN, and the primary decision unit **21**, the alternative decision unit **22**, the controller **3**, and the bottom vehicle controller can all be connected to the CAN bus.

(51) In an embodiment of the present disclosure, the primary decision unit **21** and the alternative decision unit **22** can be provided as same devices if their costs are not an issue, i.e., the primary decision unit **21** and the alternative decision unit **22** can each have a decision function of Level-4 (L4) autonomous driving.

(52) However, in practice, in order to have the decision function of L4 autonomous driving, a decision unit must have characteristics such as high computing performance, large data throughputs, and complicated calculation logics. The decision unit having such characteristics has a high cost. If both the primary decision unit **21** and the alternative decision unit **22** are configured to have the decision function of L4 autonomous driving, the cost may be too high for

commercialization. Therefore, in an embodiment of the present disclosure, the primary decision unit **21** may be provided as a unit having a decision function of L4 level autonomous driving, and the alternative decision unit **22** may be provided as a unit having a decision function of Level-2 (L2) autonomous driving. For example, the alternative decision unit **22** may have decision capabilities such as lane keeping and following a vehicle ahead, i.e., the alternative decision unit **22** has the capability to guarantee safe driving of the vehicle when the primary decision unit **21** fails. Therefore, in an embodiment of the present disclosure, the alternative decision unit **22** calculating the second decision information based on the environment information collected by the at least one sensor may include: generating decision information for lane keeping based on the environment information; generating decision information for following a vehicle ahead based on the environment information; generating decision information for moving from a current location to an emergency lane and stopping in the emergency lane based on the environment information; or generating decision information for stopping in a current lane based on the environment information.

(53) In the embodiment of the present disclosure, in order to further guarantee the safe driving of the vehicle, the above alternative decision unit **22** may be further configured to: transmit alarm or request for help information to a remote server, to wait for rescue; display warning information indicating a vehicle fault on a display screen on a top or back of the vehicle, to warn other vehicles or pedestrians about the status of the vehicle; and/or generate request information requesting for intervention of a driver, e.g., triggering an audible alarm to warn the driver to switch from an autonomous driving mode to a manual driving mode so as to take over the vehicle.

(54) The basic principles of the present disclosure have been described above with reference to the embodiments. However, it can be appreciated by those skilled in the art that all or any of the steps or components of the method or apparatus according to the present disclosure can be implemented in hardware, firmware, software or any combination thereof in any computing device (including a processor, a storage medium, etc.) or a network of computing devices. This can be achieved by those skilled in the art using their basic programming skills based on the description of the present disclosure.

(55) It can be appreciated by those skilled in the art that all or part of the steps in the method according to the above embodiment can be implemented in hardware following instructions of a program. The program can be stored in a computer readable storage medium. The program, when executed, may include one or any combination of the steps in the method according to the above embodiment.

(56) Further, the functional units in the embodiments of the present disclosure can be integrated into one processing module or can be physically separate, or two or more units can be integrated into one module. Such integrated module can be implemented in hardware or software functional units. When implemented in software functional units and sold or used as a standalone product, the integrated module can be stored in a computer readable storage medium.

(57) It can be appreciated by those skilled in the art that the embodiments of the present disclosure can be implemented as a method, a system or a computer program product. The present disclosure may include pure hardware embodiments, pure software embodiments and any combination thereof. Also, the present disclosure may include a computer program product implemented on one or more computer readable storage mediums (including, but not limited to, magnetic disk storage and optical storage) containing computer readable program codes.

(58) The present disclosure has been described with reference to the flowcharts and/or block diagrams of the method, device (system) and computer program product according to the embodiments of the present disclosure. It can be appreciated that each process and/or block in the flowcharts and/or block diagrams, or any combination thereof, can be implemented by computer program instructions. Such computer program instructions can be provided to a general computer, a dedicated computer, an embedded processor or a processor of any other programmable data

processing device to constitute a machine, such that the instructions executed by a processor of a computer or any other programmable data processing device can constitute means for implementing the functions specified by one or more processes in the flowcharts and/or one or more blocks in the block diagrams.

(59) These computer program instructions can also be stored in a computer readable memory that can direct a computer or any other programmable data processing device to operate in a particular way. Thus, the instructions stored in the computer readable memory constitute a manufacture including instruction means for implementing the functions specified by one or more processes in the flowcharts and/or one or more blocks in the block diagrams.

(60) These computer program instructions can also be loaded onto a computer or any other programmable data processing device, such that the computer or the programmable data processing device can perform a series of operations/steps to achieve a computer-implemented process. In this way, the instructions executed on the computer or the programmable data processing device can provide steps for implementing the functions specified by one or more processes in the flowcharts and/or one or more blocks in the block diagrams.

(61) While the embodiments of the present disclosure have described above, further alternatives and modifications can be made to these embodiments by those skilled in the art in light of the basic inventive concept of the present disclosure. The claims as attached are intended to cover the above embodiments and all these alternatives and modifications that fall within the scope of the present disclosure.

(62) Obviously, various modifications and variants can be made to the present disclosure by those skilled in the art without departing from the spirit and scope of the present disclosure. Therefore, these modifications and variants are to be encompassed by the present disclosure if they fall within the scope of the present disclosure as defined by the claims and their equivalents.

Claims

1. A method of operating a vehicle, comprising: receiving information related to a plurality of waypoints of a path on which the vehicle is to operate; calculating first vehicle control information based on the information related to the plurality of waypoints, wherein the first vehicle control information includes one or more parameters to control a driving operation of the vehicle; calculating second vehicle control information in response to detecting an abnormal condition, wherein the second vehicle control information is calculated based on the plurality of waypoints, and wherein the second vehicle control information includes the one or more parameters to control the driving operation of the vehicle; and transmitting the second vehicle control information to cause the vehicle to perform the driving operation, wherein the one or more parameters includes lighting control information of the vehicle or horn control information of the vehicle.
2. The method of claim 1, wherein the abnormal condition is associated with an entity that calculated the first vehicle control information, and wherein the method further comprises: transmitting a plurality of verification information to verify whether the entity is abnormal, wherein the abnormal condition is detected based on the plurality of verification information.
3. The method of claim 2, wherein the plurality of verification information is transmitted periodically.
4. The method of claim 2, wherein each of the plurality of verification information includes a verification code that is generated in accordance with a predetermined technique, wherein a verification process is performed where each verification code in each verification information is verified in accordance with the predetermined technique.
5. The method of claim 4, wherein the abnormal condition is detected upon determining that the verification process has failed.
6. The method of claim 5, wherein the verification process is determined to fail based on

comparing two consecutive verification codes.

7. The method of claim 4, wherein the abnormal condition is detected upon determining that values of two consecutive verification codes are not expected values.

8. The method of claim 1, wherein the abnormal condition is associated with the one or more parameters, and wherein the abnormal condition is detected in response to determining that a turn signal is on while the vehicle is in a through lane or in response to determining that a turn signal associated with a first direction is on while the vehicle is lane to turn in a second direction opposite to the first direction.

9. The method of claim 1, wherein the abnormal condition is associated with the one or more parameters, and wherein the abnormal condition is detected in response to determining that a value for acceleration is greater than zero when a distance between the vehicle and another vehicle in front of the vehicle is less than a safe distance.

10. A device in a vehicle, comprising: a processor configured to: receive information related to a plurality of waypoints of a path on which the vehicle is to operate; calculate first vehicle control information based on the information related to the plurality of waypoints, wherein the first vehicle control information includes one or more parameters to control a driving operation of the vehicle; calculate second vehicle control information in response to a detection of an abnormal condition, wherein the second vehicle control information is calculated based on the plurality of waypoints, and wherein the second vehicle control information includes the one or more parameters to control the driving operation of the vehicle; and transmit the second vehicle control information to cause the vehicle to perform the driving operation, wherein the one or more parameters includes lighting control information of the vehicle or horn control information of the vehicle.

11. The device of claim 10, wherein each of the plurality of waypoints include latitude coordinate information and longitude coordinate information.

12. The device of claim 10, wherein the one or more parameters further includes a steering angle of a steering wheel of the vehicle, a torque of the vehicle, throttle information for the vehicle, or brake information for the vehicle.

13. The device of claim 10, wherein the first vehicle control information and the second vehicle control information include information that causes the vehicle to move from a current position to a next waypoint position.

14. The device of claim 10, wherein the abnormal condition is associated with the one or more parameters, and wherein the abnormal condition is detected in response to determining that a turn signal is on while the vehicle is in a through lane or in response to determining that a turn signal associated with a first direction is on while the vehicle is lane to turn in a second direction opposite to the first direction.

15. The device of claim 10, wherein the abnormal condition is associated with the one or more parameters, and wherein the abnormal condition is detected in response to determining that a value for acceleration is greater than zero when a distance between the vehicle and another vehicle in front of the vehicle is less than a safe distance.

16. A computer program product comprising a non-transitory computer-readable media that includes code stored thereupon, the code, when executed by a processor, causing the processor to implement a method, comprising: receiving information related to a plurality of waypoints of a path on which a vehicle is to operate; calculating first vehicle control information based on the information related to the plurality of waypoints, wherein the first vehicle control information includes one or more parameters to control a driving operation of the vehicle; calculating second vehicle control information in response to detecting an abnormal condition, wherein the second vehicle control information is calculated based on the plurality of waypoints, and wherein the second vehicle control information includes the one or more parameters to control the driving operation of the vehicle; and transmitting the second vehicle control information to cause the vehicle to perform the driving operation, wherein the abnormal condition is associated with the one

or more parameters, and wherein the abnormal condition is detected in response to determining that a turn signal is on while the vehicle is in a through lane or in response to determining that a turn signal associated with a first direction is on while the vehicle is lane to turn in a second direction opposite to the first direction.

17. The computer program product of claim 16, wherein the method further comprises: displaying a fault information on a display in the vehicle in response to detecting the abnormal condition for both the first vehicle control information and the second vehicle control information.

18. The computer program product of claim 16, wherein the method further comprises: transmitting an alarm information to a remote server in response to detecting the abnormal condition for both the first vehicle control information and the second vehicle control information.

19. The computer program product of claim 16, wherein the one or more parameters includes lighting control information of the vehicle or horn control information of the vehicle.
