

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent Application Publication

20250266108

Kind Code

A1

Publication Date

August 21, 2025

Inventor(s)

Lee; Eric N. et al.

---

### RESUMPTION OF PROGRAM OR ERASE OPERATIONS IN MEMORY

---

#### Abstract

A system includes a memory component and a processing device, operatively coupled with the memory component, to send a read command to the memory component while a program or erase operation being executed by the memory component is suspended. The processing device, operatively coupled with the memory component, can then send an auto resume command to the memory component to automatically resume execution of the program or erase operation after the read command is executed.

---

**Inventors:** Lee; Eric N. (San Jose, CA), Srinivasan; Dheeraj (San Jose, CA)

**Applicant:** Micron Technology, Inc. (Boise, ID)

**Family ID:** 1000008586900

**Appl. No.:** 19/202675

**Filed:** May 08, 2025

#### Related U.S. Application Data

parent US continuation 18369479 20230918 parent-grant-document US 12300332 child US 19202675

parent US continuation 17951754 20220923 parent-grant-document US 11763900 child US 18369479

parent US continuation 17102876 20201124 parent-grant-document US 11456039 child US 17951754

---

#### Publication Classification

**Int. Cl.:** G11C16/34 (20060101); G11C7/10 (20060101); G11C16/10 (20060101); G11C16/26 (20060101)

## U.S. Cl.:

CPC      **G11C16/3436** (20130101); **G11C7/1057** (20130101); **G11C7/1084** (20130101);  
**G11C16/10** (20130101); **G11C16/26** (20130101);

---

## Background/Summary

PRIORITY INFORMATION [0001] This application is a Continuation of U.S. application Ser. No. 18/369,479, filed September 18, 2023, which issues as U.S. Patent No. 12,300,332 on May 13, 2025, which is a Continuation of U.S. application Ser. No. 17/951,754, filed on Sep. 23, 2022, which issued as U.S. Pat. No. 11,763,900 on Sep. 19, 2023, which is a Continuation of U.S. application Ser. No. 17/102,039, filed on Nov. 24, 2020, which issued as U.S. Pat. No. 11,456,039 on Sep. 27, 2022, the contents of which are incorporated herein by reference.

### TECHNICAL FIELD

[0002] Embodiments of the disclosure relate generally to memory sub-systems, and more specifically, relate to resumption of program or erase operations in memory.

### BACKGROUND

[0003] A memory sub-system can include one or more memory devices that store data. The memory devices can be, for example, non-volatile memory devices and volatile memory devices. In general, a host system can utilize a memory sub-system to store data at the memory devices and to retrieve data from the memory devices.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

[0004] The present disclosure will be understood more fully from the detailed description given below and from the accompanying drawings of various embodiments of the disclosure.

[0005] FIG. 1 illustrates an example computing system that includes a memory sub-system in accordance with some embodiments of the present disclosure.

[0006] FIG. 2 is a flow diagram of a process to resume program or erase operations in memory in accordance with some embodiments of the present disclosure.

[0007] FIG. 3 is a flow diagram of a process to resume program or erase operations in memory in accordance with some embodiments of the present disclosure.

[0008] FIG. 4 is a flow diagram of a process to resume program or erase operations in memory in accordance with some embodiments of the present disclosure.

[0009] FIG. 5 is a flow diagram of a process to resume program or erase operations in memory in accordance with some embodiments of the present disclosure.

[0010] FIG. 6 is a flow diagram of an example method to resume program or erase operations in memory in accordance with some embodiments of the present disclosure.

[0011] FIG. 7 is a block diagram of an example computer system in which embodiments of the present disclosure can operate.

### DETAILED DESCRIPTION

[0012] Aspects of the present disclosure are directed to resumption of program or erase operations in memory. A memory sub-system can be a storage system, storage device, a memory module, or a combination of such. An example of a memory sub-system is a storage system such as a solid-state drive (SSD). Examples of storage devices and memory modules are described below in conjunction with FIG. 1. In general, a host system can utilize a memory sub-system that includes one or more components, such as memory devices that store data. The host system can provide data to be stored

at the memory sub-system and can request data to be retrieved from the memory sub-system.

[0013] A read command can be sent to, and executed by, a storage device of a memory sub-system while another memory operation (e.g., a program, erase, or other memory operation) being performed by the memory device is suspended. In a conventional memory sub-system, the read command can automatically trigger a resumption of the other operation, causing a drain of page buffer resources in the memory sub-system. For example, the same page buffer resources used to resume the other memory operation can also be used to execute the read command (e.g., to transfer the read data), creating a conflict between executing the read command and executing the other memory operation. A memory sub-system traditionally may not have the resources to support the resumption of the other memory operation concurrently with the read data transfer.

[0014] Aspects of the present disclosure address the above and other deficiencies by sending an auto resume command to the memory component (e.g., storage device) such that the other memory operation does not resume until an auto resume command is received and the read command is executed. A resume continuation command can also be sent after the read command has been executed, when page buffer resources are to be used. The resume continuation can resume the memory operation responsive to whether a checkpoint for resuming the memory operation has been met.

[0015] The auto resume command allows for the execution of read commands while the other memory operation is suspended and there are not enough page buffer resources to execute both the read command and the other memory operation. As such, issuing a read command will not automatically trigger a resumption of memory operations and as such, page buffer resources can be used more efficiently. The resume continuation command also allows for more effective use of page buffer resources because the page buffer resources are not activated until used. In some embodiments, after the read command has been executed, the resume continuation command can pause the memory operation until a checkpoint is reached. A checkpoint is triggered responsive to a request for page buffer resources. Therefore, page buffer resources are not used until requested.

[0016] FIG. 1 illustrates an example computing system **100** that includes a memory sub-system **110** in accordance with some embodiments of the present disclosure. The memory sub-system **110** can include media, such as one or more volatile memory devices (e.g., memory device **140**), one or more non-volatile memory devices (e.g., memory device **130**), or a combination of such.

[0017] A memory sub-system **110** can be a storage device, a memory module, or a hybrid of a storage device and memory module. Examples of a storage device include a solid-state drive (SSD), a flash drive, a universal serial bus (USB) flash drive, an embedded Multi-Media Controller (eMMC) drive, a Universal Flash Storage (UFS) drive, a secure digital (SD) card, and a hard disk drive (HDD). Examples of memory modules include a dual in-line memory module (DIMM), a small outline DIMM (SO-DIMM), and various types of non-volatile dual in-line memory modules (NVDIMMs). The memory sub-system **110** can include one or more memory components that store data. The memory components can be, for example, non-volatile memory components and volatile memory components. In general, a host system can utilize a memory sub-system **110** to store data at the memory components and to retrieve data from the memory components.

[0018] The computing system **100** can be a computing device such as a desktop computer, laptop computer, server, network server, mobile device, a vehicle (e.g., airplane, drone, train, automobile, or other conveyance), Internet of Things (IoT) enabled device, embedded computer (e.g., one included in a vehicle, industrial equipment, or a networked commercial device), or such computing device that includes memory and a processing device.

[0019] The computing system **100** can include a host system **120** that is coupled to one or more memory sub-systems **110**. In some embodiments, the host system **120** is coupled to different types of memory sub-system **110**. FIG. 1 illustrates one example of a host system **120** coupled to one memory sub-system **110**. As used herein, “coupled to” or “coupled with” generally refers to a connection between components, which can be an indirect communicative connection or direct

communicative connection (e.g., without intervening components), whether wired or wireless, including connections such as electrical, optical, magnetic, and the like.

[0020] The host system **120** can include a processor chipset and a software stack executed by the processor chipset. The processor chipset can include one or more cores, one or more caches, a memory controller (e.g., an SSD controller), and a storage protocol controller (e.g., PCIe controller, SATA controller). The host system **120** uses the memory sub-system **110**, for example, to write data to the memory sub-system **110** and read data from the memory sub-system **110**.

[0021] The host system **120** can be coupled to the memory sub-system **110** via a physical host interface. Examples of a physical host interface include, but are not limited to, a serial advanced technology attachment (SATA) interface, a peripheral component interconnect express (PCIe) interface, universal serial bus (USB) interface, Fibre Channel, Serial Attached SCSI (SAS), Small Computer System Interface (SCSI), a double data rate (DDR) memory bus, a dual in-line memory module (DIMM) interface (e.g., DIMM socket interface that supports Double Data Rate (DDR), Open NAND Flash Interface (ONFI), Double Data Rate (DDR), Low Power Double Data Rate (LPDDR), or any other interface. The physical host interface can be used to transmit data between the host system **120** and the memory sub-system **110**. The host system **120** can further utilize an NVM Express (NVMe) interface to access components (e.g., memory devices **130**) when the memory sub-system **110** is coupled with the host system **120** by the PCIe interface. The physical host interface can provide an interface for passing control, address, data, and other signals between the memory sub-system **110** and the host system **120**. FIG. 1 illustrates a memory sub-system **110** as an example. In general, the host system **120** can access multiple memory sub-systems via a same communication connection, multiple separate communication connections, and/or a combination of communication connections.

[0022] The memory devices **130**, **140** can include any combination of the different types of non-volatile memory devices and/or volatile memory devices. The volatile memory devices (e.g., memory device **140**) can be, but are not limited to, random access memory (RAM), such as dynamic random-access memory (DRAM) and synchronous dynamic random access memory (SDRAM).

[0023] An example of non-volatile memory devices (e.g., memory device **130**) includes a negative-and (NAND) type flash memory. Each of the memory devices **130** can include one or more arrays of memory cells. The memory cells can include single level cells (SLCs) that can store one bit per cell, multi-level cells (MLCs) that can store two bits per cell, (e.g., triple level cells (TLCs) that can store three bits per cell, quad-level cells (QLCs) that can store four bits per cell, and/or penta-level cells (PLCs) that can store five bits per cell, among others. As used herein, the term multiple level cells is used to refer to cells configured to store more than one bit per cell (e.g., MLC, TLC, QLC, PLC, etc.). In some embodiments, a particular memory component can include an SLC portion, and an MLC portion, a TLC portion, a QLC portion, and/or a PLC portion of memory cells. Each of the memory cells can store one or more bits of data used by the host system **120**. Furthermore, the memory cells of the memory devices **130** can be grouped as memory pages or memory blocks that can refer to a unit of the memory component used to store data.

[0024] Although non-volatile memory components such as NAND type memory (e.g., 2D NAND, 3D NAND) are described, the memory device **130** can be based on any other type of non-volatile memory or storage device, such as, read-only memory (ROM), phase change memory (PCM), self-selecting memory, other chalcogenide based memories, ferroelectric transistor random-access memory (FeTRAM), ferroelectric random access memory (FeRAM), magneto random access memory (MRAM), Spin Transfer Torque (STT)-MRAM, conductive bridging RAM (CBRAM), resistive random access memory (RRAM), oxide based RRAM (OxRAM), negative-or (NOR) flash memory, electrically erasable programmable read-only memory (EEPROM), and a cross-point array of non-volatile memory cells. A cross-point array of non-volatile memory can perform bit storage based on a change of bulk resistance, in conjunction with a stackable cross-gridded data

access array. Additionally, in contrast to many flash-based memories, cross-point non-volatile memory can perform a write in-place operation, where a non-volatile memory cell can be programmed without the non-volatile memory cell being previously erased.

[0025] The memory sub-system controller **115** (or controller **115** for simplicity) can communicate with the memory devices **130** to perform operations such as reading data, writing data, or erasing data at the memory devices **130** and other such operations. The memory sub-system controller **115** can include hardware such as one or more integrated circuits and/or discrete components, a buffer memory, or a combination thereof. The hardware can include digital circuitry with dedicated (i.e., hard-coded) logic to perform the operations described herein. The memory sub-system controller **115** can be a microcontroller, special purpose logic circuitry (e.g., a field programmable gate array (FPGA), an application specific integrated circuit (ASIC), etc.), or other suitable processor.

[0026] The memory sub-system controller **115** can include a processing device, which includes one or more processors (e.g., processor **117**) configured to execute instructions stored in a local memory **119**. In the illustrated example, the local memory **119** of the memory sub-system controller **115** includes an embedded memory configured to store instructions for performing various processes, operations, logic flows, and routines that control operation of the memory sub-system **110**, including handling communications between the memory sub-system **110** and the host system **120**.

[0027] In some embodiments, the local memory **119** can include memory registers storing memory pointers, fetched data, etc. The local memory **119** can also include read-only memory (ROM) for storing micro-code. While the example memory sub-system **110** in FIG. **1** has been illustrated as including the memory sub-system controller **115**, in another embodiment of the present disclosure, a memory sub-system **110** does not include a memory sub-system controller **115**, and can instead rely upon external control (e.g., provided by an external host, or by a processor or controller separate from the memory sub-system).

[0028] In general, the memory sub-system controller **115** can receive commands or operations from the host system **120** and can convert the commands or operations into instructions or appropriate commands to achieve the desired access to the memory device **130** and/or the memory device **140**. The memory sub-system controller **115** can be responsible for other operations such as wear leveling operations, garbage collection operations, error detection and error-correcting code (ECC) operations, encryption operations, caching operations, and address translations between a logical address (e.g., logical block address (LBA), namespace) and a physical address (e.g., physical block address, physical media locations, etc.) that are associated with the memory devices **130**. The memory sub-system controller **115** can further include host interface circuitry to communicate with the host system **120** via the physical host interface. The host interface circuitry can convert the commands received from the host system into command instructions to access the memory device **130** and/or the memory device **140** as well as convert responses associated with the memory device **130** and/or the memory device **140** into information for the host system **120**.

[0029] The memory sub-system **110** can also include additional circuitry or components that are not illustrated. In some embodiments, the memory sub-system **110** can include a cache or buffer (e.g., DRAM) and address circuitry (e.g., a row decoder and a column decoder) that can receive an address from the memory sub-system controller **115** and decode the address to access the memory device **130** and/or the memory device **140**.

[0030] In some embodiments, the memory device **130** includes local media controllers **135** that operate in conjunction with memory sub-system controller **115** to execute operations on one or more memory cells of the memory devices **130**. An external controller (e.g., memory sub-system controller **115**) can externally manage the memory device **130** (e.g., perform media management operations on the memory device **130**). In some embodiments, a memory device **130** is a managed memory device, which is a raw memory device combined with a local controller (e.g., local controller **135**) for media management within the same memory device package. An example of a

managed memory device is a managed NAND (MNAND) device.

[0031] The memory sub-system **110** can include an auto resume component **113**. Although not shown in FIG. **1** so as to not obfuscate the drawings, the auto resume component **113** can include various circuitry to facilitate continuing the suspension of memory operations (e.g., program or erase operations) unless an auto resume command is received by memory device **130**. For example, the execution of a read command sent to the memory device will not trigger a resumption of a suspended program or erase operation by memory device **130** unless an auto resume command has been received by the memory device, as will be further described herein. The auto resume component **113** can include a special purpose circuitry in the form of an ASIC, FPGA, state machine, and/or other logic circuitry that can allow the auto resume component **113** to orchestrate and/or perform the operations described herein.

[0032] The memory sub-system **110** can also include a resume continuation component **116**. Although not shown in FIG. **1** so as to not obfuscate the drawings, the resume continuation component **116** can include various circuitry to facilitate confirming a resume continuation command has been received by memory device **130**. For example, the memory device **130** can resume execution of a memory operation (e.g. a program or erase operation) responsive to receiving the resume continuation command prior to, or subsequent to, a checkpoint for resuming the operation being met, as will be further described herein. The checkpoint can correspond to page buffer resources being sought for execution of a memory operation. The resume continuation component **116** can include a special purpose circuitry in the form of an ASIC, FPGA, state machine, and/or other logic circuitry that can allow the resume continuation component **116** to orchestrate and/or perform the operations described herein.

[0033] In some embodiments, the memory sub-system controller **115** includes at least a portion of the auto resume component **113** and the resume continuation component **116**. For example, the memory sub-system controller **115** can include a processor **117** (processing device) configured to execute instructions stored in local memory **119** for performing the operations described herein. In some embodiments, the auto resume component **113** and the resume continuation component **116** are part of the host system **110**, an application, or an operating system

[0034] As an example, controller **115** can send a read command to memory device **130** while a program or erase operation being executed by memory device **130** is suspended, and auto resume component **113** can send an auto resume command to memory device **130** to automatically resume execution of the program or erase operation after the read command is executed. The auto resume command can be sent by auto resume component **113** before or after the read command is sent to memory device **130**. For instance, the auto resume command can be sent any time during the execution of the read command. In one example where the auto resume command is sent to memory device **130** after the read command is sent to the memory device **130**, the memory device **130** is given a longer period to execute the read command than an example where the auto resume command is sent to the memory device **130** before the read command. Execution of the suspended program or erase operation may only resume after execution of the read command, and the data read during execution of the read command can be transferred to controller **115** while the execution of the suspended program or erase operation has resumed (e.g., concurrently with the execution of the program or erase operation).

[0035] The resumption of the program or erase operation execution can be temporary. For example, the memory device **130** can confirm if a resume continuation command has been received from the resume continuation component **116**. The memory device **130** can resume (e.g., continue resumption of) execution of the program or erase operation responsive to confirming that the resume continuation has been received and that a checkpoint for resuming the operation has been met. The checkpoint for resuming the operation can correspond to, for instance, an amount of page buffer resources being used by the memory device **130**. The resume continuation command can be sent before or after the memory device **130** has confirmed whether it has received the resume

continuation command. For instance, the confirmation of the resume continuation command can be responsive to page buffer resources being used by the memory device **130**. In an example where the resume continuation command is sent after memory device **130** has confirmed the resume continuation command has been received and the checkpoint for resuming the operation has not been met, the memory device **130** can pause execution of the program or erase operation. The paused program or erase operation can be resumed responsive to receiving the resume continuation command.

[0036] During suspension of a program or erase operation, the memory device **130** can ensure received read commands do not trigger a complete resumption of the program or erase operation before confirming if a resume continuation command has been received. For example, memory device **130** can temporarily resume execution of the program or erase operation after the auto resume command has been sent, while the data during execution of the read command is being transferred and prior to the resume continuation component **116** sending the resume continuation command. The execution of the read command and the execution of the program or erase operation can occur consecutively to increase bandwidth efficiency of the memory component and will not occur in parallel until the auto resume command has been received by the memory device **130**. The program or erase operation may not resume without the auto resume command being sent by the auto resume component **113**.

[0037] FIG. **2** is a flow diagram of a process **202** to resume program or erase operations in memory in accordance with some embodiments of the present disclosure. The process **202** can be performed by processing logic that can include hardware (e.g., processing device, circuitry, dedicated logic, programmable logic, microcode, hardware of a device, integrated circuit, etc.), software (e.g., instructions run or executed on a processing device), or a combination thereof. In some embodiments, the process **202** is performed by and/or utilizing the auto resume component **113** of FIG. **1**. Although shown in a particular sequence or order, unless otherwise specified, the order of the processes can be modified. Thus, the illustrated embodiments should be understood only as examples, and the illustrated processes can be performed in a different order, and some processes can be performed in parallel. Additionally, one or more processes can be omitted in various embodiments. Thus, not all processes are required in every embodiment. Other process flows are possible.

[0038] A computing system can include a memory component (e.g. memory device **130** of FIG. **1**) and a processing device (e.g., controller **115** of FIG. **1**), among other components. The memory component can include a read buffer, a write buffer, a memory array **222**, and/or an input/output (I/O) device **221**.

[0039] In process **202**, a program or erase operation can be suspended while a read command **223** is sent from the processing device to array **222** via the I/O device **221**. The read command can be received by the memory array **222** and executed **224**. For example, data **225** can be read from array **222** and sent to the processing device via the I/O device **221**. However, the suspended program or erase operation does not automatically resume after execution **224** of the read command. Further, although not shown in FIG. **2**, multiple read commands can be sent from the processing device to the memory array **222** for execution in a similar manner.

[0040] To restore the program or erase operation from its suspended state, an auto resume command **226** can be sent to memory array **222** from the processing device via I/O device **221** prior to sending the last read command **227**. The auto resume command **226** can signal the array **222** such that the array can automatically resume execution of the suspended program or erase operation after the last read command has been executed **228**. The memory array **222** can execute **228** the last read command and send the read data **237** back to the processing device via I/O device **221**. Execution of the suspended program or erase operation can then be resumed **229** by the memory array **222** after executing the last read command. For instance, the execution of the suspended program or erase operation may only be resumed after executing **228** the last read

command **227** that was sent after sending the auto resume command **226**. Further, the execution of the suspended program or erase operation can be resumed **229** while the read data **237** is being sent to the processing device via I/O device **221**.

[0041] FIG. **3** is a flow diagram of a process **333** to resume program or erase operations in memory in accordance with some embodiments of the present disclosure. The process **333** can be performed by processing logic that can include hardware (e.g., processing device, circuitry, dedicated logic, programmable logic, microcode, hardware of a device, integrated circuit, etc.), software (e.g., instructions run or executed on a processing device), or a combination thereof. In some embodiments, the process **333** is performed by and/or utilizing the auto resume component **113** of FIG. **1**. Although shown in a particular sequence or order, unless otherwise specified, the order of the processes can be modified. Thus, the illustrated embodiments should be understood only as examples, and the illustrated processes can be performed in a different order, and some processes can be performed in parallel. Additionally, one or more processes can be omitted in various embodiments. Thus, not all processes are required in every embodiment. Other process flows are possible.

[0042] As shown in FIG. **3**, the process **333** can involve an input/output (I/O) device **341** which can be analogous to input/output (I/O) device **221** illustrated in FIG. **2**. The process **333** can also involve a memory array **342**, which can be analogous to memory array **222** of FIG. **2**.

[0043] In process **341**, a program or erase operation can be suspended while a read command **343** is sent from the processing device to memory array **342** via the I/O device **341**. The read command can be received by the memory array **342** and executed **344**. For example, data **345** can be read from array **342** and sent to the processing device via the I/O device **341**. However, the suspended program or erase operation does not automatically resume after execution **344** of the read command. Further, although not shown in FIG. **2**, multiple read commands can be sent via the I/O device **341** to the memory array **342** for execution in a similar manner.

[0044] To restore the program or erase operation from its suspended state, an auto resume command **347** can be sent to memory array **342** via I/O device **341** after the last read command **346** has been sent to the memory array **342**. The auto resume command **347** can signal the array **342** to automatically resume execution of the suspended program or erase operation after the last read command has been executed **348**. The memory array **342** can execute **348** the last read command and send the read data **334** back to the processing device via I/O device **341**. The last read command **346** can be executed **348** for a longer time by the memory array **342** than if the auto resume command were sent prior to the last read command (e.g., as illustrated in FIG. **2**) because the last read command **346** can begin to be executed immediately after being sent. Further, the auto resume command **347** can be sent to array **342** at any point during the execution **348** of the last read command. Execution of the suspended program or erase operation can then be resumed **349** by the memory array **342** after executing the last read command **346**. For instance, the execution of the suspended program or erase operation may only be resumed after executing **348** the last read command **346** that was sent prior to sending the auto resume command **347**. Further, the execution of the suspended program or erase operation can be resumed **349** while the read data **334** is being sent to the processing device via I/O device **341**.

[0045] FIG. **4** is a flow diagram of a process **450** to resume program or erase operations in memory in accordance with some embodiments of the present disclosure. The process **450** can be performed by processing logic that can include hardware (e.g., processing device, circuitry, dedicated logic, programmable logic, microcode, hardware of a device, integrated circuit, etc.), software (e.g., instructions run or executed on a processing device), or a combination thereof. In some embodiments, the process **450** is performed by and/or utilizing the resume continuation component **116** of FIG. **1**. Although shown in a particular sequence or order, unless otherwise specified, the order of the processes can be modified. Thus, the illustrated embodiments should be understood only as examples, and the illustrated processes can be performed in a different order, and some



processes can be performed in parallel. Additionally, one or more processes can be omitted in various embodiments. Thus, not all processes are required in every embodiment. Other process flows are possible.

[0046] As shown in FIG. 4, the process 450 can involve an input/output (I/O) device 451 which can be analogous to I/O device 221 and I/O device 341 illustrated in FIG. 2 and FIG. 3 respectively. The process 450 can also involve memory array 452, which can be analogous to memory array 222 and memory array 342 of FIG. 2 and FIG. 3 respectively.

[0047] A computing system can include a memory component (e.g., memory device 130 of FIG. 1) and a processing device (e.g., controller 115 of FIG. 1), among other components. The memory component can, can include a read buffer, a write buffer, a memory array 452, and/or an input/output (I/O) device 451.

[0048] In process 450, a program or erase operation can be suspended while a read command 454 is sent from the processing device to memory array 452 via the I/O device 451. An auto resume command 453 can accompany the last read command 454 to the memory array 452. The auto resume command 453 can be sent with (e.g., accompany) the read command 454 sent to the memory array 452. The auto resume command 453 can signal the memory array 452 to automatically resume execution of the suspended program or erase operation after read command 454 has been executed 455. The read command 454 can be sent by the I/O device 451 to be executed. The memory array 452 can execute 455 the read command 454 and send the read data 456 back to the processing device via I/O device 451. As illustrated in FIG. 4, the auto resume command 453 is sent prior to read command 454. However, embodiments are not so limited and, in another embodiment, the auto resume command 453 can be sent after the read command 454.

[0049] Execution of the suspended program or erase operation 457-1 can be temporarily resumed by the memory array 452 after the read command 454 has been executed 455 and while the read data 456 is being sent to the processing device via I/O device 451. A resume continuation command 458 can be sent from the processing device to memory array 452 via I/O device 451 after the read data 456 has been sent to the processing device. As such, the execution 455 of the read command 454 and the execution of the program or erase operation 457-1 occur consecutively, such that both do not occur at the same time.

[0050] In process 451, resume continuation command 458 is sent prior to a checkpoint being met. Upon confirming the checkpoint has been met, memory array 452 can continue to execute the program or erase operation 457-2. The checkpoint can correspond to a request for page buffer resources by the memory array 452. For instance, the checkpoint can correspond to an amount of page buffer resources being used, requested, or to be used. The execution 455 of the read command 454 and the execution of the program or erase operation 457 occurring consecutively can increase efficiency in management of page buffer resources and bandwidth efficiency. For instance, page buffer resources may not be activated until the checkpoint has been met.

[0051] FIG. 5 is a flow diagram of a process 570 to resume program or erase operations in memory in accordance with some embodiments of the present disclosure. The process 570 can be performed by processing logic that can include hardware (e.g., processing device, circuitry, dedicated logic, programmable logic, microcode, hardware of a device, integrated circuit, etc.), software (e.g., instructions run or executed on a processing device), or a combination thereof. In some embodiments, the process 570 is performed by and/or utilizing the resume continuation component 116 of FIG. 1. Although shown in a particular sequence or order, unless otherwise specified, the order of the processes can be modified. Thus, the illustrated embodiments should be understood only as examples, and the illustrated processes can be performed in a different order, and some processes can be performed in parallel. Additionally, one or more processes can be omitted in various embodiments. Thus, not all processes are required in every embodiment. Other process flows are possible.

[0052] As shown in FIG. 5, the process 570 can involve an input/output (I/O) 571 which can be

analogous to I/O device **221**, I/O device **341**, and I/O device **451** illustrated in FIG. 2, FIG. 3, and FIG. 4 respectively. The process **570** can also involve memory array **572**, which can also be analogous to memory array **222**, memory array **342**, and memory array **452** of FIG. 2, FIG. 3, and FIG. 4 respectively.

[0053] In process **570**, a program or erase operation can be suspended while a read command **574** is sent from the processing device to memory array **572** via the I/O device **571**. The processing device can send an auto resume command **573** along with read command **574** to the memory array **572**. The auto resume command **573** can signal the memory array **572** to automatically resume execution of the suspended program or erase operation after read command **574** has been executed **575**. The read command **574** can be sent by the I/O device **571** to be executed. The memory array **572** can execute **575** the read command **574** and send the read data **576** to the processing device via I/O device **571**. As illustrated in FIG. 5, the auto resume command **573** is sent prior to read command **574**. However, embodiments are not so limited and, in another embodiment, the auto resume command **573** can be sent after the read command **574**.

[0054] Execution of the suspended program or erase operation **577-1** can be temporarily resumed by the memory array **572** after the read command **574** has been executed **575** and while the read data **576** is being sent to the processing device via I/O device **571**. A resume continuation command **578** can be sent from the processing device to memory array **572** via I/O device **571** after the read data **576** has been sent to the processing device. For instance, the read data **576** can continue to be sent to the processing device until a resume continuation command **578** is received.

[0055] In process **570**, the resume continuation command **578** is sent after a checkpoint is met. Upon confirming the checkpoint has been met, but before receiving the resume continuation command **578**, memory array **572** can temporarily pause **579** the program or erase operation. The checkpoint can correspond to a request for page buffer resources by the memory array **572**. For instance, the checkpoint can correspond to an amount of page buffer resources being used, requested, or to be used. Once the checkpoint is met, and the resume continuation command **578** is received, memory array **572** can continue **577-2** the program or erase operation. That is, the program or erase operation is only continued **577-2** responsive to meeting the checkpoint and receiving the resume continuation command **578**.

[0056] FIG. 6 is a flow diagram of an example method **660** to resume program or erase operations in memory in accordance with some embodiments of the present disclosure. The method **660** can be performed by processing logic that can include hardware (e.g., processing device, circuitry, dedicated logic, programmable logic, microcode, hardware of a device, integrated circuit, etc.), software (e.g., instructions run or executed on a processing device), or a combination thereof. In some embodiments, the method **660** is performed by and/or utilizing the resume continuation component **116** of FIG. 1 and/or the resume continuation component **716** of FIG. 7. Although shown in a particular sequence or order, unless otherwise specified, the order of the processes can be modified. Thus, the illustrated embodiments should be understood only as examples, and the illustrated processes can be performed in a different order, and some processes can be performed in parallel. Additionally, one or more processes can be omitted in various embodiments. Thus, not all processes are required in every embodiment. Other process flows are possible.

[0057] At operation **662**, a memory component receives a read command while a program or erase operation being executed by the memory component is suspended. For instance, a processing device (e.g., the processor **117** illustrated in FIG. 1, herein) can send the read command to the memory component. The memory component can receive the read command while a program or erase operation is suspended. The received read command does not automatically resume the suspended program or erase operation.

[0058] At operation **664**, the memory component confirms a resume continuation command has been received. In one embodiment, the resume continuation command can be confirmed after receiving the resume continuation command. In another embodiment, the memory component can

seek to confirm if the resume continuation command has been received prior to receiving the resume continuation command. The resume continuation command can be sent to the memory component after the execution of a last read command.

[0059] At operation **667**, the memory component resumes execution of the program or erase operation responsive to confirming the resume continuation command has been received and a checkpoint for resuming the program or erase operation has been met. The suspended program or erase operation can be temporarily resumed by the memory component after the execution of a last read command. A resume continuation command can be received by the memory component after the execution of the last read command. If a resume continuation command is sent prior to the checkpoint being met, the resumption of the program or erase operation can be continued. If the resume continuation command is sent after the checkpoint is met, the resumption of the program or erase operation would have been temporarily paused once the checkpoint was met, but can then be continued once the resume continuation command is sent. The checkpoint can correspond to a request for page buffer resources by the memory array. For instance, the checkpoint can correspond to an amount of page buffer resources being used, requested, or to be used. Once the checkpoint is met, and the resume continuation command is confirmed to have been previously received, the program or erase operation can be resumed. For instance, the program or erase operation may only be resumed responsive to meeting the checkpoint and receiving the resume continuation command.

[0060] FIG. 7 is a block diagram of an example computer system **701** in which embodiments of the present disclosure can operate. For example, FIG. 7 illustrates an example machine of a computer system **701** within which a set of instructions, for causing the machine to perform any one or more of the methodologies discussed herein, can be executed. In some embodiments, the computer system **701** can correspond to a host system (e.g., the host system **120** of FIG. 1) that includes, is coupled to, or utilizes a memory sub-system (e.g., the memory sub-system **110** of FIG. 1) or can be used to perform the operations of a controller (e.g., to execute an operating system to perform operations corresponding to the auto resume component **113** and the resume continuation component **116** of FIG. 1). In alternative embodiments, the machine can be connected (e.g., networked) to other machines in a LAN, an intranet, an extranet, and/or the Internet. The machine can operate in the capacity of a server or a client machine in client-server network environment, as a peer machine in a peer-to-peer (or distributed) network environment, or as a server or a client machine in a cloud computing infrastructure or environment.

[0061] The machine can be a personal computer (PC), a tablet PC, a set-top box (STB), a Personal Digital Assistant (PDA), a cellular telephone, a web appliance, a server, a network router, a switch or bridge, or any machine capable of executing a set of instructions (sequential or otherwise) that specify actions to be taken by that machine. Further, while a single machine is illustrated, the term “machine” shall also be taken to include any collection of machines that individually or jointly execute a set (or multiple sets) of instructions to perform any one or more of the methodologies discussed herein.

[0062] The example computer system **701** includes a processing device **702**, a main memory **704** (e.g., read-only memory (ROM), flash memory, dynamic random access memory (DRAM) such as synchronous DRAM (SDRAM) or Rambus DRAM (RDRAM), etc.), a static memory **706** (e.g., flash memory, static random access memory (SRAM), etc.), and a data storage system **718**, which communicate with each other via a bus **730**.

[0063] The processing device **702** represents one or more general-purpose processing devices such as a microprocessor, a central processing unit, or the like. More particularly, the processing device can be a complex instruction set computing (CISC) microprocessor, reduced instruction set computing (RISC) microprocessor, very long instruction word (VLIW) microprocessor, or a processor implementing other instruction sets, or processors implementing a combination of instruction sets. The processing device **702** can also be one or more special-purpose processing devices such as an application specific integrated circuit (ASIC), a field programmable gate array

(FPGA), a digital signal processor (DSP), network processor, or the like. The processing device **702** can execute instructions **726** for performing the operations and steps discussed herein. The computer system **701** can further include a network interface device **708** to communicate over the network **720**.

[0064] The data storage system **718** can include a machine-readable storage medium **724** (also known as a computer-readable medium) on which is stored one or more sets of instructions **726** or software embodying any one or more of the methodologies or functions described herein. The instructions **726** can also reside, completely or at least partially, within the main memory **704** and/or within the processing device **702** during execution thereof by the computer system **701**, the main memory **704** and the processing device **702** also constituting machine-readable storage media. The machine-readable storage medium **724**, data storage system **718**, and/or main memory **704** can correspond to the memory sub-system **110** of FIG. **1**.

[0065] In one embodiment, the instructions **726** include instructions to implement functionality corresponding to auto resume component **713** and the resume continuation component **716**. While the machine-readable storage medium **724** is shown in an example embodiment to be a single medium, the term “machine-readable storage medium” should be taken to include a single medium or multiple media that store the one or more sets of instructions. The term “machine-readable storage medium” shall also be taken to include any medium that is capable of storing or encoding a set of instructions for execution by the machine and that cause the machine to perform any one or more of the methodologies of the present disclosure. The term “machine-readable storage medium” shall accordingly be taken to include, but not be limited to, solid-state memories, optical media, and magnetic media.

[0066] Some portions of the preceding detailed descriptions have been presented in terms of algorithms and symbolic representations of operations on data bits within a computer memory. These algorithmic descriptions and representations are the ways used by those skilled in the data processing arts to most effectively convey the substance of their work to others skilled in the art. An algorithm is here, and generally, conceived to be a self-consistent sequence of operations leading to a desired result. The operations are those requiring physical manipulations of physical quantities. Usually, though not necessarily, these quantities take the form of electrical or magnetic signals capable of being stored, combined, compared, and otherwise manipulated. It has proven convenient at times, principally for reasons of common usage, to refer to these signals as bits, values, elements, symbols, characters, terms, numbers, or the like.

[0067] It should be borne in mind, however, that all of these and similar terms are to be associated with the appropriate physical quantities and are merely convenient labels applied to these quantities. The present disclosure can refer to the action and processes of a computer system, or similar electronic computing device, that manipulates and transforms data represented as physical (electronic) quantities within the computer system's registers and memories into other data similarly represented as physical quantities within the computer system memories or registers or other such information storage systems.

[0068] The present disclosure also relates to an apparatus for performing the operations herein. This apparatus can be specially constructed for the intended purposes, or it can include a general purpose computer selectively activated or reconfigured by a computer program stored in the computer. Such a computer program can be stored in a computer readable storage medium, such as, but not limited to, any type of disk including floppy disks, optical disks, CD-ROMs, and magnetic-optical disks, read-only memories (ROMs), random access memories (RAMs), EPROMs, EEPROMs, magnetic or optical cards, or any type of media suitable for storing electronic instructions, each coupled to a computer system bus.

[0069] The algorithms and displays presented herein are not inherently related to any particular computer or other apparatus. Various general purpose systems can be used with programs in accordance with the teachings herein, or it can prove convenient to construct a more specialized

apparatus to perform the method. The structure for a variety of these systems will appear as set forth in the description below. In addition, the present disclosure is not described with reference to any particular programming language. It will be appreciated that a variety of programming languages can be used to implement the teachings of the disclosure as described herein.

[0070] The present disclosure can be provided as a computer program product, or software, that can include a machine-readable medium having stored thereon instructions, which can be used to program a computer system (or other electronic devices) to perform a process according to the present disclosure. A machine-readable medium includes any mechanism for storing information in a form readable by a machine (e.g., a computer). In some embodiments, a machine-readable (e.g., computer-readable) medium includes a machine (e.g., a computer) readable storage medium such as a read only memory (“ROM”), random access memory (“RAM”), magnetic disk storage media, optical storage media, flash memory devices, etc.

[0071] In the foregoing specification, embodiments of the disclosure have been described with reference to specific example embodiments thereof. It will be evident that various modifications can be made thereto without departing from the broader spirit and scope of embodiments of the disclosure as set forth in the following claims. The specification and drawings are, accordingly, to be regarded in an illustrative sense rather than a restrictive sense.

## Claims

1. A system, comprising: a memory component; and a processing device, operatively coupled with the memory component, to: send a read command to the memory component while a program or erase operation being executed by the memory component is suspended; and send a resume continuation command to the memory component prior to a checkpoint for resuming the program or erase operation being met.
2. The system of claim 1, wherein the processing device is to receive data read from the memory component during execution of the read command concurrently with execution of the program or erase operation.
3. The system of claim 1, wherein the resume continuation command is sent any time during execution of the read command.
4. The system of claim 1, wherein the checkpoint for resuming the program or erase operation corresponds to an amount of page buffer resources of the memory component being used.
5. The system of claim 1, wherein the resume continuation command is an auto resume command.
6. A method, comprising: receiving, by a memory component, a read command while a program or erase operation being executed by the memory component is suspended; and receiving, by the memory component, a resume continuation command prior to a checkpoint for resuming the program or erase operation being met.
7. The method of claim 6, wherein the method includes pausing, by the memory component, execution of the program or erase operation responsive to receiving the resume continuation command.
8. The method of claim 7, wherein the method includes resuming, by the memory component, execution of the program or erase operation responsive to the checkpoint being met.
9. The method of claim 6, wherein the method includes resuming, by the memory component, execution of the program or erase operation only after execution of the read command.
10. The method of claim 6, wherein the method includes resuming, by the memory component, execution of the program or erase operation before the read command is executed.
11. The method of claim 6, wherein the method includes triggering, by the memory component, a determination of whether the checkpoint has been met responsive to a request for page buffer resources.
12. The method of claim 11, wherein the page buffer resources are not used until requested.

- 13.** The method of claim 6, wherein the method includes confirming, by the memory component, the resume continuation command has been received.
- 14.** The method of claim 13, wherein the method includes confirming the resume continuation command has been received responsive to an amount of page buffer resources of the memory component being used.
- 15.** A method, comprising: sending a read command to a memory component while a program or erase operation being executed by the memory component is suspended; and sending a resume continuation command to the memory component subsequent to a checkpoint for resuming the program or erase operation being met.
- 16.** The method of claim 15, wherein the method includes executing the read command and a portion of the program or erase operation concurrently.
- 17.** The method of claim 15, wherein the resume continuation command is sent to the memory component before the read command is sent to the memory component.
- 18.** A system, comprising: a memory component to: receive a read command while a program or erase operation being executed by the memory component is suspended; and receive a resume continuation command subsequent to a checkpoint for resuming the program or erase operation being met.
- 19.** The system of claim 18, wherein the memory component is to resume execution of the program or erase operation responsive to receiving the resume continuation command.
- 20.** The system of claim 18, wherein the memory component is to not activate page buffer resources of the memory component until the checkpoint has been met.
-