

# US Patent & Trademark Office

## Patent Public Search | Text View

---

United States Patent	12395201
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Balderston; Brian Robert

---

### Adaptive support accessory for mobile devices

---

#### Abstract

An adaptive support accessory for providing improved handling, positioning, mounting, and adapting of a mobile device is disclosed. The accessory includes a structure and an attachment interface configured for attaching the structure to the mobile device. One or more magnetic attachment elements disposed in the structure may be configured to magnetically attach the accessory to the mobile device. An aperture may be formed in the center of the accessory and provide one or more engagement or attachment features configured for engaging one or more of a user's fingers, attaching two or more accessory components together, or mounting the accessory to another structure. One or more supports attached to the accessory may be configured to engage one or more of a user's fingers or to selectively position the accessory. One or more plugs, attachment features, or attachment elements may provide additional mechanisms for mounting, adapting, and augmenting the accessory.

---

<b>Inventors:</b>	<b>Balderston; Brian Robert (Centennial, CO)</b>
<b>Applicant:</b>	<b>Balderston; Brian Robert (Centennial, CO)</b>
<b>Family ID:</b>	<b>1000008763671</b>
<b>Appl. No.:</b>	<b>18/151895</b>
<b>Filed:</b>	<b>January 09, 2023</b>

#### Prior Publication Data

<b>Document Identifier</b>	<b>Publication Date</b>
US 20230142845 A1	May. 11, 2023

#### Related U.S. Application Data

continuation parent-doc US 17028745 20200922 US 11552667 child-doc US 18151895

---

## Publication Classification

**Int. Cl.:** H04B1/3877 (20150101); H04B1/3827 (20150101); H04M1/725 (20210101)

**U.S. Cl.:**

**CPC** H04B1/3877 (20130101); H04B1/385 (20130101); H04M1/725 (20130101);  
H04B2001/3861 (20130101)

## Field of Classification Search

**CPC:** H04B (1/3877)

---

## References Cited

### U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6550108	12/2002	Pratl	N/A	N/A
6888940	12/2004	Deppen	N/A	N/A
7374142	12/2007	Carnevali	N/A	N/A
8550317	12/2012	Hyseni	N/A	N/A
8830663	12/2013	Child et al.	N/A	N/A
8936222	12/2014	Bastian et al.	N/A	N/A
9019698	12/2014	Thiers	N/A	N/A
9243739	12/2015	Peters	N/A	N/A
9379759	12/2015	Platt	N/A	N/A
9397719	12/2015	Schmidt	N/A	F16M 11/24
9421920	12/2015	Jang	N/A	N/A
9616821	12/2016	Elharar	N/A	N/A
9799436	12/2016	Lee	N/A	N/A
9800283	12/2016	Schmidt	N/A	N/A
9913388	12/2017	Mchatet	N/A	N/A
9930943	12/2017	Lach et al.	N/A	N/A
10093377	12/2017	Whitten et al.	N/A	N/A
10117505	12/2017	Alvarez	N/A	N/A
10237384	12/2018	Holder	N/A	N/A
10327538	12/2018	Alexader	N/A	N/A
10419054	12/2018	VanTassell et al.	N/A	N/A
10627046	12/2019	Jang	N/A	N/A
10666781	12/2019	Gyasi	N/A	N/A
10694835	12/2019	Peterson et al.	N/A	N/A
11552667	12/2022	Balderston	N/A	N/A
2011/0192857	12/2010	Rothbaum et al.	N/A	N/A
2013/0279098	12/2012	Cho	N/A	N/A
2014/0166707	12/2013	Leisey-Bartsch	N/A	N/A
2014/0354218	12/2013	Kaynar et al.	N/A	N/A
2014/0364176	12/2013	Pintor	N/A	N/A
2015/0207535	12/2014	Wilson	N/A	N/A
2015/0257288	12/2014	Livernois	N/A	N/A

2015/0312389	12/2014	Curran	N/A	N/A
2016/0049983	12/2015	Ripka	N/A	N/A
2016/0088924	12/2015	Haymond et al.	N/A	N/A
2016/0150861	12/2015	Yao et al.	N/A	N/A
2017/0104854	12/2016	Park	N/A	N/A
2017/0201286	12/2016	Qian et al.	N/A	N/A
2018/0007184	12/2017	Palacino	N/A	N/A
2018/0348819	12/2017	Lay et al.	N/A	N/A
2018/0359346	12/2017	Chen	N/A	N/A
2019/0126154	12/2018	Sears	N/A	N/A
2019/0198212	12/2018	Levy	N/A	N/A
2020/0021325	12/2019	Kim	N/A	N/A
2020/0098498	12/2019	Mora et al.	N/A	N/A
2020/0099413	12/2019	Kim	N/A	N/A
2020/0329133	12/2019	Surani et al.	N/A	N/A
2021/0227960	12/2020	Carnevali	N/A	N/A
2022/0094379	12/2021	Balderston	N/A	N/A

#### **FOREIGN PATENT DOCUMENTS**

<b>Patent No.</b>	<b>Application Date</b>	<b>Country</b>	<b>CPC</b>
3043538	12/2015	EP	N/A
20140003807	12/2013	KR	N/A
101733435	12/2016	KR	N/A
200485274	12/2016	KR	N/A
101825404	12/2017	KR	N/A
2018096843	12/2017	WO	N/A

*Primary Examiner:* Liao; Hsinchun

*Attorney, Agent or Firm:* Holzer Patel Drennan

#### **Background/Summary**

CROSS-REFERENCE TO RELATED APPLICATIONS (1) The present application is a continuation of U.S. patent application Ser. No. 17/028,745, entitled “ADAPTIVE SUPPORT ACCESSORY FOR MOBILE DEVICES,” and filed on Sep. 22, 2020, which is specifically incorporated by reference herein for all that it discloses or teaches.

#### **BACKGROUND**

(1) The use of mobile devices has become nearly ubiquitous in modern society. Owing largely to their usefulness, mobile devices have become so indispensable to modern life that it is not unusual for users to keep some type of mobile device with them at all times. Although mobile devices come in a variety of shapes and sizes, most devices are ostensibly designed to be held in a user's hand with the device resting in a user's palm and supported by the fingers, leaving the user's thumb free to manipulate the device. With the exception of certain use-case scenarios where two-handed interaction may be more expedient or secure, a user may frequently find one-handed operation of their mobile device preferable, particularly insofar as it leaves their other hand free to engage in different tasks. In practice, however, the size and shape of modern mobile devices makes them difficult to hold and operate single-handedly.

(2) Consequently, a variety of accessories for mobile devices have been proposed. While ostensibly

aimed at addressing the need for improved handling and operation of mobile devices, in practice, many of these accessories only exacerbate unwanted issues hindering usability. When attached to a surface of the mobile device many of these accessories protrude so significantly that they cause undesirable complications for users, such as when the user tries to insert or remove the mobile device from their pocket, operate the device when positioned on a flat surface, or attempts to inductively charge the device's battery. While there are many different types of accessories that include some type of gripping or holding apparatus, many of these accessories necessitate fixing a user's fingers or hand in one position relative to the mobile device, restricting the flexion of a user's fingers and wrist and making it difficult for users to easily and securely adjust their grip in order to effectively interface with the outer portions of the device's display. Moreover, many of these types of accessories utilize components that are susceptible to premature wear or failure, which can result in unwanted expense and increased potential risk of damage to the mobile device. Still other types of mobile accessories are a one-size fits all type of apparatus, frequently designed for accommodating no more than one of a user's fingers and often resulting in a fit that presents users with a trade-off between comfort and security. Furthermore, many of these accessories require the use of two hands to deploy or operate, thereby reducing the practical effectiveness and utility for improved single-handed use they were intended to provide.

(3) In addition to usability issues, the size and fragility of mobile devices can make personal concurrent conveyance of other common everyday carry items challenging. While the technological capabilities included in many modern mobile devices may have reduced the need for user's to convey certain types of everyday items like cameras or flashlights, the sheer size of modern mobile devices can leave little room in one's pocket for accommodating items that a user might frequently find useful or desirable. Moreover, because the surface displays of modern mobile devices such as mobile phones are so susceptible to damage and expensive to repair, conveying other types of everyday carry items in close proximity with these types of devices can pose a substantial and costly risk to users.

(4) In many instances, a user may even find that hands-free use of a mobile device is more appropriate and preferable. Unfortunately, most mobile devices don't provide any incorporated mechanism for supporting hands-free use. As a result, users are often required to purchase complicated or expensive equipment typically designed to support just one limited hands-free use case scenario, such as mounting a mobile device to the dashboard of a vehicle or propping a mobile device up on a flat support surface.

(5) Due to the lack of versatility present in most modern mobile accessories, a user may feel compelled to purchase a variety of different accessories in order to fully accommodate the wide range of different hands-free use case scenarios that are now commonplace. Upon examination, none of the prior art can be shown to satisfy the requirements for sufficiently enabling effective single-handed operation of modern mobile devices, accommodating concomitant transport of everyday carry items, and providing for the variety of different hands-free use case scenarios common among modern mobile device users.

#### SUMMARY OF THE INVENTION

(6) The inventions described and claimed herein address the aforementioned problems by providing an adaptive support accessory that is attached to a surface of a mobile device and enables effective and secure single-handed operation of the mobile device, supports a variety of common hands-free use case scenarios, adjusts to fit a variety of different users, accommodates concomitant transport of everyday carry items, provides users with kinetic amusement, and is adaptable to a wide variety of different holding, transporting, positioning and mounting configurations. These and other features and advantages of one or more aspects will be apparent from a consideration of the drawings and ensuing detailed description.

(7) Implementations described and claimed herein provide an adaptive support accessory including a base attachable to a mobile device, a cap coupled to the base, one or more supports attached to

the cap, and a detachably attachable plug.

(8) Implementations described and claimed herein further provide a method of using an adaptive support accessory comprising attaching a base to a surface of a mobile device via a removable attachment interface; attaching a cap and one or more supports to the base; extending one or more supports from a retained position to a deployed position using one or more fingers of a user's hand; rotating the cap and/or one or more supports around the base; engaging one or more fingers of a user's hand with one or more of the cap, base, plug, and one or more supports; rotating one or both of the base and mobile device around the cap and/or one or more supports; and retracting one or more supports from a deployed position to a retained position using one or more fingers of a user's hand.

(9) Additional methods of using the adaptive support accessory further comprise attaching one or both of a plug and an attachment element to the adaptive support accessory; attaching one or more of the cap, base, and plug to one or both of a compatible mount and mounting structure, engaging one or more fingers of a user's hand with one or both of an interior and exterior perimetric face of the adaptive support accessory; attaching one or more of the cap, base, plug and one or more extended supports to one or both of a compatible mount and mounting structure; rotating one or both of the base and mobile device around the cap and/or one or more supports; positioning one or more supports on a support surface to dispose the mobile device in a preferred orientation; and rotating the cap and/or one or more supports around the base to change the orientation of the mobile device.

(10) Implementations described and claimed herein still further provide an adaptive support accessory comprising an intermediate mounting pad for configuring a mobile device for attachment to the attachment interface, a plug removal feature for detaching one or more attachable plugs, attachment features and attachment elements disposed in one or more components of the accessory and configured for attaching different accessory components together and/or attaching the accessory to a mount or mounting structure, and a mount and mounting structure configured for attachment to one another and/or the accessory.

(11) Other implementations are also described and recited herein. This Summary is provided to introduce a section of concepts in a simplified form that are further described below in the Detailed Descriptions. This Summary is not intended to identify key features or essential features of the claimed subject matter, nor is it intended to be used to limit the scope of the claimed subject matter.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 illustrates a top view of an example adaptive support accessory shown affixed to a mobile device and held in a user's hand, in accordance with an aspect of the present invention.

(2) FIG. 2 illustrates a top perspective view of an example adaptive support accessory affixed to a mobile device, with a first support extended in a deployed position, a second support retracted in a retained position, and a plug disposed in the center of the accessory.

(3) FIG. 3 illustrates a top perspective projected view of an example adaptive support accessory affixed to a mobile device with two supports retracted in a retained position and a detachably attachable plug configured for attachment to the accessory.

(4) FIG. 4A illustrates a top perspective view of an example adaptive support accessory with two supports retracted in a retained position.

(5) FIG. 4B illustrates a sectional view of the example adaptive support accessory of FIG. 4A

(6) FIG. 4C illustrates an enlarged sectional view of FIG. 4B.

(7) FIG. 4D illustrates a top exploded perspective view of an example adaptive support accessory with a base, two supports, a cap, and a plug.

- (8) FIG. 4E illustrates a bottom exploded perspective view of an example adaptive support accessory with a base, two supports, a cap, and a plug.
- (9) FIG. 4F illustrates a top perspective sectional view of an example adaptive support accessory.
- (10) FIG. 4G illustrates a top view of an example adaptive support accessory.
- (11) FIG. 4H illustrates a bottom view of an example adaptive support accessory.
- (12) FIG. 4I illustrates a top perspective view of an example adaptive support accessory.
- (13) FIG. 4J illustrates a bottom perspective view of an example adaptive support accessory.
- (14) FIG. 4K illustrates a front view of an example adaptive support accessory.
- (15) FIG. 4L illustrates a side view of an example adaptive support accessory.
- (16) FIG. 5A illustrates a top exploded perspective view of a base, an attachment interface, and a protective cover.
- (17) FIG. 5B illustrates a top perspective view of an attachment interface.
- (18) FIG. 5C illustrates a top perspective view of a base attached to an attachment interface.
- (19) FIG. 5D illustrates a top perspective view of an intermediate mounting pad.
- (20) FIG. 5E illustrates a top perspective projected view of a base attached to an intermediate mounting pad affixed to a mobile device and two supports attached to a cap axially aligned with and attachable to the base.
- (21) FIG. 6A illustrates a top perspective projected view of an example adaptive support accessory affixed to a mobile device with a flexible plug removal feature disposed in the center of the accessory and a detachably attachable plug.
- (22) FIG. 6B illustrates a top perspective view of a plug configured with a flexible plug removal feature.
- (23) FIG. 6C illustrates a top perspective view of a plug configured with a rigid plug removal feature.
- (24) FIG. 6D illustrates a top perspective view of an example adaptive support accessory affixed to a mobile device with a flexible plug removal feature extending over a cap and retained between the cap and a support.
- (25) FIG. 7A illustrates a top exploded perspective view of an example adaptive support accessory with a detachably attachable plug, and multiple attachment elements and attachment features.
- (26) FIG. 7B illustrates a side projected view of an example adaptive support accessory affixed to a mobile device, with a mount configured with an attachment feature and an attachment element and affixed to a mounting structure configured with two accessory engagement features.
- (27) FIG. 7C illustrates a side view of an example adaptive support accessory affixed to a mobile device with a support attached to a hook-shaped accessory engagement feature disposed in a mounting structure.
- (28) FIG. 8A illustrates a side view of an example adaptive support accessory affixed to a mobile device and held in a user's hand, with a first and second finger of a user's hand engaged with an interior perimetric face of the accessory and a third finger engaged with an exterior perimetric face of a support.
- (29) FIG. 8B illustrates a top view of an example adaptive support accessory affixed to a mobile device and held in a user's hand, with a first finger of a user's hand engaged through a first support, a second finger engaged with an exterior perimetric face of a second support, and a third finger engaged with an exterior perimetric face of a cap.
- (30) FIG. 8C illustrates a top view of an example adaptive support accessory affixed to a mobile device and held in a user's hand, with a first and second finger of a user's hand engaged through two supports.
- (31) FIG. 8D illustrates a top view of an example adaptive support accessory affixed to a mobile device and held in a user's hand, with a first and second finger of the user's hand engaged through two supports and the user's thumb rotating the mobile device and base affixed thereto about an axis of rotation.

(32) FIG. 9A illustrates a side view of an example adaptive support accessory affixed to a mobile device, with a support extended in a deployed position and supporting the mobile device in a first example portrait orientation.

(33) FIG. 9B illustrates a side view of an example adaptive support accessory affixed to a mobile device, with two supports extended in a deployed position and supporting the mobile device in a second example portrait orientation.

(34) FIG. 9C illustrates a bottom perspective view of an example adaptive support accessory affixed to a mobile device, with two supports extended in a deployed position and supporting the mobile device in a first example portrait orientation.

(35) FIG. 9D illustrates a top perspective view of an example adaptive support accessory affixed to a mobile device, with a support extended in a deployed position and orienting the mobile device in a first example landscape orientation.

(36) FIG. 9E illustrates a bottom perspective view of an example adaptive support accessory affixed to a mobile device, with two supports extended in a deployed position and orienting the mobile device in a second example landscape orientation.

(37) FIG. 10 illustrates example operations for using an example adaptive support accessory.

(38) FIG. 11A illustrates a top perspective exploded view of a disc-shaped accessory cover attachable to the top of a plug.

(39) FIG. 11B illustrates a bottom perspective view of a disc-shaped accessory cover attached to the top of a plug.

(40) FIG. 11C illustrates a top perspective exploded view of a disc-shaped accessory cover attachable to the top of a cap.

(41) FIG. 11D illustrates a top perspective exploded view of a ring-shaped accessory cover attachable to the top of a cap.

(42) FIG. 11E illustrates a top perspective sectional view of a flanged accessory cover with an aperture disposed in the bottom and a partially enclosed bottom.

(43) FIG. 11F illustrates a top perspective sectional view of a flanged accessory cover with an aperture disposed in the center and an enclosed bottom.

(44) FIG. 11G illustrates a top perspective sectional view of a flanged accessory cover with an aperture disposed in the center and a recess disposed in an interior perimetric face.

(45) FIG. 12A illustrates a top perspective view of a plug configured with a twist lock attachment feature and an attachment element.

(46) FIG. 12B illustrates a top perspective view of a plug with an attachment feature configured for attachment to an expandable grip.

(47) FIG. 12C illustrates a top view of a plug and a cap with an alignment indicator disposed on a top surface.

(48) FIG. 12D illustrates a top perspective view of a plug with a selectively rotatable center portion with different attachment elements disposed on opposite faces thereof.

(49) FIG. 12E illustrates a top perspective sectional view of a plug with a selectively attachable and reversible center portion with different attachment elements disposed on opposite faces thereof.

(50) FIG. 12F illustrates a top perspective view of a plug with a magnetic attachment element configured with a plug removal feature.

(51) FIG. 12G illustrates a top perspective view of a plug with two selectively rotatable attachment features.

(52) FIG. 12H illustrates a top perspective view of a plug with a rotatable center portion.

(53) FIG. 12I illustrates a top perspective view of a plug with a threaded attachment feature and a flanged bottom.

(54) FIG. 12J illustrates a top perspective view of a plug configured with an attachment hole and a plug removal feature and disposed in a plug receptacle.

(55) FIG. 13A illustrates a top perspective view of a plug configured with an extendable and

retractable knife and bottle opener.

(56) FIG. 13B illustrates a top perspective view of a plug configured with a rotatably extendable bottle opener and box cutter.

(57) FIG. 13C illustrates a top perspective view of a plug container configured with a hinged lid and a magnetic closure.

(58) FIG. 13D illustrates a top perspective view of a plug configured with a rotatably extendable key.

(59) FIG. 14A illustrates a top perspective view of an example accessory with a plug and a cap each configured with corresponding design elements.

(60) FIG. 14B illustrates a top perspective view of an example accessory with a circular aperture disposed in the center of a plug.

(61) FIG. 14C illustrates a top perspective view of an example accessory with a heart-shaped aperture disposed in the center of a plug.

(62) FIG. 14D illustrates a top perspective view of an annular-shaped example accessory with an aperture disposed in the center of the accessory.

(63) FIG. 14E illustrates a top perspective view of a substantially square-shaped example accessory.

(64) FIG. 14F illustrates a top perspective view of a substantially rectangular-shaped example accessory.

(65) FIG. 14G illustrates a top perspective view of a substantially circular-shaped example accessory with two flat sides disposed opposite one another.

(66) FIG. 14H illustrates a top perspective view of a substantially oblong-shaped example accessory.

(67) FIG. 14I illustrates a top perspective view of a substantially hexagonal-shaped example accessory.

(68) FIG. 14J illustrates a top perspective view of an example accessory including a substantially polygonal-shaped cap.

(69) FIG. 14K illustrates a top perspective view of a substantially heart-shaped example accessory.

(70) FIG. 14L illustrates a top view of an example accessory with a shape and ornamentation depicting a fictional creature.

(71) FIG. 15A illustrates a top perspective view of a base with a partially enclosed bottom center portion.

(72) FIG. 15B illustrates a top perspective sectional view of a cap with an enclosed bottom center portion.

(73) FIG. 15C illustrates a bottom perspective view of a cap with an enclosed top center portion.

(74) FIG. 15D illustrates a top perspective view of a cap with an enclosed top.

(75) FIG. 15E illustrates a top perspective sectional view of a cap with a fourth annular cap protrusion.

(76) FIG. 15F illustrates a top perspective sectional view of an example accessory with a base and a cap configured with a pair of corresponding engagement features.

(77) FIG. 16A illustrates a top perspective sectional view of an example accessory with an outward extending base engagement feature and inward extending cap engagement feature.

(78) FIG. 16B illustrates an enlarged sectional view of FIG. 16A.

(79) FIG. 16C illustrates a top perspective sectional view of an example accessory with an outward extending base engagement feature and inward extending cap engagement feature.

(80) FIG. 16D illustrates a top perspective sectional view of an example accessory with a cap extending over an annular base protrusion.

(81) FIG. 16E illustrates a top perspective sectional view of an example accessory with three base components.

(82) FIG. 16F illustrates a top perspective sectional view of an example accessory with two base



components.

(83) FIG. **16G** illustrates a top perspective assembly view of an example accessory with two base components and an accessory cover attached to the top of a cap.

(84) FIG. **16H** illustrates a top perspective view of an example accessory with two base components and two cap components.

(85) FIG. **16I** illustrates a top perspective sectional view of FIG. **16H**.

(86) FIG. **16J** illustrates a top perspective assembly view of FIG. **16H**.

(87) FIG. **17A** illustrates a top perspective view of an example accessory with a support fastened to a cap.

(88) FIG. **17B** illustrates a top view of two supports connected together and fastened to a cap.

(89) FIG. **17C** illustrates a top perspective assembly view of FIG. **17B**.

(90) FIG. **18A** illustrates a top perspective assembly view of two projections fastened to a cap.

(91) FIG. **18B** illustrates a top perspective view of two projections and supports fastened to a cap.

(92) FIG. **18C** illustrates a top perspective assembly view of FIG. **18B**.

(93) FIG. **18D** illustrates a bottom perspective view of a cap configured with multiple exterior cap recesses and fastening blocks.

(94) FIG. **18E** illustrates a top perspective view of an example accessory with two projections and two supports attached to the cap via multiple fasteners.

(95) FIG. **18F** illustrates a top perspective assembly view FIG. **18E**.

(96) FIG. **19A** illustrates a top perspective view of a rigid support attached to a cap.

(97) FIG. **19B** illustrates a top perspective view of an example accessory with three supports rotatably attached to a cap.

(98) FIG. **19C** illustrates a top perspective assembly view of FIG. **19B**.

(99) FIG. **19D** illustrates a top perspective view of an example accessory with three supports rotatably attached to a cap.

(100) FIG. **19E** illustrates a top perspective assembly view of FIG. **19D**.

(101) FIG. **19F** illustrates a top perspective view of a support rotatably attached to a plug.

(102) FIG. **19G** illustrates a top perspective view of an example accessory with three supports attached to a cap.

(103) FIG. **19H** illustrates a top perspective assembly view of FIG. **19G**.

(104) FIG. **19I** illustrates a top perspective assembly view of two rigid supports rotatably attached to a cap and a third flexible support configured with an adjustable tensioner and disposed in a pair of projections attached to the cap via fasteners.

(105) FIG. **19J** illustrates a top perspective view of a flexible support configured with a mechanism for self-attachment and attached to a cap through a pair of slots.

(106) FIG. **19K** illustrates a top perspective view of a flexible support attached to a cap through a pair of slots and secured via fasteners.

(107) FIG. **19L** illustrates a bottom perspective view of a cap with fasteners disposed in opposite ends of the cap and configured for attaching a flexible support.

(108) FIG. **19M** illustrates a bottom perspective assembly view of a flexible support with a fastener attached at each end and configured for attachment to a cap through a pair of slots.

(109) FIG. **19N** illustrates a top perspective view of a plug with a flexible support attached to the plug through a pair of slots disposed in the plug.

(110) FIG. **19O** illustrates a top perspective sectional view of FIG. **19N**.

(111) FIG. **19P** illustrates a top perspective sectional view of a plug with a flexible support attached through a pair of slots disposed in the plug.

(112) FIG. **19Q** illustrates a top perspective view of a plug with enlarged distal ends and disposed in a pair of slots disposed in a plug.

(113) FIG. **19R** illustrates a top perspective view of a support with enlarged distal ends and disposed in a pair of slots disposed in a plug and a rigid prop attached to the support and configured

for engagement with a pair of prop engagement features.

(114) FIG. **19S** illustrates a top perspective view of a plug with enlarged distal ends and disposed in a pair of slots disposed in a plug and a rigid prop rotatably attached to the support and configured for engagement with a pair of prop engagement features.

(115) FIG. **20A** illustrates a bottom perspective assembly view of an example accessory with multiple magnetic attachment elements disposed in a cap and configured to attach to a magnetic attachment interface disposed in the bottom of a base.

(116) FIG. **20B** illustrates a bottom perspective assembly view of multiple magnetic attachment elements combinable together in a continuous shape and disposed in a cap.

(117) FIG. **20C** illustrates a bottom perspective assembly view of cap with an annular attachment element disposed therein.

(118) FIG. **20D** illustrates a top perspective sectional view of an example accessory with multiple magnetic attachment elements disposed in a cap and configured to attach to a magnetic attachment interface disposed in the bottom of a base, the cap including multiple annular cap protrusions disposed adjacent to an annular base protrusion.

(119) FIG. **20E** illustrates an enlarged sectional view of an example accessory with a ball bearing attachment element disposed in between a cap and a base.

(120) FIG. **20F** illustrates a top perspective assembly view of an example accessory with a magnetic bearing attachment element disposed in a cap configured to rotatably couple to a magnetic attachment interface disposed on a surface of a mobile device.

(121) FIG. **20G** illustrates a top perspective assembly view of an example accessory including a cap with a magnetic attachment element disposed therein and configured to attach to a magnetic attachment interface disposed in the top of a mobile device case and a plug with a magnetic attachment element disposed on a bottom surface thereof configured to attach to another attachment element disposed in the bottom interior of the case.

(122) FIG. **20H** illustrates top perspective assembly view of an example accessory with a cap rotatably coupled to a base attached to a magnetic attachment interface configured for attachment to a mobile device with multiple magnetic attachment elements disposed therein.

(123) FIG. **21A** illustrates a top perspective assembly view of an example accessory with a base substantially integrated into a surface of a mobile device case.

(124) FIG. **21B** illustrates a top perspective view of a base substantially integrated into a mobile device cover.

(125) FIG. **21C** illustrates a top perspective assembly view of an example accessory with a base of a shape and size generally conforming with and configured for attachment to a surface of a mobile device.

(126) FIG. **21D** illustrates a top perspective view of an example accessory with a base configured for attachment to two sides of a mobile device.

(127) FIG. **21E** illustrates a top perspective view of an example accessory with a base attached around two sides of the mobile device.

(128) FIG. **21F** illustrates a top perspective view of an example accessory disposed on top of an example second mobile accessory.

(129) FIG. **21G** illustrates a top perspective sectional view of an example second mobile accessory with a recess formed in the top configured for receiving a portion of a base.

(130) FIG. **21H** illustrates a top perspective sectional view of an example second mobile accessory configured to attach to a base.

(131) FIG. **22A** illustrates a top perspective view of a base with an opening formed in the bottom and extending through an exterior perimetric face thereof.

(132) FIG. **22B** illustrates a bottom perspective view of an attachment interface with two openings formed in the bottom surface thereof and attached to the bottom of a base.

(133) FIG. **22C** illustrates a top perspective view of an intermediate mounting pad with an opening

formed in the top surface thereof.

(134) FIG. 22D illustrates a top perspective view of a plug configured with a flexible support disposed in one end.

(135) FIG. 22E illustrates a top perspective view of a plug disposed in a cap and configured with a flexible support extending outward through an opening formed in the bottom of a base.

(136) FIG. 22F illustrates a top perspective assembly view of an electronic port connected to an electronic connector via a flexible cable and configured for connection with a second electronic port disposed in a plug.

(137) FIG. 22G illustrates a top perspective assembly view of an example accessory with an electronic port disposed in a base and configured for connection with a second electronic port disposed in a plug.

(138) FIG. 22H illustrates a top perspective view of an example accessory with an electronic connector attached to a mobile device and an electronic port configured for attachment to another electronic port disposed in a plug.

(139) FIG. 23A illustrates a top perspective view of a flexible support disposed in one end of an intermediate mounting pad.

(140) FIG. 23B illustrates a top perspective view of a flexible support disposed in a lateral projection of a base.

(141) FIG. 23C illustrates a top perspective view of a flexible support and a rotatable rigid support disposed in a lateral projection of a base.

(142) FIG. 23D illustrates a top perspective view of a rotatable rigid support disposed in a lateral projection of a base.

(143) FIG. 23E illustrates a top perspective view of a rotatable rigid support attached to a lateral projection of a base.

(144) FIG. 23F illustrates a top perspective view of a rotatable rigid support disposed in the bottom of a base with a stop extending from the support through an opening disposed in the bottom of the base.

(145) FIG. 23G illustrates a top perspective view of an example accessory and support retainer attached to a mobile device, the accessory including three rotatable rigid supports extended in a deployed position.

(146) FIG. 23H illustrates a side view of an example accessory with three rotatable rigid supports retracted in a retained position.

(147) FIG. 23I illustrates a top perspective view of an example accessory with three rotatable rigid supports retracted in a retained position.

(148) FIG. 23J illustrates a front view of an example accessory with three rotatable rigid supports retracted in a retained position.

(149) FIG. 23K illustrates a back view of an example accessory with three rotatable rigid supports retracted in a retained position.

(150) FIG. 23L illustrates a bottom perspective view of an example accessory with three rotatable rigid supports retracted in a retained position.

(151) FIG. 23M illustrates a top view of an example accessory with three rotatable rigid supports retracted in a retained position.

(152) FIG. 23N illustrates a bottom view of an example accessory with three rotatable rigid supports retracted in a retained position.

(153) FIG. 24 illustrates a top perspective view of an example accessory with a base slidably disposed inside a base track.

#### DETAILED DESCRIPTIONS

(154) The following disclosure is directed to accessories for mobile devices that improve a user's ability to hold, operate, mount, and position a mobile device. Variations of an adaptive support accessory are further directed to mobile device accessories that improve the usability and versatility

of a mobile device. The accessory may be adaptive to the wide variety of common mobile device use-case scenarios and provides improved single-handed and hands-free use of a mobile device. In addition, multiple options for adapting and augmenting the utility of the mobile device are provided. The disclosed adaptable support accessory implementations are intended to address some or all of the foregoing problems with prior mobile device accessories, as well as additional problems with prior mobile device accessories not specifically identified herein.

(155) FIG. 1 is a top view illustrating an example adaptive support accessory indicated generally at **1010** shown affixed to an exterior surface of an example mobile device **1012**, such as a cellular phone or tablet, and held in a user's hand **1014**. The adaptive support accessory **1010** (hereinafter referred to as “accessory”) enables the user to securely hold and operate the mobile device **1012** single-handedly by providing multiple engagement options for one or more fingers of the user's hand **1014**.

(156) FIG. 2 is a top perspective view illustrating an example accessory **2010** affixed to an exterior surface of a mobile device **2012**. The accessory **2010** includes a base **2016** configured for attachment to a surface of the mobile device **2012** via one or more of an attachment interface (not shown, e.g., see **5042** in FIG. 5C) and an intermediate mounting pad (not shown, e.g., see **5072** in FIGS. 5D-5E), a cap **2018** rotatably coupled to the base **2016** and centered around an axis of rotation (not shown, e.g., see axis **3034** in FIG. 3), one or more detachably attachable plugs **2028**, and one or more supports **2020**, **2022** attached to one or more of the cap **2018**, base **2016**, and plug **2028**.

(157) One or more supports **2020**, **2022** attached to the cap **2018** may be retracted to a retained position (e.g., support **2022** in FIG. 2) and/or extended to a deployed position (e.g., support **2020** in FIG. 2). The supports **2020**, **2022** provide an engagement feature by which the accessory **2010** can be held in a user's hand (e.g., see FIGS. 1 and 8A-8D), attached to a mount or mounting structure (e.g., see FIGS. 7B-7C), and positioned to support the mobile device **2012** in a preferred orientation on a support surface such as a table (e.g., see FIGS. 9A-9E). In various implementations, one or more projections **2024**, **2026** laterally disposed on opposite ends of the exterior perimeter of the cap **2018** are configured to limit the movement of one or more supports **2020**, **2022** by at least one degree of freedom, restricting the supports from being extended beyond a pre-determined position with respect to the cap **2018**. In some implementations, the cap **2018**, supports **2020**, **2022**, projections **2024**, **2026**, and plug **2028** substantially surround and conceal the base **2016**.

(158) FIG. 3 is a top perspective view illustrating an example accessory **3010** affixed to an exterior surface of a mobile device **3012**. A base (e.g., see base **4016** in FIGS. 4D-4E) and a cap **3018** are rotatably coupled and centered about an axis of rotation **3034**. One or more supports **3020**, **3022** attached to the cap **3018** may be retracted to a retained position wherein the accessory **3010** is able to maintain a low profile with respect to the mobile device **3012**, facilitating conveyance and storage of the accessory **3010** and affixed mobile device **3012**. One or more plugs **3028** may be permanently or detachably attached to the accessory **3010** to adapt and/or augment one or both of the accessory **3010** and the mobile device **3012**. In various implementations, the plug **3028** augments the utility, functionality, and ornamentation of the accessory **3010**. The plug **3028** may have an exterior perimeter generally conforming to an aperture **3030** disposed in the center of accessory **3010** and formed in one or both of the base and the cap **3018**. An interior perimetric face **3032** of the accessory **3010** circumscribing the aperture **3030** may provide an engagement for one or more of a user's fingers, a plug **3028**, a mount (e.g., see **7092** in FIG. 7B), and a mounting structure (e.g., see **7094** in FIG. 7B).

(159) FIG. 4A is a top perspective view illustrating an example accessory **4010** with a cap **4018** rotationally coupled to a base **4016** and centered about an axis of rotation **4034**, with two supports **4020**, **4022** attached to the cap **4018** and retracted in a retained position. FIG. 4B is a top sectional perspective view of FIG. 4A. FIG. 4C is an enlarged detail view of FIG. 4B. FIG. 4D is a top

exploded perspective view of an example accessory **4010**. FIG. 4E is a bottom exploded perspective view of an example accessory **4010**. FIG. 4F is a top perspective sectional view of an example adaptive support accessory. FIG. 4G is a top view of an example adaptive support accessory **4010**. FIG. 4H illustrates a bottom view of an example adaptive support accessory **4010**. FIG. 4I is a top perspective view of an example adaptive support accessory **4010**. FIG. 4J is a bottom perspective view of an example adaptive support accessory **4010**. FIG. 4K is a front view of an example adaptive support accessory **4010**. FIG. 4L is a side view of an example adaptive support accessory **4010**.

(160) Referring to FIGS. 4A-4E, in various implementations, a base (e.g., base **4016**) includes a first annular base protrusion (e.g., see protrusion **4036** in FIG. 4C) extending longitudinally from the base **4016** and centered about an axis of rotation **4034**. The interior and exterior perimetric faces of the first annular base protrusion **4036** may be symmetrical or asymmetrical with respect to one another. The base **4016** may extend radially inward and/or outward from the first annular base protrusion **4036**, as shown in FIG. 4C.

(161) A first base engagement feature (e.g., see feature **4038** in FIG. 4C) may extend radially inward and/or outward from the first annular base protrusion **4036**. The first base engagement feature **4038** may have a profile and shape configured to engage with a corresponding feature of another component of the accessory **4010** such as a plug **4028** or a cap (e.g., cap **4018**). In various implementations, the first base engagement feature **4038** is one of a type of mechanical joint or snap type connector and may operate by an interference fit or friction fit with another component of the accessory **4010**. In some implementations, the first base engagement feature **4038** is configured to engage with a corresponding engagement feature disposed in the cap **4018** (e.g., see feature **4046** in FIG. 4C). In various implementations, the first base engagement feature **4038** is annular. In some implementations, the first base engagement feature **4038** is a permanent or removable annular snap. In other implementations, the first base engagement feature is a torsional or cantilevered snap. In other implementations, the first base engagement feature is a removable snap ring disposed in an annular recess formed in one of an interior and exterior perimetric face of the first annular base protrusion **4036**. In other implementations, the first base engagement feature includes one or more pins or fasteners attached to the base **4016** and laterally disposed through one or both of the interior and exterior perimetric faces of the first annular base protrusion **4036**.

(162) The bottom of the base **4016** may have a profile generally conforming to a portion of one or more exterior surfaces of a mobile device (e.g., see device **3012** in FIG. 3). In various implementations, an aperture **4030** formed in the center of the accessory **4010** may also be formed in the center of the base **4016** and may extend therethrough. In various implementations, the first annular base protrusion **4036** circumscribes the aperture **4030** formed in the base, defining an interior perimetric face **4032** of one or both of the base **4016** and the accessory **4010**. A first exterior base recess **4040** may be formed in the bottom of the base **4016** and may be configured to receive an attachment interface **4042** for attaching the base **4016** to one of a housing, case, and cover for the mobile device. In some implementations, the bottom of the base **4016** or a portion thereof is formed separately from the base **4016** and may be permanently or detachably attached.

(163) The base **4016** may be substantially rigid or substantially flexible. The base **4016** may have a shape that is generally annular or circular. In various implementations, the base **4016** has a profile generally conforming to the shape and profile of the cap **4018** and/or one or more supports **4020**, **4022**. A portion of one or both of an interior and exterior perimeter of the base **4016** may have a squared, rounded, or chamfered profile, and may be configured for facilitating removal of the base **4016** from the mobile device. In addition, indicia, such as a name, logo, slogan, trademark, or service mark representing one or more of a business, product, or person may be disposed on, across, or around one or more surfaces of the base **4016**.

(164) In various implementations, the cap (e.g., cap **4018**) is rotatably coupled to the base **4016** about the axis of rotation **4034**. The cap **4018** may be permanently or detachably coupled to the

base **4016**. As shown in FIG. **4C**, the cap **4018** may include a first annular cap protrusion **4044** extending longitudinally from the cap **4018**, centered about the axis of rotation **4034**, and disposed adjacent to the first annular base protrusion **4036** extending longitudinally from the base **4016**. The interior and exterior perimetric faces of the first annular cap protrusion **4044** may be symmetrical or asymmetrical with respect to one another. The cap **4018** may extend radially inward and/or outward from the first annular cap protrusion **4044**.

(165) In various implementations, the aperture **4030** formed in the center of the accessory is also formed in the center of the cap **4018** and may extend therethrough. The aperture **4030** formed in the cap **4018** may be axially aligned with and generally correspond to the aperture **4030** formed in the base **4016**, each aperture **4030** being either slightly larger or smaller in diameter with respect to the one another. In various implementations, the first annular cap protrusion **4044** circumscribes the aperture **4030**, defining an interior perimetric face **4032** of one or both of the cap **4018** and the accessory **4010**. In some implementations, the shape of the aperture **4030** may be circular or round. In other implementations, the shape of the aperture may be triangular, square, rectangular, or polygonal. One or both of the aperture **4030** and the interior perimetric face **4032** of the accessory **4010** may be configured to receive and engage one or more of a user's finger (e.g., see FIG. **8A**), a mount (e.g., see mount **7092** in FIG. **7B**), and a mounting structure (e.g., see mounting structure **7094** in FIGS. **7B-7C**).

(166) As shown in FIG. **4C**, the first annular cap protrusion **4044** may include one or more first cap engagement features **4046** extending radially inward and/or outward from the first annular cap protrusion **4044**. The first cap engagement feature **4046** may have a shape and profile configured to engage with a corresponding feature disposed in another component of the support accessory **4010** such as the plug **4028** or the base **4016**. The first cap engagement feature **4046** may be one of a type of mechanical joint or connector and may operate by an interference fit or friction fit with another component of the accessory **4010**. The first cap engagement feature **4046** may be configured to engage with a corresponding engagement feature disposed in the base **4016**, such as the first base engagement feature **4038**. In various implementations, the first cap engagement feature **4046** is annular. In some implementations, the first cap engagement feature **4046** is a permanent or removable annular snap. In other implementations, the first cap engagement feature is a torsional or cantilevered snap. In other implementations, the first cap engagement feature is a removable snap ring disposed in an annular recess formed in one of the interior and exterior perimetric faces of the first annular cap protrusion **4044**. In other implementations, the first cap engagement feature includes one or more pins or fasteners attached to the cap **4018** and laterally disposed through one or both of the interior and exterior perimetric faces of the first annular cap protrusion **4044**.

(167) A second annular cap protrusion **4048** may extend longitudinally from the cap **4018** and define an exterior perimetric face **4050** of the cap **4018**. The exterior perimetric face **4050** of the cap **4018** may provide an engagement for one or more of a user's fingers, a mount, and a mounting structure. In some implementations, a third annular cap protrusion **4054** extends longitudinally from the cap **4018** and is disposed between the first and second annular cap protrusions **4044**, **4048**. The third annular cap protrusion **4054** may be configured to provide structural reinforcement to the cap **4018** and aid in maintaining concentricity and engagement between the cap **4018** and the base **4016**.

(168) As shown in FIG. **4C**, a first interior cap recess **4052** may be formed in the bottom of the cap **4018** adjacent to the first annular cap protrusion **4044** and configured to receive at least a portion of one or both of the first annular base protrusion **4036** and the first base engagement feature **4038**. A second interior cap recess **4056** may be formed in the bottom of the cap **4018** adjacent to the second annular cap protrusion **4048**. In some implementations, one or both of the first and second interior cap recesses **4052**, **4056** formed in the cap **4018** may be configured to receive and retain one or more ferrous or magnetic elements. In other implementations, one or more of the first,

second, and third annular cap protrusions **4044**, **4048**, **4054** include one or more radially extending continuous or segmented engagement features arranged around the protrusion and configured to retain one or more ferrous or magnetic elements within the cap **4018**. In other implementations, third annular cap protrusion **4054** and second interior cap recess **4056** are omitted and the first annular base protrusion **4036** and first base engagement feature **4038** are disposed in the first interior cap recess **4052** between the first and second annular cap protrusions **4044**, **4048**, as shown in FIG. 4F. In some implementations, a low-friction washer, spacer, or element made of a material such as PTFE or Teflon is disposed between the base **4016** and the cap **4018** in order to reduce friction between the components. In other implementations, one or more attachment elements such as bearing, selected from the group of bearings including, ball bearings, roller bearings, thin section bearings, race bearings, needle roller bearings, thrust bearings, or turntable type bearings, may be disposed in between or attached to one or both of the base **4016** and the cap **4018** to facilitate smooth and continuous rotation between the components (e.g., see bearing **20084** in FIG. 20D). (169) The cap **4018** may be substantially rigid or substantially flexible. The cap **4018** may have a shape or profile that is substantially annular or circular. In other implementations, the cap has a shape that is substantially square, rectangular, oblong, or polygonal, as shown in FIGS. 14E-14J. Indicia, such as a name, logo, slogan, trademark, or service mark representing one or more of a business, product, or person may be disposed on, across, or around one or more surfaces of the cap **4018** or another component attached thereto, as shown in FIGS. 11C-11D. In some implementations, a portion of the interior perimetric face **4032** of the cap **4018** may be over-molded, separately formed from, or detachably attached to the cap **4018**. In other implementations, one or more exterior portions of the cap may be extendable and collapsible. In other implementations, an expandable grip or knob may be disposed in or attached to the cap **4018**. One or both of the interior and exterior perimeters of the cap **4018** may have a squared, rounded, or chamfered profile. In some implementations, the top surface of the cap is sloped or angled. In other implementations, one or both of the top and bottom surfaces of the cap **4018** are substantially planar and flat.

(170) In various implementations, one or more supports (e.g., supports **4020**, **4022**) are permanently or detachably attached to one or more components of the accessory **4010** and configured to engage with one or more of a user's fingers (e.g., see FIGS. 8A-8D), a mount (e.g., see FIG. 7B), and a mounting structure (e.g., see FIG. 7C). One or more supports may be disposed in or attached to one or more of the base **4016**, the cap **4018**, and the plug **4028**. In some implementations, the supports **4020**, **4022** are attached to the cap **4018** at their opposing distal ends. A portion of an interior perimetric face of one or more supports **4020**, **4022** may be disposed adjacent to the exterior perimetric face **4050** of the cap **4018** when retracted in a retained position. In some implementations, one or more supports **4020**, **4022** may have an interior profile generally conforming to at least a portion of the exterior profile of the cap **4018**.

(171) In some implementations, one or more supports (e.g., supports **4020**, **4022**) are substantially rigid. One or more supports **4020**, **4022** may be arc-shaped or ring-shaped. In other implementations, one or more supports may be flexible and in the general form of a strap, loop, band, ribbon, or cord (e.g., see supports **19164** in FIGS. 19G-19I). One or more supports **4020**, **4022** may have a profile that is substantially cylindrical or oval. In other implementations, one or more supports have an exterior profile that is sloped downward and outward at an angle. In some implementations, an exterior portion of one or more supports **4020**, **4022** is flat, beveled, or chamfered and configured to maximize surface contact with a substantially flat support surface upon which they may be disposed (e.g., see support **4022** FIGS. 4H-4K). In other implementations, two or more proximally disposed projections (not shown) spaced apart and extending outward from the exterior the supports are configured to provide additional contact points for improved stability when placed on a flat support surface. In other implementations, one or both of the top and bottom of the supports are substantially flat (e.g., see FIGS. 14E-14H). In other implementations, one or

more supports include a projecting portion that is permanently or detachably attached (e.g., see supports **14020**, **14022** in FIG. **14L**). In some implementations, the supports include an interior or exterior portion that is over-molded and configured for providing improved contact between the supports and one or more of a user's fingers and/or a support surface, (e.g., see inside portion of supports **19020**, **19022** in FIG. **19C** and bottom edge and circumscribing aperture **23030** of support **23196** in FIG. **23D**). In other implementations, two supports are connected together at their distal ends by a flexible tether configured for preventing the supports from rotating beyond a predetermined position with respect to the cap **4018**. In other implementations, a proximal interior portion of the supports is spaced apart from the exterior perimetric face of the cap **4018** and configured to accommodate a user's fingers of larger diameter. In various implementations, the movement of one or more supports (e.g., supports **4020**, **4022**) attached to one of the base **4016** and the cap **4018** is restricted by at least one degree of freedom.

(172) As shown in FIGS. **4D-4E**), a support arbor **4068** may be disposed in and extend laterally inward and/or outward from each distal end of the supports (e.g., supports **4020**, **4022**), about which the supports **4020**, **4022** may pivot with respect to the cap **4018**. The support arbors **4068** may have a substantially cylindrical shape and round profile. In other implementations, one or more support arbors have a substantially semi-circular, square, or rectangular profile. In various implementations, one or more pairs of exterior cap recesses **4058** formed in opposite sides of the exterior of the cap **4018** are configured to receive a portion of a corresponding pair of support arbors **4068** and wherein the movement of the arbors **4068** and attached support may be restricted by at least one degree of freedom.

(173) In other implementations, one side of the support arbors are flat and configured to engage with corresponding portions of the exterior cap recesses whereby rotation of the support arbors and attached support may be limited at a predetermined position. In other implementations, the support arbors have enlarged distal ends disposed in the exterior cap recesses and configured to engage with a portion of the exterior cap recesses, whereby the lateral movement of one or more supports is limited with respect to the cap. In other implementations, the supports include partial spherical projections disposed on an interior perimetric face of the supports and configured for engaging with the top of the cap and/or corresponding partial spherical recesses disposed in the exterior perimetric face of the cap, the partial spherical projections providing a mechanism for indexing the supports in one or both of a retained and deployed position. In other implementations, one or more longitudinally extending recesses disposed on the exterior perimetric face of the cap above one or more exterior cap recesses are configured to receive an interior portion of one or more supports, releasably indexing the supports in a deployed position. In other implementations, a recess disposed in the exterior perimetric face of the cap and extending radially inward is configured to receive and engage an interior portion of one or more supports, releasably indexing the supports in a retained position. In other implementations, one or more supports is attached to the cap via one or more fasteners (e.g., see FIGS. **18B-18C**). In other implementations, two supports are connected to the cap and each other via one or more fasteners (e.g., see FIGS. **17A-17C**). In other implementations, one continuous support arbor connects each distal end of one or more supports.

(174) As shown in FIGS. **4A-4H**, in various implementations, one or more projections (e.g., projections **4024**, **4026**) are disposed in the exterior of the cap **4018** at opposite ends and configured to limit the movement of one or more supports (e.g., supports **4020**, **4022**) by at least one degree of freedom. The projections **4024**, **4026** may limit extension of one or more supports **4020**, **4022** away from the accessory **4010** at a predetermined angle, as shown in FIGS. **1-2**. In some implementations, the projections **4024**, **4026** include one or more features configured to limit the movement of one or more supports **4020**, **4022** by a second degree of freedom. A pair of projection openings (e.g., see openings **4064** in FIG. **4D**) may be disposed in one or more sides of one or more projections **4024**, **4026** and configured to receive a portion of the distal ends of one or more supports **4020**, **4022**, the projections restricting lateral movement of the supports away from



the accessory **4010**. One or more projections may be permanently or detachably attached to the cap **4018** (e.g., see projections **18024**, **18026** in FIG. **18A**). In some implementations, one or more supports may be detachably attached to one or more projections via fasteners, (e.g., see projections **18024**, **18026** and supports **18020**, **18022** in FIGS. **18E-18F**).

(175) In some implementations, one or more projections **4024**, **4026** may be arc-shaped or T-shaped and have a substantially rounded or tapered exterior profile. In some implementations, the projections **4024**, **4026** have an exterior profile generally matching the exterior profile of one or more supports (e.g., supports **4020**, **4022**). In other implementations, one or more projections have a shape or profile that is substantially square, rectangular, circular, triangular, or trapezoidal.

(176) As shown in FIGS. **4D-4E**, the projections **4024**, **4026** may include one or more proud or recessed partial spherical projection detents **4060** disposed on an interior faces thereof and configured to engage with a corresponding proud or recessed support detent **4062** disposed on an exterior face of a distal end of one or more supports (e.g., supports **4020**, **4022**). The projection detents **4060** and support detents **4062** may be configured for keeping one or more support arbors **4068** centrally aligned in one or more exterior cap recesses **4058**. In some implementations, a portion of one or more support arbors extends laterally outward from an exterior face of the distal ends of one or more supports and may be received and engaged in one or more recesses disposed in a bottom interior face of one or more projections.

(177) As shown in FIGS. **4A-4E**, one or more retaining protrusions **4066** extending radially outward from the exterior perimeter of the cap **4018** may be configured to selectively engage and retain one or more supports (e.g., supports **4020**, **4022**) in a retracted position. The retaining protrusions **4066** may be permanently or detachably attached to the cap **4018**. In some implementations, one or more retaining protrusions may be attached to the cap **4018** via one or more fasteners. One or more retaining protrusions **4066** may be substantially annular or arc-shaped. One or more retaining protrusions **4066** may have a rounded or tapered profile. The protrusions **4066** may provide a snap feature by which an interior portion of the supports **4020**, **4022** may be engaged and the supports retained in a retracted position until they are selectively disengaged from the retaining protrusions **4066** by the user. In other implementations, one or more retaining protrusions **4066** are configured to engage with one or more recesses disposed in the interior face of one or more supports.

(178) One or more components of the accessory **4010** such as the base **4016**, cap **4018**, plug **4028**, supports **4020**, **4022**, and projections **4024**, **4026**, may be constructed of a thermoplastic such as nylon or polypropylene, but other plastics such as PETG, ABS, Polyethylene, Polycarbonate, TPU, TPE, or some combination of one or more plastics or formable materials may also be used. In other implementations, one or more components of the accessory **4010** may be constructed of wood, metal, fiberglass, carbon fiber, Kevlar, composite materials, or from some combination of different materials. One or more components of the accessory **4010** may be made by injection molding, rotational molding, thermoforming, extruding, casting, machining, and additive or subtractive manufacturing such as 3d printing. In some implementations where the accessory includes one or more flexible supports, the supports may be made of silicone, rubber, synthetic fabric, nylon, polyester, leather, a composite fabric, or from some combination thereof.

(179) FIG. **5A** is top perspective projected view illustrating a base **5016**, an annular-shaped attachment interface **5042** and a protective cover **5070**. FIG. **5B** is a top perspective view illustrating a disc-shaped attachment interface **5042** with a protective interior portion. FIG. **5C** is a top perspective view illustrating a base **5016** attached to an annular-shaped attachment interface **5042** with a protective interior portion. FIG. **5D** is a top perspective view illustrating a disc-shaped intermediate mounting pad **5072**. FIG. **5E** is a top perspective projected view illustrating a base **5016** attached to an intermediate mounting pad **5072** affixed to an exterior surface of a mobile device case **5073**, with two supports **5020** and **5022** disposed in a cap **5018** axially aligned with and attachable to the base **5016**.

(180) Referring to FIGS. 5A-5E, in various implementations, an attachment interface **5042** is configured for permanently or detachably attaching one or both of a base **5016** and a cap **5018** to one of a housing, case **5073**, and cover for a mobile device (e.g., see mobile device **6012** in FIG. 6A). The attachment interface **5042** may be permanently or detachably attached to or disposed in or on a surface of one of the base **5016**, the cap **5018**, and the mobile device housing, case **5073**, or cover thereof. In some implementations, the attachment interface **5042** includes one or more attachment elements, such as a single or double-sided adhesive layer, film, liquid, sticky gel, or nano-suction pad, or hook-and-loop fastener. The top and bottom of the attachment interface **5042** may have different mechanisms for attachment disposed thereon. The attachment interface **5042** may be pliable, or configured with a pliable substrate, such as a thin foam layer, enabling the attachment interface **5042** to conform to one or more curvatures in the surface of the mobile device, housing, case **5073**, or cover thereof. In some implementations, the attachment interface **5042** is magnetic and/or includes one or more magnetic attachment elements attached to or disposed in or on a surface thereof and is configured to attach to one or more ferrous or magnetic attachment elements attached to or disposed in or on a surface of one or more of the cap **5018**, the base **5016**, the intermediate mounting pad (e.g., see **5072** in FIG. 5D), a plug, and the mobile device housing, case **5073**, and cover thereof, as shown in FIGS. 20F-20H. In some implementations, the attachment interface **5042** includes two or more attachment elements of the same or different type, such as a ferrous ring disposed between two layers of adhesive, or a polyurethane sticky gel pad disposed on the bottom of a magnetic disc, or a magnetic ring disposed between a hook-and-loop-fastener and an adhesive layer. In other implementations, two attachment elements may be configured to attach to one another, such as when one attachment element is attached to the bottom of one of the base **5016** and the cap **5018** and another attachment element is attached to the surface of the mobile device housing, case **5073**, or cover thereof. In some implementations, the attachment interface **5042** includes one or more elements made of plastic, metal, magnets, carbon fiber, PTFE, Teflon, Kevlar, wood, or other composite material. In other implementations, a low friction washer, spacer, or element is attached to or disposed in or on one of the attachment interface **5042**, the base **5016**, and the cap **5018** to reduce friction between one or more components. In other implementations, a bearing type attachment element may be disposed in or attached to one of the attachment interface **5042**, base **5016**, and cap **5018** to facilitate continuous rotation between one or more components, as shown in FIGS. 20D-20E.

(181) In various implementations, the attachment interface **5042** is attached to and substantially disposed in or on the bottom of the base **5016**. In some implementations, the attachment interface **5042** is partially or substantially disposed in a first exterior base recess (e.g., see recess **4040** in FIG. 4C) formed in the bottom of the base **5016**. In other implementations, the attachment interface **5042** is embedded in or partially or substantially disposed in a surface of the mobile device housing, case **5073**, or cover thereof. The attachment interface **5042** may have a profile generally conforming to the profile of the mobile device housing, case **5073**, or cover thereof. The attachment interface **5042** may be annular, circular, or have a shape generally conforming to one of the base **5016**, cap **5018**, and supports **5020**, **5022**. An aperture **5030** may be formed in the center of the attachment interface **5042**, generally corresponding to an aperture **5030** formed in one of the base **5016** and the cap **5018**, and may be relatively larger or smaller in diameter. A protective film, backing, or cover **5070** detachably attached to an exterior surface of the attachment interface **5042**, may protect the attachment interface **5042** from unwanted adhesion or attachment prior to user installation. The protective cover **5070** may have an interior and exterior perimeter generally matching an interior and exterior perimeter of the attachment interface **5042** and may include a tabbed portion configured to be grasped between a user's finger and thumb in order to facilitate its removal from the attachment interface **5042**, as shown in FIG. 5A.

(182) As shown in FIGS. 5B-5C, in some implementations, the attachment interface **5042** has an interior portion extending radially inward beyond the interior perimeter of the base **5016** and

configured to protect the surface of one of the mobile device housing, case **5073**, or cover thereof from contact with one or both of a first annular cap protrusion and first cap engagement feature (e.g., see cap protrusion **4044** and cap engagement feature **4046** in FIG. 4C). One or more portions of the attachment interface **5042** may have a mirrored, reflective, or glow-in-the-dark surface. Indicia, such as a name, logo, slogan, trademark, or service mark representing one or more of a business, product, or person may be disposed on, across, or around one or more surfaces of the attachment interface **5042**, as shown in FIGS. 5B-5C.

(183) As shown in FIGS. 5D-5E, in some implementations, an intermediate mounting pad (e.g., mounting pad **5072**) is attached to a surface of the mobile device housing, case **5073**, or cover thereof. In some implementations, the intermediate mounting pad **5072** is disposed between the attachment interface and the mobile device housing, case **5073**, or cover thereof, the mounting pad **5072** configured to provide an improved attachment between the attachment interface **5042** and the mobile device housing, case **5073**, or cover thereof. The intermediate mounting pad **5072** may be annular, circular, or have a shape generally matching the shape of either the base **5016** and/or a surface of the mobile device, housing, case **5073**, or cover thereof upon which the base **5016** may be attached. The intermediate mounting pad **5072** may have a profile generally conforming to the profile of a surface of the mobile device housing, case **5073**, or cover thereof. In some implementations, an aperture may be disposed in the center of the intermediate mounting pad **5072** and may extend therethrough.

(184) The intermediate mounting pad **5072** may have a top surface configured for optimizing attachment to the attachment interface **5042** and a bottom surface configured for optimizing attachment to the mobile device, housing, case **5073**, or cover thereof, the bottom of the intermediate mounting pad **5072** configured with an adhesive formulated for bonding to adhesion-resistant material surfaces such as those containing silicone, textured surfaces, or surfaces coated with an oleophobic coating. In some implementations, the intermediate mounting pad **5072** may be pliable, or configured with a pliable substrate, such as a thin foam layer, enabling the intermediate mounting pad **5072** to conform to one or more curvatures in the surface of the mobile device, housing, case **5073**, or cover thereof. In other implementations, the intermediate mounting pad **5072** is magnetic or includes one or more attachment elements attached to or disposed in a surface thereof. One or more portions of the intermediate mounting pad **5072** may have a mirrored, reflective, or glow-in-the-dark surface. In some implementations, the intermediate mounting pad **5072** includes a low-friction layer or coating disposed on the top surface thereof. In other implementations, the intermediate mounting pad **5072** includes a thermal insulating layer disposed on a top or bottom surface thereof. Indicia such as a name, logo, slogan, trademark, or service mark representing one or more of a business, product, or person may be disposed on, across, or around one or more surfaces of the mounting pad **5072** as shown in FIGS. 5D-5E.

(185) FIG. 6A is a top exploded perspective view illustrating the example accessory **6010** attached to an exterior surface of a mobile device **6012** and a plug removal feature **6074** disposed in the center of the accessory **6010**. FIG. 6B is a top perspective view illustrating a plug **6028** configured with a flexible plug removal feature **6074**. FIG. 6C is a top perspective view illustrating a plug **6028** configured with a rigid plug removal feature **6074**. FIG. 6D is a top perspective view illustrating an example accessory **6010** attached to an exterior surface of a mobile device **6012** and a flexible plug removal feature **6074** retained between a cap **6018** and a support **6022**.

(186) Referring to FIGS. 6A-6D, in various implementations, the accessory **6010** includes one or more plugs (e.g., plug **6028**). The plug **6028** may be permanently or detachably attached to one or more components of the accessory **6010** and/or to a mobile device **6012** housing, case, or cover thereof. In various implementations, the plug **6028** augments the utility, functionality, and ornamentation of the accessory **6010**.

(187) In some implementations, the plug **6028** is used to attach different accessories or tools to the accessory **6010**. In other implementations, the plug **6028** is used to mount the accessory **6010** to

one or both of a mount (not shown, e.g., see **7092** in FIG. 7B), and a mounting structure (not shown, e.g., see **7094** in FIG. 7B).

(188) In various implementations, the plug **6028** has a shape generally conforming to an aperture **6030** disposed in the center of the accessory **6010** and an exterior profile generally matching an interior profile of the accessory **6010**. In some implementations, the plug **6028** has an exterior profile that is substantially circular. The plug **6028** may be disc-shaped or ring-shaped. In other implementations, the plug has an exterior profile that is triangular, square, rectangular, or polygonal. One or more apertures or recesses may be formed in the plug **6028** and may extend therethrough, (e.g., see plugs **14028** in FIGS. 14B-14C). In some implementations, the plug **6028** is magnetic or includes one or more attachment elements disposed therein or on a surface thereof. In other implementations, the plug is substantially thin and flat. In some implementations, the top surface of the plug **6028** is substantially co-planar with the top surface of a cap **6018** when the plug **6028** is attached to the accessory **6010**. In other implementations, the top surface of the attached plug is recessed or proud with respect to the top of the cap **6018**. In other implementations, the top of the plug is rounded. In other implementations, a portion of the top of the plug extends over a portion of the top of the cap **6018**. In other implementations, a portion of the plug is configured for engagement with the first annular cap protrusion (e.g., see protrusion **4044** in FIG. 4C). In other implementations, one or more parts of the plug is extendable, collapsible, rotatable, or reversible (e.g., see FIGS. 12D-12E and 12G).

(189) The plug **6028** may be permanently or detachably attached to one or more of an intermediate mounting pad **6072**, an attachment interface (e.g., see **5042** in FIGS. 5A-5C), a base **6016**, the cap **6018**, and a mobile device **6012** housing, case, or cover thereof. The plug **6028** may be attached to the cap **6018** from a top or bottom side of the accessory **6010** and may be attached prior to or after attaching the base **6016** to the mobile device **6012** and/or attaching the cap **6018** to the base **6016**. The plug **6028** may be detachably attached to one or both of the base **6016** and the cap **6018** and retained therein by a friction fit or interference fit. In some implementations, one or more recesses or projections disposed in the interior perimetric face of one of the base **6016** and the cap **6018** are configured for engaging one or more corresponding recesses or protrusions disposed in the exterior perimetric face of the plug **6028** whereby the plug **6028** may be securely attached to the accessory **6010** and/or prevented from rotating independently from one of the base **6016** and the cap **6018**. In some implementations, the plug **6028** is configured for attachment to another plug. In other implementations, the plug **6028** is configured to attach to an accessory cover (e.g., see cover **11130** in FIG. 11G). In other implementations, the plug includes an adjustment mechanism by which the diameter of the plug may be increased or decreased in order to adjust the fit of the plug within one or more components of the accessory, such as the base **6016**, cap **6018**.

(190) As shown in FIGS. 6A-6D, the accessory **6010** may include a plug removal feature **6074** for detaching one or more plugs **6028** from the accessory **6010**. The plug removal feature **6074** may be substantially rigid or substantially flexible. The plug removal feature **6074** may be in the general form of a strap, loop, band, ribbon, or cord. In some implementations, the plug removal feature **6074** is integrally formed in one of the intermediate mounting pad **6072**, the attachment interface, the base **6016**, the cap **6018**, plug **6028**, and the mobile **6012** device housing, case, or cover thereof. In other implementations, the plug removal feature **6074** is permanently or detachably attached to a surface of one of the intermediary mounting pad **6072**, the attachment interface, the base **6016**, the cap **6018**, the plug **6028**, and the mobile device **6012** housing, case, or cover thereof by welding or an adhesive. In other implementations, one end of the plug removal feature **6074** is fixed in a recess formed in a bottom portion of one of the intermediate mounting pad **6072**, the attachment interface, the base **6016**, the cap **6018**, and the mobile device **6012** housing, case, or cover thereof, and the other unfixed end of the plug removal feature **6074** passes through a slot formed in the component and extends back across the top surface thereof. In some implementations, one or both of the top and bottom of the plug removal feature **6074** is

substantially co-planar with one or both of the top and bottom of one or more of the intermediate mounting pad **6072**, the attachment interface, the base **6016**, the cap **6018**, the plug **6028**, and the mobile device **6012** housing, case, or cover thereof.

(191) In some implementations, the plug removal feature **6074** is substantially thin, flat and rectangular. In other implementations, the plug removal feature has a profile generally conforming to the interior perimeter of one of the base **6016** and the cap **6018**. In some implementations, the plug removal feature **6074** includes a flexible portion configured to extend over the top of the cap **6018**. In other implementations, a recess formed in the interior perimetric face of one of the base, the cap, and an accessory cover (e.g., see cover **11130** in FIG. **11G**) is configured for receiving a portion of the plug removal feature **6074**.

(192) As shown in FIG. **6A**, the plug removal feature **6074** may be disposed in the center of the accessory **6010** and may extend over a portion of the cap **6018**. In other implementations, the plug removal feature **6074** is flexible and disposed in an exterior surface of the plug **6028**, a recess formed in an exterior surface of the plug **6028**, or in one or more slots formed in the plug **6028**, as shown in FIG. **6B**. In other implementations, the plug removal feature is embedded or insert-molded in the plug **6028**. In some implementations, the plug removal feature **6074** is a rigid projection extending outward laterally and/or longitudinally from an exterior surface of the plug **6028**, as shown in FIG. **6C**. In other implementations, the plug removal feature is an undercut formed in the top surface or outer perimetric face of the plug **6028**. In some implementations, the plug removal feature **6074** extends over the top of the cap **6018** and under one or more supports **6020**, **6022** and may be retained therebetween, as shown in FIG. **6D**. In other implementations, the plug removal feature is a torsional or cantilevered snap disposed in the interior perimeter of the accessory **6010** and configured to engage a portion of or engagement feature disposed on the exterior perimeter of the plug **6028**. In other implementations, the plug removal feature is a torsional or cantilevered snap disposed in the exterior perimeter of the plug **6028** and configured to engage a portion of or engagement feature disposed in the interior perimeter of the accessory **6010**. In other implementations, the plug removal feature includes a mechanism such as a wedge-shaped ejector release structure disposed beneath the plug **6028** and connected to a spring assisted push button operator disposed on an exterior of the accessory **6010**.

(193) FIG. **7A** is a top exploded perspective view illustrating the example accessory **7010** configured with multiple attachment features **7076**, **7078**, **7080** and multiple attachment elements **7084**, **7086**, **7088**. FIG. **7B** is a side projected view illustrating a mobile device **7012** and affixed example accessory **7010** detachably attachable to a mount **7092** and a mounting structure **7094**, the mount **7092** including an attachment feature **7082** and attachment element **7090**, and the mounting structure **7094** including two accessory engagement features **7096**, with the mobile device **7012** rotatably positioned to attach in a portrait orientation. FIG. **7C** is a side view illustrating a mobile device **7012** and affixed example accessory **7010** attached to a mounting structure **7094** configured with a hook-shaped accessory engagement feature **7096** whereto the accessory **7010** is attached by a support **7020** and the mobile device **7012** is rotatably positioned in a landscape orientation.

(194) As illustrated in FIGS. **7A-7B**, the accessory **7010** may include one or more permanently or detachably attached attachment features (e.g., **7076**, **7078**, **7080**, **7082**) for attaching various components of the accessory **7010** together and/or for attaching the accessory **7010** to another object, such as a mount **7092** or mounting structure **7094**. One or more attachment features (e.g., **7076**, **7078**, **7080**, **7082**) may be disposed in or attached to or disposed in or on an exterior or interior perimeter or surface of one or more of an intermediate mounting pad (e.g., see mounting pad **5072** in FIG. **5D**), an attachment interface (e.g., see attachment interface **5042** in FIG. **5A**), a base **7016**, a cap **7018**, an accessory cover (e.g., see feature **11076** in cover **11130** of FIG. **11F**), a mobile device **7012** housing, case, or cover thereof, a plug **7028**, and a mount **7092**, as shown in FIGS. **7A-7B**. The attachment features (e.g., **7076**, **7078**, **7080**, **7082**) may be proud or recessed with respect to the surface in which they are disposed (e.g., see attachment feature **7082** in FIG.

7B). One or more attachment features (e.g., **7076, 7078, 7080, 7082**) may be separately formed from or substantially integrated into one or more components of the accessory **7010**.

(195) In some implementations, the attachment features (e.g., **7076, 7078, 7080, 7082**) comprise an annular, torsional, or cantilevered snap. The attachment features (e.g., **7076, 7078, 7080, 7082**) may be continuous or segmented. The attachment features (e.g., **7076, 7078, 7080, 7082**) may include one or more openings or recesses configured for receiving a portion of another attachment feature or a plug removal feature (e.g., see feature **6074** in FIG. 6B), as shown in FIG. 7A. The attachment features (e.g., **7076, 7078, 7080, 7082**) may include one or more detents configured to limit the movement of one or more other attachment features. The attachment features (e.g., **7076, 7078, 7080, 7082**) may be configured to laterally or longitudinally constrain one or more other attachment features. In other implementations, the attachment features (e.g., **7076, 7078, 7080, 7082**) comprise one or more fasteners, such as a ball-and-socket snap, a twist lock, a key slot, a slide lock, a spring clip, a hook, a suction cup, or threaded fasteners, and may operate by friction fit, interference fit, snap fit, suction, rotation, or other mechanical advantage.

(196) One or more attachment features (e.g., **7076, 7078, 7080, 7082**) may be configured for attachment to one or more other attachment features. For example, a first attachment feature **7076** may be configured for attachment to one or more of a second, third, and fourth attachment feature **7078, 7080, 7082**. The second attachment feature **7078** may be configured for attachment to one or more of the first, third, and fourth attachment features **7076, 7080, 7082**. The third attachment feature **7080** may be configured for attachment to one or more of the first, second, and fourth attachment features **7076, 7078, 7082**. The fourth attachment feature **7082** may be configured for attachment to one or more of the first, second, and third attachment features **7076, 7078, 7080**.

(197) In various implementations, the accessory **7010** further includes one or more permanently or detachably attached attachment elements (e.g., **7084, 7086, 7088 7090**) for attaching various components of the accessory **7010** together and/or for attaching the accessory **7010** to another object. One or more attachment elements (e.g., **7084, 7086, 7088 7090**) may include one or more attachment features (e.g., **7076, 7078, 7080, 7082**). One or more attachment elements (e.g., **7084, 7086, 7088 7090**) may be attached to or disposed in or on an interior or exterior perimeter or surface of one or more of the intermediate mounting pad, the attachment interface, the base **7016**, the cap **7018**, the accessory cover, a mobile device **7012** housing, case, or cover thereof, the plug **7028**, and the mount **7092**, as shown in FIGS. 7A-7B.

(198) One or more attachment elements (e.g., **7084, 7086, 7088 7090**) may be magnetic. One or more surfaces of one or more attachment elements (e.g., **7084, 7086, 7088 7090**) may be configured with a single or double-sided fastener, such as an adhesive tape, reusable adhesive, sticky gel pad, nano-suction pad, two-part interlocking fastener, or hook-and-loop fastener. In some implementations, one or more attachment elements (e.g., **7084, 7086, 7088 7090**) are embedded in or substantially integrated in one of the intermediate mounting pad, the attachment interface, the base **7016**, the cap **7018**, the accessory cover, the mobile device **7012** housing, case, or cover thereof, the plug **7028**, and the mount **7092**.

(199) The attachment elements (e.g., **7084, 7086, 7088 7090**) may be substantially rigid or substantially flexible. The attachment elements (e.g., **7084, 7086, 7088 7090**) may have an annular, circular, triangular, square, rectangular, or polygonal shape and may be in the general form of a disc, ring, cap, or flanged insert. One or more attachment elements (e.g., **7084, 7086, 7088 7090**) may have a shape or profile generally matching the shape or profile of one or more of the intermediate mounting pad, the attachment interface, the base **7016**, the cap **7018**, the accessory cover, the plug **7028**, or the mount **7092**. In other implementations, one or more attachment elements (e.g., **7084, 7086, 7088 7090**) has a profile generally matching an interior or exterior profile of one or more attachment features (e.g., **7076, 7078, 7080, 7082**).

(200) One or more attachment elements (e.g., **7084, 7086, 7088 7090**) may be configured for attachment to one or more other attachment elements. For example, a first attachment element **7084**

may be configured for attachment to one or more of a second, third, and fourth attachment element **7086, 7088, 7090**. The second attachment element **7086** may be configured for attachment to one or more of the first, third, and fourth attachment elements **7084, 7088, 7090**. The third attachment element **7088** may be configured for attachment to one or more of the first, second, and fourth attachment elements **7084, 7086, 7090**. The fourth attachment element **7090** may be configured for attachment to one or more of the first, second, and third attachment elements **7084, 7086, 7088**. In some implementations, multiple attachment elements (e.g., **7084, 7086, 7088 7090**) are disposed in one or more components of the accessory **7010**, such as the cap **7018** (e.g., see FIGS. **20A-20B**). (201) In some implementations, one or more attachment features (e.g., **7076, 7078, 7080, 7082**) are configured for engaging and retaining one or more attachment elements (e.g., elements **7084, 7086, 7088, 7090**). A portion of one or more attachment features (e.g., **7076, 7078, 7080, 7082**) may be configured to engage with and constrain the movement one or more attachment elements (e.g., **7084, 7086, 7088 7090**) by at least one degree of freedom. One or more attachment elements (e.g., **7084, 7086, 7088 7090**) may be permanently or detachably attached to one or more components of the accessory **7010** by magnets, friction fit, compression fit, interference fit, snap fit, rotational engagement, twist lock, slide lock, threaded fasteners, two-part interlocking fasteners, hook-and-loop fasteners, suction, or adhesive. In some implementations, one or more attachment features (e.g., **7076, 7078, 7080, 7082**) and attachment elements (e.g., **7084, 7086, 7088 7090**) include an opening or recess configured to receive a portion of a plug removal feature (e.g., see **6074** in FIGS. **6A-6D**). In other implementations, indicia such as a name, logo, slogan, trademark, or service mark representing one or more of a business, product, or person may be disposed on, across, or around one or more surfaces of one or more attachment elements **7084, 7086, 7088, 7090**.

(202) As illustrated in FIGS. **7B-7C**, the accessory **7010** is used for attaching the mobile device **7012** to one or both of the mount **7092** and mounting structure **7094**. The mount **7092** may be permanently or detachably attached to the mounting structure **7094**. The mount **7092** may be attached to the mounting structure **7094** by magnets, friction fit, compression fit, interference fit, snap fit, rotational engagement, twist lock, slide lock, threaded fasteners, two-part interlocking fasteners, hook-and-loop fasteners, suction, or adhesive. In some implementations, the mount **7092** swivels or rotates in one or more directions with respect to the mounting structure **7094**. In other implementations, the mount **7092** is extendable or retractable with respect to the mounting structure **7094**. In other implementations, the mount **7092** is repositionable or slidable with respect to the mounting structure **7094**. In some implementations, one or more accessory engagement features **7096** are disposed in one or both of the mount **7092** and mounting structure **7094** and configured to engage with one or more of the cap **7018**, projections **7024, 7026**, and supports **7020, 7022**, as shown in FIGS. **7B-7C**.

(203) The accessory **7010** may detachably attach to one or both of the mount **7092** and mounting structure **7094** by magnets, friction fit, compression fit, interference fit, snap fit, rotational engagement, twist lock, slide lock, threaded fasteners, two-part interlocking fasteners, hook-and-loop fasteners, suction, or adhesive. In some implementations, one or more plugs **7028** configured for attachment to the accessory **7010** may be attached to the mounting structure **7094** and may function as the mount **7092**. In some implementations, one or more plugs **7028** include more than one type of attachment feature and/or attachment element, enabling the user to selectively attach one or both of the plug **7028** and the accessory **7010** to different types of mounting structures **7094** (e.g., see FIGS. **12A-12F**).

(204) As illustrated in FIG. **7C**, in some implementations, one or more accessory engagement features **7096** disposed in one or both of the mount **7092** and mounting structure **7094** are configured for engaging one or more supports **7020, 7022**. In some implementations, one or more engagement features **7096** disposed in the mounting structure **7094** are hook-shaped or include a clip or recess with a profile generally matching the profile of one or more supports **7020, 7022**, as shown in FIG. **7C**. In other implementations, the accessory **7010** is attached to one or both of the

mount **7092** and mounting structure **7094** by one or more attachment features (e.g., **7076**, **7078**, **7080** **7082**) and/or attachment elements (e.g., **7084**, **7086**, **7088**, **7090**). In other implementations, one or more supports **7020**, **7022** may be engaged in one or more accessory engagement features **7096** disposed in one of mount **7092** and mounting structure **7094**. In some implementations, a low friction washer or spacer is disposed between the mount **7092** and mounting structure **7094** to reduce friction between the two. In other implementations, a bearing, such as a race, roller, ultra thin, and ball bearing is disposed in between the mount **7092** and mounting structure **7094** to facilitate continuous rotation between the two.

(205) FIG. **8A** is a top view illustrating an example accessory **8010** affixed to an exterior surface of a mobile device **8012** with a first and second finger of a user's hand **8014** placed inside the aperture **8030** and engaged with an interior perimetric face **8032** of a cap **8018**, and a third finger of a user's hand **8014** engaged with the exterior perimetric face of a support **8022**. FIG. **8B** is a top view illustrating an example accessory **8010** affixed to an exterior surface of a mobile device **8012** with a first finger of a user's hand **8014** inserted through and engaged with a support **8020**, a second finger of a user's hand **8014** engaged with an exterior perimetric face of a support **8022**, and a third finger of a user's hand **8014** engaged with an exterior perimetric face **8050** of a cap **8018**. FIG. **8C** is a top view illustrating an example accessory **8010** affixed to an exterior surface of a mobile device **8012** with a first and second finger of a user's hand **8014** inserted through and engaged with supports **8020**, **8022** and partially disposed on a top surface of a cap **8018**, the first finger further engaged with an interior perimetric face **8032** of the cap **8018** and the second finger further engaged with an exterior perimetric face **8050** of the cap **8018**. FIG. **8D** is a top view illustrating an example accessory **8010** affixed to an exterior surface of a mobile device **8012** with a first and second finger of a user's hand **8014** inserted through and engaged with supports **8020**, **8022** and partially disposed on a top surface of a cap **8018**, the first finger further engaged with an interior perimetric face **8032** of the cap **8018** and the second finger further engaged with an exterior perimetric face **8050** of the cap **8018**, the user's thumb disposed on an exterior side of the mobile device **8012** and used to rotate the mobile device **8012** and affixed base **8016** with respect to the cap **8018** and supports **8020**, **8022** which are held in a fixed position by the first and second fingers of the user's hand **8014**.

(206) As shown in FIGS. **8A-8D**, in various implementations, one or more components of the accessory **8010** such as a base **8016**, a cap **8018**, a plug, and one or more supports **8020**, **8022** provide a mechanism for engaging one or more fingers of a user's hand **8014**, a mount, a mounting structure, and an accessory engagement feature (e.g., see FIG. **7B**). One or more supports **8020**, **8022** may be extended, retracted, and rotated to accommodate a variety of user preferences, interactive modalities, and use-case scenarios. Various components of the accessory **8010** are configured to work in conjunction to provide the user with an improved mechanism for mounting, holding, manipulating, and interacting with a mobile device **8012**, as further detailed in the example operations of FIG. **10**.

(207) FIG. **9A** is a right side view illustrating an example accessory **9010** affixed to an exterior surface of a mobile device **9012** with a front edge of the mobile device **9012** disposed on a support surface (for example, a table) and a first support **9020** of the accessory **9010** extended and disposed on the support surface to position the mobile device **9012** in a first portrait orientation. FIG. **9B** is a left side view illustrating an example accessory **9010** affixed to an exterior surface of the mobile device **9012** with a back edge of the mobile device **9012** disposed on a support surface and a first and second support **9020**, **9022** (second support **9022** hidden from view) of the accessory **9010** extended and disposed on the support surface to position the mobile device **9012** in a second portrait orientation. FIG. **9C** is a bottom perspective view illustrating an example accessory **9010** affixed to an exterior surface of a mobile device **9012** with the front edge of the mobile device **9012** positioned on a support surface and a first and second support **9020**, **9022** of the accessory **9010** extended and disposed on the support surface to position the mobile device **9012** in a first



portrait orientation. FIG. 9D is a top perspective view illustrating an example accessory **9010** affixed to an exterior surface of a mobile device **9012** positioned on a support surface with a first support **9020** extended and positioned to support the mobile device **9012** in a first landscape orientation. FIG. 9E is a top perspective view illustrating an example accessory **9010** affixed to an exterior surface of a mobile device **9012** and positioned on a support surface with a first and second support **9020**, **9022** extended and positioned to support the mobile device **9012** in a second landscape orientation.

(208) One or more supports **9020**, **9022** may be extended and disposed on a substantially flat support surface to position a mobile device **9102** in one or more display orientations to optimize one or both of a user's viewing angle and interaction with the mobile device **9012**. The supports **9020**, **9022** may be rotated around an axis of rotation (e.g., see **3034** in FIG. 3) in conjunction with one of a cap **9018** and a base **9016** in order to change or adjust the display orientation of the mobile device **9012**. Furthermore, different portions of one or more supports **9020**, **9022** may be disposed on the support surface in order to achieve different display orientations.

(209) FIG. 10 illustrates example operations **10100** for using an adaptive support accessory. The example operations are, in part, supported by the illustrations of FIGS. 7A-9E. The example accessory **10100** accommodates a wide range of different interactive modalities and, therefore, a variety of different possible example operations. A description of common sequentially linked interactive modalities will be set forth along with descriptions of some other optional modalities, which together provide a non-exhaustive representation of some example operations for using the accessory **10100**. The operations making up the embodiments of the invention described herein may be performed in any order, adding or omitting operations as desired, unless explicitly claimed otherwise or a specific order is inherently necessitated by the claim language.

(210) In a first example attaching operation **10102**, a user attaches a base to a surface of a mobile device housing, case, or cover thereof via a removable attachment interface. If the attachment interface includes an adhesive covered by a protective cover, the user may first remove the protective adhesive cover before attaching the base and attachment interface to the mobile device. In some implementations, such as if one or more surfaces of the mobile device is not suitable for attachment by the attachment interface, the user may attach an intermediate mounting pad to the mobile device prior to attaching the attachment interface and base. In other implementations where the base is pre-disposed or substantially incorporated in one of the mobile device case or cover thereof, a user may attach one of the case and cover to the mobile device.

(211) In a second example attaching operation **10104**, a cap with one or more supports attached thereto is attached to the base. The cap is axially aligned with and positioned over the base. The cap and base are then pressed together until one or more cap engagement features are engaged with one or more corresponding base engagement features, rotatably coupling the cap and one or more attached supports to the base. In some implementations the cap may be attached to the base prior to attaching one or more attachable supports to the cap. In other implementations, one or more supports may be attached to the accessory by inserting one end of the support into an opening formed in the base and then securing it to the accessory by inserting a plug into an aperture formed in the center of the accessory.

(212) Once the cap is rotatably coupled to the base, the user may decide to further adapt the accessory. In a third example attaching operation **10116**, the user may attach one or more plugs and/or attachment elements to the accessory, as illustrated in FIG. 7A. One or more components of the accessory may be configured with one or more attachment features or attachment elements, as shown in FIG. 7A. In some cases, the plug provides an additional feature or function to the accessory. For example, the plug may include one or more tools or everyday carry items the user might normally carry in their pocket separately from their mobile device, as shown in FIGS. 13A-13D. In other cases, the plug may be configured with one or more attachment features or attachment elements for attaching one or both of the plug and the accessory to another object, as

shown in FIGS. 12A-12I. For example, the plug may be configured with a twist lock attachment feature for attaching the accessory to a correspondingly configured twist lock mount. In some cases, the attached plug may provide both an additional feature or function for attaching the accessory to another object. For example, the plug may be a container configured with one or more magnetic attachment elements disposed therein and configured for attachment to a magnetic mounting structure. One or more indicators disposed on an exterior surface of one of the cap, the base, the plug, and one or more supports may visually or tactilely aid the user in orienting the plug to a position in which it may be most easily or optimally attached to the accessory, as shown in FIG. 12C. In other examples, an accessory cover may be attached to one of the cap and the base prior to or in lieu of attaching the plug and may provide for adapting one of the cap and the base to receive and/or engage the plug, as shown in FIGS. 11E-11G. Like the plug, the accessory cover may include one or more attachment features or attachment elements configured for attaching to or engaging with another attachment feature or attachment element disposed in one or more other accessory components, mount, or mounting structure.

(213) There are a variety of scenarios in which a user may decide to use the accessory to attach the mobile device to another object. In a fourth example attaching operation **10118**, the user may attach one or more of the cap, the base, and the plug to one or both of a compatible mount and mounting structure, as illustrated in FIG. 7B. For example, in some scenarios where one or more of the base, the cap, and the plug include one or more magnetic attachment elements and/or are configured for magnetic attachment to the mount, the user may mount the accessory and the attached mobile device by simply aligning the center of the accessory with the center of the mount. In other example scenarios where an aperture is disposed in the center of the accessory, the user may simply align the aperture in the accessory with the center of the correspondingly shaped mount and presses the accessory and the attached mobile device onto the mount. Depending on the configuration of the mount, the accessory may attach to the mount by engagement between one or more attachment features disposed in the accessory and one or more other attachment features disposed in one or both of the mount and mounting structure. In other scenarios, the accessory may be attached to the mount and/or mounting structure by engagement between one or more attachment elements disposed in the accessory with one or more other attachment elements disposed in one or both of the mount and mounting structure.

(214) In some examples, one or more attachment features and attachment elements disposed in one of the intermediate mounting pad, the attachment interface, the base, the cap, the plug, and the mobile device housing, case, and cover thereof, may be selectively or rotatably engaged with one or more other attachment features and/or attachment elements disposed in one or both of the mount and the mounting structure. In some implementations, such as when the accessory is attached to one or both of the mount and the mounting structure by twist lock or correlated magnetic force (as may be imparted through one or more correlated magnets disposed in one or more components of the accessory and one or both of the mount and mounting structure), the user may selectively rotate one or more of the accessory, the mobile device, or the mount to disengage the accessory from the mount or the mounting structure. In other implementations, the user may rotate one or more of the accessory, the mobile device, or the mount in order to securely latch or engage one or more attachment features and/or attachment elements disposed in the mount with one or more attachment features and/or attachment elements disposed in the accessory. In other implementations, the user may attach the accessory to one of the mount and the mounting structure by aligning the accessory between one or more accessory engagement features disposed in one of the mount and the mounting structure and pressing the accessory into and/or between the accessory engagement features, as illustrated in FIG. 7B.

(215) There are a variety of examples in which the user may use the accessory to attach the mobile device to one or both of the mount and the mounting structure in order to enhance the usability of the mobile device. In one example, the mount and/or the mounting structure may be connected to a

dash of a vehicle, to which the user may attach the accessory and the mobile device, enabling the mobile device to be used as a navigational aid. In other examples, the mount and/or the mounting structure may be connected to the handlebars of a bicycle or a flexible band configured for attachment to a part of the user's body in order to provide more accessible navigational information or fitness tracking information to the user. In another example, the mount and/or the mounting structure may be configured with an inductive charger which may be incorporated into a display stand in order to charge a battery disposed in the mobile device and/or position the mobile device in a preferred display orientation.

(216) There are also a variety of situations in which the user may desire to improve their handling or operation of the mobile device. The accessory supports different types of user engagements and is adaptable to different situationally based user preferences. In some situations, such as when the user expects to interact with the mobile device for a brief period of time, the user may prefer a more expedient type of support engagement, without having to deploy one or more supports. In a fifth example engaging operation **10120**, a user may engage one or more fingers of a user's hand with one or both of an interior and exterior perimetric face of the accessory. For example, the user may place one or more fingers of the user's hand inside the aperture formed in the center of the accessory and against the interior perimetric face of one of the base and the cap. In another example, the user may position one finger of the user's hand adjacent to the exterior perimetric face of a first retained support and position another finger of the user's hand on an opposite side of the accessory adjacent to the exterior perimetric face of a second retained support, gripping the accessory between the first and second fingers. In another example, the user may engage one or more fingers of the user's hand with the interior perimetric face of one of the base and the cap and engage one or more other fingers with the exterior perimetric face of one or more retained supports, as illustrated in FIG. 8A.

(217) In other situations, such as when the user expects to interact with the mobile device for a longer period of time, the user may prefer a more secure type of support engagement with one or more extended supports, in which case the user may need to extend one or more of the supports prior to engagement. In a sixth example extending operation **10106**, the user may extend one or more supports from a retained position to a deployed position using one or more fingers of the user's hand. In an example single-handed extending operation, the user may deploy one or more supports using one or more fingers of the user's hand while holding the mobile device between the user's thumb and one or more other fingers of the user's hand. Alternatively, the user may hold the mobile device in one of the user's hands and use one or more fingers of the user's other hand to deploy one or more of the supports. In some example extending operations, such as where one or more rigid arc-shaped supports are connected to the cap and retained in a retracted position by engagement with one or more retaining protrusions disposed on the outer perimetric face of the cap, the user may place the tip of one or more fingers of the user's hand adjacent to the bottom exterior perimeter of one or more of the supports and apply inward or upward pressure against the supports in order to release them from a retained position before extending them to a deployed position. In some implementations, one or more features disposed on an exterior surface of the cap and/or one or more of the supports may visually or tactilely aid the user in orienting the accessory to a position in which one or more of the supports may be most easily or optimally deployed. In other implementations, the accessory may include a mechanism activated by either a push button or a pull tab by which one or more of the supports may be extended and/or retracted separately or simultaneously by the user.

(218) In some implementations, one or more of the supports may be extended beyond a predetermined angle defined by a portion of one or more projections laterally disposed on the exterior of the cap in order to cause one or more the supports and/or support arbors to be forcibly detached from the accessory. Thus, in some implementations, one or more of the supports may be interchangeable without requiring the user to detachably separate the cap from the base. In some

implementations, however, a user may also detach the cap from the base by extending one or more of the supports to a deployed position, engaging one or more fingers of the user's hand through one or more of the supports, and applying a pulling force against one or more of the supports in the direction away from the mobile device while simultaneously keeping the mobile device in a fixed position. In order to reattach the cap to the base, the user may axially align the cap over the base and apply downward pressure to the top of the cap until the first cap engagement feature fully engages with the first base engagement feature and the cap and base are rotatably coupled, as described in the first example attaching operation (e.g., see operation **10102**).

(219) In a seventh example rotating operation **10108**, the user may rotate the cap and/or one or more of the supports around the base. This rotation may aid the user in orienting one or more of the supports to an optimal position wherein one or more of the user's fingers may be most easily engaged with one or more of the extended supports. In other situations, one or more of the supports may need to be rotated prior to engaging the accessory with one or both of the mount and the mounting structure. In one example rotating operation, the user may rotate one or more of the extended supports to a particular position prior to engaging them with one or more accessory engagement features disposed in one of the mount and/or the mounting structure.

(220) In an eighth example attaching operation **10122**, a user may attach one or more of the cap, the base, the plug, and one or more of the extended supports to one or both of the mount and the mounting structure. In one example attaching operation, one or more of the extended supports may be engaged with one or more compatible engagement features disposed in one or both of the mount and the mounting structure, such as the hook-shaped accessory engagement feature shown in FIG. 7C. In some implementations, multiple components of the accessory may be simultaneously attached to one or both of the mount and the mounting structure. For example, the cap may be attached to the mount while one or more of the supports are simultaneously attached to one or more accessory engagement features disposed in the mounting structure.

(221) Once the accessory has been attached to one or both of the mount and/or the mounting structure, the user may desire to change the orientation of the mobile device with respect to one or both of the mount and/or the mounting structure. For example, the user might want to change the mobile device display orientation from portrait orientation to a landscape orientation. Thus, in a ninth example rotating operation **10124**, the user may rotate one or both of the base and the mobile device around the cap and/or one or more of the supports. In another example rotating operation, the user may rotate one or both of the mount and the mobile device in order to change the orientation of the mobile device.

(222) In addition to providing improved handling, operation, and mounting of the mobile device, the accessory may also be used to position the mobile device in a preferred orientation for hands-free use as illustrated in FIGS. 9A-9E. In a tenth positioning operation **10126**, the user may position one or more extended supports on a support surface to dispose the mobile device in a preferred orientation. For example, the user may want to position the mobile device in a portrait orientation on a desk in order to better interact with the mobile device's graphical user interface. In another example positioning operation, the user may want to position the mobile device on a table in a landscape orientation optimized for watching a video on the mobile device.

(223) To adjust the user's viewing angle with respect to the mobile device's display orientation, in an eleventh rotating operation **10128**, the user may rotate the cap and/or one or more of the supports around the base to change the display orientation of the mobile device. For example, a user may rotate one or more of the extended supports supporting the mobile device on a support surface in a portrait orientation as shown in FIGS. 9A-9C to change the orientation of the mobile device to a landscape orientation, as shown in FIGS. 9D-9E. In another example rotating operation, the user may rotate one or more of the supports supporting the mobile device in a landscape orientation approximately ninety degrees in order to increase or decrease the viewing angle of the mobile device display as shown in FIGS. 9D-9E. Different mobile device orientations may be

obtained depending on the size and shape of the supports, how many of the supports are extended, how the supports are oriented with respect to the mobile device, and the support surface upon which the supports are disposed.

(224) In a twelfth engaging operation **10110**, the user may engage one or more fingers of the user's hand with one or more of the cap, the base, the plug, and one or more of the supports, as shown in FIGS. **8B-8C**. The user may choose to dispose one or more of the supports in a variety of positions relative to one or more of the user's fingers, such as positioning an engaging portion of one or more of the supports closer or further away from the distal end of one or more fingers of the user's hand. This flexibility with regard to support placement provides for different comfort fits depending on the user's preferences and preferred methods of engagement and allows for greater reach with respect to the user's thumb in relation to the mobile device's display. Moreover, because the cap and one or more of the supports may rotate with respect to one or both of the base and the mobile device, the user's grip may easily be adjusted in order to optimize the user's interaction with the mobile device.

(225) For example, in one example engaging operation, the user may place one or more fingers of the user's hand underneath and adjacent to one or more fully extended supports, using the support as a kind of shelf to support the mobile device in one of the user's hands. In another example main engaging operation, the user may place one side of the mobile device in the palm of the user's hand, and grip around the exterior of the support disposed on the opposite side of the mobile device with one or more fingers of the user's hand. In another example engaging operation, the user may squeeze one or more of the extended supports between two or more fingers of the user's hand.

(226) In various example engaging operations, the user may engage one or more fingers of the user's hand through one or more of the extended supports, which may enable the user to more securely hold and operate the mobile device single-handedly. For example, in one example engaging operation, the user may engage one of the user's fingers through one of the extended supports and position each end of the support flush against opposite sides of the user's finger such that the fingers of the user's hand may be held together comfortably in close proximity to one another in a natural position, as shown in FIG. **8B**. In another example engaging operation, the user may engage one or more fingers of the user's hand into one or more of the extended supports with the back of the user's fingers disposed adjacent to the top of the cap such that the mobile device is positioned toward the back of the user's hand. This type of engagement can be convenient insofar as it leaves the fingers of the user's hand substantially free to engage with other objects, such as holding a cup or carrying a bag, while simultaneously enabling the user to maintain a secure grip on the mobile device. In another example engaging operation, the user may engage one or more fingers of the user's hand through one or more of the extended supports and also simultaneously engage one or more fingers with one or both of an interior and exterior perimetric face of one or more of the cap, the base, and the mobile device, as shown in FIG. **8C**. In this type of engagement, the user is able to maintain a secure hold of the mobile device while dynamically adjusting the position of the user's hand with respect to the mobile device, optimizing the distance the user's thumb is able to reach with respect to the exterior perimeters of the mobile device's display.

(227) In a thirteenth rotating operation **10112**, the user may rotate one or both of the base and the mobile device around the cap and/or one or more of the supports. For example, the user may engage one or more fingers of the user's hand through one or more of the supports and use another finger or thumb of the user's hand to rotate the mobile device around the axis of rotation with respect to one or both of the cap and the base, as shown in FIG. **8D**. This type of engagement allows the user to easily and securely hold the mobile device single-handedly while dynamically manipulating its display orientation. The user may easily manipulate the mobile device between different display orientations by rotating the mobile device in either direction with one or more unengaged fingers. This flexibility provides the user with a high degree of operational dexterity to manipulate the mobile device while enabling the user to maintain a secure grip on the mobile

device. For example, the user may have one or more fingers engaged through one or more of the supports with the mobile device positioned in a preferred portrait display orientation to interact with the mobile device's graphical user interface, then rotate the device to a preferred landscape display orientation using one or more fingers of the same or opposite hand to capture a picture or record a video using the mobile device's camera, before rotating the mobile device back to a preferred portrait orientation to further interact with the mobile device's graphical user interface. In another example rotating operation, the user may have one or more fingers of the user's hand engaged through one or more of the supports and then rotate the mobile device and the base around the cap and one or more of the supports using the thumb or one or more fingers of the same or opposite hand. In this way, the accessory may provide the user with kinetic amusement, as it enables the user to simultaneously hold and repeatedly rotate the mobile device around the axis of rotation with respect to the cap.

(228) In a fourteenth retracting operation **10114**, the user may retract one or more of the extended supports from a deployed position to a retained position using one or more fingers of the user's hand. In some implementations, the user may press one or more of the extended supports in the direction of retraction using one or more fingers of the user's hand until either the supports are engaged by one or more retaining protrusions disposed in the exterior perimetric face of the cap or until the support is no longer movable with respect to one of the cap and the base. The user would typically perform this operation when preparing the mobile device and the attached accessory for transport or personal conveyance. In other scenarios, a user may retract one or more extended supports prior to attaching the accessory to one or both of the mount and the mounting structure or before placing the accessory flat on the support surface. In some implementations, such as where one or more of the supports are flexible, the user may apply pressure to the support in a direction opposite the direction of retraction and beyond the position normally arrested by one or more of the cap projections, imparting tension or spring forces in the support which, when released, may be sufficient to cause the support to move in the opposite direction and retract to a retained position. In other implementations, one or more of the supports may be retracted separately or simultaneously via a support retraction mechanism disposed in or attached to the accessory.

(229) FIG. **11A** is a top perspective exploded view of a disc-shaped accessory cover **11130** attachable to the top of a plug **11028**. FIG. **11B** is a bottom perspective view of a disc-shaped accessory cover **11130** attached to the top of a plug **11028**. FIG. **11C** is a top perspective exploded view of a disc-shaped accessory cover **11130** attachable to the top of a cap **11018**. FIG. **11D** is a top perspective exploded view of a ring-shaped accessory cover **11130** attachable to the top of a cap **11018**. FIG. **11E** is a top perspective sectional view of a flanged accessory cover **11130** with an aperture disposed in the center and a partially enclosed bottom. FIG. **11F** is a top perspective sectional view of a flanged accessory cover **11130** with an aperture disposed in the center and an enclosed bottom. FIG. **11G** is a top perspective sectional view of a flanged accessory cover **11130** with an aperture disposed in the center and a recess disposed in an interior perimetric face.

(230) As illustrated in FIGS. **11A-11G**, in some implementations, an accessory cover **11130** may be permanently or detachably attached to an exterior surface of one or more of a cap **11018**, a plug **11028**, and a base (not shown, e.g., see base **4016** in FIG. **4D**). The accessory cover **11130** may be substantially flat and thin. The top of the cover **11130** may be flat, as shown in FIG. **11E** or sloped at an angle, as shown in FIG. **11F**. The accessory cover **11130** may be disc or ring-shaped. The accessory cover **11130** may have an interior and exterior perimeter generally matching the interior and exterior perimeters of one or more of the cap **11018**, the base **11016**, and the plug **11028**. In some implementations, the accessory cover **11130** extends beyond one or both of the interior and exterior perimetric faces of one or more of the cap **11018**, the base **11016**, and the plug **11028**, as shown in FIG. **11B**. In other implementations, the accessory cover **11130** is flanged and is configured to cover at least a portion of both the top exterior surface of the cap **11018** and the interior perimetric face of one or both of the cap **11018** and the base **11016**, as shown in FIGS. **11E-**

**11G.**

(231) In some implementations, the top of one or both of the plug **11028** and the cap **11018** includes a recess configured for receiving and/or engaging a portion of the accessory cover **11130**. In some implementations, an aperture **11030** is formed in the center of the accessory cover **11130** and may be of a dimension similar to an aperture **11030** formed in one of the cap **11018**, the base **11016**, and the plug **11028**, as shown in FIGS. **11B** and **11D**. In some implementations, the aperture **11030** formed in the center of the accessory cover **11130** may extend therethrough. In other implementations, the bottom surface of the accessory cover **11130** is enclosed, as shown in FIG. **11F**. In other implementations, the bottom surface of the accessory cover **11130** is partially enclosed, as shown in FIG. **11E**. In some implementations, one or more continuous or segmented annular features are disposed around the interior perimetric face of the accessory cover **11130** circumscribing the aperture **11030** and may protect a surface of a mobile device (not shown) from contact with an attachable plug **11028**. In other implementations, one or more attachment features and/or attachment elements are disposed in the accessory cover **11130**, such as a twist lock attachment feature **11076** disposed around the interior perimetric face of the accessory cover **11130**, as shown in FIG. **11F**. In other implementations, one or more recesses disposed in the interior perimetric face of the accessory cover **11130** may be configured to receive a portion of one or both of a lateral projection disposed in an outer surface of the plug **11028** and a plug removal feature (e.g. see **6074** in FIG. **6A**).

(232) In some implementations, the accessory cover **11130** has one of an adhesive or nano-suction pad disposed on one or more surfaces configured for attachment to one of the base **11016**, the cap **11018**, and the plug **11028**. In other implementations, the accessory cover **11130** attaches to one of the cap **11018** and the base **11016** by a friction or interference fit. In some implementations, the accessory cover **11130** is magnetic and may attach to one of the plug **11028**, the base **11016**, and the cap **11028** magnetically. The accessory cover **11130** may be rigid or flexible. The accessory cover **11130** may be made of plastic, vinyl, paper, rubber, silicone, wood, metal, carbon fiber, or other composite material. In some implementations, the accessory cover **11130** includes one or more proud or recessed ornamental design features. In some implementations, the accessory cover is a sticker. Indicia, such as a name, logo, slogan, trademark, or service mark representing one or more of a business, product, or person may be disposed on, across, or around one or more surfaces of the accessory cover **11130**.

(233) FIG. **12A** is a top perspective view of a plug **12028** configured with a twist lock attachment feature **12078** and an attachment element **12086** disposed in a top interior surface of the plug **12028**. FIG. **12B** is a top perspective view of a plug **12028** with an attachment features **12078** configured for attachment to an expandable grip support. FIG. **12C** is a top view of a plug **12028** and a cap **12018** with alignment indicators **12134** disposed on a top surface thereof for aligning the attachment features **12078** disposed in the plug with an attachment feature **12076** disposed in the cap **12018**. FIG. **12D** is a top perspective view of a plug **12028** with a selectively rotatable center portion configured with different attachment elements **12086**, **12088** disposed on opposite faces thereof. FIG. **12E** is a top perspective sectional view of a plug **12028** with a selectively attachable and reversible center portion configured with different attachment elements **12086**, **12088** disposed on opposite faces thereof. FIG. **12F** is a top perspective view of a plug **12028** with a magnetic attachment element **12086** configured with a plug removal feature **12074** and disposed in a recess formed in the bottom an attachment feature **12078**. FIG. **12G** is a top perspective view of a plug **12028** with two selectively rotatable attachment features **12078**, **12080**, showing the attachment features in both a retracted position and a retained position. FIG. **12H** is a top perspective view of a plug **12028** with a rotatable center portion and an attachment element **12086** disposed therein. FIG. **12I** is a top perspective view of a plug **12028** with a threaded attachment feature **12078** and a flanged bottom configured for attachment under a cap **12018**. FIG. **12J** is a top perspective view of a plug **12028** configured with an attachment hole **12137** and a plug removal feature **12074** and

disposed in a plug receptacle **12136**.

(234) In various implementations, one or more attachment features (e.g., **12076**, **12078**, **12080**) and/or attachment elements (e.g., **12086**, **12088**) may be attached to or disposed in or on an interior or exterior surface of one or more components of the accessory such as a plug (e.g., plug **12028**) and a cap (e.g., cap **12018**). In some implementations, one or more attachment features (e.g., feature **12078**) or attachment elements (e.g., element **12086**) operate by rotational engagement and may include one or more stops or detents for engaging and/or inhibiting the rotation of one or more other attachment features or attachment elements at one or more predetermined positions, as shown in FIG. **12A**. In other implementations, one or more attachment features (e.g., feature **12078**) or attachment elements (e.g., element **12088**) may be configured for attachment to a second mobile accessory or support such as an expandable grip or knob, as shown in FIG. **12B**. In some implementations, the plug **12028** includes one or more recesses disposed in one or both of the top and bottom of the plug **12028** configured for receiving one or more attachment elements (e.g., elements **12086**, **12088**), as shown in FIGS. **12A-12B**. In some implementations, one or more alignment indicators **12134** may be disposed on one or more surfaces of one or more of a base, the cap **12018**, the plug **12028**, a mount, and a mounting structure, and may aid the user in aligning one or more attachment features (e.g., feature **12078**) with respect to one or more other attachment features (e.g., feature **12076**), as shown in FIG. **12C**.

(235) In some implementations, two or more attachment features (e.g., features **12078**, **12080**) and/or attachment elements (e.g., elements **12086**, **12088**) are disposed in the plug **12028**, as shown in FIGS. **12D** and **12G**. In some implementations, two or more attachment elements (e.g., **12086**, **12088**) are attached to the plug **12028** and may be disposed on the same side or on opposite sides of the plug **12028**. As shown in FIGS. **12D-12E**, the plug **12028** may include two or more attachment features and/or attachment elements (e.g., elements **12086**, **12088**) disposed on one or more faces of a detachably attachable or selectively rotatable center portion. This configuration provides the user with the ability to selectively attach the plug **12028** to different types of mounts and mounting structures. In other implementations, one or more attachment elements (e.g., element **12086**) may include a substantially rigid or substantially flexible removal feature (e.g., feature **12074**), which may enable the user to detach one or both of the attachment element **12086** and the plug **12028** from another accessory component, as shown in FIG. **12F**.

(236) As shown in FIG. **12G**, in other implementations, one or more attachment features (e.g., features **12078**, **12080**) or attachment elements may articulate, rotate, or extend outward from a retracted position to a deployed position, providing a mechanism for attaching one or more accessory components such as the plug **12028** to another accessory component or to one or both of the mount and the mounting structure, such as a vehicle air vent. In other implementations, the plug **12028** includes a rotatable center portion with an attachment element (e.g., element **12086**) disposed on a top surface thereof, the center portion of the plug **12028** configured to freely rotate with respect to a fixed outer plug portion and enabling a second mobile accessory or support attached to the rotatable attachment element **12086**, such as an expandable grip, to freely rotate, as shown in FIG. **12H**. In other implementations, one or more attachment features (e.g., feature **12078**) or attachment elements may include one or more threaded fasteners, as shown in FIG. **12I**. In some implementations, the plug **12028** includes a continuous or segmented flange extending radially outward from the bottom exterior perimeter of the plug **12028**, as shown in FIG. **12I**. The flange **12135** may be disposed underneath a portion of the cap **12018** such as a first annular cap protrusion, wherein movement of both the flange **12135** and the plug **12028** may be longitudinally restricted and whereby the plug **12028** may be secured to the cap **12028**.

(237) In other implementations, one or more plugs **12028** may be disposed in a plug receptacle (e.g., receptacle **12136**), as shown in FIG. **12J**. The top of the plug receptacle **12136** may include a recess configured for receiving the plug **12028** and removal feature **12074** attached thereto, and a bottom surface configured for attachment to a mobile device housing, case, or cover thereof. The



plug receptacle **12136** and the accessory may be concurrently attached to a surface of the mobile device housing, case, or cover thereof. One or more plugs **12028** may be interchangeably attached and detached from the plug receptacle **12136** and the accessory, facilitating simultaneous attachment of multiple plugs to the mobile device housing, case, or cover thereof, and enabling a user to selectively adapt the accessory with the plug **12028** that best suits a particular application. One or more attachment holes **12137** disposed in one or both of the plug **12028** and the plug receptacle **12136** and extending therethrough may be configured for attachment to another object, such as a key ring or a lanyard.

(238) FIG. **13A** is a top perspective view of a plug **13028** configured with an extendable and retractable knife and bottle opener. FIG. **13B** is a top perspective view of a plug **13028** configured with a rotatably extendable and retractable bottle opener and box cutter. FIG. **13C** is a top perspective view of a plug **13028** container configured with a hinged lid and a magnetic closure. FIG. **13D** is a top perspective view of a plug **13028** configured with a rotatably extendable and retractable key.

(239) In various implementations, one or more plugs **13028** include one or more features or components for accessorizing a mobile device or for providing additional utility to a user. In some implementations, the plug **13028** includes an extendable or rotatable tool such as a knife or bottle opener as shown in FIGS. **13A-13B**. In some implementations, the plug **13028** includes one or more features for locking one or more extendable plug components in an extended or retracted position. In other implementations, the plug **13028** comprises a container with a lid that is hinged, rotatable, or removable, the container including one or more recesses configured for receiving and retaining one or more objects a user may find desirable to convey with a mobile device such as hearing aid batteries, breath mints, a pair of earbuds, or lip balm, as shown in FIG. **13C**. In some implementations, the plug **13028** includes other linearly or rotatably extendable and retractable implements or tools, such as a key, as shown in FIG. **13D**.

(240) The aforementioned plugs **13028** are just a representational sample of the types of accessories that may be included in one or more plugs **13028**. Other examples of accessories that may be disposed in or attached to one or more plugs **13028** include, but are not limited to: tools such as knives, wrenches, screw drivers, pliers, tape measures, scissors, box cutters, wire strippers, letter openers, keys, smoking pipes, cigar cutters, lighters, fire starters, hand crank chargers, compasses, whistles, writing pads, writing instruments, personal care items such as makeup applicators, tweezers, nail files, mirrors, electronic accessories such as LED lights, laser pointers, flash storage devices, memory cards, hard drives, clocks, cameras, camera flashes, adapters, cable interfaces, connector interfaces, projectors, printers, identification tags, authorization devices, vaporizers, batteries, speakers, headphones, geo-spatial location tags, radios, microphones, Bluetooth devices, wi-fi enabled devices, cellular radio enabled devices, scanners, smart watches, smart watch connectors, hearing aids, augmented reality glasses, lamps, fans, control devices such as remote controls, game controllers, keyboards, robotic mechanisms, programmable function controllers, camera shutter controllers, computer input control devices, computer peripherals, headset control devices, sensors such as motion sensors, altimeters, barometers, wind direction sensors, weather sensors, spectrometers, chemical sensors, particulate sensors, oxygen monitors, pulse oximeters, glucose monitors, infrared fat monitors, pressure sensors, weight sensors, electrophysiology sensors, hygrometer, thermometer, electrocardiography sensors, health monitors, heart rate monitors, breathalyzers, breath monitors, vibrators, massage paddles, recording devices such as audio recording devices, video recording devices, image recording devices, optical devices such as camera lenses, magnifying glasses, monocles, bifocals, prisms, periscopes, containers for containing and dispensing things such as makeup, moisturizer, lip balm, liquid, perfume, hand sanitizer, viral testing kits, aromatherapy pods, cleaning pads, condoms, breath mints, gum, pills, earbuds, headphones, hearing aid batteries, dental floss, guitar picks, ball markers, toys and games such as tops, mazes, fidget toys, spinners, gyroscopes, drones, musical instruments, mounts such as

surface attachment mechanisms, magnetic mounts, suction cup mounts, nano suction pad mounts, wall mounts, vehicle mounts, bike mounts, armband mounts, wristband mounts, headband mounts, and attachment supports such as straps, loops, bands, grips, extendable socket grips, kickstands, clips, tri-pods, extendable selfie sticks, lanyards, and keyrings, among many others.

(241) FIG. 14A is a top perspective view of an example accessory **14010** including a plug **14028** and a cap **14018** configured with corresponding design elements. FIG. 14B is a top perspective view of an example accessory **14010** with a circular aperture **14030** disposed in the center of a plug **14028** and extending therethrough. FIG. 14C is a top perspective view of an example accessory **14010** with a heart-shaped aperture **14030** disposed in the center of a plug **14028**. FIG. 14D is a top perspective view of an annular-shaped example accessory with an aperture **14030** disposed in the center of a cap **14028**. FIG. 14E is a top perspective view of a substantially square-shaped example accessory **14010**. FIG. 14F is a top perspective view of a substantially rectangular-shaped example accessory **14010**. FIG. 14G is a top perspective view of a substantially circular-shaped example accessory **14010** with two flat sides disposed opposite one another. FIG. 14H is a top perspective view of a substantially oblong-shaped example accessory **14010**. FIG. 14I is a top perspective view of a substantially hexagonal-shaped example accessory **14010**. FIG. 14J is a top perspective view of an example accessory **14010** including a substantially polygonal-shaped cap **14018**. FIG. 14K is a top perspective view of a substantially heart-shaped example accessory **14010**. FIG. 14L is a top view of an example accessory **14010** with a shape and ornamentation depicting a fictional creature.

(242) In some implementations, corresponding design elements may be disposed in one or both of an interior and exterior surface of a plug **14028** and a cap **14018**, as shown in FIG. 14A. One or more apertures **14030** disposed in the accessory **14010** may be one of a variety of different shapes or symbols. For example, circles, stars, and hearts are just three of a variety of different shapes and symbols that may be formed in the accessory **14010**, as shown in FIGS. 14A-14D. In some implementations, one or more apertures **14030** disposed in a surface of one or more of a base **14016**, the cap **14018**, and the plug **14028** may be fully or partially enclosed as shown in FIG. 14C or may extend therethrough, as shown in FIGS. 14B-14D. One or more shapes or symbols disposed in one or both of the plug **14028** and the cap **14018** may be proud or recessed.

(243) One or both of the interior and exterior perimeters of the accessory **14010** may resemble one of a variety of different shapes or symbols. In some implementations, the accessory **14010** has a circular or annular shape that may resemble a real-world object such as a wheel or a donut, as shown in FIG. 14D. In other implementations, the shape of the accessory **14010** is substantially square or rectangular shaped, as shown in FIGS. 14E-14F. In other implementations, the accessory **14010** is substantially circular shaped with two flat sides disposed opposite one another, as shown in FIG. 14G. In some implementations, the accessory **14010** has a shape that is substantially oval or oblong, as shown in FIG. 14H. In other implementations, the accessory **14010** has a shape that is substantially hexagonal, as shown in FIG. 14I. In other implementations, the accessory **14010** has as shape that is substantially triangular, or polygonal.

(244) In some implementations one or more supports (e.g., supports **14020**, **14022**) has a shape and profile substantially conforming to the shape and profile of one or both of the base **14016** and the cap **14018**, as shown in FIGS. 14A-14K. In other implementations, one or both of the cap **14018** and the base **14016** may have an inner or outer perimeter that differs from the inner or outer perimeter of one or more supports (e.g., supports **14020**, **14022**), as shown in FIG. 14J. One or more corners or edges of the accessory **14010** may be sharp or rounded. In some implementations, the aperture **14030** formed in the center of the accessory **14010** has a shape generally matching the outer perimeter of the accessory **14010**. In other implementations, the aperture **14030** may have a shape that is substantially triangular, circular, square, rectangular, or polygonal, as shown in FIG. 14J.

(245) In some implementations, the accessory **14010** has a shape resembling a symbol, logo, emblem, or icon, such as a heart, as shown in FIG. 14K. Other possible accessory **14010** shapes

may be representations that include, but are not limited to: flowers, plants, human forms, heads, sporting equipment, imaginary creatures, fictional characters, cartoon figures, animals, fish, insects, birds, vegetables, fruits, and vehicles, among others. In various implementations, one or more features or shapes extend laterally or protrude longitudinally from one or more of the base **14016**, the cap **14018**, the plug **14028**, the projections **14024**, **14026**, and the supports **14020**, **14022**, and may provide additional functionality or ornamentation to the accessory **14010**, as shown in FIG. **14L**. In some implementations, the accessory includes corresponding design elements disposed in two or more of the base **14016**, the cap **14018**, the plug **14028**, the projections **14024**, **14026**, and the supports **14020**, **14022**, as shown in FIG. **14L**.

(246) FIG. **15A** is a top perspective view of a base **15016** with a bottom portion extending radially inward and outward from a first annular base protrusion **15036** and an aperture **15030** formed in the center of the base **15016**. FIG. **15B** is a top perspective sectional view of a cap **15018** with an enclosed bottom center portion extending radially inward from a first annular cap protrusion **15044**. FIG. **15C** is a bottom perspective view of a cap **15018** with an enclosed top center portion extending inward from a first annular cap protrusion **15044**. FIG. **15D** is a top perspective view of a cap **15018** with an enclosed top center portion. FIG. **15E** is a top perspective sectional view of a cap **15018** with a fourth annular cap protrusion **15138**. FIG. **15F** is a top perspective sectional view of an example accessory **15010** with a base **15016** and a cap **15018**, each configured with a pair of corresponding engagement features **15038**, **15144**, and **15046**, **15142**.

(247) In some implementations, the bottom of a base (e.g., base **15016**) extends radially inward from a first annular base protrusion **15036** and may fully or partially enclose the center of the base **15016**, as shown in FIG. **15A**. In other implementations, the bottom of the base **15016** extends inward from the first annular base protrusion **15036** and the flanged portion extending outward from the first annular base protrusion **15036** is omitted. In some implementations, a portion of a cap (e.g., cap **15018**) extends radially inward from the bottom of the first annular cap protrusion **15044** and fully or partially encloses the bottom center portion of the cap **15018**, as shown in FIG. **15B**. In other implementations, a portion of the cap **15018** extends radially inward from the top of the first annular cap protrusion **15044** and fully or partially encloses the top center portion of the cap **15018**, as shown in FIGS. **15C-15D**.

(248) In some implementations, the cap **15018** includes a fourth annular cap protrusion **15138**, as shown in FIG. **15E**. The fourth annular cap protrusion **15138** may be located interior to the first annular cap protrusion **15044** separated by a third interior cap recess **15140** and may circumscribe an aperture **15030** formed in the center of the cap **15018**. The fourth annular cap protrusion **15138** may define the interior perimetric face of the cap **15018** and may be configured for receiving a plug. In some implementations, the cap **15018** extends radially inward from the fourth annular cap protrusion **15138** and may fully or partially enclose the top or bottom center of the cap **15018**. In other implementations, the cap **15018** includes only the first and second annular cap protrusions **15044** **15048** and one or both of a third and the fourth annular cap protrusions **15054**, **15138** are omitted.

(249) In some implementations, the cap **15018** and the base **15016** include multiple corresponding engagement features **15046**, **15142**, and **15038**, **15144**, as shown in FIG. **15F**. In some implementations, the cap **15018** may include a first cap engagement feature **15046** disposed on a first annular cap protrusion **15044** and a second cap engagement feature **15142** disposed on a third annular cap protrusion **15054**. The base **15016** may include a first base engagement feature **15038** disposed on a first annular base protrusion **15036** and a second base engagement feature **15144** disposed on a second annular base protrusion **15146**, as shown in FIG. **15F**. In some implementations, one or more attachment elements are disposed on top of the base **15016** around the first base protrusion **15038** or in between the first and second annular base protrusions **15036**, **15146**.

(250) FIG. **16A** is a top perspective sectional view of an example accessory **16010** with an outward

extending base engagement feature **16038** and an inward extending cap engagement feature **16046**. FIG. **16B** is an enlarged sectional view of FIG. **16A** showing an outward extending base engagement feature **16038** disposed on an exterior face of a first annular base protrusion **16036** and an inward extending cap engagement feature **16046** disposed on an interior face of a third annular cap protrusion **16054**. FIG. **16C** is a top perspective sectional view of an example accessory **16010** with an outward extending base engagement feature **16038** disposed on an exterior face of a first annular base protrusion **16036** and an inward extending cap engagement feature **16046** disposed on an interior face of a first annular cap protrusion **16044**. FIG. **16D** is a top perspective sectional view of an example accessory **16010** with a top interior portion of a cap extending inward over a first annular base protrusion **16036**. FIG. **16E** is a top perspective sectional view of an example accessory **16010** with three base components **16148**, **16150**, **16152**. FIG. **16F** is a top perspective sectional view of an example accessory **16010** with two base components **16148**, **16150**. FIG. **16G** is a top perspective assembly view of an example accessory **16010** with two base components **16148**, **16150** and an accessory cover **16130** attached to a cap **16018**. FIG. **16H** is a top perspective view of an example accessory **16010** with two cap components **16154**, **16156** and two base components **16148**, **16150** (not shown). FIG. **16I** is a top perspective sectional view of FIG. **16H**. FIG. **16J** is a top perspective assembly view of FIG. **16H**.

(251) As shown in FIGS. **16A-16B**, in some implementations, a first base engagement feature **16038** extends radially outward from an exterior face of a first annular base protrusion **16036** and is configured to engage with a first cap engagement feature **16046** extending radially inward from an interior face of a third annular cap protrusion **16054**. In other implementations, the first base engagement feature **16038** extends radially outward from an exterior face of the first annular base protrusion **16036** and is configured to engage with the first cap engagement feature **16046** extending radially inward from an interior face of the second annular cap protrusion **16048** (e.g., see FIGS. **19K-19L**). In other implementations, the first base engagement feature **16038** extends radially outward from a first annular base protrusion **16036** is configured to engage with a first cap engagement feature **16046** extending radially inward from a first annular cap protrusion **16044**, as shown in FIG. **16C**. In some implementations, an inner portion of a cap **16018** extends radially inward from the first annular cap protrusion **16044** and covers a portion of one or both of the first annular base protrusion **16036** and the first base engagement feature **16038**, as shown in FIGS. **16C-16D**. In some implementations, the portion of the cap **16018** extending over the first annular base protrusion **16036** may be a separately formed component and permanently or detachably attached to the top of the cap **16018** and may be configured to protect one or both of the first base engagement feature **16038** and the first annular base protrusion **16036** from contact with one or more of a user's fingers.

(252) In various implementations, one or both of the base **16016** and the cap **16018** are constructed of two or more components. Two or more base **16016** and/or cap **16018** components may be attached together via adhesive, mechanical fasteners, hook and loop fasteners, two-part interlocking fastener system, or magnets, or may be welded together. One or more base **16016** and/or cap **16018** components may be made of plastic, metal, wood, carbon fiber, or other composite material. In some implementations, a portion of the cap **16018** is rotatably disposed between a first base component **16148** and a second base component **16150**, as shown in FIG. **16E**. In other implementations, the first cap engagement feature **16046** is rotatably disposed between the first base engagement feature **16038** and the second base component **16150**, as shown in FIG. **16F**. In some implementations, a third base component **16152** is disposed between the first and second base components **16148**, **16150** and may include one or more magnets or adhesive layers for connecting the first and second base components **16148**, **16150** together, as shown in FIG. **16E**. In other implementations, the first **16148** and third base **16152** components are combined and form a single body. In some implementations, one or more of the first, second, and third base components **16148**, **16150**, **16152** are magnetic and are configured to attach to a magnetic attachment interface and/or

one or more magnetic attachment elements disposed in the mobile device housing, case, or cover thereof (e.g., see attachment interface **20042** and magnetic elements **20090** in FIGS. **20F-20H**). In other implementations, the bottom of the first base component **16148** is disposed in a recess formed in the top of the second base component **16150**, as shown in FIG. **16F**. In some implementations, the top of the first base component **16148** may be flush with the top of the cap **16018**, as shown in FIG. **16G**. In other implementations, the top of the first base component **16148** is recessed with respect to the top of the cap **16018**, as shown in FIG. **16E**. The bottom of the second base component **16150** may be configured to receive an attachment interface for attaching the base **16016** to a surface of a mobile device housing, case, or cover thereof. In some implementations, an accessory cover **16130** is attached to the top surface of the cap **16018** and may cover a portion of the top of the first base component **16148**, as shown in FIG. **16G**. The accessory cover **16130** may protect the top of the first base component **16148** from contact with one or more of a user's fingers. (253) As shown in FIGS. **16H-16J**, the cap **16018** may also be constructed of two or more component parts. The bottom of a first cap component **16154** may be configured for attachment to the top of a second cap component **16156**. One or more supports **16020**, **16022** may be rotatably attached to the first cap component **16154**. As shown in FIGS. **16J-16I**, the first base component **16148** may include a laterally protruding outer flanged portion and a longitudinally protruding inner center portion. An annular protrusion may extend longitudinally from the top of the second base component **16150** and may circumscribe an aperture **16030** disposed in the center of the second base component **16150** and extending therethrough. A recess may be formed in the bottom of the second base component **16150** circumscribing the aperture **16030** and configured to substantially receive the laterally protruding outer flanged portion of the first base component **16148**. The longitudinally protruding center portion of the first base component **16148** may be configured to pass through the apertures **16030** disposed in the center of and extending through the second base component **16150** and the second cap component **16156**. The top of the first base component **16148** may be configured to attach to the bottom of the first cap component **16154**, longitudinally constraining the second base component **16150** and second cap component **16156** between the first base component **16148** and the first cap component **16154**. The first and second cap components **16154**, **16156** and first base component **16148** may rotate with respect to the second base component **16150**, the bottom of the second base component **16150** configured to attach to the mobile device housing, case, or cover thereof via the attachment interface.

(254) One or more cap components **16154**, **16156** may have a shape resembling a symbol, logo, emblem, or icon, as shown in FIG. **16H**. Corresponding design features may be disposed in one or more of the first and second cap components **16154**, **16156**, first and second projections **16024**, **16026**, and first and second supports **16020**, **16022**, as shown in FIGS. **16H-16J**. In some implementations, one or more recesses are formed in the bottom of the first cap component **16154** and configured to receive and engage a corresponding portion of one or both of the first and second projections **16024**, **16026**.

(255) In other implementations, one of a first and a second base component **16148**, **16150** is substantially incorporated into the mobile device housing, case, or cover thereof. In some implementations, the second base component **16150** is substantially incorporated into the mobile device housing, case, or cover thereof, and a recess formed in an interior surface thereof is configured for receiving a portion of a first base component **16148** configured for attachment to one or both of the first and second cap components **16154**, **16156**.

(256) FIG. **17A** is a top perspective view of an example accessory **17010** with a support **17020** attached to a cap **17018** via a pair of fasteners **17158**. FIG. **17B** is a top view of two supports **17020**, **17022** connected together at their distal ends and attached to a cap **17018** via a pair of fasteners (not shown). FIG. **17C** is a top perspective assembly view of FIG. **17B**.

(257) In some implementations, the accessory includes no supports. In other implementations, the accessory **17010** includes just one support (e.g., support **17020**). As shown in FIG. **17A**, one or

more supports **17020** may be attached to a cap (e.g., cap **17018**) via a pair of fasteners **17158**. The fasteners **17158** may be disposed in a pair of holes **17160** formed through each end of the support **17020** and in opposite sides of the exterior of the cap **17018**, the holes **17160** configured for receiving and/or engaging the fasteners **17158** and the fasteners **17158** limiting the movement of the support **17020** by at least one degree of freedom with respect to the cap **17018**. In some implementations, the cap **17018** includes a laterally extending projection **17024** disposed on the exterior of the cap **17018** configured to limit the rotation of the support **17020** at a predetermined angle, as shown in FIG. 17A.

(258) In other implementations, the accessory **17010** includes two or more supports (e.g., supports **17020**, **17022**) connected together at their distal ends and rotatably attached to the cap **17018** via a pair of fasteners **17158**, as shown in FIGS. 17B-17C. A recess disposed in one or more distal ends of one of the supports **17020**, **17022** may be configured for receiving a corresponding portion protruding from one or more distal ends of another one of the supports **17020**, **17022**, as shown in FIGS. 17B-17C. One or more fasteners **17158** selected from the group of fasteners including screws, bolts, rivets, dowels, rods, and pins, and may be configured for permanently or detachably attaching one or more supports **17020**, **17022** to the cap **17018**, as shown in FIGS. 17A-17C.

(259) FIG. 18A is a top perspective assembly view of two projections **18024**, **18026** each attachable to a cap **18018** via a fastener **18158**. FIG. 18B is a top perspective view of an example accessory **18010** with two projection **18024**, **18026** each attached to a cap **18018** via a fastener **18158** and two supports **18020**, **18022** each attached to the cap **18018** via multiple fasteners **18158**. FIG. 18C is a top perspective assembly view of two projections **18024**, **18026** each attachable to a cap **18018** via a fastener **18158** and a two supports **18020**, **18022** each attachable to the cap **18018** via multiple fasteners **18158**. FIG. 18D is a bottom perspective view of a cap **18018** with multiple holes **18160** formed in the exterior of the cap **18018** and extending into a fastening block **18162** disposed on the interior of a second annular cap protrusion **18048**. FIG. 18E is a top perspective view of an example accessory **18010** with two projections **18024**, **18026** and two supports **18020**, **18022** attached to a cap **18018** via multiple fasteners **18158**. FIG. 18F is a top perspective assembly view two projections **18024**, **18026** and two supports **18020**, **18022** attached to a cap **18018** via multiple fasteners **18158**.

(260) In some implementations, one or more projections (e.g., projections **18024**, **18026**) are permanently or detachably attached to the exterior of a cap **18018** by one or more fasteners **18158**, as shown in FIGS. 18A-18C and FIGS. 18E-18F. In some implementations, one or more supports (e.g., supports **18020**, **18022**) are permanently or detachably attached to the exterior of the cap **18018** by two or more fasteners **18158**, as shown in FIGS. 18B-18C and FIGS. 18E-18F. In various implementations, one or more fasteners **18158** selected from the group of fasteners including screws, bolts, rivets, dowels, rods, and pins, are configured for permanently or detachably attaching one or more supports (e.g., supports **18020**, **18022**) and/or projections (e.g., projections **18024**, **18026**) to the cap **18018**, as shown in FIGS. 18A-18C and 18E-18F.

(261) In some implementations, one or more holes **18160** formed in the exterior perimetric face of the cap **18018** are configured to receive and/or engage a portion of one or more fasteners **18158** and may include threaded engagement features disposed therein. One or more holes **18160** formed in and extending through one or more projections **18024**, **18026** and/or one or more supports **18020**, **18022** may be configured to receive and/or engage a portion of the fastener **18158**, as shown in FIGS. 18C and 18F. In some implementations, one or more fastening blocks **18162** are disposed on an interior face of a second annular cap protrusion **18048** and configured for receiving a portion of one or more fasteners **18158**, as shown in FIG. 18D. One or more holes **18160** formed in the exterior of the cap **18018** may extend through the second annular cap protrusion **18048** and into a portion of the fastening block **18162**, wherein one or more fasteners **18158** may be received and engaged. In other implementations, the end of one or more fasteners **18158** attaching one or more supports **18020**, **18022** and/or projections **18024**, **18026** to the cap **18018** is enlarged and of a

size larger than the size of the holes **18160** formed in the supports **18020**, **18022** and/or projections **18024**, **18026** and configured to limit the lateral movement of one or more supports **18020**, **18022** and/or projections **18024**, **18026** with respect to the cap **18018**, as shown in FIGS. **18C** and **18F**. (262) In some implementations, one or more projections (e.g., projections **18024**, **18026**) are attached to the cap **18018** by a single fastener **18158**, as shown in FIGS. **18A-18C**. As shown in FIG. **18C**, one or more exterior cap recesses **18058** formed in the exterior perimetric face of the cap **18018** may be configured for receiving and engaging a corresponding portion of one of the projections **18024**, **18026** protruding from an interior side of the projection, wherein rotational movement of the projection with respect to the cap **18018** may be limited. In other implementations, the projections **18024**, **18026** and the supports **18020**, **18022** are attached to the cap **18018** by two or more fasteners **18158**, as shown in FIGS. **18E-18F**. A portion of the fasteners **18158** attaching the supports **18020**, **18022** to the cap **18018** may be disposed in corresponding holes **18160** formed in the projections **18024**, **18026**, as shown in FIGS. **18E-18F**.

(263) In some implementations, the distal end of one or more fasteners **18158** attached to the cap **18018** is in contact with a portion of a base **18016**, such as a first annular base protrusion, and is configured to enable a user to regulate the amount of rotational friction between the cap **18018** and the base **18016** or to restrict rotational movement of the cap **18018** to or between one or more predetermined positions. In other implementations, one or more fasteners **18158** are configured to regulate the amount of rotational friction between the cap **18018** and one or more attached supports **18020**, **18022**. In some implementations, one or more fasteners **18158** attached to the cap **18018** extend through one or more annular cap protrusions and are configured to engage with one or more base engagement features, the fasteners **18158** functioning as one or more cap engagement features for rotatably coupling and/or securing the cap **18018** to the base **18016**. In other implementations, a distal end of one or more fasteners **18158** may be enlarged and/or include an annular recess disposed therein and configured for engaging an attachable retaining fastener such as a nut, retaining ring, or spring clip, whereby the end of the fastener may be secured to one or more components of the accessory **18010**. In some implementations one or more fasteners **18158** may pass through a hole extending lengthwise through the center of one or more support arbors disposed in the ends of one or more supports **18020**, **18022**.

(264) FIG. **19A** is a top perspective view of a cap **19018** with a rigid support **19164** rotatably attached to the cap **19018**. FIG. **19B** is a top perspective view of an example accessory **19010** with three rigid supports **19020**, **19022**, **19164** rotatably attached to a cap **19018**. FIG. **19C** is a top perspective assembly view of FIG. **19B**. FIG. **19D** is a top perspective view of an example accessory **19010** with three rigid supports **19020**, **19022**, **19164** rotatably attached to a cap **19018**. FIG. **19E** is a top perspective assembly view of FIG. **19D**. FIG. **19F** is a top perspective view of a rigid support **19164** rotatably attached to a plug **19028**. FIG. **19G** is a top perspective view of an example accessory **19010** with two rigid supports **19020**, **19022** each attached to a cap **19018** via fasteners **19158** and a flexible support **19164** attached to the cap **19018** through two pairs of slots **19166** disposed at opposite ends of the cap **19018**. FIG. **19H** is a top perspective assembly view of two rigid supports **19020**, **19022** each attached to a cap **19018** via fasteners **19158** and a flexible support **19164** attached to the cap **19018** through two pairs of slots **19166** disposed at opposite ends of the cap **19018**. FIG. **19I** is a top perspective assembly view of two rigid supports **19020**, **19022** each attached to a cap **19018** via a pair of support arbors **19068** and a third flexible support **19164** configured with an adjustable tensioner **19172** and attached to the cap **19018** via a pair of fasteners **19158**. FIG. **19J** is a top perspective view of a flexible support **19020** configured with a mechanism for self-attachment and attached to a cap **19018** through a pair of slots **19166** formed in opposite ends of the cap **19018**. FIG. **19K** is a top perspective view of a flexible support **19022** attached to a cap **19018** through a pair of slots **19166** formed in opposite ends of the cap **19018** and secured via fasteners **19158** at each end, the cap **19018** rotatably coupled to a base **19016**. FIG. **19L** is a bottom perspective view of a cap **19018** with two fasteners **19158** disposed at opposite ends in the interior

of the cap **19018** and configured for attaching a flexible support. FIG. **19M** is a bottom perspective assembly view of a flexible support **19020** with fasteners **19158** disposed in each end and configured for attachment to a pair of slots **19166** disposed opposite in the interior perimeter of a cap **19018**. FIG. **19N** is a top perspective view of a plug **19028** with a flexible support **19164** disposed in a pair of slots **19166** formed in opposite sides of the plug **19028**. FIG. **19O** is a top perspective sectional view of FIG. **19N** showing the flexible support **19164** configured with enlarged distal ends. FIG. **19P** is a top perspective sectional view of a plug **19028** with a concave top portion and a flexible support **19164** disposed in a pair of slots **19166** formed in opposites sides of the plug **19028**. FIG. **19Q** is a top perspective view of a plug **19028** with a flexible support **19164** laterally disposed in a pair of slots **19166** formed in opposites sides of the plug **19028**. FIG. **19R** is a top perspective view of a plug **19028** with a flexible support **19164** laterally disposed in a pair of slots **19166** formed in opposites sides of the plug **19028** and a rigid prop **19168** attached to the support **19164** and configured for engagement with a pair of prop engagement features **19170**. FIG. **19S** is a top perspective view of a plug **19028** with a flexible support **19164** laterally disposed in a pair of recesses **19166** formed in opposites sides of the plug **19028** and a rigid prop **19168** configured for engagement with a prop engagement feature **19170** and rotatably attached to the support **19164** via a fastener **19158**.

(265) In various implementations, the accessory **19010** includes more than two supports. In some implementations, a third support (e.g., support **19164**) is attached to the accessory **19010**. In some implementations, the third support **19164** is substantially rigid, as in FIGS. **19A-19F**. In other implementations, the third support **19164** is substantially flexible, as shown in FIGS. **19G-19I**. In some implementations, the third support **19164** is disposed in the center of a cap **19018** and is rotatable with respect to the cap, as shown in FIG. **19A**. In other implementations, the third support **19164** may be disposed in one or more slots **19166** formed in one or more of the cap **19018**, a base **19016**, one or more projections **19024**, **19026**, and a plug **19028**, the slots **19166** having a profile corresponding to and configured for receiving a portion of the support **19164**, as shown in FIGS. **19H-19I**.

(266) In some implementations, the third support **19164** is substantially arc-shaped, annular, or rectangular, as shown in FIGS. **19A-19F**. An exterior portion of the third support **19164** may be flat, beveled, or chamfered, as shown in FIG. **19D**. In some implementations, the ends of the third support **19164** are attached to the accessory **19010** by one or more fasteners **19158**. In other implementations, one or more support arbors **19068** extending from one or more distal ends of the third support **19164** are disposed in one or more corresponding exterior cap recesses and/or slots **19166** formed in one of the cap **19018** and the plug **19028** and configured for limiting movement of the third support **19164** in one or both of a lateral and longitudinal direction, as shown in FIGS. **19A-19C** and **19F**. In other implementations, one or more features for retaining a portion of the third support **19164** are included in one or more projections **19024**, **19026**, (e.g., see slot **19166** in FIG. **19E**) whereby the third support **19164** may be rotatably connected to the cap **19018** and movement of the support **19164** in one or both of a lateral and longitudinal direction may be restricted, as shown in FIGS. **19D-19E**.

(267) As shown in FIGS. **19G-19S**, one or more of a first, second, and third support (e.g., supports **19020**, **19022**, **19164**) attachable to the accessory **19010** may be substantially flexible, in the general form of a band, loop, strap, ribbon, or cord. One or more slots **19166** formed in one or more components of the accessory **19010**, such as the base **19016**, the cap **19018**, the plug **19028**, and the projections **19024**, **19026**, may be configured for receiving one or more flexible supports (e.g., support **19164**) and may extend through a portion of one or both of the interior and exterior perimeters of the component, facilitating attachment of one or more flexible supports thereto and detachment therefrom, as shown in FIGS. **19G-19I** and **19N-19S**. In some implementations, a portion of the flexible support (e.g., support **19164**) may be configured to pass through a slot formed in one or more projections **19024**, **19026** and may be secured to the cap **19018** via one or



more fasteners **19158**, as shown in FIG. **19I**. In other implementations, one end of the flexible support **19164** may be configured to pass through a slot formed in one projection **19026** and the other end of the flexible support **19164** configured to loop around the sides and underneath the other projection **19024**, enabling a user to easily attach or detach the support from the accessory **19010** as needed.

(268) One or more adjustment mechanisms **19172** configured for adjusting the length, tautness, or tension of the flexible support (e.g., support **19164**), such as a spring-loaded adjustable tensioner, may be attached to one end of the flexible support **19164**, as shown in FIG. **19I**. In other implementations, one or more flexible supports (e.g., support **19164**) may include a mechanism for fastening one portion of the support to another portion, such as hook-and-loop fasteners, interlocking connectors, slide buckles, ladder lock buckles, or reusable adhesive, whereby the length, tautness, or tension of the support **19020** may be adjusted, as shown in FIG. **19J**. In other implementations, one or more flexible supports are permanently attached to one or more components of the accessory **19010** and may be joined together by thermoforming, heat staking, welding, or adhesive.

(269) In some implementations, one or more holes or loops formed in one or more ends of one or more flexible supports (e.g., supports **19020**, **19022**, **19164**) are configured for receiving one or more fasteners **19158**, whereby the ends of the supports may be secured to the accessory **19010**, as shown in FIGS. **19I** and **19K**. The fasteners **19158** securing one or more ends of one or more flexible supports to the accessory **19010** may be of a size and shape larger than the slots **19166** formed in one of the base **19016**, the cap **19018**, the plug **19028**, and the projections **19024**, **19026** in which one or more flexible supports may be disposed, and may restrict the ends of the supports from passing through the slots **19166** and detaching from the accessory **19010**. In other implementations, the ends of one or more flexible supports may be configured to attach to one or more fasteners **19158** disposed in one or more of the base **19016**, the cap **19018**, the plug **19028**, and the projections **19024**, **19026**, as shown in FIG. **19L**. In other implementations, one or more fasteners **19158**, such as a buckle, hook, or clasp, are attached to one or more ends of one or more flexible supports (e.g., support **19020**) and configured for engaging with one or more corresponding engagement features, fasteners **19158**, or slots **19166** disposed in one or more of the cap **19018**, the base **19016**, the plug **19028**, and the projections **19024**, **19026**, as shown in FIG. **19M**.

(270) In other implementations, a rigid feature is disposed in one or more ends of one or more flexible supports (e.g., supports **19020**, **19022**, **19164**) and configured to be received and engaged in one or more slots **19166** formed in one or more of the base **19016**, the cap **19018**, the plug **19028**, and the projections **19024**, **19026**, the rigid feature preventing the end of the flexible support from passing through one or more slots **19166** in which it is disposed.

(271) In some implementations, the flexible support (e.g., support **19164**) is attached to the plug **19028** through a pair of slots **19166** formed in opposite sides of the plug **19028**. A portion of one or more of the slots **19166** formed in the plug **19028** may extend through the exterior perimeter of the plug **19028** facilitating attachment and detachment of the support **19164** from the plug **19028**, as shown in FIG. **19N**. In some implementations, one or more distal ends of the flexible support **19164** are rigid or enlarged and configured to engage with a portion of one or more corresponding slots **19166** formed in the plug **19028** wherein the ends of the support **19164** are constrained from moving in one or both of a lateral and longitudinal direction, as shown in FIGS. **19N-19O** and **19Q-19S**. An aperture **19030** may be formed in the center of one or both of the cap **19018** and the plug **19028** or a top portion of one or both of the cap **19018** and the plug **19028** may be recessed or concave, in order to facilitate user engagement with and deployment of the flexible support attached therein, as shown in FIGS. **19F-19S**.

(272) In other implementations, a substantially flat and rigid prop **19168** is attached to a proximal portion of the flexible support (e.g., support **19164**) and configured to engage with one or more

prop engagement features **19170** disposed in the plug **19028** wherein one or more ends of the prop **19168** may be rotatably inserted, secured, and oriented such that the opposite end of the prop extends away from the plug **19028** at a predetermined angle and whereby the prop **19168** may be used to support a mobile device in one or more display orientations on a support surface, as shown in FIGS. **19R-19S**. A notch may be formed in a portion of one end of the prop **19168**, enabling the prop to be inserted into one or more prop engagement features **19170**, as shown in FIG. **19R**. In some implementations, the prop **19168** is pliable or flexible and may be shaped to conform to an inner or outer profile of the plug **19028** or one or more prop engagement features **19170**. In other implementations, the center of the prop **19168** may be attached to the center of the flexible support **19164** by one or more fasteners **19158**, the fasteners defining an axis of rotation about which the prop **19168** may freely rotate with respect to the flexible support **19164**, as shown in FIG. **19S**. In some implementations, the plug **19028** includes multiple prop engagement features **19170** configured for engaging one or more sides or ends of the prop **19168** and orienting the prop at different predetermined angles with respect to the plug **19028**. In various implementations, one or more supports (e.g., supports **19020**, **19022**, **19164**) include both rigid and flexible parts. Indicia may be disposed on one or more surfaces of one or more of the supports **19020**, **19022**, **19164**, and the prop **19168**, as shown in FIG. **19N**.

(273) FIG. **20A** is a bottom perspective assembly view of an example accessory **20010** with multiple magnetic attachment elements **20084** arranged annularly around the inside of a cap **20018** and configured to attach to a magnetic attachment interface **20042** disposed in the bottom of a base **20016**. FIG. **20B** is a bottom perspective assembly view of multiple magnetic attachment elements **20084**, **20086**, **20088** combinable together in a continuous shape and disposed inside a cap **20018**. FIG. **20C** is a bottom perspective assembly view of a cap **20018** configured for receiving and engaging an annular attachment element **20084** disposed therein. FIG. **20D** is a top perspective sectional view of an example accessory **20010** with multiple magnetic attachment elements **20084**, **20086**, **20088** disposed in a cap **20018** and configured to attach to a magnetic attachment interface **20042** disposed in the bottom of a base **20016**, the cap further including multiple annular cap protrusions **20044**, **20054** disposed adjacent to an annular base protrusion **20036**. FIG. **20E** is an enlarged sectional view of an example accessory **20010** with a ball bearing attachment element **20084** disposed in between a cap **20018** and a base **20016**. FIG. **20F** is a top perspective assembly view of an example accessory **20010** with a magnetic bearing attachment element **20084** attached to one or more magnetic attachment elements (not shown) disposed in a cap **20018** configured to rotatably couple to a magnetic attachment interface **20042** disposed on an exterior surface of a mobile device **20012**. FIG. **20G** is a top perspective assembly view of an example accessory **20010** including a cap **20018** with a magnetic attachment element **20084** disposed therein and configured to magnetically couple to a magnetic attachment interface **20042** disposed in a recess formed in an exterior surface of a mobile device case **20073**, and a plug **20028** with a magnetic attachment element **20088** disposed on a bottom surface thereof and configured for attachment to another magnetic attachment element **20090** disposed in a recess (not shown) formed in the bottom interior surface of the mobile device case **20073**. FIG. **20H** is a top perspective assembly view of an example accessory **20010** with a cap **20018** rotatably coupled to a base **20016** attached to a magnetic attachment interface **20042** configured for attachment to a mobile device **20012** with multiple magnetic attachment elements **20090** disposed therein.

(274) In various implementations, one or more attachment elements (e.g., elements **20084**, **20086**, **20088**) are attached to or disposed in or on a surface of one or more components of the accessory **20010** such as a base **20016**, a cap **20018**, a plug **20028**, an attachment interface **20042**, and an intermediate mounting pad, and are configured for coupling one or more components of the accessory **20010** together. In some implementations, one or more attachment elements (e.g., elements **20084**, **20086**, **20088**), are magnetic and configured for rotatably coupling the base **20016** and the cap **20018** together, as shown in FIGS. **20A** and **20D**. In other implementations, one or

more magnetic attachment elements (e.g., elements **20084**, **20086**, **20088**, **20090**) are configured for rotatably coupling the cap **20018** to one or more of the attachment interface **20042** and the mobile device **20012** housing, case **20073**, or cover thereof, as shown in FIGS. **20A-20D**. In other implementations, one or more attachment elements (e.g., element **20090**) are attached to or disposed in or on a surface of one or more of the mobile device **20012** housing, case **20073**, or cover thereof and may be configured to mechanically, magnetically, or adhesively engage with one or more of the supports **20020**, **20022** and/or other attachment elements attached to or disposed in or on a surface of one or more of the supports **20020**, **20022**, and may be configured to retain one or more of the supports **20020**, **20022** in a retracted position.

(275) One or more attachment elements may be substantially annular, circular, semi-circular, arc-shaped, disc-shaped, wedge-shaped, crescent-shaped, square, rectangular, or cylindrical, and disposed in one or more corresponding recesses formed in one or more of the base **20016**, the cap **20018**, the attachment interface **20042**, and the mobile device **20012** housing, case **20073**, or cover thereof. As shown in FIG. **20A**, multiple magnetic attachment elements (e.g., element **20084**) may be disposed in correspondingly shaped cap recesses **20056** arranged annularly around the inside of the cap **20018** and configured to attach to the magnetic attachment interface **20042** disposed in a corresponding recess **20040** formed in the bottom of the base **20016** circumscribing the first annular base protrusion **20036**. The first annular base protrusion **20036** may be disposed adjacent to the first annular cap protrusion **20044** and configured for limiting lateral movement of the cap **20018** and keeping the cap **20018** concentrically aligned with the base **20016** about a common axis of rotation. In some implementations, one or more magnetic attachment elements (e.g., element **20084**) are disposed in the cap **20018** between a first and second annular cap protrusion **20044**, **20048**, as shown in FIGS. **20A-20C**. In other implementations, one or more magnetic attachment elements (e.g., element **20084**) are disposed in the cap **20018** between the first and third **20044**, **20054** or second and third annular cap protrusions **20048**, **20054**, as shown in FIG. **20D**.

(276) One or more magnetic attachment elements (e.g., elements **20084**, **20086**, **20088**, **20090**) may have a shape and/or profile corresponding to an exterior or interior perimeter or surface of one or more of the base **20016**, the cap **20018**, the attachment interface **20042**, and the mobile device **20012** housing, case **20073**, or cover thereof. In some implementations, one or more magnetic attachment elements (e.g., elements **20084**, **20086**, **20088**) may be combined together to form a continuous shape, as shown in FIG. **20B**. In other implementations, one or more annular cap protrusions (e.g., protrusions **20044**, **20054**) disposed adjacent to a first annular base protrusion **20036** provide a mechanism for concentrically centering the magnetically coupled base **20016** and cap **20018** around a common axis of rotation **20034**, as shown in FIGS. **20A-20D**.

(277) In some implementations, the attachment interface **20042** is magnetic or includes one or more magnetic attachment elements (e.g., elements **20084**, **20086**, **20088**) attached to or disposed in or on a surface thereof, as shown in FIGS. **20A**, **20D**, and **20F-20H**. The attachment interface **20042** may be attached to or disposed in or on a surface of the mobile device **20012** housing, case **20073**, or cover thereof, and may be configured for attachment to one or more other attachment elements (e.g., elements **20084**, **20086**, **20088**) disposed in one or more of the cap **20018**, the base **20016**, and the plug **20028**, as shown in FIGS. **20A**, **20D**, and **20F-20H**. In some implementations one or both of the cap **20018** and the plug **20028** are configured to attach directly to the attachment interface **20042** and/or one or more attachment elements (e.g., element **20090**) disposed in the mobile device **20012** housing, case **20073**, or cover thereof without a base **20016** disposed in between, as shown in FIGS. **20F-20G**. In some implementations, the cap **20018** includes one or more magnetic attachment elements (e.g., elements **20084**, **20086**) disposed therein and configured to rotatably couple to a magnetic attachment interface **20042** adhesively attached to an exterior surface of the mobile device **20012** housing, case **20073**, or cover thereof, or in a recess formed in a surface thereof, as shown in FIGS. **20F-20G**. In some implementations, the attachment interface **20042** is wholly or partially received in a recess formed in the bottom of the cap **20018**. One or

move annular cap protrusions **20044**, **20048** disposed adjacent to an inner or outer perimeter of the attachment interface **20042** may keep the cap **20018** concentrically aligned with the attachment interface **20042** about the common axis of rotation **20034** and limit the cap **20018** from moving laterally with respect to the attachment interface **20044**. In some implementations, one or both of the cap **20018** and the plug **20028** substantially surround and conceal the attachment interface **20042**.

(278) One or more magnetic attachment elements (e.g., elements **20084**, **20086**, **20088**) attached to or disposed in the cap **20018** may be secured to the cap **20018** via friction fit, press fit, adhesive, or epoxy and may be encased in a protective plastic, silicone, or rubber encasement to protect the attachment elements from damage. In some implementations, one or more cap engagement features (e.g., feature **20046**) disposed on one or more annular cap protrusions (e.g., protrusion **20044**) are configured for engaging and retaining the attachment element in the cap **20018**. In other implementations, the base **20016** may be adhesively attached to the top of the magnetic attachment interface **20042**, the attachment interface **20042** configured to attach to one or more magnetic attachment elements (e.g., element **20090**) disposed in the mobile device **20012** housing, case **20073**, or cover thereof, as shown in FIG. **20H**.

(279) In some implementations, one or more magnetic attachment elements (e.g., element **20090**), are attached to or disposed in or on a surface of one or more of the mobile device **20012** housing, case **20073**, and cover thereof, and configured for attachment to one or more other magnetic attachment elements (e.g., elements **20084**, **20086**, **20088**) disposed in one or more of the attachment interface **20042**, the base **20016**, the cap **20018**, the plug **20028**, and supports **20020**, **20022**, as shown in FIG. **20F-20H**. One or more recesses may be formed in one or both of an interior and exterior surface of the mobile device **20012** housing, case **20073**, or cover thereof, and configured for receiving the attachment interface **20042** and/or one or more attachment elements (e.g., element **20090**), as shown in FIG. **20G**. In some implementations, one or more magnetic attachment elements (e.g., element **20090**) are disposed in a recess (not shown) formed in the interior of a mobile device case **20073** and configured for magnetically attaching to one or more other magnetic attachments element (e.g., element **20088**) attached to or disposed in or on a surface of one or more of the base **20016**, the cap **20018**, and the plug **20028**, as shown in FIG. **20G**. In some implementations, a substantially rigid or substantially flexible support (e.g., support **20164**) may be attached to or disposed in or on a surface of the attachment interface **20042** and/or attachment element (e.g., element **20088**), the support **20164** providing a user engagement for detaching one or both of the attachment interface **20042** and the attachment element (e.g., element **20088**) from one or more other attachment elements (e.g., element **20090**) or from the mobile device **20012** housing, case **20073**, or cover thereof, as shown in FIG. **20H**.

(280) One or more recesses or protrusions extending longitudinally from one or more surfaces of the attachment interface **20042**, the mobile device **20012** housing, case **20073**, or cover thereof, may be configured to engage with one or more annular protrusions disposed in one of the base **20016**, the cap **20018**, and the plug **20028** to concentrically align the components and limit their movement in a lateral direction as shown in FIGS. **20F-20H**. In some implementations, the attachment interface **20042** includes one or more recesses formed in the bottom surface thereof and configured for receiving one or more magnetic attachment elements (e.g., element **20086**), the magnetic attachment elements configured to magnetically attach to and correlate with one or more other magnetic attachment elements (e.g., element **20090**) disposed in the mobile device **20012** housing, case **20073**, or cover thereof, as shown in FIG. **20H**. In other implementations, one or more attachment elements (e.g., element **20084**) with a shape or profile generally conforming to an aperture **20030** formed in one of the base **20016** and the cap **20018** may be attached to or disposed in or on a surface of the attachment interface **20042**, and may protrude longitudinally from the top surface of the attachment interface **20042**, the inner and/or outer perimetric faces of the attachment element **20086** providing an engagement for limiting the lateral movement of one or more annular

protrusions disposed in one or both of the base **20016** and the cap **20018**, as shown in FIG. **20H**. In other implementations, the aperture **20030** formed in one of the base **20016** and the cap **20018** is enclosed on a bottom side and a magnetic attachment element may be disposed in the aperture **20030** on a top surface thereof, the attachment element configured to magnetically attach one of the base **20016** and the cap **20018** with one or more magnetic attachment elements (e.g., element **20090**) attached to or disposed in or on a surface of the mobile device **20012** housing, case **20073**, or cover thereof.

(281) In some implementations, a bearing **20175**, such as a ball bearing, roller bearing, ultra-thin bearing, race bearing, or turntable type bearing, is attached to or disposed in or around one or both of the cap **20018** and the base **20016**, or between the cap **20018** and the attachment interface **20042**, the bearing configured for facilitating smooth and continuous rotation between one or more components of the accessory **20010**, as shown in FIGS. **20E-20F**. In some implementations, the bearing **20175** is magnetic and configured for attachment to the magnetic attachment interface **20042** or one or more magnetic attachment elements disposed in one or both of the cap **20018** and the base **20016**. In other implementations, a low-friction element **20174** composed of a material like PTFE, nylon, or Teflon is disposed between two or more components of the accessory **20010**, such as the cap **20018** and the attachment interface **20042**, or between one or more magnetic attachment elements (e.g., element **20084**) and the attachment interface **20042**, the low-friction element **20174** configured for reducing rotational friction between two or more components of the accessory **20010**, as shown in FIG. **20G**. In other implementations, a portion of one or more components of the accessory **20010** may be covered with a low-friction coating.

(282) FIG. **21A** is a top perspective assembly view of an example accessory **21010** with a base **21016** substantially integrated into a mobile device case **21073** with a recess (not shown) formed in an interior surface of the case **21073** configured to receive one or more of an attachment interface, a protective cover **21070**, and an attachment element **21084**. FIG. **21B** is a top perspective view of a base **21016** substantially integrated into a mobile device cover **21176** with a first annular base protrusion extending longitudinally from an exterior surface of the cover **21176**. FIG. **21C** is a top perspective assembly view of an example accessory **21010** with a base **21016** having a shape and profile generally conforming with and configured for attachment to an exterior surface of a mobile device **21012**. FIG. **21D** is a top perspective view of an example accessory **21010** with a base **21016** configured for attachment to two sides of a mobile device **21012**. FIG. **21E** is a top perspective view of an example accessory **21010** with a base **21016** disposed on a surface of and attached around two opposite sides of a mobile device **21012**. FIG. **21F** is a top perspective view of an example accessory **21010** disposed on top of an example second mobile accessory **21178** configured for attachment to a surface of a mobile device **21012** housing, case **21073**, or cover **21176** thereof. FIG. **21G** is a top perspective sectional view of an example second mobile accessory **21178** with a recess formed in the top configured for receiving a portion of a base **21016**. FIG. **21H** is a top perspective sectional view of an example second mobile accessory **21178** with a bottom portion configured to attach to a corresponding base engagement feature disposed in one of a base **21016** and a mobile device **21012** housing, case **21073**, and cover **21176** thereof.

(283) As shown in FIGS. **21A-21E**, in various implementations, a base **21016** has a profile generally matching a portion of the profile of a mobile device **21012** and is configured to attach to one or more exterior surfaces of the mobile device **21012**. In other implementations, the base **21016** is substantially incorporated into one of the mobile device **21012** housing, case **21073**, and cover **21176** thereof, as shown in FIGS. **21A-21B**. In some implementations, one or more base engagement features **21038** extends radially inward or outward from an interior or exterior perimetric face of one or more annular base protrusions **21036** disposed in and extending longitudinally from a surface of one of the base **21016** and/or a mobile device **21012** housing, case **21073**, and cover **21176** thereof, as shown in FIGS. **21A-21B**.

(284) An aperture **21030** circumscribed by the first annular base protrusion **21036** may be formed

in the center of the base **21016** and may be enclosed on one side (e.g., see FIG. **21B**) or extend therethrough (e.g., see FIG. **21A**). A recess (not shown) formed in the bottom of the base **21016** and/or in an interior surface of one of the mobile device case **21073** and the mobile device cover **21176** may be configured for receiving and/or engaging one or more of a permanently or detachably attachable attachment interface (not shown), one or more attachment elements (e.g., element **21084**), and a protective cover **21070**. In some implementations, the protective cover **21070** is permanently attached to the interior surface of one of the base **21016**, the mobile device case **21073**, and the mobile device cover **21176** via thermoforming, welding, or adhesive and is configured to protect a surface of the mobile device **21012**. In other implementations one of the protective cover **21070** and one or more attachment elements (e.g., element **21084**) may be attached to the interior surface of one of the mobile device case **21073** and cover **21176** via the attachment interface. In some implementations, one or more attachment elements (e.g., element **21084**) disposed in the bottom of the base **21016** and/or an interior surface of one of the mobile device case **21073** and cover **21176** are magnetic or otherwise configured to provide a mechanism for attaching to one or more other attachment elements (e.g., element **21090**) disposed in one or more of a cap **21018**, a plug **21028**, or a mount (not shown), as shown in FIG. **21A**.

(285) As shown in FIG. **21B**, one or more magnetic attachment elements (e.g., element **21084**) may be attached to or embedded in one or more portions of a mobile device cover **21176** and configured for attachment to one or more other magnetic attachment elements disposed in one of the cap **21018** and the plug **21028**. In some implementations, the mobile device cover **21176** includes two substantially flat portions connected by a flexible hinged portion, as shown in FIG. **21B**. One substantially flat portion of the mobile device cover **21176** containing one or more magnetic attachment elements (e.g., element **21084**) may be folded back and placed adjacent to or in close proximity to one or more other magnetic attachment elements disposed in one of the cap **21018** and the plug **21028**, whereby a magnetic force is exerted between the magnetic elements sufficient to magnetically secure the folded cover portion to the accessory **21010**. In other implementations, a protrusion may be disposed on an exterior surface of a substantially flat portion of the mobile device cover **21176**, with the exterior perimeter of the protrusion configured to fit inside the aperture **21030** formed in the center of the accessory **21010**, the interior perimeter of the cap **21010** configured to retain the annular protrusion disposed in the cover **21176** by friction, interference fit, or snap fit. In other implementations, the protrusion extending from the exterior surface of the cover **21176** includes one or more attachment features or attachment elements (e.g., element **21084**) disposed in an outer surface thereof and may be configured to engage with one or more attachment features or attachment elements disposed in one of the base **21016** and the cap **21018**, or on an opposite side of the cover **21176**.

(286) In some implementations, the base **21016** has a shape generally conforming to one of the two largest surfaces of the mobile device **21012** and is configured to substantially cover and protect the surface of the mobile device **21012** from damage, as shown in FIG. **21C**. In some implementations, an attachment interface (not shown), such as an adhesive film, nano-suction pad, or sticky gel pad, having a profile generally matching the profile of the base **21016**, is disposed on a bottom surface of the base **21016** or disposed in a recess formed therein and configured for attachment to the mobile device **21012** housing, case **21073**, or cover **21176** thereof. In some implementations, the base **21016** is substantially flat and configured for attachment to a substantially flat surface of the mobile device **21012** housing, case **21073**, or cover **21176** thereof, as shown in FIG. **21C**. In other implementations, one or more portions of the base **21016** is configured to detachably attach to one or more edges or sides of the mobile device **21012**. One or more portions of the base **21016** may attach to the mobile device **21012** by snap fit or friction fit. In some implementations, the base **21016** is attached to two opposing sides of the mobile device **21012**, allowing the accessory **21010** to be secured to the mobile device **21012** at one or more predetermined positions, as shown in FIGS. **21D-21E**.

(287) In other implementations, the base **21016** is disposed in or configured for attachment to the top of a second mobile accessory **21178** such as a card case configured for storing one or more of a user's cards. The bottom of the second mobile accessory **21178** may be configured for attachment to one of the base **21016** and the mobile device **21012** housing, case **21073**, and cover **21176** thereof, and the top of the second mobile accessory **21178** may be configured for attachment to one of the attachment interface, the base **21016**, and the cap **21018**. Other examples of second mobile accessories **21178** include, but are not limited to, wallets, charging devices, batteries, scanners, cameras, spatial location beacons, and financial payment processors.

(288) In some implementations, a protrusion with a shape and profile generally conforming to the shape of the aperture **21030** formed in the center of the accessory **21010** extends longitudinally from the bottom of the second accessory **21178** and is configured to attach to one of the base **21016** and the cap **21018**, as shown in FIG. **21G**. In other implementations, a recess is disposed in the top surface of the second accessory **21178** and configured for substantially receiving a bottom portion of the base **21016**, as shown in FIG. **21G**. In other implementations, one or more recesses or apertures may be disposed in the top of the second mobile accessory **21178** and configured for receiving and engaging a portion of one or both of a first and second base components, (e.g., see first and second base components **16148**, **16150** in FIG. **16J**). In other implementations, one or more base engagement features (e.g., see feature **21038** in FIG. **21B**) extends radially inward or outward from an interior or exterior perimetric face of one or more annular base protrusions **21036** (e.g., see protrusion **21036** in FIG. **21B**) disposed in and extending longitudinally from the top of the second mobile accessory **21178** and are configured to attach to the cap **21018**. In other implementations, an attachment element may be attached to or disposed in or on a surface of the second mobile accessory **21178** and configured for attachment to one or more of the attachment interface, the base **21016**, the cap **21018**, the plug **21028**, and another attachment element. In other implementations, one or more portions of the cap **21018**, such as an annular cap protrusion **21044** and cap engagement feature **21046**, are disposed in the bottom of the second mobile accessory **21178** and configured for attaching to a portion of the base **21016**, such as the base engagement feature (e.g., see **21038** in FIG. **21B**), as shown in FIG. **21H**. In some implementations, one or both of the top and bottom exterior surfaces of the second mobile accessory **21178** are substantially flat. In other implementations, a recess is formed in the bottom of the second mobile accessory **21178** configured for substantially receiving one or more portions of the base **21016**, as shown in FIG. **21H**. Other recesses may be formed in the top, bottom, or sides of the second mobile accessory **21178** and configured for receiving and/or retaining one or more tools or common items of everyday personal conveyance such as a key or a pocket-knife, as shown in FIG. **21H**.

(289) FIG. **22A** is a top perspective view of a base **22016** with an opening **22180** formed in the bottom surface and extending through an interior and exterior perimetric face thereof. FIG. **22B** is a bottom perspective view of an attachment interface **22042** with two openings **22180** extending through an interior and exterior perimetric face thereof and attached to the bottom of a base. FIG. **22C** is a top perspective view of an intermediate mounting pad **22072** with an opening **22180** formed in and extending through an interior and exterior perimetric face thereof. FIG. **22D** is a top perspective view of a plug **22028** with a flexible support **22164** attached at one end. FIG. **22E** is a top perspective view of a plug **22028** disposed in a cap **22018** and configured with a flexible support **22164** extending outward through an opening **22180** (not shown) formed in the bottom of a base **22016**. FIG. **22F** is a top perspective assembly view of an electronic port **22184** connected to an electronic connector **22188** via a flexible cable **22186** and configured for connection with a second electronic port **22190** disposed in a plug **22028**. FIG. **22G** is a top perspective assembly view of an example accessory **22010** with an electronic port **22184** disposed in a base **22016** and configured for connection with a second electronic port **22190** (not shown) disposed in a plug **22028** with visual indicators **22192** disposed in a top surface thereof. FIG. **22H** is a top perspective view of an example accessory **22010** with an electronic connector **22188** disposed in the electronic

port of a mobile device **22012**, with a flexible cable **22186** connecting the electronic connector **22188** and a first electronic port **22184** (not shown) configured for attachment to a second electronic port **22190** (not shown) disposed in a plug **22028**.

(290) In some implementations, one or more openings **22180** formed in one or more of an intermediate mounting pad **22072**, an attachment interface **22042**, and a base **22016** and extending through a portion of the interior and exterior perimeters thereof are configured for receiving a portion of a substantially thin, flat, or flexible component, such as a portion of a plug removal feature (not shown, e.g., see **6074** in FIG. **6B**) or a support (e.g., **22164** in FIG. **22D**). In some implementations, one or more base openings **22180** are formed in the bottom of the base **22016** and extend through a portion of the interior and exterior perimeters thereof, as shown in FIG. **22A**. In other implementations, one or more openings **22180** are disposed in the attachment interface **22042** and extend through a portion of the interior and exterior perimeters thereof, as shown in FIG. **22B**. In other implementations one or more openings **22180** are disposed in the intermediate mounting pad **22072** and extend through a portion of the interior and exterior perimeters thereof, as shown in FIG. **22C**. One or more openings formed in one or more of the intermediate mounting pad **22072**, the attachment interface **22042**, and the base **22016** may extend into an aperture **22030** formed in the center of one of the intermediate mounting pad **22072**, the attachment interface **22042**, and the base **22016**.

(291) As shown in FIGS. **22D-22E**, one or more flexible supports (e.g., support **22164**) may be configured to pass through one or more openings **22180** formed in one of the intermediate mounting pad **22072**, the attachment interface **22042**, and the base **22016**. In some implementations, one or more flexible supports **22164** attached to one of the cap **22018** and a plug **22028** are configured to extend through one or more openings **22180** formed in one of the intermediate mounting pad **22072**, the attachment interface **22042**, and the base **22016**, and may be configured for engaging one or more of a user's fingers.

(292) As shown in FIGS. **22F-22H**, in other implementations, an electronic port (e.g., port **22184**) with a flexible cable **22186** extending therefrom is configured to pass through one or more openings **22180** formed in one or more of the intermediate mounting pad **22072**, the attachment interface **22042**, and the base **22016**. An electronic connector (e.g., connector **22188**) configured for connecting to an electronic port (not shown) disposed in a mobile device **22012** may be disposed on one distal end of the cable **22186** opposite the electronic port **22184**. The electronic port **22184**, cable **22186**, and electronic connector **22188** may be configured to transmit one or both of power and data between the mobile device **22012** and a second electronic port **22190** disposed in the plug **22028**. In some implementations, a flexible support is disposed on top of the cable **22186** and configured for receiving one or more of a user's fingers. In other implementations, the cable **22186** may function as a flexible support and be configured for receiving one or more of a user's fingers. In other implementations, an adhesive film, nano-suction pad, or sticky gel pad may be disposed on a bottom surface of one or both of the electronic port **22184** and cable **22186** and configured to adhere to a surface of the mobile device **22012** housing, case, or cover thereof, or an intermediate mounting pad **22072**. In other implementations, one or more of the electronic port **22184**, cable **22186**, and electronic connector **22188** are substantially integrated into or embedded in the mobile device **22012** housing, case, or cover thereof. In some implementations, one or more plugs **22028** configured with an electronic port **22190** include one or more LED indicators **22192** disposed in the top of the plug **22028** and configured to display information to a user related to one or both of power and data, as shown in FIGS. **22G-22H**.

(293) In some implementations, one or more magnetic elements are disposed in or around the electronic port **22184** and are configured for aligning with and attaching to one or more magnetic elements disposed in or around the second electronic port **22190** disposed in the plug **22028**. In some implementations, the plug **22028** includes a battery capable of charging one or more other batteries disposed in the mobile device **22012** through the second electronic port **22190**, first



electronic port **22184**, cable **22186**, and connector **22188**. In other implementations, the plug **22028** includes one or both of a solid-state data drive and data processor, capable of transmitting, storing, and/or processing data to and/or from the mobile device **22012**.

(294) FIG. **23A** is a top perspective view of a flexible support **23194** disposed in an intermediate mounting pad **23072**. FIG. **23B** is a top perspective view of a flexible support **23194** disposed in a base projection **23198**. FIG. **23C** is a top perspective view of a flexible support **23194** and a rotatable rigid support **23196** disposed in a base projection **23198**. FIG. **23D** is a top perspective view of a rotatable rigid support **23196** attached to a base projection **23198** by a hinge **23200**. FIG. **23E** is a top perspective view of a rotatable rigid support **23196** attached to a base projection **23198** by a hinge **23200**. FIG. **23F** is a top perspective view of a rotatable rigid support **23196** disposed in the bottom of a base **23016** and with a stop **23204** extending from one end of the support **23196** through an opening disposed in the bottom of the base **23016**, the stop **23204** configured to be received in a corresponding recess formed in the bottom of a plug **23028**. FIG. **23G** is a top perspective view of an example accessory **23010** and support retainer **23202** attached to a surface of a mobile device **23012**, the accessory including three rotatable rigid supports **23020**, **23022**, **23196**, extended in a deployed position. FIG. **23H** is a side view of an example accessory **23010** with three rotatable rigid supports **23020**, **23022**, **23196**, retracted in a retained position. FIG. **23I** is a top perspective view of an example accessory **23010** with three rotatable rigid supports **23020**, **23022**, **23196**, retracted in a retained position. FIG. **23J** is a front view of an example accessory **23010** with three rotatable rigid supports **23020**, **23022**, **23196**, retracted in a retained position. FIG. **23K** is a back view of an example accessory **23010** with three rotatable rigid supports **23020**, **23022**, **23196**, retracted in a retained position. FIG. **23L** is a bottom perspective view of an example accessory **23010** with three rotatable rigid supports **23020**, **23022**, **23196**, retracted in a retained position. FIG. **23M** is a top view of an example accessory **23010** with three rotatable rigid supports **23020**, **23022**, **23196**, retracted in a retained position. FIG. **23N** is a bottom view of an example accessory **23010** with three rotatable rigid supports **23020**, **23022**, **23196**, retracted in a retained position.

(295) In some implementations, one or more supports (e.g., supports **23194**, **23196**) are disposed in one or both of an intermediate mounting pad **23072** and a base **23016**. One or more supports (e.g., supports **23194**, **23196**) disposed in one of the intermediate mounting pad **23072** and the base **23016** may be substantially flexible or substantially rigid. In various implementations, one or more supports (e.g., supports **23194**, **23196**) disposed in one or both of the intermediate mounting pad **23072** and the base **23016** are configured for engaging one or more of a user's fingers, supporting a mobile device **23012** in a preferred display orientation, or mounting the accessory **23010** to one of a mount (not shown) and a mounting structure (not shown).

(296) In some implementations, one or more supports (e.g., support **23194**) are attached to the intermediate mounting pad **23072** as shown in FIG. **23A**. In other implementations, one or more supports (e.g., supports **23194**, **23196**) are disposed in the base **23016**, as shown in FIGS. **23B-23N**. In some implementations, the base **23016** includes a laterally extending base projection **23198** wherein one or more flexible and/or rigid supports (e.g., supports **23194**, **23196**) may be disposed. In some implementations, the base projection **23198** includes two slots (not shown) formed therethrough wherein each end of a flexible support (e.g., support **23194**) may be attached, as shown in FIG. **23B**. A recess (not shown) may be formed in the bottom of the base projection **23198** wherein a portion of the attached flexible support **23194** may be substantially received.

(297) In some implementations, a portion of the exterior perimeter of the base projection **23198** is configured to engage with an interior portion of the support (e.g., support **23196**) whereby the support **23196** may be disposed in retained position, as shown in FIG. **23C**. In some implementations, the support **23196** is rotatably attached to the base projection **23198** via a pair of support arbors (not shown), rotatably disposed in a pair of recesses (not shown) formed in the sides of the base projection **23198**, as shown in FIG. **23C**. In other implementations, one or more

supports are rotatably attached to the base projection **23198** via one or more fasteners (not shown). In other implementations, one or more substantially rigid supports (e.g., support **23196**) are rotatably connected to the base projection **23198** via a hinge **23200**, such as a living hinge, as shown in FIG. **23D**, or a pin hinge, as shown in FIG. **23E**. A distal portion of one or more supports (e.g., support **23196**) disposed in one of the intermediate mounting pad **23072** and the base **23016** may be beveled. In some implementations, a distal portion of one or more supports (e.g., supports **23194**, **23196**) disposed in one of the intermediate mounting pad **23072** and the base **23016** may extend beyond one end of the mobile device **23012** in order to facilitate user deployment.

(298) An aperture **23030** formed in one or more supports (e.g., supports **23194**, **23196**) and extending therethrough may be configured for receiving and engaging one or more of a user's fingers, as shown in FIGS. **23D-23G**. In some implementations, a support retainer **23202** is attached to the mobile device **23012** housing, case, or cover thereof, and has an exterior perimeter configured to engage with the aperture **23030** formed in the support (e.g., support **23196**) whereby the support **23196** may be disposed in a retained position, as shown in FIG. **23G**. In some implementations, the support retainer **23202** is magnetic or has one or more magnetic attachment elements disposed therein.

(299) In some implementations, one or more attachment elements **23088** such as a magnet or a hook-and-loop fastener may be attached to or disposed in or on a surface of the support retainer **23202** or disposed in a recess formed in a top or bottom side thereof. As shown in FIG. **23G**, one or more attachment elements **23090** may be attached to or disposed in or on a surface of one or more of the mobile device housing **23012**, case, and cover thereof, and may be configured to mechanically, magnetically, or adhesively engage with one or more other attachment elements **23086** attached to or disposed in or on a surface of one or more of the supports (e.g., supports **23020**, **23022**, **23196**) and may be configured to retain one or more of the supports **23020**, **23022**, **23194**, **23196** in a retracted position. The bottom of the support retainer **23202** may be attached to the mobile device **23012**, housing, case, or cover thereof via an attachment element, such as an adhesive film.

(300) In some implementations, one or more supports (e.g., support **23196**) may be detachably attached to the accessory **23010** and secured by a plug **23028**. A support stop **23204** disposed on one end of the support **23196** may be inserted through an opening (not shown, e.g., see **22180** in FIG. **22A**) formed in the bottom of the base **23016** and extending through an interior and exterior perimetric face thereof and wherein longitudinal movement of the support **23196** may be restricted. One end of the support stop **23204** may be configured for engagement in a corresponding recess disposed in the bottom of the plug **23028** whereby the support **23196** may be secured to the accessory **23010** and movement of the support **23196** may be restricted by at least one degree of freedom, as shown in FIG. **23F**. In some implementations, an exterior perimetric portion of the accessory **23010** (e.g., an exterior portion of supports **23020**, **23022**, or cap projections **23024**, **23026**) may limit one or more supports (e.g., support **23196**) rotatably disposed in one of the base **23016** and the intermediate mounting pad **23072** from rotating beyond a predetermined position, as shown in FIG. **23G**. In other implementations, one or more slidable, rotatable, stretchable, or extendable supports (e.g., supports **23194**, **23196**) attached to or disposed in one or more of the base **23016**, the cap **23018**, the plug **23028**, the intermediate mounting pad **23072**, the cap projections **23024**, **23026**, and the base projection **23198** are configured for engaging and restricting the movement of one or more other supports (e.g., supports **23020**, **23022**) attached to the accessory **23010** by at least one degree of freedom.

(301) FIG. **24** is a top perspective view of an example accessory **24010** with a base **24016** slidably disposed inside a base track **24206**. In some implementations, the base **24016** may be disposed in a base track **24206**, as shown in FIG. **24**. In some implementations, the base track **24206** is attached to the top of an intermediate mounting pad **24072**. An inner perimetric portion of the base track **24206** may be configured to engage with an outer perimetric portion of the base **24016**, restricting

the base **24016** from moving longitudinally while enabling the base **24016** to traverse linearly along a lateral axis parallel to the two longest edges of the base track **24206**. In some implementations the inner perimeter of the base track **24206** and the outer perimeter of the base **24016** are substantially rectangular. In other implementations, the inner perimeter of the base track **24206** and the outer perimeter of the base **24016** are substantially oblong. The inner perimeter of the base track **24206** and the outer perimeter of the base **24016** may have corresponding beveled edges and one or more interior or exterior corners of one or both of the base **24016** and the base track **24206** may be rounded. In some implementations, the base track **24206** is permanently attached to the intermediate mounting pad **24072** via an adhesive layer or welding. In other implementations, the base track **24206** is detachably attached to the intermediate mounting pad **24072** via one or more fasteners. One or more portions of the base track **24206** may be hinged or separably detachable from the rest of the base track **24206** in order to allow the base **24016** to be inserted into and removed from the base track **24206**.

(302) Although the invention has been discussed with reference to specific embodiments, it is apparent and should be understood that the concept can be otherwise embodied to achieve the advantages discussed. The preferred embodiments above have been described primarily as mobile device accessories for use with mobile devices such as mobile phones, however, the accessory may be used in conjunction with any mobile device capable of being held, operated, positioned, mounted, accessorized, or adapted. The foregoing description of the adaptive support accessory is presented for purposes of illustration and description. Furthermore, the description is not intended to limit the invention in any way to the form disclosed herein.

(303) Accordingly, variants and modifications consistent with the following teaching, skill, and knowledge of the relevant art are within the scope of the present invention. Moreover, the accessory may be used in applications other than those specifically directed toward what are commonly regarded as mobile devices, such as carrying water bottles, or mounting picture frames. The embodiments described herein are further intended to explain modes known for practicing the invention disclosed herewith and to enable others skilled in the art to utilize the invention in equivalent or alternative embodiments and with various modifications considered necessary by the particular application(s) or use(s) of the present invention. Furthermore, structural features of different embodiments may be combined in yet another embodiment without departing from the recited claims. Since many embodiments of the invention can be made without departing from the spirit and scope of the invention, the invention resides in the claims hereinafter appended.

## Claims

1. A mobile device accessory comprising: a structure comprising: a first protrusion extending longitudinally along an axis oriented perpendicular to an attachable surface of a mobile device; a second protrusion extending longitudinally along the axis and surrounding the first protrusion, and wherein the structure extends radially about the axis between the first and second protrusions defining one or more recesses; and an aperture formed in the structure centrally along the axis; and an attachment interface attached to the structure and configured to attach to the mobile device, the attachment interface comprising one or more annular or arc-shaped magnetic attachment elements arranged in a substantially annular shape and centered about the axis, the magnetic attachment elements configured to magnetically attach along the axis, and wherein the magnetic attachment elements are enclosed in the structure within one or more of the recesses.
2. The mobile device accessory of claim 1, wherein the magnetic attachment elements comprise one or more magnets.
3. The mobile device accessory of claim 2, wherein the magnets are configured to magnetically attach the structure to the mobile device, and wherein one or both of the magnets and the structure are configured to rotatably couple to the mobile device.

4. The mobile device accessory of claim 3, wherein the magnetic attachment elements comprise a plurality of annular, arc-shaped, or wedge-shaped magnets.
5. The mobile device accessory of claim 2, further comprising: one or more ferrous, metallic, magnetic, plastic, or adhesive attachment elements attached to the accessory and disposed concentrically with the magnets.
6. The mobile device accessory of claim 1, wherein one or both of the structure and the magnetic attachment elements are configured to attach around a perimeter of a predetermined area configured for inductively charging the mobile device.
7. The mobile device accessory of claim 1, further comprising: one or more supports configured to engage one or more of a user's fingers, a mount, a mounting structure, and a support surface to selectively position the mobile device.
8. The mobile device accessory of claim 7, wherein one or more of the supports comprise one or more of a ring, an arc, an annulus, a strap, a cord, a band, a loop, a tab, a disc, a prop, a plug, a lanyard, a selfie stick, a handle, a kickstand, an extendable socket grip, and an expandable grip or knob.
9. The mobile device accessory of claim 1, wherein one or both of the first and second protrusions and one or more of the recesses have a substantially circular, annular, or arcuate shape.
10. The mobile device accessory of claim 1, wherein the aperture defines an interior perimetric face of the structure, and wherein the interior perimetric face provides one or more engagement or attachment features configured for engaging or attaching one or more of a user's fingers, a plug, a cap, a base, an attachment element, an attachment feature, an accessory cover, a support, a mount, or a mounting structure.
11. The mobile device accessory of claim 1, wherein the aperture extends partially or fully through the structure and defines a non-magnetized region of the structure.
12. The mobile device accessory of claim 1, wherein the magnetic attachment elements comprise a first magnetic array, the accessory further comprising: a second magnetic array of one or more magnetic attachment elements disposed around a perimeter of the first magnetic array.
13. The mobile device accessory of claim 12, wherein one or both of the first and second magnetic arrays comprise a plurality of magnetic attachment elements disposed at angular intervals about the axis.
14. The mobile device accessory of claim 12, wherein the magnetic attachment elements of the first and second magnetic arrays are arranged concentrically about the axis in a substantially annular shape, and wherein the magnetic arrays are separated by a non-magnetic region disposed therebetween.
15. The mobile device accessory of claim 12, wherein one or both of the first and second magnetic arrays comprise one or more correlated or programmed magnets incorporating one or more multi-pole arrays having a programmed pattern of polarity and magnetic field strength.
16. The mobile device accessory of claim 12, wherein two or more magnetic attachment elements of the second magnetic array are disposed parallel about the axis.
17. The mobile device accessory of claim 12, wherein two or more magnetic attachment elements of one or both of the first and second magnetic arrays are combinable together and form a continuous shape.
18. The mobile device accessory of claim 12, wherein one or more magnetic attachment elements of the first and second magnetic arrays are combinable together and form a continuous shape.
19. The mobile device accessory of claim 12, wherein one or more magnetic attachment elements of the second magnetic array are configured to magnetically attach to one or more corresponding magnetic attachment elements disposed within or on a surface of one of a case, a cover, or a housing for the mobile device, and wherein one or both of the second magnetic array and the corresponding magnetic attachment elements comprise one or more magnets.
20. The mobile device accessory of claim 1, wherein one or more of the magnetic attachment

elements disposed within the structure are configured to coaxially align with and magnetically attach to one or more corresponding magnetic attachment elements disposed within or on a surface of one of a case, a cover, or a housing for the mobile device, and wherein one or both of the magnetic attachment elements and the corresponding magnetic attachment elements comprise one or more magnets.

21. The mobile device accessory of claim 1, wherein the structure is a first component, the accessory further comprising: a second component comprising one of a base, a cap, a plug, a mount, an accessory cover, a protective cover, an intermediate mounting pad, or a support.

22. The mobile device accessory of claim 21, wherein the first and second components are rotatably attachable.

23. The mobile device accessory of claim 21, wherein the first and second components are magnetically attachable.

24. The mobile device accessory of claim 21, wherein the first and second components are configured to selectively engage and disengage or detachably attach.

25. The mobile device accessory of claim 21, wherein the second component is configured to attach within the aperture, or within one or more of the recesses, other recesses, openings, or slots formed in the first component.

26. The mobile device accessory of claim 21, wherein the second component is configured to attach around, across, through, or between one or both of the first and second protrusions of the first component.

27. The mobile device accessory of claim 21, further comprising: one or more engagement or attachment features disposed in or attachable to one or both of the first and second components and configured to engage or attach two or more accessory components, a second accessory, a mount, or a mounting structure.

28. The mobile device accessory of claim 21, further comprising: one or more attachment elements disposed in or attachable to one or both of the first and second components and configured to engage or attach two or more accessory components, a second accessory, or a mounting structure.

29. The mobile device accessory of claim 1, further comprising: one or more projections attached to or extending from the accessory and providing an attachment to one or more attachment features, attachment elements, or supports.

30. The mobile device accessory of claim 1, further comprising: one or more engagement or attachment features disposed in or attachable to the accessory and configured to engage or attach two or more accessory components, a second accessory, a mount, or a mounting structure, wherein the engagement or attachment features comprise one or more of a fastener, a snap-fit joint, a spring clip, a snap ring, a twist lock, a slide lock, a slot, another recess, an opening, a detent, a projection, and a protrusion.

31. The mobile device accessory of claim 1, further comprising: one or more attachment elements disposed in or attachable to the accessory and configured to engage or attach two or more accessory components, a second accessory, a mount, or a mounting structure, wherein the attachment elements comprise one or more of a nano-suction or sticky gel pad, a magnet, a two-part interlocking fastener, a bearing, a low friction washer, a spacer, and an adhesive.

32. The mobile device accessory of claim 1, wherein the accessory is configured to attach to, disposed in, or is substantially incorporated into a second accessory, wherein the second accessory comprises one or more of a case, a cover, a wallet, a charging device, a battery, a scanner, a camera, a spatial location beacon, and a payment processor.

33. The mobile device accessory of claim 1, wherein the accessory is configured to attach to, shaped as, disposed in, or substantially incorporated into a case or a cover for the mobile device.

34. The mobile device accessory of claim 1, wherein the accessory is configured to attach to, shaped as, disposed in, or substantially incorporated into one of a card case and a wallet attachable to the mobile device.

35. The mobile device accessory of claim 1, wherein one or both of the structure and the aperture have a shape that is substantially circular, annular, oblong, oval, triangular, square, rectangular, hexagonal, polygonal, or heart-shaped.

36. A mobile device accessory comprising: a structure comprising: a first protrusion extending longitudinally along an axis oriented perpendicular to an attachable surface of a mobile device; a second protrusion extending longitudinally along the axis and surrounding the first protrusion, and wherein the structure extends radially about the axis between the first and second protrusions defining one or more recesses; and an aperture formed in the structure along the axis; and an attachment interface attached to the structure and configured to attach to the mobile device, the attachment interface comprising a plurality of arc-shaped magnets arranged in a substantially annular shape and centered about the axis, the magnets configured to attach along the axis, and wherein the magnets are enclosed in the structure within one or more of the recesses.

37. The mobile device accessory of claim 36, wherein two or more of the magnets are combinable together and form a continuous shape.

38. The mobile device accessory of claim 36, further comprising: one or more supports configured to engage one or more of a user's fingers, a mount, a mounting structure, and a support surface to selectively position the mobile device.

39. The mobile device accessory of claim 38, wherein the supports comprise one or more of a ring, an arc, an annulus, a strap, a cord, a band, a loop, a tab, a disc, a prop, a plug, a lanyard, a selfie stick, a tripod, a handle, a kickstand, an extendable socket grip, and an expandable grip or knob.

40. The mobile device accessory of claim 38, wherein one or more of the supports is movable between a position proximal to one or both of the accessory and the mobile device and a position distal from one or both of the accessory and the mobile device.

41. The mobile device accessory of claim 38, wherein one or more of the supports are configured to attach around, across, through, or between one or both of the first and second protrusions, within the aperture, or within one or more of the recesses, other recesses, openings, or slots formed in the accessory.

42. The mobile device accessory of claim 38, wherein one or more of the supports are configured to attach to the accessory by one or more fasteners, pins, screws, bolts, rivets, dowels, rods, arbors, bearings, hinges, adhesives, magnets, attachment elements, or attachment features.

43. The mobile device accessory of claim 38, wherein one or more of the supports are configured to rotatably or detachably attach to the accessory.

44. The mobile device accessory of claim 38, wherein one or more of the supports are configured to rotate, pivot, slide, flex, stretch, retract, extend, or collapse.

45. The mobile device accessory of claim 38, wherein one or more of the supports comprise one or more of a ring, an arc, and an annulus.

46. The mobile device accessory of claim 38, wherein one or more of the supports comprise one or more of a band, a loop, a cord, a strap, a kickstand, a prop, and a projection.

47. The mobile device accessory of claim 38, wherein one or more of the supports comprise an extendable socket grip or an expandable grip or knob.

48. The mobile device accessory of claim 36, wherein the magnets are configured to axially align with and magnetically attach to one or more corresponding magnetic attachment elements disposed in or on a surface of one of a case, a cover, or a housing for the mobile device.

49. The mobile device accessory of claim 36, wherein an interior perimetric face of the structure surrounding the aperture provides one or more engagement or attachment features configured for engaging one or more of a user's fingers or attaching a second accessory component or second mobile accessory to the mobile device.

50. The mobile device accessory of claim 36, wherein the magnets are configured to attach around a perimeter of a predetermined area of the mobile device configured for the transfer of one or both of power and data.

51. The mobile device accessory of claim 36, further comprising: one or more ferrous, metallic, magnetic, plastic, or adhesive attachment elements attached to the accessory and disposed concentrically with the magnets about the axis.
52. The mobile device accessory of claim 36, further comprising: one or more magnets disposed around a perimeter of the arc-shaped magnets.
53. The mobile device accessory of claim 36, further comprising: one or more engagement or attachment features disposed in or attachable to the accessory and configured to engage or attach two or more accessory components, a second accessory, a mount, or a mounting structure, wherein the engagement or attachment features comprise one or more of a fastener, a snap-fit joint, a spring clip, a snap ring, a twist lock, a slide lock, a slot, another recess, an opening, a detent, a projection, and a protrusion.
54. The mobile device accessory of claim 36, further comprising: one or more attachment elements disposed in or attachable to the accessory and configured to engage or attach two or more accessory components, a second accessory, a mount, or a mounting structure, wherein the attachment elements comprise one or more of a nano-suction or sticky gel pad, a magnet, a two-part interlocking fastener, a bearing, a low friction spacer, a washer, or an adhesive.
55. The mobile device accessory of claim 36, further comprising: a plug configured to attach to the accessory within the aperture, wherein the plug adds one or more of a storage device, a charging device, a battery, a communication device, a radio, a meter, a stand, a tool, a personal care item, an electronic accessory, a control device, a sensor, a recording device, an optical device, a container, a toy, a game, a mount, a support, an accessory cover, an attachment element, and an attachment feature to the accessory.
56. The mobile device accessory of claim 36, wherein one or both of the structure and the aperture have a shape that is substantially circular, annular, oblong, oval, triangular, square, rectangular, hexagonal, polygonal, or heart-shaped.
57. The mobile device accessory of claim 36, wherein the accessory is configured to attach to, shaped as, disposed in, or substantially incorporated into a protective case or a cover attachable to the mobile device.
58. The mobile device accessory of claim 36, wherein the accessory is configured to attach to, shaped as, disposed in, or substantially incorporated into a card case or a wallet attachable to the mobile device.
59. The mobile device accessory of claim 36, wherein one or more of the magnets comprise correlated or programmed magnets incorporating one or more multi-pole arrays.
60. The mobile device accessory of claim 36, further comprising: one or more projections attached to or extending from the accessory and providing an attachment to one or more attachment elements, attachment features, or supports.
61. A mobile device accessory comprising: a structure comprising: a first protrusion extending longitudinally along an axis oriented perpendicular to an attachable surface of a mobile device; a second protrusion extending longitudinally along the axis and surrounding the first protrusion, and wherein the structure extends radially about the axis between the first and second protrusions defining a recess; and an aperture formed in the structure centrally along the axis, wherein an interior perimetric face of the structure surrounding the aperture provides one or more engagement or attachment features configured for engaging one or more of a user's fingers or attaching a second accessory component or second mobile accessory to the mobile device; and an attachment interface attached to the structure and configured to attach to the mobile device, the attachment interface comprising one or more annular or arc-shaped attachment elements arranged in a substantially annular shape and centered about the axis, wherein one or both of the structure and the attachment elements are configured to attach around a perimeter of a predetermined area configured for inductively charging the mobile device.
62. The mobile device accessory of claim 61, further comprising: one or more attachment elements

or attachment features disposed around, across, through, or between one or both of the first and second protrusions and configured to engage or attach two or more accessory components, a second accessory, a mount, or a mounting structure.

63. The mobile device accessory of claim 61, further comprising: one or more supports configured to engage one or more of a user's fingers, a mount, a mounting structure, and a support surface to selectively position the mobile device.

64. The mobile device accessory of claim 63, wherein the supports comprise one or more of a ring, an arc, an annulus, a strap, a cord, a band, a loop, a tab, a disc, a prop, a plug, a lanyard, a selfie stick, a tripod, a handle, a kickstand, an extendable socket grip, and an expandable grip or knob.

65. The mobile device accessory of claim 61, further comprising: one or more projections attached to or extending from the accessory and providing an attachment to one or more attachment elements, attachment features, or supports.

66. The mobile device accessory of claim 61, wherein the aperture extends partially or fully through the structure.

67. The mobile device accessory of claim 61, wherein one or both of the structure and the aperture are substantially circular, annular, oblong, oval, triangular, square, rectangular, hexagonal, polygonal, or heart-shaped.

68. The mobile device accessory of claim 61, wherein one or more of the attachment elements are magnetic and configured to magnetically attach along or about the axis.

69. The mobile device accessory of claim 68, wherein one or more of the magnetic attachment elements disposed in the accessory are configured to axially align with and magnetically attach to one or more corresponding magnetic attachment elements disposed in or on a surface of one of a case, a cover, or a housing for the mobile device.

70. The mobile device accessory of claim 61, wherein the structure and the attachment interface are a first component, the accessory further comprising: a second component configured to adhesively, magnetically, permanently, detachably, selectively, or rotatably attach to the first component.

71. The mobile device accessory of claim 70, wherein the first component comprises one of a base, a cap, or a plug, and the second component comprises one or more of a base, a cap, a plug, a mount, an accessory cover, a protective cover, an intermediate mounting pad, and a support.

72. The mobile device accessory of claim 71, further comprising: one or more supports attachable to one or both of the first and the second components, the supports configured to engage one or more of a user's fingers, a mount, a mounting structure, and a support surface to selectively position the mobile device, and wherein the supports comprise one or more of a ring, an arc, an annulus, a strap, a cord, a band, a loop, a tab, a disc, a prop, a plug, a lanyard, a selfie stick, a tripod, a handle, a kickstand, an extendable socket grip, and an expandable grip or knob.

73. The mobile device accessory of claim 70, wherein the first component comprises one of a case, a cover, a card case, and a wallet for the mobile device, and the second component comprises one or more of a base, a cap, a plug, a mount, an accessory cover, a protective cover, an intermediate mounting pad, and a support.

74. The mobile device accessory of claim 61, wherein the first protrusion circumscribes the aperture and defines the interior perimetric face of the structure, and wherein the engagement or attachment features comprise one or more of a fastener, a snap joint, a spring clip, a snap ring, a twist lock, a slide lock, a slot, a feature another recess, an opening, a detent, a projection, or a protrusion.

75. The mobile device accessory of claim 61, further comprising: one or more magnetic attachment elements disposed around a perimeter of the annular or arc-shaped attachment elements.

76. A mobile device accessory comprising: a structure comprising: a first protrusion extending longitudinally along an axis oriented perpendicular to an attachable surface of a mobile device; and a second protrusion extending longitudinally along the axis and surrounding the first protrusion, and wherein the structure extends radially about the axis between the first and second protrusions



defining one or more recesses; and an attachment interface attached to the structure and configured to attach to the mobile device, the attachment interface comprising one or more annular or arc-shaped magnets arranged in a substantially annular shape and centered about the axis, the magnets configured to magnetically attach along the axis, and wherein the magnets are enclosed in the structure within one or more of the recesses.

77. The mobile device accessory of claim 76, wherein the attachment interface comprises a plurality of annular, arcuate, or wedge-shaped magnets.

78. The mobile device accessory of claim 76, wherein the magnets are configured to attach around a predetermined area configured for inductively charging the mobile device.

79. The mobile device accessory of claim 76, wherein the magnets comprise one or more correlated or programmed magnets incorporating one or more multi-pole arrays.

80. The mobile device accessory of claim 76, wherein the accessory is configured to attach to, shaped as, disposed in, or substantially incorporated into one or more of a case, a cover, a card case, and a wallet attachable to the mobile device.

81. The mobile device accessory of claim 80, further comprising: one or more magnets disposed around a perimeter of the annular or arc-shaped magnets.

82. The mobile device accessory of claim 76, further comprising: one or more magnets disposed around a perimeter of the annular or arc-shaped magnets and configured to align one or more accessory components or a second mobile accessory in a select rotational position relative to the mobile device.

83. The mobile device accessory of claim 76, wherein the accessory has a shape that is substantially circular, annular, oblong, oval, triangular, square, rectangular, hexagonal, polygonal, or heart-shaped.

84. The mobile device accessory of claim 76, further comprising: one or more supports configured to engage one or more of a user's fingers, a mount, a mounting structure, and a support surface to selectively position the mobile device.

85. A mobile device accessory comprising: a structure comprising: a first protrusion extending longitudinally along an axis oriented perpendicular to an attachable surface of a mobile device; and a second protrusion extending longitudinally along the axis and surrounding the first protrusion, and wherein the structure extends radially about the axis between the first and second protrusions defining one or more recesses; an attachment interface attached to the structure and configured to attach to the mobile device, the attachment interface comprising one or more annular or arc-shaped magnets arranged in a substantially annular shape and centered about the axis, the magnets configured to magnetically attach along the axis, wherein the magnets are enclosed in the structure within one or more of the recesses; and one or more supports attached to the structure and configured to engage one or more of a user's fingers, a mount, a mounting structure, and a support surface to selectively position the mobile device.

---