

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12385654
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	LePoudre; Philip Paul et al.

Systems and methods for managing conditions in enclosed space

Abstract

A conditioning system includes a first plenum and a second plenum. The second plenum receives heated air from an enclosed space and supplies cooled air to the space. The system also includes a first liquid-to-air membrane energy exchanger (LAMEE1) arranged inside the first plenum. LAMEE1 is configured to use a liquid desiccant to lower an enthalpy of the first air stream. A LAMEE2 is arranged inside the first plenum downstream of LAMEE1. LAMEE2 is configured to use the first air stream to evaporatively cool water flowing through LAMEE2. A first LAHX (LAHX1) is arranged inside the second plenum. LAHX1 is configured to directly and sensibly cool the second air stream using a first cooling fluid. A second LAHX (LAHX2) is in fluid communication with LAMEE1 and is configured to receive the liquid desiccant from LAMEE1 and cool the liquid desiccant using outdoor air.

Inventors:	LePoudre; Philip Paul (Saskatoon, CA), Gerber; Manfred (Saskatoon, CA)
Applicant:	Nortek Air Solutions, Canada, Inc. (N/A, N/A)
Family ID:	63856165
Assignee:	Nortek Air Solutions Canada, Inc. (Saskatoon, CA)
Appl. No.:	16/606673
Filed (or PCT Filed):	April 18, 2017
PCT No.:	PCT/CA2017/050478
PCT Pub. No.:	WO2018/191805
PCT Pub. Date:	October 25, 2018

Prior Publication Data

Document Identifier	Publication Date
----------------------------	-------------------------

Publication Classification**Int. Cl.:** F24F3/14 (20060101); F24F5/00 (20060101); F24F12/00 (20060101)**U.S. Cl.:****CPC** F24F3/1417 (20130101); F24F5/0035 (20130101); F24F12/002 (20130101);**Field of Classification Search****CPC:** F24F (3/1417); F24F (5/0035); F24F (12/002); F25B (17/02)

References Cited**U.S. PATENT DOCUMENTS**

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
1015831	12/1911	Pielock et al.	N/A	N/A
2186844	12/1939	Smith	N/A	N/A
2214880	12/1939	Crawford	N/A	N/A
2290465	12/1941	Crawford et al.	N/A	N/A
2562811	12/1950	Muffly	N/A	N/A
2852090	12/1957	Kelley	N/A	N/A
2946201	12/1959	Munters	N/A	N/A
2968165	12/1960	Norback	N/A	N/A
3009684	12/1960	Munters	N/A	N/A
3018231	12/1961	Valentine et al.	N/A	N/A
3144901	12/1963	Meek	N/A	N/A
3247679	12/1965	Meckler	N/A	N/A
3291206	12/1965	Nicholson	N/A	N/A
3401530	12/1967	Meckler	N/A	N/A
3467072	12/1968	Toesca	N/A	N/A
3735559	12/1972	Salemme	N/A	N/A
3820353	12/1973	Shiraishi et al.	N/A	N/A
3905205	12/1974	Zusmanovich	N/A	N/A
4011731	12/1976	Meckler	N/A	N/A
4113004	12/1977	Rush et al.	N/A	N/A
4171620	12/1978	Turner	N/A	N/A
4180985	12/1979	Northrup, Jr.	N/A	N/A
4233796	12/1979	Mazzoni et al.	N/A	N/A
4235081	12/1979	Dowling	N/A	N/A
4257169	12/1980	Pierce	N/A	N/A
4259849	12/1980	Griffiths	N/A	N/A
4373347	12/1982	Howell et al.	N/A	N/A
4380910	12/1982	Hood	62/91	F24F 1/0007
4430864	12/1983	Mathiprakasam	N/A	N/A
4434845	12/1983	Steeb	N/A	N/A

4474021	12/1983	Harband	N/A	N/A
4532347	12/1984	Vaughan	N/A	N/A
4538426	12/1984	Bock	N/A	N/A
4594860	12/1985	Coellner et al.	N/A	N/A
4691530	12/1986	Meckler	N/A	N/A
4700550	12/1986	Rhodes	N/A	N/A
4719761	12/1987	Cromer	N/A	N/A
4723417	12/1987	Meckler	N/A	N/A
4729428	12/1987	Yasutake et al.	N/A	N/A
4729774	12/1987	Cohen et al.	N/A	N/A
4805317	12/1988	Inglis et al.	N/A	N/A
4841733	12/1988	Dussault et al.	N/A	N/A
4887438	12/1988	Meckler	N/A	N/A
4900448	12/1989	Bonne et al.	N/A	N/A
4905479	12/1989	Wilkinson	N/A	N/A
4909810	12/1989	Nakao et al.	N/A	N/A
4930322	12/1989	Ashley et al.	N/A	N/A
4936107	12/1989	Kitagaki et al.	N/A	N/A
4939906	12/1989	Spatz et al.	N/A	N/A
4941324	12/1989	Peterson et al.	N/A	N/A
4982575	12/1990	Besik	N/A	N/A
5003961	12/1990	Besik	N/A	N/A
5020334	12/1990	Wilkinson	N/A	N/A
5020335	12/1990	Albers et al.	N/A	N/A
5022241	12/1990	Wilkinson	N/A	N/A
5076065	12/1990	Brogan	N/A	N/A
5120445	12/1991	Colman	N/A	N/A
5131238	12/1991	Meckler	N/A	N/A
5148374	12/1991	Coellner	N/A	N/A
5170633	12/1991	Kaplan	N/A	N/A
5176005	12/1992	Kaplan	N/A	N/A
5181387	12/1992	Meckler	N/A	N/A
5191771	12/1992	Meckler	N/A	N/A
5203161	12/1992	Lehto	N/A	N/A
5206002	12/1992	Skelley et al.	N/A	N/A
5297398	12/1993	Meckler	N/A	N/A
5311929	12/1993	Verret	N/A	N/A
5325676	12/1993	Meckler	N/A	N/A
5337574	12/1993	Dick	N/A	N/A
5351497	12/1993	Lowenstein	N/A	N/A
5353606	12/1993	Yoho et al.	N/A	N/A
5373704	12/1993	Mcfadden	N/A	N/A
5387376	12/1994	Gasser	N/A	N/A
5448895	12/1994	Coellner et al.	N/A	N/A
5460004	12/1994	Tsimerman	N/A	N/A
5471852	12/1994	Meckler	N/A	N/A
5482625	12/1995	Shimizu et al.	N/A	N/A
5496397	12/1995	Fischer et al.	N/A	N/A
5502975	12/1995	Brickley et al.	N/A	N/A
5517828	12/1995	Calton et al.	N/A	N/A

5526651	12/1995	Worek et al.	N/A	N/A
5536405	12/1995	Myrna et al.	N/A	N/A
5542968	12/1995	Belding et al.	N/A	N/A
5551245	12/1995	Calton et al.	N/A	N/A
5564281	12/1995	Calton et al.	N/A	N/A
5579647	12/1995	Calton et al.	N/A	N/A
5580369	12/1995	Belding et al.	N/A	N/A
5632954	12/1996	Coellner et al.	N/A	N/A
5638900	12/1996	Lowenstein et al.	N/A	N/A
5649428	12/1996	Calton et al.	N/A	N/A
5650221	12/1996	Belding et al.	N/A	N/A
5653115	12/1996	Brickley et al.	N/A	N/A
5660048	12/1996	Belding et al.	N/A	N/A
5661983	12/1996	Groten et al.	N/A	N/A
5685897	12/1996	Belding et al.	N/A	N/A
5701762	12/1996	Akamatsu et al.	N/A	N/A
5718286	12/1997	Damsohn et al.	N/A	N/A
5727394	12/1997	Belding et al.	N/A	N/A
5732562	12/1997	Moratalla	N/A	N/A
5749230	12/1997	Coellner et al.	N/A	N/A
5758508	12/1997	Belding et al.	N/A	N/A
5758511	12/1997	Yoho et al.	N/A	N/A
5761915	12/1997	Rao	N/A	N/A
5761923	12/1997	Maeda	N/A	N/A
5791153	12/1997	Belding et al.	N/A	N/A
5791157	12/1997	Maeda	N/A	N/A
5816065	12/1997	Maeda	N/A	N/A
5825641	12/1997	Mangtani	N/A	N/A
5826434	12/1997	Belding et al.	N/A	N/A
5826641	12/1997	Bierwirth et al.	N/A	N/A
5832736	12/1997	Yoshioka et al.	N/A	N/A
5860284	12/1998	Goland et al.	N/A	N/A
5890372	12/1998	Belding et al.	N/A	N/A
5911273	12/1998	Brenner et al.	N/A	N/A
5931016	12/1998	Yoho	N/A	N/A
5943874	12/1998	Maeda	N/A	N/A
5946931	12/1998	Lomax et al.	N/A	N/A
5950447	12/1998	Maeda et al.	N/A	N/A
5992160	12/1998	Bussjager et al.	N/A	N/A
6003327	12/1998	Belding et al.	N/A	N/A
6018953	12/1999	Belding et al.	N/A	N/A
6018954	12/1999	Assaf	N/A	N/A
6029462	12/1999	Denniston	N/A	N/A
6029467	12/1999	Moratalla	N/A	N/A
6050100	12/1999	Belding et al.	N/A	N/A
6079481	12/1999	Lowenstein et al.	N/A	N/A
6094835	12/1999	Cromer	N/A	N/A
6138470	12/1999	Potnis et al.	N/A	N/A
6141979	12/1999	Dunlap	N/A	N/A
6145588	12/1999	Martin et al.	N/A	N/A

6156102	12/1999	Conrad et al.	N/A	N/A
6176101	12/2000	Lowenstein	N/A	N/A
6176305	12/2000	Haglid	N/A	N/A
6178762	12/2000	Flax	N/A	N/A
6199388	12/2000	Fischer	N/A	N/A
6199392	12/2000	Maeda	N/A	N/A
6237354	12/2000	Cromer	N/A	N/A
6269650	12/2000	Shaw	N/A	N/A
6318106	12/2000	Maeda	N/A	N/A
RE37464	12/2000	Meckler	N/A	N/A
6363218	12/2001	Lowenstein et al.	N/A	N/A
6412295	12/2001	Weiss et al.	N/A	N/A
6442951	12/2001	Maeda et al.	N/A	N/A
6494053	12/2001	Forkosh	N/A	N/A
6497107	12/2001	Maisotsenko et al.	N/A	N/A
6532763	12/2002	Gupte	N/A	N/A
6546746	12/2002	Forkosh et al.	N/A	N/A
6568466	12/2002	Lowenstein et al.	N/A	N/A
6575228	12/2002	Ragland et al.	N/A	N/A
6598862	12/2002	Merrill et al.	N/A	N/A
6635104	12/2002	Komkova et al.	N/A	N/A
6644059	12/2002	Maeda et al.	N/A	N/A
6684649	12/2003	Thompson	N/A	N/A
6709492	12/2003	Spadaccini et al.	N/A	N/A
6720990	12/2003	Walker et al.	N/A	N/A
6739142	12/2003	Korin	N/A	N/A
6745826	12/2003	Lowenstein et al.	N/A	N/A
6751964	12/2003	Fischer	N/A	N/A
6800118	12/2003	Kusunose et al.	N/A	N/A
6841601	12/2004	Serpico et al.	N/A	N/A
6848265	12/2004	Lowenstein et al.	N/A	N/A
6854278	12/2004	Maisotsenko et al.	N/A	N/A
6864005	12/2004	Mossman	N/A	N/A
6935416	12/2004	Tsunoda et al.	N/A	N/A
6973795	12/2004	Moffitt	N/A	N/A
6976365	12/2004	Forkosh et al.	N/A	N/A
6978633	12/2004	Yamazaki	N/A	N/A
7000427	12/2005	Mathias et al.	N/A	N/A
7017356	12/2005	Moffitt	N/A	N/A
7092006	12/2005	Walker et al.	N/A	N/A
7093452	12/2005	Chee et al.	N/A	N/A
7093649	12/2005	Dawson	N/A	N/A
RE39288	12/2005	Assaf	N/A	N/A
7178355	12/2006	Moffitt	N/A	N/A
7181918	12/2006	Reinders et al.	N/A	N/A
7231967	12/2006	Haglid	N/A	N/A
7251945	12/2006	Tongue	N/A	N/A
7269966	12/2006	Lowenstein et al.	N/A	N/A
7306650	12/2006	Slayzak et al.	N/A	N/A
7331376	12/2007	Gagnon et al.	N/A	N/A

7340906	12/2007	Moffitt	N/A	N/A
7389646	12/2007	Moffitt	N/A	N/A
7389652	12/2007	Fair	N/A	N/A
7593033	12/2008	Walker et al.	N/A	N/A
7601208	12/2008	Tongue	N/A	N/A
7602414	12/2008	Walker et al.	N/A	N/A
7605840	12/2008	Walker et al.	N/A	N/A
7717404	12/2009	Hasegawa et al.	N/A	N/A
7719565	12/2009	Walker et al.	N/A	N/A
7737224	12/2009	Willis et al.	N/A	N/A
7753991	12/2009	Kertzman	N/A	N/A
7781034	12/2009	Yializis et al.	N/A	N/A
7817182	12/2009	Walker et al.	N/A	N/A
D638925	12/2010	Charlebois et al.	N/A	N/A
7942387	12/2010	Forkosh	N/A	N/A
7966841	12/2010	Lowenstein et al.	N/A	N/A
8002023	12/2010	Murayama	N/A	N/A
8033532	12/2010	Yabu	N/A	N/A
8047511	12/2010	Miyauchi et al.	N/A	N/A
8137436	12/2011	Calis et al.	N/A	N/A
8141379	12/2011	Al-Hadhrami et al.	N/A	N/A
8157891	12/2011	Montie et al.	N/A	N/A
8318824	12/2011	Matsuoka et al.	N/A	N/A
8469782	12/2012	Roy	N/A	N/A
8470071	12/2012	Ehrenberg et al.	N/A	N/A
8511074	12/2012	Kuehnel et al.	N/A	N/A
8550151	12/2012	Murayama et al.	N/A	N/A
8769971	12/2013	Kozubal et al.	N/A	N/A
8783053	12/2013	McCann	N/A	N/A
8887523	12/2013	Gommed et al.	N/A	N/A
8899061	12/2013	Reytblat	N/A	N/A
8915092	12/2013	Gerber et al.	N/A	N/A
8920699	12/2013	Marutani et al.	N/A	N/A
8943848	12/2014	Phannavong et al.	N/A	N/A
8966924	12/2014	Pichai	N/A	N/A
9021821	12/2014	Dunnavant	N/A	N/A
9027764	12/2014	Murutani et al.	N/A	N/A
9109808	12/2014	Gerber et al.	N/A	N/A
9140460	12/2014	Woods et al.	N/A	N/A
9146040	12/2014	DeValve	N/A	N/A
9188349	12/2014	Warmerdam et al.	N/A	N/A
9234665	12/2015	Erb et al.	N/A	N/A
9243810	12/2015	Vandermeulen et al.	N/A	N/A
9273877	12/2015	Vandermeulen	N/A	N/A
9377207	12/2015	Vandermeulen et al.	N/A	N/A
9423140	12/2015	Betts et al.	N/A	N/A
9429332	12/2015	Vandermeulen et al.	N/A	N/A
9429366	12/2015	Dubois	N/A	N/A
9664452	12/2016	Takada et al.	N/A	N/A
9810439	12/2016	Coutu et al.	N/A	N/A

9816760	12/2016	LePoudre et al.	N/A	N/A
9909768	12/2017	Gerber et al.	N/A	N/A
10197310	12/2018	Ghadiri Moghaddam et al.	N/A	N/A
10302317	12/2018	Besant et al.	N/A	N/A
10352628	12/2018	Erb et al.	N/A	N/A
10480801	12/2018	Gerber et al.	N/A	N/A
10584884	12/2019	Coutu et al.	N/A	N/A
10712024	12/2019	LePoudre et al.	N/A	N/A
10782045	12/2019	LePoudre et al.	N/A	N/A
10808951	12/2019	LePoudre et al.	N/A	N/A
10928082	12/2020	Coutu et al.	N/A	N/A
10962252	12/2020	LePoudre et al.	N/A	N/A
11035618	12/2020	Lepoudre et al.	N/A	N/A
11092349	12/2020	Lepoudre et al.	N/A	N/A
11143430	12/2020	Ghadiri Moghaddam et al.	N/A	N/A
11300364	12/2021	Erb et al.	N/A	N/A
11408681	12/2021	Lepoudre	N/A	N/A
11892193	12/2023	Lepoudre	N/A	N/A
2001/0003902	12/2000	Kopko	N/A	N/A
2002/0005271	12/2001	Weiss et al.	N/A	N/A
2002/0038552	12/2001	Maisotsenko	N/A	N/A
2002/0074105	12/2001	Hayashi et al.	N/A	N/A
2002/0158023	12/2001	Wurzbürger	N/A	N/A
2002/0161254	12/2001	Schattenmann	N/A	N/A
2003/0014983	12/2002	Maisotsenko et al.	N/A	N/A
2003/0033821	12/2002	Maisotsenko et al.	N/A	N/A
2003/0037905	12/2002	Weng	N/A	N/A
2003/0070787	12/2002	Moffitt	N/A	N/A
2003/0121271	12/2002	Dinnage et al.	N/A	N/A
2003/0132166	12/2002	Rey	N/A	N/A
2003/0145609	12/2002	Maisotsenko et al.	N/A	N/A
2004/0000152	12/2003	Fischer	N/A	N/A
2004/0026225	12/2003	Domen	N/A	N/A
2004/0055329	12/2003	Mathias et al.	N/A	N/A
2004/0061245	12/2003	Maisotsenko et al.	N/A	N/A
2004/0134211	12/2003	Lee et al.	N/A	N/A
2004/0134212	12/2003	Lee et al.	N/A	N/A
2004/0168462	12/2003	Assaf	N/A	N/A
2004/0226685	12/2003	Gagnon et al.	N/A	N/A
2005/0056042	12/2004	Bourne et al.	N/A	N/A
2005/0072303	12/2004	Weidenmann	N/A	N/A
2005/0132738	12/2004	Bourne et al.	N/A	N/A
2005/0230080	12/2004	Paul et al.	N/A	N/A
2005/0249901	12/2004	Yializis et al.	N/A	N/A
2005/0262862	12/2004	Moffitt	N/A	N/A
2005/0279115	12/2004	Lee et al.	N/A	N/A
2006/0021615	12/2005	Kertzman	N/A	N/A
2006/0032258	12/2005	Pruitt et al.	N/A	N/A

2006/0042295	12/2005	Assaf	N/A	N/A
2006/0118979	12/2005	Beck et al.	N/A	N/A
2006/0205301	12/2005	Klare et al.	N/A	N/A
2007/0029685	12/2006	Lin	N/A	N/A
2007/0056894	12/2006	Connors	N/A	N/A
2007/0068663	12/2006	Thomer et al.	N/A	N/A
2007/0095519	12/2006	Hombucher	N/A	N/A
2007/0234743	12/2006	Assaf	N/A	N/A
2007/0279861	12/2006	Doll et al.	N/A	N/A
2008/0023182	12/2007	Beamer et al.	N/A	N/A
2008/0066888	12/2007	Tong et al.	N/A	N/A
2008/0085437	12/2007	Dean et al.	N/A	N/A
2008/0099184	12/2007	Han	N/A	N/A
2008/0283217	12/2007	Gagnon et al.	N/A	N/A
2009/0071638	12/2008	Sugiyama et al.	N/A	N/A
2009/0095162	12/2008	Hargis et al.	N/A	N/A
2009/0126913	12/2008	Lee et al.	N/A	N/A
2009/0133866	12/2008	Campbell et al.	N/A	N/A
2009/0193974	12/2008	Montie et al.	N/A	N/A
2009/0211977	12/2008	Miller	N/A	N/A
2009/0294110	12/2008	Foust	N/A	N/A
2009/0324929	12/2008	Yamakawa et al.	N/A	N/A
2010/0055276	12/2009	Chen	N/A	N/A
2010/0058778	12/2009	Bhatti et al.	N/A	N/A
2010/0090356	12/2009	Sines et al.	N/A	N/A
2010/0170655	12/2009	Kronvall et al.	N/A	N/A
2010/0170776	12/2009	Ehrenberg et al.	N/A	N/A
2010/0181062	12/2009	Mccann	N/A	N/A
2010/0192605	12/2009	Fang et al.	N/A	N/A
2010/0200068	12/2009	D'Arcy et al.	N/A	N/A
2010/0275629	12/2009	Erickson	N/A	N/A
2010/0300123	12/2009	Park et al.	N/A	N/A
2010/0319370	12/2009	Kozubal et al.	N/A	N/A
2010/0326914	12/2009	Drost et al.	N/A	N/A
2011/0056384	12/2010	Kadota	N/A	N/A
2011/0101549	12/2010	Miyauchi et al.	N/A	N/A
2011/0138832	12/2010	Al-hadhrami et al.	N/A	N/A
2011/0192579	12/2010	Sotokawa et al.	N/A	N/A
2011/0223486	12/2010	Zhang et al.	N/A	N/A
2011/0232485	12/2010	Ellsworth	N/A	N/A
2011/0232633	12/2010	Lima	N/A	N/A
2011/0259572	12/2010	Muratani et al.	N/A	N/A
2011/0283720	12/2010	Martin	N/A	N/A
2011/0308265	12/2010	Phannavong et al.	N/A	N/A
2012/0000227	12/2011	Matsuura et al.	N/A	N/A
2012/0016700	12/2011	Jabbour et al.	N/A	N/A
2012/0023988	12/2011	Togano et al.	N/A	N/A
2012/0031133	12/2011	Kuwabara et al.	N/A	N/A
2012/0061045	12/2011	Huizing	N/A	N/A
2012/0073791	12/2011	Dubois	N/A	N/A

2012/0085112	12/2011	Wintemute	N/A	N/A
2012/0106073	12/2011	Wu et al.	N/A	N/A
2012/0125020	12/2011	Vandermeulen et al.	N/A	N/A
2012/0125021	12/2011	Vandermeulen et al.	N/A	N/A
2012/0125023	12/2011	Kopko et al.	N/A	N/A
2012/0125031	12/2011	Vandermeulen et al.	N/A	N/A
2012/0125405	12/2011	Vandermeulen et al.	N/A	N/A
2012/0125581	12/2011	Allen et al.	N/A	N/A
2012/0131934	12/2011	Vandermeulen et al.	N/A	N/A
2012/0131937	12/2011	Vandermeulen et al.	N/A	N/A
2012/0131938	12/2011	Vandermeulen et al.	N/A	N/A
2012/0131939	12/2011	Vandermeulen et al.	N/A	N/A
2012/0131940	12/2011	Vandermeulen et al.	N/A	N/A
2012/0132513	12/2011	Vandermeulen et al.	N/A	N/A
2012/0162918	12/2011	Thyni et al.	N/A	N/A
2012/0167600	12/2011	Dunnavant	N/A	N/A
2012/0168369	12/2011	Van Medevoort et al.	N/A	N/A
2012/0180505	12/2011	Gerber et al.	N/A	N/A
2012/0186281	12/2011	Vandermeulen et al.	N/A	N/A
2012/0247132	12/2011	Lakdawala et al.	N/A	N/A
2012/0298340	12/2011	Al-Otaibi	N/A	N/A
2013/0056177	12/2012	Coutu et al.	N/A	N/A
2013/0075066	12/2012	Reytblat	N/A	N/A
2013/0186121	12/2012	Erb et al.	N/A	N/A
2013/0199220	12/2012	Ma et al.	N/A	N/A
2013/0240438	12/2012	Willis et al.	N/A	N/A
2013/0244046	12/2012	Yaegar et al.	N/A	N/A
2013/0248147	12/2012	Wintemute et al.	N/A	N/A
2013/0283837	12/2012	Takahashi et al.	N/A	N/A
2013/0340449	12/2012	Kozubal et al.	N/A	N/A
2014/0054004	12/2013	LePoudre et al.	N/A	N/A
2014/0054013	12/2013	Lepoudre et al.	N/A	N/A
2014/0069134	12/2013	Grabon	N/A	N/A
2014/0083648	12/2013	Wawryk	N/A	N/A
2014/0125060	12/2013	Sahm	N/A	N/A
2014/0138851	12/2013	Kim et al.	N/A	N/A
2014/0150481	12/2013	Vandermeulen	N/A	N/A
2014/0190037	12/2013	Erb et al.	N/A	N/A
2014/0190198	12/2013	Slessman et al.	N/A	N/A
2014/0223947	12/2013	Ranjan et al.	N/A	N/A
2014/0242900	12/2013	Takada et al.	N/A	N/A
2014/0245769	12/2013	Vandermeulen et al.	N/A	N/A
2014/0250935	12/2013	Prochaska	62/271	F28B 9/06
2014/0260367	12/2013	Coutu	62/89	F24F 3/147
2014/0260369	12/2013	LePoudre	62/91	F24F 12/002
2014/0260373	12/2013	Gerber et al.	N/A	N/A
2014/0260399	12/2013	Vandermeulen	N/A	N/A
2014/0262125	12/2013	Erb et al.	N/A	N/A

2014/0262144	12/2013	Erb et al.	N/A	N/A
2014/0326433	12/2013	Kozubal	N/A	N/A
2014/0340842	12/2013	Towner et al.	N/A	N/A
2015/0068225	12/2014	Laughman	62/77	F24F 3/065
2015/0096714	12/2014	Dagley	N/A	N/A
2015/0184876	12/2014	Vandermeulen et al.	N/A	N/A
2015/0233588	12/2014	Betts et al.	N/A	N/A
2015/0253018	12/2014	Eguchi et al.	N/A	N/A
2015/0292754	12/2014	Mongar	N/A	N/A
2015/0323203	12/2014	Gerber et al.	N/A	N/A
2016/0054012	12/2015	Lepoudre et al.	N/A	N/A
2016/0084512	12/2015	Erb et al.	N/A	N/A
2016/0187010	12/2015	Vandermeulen	N/A	N/A
2016/0209087	12/2015	Reytblat et al.	N/A	N/A
2016/0290666	12/2015	Coutu et al.	N/A	N/A
2016/0298865	12/2015	Gerber et al.	N/A	N/A
2016/0327345	12/2015	Lowenstein	N/A	N/A
2017/0241655	12/2016	Lepoudre et al.	N/A	N/A
2018/0073753	12/2017	Lepoudre et al.	N/A	N/A
2018/0128510	12/2017	Lepoudre et al.	N/A	N/A
2018/0135880	12/2017	Ghadiri Moghaddam et al.	N/A	N/A
2018/0187918	12/2017	Lepoudre et al.	N/A	N/A
2019/0113247	12/2018	Lepoudre et al.	N/A	N/A
2019/0212020	12/2018	Besant et al.	N/A	N/A
2019/0346212	12/2018	Norman Erb et al.	N/A	N/A
2020/0063995	12/2019	Lepoudre	N/A	N/A
2020/0096212	12/2019	Lepoudre	N/A	N/A
2020/0173672	12/2019	Coutu et al.	N/A	N/A
2021/0231384	12/2020	Lepoudre et al.	N/A	N/A
2021/0332993	12/2020	Coutu et al.	N/A	N/A
2021/0396422	12/2020	Ghadiri Moghaddam et al.	N/A	N/A
2022/0003436	12/2021	Besant et al.	N/A	N/A
2022/0003437	12/2021	Lepoudre et al.	N/A	N/A
2022/0333868	12/2021	Lepoudre	N/A	N/A
2022/0333869	12/2021	Lepoudre	N/A	N/A
2024/0027083	12/2023	Lepoudre	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2011286700	12/2011	AU	N/A
2011268661	12/2012	AU	N/A
2014231672	12/2017	AU	N/A
2015230799	12/2017	AU	N/A
2013305427	12/2017	AU	N/A
2014231681	12/2017	AU	N/A
2013305428	12/2017	AU	N/A
2014231668	12/2018	AU	N/A

2014231667	12/2018	AU	N/A
2017204552	12/2018	AU	N/A
2018236791	12/2019	AU	N/A
2018204774	12/2019	AU	N/A
2283089	12/1999	CA	N/A
122381	12/2008	CA	N/A
2801352	12/2010	CA	N/A
2798928	12/2011	CA	N/A
2843763	12/2012	CA	N/A
2904224	12/2013	CA	N/A
2901483	12/2018	CA	N/A
2880353	12/2019	CA	N/A
3034592	12/2020	CA	N/A
2904224	12/2021	CA	N/A
2901484	12/2021	CA	N/A
2958480	12/2021	CA	N/A
193732	12/1936	CH	N/A
1163389	12/1996	CN	N/A
1343292	12/2001	CN	N/A
1456855	12/2002	CN	N/A
1517610	12/2003	CN	N/A
1518477	12/2003	CN	N/A
1666081	12/2004	CN	N/A
1711448	12/2004	CN	N/A
2821506	12/2005	CN	N/A
101014807	12/2006	CN	N/A
200958820	12/2006	CN	N/A
101368754	12/2008	CN	N/A
201203217	12/2008	CN	N/A
101405559	12/2008	CN	N/A
101421580	12/2008	CN	N/A
101469090	12/2008	CN	N/A
101776406	12/2009	CN	N/A
101900385	12/2009	CN	N/A
101918777	12/2009	CN	N/A
102076401	12/2010	CN	N/A
201906567	12/2010	CN	N/A
102149979	12/2010	CN	N/A
102165268	12/2010	CN	N/A
102232015	12/2010	CN	N/A
102259570	12/2010	CN	N/A
102345909	12/2011	CN	N/A
102395419	12/2011	CN	N/A
202202899	12/2011	CN	N/A
102548727	12/2011	CN	N/A
102549361	12/2011	CN	N/A
102667350	12/2011	CN	N/A
102713154	12/2011	CN	N/A
102721133	12/2011	CN	N/A
102933931	12/2012	CN	N/A

102939397	12/2012	CN	N/A
103068246	12/2012	CN	N/A
103069246	12/2012	CN	N/A
103245018	12/2012	CN	N/A
203116208	12/2012	CN	N/A
103827595	12/2013	CN	N/A
104024748	12/2013	CN	N/A
104048434	12/2013	CN	N/A
203893703	12/2013	CN	N/A
104136855	12/2013	CN	N/A
104541122	12/2014	CN	N/A
104583706	12/2014	CN	N/A
103261801	12/2014	CN	N/A
105121965	12/2014	CN	N/A
105121989	12/2014	CN	N/A
105164474	12/2014	CN	N/A
105164484	12/2014	CN	N/A
105202795	12/2014	CN	N/A
105283715	12/2015	CN	N/A
101512238	12/2015	CN	N/A
106170660	12/2015	CN	N/A
106471315	12/2016	CN	N/A
103827595	12/2016	CN	N/A
105164484	12/2016	CN	N/A
105121989	12/2016	CN	N/A
107249715	12/2016	CN	N/A
107300230	12/2016	CN	N/A
107560482	12/2017	CN	N/A
107850335	12/2017	CN	N/A
107923647	12/2017	CN	N/A
108027221	12/2017	CN	N/A
109028519	12/2017	CN	N/A
109073265	12/2017	CN	N/A
110345803	12/2018	CN	N/A
107300230	12/2018	CN	N/A
107560482	12/2019	CN	N/A
110753819	12/2019	CN	N/A
110785615	12/2019	CN	N/A
110809698	12/2019	CN	N/A
107249715	12/2019	CN	N/A
107850335	12/2020	CN	N/A
108027221	12/2020	CN	N/A
110809698	12/2020	CN	N/A
109073265	12/2020	CN	N/A
107923647	12/2020	CN	N/A
114935182	12/2021	CN	N/A
10143092	12/2002	DE	N/A
0448991	12/1990	EP	N/A
0661502	12/1994	EP	N/A
0678321	12/1994	EP	N/A

1108575	12/2000	EP	N/A
1347260	12/2002	EP	N/A
2351639	12/2010	EP	N/A
2397787	12/2010	EP	N/A
2751493	12/2017	EP	N/A
3314188	12/2017	EP	N/A
2893283	12/2017	EP	N/A
2972039	12/2017	EP	N/A
2971993	12/2018	EP	N/A
2971992	12/2019	EP	N/A
3421921	12/2019	EP	N/A
3183051	12/2019	EP	N/A
3486577	12/2019	EP	N/A
2972046	12/2019	EP	N/A
3499168	12/2020	EP	N/A
3314188	12/2020	EP	N/A
3295089	12/2020	EP	N/A
3295088	12/2021	EP	N/A
3612770	12/2022	EP	N/A
3612771	12/2022	EP	N/A
2291457	12/1975	FR	N/A
1354502	12/1973	GB	N/A
2015384	12/1978	GB	N/A
40009311	12/2019	HK	N/A
4009311	12/2020	HK	N/A
201717044889	12/2017	IN	N/A
201717044890	12/2017	IN	N/A
201817002765	12/2017	IN	N/A
201817037404	12/2017	IN	N/A
201917046207	12/2019	IN	N/A
201917046210	12/2019	IN	N/A
201917046215	12/2019	IN	N/A
531453	12/2023	IN	N/A
6152594	12/1985	JP	N/A
05157282	12/1992	JP	N/A
H09113167	12/1996	JP	N/A
09196482	12/1996	JP	N/A
10170177	12/1997	JP	N/A
2004116419	12/2003	JP	N/A
2004257588	12/2003	JP	N/A
2008070046	12/2007	JP	N/A
2009275955	12/2008	JP	N/A
4870843	12/2010	JP	N/A
100607204	12/2005	KR	N/A
20110092773	12/2010	KR	N/A
101528640	12/2014	KR	N/A
10201809840	12/2017	SG	N/A
11201807692	12/2019	SG	N/A
10201913923	12/2019	SG	N/A
I271499	12/2006	TW	N/A

WO-9641107	12/1995	WO	N/A
WO-1996041107	12/1995	WO	N/A
WO-1999014535	12/1998	WO	N/A
WO-0135039	12/2000	WO	N/A
WO-0171260	12/2000	WO	N/A
WO-0201132	12/2001	WO	N/A
WO-03049835	12/2002	WO	N/A
WO-2004065875	12/2003	WO	N/A
WO-2005100243	12/2004	WO	N/A
WO-2008037079	12/2007	WO	N/A
WO-2008053367	12/2007	WO	N/A
WO-2008089484	12/2007	WO	N/A
WO-2009000974	12/2007	WO	N/A
WO-2009094032	12/2008	WO	N/A
WO-2009158030	12/2008	WO	N/A
WO-2010006968	12/2009	WO	N/A
WO-2011062808	12/2010	WO	N/A
2011161547	12/2010	WO	N/A
WO-2011150081	12/2010	WO	N/A
WO-2011161547	12/2010	WO	N/A
WO-2012018089	12/2011	WO	N/A
WO-2012042553	12/2011	WO	N/A
WO-2012050860	12/2011	WO	N/A
WO-2012087273	12/2011	WO	N/A
WO-2012097445	12/2011	WO	N/A
WO-2012167366	12/2011	WO	N/A
WO-2013029148	12/2012	WO	N/A
WO-2013094206	12/2012	WO	N/A
WO-2013107554	12/2012	WO	N/A
WO-2013192397	12/2012	WO	N/A
WO-2014029003	12/2013	WO	N/A
WO-2014029004	12/2013	WO	N/A
WO-2014107790	12/2013	WO	N/A
2014138851	12/2013	WO	N/A
WO-2014138846	12/2013	WO	N/A
WO-2014138847	12/2013	WO	N/A
WO-2014138859	12/2013	WO	N/A
WO-2014138860	12/2013	WO	N/A
WO-2014142277	12/2013	WO	N/A
2015123659	12/2014	WO	N/A
WO-2015192249	12/2014	WO	N/A
WO-2016026042	12/2015	WO	N/A
WO-2016074077	12/2015	WO	N/A
2016183667	12/2015	WO	N/A
WO-2016183668	12/2015	WO	N/A
WO-2016207864	12/2015	WO	N/A
WO-2017152268	12/2016	WO	N/A
WO-2018191805	12/2017	WO	N/A
WO-2018191806	12/2017	WO	N/A
WO-2018191807	12/2017	WO	N/A

OTHER PUBLICATIONS

US 10,739,032 B2, 08/2020, LePoudre et al. (withdrawn) cited by applicant

“International Application Serial No. PCT/CA2017/050478, International Preliminary Report on Patentability mailed Oct. 31, 2019”, 7 pgs. cited by applicant

“International Application Serial No. PCT/CA2017/050479, International Preliminary Report on Patentability mailed Oct. 31, 2019”, 6 pgs. cited by applicant

“International Application Serial No. PCT/CA2017/050480, International Preliminary Report on Patentability mailed Oct. 31, 2019”, 7 pgs. cited by applicant

“Singaporean Application Serial No. 11201909648V, Voluntary Amendment filed Apr. 17, 2020”, 10 pgs. cited by applicant

“Singaporean Application Serial No. 11201909681X, Voluntary Amendment filed Apr. 20, 2020”, 12 pgs. cited by applicant

“Singaporean Application Serial No. 11201909695X, Voluntary Amendment filed Apr. 17, 2020”, 12 pgs. cited by applicant

“European Application Serial No. 17905967.0, Response to Communication Pursuant to Rules 161 and 162 filed Jun. 5, 2020”, 5 pgs. cited by applicant

“European Application Serial No. 17906408.4, Response to Communication Pursuant to Rules 161 and 162 filed Jun. 5, 2020”, 5 pgs. cited by applicant

“European Application Serial No. 17906575.0, Response to Communication Pursuant to Rules 161 and 162 filed Jun. 5, 2020”, 6 pgs. cited by applicant

“Singaporean Application Serial No. 11201909695X, Written Opinion dated Sep. 1, 2020”, 6 pgs. cited by applicant

“Singaporean Application Serial No. 11201909648V, Written Opinion dated Sep. 1, 2020”, 7 pgs. cited by applicant

“Singaporean Application Serial No. 11201909681X, Written Opinion dated Sep. 1, 2020”, 6 pgs. cited by applicant

“European Application Serial No. 17906575.0, Extended European Search Report mailed Oct. 16, 2020”, 8 pgs. cited by applicant

“Chinese Application Serial No. 201780092237.9, Office Action mailed Oct. 30, 2020”, w/ English translation, 38 pgs. cited by applicant

“European Application Serial No. 17905967.0, Extended European Search Report mailed Nov. 5, 2020”, 10 pgs. cited by applicant

“Chinese Application Serial No. 201780092236.4, Office Action mailed Nov. 11, 2020”, w/ English machine translation, 11 pgs. cited by applicant

“Chinese Application Serial No. 201780092213.3, Office Action mailed Nov. 11, 2020”, w/ English Translation, 32 pgs. cited by applicant

“European Application Serial No. 17906408.4, Extended European Search Report mailed Nov. 27, 2020”, 7 pgs. cited by applicant

“Singaporean Application Serial No. 11201909681X, Response filed Jan. 29, 2021 to Written Opinion dated Sep. 1, 2020”, 23 pgs. cited by applicant

“Singaporean Application Serial No. 11201909648V, Response filed Feb. 1, 2021 to Written Opinion dated Sep. 1, 2020”, 24 pgs. cited by applicant

“Singaporean Application Serial No. 11201909695X, Response filed Feb. 1, 2021 to Written Opinion dated Sep. 1, 2020”, 28 pgs. cited by applicant

“NREL's Energy-Saving Technology for Air Conditioning Cuts Peak Power Loads Without Using Harmful Refrigerants”, National Renewable Energy Laboratory, Golden, CO, (Jul. 2012), 2 pgs. cited by applicant

Kozubal, Eric, “Seminar 14—Desiccant Enhanced Air Conditioning”, NREL 2013 Winter Conference, Dallas, TX, (2013), 5 pgs. cited by applicant

“Energy Savings Potential and RD&D Opportunities for Non-Vapor Compression HVAC Technologies”. (Mar. 1, 2014), 199. cited by applicant

“International Application Serial No. PCT/CA2017/050478, International Search Report mailed May 9, 2018”, 3 pgs. cited by applicant

“International Application Serial No. PCT/CA2017/050478, Written Opinion mailed May 9, 2018”, 5 pgs. cited by applicant

“International Application Serial No. PCT/CA2017/050479, International Search Report mailed Jan. 9, 2018”, 3 pgs. cited by applicant

“International Application Serial No. PCT/CA2017/050479, Written Opinion mailed Jan. 9, 2018”, 4 pgs. cited by applicant

“International Application Serial No. PCT/CA2017/050480, International Search Report mailed Jan. 11, 2018”, 3 pgs. cited by applicant

“International Application Serial No. PCT/CA2017/050480, Written Opinion mailed Jan. 11, 2018”, 5 pgs. cited by applicant

El-Dessouky, H T, et al., “A Novel air conditioning system Membrane Air Drying and Evaporative Cooling”, Institution of Chemical Engineers Trans IChemE, vol. 78, Part A, Oct. 2000, (Oct. 2000), 999-1009. cited by applicant

Kassai, M, et al., “Performance investigation of liquid-to-air membrane energy exchanger under low solution/air heat capacity rates ratio conditions”, Building services engineering research and technology vol. 36(5), (2015), 535-545. cited by applicant

“U.S. Appl. No. 16/606,708, Non Final Office Action mailed Jun. 22, 2021”, 18 pgs. cited by applicant

“U.S. Appl. No. 16/606,708, Response filed Sep. 14, 2021 to Non Final Office Action mailed Jun. 22, 2021”, 14 pgs. cited by applicant

“U.S. Appl. No. 16/606,716, Non Final Office Action mailed Sep. 17, 2021”, 16 pgs. cited by applicant

“Chinese Application Serial No. 201780092213.3, Office Action mailed Aug. 6, 2021”, with English translation, 28 pages. cited by applicant

“Chinese Application Serial No. 201780092213.3, Response filed May 26, 2021 to Office Action mailed Nov. 11, 2020”, with English claims, 26 pages. cited by applicant

“Chinese Application Serial No. 201780092236.4, Response filed Apr. 14, 2021 to Office Action mailed Nov. 11, 2020”, with English claims, 21 pages. cited by applicant

“Chinese Application Serial No. 201780092237.9, Office Action mailed Jul. 28, 2021”, with English translation, 41 pages. cited by applicant

“Chinese Application Serial No. 201780092237.9, Response filed May 14, 2021 to Office Action mailed Oct. 30, 2020”, with English claims, 35 pages. cited by applicant

“European Application Serial No. 17905967.0, Response filed Jun. 3, 2021 to Extended European Search Report mailed Nov. 5, 2020”, 10 pgs. cited by applicant

“European Application Serial No. 17906408.4, Response filed Jun. 22, 2021 to Extended European Search Report mailed Nov. 27, 2020”, 16 pgs. cited by applicant

“European Application Serial No. 17906575.0, Response filed May 13, 2021 to Extended European Search Report mailed Oct. 16, 2020”, 21 pgs. cited by applicant

“Indian Application Serial No. 201917046207, First Examination Report mailed Sep. 20, 2021”, 8 pgs. cited by applicant

“Indian Application Serial No. 201917046210, First Examination Report mailed Jun. 9, 2021”, with English translation, 6 pages. cited by applicant

“Indian Application Serial No. 201917046215, First Examination Report mailed Sep. 9, 2021”, 9 pgs. cited by applicant

Al-Sulaiman, et al., “Liquid Desiccant based two-stage evaporative cooling system using reverse osmosis (RO) process for regeneration”, Applied Thermal Engineering, vol. 27, Issues 14-15, (Oct.

2007), 2449-2452. cited by applicant

“AAONAIRE Energy Recovery Units Users Information Manual”, AAON, Inc., (Aug. 2006), 16 pgs. cited by applicant

“Advances in Desiccant-Based Dehumidification”, American Standard, TRANE Engineers Newsletter, vol. 34-4, (2005), 8 pgs. cited by applicant

“U.S. Appl. No. 14/190,715, Response filed Jul. 20, 18 to Final Office Action mailed Feb. 20, 2018”, 14 pgs. cited by applicant

“U.S. Appl. No. 10/048,797, Amendment and Response filed Apr. 29, 2003 to Non-Final Office mailed Mar. 11, 2003”, 10 pgs. cited by applicant

“U.S. Appl. No. 10/048,797, Non-Final Office mailed Mar. 11, 2003”, 4 pgs. cited by applicant

“U.S. Appl. No. 10/048,797, Notice of Allowance mailed May 13, 2003”, 5 pgs. cited by applicant

“U.S. Appl. No. 13/350,902, Appeal Brief filed Apr. 4, 2014”, 24 pgs. cited by applicant

“U.S. Appl. No. 13/350,902, Appeal Decision mailed Sep. 30, 2016”, 6 pgs. cited by applicant

“U.S. Appl. No. 13/350,902, Examiner's Answer mailed Jun. 16, 2014”, 17 pgs. cited by applicant

“U.S. Appl. No. 13/350,902, Final Office Action mailed Dec. 30, 2013”, 13 pgs. cited by applicant

“U.S. Appl. No. 13/350,902, Non Final Office Action mailed Oct. 1, 2013”, 13 pgs. cited by applicant

“U.S. Appl. No. 13/350,902, Notice of Allowance mailed Mar. 1, 2017”, 7 pgs. cited by applicant

“U.S. Appl. No. 13/350,902, Notice of Allowance mailed Nov. 9, 2016”, 9 pgs. cited by applicant

“U.S. Appl. No. 13/350,902, Reply Brief filed Jul. 8, 2014”, 9 pgs. cited by applicant

“U.S. Appl. No. 13/350,902, Response filed Aug. 5, 2013 to Restriction Requirement mailed Jul. 23, 2013”, 2 pgs. cited by applicant

“U.S. Appl. No. 13/350,902, Response filed Oct. 29, 2013 to Non Final Office Action mailed Oct. 1, 2013”, 15 pgs. cited by applicant

“U.S. Appl. No. 13/350,902, Restriction Requirement mailed Jul. 23, 2013”, 8 pgs. cited by applicant

“U.S. Appl. No. 13/449,598, Final Office Action mailed Feb. 4, 2016”, 23 pgs. cited by applicant

“U.S. Appl. No. 13/449,598, Non Final Office Action mailed Apr. 24, 2015”, 18 pgs. cited by applicant

“U.S. Appl. No. 13/449,598, Non Final Office Action mailed Aug. 27, 2015”, 20 pgs. cited by applicant

“U.S. Appl. No. 13/449,598, Notice of Allowance mailed Mar. 10, 2017”, 7 pgs. cited by applicant

“U.S. Appl. No. 13/449,598, Notice of Allowance mailed Jul. 6, 2017”, 7 pgs. cited by applicant

“U.S. Appl. No. 13/449,598, Notice of Allowance mailed Nov. 4, 2016”, 9 pgs. cited by applicant

“U.S. Appl. No. 13/449,598, Response filed Jan. 29, 2015 to Restriction Requirement mailed Jan. 5, 2015”, 2 pgs. cited by applicant

“U.S. Appl. No. 13/449,598, Response filed Jul. 17, 2015 to Non Final Office Action mailed Apr. 24, 2015”, 17 pgs. cited by applicant

“U.S. Appl. No. 13/449,598, Response filed Nov. 16, 2015 to Non Final Office Action mailed Aug. 27, 2015”, 18 pgs. cited by applicant

“U.S. Appl. No. 13/449,598, Restriction Requirement mailed Jan. 5, 2015”, 10 pgs. cited by applicant

“U.S. Appl. No. 13/702,596, Appeal Brief filed Jun. 15, 2015”, 82 pgs. cited by applicant

“U.S. Appl. No. 13/702,596, Final Office Action mailed Jan. 30, 2015”, 15 pgs. cited by applicant

“U.S. Appl. No. 13/702,596, Non Final Office Action mailed Oct. 30, 2014”, 16 pgs. cited by applicant

“U.S. Appl. No. 13/702,596, Notice of Allowance mailed Oct. 1, 2015”, 7 pgs. cited by applicant

“U.S. Appl. No. 13/702,596, Notice of Allowance mailed Nov. 25, 2015”, 2 pgs. cited by applicant

“U.S. Appl. No. 13/702,596, Post Allowance Amendment filed Oct. 7, 2015”, 13 pgs. cited by applicant

“U.S. Appl. No. 13/702,596, PTO Response to Rule 312 Communication mailed Oct. 19, 2015”, 2 pgs. cited by applicant

“U.S. Appl. No. 13/702,596, Response filed Dec. 15, 2014 to Non Final Office Action mailed Oct. 30, 2014”, 21 pgs. cited by applicant

“U.S. Appl. No. 13/797,062 , Appeal Decision mailed Jun. 18, 2021”, 12 pgs. cited by applicant

“U.S. Appl. No. 13/797,062, Amendment and Response Under 37 C.F.R. 1.116 Filed Jan. 22, 2018 to Final Office Action mailed Feb. 24, 2016”, 11 pgs. cited by applicant

“U.S. Appl. No. 13/797,062, Appeal Brief filed Mar. 25, 2020”, 27 pgs. cited by applicant

“U.S. Appl. No. 13/797,062, Appeal Brief filed Jun. 9, 2016”, 33 pgs. cited by applicant

“U.S. Appl. No. 13/797,062, Appeal Decision mailed Nov. 22, 2017”, 15 pgs. cited by applicant

“U.S. Appl. No. 13/797,062, Final Office Action mailed Feb. 24, 2016”, 29 pgs. cited by applicant

“U.S. Appl. No. 13/797,062, Final Office Action mailed Jul. 13, 2018”, 22 pgs. cited by applicant

“U.S. Appl. No. 13/797,062, Final Office Action mailed Jul. 25, 2019”, 50 pgs. cited by applicant

“U.S. Appl. No. 13/797,062, Non Final Office Action mailed Feb. 21, 2018”, 21 pgs. cited by applicant

“U.S. Appl. No. 13/797,062, Non Final Office Action mailed May 7, 2015”, 19 pgs. cited by applicant

“U.S. Appl. No. 13/797,062, Non Final Office Action mailed Sep. 25, 2015”, 24 pgs. cited by applicant

“U.S. Appl. No. 13/797,062, Non Final Office Action mailed Dec. 28, 2018”, 50 pgs. cited by applicant

“U.S. Appl. No. 13/797,062, Respnose filed Jun. 28, 2019 to Non Final Office Action mailed Jun. 28, 2019”, 12 pgs. cited by applicant

“U.S. Appl. No. 13/797,062, Response filed Apr. 23, 2015 to Restriction Requirement mailed Mar. 13, 2015”, 3 pgs. cited by applicant

“U.S. Appl. No. 13/797,062, Response filed Jul. 17, 2015 to Non Final Office Action mailed May 7, 2015”, 16 pgs. cited by applicant

“U.S. Appl. No. 13/797,062, Response filed Nov. 30, 2015 to Non Final Office Action mailed Sep. 25, 2015”, 16 pgs. cited by applicant

“U.S. Appl. No. 13/797,062, Response filed Dec. 13, 2018 to Final Office Action mailed Jul. 13, 2018”, 12 pgs. cited by applicant

“U.S. Appl. No. 13/797,062, Response filed May 21, 2018 to Non Final Office Action mailed Feb. 21, 2018”, 12 pgs. cited by applicant

“U.S. Appl. No. 13/797,062, Restriction Requirement mailed Mar. 13, 2015”, 8 pgs. cited by applicant

“U.S. Appl. No. 13/797,152, Appeal Brief filed Jun. 9, 2016”, 29 pgs. cited by applicant

“U.S. Appl. No. 13/797,152, Corrected Notice of Allowance mailed Mar. 9, 2017”, 7 pgs. cited by applicant

“U.S. Appl. No. 13/797,152, Final Office Action mailed Feb. 25, 2016”, 14 pgs. cited by applicant

“U.S. Appl. No. 13/797,152, Non Final Office Action mailed Aug. 25, 2015”, 10 pgs. cited by applicant

“U.S. Appl. No. 13/797,152, Notice of Allowance mailed Mar. 9, 2017”, 7 pgs. cited by applicant

“U.S. Appl. No. 13/797,152, Notice of Allowance mailed Jun. 27, 2017”, 8 pgs. cited by applicant

“U.S. Appl. No. 13/797,152, Notice of Allowance mailed Oct. 31, 2016”, 7 pgs. cited by applicant

“U.S. Appl. No. 13/797,152, Response file Nov. 20, 2015 to Non Final Office Action mailed Aug. 25, 2015”, 12 pgs. cited by applicant

“U.S. Appl. No. 13/801,280, 312 Amendment filed Jun. 18, 2015”, 8 pgs. cited by applicant

“U.S. Appl. No. 13/801,280, Non Final Office Action mailed Feb. 12, 2015”, 7 pgs. cited by applicant

“U.S. Appl. No. 13/801,280, Notice of Allowance mailed May 19, 2015”, 7 pgs. cited by applicant

"U.S. Appl. No. 13/801,280, PTO Response to 312 Amendment mailed Jul. 9, 2015", 2 pgs. cited by applicant

"U.S. Appl. No. 13/801,280, Response filed Jan. 7, 2015 to Restriction Requirement mailed Dec. 10, 2014", 1 pg. cited by applicant

"U.S. Appl. No. 13/801,280, Response filed Mar. 31, 2015 to Non Final Office Action mailed Dec. 10, 2014", 1 pg. cited by applicant

"U.S. Appl. No. 13/801,280, Response filed Mar. 31, 2015 to Non-Final Office Action mailed Feb. 12, 2015", 9 pgs. cited by applicant

"U.S. Appl. No. 13/801,280, Restriction Requirement mailed Dec. 10, 2014", 9 pgs. cited by applicant

"U.S. Appl. No. 14/171,951, Advisory Action mailed Nov. 10, 2016", 3 pgs. cited by applicant

"U.S. Appl. No. 14/171,951, Final Office Action mailed Jun. 28, 2016", 36 pgs. cited by applicant

"U.S. Appl. No. 14/171,951, Non Final Office Action mailed May 2, 2016", 35 pgs. cited by applicant

"U.S. Appl. No. 14/171,951, Notice of Allowability mailed Jul. 18, 2018", 2 pgs. cited by applicant

"U.S. Appl. No. 14/171,951, Notice of Allowance mailed Jan. 9, 2019", 6 pgs. cited by applicant

"U.S. Appl. No. 14/171,951, Notice of Allowance mailed Jan. 19, 2018", 5 pgs. cited by applicant

"U.S. Appl. No. 14/171,951, Notice of Allowance mailed Feb. 3, 2017", 5 pgs. cited by applicant

"U.S. Appl. No. 14/171,951, Notice of Allowance mailed May 23, 2018", 5 pgs. cited by applicant

"U.S. Appl. No. 14/171,951, Notice of Allowance mailed Jun. 8, 2017", 5 pgs. cited by applicant

"U.S. Appl. No. 14/171,951, Notice of Allowance mailed Oct. 3, 2017", 5 pgs. cited by applicant

"U.S. Appl. No. 14/171,951, Notice of Allowance mailed Nov. 6, 2019", 6 pgs. cited by applicant

"U.S. Appl. No. 14/171,951, Response filed Mar. 28, 2016 to Non Final Office Action mailed Jan. 5, 2016", 18 pgs. cited by applicant

"U.S. Appl. No. 14/171,951, Response filed Jun. 9, 2016 to Non Final Office Action mailed May 2, 2016", 24 pgs. cited by applicant

"U.S. Appl. No. 14/171,951, Response filed Oct. 28, 2016 to Final Office Action mailed Jun. 28, 2016", 15 pgs. cited by applicant

"U.S. Appl. No. 14/171,951, Response filed Dec. 3, 2015 to Restriction Requirement mailed Nov. 16, 2015", 6 pgs. cited by applicant

"U.S. Appl. No. 14/171,951, Response filed Dec. 15, 2016 to Advisory Action mailed Nov. 10, 2016", 16 pgs. cited by applicant

"U.S. Appl. No. 14/171,951, Restriction Requirement mailed Nov. 16, 2015", 13 pgs. cited by applicant

"U.S. Appl. No. 14/186,420, Notice of Allowance mailed Jan. 27, 2017", 7 pgs. cited by applicant

"U.S. Appl. No. 14/187,413 Response to Non-Final Office Action filed Jun. 2, 2020", 25 pgs. cited by applicant

"U.S. Appl. No. 14/187,413, Advisory Action mailed Nov. 10, 2016", 4 pgs. cited by applicant

"U.S. Appl. No. 14/187,413, Advisory Action mailed Dec. 17, 2018", 5 pgs. cited by applicant

"U.S. Appl. No. 14/187,413, Amendment and Response filed Nov. 30, 2018 to Final Office Action mailed Jul. 26, 2018", 19 pgs. cited by applicant

"U.S. Appl. No. 14/187,413, Appeal Decision mailed Mar. 10, 2022", 11 pgs. cited by applicant

"U.S. Appl. No. 14/187,413, Examiner's Answer mailed Jun. 11, 2021", 10 pgs. cited by applicant

"U.S. Appl. No. 14/187,413, Final Office Action mailed Jun. 15, 2020", 19 pgs. cited by applicant

"U.S. Appl. No. 14/187,413, Final Office Action mailed Jun. 27, 2017", 16 pgs. cited by applicant

"U.S. Appl. No. 14/187,413, Final Office Action mailed Jul. 26, 2018", 16 pgs. cited by applicant

"U.S. Appl. No. 14/187,413, Final Office Action mailed Jul. 28, 2016", 20 pgs. cited by applicant

"U.S. Appl. No. 14/187,413, Non Final Office Action mailed Feb. 8, 2017", 15 pgs. cited by applicant

"U.S. Appl. No. 14/187,413, Non Final Office Action mailed Mar. 17, 2016", 15 pgs. cited by

applicant

“U.S. Appl. No. 14/187,413, Non Final Office Action mailed Jul. 31, 2019”, 22 pgs. cited by applicant

“U.S. Appl. No. 14/187,413, Non Final Office Action mailed Dec. 18, 2017”, 20 pgs. cited by applicant

“U.S. Appl. No. 14/187,413, Notice of Allowance mailed Mar. 29, 2022”, 7 pgs. cited by applicant

“U.S. Appl. No. 14/187,413, Response filed Feb. 25, 2015 to Restriction Requirement mailed Feb. 16, 2016”, 3 pgs. cited by applicant

“U.S. Appl. No. 14/187,413, Response filed May 26, 2016 to Non Final Office Action mailed Mar. 17, 2016”, 15 pgs. cited by applicant

“U.S. Appl. No. 14/187,413, Response filed Jun. 8, 2017 to Non Final Office Action mailed Feb. 8, 2017”, 15 pgs. cited by applicant

“U.S. Appl. No. 14/187,413, Response filed Oct. 28, 2016 to Final Office Action mailed Jul. 28, 2016”, 17 pgs. cited by applicant

“U.S. Appl. No. 14/187,413, Response filed Nov. 27, 2017 to Final Office Action mailed Jun. 27, 2017”, 14 pgs. cited by applicant

“U.S. Appl. No. 14/187,413, Response filed Dec. 21, 2016 to Final Office Action mailed Jul. 28, 2016 and Advisory Action mailed Nov. 10, 2016”, 15 pgs. cited by applicant

“U.S. Appl. No. 14/187,413, Restriction Requirement mailed Feb. 16, 2016”, 6 pgs. cited by applicant

“U.S. Appl. No. 14/190,715, Advisory Action mailed Aug. 16, 2018”, 6 pgs. cited by applicant

“U.S. Appl. No. 14/190,715, Examiner Interview Summary mailed Oct. 31, 2018”, 3 pgs. cited by applicant

“U.S. Appl. No. 14/190,715, Final Office Action mailed Feb. 20, 2018”, 9 pgs. cited by applicant

“U.S. Appl. No. 14/190,715, Non Final Office Action mailed Aug. 10, 2017”, 9 pgs. cited by applicant

“U.S. Appl. No. 14/190,715, Notice of Allowance mailed Mar. 4, 2019”, 7 pgs. cited by applicant

“U.S. Appl. No. 14/190,715, Response filed Jul. 12, 2017 to Restriction Requirement mailed Apr. 12, 2017”, 7 pgs. cited by applicant

“U.S. Appl. No. 14/190,715, Response filed Nov. 9, 2017 to Non Final Office Action mailed Aug. 10, 2017”, 10 pgs. cited by applicant

“U.S. Appl. No. 14/190,715, Restriction Requirement mailed Apr. 13, 2017”, 7 pgs. cited by applicant

“U.S. Appl. No. 14/192,019, Final Office Action mailed Jan. 10, 2019”, 16 pgs. cited by applicant

“U.S. Appl. No. 14/192,019, Final Office Action mailed Nov. 28, 2017”, 16 pgs. cited by applicant

“U.S. Appl. No. 14/192,019, Non Final Office Action mailed May 11, 2018”, 16 pgs. cited by applicant

“U.S. Appl. No. 14/192,019, Non Final Office Action mailed May 19, 2017”, 15 pgs. cited by applicant

“U.S. Appl. No. 14/192,019, Non Final Office Action mailed Jun. 25, 2019”, 13 pgs. cited by applicant

“U.S. Appl. No. 14/192,019, Response filed Jun. 10, 2019 to Final Office Action mailed Jan. 20, 2019”, 10 pgs. cited by applicant

“U.S. Appl. No. 14/192,019, Response filed Aug. 21, 2017 to Non Final Office Action mailed May 19, 2017”, 13 pgs. cited by applicant

“U.S. Appl. No. 14/192,019, Response filed Sep. 11, 2018 to Non Final Office Action mailed May 11, 2018”, 12 pgs. cited by applicant

“U.S. Appl. No. 14/192,019, Response filed Apr. 27, 2018 to Final Office Action mailed Nov. 28, 2017”, 11 pgs. cited by applicant

“U.S. Appl. No. 14/804,953, Corrected Notice of Allowance mailed Jan. 25, 2018”, 4 pgs. cited by

applicant

“U.S. Appl. No. 14/804,953, Non Final Office Action mailed Sep. 15, 2016”, 8 pgs. cited by applicant

“U.S. Appl. No. 14/804,953, Notice of Allowance mailed Feb. 27, 2017”, 7 pgs. cited by applicant

“U.S. Appl. No. 14/804,953, Notice of Allowance mailed May 9, 2017”, 7 pgs. cited by applicant

“U.S. Appl. No. 14/804,953, Notice of Allowance mailed Sep. 7, 2017”, 7 pgs. cited by applicant

“U.S. Appl. No. 14/804,953, Response filed Dec. 15, 2016 to Non Final Office Action mailed Sep. 15, 2016”, 7 pgs. cited by applicant

“U.S. Appl. No. 14/830,492, Corrected Notice of Allowability mailed Jun. 15, 2020”, 2 pgs. cited by applicant

“U.S. Appl. No. 14/830,492, Final Office Action mailed Dec. 28, 2018”, 9 pgs. cited by applicant

“U.S. Appl. No. 14/830,492, Non-Final Action mailed Mar. 15, 2018”, 9 pgs. cited by applicant

“U.S. Appl. No. 14/830,492, Notice of Allowance mailed Feb. 27, 2020”, 5 pgs. cited by applicant

“U.S. Appl. No. 14/830,492, Notice of Allowance mailed Sep. 24, 2019”, 7 pgs. cited by applicant

“U.S. Appl. No. 14/830,492, Response filed Feb. 15, 2018 to Restriction Requirement mailed Dec. 15, 2017”, 7 pgs. cited by applicant

“U.S. Appl. No. 14/830,492, Response filed Jun. 29, 2019 to Final Office Action mailed Dec. 28, 2018”, 6 pgs. cited by applicant

“U.S. Appl. No. 14/830,492, Response filed Aug. 15, 2018 to Non Final Office Action mailed Mar. 15, 2018”, 12 pgs. cited by applicant

“U.S. Appl. No. 14/830,492, Restriction Requirement mailed Dec. 15, 2017”, 6 pgs. cited by applicant

“U.S. Appl. No. 14/957,795, Corrected Notice of Allowability mailed Feb. 1, 2019”, 4 pgs. cited by applicant

“U.S. Appl. No. 14/957,795, Corrected Notice of Allowance mailed May 16, 2018”, 4 pgs. cited by applicant

“U.S. Appl. No. 14/957,795, Final Office Action mailed Nov. 6, 2017”, 17 pgs. cited by applicant

“U.S. Appl. No. 14/957,795, Non Final Office Action mailed Apr. 3, 2017”, 19 pgs. cited by applicant

“U.S. Appl. No. 14/957,795, Notice of Allowance mailed Jan. 17, 2019”, 7 pgs. cited by applicant

“U.S. Appl. No. 14/957,795, Notice of Allowance mailed Apr. 27, 2018”, 8 pgs. cited by applicant

“U.S. Appl. No. 14/957,795, Notice of Allowance mailed Sep. 11, 2018”, 9 pgs. cited by applicant

“U.S. Appl. No. 14/957,795, Response filed Apr. 3, 2018 to Final Office Action mailed Nov. 6, 2017”, 11 pgs. cited by applicant

“U.S. Appl. No. 14/957,795, Response filed Aug. 3, 2017 to Non Final Office Action mailed Apr. 3, 2017”, 17 pgs. cited by applicant

“U.S. Appl. No. 15/185,155, Corrected Notice of Allowability mailed May 15, 2019”, 2 pgs. cited by applicant

“U.S. Appl. No. 15/185,155, Corrected Notice of Allowability mailed May 22, 2019”, 2 pgs. cited by applicant

“U.S. Appl. No. 15/185,155, Examiner Interview Summary mailed Feb. 21, 2019”, 3 pgs. cited by applicant

“U.S. Appl. No. 15/185,155, Final Office Action mailed Dec. 5, 2018”, 11 pgs. cited by applicant

“U.S. Appl. No. 15/185,155, Non Final Office Action mailed Apr. 10, 2018”, 13 pgs. cited by applicant

“U.S. Appl. No. 15/185,155, Notice of Allowance mailed Mar. 25, 2019”, 7 pgs. cited by applicant

“U.S. Appl. No. 15/185,155, Notice of Allowance mailed Jul. 17, 2019”, 8 pgs. cited by applicant

“U.S. Appl. No. 15/185,155, Response filed Aug. 6, 2018 to Non Final Office Action mailed Apr. 10, 2018”, 10 pgs. cited by applicant

“U.S. Appl. No. 15/185,155, Response filed Mar. 5, 2019 to Final Office Action mailed Dec. 5,

2018", 9 pgs. cited by applicant
"U.S. Appl. No. 15/185,180, Final Office Action mailed Jul. 31, 2019", 15 pgs. cited by applicant
"U.S. Appl. No. 15/185,180, Non Final Office Action mailed Jan. 8, 2019", 14 pgs. cited by applicant
"U.S. Appl. No. 15/185,180, Notice of Allowance mailed Oct. 15, 2020", 6 pgs. cited by applicant
"U.S. Appl. No. 15/185,180, Response filed Nov. 19, 2018 to Restriction Requirement mailed Jun. 21, 2018", 9 pgs. cited by applicant
"U.S. Appl. No. 15/185,180, Response filed May 1, 2019 to Non Final Office Action mailed Jan. 8, 2019", 11 pgs. cited by applicant
"U.S. Appl. No. 15/185,180, Restriction Requirement mailed Jun. 21, 2018", 10 pgs. cited by applicant
"U.S. Appl. No. 15/574,201, Non Final Office Action mailed Jan. 15, 2020", 8 pgs. cited by applicant
"U.S. Appl. No. 15/574,201, Non Final Office Action mailed Jan. 26, 2021", 8 pgs. cited by applicant
"U.S. Appl. No. 15/574,201, Non Final Office Action mailed Jan. 29, 2019", 6 pgs. cited by applicant
"U.S. Appl. No. 15/574,201, Notice of Allowability mailed Jun. 18, 2021", 3 pgs. cited by applicant
"U.S. Appl. No. 15/574,201, Notice of Allowance mailed May 21, 2020", 5 pgs. cited by applicant
"U.S. Appl. No. 15/574,201, Notice of Allowance mailed Jun. 4, 2021", 5 pgs. cited by applicant
"U.S. Appl. No. 15/574,201, Notice of Allowance mailed Aug. 20, 2019", 7 pgs. cited by applicant
"U.S. Appl. No. 15/574,201, Notice of Allowance mailed Sep. 10, 2020", 6 pgs. cited by applicant
"U.S. Appl. No. 15/574,201, Response Filed Jan. 7, 2019 to Restriction Requirement mailed Sep. 5, 2018", 8 pgs. cited by applicant
"U.S. Appl. No. 15/574,201, Response filed May 15, 2020 to Non Final Office Action mailed Jan. 15, 2020", 13 pgs. cited by applicant
"U.S. Appl. No. 15/574,201, Response filed May 26, 2021 to Non Final Office Action mailed Jan. 26, 2021", 10 pgs. cited by applicant
"U.S. Appl. No. 15/574,201, Response filed Jul. 29, 2019 to Non-Final Office Action mailed Jan. 29, 2019", 12 pgs. cited by applicant
"U.S. Appl. No. 15/574,201, Restriction Requirement mailed Sep. 5, 2018", 6 pgs. cited by applicant
"U.S. Appl. No. 15/574,205, Corrected Notice of Allowability mailed Apr. 17, 2020", 2 pgs. cited by applicant
"U.S. Appl. No. 15/574,205, Non Final Office Action mailed Jun. 17, 2019", 3 pgs. cited by applicant
"U.S. Appl. No. 15/574,205, Non Final Office Action mailed Sep. 11, 2018", 6 pgs. cited by applicant
"U.S. Appl. No. 15/574,205, Notice of Allowance mailed Feb. 13, 2019", 6 pgs. cited by applicant
"U.S. Appl. No. 15/574,205, Notice of Allowance mailed Apr. 9, 2020", 5 pgs. cited by applicant
"U.S. Appl. No. 15/574,205, Notice of Allowance mailed Dec. 2, 2019", 5 pgs. cited by applicant
"U.S. Appl. No. 15/574,205, Response filed Jan. 11, 2019 to Non-Final Office Action mailed Sep. 11, 2018", 12 pgs. cited by applicant
"U.S. Appl. No. 15/574,205, Response filed Nov. 18, 2019 to Non-Final Office Action mailed Jun. 17, 2019", 8 pgs. cited by applicant
"U.S. Appl. No. 15/590,685, Advisory Action mailed Dec. 12, 2018", 3 pgs. cited by applicant
"U.S. Appl. No. 15/590,685, Examiner Interview Summary mailed Dec. 11, 2020", 3 pgs. cited by applicant
"U.S. Appl. No. 15/590,685, Final Office Action mailed Jun. 7, 2018", 12 pgs. cited by applicant

“U.S. Appl. No. 15/590,685, Final Office Action mailed Jun. 26, 2019”, 14 pgs. cited by applicant

“U.S. Appl. No. 15/590,685, Non Final Office Action mailed Jan. 7, 2020”, 15 pgs. cited by applicant

“U.S. Appl. No. 15/590,685, Non Final Office Action mailed Jan. 11, 2019”, 13 pgs. cited by applicant

“U.S. Appl. No. 15/590,685, Non Final Office Action mailed Oct. 6, 2017”, 11 pgs. cited by applicant

“U.S. Appl. No. 15/590,685, Notice of Allowance mailed Feb. 9, 2021”, 6 pgs. cited by applicant

“U.S. Appl. No. 15/590,685, PTO Response to Rule 312 Communication mailed Apr. 27, 2021”, 2 pgs. cited by applicant

“U.S. Appl. No. 15/590,685, Response filed Feb. 20, 2018 to Non Final Office Action mailed Oct. 6, 2017”, 7 pgs. cited by applicant

“U.S. Appl. No. 15/590,685, Response filed Apr. 18, 2019 to NonFinal Office Action mailed Jan. 11, 2019”, 11 pgs. cited by applicant

“U.S. Appl. No. 15/590,685, Response filed Nov. 30, 2018 to Final Office Action mailed Jun. 7, 2018”, 10 pgs. cited by applicant

“U.S. Appl. No. 15/590,685, Response filed Dec. 19, 2019 to Final Office Action mailed Jun. 26, 2019”, 11 pgs. cited by applicant

“U.S. Appl. No. 15/739,016, Corrected Notice of Allowability mailed Jul. 1, 2020”, 2 pgs. cited by applicant

“U.S. Appl. No. 15/739,016, Non Final Office Action mailed Feb. 13, 2019”, 6 pgs. cited by applicant

“U.S. Appl. No. 15/739,016, Notice of Allowance mailed Mar. 25, 2020”, 5 pgs. cited by applicant

“U.S. Appl. No. 15/739,016, Notice of Allowance mailed Aug. 1, 2019”, 6 pgs. cited by applicant

“U.S. Appl. No. 15/739,016, Notice of Allowance mailed Nov. 20, 2019”, 7 pgs. cited by applicant

“U.S. Appl. No. 15/739,016, Response filed Jan. 28, 2019 to Restriction Requirement mailed Nov. 26, 2018”, 8 pgs. cited by applicant

“U.S. Appl. No. 15/739,016, Restriction Requirement mailed Nov. 26, 2018”, 5 pgs. cited by applicant

“U.S. Appl. No. 15/814,153, Corrected Notice of Allowability mailed May 13, 2021”, 3 pgs. cited by applicant

“U.S. Appl. No. 15/814,153, Corrected Notice of Allowability mailed May 27, 2021”, 3 pgs. cited by applicant

“U.S. Appl. No. 15/814,153, Corrected Notice of Allowability mailed Jul. 15, 2021”, 2 pgs. cited by applicant

“U.S. Appl. No. 15/814,153, Non Final Office Action mailed Jul. 6, 2020”, 12 pgs. cited by applicant

“U.S. Appl. No. 15/814,153, Non Final Office Action mailed Oct. 9, 2019”, 16 pgs. cited by applicant

“U.S. Appl. No. 15/814,153, Notice of Allowance mailed Apr. 8, 2021”, 10 pgs. cited by applicant

“U.S. Appl. No. 15/814,153, Response filed Jan. 6, 2021 to Non Final Office Action mailed Jul. 6, 2020”, 12 pgs. cited by applicant

“U.S. Appl. No. 15/814,153, Response filed Apr. 9, 2020 to Non Final Office Action mailed Oct. 9, 2019”, 15 pgs. cited by applicant

“U.S. Appl. No. 15/814,153, Response filed Jul. 15, 2019 to Restriction Requirement mailed May 15, 2019”, 9 pgs. cited by applicant

“U.S. Appl. No. 15/814,153, Restriction Requirement mailed May 15, 2019”, 6 pgs. cited by applicant

“U.S. Appl. No. 16/083,280, Corrected Notice of Allowability mailed Aug. 3, 2020”, 2 pgs. cited by applicant

"U.S. Appl. No. 16/083,280, Corrected Notice of Allowability mailed Sep. 18, 2020", 2 pgs. cited by applicant

"U.S. Appl. No. 16/083,280, Non Final Office Action mailed Jan. 28, 2020", 6 pgs. cited by applicant

"U.S. Appl. No. 16/083,280, Notice of Allowance mailed Jun. 12, 2020", 5 pgs. cited by applicant

"U.S. Appl. No. 16/083,280, Response filed May 28, 2020 to Non Final Office Action mailed Jan. 28, 2020", 8 pgs. cited by applicant

"U.S. Appl. No. 16/351,046, Non Final Office Action mailed Dec. 21, 2020", 8 pgs. cited by applicant

"U.S. Appl. No. 16/431,397, Notice of Allowance mailed Dec. 10, 2021", 11 pgs. cited by applicant

"U.S. Appl. No. 16/431,397, Response filed Aug. 23, 2021 to Restriction Requirement mailed Jun. 23, 2021", 7 pgs. cited by applicant

"U.S. Appl. No. 16/431,397, Restriction Requirement mailed Jun. 23, 2021", 6 pgs. cited by applicant

"U.S. Appl. No. 16/431,397, Supplemental Notice of Allowability mailed Dec. 24, 2021", 2 pgs. cited by applicant

"U.S. Appl. No. 16/431,397, Supplemental Preliminary Amendment filed Aug. 2, 2019", 6 pgs. cited by applicant

"U.S. Appl. No. 16/606,708, Appeal Brief filed Dec. 28, 2022", 30 pgs. cited by applicant

"U.S. Appl. No. 16/606,708, Corrected Notice of Allowability mailed May 1, 2023", 2 pgs. cited by applicant

"U.S. Appl. No. 16/606,708, Corrected Notice of Allowability mailed Nov. 27, 2023", 2 pgs. cited by applicant

"U.S. Appl. No. 16/606,708, Final Office Action mailed Mar. 15, 2022", 20 pgs. cited by applicant

"U.S. Appl. No. 16/606,708, Non Final Office Action mailed Sep. 23, 2021", 20 pgs. cited by applicant

"U.S. Appl. No. 16/606,708, Notice of Allowance mailed Apr. 19, 2023", 8 pgs. cited by applicant

"U.S. Appl. No. 16/606,708, Notice of Allowance mailed Aug. 9, 2023", 8 pgs. cited by applicant

"U.S. Appl. No. 16/606,708, Response filed Jan. 24, 2022 to Non Final Office Action mailed Sep. 23, 2021", 14 pages. cited by applicant

"U.S. Appl. No. 16/606,708, Response filed May 16, 2022 to Final Office Action mailed Mar. 15, 2022", 14 pgs. cited by applicant

"U.S. Appl. No. 16/606,716, Appeal Brief filed Sep. 6, 2022", 25 pgs. cited by applicant

"U.S. Appl. No. 16/606,716, Appeal Decision mailed Jul. 2, 2024", 8 pgs. cited by applicant

"U.S. Appl. No. 16/606,716, Examiner's Answer mailed Oct. 28, 2022", 11 pgs. cited by applicant

"U.S. Appl. No. 16/606,716, Final Office Action mailed Feb. 4, 2022", 15 pgs. cited by applicant

"U.S. Appl. No. 16/606,716, Response filed Jan. 18, 2022 to Non Final Office Action mailed Sep. 17, 2021", 13 pgs. cited by applicant

"U.S. Appl. No. 16/606,716, Response filed May 4, 2022 to Final Office Action mailed Feb. 4, 2022", 20 pgs. cited by applicant

"U.S. Appl. No. 16/784,822, Final Office Action mailed Jul. 26, 2022", 7 pgs. cited by applicant

"U.S. Appl. No. 16/784,822, Non Final Office Action mailed Mar. 14, 2022", 9 pgs. cited by applicant

"U.S. Appl. No. 16/784,822, Notice of Allowance mailed Nov. 9, 2022", 5 pgs. cited by applicant

"U.S. Appl. No. 16/784,822, Response filed Feb. 28, 2022 to Restriction Requirement mailed Dec. 27, 2021", 6 pgs. cited by applicant

"U.S. Appl. No. 16/784,822, Response filed Jul. 11, 2022 to Non Final Office Action mailed Mar. 14, 2022", 9 pgs. cited by applicant

"U.S. Appl. No. 16/784,822, Response filed Oct. 25, 2022 to Final Office Action mailed Jul. 26, 2022", 5 pgs. cited by applicant

"U.S. Appl. No. 16/784,822, Restriction Requirement mailed Dec. 27, 2021", 6 pgs. cited by applicant

"U.S. Appl. No. 16/784,822, Supplemental Preliminary Amendment filed Feb. 14, 2020", 6 pgs. cited by applicant

"U.S. Appl. No. 17/168,928, Response filed Feb. 27, 2023 to Restriction Requirement mailed Nov. 25, 2022", 8 pgs. cited by applicant

"U.S. Appl. No. 17/168,928, Restriction Requirement mailed Nov. 25, 2022", 9 pgs. cited by applicant

"U.S. Appl. No. 17/168,928, Supplemental Preliminary Amendment filed Aug. 12, 2021", 5 pages. cited by applicant

"U.S. Appl. No. 17/231,634, Corrected Notice of Allowability mailed Feb. 10, 2023", 2 pgs. cited by applicant

"U.S. Appl. No. 17/231,634, Notice of Allowance mailed Jan. 11, 2023", 8 pgs. cited by applicant

"U.S. Appl. No. 17/305,681, Preliminary Amendment filed Oct. 15, 2021". cited by applicant

"U.S. Appl. No. 17/345,852 Preliminary Amendment Filed with Application", 3 pgs. cited by applicant

"U.S. Appl. No. 17/345,852 Supplemental Preliminary Amendment", 6 pgs. cited by applicant

"U.S. Appl. No. 17/345,852, Non Final Office Action mailed Feb. 23, 2023", 12 pgs. cited by applicant

"U.S. Appl. No. 17/855,344 Preliminary Amendment Filed with Application", 7 pgs. cited by applicant

"U.S. Appl. No. 17/855,344, Advisory Action mailed Nov. 28, 2023", 3 pgs. cited by applicant

"U.S. Appl. No. 17/855,344, Examiner Interview Summary mailed Jan. 24, 2024", 2 pgs. cited by applicant

"U.S. Appl. No. 17/855,344, Examiner Interview Summary mailed Sep. 1, 2023", 2 pgs. cited by applicant

"U.S. Appl. No. 17/855,344, Final Office Action mailed Apr. 24, 2024", 19 pgs. cited by applicant

"U.S. Appl. No. 17/855,344, Final Office Action mailed Jul. 17, 2023", 13 pgs. cited by applicant

"U.S. Appl. No. 17/855,344, Non Final Office Action mailed Jan. 9, 2024", 9 pgs. cited by applicant

"U.S. Appl. No. 17/855,344, Non Final Office Action mailed Jan. 27, 2023", 15 pgs. cited by applicant

"U.S. Appl. No. 17/855,344, Response filed Mar. 29, 2024 to Non Final Office Action mailed Jan. 9, 2024", 8 pgs. cited by applicant

"U.S. Appl. No. 17/855,344, Response filed Jun. 27, 2023 to Non Final Office Action mailed Jan. 27, 2023", 13 pgs. cited by applicant

"U.S. Appl. No. 17/855,344, Response filed Nov. 17, 2023 to Final Office Action mailed Jul. 17, 2023", 15 pgs. cited by applicant

"U.S. Appl. No. 17/855,413, Non Final Office Action mailed Jan. 27, 2023", 15 pgs. cited by applicant

"Australian Application Serial No. 2011268661, First Examiner Report mailed Sep. 24, 2014", 5 pgs. cited by applicant

"Australian Application Serial No. 2011268661, Response filed Jul. 20, 2015 to First Examiner Report mailed Sep. 24, 2014", 8 pgs. cited by applicant

"Australian Application Serial No. 2011268661, Response filed Sep. 2023, 15 to Second Examiner Report mailed Aug. 18, 2015", 5 pgs. cited by applicant

"Australian Application Serial No. 2011268661, Second Examiner Report mailed Aug. 18, 2015", 6 pgs. cited by applicant

"Australian Application Serial No. 2012208921, First Examiner Report mailed Jun. 2, 2016", 7 pgs. cited by applicant

"Australian Application Serial No. 2012304223, First Examiner Report mailed Aug. 5, 2016", 4 pgs. cited by applicant

"Australian Application Serial No. 2012304223, Response filed Feb. 16, 2017 to First Examiner Report mailed Aug. 5, 2016", 25 pgs. cited by applicant

"Australian Application Serial No. 2013305427, Examination Report mailed Mar. 3, 2017", 4 pgs. cited by applicant

"Australian Application Serial No. 2013305427, Response filed Oct. 10, 2017 to Examination Report mailed Mar. 3, 2017", 30 pgs. cited by applicant

"Australian Application Serial No. 2013305428, Office Action mailed May 30, 2017", 5 pgs. cited by applicant

"Australian Application Serial No. 2013305428, Response filed May 15, 2018 to Office Action mailed May 30, 2017", 23 pgs. cited by applicant

"Australian Application Serial No. 2014231667, First Examination Report mailed Apr. 5, 2018", 4 pgs. cited by applicant

"Australian Application Serial No. 2014231667, Response filed Jan. 15, 2019 to Subsequent Examiners Report mailed Aug. 29, 2018", 12 pgs. cited by applicant

"Australian Application Serial No. 2014231667, Response filed Jul. 20, 2018 to First Examination Report mailed Apr. 5, 2018", 19 pgs. cited by applicant

"Australian Application Serial No. 2014231667, Subsequent Examiners Report mailed Aug. 29, 2018", 4 pgs. cited by applicant

"Australian Application Serial No. 2014231668, First Examination Report mailed Dec. 6, 2017", 6 pgs. cited by applicant

"Australian Application Serial No. 2014231668, Response filed Mar. 14, 2018 to First Examination Report mailed Dec. 6, 2017", 31 pgs. cited by applicant

"Australian Application Serial No. 2014231668, Subsequent Examiners Report mailed Apr. 5, 2018", 3 pgs. cited by applicant

"Australian Application Serial No. 2014231672, First Examiners Report mailed Jul. 14, 2017", 4 pgs. cited by applicant

"Australian Application Serial No. 2014231672, Response filed Oct. 9, 2017 to First Examiners Report mailed Jul. 14, 2017", 24 pgs. cited by applicant

"Australian Application Serial No. 2014231680, First Examiners Report mailed Aug. 4, 2017", 4 pgs. cited by applicant

"Australian Application Serial No. 2014231681, First Examiners Report mailed Jul. 12, 2017", 4 pgs. cited by applicant

"Australian Application Serial No. 2014231681, Response filed Jan. 30, 2018 to Subsequent Examiners Report mailed Sep. 26, 2017", 15 pgs. cited by applicant

"Australian Application Serial No. 2014231681, Response filed Apr. 26, 2018 to Subsequent Examiners Report mailed Mar. 13, 2018", 3 pgs. cited by applicant

"Australian Application Serial No. 2014231681, Response filed Sep. 15, 2017 to First Examiners Report mailed Jul. 12, 2017", 9 pgs. cited by applicant

"Australian Application Serial No. 2014231681, Subsequent Examiners Report mailed Mar. 13, 2018", 4 pgs. cited by applicant

"Australian Application Serial No. 2014231681, Subsequent Examiners Report mailed Sep. 26, 2017", 4 pgs. cited by applicant

"Australian Application Serial No. 2015230799, First Examiner Report mailed Mar. 27, 2017", 10 pgs. cited by applicant

"Australian Application Serial No. 2015230799, Response filed Feb. 16, 2018 to First Examiner Report mailed Mar. 27, 2017", 24 pgs. cited by applicant

"Australian Application Serial No. 2015306040, First Examination Report mailed Nov. 8, 2019", 14 pgs. cited by applicant

"Australian Application Serial No. 2016265882, First Examination Report mailed Aug. 5, 2020", 4 pgs. cited by applicant

"Australian Application Serial No. 2016265883, First Examination Report mailed Sep. 22, 2020", 4 pgs. cited by applicant

"Australian Application Serial No. 2016281963, First Examination Report mailed Oct. 15, 2020", 5 pgs. cited by applicant

"Australian Application Serial No. 2017204552, First Examination Report mailed Oct. 9, 2018", 3 pgs. cited by applicant

"Australian Application Serial No. 2017228937, First Examination Report mailed Jan. 6, 2022", 3 pgs. cited by applicant

"Australian Application Serial No. 2018202342, First Examination Report mailed Jun. 17, 2019", 5 pgs. cited by applicant

"Australian Application Serial No. 2018202342, Response filed Aug. 1, 2019 to First Examination Report mailed Jun. 17, 2019", 17 pgs. cited by applicant

"Australian Application Serial No. 2018202342, Subsequent Examiners Report mailed Aug. 23, 2019", 4 pgs. cited by applicant

"Australian Application Serial No. 2018204774, First Examination Report mailed Jul. 18, 2019", 4 pgs. cited by applicant

"Australian Application Serial No. 2018204774, Response filed May 28, 2020 to First Examination Report mailed Jul. 18, 2019", 14 pgs. cited by applicant

"Australian Application Serial No. 2018226496, First Examination Report mailed Jul. 25, 2019", 4 pgs. cited by applicant

"Australian Application Serial No. 2018236791, First Examination Report mailed Mar. 2, 2020", 3 pgs. cited by applicant

"Australian Application Serial No. 2018236791, Response filed Jun. 9, 2020 to First Examination Report mailed Mar. 2, 2020", 12 pgs. cited by applicant

"Australian Application Serial No. 2018236791, Voluntary Amendment filed Dec. 3, 2018", 8 pgs. cited by applicant

"Australian Application Serial No. 2019201063, First Examination Report mailed Aug. 6, 2019", 7 pgs. cited by applicant

"Australian Application Serial No. 2019250148, First Examination Report mailed Nov. 23, 2020", 5 pgs. cited by applicant

"Canadian Application Serial No. 2,801,352, Office Action mailed Jul. 4, 2017", 3 pgs. cited by applicant

"Canadian Application Serial No. 2,801,352, Office Action mailed Aug. 2, 2018", 3 pgs. cited by applicant

"Canadian Application Serial No. 2,801,352, Office Action mailed Aug. 15, 2016", 3 pgs. cited by applicant

"Canadian Application Serial No. 2,801,352, Response filed Jan. 29, 2019 to Office Action mailed Aug. 2, 2018", 12 pgs. cited by applicant

"Canadian Application Serial No. 2,801,352, Response filed Feb. 8, 2017 to Office Action mailed Aug. 15, 2016", 89 pgs. cited by applicant

"Canadian Application Serial No. 2,801,352, Response filed Dec. 18, 2017 to Office Action mailed Jul. 4, 2017", 8 pgs. cited by applicant

"Canadian Application Serial No. 2,843,763, Office Action mailed Dec. 4, 2014", 3 pgs. cited by applicant

"Canadian Application Serial No. 2,843,763, Response filed May 12, 2015 to Office Action mailed Dec. 4, 2014", 31 pgs. cited by applicant

"Canadian Application Serial No. 2,880,350 Examiner's Rule 86 2 Requisition mailed Jun. 20, 2022", 3 pgs. cited by applicant

"Canadian Application Serial No. 2,880,350, Examiner's Rule 30(2) Requisition mailed May 01, 2019", 4 pgs. cited by applicant

"Canadian Application Serial No. 2,880,350, Response filed Oct. 6, 2022 to Examiner's Rule 86 2 Requisition mailed Jun. 20, 2022", 25 pgs. cited by applicant

"Canadian Application Serial No. 2,880,350, Response filed Oct. 28, 2020 to Examiner's Rule 30(2) Requisition mailed May 1, 2019", 36 pgs. cited by applicant

"Canadian Application Serial No. 2,880,350, Voluntary Amendment filed Apr. 29, 2021", 7 pgs. cited by applicant

"Canadian Application Serial No. 2,880,353, Office Action mailed Apr. 29, 19", 4 pgs. cited by applicant

"Canadian Application Serial No. 2,880,353, Response filed Oct. 29, 2019 to Office Action mailed Apr. 29, 2019", 28 pgs. cited by applicant

"Canadian Application Serial No. 2,901,483, Office Action mailed Jul. 19, 2017", 3 pgs. cited by applicant

"Canadian Application Serial No. 2,901,483, Office Action mailed Nov. 23, 2016", 4 pgs. cited by applicant

"Canadian Application Serial No. 2,901,483, Response filed Jan. 16, 2018 to Office Action mailed Jul. 19, 2017", 28 pgs. cited by applicant

"Canadian Application Serial No. 2,901,483, Response filed May 23, 2017 to Office Action mailed Nov. 23, 2016", 40 pgs. cited by applicant

"Canadian Application Serial No. 2,901,484, Office Action mailed Apr. 27, 2021", 4 pgs. cited by applicant

"Canadian Application Serial No. 2,901,484, Office Action mailed Jun. 5, 2020", 6 pgs. cited by applicant

"Canadian Application Serial No. 2,901,484, Office Action mailed Dec. 11, 2019", 6 pgs. cited by applicant

"Canadian Application Serial No. 2,901,484, Response filed Apr. 7, 2020 to Office Action mailed Dec. 11, 2019", 25 pgs. cited by applicant

"Canadian Application Serial No. 2,901,484, Response filed Aug. 26, 2021 to Office Action mailed Apr. 27, 2021", 9 pgs. cited by applicant

"Canadian Application Serial No. 2,901,484, Response filed Sep. 29, 2020 to Office Action mailed Jun. 5, 2020", 20 pgs. cited by applicant

"Canadian Application Serial No. 2,901,492, Office Action mailed Jan. 29, 2020", 4 pgs. cited by applicant

"Canadian Application Serial No. 2,901,495, Office Action mailed Jan. 29, 2020", 4 pgs. cited by applicant

"Canadian Application Serial No. 2,901,495, Response filed May 13, 21 to Office Action mailed Jan. 29, 2020", 23 pgs. cited by applicant

"Canadian Application Serial No. 2,904,224, Office Action mailed Jan. 3, 2020", 4 pgs. cited by applicant

"Canadian Application Serial No. 2,904,224, Response filed May 11, 2021 to Office Action mailed Jan. 3, 2020", 36 pgs. cited by applicant

"Canadian Application Serial No. 2,958,480, Office Action mailed Sep. 16, 2021", 4 pgs. cited by applicant

"Canadian Application Serial No. 2,958,480, Response filed Jan. 17, 2022 to Office Action mailed Sep. 16, 2021", 12 pgs. cited by applicant

"Canadian Application Serial No. 2,986,055, Office Action mailed Dec. 12, 2022", 5 pgs. cited by applicant

"Canadian Application Serial No. 2,986,058, Office Action mailed Jul. 27, 2022", 3 pgs. cited by applicant

"Canadian Application Serial No. 3,016,808, Non Final Office Action mailed Mar. 9, 2022", 3 pgs. cited by applicant

"Canadian Application Serial No. 3,016,808, Response filed Jul. 11, 2022 to Non Final Office Action mailed Mar. 9, 2022", w/o Claims, 2 pgs. cited by applicant

"Canadian Application Serial No. 3,016,808, Voluntary Amendment mailed Feb. 11, 2022.", 31 pgs. cited by applicant

"Canadian Application Serial No. 3,034,592, Office Action mailed Mar. 17, 2020", 5 pgs. cited by applicant

"Canadian Application Serial No. 3,034,592, Response filed Jul. 14, 2020 to Office Action mailed Mar. 17, 2020", 20 pgs. cited by applicant

"Canadian Application Serial No. 3,046,529, Office Action mailed Mar. 5, 2020", 4 pgs. cited by applicant

"Canadian Application Serial No. 3,046,529, Office Action mailed Sep. 18, 2019", 6 pgs. cited by applicant

"Canadian Application Serial No. 3,046,529, Response Filed Aug. 26, 2021 to Office Action mailed Mar. 5, 2020", 15 pgs. cited by applicant

"Canadian Application Serial No. 3,046,529, Response filed Nov. 14, 2019 to Office Action mailed Sep. 18, 2019", 9 pgs. cited by applicant

"Canadian Application Serial No. 3,060,323, Examiners Rule 86(2) Report mailed Sep. 13, 2023", 3 pgs. cited by applicant

"Canadian Application Serial No. 3,060,323, Response filed Jan. 11, 2024 to Examiners Rule 86(2) Report mailed Sep. 13, 2023", 20 pgs. cited by applicant

"Canadian Application Serial No. 3,060,328, Examiners Rule 86(2) Report mailed Jun. 23, 2023", 3 pgs. cited by applicant

"Canadian Application Serial No. 3,060,328, Response filed Oct. 5, 2023 to Examiners Rule 86(2) Report mailed Jun. 12, 2023", 21 pgs. cited by applicant

"Canadian Application Serial No. 3,060,332, Examiners Rule 86(2) Report mailed Jun. 13, 2023", 4 pgs. cited by applicant

"Canadian Application Serial No. 3,060,332, Response filed Oct. 10, 2023 to Examiners Rule 86(2) Report mailed Jun. 13, 2023", 31 pgs. cited by applicant

"Canadian Application Serial No. 3,167,769, Examiners Rule 86(2) Requisition mailed Jan. 13, 2023", 4 pgs. cited by applicant

"Canadian Application Serial No. 3129123 Examiner's Rule 86 2 Report mailed Nov. 25, 2022", 3 pgs. cited by applicant

"Canadian Application Serial No. 3148296, Examiners Rule 86(2) Requisition mailed Dec. 9, 2022", 3 pgs. cited by applicant

"Canadian Application Serial No. 3148296, Voluntary Amendment filed Jun. 30, 2022", 17 pgs. cited by applicant

"Chapter 8—Heating, Ventilating, and Air Conditioning (HVAC) Demonstration", HVAC Demonstration, (published prior to Feb. 21, 2014), 16 pgs. cited by applicant

"Chinese Application Serial No. 201280006006.9, Office Action mailed Feb. 2, 2016", w/ English Summary, 19 pgs. cited by applicant

"Chinese Application Serial No. 201280006006.9, Response filed Apr. 8, 2016 to Office Action mailed Feb. 2, 2016", w/ English Translation of Claims, 64 pgs. cited by applicant

"Chinese Application Serial No. 201280006006.9, Voluntary Amendment filed Apr. 14, 2014", w/ English Translation of Claims, 83 pgs. cited by applicant

"Chinese Application Serial No. 201180031103.9, Office Action mailed Feb. 11, 2015", w/ English Translation, 16 pgs. cited by applicant

"Chinese Application Serial No. 201180031103.9, Office Action mailed Jun. 13, 2014", w/ English Translation, 19 pgs. cited by applicant

“Chinese Application Serial No. 201180031103.9, Office Action mailed Sep. 9, 2015”, w/ English Translation, 7 pgs. cited by applicant

“Chinese Application Serial No. 201180031103.9, Office Action mailed Nov. 6, 2015”, w/ English Translation, 5 pgs. cited by applicant

“Chinese Application Serial No. 201180031103.9, Response filed Apr. 27, 2015 to Office Action mailed Feb. 11, 2015”, w/ English Translation, 15 pgs. cited by applicant

“Chinese Application Serial No. 201180031103.9, Response filed Sep. 26, 2014 to Office Action mailed Jun. 13, 2014”, w/ English Translation, 12 pgs. cited by applicant

“Chinese Application Serial No. 201180031103.9, Response filed Sep. 29, 2015 to Office Action mailed Sep. 9, 2015”, w/ English Translation, 78 pgs. cited by applicant

“Chinese Application Serial No. 201280006006.9, Office Action mailed May 13, 2015”, w/ English Translation, 7 pgs. cited by applicant

“Chinese Application Serial No. 201280006006.9, Office Action mailed Aug. 15, 2016”, w/ English Translation, 18 pgs. cited by applicant

“Chinese Application Serial No. 201280006006.9, Response filed Sep. 28, 2015 to Office Action mailed May 13, 2015”, w/ English Translation of Claims, 71 pgs. cited by applicant

“Chinese Application Serial No. 201280006006.9, Response filed Dec. 30, 2016 to Office Action mailed Aug. 15, 2016”, w/ English Translation of Claims, 69 pgs. cited by applicant

“Chinese Application Serial No. 201280042778.8, Office Action mailed Feb. 3, 2016”, w/ English Translation, 9 pgs. cited by applicant

“Chinese Application Serial No. 201280042778.8, Office Action mailed Sep. 7, 2016”, w/ English Translation of Claims, 17 pgs. cited by applicant

“Chinese Application Serial No. 201280042778.8, Response filed May 25, 2016 to Office Action mailed Feb. 3, 2016”, w/ English Translation, 11 pgs. cited by applicant

“Chinese Application Serial No. 201280042778.8, Response filed Nov. 16, 2016 to Office Action mailed Sep. 7, 2016”, w/ English Translation, 44 pgs. cited by applicant

“Chinese Application Serial No. 201380042926.0, Decision of Reexamination—Upholding Decision of Rejection mailed Mar. 15, 2019”, w/ English Translation, 18 pgs. cited by applicant

“Chinese Application Serial No. 201380042926.0, Decision of Rejection mailed Jan. 5, 2018”, w/ English Claims, 11 pgs. cited by applicant

“Chinese Application Serial No. 201380042926.0, Notice of Reexamination mailed Aug. 23, 2018”, w/ English Machine Translation, 18 pgs. cited by applicant

“Chinese Application Serial No. 201380042926.0, Office Action mailed Feb. 26, 2016”, w/ English Translation, 15 pgs. cited by applicant

“Chinese Application Serial No. 201380042926.0, Office Action mailed May 11, 2017”, W/ English Translation, 13 pgs. cited by applicant

“Chinese Application Serial No. 201380042926.0, Office Action mailed Sep. 28, 2016”, w/ English Translation, 12 pgs. cited by applicant

“Chinese Application Serial No. 201380042926.0, Request for Reexamination filed Apr. 20, 2018 to Decision of Rejection mailed Jan. 5, 2018”, w/ English claims, 52 pgs. cited by applicant

“Chinese Application Serial No. 201380042926.0, Response filed Feb. 13, 2017 to Office Action mailed Sep. 28, 2016”, w/ English Translation of Amended Claims, 56 pgs. cited by applicant

“Chinese Application Serial No. 201380042926.0, Response filed Jul. 7, 2016 to Office Action mailed Feb. 26, 2016”, w/ English Translation of Claims, 40 pgs. cited by applicant

“Chinese Application Serial No. 201380042926.0, Response filed Sep. 26, 2017 to Office Action mailed May 11, 2017”, w/ English Translation of Claims (not amended), 13 pgs. cited by applicant

“Chinese Application Serial No. 201380042926.0, Response filed Dec. 7, 2018 to Notice of Reexamination mailed Aug. 23, 2018”, w/ English Translation, 15 pgs. cited by applicant

“Chinese Application Serial No. 201380044484.3, Examiner Interview Summary Jan. 3, 2018”, w/ English Translation, 1 pg. cited by applicant

“Chinese Application Serial No. 201380044484.3, Office Action mailed Jan. 13, 2017”, w/ English Translation, 16 pgs. cited by applicant

“Chinese Application Serial No. 201380044484.3, Office Action mailed Mar. 28, 2016”, w/ English Translation, 16 pgs. cited by applicant

“Chinese Application Serial No. 201380044484.3, Office Action mailed Jul. 31, 2017”, w/ English Translation, 21 pgs. cited by applicant

“Chinese Application Serial No. 201380044484.3, Response filed Jan. 3, 2018 to Examiner Interview Summary Jan. 3, 2018”, w/ English claims, 53 pgs. cited by applicant

“Chinese Application Serial No. 201380044484.3, Response filed Mar. 28, 2017 to Office Action mailed Jan. 13, 2017”, w/ English Translation of Claims, 58 pgs. cited by applicant

“Chinese Application Serial No. 201380044484.3, Response filed Oct. 12, 2016 to Office Action mailed Mar. 28, 2016”, w/ English Translation of Claims, 54 pgs. cited by applicant

“Chinese Application Serial No. 201380044484.3, Response filed Oct. 12, 2017 to Office Action mailed Jul. 31, 2017”, w/ English Translation of Claims, 54 pgs. cited by applicant

“Chinese Application Serial No. 201480014783.7, Office Action mailed Mar. 26, 2018”, w/ English Translation, 16 pgs. cited by applicant

“Chinese Application Serial No. 201480014783.7, Office Action mailed Jun. 30, 2017”, w/ English Translation, 19 pgs. cited by applicant

“Chinese Application Serial No. 201480014783.7, Response filed Jun. 11, 2018 to Office Action mailed Mar. 26, 2018”, w/ English claims, 18 pgs. cited by applicant

“Chinese Application Serial No. 201480014783.7, Response filed Nov. 10, 2017 to Office Action mailed Jun. 30, 2017”, w/ English Claims, 48 pgs. cited by applicant

“Chinese Application Serial No. 201480015355.6, Decision of Rejection mailed Mar. 18, 2019”, w/ English Translation, 7 pgs. cited by applicant

“Chinese Application Serial No. 201480015355.6, Office Action mailed Jun. 14, 2018”, w/ English Translation, 16 pgs. cited by applicant

“Chinese Application Serial No. 201480015355.6, Office Action mailed Oct. 13, 2017”, w/ English Translation, 18 pgs. cited by applicant

“Chinese Application Serial No. 201480015355.6, Office Action mailed Nov. 28, 2016”, w/ English Translation, 16 pgs. cited by applicant

“Chinese Application Serial No. 201480015355.6, Response filed Feb. 28, 2018 to Office Action mailed Oct. 13, 2017”, w/ English claims, 36 pgs. cited by applicant

“Chinese Application Serial No. 201480015355.6, Response filed Jun. 13, 2017 to Office Action mailed Nov. 28, 2016”, w/ English Translation of Claims, 36 pgs. cited by applicant

“Chinese Application Serial No. 201480015355.6, Response filed Dec. 4, 2018 to Office Action mailed Jun. 14, 2018”, w/ English claims, 16 pgs. cited by applicant

“Chinese Application Serial No. 201480015422.4, Office Action mailed Nov. 1, 2016”, w/ English Translation, 13 pgs. cited by applicant

“Chinese Application Serial No. 201480015422.4, Response filed May 12, 2017 to Office Action mailed Nov. 1, 2016”, w/ English Translation of Claims, 47 pgs. cited by applicant

“Chinese Application Serial No. 201480015766.5, Office Action mailed Oct. 19, 2016”, w/ English Translation, 9 pgs. cited by applicant

“Chinese Application Serial No. 201480015766.5, Response filed Jan. 20, 2017 to Office Action mailed Oct. 19, 2016”, w/ English Translation of Claims, 52 pgs. cited by applicant

“Chinese Application Serial No. 201480016150.X, Office Action mailed Jun. 19, 2017”, w/ English Translation, 22 pgs. cited by applicant

“Chinese Application Serial No. 201480016150.X, Response filed Nov. 2, 2017 to Office Action mailed Jun. 19, 2017”, w/ English Claims, 82 pgs. cited by applicant

“Chinese Application Serial No. 201580053421.3, Office Action mailed Sep. 17, 2019”, w/ English Translation, 31 pgs. cited by applicant

“Chinese Application Serial No. 201680038134.X, Office Action mailed Apr. 7, 2020”, with English translation, 29 pages. cited by applicant

“Chinese Application Serial No. 201680038134.X, Office Action mailed Jul. 8, 2019”, w/ English Translation, 30 pgs. cited by applicant

“Chinese Application Serial No. 201680038134.X, Response filed Jan. 23, 2020 to Office Action mailed Jul. 8, 2019”, with English claims, 32 pages. cited by applicant

“Chinese Application Serial No. 201680038134.X, Response filed Aug. 24, 2020 to Office Action mailed Apr. 7, 2020”, with English claims, 24 pages. cited by applicant

“Chinese Application Serial No. 201680038134.X, Response to Examiner Telephone Interview filed Oct. 20, 2020”, with English claims, 26 pages. cited by applicant

“Chinese Application Serial No. 201680038135.4, Office Action mailed Apr. 8, 2021”, with English Machine Translation, 7 pages. cited by applicant

“Chinese Application Serial No. 201680038135.4, Office Action mailed Jun. 28, 2020”, with English translation, 25 pages. cited by applicant

“Chinese Application Serial No. 201680038135.4, Office Action mailed Aug. 26, 2019”, w/ English Translation, 23 pgs. cited by applicant

“Chinese Application Serial No. 201680038135.4, Response filed Mar. 10, 2020 to First Office Action mailed Aug. 26, 2019”, with English claims, 12 pages. cited by applicant

“Chinese Application Serial No. 201680038135.4, Response filed Nov. 13, 2020 to Office Action mailed Jun. 28, 2020”, with current English claims, claims not amended in response filed, 8 pages. cited by applicant

“Chinese Application Serial No. 201680048895.3, Office Action mailed Apr. 15, 2020”, with English translation, 12 pages. cited by applicant

“Chinese Application Serial No. 201680048895.3, Office Action mailed Apr. 17, 2019”, w/ English Translation, 33 pgs. cited by applicant

“Chinese Application Serial No. 201680048895.3, Response filed Aug. 31, 2020 to Office Action mailed Apr. 15, 2020”, with English claims, 25 pages. cited by applicant

“Chinese Application Serial No. 201680048895.3, Response filed Nov. 4, 2019 to Office Action mailed Apr. 17, 2019”, with English claims, 29 pages. cited by applicant

“Chinese Application Serial No. 201680048895.3, Response to Examiner Telephone Interview filed Oct. 22, 2020”, with English claims, 22 pages. cited by applicant

“Chinese Application Serial No. 201710339973.1, Office Action mailed Apr. 26, 2019”, w/ English Translation, 9 pgs. cited by applicant

“Chinese Application Serial No. 201710339973.1, Response filed Jul. 3, 2019 to Office Action mailed Apr. 26, 2019”, w/ English Claims, 14 pgs. cited by applicant

“Chinese Application Serial No. 201710708143.1, Office Action mailed Aug. 16, 2019”, w/ English Translation, 10 pgs. cited by applicant

“Chinese Application Serial No. 201710708143.1, Office Action mailed Dec. 29, 2018”, w/ English Translation, 9 pgs. cited by applicant

“Chinese Application Serial No. 201710708143.1, Response filed Apr. 29, 2019 to Office Action mailed Dec. 29, 2018”, w/ English Claims, 10 pgs. cited by applicant

“Chinese Application Serial No. 201710708143.1, Response filed Sep. 27, 2019 to Office Action mailed Aug. 16, 2019”, with English claims, 10 pages. cited by applicant

“Chinese Application Serial No. 201780027034.1, Office Action mailed Mar. 5, 2021”, with English translation, 7 pages. cited by applicant

“Chinese Application Serial No. 201780027034.1, Office Action mailed Apr. 13, 2020”, with English translation, 35 pages. cited by applicant

“Chinese Application Serial No. 201780027034.1, Response filed Oct. 28, 2020 to Office Action mailed Apr. 13, 2020”, with English claims, 46 pages. cited by applicant

“Chinese Application Serial No. 201780027034.1, Response filed Oct. 28, 2020 to Office Action

mailed Apr. 13, 2020”, with English claims, 39 pages. cited by applicant

“Chinese Application Serial No. 201780092213.3, Decision of Rejection mailed Dec. 30, 2021”, with machine English translation, 19 pages. cited by applicant

“Chinese Application Serial No. 201780092213.3, Notice of Reexamination mailed Feb. 5, 2024”, With English Machine Translation, 3 pgs. cited by applicant

“Chinese Application Serial No. 201780092213.3, Notice of Reexamination mailed Oct. 27, 2023”, With English machine translation, 27 pgs. cited by applicant

“Chinese Application Serial No. 201780092213.3, Response filed Oct. 21, 2021 to Office Action mailed Aug. 6, 2021”, with English claims, 13 pages. cited by applicant

“Chinese Application Serial No. 201780092213.3, Response Filed Apr. 14, 2022 to Decision of Rejection mailed Dec. 30, 2021”, With English machine translation, 14 pgs. cited by applicant

“Chinese Application Serial No. 201780092237.9, Decision of Rejection mailed Jan. 21, 2022”, with Concise Statement of Relevance, 12 pages. cited by applicant

“Chinese Application Serial No. 201780092237.9, Response filed Oct. 12, 2021 to Office Action mailed Jul. 28, 2021”, with English claims, 16 pages. cited by applicant

“Chinese Application Serial No. 201810432187.0, Office Action mailed Jan. 16, 2020”, with English translation, 12 pages. cited by applicant

“Chinese Application Serial No. 201910516006.7, Office Action mailed Mar. 1, 2021”, with English Summary, 9 pages. cited by applicant

“Chinese Application Serial No. 201910516006.7, Office Action mailed Jul. 2, 2020”, with English translation, 16 pages. cited by applicant

“Chinese Application Serial No. 201910516006.7, Response filed Jan. 18, 2021 to Office Action mailed Jul. 2, 2020”, with English claims, 21 pages. cited by applicant

“Chinese Application Serial No. 201910516006.7, Voluntary Amendment filed Feb. 10, 2020”, with English claims, 15 pages. cited by applicant

“Chinese Application Serial No. 202210506642.3, Office Action mailed Sep. 12, 2023”, w/ English Translation, 73 pgs. cited by applicant

“Chinese Application Serial No. 202210506642.3, Voluntary Amendment filed Dec. 13, 2022”, w/ English Claims, 40 pgs. cited by applicant

“Dehumidification Solutions”, Des Champs Laboratories, Inc., (2001), 18 pgs. cited by applicant

“Desi-Wringer™ Precision Desiccant Dehumidification Systems”, Des Champs Technologies, (2007), 12 pgs. cited by applicant

“Energy Recovery—Fresh In Air Quality”, SEMCO Inc., (published before Apr. 12, 2012), 131 pgs. cited by applicant

“European Application Serial No. 11797695.1, Communication Pursuant to Article 94(3) EPC mailed Jan. 12, 2022”, 7 pgs. cited by applicant

“European Application Serial No. 11797695.1, Communication Pursuant to Article 94(3) EPC mailed Aug. 24, 2018”, 5 pgs. cited by applicant

“European Application Serial No. 11797695.1, Communication Pursuant to Article 94(3) EPC mailed Nov. 19, 2020”, 5 pgs. cited by applicant

“European Application Serial No. 11797695.1, Extended European Search Report mailed Jan. 25, 2016”, 11 pgs. cited by applicant

“European Application Serial No. 11797695.1, Partial Supplementary European Search Report mailed Oct. 7, 2015”, 6 pgs. cited by applicant

“European Application Serial No. 11797695.1, Response filed Jan. 9, 19 to Communication Pursuant to Article 94(3) EPC mailed Aug. 24, 2018”, 11 pgs. cited by applicant

“European Application Serial No. 11797695.1, Response filed Mar. 26, 2021 to Communication Pursuant to Article 94(3) EPC mailed Nov. 19, 2020”, 3 pgs. cited by applicant

“European Application Serial No. 11797695.1, Response filed Jul. 20, 2022 to Communication Pursuant to Article 94(3) EPC mailed Jan. 12, 2022”, 10 pgs. cited by applicant

“European Application Serial No. 11797695.1, Response filed Aug. 22, 2016 to Office Action mailed Feb. 11, 2016”, 9 pgs. cited by applicant

“European Application Serial No. 12736074.1, Extended European Search Report mailed Jul. 13, 2015”, 8 pgs. cited by applicant

“European Application Serial No. 12736074.1, Response filed Oct. 2, 2015 to Extended European Search Report mailed Jul. 13, 2015”, 10 pgs. cited by applicant

“European Application Serial No. 12827918.9, Extended European Search Report mailed Jul. 6, 2015”, 6 pgs. cited by applicant

“European Application Serial No. 12827918.9, Response filed Sep. 28, 2015 to Extended European Search Report mailed Jul. 6, 2015”, 8 pgs. cited by applicant

“European Application Serial No. 13830357.3, Extended European Search Report mailed Jun. 8, 2016”, 5 pgs. cited by applicant

“European Application Serial No. 13830357.3, Response filed Dec. 23, 2016 to Extended European Search Report mailed Jun. 8, 2016”, 11 pgs. cited by applicant

“European Application Serial No. 13830940.6, Extended European Search Report mailed Jul. 4, 2016”, 5 pgs. cited by applicant

“European Application Serial No. 13830940.6, Response filed Jan. 16, 2017 to Communication Pursuant to Rules 70(2) and 70a(2) EPC mailed Jul. 21, 2016”, 1 pg. cited by applicant

“European Application Serial No. 14764192.2, Extended European Search Report mailed Oct. 27, 2016”, 7 pgs. cited by applicant

“European Application Serial No. 14764192.2, Response filed Jan. 30, 2017 to Extended European Search Report mailed Oct. 27, 2016”, 19 pgs. cited by applicant

“European Application Serial No. 14764192.2, Response filed Apr. 13, 2016 to Communication Pursuant Rules 161(2) and 162 EPC mailed Nov. 19, 2015”, 9 pgs. cited by applicant

“European Application Serial No. 14764305.0, Communication Pursuant to Article 94(3) EPC Feb. 14, 2019”, 4 pgs. cited by applicant

“European Application Serial No. 14764305.0, Extended European Search Report mailed Apr. 4, 2017”, 8 pgs. cited by applicant

“European Application Serial No. 14764305.0, Response filed Apr. 13, 2016 to Communication Pursuant to Article 94(3) EPC mailed Oct. 8, 2015”, 10 pgs. cited by applicant

“European Application Serial No. 14764305.0, Response filed Jun. 21, 2019 to Communication Pursuant to Article 94(3) EPC Feb. 14, 2019”, 24 pgs. cited by applicant

“European Application Serial No. 14764305.0, Response filed Oct. 31, 2017 to Extended European Search Report mailed Apr. 4, 2017”, 7 pgs. cited by applicant

“European Application Serial No. 14764318.3, Extended European Search Report mailed Mar. 15, 2017”, 10 pgs. cited by applicant

“European Application Serial No. 14764318.3, Response filed Jan. 28, 2016 to Communication pursuant to Rules 161(1) and 162 EPC mailed Nov. 19, 2015”, 17 pgs. cited by applicant

“European Application Serial No. 14764318.3, Response filed Oct. 10, 2017 to Extended European Search Report mailed Mar. 15, 2017”, 11 pgs. cited by applicant

“European Application Serial No. 14764713.5, Communication pursuant to Article 94(3) EPC mailed Dec. 18, 2018”, 3 pgs. cited by applicant

“European Application Serial No. 14764713.5, Extended European Search Report mailed Dec. 9, 2016”, 6 pgs. cited by applicant

“European Application Serial No. 14764713.5, Response filed Jan. 28, 2016 to Communication pursuant to Rules 161(1) and 162 EPC mailed Dec. 2, 2015”, 9 pgs. cited by applicant

“European Application Serial No. 14764713.5, Response filed Jun. 28, 2019 to Communication pursuant to Article 94(3) EPC mailed Dec. 18, 2018”, 8 pgs. cited by applicant

“European Application Serial No. 14764713.5, Response filed Jul. 13, 2017 to Extended European Search Report mailed Dec. 9, 2016”, 9 pgs. cited by applicant

“European Application Serial No. 14765396.8, Communication Pursuant to Article 94(3) EPC mailed Dec. 5, 2018”, 4 pgs. cited by applicant

“European Application Serial No. 14765396.8, Extended European Search Report mailed Oct. 28, 2016”, 6 pgs. cited by applicant

“European Application Serial No. 14765396.8, Office Action mailed Nov. 20, 2015”, 2 pgs. cited by applicant

“European Application Serial No. 14765396.8, Response filed Jan. 29, 2016 to Office Action mailed Nov. 20, 2015”, 12 pgs. cited by applicant

“European Application Serial No. 14765396.8, Response filed May 23, 2019 to Communication Pursuant to Article 94(3) EPC mailed Dec. 5, 2018”, 16 pgs. cited by applicant

“European Application Serial No. 14765396.8, Response filed May 25, 2017 to Extended European Search Report mailed Oct. 28, 2016”, 5 pgs. cited by applicant

“European Application Serial No. 15834201.4, Extended European Search Report mailed Mar. 16, 2018”, 8 pgs. cited by applicant

“European Application Serial No. 15834201.4, Response filed Oct. 9, 2017 to Communication Pursuant to Rules 161(2) and 162 EPC mailed Mar. 29, 2017”, 15 pgs. cited by applicant

“European Application Serial No. 15834201.4, Response filed Oct. 15, 2018 to Extended European Search Report mailed Mar. 16, 2018”, 17 pgs. cited by applicant

“European Application Serial No. 16795581.4, Extended European Search Report mailed Feb. 12, 2019”, 9 pgs. cited by applicant

“European Application Serial No. 16795581.4, Response filed Aug. 6, 2018 to Communication Pursuant to Rules 161(2) and 162 EPC mailed Jan. 26, 2018”, 16 pgs. cited by applicant

“European Application Serial No. 16795581.4, Response filed Sep. 11, 2019 to Extended European Search Report mailed Feb. 12, 2019”, 14 pgs. cited by applicant

“European Application Serial No. 16795582.2, Extended European Search Report mailed Nov. 20, 2018”, 8 pgs. cited by applicant

“European Application Serial No. 16795582.2, Response filed Jun. 17, 2019 to Extended European Search Report mailed Nov. 20, 2018”, 16 pgs. cited by applicant

“European Application Serial No. 16795582.2, Response filed Jul. 17, 2018 to Communication Pursuant to Rules 161(2) and 162 EPC mailed Jan. 8, 2018”, 12 pgs. cited by applicant

“European Application Serial No. 16813836.0, Communication Pursuant to Article 94(3) EPC mailed Mar. 24, 2020”, 5 pgs. cited by applicant

“European Application Serial No. 16813836.0, Extended European Search Report mailed Mar. 25, 2019”, 9 pgs. cited by applicant

“European Application Serial No. 16813836.0, Partial Supplementary European Search Report mailed Dec. 5, 2018”, 11 pgs. cited by applicant

“European Application Serial No. 16813836.0, Response filed Aug. 3, 2020 to Communication Pursuant to Article 94(3) EPC mailed Mar. 24, 2020”, 8 pgs. cited by applicant

“European Application Serial No. 16813836.0, Response filed Aug. 21, 2018 to Communication Pursuant to Rules 161(2) and 162 EPC mailed Feb. 13, 2018”, 37 pgs. cited by applicant

“European Application Serial No. 16813836.0, Response to Extended European Search Report mailed Mar. 25, 2019”, 11 pgs. cited by applicant

“European Application Serial No. 17762365.9, Communication Pursuant to Article 94(3) EPC mailed Dec. 9, 2021”, 6 pgs. cited by applicant

“European Application Serial No. 17762365.9, Extended European Search Report mailed Oct. 17, 2019”, 8 pgs. cited by applicant

“European Application Serial No. 17762365.9, Response filed Apr. 19, 2022 to Communication Pursuant to Article 94(3) EPC mailed Dec. 9, 2021”, 29 pgs. cited by applicant

“European Application Serial No. 17762365.9, Response filed Apr. 25, 2019 to Communication Pursuant to Rules 161 and 162 mailed Oct. 16, 2018”, 12 pgs. cited by applicant

“European Application Serial No. 17762365.9, Response filed May 15, 2020 to Extended European Search Report mailed Oct. 17, 2019”, 13 pgs. cited by applicant

“European Application Serial No. 17906575.0, Communication Pursuant to Article 94(3) EPC mailed Oct. 31, 2022”, 4 pgs. cited by applicant

“European Application Serial No. 17906575.0, Response filed Mar. 8, 2023 to Communication Pursuant to Article 94(3) EPC mailed Oct. 31, 2022”, 17 pgs. cited by applicant

“European Application Serial No. 18153408.2, Communication Pursuant to Rule 55 EPC mailed May 17, 2018”, 2 pgs. cited by applicant

“European Application Serial No. 18153408.2, Extended European Search Report mailed Dec. 4, 2018”, 5 pgs. cited by applicant

“European Application Serial No. 18153408.2, Response filed Jul. 2, 2019 to Extended European Search Report mailed Dec. 4, 2018”, 12 pgs. cited by applicant

“European Application Serial No. 18160812.6, Communication Pursuant to Article 94(3) EPC mailed Nov. 19, 2020”, 4 pgs. cited by applicant

“European Application Serial No. 18160812.6, Extended European Search Report mailed Feb. 11, 2019”, 6 pgs. cited by applicant

“European Application Serial No. 18160812.6, Response filed Mar. 2, 2021 to Communication Pursuant to Article 94(3) EPC mailed Nov. 19, 2020”, 2 pgs. cited by applicant

“European Application Serial No. 18160812.6, Response filed Aug. 6, 2019 to Extended European Search Report mailed Feb. 11, 2019”, 23 pgs. cited by applicant

“European Application Serial No. 18211142.7, Extended European Search Report mailed Apr. 11, 2019”, 6 pgs. cited by applicant

“European Application Serial No. 18211142.7, Response filed Aug. 8, 2019 to Extended European Search Report mailed Apr. 11, 2019”, 10 pgs. cited by applicant

“European Application Serial No. 18214518.5, Extended European Search Report mailed Apr. 17, 2019”, 5 pgs. cited by applicant

“European Application Serial No. 18214518.5, Response filed Jul. 16, 2019 to Extended European Search Report mailed Apr. 17, 2019”, 3 pgs. cited by applicant

“European Application Serial No. 20180081.0, Extended European Search Report mailed Sep. 28, 2020”, 7 pgs. cited by applicant

“European Application Serial No. 20180081.0, Response filed Apr. 20, 2021 to Extended European Search Report mailed Sep. 28, 2020”, 11 pgs. cited by applicant

“European Application Serial No. 21154403.6, Extended European Search Report mailed Apr. 26, 2021”, 8 pgs. cited by applicant

“European Application Serial No. 21154403.6, Response filed Dec. 9, 2021 to Extended European Search Report mailed Apr. 26, 2021”, 15 pgs. cited by applicant

“European Application Serial No. 21212796.3, Extended European Search Report mailed Aug. 1, 2022”, 11 pgs. cited by applicant

“European Application Serial No. 23155095.5, Extended European Search Report mailed Mar. 31, 2023”, 11 pgs. cited by applicant

“European Application Serial No. 23155095.5, Response filed Dec. 12, 2023 to Extended European Search Report mailed Mar. 31, 2023”, 12 pgs. cited by applicant

“Indian Application Serial No. 201717044889, First Examination Report dated Dec. 17, 2020”, with English translation, 6 pages. cited by applicant

“Indian Application Serial No. 201717044889, Response filed Jun. 14, 2021 to First Examination Report dated Dec. 17, 2020”, with English translation, 82 pages. cited by applicant

“Indian Application Serial No. 201717044890, First Examination Report mailed Oct. 23, 2020”, with English translation, 6 pages. cited by applicant

“Indian Application Serial No. 201817002765, First Examination Report mailed Dec. 24, 2019”, with English translation, 6 pages. cited by applicant

“Indian Application Serial No. 201817002765, Response filed Sep. 24, 2020 to First Examination Report mailed Dec. 24, 2019”, with English translation, 30 pages. cited by applicant

“Indian Application Serial No. 201817037404, First Examination Report mailed Feb. 19, 2021”, with English translation, 7 pages. cited by applicant

“Indian Application Serial No. 201817037404, Response filed Aug. 16, 2021 to First Examination Report mailed Feb. 19, 2021”, 24 pgs. cited by applicant

“Indian Application Serial No. 201917046207, Hearing Notice mailed Dec. 26, 2023”, 3 pgs. cited by applicant

“Indian Application Serial No. 201917046207, Response filed Jul. 20, 2022 to First Examination Report mailed Sep. 20, 2021”, 34 pgs. cited by applicant

“Indian Application Serial No. 201917046210, Response filed Oct. 4, 2021 to First Examination Report mailed Jun. 9, 2021”, 26 pgs. cited by applicant

“Indian Application Serial No. 201917046215, Hearing Notice mailed Jan. 11, 2024”, 3 pgs. cited by applicant

“Indian Application Serial No. 201917046215, Hearing Notice mailed Feb. 2, 2024”, 3 pgs. cited by applicant

“Indian Application Serial No. 201917046215, Hearing Notice mailed Feb. 20, 2024”, 3 pgs. cited by applicant

“Indian Application Serial No. 201917046215, Response filed Mar. 31, 2022 to First Examination Report mailed Sep. 9, 2021”, 50 pgs. cited by applicant

“Indian Application Serial No. 201917046215, Written Submission filed Mar. 15, 2024”, 154 pgs. cited by applicant

“International Application Serial No. PCT/CA2012/000055, International Preliminary Report on Patentability mailed Aug. 1, 2013”, 9 pgs. cited by applicant

“International Application Serial No. PCT/CA2012/000055, International Search Report mailed May 24, 2012”, 4 pgs. cited by applicant

“International Application Serial No. PCT/CA2012/000055, Invitation to Pay Add'l Fees and Partial Search Report Mailed Mar. 23, 2012”, 2 pgs. cited by applicant

“International Application Serial No. PCT/CA2012/000055, Written Opinion mailed May 24, 2012”, 7 pgs. cited by applicant

“International Application Serial No. PCT/CA2012/00055, International Preliminary Report on Patentability mailed Aug. 1, 2013”, 9 pgs. cited by applicant

“International Application Serial No. PCT/CA2012/00055, International Search Report mailed May 24, 2012”, 4 pgs. cited by applicant

“International Application Serial No. PCT/CA2012/00055, Written Opinion mailed May 24, 2012”, 7 pgs. cited by applicant

“International Application Serial No. PCT/CA2012/000749, International Search Report mailed Oct. 26, 2012”, 3 pgs. cited by applicant

“International Application Serial No. PCT/CA2012/000749, Written Opinion mailed Oct. 26, 2012”, 5 pgs. cited by applicant

“International Application Serial No. PCT/CA2013/000608, International Preliminary Report on Patentability mailed Mar. 5, 2015”, 7 pgs. cited by applicant

“International Application Serial No. PCT/CA2013/000608, International Search Report mailed Sep. 23, 2013”, 3 pgs. cited by applicant

“International Application Serial No. PCT/CA2013/000608, Written Opinion mailed Sep. 23, 2013”, 5 pgs. cited by applicant

“International Application Serial No. PCT/CA2013/000609, International Preliminary Report on Patentability mailed Mar. 5, 2015”, 7 pgs. cited by applicant

“International Application Serial No. PCT/CA2013/000609, International Search Report mailed Sep. 17, 2013”, 3 pgs. cited by applicant

“International Application Serial No. PCT/CA2013/000609, Written Opinion mailed Sep. 17, 2013”, 5 pgs. cited by applicant

“International Application Serial No. PCT/CA2013/000964, International Search Report mailed Feb. 7, 2014”, 3 pgs. cited by applicant

“International Application Serial No. PCT/CA2013/000964, Written Opinion mailed Feb. 7, 2014”, 6 pgs. cited by applicant

“International Application Serial No. PCT/CA2014/000048, International Preliminary Report on Patentability mailed Sep. 24, 2015”, 8 pgs. cited by applicant

“International Application Serial No. PCT/CA2014/000048, International Search Report mailed Apr. 29, 2014”, 3 pgs. cited by applicant

“International Application Serial No. PCT/CA2014/000048, Written Opinion mailed Apr. 29, 2014”, 6 pgs. cited by applicant

“International Application Serial No. PCT/CA2014/000083, International Preliminary Report on Patentability mailed Sep. 24, 2015”, 9 pgs. cited by applicant

“International Application Serial No. PCT/CA2014/000083, International Search Report mailed May 14, 2014”, 3 pgs. cited by applicant

“International Application Serial No. PCT/CA2014/000083, Written Opinion mailed May 14, 2014”, 7 pgs. cited by applicant

“International Application Serial No. PCT/CA2014/000148, International Preliminary Report on Patentability mailed Sep. 24, 2015”, 5 pgs. cited by applicant

“International Application Serial No. PCT/CA2014/000148, International Search Report mailed May 9, 2014”, 4 pgs. cited by applicant

“International Application Serial No. PCT/CA2014/000148, Written Opinion mailed May 9, 2014”, 3 pgs. cited by applicant

“International Application Serial No. PCT/CA2014/000169, International Preliminary Report on Patentability mailed Sep. 24, 2015”, 8 pgs. cited by applicant

“International Application Serial No. PCT/CA2014/000169, International Search Report mailed May 27, 2014”, 3 pgs. cited by applicant

“International Application Serial No. PCT/CA2014/000169, Written Opinion mailed May 27, 2014”, 6 pgs. cited by applicant

“International Application Serial No. PCT/CA2014/000171, International Preliminary Report on Patentability mailed Sep. 24, 2015”, 7 pgs. cited by applicant

“International Application Serial No. PCT/CA2014/000171, International Search Report mailed May 27, 2014”, 3 pgs. cited by applicant

“International Application Serial No. PCT/CA2014/000171, Written Opinion mailed May 27, 2014”, 5 pgs. cited by applicant

“International Application Serial No. PCT/CA2015/050570, International Search Report mailed Sep. 1, 2015”, 5 pgs. cited by applicant

“International Application Serial No. PCT/CA2015/050570, Written Opinion mailed Sep. 1, 2015”, 4 pgs. cited by applicant

“International Application Serial No. PCT/CA2015/050787, International Search Report mailed Nov. 4, 2015”, 3 pgs. cited by applicant

“International Application Serial No. PCT/CA2015/050787, Written Opinion mailed Nov. 4, 2015”, 3 pgs. cited by applicant

“International Application Serial No. PCT/CA2016/050252, International Preliminary Report on Patentability mailed Nov. 30, 2017”, 6 pgs. cited by applicant

“International Application Serial No. PCT/CA2016/050252, International Search Report mailed May 26, 2016”, 3 pgs. cited by applicant

“International Application Serial No. PCT/CA2016/050252, Written Opinion mailed May 26, 2016”, 4 pgs. cited by applicant

“International Application Serial No. PCT/CA2016/050507, International Preliminary Report on Patentability mailed Nov. 30, 2017”, 5 pgs. cited by applicant

“International Application Serial No. PCT/CA2016/050507, International Search Report mailed Jul. 21, 2016”, 3 pgs. cited by applicant

“International Application Serial No. PCT/CA2016/050507, Written Opinion mailed Jul. 21, 2016”, 3 pgs. cited by applicant

“International Application Serial No. PCT/CA2017/050180, International Preliminary Report on Patentability mailed Sep. 20, 2018”, 6 pgs. cited by applicant

“International Application Serial No. PCT/CA2017/050180, International Search Report mailed Apr. 26, 2017”, 3 pgs. cited by applicant

“International Application Serial No. PCT/CA2017/050180, Written Opinion mailed Apr. 26, 2017”, 4 pgs. cited by applicant

“International Application Serial No. PCT/IB2011/002145, International Preliminary Report on Patentability mailed Jan. 10, 2013”, 13 pgs. cited by applicant

“International Application Serial No. PCT/IB2011/002145, International Search Report mailed Feb. 15, 2012”, 7 pgs. cited by applicant

“International Application Serial No. PCT/IB2011/002145, Written Opinion mailed Feb. 15, 2012”, 11 pgs. cited by applicant

“International Application Serial No. PCT/IB2016/053799, International Preliminary Report on Patentability mailed Jan. 4, 2018”, 8 pgs. cited by applicant

“International Application Serial No. PCT/IB2016/053799, International Search Report mailed Aug. 26, 2016”, 3 pgs. cited by applicant

“International Application Serial No. PCT/IB2016/053799, Written Opinion mailed Aug. 26, 2016”, 6 pgs. cited by applicant

“International Application Serial No. PCT/US00/02956, International Preliminary Report on Patentability dated Jul. 9, 2001”, 3 pgs. cited by applicant

“International Application Serial No. PCT/US00/02956, International Search Report mailed Nov. 8, 2000”, 1 pg. cited by applicant

“Machine Translation of JP 09113167 A”, Espacenet Patent Translate, [Online] Retrieved from the internet: <URL: https://worldwide.espacenet.com/publicationDetails/description?CC=JP&NR=H09113167A&KC=A&FT=D&ND=3&date=19970502&DB=&locale=en_EP>, (retrieved Dec. 24, 2018), 7 pgs. cited by applicant

“Meeting Programs”, ASHRAE Technical Committee, (1997-2001), 13 pgs. cited by applicant

“Munters PFC Polymer Fluid Cooler”, Munters Corp., (Sep. 2015), 2 pgs. cited by applicant

“Oasis PFC Polymer Fluid Cooler Product Information”, Munters Corp., (Nov. 2013), 2 pgs. cited by applicant

“Plane plate membrane contactor prototypes”, University of Genoa, (Published prior to Mar. 28, 2013), 1 pg. cited by applicant

“Singapore Application Serial No. 11201710777Y, Office Action mailed Jan. 31, 2019”, in English, 7 pgs. cited by applicant

“Singapore Application Serial No. 11201710777Y, Response filed Jul. 1, 2019 to Office Action mailed Jan. 31, 2019”, in English, 31 pgs. cited by applicant

“Singaporean Application Serial No. 11201709404P, Response filed Jul. 22, 2019 to Written Opinion mailed Feb. 22, 2019”, in English, 62 pgs. cited by applicant

“Singaporean Application Serial No. 11201709404P, Written Opinion mailed Feb. 22, 2019”, in English, 8 pgs. cited by applicant

“Singaporean Application Serial No. 11201909648V, Response filed Jan. 25, 2022 to Written Opinion dated Aug. 2025, 21”, 16 pgs. cited by applicant

“Singaporean Application Serial No. 11201909695X, Response Filed Jan. 26, 2022 to Written Opinion mailed Aug. 26, 2021”, W/out English Claims, 6 pgs. cited by applicant

“Translation of CN 201906567 U”, Espacenet Patent Translate, [Online] Retrieved from the internet: <URL: http://translationportal.epo.org/emtp/translate/?ACTION=description-retrieval&COUNTRY=CN&ENGINE=google&FORMAT=docdb&KIND=U&LOCALE=en_EP&NUMBER=201906567&OPS=ops.epo.org/3.2&SRCLANG=zh&TRGLANG=en>, (Feb. 2, 2018), 4 pgs. cited by applicant

“Two-Wheel Desiccant Dehumidification System—Technology for Dehumidification and Improving Indoor Air Quality”, Federal Technology Alert, (Apr. 1997), 24 pgs. cited by applicant

Abdel-Salam, Mohamed R.H., et al., “Design and testing of a novel 3-fluid liquid-to-air membrane energy exchanger (3-fluid LAMEE)”, International Journal of Heat and Mass Transfer 92, (2016), 312-329. cited by applicant

Abdel-Salam, Mohamed R. H., et al., “Experimental Study of Effects of Phase-Change Energy and Operating Parameters on Performances of Two-Fluid and Three-Fluid Liquid-to- Air Membrane Energy Exchangers”, ASHRAE Transactions, vol. 122, Part 1, (Jan. 2016), 134-145. cited by applicant

Abdel-Salam, Mohamed R. H., et al., “Performance testing of 2-fluid and 3-fluid liquid-to-air membrane energy exchangers for HVAC applications in cold-dry climates”, International Journal of Heat and Mass Transfer, 106, (2017), 12 pgs. cited by applicant

Abdel-Salam, Mohamed R.H., et al., “Performance Testing of a Novel 3-Fluid Liquid-to-Air Membrane Energy Exchanger (3-Fluid LAMEE) for HVAC Applications”, 28th Intl. Conference on Efficiency, Cost, Optimization, Simulation and Environmental Impact of Energy Systems (ECOS), Pau, France, (Jun. 30, 2015), 12 pgs. cited by applicant

Abdel-Salam, Mohamed R. H., et al., “Performance testing of a novel 3-fluid liquid-to-air membrane energy exchanger (3-fluid LAMEE) under desiccant solution regeneration operating conditions”, International Journal of Heat and Mass Transfer, 95, (2015), 14 pgs. cited by applicant

Acker, William, “Industrial Dehumidification: Water Vapor Load Calculations And System Descriptions”, HPAC Heating/Piping/Air Conditioning, (Mar. 1999), 49-59. cited by applicant

Bellia, L., et al., “Air Conditioning Systems With Desiccant Wheel for Italian Climates”, International Journal on Architectural Science, vol. 1 No. 4, (2000), 193-213. cited by applicant

Bergero, Stefano, et al., “On the performances of a hybrid air-conditioning system in different climatic conditions”, Energy 36(8), (2011), 13 pgs. cited by applicant

Bergero, Stefano, et al., “Performance analysis of a liquid desiccant and membrane contactor hybrid air-conditioning system”, Energy and Buildings 42, (2010), 11 pgs. cited by applicant

Chant, Eileen E., et al., “A Steady-State Simulation Of An Advanced Desiccant-Enhanced Cooling And Dehumidification System”, ASHRAE Transactions: Research, (Jul. 1992), 339-347. cited by applicant

Coad, William J., “Conditioning Ventilation Air for Improved Performance and Air Quality”, HPAC Heating/Piping/Air Conditioning, (Sep. 1999), 6 pgs. cited by applicant

Diblasio, Robert, “Desiccants in Hospitals - Conditioning A Research Facility”, Engineered Systems, (Sep. 1995), 4 pgs. cited by applicant

Downing, et al., “Operation and Maintenance for Quality Indoor Air”, Proc. of the 7th Symposium On Improving Building Systems in Hot and Humid Climates, Ft. Worth, TX, (Oct. 9, 1990), 5 pgs. cited by applicant

Downing, Chris, “Humidity Control - No. Place Like Home”, Engineered Systems, (1996), 4 pgs. cited by applicant

Erb, Blake, et al., “Experimental Measurements of a Run-Around Membrane Energy Exchanger (RAMEE) with Comparison to a Numerical Model”, ASHRAE Transactions, vol. 115, Part 2, (2009), 689-705. cited by applicant

Fischer, J., et al., “Active Desiccant Dehumidification Module Integration With Rooftop Packaged HVAC Units - Final Report Phase 3B”, Oak Ridge National Laboratory, Final Report: Phase 3B, (Mar. 2002), 36 pgs. cited by applicant

Fischer, John C., "Optimizing IAQ, Humidity Control, and Energy Efficiency In School Environments Through The Application Of Desiccant-Based Total Energy Recovery Systems", IAQ Atlanta: Paths to Better Building Environments/Environmental Effects on Health and Productivity, (1996), 16 pgs. cited by applicant

Harriman, III, et al., "Dehumidification and Cooling Loads From Ventilation Air", ASHRAE Journal, (Nov. 1997), 7 pgs. cited by applicant

Harriman, III, et al., "Evaluating Active Desiccant Systems For Ventilating Commercial Buildings", ASHRAE Journal, (Oct. 1999), 7 pgs. cited by applicant

Harriman, III, et al., "New Weather Data For Energy Calculations", ASHRAE Journal, (Mar. 1999), 7 pgs. cited by applicant

Jeong, et al., "Energy Conservation Benefits of a Dedicated Outdoor Air System with Parallel Sensible Cooling By Ceiling Radiant Panels", ASHRAE Transactions; vol. 109. Part 2, (2003), 10 pgs. cited by applicant

Karniadakis, George E., et al., "Minimum-dissipation transport enhancement by flow destabilization: Reynolds' analogy revisited", J. Fluid Mech vol. 192, (1988), 365-391. cited by applicant

Kosar, Douglas R., et al., "Dehumidification Issues of Standard 62-1989", ASHRAE Journal, (Mar. 1998), 71-75. cited by applicant

Larson, Michael D., et al., "The elastic and moisture transfer properties of polyethylene and polypropylene membranes for use in liquid-to-air energy exchangers", Journal of Membrane Science 302, (2007), 14 pgs. cited by applicant

Larson, Michael David, et al., "The Performance of Membranes in a Newly Proposed Run-Around Heat and Moisture Exchanger", MS Thesis in Mechanical Engineering, University of Saskatchewan, Saskatoon, Canada, [Online] Retrieved from the internet: <URL: [http://libran.usask.ca/theses/available/etd-12192006-094159/umestricted/Larson Thesis.pdf](http://libran.usask.ca/theses/available/etd-12192006-094159/umestricted/Larson%20Thesis.pdf)>, (Dec. 2006), 177 pgs. cited by applicant

Lepoudre, P., et al., "Channel Flow with Sinusoidal Screen Insert", Dept. of Mech Engineering, Univ. of Saskatchewan, Proceedings of the 19th Annual Conference of the CFD Society of Canada, Montreal, (Apr. 2011), 6 pgs. cited by applicant

Mahmud, Khizir, "Design and Performance Testing of Counter-Cross-Flow Run-Around Membrane Energy Exchanger System", MS Thesis in Mechanical Engineering, University of Saskatchewan, Saskatoon, Canada, [Online] Retrieved from the internet: < URL: <http://libranusask.ca/theses/available/etd-09092009-223833/umestricted/KhizirMahmud2009-Sep-28a.pdf>>, (Sep. 2009), 168 pgs. cited by applicant

Mahmud, Khizir, et al., "Performance testing of a counter-cross-flow run-around membrane energy exchanger (RAMEE) system for HVAC applications", Energy and Buildings, 42, (2010), 9 pgs. cited by applicant

McGahey, Kevin, et al., "Desiccants: Benefits for the Second Century of Air Conditioning", Proceedings of the 10th Symposium On Improving Building Systems In Hot and Humid Climates, Ft. Worth, Texas, (May 14, 1996), 9 pgs. cited by applicant

McGahey, Kevin, "New Commercial Applications For Desiccant-Based Cooling", ASHRAE Journal, (Jul. 1998), 41-45. cited by applicant

Mumma, Stanley A., et al., "Achieving Dry Outside Air in an Energy-Efficient Manner", ASHRAE Transactions 2001, vol. 107, Part 1, (2001), 8 pgs. cited by applicant

Mumma, Stanley A., "Dedicated Outdoor Air-Dual Wheel System Control Requirements", ASHRAE Transactions, vol. 107, Part 1, (2001), 9 pgs. cited by applicant

Mumma, Stanley A., et al., "Extension of the Multiple Spaces Concept of Ash Rae Standard 62 to Include Infiltration, Exhaust/Exfiltration, Interzonal Transfer, and Additional Short-Circuit Paths", ASHRAE Transactions: Symposia, (1998), 1232-1241. cited by applicant

Mumma, Stanley A, "Overview of Integrating Dedicated Outdoor Air Systems With Parallel

Terminal Systems”, ASHRAE Transactions vol. 107, Part 1, (2001), 7 pgs. cited by applicant

Nimmo, B. G., et al., “DEAC: Desiccant Enhancement of Cooling-Based Dehumidification”, ASHRAE Transactions: Symposia, (1993), 842-848. cited by applicant

Philip, Lepoudre, et al., “U.S. Appl. No. 15/574,205”, Specification, (Nov. 15, 2017), 32 pgs. cited by applicant

Philip, Lepoudre, et al., “U.S. Appl. No. 15/574,205”, Drawings, (Nov. 15, 2017), 9 pgs. cited by applicant

Philip, Lepoudre, et al., “U.S. Appl. No. 15/574,205”, Claims, (Nov. 15, 2017), 5 pgs. cited by applicant

Qin, C. K., et al., “Engine-driven Desiccant-assisted Hybrid Air-conditioning System”, 23rd World Gas Conference, Amsterdam, (2006), 15 pgs. cited by applicant

Ryan, K., et al., “Three-dimensional transition in the wake of bluff elongated cylinders”, J. Fluid Mech., vol. 538, (2005), 29 pgs. cited by applicant

Scofield, C. Mike, et al., “HVAC Design for Classrooms: Divide and Conquer”, Heating/Piping/Air Conditioning, (May 1993), 53-59. cited by applicant

Seigny, Scoot P., et al., “Air Handling Unit Direct Digital Control System Retrofit To Provide Acceptable Indoor Air Quality And Global Energy Optimization”, Energy Engineering, vol. 94, No. 5, (1997), 24-43. cited by applicant

Shank, Kurt M., et al., “Selecting the Supply Air Conditions for a Dedicated Outdoor Air System Working in Parallel with Distributed Sensible Cooling Terminal Equipment”, ASHRAE Transactions, vol. 107, Part 1, (2001), 10 pgs. cited by applicant

Smith, Christopher S., et al., “Outdoor Air, Heat Wheels and JC Penny: A New Approach to Retail Ventilation”, Proc. of the 11th Symposium On Improving Building Systems In Hot and Humid Climates, Ft. Worth, Texas, (Jun. 2, 1998), 1 pg. cited by applicant

Smith, James C., “Schools Resolve IAQ/Humidity Problems with Desiccant Preconditioning”, Heating/Piping/Air Conditioning, (Apr. 1996), 6 pgs. cited by applicant

Sonin, Ain A., et al., “Optimization of Flow Design in Forced Flow Electrochemical Systems, with Special Application to Electrodialysis”, Ind. Eng. Chem, Process Des. Develop vol. 13, No. 3, (1974), 8 pgs. cited by applicant

Swails, James F., et al., “A Cure for Growing Pains”, Consulting Specifying Engineer, [Online] Retrieved from the internet: <URL: <https://www.csemag.com>>, (Jun. 1997), 4 pgs. cited by applicant

Turpin, Joanna, “Dehumidification: The Problem No One Wants To Talk About”, [Online] Retrieved from the internet: <URL: http://www.esmagazine.com/copyrighVde12c1c879ba8010VgnVCM1 00000f932a8c0_?>, (Apr. 5, 2000), 6 pgs. cited by applicant

Vali, Alireza, “Modeling a Run-Around Heat and Moisture Exchanger Using Two Counter/Cross Flow Exchangers”, MS Thesis in Mechanical Engineering, University of Saskatchewan, Saskatoon, Canada, [Online] Retrieved from the internet: <URL: <http://library.usask.ca/theses/mailable/etd-06032009-15-J.6-J.-1./unrestricted/Vali.AlirezaThesis.pdf>>, (2009), 193 pgs. cited by applicant

Vali, Alireza, et al., “Numerical model and effectiveness correlations for a run-around heat recovery system with combined counter and cross flow exchangers”, International Journal of Heat and Mass Transfer 52, (2009), 14 pgs. cited by applicant

Woods, J, et al., “Desiccant Enhanced Evaporative Air Conditioning: Parametric Analysis and Design”, 2nd International Conference on Building Energy and Environment (COBEE), (Oct. 2012), 10 pgs. cited by applicant

Yborra, Stephen C., “Field Evaluation of Desiccant-Integrated HVAC Systems: A Review of Case Studies in Multiple Commercial/Institutional Building Types”, Proc. of the 11th Symposium On Improving Building Systems In Hot and Humid Climates, Ft. Worth, Texas, (Jun. 2, 1998), 10 pgs. cited by applicant

U.S. Appl. No. 17/855,344, filed Jun. 30, 2022, Evaporate Cooling System With Liquid-To-Air Membrane Energy Exchanger. cited by applicant
U.S. Appl. No. 18/481,032, filed Oct. 4, 2023, Desiccant Enhanced Evaporative Cooling Systems And Methods. cited by applicant
U.S. Appl. No. 18/821,672, filed Aug. 30, 2024, Water Recovery In Desiccant Enhanced Evaporative Cooling Systems. cited by applicant

Primary Examiner: Teitelbaum; David J

Attorney, Agent or Firm: Schwegman Lundberg & Woessner, P.A.

Background/Summary

CLAIM OF PRIORITY

(1) This application is a U.S. National Stage Filing under 35 U.S.C. § 371 from International Patent Application No. PCT/CA2017/050478, titled “SYSTEMS AND METHODS FOR MANAGING CONDITIONS IN ENCLOSED SPACE,” filed on Apr. 18, 2017 and published as WO 2018/191805 A1 on Oct. 25, 2018, the benefit of priority of which is claimed hereby, and which is incorporated by reference herein in its entirety.

DESCRIPTION OF DRAWINGS

(2) In the drawings, which are not necessarily drawn to scale, like numerals may describe similar components in different views. Like numerals having different letter suffixes may represent different instances of similar components, sub-components of a larger logical or physical system, or the like. The drawings illustrate generally, by way of example, but not by way of limitation, various examples described in the present disclosure.

(3) FIG. 1 schematically depicts an example conditioning system in accordance with this disclosure.

(4) FIG. 2 depicts another example conditioning system in accordance with this disclosure.

(5) FIG. 3 is a psychometric process diagram for a theoretical system substantially similar to example system of FIG. 2.

(6) FIG. 4 depicts another example conditioning system.

(7) FIG. 5 is a psychometric process diagram for a theoretical system substantially similar to example system of FIG. 4.

(8) FIG. 6 is a psychometric process diagram for a theoretical system with the same components and arrangements thereof as the system modeled to produce the process diagram of FIG. 5, except the pre-cooler and the recovery coil have lower capacities/conditioning effectiveness, and a different outdoor air condition is evaluated.

(9) FIG. 7 depicts an example liquid desiccant regeneration system connected to a conditioning system in accordance with this disclosure.

(10) FIG. 8 depicts an example liquid-to-air heat exchanger configured to cool a liquid desiccant employed in a desiccant dryer liquid-to-air membrane energy exchanger.

(11) FIGS. 9 and 10 depict two other example conditioning systems.

(12) FIG. 11 depicts another example conditioning system.

(13) FIG. 12 depicts another example conditioning system.

(14) FIG. 13 depicts another example conditioning system.

(15) FIG. 14 is a flowchart depicting a method of operating a conditioning system in accordance

with this disclosure.

(16) FIG. 15 depicts another example conditioning system.

Description

DETAILED DESCRIPTION

(1) The inventor(s) recognize, among other things, an opportunity for improved performance in providing cooling to an enclosed space by employing a liquid desiccant conditioning module to lower the relative humidity of a scavenger (or outdoor) air stream before supplying the scavenger air to an indirect evaporative cooler, which indirectly and sensibly cools the process (or supply) air supplied to the enclosed space. Such systems with a liquid desiccant dryer can meet a discharge cooling set point temperature (for product/process cooling or for comfort cooling applications) over a larger range of inlet working air temperatures and humidity levels than other types of systems and potentially for any inlet working air conditions. In some cases, the water collected in the liquid desiccant dryer module exceeds the water needed in the evaporative cooler, thus potentially substantially reducing or eliminating large amounts of water usage typical of various types of heating and cooling systems.

(2) Comfort cooling of residential, commercial and institutional buildings is predominantly done using vapor-compression cooling equipment. Many process applications, such as data centers, also use mechanical cooling for primary or supplemental cooling. In most of these applications the required cooling temperature is moderate (for example, in a range from about 50 degrees Fahrenheit to about 85 degrees Fahrenheit). Vapor-compression mechanical cooling equipment can produce high cooling capacities, operate reliably and can have acceptable cost due to mass production of compressors, exchangers and other components. However, these systems require significant amounts of high grade energy (usually electricity) to operate. For example, some studies have estimated that about 15% of the total annual US domestic electricity production is consumed by air conditioning units. Moreover, it has been estimated that about $\frac{1}{3}$ of the peak electricity demand in hot summer months is driven by air conditioning units, leading, in some cases, to issues with power grid loading and stability.

(3) The production of electricity remains carbon intensive, so electricity driven cooling systems can contribute to carbon dioxide (CO₂) emissions and potentially to other issues like global warming and climate change. In addition, thermoelectric power production requires relatively large amounts of water for cooling, and the US average water consumption (evaporated water) for combined thermoelectric and hydroelectric power production is about 2 gallons/kWh. In fact, it has been estimated that the water consumed to produce the electricity required by an EER 11 air conditioner is about equivalent to the water consumed by a good efficiency evaporative cooling system producing an equivalent amount of cooling. However, evaporative cooling systems consume far less electricity.

(4) Vapor-compression systems also typically require synthetic refrigerants operating at high pressures. The deployment of large quantities of refrigerants in air conditioning and refrigeration systems can result in safety, health and environmental issues, including, for example ozone depletion caused by chlorofluorocarbon (CFC) refrigerants. Modern high efficiency refrigerants such as hydrofluorocarbons (HFCs) may have very high global warming potential and are being phased out of use. Additionally, proposed replacement hydrofluro-olefins (HFO) refrigerants and refrigerant mixtures may still have modestly high global warming potential (GWP) and are flammable, potentially toxic and expensive. Thus, there is a challenge in discovering or designing direct replacement refrigerant options for new and already installed vapor-compression systems, which has the desired properties in terms of efficiency, stability, flammability, toxicity, and environmental impact.

- (5) Evaporative cooling systems are used successfully in many applications, especially in dry climates. Direct evaporative coolers are generally considered simple and efficient, but can lead to indoor humidity problems. Indirect evaporative coolers generally address the humidity issue, but may operate at lower wet bulb efficiencies. Dew-point evaporative coolers can deliver lower cooling temperatures than conventional direct or indirect evaporative systems and can maintain cooling power to higher outdoor wet bulb temperatures. However, all evaporative cooling technologies lose cooling performance as the working air humidity rises and may not be able to be used in humid climates without supplemental (usually vapor-compression) cooling equipment.
- (6) The water usage efficiency of evaporative cooling systems also varies widely depending on the system design and control characteristics. The water usage of evaporative coolers can be a significant perceived or real problem. For example, large scale data centers can consume surprisingly large quantities of potable water, and in locations where evaporative cooling works best (dry climates), the water demand may not be sustainable.
- (7) Absorption chillers have been employed for comfort and process cooling, especially when waste heat is available. Absorption chiller systems have been commercialized for larger scale applications and may be an alternative to mechanical cooling in integrated building designs where the required technical and maintenance support is available. Single-effect absorptions chillers have a $COP < 1$, so significant quantities of heat are required to drive the system. Current absorption chiller designs are intended to replace electric chillers and deliver comparable cooling temperatures (for example, 40° F.-50° F.). However, this may require the use of specialized materials (alloy metals), vacuum vessels, multiple heat exchangers, relatively high grade heat input for the generator, control methods to prevent crystallization, etc. Higher efficiency double and triple effect designs are increasingly complex and expensive. The complexity, cost and maintenance requirements of absorption systems may limit their widespread acceptance as an alternative to mechanical cooling, especially in lighter load commercial and residential applications.
- (8) There remains an urgent need for alternative cooling technologies for comfort conditioning applications which can largely replace mechanical cooling. The growing awareness of environmental impacts, electricity consumption and increasing regulatory pressure on refrigerants are pressing challenges for current HVAC cooling equipment. This need was identified and articulated in the U.S. Department of Energy BTO report in 2014 titled “Energy Savings Potential and RD&D Opportunities for Non-Vapor-Compression HVAC Technologies.”
- (9) One of the most promising technologies identified in this DOE report was desiccant enhanced evaporative cooling systems. However, there is a need for a commercially viable design which meets requirements for first cost, ongoing operation costs, performance, reliability, size/weight restrictions, etc., while avoiding the creation of any new resource utilization problems such as excessive water or natural gas consumption.
- (10) The ideal system design would have good cooling performance and compactness, make use of low cost materials, and avoid the use of any environmentally harmful or toxic substances. From a thermodynamic perspective, the system should operate near atmospheric pressures with low grade heat input, employ moderate temperature changes and exchange fluxes to minimize irreversibility in the system and improve second law efficiency. Comfort conditioning only requires low grade cooling, and an exergy analysis can illustrate how wasteful it may be to use precious high grade energy sources such as electricity to drive cooling equipment. Currently this is most clearly evident in data center applications, where operators want to maximize the utilization of available electricity supplies for running computing equipment (an appropriate use of electricity) and minimize electricity consumption by cooling equipment.
- (11) In one example, a system for controlling conditions in an enclosed space includes a scavenger plenum, a process plenum, a first liquid-to-air membrane energy exchanger (LAMEE1), a second LAMEE (LAMEE2), a first liquid-to-air heat exchanger (LAHX1), and a second LAHX (LAHX2). The process plenum is configured to direct scavenger air from a scavenger inlet to a scavenger

outlet. The process plenum is configured to direct process air from a process inlet to a process outlet. The process inlet receives heated air from the space and the process outlet supplies cooled air to the space. LAMEE1 is arranged inside the scavenger plenum. LAMEE1 is configured to use a first fluid flowing there through to reduce the humidity of the scavenger air. A first concentration of water in the first fluid at a fluid inlet of LAMEE1 is lower than a second concentration of water in the first fluid at a fluid outlet of LAMEE1. LAMEE2 is arranged inside the scavenger plenum downstream of LAMEE1. LAMEE2 is configured to use the scavenger air to evaporatively cool a second fluid flowing through LAMEE2. A temperature of the second fluid at a fluid outlet of LAMEE2 is lower than a temperature of the second fluid at a fluid inlet of LAMEE2. LAHX1 is arranged inside the process plenum. LAHX1 is configured to directly and sensibly cool the process air being directed through the process plenum using a third fluid flowing through LAHX1. LAHX2 is in fluid communication with LAMEE1 and is configured to receive and cool the first fluid using outdoor air.

(12) FIG. 1 depicts an example conditioning system **100**. Conditioning system **100** is configured to condition the air in an enclosed space like a data center. Conditioning system **100** is what is sometimes referred to as a 100% recirculation system, which generally means that the air within the enclosed space recirculates through the conditioning system (in this case through one portion of the system, for example, the process side of the system) in a continuous cycle of being cooled by the system to a target supply air temperature, supplied to the space, heated by elements in the space (for example, computers, servers, and other electronics), and returned to the system for cooling. Although not shown or described in detail, the conditioning system can include a make-up air unit or system, to continuously or periodically refresh the air within the space. With the addition of make-up air, in some cases, humidification and/or dehumidification units may be employed to control the humidity of the air in the enclosed space.

(13) In FIG. 1, conditioning system **100** includes system cabinet **102**, scavenger plenum **104**, process plenum **106**, LAMEE1 **108**, LAMEE2 **110**, LAHX1 **112**, LAHX2 **114** and first fluid circuit **116** and second fluid circuit **118**. Scavenger plenum **104** includes inlet **120** and outlet **122**. Associated and generally collocated with each of inlet **120** and outlet **122** are dampers **124**, **126**, respectively. Process plenum **106** includes inlet **128**, with which is associated and collocated damper **130**, and outlet **132**, which is associated and collocated damper **134**. Conditioning system **100** also includes a liquid desiccant regeneration system, which is configured to regenerate desiccant leaving LAMEE1 **108**, which has been diluted by water from the scavenger air, and, in some cases, to supply the water removed from the desiccant to other components, including, for example, LAMEE2 **110**.

(14) Although not shown in FIG. 1, in some examples, scavenger plenum **104** could also include a bypass inlet and bypass damper disposed between LAMEE1 **108** and LAMEE2 **110**. In such situations, system **100** could be configured to close damper **124** at inlet **120** and open the bypass damper to bypass LAMEE1 **108** and direct the scavenger air (for example, outdoor air) in through the damper inlet and through LAMEE2 **110**.

(15) Air from the enclosed space enters system **100** through process inlet **128**. The air entering system **100** has been heated in the enclosed space and requires cooling to a target supply air temperature, which is generally determined based on the amount and characteristics of equipment housed in the enclosed space, for example, computing, networking, data storage and other equipment. Air is supplied to the enclosed space from system **100** through process outlet **132**. This supply air is cooled by system **100** and is transported into the space at or within an acceptable tolerance of the target supply air temperature.

(16) Scavenger plenum **104** and the scavenger air flowing there through can be a plenum that transports outdoor air (OA) from inlet **120** through/by LAMEE1 **108** and LAMEE2 **110**, and then exhausts the increased enthalpy OA air through scavenger outlet **122**. The scavenger and process plenums **104** and **106** are sealed from one another such that the scavenger and process air streams

do not intermix with one another (other than ordinary leakage between the two plenums, if collocated).

(17) Scavenger plenum **104** and process plenum **106** are defined by partitioned sub-sections of the interior space of cabinet **102**, as is schematically depicted in FIG. **1**. In other examples, scavenger and process plenums **104** and **106** can be separate from and mounted within system cabinet **102** of system **100**. Although some components of example systems in accordance with this disclosure are schematically depicted as outside of the overall system cabinet and/or outside of the two separate plenums, at least in some examples all of the cooling/conditioning components of example system(s) are located within a single system enclosure, which can be conveniently packaged, transported, and installed. In such cases, the scavenger and process inlets and outlets can be connected directly to or indirectly via appropriate ducting or other fluid flow conduit to additional scavenger air supply and exhaust flow paths and to additional enclosed space supply and return flow paths. Additionally, one or more of the components depicted within cabinet **102** and/or plenums **104** and **106** can be located external to and/or separate from such enclosures. Additionally, plenums may be located and/or packaged separate from one another instead of sharing a common cabinet. Moreover, example systems in accordance with this disclosure can be employed in combination with other heating, cooling, humidification, dehumidification, recovery, regeneration and other components or systems located within or otherwise along these additional scavenger and process air flow paths.

(18) Example conditioning systems in accordance with this disclosure include liquid to air membrane energy exchangers (LAMEEs), which are configured to transfer heat and moisture between a liquid and an air stream to condition the temperature and humidity of the air and/or to condition the liquid flowing through the LAMEE. In an example, the membrane in a LAMEE can be a non-porous film having selective permeability for water, but not for other constituents that may be present in the liquid. Many different types of liquids can be used in combination with the non-porous membrane, including, for example, water, liquid desiccants, glycols. In an example, the membrane in the LAMEE can be semi-permeable or vapor permeable, and generally anything in a gas phase can pass through the membrane and generally anything in a liquid phase cannot pass through the membrane. In an example, the membrane in the LAMEE can be micro-porous such that one or more gases can pass through the membrane. In an example, the membrane can be a selectively-permeable membrane such that some constituents, but not others, can pass through the membrane. It is recognized that the LAMEEs included in the conditioning systems disclosed herein can use any type of membrane suitable for use with devices that are the same or equivalent to a LAMEE.

(19) LAMEE1 **108** can be used to lower the enthalpy of and dehumidify the scavenger air flowing through scavenger plenum **104**. LAMEE1 **108** can also collect water, which can be employed in/by other components of conditioning system **100** or other such systems in accordance with this disclosure. The water collection rate/capacity of LAMEE1 **108** can exceed the evaporation rate of LAMEE2 **110** (or another type of evaporative cooler), which can make operation of conditioning system **100**, or at least operation of LAMEE2 independent of additional/external water sources. Additionally, because LAMEE1 **108** can effectively operate in a variety of ambient conditions using a liquid desiccant at temperatures (for example, on the order of 35 degrees Celsius) that are higher than the outdoor ambient dry bulb temperature, cooling/heat rejection of the desiccant exiting LAMEE1 can occur in an air cooler (for example, a polymer fluid cooler or PFC) using only outdoor air.

(20) LAMEE1 **108** of conditioning system **100** can function to remove water from the scavenger air using a liquid desiccant to decrease the humidity of the scavenger air and thereby lower the wet bulb temperature. The temperature of the scavenger air passing through LAMEE1 **108** may be lowered modestly, but the decrease in humidity and associated effect of lowering wet bulb temperature can significantly increase the cooling capacity of LAMEE2 **110** (configured to operate

as an evaporative cooler) and thereby improve and expand the efficiency with which and the conditions under which system **100** can meet the target supply air temperature for a data center or other enclosed space.

(21) The cooling fluid circulating through LAMEE1 **108** and/or LAMEE2 **110** can include water, liquid desiccant, glycol, other hygroscopic fluids, other evaporative liquids, and/or combinations thereof. In an example, the cooling fluid employed in and flowing through LAMEE1 **108** is a liquid desiccant that is a high concentration salt solution. The presence of salt can sanitize the cooling fluid to prevent microbial growth. In addition, the desiccant salt can affect the vapor pressure of the solution and allow the cooling fluid to either release or absorb moisture from the air. The concentration of the liquid desiccant can be adjusted for control purposes to control the amount of cooling and/or dehumidification of the scavenger air or cooling fluid within/passing through/by LAMEE1 **108**.

(22) In an example, the cooling fluid employed in and flowing through LAMEE2 **110** is water and, in some cases, the water flowing through LAMEE2 **110** or a portion thereof is water removed from the scavenger air by LAMEE1 **108**. LAMEE2 **110** can include a water inlet and a water outlet for passing water through the exchanger. In other cases, other types of evaporative cooling fluids, including those listed above, can be used in combination with or as an alternative to water for LAMEE2 **110** and other such examples in accordance with this disclosure.

(23) In one example, a liquid desiccant, for example a salt solution desiccant flows into LAMEE1 **108** via a liquid inlet and out of LAMEE1 **108** via a liquid outlet. The scavenger air enters scavenger plenum **104** and flows through LAMEE1 **108** via air inlets and outlets thereof. As the scavenger air flows by the liquid desiccant, separated by the membrane(s) employed in LAMEE1 **108**, water in the scavenger air condenses through the membrane into the liquid desiccant. The scavenger air exiting LAMEE1 **108** can have a lower temperature and/or a lower humidity than the scavenger air entering LAMEE1, and, as a result, the enthalpy and the wet bulb temperature of the scavenger air are decreased. The reduced wet bulb temperature scavenger air flows out of LAMEE1 **108** downstream through scavenger plenum **104** into LAMEE2 **110**.

(24) LAMEE2 **110** of conditioning system **100** can recirculate a cooling fluid, including an evaporative fluid to reduce the temperature of the cooling fluid by evaporating water from the fluid into the scavenger air passing through LAMEE2. LAMEE2 **110** can operate as an evaporative cooler, using the cooling potential in both the scavenger air and the cooling fluid (for example, water) to reject heat. Although the examples disclosed include LAMEE2 configured as an evaporative cooler in the scavenger plenum **104**, in other examples, different types of evaporative cooling devices can be employed, including, for example, a wetted media direct evaporative cooler. In an example, LAMEE2 **110** can use a flexible polymer membrane, which is vapor permeable, to separate the scavenger air and water or other fluid flowing through LAMEE2. Relative to other systems/devices, the water flow rate and air flow rate through LAMEE2 **110** may not be limited by concerns such as droplet carryover at high face velocities. In addition, LAMEE2 **110** can operate with water flow rates that enable the transport of thermal energy into the cooler similar to a cooling tower, and the elevated inlet water temperatures can boost the evaporative cooling power of LAMEE2.

(25) LAMEE2 **110** can be referred to herein as an evaporative cooler and/or an evaporative cooler LAMEE. As scavenger air flows through LAMEE2 **110**, the water, or both the scavenger air and the water, can be cooled to temperatures approaching the entering air wet bulb (WB) temperature, as a portion of the water flowing through LAMEE2 evaporates into the scavenger air. The scavenger air exiting LAMEE2 **110** can pass through scavenger fan **136** and exit scavenger plenum **104** at the outlet thereof as exhaust.

(26) Due to the evaporative cooling process in LAMEE2 **110**, a temperature of the water at the outlet of the exchanger can be less than a temperature of the water at the inlet. In other words, the water flowing through the LAMEE2 **110** is cooled by the device between the inlet and the outlet.

The reduced-temperature, or “cooled” water from LAMEE2 **110** can be used to provide cooling to process air flowing through/by LAHX1 **112**.

(27) LAMEE1 **108** can be referred to as a dehumidification LAMEE and/or desiccant driven dehumidification LAMEE. As noted above, LAMEE2 **110** can be referred to as an evaporative cooler LAMEE. As shown in FIG. 1, dehumidification LAMEE1 **108** is arranged upstream of evaporative cooler LAMEE2 **110** in scavenger plenum **104** to reduce the humidity of the scavenger air prior to evaporative cooling in the evaporative cooler LAMEE2. Pre-drying the scavenger air boosts the cooling potential in system **100** by lowering the wet bulb temperature of the scavenger air and thereby lowering the ideal and actual cooling limits of evaporative cooler LAMEE2 **110**. Dehumidification LAMEE1 **108** may also pre-cool the scavenger air. Desiccant driven dehumidification may allow cooling of the process air by system **100** to even lower temperatures with modest amounts of additional energy input.

(28) Dehumidification LAMEE1 **108** may be similar in construction to evaporative cooler LAMEE2 **110**. However, dehumidification LAMEE1 **108** can employ a different cooling fluid than evaporative cooler LAMEE2 **110**. For example, the desiccant fluid flowing through LAMEE1 **108** may be a lithium chloride solution, while the cooling (or “evaporative”) fluid flowing through LAMEE2 **110** may be pure water or water of a relatively high purity.

(29) Example conditioning system **100** also includes two liquid-to-air heat exchangers, LAHX1 **112** and LAHX2 **114**, which generally exchange heat between a cooling fluid flowing through the exchanger and air flowing over/by the exchanger. LAHX1 **112** is arranged in process plenum **106** and is the cooling component in conditioning system **100** that ultimately directly and sensibly cools the process air from the enclosed space.

(30) LAHX1 **110** can be a variety of types of liquid-to-air exchangers, including, for example, cooling coils. Cooling coils are commonly formed of coiled copper tubes embedded in a matrix of fins. A variety of particular configurations, capacities, etcetera can be employed in examples according to this disclosure. Other example LAHXs that can be used include micro-channel heat exchangers. The cooling fluid circulating through one or both of LAHX1 **110** and LAHX2 **112** can include water, liquid desiccant, glycol, other hygroscopic fluids, other evaporative liquids, and/or combinations thereof. Additionally, the cooling fluid flowing through LAHX1 **112** can be the same as or different than the cooling fluid flowing through LAMEE2 **110**, as described in more detail with other examples in accordance with this disclosure.

(31) LAHX2 **114** is configured to cool the liquid desiccant exiting LAMEE1 **108** and return the desiccant to the fluid inlet of LAMEE1. As noted above, in some examples, the inlet temperature threshold (or set point) of LAMEE1 **108** can be higher than the outdoor air dry bulb temperature. In at least some such cases, LAHX2 **114** can cool the liquid desiccant to the inlet temperature threshold of LAMEE1 **108** using only outdoor air in a sensible cooling process. In some cases, however, a combination of outdoor air and some kind of evaporative cooling augmentation (for example, adiabatic cooling or water sprays) may be employed in LAHX2 **114** to cool the liquid desiccant exiting LAMEE1 **108**.

(32) LAHX1 **112** can be a variety of types of fluid cooling components and/or liquid-to-air exchangers. In one example, LAHX1 **110** is a polymer fluid cooler (PFC), which is configured to employ outdoor air to cool the liquid desiccant exiting LAMEE1 **108** to a target inlet desiccant temperature. Such a PFC can be, for example, a PolyCoil polymeric heat exchanger from Cesaroni Technology Inc. of Gormley, Ontario in Canada. Additional details and examples of the types of components employed as LAHX1 **110** (or another similar component in other examples according to this disclosure) is illustrated in and described with reference to FIGS. 7 and 8.

(33) Referring again to FIG. 1, conditioning system **100** also includes scavenger fan (or fan array) **136** and process fan (or fan array) **138**, which drive the scavenger air and the process air, respectively, through system **100**. Example conditioning system **100** and other example systems in accordance with this disclosure can include more or fewer fans than shown in the example of FIG.

1. Moreover, the fans can be located in different locations within the system **100** relative to what is shown in FIG. **1**. For example, one or both of scavenger fan **136** and process fan **138** can be configured as a single fan or multiple fans, including a fan array, such as, for example, FANWALL® Systems provided by Nortek Air Solutions of O'Fallon, Missouri. Although not shown in the figures, example conditioning systems in accordance with this disclosure can include one or more filters disposed at a variety of locations in one or both of scavenger plenum **104** and process plenum **106**.

(34) In the example of FIG. **1**, scavenger fan **136** is arranged inside scavenger plenum **104** downstream of LAMEE2 **110**. In this position, at least some of the heat generated by scavenger fan **136** is exhausted out of scavenger plenum **104** through scavenger outlet **122**, which is just downstream of scavenger fan **136**. Process fan **138** is arranged inside process plenum **106** upstream of LAHX1 **112**. In this position, some heat generated by process fan **138** can be removed by LAHX1 **112**. In other examples, scavenger fan **136** can be located at different positions within/along scavenger plenum **104** and process fan **138** can be located at different positions within/along process plenum **106**.

(35) In the example of FIG. **1**, conditioning system **100** includes first fluid circuit **116** and second fluid circuit **118**. Fluid circuits employed in examples according to this disclosure, including first and second fluid circuits **116** and **118** can include a number of different interconnected conduits or fluid flow pathways, as well as other cooling fluid related components, including, for example, valves, pumps, tanks or other storage vessels, etc. Each of first and second fluid circuits **116** and **118** can be thought of as including multiple interconnected fluid flow branches or could also be characterized as including multiple fluid circuits.

(36) First and second fluid circuits **116** and **118** are structured and configured to transport one or more cooling fluids (or more generally “heat transfer” fluids) among the components of system **100**. In the example of FIG. **1**, first fluid circuit **116** transports a first cooling fluid among LAMEE1 **108** and LAHX2 **114**. Second fluid circuit **118** transports a second cooling fluid among LAMEE2 **110** and LAHX **112**. As noted above, in one example, first fluid circuit **116** transports a salt solution liquid desiccant among LAMEE1 **108** and LAHX2 **114** and second fluid circuit **118** transports water among LAMEE2 **110** and LAHX **112**.

(37) Conditioning system **100** also includes system controller **150**. System controller **150** can include hardware, software, and combinations thereof to implement the functions attributed to the controller herein. System controller **150** can be an analog, digital, or combination analog and digital controller including a number of components. As examples, controller **150** can include ICB(s), PCB(s), processor(s), data storage devices, switches, relays, etcetera. Examples of processors can include any one or more of a microprocessor, a controller, a digital signal processor (DSP), an application specific integrated circuit (ASIC), a field-programmable gate array (FPGA), or equivalent discrete or integrated logic circuitry.

(38) Storage devices, in some examples, are described as a computer-readable storage medium. In some examples, storage devices include a temporary memory, meaning that a primary purpose of one or more storage devices is not long-term storage. Storage devices are, in some examples, described as a volatile memory, meaning that storage devices do not maintain stored contents when the computer is turned off. Examples of volatile memories include random access memories (RAM), dynamic random access memories (DRAM), static random access memories (SRAM), and other forms of volatile memories known in the art. The data storage devices can be used to store program instructions for execution by processor(s) of controller **150**. The storage devices, for example, are used by software, applications, algorithms, as examples, running on and/or executed by controller **150**. The storage devices can include short-term and/or long-term memory, and can be volatile and/or non-volatile. Examples of non-volatile storage elements include magnetic hard discs, optical discs, floppy discs, flash memories, or forms of electrically programmable memories (EPROM) or electrically erasable and programmable (EEPROM) memories.

(39) System controller **150** can be configured to communicate with conditioning system **100** and components thereof via various wired or wireless communications technologies and components using various public and/or proprietary standards and/or protocols. For example, a power and/or communications network of some kind may be employed to facilitate communication and control between controller **150** and conditioning system **100**. In one example, system controller **150** may communicate with conditioning system **100** via a private or public local area network (LAN), which can include wired and/or wireless elements functioning in accordance with one or more standards and/or via one or more transport mediums. In one example, system **100** can be configured to use wireless communications according to one of the 802.11 or Bluetooth specification sets, or another standard or proprietary wireless communication protocol. Data transmitted to and from components of system **100**, including controller **150**, can be formatted in accordance with a variety of different communications protocols. For example, all or a portion of the communications can be via a packet-based, Internet Protocol (IP) network that communicates data in Transmission Control Protocol/Internet Protocol (TCP/IP) packets, over, for example, Category 5, Ethernet cables or over an 802.11 or Bluetooth wireless connection.

(40) System controller **150** can include one or more programs, circuits, algorithms or other mechanisms for controlling the operation of conditioning system **100**. For example, system controller **150** can be configured to modulate the speed of scavenger and process fans **136** and **138** and/or control actuation of valves, pumps, etc. in one or both of first fluid circuit **116** and second fluid circuit **118**. System controller **150** can also be configured to operate system **100** in multiple conditioning (for example, cooling) modes. For example, system controller **150** can also be configured to operate system **100** in an evaporative mode in which LAMEE1 **108** is deactivated, damper **124** is closed, a bypass damper (in scavenger plenum **104** between LAMEE1 **108** and LAMEE2 **110**) is opened, and cooling fluid is circulated through a run-around loop defined by first fluid circuit **116** from the outlet of LAHX1 **112** to the inlet of LAMEE2 **110**, through LAMEE2 **110**, from the outlet of LAMEE2 **110** to the inlet of LAHX1 **112**, and through LAHX1 **112** back to the outlet thereof. Additionally, system controller **150** can also be configured to operate system **100** in a desiccant enhanced evaporation mode in which LAMEE1 **108** is activated, damper **124** is opened, the bypass damper is closed, and cooling fluid is circulated by first fluid circuit **116** among all of LAMEE1 **108** and LAHX1 **112**.

(41) Although not shown in detail in the example of FIG. 1, conditioning system **100** can also include one or more components to recover the fluid flowing through LAHX1 **112** before returning to LAMEE2 **110** and/or one or more components to regenerate the liquid desiccant flowing through LAMEE1 **108**. In the case of regeneration of liquid desiccant flowing through LAMEE1 **108**, in some examples, the regeneration circuit and components can be configured to regenerate less than 100% of the desiccant in each cycle through LAMEE1 and LAHX2.

(42) In some examples according to this disclosure, an important feature/advantage of employing LAMEE1 (versus some other type of liquid desiccant device) is the relatively high desiccant flow rate that is possible through such example LAMEEs in accordance with this disclosure. Due to the high flow rates through the desiccant dryer LAMEE, even though the desiccant may pick up heat in LAMEE1 (in addition to moisture) the flow rates are such that the increase in temperature is tolerable without additional desiccant cooling such as requiring an additional cooling flowing through the same exchanger to cool the desiccant. The control of desiccant temperature is important in such systems, because, for a given desiccant salt concentration, the capacity of the desiccant to absorb moisture degrades as the desiccant temperature increases. Maintaining relatively high flow rates through the desiccant dryer LAMEE is assisted by only regenerating a portion of the total flow between LAMEE1 and LAHX2. Examples of such components or systems are described in more detail with reference to the examples of FIGS. 2 and 4.

(43) FIG. 2 depicts another example conditioning system **200** in accordance with this disclosure. As is apparent from FIG. 2, conditioning system **200** shares many of the components and functions

of example conditioning system **100** of FIG. **1**. For example, conditioning system **200** includes system cabinet **102**, scavenger plenum **104**, process plenum **106**, LAMEE1 **108**, LAMEE2 **110**, LAHX1 **112**, and LAHX2 **114**. Scavenger plenum **104** includes inlet **120** and outlet **122**, and dampers **124** and **126**, which are associated and generally collocated with each of inlet **116** and outlet **118**. Process plenum **106** includes inlet **128**, with which is associated and collocated damper **130**, and outlet **132**, which is associated and collocated damper **134**. Conditioning system **200** also includes scavenger fan **136**, process fan **138**, and system controller **150**. Conditioning system **200** includes a liquid desiccant regeneration system, which is configured to regenerate desiccant leaving LAMEE1 **108**, which has been diluted by water from the scavenger air, and, in some cases, to supply the water removed from the desiccant to other components, including, for example, LAMEE2 **110**.

(44) In addition to the components in common with conditioning system **100**, conditioning system **200** includes recovery coil **202**, first storage tank **204** and first pump **206**, and second storage tank **208** and second pump **210**. Recovery coil **202** can include a number of different types of devices configured to use the air flowing out of LAMEE2 **110** in scavenger plenum **104** to cool down the fluid returning from LAHX1 **112** to LAMEE2. In one example, recovery coil **202** is one of a number of different types of LAHX devices.

(45) The fluid exiting LAHX1 **112** will be at an increased-temperature or “heated,” because the rejected heat from the process air has been picked up by the fluid. The fluid can therefore be transported to recovery coil **202** in scavenger plenum **104**, which cools the fluid before it returns to LAMEE2 **110**. Recovery coil **202** can cool the fluid using the cooling potential of the scavenger air. The scavenger air exiting LAMEE2 **110** can be relatively cool and additional sensible heat from the cooling fluid can therefore be rejected into the scavenger air. One reason for the amount of energy still available in the scavenger air after going through LAMEE2 **110** is that LAMEE2 cools the water or other fluid by increasing the humidity of the scavenger air versus substantially increasing the temperature of the air. In this sense, system **200** uses the latent heat transfer capacity of the scavenger air to cool a cooling fluid (for example, water) that is used to sensibly cool the process air and uses the sensible heat transfer capacity of the scavenger air to cool the fluid after it has picked up heat from the process air.

(46) Therefore, one advantage of conditioning system **200** is the ability to use the scavenger air as a working fluid to cool down and recover the cooling fluid flowing through LAMEE2 **110**. Recovery coil **202** or an equivalent device can be relatively inexpensive, simple in construction and maintenance, thus potentially simplifying and reducing the cost and complexity of at least some example conditioning systems and methods in accordance with this disclosure. Moreover, recovery coil **202** may provide a number of advantages related to water usage efficiency over systems not including such a component. For example, inclusion of recovery coil **202** may make a true economizer operating mode possible in which no evaporative conditioning takes place and fluid is transported in a run around loop between recovery coil **202** and LAHX1 **112**. Additionally, the recovery coil **202** can increase the water efficiency of evaporative modes by increasing the temperature of the scavenger exhaust air.

(47) In the example of conditioning system **200** of FIG. **2**, first storage tank **204** and first pump **206** are included in and connected to first fluid circuit **212**. First fluid circuit **212** can be similar in structure and function to first fluid circuit **116** of FIG. **1**, except that first fluid circuit **212** includes tank **204** and pump **206** and associated couplings to incorporate these components into the circuit. Second storage tank **208** and second pump **210** are included in and connected to second fluid circuit **214**. Second fluid circuit **214** can be similar in structure and function to second fluid circuit **118** of FIG. **1**, except that second fluid circuit **214** includes tank **208** and pump **210** and associated couplings to incorporate these components into the circuit.

(48) Storage tank **204** can be employed to store fluid cooled by LAMEE2 **110**. Although not shown in FIG. **2**, tank **204** can include a make-up valve and a drain valve to maintain the fluid level and

hardness level inside the tank. Tank **204** can include one or more temperature sensors in or around the tank to monitor a temperature of the fluid stored therein. In an example, the control scheme for conditioning system **200** can be based, in part, on a measured temperature of the fluid in tank **204** compared to a set point temperature. In an example, the set point temperature can be pre-determined based on an estimated cooling load from the enclosed space or a temperature required by the equipment of occupants of the enclosed space (for example, computing, networking, etc. equipment in a data center). The set point water temperature can also vary during operation of conditioning system **100**, based in part on conditions in the enclosed space (for example, operation of the data center like periodic processing or data storage load variations).

(49) Pump **206**, which can be controlled by system controller **150**, pumps the cooled fluid from storage tank **204** into LAHX1 **112**, by which LAHX1 **112** cools the process air supplied to the enclosed space. After the fluid provides cooling to the process air, the fluid can be recirculated back to LAMEE2 **110** (including through recovery coil **202**).

(50) Fluid circuit **212** can include a number of different interconnected conduits or fluid flow pathways, as well as other cooling fluid related components. Fluid circuit **212** can be thought of as including multiple interconnected fluid flow branches or could also be characterized as including multiple fluid circuits. In any event, fluid circuit **212** is structured and configured to transport one or more cooling fluids (or more generally “heat transfer” fluids) among the cooling components of system **200**. In the example of FIG. 2, fluid circuit **212** transports cooling fluid, for example, water among LAMEE2 **110**, LAHX1 **112**, and recovery coil **202**, stores the fluid in tank **204** and transports the fluid to LAHX1 **112** from tank **204** using pump **206**.

(51) Storage tank **208** can be employed to store fluid that is used by LAMEE1 **108** to dehumidify the scavenger air and to thereby lower the enthalpy/wet bulb temperature of the scavenger air to boost the cooling capacity of the evaporative cooler LAMEE2 **110**. Tank **208** can include one or more temperature sensors in or around the tank to monitor a temperature of the fluid stored therein. In an example, the control scheme for conditioning system **200** can be based, in part, on a measured temperature of the fluid in tank **208** compared to a set point temperature. In an example, the set point temperature can be pre-determined based on, inter alia, an estimated cooling load from the enclosed space. The set point temperature for the fluid flowing through LAMEE1 **108** can also vary during operation of conditioning system **200**, based in part on conditions in the enclosed space (for example, operation of the data center like periodic processing or data storage load variations). In an example, the temperature of the fluid entering LAMEE1 **108** can be controlled by modulating the capacity of LAHX2 **114**.

(52) Pump **210**, which can be controlled by system controller **150**, pumps the fluid from storage tank **208** to LAHX2 **114**, which cools the fluid using outdoor air and returns the cooled fluid to the fluid inlet of LAMEE1 **108**. Fluid circuit **214** can include a number of different interconnected conduits or fluid flow pathways, as well as other cooling fluid related components. Fluid circuit **214** can be thought of as including multiple interconnected fluid flow branches or could also be characterized as including multiple fluid circuits. In any event, fluid circuit **214** is structured and configured to transport one or more fluids among the select components of system **200**. In the example of FIG. 2, fluid circuit **214** transports a fluid, for example, a liquid desiccant among LAMEE1 **108** and LAHX2 **114**, stores the fluid in tank **208** and transports the fluid to LAHX2 **114** from tank **208** using pump **210**.

(53) System controller **150** can be structured and operate in association with conditioning system **200** in a manner similar to that described with reference to conditioning system **100** of FIG. 1. For example, controller **150** can be communicatively connected to system **200**, can control operation of components thereof, and can operate the system in multiple modes, including, for example, modes similar to the evaporation mode and the desiccant enhanced evaporation mode described above with reference to the example of FIG. 1. Additionally, system controller **150** can operate system **200** in a true economizer mode by transmitting a cooling fluid in a runaround loop between

recovery coil **202** and LAHX1 **112**. In this true economizer mode, LAMEE1 **108** and LAMEE2 **110** (or another evaporative cooler in place of LAMEE2) are deactivated and the scavenger air sensibly cools the cooling fluid and the cooling fluid sensibly cools the process air.

(54) FIG. **3** is a psychometric process diagram for a theoretical system substantially similar to example system **200** of FIG. **2**. The psychometric process diagram illustrates the conditions of a modeled conditioning system and, in particular, conditions of the working fluid(s) thereof at different components of the system and/or at different points during operation. The process diagram depicted in FIG. **3** was created using various numerical, analytical, algorithmic, etc. methods, tools, etc. to estimate the physical characteristics of a system in accordance with this disclosure when operated under certain initial conditions.

(55) The example modeled system is operated at ambient conditions including outdoor air dry bulb temperature of approximately 32.2 degrees Celsius, outdoor air wet bulb temperature of 29.4 degrees Celsius and relative humidity of 81.6%. Additionally, the altitude of the modeled system is sea level (0 meters), the barometric pressure is approximately 760 mm Hg, and the atmospheric pressure is approximately 101.325 kPa. The liquid desiccant employed in LAMEE1 is a lithium chloride solution with a salt concentration of approximately 38% and a target fluid inlet temperature of 35 degrees Celsius. The target set-point temperature for the process air supplied to the enclosed space from the outlet of the process plenum is approximately 30 degrees Celsius. The characteristic values associated with the process diagram of FIG. **3** are as follows:

(56) TABLE-US-00001 1. Air Condition and Flow Rate at Scavenger Inlet 120 Air Flow Dry Wet Relative Humidity Specific Dew Density Vapor Absolute (Standard) bulb Bulb Humidity Ratio Volume Enthalpy Point (kg/ Pressure Humidity (L/s) (° C.) (° C.) (%) (g/kg) (cu .Math. m/kg) (kJ/kg) (° C.) cu .Math. m) (mm Hg) (g/cu .Math. m) 14.159 32.222 29.444 81.6 25.23 0.900 96.906 28.667 1.1394 29.4898 28.037 Energy Change of Air across LAMEE1 108 Start Total Sensible Latent Moisture Sensible Enthalpy/ Point Energy Energy Energy Difference Heat Humidity Ratio Name (W) (W) (W) (kg/hr) Ratio (kJ/kg/g/kg) Inlet 120 -365,991 57,615 -423,606 -595.7 -0.157 N/A 2. Air Condition Leaving LAMEE1 108 Air Flow Dry Wet Relative Humidity Specific Dew Density Vapor Absolute (Standard) bulb Bulb Humidity Ratio Volume Enthalpy Point (kg/ Pressure Humidity (L/s) (° C.) (° C.) (%) (g/kg) (cu .Math. m/kg) (kJ/kg) (° C.) cu .Math. m) (mm Hg) (g/cu .Math. m) 14,159 35.500 24.867 42.4 15.50 0.896 75.384 20.772 1.1336 18.3994 17.303 Energy Chang of Air across LAMEE2 110 Start Total Sensible Latent Moisture Sensible Enthalpy/ Point Energy Energy Energy Energy Difference Heat Humidity Ratio Name (W) (W) (W) (kg/hr) Ratio (kJ/kg/g/kg) LAMEE1 197,590 -81,791 279,381 391.9 -0.414 N/A 3. Air Condition Leaving LAMEE2 110 Air Flow Dry Wet Relative Humidity Specific Dew Density Vapor Absolute (Standard) bulb Bulb Humidity Ratio Volume Enthalpy Point (kg/ Pressure Humidity (L/s) (° C.) (° C.) (%) (g/kg) (cu .Math. m/kg) (kJ/kg) (° C.) cu.m) (mm Hg) (g/cu .Math. m) 14,159 30.900 27.425 76.8 21.90 0.891 87.003 26.339 1.1465 25.7358 24.571 4. Air Condition Leaving Recovery Coil 202 Air Flow Dry Wet Relative Humidity Specific Dew Density Vapor Absolute (Standard) bulb Bulb Humidity Ratio Volume Enthalpy Point (kg/ Pressure Humidity (L/s) (° C.) (° C.) (%) (g/kg) (cu .Math. m/kg) (kJ/kg) (° C.) cu .Math. m) (mm Hg) (g/cu .Math. m) 14,159 32.300 27.748 70.9 21.90 0.895 88.467 26.339 1.1413 25.7358 24.458 Energy Chang of Air across Recovery Coil 202 Start Total Total Sensible Latent Moisture Sensible Enthalpy/ Point Heating Energy Energy Energy Energy Difference Heat Humidity Ratio Name (kW) (W) (W) (W) (kg/hr) Ratio (kJ/kg/g/kg) LAMEE2 24.9 24,892 24,892 0 0.0 1.000 N/A 5. Fluid Outlet of LAMEE2 110 Temperature (° C.) 27.400

(57) Referring to the psychometric process diagram of FIG. **3**, the scavenger air, which in this example is outdoor air, enters the cooling system scavenger plenum via a scavenger inlet at a dry bulb temperature of 32.2 degrees Celsius, a wet bulb temperature of 29.4 degrees Celsius and has a relative humidity of 81.6%. After passing through LAMEE1, the enthalpy of the scavenger air has been markedly reduced and the scavenger air is at a dry bulb temperature of approximately 35.5

degrees Celsius, a wet bulb temperature of 24.9 degrees Celsius and has a relative humidity of 42.4%. After passing through LAMEE2, the scavenger air is at a dry bulb temperature of about 31 degrees Celsius, at a wet bulb temperature of 27.4 degrees Celsius, and has a relative humidity of 76.8%.

(58) Additionally, the process diagram of FIG. 3 illustrates that as the scavenger air passes through the recovery coil, the air sensibly cools the fluid flowing through the recovery coil and thus the scavenger air humidity ratio remains nearly unchanged, while the dry bulb temperature is increased as the scavenger air is sensibly heated by the fluid being circulated through the recovery coil. Finally, the temperature of the cooling fluid supplied from the outlet of LAMEE2 in the scavenger plenum to the inlet of LAHX1 in the process plenum is approximately 27.4 degrees Celsius, which, in this example, is sufficient for LAHX1 to sensibly cool the process air to a target set-point temperature for the enclosed space of approximately 30 degrees Celsius.

(59) A target temperature of the fluid at the fluid outlet of LAMEE2 110 may be determined using the target set-point temperature for the enclosed space and the efficiency of LAHX1 112. The target set-point temperature for the enclosed space may be a known, constant, which is prescribed by desired conditions in the space. For example, in a data center, the target set-point temperature may be a temperature at or below which the computer, networking, data storage, etc. components in the data center need to be maintained for proper operation. Similarly, the efficiency of LAHX1 112 will be a value or range that is known and that is prescribed by the particular cooling component employed as LAHX1 112. Thus, the temperature of the fluid at the fluid outlet of LAMEE2 110, $T_{\text{sub.LAMEE2_fluid_outlet}}$, can be determined by subtracting a known constant, A, which accounts for the inefficiency of LAHX1 112, from the target set-point temperature of the space, $T_{\text{sub.space}}$, as follows:

$$T_{\text{sub.LAMEE2_fluid_outlet}} = T_{\text{sub.space}} - A \quad (1)$$

(60) In the foregoing formula, “A” is sometimes referred to as the approach temperature, i.e. how close the air temperature, $T_{\text{sub.space}}$, coming out of the coil approaches the inlet water temperature, $T_{\text{sub.LAMEE2_fluid_outlet}}$. This term can be used at the design stage. However, in operation, the system would typically use a feedback control loop to maintain the leaving air temperature, $T_{\text{sub.space}}$. The water temperature would be, for example, dynamically modulated to hold $T_{\text{sub.space}}$ at a target value.

(61) Referring again to FIG. 2, conditioning system 200 includes a liquid desiccant regeneration system, which is fluidically connected to LAMEE1 108 via second fluid circuit 214. The liquid desiccant regeneration system can take a number of different specific forms and is generally configured to regenerate diluted desiccant leaving LAMEE1 108 and, in some cases, to supply the water removed from the desiccant to other components, including, for example, LAMEE2 110. Thus, desiccant at a target concentration can be returned to LAMEE1 108 for use thereby/therein and water removed from the scavenger air by LAMEE1 can be supplied to a component that employs water to some useful effect(s) like replacing/supplying the water consumed in LAMEE2 110.

(62) In general, example liquid desiccant regeneration systems can include thermally driven brine concentration systems. For example, a vacuum membrane distillation system could be employed, a byproduct of which is distilled water. In one example, a vacuum membrane distillation system from memsys GmbH of Germany. Other types of regenerations systems that are electrically or mechanically driven can also be used in examples according to this disclosure.

(63) Liquid desiccant regeneration systems can be employed in any examples in accordance with this disclosure, both to reconstitute a liquid desiccant used in a dehumidifying LAMEE and also to extract water removed from the scavenger air for some useful effect elsewhere in the same or a different system. FIG. 4 depicts another example conditioning system 400. Conditioning system 400 shares many of the components and functions of example conditioning system 200 of FIG. 2, and adds pre-cooler 402, pump 404 and valve 406, which are incorporated into and interconnected

with the system via first fluid circuit **408**. Thus, example conditioning system **400** includes LAMEE1 **108** to lower the enthalpy/wet bulb temperature of the incoming scavenger air (for example, outdoor air) using a liquid desiccant, pre-cooler **402** to sensibly cool the dehumidified scavenger air from LAMEE1 before it flows through/by LAMEE2 **110**, LAMEE2 **110** to cool a fluid for use by LAHX1 **112** to directly and sensibly cool the process return air to be supplied back to the enclosed space, and recovery coil **202** to cool the fluid flowing out of LAHX1 **112** before it is returned to the inlet of LAMEE2. Conditioning system **400** also includes a liquid desiccant regeneration system, which is configured to regenerate desiccant leaving LAMEE1 **108**, which has been diluted by water from the scavenger air, and, in some cases, to supply the water removed from the desiccant to other components, including, for example, LAMEE2 **110**.

(64) In FIG. **4**, conditioning system **400** includes system cabinet **102**, scavenger plenum **104**, process plenum **106**, LAMEE1 **108**, LAMEE2 **110**, LAHX1 **112**, LAHX2 **114** and recovery coil **202**. Scavenger plenum **104** includes inlet **120** and outlet **122**, and associated and generally collocated with each of inlet **120** and outlet **122** are dampers **124** and **126**, respectively. Process plenum **106** includes inlet **128**, with which is associated and collocated with damper **130**, and outlet **132**, which is associated and collocated with damper **134**. Conditioning system **400** also includes scavenger fan **136**, process fan **138**, system controller **150**, tanks **204** and **208** and associated pumps **206** and **210**, and second fluid circuit **214**.

(65) Pre-cooler **402** of conditioning system **400** is arranged in scavenger plenum **104** between LAMEE1 **108** and LAMEE2 **110**. Pre-cooler **402** can be, for example, a cooling coil that is configured to condition the scavenger air and/or the fluid flowing through the pre-cooler before it enters LAMEE2 **110**. In some examples, a filter (not shown) can be arranged inside scavenger plenum **104** and/or process plenum **106** near the air inlet.

(66) In the example of FIG. **4**, a branch of first fluid circuit **408** can transport water (or another heat transfer fluid) from tank **204** to the inlet of pre-cooler **402**. The cooling fluid flowing through pre-cooler **402** is transported via fluid circuit **408** from the outlet of the pre-cooler to the inlet of LAMEE2 **110** (and, in some cases, mixed with fluid exiting recovery coil **202**).

(67) First fluid circuit **408** of system **400** also includes valve **406**. A branch **408a** of first fluid circuit **408** transports cooling fluid cooled by recovery coil **202** out of the fluid outlet of the recovery coil to valve **406**. Depending upon the state of valve **406**, the fluid flowing through branch **408a** either can flow through branch **408b** to the inlet of LAMEE2 **110** or can flow through branch **408c** into tank **204**. Branch **408d** of fluid circuit **408** transports fluid from the outlet of pre-cooler **402** and intermixes with the fluid flowing through branch **408b** (from valve **406**), before flowing to the inlet of LAMEE2 **110**. Branch **408e** transports fluid from tank **204** to the fluid inlet of LAHX1 **112** in process plenum **106**. Finally, branch **408f** transports fluid from the outlet of LAHX1 **112** in process plenum **106** to the inlet of recovery coil **202** in scavenger plenum **104**.

(68) In at least some cases, pre-cooler **402** can be effective when the temperature of the water entering the pre-cooler **402** is lower than the entering air (air leaving LAMEE1 if this device is operating and not bypassed) dry bulb temperature. Conditioning system **400** can be used in typical summer conditions as well as extreme summer conditions when the outdoor air can be very hot and humid. Pre-cooler **402** can function to depress the scavenger air dry bulb temperature, thus pre-cooling the scavenger air passing through the pre-cooler and heating the water in the pre-cooler **402**. The scavenger air and the water can then pass through LAMEE2 **110**, as described above, in which case evaporation occurs and water (or other fluid) or both the air and water can be cooled to a temperature approaching the wet bulb temperature of the scavenger air leaving the pre-cooler, which is lower than the wet bulb temperature entering the pre-cooler. After passing through LAMEE2 **110**, the scavenger air can then pass through recovery coil **202** and thereby cool the heated fluid received by recovery coil **202** from LAHX1 **112**.

(69) Conditioning system **400** can allow for a plurality of operating modes and selection of the mode can depend, for example, on the outdoor air conditions and a cooling load for the system.

When the outdoor air is relatively cold (for example, at or below a threshold temperature), conditioning system **400** can operate in a first mode, an economizer mode. In this first example mode of operation, LAMEE1 **108**, pre-cooler **402** and LAMEE2 **110** are all deactivated and/or bypassed from air and/or fluid flow. Recovery coil **202** in scavenger plenum **104** and LAHX1 **112** in process plenum **106** are coupled such that the cooling fluid, for example, water circulates through the recovery coil and LAHX1 in a closed loop.

(70) In a second operating mode, which can also be referred to as an adiabatic mode, the cooling fluid, for example, water continues to travel in a closed loop through recovery coil **202** in scavenger plenum **104** and LAHX1 **112** in process plenum **106**. LAMEE2 **110** is engaged to adiabatically cool the incoming scavenger air before it goes through the recovery coil. In one example employing this or a similar adiabatic mode, water or another heat transfer fluid is pumped through LAMEE2 **110** in a closed circuit, independent of the water or other fluid circuit transporting water among recovery coil **202** and LAHX1 **112**. LAMEE1 **108** and pre-cooler **402** can be deactivated and/or bypassed from air and/or fluid flow in this second example mode of operation. LAMEE1 may also be actuated to pre-dry the air before it is adiabatically cooled in LAMEE2.

(71) In a third operating mode, which can also be referred to as an evaporation mode, the water or other fluid flowing out of the outlet of recovery coil **202** is directed into the fluid inlet of LAMEE2 **110**, for example by activation or deactivation of valve **406**. LAMEE2 **110** cools the water to a set point temperature. The water flowing from the fluid outlet of LAMEE2 **110** is transported to the fluid inlet of LAHX1 **112** (for example, via tank1 **204**). In this mode, LAMEE2 **110**, recovery coil **202** and LAHX1 **112** are all in the process water (or other fluid) circuit, while LAMEE1 **108** and pre-cooler **402** are deactivated and/or bypassed from air and/or fluid flow in this second example mode of operation.

(72) In a fourth operating mode, which can also be referred to as an enhanced or super evaporation mode, LAMEE1 **108** and/or pre-cooler **402** are activated to lower the enthalpy of the scavenger air stream. Pre-cooler **402** may use some of the cold process water in tank1 **204**, or be supplied by another cold water source. In some examples, pre-cooler **402** and LAMEE1 **108** may be staged on separately/sequentially, defining additional modes of operation.

(73) FIG. 5 is a psychometric process diagram for a theoretical system substantially similar to example system **400** of FIG. 4. The psychometric process diagram illustrates the conditions of the example modeled system and, in particular, conditions of the working fluid(s) thereof at different components of the system and/or at different points during operation. The process diagram depicted in FIG. 5 was created using various numerical, analytical, algorithmic, etc. methods, tools, etc. to estimate the physical characteristics of a system in accordance with this disclosure when operated under certain initial conditions.

(74) The example modeled system is operated at ambient conditions including outdoor air dry bulb temperature of approximately 30.7 degrees Celsius, outdoor air wet bulb temperature of 27.7 degrees Celsius and relative humidity of 80%. Additionally, the altitude of the modeled system is 16 meters, the barometric pressure is approximately 758.56 mm Hg, and the atmospheric pressure is approximately 101.133 kPa. The liquid desiccant employed in LAMEE1 is a lithium chloride solution with a salt concentration of approximately 32% and a target fluid inlet temperature of 35 degrees Celsius. The target set-point temperature for the process air supplied to the enclosed space from the outlet of the process plenum is 85 degrees Fahrenheit. The characteristic values associated with the process diagram of FIG. 5 are as follows:

(75) TABLE-US-00002 1. Air Condition and Flow Rate at Scavenger Inlet 120 Air Flow Dry Wet
Relative Humidity Specific Dew Density Vapor Absolute (Standard) bulb Bulb Humidity Ratio
Volume Enthalpy Point (kg/ Pressure Humidity (L/s) (° C.) (° C.) (%) (g/kg) (cu .Math. m/kg)
(kJ/kg) (° C.) cu .Math. m) (mm Hg) (g/cu .Math. m) 14,159 30.667 27.722 80.0 22.60 0.893
88.549 26.822 1.1448 26.4790 25.300 2. Air Condition Leaving LAMEE1 108 Air Flow Dry Wet

Relative Humidity Specific Dew Density Vapor Absolute (Standard) bulb Bulb Humidity Ratio
Volume Enthalpy Point (kg/ Pressure Humidity (L/s) (° C.) (° C.) (%) (g/kg) (cu .Math. m/kg)
(kJ/kg) (° C.) cu .Math. m) (mm Hg) (g/cu .Math. m) 14,159 34.900 26.001 49.8 17.70 0.899
80.410 22.861 1.1322 20.9035 19.692 Energy Change of Air across LAMEE1 108 Start Total
Sensible Latent Moisture Sensible Enthalpy/Humidity Point Energy Energy Energy Difference
Heat Ratio Name (W) (W) (W) (kg/hr) Ratio (kJ/kg/g/kg) Inlet 120 -138,411 74,706 -213,117
-300.0 -0.540 N/A 3. Air Condition Leaving Pre-cooler 402 Air Flow Dry Wet Relative Humidity
Specific Dew Density Vapor Absolute (Standard) bulb Bulb Humidity Ratio Volume Enthalpy
Point (kg/ Pressure Humidity (L/s) (° C.) (° C.) (%) (g/kg) (cu .Math. m/kg) (kJ/kg) (° C.) cu
.Math. m) (mm Hg) (g/cu .Math. m) 14,159 28.400 24.355 72.0 17.70 0.880 73.664 22.861 1.1566
20.9035 20.116 Energy Chang of Air across Pre-cooler 402 Start Total Total Sensible Latent
Moisture Sensible Enthalpy/Humidity Point Cooling Energy Energy Energy Difference Heat Ratio
Name (kW) (W) (W) (W) (kg/hr) Ratio (kJ/kg/g/kg) LAMEE1 -114.7 -114,711 -114,711 0 0.0
1.000 N/A 4. Air Condition Leaving LAMEE2 110 Air Flow Dry Wet Relative Humidity Specific
Dew Density Vapor Absolute (Standard) bulb Bulb Humidity Ratio Volume Enthalpy Point (kg/
Pressure Humidity (L/s) (° C.) (° C.) (%) (g/kg) (cu .Math. m/kg) (kJ/kg) (° C.) cu .Math. m) (mm
Hg) (g/cu .Math. m) 14,159 29.300 27.190 85.1 22.20 0.889 86.098 26.533 1.1502 26.0326 24.980
Energy Chang of Air across LAMEE2 110 Start Total Sensible Latent Moisture Sensible
Enthalpy/Humidity Point Energy Energy Energy Energy Difference Heat Ratio Name (W) (W) (W) (kg/hr)
Ratio (kJ/kg/g/kg) Pre-cooler 211,440 16,011 195,429 275.6 0.076 N/A 5. Air Condition Leaving
Recovery Coil 202 Air Flow Dry Wet Relative Humidity Specific Dew Density Vapor Absolute
(Standard) bulb Bulb Humidity Ratio Volume Enthalpy Point (kg/ Pressure Humidity (L/s) (° C.) (°
C.) (%) (g/kg) (cu .Math. m/kg) (kJ/kg) (° C.) cu .Math. m) (mm Hg) (g/cu .Math. m) 14,159
35.500 28.600 60.0 22.20 0.907 92.583 26.533 1.1271 26.0326 24.479 Energy Chang of Air across
Recovery Coil 202 Start Total Total Sensible Latent Moisture Sensible Enthalpy/Humidity Point
Heating Energy Energy Energy Energy Difference Heat Ratio Name (kW) (W) (W) (W) (kg/hr) Ratio
(kJ/kg/g/kg) LAMEE2 110.3 110,298 110,298 0 0.0 1.000 N/A 6. Fluid Outlet of LAMEE2 110
Temperature (° C.) 26.600

(76) Referring to the psychrometric process diagram of FIG. 5, the scavenger air, which in this example is outdoor air, enters the conditioning system scavenger plenum via a scavenger inlet at a dry bulb temperature of 30.7 degrees Celsius, a wet bulb temperature of 27.7 degrees Celsius and has a relative humidity of 80%. After passing through LAMEE1, the enthalpy of the scavenger air has been markedly reduced and the scavenger air is at a dry bulb temperature of approximately 34.9 degrees Celsius, a wet bulb temperature of 26 degrees Celsius and has a relative humidity of 49.8%. After passing through the pre-cooler, the scavenger air has a dry bulb temperature of 28.4 degrees Celsius, a wet bulb temperature of 24.4 degrees Celsius and a relative humidity of 72%. After passing through LAMEE2, the scavenger air is at a dry bulb temperature of about 29.3 degrees Celsius, at a wet bulb temperature of 27.2 degrees Celsius, and has a relatively humidity of 85.1%.

(77) Additionally, the process diagram of FIG. 5 illustrates that as the scavenger air passes through the recovery coil, the air sensibly cools the fluid flowing through the recovery coil and thus the scavenger air temperature is increased as the scavenger air is heated by the fluid being circulated through the recovery coil. Finally, the temperature of the cooling fluid supplied from the outlet of LAMEE2 in the scavenger plenum to the inlet of LAHX1 in the process plenum is approximately 26.6 degrees Celsius, which, in this example, is sufficient for LAHX1 to directly and sensibly cool the process air to a target set-point temperature for the enclosed space of approximately 30 degrees Celsius.

(78) FIG. 6 is a psychrometric process diagram for a theoretical system with the same components and arrangements thereof as the system modeled to produce the process diagram of FIG. 5, except the pre-cooler and the recovery coil have lower capacities/conditioning effectiveness. The

psychometric process diagram of FIG. 6 illustrates the conditions of the example modeled system and, in particular, conditions of the working fluid(s) thereof at different components of the system and/or at different points during operation. The process diagram depicted in FIG. 6 was created using various numerical, analytical, algorithmic, etc. methods, tools, etc. to estimate the physical characteristics of a system in accordance with this disclosure when operated under certain initial conditions.

(79) The example modeled system is operated at ambient conditions including outdoor air dry bulb temperature of approximately 32.2 degrees Celsius, outdoor air wet bulb temperature of 29.4 degrees Celsius and relative humidity of 81.5%. Additionally, the altitude of the modeled system is 16 meters, the barometric pressure is approximately 758.56 mm Hg, and the atmospheric pressure is approximately 101.133 kPa. The liquid desiccant employed in LAMEE1 is a lithium chloride solution with a salt concentration of approximately 38% and a target fluid inlet temperature of approximately 33.9 degrees Celsius. The target set-point temperature for the process air supplied to the enclosed space from the outlet of the process plenum is approximately 28.7 degrees Celsius. The characteristic values associated with the process diagram of FIG. 6 are as follows:

(80) TABLE-US-00003

1. Air Condition and Flow Rate at Scavenger Inlet 120													
Air Flow	Dry Wet	Relative Humidity	Specific Dew Density	Vapor Absolute (Standard)	Bulb Bulb Humidity Ratio	Volume Enthalpy Point (kg/	Pressure Humidity (L/s)	(° C.)	(° C.)	(%)	(g/kg)	(cu .Math. m/kg)	(kJ/jg)
(° C.)	(° C.)	(cu .Math. m)	(mm Hg)	(g/cu .Math. m)									
14,159	32.200	29.400	81.5	25.20	0.901	96.814	28.617	1.1373	29.4044	27.957			
2. Air Condition Leaving LAMEE1 108													
Air Flow	Dry Wet	Relative Humidity	Specific Dew Density	Vapor Absolute (Standard)	Bulb Bulb Humidity Ratio	Volume Enthalpy Point (kg/	Pressure Humidity (L/s)	(° C.)	(° C.)	(%)	(g/kg)	(cu .Math. m/kg)	(kJ/jg)
(° C.)	(° C.)	(cu .Math. m)	(mm Hg)	(g/cu .Math. m)									
14,159	35.500	24.843	42.3	15.50	0.897	75.385	20.744	1.1315	18.3679	17.270			
Energy Change of Air across LAMEE1 108													
Start	Total	Sensible Energy	Moisture Sensible Enthalpy/	Point Energy	Energy (W)	Difference	Heat	Humidity	Ratio	Name (W)	(W)	Latent (kg/hr)	Ratio (kJ/kg/g/kg)
Inlet 120	-364,416	58,008	-422,424	-594.0	-0.159	N/A							
3. Air Condition Leaving Pre-cooler 402													
Air Flow	Dry Wet	Relative Humidity	Specific Dew Density	Vapor Absolute (Standard)	Bulb Bulb Humidity Ratio	Volume Enthalpy Point (kg/	Pressure Humidity (L/s)	(° C.)	(° C.)	(%)	(g/kg)	(cu .Math. m/kg)	(kJ/jg)
(° C.)	(° C.)	(cu .Math. m)	(mm Hg)	(g/cu .Math. m)									
14,159	28.600	23.009	62.5	15.50	0.877	68.253	20.744	1.1574	18.3679	17.665			
Energy Change of Air across Pre-cooler 402													
Start	Total	Total Sensible	Latent	Moisture Sensible Enthalpy/	Point Cooling	Energy	Energy	Energy	Difference	Heat	Humidity	Ratio	Name (kW)
LAMEE1	-121.3	-121,290	121,290	0	0.0	1.000	N/A						
4. Air Condition Leaving LAMEE2 110													
Air Flow	Dry Wet	Relative Humidity	Specific Dew Density	Vapor Absolute (Standard)	Bulb Bulb Humidity Ratio	Volume Enthalpy Point (kg/	Pressure Humidity (L/s)	(° C.)	(° C.)	(%)	(g/kg)	(cu .Math. m/kg)	(kJ/jg)
(° C.)	(° C.)	(cu .Math. m)	(mm Hg)	(g/cu .Math. m)									
14,159	28.700	26.210	82.3	20.70	0.885	81.638	25.389	1.1535	24.3278	23.393			
Energy Change of Air across LAMEE2 110													
Start	Total	Total Sensible	Latent	Moisture Sensible Enthalpy/	Point	Heating	Energy	Energy	Energy	Difference	Heat	Humidity	Ratio Name (kW)
LAMEE2	120.6	120,650	120,650	0	0.0	1.000	N/A						
6. Fluid Outlet of LAMEE2 110													
Temperature (° C.)	25.700												

(81) Referring to the psychometric process diagram of FIG. 6, the scavenger air, which in this example is outdoor air, enters the conditioning system scavenger plenum via a scavenger inlet at a

dry bulb temperature of 32.2 degrees Celsius, a wet bulb temperature of 29.4 degrees Celsius and has a relative humidity of 81.5%. After passing through LAMEE1, the enthalpy of the scavenger air has been markedly reduced and the scavenger air is at a dry bulb temperature of approximately 35.5 degrees Celsius, a wet bulb temperature of 24.8 degrees Celsius and has a relative humidity of 42.3%. After passing through the pre-cooler, the scavenger air has a dry bulb temperature of 28.6 degrees Celsius, a wet bulb temperature of approximately 23 degrees Celsius and a relative humidity of 62.5%. After passing through LAMEE2, the scavenger air is at a dry bulb temperature of about 28.7 degrees Celsius, at a wet bulb temperature of 26.2 degrees Celsius, and has a relative humidity of 82.3%.

(82) Additionally, the process diagram of FIG. 6 illustrates that as the scavenger air passes through the recovery coil, the air sensibly cools the fluid flowing through the recovery coil and thus the scavenger air temperature is increased as the scavenger air is heated by the fluid being circulated through the recovery coil. Finally, the temperature of the cooling fluid supplied from the outlet of LAMEE2 in the scavenger plenum to the inlet of LAHX1 in the process plenum is approximately 25.7 degrees Celsius, which, in this example, is sufficient for LAHX1 to directly and sensibly cool the process air to a target set-point temperature for the enclosed space of approximately 28.7 degrees Celsius.

(83) Referring again to FIG. 4, conditioning system 400 includes a liquid desiccant regeneration system, which is fluidically connected to LAMEE1 108 via second fluid circuit 214. The liquid desiccant regeneration system can take a number of different specific forms and is generally configured to regenerate diluted desiccant leaving LAMEE1 108 and, in some cases, to supply the water removed from the desiccant to other components, including, for example, LAMEE2 110. Thus, desiccant at a target concentration can be returned to LAMEE1 108 for use thereby/therein and water removed from the scavenger air by LAMEE1 can be supplied to a component that employs water to some useful effect(s) like replacing/supplying the water consumed in LAMEE2 110.

(84) In general, example liquid desiccant regeneration systems can include thermally driven brine concentration systems. For example, a vacuum membrane distillation system could be employed, a byproduct of which is distilled water. In one example, a vacuum membrane distillation system from memsys GmbH of Germany. Liquid desiccant regeneration systems can be employed in any examples in accordance with this disclosure, both to reconstitute a liquid desiccant used in a dehumidifying LAMEE and also to extract water removed from the scavenger air for some useful effect elsewhere in the same or a different system.

(85) FIG. 7 depicts an example liquid desiccant regeneration system connected to a conditioning system in accordance with this disclosure. The regeneration system including a desiccant regenerator 700 is fluidically coupled to LAMEE1 108 and LAMEE2 110. The system of FIG. 7 can thus be employed with and generally connected to any example conditioning systems in accordance with this disclosure, including the examples of FIGS. 1, 2, 4 and 9-13.

(86) Regenerator 700 is generally configured to modulate and maintain the liquid desiccant flowing through LAMEE1 at a target relative concentration (for example, water to salt), including, for example, delivering a lithium chloride liquid desiccant to the fluid inlet of LAMEE1 at a concentration in a range from approximately 32% lithium chloride to approximately 38% lithium chloride. Additionally, regenerator 700 can extract water from the diluted desiccant flowing out of LAMEE1 and supply this water to LAMEE2. As noted above, the water collection rate/capacity of dryer LAMEE1 in examples according to this disclosure may exceed the evaporation rate of the evaporative cooler LAMEE2. As such, in at least some examples and operating conditions, the water removed from the scavenger air by LAMEE1 (in addition to markedly reducing the enthalpy of the scavenger air and thereby boosting the cooling capacity of LAMEE2) can be collected in quantities sufficient to completely supply the fluid necessary to drive operation of LAMEE2.

(87) FIG. 7 depicts a portion of an example conditioning system including LAMEE1 108 and

LAMEE2 110 disposed in scavenger plenum 104. The fluid tanks 204 and 208 and associated pumps are fluidically interconnected with LAMEE1 108 and LAMEE2 110 and regenerator 700 by one or more fluid circuits, including, for example, first and second fluid circuits 702 and 704. As explained above, LAMEE1 108 is configured to remove water from the scavenger air flowing through scavenger plenum 104. The water extracted from the scavenger air by LAMEE1 108 dilutes the liquid desiccant flowing through LAMEE1. In the example of FIG. 7, The diluted desiccant flows out of the fluid outlet of LAMEE1 108 and into tank 208, where the diluted desiccant intermixes with concentrated desiccant supplied by regenerator 700 and from which liquid desiccant flows to the fluid inlet of LAMEE1 108 and flows into regenerator 700 via modulating transfer valve 706.

(88) In this example, valve 706 can be controlled to modulate the flow rate of desiccant out of tank 208 and thereby divert an amount of desiccant to regenerator 700 necessary to maintain the intermixed desiccant in tank 208 at a target or within a threshold range of desiccant concentration, including, for example, maintaining the desiccant in tank 208 at a concentration in a range from approximately 32% lithium chloride to approximately 38% lithium chloride. In one example, transfer valve 706 is controlled to deliver approximately 250 gallons per minute (gpm) to the fluid inlet of LAMEE1 108 and to deliver approximately 12 gpm to regenerator 700. As the humidity of the scavenger air flowing into LAMEE1 108 rises, the amount of desiccant diverted into regenerator 700 can be increased by controlling transfer valve 706. In some examples, transfer valve 706 can be controlled by system controller 150 described with reference to the examples of FIGS. 1, 2 and 4.

(89) The dehumidification capacity of LAMEE1 108 can depend on a flow rate, a temperature, and a concentration of the liquid desiccant passing there through. In some cases, an example conditioning system in accordance with this disclosure can operate with a set point temperature and a set point concentration of the liquid desiccant flowing into LAMEE1 108. Additionally, in some examples, the flow rate of the desiccant through LAMEE1 108 can be constant. The load on the LAMEE1 108 can vary as the conditions of the air stream passing through scavenger plenum 104 vary. For example, if the air stream increases in humidity, the load on the LAMEE1 108 can increase. As a result, the liquid desiccant exiting LAMEE1 108 can require more regeneration, relative to if LAMEE1 receives a relatively lower humidity air stream. The regeneration system can therefore be configured such that as additional regeneration of the desiccant is required, the flow rate of liquid desiccant to regenerator 700 can be increased via the modulating valve 706. To achieve selective modulation of desiccant flow rate and concentration, for example intermixed in tank 208, the regeneration system can be configured such that the flow of liquid desiccant to the LAHX2 114 can be relatively constant and the flow of liquid desiccant through the modulating valve 706 can be variable.

(90) Regenerator 700 can be a thermally driven brine concentration device/system. In one example, regenerator 700 is a vacuum multi-effect membrane distillation device, which is configured to employ heat to distill the desiccant solution flowing there through. In one example, regenerator 700 can distill 3 liters of water per kW hr of heat input at approximately 80 degrees Celsius. It may be possible, in some cases, to use heat removed from the enclosed space to drive regenerator 700, including, for example, using heat removed from servers and other equipment in a data center to drive the regenerator. However, the heat input requirements to distill the liquid desiccant may be greater than can be typically removed from such equipment in a data center and, as such, in some cases, an additional heat/energy source may be needed to drive distillation of the desiccant by regenerator 700. Regenerator 700 can also include other types of devices, including, for example, electro dialysis, reverse osmosis (RO) filtration, a gas boiler with condenser, a vacuum assisted, multi-stage flash, or other membrane distillation devices other than a vacuum multi-effect membrane distillation device.

(91) In operation, the desiccant exiting tank 208 can be transported to regenerator 700 via second

fluid circuit **704**. Regenerator **700** can separate water from the desiccant such that a concentrated desiccant supply can be transported back to tank **208** via second fluid circuit **704** and a supply of distilled water can be transported from regenerator to various components/locations via first fluid circuit **702**.

(92) In one example, the distilled water can be transported to tank **204** for evaporative cooler LAMEE2 **110**. Thus the water in the air stream passing through scavenger plenum **104** can be absorbed by the desiccant in the desiccant dryer LAMEE1 **108**, separated from the desiccant in regenerator **700**, and then used as the cooling fluid for the evaporative cooler LAMEEs **110**. This can result in a significant reduction or elimination of water for operation of an evaporative cooler LAMEE or other type of evaporative cooler.

(93) As described above, one feature of example conditioning systems in accordance with this disclosure is the ability to sensibly cool the liquid desiccant employed in LAMEE1 **108** using only outdoor air. FIG. **8** depicts an example LAHX **800** that cools the liquid desiccant employed in LAMEE1 **108**. LAHX **800** is fluidically connected to LAMEE1 **108** by a fluid circuit **802** in a manner similar to LAHX2 **114** of the examples of FIGS. **1**, **2**, **4** and **9-13**.

(94) As described above with reference to FIG. **7**, after the liquid desiccant exits the LAMEE1 **108**, the liquid desiccant can be discharged into a tank **208**, onto the regeneration system and from the regeneration system to LAHX **800**. LAHX **800** can be configured to reduce a temperature of the desiccant prior to passing the desiccant into LAMEE1 **108**. LAHX **800** and regenerator **700**, in combination, can thus decrease a temperature and increase a concentration of the liquid desiccant prior to circulating the desiccant through the desiccant dryer LAMEE1 **108** in scavenger plenum **104**. Both capabilities can be important in order for the desiccant to effectively remove moisture from the air stream passing through LAMEE1 **108**.

(95) LAHX **800** can include any type of device suitable for cooling the liquid desiccant. In one example, LAHX **800** is configured to cool the liquid desiccant employed in LAMEE1 **108** using outdoor air only. In one example, LAHX **800** is a polymer fluid cooler (with or without evaporative cooling capability), a plate exchanger, or other suitable heat exchangers. As schematically depicted, LAHX **800** can be located external to and separate from scavenger plenum **104** and/or other components of the conditioning system. In another example, however, LAHX **800** could be collocated in a common cabinet with other components of the system and outdoor air could be ducted through the LAHX.

(96) The design of example regeneration systems in combination with desiccant dryer LAMEE1 **108** can facilitate operation of conditioning systems in accordance with this disclosure with little to no external water consumption. LAMEE1 **108** can remove the water from the air stream and use that water (which is separated from the desiccant for regeneration of the desiccant) as the cooling fluid for one or more coolers in the conditioning system. The recovered water can be stored in a tank and can be used as needed. Operation of evaporative coolers, like LAMEE2 **110**, can commonly require a significant amount of water. Example conditioning systems having such desiccant regeneration/water extraction can eliminate or markedly decrease the external water needed to operate the system, which, in turn, can decrease costs, complexity, and externalities of the system.

(97) The design of example regeneration systems in combination with desiccant dryer LAMEE1 **108** can also improve operation of evaporative cooler LAMEE2 **110** (or other evaporative cooling device) since water can be collected directly from the atmosphere. Such water recovered from the liquid desiccant in the regenerator is often considered relatively high quality water, which can be ideal for many cooling applications, including evaporative coolers. Such high quality water can increase the lifespan of the media in LAMEE2 **110** and can decrease required maintenance on the cooler. In contrast, if the water supplied to the LAMEE2 **110** is potable water from wells or surface water sources, in some cases, mineral build up or scaling can occur, which may require the conditioning system or portions thereof to include management of mineral concentrations or other

water treatment units.

(98) FIGS. **9** and **10** depict two other example conditioning systems **900** and **1000**. Conditioning systems **900** and **1000** share many of the components and functions of example conditioning systems **100**, **200** and **400** of FIGS. **1**, **2** and **4**, and each adds a mechanical cooling system to the fluid circuit to provide cooling to the water (or other fluid) stored in tank **204**. The mechanical cooling system included in conditioning system **900** of FIG. **9** includes a water-cooled condenser, while the mechanical cooling system included in conditioning system **1000** of FIG. **10** includes an air-cooled condenser.

(99) In FIG. **9**, conditioning system **900** includes system cabinet **102**, scavenger plenum **104**, process plenum **106**, LAMEE1 **108**, pre-cooler **402**, LAMEE2 **110**, recovery coil **202**, LAHX1 **112**, LAHX2 **114**, and DX unit **902**. Scavenger plenum **104** includes inlet **120** and outlet **122** and associated and generally collocated dampers **124** and **126**, respectively. Process plenum **106** includes inlet **128**, with which is associated and collocated damper **130**, and outlet **132**, which is associated and collocated damper **134**. Conditioning system **900** also includes scavenger fan **136**, process fan **138**, valve **406**, system controller **150** and tanks **204** and **208**. Pumps to facilitate transport of cooling fluid through system **900** have been omitted from FIG. **9**, but the appropriate number and arrangement of such pumps could be included in this and other conditioning systems in accordance with this disclosure.

(100) In FIG. **9**, conditioning system **900** includes DX or direct expansion unit **902**. A conditioning system having pre-cooler **402**, as shown in FIG. **9**, in combination with a DX unit **902** can be used, for example, in extreme outdoor air conditions. If the temperature in tank **204** is higher than a target set point temperature (to cover 100% of the load), DX unit **902** can cool the water to the target set point temperature. Thus, DX unit **902** can provide additional cooling of the water (or other fluid) leaving tank **204** so that the water can be sufficiently cool to cover the heating/cooling load for the enclosed space.

(101) DX unit **902** includes evaporator **904**, compressor **906**, condenser **908** and expansion valve **910**. DX unit **902** is configured to cool the water in tank **204** using, for example, a condensed refrigerant liquid. In operation, DX unit **902** cools the water or other fluid in tank **204** by passing the condensed refrigerant through one side of a first heat exchanger, evaporator **904**, which cools the water flowing through the other side of evaporator **904**. In evaporator **904**, the refrigerant expands as it absorbs heat, eventually converting to a gas. DX unit **902** then pumps the refrigerant to compressor **906**, which compresses the gas refrigerant and passes it through another heat exchanger, condenser **908**. The heat that is absorbed by the refrigerant can be exhausted, and the cooled, compressed refrigerant is once again in liquid form. DX unit **902** then pumps (or otherwise transports) the cooled refrigerant liquid back to evaporator **904** through expansion valve **910** and the cycle begins again.

(102) In the example of FIG. **9**, condenser **908** is a water-cooled condenser. Condenser **908** is a heat exchanger through which flows the refrigerant of DX unit **902** and the water (or other fluid) of LAMEE2 **110**. The water is cooled in LAMEE2 **110**, as described with reference to other examples. The cooled water from LAMEE2 **110** is transported by the fluid circuit of conditioning system **900** to and flows through condenser **908**. The cooled water cools the compressed refrigerant flowing through the other side of condenser **908** and the cooled refrigerant flows back to evaporator **904** through expansion valve **910**. The water exiting condenser **908** is conveyed to the inlet of LAMEE2 **110**, for example, after mixing with water from pre-cooler **402**, which is also conveyed to the inlet of the LAMEE2 **110**.

(103) As with at least some other examples in accordance with this disclosure, conditioning system **900** can be operated in multiple modes depending upon various factors, including the heat load from the enclosed space and/or the outdoor air (or incoming scavenger air) conditions. For example, system controller **150** can be configured to control elements of system **900** (and other example systems in accordance with this disclosure) to operate differently in different modes.

System controller **150** can be configured to operate system **900** in an economizer mode and evaporation mode, as well as other modes. In the economizer mode, generally, there is sufficient cooling capacity in the outdoor air entering the system that LAMEE2 **110** (or pre-cooler **402** with a slightly modified fluid circuit) can cool the water or other fluid with the scavenger air without cooling by LAMEE1 **108** being required. In the evaporation mode, for example, pre-cooler **402**, LAMEE1 **108**, LAMEE2 **110** and recovery coil **202** may all be activated and used to cool the water flowing through the system using the scavenger air passing through scavenger plenum **104**.

(104) In one example, system controller **150** is configured to cause conditioning system **900** to operate in the evaporation mode. In this mode, for example, outdoor scavenger air is drawn into and through scavenger plenum **104** by fan **136**. The outdoor air passes through LAMEE1 **108**, by which the enthalpy of the outdoor/scavenger air is reduced. The outdoor air passes through and is cooled by pre-cooler **402** using fluid delivered to the inlet of the pre-cooler by a fluid circuit from tank1 **204**. The cooled outdoor air then flows through and evaporatively cools the fluid flowing through LAMEE2 **110**. The cooling fluid is delivered to LAMEE2 **110** by the fluid circuit from the outlet of water-side of condenser **908** and from the outlet of pre-cooler **402**. The scavenger air passes LAMEE2 **110** and flows through recovery coil **202**. Recovery coil **202** receives fluid from the outlet of LAHX1 **112** and the scavenger air cools the heated fluid received from LAHX1. Fan **136** then exhausts the scavenger air out of outlet **122** of scavenger plenum **104**.

(105) The water or other evaporative cooling fluid cooled by LAMEE2 **110** is transported by the fluid circuit to tank1 **204**, which stores the water. As described above, DX unit **902** can be activated to cool the water or other fluid stored in tank1 **204** to keep the fluid at a target set point temperature. From tank1 **204**, the water is transported to the inlet of pre-cooler **402** and to the inlet of the water-side of evaporator **904**. The water is transported from the outlet of the water-side of evaporator **904** to LAHX1 **112**. LAHX1 **112** cools the heated process air returned to process plenum **106** from the enclosed space using the water cooled by LAMEE2 **110** and DX unit **902**.

(106) Still in the evaporation mode, the water flows from the outlet of LAHX1 **112** in process plenum **106** to the inlet of recovery coil **202** in scavenger plenum **104**. System controller **150** can, in the evaporation mode, activate or not activate valve **406** (depending upon the default state of the valve) to cause the water from the outlet of recovery coil **202** to flow into the water-side of condenser **908**. The water exits condenser **908** and returns to the inlet of LAMEE2 **110**.

(107) System controller **150** can also be configured to cause conditioning system **900** to operate in the economizer mode. For example, in the economizer mode, system controller **150** can cause pre-cooler **402**, LAMEE1 **108** and, in some cases, DX unit **902** to be deactivated and/or cause the scavenger air to bypass the pre-cooler **402** and the LAMEE1 **108**. In this mode, LAMEE2 **110** cools the water using the scavenger air and transports the water to LAHX1 **112** via valve **406**, tank1 **204**, and the water-side of evaporator **904**.

(108) FIG. **10** depicts another example conditioning system **1000**. The primary substantive difference between conditioning system **900** of FIG. **9** and conditioning system **1000** of FIG. **10** is that DX unit **902** of conditioning system **900** includes a water-cooled condenser **908**, while DX unit **1002** of conditioning system **1000** includes an air-cooled condenser **1008**. DX unit **1002** can be employed in system **1000** to maintain cooling fluid stored in tank **204** at a target set point temperature.

(109) In FIG. **10**, DX unit **1002** includes evaporator **1004**, compressor **1006**, air-cooled condenser **1008**, and expansion valve **1010**. Air-cooled condenser **1008** is arranged in scavenger plenum **104** downstream of recovery coil **202** and, in some examples, downstream of fan **136**, close to outlet **122** of scavenger plenum **104**. Compressed refrigerant is transported by the fluid circuit of DX unit **1002** from compressor **1006** to condenser **1008**. The scavenger air flowing through scavenger plenum **104** passes through and cools the refrigerant flowing through condenser **1008**.

(110) Although the condenser **1008** is shown inside the plenum **104** in FIG. **10**, the condenser **1008** can be located outside of the plenum **104** and outside of the cabinet **102**. The condenser **1008** can

be located external to the cabinet **102** and can be used, for example, in climates typically having mild outdoor air conditions. Condenser **1008** can use outdoor air, which in some cases can be at a lower temperature than scavenger air passing through the condenser in plenum **104** as shown in FIG. **10**. If condenser **1008** is located external to cabinet **102**, it is recognized that additional components may be included with the condenser, for example, one or more fans.

(111) Conditioning systems **900** and **1000** can include multiple cooling fluids and associated cooling fluid circuits. For example, the refrigerant flowing through DX unit **1002** can be a first cooling fluid and the conduits and other components for conveying the refrigerant can be a first or a first portion of a fluid circuit. The second cooling fluid flowing through pre-cooler **402**, LAMEE2 **110**, LAHX1 **112** and recovery coil **202** can be water or predominantly water. A separate or a portion of a larger fluid cooling circuit (for example, conduits, valves, pumps, filters, etcetera) can be employed to transport the water among the various components in conditioning systems **900** and **1000**. The two cooling fluid circuits or two portions of one circuit can be fluidically isolated from one another such that the first and second cooling fluids do not intermix.

(112) FIG. **11** depicts another example conditioning system **1100**. Conditioning system **1100** shares many of the components and functions of example conditioning systems **900** and **1000** of FIGS. **9** and **10**, except that system **1100** employs a mechanical cooling system **1102** to supplement cooling of the process air flowing through process plenum **106**. Mechanical cooling system **1102** includes an air-cooled condenser **1108**, but, in another example, a water-cooled condenser could be employed in conditioning system **1100**.

(113) Mechanical cooling of the process air can function to provide needed cooling in certain outdoor or other conditions. Additionally, if the water cooling system or components thereof, for example, pre-cooler **402**, LAMEE2 **110**, LAHX1 **112**, and/or recovery coil **202**, malfunction or go offline for some reason, mechanical cooling system **1102** may be employed to provide some or all the required cooling of the heated process air received from the enclosed space to the target supply air temperature.

(114) In FIG. **11**, conditioning system **1100** includes system cabinet **102**, scavenger plenum **104**, process plenum **106**, LAMEE1 **108**, pre-cooler **402**, LAMEE2 **110**, recovery coil **202**, LAHX1 **112**, LAHX2 **114**, and mechanical cooling system **1102**. Scavenger plenum **104** includes inlet **120** and outlet **122** and associated and generally collocated dampers **122** and **124**, respectively. Process plenum **106** includes inlet **128**, with which is associated and collocated damper **130**, and outlet **132**, which is associated and collocated damper **134**. Conditioning system **1100** also includes scavenger fan **136**, process fan **138**, valve **406**, system controller **150** and tank1 **204** and tank2 **208**. Pumps to facilitate transport of cooling fluid through system **1100** have been omitted from FIG. **11**, but the appropriate number and arrangement of such pumps could be included in this and other conditioning systems in accordance with this disclosure.

(115) Conditioning system **1100** includes DX unit **1102** (or some other similar mechanical cooling system). DX unit **1102** includes DX coil **1104**, compressor **1106**, condenser **1108** and expansion valve **1110**. DX coil **1104** is arranged downstream of LAHX1 **110** in process plenum **106**. DX unit **1102** is configured to cool the process air flowing through process plenum **106** using, for example, a condensed refrigerant liquid. In operation, DX unit **1102** cools the process air by passing the condensed refrigerant through the coil, which cools the process air and causes the refrigerant to expand as it absorbs heat, eventually converting to a gas. DX unit **1102** then pumps the refrigerant to compressor **1106**, which compresses the gas refrigerant and passes it through another heat exchanger, condenser **1108** arranged in scavenger plenum **104**. The scavenger air cools the refrigerant flowing through condenser **1108**, after which the cooled, compressed refrigerant is once again in liquid form. DX unit **1102** then pumps (or otherwise transports) the cooled refrigerant liquid back to DX coil **1104** through expansion valve **1110** and the cycle begins again.

(116) As with at least some other examples in accordance with this disclosure, conditioning system **1100** can be operated in multiple modes depending upon various factors, including the heat load

from the enclosed space and/or the outdoor air (or incoming scavenger air) conditions. For example, system controller **150** can be configured to control elements of system **1100** (and other example systems in accordance with this disclosure) to operate differently in different modes. System controller **150** can be configured to operate system **1100** in an economizer mode and evaporation mode, as well as other modes. For example, in the economizer mode, generally, there is sufficient cooling capacity in the outdoor air entering the system that LAMEE2 **110** can cool the water or other fluid with the scavenger air without conditioning by LAMEE1 **108** being required. In this mode, for example, system controller **150** can cause LAMEE1 **108**, pre-cooler **402**, and, in some cases, DX unit **1102** to be deactivated and/or cause the scavenger air to bypass the pre-cooler and LAMEE1. In this mode, as described with reference to other examples in accordance with this disclosure, LAMEE2 **110** cools the water using the scavenger air and transports the water to LAHX1 **112** via valve **406** and tank **204**. In the evaporation mode, for example, LAMEE1 **108**, pre-cooler **402**, LAMEE2 **110** and recovery coil **202** may all be activated and used to cool the water (or other heat transfer fluid) flowing to and employed by LAHX1 **112** to cool the process air. Additionally, in an evaporation plus DX mode, DX unit **1102** may be activated and used to provide supplemental cooling to the process air cooled by LAHX1 **112**.

(117) In one example, system controller **150** is configured to cause conditioning system **1100** to operate in the evaporation mode. In this mode, for example, outdoor scavenger air is drawn into and through scavenger plenum **104** by fan **136**. The outdoor air passes through LAMEE1 **108**, by which the enthalpy of the outdoor/scavenger air is reduced. The outdoor air then passes through and is cooled by pre-cooler **402** using fluid delivered to the inlet of the pre-cooler by a fluid circuit from tank **204**. The cooled outdoor air then flows through and evaporatively cools the fluid flowing through LAMEE2 **110**. The scavenger air passes LAMEE2 **110** and flows through recovery coil **202**. Recovery coil **202** receives fluid from the outlet of LAHX1 **112** and the scavenger air cools the heated fluid received from LAHX1 **112**. Fan **136** then exhausts the scavenger air out of outlet **122** of scavenger plenum **104**.

(118) The water or other evaporative cooling fluid cooled by LAMEE1 **108** is transported by the fluid circuit to tank **204**, which stores the water. From tank **204**, the water is transported to the inlet of pre-cooler **402** and to the inlet of LAHX1 **112**. LAHX1 **112** directly and sensibly cools the heated process air returned to process plenum **106** from the enclosed space using the water cooled by LAMEE2 **110**.

(119) Still in the evaporation mode, the water flows from the outlet of LAHX1 **112** in process plenum **106** to the inlet of recovery coil **202** in scavenger plenum **104**. System controller **150** can, in the evaporation mode, activate or not activate valve **406** (depending upon the default state of the valve) to cause the water from the outlet of recovery coil **202** to flow into tank **204**.

(120) In the evaporation plus DX mode, system controller **150** activates DX unit **1102**. In this mode, LAHX1 **112** cools the process air using the cooled water or other fluid from tank **204**. Additionally, the process air passes LAHX1 **112** and is cooled further by DX coil **1104** arranged in process plenum **106** downstream of LAHX1 **112**. In this case, DX coil **1104** may cool the process air to the target supply temperature before the air is supplied to the enclosed space.

(121) System controller **150** can also be configured to cause conditioning system **1100** to operate in the economizer mode. For example, in the economizer mode, system controller **150** can cause LAMEE1 **108**, pre-cooler **402**, and, in some cases, DX unit **1102** to be deactivated and/or cause the scavenger air to bypass the pre-cooler and LAMEE1. In this mode, as described with reference to other examples in accordance with this disclosure, LAMEE2 **110** cools the water using the scavenger air and transports the water to LAHX1 **112** via valve **406** and tank **204**.

(122) FIG. **12** depicts another example conditioning system **1200** including a liquid-to-liquid heat exchanger (LLHX) **1202**. Conditioning system **1200** has many components and functions in common with the above-described examples. For example, in FIG. **12**, conditioning system **1200** includes system cabinet **102**, scavenger plenum **104**, process plenum **106**, LAMEE1 **108**, LAMEE2

110, **LAHX1 112** and **LAHX2 114**. Scavenger plenum **104** includes inlet **120**, outlet **122** and associated and generally collocated therewith are dampers **124** and **126**, respectively. Process plenum **106** includes inlet **128**, with which is associated and collocated damper **130**, and outlet **132**, which is associated and collocated damper **134**. Conditioning system **1200** also includes scavenger fan **136**, process fan **138**, system controller **150** and tanks **204** and **208**. Pumps to facilitate transport of cooling fluids through system **1200** have been omitted from FIG. **12**, but the appropriate number and arrangement of such pumps could be included in this and other conditioning systems in accordance with this disclosure.

(123) In the example of FIG. **12**, conditioning system **LLHX 1202**, which is configured and arranged to use the water or other first cooling fluid coming from **LAMEE2 110**, via a first fluid circuit **1204** and tank **1 204**, to cool a second cooling fluid flowing through the **LLHX 1202**, **LAHX1 112** and recovery coil **202** via second fluid circuit **1206**. Employing **LLHX 1202** in conditioning system **1200** can have a number of advantages, including, for example, reducing the risk of freezing in the fluid circuit **1206** in a winter/economizer mode, because the second cooling fluid can be glycol or another fluid with anti-freeze properties.

(124) Water cooled by **LAMEE2 110** is transported via fluid circuit **1204** from the outlet of **LAMEE2** to tank **1 204**. The cooled water leaves tank **204** and enters the first side of **LLHX 1202** (for example, the water side of the **LLHX**). The second fluid can enter the **LLHX 1202** through an input line of fluid circuit **1206** and exit and be transported via another portion of circuit **1206** to **LAHX1 112**. The coolant can be any suitable heat transfer fluid, and, in some cases, can include anti-freeze to minimize the risk of the coolant freezing in the winter. The cooled water flowing through the water side of **LLHX 1202** cools the second cooling fluid flowing through the second side of the **LLHX**. The cooled second cooling fluid is then transported to **LAHX1 112**, which uses the second cooling fluid to cool the heated process air received in process plenum **106** from the enclosed space. **LAHX1 112**, as described with other examples, can be configured to cool the process air to a target supply air temperature.

(125) After being used to cool the process air, the higher-temperature (also referred to as heated) coolant can be transported via fluid circuit **1206** from an outlet of **LAHX 112** in process plenum **106** to the inlet of recovery coil **202** in scavenger plenum **104**. The scavenger air flowing through scavenger plenum **106** cools the heated second cooling fluid, after which the second cooling fluid recirculates back to the second side of **LLHX 1202**.

(126) **LLHX 1202** can be located physically in system cabinet **102**, but outside of plenums **104** and **106**. In some examples, **LLHX 1202** may be located in either scavenger plenum **104** or process plenum **106**. Additionally, **LLHX 1202** can be located separate from system cabinet **102** and plenums **104** and **106**, in which case pumps or other mechanisms may be employed to transport cooling fluids among the **LLHX** and the other components of conditioning system **1200**.

(127) Although not shown in the example of FIG. **12**, conditioning system **1200** could also include a mechanical cooling system like a DX unit to provide cooling to the water or other cooling fluid stored in tank **1 204** or to the second cooling fluid circulating between the **LLHX 1202**, **LAHX1 112**, and recovery coil **202**. Such a DX unit can be coupled to and function in concert with conditioning system **1200** in a manner similar to that described with reference to conditioning system **1100** of FIG. **11**. Additionally, in examples according to this disclosure, conditioning system **1200** may be configured with **LLHX**, with or without an additional mechanical cooling system, and without pre-cooler **402**.

(128) System controller **150** can be configured to control operation of conditioning system **1200** in multiple modes. A first or evaporation mode is described above, in which all of the components of conditioning system are active and providing cooling.

(129) Additionally, system controller **150** can operate conditioning system **1200** in an economizer mode. In the economizer mode, for example, system controller **150** can cause **LAMEE1 108**, pre-cooler **402** and/or **LAMEE2 110** to be deactivated and/or bypassed from air and/or fluid flow. In

this mode, LLHX **1202** is generally inactive and the second cooling fluid is circulated via second fluid circuit **1206** in a run-around loop between LAHX1 **112** and recovery coil **202**. Recovery coil **202** cools the second cooling fluid using the scavenger air and transports the second fluid to LAHX1 **112**, which uses the cooled second fluid to cool the heated process air received from the enclosed space.

(130) Conditioning system **1200** includes multiple cooling fluids and associated cooling fluid circuits **1204** and **1206**. The first cooling fluid, for example, water or predominantly water flows through LAMEE2 **110**, pre-cooler **402** and LLHX **1202** (at least in evaporation mode in which the LAMEE is activated to provide evaporative cooling). The second cooling fluid, for example, glycol flows through LAHX1 **112**, recovery coil **202** and LLHX **1202**, the second cooling fluid being used in both the evaporation and the economizer modes of operation.

(131) FIG. **13** depicts another example conditioning system **1300** in accordance with this disclosure. In some examples, the scavenger air circuit and the process air circuit, instead of being commonly housed/packaged and collocated, may be separated by some distance. Example conditioning system **1300** of FIG. **13** is substantially the same as conditioning system **400** of FIG. **4**, except that conditioning system **1300** does not include a system cabinet **102** housing the scavenger and process air circuits (and, in some cases, the fluid circuit(s)). In the example of FIG. **13**, instead, scavenger plenum **104** and the associated components and process plenum **106** and the associated components are separately located and separated from one another by some distance. Although this example, in terms of componentry and functionality, is modeled after the example of FIG. **4**, other example conditioning systems in accordance with this disclosure could also be so arranged and configured. For example, any of conditioning systems **100**, **200**, **900**, **1000**, **1100**, and **1200** could also include scavenger and process air circuits (for example, plenum, cooling components, fluid circuits or portions thereof, etcetera) that are separate and located at a distance from one another.

(132) FIG. **14** is a flowchart depicting an example method **1400** of operating a conditioning system in accordance with this disclosure. In FIG. **14**, method **1400** includes directing a first air stream through a first liquid-to-air membrane energy exchanger (LAMEE1) arranged inside a first plenum (**1402**), directing the first air stream through a second LAMEE (LAMEE2) arranged inside the first plenum downstream of LAMEE1 (**1404**), directing a first cooling fluid through a first liquid-to-air heat exchanger (LAHX1) arranged inside a second plenum (**1406**), and directing the liquid desiccant through a second LAHX (LAHX2) in fluid communication with LAMEE1 (**1408**).

(133) In the example method of FIG. **14**, LAMEE1 configured to use a liquid desiccant to lower an enthalpy of the first air stream flowing through the first plenum. LAMEE2 is configured to use the first air stream to evaporatively cool water flowing through LAMEE2. The second plenum is configured to direct a second air stream from a second inlet to a second outlet. Additionally, the second inlet receives heated air from an enclosed space (being conditioned in whole or in part by the system) and the second outlet supplies cooled air to the space. LAHX1 is configured to directly and sensibly cool the second air stream using the first cooling fluid. LAHX2 is configured to cool the liquid desiccant using outdoor air.

(134) Example method **1400** of FIG. **14** illustrates generally the manner in which examples according to this disclosure function to condition the air in an enclosed space. The functions of the method of FIG. **14** can be carried out by a variety of conditioning systems in accordance with this disclosure. For example, the functions of method **1400** can be carried out by conditioning system **100**, **200**, **400**, **900**, **1000**, **1100**, **1200** and/or **1300**, the components and functions of which are described above with reference to FIGS. **1-13**.

(135) FIG. **15** shows an example conditioning system **300** that can be similar to other example systems described and including an alternative design for the fluid circuits for regeneration. Only a portion of the system **1500** is shown in FIG. **15** for simplicity and it is recognized that additional components can be included. For example, only a portion of plenum **104** is shown in FIG. **15**, but it

is recognized that the plenum **104** can include some or all of the additional components shown and described above in reference to other examples.

(136) LAMEE1 **108** can be structured and operate in a similar manner as described in the above examples. The dilute desiccant exiting LAMEE1 **108** at an outlet **1510** can be split into two flow paths—a first flow path to tank **208** or a second flow path directly to regenerator **700** (via a desiccant circuit **1520**). Regenerator **700** can operate similar to the regenerators described above. The desiccant entering regenerator **700** at an inlet **1530** can be at a first concentration **C1**. The concentrated desiccant exiting the regenerator **700** at an outlet **1540** can be at a third concentration **C3** and can be transported to the tank **208** for mixing with the desiccant already in the tank. As such, the desiccant in the tank **208** can be at a second concentration **C2** that is greater than the first concentration **C1** and less than the third concentration **C3**.

(137) In contrast examples depicted and described above, instead of the dilute desiccant (at the concentration **C1**) mixing with the desiccant in the tank and then flowing to the regenerator (at the second concentration **C2**), the dilute desiccant exiting LAMEE1 **108** in FIG. **15** is transported directly to the regenerator **700** at the first concentration **C1**. All of the desiccant exiting the tank **208** at the second concentration **C2** is circulated through LAHX2 **114** and back through LAMEE1, rather than selectively directing a portion of the desiccant at the second concentration **C2** to the regenerator **700**. Thus in the design of FIG. **15** the split of the desiccant flow path is at the outlet **1510** of LAMEE1 **108**, rather than at an outlet of the tank **208**.

NOTES & EXAMPLES

(138) The present application provides for the following exemplary embodiments or examples, the numbering of which is not to be construed as designating levels of importance:

(139) Example 1 provides a system for controlling conditions in an enclosed space, the system comprising: a first plenum configured to direct a first air stream from a first inlet to a first outlet; a second plenum configured to direct a second air stream from a second inlet to a second outlet, the second inlet receiving heated air from the space and the second outlet supplying cooled air to the space; a first liquid-to-air membrane energy exchanger (LAMEE1) arranged inside the first plenum, LAMEE1 configured to use a liquid desiccant to lower an enthalpy of the first air stream; a second LAMEE (LAMEE2) arranged inside the first plenum downstream of LAMEE1, LAMEE2 configured to use the first air stream to evaporatively cool water flowing through LAMEE2; a first liquid-to-air heat exchanger (LAHX1) arranged inside the second plenum, LAHX1 configured to directly and sensibly cool the second air stream using a first cooling fluid; and a second LAHX (LAHX2) in fluid communication with LAMEE1, LAHX2 being configured to receive the liquid desiccant from LAMEE1 and cool the liquid desiccant using outdoor air.

(140) Example 2 provides the system of Example 1 and optionally wherein LAMEE1 is configured to lower the enthalpy of the first air stream by removing water therefrom.

(141) Example 3 provides the system of Example 1 and/or Example 2 and optionally wherein LAMEE1 is configured to lower the enthalpy of the first air stream by removing water therefrom and wherein at least a portion of the water flowing through LAMEE2 comprises the water removed from the first air stream by LAMEE1.

(142) Example 4 provides the system of any of Examples 1-3 and optionally further comprising a pre-cooler coil arranged inside the scavenger plenum upstream of LAMEE2, the pre-cooler coil configured to condition the scavenger air prior to the scavenger air entering LAMEE2.

(143) Example 5 provides the system of Example 4 and optionally wherein the pre-cooler coil is configured to receive at least a portion of the water cooled by LAMEE2 to condition the scavenger air.

(144) Example 6 provides the system of Example 4 and optionally further comprising a fluid storage tank to store the water received from a fluid outlet of LAMEE2.

(145) Example 7 provides the system of Example 6 and optionally further comprising a mechanical cooling system configured to cool the water in the storage tank using a first cooling fluid.

(146) Example 8 provides the system of Example 6 and optionally further comprising a liquid-to-liquid heat exchanger (LLHX) configured to cool the water in the storage tank using a first cooling fluid.

(147) Example 9 provides the system of Example 8 and optionally further comprising a third LAHX (LAHX3), LAHX3 arranged inside of the first plenum downstream of LAMEE2 and configured to cool at least one of the water and the first cooling fluid using the scavenger air.

(148) Example 10 provides the system of Example 9 and optionally further comprising: a first fluid circuit configured to transport the water from a fluid outlet of LAMEE2, through the LLHX and return the water to a fluid inlet of LAMEE2; and a second fluid circuit fluidically isolated from the first fluid circuit, the second fluid circuit configured to transport the first cooling fluid from an outlet of LAHX3 through the LLHX to an inlet of LAHX1, and return the first cooling fluid from the fluid outlet of LAHX1 to a fluid inlet of LAHX3.

(149) Example 11 provides the system of any of Examples 1-10 and optionally further comprising a direct exchange (DX) coil arranged inside the process plenum downstream of LAHX1, the DX coil being configured to cool the process air using a second cooling fluid flowing there through.

(150) Example 12 provides the system of any of Examples 1-11 and optionally wherein LAMEE1 is configured to lower the enthalpy of the first air stream by removing water and heat therefrom, a temperature of the liquid desiccant at a fluid inlet of LAMEE1 being lower than a temperature of the liquid desiccant at a fluid outlet of LAMEE1.

(151) Example 13 provides a system for controlling conditions in an enclosed space, the system comprising: a scavenger plenum configured to direct scavenger air from a scavenger inlet to a scavenger outlet; a process plenum configured to direct process air from a process inlet to a process outlet, the process inlet receiving heated air from the space and the process outlet supplying cooled air to the space; a first liquid-to-air membrane energy exchanger (LAMEE1) arranged inside the scavenger plenum, LAMEE1 configured to use a first fluid flowing through LAMEE1 to reduce a humidity of the scavenger air, a first concentration of water in the scavenger air at an air inlet of LAMEE1 being higher than a second concentration of water in the scavenger air at an air outlet of LAMEE1; an evaporative cooler arranged inside the scavenger plenum downstream of LAMEE1, the evaporative cooler configured to use the scavenger air to evaporatively cool a second fluid flowing there through, a temperature of the second fluid at a fluid outlet of the evaporative cooler being lower than a temperature of the second fluid at a fluid inlet of the evaporative cooler; a first liquid-to-air heat exchanger (LAHX1) arranged inside the process plenum, LAHX1 configured to directly and sensibly cool the process air being directed through the process plenum using a third fluid flowing through LAHX1; and a second LAHX (LAHX2), LAHX2 in fluid communication with LAMEE1 and configured to receive and cool the first fluid using outdoor air.

(152) Example 14 provides the system of Example 13 and optionally wherein LAMEE1 is configured to lower the enthalpy of the first air stream by removing water therefrom.

(153) Example 15 provides the system of Example 13 and/or Example 14 and optionally wherein the second fluid comprises water, and wherein LAMEE1 is configured to lower the enthalpy of the first air stream by removing water therefrom, and wherein at least a portion of the water flowing through the evaporative cooler comprises the water removed from the first air stream by LAMEE1.

(154) Example 16 provides the system of any of Examples 13-15 and optionally further comprising a pre-cooler coil arranged inside the scavenger plenum upstream of LAMEE2, the pre-cooler coil configured to condition the scavenger air prior to the scavenger air entering LAMEE2.

(155) Example 17 provides the system of Example 16 and optionally wherein the pre-cooler coil is configured to receive at least a portion of the second fluid cooled by the evaporative cooler to condition the scavenger air.

(156) Example 18 provides the system of Example 16 and optionally further comprising a fluid storage tank to store the second fluid received from a fluid outlet of the evaporative cooler.

(157) Example 19 provides the system of Example 18 and optionally further comprising a

mechanical cooling system configured to cool the second fluid in the storage tank using a first cooling fluid.

(158) Example 20 provides the system of Example 18 and optionally further comprising a liquid-to-liquid heat exchanger (LLHX) configured to cool the second fluid in the storage tank using a first cooling fluid.

(159) Example 21 provides the system of Example 20 and optionally further comprising a third LAHX (LAHX3), LAHX3 arranged inside of the first plenum downstream of the evaporative cooler and configured to cool at least one of the second fluid and the first cooling fluid using the scavenger air.

(160) Example 22 provides the system of Example 21 and optionally further comprising: a first fluid circuit configured to transport the water from a fluid outlet of the evaporative cooler, through the LLHX and return the water to a fluid inlet of the evaporative cooler; and a second fluid circuit fluidically isolated from the first fluid circuit, the second fluid circuit configured to transport the first cooling fluid from an outlet of LAHX3 through the LLHX to an inlet of LAHX1, and return the first cooling fluid from the fluid outlet of LAHX1 to a fluid inlet of LAHX3.

(161) Example 23 provides the system of any of Examples 13-22 and optionally further comprising a direct exchange (DX) coil arranged inside the process plenum downstream of LAHX1, the DX coil being configured to cool the process air using a second cooling fluid flowing there through.

(162) Example 24 provides the system of any of Examples 13-23 and optionally wherein LAMEE1 is configured to lower the enthalpy of the first air stream by removing water and heat therefrom, a temperature of the liquid desiccant at a fluid inlet of LAMEE1 being lower than a temperature of the liquid desiccant at a fluid outlet of LAMEE1.

(163) Example 25 provides a method for controlling conditions in an enclosed space, the method comprising: directing a first air stream through a first liquid-to-air membrane energy exchanger (LAMEE1) arranged inside a first plenum, LAMEE1 configured to use a liquid desiccant to lower an enthalpy of the first air stream; directing the first air stream through a second LAMEE (LAMEE2) arranged inside the first plenum downstream of LAMEE1, LAMEE2 configured to use the first air stream to evaporatively cool water flowing through LAMEE2; directing a first cooling fluid through a first liquid-to-air heat exchanger (LAHX1) arranged inside a second plenum, the second plenum configured to direct a second air stream from a second inlet to a second outlet, the second inlet receiving heated air from the space and the second outlet supplying cooled air to the space, LAHX1 configured to directly and sensibly cool the second air stream using the first cooling fluid; and directing the liquid desiccant through a second LAHX (LAHX2) in fluid communication with LAMEE1, LAHX2 being configured to cool the liquid desiccant using outdoor air.

(164) Example 26 provides a system for controlling conditions in an enclosed space, the system comprising: a first plenum configured to direct a first air stream from a first inlet to a first outlet; a second plenum configured to direct a second air stream from a second inlet to a second outlet, the second inlet receiving heated air from the space and the second outlet supplying cooled air to the space; a first liquid-to-air membrane energy exchanger (LAMEE1) arranged inside the first plenum, LAMEE1 configured to use a liquid desiccant to lower an enthalpy of the first air stream; an evaporative cooler arranged inside the first plenum downstream of LAMEE1, the evaporative cooler configured to use the first air stream to evaporatively cool water flowing therethrough; a first liquid-to-air heat exchanger (LAHX1) arranged inside the second plenum, LAHX1 configured to directly and sensibly cool the second air stream using a first cooling fluid; and a second LAHX (LAHX2) in fluid communication with LAMEE1, LAHX2 being configured to receive the liquid desiccant from LAMEE1 and cool the liquid desiccant using outdoor air.

(165) Example 27 provides the system of Example 26 and optionally wherein the evaporative cooler comprises a second LAMEE.

(166) Example 28 provides the system of Example 26 and/or Example 27 and optionally wherein LAMEE1 is configured to lower the enthalpy of the first air stream by removing water therefrom.

(167) Example 29 provides the system of any of Examples 26-28 and optionally wherein LAMEE1 is configured to lower the enthalpy of the first air stream by removing water therefrom and wherein at least a portion of the water flowing through LAMEE2 comprises the water removed from the first air stream by LAMEE1.

(168) Example 29 provides the system of any of Examples 26-29 and optionally wherein LAMEE1 is configured to lower the enthalpy of the first air stream by removing water and heat therefrom, a temperature of the liquid desiccant at a fluid inlet of LAMEE1 being lower than a temperature of the liquid desiccant at a fluid outlet of LAMEE1.

(169) Various examples according to this disclosure have been described. These and other examples are within the scope of the following claims.

Claims

1. A system for controlling conditions in an enclosed space, the system comprising: a first plenum configured to direct a first air stream from a first inlet to a first outlet; a second plenum configured to direct a second air stream from a second inlet to a second outlet, the second inlet receiving heated air from the space and the second outlet supplying cooled air to the space; a first liquid-to-air membrane energy exchanger (LAMEE1) arranged inside the first plenum, LAMEE1 configured to use a liquid desiccant to lower an enthalpy of the first air stream; a second LAMEE (LAMEE2) arranged inside the first plenum downstream of LAMEE1, LAMEE2 configured to use the first air stream to evaporatively cool water flowing through LAMEE2; a first liquid-to-air heat exchanger (LAHX1) arranged inside the second plenum, LAHX1 configured to directly and sensibly cool the second air stream using a first cooling fluid; and a second LAHX (LAHX2) in fluid communication with LAMEE1, LAHX2 being configured to receive the liquid desiccant from LAMEE1 and cool the liquid desiccant using outdoor air.
2. The system of claim 1, wherein LAMEE1 is configured to lower the enthalpy of the first air stream by removing water therefrom.
3. The system of claim 1, wherein LAMEE1 is configured to lower the enthalpy of the first air stream by removing water therefrom and wherein at least a portion of the water flowing through LAMEE2 comprises the water removed from the first air stream by LAMEE1.
4. The system of claim 1, further comprising a pre-cooler coil arranged inside the first plenum upstream of LAMEE2, the pre-cooler coil configured to condition the first air stream prior to the first air stream entering LAMEE2.
5. The system of claim 4, wherein the pre-cooler coil is configured to receive at least a portion of the water cooled by LAMEE2 to condition the first air stream.
6. The system of claim 4, further comprising a fluid storage tank to store the water received from a fluid outlet of LAMEE2.
7. The system of claim 6, further comprising a mechanical cooling system configured to cool the water in the storage tank using the first cooling fluid.
8. The system of claim 6, further comprising a liquid-to-liquid heat exchanger (LLHX) configured to cool the water in the storage tank using the first cooling fluid.
9. The system of claim 8, further comprising a third LAHX (LAHX3), LAHX3 arranged inside of the first plenum downstream of LAMEE2 and configured to cool at least one of the water and the first cooling fluid using the first air stream.
10. The system of claim 9, further comprising: a first fluid circuit configured to transport the water from a fluid outlet of LAMEE2, through the LLHX and return the water to a fluid inlet of LAMEE2; and a second fluid circuit fluidically isolated from the first fluid circuit, the second fluid circuit configured to transport the first cooling fluid from an outlet of LAHX3 through the LLHX to an inlet of LAHX1, and return the first cooling fluid from the fluid outlet of LAHX1 to a fluid inlet of LAHX3.

11. The system of claim 1, further comprising a direct exchange (DX) coil arranged inside the second plenum downstream of LAHX1, the DX coil being configured to cool the second air stream using a second cooling fluid flowing there through.
12. The system of claim 1, wherein LAMEE1 is configured to lower the enthalpy of the first air stream by removing water and heat therefrom, a temperature of the liquid desiccant at a fluid inlet of LAMEE1 being lower than a temperature of the liquid desiccant at a fluid outlet of LAMEE1.
13. The system of claim 1, further comprising a third LAHX (LAHX3) arranged inside of the first plenum downstream of LAMEE2 and configured to receive the first cooling fluid from LAHX1 and to cool the first cooling fluid using the first air stream.
14. The system of claim 13, wherein: the first cooling fluid is the water; and the water flows from an outlet of the LAHX3 to an inlet of the LAMEE2.
15. A system for controlling conditions in an enclosed space, the system comprising: a scavenger plenum configured to direct scavenger air from a scavenger inlet to a scavenger outlet; a process plenum configured to direct process air from a process inlet to a process outlet, the process inlet receiving heated air from the space and the process outlet supplying cooled air to the space; a first liquid-to-air membrane energy exchanger (LAMEE1) arranged inside the scavenger plenum, LAMEE1 configured to use a first fluid flowing through LAMEE1 to reduce a humidity of the scavenger air, a first concentration of water in the scavenger air at an air inlet of LAMEE1 being higher than a second concentration of water in the scavenger air at an air outlet of LAMEE1; an evaporative cooler arranged inside the scavenger plenum downstream of LAMEE1, the evaporative cooler configured to use the scavenger air to evaporatively cool a second fluid flowing there through, a temperature of the second fluid at a fluid outlet of the evaporative cooler being lower than a temperature of the second fluid at a fluid inlet of the evaporative cooler; a first liquid-to-air heat exchanger (LAHX1) arranged inside the process plenum, LAHX1 configured to directly and sensibly cool the process air being directed through the process plenum using a third fluid flowing through LAHX1; and a second LAHX (LAHX2), LAHX2 in fluid communication with LAMEE1 and configured to receive the first fluid from the LAMEE1 and cool the first fluid using outdoor air.
16. The system of claim 15, wherein LAMEE1 is configured to lower the enthalpy of the scavenger air by removing water therefrom.
17. The system of claim 15, wherein the second fluid comprises water, and wherein LAMEE1 is configured to lower the enthalpy of the scavenger air by removing water therefrom, and wherein at least a portion of the water flowing through the evaporative cooler comprises the water removed from the scavenger air by LAMEE1.
18. The system of claim 15, further comprising a pre-cooler coil arranged inside the scavenger plenum upstream of LAMEE2, the pre-cooler coil configured to condition the scavenger air prior to the scavenger air entering LAMEE2.
19. The system of claim 18, wherein the pre-cooler coil is configured to receive at least a portion of the second fluid cooled by the evaporative cooler to condition the scavenger air.
20. The system of claim 18, further comprising a fluid storage tank to store the second fluid received from a fluid outlet of the evaporative cooler.
21. The system of claim 20, further comprising a mechanical cooling system configured to cool the second fluid in the storage tank using a first cooling fluid.
22. The system of claim 20, further comprising a liquid-to-liquid heat exchanger (LLHX) configured to cool the second fluid in the storage tank using a first cooling fluid.
23. The system of claim 22, further comprising a third LAHX (LAHX3), LAHX3 arranged inside of the scavenger plenum downstream of the evaporative cooler and configured to cool at least one of the second fluid and the first cooling fluid using the scavenger air.
24. The system of claim 23, further comprising: a first fluid circuit configured to transport the water from a fluid outlet of the evaporative cooler, through the LLHX and return the water to a

fluid inlet of the evaporative cooler; and a second fluid circuit fluidically isolated from the first fluid circuit, the second fluid circuit configured to transport the first cooling fluid from an outlet of LAHX3 through the LLHX to an inlet of LAHX1, and return the first cooling fluid from the fluid outlet of LAHX1 to a fluid inlet of LAHX3.

25. The system of claim 15, further comprising a third LAHX (LAHX3) arranged inside of the scavenger plenum downstream of evaporative cooler and configured to receive the third fluid from LAHX1 and to cool the third fluid using the scavenger air.

26. The system of claim 25, wherein: the third fluid is the second fluid; and the water flows from an outlet of the LAHX3 to an inlet of the evaporative cooler.

27. A method for controlling conditions in an enclosed space, the method comprising: directing a first air stream through a first liquid-to-air membrane energy exchanger (LAMEE1) arranged inside a first plenum, LAMEE1 configured to use a liquid desiccant to lower an enthalpy of the first air stream; directing the first air stream through a second LAMEE (LAMEE2) arranged inside the first plenum downstream of LAMEE1, LAMEE2 configured to use the first air stream to evaporatively cool water flowing through LAMEE2; directing a first cooling fluid through a first liquid-to-air heat exchanger (LAHX1) arranged inside a second plenum, the second plenum configured to direct a second air stream from a second inlet to a second outlet, the second inlet receiving heated air from the space and the second outlet supplying cooled air to the space, LAHX1 configured to directly and sensibly cool the second air stream using the first cooling fluid; and directing the liquid desiccant through a second LAHX (LAHX2) in fluid communication with LAMEE1, LAHX2 being configured to receive the liquid desiccant from the LAMEE1 and to cool the liquid desiccant using outdoor air.

28. The method of claim 27, further comprising directing the first cooling fluid received from the LAHX1 through a third LAHX (LAHX3), the LAHX3 arranged inside the first plenum downstream of the LAMEE2 and configured to cool the first cooling fluid using the first air stream.

29. The method of claim 28, wherein: the first cooling fluid is the water; and the water flows from an outlet of the LAHX3 to an inlet of the LAMEE2.
