US Patent & Trademark Office
Patent Public Search | Text View

United States Patent	12391199
Kind Code	B2
Date of Patent	August 19, 2025
Inventor(s)	Wuollet; Pekka et al.

Utility vehicle fluid containment system

Abstract

A vehicle includes a plurality of ground engaging members and a frame supported by the ground engaging members. A powertrain and a utility or cargo bed are supported by the frame. The cargo bed comprises a first wall extending generally longitudinally and a second wall extending generally longitudinally, and the second wall is laterally spaced from the first wall. The cargo bed further comprises a bed floor extending between the first wall and the second wall and a tailgate. The vehicle further comprises a drain coupled to a rearward portion of the utility bed and the drain is configured to direct fluid from the bed floor to a position rearward of the bed floor and away from at least a portion of the powertrain.

Inventors: **Wuollet; Pekka (East Bethel, MN), Albers; Jared M. (St. Croix Falls, WI), Shaw; William R. (Blaine, MN)**

Applicant: **Polaris Industries Inc.** (Medina, MN)

Family ID: **1000008764438**

Assignee: **Polaris Industries Inc. (Medina, MN)**

Appl. No.: **17/985511**

Filed: **November 11, 2022**

Prior Publication Data

Document Identifier	Publication Date
US 20240157898 A1	May. 16, 2024

Publication Classification

Int. Cl.: **B60R16/00** (20060101); **B60R13/06** (20060101); **B60R16/08** (20060101); **B62D33/023** (20060101)

U.S. Cl.:

CPC **B60R16/08** (20130101); **B60R13/06** (20130101); **B62D33/023** (20130101);

Field of Classification Search

CPC: B60J (10/00); B60J (7/0084); B60R (13/06); B60R (13/07); B60R (5/04); B60R (9/065); B60R (2021/134); B62D (25/24); B62D (33/027); B62D (33/03); B62D (33/02); B62D (25/2054)

USPC: 296/208; 296/213; 296/37.6

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2762090	12/1955	Spraragen	49/500.1	B60R 13/06
3007726	12/1960	Parkin	N/A	N/A
3600768	12/1970	Romanzi et al.	N/A	N/A
3734219	12/1972	Christensen et al.	N/A	N/A
4188058	12/1979	Resa	296/39.2	B60R 13/01
4217970	12/1979	Chika	N/A	N/A
4429588	12/1983	Emundts et al.	N/A	N/A
4561323	12/1984	Stromberg	N/A	N/A
4577716	12/1985	Norton	N/A	N/A
4807921	12/1988	Champie, III	296/100.09	B60J 7/068
4934737	12/1989	Nakatsuka	N/A	N/A
4967944	12/1989	Waters	N/A	N/A
5010970	12/1990	Yamamoto	N/A	N/A
5020616	12/1990	Yagi et al.	N/A	N/A
5021721	12/1990	Oshita et al.	N/A	N/A
5027915	12/1990	Suzuki et al.	N/A	N/A
5076383	12/1990	Inoue et al.	N/A	N/A
5078225	12/1991	Ohmura et al.	N/A	N/A
5083827	12/1991	Hollenbaugh, Sr.	N/A	N/A
5167433	12/1991	Ryan	N/A	N/A
5201562	12/1992	Dorsey	N/A	N/A
5205371	12/1992	Karnopp	N/A	N/A
5251713	12/1992	Enokimoto	N/A	N/A
5253730	12/1992	Hayashi et al.	N/A	N/A
5306044	12/1993	Tucker	N/A	N/A
5327989	12/1993	Furuhashi et al.	N/A	N/A
5440998	12/1994	Morgan, IV	108/901	B65D 19/0048
5473990	12/1994	Anderson et al.	N/A	N/A
5562066	12/1995	Gere et al.	N/A	N/A
5653304	12/1996	Renfroe	N/A	N/A
5772276	12/1997	Fetz	296/181.6	B62D 25/2054

5865498	12/1998	Grogan	N/A	N/A
5887671	12/1998	Yuki et al.	N/A	N/A
5921343	12/1998	Yamakaji	N/A	N/A
6067078	12/1999	Hartman	N/A	N/A
6086158	12/1999	Zeoli	N/A	N/A
6128815	12/1999	Jurica	296/184.1	B62D 65/02
6186547	12/2000	Skabrond et al.	N/A	N/A
6293588	12/2000	Clune	N/A	N/A
6309024	12/2000	Busch	N/A	N/A
6328364	12/2000	Darbishire	N/A	N/A
6347454	12/2001	Jurica	72/379.6	B62D 25/2054
6467787	12/2001	Marsh	N/A	N/A
6502886	12/2002	Bleau et al.	N/A	N/A
6523634	12/2002	Gagnon et al.	N/A	N/A
6582012	12/2002	Smith	296/26.11	B62D 47/003
6626260	12/2002	Gagnon et al.	N/A	N/A
6644709	12/2002	Inagaki et al.	N/A	N/A
6682118	12/2003	Ryan	N/A	N/A
6732830	12/2003	Gagnon et al.	N/A	N/A
6733060	12/2003	Pavkov et al.	N/A	N/A
6767022	12/2003	Chevalier	N/A	N/A
6799779	12/2003	Shibayama	N/A	N/A
6857498	12/2004	Vitale et al.	N/A	N/A
6880875	12/2004	McClure	224/42.2	B62D 43/10
6883851	12/2004	McClure	224/42.2	B62D 33/02
6895318	12/2004	Barton et al.	N/A	N/A
6966399	12/2004	Tanigaki et al.	N/A	N/A
7000931	12/2005	Chevalier	N/A	N/A
7077233	12/2005	Hasegawa	N/A	N/A
7096988	12/2005	Moriyama	N/A	N/A
7118151	12/2005	Bejin	296/37.6	B60R 5/04
7156439	12/2006	Bejin et al.	N/A	N/A
7182169	12/2006	Suzuki	N/A	N/A
7185732	12/2006	Saito et al.	N/A	N/A
7216733	12/2006	Iwami et al.	N/A	N/A
7234707	12/2006	Green et al.	N/A	N/A
7344156	12/2007	Suzuki et al.	N/A	N/A
7357211	12/2007	Inui	N/A	N/A
7370724	12/2007	Saito et al.	N/A	N/A
7374012	12/2007	Inui et al.	N/A	N/A
7374234	12/2007	Deschatres	296/213	B60J 10/90
7380622	12/2007	Shimizu	N/A	N/A
7407190	12/2007	Berg et al.	N/A	N/A
7458593	12/2007	Saito et al.	N/A	N/A
7481293	12/2008	Ogawa et al.	N/A	N/A
7490694	12/2008	Berg et al.	N/A	N/A
7497299	12/2008	Kobayashi	N/A	N/A
7497471	12/2008	Kobayashi	N/A	N/A

7497472	12/2008	Cymbal et al.	N/A	N/A
7503610	12/2008	Karagitz et al.	N/A	N/A
7540511	12/2008	Saito et al.	N/A	N/A
7565944	12/2008	Sakamoto et al.	N/A	N/A
7565945	12/2008	Okada et al.	N/A	N/A
7600603	12/2008	Okada et al.	N/A	N/A
7604084	12/2008	Okada et al.	N/A	N/A
7610132	12/2008	Yanai et al.	N/A	N/A
7625048	12/2008	Rouhana et al.	N/A	N/A
7630807	12/2008	Yoshimura et al.	N/A	N/A
7740103	12/2009	Sasajima	N/A	N/A
7786886	12/2009	Maruyama et al.	N/A	N/A
7819220	12/2009	Sunsdahl et al.	N/A	N/A
7832770	12/2009	Bradley et al.	N/A	N/A
D633006	12/2010	Sanschagrin et al.	N/A	N/A
7950486	12/2010	Van Bronkhorst	180/89.11	B60G 17/021
7954679	12/2010	Edwards	N/A	N/A
8027775	12/2010	Takenaka et al.	N/A	N/A
8056966	12/2010	Edwards	296/37.6	B60R 5/04
8079602	12/2010	Kinsman	280/5.512	B62D 21/14
8104524	12/2011	Manesh et al.	N/A	N/A
8123283	12/2011	Edwards	296/183.1	B60R 9/00
8176957	12/2011	Manesh et al.	N/A	N/A
8215694	12/2011	Smith et al.	N/A	N/A
8231164	12/2011	Schubring et al.	N/A	N/A
8271175	12/2011	Takenaka et al.	N/A	N/A
8302711	12/2011	Kinsman et al.	N/A	N/A
8328235	12/2011	Schneider et al.	N/A	N/A
8382125	12/2012	Sunsdahl et al.	N/A	N/A
8464824	12/2012	Reisenberger	N/A	N/A
8465050	12/2012	Spindler et al.	N/A	N/A
8538628	12/2012	Backman	N/A	N/A
8548710	12/2012	Reisenberger	N/A	N/A
8596405	12/2012	Sunsdahl et al.	N/A	N/A
8613335	12/2012	Deckard et al.	N/A	N/A
8613337	12/2012	Kinsman et al.	N/A	N/A
8640814	12/2013	Deckard et al.	N/A	N/A
8668246	12/2013	Gagnon	296/183.1	B62D 33/02
8781705	12/2013	Reisenberger	N/A	N/A
D711778	12/2013	Chun et al.	N/A	N/A
D712309	12/2013	Wu et al.	N/A	N/A
8827025	12/2013	Hapka	N/A	N/A
8827028	12/2013	Sunsdahl	N/A	B62D 21/183
8997908	12/2014	Kinsman et al.	N/A	N/A
8998253	12/2014	Novotny et al.	N/A	N/A
9010768	12/2014	Kinsman et al.	N/A	N/A
D730239	12/2014	Gonzalez	N/A	N/A

9102287	12/2014	Courtright	N/A	B62D 29/008
9150182	12/2014	Schlangen	N/A	B60G 3/20
D756845	12/2015	Flores	N/A	N/A
D764974	12/2015	Mikhailov et al.	N/A	N/A
9434244	12/2015	Sunsdahl et al.	N/A	N/A
9440671	12/2015	Schlangen et al.	N/A	N/A
9469329	12/2015	Leanza	N/A	N/A
D772755	12/2015	Tandrup et al.	N/A	N/A
9540052	12/2016	Burt, II et al.	N/A	N/A
9555702	12/2016	Olli	N/A	B62D 61/10
9573561	12/2016	Muto et al.	N/A	N/A
D780627	12/2016	Jhant et al.	N/A	N/A
9592713	12/2016	Kinsman et al.	N/A	N/A
D784200	12/2016	Dunshee et al.	N/A	N/A
9623912	12/2016	Schlangen	N/A	N/A
D785502	12/2016	Dunshee et al.	N/A	N/A
9649928	12/2016	Danielson et al.	N/A	N/A
9713976	12/2016	Miller et al.	N/A	N/A
9725023	12/2016	Miller et al.	N/A	N/A
9776481	12/2016	Deckard et al.	N/A	N/A
9783245	12/2016	Marchlewski	N/A	B62D 27/026
9789909	12/2016	Erspamer et al.	N/A	N/A
9809102	12/2016	Sunsdahl et al.	N/A	N/A
9895946	12/2017	Schlangen et al.	N/A	N/A
9994130	12/2017	Michels et al.	N/A	N/A
10011189	12/2017	Sunsdahl et al.	N/A	N/A
10017090	12/2017	Franker et al.	N/A	N/A
10112555	12/2017	Aguilera et al.	N/A	N/A
10124709	12/2017	Bohnsack et al.	N/A	N/A
10154377	12/2017	Post et al.	N/A	N/A
10183596	12/2018	Watanabe et al.	N/A	N/A
10183605	12/2018	Weber et al.	N/A	N/A
10246153	12/2018	Deckard et al.	N/A	N/A
10369861	12/2018	Deckard et al.	N/A	N/A
10399401	12/2018	Schlangen et al.	N/A	N/A
10479290	12/2018	Simard	N/A	B60R 11/06
10486748	12/2018	Deckard et al.	N/A	N/A
10526079	12/2019	Reichert	N/A	N/A
10596924	12/2019	Sprenger	N/A	N/A
D890026	12/2019	Nightingale et al.	N/A	N/A
10864828	12/2019	Sunsdahl et al.	N/A	N/A
D906888	12/2020	Satulovsky	N/A	N/A
10926618	12/2020	Deckard et al.	N/A	N/A
10926664	12/2020	Sunsdahl et al.	N/A	N/A
10960941	12/2020	Endrizzi	N/A	N/A
11299071	12/2021	Gropp et al.	N/A	N/A
11572110	12/2022	Levin et al.	N/A	N/A
2001/0021887	12/2000	Obradovich et al.	N/A	N/A

2001/0035642	12/2000	Gotz et al.	N/A	N/A
2001/0041126	12/2000	Morin et al.	N/A	N/A
2002/0082752	12/2001	Obradovich	N/A	N/A
2002/0135175	12/2001	Schroth	N/A	N/A
2002/0172574	12/2001	McCormack et al.	N/A	N/A
2003/0015531	12/2002	Choi	N/A	N/A
2003/0057724	12/2002	Inagaki et al.	N/A	N/A
2003/0132075	12/2002	Drivers	N/A	N/A
2003/0205867	12/2002	Coelingh et al.	N/A	N/A
2004/0010383	12/2003	Lu et al.	N/A	N/A
2004/0041358	12/2003	Hrovat et al.	N/A	N/A
2004/0066091	12/2003	King	N/A	N/A
2004/0079561	12/2003	Ozawa et al.	N/A	N/A
2004/0107591	12/2003	Cuddy	N/A	N/A
2004/0108159	12/2003	Rondeau et al.	N/A	N/A
2004/0169347	12/2003	Seki	N/A	N/A
2004/0195019	12/2003	Kato et al.	N/A	N/A
2004/0221669	12/2003	Shimizu et al.	N/A	N/A
2004/0226384	12/2003	Shimizu et al.	N/A	N/A
2004/0231900	12/2003	Tanaka et al.	N/A	N/A
2005/0012421	12/2004	Fukuda et al.	N/A	N/A
2005/0045414	12/2004	Takagi et al.	N/A	N/A
2005/0057061	12/2004	McClure	296/37.2	B62D 43/10
2005/0073187	12/2004	Frank et al.	N/A	N/A
2005/0131604	12/2004	Lu	N/A	N/A
2005/0194816	12/2004	Kiester	296/182.1	B62D 33/02
2005/0231145	12/2004	Mukai et al.	N/A	N/A
2005/0235767	12/2004	Shimizu et al.	N/A	N/A
2005/0235768	12/2004	Shimizu et al.	N/A	N/A
2005/0242677	12/2004	Akutsu et al.	N/A	N/A
2005/0248173	12/2004	Bejin et al.	N/A	N/A
2005/0257989	12/2004	Iwami et al.	N/A	N/A
2005/0257990	12/2004	Shimizu	N/A	N/A
2005/0267660	12/2004	Fujiwara et al.	N/A	N/A
2006/0017301	12/2005	Edwards	N/A	N/A
2006/0022619	12/2005	Koike et al.	N/A	N/A
2006/0042862	12/2005	Saito et al.	N/A	N/A
2006/0055139	12/2005	Furumi et al.	N/A	N/A
2006/0061117	12/2005	Lester	N/A	N/A
2006/0065472	12/2005	Ogawa et al.	N/A	N/A
2006/0075840	12/2005	Saito et al.	N/A	N/A
2006/0076180	12/2005	Saito et al.	N/A	N/A
2006/0108174	12/2005	Saito et al.	N/A	N/A
2006/0131088	12/2005	Pawusch et al.	N/A	N/A
2006/0131865	12/2005	Wasek et al.	N/A	N/A
2006/0154762	12/2005	Brown	N/A	N/A
2006/0162990	12/2005	Saito et al.	N/A	N/A
2006/0169525	12/2005	Saito et al.	N/A	N/A
2006/0175124	12/2005	Saito et al.	N/A	N/A
2006/0180385	12/2005	Yanai et al.	N/A	N/A

2006/0181104	12/2005	Khan et al.	N/A	N/A
2006/0185741	12/2005	McKee	N/A	N/A
2006/0185927	12/2005	Sakamoto et al.	N/A	N/A
2006/0191734	12/2005	Kobayashi	N/A	N/A
2006/0191735	12/2005	Kobayashi	N/A	N/A
2006/0191737	12/2005	Kobayashi	N/A	N/A
2006/0191739	12/2005	Koga	N/A	N/A
2006/0196721	12/2005	Saito et al.	N/A	N/A
2006/0196722	12/2005	Makabe et al.	N/A	N/A
2006/0201270	12/2005	Kobayashi	N/A	N/A
2006/0207823	12/2005	Okada et al.	N/A	N/A
2006/0207824	12/2005	Saito et al.	N/A	N/A
2006/0207825	12/2005	Okada et al.	N/A	N/A
2006/0208564	12/2005	Yuda et al.	N/A	N/A
2006/0212200	12/2005	Yanai et al.	N/A	N/A
2006/0219463	12/2005	Seki et al.	N/A	N/A
2006/0219469	12/2005	Okada et al.	N/A	N/A
2006/0219470	12/2005	Imagawa et al.	N/A	N/A
2006/0255610	12/2005	Bejin et al.	N/A	N/A
2006/0283914	12/2005	Murase	228/101	B62D 33/00
2006/0288800	12/2005	Mukai et al.	N/A	N/A
2007/0013181	12/2006	Heck	N/A	N/A
2007/0023566	12/2006	Howard	N/A	N/A
2007/0068726	12/2006	Shimizu	N/A	N/A
2007/0074588	12/2006	Harata et al.	N/A	N/A
2007/0074589	12/2006	Harata et al.	N/A	N/A
2007/0074927	12/2006	Okada et al.	N/A	N/A
2007/0074928	12/2006	Okada et al.	N/A	N/A
2007/0095601	12/2006	Okada et al.	N/A	N/A
2007/0096449	12/2006	Okada et al.	N/A	N/A
2007/0175696	12/2006	Saito et al.	N/A	N/A
2007/0242398	12/2006	Ogawa	N/A	N/A
2007/0261904	12/2006	Fecteau et al.	N/A	N/A
2008/0023240	12/2007	Sunsdahl et al.	N/A	N/A
2008/0023249	12/2007	Sunsdahl et al.	N/A	N/A
2008/0053743	12/2007	Tomita	N/A	N/A
2008/0059034	12/2007	Lu	N/A	N/A
2008/0106115	12/2007	Hughes	N/A	N/A
2008/0143505	12/2007	Maruyama et al.	N/A	N/A
2008/0172155	12/2007	Takamatsu et al.	N/A	N/A
2008/0183353	12/2007	Post et al.	N/A	N/A
2008/0199253	12/2007	Okada et al.	N/A	N/A
2008/0296884	12/2007	Rouhana et al.	N/A	N/A
2009/0065285	12/2008	Maeda et al.	N/A	N/A
2009/0078491	12/2008	Tsutsumikoshi et al.	N/A	N/A
2009/0093928	12/2008	Getman et al.	N/A	N/A
2009/0108617	12/2008	Songwe, Jr.	N/A	N/A
2009/0152035	12/2008	Okada et al.	N/A	N/A
2009/0152036	12/2008	Okada et al.	N/A	N/A

2009/0178871	12/2008	Sunsdahl et al.	N/A	N/A
2009/0184531	12/2008	Yamamura et al.	N/A	N/A
2009/0184540	12/2008	Edwards	296/183.1	B62D 33/0273
2009/0189373	12/2008	Schramm et al.	N/A	N/A
2009/0301830	12/2008	Kinsman et al.	N/A	N/A
2009/0302590	12/2008	Van et al.	N/A	N/A
2010/0017059	12/2009	Lu et al.	N/A	N/A
2010/0066129	12/2009	Edwards	296/208	B60R 13/07
2010/0090797	12/2009	Koenig et al.	N/A	N/A
2010/0194086	12/2009	Yamamura et al.	N/A	N/A
2010/0211261	12/2009	Sasaki et al.	N/A	N/A
2010/0314191	12/2009	Deckard et al.	N/A	N/A
2011/0035089	12/2010	Hirao et al.	N/A	N/A
2011/0279282	12/2010	Bryant	N/A	N/A
2011/0297462	12/2010	Grajkowski et al.	N/A	N/A
2011/0298189	12/2010	Schneider et al.	N/A	N/A
2011/0304114	12/2010	Spanjers	N/A	N/A
2011/0309118	12/2010	Wada	N/A	N/A
2012/0029770	12/2011	Hirao et al.	N/A	N/A
2012/0078470	12/2011	Hirao et al.	N/A	N/A
2012/0085588	12/2011	Kinsman et al.	N/A	N/A
2012/0193163	12/2011	Wimpfheimer et al.	N/A	N/A
2012/0223500	12/2011	Kinsman et al.	N/A	N/A
2012/0247888	12/2011	Chikuma et al.	N/A	N/A
2013/0033070	12/2012	Kinsman et al.	N/A	N/A
2013/0041545	12/2012	Baer et al.	N/A	N/A
2013/0079988	12/2012	Hirao et al.	N/A	N/A
2013/0199097	12/2012	Spindler et al.	N/A	N/A
2013/0319785	12/2012	Spindler et al.	N/A	N/A
2013/0338869	12/2012	Tsumano	N/A	N/A
2014/0103627	12/2013	Deckard et al.	N/A	N/A
2014/0294195	12/2013	Perez et al.	N/A	N/A
2014/0358373	12/2013	Kikuchi et al.	N/A	N/A
2015/0002404	12/2014	Hooton	N/A	N/A
2015/0029018	12/2014	Bowden et al.	N/A	N/A
2015/0039199	12/2014	Kikuchi	N/A	N/A
2015/0057885	12/2014	Brady et al.	N/A	N/A
2015/0061275	12/2014	Deckard et al.	N/A	N/A
2015/0078580	12/2014	Schwerdtfeger et al.	N/A	N/A
2015/0210137	12/2014	Kinsman et al.	N/A	N/A
2015/0259011	12/2014	Deckard	280/781	B60K 13/04
2016/0059660	12/2015	Brady et al.	N/A	N/A
2016/0332553	12/2015	Miller et al.	N/A	N/A
2016/0332676	12/2015	Miller et al.	N/A	N/A
2017/0013336	12/2016	Stys et al.	N/A	N/A
2017/0036617	12/2016	Greggs	N/A	B60P 1/44
2017/0120946	12/2016	Gong et al.	N/A	N/A
2017/0131095	12/2016	Kim	N/A	N/A

2017/0199094	12/2016	Duff et al.	N/A	N/A
2017/0247062	12/2016	Vu	N/A	B60R 13/01
2017/0334500	12/2016	Jarek et al.	N/A	N/A
2018/0007466	12/2017	Hess et al.	N/A	N/A
2018/0022391	12/2017	Erspamer et al.	N/A	N/A
2018/0065465	12/2017	Ward et al.	N/A	N/A
2018/0326843	12/2017	Danielson	N/A	B60K 20/06
2018/0328321	12/2017	Toda et al.	N/A	N/A
2019/0110161	12/2018	Rentz et al.	N/A	N/A
2019/0143871	12/2018	Weber et al.	N/A	N/A
2019/0193501	12/2018	Brady et al.	N/A	N/A
2019/0210668	12/2018	Endrizzi et al.	N/A	N/A
2019/0215606	12/2018	You et al.	N/A	N/A
2019/0217909	12/2018	Deckard et al.	N/A	N/A
2019/0256010	12/2018	Baba et al.	N/A	N/A
2019/0265064	12/2018	Koenig et al.	N/A	N/A
2019/0306599	12/2018	Nagai et al.	N/A	N/A
2020/0001673	12/2019	Schlangen et al.	N/A	N/A
2020/0070709	12/2019	Weber et al.	N/A	N/A
2020/0122776	12/2019	Schlangen et al.	N/A	N/A
2020/0262285	12/2019	Sunsdahl et al.	N/A	N/A
2020/0363054	12/2019	Wilson et al.	N/A	N/A
2021/0024007	12/2020	Fredrickson et al.	N/A	N/A
2021/0070374	12/2020	Domon	N/A	B62D 25/20
2021/0206438	12/2020	Levin et al.	N/A	N/A
2022/0041115	12/2021	Fredrickson et al.	N/A	N/A
2022/0073154	12/2021	Peterson	N/A	B60N 2/305
2022/0135145	12/2021	Veillette	180/291	B62D 21/183
2022/0315115	12/2021	Lyons	N/A	B60K 11/02
2023/0150588	12/2022	Deckard et al.	N/A	N/A
2023/0339541	12/2022	Nysse	N/A	B62D 65/024
2024/0157898	12/2023	Wuollet	N/A	B62D 33/0273
2024/0174184	12/2023	Fredrickson et al.	N/A	N/A
2024/0326931	12/2023	Purcell	N/A	B62D 21/183

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2433019	12/2002	CA	N/A
2903511	12/2015	CA	N/A
1489675	12/2003	CN	N/A
1646359	12/2004	CN	N/A
201007087	12/2007	CN	N/A
202986930	12/2012	CN	N/A
104442637	12/2014	CN	N/A
104564935	12/2014	CN	N/A

104661903	12/2014	CN	N/A
104703866	12/2014	CN	N/A
204437029	12/2014	CN	N/A
204511639	12/2014	CN	N/A
105730221	12/2015	CN	N/A
107251577	12/2016	CN	N/A
107635800	12/2017	CN	N/A
108859990	12/2017	CN	N/A
2752798	12/1977	DE	N/A
3007726	12/1980	DE	N/A
102004049557	12/2005	DE	N/A
102010020544	12/2010	DE	N/A
0697306	12/1995	EP	N/A
1548298	12/2004	EP	N/A
2907410	12/2007	FR	N/A
2316923	12/1997	GB	N/A
53-101625	12/1977	JP	N/A
2000-025494	12/1999	JP	N/A
2005-193788	12/2004	JP	N/A
2006-232058	12/2005	JP	N/A
2006-232061	12/2005	JP	N/A
2006-256579	12/2005	JP	N/A
2006-256580	12/2005	JP	N/A
2006-281839	12/2005	JP	N/A
2007-106319	12/2006	JP	N/A
2010-095106	12/2009	JP	N/A
84/00524	12/1983	WO	N/A
03/41446	12/2002	WO	N/A
03/70543	12/2002	WO	N/A
2009/096998	12/2008	WO	N/A
2013/047741	12/2012	WO	N/A
2014/039432	12/2013	WO	N/A
2014/039433	12/2013	WO	N/A
2014/047488	12/2013	WO	N/A
2014/059258	12/2013	WO	N/A
2017/187413	12/2016	WO	N/A
2019/140026	12/2018	WO	N/A

OTHER PUBLICATIONS

“2020 Polaris RZR—Is this the Real Deal?” Jul. 16, 2019. Youtube. https://www.youtube.com/watch?v=8J7uX6Y4UOc. cited by applicant

“Evolution of the RZR: Which One is the Best?” Aug. 23, 2018. Youtube. https://www.youtube.com/watch?v=QE6VyxWxoow. cited by applicant

Polaris RZR XP4 1000 Launch Video—Polaris RZR Sport Side By Side ATV. Apr. 25, 2014. Youtube, https://www.youtube.com/watch?v=roncbPaRIMU. cited by applicant

2009 Honda Big Red, ATV Illustrated at http://www.atvillustrated.com/?q=node/6615/20/2008, 6 pgs. cited by applicant

2016 MUDPRO 700 Limited, Artic Cat, http://www.articcat.com/dirt/atvs/model/2016-en-mudpro-700-limited/, copyright 2015, 23 pages. cited by applicant

All-Terrain Vehicles. Design—(Copyrights) Questel) orbit.com. [Online PDF compilation of

references selected by examiner] 72 pgs. Print Dates Range Aug. 7, 2020-Mar. 18, 2019 [Retrieved Jun. 25, 2021]. cited by applicant
Arctic Cat, company website, Prowler XT 650 H1, undated, 9 pgs. cited by applicant
BRP Can-Am Commander photo, undated; 1 page. cited by applicant
Buyer's Guide Supplement, 2006 Kart Guide, Powersports Business Magazine; 6 pages. cited by applicant
Club Car, Company Website, product pages for XRT 1500 SE, undated; 2 pages. cited by applicant
DuneGuide.com, "Product Review 2009 Honda Big Red MUV," retrieved from http:www.duneguide.com/ProductReview.sub.--Honda.sub.--BigRed.htm, May 20, 2008, 3 pgs. cited by applicant
High-Performance "Truck Steering" Automotive Engineering, Society of Automotive Engineers. Warrendale, US, vol. 98. No. 4, Apr. 1, 1990, pp. 56-60. cited by applicant
Honda Hippo 1800 New Competition for Yamaha's Rhino, Dirt Wheels Magazine, Apr. 2006, pp. 91-92. cited by applicant
International Preliminary Report on Patentability issued by The International Bureau of WIPO, dated Apr. 14, 2015, for International Patent Application No. PCT/US2013/064516; 18 pages. cited by applicant
International Preliminary Report on Patentability received for PCT Patent Application No. PCT/US2019/012958, mailed on Jul. 23, 2020, 20 pages. cited by applicant
International Preliminary Report on Patentability received for PCT Patent Application No. PCT/US2020/042787, mailed on Jun. 24, 2021, 17 pages. cited by applicant
International Search Report and Written Opinion issued by the European Patent Office, dated Jan. 14, 2014, for International Patent Application No. PCT/US2013/064516; 24 pages. cited by applicant
International Search Report and Written Opinion issued by the International Searching Authority, dated Oct. 21, 2020, for International Patent Application No. PCT/US2020/42787; 18 pages. cited by applicant
International Search Report and Written Opinion received for PCT Patent Application No. PCT/US2019/012958, mailed on Jul. 3, 2019, 27 pages. cited by applicant
Kawasaki Mule The Off-Road Capable 610 4 .times. 4 XC Brochure 2011, .COPYRGT. 2010, 6 pages. cited by applicant
Kawasaki Mule Utility Vehicle Brochure 2009, .COPYRGT. 2008; 10 pages. cited by applicant
Kawasaki Teryx 750 F1 4 × 4 Sport Brochure 2011, (Copyrights) 2010; 6 pages. cited by applicant
MTX (IMTX Audio Thunder Sports RZRPod65-owners-manual, 2016); 8 pages. cited by applicant
Office Action issued by the Chinese Patent Office, dated Jun. 9, 2021, for Chinese Patent Application No. 201980007897.1; 6 pages (3 pages of English Translation and 3 pages of Original Document). cited by applicant
Outlander X mr 850, available at https://can-am.brp.com/off-road/atv/outlander/outlander-x-mr-850.html; .COPYRGT. 2003-2017; 3 pages. cited by applicant
Patent Examination Report issued by the Australian Government IP Australia, dated Apr. 7, 2016, for Australian Patent Application No. 2013329090; 3 pages. cited by applicant
Polaris Ranger Brochure 2009, copyright 2008; 32 pages. cited by applicant
Polaris Ranger Brochure ATVs and Side .times. Sides Brochure 2010, .COPYRGT. 2009, 26 pages. cited by applicant
Polaris Ranger Off-Road Utility Vehicles Brochure 2004, .COPYRGT. 2003; 20 pages. cited by applicant
Polaris Ranger RZR Brochure 2011, .COPYRGT. 2010; 16 pages. cited by applicant
Polaris Ranger Welcome to Ranger Country Brochure 2006, .COPYRGT. 2005, 24 pages. cited by applicant
Ray Sedorchuk, New for 2004, Yamaha Rhino 660 4 × 4, ATV Connection Magazine, (Copyrights)

2006; 3 pages. cited by applicant
Redline Specs, copyright 2008, available at www.RedlinePerforms.com., 2 pages. cited by applicant
Renegade X MR 1000R, Can-Am, http://can-am.brp.com/off-road/atv/renegade/renegade-x-mr-1000R.html, copyright 2003-2015, 12 pages. cited by applicant
Select Increments 2007-2018 Compatible With Jeep Wrangler JK and Unlimited With Infinity or Alpine Premium Factory Systems Pillar Pods with Kicker speakers PP0718-IA-K (Select), Dec. 14, 2018; 6 pages. cited by applicant
Work/Play Only Ranger brochure, .COPYRGT. 2007, Polaris Industries Inc., 28 pgs. cited by applicant
Yamaha, Company Website, 2006 Rhino 450 Auto 4 .times. 4, .COPYRGT. 2005, 3 pages. cited by applicant
Yamaha, Company Website, Rhino 660 Auto 4 × 4 Exploring Edition Specifications, (Copyrights) 2006; 3 pages. cited by applicant

---

Primary Examiner: Douglas; Steven O

Attorney, Agent or Firm: Merchant & Gould P.C.

Background/Summary

TECHNICAL FIELD

(1) The present disclosure relates to a cargo box assembly for a utility, recreational, or off-road vehicle.

BACKGROUND

(2) Utility, recreational, or off-road vehicles often have cargo box assemblies that are configured to store cargo. Due to spills of liquid cargo, weather elements such as rain or snow, and/or other factors, fluid may be retained within the cargo box assembly.

SUMMARY

(3) The present disclosure relates to configurations of the cargo box assembly which prevent fluid build-up therein and are configured for directing fluid flow from the cargo box.

(4) In some examples, a vehicle may include a frame supported by a plurality of ground engaging members, a powertrain supported by the frame, and a cargo bed supported by the frame. The cargo bed may include a bed floor extending between a first wall and a second wall. A drain may be coupled to a rearward portion of the cargo bed. The drain may be configured to direct fluid from the bed floor to a position rearward of the bed floor and away from at least a portion of the powertrain.

(5) In some examples, a cargo box assembly for a utility vehicle may include a cargo bed comprising a bed floor, a first wall, a second wall, as well as a tailgate, a seal, and a drain. The first wall may be sealingly coupled to a first edge of the bed floor. The second wall may be sealingly coupled to a second edge of the bed floor, such that the first edge is opposing and substantially parallel to the second edge. The tailgate may extend from a third edge of the bed floor, between the first wall and the second wall. The seal may be positioned intermediate at least a portion of the tailgate and the bed floor. Additionally, the seal may define a seal opening configured to allow fluid to pass between the bed floor and the tailgate. The drain may be coupled to the cargo bed and define a drain opening positioned vertically below the seal opening. The drain may be configured to direct the fluid away from a selected portion of the utility vehicle.

(6) In some examples, a drain assembly for a cargo box assembly may include a drain, a seal, and a

wick. The cargo box assembly may include a cargo bed having a cargo bed width and a tailgate coupled to a rearward portion of the cargo bed. The drain of the drain assembly may be coupled to a rearward portion of the cargo bed along a drain width. Also, the drain may define a drain opening directed generally downwardly. The seal may be positioned intermediate the cargo bed and the tailgate, and define a seal opening fluidly coupled to the drain. The wick may be coupled to a bottom of the tailgate and configured to direct fluid from the tailgate toward the drain.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. **1** is a front left perspective view of a vehicle of the present disclosure;

(2) FIG. **2** is a rear right perspective view of the vehicle of FIG. **1**;

(3) FIG. **3** is an exploded view of a portion of a cargo box assembly of the vehicle of FIG. **1**;

(4) FIG. **4** is a perspective view of a drain of a drain assembly of the cargo box assembly of FIG. **3**;

(5) FIG. **5** is a top view of a cargo bed of the cargo box assembly of FIG. **3** without a tailgate of the cargo box assembly;

(6) FIG. **6** is an exploded view of the drain assembly of FIG. **4** coupled to the cargo box assembly;

(7) FIG. **7** is an exploded view of a wick of the drain assembly of the cargo box assembly of FIG. **3**;

(8) FIG. **8** is a cross-sectional view of the cargo box assembly of the vehicle of FIG. **1**, taken along line **8**-**8** of FIG. **5** illustrating an exemplary fluid path with the tailgate in a closed position; and

(9) FIG. **9** is a cross-sectional view of the cargo box assembly of the vehicle of FIG. **1**, taken along line **8**-**8** of FIG. **5** illustrating an exemplary fluid path with the tailgate in an open position.

DETAILED DESCRIPTION

(10) For the purposes of promoting an understanding of the principles of the present disclosure, reference is now made to the embodiments illustrated in the drawings, which are described below. The embodiments disclosed below are not intended to be exhaustive or limit the present disclosure to the precise form disclosed in the following detailed description. Rather, the embodiments are chosen and described so that others skilled in the art may utilize their teachings. Therefore, no limitation of the scope of the present disclosure is thereby intended. Corresponding reference characters indicate corresponding parts throughout the several views.

(11) The terms “couples”, “coupled”, “coupler”, and variations thereof are used to include both arrangements wherein two or more components are in direct physical contact and arrangements wherein the two or more components are not in direct contact with each other (e.g., the components are “coupled” via at least a third component, but still cooperates or interact with each other).

(12) In some instances throughout this disclosure and in the claims, numeric terminology, such as first, second, third, and fourth, is used in reference to various operative transmission components and other components and features. Such use is not intended to denote an ordering of the components. Rather, numeric terminology is used to assist the reader in identifying the component being referenced and should not be narrowly interpreted as providing a specific order of components.

(13) The present disclosure describes cargo box assemblies of utility vehicles that are configured to reduce fluid build-up in the cargo box, direct fluid flow from the cargo box toward a selected location, or both. For example, the described cargo box assemblies may direct fluid away from hot components of a utility vehicle. In some examples, the cargo box assemblies may include a drain assembly configured to channel fluid from within a cargo bed, a seal configured to control fluid flow between a tailgate and the cargo bed, and a wick configured to direct fluid from the tailgate toward the drain. By controlling the flow of fluid from the cargo box, the described cargo box assemblies may improve useable life of selected components, and prevent fluids from being

directed, directly or indirectly, towards hot components of the vehicle.
(14) FIGS. **1** and **2** are conceptual diagrams illustrating an example vehicle **2**. Vehicle **2** includes a plurality of ground engaging members, such as, for example a pair of front ground engaging members **3** and a pair of rear ground engaging members **4**. As illustrated in FIGS. **1** and **2**, front ground engaging members **3** and rear ground engaging members **4** are wheels. In other examples, any of front ground engaging members **3** or rear ground engaging members **4** may be wheels, tracks, skis, or other types of ground engaging members. Vehicle **2** also includes a frame **5** supported by ground engaging members **3** and **4**. Frame **5** may include a plurality of frame portions, such as, for example, a lower frame assembly and an upper frame assembly. An operator area **11** may be defined by frame **5**, e.g., portions of the upper and lower frame assemblies, and may further be configured to support an operator and possibly at least one passenger, as well as a variety of operator inputs. Example operator inputs include a steering input such as a steering wheel or a handlebar, a throttle control such as an accelerator pedal or a throttle input, a brake control such as a brake pedal or a brake lever, a clutch control, a transmission or gear shifting control, or other input devices configured to control an operation of vehicle **2**. Further, vehicle **2** also may include a skid plate **18** configured to protect and surround at least a portion of frame **5**. Skid plate **18** may be a single piece or a plurality of pieces.
(15) As illustrated in FIGS. **1** and **2**, vehicle **2** includes a front suspension **8** coupled between frame **5** and front ground engaging members **3** and a rear suspension **10** coupled between frame **5** and rear ground engaging members **4**. Front suspension **8** may be a dual A-arm suspension. In other examples, front suspension **8** may be a strut-style suspension or another type of suspension. Rear suspension **10** may be a strut style suspension. In various embodiments, rear suspension **10** may be a dual A-arm suspension, a trailing arm suspension, a swingarm suspension, or another type of suspension. Although illustrated as including a dual A-arm front suspension and a strut style rear suspension, in other example, vehicle **2** may include any front or rear suspension suitable for the operation over in a particular terrain.
(16) Vehicle **2** includes a body **12** supported by frame **5**. Body **12** includes a pair of front doors **13** and a pair of rear doors **14**. In various embodiments, front doors **13** and rear doors **14** are not required. Body **12** also includes a hood **15** positioned generally adjacent front fenders or side panels. In some examples, a windshield **16** may be positioned forwardly of operator area **11** and configured to reduce intrusion of dust, debris, and water into operator area **11**. Body **12** also may include a roof **17** supported by an upper portion of frame **5** and positioned above operator area **11**. Body **12** may include a utility or cargo box assembly **20** positioned rearward of operator area **11** and generally above at least a portion of rear suspension **10**.
(17) Vehicle **2** also includes a powertrain **25** supported by frame **5** and, in at least one embodiment, positioned generally beneath cargo box assembly **20**. Powertrain **25** may include an internal combustion engine (not shown), a hybrid powertrain, or an electric powertrain. In various embodiments of powertrain **25**, an intake assembly (not shown) and an exhaust assembly (not shown) may be fluidly coupled to the engine. The exhaust assembly may include at least one hot component, such as exhaust conduit **26**, and an exhaust shield, such as cover **26**A. In various embodiments, cover **26**A may be positioned over at least a portion of exhaust conduit **26** and configured to provide thermal insulation between the portion of exhaust conduit **26** and vehicle **2**, or an operator of vehicle **2** or cargo box assembly **20**.
(18) Additional details regarding vehicle **2** can be found in U.S. application Ser. No. 17/708,327, filed Mar. 30, 2022, titled OFF-ROAD VEHICLE, the entire disclosure of which is expressly incorporated by reference herein.
(19) As illustrated in FIGS. **1** and **2**, cargo box assembly **20** includes a utility bed, or cargo bed **20**A and a tailgate or rear wall **20**B. Cargo bed **20**A is defined by a first side wall **31**, a second side wall **32**, and a cargo bed floor **33**. First side wall **31** and second side wall **32** extend generally longitudinally and may be parallel to a vehicle centerline **22**. First side wall **31** and second side

wall **32** are spaced apart from one another and coupled together by cargo bed floor **33**. In the present embodiment, first side wall **31** and second side wall **32** are spaced by a cargo bed floor width **33**A (FIG. **5**). A front wall (not shown) is coupled to cargo bed floor **33**, first side wall **31**, and second side wall **32**. In the present embodiment, the interfaces between first side wall **31**, second side wall **32**, front wall, and cargo bed floor **33** are sealed. The term seal may include a joint between two or more surfaces or components that is configured to reduce or prevent selected material, such as solid debris, water, liquid fuel, or the like, from passing between the two or more surfaces or components. In the present embodiment, tailgate **20**B is configured to be coupled to cargo bed **20**A and is illustratively configured to rotate between a closed position (i.e., shown in FIGS. **1** and **2**, tailgate **20**B is positioned generally perpendicular to cargo bed floor **33**) and an open position (i.e., tailgate **20**B is generally parallel to cargo bed floor **33**).

(20) FIG. **3** is a conceptual diagram illustrating a partially exploded view of cargo box assembly **20**. As illustrated in FIG. **3**, a seal **70** is coupled to cargo bed **20**A to seal at least a portion of the interface between cargo bed **20**A and tailgate **20**B. In one embodiment, tailgate **20**B is configured as a stationary rear wall and does not rotate between open and closed positions.

(21) In the present embodiment, tailgate **20**B further includes a latch, or handle **34** (FIG. **2**) configured to actuate a latch assembly (not shown) to allow tailgate **20**B to rotate between the open position and the closed position. Cargo box assembly **20** also has a left taillight **35**L and a right taillight **35**R. In various embodiments, left taillight **35**L and right taillight **35**R may be on cargo bed **20**A, tailgate **20**B, or on each of cargo bed **20**A and tailgate **20**B.

(22) In some examples, cargo box assembly **20** may be configured to rotate relative to frame **5**. For example, a box bottom **30** of cargo box assembly **20** may be rotatably coupled to frame **5** such that cargo box assembly **20** is configured to rotate about box rotation axis **21**. In the present embodiment, box rotation axis **21** is positioned vertically above at least a portion of powertrain **25**. For example, in various embodiments, box rotation axis **21** is positioned vertically above and vertically aligned with a portion of exhaust conduits **26** or cover **26**A. In various embodiments, box rotation axis **21** is positioned vertically above exhaust conduits **26** or cover **26**A on or near a plane extending vertically from a rear most portion of exhaust conduits **26** or cover **26**A.

(23) Referring now to FIGS. **3-7**, cargo box assembly **20** includes a drain assembly **75** configured to direct fluid within, or passing through, cargo bed **20**A toward one or more selected locations. Drain assembly **75** may include a drain **50** and a wick **40**. Referring to FIG. **3**, drain **50** is coupled to a portion of cargo box bottom **30** (e.g., a lower surface of cargo bed floor **33**). In this way, drain **50** is generally positioned lower than a cargo, or uppermost surface, of cargo bed floor **33**. In the present embodiment, wick **40** is coupled to a bottom extent **23** of tailgate **20**B.

(24) Drain **50** may include one or more drain channels configured to direct material toward a selected location. For example, referring to FIG. **4**, drain **50** includes a first drain **51**A and a second drain **51**B. Illustratively, first drain **51**A comprises a first trough **56**A and a first flange **52**A. Illustratively, first flange **52**A is configured to retain fluid that flows within first trough **56**A. Additionally, second drain **51**B comprises a second trough **56**B and a second flange **52**B. Illustratively, second flange **52**B is configured to retain fluid that flows within second trough **56**B. Each of first drain **51**A and second drain **51**B are angled downwardly toward a middle or center portion **51**C of drain **50**. An opening **54** is positioned in center portion **51**C (e.g., a drain middle portion of drain **50**) intermediate first drain **51**A and second drain **51**B. Illustratively, opening **54** is positioned at or defines a bottom extent of drain **50**. In other words, first drain **51**A and second drain **51**B are angled towards each other and converge or otherwise meet at center portion **51**C.

(25) In the present embodiment, each of first drain **51**A and second drain **51**B are angled downwardly, from a lateral outer extent, toward center portion **51**C at an angle **55** relative to a substantially horizontal plane of vehicle **2**. In the present embodiment, angle **55** is approximately two degrees. In various embodiments, angle **55** may be within a range from about one degree to about 30-degrees, such as about two degrees to about 15-degrees.

(26) Still referring to FIG. **4**, drain **50** comprises a drain wall **58** extending generally vertically and laterally. Drain wall **58** may define a plurality of bosses or indents **58**A which may strengthen drain wall **58**. Drain wall **58** partially defines first drain **51**A and second drain **51**B and extends continuously therebetween. In this way, first drain **51**A may be generally defined by a portion of drain wall **58** and flange **52**A while second drain may be generally defined by a portion of drain wall **58** and flange **52**B. A flange **53** may be coupled to or integrally formed with drain wall **58**. Flange **53** may include a plurality of apertures **53**A configured to receive a fastener **59** (FIG. **6**). In the present embodiment, drain **50** has a drain width **50**A and a drain height **50**B. In the present embodiment, drain width **50**A is greater than a cargo bed floor width **33**A. In various embodiments, drain width **50**A is less than cargo bed floor width **33**A. For example, drain width **50**A may be less than cargo bed floor width **33**A and greater than a width of at least one of exhaust conduit **26** and/or cover **26**A. In various embodiments, drain width **50**A is greater than about fifty-percent of cargo bed floor width **33**A. In various embodiments, drain width **50**A is greater than about seventy-five percent of cargo bed floor width **33**A. In various embodiments, drain width **50**A is greater than about twenty-five percent of cargo bed floor width **33**A.

(27) Now referring to FIG. **5**, cargo bed floor **33** includes a plurality of longitudinal channels **36**A and at least one horizontal channel **36**B. Illustratively, horizontal channel **36**B extends continuously and entirely along a rear extent of cargo bed floor **33** and is generally adjacent drain **50** and/or tailgate **20**B. In the present embodiment, longitudinal channels **36**A are configured to direct fluid within cargo bed **20**A toward a rear of cargo bed **20**A into the at least one horizontal channel **36**B.

(28) An extension or flange **37** is positioned rearwardly of the at least one horizontal channel **36**B and extends generally upwardly from cargo bed floor **33**. In the present embodiment, extension **37** includes a first extension portion **37**A and second extension portion **37**B separated by an extension opening **38**. Illustratively, extension opening **38** is positioned along the vehicle centerline **22**. In the present embodiment, extension **37** extends upwardly about one-half inch. In other examples, extension **37** may extend upwardly about one-quarter inch, about one inch, or another height. In various embodiments, extension **37** is a greater height than the remaining portions of cargo bed floor **33**. In some examples, the height of extension **37** may be based on a total volume defined by the height of extension **37** and the area of cargo bed floor **33**. For example, height of extension **37** may be selected such that the total volume is greater than one gallon, such as greater than 5 gallons or greater than ten gallons.

(29) In some examples, seal **70** includes a first seal portion **70**A and a second seal portion **70**B positioned adjacent first extension portion **37**A and second extension portion **37**B, respectively. First seal portion **70**A and second seal portion **70**B are configured to separate cargo bed floor **33** from tailgate **20**B and seal the space therebetween. First seal portion **70**A also extends upwardly to separate tailgate **20**B and first side wall **31** and second seal portion **70**B extends upwardly to separate tailgate **20**B and second side wall **32**. First seal portion **70**A and second seal portion **70**B are separated by a seal opening **71**. Illustratively, seal **70** is positioned adjacent extension **37**. Further, in the present embodiment, seal opening **71** is aligned with opening **38**. Referring to FIG. **6**, each of seal **70**A and seal **70**B are shaped as a right-angle and configured to extend along a rearward edge of cargo bed floor **33**. Further, seal **70**A is configured to extend along a rearward edge of first side wall **31** and seal **70**B is configured to extend along a rearward edge of second side wall **32**.

(30) As illustrated in FIG. **5**, each of extension opening **38**, seal opening **71**, and opening **54** are at least partially longitudinally aligned, thereby generally forming a fluid channel. In various embodiments, any of extension opening **38**, seal opening **71** and opening **54** are at least partially laterally aligned. Cargo box assembly **20** is configured such that at least a portion of fluid within cargo box assembly **20** is directed through one or more channels **36**A and into channel **36**B, and each of first extension portion **37**A and second extension portion **37**B are configured to prevent or minimize fluid from flowing onto, and stagnating on, seal **70**. That is, extension **37** extends

vertically higher from cargo bed floor **33** than seal **70**, thereby reducing the flow of fluid within cargo box assembly **20** onto seal **70** relative to a configuration in which extensions do not extend vertically higher from a cargo bed floor than a seal. Fluid that stagnates on seal **70** may reduce the useful life of seal **70**, or otherwise at least partially reduce a functionality of seal **70**.

(31) In various embodiments, each of channels **36**A and channels **36**B are angled relative to a horizontal plane of vehicle **2** to direct water towards extension opening **38**. That is, as illustrated in FIGS. **5** and **8**-**9**, channels **36**A are angled downwardly towards the rear of cargo box assembly **20**, towards tailgate **20**B. Further, channels **36**B are angled downwardly towards the center of cargo box assembly **20**, towards vehicle centerline **22**. Cargo bed floor **33** of cargo box assembly **20** is configured to direct fluid flow through channels **36**A into channels **36**B, and ultimately towards a rearmost and laterally center point of cargo bed floor **33**, toward extension opening **38**. In various embodiments, cargo bed floor **33** is configured to direct fluid to a rearmost point of cargo bed floor **33** that is laterally offset from vehicle centerline **22**.

(32) In the present embodiment, cargo bed floor **33** is configured to direct fluid from within cargo box assembly **20** towards extension opening **38**, through seal opening **71**, and into drain assembly **75**. Fluid that flows through extension opening **38** and seal opening **71** will be directed toward opening **54**. In the event that fluid within cargo bed **20**A flows over first extension portion **37**A or second extension portion **37**B, and in the event seal **70** is imperfect and allows fluid to flow between cargo bed **20**A and tailgate **20**B, fluid will flow into first trough **56**A and second trough **56**B, and out of drain **50** through opening **54**.

(33) Referring to FIG. **6**, box bottom **30** includes a box bottom body **30**B and a box bottom cover **30**A. In the present embodiment, bottom cover **30**A is a heat shield configured to separate and at least partially thermally insulate bottom body **30**B from powertrain **25**. In the present embodiment, box bottom cover **30**A defines a bottom extent of cargo bed **20**A. Illustratively, drain **50** is coupled between box bottom body **30**B and box bottom cover **30**A. A gasket **57** is positioned vertically between bottom body **30**B and drain **50** to prevent fluid from flowing backward along box bottom body **30**B between drain **50** and box bottom body **30**B. Gasket **57** is configured to prevent fluid from flowing along box bottom body **30**B between box bottom body **30**B and flange **53**. Illustratively, gasket **57** defines a plurality of mounting holes **57**A, box bottom cover **30**A defines a plurality of apertures **30**C generally aligned with holes **57**A, and box bottom body **30**B defines a plurality of apertures **30**D generally aligned with holes **57**A and apertures **30**C. A plurality of fasteners extend through mounting holes **57**A, apertures **30**C, apertures **53**A, and apertures **30**D to couple each of drain **50**, box bottom cover **30**A and gasket **57** to box bottom body **30**B.

(34) Referring now to FIG. **7**, wick **40** is coupled to the bottom extent of tailgate **20**B. Wick **40** defines a plurality of apertures **41** configured to receive a plurality of fasteners **44** to couple wick **40** to tailgate **20**B. Wick **40** also includes a first extension **42** and a second extension **43**. First extension **42** extends along a forward side of wick **40** and second extension **43** extends along a rearward side of wick **40**. As illustrated in FIG. **8**, wick **40** is positioned vertically higher than a bottom extent of drain **50**. That is, wick **40** is spaced from opening **54** of drain **50**. Further, wick **40** has a wick width **45** (FIG. **7**) that is less than or equal to drain width **50**A (FIG. **5**). Each of first extension **42** and second extension **43** are configured to wick fluid toward drain **50** whether tailgate **20**B is in a closed or up position or an open or down position.

(35) Referring now to FIG. **8**, the operation of cargo bed floor **33** and drain assembly **75** is provided. Fluid is configured to flow within longitudinal channels **36**A and horizontal channel **36**B, according to the arrows **39**A, **39**B which show the direction of fluid flow. Seal **70** is protected from fluid stagnation by extension **37** extending upwardly from cargo bed floor **33**. Fluid is configured to flow through extension opening **38** and seal opening **71**, between cargo bed floor **33** and tailgate **20**B into drain assembly **75**. When fluid flows into drain assembly **75**, fluid is configured to flow downwardly out of drain opening **54**. In the present embodiment, drain opening **54** is positioned vertically lower than box bottom **30**.

(36) As illustrated in FIG. **8**, fluid may flow through extension opening **38** and seal opening **71** and contact tailgate **20**B before flowing into drain **50**. Fluid that flows down tailgate **20**B contacts first extension **42** of wick **40** to direct fluid downwardly into drain **50**. Wick **40** is configured to prevent fluid from flowing rearwardly, along a bottom edge of tailgate **20**B due to the capillary effect, wherein fluid would flow further rearward and flow downwardly, outside of drain **50**. First extension **42** of wick **40** ensures that fluid that flows down tailgate **20**B falls into drain **50**.
(37) Still referring to FIG. **8**, tailgate **20**B is shown in the closed position. As previously described, when tailgate **20**B is in the closed position, first extension **42** of wick **40** acts as the wicking member for fluid flowing down tailgate **20**B. Referring to FIG. **9**, tailgate **20**B is shown in the open position. When fluid flows through extension opening **38** and seal opening **71** when tailgate **20**B is in the open position, fluid flows by a bottom extent of tailgate **20**B, along wick **40**. Fluid flows down wick **40** onto second extension **43**, and thereby flows into drain **50**.
(38) As illustrated in FIG. **2**, opening **54** is positioned vertically above cover **26**A such that fluid is configured to flow onto cover **26**A. Drain **50** is configured to direct the flow of fluid onto cover **26**A. That is, drain **50** is configured to direct fluid toward a designated area that is thermally cooler than at least some of the surrounding areas. In various embodiments, drain **50** is configured with opening **54** positioned rearwardly of cover **26**A such that drain **50** directs fluid flow downward at a position rearward of any components of powertrain **25**.
(39) Further, because wick width **45** is less than or equal to that of the width of drain width **50**A, any fluid that flows onto first extension **42** of wick **40** is configured to fall into drain **50**.
(40) The following clauses illustrate example subject matter described herein.
(41) Clause 1. A vehicle, comprising: a plurality of ground engaging members and a frame supported by the plurality of ground engaging members; a powertrain supported by the frame; a cargo bed supported by the frame, the cargo bed comprising a bed floor extending between a first wall and a second wall; and a drain coupled to a rearward portion of the cargo bed, the drain configured to direct fluid from the bed floor to a position rearward of the bed floor and away from at least a portion of the powertrain.
(42) Clause 2. The vehicle of clause 1, further comprising a cover configured to conceal a portion of the powertrain, and the drain is configured to direct fluid toward the cover.
(43) Clause 3. The vehicle of clause 1 or 2, wherein the cargo bed further comprises a tailgate coupled to the rearward portion of the cargo bed; and a wick extending laterally along at least a portion of a bottom extent of the tailgate, the wick positioned vertically higher than a bottom extent of the drain, wherein the wick is configured to direct fluid toward the drain.
(44) Clause 4. The vehicle of any of clauses 1 through 3, wherein the drain is configured to extend a lateral width of the bed floor and at least a portion of the drain is sloped downwardly from a lateral outward extent toward a drain center portion.
(45) Clause 5. The vehicle of clause 1, further comprising a tailgate coupled to a rearward portion of the cargo bed, and the cargo bed further comprising a seal positioned between the tailgate and the bed floor, the seal having a seal opening fluidly coupled to the drain.
(46) Clause 6. The vehicle of clause 5, wherein the cargo bed further comprises a flange positioned adjacent the seal, the flange extending generally upwardly from the bed floor and having a flange opening at least partially laterally aligned with the seal opening.
(47) Clause 7. A cargo box assembly for a utility vehicle, the cargo box assembly comprising: a bed floor comprising a bed floor, a first wall sealingly coupled to a first edge of the bed floor, and a second wall sealing coupled to a second edge of the bed floor, wherein the first edge is opposing and substantially parallel to the second edge; a tailgate extending from a third edge of the bed floor, between the first wall and the second wall; a seal positioned intermediate at least a portion of the tailgate and the bed floor, the seal defining a seal opening configured to allow fluid to pass between the bed floor and the tailgate; and a drain coupled to the cargo bed, the drain defining a drain opening positioned vertically below the seal opening and configured to direct the fluid away from a

selected portion of the utility vehicle.
(48) Clause 8. The cargo box assembly of clause 7, wherein the tailgate is configured to rotate relative to the bed floor, the cargo box assembly further comprising a wick coupled to a bottom extent of the tailgate.
(49) Clause 9. The cargo box assembly of any of clauses 7 or 8, wherein the drain opening is positioned rearward of the bed floor.
(50) Clause 10. The cargo box assembly of any of clauses 7 through 9, wherein the cargo box assembly has a bottom extent, and the drain opening is positioned lower than the bottom extent.
(51) Clause 11. The cargo box assembly of any of clauses 7 through 10, wherein the drain is angled downwardly from a lateral outer extent toward the drain opening.
(52) Clause 12. The cargo box assembly of any of clauses 7 through 11, further comprising an extension extending upwardly from the bed floor, the extension positioned adjacent the seal, and the extension defining an extension opening at least partially aligned with the seal opening.
(53) Clause 13. A drain assembly for a cargo box assembly having a cargo bed with a cargo bed width and a tailgate coupled to a rearward portion of the cargo bed, the drain assembly comprising: a drain coupled to a rearward portion of the cargo bed, wherein the drain defines a drain opening directed generally downwardly, the drain having a drain width; a seal positioned intermediate the cargo bed and the tailgate, wherein the seal defines a seal opening fluidly coupled to the drain; and a wick coupled to a bottom of the tailgate, the wick configured to direct fluid from the tailgate toward the drain.
(54) Clause 14. The drain assembly of clause 13, wherein the drain width is at least one-half the cargo bed width.
(55) Clause 15. The drain assembly of any of clauses 13 or 14, wherein the seal opening is positioned vertically above the drain opening.
(56) Clause 16. The drain assembly of any of clauses 13 through 15, wherein the wick comprises a wick width, and the wick width is less than or equal to the drain width.
(57) Clause 17. The drain assembly of any of clauses 13 through 16, further comprising a flange positioned adjacent the seal, wherein the flange extends upwardly from the cargo bed.
(58) Clause 18. The drain assembly of clause 17, wherein the flange comprises a flange opening, and wherein the flange opening is at least partially laterally aligned with the seal opening.
(59) Clause 19. The drain assembly of any of clauses 13 through 18, wherein the drain is angled downwardly from a laterally outer portion to a laterally inner portion.
(60) Clause 20. The drain assembly of any of clauses 13 through 19, wherein the drain comprises an integral flange configured to couple to a box bottom of the cargo bed.
(61) While this invention has been described as having an exemplary design, the present invention may be further modified within the spirit and scope of this disclosure. This application is therefore intended to cover any variations, uses, or adaptations of the invention using its general principles. Further, this application is intended to cover such departures from the present disclosure as come within known or customary practice in the art to which this invention pertains.

Claims

1. A vehicle, comprising: a plurality of ground engaging members and a frame supported by the plurality of ground engaging members; a powertrain supported by the frame; a cargo bed supported by the frame, the cargo bed comprising a bed floor extending between a first wall and a second wall; and a drain coupled to a rearward portion of the cargo bed, the drain configured to direct fluid from the bed floor to a position rearward of the bed floor and away from at least a portion of the powertrain, wherein at least a portion of the drain is sloped downwardly from a lateral outward extent toward a drain center portion.
2. The vehicle of claim 1, further comprising a cover configured to conceal a portion of the

powertrain, wherein the drain is configured to direct fluid toward the cover.
3. The vehicle of claim 1, wherein the cargo bed further comprises a tailgate coupled to the rearward portion of the cargo bed; and a wick extending laterally along at least a portion of a bottom extent of the tailgate, the wick positioned vertically higher than a bottom extent of the drain, wherein the wick is configured to direct fluid toward the drain.
4. The vehicle of claim 1, wherein the drain is configured to extend a lateral width of the bed floor.
5. The vehicle of claim 1, further comprising a tailgate coupled to the rearward portion of the cargo bed, and the cargo bed further comprising a seal positioned between the tailgate and the bed floor, the seal having a seal opening fluidly coupled to the drain.
6. The vehicle of claim 5, wherein the cargo bed further comprises a flange positioned adjacent the seal, the flange extending generally upwardly from the bed floor and having a flange opening at least partially laterally aligned with the seal opening.
7. A cargo box assembly for a utility vehicle, the cargo box assembly comprising: a cargo bed comprising a bed floor, a first wall sealingly coupled to a first edge of the bed floor, and a second wall sealingly coupled to a second edge of the bed floor, wherein the first edge is opposing and substantially parallel to the second edge; a tailgate extending from a third edge of the bed floor, between the first wall and the second wall; a seal positioned intermediate at least a portion of the tailgate and the bed floor, the seal defining a seal opening configured to allow fluid to pass between the bed floor and the tailgate; and a drain coupled to the cargo bed, the drain defining a drain opening positioned vertically below the seal opening and configured to direct the fluid away from a selected portion of the utility vehicle.
8. The cargo box assembly of claim 7, wherein the tailgate is configured to rotate relative to the bed floor, the cargo box assembly further comprising a wick coupled to a bottom extent of the tailgate.
9. The cargo box assembly of claim 7, wherein the drain opening is positioned rearward of the bed floor.
10. The cargo box assembly of claim 7, wherein the cargo box assembly has a bottom extent, and the drain opening is positioned lower than the bottom extent.
11. The cargo box assembly of claim 7, wherein the drain is angled downwardly from a lateral outer extent toward the drain opening.
12. The cargo box assembly of claim 7, further comprising an extension extending upwardly from the bed floor, the extension positioned adjacent the seal, and the extension defining an extension opening at least partially aligned with the seal opening.
13. A drain assembly for a cargo box assembly having a cargo bed with a cargo bed width and a tailgate coupled to a rearward portion of the cargo bed, the drain assembly comprising: a drain coupled to a rearward portion of the cargo bed, wherein the drain defines a drain opening directed generally downwardly, the drain having a drain width; a seal positioned intermediate the cargo bed and the tailgate, wherein the seal defines a seal opening fluidly coupled to the drain; and a wick coupled to a bottom of the tailgate, the wick configured to direct fluid from the tailgate toward the drain.
14. The drain assembly of claim 13, wherein the drain width is at least one-half the cargo bed width.
15. The drain assembly of claim 13, wherein the seal opening is positioned vertically above the drain opening.
16. The drain assembly of claim 13, wherein the wick comprises a wick width, and the wick width is less than or equal to the drain width.
17. The drain assembly of claim 13, further comprising a flange positioned adjacent the seal, wherein the flange extends upwardly from the cargo bed.
18. The drain assembly of claim 17, wherein the flange comprises a flange opening, and wherein the flange opening is at least partially laterally aligned with the seal opening.
19. The drain assembly of claim 13, wherein the drain is angled downwardly from a laterally outer

portion to a laterally inner portion.
20. The drain assembly of claim 13, wherein the drain comprises an integral flange configured to couple the drain to a box bottom of the cargo bed.