

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250265801

Kind Code

A1

Publication Date

August 21, 2025

Inventor(s)

Sharma; Ambuj et al.

SYSTEM AND METHOD FOR DETERMINING PERSONAL PROTECTIVE EQUIPMENT COMFORT

Abstract

A method for determining personal protective equipment (PPE) comfort for an individual wearer includes defining a first anatomical shape data representative of an anatomical area of the individual wearer prior to donning a PPE, a second anatomical shape data representative of the anatomical area of the individual wearer after donning the PPE, and comparing the first anatomical shape data with the second anatomical shape data. The method further includes determining a soft skin tissue deformation at a plurality of predetermined anatomical positions based on the comparison between the first anatomical shape data and the second anatomical shape data, and determining a displacement comfort threshold (CT.sub.d) value based on the soft skin tissue deformation. The method also includes determining a pressure pain threshold (PPT) value, and determining a comfort metric based on the PPT values and the CT.sub.d values. The method also includes generating a notification corresponding to the comfort metric.

Inventors: Sharma; Ambuj (Woodbury, MN), Donoghue; Claire R. (Twyford, GB), Gamble; Stephen R. (Bishop Auckland, GB), Long; Andrew W. (Woodbury, MN), McCool; Christine L. (St. Paul, MN), Meree; Caitlin E. (St. Paul, MN), Urban; Henning T. (Kuehlungsborn, DE), Viner; Andrew S. (St. Paul, MN), Webb; Richard C. (St. Paul, MN), Ylitalo; Caroline M. (Stillwater, MN)

Applicant: 3M INNOVATIVE PROPERTIES COMPANY (N/A, N/A)

Family ID: 1000008574816

Appl. No.: 19/199593

Filed: May 06, 2025

Related U.S. Application Data

parent US continuation 18007213 20230127 parent-grant-document US 12307619 WO
continuation PCT/IB2021/056865 20210728 child US 19199593

Publication Classification

Int. Cl.: G06T19/20 (20110101)

U.S. Cl.:

CPC G06T19/20 (20130101); G06T2219/2021 (20130101)

Background/Summary

TECHNICAL FIELD

[0001] The present disclosure relates generally to a personal protective equipment (PPE), and in particular, to a system and a method for determining PPE comfort for an individual wearer.

BACKGROUND

[0002] Personal protective equipment (PPE), such as respirators, are widely used for respiratory protection by users. In some applications, users may wear the PPE for several hours a day. A goal for the PPE is provision of efficient sealing without causing discomfort. A poor scaling and/or poor fit of the PPE may hamper an effectiveness of the PPE resulting in leakage and a possibility of contaminant inhalation, which is not desirable. Thus, a good PPE fit is important to ensure the user is well protected against gases and particulates.

[0003] In some cases, users may have to try different types and sizes of the PPE that provides efficient sealing as well as comfort, which may be time consuming. Further, in some situations, the users may not be able to judge whether a particular type and/or size of the PPE provides efficient sealing. Moreover, the users may not wear the PPE as intended, which may either cause inefficient sealing and/or discomfort. Further, the user may feel discomfort when the skin deforms due to applied pressure by the PPE.

[0004] Currently, there are no methods available that quantify the PPE comfort by addressing a discomfort factor. Some amount of pressure may be required for secure fitting of the PPE, however, any excess pressure may cause discomfort to the user. In some cases, high pressures may be felt by the users due to an inadequate design of the PPE. Conventional methods and systems to determine PPE fit and comfort typically use facial shape data of the users. There is a need for an improved system and method that allows determination of PPE comfort on different users that solves one or more of the aforementioned challenges.

SUMMARY

[0005] In a first aspect, the present disclosure provides a method for determining personal protective equipment (PPE) comfort for an individual wearer. The method includes defining a first anatomical shape data representative of an anatomical area of the individual wearer prior to donning a PPE. The method also includes defining a second anatomical shape data representative of the anatomical area of the individual wearer after donning the PPE. The method further includes comparing the first anatomical shape data with the second anatomical shape data. The method includes determining a soft skin tissue deformation at a plurality of predetermined anatomical positions based on the comparison between the first anatomical shape data and the second anatomical shape data. The method also includes determining a displacement comfort threshold (CT.sub.d) value based on the soft skin tissue deformation at the plurality of predetermined anatomical positions. The method further includes determining a pressure pain threshold (PPT) value at the plurality of predetermined anatomical positions. The method further includes

determining a comfort metric based on the PPT values and the CT.sub.d values. The method also includes generating a notification corresponding to the comfort metric.

[0006] In a second aspect, the present disclosure provides a system for determining PPE comfort for an individual wearer. The system includes a processor configured to define a first anatomical shape data representative of an anatomical area of the individual wearer prior to donning a PPE. The processor is also configured to define a second anatomical shape data representative of the anatomical area of the individual wearer after donning the PPE. The processor is further configured to compare the first anatomical shape data with the second anatomical shape data. The processor is configured to determine a soft skin tissue deformation at a plurality of predetermined anatomical positions based on the comparison between the first anatomical shape data and the second anatomical shape data. The processor is also configured to determine a CT.sub.d value based on the soft skin tissue deformation at the plurality of predetermined anatomical positions. The processor is further configured to determine a PPT value at the plurality of predetermined anatomical positions. The processor is further configured to determine a comfort metric based on the PPT values and the CT.sub.d values. The system also includes an output module communicably coupled with the processor. The output module is configured to provide a notification corresponding to the comfort metric received from the processor thereon.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0007] Exemplary embodiments disclosed herein may be more completely understood in consideration of the following detailed description in connection with the following figures. The figures are not necessarily drawn to scale. Like numbers used in the figures refer to like components. However, it will be understood that the use of a number to refer to a component in a given figure is not intended to limit the component in another figure labeled with the same number.

[0008] FIG. 1 is a block diagram of a system for determining personal protective equipment (PPE) comfort for an individual wearer, according to an embodiment of the present disclosure;

[0009] FIGS. 2A and 2B illustrate an exemplary face of the individual wearer on which the PPE will be donned, according to an embodiment of the present disclosure;

[0010] FIG. 3 is an exemplary graph illustrating a pressure displacement curve characterizing biomechanical properties of the face of the individual wearer;

[0011] FIG. 4A is a Three-Dimensional (3D) facial scan of the individual wearer prior to donning the PPE, according to an embodiment of the present disclosure;

[0012] FIG. 4B is a 3D facial scan of the individual wearer after donning the PPE, according to an embodiment of the present disclosure;

[0013] FIG. 4C is a composite image of the individual wearer obtained by superimposing the 3D facial scans of FIGS. 4A and 4B, according to an embodiment of the present disclosure;

[0014] FIG. 4D illustrates skin deformation regions in the composite image of FIG. 4C, according to an embodiment of the present disclosure;

[0015] FIG. 5 is a 3D image indicating soft skin tissue deformation of the face of the individual wearer, according to an embodiment of the present disclosure;

[0016] FIGS. 6A to 6C illustrate 3D facial scans of the individual wearer after donning the PPE indicating skin deformation regions corresponding to varying pressures applied by the PPE, according to an embodiment of the present disclosure;

[0017] FIG. 6D is a schematic view of a soft skin tissue deformation in a skin tissue having a soft skin tissue thickness, according to an embodiment of the present disclosure;

[0018] FIG. 7A is a scanned image of the PPE, according to an embodiment of the present disclosure;

[0019] FIGS. 7B and 7C are 3D scanned images of the face of the individual wearer after donning the PPE for indicating sealing characteristics of the PPE, according to an embodiment of the present disclosure;

[0020] FIG. 7D illustrates a type of the PPE with markings on a strap of the PPE, according to an embodiment of the present disclosure;

[0021] FIG. 7E is an exemplary graph illustrating a force extension curve characterizing tension on the PPE strap of the PPE of FIG. 7D, according to an embodiment of the present disclosure;

[0022] FIG. 8 illustrates a flowchart for a process for determining a sealing effectiveness factor of the PPE, according to an embodiment of the present disclosure;

[0023] FIG. 9 illustrates a flowchart for a process for determining a comfort metric of the PPE for the individual wearer, according to an embodiment of the present disclosure; and

[0024] FIG. 10 is a flowchart for a method for determining PPE comfort for the individual wearer, according to an embodiment of the present disclosure.

DETAILED DESCRIPTION

[0025] In the following description, reference is made to the accompanying figures that form a part thereof and in which various embodiments are shown by way of illustration. It is to be understood that other embodiments are contemplated and may be made without departing from the scope or spirit of the present disclosure. The following detailed description, therefore, is not to be taken in a limiting sense.

[0026] Various types of personal protective equipment (PPE) are commonly worn by people who work in areas where air may be contaminated with toxic substances, such as, airborne particulates, gases, and vapors. A type of the PPE used in a particular environment depends on an amount of the toxic substances and type of protection required by an individual wearer. The PPE type used may also depend on factors, such as biomechanical properties, skin deformation on donning of the PPE, etc. of the individual wearer.

[0027] While selecting the PPE for the individual wearer, it is important to ensure that the PPE is comfortable to wear and provides efficient sealing so that the individual wearer is well protected against gases and particulates. Conventional PPE selection methods do not consider biomechanical properties of an individual wearer's face, or in other words, response of the individual wearer's face upon application of a force. Thus, the PPE selected using conventional techniques may not be comfortable for the user.

[0028] The present disclosure relates to a system and a method of assessing PPE comfort for the individual wearer by addressing the biomechanical properties of the face of the individual wearer. The system disclosed herein includes a processor that is configured to determine a comfort metric of the PPE as well as a sealing of the PPE using anatomical shape data of the individual wearer before and after donning the PPE. By determining the comfort metric, skin pressure comfort for the PPE may be quantified which ultimately allows product comparison, design evaluation and development, claims verification, and customer education. The disclosed system may help to quantify the PPE comfort and develop PPE products that provide improved comfort. The system also considers biological properties of the face of the individual wearer to select an appropriate PPE for a particular individual wearer. As the PPE selection is based on determination of the comfort metric, the individual wearer may feel comfortable and confident with the selected configuration of the PPE. The comfort metric determination also considers factors, such as skin deformation due to pressure applied by the PPE, to evaluate an appropriate PPE that fits well to the individual wearer. More particularly, the system and the method described in the present disclosure allows determination of pressure distribution of the PPE on the user's skin, which may in turn allow improvement in PPE design and prevent excessive pressure points on the user's skin.

[0029] As skin deformation or skin displacement is an important factor that is considered while selecting the PPE for the individual wearer, the disclosure describes a method to quantify skin pressure comfort for different PPE types and sizes. The system and method consider the skin

pressure discomfort due to combined effects of applied pressure and PPE design. Hence, by measuring skin deformations due to the PPE design and pressure applied by the PPE, various adjustments or modifications may be applied to select a comfortable PPE for the individual wearer. Further, the comfort metric value also gives an indication about sealing effectiveness provided by the PPE which may in turn help the individual wearer to choose a PPE that exhibits an improved sealing and is comfortable to wear.

[0030] Referring now to FIG. 1, a system **100** for determining PPE comfort for the individual wearer is illustrated. The system **100** includes a processor **102**, an output module **104**, and a memory **106**. The processor **102** may be a programmable analog and/or digital device that can store, retrieve, and process data. In an application, the processor **102** may be a controller, a control circuit, a computer, a workstation, a microprocessor, a microcomputer, a central processing unit, a server, or any suitable device or apparatus. Some examples may also include input devices (not shown) connected to the processor **102**.

[0031] The output module **104** is communicably coupled with the processor **102**. The output module **104** may be a display panel, a printer, a speaker, a monitor, a plotter, a graphic output device, or any electronic device with a user interface. The output module **104** may be present with the individual wearer, a PPE selector, a PPE designer, a PPE manufacturer, a control module, and the like. The memory **106** includes a database **108**. The database **108** may have a data structure to store organized information and data. The memory **106** may also include a suitable combination of computing devices and software modules for storing, manipulating, and retrieving data records related to different types of PPE **406** (shown in FIG. 4B) and the individual wearers. The system **100** further includes at least one Three-Dimensional (3D) scanner **110** communicably coupled with the processor **102**.

[0032] Further, the present disclosure utilizes biomechanical properties of the individual wearer to determine PPE comfort and PPE sealing. A first technique of determining one or more biomechanical properties of the individual wearer will now be explained in conjunction with FIGS. 2A and 2B. As shown in FIGS. 2A and 2B, while determining the PPE comfort for the individual wearer, the processor **102** (see FIG. 1) determines one or more biomechanical properties of a face **200** of the individual wearer, according to an embodiment of the present disclosure. The biomechanical properties of the face **200** may include a response of the face **200** on application of an external force, for example, after donning the PPE **406** (shown in FIG. 4B). To determine the biomechanical properties of the face **200**, a zone **202** is quantified where the PPE **406** would contact the face **200**. The zone **202** is quantified by placing a gasket **206** (shown in FIG. 2A) having a number of holes **208** (shown in FIG. 2A) over the face **200**. The gasket **206** may embody a 3D printed gasket. Further, a number of data points **204** (shown in FIG. 2B) are marked on the face **200** with a marker (not shown).

[0033] After marking the zone **202** with the data points **204**, measuring devices (not shown) may be used for measuring pressure and displacement values at each data point **204**. For example, a pressure sensor and a caliper may be used to determine pressure and displacement values at each data point **204**. In some examples, a hardware, such as Arduino or any other hardware, may be used to capture data corresponding to the pressure and the displacement values at the data points **204**. Further, the face **200** may be digitized with a depth camera to link shape models with pressure/displacement models.

[0034] Moreover, the pressure and the displacement values at the data points **204** may be used to generate pressure-displacement curves by the processor **102** to characterize the biomechanical properties of the face **200**. Specifically, pressure and displacement caused due to donning of the PPE **406** are measured at each data point **204** to prepare a pressure-displacement curve. An exemplary pressure-displacement curve **300** is shown in FIG. 3. As illustrated in FIG. 3, with increase in the pressure on the face **200** (see FIGS. 2A and 2B), a displacement or deformation of the skin also increases in a substantially linear trend.

[0035] Further, the processor **102** (see FIG. **1**) may generate a new vector (x, y, z, d, p) for each data point **204** (see FIGS. **2A** and **2B**) in a 3D space (x, y, z), a displacement vector (d), and a pressure vector (p). As the data is collected for population statistics, pressure-displacement curves **300** are generated for a number of samples, which may enhance accuracy of data collection. In some embodiments, the pressure-displacement curves **300** may be resampled at regular predefined pressure intervals, such that a precise data acquisition could be established. The resampling may be interpolated to ensure that the resampled data is following underlying pressure-displacement curve trends. In some embodiments, the processor **102** may be used to conduct a bicubic interpolation. In another embodiment, linear interpolation may be used, such as in examples where data is acquired at a high sample rate.

[0036] Once the new vectors (x, y, z, d, p) are generated, resampled, and interpolated, preprocessing of the results may be performed to format pressure and displacement values. In other words, pressure values may be normalized against the maximum pressure, and the displacement values may be normalized against the maximum displacement.

[0037] Further, a feature vector for faces of multiple wearers may be constructed based on normalized measurements or values of pressure and displacement. The feature vector for each face may be depicted as: [0038] (x.sub.1, y.sub.1, z.sub.1, x.sub.2, y.sub.2, z.sub.2, . . . , x.sub.n, y.sub.n, z.sub.n, d.sub.1, p.sub.1, d.sub.2, p.sub.2, . . . , d.sub.m, p.sub.m)

[0039] Further, the processor **102** is configured to use statistical shape modeling tools and principal component analysis to create a low dimensional representation of the feature vector data for each face. This approach may allow easier interpretation and summarizing of data using fewer parameters. Therefore, by using biomechanical properties or the pressure-displacement curves **300**, population statistics data, and statistical shape modeling tools, the processor **102** may determine comfort fit of the PPE **406** for one or more individual wearers. Utilization of biomechanical properties to predict the comfort fit of the PPE **406** for the individual wearer may help to customize the PPE **406** for the individual wearer. Thus, the details described in relation to FIGS. **2A** to **3** may assist in selection of the PPE **406** for the individual wearer.

[0040] Further, the processor **102** is configured to define a first anatomical shape data representative of an anatomical area of the individual wearer prior to donning the PPE **406**. The processor **102** are also configured to define a second anatomical shape data representative of the anatomical area of the individual wearer after donning the PPE **406**. Furthermore, the first anatomical shape data and the second anatomical shape data is defined based on scanning the anatomical area of the individual wearer prior to donning the PPE **406** and after donning the PPE **406**, respectively, using the 3D scanner **110** (shown in FIG. **1**).

[0041] FIG. **4A** illustrates a 3D facial scan **402** of the individual wearer prior to donning the PPE **406** and FIG. **4B** illustrates a 3D facial scan **404** of the individual wearer after donning the PPE **406**. The 3D facial scans **402**, **404** may be performed by the 3D scanner **110** (see FIG. **1**). The processor **102** (see FIG. **1**) may communicate with the 3D scanner **110** for obtaining the 3D facial scans **402**, **404** therefrom. The 3D scanner **110** may pick up small features in a range of 0.15 millimeters (mm) with a resolution of 50 micrometers (μm). In some embodiments, the 3D scanner **110** may include a structured light scanner from Artec 3D. For example, Artec Eva may be used for coarse resolution scanning, whereas more finer details may be captured by Artec Spider. The 3D facial scans **402**, **404** may be processed by the processor **102** using a software, such as Artec Studio **12 Professional**.

[0042] Further, the processor **102** processes the 3D facial scan **402** to define the first anatomical shape data representative of the anatomical area of the individual wearer prior to donning the PPE **406**. Similarly, the processor **102** processes the 3D facial scan **404** to define the second anatomical shape data representative of the anatomical area of the individual wearer after donning the PPE **406**.

[0043] Moreover, the processor **102** is configured to superimpose the processed 3D facial scans

402, 404 to generate a composite image **412**, as shown in FIG. 4C. In other words, the processor **102** is configured to compare the first anatomical shape data with the second anatomical shape data to generate the composite image **412**. Further, the processor **102** may analyze the composite image **412** to determine regions on the face **200** that are subjected to soft skin tissue deformation “u” after donning the PPE **406**. More particularly, FIG. 4D illustrates a facial image **414** indicating a skin deformation region **415** on the face **200** after donning the PPE **406**. The skin deformation region **415** is shown using a hatched section in FIG. 4D.

[0044] The processor **102** is also configured to determine the soft skin tissue deformation “u” at a plurality of predetermined anatomical positions based on the comparison between the first anatomical shape data and the second anatomical shape data. The processor **102** is configured to generate the plurality of the predetermined anatomical positions based on at least two dynamic movements performed by the individual wearer. FIG. 5 shows a 3D scanned image **500** for investigation of the skin deformation region **415** in the facial image **414** of FIG. 4D. The scanned image **500** includes an undeformed surface **502** on the face **200** prior to donning the PPE **406**. The scanned image **500** also includes a deformed surface **504** on the face **200** after donning the PPE **406**. Further, a distance “D” is defined between the undeformed and deformed surfaces **502, 504**. The distance “D” reflects an amount of the soft skin tissue deformation “u” on the face **200** after donning the PPE **406**. Such an investigation of the soft skin tissue deformation “u” using scanned images may be considered equivalent to measuring the deformation directly on the skin.

[0045] In an embodiment with reference to FIGS. 6A to 6C, the processor **102** may receive 3D facial scans **602, 604, 606** of the individual wearer after donning the PPE **406** from the 3D scanner **110** (see FIG. 1). FIG. 6D schematically shows the soft skin tissue deformation “u” of the individual wearer. The PPE **406** (see FIGS. 6A to 6C) includes a strap **408** by which the PPE **406** can be adjusted as per requirements. Referring to FIG. 6A, the 3D facial scan **602** is illustrated in which a high pressure is applied by the PPE **406** or the strap **408**, which is in line with an expected outcome of tightening the strap **408**. The high pressure applied by the PPE **406** in FIG. 6A generates a high skin deformation region **603** illustrated by a hatched section herein.

[0046] Referring to FIG. 6B, the 3D facial scan **604** is illustrated in which a medium pressure is applied by the PPE **406** or the strap **408**. The medium pressure applied by the PPE **406** in FIG. 6B generates a medium skin deformation region **605** illustrated by a hatched section herein. Referring now to FIG. 6C, the 3D facial scan **606** is illustrated in which a low pressure is applied by the PPE **406** or the strap **408**. The low pressure applied by the PPE **406** in FIG. 6C generates a low skin deformation region **607** illustrated by a hatched section herein.

[0047] Therefore, with reference to the high, medium, and low skin deformation regions **603, 605, 607** in FIGS. 6A, 6B, and 6C, respectively, it is evident that the amount of the soft skin tissue deformation “u” increases with an increase in the strap pressure or a PPE pressure. In other words, a magnitude of the soft skin tissue deformation “u” is proportional to the pressure applied by the PPE **406**.

[0048] FIG. 6D shows the soft skin tissue deformation “u” in a skin tissue having a soft skin tissue thickness “t”. With continued reference to FIGS. 6A to 6D, the soft skin tissue deformation “u” in the skin deformation regions **603, 605, 607** also depends on the soft skin tissue thickness “t” at the corresponding skin deformation regions **603, 605, 607**. Further, in an example, the soft skin tissue thickness “t” can be measured by using an ultrasound equipment (not shown) such as Episcan (LONGPORT, INC, 1620 Baltimore Pike, P.O. Box 768, Chadds Ford, PA 19317). In some cases, approximate values can be determined from the database **108** (see FIG. 1) for the soft tissue thickness “t” for various population groups. In an example, a low soft skin tissue deformation “u” in the skin deformation region **607** may result from a low soft skin tissue thickness “t”. Thus, any deformations under constant force may appear as smaller deformations than in thicker skin tissue regions.

[0049] The processor **102**, while determining the soft skin tissue deformation “u” in a particular

region, may consider the soft skin tissue thickness “t” for the same region. The processor **102** is configured to determine the soft skin tissue thickness “t” at the plurality of predetermined anatomical positions. More particularly, the processor **102** determines distribution of the soft skin tissue thickness “t” across the skin deformation regions **603**, **605**, **607**. Further, the soft skin tissue thickness “t” is utilized to normalize deformation distribution. In an example, the processor **102** is configured to retrieve stored data for the soft skin tissue thickness “t” at the plurality of predetermined anatomical positions based on at least one of a previous assessment of the individual wearer and an aggregated data from a plurality of previous wearers. In another example, the soft skin tissue thickness “t” may be stored in the database **108**. Accordingly, the processor **102** is configured to receive the soft skin tissue thickness “t” at the predetermined anatomical positions from the previously created database **108**. In some embodiments, the plurality of predetermined anatomical positions are generated using a static modeling module. In an example, the static modeling module may include determining the predetermined anatomical positions by quantifying the zone **202** (see FIGS. 2A and 2B) using the gasket **206** (see FIG. 2A) and marking the data points **204** (see FIG. 2B) with the marker. In another example, the static modeling module may include determining the predetermined anatomical positions by scanning the anatomical area of the individual wearer prior to donning the PPE **406** and after donning the PPE **406** using the 3D scanner **110**. The 3D facial scans **402**, **404** (see FIGS. 4A and 4B) may be superimposed and analyzed to generate the composite and facial images **412**, **414** (see FIGS. 4C and 4D) to indicate the predetermined anatomical positions.

[0050] In other embodiments, the plurality of predetermined anatomical positions are generated using a dynamic modeling module. In the dynamic modeling module, actual facial movement of the individual wearer may also be considered. The dynamic modeling module may also consider a simulated facial movement in order to evaluate the predetermined anatomical positions.

[0051] In some examples, the processor **102** is configured to correlate the soft skin tissue deformation “u” at the plurality of predetermined anatomical positions for each individual wearer and the pressure applied by the PPE **406** at the plurality of predetermined anatomical positions for each individual wearer. The processor **102** is further configured to aggregate the correlation for generating a predicted wearer comfort metric (CM.sub.PRE).

[0052] In an example, a discomfort factor due to a design of the PPE **406** and the applied pressure from the PPE **406** may be considered as a function of the amount of the soft skin tissue deformation “u” produced relative to the overall soft skin tissue thickness “t”. The ratio between the soft skin tissue deformation “u” and the soft skin tissue thickness “t” at the predetermined anatomical positions is defined as a first ratio “u/t”.

[0053] Based on determination of the soft skin tissue deformation “u” and the soft skin tissue thickness “t”, the processor **102** is configured to compute an initial comfort metric. The initial comfort metric may be defined as the ratio of the soft skin tissue deformation “u” to the soft skin tissue thickness “t”, which is normalized by an overall relative skin displacement comfort threshold (CT.sub.d) value. The processor **102** is configured to determine the CT.sub.d value based on the soft skin tissue deformation “u” at the plurality of predetermined anatomical positions. The CT.sub.d value is determined by changing the relative soft skin tissue deformation levels under the PPE **406** and using inputs from the individual wearer for gauging a pressure being perceived by the individual wearer and whether the deformations are comfortable for the individual wearer. The initial comfort metric may be determined using following Equation 1:

[00001]
$$CM = \frac{1}{CT_d} \frac{u}{t}$$
 Equation 1

[0054] To determine a generalized value of the initial comfort metric of Equation 1, the processor **102** determines the soft skin tissue thickness “t” for various anatomical positions on the face **200**. As the soft skin tissue thickness “t” may vary across the area covered by the PPE **406**, the processor **102** may take into consideration different values for the soft skin tissue thickness “t”

across the face **200** covered by the PPE **406**. In order to compare distribution of the soft skin tissue thicknesses “t” among different individual wearers, the processor **102** may determine the soft skin tissue thickness “t” at the various anatomical positions on the face **200** proximate to a location where the PPE **406** is worn. The determined soft skin tissue deformations “u” around the anatomical positions may be divided by the soft skin tissue thickness “t” and summed together. Specifically, the processor **102** is configured to determine the first ratio “u/t” between the determined soft skin tissue deformation “u” and the soft skin tissue thickness “t” at the plurality of predetermined anatomical positions. The first ratio “u/t” is then summed together for the predetermined anatomical positions, and normalized by the overall CT.sub.d value, to determine a comfort metric (CM). The processor **102** may be configured to determine a value of the CM by using following Equation 2:

[00002]
$$CM = \frac{1}{CT_d \cdot \text{Math. } N} \left[\frac{u_1}{t_1} + \frac{u_2}{t_2} + \frac{u_3}{t_3} \cdot \text{Math.} + \frac{u_n}{t_n} \right] \quad \text{Equation 2}$$
 [0055] where, [0056] CT.sub.d value is skin displacement comfort threshold value of the PPE **406** for all trials and wearers; [0057] u.sub.1 to u.sub.n are determined soft skin tissue deformations; and [0058] t.sub.1 to t.sub.n are soft skin tissue thicknesses at various predetermined anatomical positions.

[0059] To make the determined CM furthermore accurate, the processor **102** may consider variability in neurological pressure response at each of the anatomical positions for each wearer. For this purpose, the first ratio “u/t” can be multiplied by a pressure pain threshold (PPT) value. The PPT value may be defined as a minimum force applied on the face **200** of the individual wearer which induces pain and can be measured by using an algometer. Specifically, the processor **102** is configured to determine the PPT value at the plurality of predetermined anatomical positions. Therefore, an individual wearer comfort metric (CMP) is determined based on the PPT values, the CT.sub.d values, and the first ratio “u/t”. The CMP may be hereinafter interchangeably referred to as “comfort metric”. The processor **102** is configured to determine the individual wearer comfort metric CMP based on the PPT values, the CTd values, and the first ratio “u/t”. Following Equation 3 may be used to determine a value of the CMP:

[00003]
$$CMP = \frac{1}{CT_d \cdot \text{Math. } N \cdot \text{Math. } PPT} \left[PPT_1 \frac{u_1}{t_1} + PPT_2 \frac{u_2}{t_2} + PPT_3 \frac{u_3}{t_3} \cdot \text{Math.} + PPT_n \frac{u_n}{t_n} \right] \quad \text{Equation 3}$$

[0060] where, [0061] PPT.sub.i are the PPT values at each of the predetermined anatomical positions and, [0062] $PPT = \sum_{i=1}^{sup.N} PPT_{sub.i}$

[0063] Based on determination of the CMP using Equation 3, the output module **104** (see FIG. 1) is configured to provide a notification corresponding to the CMP received from the processor **102**. Further, the notification corresponding to the CMP may be provided to the individual wearer, the PPE selector, the PPE designer/manufacturer, and/or the control station. In some embodiments, the output module **104** may generate a visual notification of a value of the CMP on a display panel. In some embodiments, the output module **104** may generate an audible signal to notify the value of the CMP by using a speaker. In yet other embodiments, the output module **104** may generate a printed report summary of the CMP.

[0064] Moreover, the processor **102** is also configured to compare the CMP to the CM.sub.PRE. The calculation of the CMP acts as a factor to quantify the PPE comfort for one or more individual wearers. The CMP also takes into consideration the pressure distribution of the PPE **406** on the face **200** of the individual wearer, and the soft skin tissue thickness “t” of the face **200** of the individual wearer under the PPE **406**. Determination of such values and using the same in the calculation of the CMP may help to choose an acceptable PPE **406** for the individual wearer.

[0065] In an example, a quality of fit can also be determined for an earmuff donned by the individual wearer. Donning the earmuff may also cause the soft skin tissue deformation “u” around an ear or in vicinity of the ear. Similarly, as described with reference to FIGS. 6A to 6C, the soft skin tissue deformation “u” can also be observed and determined for the earmuff. Therefore, regions of low, medium, and high skin deformations can be determined on the individual wearer. The regions with low or negligible soft skin tissue deformation “u” may indicate higher chances of

a poor sealing which translates to inadequate protection for the individual wearer. Such regions are areas of potential concern which may be informed to the individual wearer, the PPE selector, the PPE designer/manufacturer, and/or the control station to make targeted adjustments to improve sealing quality of the earmuff.

[0066] Further, it should be noted that the regions of a low soft skin tissue deformation “u” after donning the earmuff may result from the low soft skin tissue thickness “t”, so that any soft skin tissue deformation “u” under a constant force would appear as a small soft skin tissue deformation “u” than in thicker skin regions. Thus, a comfort metric can also be determined for a particular earmuff donned by the individual wearer, by following Equation 3, and entering the various values determined with respect to the earmuff. In another example, a similar approach may be applied on headbands to determine the quality of fit of the headbands for the individual wearer.

[0067] In an embodiment illustrated in FIGS. 7A to 7C, another factor that is considered in selecting the PPE **406** for a particular wearer is a sealing effectiveness factor. A head **210** of the wearer is shown in FIGS. 7A to 7C. For determining a scaling effectiveness of the PPE **406** (see FIG. 4B), the processor **102** (see FIG. 1) is configured to use the 3D scanner **110** (see FIG. 1) to estimate whether the PPE **406** seals with the face **200** adequately to provide protection to the individual wearer. Based on the estimated sealing area, a qualitative prediction of a fit factor of the PPE **406** can be projected. In case of an improperly created seal, the processor **102** can also point out a location of ineffective seal and suggest the individual wearer, the PPE selector, the PPE designer/manufacturer, and/or the control station to make targeted adjustments to improve sealing quality at that location. The processor **102**, therefore, can determine if a proper seal has been created after donning the PPE **406**.

[0068] The sealing effectiveness of the PPE **406** on the individual wearer can be determined by calculating a ratio of a particle concentration outside the PPE **406** to a particle concentration inside the PPE **406** while the PPE **406** is worn by the individual wearer. Further, the processor **102** is configured to define a first PPE shape data before donning the PPE **406** by the individual wearer and a second PPE shape data after donning the PPE **406** by the individual wearer. More particularly, the processor **102** receives a scan of the PPE **406** of the individual wearer before donning the PPE **406** from the 3D scanner **110**. The processor **102** is also configured to determine a first contour data of the PPE **406** based on the first PPE shape data.

[0069] FIG. 7A is a scanned image **702** illustrating the PPE **406** before donning the PPE **406** by the individual wearer. The scanned image **702** defines the first PPE shape data before donning the PPE **406** by the individual wearer. In an example, a thickness of the PPE **406** is determined at points of interest from the scanned image **702** of the PPE **406**. More particularly, the entire PPE **406** is scanned and split into front side scans and back side scans. After creating two separate scans, the thickness of the PPE **406** is measured, and accordingly the first contour data is defined. The first contour data defines various thickness values. For example, the scanned image **702** illustrates first thickness values “bd1”, “bd2”, “bd3” of the PPE **406** at different points of interest. The first thickness values “bd1”, “bd2”, “bd3” may collectively represent the first contour data.

[0070] The processor **102** also receives a scan of the PPE **406** and the face **200** of the individual wearer after donning the PPE **406** from the 3D scanner **110**. The processor **102** is configured to determine a second contour data of the PPE **406** based on the second PPE shape data. FIG. 7B is a scanned image **704** illustrating the PPE **406** and the face **200** after donning the PPE **406** by the individual wearer. The scanned image **704** defines the second PPE shape data after donning the PPE **406** by the individual wearer. The scanned image **704** illustrates second thickness values “ad1”, “ad2”, “ad3” at the different points of interest. The second thickness values “ad1”, “ad2”, “ad3” may collectively represent the second contour data. It should be noted that the second thickness values “ad1”, “ad2”, “ad3” of the scanned image **704** represent the distances between a first outer edge **701** of the PPE **406** and a second outer edge **703** of the face **200** without donning the PPE **406**.

[0071] Further, the processor **102** is configured to compare the first contour data with the second contour data. More particularly, the processor **102** compares a position of the second outer edge **703** relative to the first outer edge **701** which may be indicative of the sealing of the PPE **406**. For example, in FIG. 7B, after donning the PPE **406**, the second thickness values “ad1”, “ad2”, “ad3” between the second outer edge **703** and the first outer edge **701** is greater than the corresponding first thickness values “bd1”, “bd2”, “bd3” (see FIG. 7A) before donning the PPE **406**. For example, the second thickness value “ad1” is greater than the first thickness value “bd1”, the second thickness value “ad2” is greater than the first thickness value “bd2”, the second thickness value “ad3” is greater than the first thickness value “bd3”, and so on. This implies that the sealing effectiveness factor is high, and the PPE **406** provides a good seal. In other words, since the second thickness values “ad1”, “ad2”, “ad3” representing the second contour data are greater than the first thickness values “bd1”, “bd2”, “bd3” representing the first contour data, a good seal is expected from the PPE **406**. In some examples, the scaling effectiveness factor/fit factor may be measured using a PortaCount (8030, TSI) and ambient particles. The sealing effectiveness factors/fit factors may be measured with constant inhalation through the PPE **406** at 30 Liters Per Minute (LPM). [0072] On the other hand, for exemplary purpose, FIG. 7C illustrates a scanned image **706** in which the second outer edge **703** is comparatively closer to the first outer edge **701**. Moreover, the second outer edge **703** includes multiple breaks. This phenomenon indicates that there are some areas where an inner edge **407** (shown in FIG. 7D) of the PPE **406** is not touching the face **200**. Hence, the scanned image **706** depicts that there is a leak at a region **712** after the PPE **406** is donned by the individual wearer. This implies that the sealing effectiveness factor is low, and the PPE **406** is not providing a good seal.

[0073] The processor **102** is configured to generate a notification of the sealing effectiveness factor for the individual wearer based on the comparison between the first contour data and the second contour data. More particularly, the output module **104** (see FIG. 1), connected to the processor **102**, is configured to provide the notification indicative of a fit or the scaling effectiveness factor of the PPE **406** on the individual wearer. The output module **104** may generate a visual notification or an audio notification. Further, the output module **104** may provide the notification corresponding to the sealing effectiveness factor to the individual wearer, the PPE designer/manufacturer, the PPE selector, and/or the control station. In some embodiments, the output module **104** includes a color-coded display for overlaying one or more colors indicative of the fit of the PPE **406**. For example, a red color region may indicate a region of low sealing effectiveness factor, and a green color may indicate a region of high sealing effectiveness factor, and so on.

[0074] In addition to the PPE **406**, the sealing effectiveness factor may also be determined for disposable respirators. A similar approach may be applied in case of the disposable respirators to guide the individual wearer to achieve a good fit. In an example, the sealing effectiveness factor may be determined for the disposable respirators at selected locations to highlight sealing quality at locations such as nose area, chin area, etc.

[0075] A data of a variety of different faces/heads and sealing effectiveness factors from a variety of different PPE choices can be stored in the database **108** (see FIG. 1). The processor **102**, connected to the database **108**, may therefore propose personalized PPE recommendations. The processor **102** may take a 3D scan of the face **200** of the individual wearer and calculate a similarity between the facial scan to previous facial scans from the database **108**. Each previous facial scan in the database **108** can contain fields for a quality of a fit for different PPE designs. A consensus PPE option may then be generated by polling the most similar structural profiles to the wearer's measurements, and then computing a rank ordered list for PPE options that may be recommended based on their compliance likelihood. This type of rank ordering could be generated by a number of techniques, such as ranked choice voting amongst the most similar entries in the database **108** or a weighted scheme that incorporates the degree of similarity between the database entries and the wearer's face form (e.g., inverse distance-weighted voting). Certain

recommendations can be pulled from the ranked list based on required PPE features for a given task, as certain PPEs **406** may fit well but may be unacceptable based on the exposure risks in an environment. Once the individual wearer finds a suitable fitting PPE **406**, their face scan and PPE selection can be added to the database **108** to be used for future recommendations. The updated database **108** for this recommendation process may also benefit PPE designers and thus, enables the development of the PPE **406** that ideally conforms to structural archetypes from the database **108**.

[0076] Further, according to another embodiment of the present disclosure, the processor **102** determines the first PPE shape data for a number of PPE sizes for a PPE type. The PPE sizes may include sizes, such as small, medium, large or the PPE sizes may be quantified using other parameters. It should be noted that the PPE type itself may include different models or designs of the PPE **406**. The processor **102** may accordingly store the first PPE shape data for a number of PPE sizes in the database **108**. Thus, the processor **102** can access information pertaining to the plurality of PPE sizes for the PPE type. It should be noted that the information pertaining to the PPE sizes may include first PPE shape data corresponding to the PPE type. Referring again to FIGS. 4A to 4C and FIG. 7D, the processor **102** (see FIG. 1) may determine where the inner edge **407** of the PPE **406** rests on the face **200**. The processor **102** determines this position of the PPE **406** relative to the face **200** by comparing or superimposing, for the individual wearer, the first anatomical shape data with the second anatomical shape data. Then, the processor **102** predicts the PPE size for the individual wearer from the plurality of PPE sizes based on the comparison between the first anatomical shape data and the second anatomical shape data. It should be noted that the processor **102** predicts the PPE size based on the first anatomical shape data, the second anatomical shape data, and the information pertaining to the PPE sizes for the PPE type.

[0077] Further, the processor **102** is configured to generate a notification for the individual wearer pertaining to the predicted PPE size. Specifically, the notification is provided by the output module **104** (see FIG. 1). The output module **104** may provide the notification to the individual wearer, the PPE selector, the PPE designer/manufacturer, and/or the control station. In some embodiments, the output module **104**, by using a display panel, may generate a visual notification for the predicted PPE size. In other embodiments, the output module **104**, by using a speaker, may generate an audible alert to notify the information pertaining to the predicted PPE size. In yet other embodiments, the output module **104** may generate a printed report summary of the predicted PPE size for the individual wearer. Further, in some embodiments, the output module **104** may generate a notification for the individual wearer to change the PPE size from medium to large to maximize the PPE fit and comfort. In some embodiments, the output module **104** may generate a notification for the individual wearer to change the PPE size from large to medium to maximize the PPE fit and comfort.

[0078] Furthermore, in an alternate embodiment, the system **100** may include accessing information pertaining to a plurality of PPE types and a plurality of PPE sizes from a predetermined library. The predetermined library may embody the database **108** itself, or the predetermined library may be stored in the memory **106**. Specifically, the processor **102** is configured to access information pertaining to the plurality of PPE types and PPE sizes from the predetermined library, to predict for the individual wearer, a PPE type from the plurality of PPE types and the PPE size from of the plurality of PPE sizes.

[0079] Further, the individual wearers generally try to adjust the PPE **406** by tightening or loosening the strap **408** to get a good fit. The individual wearers adjust the strap **408** in a range of different tensions while donning the PPE **406**. Each tension may cause a different soft skin tissue deformation “u” and pressure on the face **200**. Some individual wearers may tighten the strap **408** of the PPE **406** to a greater extent than other individual wearers. Most individual wearers find it difficult to assess an amount of tension in the strap **408** that is sufficient beyond their subjective impressions. Some individual wearers have also been observed to overtighten the strap **408** beyond

a value that is required to get a good fit. The overtightening of the strap **408** may affect the comfort/wear tolerance of the individual wearer while donning the PPE **406**.

[0080] In order to determine the tension in the strap **408**, the processor **102** is configured to define a plurality of predetermined setting ranges for adjusting at least one adjustable feature on the PPE **406**. In the illustrated example, the at least one adjustable feature includes strap tension.

Alternatively, the at least one adjustable feature may include any other feature associated with the PPE **406**. The predetermined setting ranges are defined based on at least one of a fit of the PPE **406** and a comfort of the PPE **406**. The predetermined setting ranges may be defined as various ranges of tensions for the PPE **406** based on a size of the PPE **406**. For example, the predetermined setting ranges may vary for a medium size PPE, a small size PPE, and so on.

[0081] In order to define the plurality of predetermined setting ranges, the strap **408** is marked with a number of first equidistant markings **708**, where each first marking **708** is at a distance “G” from an adjacent first marking **708** when the strap **408** is slack. After the PPE **406** is donned by the individual wearer, the strap **408** is further marked with a number of second equidistant markings (not shown), where each second marking may again lie at a certain distance from an adjacent second marking. It is noted that the distance between two adjacent second markings is greater than the distance “G” between two adjacent first markings **708**. The extended distance or extension between the two adjacent second markings is noted. Now referring to FIG. 7E, tension in the strap **408** when the PPE **406** is donned by the individual wearer, may be determined by plotting a force-extension curve **710** obtained on a tensile tester of the strap **408**. The force-extension curve **710** may be used to determine different predetermined setting ranges. Such technique may in turn allow modifications in the strap **408** for current or other PPEs **406** to include markings that indicate an accurate way to wear the PPE **406** for achieving a sufficient fit without sacrificing comfort.

[0082] Once the processor **102** defines the predetermined setting ranges for adjusting one or more adjustable features on the PPE **406**, the processor **102** is configured to notify the individual wearer of the predetermined setting range from the plurality of predetermined setting ranges for adjusting at least one adjustable feature. Specifically, the output module **104** may provide the notification to the individual the PPE selector, the PPE designer/manufacturer, and/or the control station. Further, the predetermined setting ranges may be marked on the strap **408** to notify the individual wearer regarding acceptable strap tension. Thus, the strap **408** may be modified in current or future PPE **406** to indicate different predetermined setting ranges. Such predetermined setting ranges may help the individual wearer to achieve a sufficient fit without sacrificing comfort. Therefore, the disclosed embodiment may be used to advise the individual wearer regarding the tightening of the strap **408** to get a good fit without causing discomfort. In some embodiments, such approach may be applied on a headband of the PPE **406**. As per the embodiment, the processor **102** may adjust one or more adjustable features on the PPE **406** to a variety of predetermined settings in order to find an optimal balance of fit and comfort. Therefore, the processor **102** may predict a wearer adjustable setting value of a particular feature that would give the individual wearer a good fit while maintaining wearer comfort. Thus, the processor **102** may prevent the individual wearer to select a wearer adjustable setting which can be uncomfortable (e.g., by overtightening headbands or straps).

[0083] Referring to FIG. 8, a flowchart for a process **800** for determining the CMP of the PPE **406** for the individual wearer is illustrated, in accordance with an embodiment of the disclosure. The process **800** is embodied as a logic/algorithm implemented by the processor **102** and may be stored in the memory **106** of the system **100**.

[0084] At block **802**, the process **800** is activated by the processor **102**. More particularly, the process **800** starts or begins operation by selecting the PPE **406** for which the CMP is to be determined. The process **800** then moves to a block **804**. At the block **804**, the processor **102** receives the 3D facial scan **402** generated by the 3D scanner **110**. The 3D facial scan **402** is the scan of the face **200** of the individual wearer prior to donning the PPE **406**. The process **800** then

moves to a block **806**. At the block **806**, the processor **102** processes the 3D facial scan **402** and stores the processed 3D facial scan **402** in the database **108**. The processed 3D facial scan **402** defines the first anatomical shape data representative of the anatomical area of the individual wearer prior to donning the PPE **406**. The process **800** then moves to a block **808**. At the block **808**, the processor **102** receives the 3D facial scan **404** generated by the 3D scanner **110**. The 3D facial scan **404** is the scan of the face **200** of the individual wearer after donning the PPE **406**.

[0085] The process **800** then moves to a block **810**. At the block **810**, the processor **102** processes the 3D facial scan **404** and stores the processed 3D facial scan **404** in the database **108**. The processed 3D facial scan **404** defines the second anatomical shape data representative of the anatomical area of the individual wearer after donning the PPE **406**. The process **800** further moves to a block **812**. At the block **812**, the processor **102** is configured to compare the processed 3D facial scans **402**, **404**. Specifically, the processor **102** aligns and superimposes the 3D facial scans **402**, **404** to generate the composite image **412**. Therefore, the processor **102** is configured to compare the first anatomical shape data with the second anatomical shape data. After generating the composite image **412**, the processor **102** is configured to determine the soft skin tissue deformation “u” at the predetermined anatomical positions based on the comparison between the first anatomical shape data and the second anatomical shape data. The processor **102** primarily determines the skin deformation region **415** on the face **200** after the PPE **406** is donned by the individual wearer. Further, the processor **102** compares the undeformed and the deformed surfaces **502**, **504** with each other to determine the amount of soft skin tissue deformation “u” after donning the PPE **406**. Similarly, the processor **102** may also determine the soft skin tissue deformation “u” in the skin deformation regions **603**, **605**, **607**.

[0086] The process **800** further moves to a block **814**. At the block **814**, the processor **102** determines the soft skin tissue thickness “t” at the predetermined anatomical positions on the face **200**. More particularly, the processor **102** determines distribution of the soft skin tissue thickness “t” across the skin deformation regions **603**, **605**, **607** and utilizes the same to normalize the deformation distribution. After determining the values of the soft skin tissue thickness “t” at the predetermined anatomical positions, the processor **102** moves to a block **816**. At the block **816**, the processor **102** determines the first ratio “u/t” at the predetermined anatomical positions and adds them all together. However, in some instances, the processor **102** moves to a block **818** if determination of the soft skin tissue thickness “t” at the predetermined anatomical positions is not feasible. At the block **818**, the processor **102** retrieves the stored data for the soft skin tissue thickness “t” at the predetermined anatomical positions based on multiple previous assessments of the individual wearer and the aggregated data from the number of previous wearers. In other words, at the block **818**, the processor **102** receives the data pertaining to the soft skin tissue thickness “t” from the database **108**. The process **800** moves to the block **816** to determine the values of the first ratio “u/t” at the predetermined anatomical positions and add them all together.

[0087] The process **800** further moves to a block **820**. At the block **820**, the processor **102** determines the CT.sub.d value. The CT.sub.d value may be determined by varying the relative skin deformation levels under the PPE **406** and asking the wearer to rate how much pressure is perceived and how comfortable these displacements are for the PPE **406** in use. After determining the CT.sub.d value, the process **800** moves to a block **822**. At the block **822**, the CM is computed by using Equation 2. However, in some cases, the process **800** moves to a block **824** if the determination of the CT.sub.d value is not feasible. At the block **824**, the processor **102** receives the CT.sub.d value from a previous comfort trial with same type of wearers. The process **800** then moves to the block **822** to determine the CM by using Equation 2.

[0088] The process **800** then moves to a block **826**. At the block **826**, the processor **102** determines the PPT values at the predetermined anatomical positions. After determining the PPT values at the predetermined anatomical positions, the process **800** moves to a block **828**. At the block **828**, the processor **102** computes the CMP by using the PPT values in Equation 3. However, in some cases,

the process **800** moves to a block **830** if the determination of the PPT values is not feasible. At the block **830**, the processor **102** receives the PPT values at the predetermined anatomical positions from the database **108**. After receiving the PPT values, the process **800** moves to the block **828** to determine the CMP by using the PPT values in Equation 3.

[0089] Further, the process **800** moves to a block **832**. At the block **832**, the output module **104** provides the notification corresponding to the CMP that is determined by the processor **102**. The notification corresponding to the CMP may be provided to the individual wearer, the PPE selector, the PPE designer/manufacturer, and/or the control station. In some embodiments, the output module **104** may generate a visual notification of the value of the CMP on a display panel. In some embodiments, the output module **104** may generate an audible signal to announce the value of the CMP by using a speaker. In some other embodiments, the output module **104** may generate a printed report summary of the CMP.

[0090] Referring to FIG. 9, a flowchart for a process **900** for determining the scaling effectiveness factor of the PPE **406** is illustrated. The process **900** is embodied as a logic/algorithm implemented by the processor **102** and may be stored in the memory **106** of the system **100**.

[0091] The processor **102** is configured to receive a raw point cloud data to automate contour data measurement. It is assumed that all point clouds are appropriately registered to each other so that direct comparisons can be made between point clouds. Registration can be done via the iterative closest point algorithm, or a similar registration technique.

[0092] The process **900** begins operation at a block **901**. The process **900** moves from the block **901** to a block **902**. At the block **902**, the processor **102** receives a first point cloud representing measurements of the head **210** of the individual wearer with the PPE **406**. At a block **904**, the processor **102** receives a second point cloud representing measurements of the head **210** without the PPE **406**. The head **210** may be scanned by the 3D scanner **110** to take the measurements. At a block **906**, the processor **102** receives an external point cloud of the PPE **406** from the 3D scanner **110**. At a block **908**, the processor **102** receives an internal point cloud of the PPE **406** from the 3D scanner **110**.

[0093] Further, at a block **910**, the processor **102** receives data that is determined at the blocks **902**, **906**. More particularly, at the block **910**, the processor **102** receives the first point cloud and the exterior point cloud from the blocks **902**, **906**, respectively. At the block **910**, the processor **102** is configured to segment the first point cloud by using the exterior point cloud as an archetype. By segmentation operation, the first point cloud is split into two point clouds, i.e., a third point cloud related to the PPE **406** that conforms to the face **200** and a fourth point cloud related to the remaining structure of the head **210** without the PPE **406**. In some embodiments, the segmentation operation can be done in a number of ways, such as using a color threshold approach from a Red Green Blue (RGB) point cloud or template matching.

[0094] The process **900** then moves from the block **910** to a block **912**. At the block **912**, the processor **102** discards the fourth point cloud, and processes only the third point cloud. Further, the process **900** moves from the block **912** to a block **914**. At the block **914**, the processor **102** receives data pertaining to the second point cloud and the third point cloud from the blocks **904**, **912**, respectively. At the block **914**, the processor **102** determines a first minimum distance between the second point cloud and the third point cloud. The process **900** then moves from the block **914** to a block **916**. At the block **916**, the processor **102** determines a first thickness of the PPE **406** based on the first minimum distance calculated at the block **914**.

[0095] Furthermore, at a block **918**, the processor **102** receives data from the blocks **906**, **908**. More particularly, at the block **918**, the processor **102** receives the exterior point cloud and the interior point cloud from the blocks **906**, **908**, respectively. At the block **918**, the processor **102** determines a second minimum distance between the exterior point cloud and the interior point cloud. The process **900** then moves from the block **918** to a block **920**. At the block **920**, the processor **102** determines a second thickness of the PPE **406** based on the second minimum

distance calculated at the block **918**.

[0096] Further, at a block **922**, the processor **102** receives data from the blocks **916**, **920**. More particularly, at the block **922**, the processor **102** receives the first thickness and the second thickness of the PPE **406** from the blocks **916**, **920**, respectively. The processor **102** further compares the first thickness with the second thickness of the PPE **406** to determine the sealing effectiveness factor of the PPE **406** for the individual wearer.

[0097] If the sealing effectiveness factor is high, the process **900** moves from the block **922** to a block **924**. At the block **924**, the processor **102** sends a command to the output module **104** to notify a value of the high sealing effectiveness factor. On the other hand, if the sealing effectiveness factor is low, the process **900** moves from the block **922** to a block **926**. At the block **926**, the processor **102** sends a command to the output module **104** to notify a value of the low sealing effectiveness factor and regions of low sealing quality. In some embodiments, the output module **104** may notify the value of high or low sealing effectiveness factor using a display panel or a speaker. In other embodiments, the output module **104** may generate the value of high or low sealing effectiveness factor in a printed report summary. After the processor **102** determines the sealing effectiveness factor, the process **900** ends the operation at a block **928**.

[0098] Referring to FIG. **10**, a flowchart for a method **1000** for determining PPE comfort for the individual wearer is illustrated. At step **1002**, the method **1000** includes defining the first anatomical shape data representative of the anatomical area of the individual wearer prior to donning the PPE **406**. At step **1004**, the method **1000** includes defining the second anatomical shape data representative of the anatomical area of the individual wearer after donning the PPE **406**. The steps **1004**, **1006** of defining the first anatomical shape data and the second anatomical shape data includes scanning the anatomical area of the individual wearer prior to donning the PPE **406** and after donning the PPE **406** using the at least one 3D scanner **110**. At step **1006**, the method **1000** includes comparing the first anatomical shape data with the second anatomical shape data.

[0099] At step **1008**, the method **1000** includes determining the soft skin tissue deformation “u” at the plurality of predetermined anatomical positions based on the comparison between the first anatomical shape data and the second anatomical shape data. The plurality of predetermined anatomical positions are generated based on at least two dynamic movements performed by the individual wearer.

[0100] At step **1010**, the method **1000** includes determining the CT.sub.d value based on the soft skin tissue deformation “u” at the plurality of predetermined anatomical positions. At step **1012**, the method **1000** includes determining the PPT value at the plurality of predetermined anatomical positions. At step **1014**, the method **1000** includes determining the CMP based on the PPT value and the CT.sub.d values. Further, the method **1000** includes determining the soft skin tissue thickness “t” at the plurality of predetermined anatomical positions. In some embodiments, the processor **102** is configured to retrieve stored data for the soft skin tissue thickness “t” at the plurality of predetermined anatomical positions based on at least one of the previous assessment of the individual wearer and the aggregated data from the plurality of previous wearers. Moreover, the method **1000** includes determining the first ratio “u/t” between the determined soft skin tissue deformation “u” and the soft skin tissue thickness “t” at the plurality of predetermined anatomical positions. Further, the method **1000** includes determining the CMP based on the PPE value, the CT.sub.d values, and the first ratio “u/t”.

[0101] The method **1000** also includes correlating the soft skin tissue deformation “u” at the plurality of predetermined anatomical positions for each individual wearer and the pressure applied by the PPE **406** at the plurality of predetermined anatomical positions for each individual wearer. The method **1000** further includes aggregating the correlation for generating the CM.sub.PRE. Moreover, the method **1000** includes comparing the CMP to the CM.sub.PRE. At step **1016**, the method **1000** includes generating the notification corresponding to the CMP.

[0102] According to an embodiment, the method **1000** also includes defining, by the processor **102**,

the plurality of predetermined setting ranges for adjusting the at least one adjustable feature on the PPE **406**. The plurality of predetermined setting ranges are defined based on at least one of the fit of the PPE **406** and the comfort of the PPE **406**. The method **1000** further includes notifying the individual wearer of the predetermined setting range from the plurality of predetermined setting ranges for adjusting the at least one adjustable feature.

[0103] In some embodiments, the method **1000** includes the step of defining the first PPE shape data before donning the PPE **406** by the individual wearer and the second PPE shape data after donning the PPE **406** by the individual wearer. Further, the method **1000** includes determining the first contour data of the PPE **406** based on the first PPE shape data. The method **1000** also includes determining the second contour data based on the second PPE shape data and the second anatomical shape data. Further, the method **1000** includes comparing the first contour data with the second contour data. Furthermore, the method **1000** includes generating the notification for the individual wearer based on the comparison between the first contour data and the second contour data. The method **1000** also includes providing the notification indicative of the fit of the PPE **406** on the individual wearer. The method **1000** further includes providing the notification on the color-coded display for overlaying one or more colors indicative of the fit of the PPE **406**.

[0104] In one embodiment, the method **1000** includes accessing information pertaining to the plurality of PPE sizes for the PPE type. The method **1000** also includes comparing, for the individual wearer, the first anatomical shape data with the second anatomical shape data. The method **1000** further includes predicting the PPE size for the individual wearer from the plurality of PPE sizes based on the comparison between the first anatomical shape data with the second anatomical shape data. Furthermore, the method **1000** includes generating the notification for the individual wearer pertaining to the predicted PPE size.

[0105] In another embodiment, the method **1000** includes accessing information pertaining to the plurality of PPE types and the plurality of PPE sizes from the predetermined library to predict, for the individual wearer, at least one of the PPE type from the plurality of PPE types and the PPE size from the plurality of PPE sizes.

[0106] Unless otherwise indicated, all numbers expressing feature sizes, amounts, and physical properties used in the specification and claims are to be understood as being modified by the term “about”. Accordingly, unless indicated to the contrary, the numerical parameters set forth in the foregoing specification and attached claims are approximations that can vary depending upon the desired properties sought to be obtained by those skilled in the art utilizing the teachings disclosed herein.

[0107] Although specific embodiments have been illustrated and described herein, it will be appreciated by those of ordinary skill in the art that a variety of alternate and/or equivalent implementations can be substituted for the specific embodiments shown and described without departing from the scope of the present disclosure. This application is intended to cover any adaptations or variations of the specific embodiments discussed herein. Therefore, it is intended that this disclosure be limited only by the claims and the equivalents thereof.

Claims

1. A method for determining personal protective equipment (PPE) fit for an individual wearer, the method comprising: prior to donning a PPE, defining (i) a first anatomical shape data representative of an anatomical area of the individual wearer; and (ii) a first PPE shape data; after donning the PPE, defining (i) a second anatomical shape data representative of the anatomical area of the individual wearer; and (ii) a second PPE shape data; comparing the first anatomical shape data with the second anatomical shape data; determining a first contour data of the PPE based on the first PPE shape data; determining a second contour data based on the second PPE shape data and the second anatomical shape data; comparing the first contour data with the second contour

data; and generating a notification for the individual wearer based on the comparison between the first contour data and the second contour data.

2. The method of claim 1, wherein the steps of defining the first anatomical shape data and the second anatomical shape data further comprises scanning the anatomical area of the individual wearer prior to donning the PPE and after donning the PPE using at least one three-dimensional scanner.

3. The method of claim 1, further comprising: defining, by the processor, a plurality of predetermined setting ranges for adjusting at least one adjustable feature on the PPE, wherein the plurality of predetermined setting ranges are defined based on a fit of the PPE; and generating a notification for a predetermined setting range from the plurality of predetermined setting ranges for adjusting the at least one adjustable feature.

4. The method of claim 1, further comprising determining a soft skin tissue deformation at a plurality of predetermined anatomical positions based on the comparison between the first anatomical shape data and the second anatomical shape data; and, determining a soft skin tissue thickness at the plurality of predetermined anatomical positions.

5. The method of claim 4, further comprising retrieving stored data for the soft skin tissue thickness at the plurality of predetermined anatomical positions based on at least one of a previous assessment of the individual wearer and an aggregated data from a plurality of previous wearers.

6. The method of claim 5, further comprising: determining a displacement comfort threshold (CT.sub.d) value based on the soft skin tissue deformation at the plurality of predetermined anatomical positions; determining a pressure pain threshold (PPT) value at the plurality of predetermined anatomical positions; determining a comfort metric based on the PPT values and the CT.sub.d values; determining a first ratio between the determined soft skin tissue deformation and the soft skin tissue thickness at the plurality of predetermined anatomical positions; and determining the comfort metric based on the PPT values, the CT.sub.d values, and the first ratio.

7. The method of claim 6, further comprising comparing the individual wearer comfort metric to a predicted wearer comfort metric.

8. The method of claim 7, further comprising: correlating a soft skin tissue deformation at a plurality of predetermined anatomical positions for each wearer and a pressure applied by the PPE at the plurality of predetermined anatomical positions for each wearer; and aggregating the correlation for generating the predicted wearer comfort metric.

9. The method of claim 1, further comprising a step of generating the plurality of predetermined anatomical positions based on at least two dynamic movements performed by the individual wearer.

10. The method of claim 1, further comprising providing the notification indicative of a fit of the PPE on the individual wearer.

11. The method of claim 10, further comprising providing the notification on a color-coded display for overlaying one or more colors indicative of the fit of the PPE.

12. The method of claim 1, further comprising: accessing information pertaining to a plurality of PPE sizes for a PPE type; comparing, for the individual wearer, the first anatomical shape data with the second anatomical shape data; predicting a PPE size for the individual wearer from the plurality of PPE sizes based on the comparison between the first anatomical shape data and the second anatomical shape data; and generating a notification for the individual wearer pertaining to the predicted PPE size.

13. The method of claim 1, further comprising accessing information pertaining to a plurality of PPE types and a plurality of PPE sizes from a predetermined library to predict, for the individual wearer, at least one of a PPE type from the plurality of PPE types and a PPE size from the plurality of PPE sizes.

14. A system for determining PPE fit for an individual wearer, the system comprising: a processor configured to: prior to donning a PPE, define (i) a first anatomical shape data representative of an

anatomical area of the individual wearer; and (ii) a first PPE shape data; after donning the PPE, define (i) a second anatomical shape data representative of the anatomical area of the individual wearer; and (ii) a second PPE shape data; compare the first anatomical shape data with the second anatomical shape data; determine a first contour data of the PPE based on the first PPE shape data; determine a second contour data based on the second PPE shape data and the second anatomical shape data; compare the first contour data with the second contour data; and an output module communicably coupled with the processor, wherein the output module is configured to provide a notification corresponding to the comparison between the first contour data and the second contour data.

15. The system of claim 14, wherein the plurality of predetermined anatomical positions are generated using a static modeling module.

16. The system of claim 14, wherein the plurality of predetermined anatomical positions are generated using a dynamic modeling module.

17. The system of claim 14, wherein the first anatomical shape data and the second anatomical shape data is defined based on scanning the anatomical area of the individual wearer prior to donning the PPE and after donning the PPE using at least one three-dimensional scanner.

18. The system of claim 14, wherein the processor is further configured to: define a plurality of predetermined setting ranges for adjusting at least one adjustable feature on the PPE, wherein the plurality of predetermined setting ranges are defined based on a fit of the PPE; and generating a notification for a predetermined setting range from the plurality of predetermined setting ranges for adjusting the at least one adjustable feature.

19. The system of claim 14, wherein the processor is further configured to determine a soft skin tissue thickness at a plurality of predetermined anatomical positions based on the comparison between the first anatomical shape data and the second anatomical shape data.

20. The system of claim 19, wherein the processor is further configured to retrieve stored data for the soft skin tissue thickness at the plurality of predetermined anatomical positions based on at least one of a previous assessment of the individual wearer and an aggregated data from a plurality of previous wearers.

21. The system of claim 19, wherein the processor is further configured to: determine a first ratio between the determined soft skin tissue deformation and the soft skin tissue thickness at the plurality of predetermined anatomical positions; and determine the fit based on the first ratio.

22. The system of claim 14, wherein the processor is further configured to compare the individual wearer fit to a predicted wearer fit.

23. The system of claim 22, wherein the processor is further configured to: correlate a soft skin tissue deformation at a plurality of predetermined anatomical positions for each wearer and a pressure applied by the PPE at the plurality of predetermined anatomical positions for each wearer; and aggregate the correlation for generating the predicted wearer fit.

24. The system of claim 14, wherein the processor is further configured to generate the plurality of the anatomical positions based on at least two dynamic movements performed by the individual wearer.

25. The system of claim 14, wherein the output module is configured to provide the notification indicative of a fit of the PPE on the individual wearer.

26. The system of claim 25, wherein the output module includes a color-coded display for overlaying one or more colors indicative of the fit of the PPE.

27. The system of claim 14, wherein the processor is further configured to: access information pertaining to a plurality of PPE sizes for a PPE type; compare, for the individual wearer, the first anatomical shape data with the second anatomical shape data; predict a PPE size for the individual wearer from the plurality of PPE sizes based on the comparison between the first anatomical shape data and the second anatomical shape data; and generate a notification for the individual wearer pertaining to the predicted PPE size.

28. The system of claim 14, wherein the processor is further configured to access information pertaining to a plurality of PPE types and a plurality of PPE sizes from a predetermined library to predict, for the individual wearer, at least one of a PPE type from the plurality of PPE types and a PPE size from the plurality of PPE sizes.
