



US 20250275523A1

(19) **United States**(12) **Patent Application Publication**
LAWYER et al.(10) **Pub. No.: US 2025/0275523 A1**(43) **Pub. Date: Sep. 4, 2025**(54) **HABITAT LIGHTING ASSEMBLY****Publication Classification**(71) Applicant: **EcoTech, LLC**, Bethlehem, PA (US)(72) Inventors: **Justin LAWYER**, Bethlehem, PA (US);
Mark Lindenmoyer, Coopersburg, PA (US); **Christian Clough**, Bethlehem, PA (US); **Timothy Marks**, Northampton, PA (US); **Patrick Clasen**, Allentown, PA (US)(51) **Int. Cl.****A01K 63/06** (2006.01)**A01K 1/00** (2006.01)**F21V 8/00** (2006.01)(52) **U.S. Cl.**CPC **A01K 63/065** (2013.01); **A01K 1/0052**(2013.01); **A01K 1/0058** (2013.01); **G02B****6/0036** (2013.01); **G02B 6/0055** (2013.01);**G02B 6/0085** (2013.01)(21) Appl. No.: **19/212,833**(22) Filed: **May 20, 2025****Related U.S. Application Data**


(63) Continuation of application No. 18/233,498, filed on Aug. 14, 2023, now Pat. No. 12,302,874, which is a continuation of application No. 17/704,617, filed on Mar. 25, 2022, now Pat. No. 11,723,346, which is a continuation of application No. 16/392,926, filed on Apr. 24, 2019, now Pat. No. 11,284,606.

(60) Provisional application No. 62/661,715, filed on Apr. 24, 2018.

(57)

ABSTRACT

A lighting assembly includes a light guide having opposite first and second major surfaces and at least one edge surface extending between the first and second major surfaces, a solid-state light source arranged to emit light into the edge surface of the light guide, and a plurality of integrated optical elements associated with the first major surface to redirect the light emitted by the solid-state light source. The lighting assembly may further include an air circulation device and a heat transfer system configured to transfer heat generated by the solid-state lighting source to a flow of air generated by the air circulation device. The solid-state light source may include light-emitting diodes, laser diodes, and/or organic light emitting diodes configured to produce multiple colors. Also provided is a habitat including the lighting assembly, and related methods.






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11

FIG. 12




FIG. 13




FIG. 14




FIG. 15

HABITAT LIGHTING ASSEMBLY**CLAIM(S) OF PRIORITY AND
CROSS-REFERENCE TO RELATED
APPLICATION(S)**

[0001] This application is a continuation of U.S. patent application Ser. No. 18/233,498 filed Aug. 14, 2023, now U.S. Pat. No. 12,302,874, which is a continuation of U.S. patent application Ser. No. 17/704,617 filed Mar. 25, 2022, now U.S. Pat. No. 11,723,346, which is a continuation of U.S. patent application Ser. No. 16/392,926 filed Apr. 24, 2019, now U.S. Pat. No. 11,284,606, which claims the benefit of priority of U.S. Provisional Application No. 62/661,715 filed Apr. 24, 2018, the complete disclosure of which is incorporated herein by reference.

FIELD OF THE INVENTION

[0002] This invention relates to a habitat lighting assembly, a habitat including a lighting assembly, and related methods.

BACKGROUND

[0003] Animal and plant habitats, for example aquariums, terrariums, green houses, etc., are environments housing one or more species of flora and/or fauna, such as fish, invertebrates, amphibians, marine mammals, turtles, plants or any combination thereof. These species require diligent care which includes specific control of environmental conditions within the habitats. Environmental conditions such as temperature, light wavelength and intensity, salinity, and flow control of air or water inside the habitat are regulated to accommodate for the sustainability or growth of the particular species living therein. Optimum conditions will vary from species to species.

[0004] One component of controlling the environmental conditions in a habitat is the amount and type of light. Standard lighting units typically utilize light emitting diodes (LEDs), and fluorescent or metal halide bulbs that produce light at a specific spectrum and intensity. These lights may be hung above the habitat or be part of a hood or other unit which connects directly to the habitat. Typical lighting units are designed to shine light downward to permit a user to observe the habitat and to sustain life within the habitat. LED lighting units are desirable because the spectrum they output can be adjusted using combinations of discrete colors.

[0005] A problem with standard lighting LED units is that the polychromatic light sources of typical lighting units each act as an independent "point light sources," which, when refracted through the moving surface of the water, create bands of light called "caustics" of different colors that are separated from each other. The separated caustics can lead to an effect in the habitat that can act as a distraction to the viewer. One way of reducing these banded caustics is to increase the number of LEDs or add a diffuser; however, doing so can increase energy costs, cause the lighting fixture to become overly large, and/or cause overheating of the lighting unit and/or of the habitat.

[0006] Further, the amount of light required by certain habitat species for sustaining life, such as through photosynthesis, can be relatively high, requiring a high energy density for the LEDs. LEDs operated at high power can overheat. As LEDs become hotter, their efficacy decreases,

so that less light is provided to the habitat species for survival functions such as photosynthesis.

SUMMARY OF THE INVENTION

[0007] The disclosed invention is a LED lighting assembly for a habitat that has a light guide assembly having a plurality of integrated optical elements that diffuse the emitted light in order to eliminate caustics, particularly in an aquarium habitat.

[0008] According to a first aspect of the invention, a habitat lighting assembly includes a light guide having opposite first and second major surfaces and at least one edge surface extending between the first and second major surfaces. A solid-state light source is arranged to emit light into the edge surface of the light guide. A plurality of integrated optical elements is associated with the first major surface for redirecting the light from the solid-state light source.

[0009] According to a second aspect of the invention, a habitat lighting assembly includes at least an outer housing, an air circulation device configured to generate a flow of air into the outer housing through an air intake opening and out of the outer housing through an air discharge opening of the outer housing, a light guide comprising opposite first and second major surfaces and at least one edge surface extending between the first and second major surfaces, a solid-state light source arranged to emit light into the edge surface of the light guide, a plurality of integrated optical elements associated with the first major surface configured to redirect the light emitted by the solid-state light source, and a heat transfer system configured to transfer heat generated by the solid-state lighting source to the flow of air generated by the air circulation device.

[0010] A third aspect of the invention is a habitat lighting assembly including at least a light guide comprising opposite first and second major surfaces and at least one edge surface extending between the first and second major surfaces, a solid-state light source arranged to emit light into the edge surface of the light guide and comprising light-emitting diodes, laser diodes, organic light emitting diodes, or any combination thereof configured to produce multiple colors, and a plurality of integrated optical elements associated with the first major surface configured to direct light emitted by the solid-state light source upward toward the light reflector and/or downward.

[0011] A fourth aspect of the invention is a combination of a habitat and the habitat lighting assembly of any one of the first, second, or third aspects.

[0012] Other aspects of the invention, including apparatus, devices, kits, habitats, combinations, methods, processes, and the like which constitute part of the invention, will become more apparent upon reading the following detailed description of the exemplary embodiments.

BRIEF DESCRIPTION OF THE DRAWING(S)

[0013] The accompanying drawings are incorporated in and constitute a part of the specification. The drawings, together with the general description given above and the detailed description of the exemplary embodiments and methods given below, serve to explain the principles of the invention. In such drawings:

[0014] FIG. 1 is a perspective view of a habitat equipped with a lighting assembly according to an exemplary embodiment;

[0015] FIG. 2 is a top perspective view of the lighting assembly of FIG. 1;

[0016] FIG. 3 is bottom perspective view of the lighting assembly of FIG. 1;

[0017] FIG. 4 is a top perspective view of the lighting assembly of FIG. 1 with a housing of the lighting assembly partially cut away;

[0018] FIG. 5 is a top perspective view of the lighting assembly of FIG. 1 in a partially disassembled state with the light assembly housing not shown;

[0019] FIG. 6 is a side perspective, partially cut-away view of the lighting assembly of FIG. 1;

[0020] FIG. 7 is a side perspective, partially cut-away view of parts of the lighting assembly of FIG. 1;

[0021] FIG. 8 is a top perspective view of a light guide of the lighting assembly of FIG. 1;

[0022] FIG. 9 is an enlarged fragmented view of oval 9 of FIG. 7;

[0023] FIG. 10 is a cross-sectional view of the lighting assembly of FIG. 1 taken along sectional line 10-10 of FIG. 5;

[0024] FIG. 11 is a horizontal cross section of the lighting assembly of FIG. 1 taken along sectional line 11-11 of FIG. 10;

[0025] FIG. 12 is a top perspective, partially disassembled view of a lighting assembly according to another embodiment of the invention;

[0026] FIG. 13 is an enlarged fragmented view of a light guide according to another embodiment of the invention;

[0027] FIG. 14 is an enlarged fragmented view of a light guide according to still another embodiment of the invention; and

[0028] FIG. 15 is a perspective view of a habitat equipped with a lighting assembly according to another exemplary embodiment.

DETAILED DESCRIPTION OF THE EXEMPLARY EMBODIMENTS AND EXEMPLARY METHODS

[0029] Reference will now be made in detail to the exemplary embodiments and exemplary methods as illustrated in the accompanying drawings, in which like reference characters designate like or corresponding parts throughout the drawings. It should be noted, however, that the invention in its broader aspects is not necessarily limited to the specific details, representative materials and methods, and illustrative examples shown and described in connection with the exemplary embodiments and exemplary methods.

[0030] FIG. 1 depicts a habitat 15 according to an exemplary embodiment of the invention. In a particularly preferred embodiment, the habitat 15 is an aquatic habitat such as a marine aquarium (e.g., fresh water or salt water), though aspects of the invention may extend to other embodiments using non-aquatic habitats. For example, the lighting assemblies embodied and described herein can be used as a light source for a wide variety of habitats, including those containing flora and/or fauna, such as fish, invertebrates, amphibians, marine mammals, turtles, plants or any combination thereof.

[0031] The habitat 15 includes a container or tank 16 having a pair of opposite side walls 17 and 18 spaced apart

from one another and a pair of spaced end walls 19 and 20 extending between opposite side edges of the side walls 17 and 18. The tank 16 has a bottom wall 22 and a top opening 24 surrounded and defined by the top edges of the walls 17, 18, 19, and 20 to provide a habitat enclosure. A cover, such as sliding panels 23, may be placed over all or a portion of the top opening 24. The cover 23 may be either integral with or connected to the tank 16. The cover 23 may be transparent or provided with openings, such as a screen or grate. Though depicted as having a standard rectangular cross-sectional shape, the tank 16 may have different sizes, shapes, and configurations while including any number of walls. The walls 17-20 may be flat as shown, or they may be curved. The walls 17-20 of the tank 16 may be made from a variety of materials, especially transparent materials, including glass or plastics such as high-strength acrylics.

[0032] Components, such as pumps, fans, filters, etc., may be attached to or used in connection with the habitat 15 to alter or control the environment within the tank 16 or other type of enclosure. Depending on the organisms living in the habitat 15, different combinations of components may be appropriate. In the exemplary embodiment illustrated in FIG. 1, the habitat 15 includes multiple pumps 26, with each of the pumps 26 located on a respective one of the side walls 17 and 18 and the end walls 19 and 20 in the illustrated embodiment. The habitat 15 may also include a filter 28 and a heater 29. These components may collectively affect specific environmental conditions to the habitat 15. For example, the pumps 26 can create different flow types to mimic natural tides.

[0033] A lighting assembly 30 is suspended by suspension system 31, which is illustrated in FIG. 1 as comprising cables anchored to the ceiling (not shown). Alternatively, a floor stand or a tank-mounted bracket can be used to suspend the lighting assembly 30, or the lighting assembly 30 can be connected to, supported on, or integrated into the top of the tank 16. FIG. 15 shows one or more brackets 31a attachable to the top or sides of the tank 16 to suspend the lighting assembly 30 over the top of the tank 16.

[0034] FIGS. 2-10 depict an exemplary embodiment of the lighting assembly 30. The lighting assembly 30 includes an outer housing 32 that may be made of metal, plastic, composite, or other material. As best shown in FIG. 2, the outer housing 32 includes an upper surface 33, which can be part of a cover separable from and reattachable to the remainder of the outer housing 32. The upper surface/cover 33 has an air intake opening 33a embodied as a circular opening. As best shown in FIG. 3, the outer housing 32 further includes a lower surface or base 34 with a light-transmissive opening 34a embodied as a rectangle. The light-transmissive opening 34a may be an empty space or may have a transparent window. Side walls and end walls 35 extend between the upper surface/cover 33 and the lower surface/base 34. The end walls 35 include air discharge openings 35a. An air circulation device such as an impeller or fan 36 is positioned below the air intake opening 33a. The fan 36 draws air into the outer housing 32 through the air intake opening 33a, and the air exits the outer housing 32 through the air discharge openings 35a. The fan 36 may be mounted, such as with a bracket (not shown), to the cover 33.

[0035] As best shown in FIGS. 6, 8, 10, and 11, the lighting assembly 30 includes a light guide 40 embodied as a plate having a first major surface 41 (FIG. 10) facing

upward and a second major surface **42** (FIG. **10**) facing downward and opposite to the first major surface **41**. The first and second major surfaces **41** and **42** are planar and parallel to one another. The first and second major surfaces **41** and **42** are parallel to one another, spaced apart, and define the thickness of the light guide **40**. The thickness is less than the length and width of the major surfaces **41** and **42**. Preferably, the thickness is uniform (with the possible exception of locations of optical elements **48** described below) over the entire length and width of the major surfaces **41** and **42**. For example, the thickness may be in a range of 3.0 mm to 8.0 mm, such as 6 mm.

[0036] As best shown in FIGS. **8** and **11**, the light guide **40** includes side (lateral) edge surfaces **43** and **44** extending between the first and second major surfaces **41** and **42**, and end edge surfaces **45** and **46** extending between the first and second major surfaces **41** and **42** and perpendicular to the side edge surfaces **43** and **44**. End edge surfaces **45** and **46** of the light guide **40** are parallel to one another and spaced apart from one another by the length of the light guide **40**. The side edge surfaces **43** and **44** are parallel to one another and spaced apart from one another by a width of the light guide **40**.

[0037] While the light guide **40** is shown generally rectangular in shape, it should be understood that the light guide **40** may possess alternative shapes, such as that of a square or another polygonal shape. Any one or more of the edge surfaces **43**, **44**, **45**, and/or **46** of the light guide **40** may be curved or non-linear. The thickness of the light guide **40** may vary so as to be non-uniform. Although the lighting assembly **30** is shown with a single light guide **40**, it should be understood that the lighting assembly **30** alternatively may be provided with multiple light guides **40** layered one on top of another and/or in side-by-side arrangement.

[0038] The light guide **40** is preferably made of an optically transmissive material. Exemplary materials include plastics such as acrylics (e.g., polymethylmethacrylate PMMA), polycarbonates, and/or liquid silicone rubber (LSR). The light guide **40** may rest on the base **34** of the outer housing **32** or otherwise be secured to the outer housing **32**.

[0039] First and second light source holders **50** and **51** are spaced apart from one another, one opposite sides of the light guide **40** adjacent to the side edge surfaces **43** and **44**, respectively, as best shown in FIGS. **10** and **11**. For the purposes of this embodiment, the first and second light source holders **50** and **51** are identical to one another, although it should be understood that they may differ. The light source holders **50** and **51** may be supported on or attached to a support base **63** (FIG. **9**). Alternatively, the light source holders **50** and **51** may be attached directly to the light guide **40** or to the outer housing **32** using, for example, mechanical fasteners, adhesive, bonding, welding, etc. The light source holders **50** and **51** may be part of a frame surrounding the light guide **40**. The light source holders **50** and **51** may be made of metal (e.g., aluminum), plastic, or another material. As best shown in FIG. **9**, the first light source holder **50** can include light reflective linings **50a**. The light reflective linings **50a** can be made of cut pieces of reflective material, such as paper, coated paper, plastic, metal coated plastic, metal foil, etc., or a combination thereof. The surfaces of the light reflective linings **50a**

preferably are white or silver. Although not shown, the second light source holder **51** can include similar light reflective linings.

[0040] As best shown in FIG. **10**, the first and second light source holders **50** and **51** each have a U-shaped cross-section/profile with an opening extending along their respective lengths to face the side edge surfaces **43** and **44**, respectively, of the light guide **40**. One or more first light sources **52** are arranged along the first light source holder **50** so as to be adjacent to and emit and introduced light into the light guide **40** through the side edge surface **43** of the light guide **40**. One or more second light sources **53** are arranged along the opposite second light source holder **51** so as to be adjacent to and emit and introduced light into the light guide **40** through the side edge surface **44** of the light guide **40**. The light sources **52** and **53** are preferably solid-state light emitters, such as semiconductor light emitting diodes (LEDs), laser diodes, and/or organic light emitting diodes (OLEDs).

[0041] The first light source(s) **52** may comprise a plurality of LEDs or other solid-state light emitters mounted on a printed circuit board (PCB) **54** arranged at the opening of the first light source holder **50**. Likewise, the second light source(s) **53** may comprise a plurality of LEDs or other solid-state light emitters mounted on a printed circuit board (PCB) **55** arranged at the opening of the second light source holder **51**. Attachment of the PCBs **54** and **55** to the first and second light source holders **50** and **51** and/or to the light guide **40** may be accomplished using, for example, mechanical fasteners, adhesives, bonding, soldering, welding, etc.

[0042] The first light source **52** and the second light source **53** are arranged to emit light into the side edge surfaces **43** and **44**, respectively, so that the light propagates along the light guide **40** between the first and second major surfaces **41** and **42** of the light guide **40**. The first light source **52** and the second light source **53** preferably are arranged along substantially the entire length of the side edge surfaces **43** and **44**, respectively, to uniformly direct light into the opposite edge surfaces **43** and **44** of the light guide **40**.

[0043] Alternative arrangements of light sources are possible. For example, the lighting assembly **30** may include fewer or more LEDs in the first and second light sources **52** and **53** than depicted in the drawings. The number of first light source LEDs **52** associated with the side edge surface **43** may be the same as or different than the number of second light source LEDs **53** associated with the side edge **44**. While the light sources **52** and **53** are arranged adjacent opposite side edge surfaces **43** and **44** of the light guide **40** in the exemplary embodiment described above, in an alternative embodiment the light sources **52** and **53** are arranged adjacent the end edge surfaces **45** and **46**. In another alternative embodiment, light sources **52** and **53** and additional light source (not shown) are respectively arranged along the edge surfaces **43**, **44**, **45**, and **46**. In yet another alternative embodiment, the light sources **52** and **53** are arranged along perpendicular edge surfaces, such as edge surfaces **43** and **45**. In still another alternative embodiment, only one of the light sources **52** or **53** is provided and arranged along one of the edge surfaces, e.g., **43**, **43**, **45**, or **46**, with the other three edge surfaces not being associated with adjacent light sources. In a further alternative embodiment, light sources are arranged adjacent three edges surfaces, such as edge surfaces **43**, **44**, and **45**, but not the fourth edge surface, e.g., **46**.

[0044] Desirably, each of the light sources **52** and **53** includes multiple sets of LEDs (or OLEDs, etc.), with each of the LED sets of light sources **52** and **53** including multiple different color light sources, optionally including a white light source. Each color LED may be part of a single channel, so that the LEDs of the light sources **52** and **53** as a group provide a multi-channel light source. The light sources **52** and **53** may emit light in the non-visible spectrum, such as ultraviolet light and/or infrared light, if desired. The light sources **52** and **53** may be capable of emitting light over a range of intensities and wavelengths, or different light sources can be monochromatic or of a dedicated wavelength or intensity. In an exemplary embodiment, the light sources **52** and **53** emit light over ranges of wavelengths that are different or slightly overlap with one another. For example, the first and second light sources **52** and **53** may include different color groups of white, red, green, blue, royal blue, and/or violet. The wavelength of the light sources **52** and **53** may be individually controlled to selectively place them into an on-state or off-state to produce different colors, shades, and intensities of color. Each color group may be separated into an individual channel and controlled separately. Preferably the first and second light sources **52**, **53** are capable of generating light that simulates natural sun light.

[0045] As best shown in FIGS. 4-6 and 10, a light reflector **60** is located adjacent to the upper first major surface **41** of the light guide **40**. The light reflector **60** may be in direct contact with or spaced apart from the first major surface **41**. The light reflector **60** may be a separate component from the light guide **40**, such as a plate. Alternatively, the light reflector **60** may be a coating or film applied on the light guide **40**. Preferably, the light reflector **60** extends at least the entire width and length of the light guide **40**. The light reflector **60** may be white, specularly reflective, or diffusely reflective, depending upon the desired light output. The light reflector **60** may be made of cut pieces of reflective material, such as paper, coated paper, plastic, metal coated plastic, metal foil, etc., or a combination thereof.

[0046] As best shown in FIGS. 3, 6, and 10, a diffuser **62**, such as in the form of a plate, film, or coating, optionally is positioned adjacent to the lower second major surface **42**, i.e., under the light guide **40**. The diffuser **62** preferably is coextensive with the light-transmissive opening **34a**. The diffuser **62** is selected to diffuse the light emitted through the second major surface **42** to provide a more uniform, homogeneous light output distribution. The diffuser **62** provides the secondary benefit of concealing the integrated optical elements **48** (discussed further below). The diffuser **62** can be, for example, a plastic, quartz, frosted, or translucent material or materials. An example of a suitable diffuser is a G-Series Glare Control Diffuser of Brightview Technologies.

[0047] At least one, and optionally both, of the first and second major surfaces **41** and **42** include integrated optical elements **48**. For example, FIG. 8 illustrates the integrated optical elements **48** integrated into the first major surface **41**. The integrated optical elements **48** have a structure suitable for directing light, such as upward from the solid-state light sources **52** and **53** into the light reflector **60**, which reflects the light downward to pass through the optional diffuser **62** and the light-transmissive opening **34a**. The integrated optical elements **48** may also or alternatively include structure suitable for directing light from the solid-state light sources **52** and **53** directly downward to pass through the optional

diffuser **62** and the light-transmissive opening **34a**. The integrated optical elements **48** may be convex, concave, cylindrical, prismatic, or a combination thereof. The integrated optical elements **48** may be arrayed in rows and columns. The density of integrated optical elements **48** can be uniform or varied over the first major surface **41** of the light guide **40**. The integrated optical elements **48** may be raised structures extending upward from the plane of the first major surface **41** or depressed structures extending downward below the plane of the first major surface **41**. The elements **48** may be a physical structure in the light guide **40**. For example, the elements **48** can be a screen-printed structure painted on the light guide **40** or a particulate material embedded in the light guide **40**.

[0048] The integrated optical elements **48** may be identical in shape and/or size to one another or may differ in shape and/or size from one another. For example, the integrated optical elements **48** may have an effective diameter of 1 mm to 1000 mm. In a particularly exemplary embodiment best illustrated in FIG. 8, the integrated optical elements **48** have the appearance of dots or dimples. The integrated optical elements **48** can be formed in or on the light guide **40** in any suitable manner, such as molding, embossing, screen printing, drilling, three-dimensional printing, etching, etc. While it is preferred that the integrated optical elements **48** have a three-dimensional structure extending into or out of the light guide **40**, the elements **48** may be formed by imprinting or otherwise depositing a material onto first major surface **41**, such as by screen printing, ink jet printing, etc.

[0049] FIG. 13 is an enlarged fragmented view of a light guide **40a** having integrated optical elements **48a** configured as cones that protrude outwardly from the surface of guide **40a**. The tops of the cones of the integrated optical elements **48a** may be flat or curved (e.g., convex). FIG. 14 is an enlarged fragmented view of a light guide **40b** having integrated optical elements **48b** configured as conical recesses that protrude inwardly from the surface of light guide **40b**. The bottoms of the conical recesses of the integrated optical elements **48b** may be flat or curved (e.g., concave). Examples of other integrated optical elements **48** are described in U.S. Patent Publication No. 2013/0314944 (which uses the terms “deformities” and “optical deformities” and the like), the complete disclosure of which is incorporated herein by reference.

[0050] A representative material that may be used as the light guide **40** is a PMMA clear light guiding prismatic plate LGP provided by Jungbecker. The LGP decouples light which is fed into the light guide from the edges across the surface area by the use of the integrated micropismatic optics **48**. The LGP uses reflection and refraction of the micropisms to direct and “deglare” light.

[0051] Without wishing to be necessarily bound by any theory, it is believed that the integrated optical elements **48**, **48a**, **48b** of the light guide **40** cause light entering the light guide **40** to experience total internal reflection (“TIR”). The integrated optical elements **48**, **48a**, **48b** interact with the light entering through the edge surfaces of the light guide **40** and propagating therethrough to redirect and uniformly distribute the light so that it is emitted through the second major surface **42**. The reflector **60** causes any light which is directed upward by the integrated optical elements **48**, **48a**, **48b** to reflect downward and emitted through the second major surface **42**. At the same time, the integrated optical elements **48**, **48a**, **48b** reduce if not eliminate the color bands

by homogeneously blending the light so that it is emitted as an incoherent and blended light appearing as a very diffused uniform spectrum. As a result, the need for an excess number of LEDs is avoided, which lowers manufacturing and operating costs and reduces the amount of heat generated by the LED light sources **52** and **53**.

[0052] In order to create a close approximation of a natural environment, the lighting assembly **30** may include a controller having the capability of providing diverse outputs such as different light intensities, different light patterns, different light colors, etc. Examples of different operating modes that may be selected by varying the outputs include night, sunrise, day, sunset, lunar colors, storms, and solar cycles. The lighting assembly **30** may be provided with a user interface (not shown) to allow programming of the operating modes. Alternatively, operating modes may be pre-programmed into the assembly **30** or may be remotely programmed by communicating with a receiver (not shown), such as a wireless communication device (e.g., Wi-Fi module), of the assembly **30**.

[0053] FIGS. **5** and **6** depict a block **64** housing, for example, controllers, microprocessors, circuitry, modules, drivers, and/or other electronic components (not shown but known in the art and described in U.S. Pat. No. 9,839,206) to control operation of the light sources and the pumps **26**. The circuitry/electronic components of the block **64** may include, for example, microcontrollers or microprocessors for receiving and processing data and providing output to control the components of the lighting assembly **30**. The microprocessor(s) may be connected to a driver that controls the output of the light sources, for example by varying the wavelength and intensity of individual or groups of light sources, by cycling on and off individual or groups of light sources, or through a combination of both. This allows the lighting assembly **30** to provide different lighting characteristics and patterns. Together with controlled water circulation via the pumps **26**, the conditions of the habitat **15** can be controlled to mimic day-and-night cycles and seasonal cycles by varying light intensity, color, and on/off state. In this manner, the overall light color emitted by the lighting assembly **30** may be controlled locally or remotely to promote the growth and health of specific organisms in the habitat **15**, such as plants, coral or anemones.

[0054] Light sources such as LEDs produce large amounts of heat that can adversely affect the efficacy of the LEDs and, in extreme circumstances, damage the electronics **64** and the PCBs **54** and **55** of the lighting assemblies **30** of the habitat **15**. Generally, the lighting assemblies of the type used with habitats **15** are relatively small and compact, and are unable to adequately disperse the heat generated by light sources such as LEDs.

[0055] According to an exemplary embodiment of the invention, heat insulators and/or a heat transfer system may be provided to protect the components **64** from the heat generated by operation of the light sources. As best shown in FIGS. **4-7**, **10**, and **11**, the lighting assembly **30** includes a heat transfer system comprising one or more heat pipes **70** configured to transfer heat away from the heat sources, i.e., the light sources **52** and **53** such as LEDs, to baffles or fins **72** and **74** adjacent opposite end edge surfaces **45** and **46**, respectively, of the light guide **40**. The heat pipes **70** extend through passages **72a** and **74a** of the fins **72** and **74**. The heat pipes **70** carry the heat from the light sources **52** and **53** to the fins **72** and **74**, so that the heat is transferred to the fins

72 and **74**. Cooler air drawn through the air intake opening **33a** into the lighting assembly **30** by the fan **36** is blown against the fins **72** and **74**. The large surface area provided by the fins **72** and **74** provides a large interface for the cool air to remove heat released from the heat pipes **70** and expel the resulting hot air through the air discharge openings **35a**.

[0056] An example of a suitable commercially available heat pipe is available from Cooling Technologies, Inc. (formerly HPEV), which advertises its heat pipes as passive (no moving parts or external power). According to Cooling Technologies, Inc., the heat pipe is a sealed tube with a layer of wick material surrounding a hollow core filled with fluid. Heat entering the sealed tube causes the fluid to vaporize and travel to the cooler end, which in the case of the embodied lighting unit will be the fins **72**, where the heat is released and the vapor condenses back into a fluid.

[0057] Other heat insulators and/or heat insulating systems may be used. For example, one or more vapor chambers may be included in the lighting assembly **30** to transfer heat away from the light sources **52** and **53**.

[0058] The lighting assembly **30** may be powered by an external power source, such as an AC source, in which case a rectifier or comparable AC/DC device may be used to rectify the alternating current (AC) to direct current (DC). A driver or drivers convert(s) constant voltage from the power supply to a constant current output with a voltage sufficient to overcome the “forward voltage” of the diode(s). Alternatively, a DC source such as a battery may be provided as the primary power source or as a backup secondary power source.

[0059] A lighting assembly according to another embodiment of the invention is generally indicated by reference numeral **130** in FIG. **12**, in which like reference numerals of the first lighting assembly **30** of FIGS. **1-10** are used to designate corresponding parts of the lighting assembly **130**, except with the addition of “**100**” to the reference numerals in FIG. **12**. The above description of those corresponding parts of the lighting assembly **30** is incorporated herein by reference with respect to the description of the lighting assembly **130**. The lighting assembly **130** is generally the same as the lighting assembly **30**, except for the addition of a second fan **137**. Although not shown, the outer housing (not shown in FIG. **12**) of the lighting assembly **130** would be provided with an additional air intake opening identical to **33a** to as to extend over the second fan **137**.

[0060] Assembly of the lighting assemblies **30** and **130** is within the purview of a person of ordinary skill in the art having reference to this disclosure. According to one exemplary embodiment, the cover **33** is separated from the remainder of the outer housing **32** to provide access to the internal cavity of the outer housing. The diffuser **62** is placed in the outer housing **32** and optionally secured to on the lower surface or base **34** to cover or fit within the light-transmissive opening **34a**. The first and second light source holders **50** and **51** are arranged to receive the heat pipe **70**, and the printed circuit boards (PCB) **54** and **55** with the solid-state light sources **52** and **53** preinstalled are arranged at and secured to (e.g., solder, fastener, etc.) the opening of the first light source holder **50**. The resulting subassembly is placed in the outer housing **32**. If the support base **63** (FIG. **9**) is used, the light source holders **50** and **51** may be supported on or attached to the support base **63**.

[0061] The light guide **40** is placed in the outer housing **32** so that the solid-state light sources **52** and **53** are adjacent to

side edge surfaces **43** and **44** of the light guide **40**. A reflector **60** is either pre-installed on the light guide **40** or is placed in the outer housing **32** on the first major surface **41** of the light guide **40**. The electronics block **64** is placed on the reflector **60**. The air circulation device/fan **36** may be secured to the cover **33** using a bracket (not shown), and the cover **33** is attached to the remainder of the outer housing **32**.

[0062] The various components and features of the above-described exemplary embodiments may be substituted into one another in any combination. It is within the scope of the invention to make the modifications necessary or desirable to incorporate one or more components and features of any one embodiment into any other embodiment. In addition, although the exemplary embodiments discuss steps performed in a particular order for purposes of illustration and discussion, the methods discussed herein are not limited to any particular order or arrangement. One skilled in the art, using the disclosures provided herein, will appreciate that various steps of the methods can be omitted, rearranged, combined, and/or adapted in various ways.

[0063] The foregoing detailed description of the certain exemplary embodiments has been provided for the purpose of explaining the principles of the invention and its practical application, thereby enabling others skilled in the art to understand the invention for various embodiments and with various modifications as are suited to the particular use contemplated. This description is not necessarily intended to be exhaustive or to necessarily limit the invention to the exemplary embodiments disclosed.

1. An aquarium lighting assembly, comprising:
 - an outer housing configured to be positioned proximate an aquarium for directing light into the aquarium and including a base with a light-transmissive opening;
 - a light guide contained in the outer housing and positioned over the light-transmissive opening, the light guide comprising opposite first and second major surfaces and at least one edge surface extending between the first and second major;
 - a solid-state light source contained in the outer housing and arranged to emit light into the edge surface of the light guide;
 - a plurality of integrated optical elements associated with the first major surface and configured to redirect the light emitted by the solid-state light source; and
 - a heat transfer system configured to transfer heat generated by the solid-state lighting source away from the light guide.
2. The aquarium lighting assembly of claim 1, wherein the heat transfer system comprises at least one heat pipe proximate the solid-state light source to transfer heat away from the solid-state light source.
3. The aquarium lighting assembly of claim 2, wherein the heat transfer system comprises a plurality of fins through which the heat pipe passes, the plurality of fins being located in a path of the flow of air generated by the air circulation device.
4. (canceled)
5. The aquarium lighting assembly of claim 1, wherein the solid-state light source comprises light-emitting diodes, laser diodes, organic light emitting diodes, or any combination thereof configured to produce multiple colors.

6. The aquarium lighting assembly of claim 1, further comprising a light reflector positioned over the light guide, wherein the optical elements are configured to redirect light emitted by the solid-state light source upward toward the light reflector.

7. The aquarium lighting assembly of claim 1, wherein the optical elements are configured to redirect light emitted by the solid-state light source downward through the light-transmissive opening.

8. The aquarium lighting assembly of claim 1, wherein the optical elements comprise three-dimensional structures extending into or out of the first major surface.

9. The aquarium lighting assembly of claim 8, wherein the optical elements are cones or recesses configured to redirect light.

10. The aquarium lighting assembly of claim 1, wherein: the at least one edge surface comprises first and second edge surfaces on opposite sides or opposite ends of the light guide; and

the solid-state light source comprises a first solid-state light source associated with the first edge surface to emit light into the first edge surface and a second solid-state light source associated with the second edge surface to emit light into the second edge surface.

11. (canceled)

12. An aquarium, comprising:

- a tank having a chamber; and
- an aquarium light assembly associated with the tank and configured to provide light to the chamber of the tank, the aquarium lighting assembly comprising
 - an outer housing including a base with a light-transmissive opening;
 - a light guide contained in the outer housing and positioned over the light-transmissive opening, the light guide comprising opposite first and second major surfaces and at least one edge surface extending between the first and second major;
 - a solid-state light source contained in the outer housing and arranged to emit light into the edge surface of the light guide;
 - a plurality of integrated optical elements associated with the first major surface and configured to redirect the light emitted by the solid-state light source; and
 - a heat transfer system configured to transfer heat generated by the solid-state lighting source away from the solid-state light source.

13. An aquarium lighting assembly, comprising:

- a light guide comprising opposite first and second major surfaces and at least one edge surface extending between the first and second major surfaces;
- a solid-state light source arranged to emit light into the edge surface of the light guide, the solid-state light source comprising at least one of light-emitting diodes, laser diodes, organic light emitting diodes, or any combination thereof configured to produce multiple colors; and
- a plurality of integrated optical elements associated with at least one of the major surfaces and configured to redirect the light emitted by the solid-state source.

14. The aquarium lighting assembly of claim 13, further comprising a light reflector positioned over the light guide, wherein the optical elements are configured to redirect light emitted by the solid-state light source upward toward the light reflector.

15. The aquarium lighting assembly of claim **13**, wherein the optical elements are configured to redirect light emitted by the solid-state light source downward.

16. The aquarium lighting assembly of claim **13**, wherein the optical elements comprise three-dimensional structures extending into or out of the first major surface.

17. The aquarium lighting assembly of claim **16**, wherein the optical elements are cones or recesses configured to redirect light.

18. The aquarium lighting assembly of claim **13**, wherein:
the at least one edge surface comprises first and second edge surfaces on opposite sides or opposite ends of the light guide; and
the solid-state light source comprises a first solid-state light source associated with the first edge surface to emit light into the first edge surface and a second solid-state light source associated with the second edge surface to emit light into the second edge surface.

19. The aquarium light assembly of claim **13**, further comprising an outer housing comprising an air intake opening, an air discharge opening, and a base with a light-transmissive opening, the outer housing containing the light guide and the solid-state light source.

20. The aquarium lighting assembly of claim **19**, further comprising means for dissipating heat generated by the solid-state light source.

* * * * *