



US 20250276102A1

(19) **United States**

(12) **Patent Application Publication**
Compo et al.

(10) **Pub. No.: US 2025/0276102 A1**

(43) **Pub. Date: Sep. 4, 2025**

(54) **POUCH WITH BREAKABLE SEAL**

Publication Classification

(71) Applicant: **Veltek Associates, Inc.**, Malvern, PA (US)

(51) **Int. Cl.**
A61L 2/00 (2006.01)

(72) Inventors: **Mark J. Compo**, Doylestown, PA (US);
Michael Balestri, Mechanicsville, VA (US)

(52) **U.S. Cl.**
CPC **A61L 2/0088** (2013.01); **A61L 2202/123** (2013.01); **A61L 2202/181** (2013.01); **A61L 2202/21** (2013.01); **A61L 2202/23** (2013.01)

(73) Assignee: **Veltek Associates, Inc.**, Malvern, PA (US)

(57) **ABSTRACT**

(21) Appl. No.: **19/207,066**

(22) Filed: **May 13, 2025**

A wipe kit includes a pouch having a first compartment with a one-way valve coupled to an end thereof, a second compartment, and a frangible seal between the first and second compartments. The first compartment receives a liquid through the one-way valve and the second compartment contains a dry wipe. The frangible seal can be broken to permit liquid to flow from the first compartment onto the wipe in the second compartment. The deactivation wipe kit may be used in a clean room to deactivate most hazardous drugs on a work surface.

Related U.S. Application Data

(63) Continuation of application No. 18/230,024, filed on Aug. 3, 2023, now Pat. No. 12,318,493.




FIG. 2




FIG. 3A




FIG. 3B




FIG. 3C




FIG. 3D




FIG. 3E




FIG. 4




FIG. 5




FIG. 6




FIG. 7

POUCH WITH BREAKABLE SEAL

RELATED APPLICATIONS

[0001] The present application claims the benefit of U.S. Provisional Application No. 62/732,360, filed Sep. 17, 2018, which is hereby incorporated by reference in its entirety into the present disclosure.

FIELD OF THE INVENTION

[0002] The invention relates to a wipe kit used for deactivation, decontamination, and disinfection or cleaning in a clean room environment and a method of preparing and using the same.

BACKGROUND OF THE INVENTION

[0003] A clean environment or controlled environment is a space designed, maintained, and controlled to prevent particle and microbiological contamination of products. Clean environments include clean rooms and clean workspaces (such as hooded workspaces), which are collectively referred to here as a clean room. Clean rooms are most commonly designed for use in manufacturing facilities and medical research and treatment facilities in the pharmaceutical, biotechnology, and healthcare industries, to name a few. Sterile clean room environments may be classified under a variety of classification schemes, including the International Organization of Standardization ("ISO") Cleanroom Standards, whereby the highest level of sterilization is an ISO 1 clean room and a normal ambient air environment (no sterilization) is classified as ISO 9.

[0004] Certain chemical compositions are used inside clean rooms including, for instance, germicidal disinfectants such as phenols, cleaners, quaternary ammonium, peracetic acid, as well as various sporicides, such as peracetic acid, bleach, and hydrogen peroxide. The disinfectants and sporicides are used in clean rooms to disinfect clean room surfaces. In certain clean room environments, such as those in the healthcare industry, surfaces can become exposed to certain hazardous drugs. In those situations, chemicals are needed that can deactivate and decontaminate hazardous drugs on work surfaces to reduce the risk of occupational exposure to technicians and other workers in the clean room, as well as to products or chemicals being prepared in the clean room. The methods of deactivating, decontaminating and disinfecting/cleaning surfaces exposed to hazardous drugs must meet the requirements set forth in USP <800> and USP <797> set forth by the U.S. Pharmacopeial Convention (USP). Conventional methods of clean room sterilization are lacking for this purpose because they do not adequately deactivate the hazardous drugs, but instead simply spread the drug around on the affected surface. On the other hand, products that may be capable of deactivating hazardous drugs are not suitable for use inside of a classified ISO 5 clean room.

[0005] Further, the chemical compositions, which are not naturally sterile, need to be sterilized before being able to enter the clean room to avoid risk of contamination. Such compositions can be sterilized by filtration inside of the clean room or can be sterilized before entering the clean room.

[0006] To sterilize the compositions outside the clean room, the concentrated composition is either terminally sterilized by irradiation or aseptically processed. To termi-

nally irradiation sterilize the composition, the composition is placed in a container, double bagged, and placed in a lined carton. The entire carton is then terminally sterilized by irradiation. A procedure for terminally irradiation sterilizing a composition is described, for instance, in U.S. Pat. No. 6,123,900 to Vellutato, the disclosure of which is incorporated herein by reference. Some chemicals used in a clean room, however, cannot be irradiated because of their chemical makeup and structure. For example, certain chemicals used to deactivate and decontaminate hazardous drugs in clean rooms cannot be irradiated. This creates problems for introducing such chemicals into a clean room environment and complicates the sterilization process.

[0007] Accordingly, the invention is directed to a deactivation wipe kit that improves deactivation, decontamination, and disinfection/cleaning of hazardous drugs from sterile surfaces in a clean room. The deactivation wipe kit of the invention is also able to be irradiated outside of the clean room environment for more efficient transfer and introduction into a clean room.

SUMMARY OF THE INVENTION

[0008] It is one aspect of the invention to have a wipe pouch with multiple compartments separated by one or more frangible seals. The wipe pouch can have a first compartment containing a dry wipe, a second compartment having a one-way filling valve coupled thereto, and a coupling assembly (such as a frangible seal) coupling the first compartment to the second compartment. In a closed configuration, the first compartment does not communicate (e.g., air or liquid) with the second compartment. In an opened configuration, the first compartment communicates with the second compartment.

BRIEF DESCRIPTION OF THE DRAWINGS

[0009] A more complete appreciation of the invention and many of the attendant advantages thereof will be readily obtained as the same becomes better understood by reference to the following detailed description when considered in connection with the accompanying drawings, wherein:

[0010] FIG. 1 is a front, perspective view of the deactivation wipe kit according to an embodiment of the invention;

[0011] FIG. 2 is a front, plan view of the first pouch of the deactivation wipe kit having a one-way valve according to an embodiment of the invention;

[0012] FIGS. 3A-E are perspective views of the one-way valve illustrated in FIG. 2;

[0013] FIG. 4 is a flowchart outlining the steps of a method of preparing a deactivation wipe kit according to an embodiment of the invention;

[0014] FIG. 5 is a flowchart outlining the steps of a method of using the deactivation wipe kit according to an embodiment of the invention;

[0015] FIG. 6 is a perspective view of a pouch in accordance with another embodiment of the invention, having side walls at the longitudinal sides between the first and second bag layers; and

[0016] FIG. 7 is a perspective view of a pouch in which the longitudinal and transverse sides of the first and second bag layers are heat sealed directly to one another, without side walls.

DETAILED DESCRIPTION

[0017] Referring now to FIG. 1, a deactivation wipe kit **100** is illustrated. As used more fully herein, the term “wipe kit” is used to refer to the deactivation wipe kit **100**. In one embodiment, the wipe kit **100** includes three pouches **102**, **104**, **106**. Each of these pouches contains a wipe that is saturated in a different chemical used to deactivate and decontaminate hazardous drugs in a clean room environment and disinfect the work surface. In use, the technician applies each wipe from each of the pouches **102**, **104**, **106** in sequence to a contaminated work surface, such that the wipe in the first pouch **102** is used first, the wipe in the second pouch **104** is used second, and the wipe in the third pouch **106** is used last. When used in this way, the deactivation wipe kit **100** deactivates, decontaminates, and disinfects/cleans most hazardous drugs from work environments for compounding sterile preparations, such as an ISO 5 clean room, as cited by USP <800> and USP <797> set forth by the U.S. Pharmacopeial Convention (USP).

[0018] In one embodiment, the first pouch **102** contains a wipe that is saturated in a 5.25% hypochlorite solution, such as sodium hypochlorite (e.g., HYPO-CHLOR® available commercially from Veltek Associates, Inc. of Malvern, PA). This composition is the primary agent that deactivates the hazardous drug(s). It deactivates potentially active drugs that may be present on a compounding surface, and renders the surface safe and decontaminated for future handlers and ensures that the compounding preparations are following USP <797> compounding sterile preparations for patient protection protocol along with USP <800> compliance for hazardous drugs (handling in healthcare settings). While the use of sodium hypochlorite is preferred, any chemical known to deactivate hazardous drugs may be used to saturate the wipe in the first pouch **102**, including, but not limited to, potassium permanganate and alkaline potassium permanganate.

[0019] The second pouch **104** contains a wipe that is saturated in 2% thiosulfate, such as sodium thiosulfate (e.g., THIO-WIPE™ available commercially from Veltek Associates, Inc.). In a preferred embodiment, the thiosulfate is USP Grade. This composition is used in order to remove the hypochlorite solution residue from the treated work surface. The thiosulfate renders the hypochlorite, which is a corrosive material, neutral on the surface so as to maintain the surface's structure and integrity. It also functions to decontaminate the work surface. While sodium thiosulfate is preferred, any chemical known to decontaminate a work surface that has been treated with hypochlorite, and which can neutralize the same, may be used. Thus, the sodium thiosulfate solution cleans, decontaminates, and neutralizes the sodium hypochlorite solution and previously deactivated hazardous drugs. It improves the overall longevity of the sterile compounding equipment and stays USP <797> and USP <800> compliant.

[0020] The third pouch **106** contains a wipe that is saturated in 70% isopropyl alcohol (IPA) (e.g., ALCOH-WIPER available commercially from Veltek Associates, Inc.), which functions as a disinfectant. In a preferred embodiment, the IPA is USP Grade. This wipe further cleans and disinfects the treated surface and returns the surface back to its original condition for worker safety. While IPA is preferred, any chemical known to clean and disinfect a work surface may be used, including, but not limited to, sterile water or known germicidal agents such as phenols, quats, peroxyacetic acid

(POAA) and H₂O₂. Thus, the IPA provides an additional measure against contaminants present on the compounding surfaces for added protection. After deactivation of the work surface, additional disinfection is needed to maintain a critical, controlled, work environment for compounding sterile products.

[0021] All three chemicals used in each of the pouches **102**, **104**, **106** may be formulated with Water for Injection (WFI) and filtered at 0.2 microns. Once a surface is fully treated by all three wipes, the surface can return to its natural composition.

[0022] Each of the wipes contained in pouches **102**, **104**, **106** is preferably formed of a non-woven, non-shedding material that is designed to be clean, have good absorption properties, and provide good surface coverage. The wipe should have good non-shedding properties, as fibers from the wipe should not be easily detached from the wipe so as to avoid contaminating the clean room work surface. In one embodiment, the wipe of the first pouch **102** is formed of 100% polypropylene, while the wipes in the second pouch **104** and third pouch **106** are formed of 100% polyester. In this embodiment, the material of each wipe is chosen for its compatibility with the particular chemical present in each of the pouches **102**, **104**, **106**. Each of these materials produces a fabric-like wipe that is strong, has good non-shedding particulate performance, and is compatible with the chemical in which it is saturated as well as use in a controlled environment. In one embodiment, the wipe is about 9"×12" in size such that it can treat a surface area of approximately six (6) square feet.

[0023] In one embodiment, the wipe for the first pouch **102** is a 162XL-4019, 48 gauge polyester with an ALOX coating bonded to **150** (6 mil) white polyethylene. This particular substrate retains the active hypochlorite, though other suitable wipes can be provided. Further, this wipe material minimizes the degradation and instability associated with hypochlorite caused by exposure to organic material. In one embodiment, a single wipe is provided in each pouch **102**, **104**, **106**; however more than one wipe can be provided in any or all of the pouches **102**, **104**, **106**.

[0024] The pouches **102**, **104**, **106** themselves are designed as flexible packaging structures for the wipes. The pouches **102**, **104**, **106** are preferably formed of a material that provides a barrier to moisture, air and light and has good chemical resistance so as to maintain its structural integrity during irradiation and when ultimately shelved in the clean room. In one embodiment, each pouch **102**, **104**, **106** is formed of a multi-layered structure comprised of layers of coated polyester, low density polyethylene, aluminum foil, hydroxypropylcellulose, and/or linear low density polyethylene. For example, the pouches **102**, **104**, **106** can be ExpressWeb EFS174, by Glenroy Inc., which is attached hereto and hereby incorporated by reference. When prepared into a multi-layered structure, these materials provide an air-tight and liquid-tight seal and are highly chemically resistant (since stability of the finished product can be affected by light, oxygen and organic matter). They also help to maintain the active agents in each of the chemicals so as to prolong their shelf life. Each of the pouches **102**, **104**, **106** preferably includes a notch or perforation **212**, such as shown in FIG. 2 in the first pouch **102**. The notch **212** can be formed in the side of the pouch **102**, **104**, **106**, so that the user can tear open the pouch **102**, **104**, **106** by pulling on the side of the pouch at the notch **212**. Thus in use, the

technician pulls the pouch along the perforation in order to tear the pouch **102**, **104**, **106** open to access the saturated wipe contained therein.

[0025] In order to introduce the deactivation wipe kit **100** into the clean room, it (and its contents) must first be sterilized. In one embodiment, parts of the deactivation wipe kit **100** is irradiated to avoid introducing contaminants into the environment. The second pouch **104** and third pouch **106** contain chemicals that may be terminally irradiation sterilized, such as by the methods described herein. Thus, assembled pouches **104**, **106** may undergo known terminally irradiation sterilization. The first pouch **102**, however, contains a chemical (i.e., sodium hypochlorite) that cannot be terminally irradiation sterilized. As such, the first pouch **102** is configured differently than the second pouch **104** and third pouch **106** such that the chemical can be added after the first pouch **102** has been sterilized.

[0026] As set forth in FIG. 2, the first pouch **102** is designed with a one-way valve **208** positioned at an end **210** thereof, and the pouch **102** contains a wipe **209**. This valve **208**, which is more fully illustrated in FIGS. 3A-E, only allows fluids to be transferred through it in one direction. As such, the first pouch **102**, containing only a dry wipe, may be terminally irradiation sterilized, together with the second pouch **104** and third pouch **106** (each of which contain the wipe and the respective chemical). Then, when the pouches **102**, **104**, **106** are transferred to the clean room, the first pouch **102** may be aseptically filled with the sterilized hypochlorite solution via the one-way valve **208** to saturate the dry wipe contained therein. The sterilized hypochlorite solution may be of any concentration determined suitable to one or ordinary skill in the art. For example, a hypochlorite concentration of 5.25% is used. At this point, the deactivation wipe kit **100** is fully ready for use in a clean room. The wipes contemplated for the kit may be of any conventional size known in the art, exemplarily 3"x4", 4"x6", 9"x9", 9"x12", or 12"x12".

[0027] A process of preparing the deactivation wipe kit **100** is outlined in the flow chart of FIG. 4. Each pouch **102**, **104**, **106** may be prepared in sequence or simultaneously by different technicians. Thus, Steps **400**, **402**, **404** can be performed sequentially or at the same time. As set forth more fully below, each of the steps utilizes the chemicals and materials described above.

[0028] In Step **400**, a dry, wipe material is placed in the first pouch **102** and hermetically sealed to form a first closed or sealed container or pouch. At this step, there are no chemicals present in the first pouch **102**. A wipe saturated with a first solution, such as for example thiosulfate solution (e.g., THIO-WIPE™), is placed in the second pouch **104** and hermetically sealed to form a second closed or sealed container or pouch, Step **402**. A wipe saturated with a second solution, such as for example 70% IPA (by concentration) (e.g., ALCOH-WIPE®), is placed in the third pouch **106** and hermetically sealed to form a third closed or sealed container or pouch, Step **404**. Each of the pouches **102**, **104**, **106** is hermetically sealed, Step **406**, to enclose the contents of each pouch. In one embodiment, the hermetic seal is a liquid and air tight seal of the pouches **102**, **104**, **106**, such as for example a heat seal. Though the heat sealing, Step **406**, is shown as a separate step, it can be part of each of the filling processes of Steps **400**, **402**, **404**.

[0029] Each of the first, second and third sealed pouches **102**, **104**, **106** are assembled in preparation for irradiation

sterilization, Step **408**. One of each of the first, second, and third sealed pouches **102**, **104**, **106** are assembled together and placed in a first container such as a first plastic bag and the first plastic bag is then hermetically sealed to form a first closed or sealed pouch enclosure, Step **410**. Optionally, the first sealed pouch enclosure can be placed in a second container such as a second plastic bag and the second plastic bag is then hermetically sealed to form a second closed or sealed pouch enclosure. In one embodiment, the first and second plastic bags are a polyethylene bag that is heat sealed. The second (or first) sealed pouch enclosure is then placed into a plastic liner bag (e.g., a polyethylene bag) which is closed and placed into a box or other container. The liner is then closed (such as by being knotted or by a fastener (tie)) and the box is closed to form a closed package, Step **412**. The box and the enclosed contents are then terminally irradiation sterilized using known techniques and equipment, Step **414**, and can be shipped to an irradiator for sterilization, to form a sterilized closed container. The irradiation sterilizes the container and its contents, including the plastic bags, wipes, pouches, solutions.

[0030] The irradiated boxes (sterilized closed containers) are then transferred to a clean environment and the sterilized closed pouch enclosure is removed from the plastic liner bag. The sterilized first, second and third sealed pouches are then removed from the inner-most sealed plastic bag, Step **416**. At this point, the second sealed pouch **104** and the third sealed pouch **106** are ready for use. However, the first sealed pouch **102** must be filled with the deactivation chemical. In one embodiment, the first sealed pouch **102** is aseptically filled with a sterile hypochlorite solution via the one-way valve **208** inside the clean room, Step **418**. At this step, when the first pouch **102** is filled with the solution, the solution is allowed to saturate the dry wipe in the pouch **102**, thereby preparing a saturated, hypochlorite wipe. The valve **208** may close automatically by virtue of its design, though other suitable valve designs can be provided.

[0031] Once the valve **208** is closed, the first sealed pouch **102** forms a first closed or sealed filled pouch that is then ready for use as well. Optionally, the first sealed filled pouch **102** can be successively hermetically sealed in a first container and optionally then a second container, such as plastic bags to form a first (and second) first filled pouch enclosure. Once the first sealed filled pouch **102** (or first/second filled pouch enclosure) is ready for use, it is matched with one of the irradiated second sealed pouch **104** and one of the irradiated third sealed pouch **106**, to form the deactivation wipe kit **100**. Optionally, the deactivation wipe kits **100** can be successively hermetically heat sealed in a first container (e.g., a polyethylene bag) and optionally then a second container (e.g., a polyethylene bag), such as plastic bags. Multiple wipe kits **100** are then placed together into a carton having a plastic liner. The plastic liner can be closed (such as by being knotted or by a fastener (tie)) and the box is closed to form the final closed package. The box can then be shipped to the customer for use.

[0032] Alternate processes of preparing the deactivation wipe kit **100** may also be performed. The drying, wiping, and placement of material in the first pouch **102** (Step **400**) may be performed before, during, or after the placement of the thiosulfate-saturated wipe in the second pouch **104** (Step **402**), and before, during or after the IPA-saturated wipe is placed in the third pouch **106** (Step **404**). Similarly, the placement of the thiosulfate-saturated wipe in the second

pouch **104** (Step **402**) and the placement of the IPA-saturated wipe in the third pouch **106** (Step **404**) may occur in any order relative to the preparation of the other pouches, as long as all three pouches **102**, **104**, and **106** can be prepared prior to the step of heat sealing, if packaged together in a same box. However, the irradiated second and third pouches can be packaged together in a box separate from the first final pouch.

[0033] In addition it will further be appreciated that other suitable techniques can be utilized to irradiation sterilize the pouches **102**, **104**, **106**. For instance, the multiple pouches **102**, **104**, and/or **106** can be heat sealed in the same or different individual first (and optionally second) plastic bags. In one embodiment, each closed pouch **102**, **104**, **106** can be individually single/double bagged (i.e., heat sealed in a first plastic bag (and optionally a successive second plastic bag) to form respective first and second sealed enclosures for the first, second and third closed pouches), then placed in a carton liner and a box and sterilized. In another embodiment, multiple first closed pouches **102** can be heat sealed together in a first bag to form a first enclosure, multiple second closed pouches **104** can be heat sealed in a second bag to form a second enclosure, and multiple third closed pouches **106** can be heat sealed in a third bag to form a third enclosure; and the first, second and third enclosures can be placed in a liner and box and simultaneously irradiated.

[0034] Still further, multiple first closed pouches **102** can individually be single/double bagged and placed into a first box; multiple second closed pouches **104** can individually be single/double bagged and placed into a second box; and multiple third pouches **106** can individually be single/double bagged and placed into a third box. Or, multiple first sealed pouch enclosures can be placed in a first box for irradiation, and multiple second and third pouch enclosures can be placed together in a second box for irradiation. In addition, the first and second containers can be any suitable containers such as pouches, and the first, second and third pouches **102**, **104**, **106** can be any suitable container.

[0035] Thus, an end user can receive a single box having multiple kits, each kit having a first, second and third sterilized closed pouch. A method of using the deactivation wipe kit **100** is outlined in FIG. **5**. Once the box arrives at the customer, the box and box liner are opened (e.g., in a clean room or staging area). A kit **100** can then be removed from the box for use, and brought into the clean room. The heat sealed bag is opened and the pouches **102**, **104**, **106** are removed. As set forth in Step **500**, the first pouch **102** is opened (e.g., by tearing the perforation **212**) and the hypochlorite-saturated wipe is removed. The wipe is then applied to the contaminated work surface in order to deactivate the hazardous drug(s), Step **502**. Next, the second pouch **104** is opened and the thiosulfate-saturated wipe is removed, Step **504**. The wipe is then applied to the work surface that has just be treated with the hypochlorite-saturated wipe, Step **506**, in order to decontaminate the surface and remove any hypochlorite residue that may still be present on the surface. The third pouch **106** is then opened and the IPA-saturated wipe is removed, Step **508**. Lastly, the wipe is applied to the work surface in order to disinfect and clean the surface to render it safe for use by a technician or worker, Step **510**. Once each wipe is used consecutively on the surface, any

hazardous drugs that are present are deactivated and decontaminated and the surface is disinfected and safe for use by the technician.

[0036] Thus, multiple variations of the invention are apparent within the scope of the present invention. The first, second and third pouches can be individually single/double-bagged (i.e., hermetically sealed in a first pouch and successive second pouch). Or the second and third pouches can be single/double-bagged together for irradiation and delivery to the end user; and either matched in a box with a double-bagged first filled pouch enclosure or boxed separately from the single/double-bagged first filled pouch enclosure. Still other variations are possible within the spirit and scope of the invention. For instance, the end user can receive a first box with the first sterilized closed pouches, and a second box with the second and third sterilized closed pouches. In addition, although the invention is described for use with three pouches each having a different solution, other suitable number of pouches and solutions can be provided, such as two or four or more.

[0037] For example, a further illustrative non-limiting example of the invention is shown in FIGS. **6**, **7**. Here, an alternative embodiment for the first pouch **250** is shown. The pouch **250** has two polyethylene layers **270**, **272** that are heat sealed at the edges (either directly to one another, FIG. **7**, or with a side wall therebetween, FIG. **6**) to define an interior space **274** therebetween. The pouch is substantially rectangular in shape with two longitudinal sides and two transverse sides that are substantially orthogonal to the longitudinal sides. A transverse coupling assembly, such as a frangible seal **260**, is formed in the center to define a first compartment **252** and a second compartment **254**. The first compartment **252** has a first layer **270a**, second layer **272a** and an interior space **274a** therebetween, and the second compartment **254** has a first layer **270a**, second layer **272a**, and an interior space **274b** therebetween. The frangible seal **260** is substantially parallel to the transverse sides and extends the entire width of the pouch **250**. The first and second compartments **252**, **254** are completely liquid tight so that liquid cannot pass from the first compartment **252** to the second compartment **254**, or vice versa.

[0038] In operation, the pouch **250** is formed by heat sealing the layers **270**, **272** along their two longitudinal sides (either directly to one another, FIG. **7**, or with a side wall therebetween, FIG. **6**), and then applying the frangible heat seal **260**. A dry wiper **256** is then placed in the interior space **274b** of the second compartment **254** and the bottom transverse side is heat sealed to fully enclose the wiper **256** in the second compartment **254**. A laser score **262** can be formed along at least a portion of the second compartment **254**, here shown extending transversely across the entire width of the pouch **250**. In addition, a valve **258** is placed at the top transverse side, and the entire top transverse side of the two layers **270**, **272** is heat sealed to engage the valve **258** at the top of the first compartment **252**. The entire pouch **250** is then sterilized by irradiation.

[0039] At this point, a liquid is filled into the interior space of the first compartment **252** via the valve **258**. In one embodiment, the liquid is a disinfectant such as a bleach, which is filtered and aseptically filled inside a clean room into the first compartment **252**. The pouch **250** is then packaged for delivery to a clean room for use, such as by

being successively double bagged in two polyethylene bags and placed in a plastic liner and then a cardboard box for delivery.

[0040] The frangible seal **260** is weaker than the outer perimeter heat seals. The frangible seal **260** can be formed, for instance, by bonding at a lower heat. When the wiper **256** is ready for use, the user opens the outer packages. The user then presses on the first and/or second compartments **252**, **254**, which breaks the frangible seal **260**. The interior space **274a**, **274b** of the first and second compartments **252**, **254** are then in liquid communication with one another, whereby breaking the seal **260** releases the liquid from the first compartment **252** to come into contact with the wiper(s) **256** in the second compartment. The frangible seal **260** does not weaken the outer plastic layers forming the pouch **250**, so that the pouch **250** is liquid-proof and no liquid escapes out of the pouch **250**. Once the liquid has been absorbed by the wiper **256**, the user opens the second compartment **254** along the laser score **262**. The user then removes the wet wiper **256** from the interior space **274**, for use in the clean room.

[0041] In this manner, the liquid does not come into contact with the wiper **256** until just prior to the wiper **256** being used, which can be important where the liquid (such as a bleach) can otherwise degrade the wiper **256**. That extends the shelf life of the product. It is further noted that the pouch **250** can be formed in any suitable manner, though the frangible heat seal **260**, score **262** and two longitudinal seals can be made prior to introducing the wiper **256** so that the wiper **256** does not inadvertently get caught in or otherwise damaged by any of those operations. However, in another embodiment, the bottom transverse side and the two longitudinal sides can be heat sealed. The wiper **256** can then be placed inside the pouch **250** and the frangible heat seal **260** and top transverse heat seals applied. In another embodiment of the invention, the wiper **256** can be placed between the two layers **270**, **272**, then all of the seals formed at the same time, including the frangible seal **260** and the heat seals along the longitudinal sides and at the top and bottom transverse sides.

[0042] The dual compartment **252**, **254** pouch **250** of FIG. **6** can be used with the second pouch **104** and third pouch **106** in the systems and methods described with respect to FIGS. **1-5**. For example, the pouch **250** with the dry wiper **256** can be irradiated together with the second pouch **104** and third pouch **106**. However, the dual compartment pouch **250** of FIG. **6** also has separate utility by itself, and can be used in other suitable applications, and need not be used with the second and third pouches **104**, **106**. For example, the pouch **250** can be used by itself when only a single wiper is needed.

[0043] It is further noted that the invention is shown and described as a pouch **250** having two compartments **252**, **254** separated by a frangible seal **260**. The two compartments **252**, **254** are directly attached to each other and separated by the frangible seal **260**, so that the compartments **252**, **254** are in liquid communication with one another when the seal **260** is opened. It should be noted that the two compartments can be placed in communication with one another in other manners without using a frangible seal, within the spirit and scope of the invention, such as for example by using a valve or other connection device or coupling assembly.

[0044] In addition, it is noted that the frangible seal **260** is shown extending the entire width of the pouch **250**. It is

noted that the frangible seal **260** need not extend the entire width. For example, part of the seal **260** can be a full heat seal that permanently separates the first compartment **252** from the second compartment **254**, and part of the seal **260** can be a frangible seal that can be opened to release liquid from the first compartment **252** into the second compartment **254**.

[0045] Still further, as shown in FIG. **7**, the frangible seal **260** seals the first layer **270** directly to the second layer **272**, which are flat, so that the two layers **270**, **272** come together at the seal. Thus, the first layer **270** is sealed directly to the second layer **272** without any other material positioned therebetween. In this manner, the seal **260** forms a tapered area between the first and second compartments **252**, **254**. The seal **260** can have any suitable thickness, either small to form a line or pinch point, or wide to form a flattened area. In one embodiment, the seal **260** can have a thickness of about 0.3125 inches, the first compartment can have a length of about 5.3125 inches, the second compartment can have a length of about 6.375 inches, and the pouch can have a width of about 4.5 inches and a total length of about 12 inches. The first compartment can hold approximately 30 mL of liquid or solution, and the second compartment can hold one or more folded 12×12 knitted wipers. In addition, the seal **260** need not be linear, as shown, but can have other shapes such as curved. In another embodiment of the invention, the first compartment **252** can be the same size as the second compartment **254**, or a different size, either smaller or larger than the second compartment **254**. The first and second compartments can be generally square or rectangular, or other suitable sizes and shapes.

[0046] In still a further embodiment, additional transverse frangible seals can be provided to define more than two liquid-tight compartments in the pouch. For example, a first compartment containing a first product (e.g., dry wipe), liquid or substance; a second compartment containing a second product, liquid or substance, and a third compartment containing a third product, liquid or substance. The compartments can be arranged so that they all communicate with each other when the frangible seals are broken, or that the second compartment is positioned between the first and second compartments, so that the first and third compartments only communicate with the second compartment. And, the frangible seals can have different breaking points or separately broken, so that, for example, a first frangible seal can be broken to release the content from a first compartment into a second compartment, then a second frangible seal can be broken to release the contents from the first and second compartments into the third compartment.

[0047] As noted, FIG. **7** shows that the longitudinal sides of the first and second layers **270**, **272** are directly heat sealed to one another. And FIG. **6** shows that the pouch **250** can have side walls that extend between the longitudinal sides of the first layer **270** and the second layer **272**, for the first compartment **252** and/or the second compartment **254**. The side walls allow the layers **270**, **272** to separate at the longitudinal sides so that they can retain more liquid, substance or product in the compartments **252**, **254**. The side walls are heat sealed to the first and second layers **270**, **272**. For example, the side wall can be substantially rectangular and tapered to a point or oblong, with a first longitudinal side that couples to the first layer **270** and a second longitudinal side that couples to the second layer **272**. There can be one side at each longitudinal side of the pouch **250**, that gets

sealed in the middle by the frangible seal **260**, or two longitudinal sides, one for the first compartment **252** and one for the second compartment **254**. In operation, the sides can be heat sealed to the layers **270**, **272** in a single heat-sealing operation that applies a heat seal to each longitudinal side of the side wall, or two heat-sealing operations, one that applies a heat seal to the first longitudinal side and a second that applies a heat seal to the second longitudinal side.

[0048] Finally, it is noted that the description and claims use several geometric or relational terms, such as parallel, linear, curved, rectangular, perpendicular, and flat. In addition, the description and claims use several directional or positioning terms and the like, such as top, bottom, sides, longitudinal, transverse, and interior. Those terms are merely for convenience to facilitate the description based on the embodiments shown in the figures. Those terms are not intended to limit the invention. Thus, it should be recognized that the invention can be described in other ways without those geometric, relational, directional or positioning terms. In addition, the geometric or relational terms may not be exact. For instance, walls may not be exactly perpendicular or parallel to one another but still be considered to be substantially perpendicular or parallel because of, for example, roughness of surfaces, tolerances allowed in manufacturing, etc. And, other suitable geometries and relationships can be provided without departing from the spirit and scope of the invention.

[0049] Although this invention has been described in connection with specific forms and embodiments thereof, it will be appreciated that various modifications other than those discussed above may be resorted to without departing from the spirit or scope of the invention. For example, equivalent elements may be substituted for those specifically shown and described, certain features may be used independently of other features, and in certain cases, particular locations of elements may be reversed or interposed, all without departing from the spirit or scope of the invention as defined in the appended Claims.

1. A hazardous drug deactivation wipe kit, comprising:
 - a first pouch having a one-way valve coupled to an end thereof, the first pouch having a first compartment containing a dry wipe, a second compartment having a disinfectant, and a frangible seal formed between the first compartment and the second compartment;
 - a second pouch containing a wipe saturated in thiosulfate solution; and
 - a third pouch containing a wipe saturated in isopropyl alcohol solution,
 wherein the deactivation wipe kit is configured for use in a controlled environment to deactivate hazardous drugs on a work surface.
2. The deactivation wipe kit of claim **1**, wherein the disinfectant comprises a hypochlorite solution that is a 5.25% sodium hypochlorite solution.
3. The deactivation wipe kit of claim **1**, wherein the thiosulfate solution is a 2% sodium thiosulfate solution.
4. The deactivation wipe kit of claim **1**, wherein the isopropyl alcohol solution is a 70% isopropyl alcohol solution.
5. The deactivation wipe kit of claim **1**, wherein the wipe in the first pouch is formed of 100% polypropylene.
6. The deactivation wipe kit of claim **1**, wherein the wipe in the second pouch and the wipe in the third pouch is formed of 100% polyester.

7. The deactivation wipe kit of claim **1**, wherein each of the first pouch, the second pouch, and the third pouch are formed of a multi-layered structure comprised of coated polyester, low density polyethylene, aluminum foil, hydroxypropylcellulose, linear low density polyethylene, or combinations thereof.

8. The deactivation wipe kit of claim **1**, wherein each of the first pouch, the second pouch, and the third pouch comprise a perforation adjacent to an end thereof.

9. The deactivation wipe kit of claim **1**, wherein the one-way valve is configured to permit the first pouch to be filled into the first compartment with the hypochlorite solution after the wipe has already been sealed in the first compartment.

10-19. (canceled)

20. A wipe pouch, comprising:

- a first compartment containing a dry wipe;
- a second compartment having a one-way filling valve coupled thereto; and
- a coupling assembly coupling the first compartment to the second compartment and having a closed configuration in which the first compartment does not communicate with the second compartment, and an opened configuration in which the first compartment communicates with the second compartment.

21. The pouch of claim **20**, wherein said coupling assembly comprises a frangible seal.

22. The pouch of claim **20**, wherein the one-way filling valve is configured to permit a liquid to be filled into the second compartment while preventing the liquid from escaping the second compartment.

23. A method of preparing a wipe kit, comprising the steps of:

- (a) placing a dry first wipe in a first compartment of a pouch having a one-way filling valve coupled to a second compartment of the pouch and closing the pouch to form a closed pouch;
- (b) irradiation sterilizing the closed pouch to form a sterilized closed pouch; and
- (c) filling the second compartment of the sterilized closed pouch with a solution via the one-way filling valve to saturate the dry wipe with the solution.

24. The method of claim **23**, wherein the step (c) forms a sterilized filled closed pouch, and further comprising the step of placing the sterilized filled closed pouch in a bag and hermetically sealing the bag to form a sterilized filled closed pouch enclosure.

25. A wipe pouch, comprising:

- a first compartment containing a dry wipe;
- a second compartment containing a liquid; and
- a coupling assembly coupling the first compartment to the second compartment and having a closed configuration in which the first compartment does not communicate with the second compartment, and an opened configuration in which the first compartment communicates with the second compartment.

26. The pouch of claim **25**, wherein said coupling assembly comprises a frangible seal.

27. The pouch of claim **25**, further comprising a one-way filling valve coupled to the second compartment and configured to permit the liquid to be filled into the second compartment while preventing the liquid from escaping the second compartment.