

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250277769

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

Garrahy; Robert J. et al.

SENSOR WITH ROTATABLE SENSOR ELEMENT AND PRESSURE EQUALIZATION MECHANISM

Abstract

A sensor may include a sensing element retained within a storage compartment filled with a storage medium, which may also be used as a calibration medium. The sensing element can include a sensing surface located away from the distal end of the sensing element, such that an inactive section of the sensing element can cooperate with a sealing member such as an O-ring to form part of the seal retaining the storage/calibration medium. The sensing element can be extended and retracted from the storage compartment to expose the sensing surface to a process medium, while preserving the storage medium within the storage compartment for post-measurement validation.

Inventors: Garrahy; Robert J. (Laguna Niguel, CA), Broadley; Scott T. (Laguna Beach, CA), Feng; Chang-Dong (Long Beach, CA), Sargent; Bradley Joseph (Mission Viejo, CA), Rothman; Josh L. (Fallbrook, CA), Palmer; Michael (Ladera Ranch, CA)

Applicant: Broadley-James Corporation (Irvine, CA)

Family ID: 70334122

Appl. No.: 19/088292

Filed: March 24, 2025

Related U.S. Application Data

parent US continuation 17599294 20210928 parent-grant-document US 12259354 US continuation PCT/US2020/025024 20200326 child US 19088292
us-provisional-application US 62825682 20190328

Publication Classification

Int. Cl.: G01N27/416 (20060101); G01N27/28 (20060101)

Background/Summary

INCORPORATION BY REFERENCE TO ANY PRIORITY APPLICATIONS

[0001] Any and all applications for which a foreign or domestic priority claim is identified in the Application Data Sheet as filed with the present application are hereby incorporated by reference under 37 CFR 1.57.

BACKGROUND

Technical Field

[0002] Embodiments described herein relate to sensor systems and associated devices, and in particular to sensor systems including integrated storage and calibration compartments.

Description of the Related Art

[0003] In biopharmaceutical manufacturing processes, the use of single-use measurement systems pushes the responsibility of cleaning, sterilization, and validation processes to the system vendors, increases the speed and flexibility of the manufacturing process and reduces the capital investment for system users who are the biopharmaceutical manufacturers.

[0004] With single-use systems, sensors such as pH and dissolved oxygen (DO) sensors can be integrated into a system such as a single-use bioreactor bag, or elsewhere in a process flow. The final system product can then go through a gamma irradiation process for the sterilization of the system and be shipped to the end user customer. At the end user site, the pH sensors on the system are not accessible to the operator for a standard calibration process without breaching the sterility of the bioreactor bag or other structure. However, an on-site calibration and/or validation of the sensors may nevertheless be required before a manufacturing process, such as a cell culture, begins. After the manufacturing process, an additional post-measurement validation of the sensors may also be required.

SUMMARY

[0005] In one embodiment, a sensor structure is provided, including a storage compartment configured to retain a storage medium therein, a sensing element extending through an aperture in the compartment and including a sensing structure, a distal end of the sensing structure located proximal a distal end of the sensing element, the sensing element movable between a first position in which the sensing structure is in fluid communication within the storage compartment and a second position in which the sensing structure is not in fluid communication with the storage compartment, and a sealing element disposed at least partially within the aperture and configured to engage a surface of the sensing element to provide a seal inhibiting fluid flow in or out of storage compartment through the aperture.

[0006] The sensing surface can be substantially flush with the adjacent surfaces of the sensing element. The sensing element can include a section of substantially constant cross-sectional shape extending between a point distal the proximal end of the sensing surface and a point proximal the distal end of the sensing surface. The sensing surface can form at least part of an outer surface of a cylindrical section of the sensing element. A shape of the surface of the sensing element in contact with the sealing element can remain substantially constant during movement of the sensing element from the first position to the second position.

[0007] The sealing element can include a gasket. The sealing element can include an O-ring. The sealing element can include a resilient material. The sensing element can include a pH probe. The sensing structure can include a glass electrode. The sensing structure can be in electrical

communication with a reference electrode.

[0008] The storage medium can be configured to be used as a calibration medium for the sensing element. The storage solution can have a pH of less than 6.0, less than 5.0, or less than 4.0. The storage solution can have a pH of between 0 and 14, between 1 and 13, between 3 and 12, between 4 and 10.5, between 5 and 10.5, or between 6 and 10.5.

[0009] Translating the sensing element between the first position and the second position can, in some embodiments, not displace a substantial amount of the storage solution from the storage compartment. Translating the sensing element between the first position and the second position can, in some embodiments, not expose the interior of the storage compartment. The translating the sensing element between the first position and the second position can displace less than 90% of the storage solution from the storage compartment, less than 50% of the storage solution from the storage compartment, less than 10% of the storage solution from the storage compartment, 5% of the storage solution from the storage compartment, or less than 3% of the storage solution from the storage compartment, or less than 1% of the storage solution from the storage compartment.

[0010] The sensor structure can additionally include a second sensing element extending parallel to the first sensing element, where the second sensing element extends through a second aperture in the storage compartment and engages with a second scaling element disposed at least partially within the second aperture to provide a seal inhibiting fluid flow in or out of storage compartment through the second aperture. The storage compartment can include a first chamber and a second chamber, the sensing element extending through both the first chamber and the second chamber, where the sensing structure of the sensing element is within the first chamber when the sensing element is in the first position, and where the sensing element is longitudinally translatable to a third position in which the sensing structure is located within the second chamber. The first chamber can retain the storage solution, and the second chamber can retain a calibration medium, the calibration medium having a pH which is different from the pH of the storage solution.

[0011] In another embodiment, a method is disclosed of measuring a property of a process medium using a sensor system including a storage compartment configured to retain a storage solution therein, and a sensing element extending through an aperture in the compartment and including a sensing structure, a distal end of the sensing structure located proximal a distal end of the sensing element, the sensing element longitudinally translatable between a first position in which the sensing structure is located within the storage compartment and a second position in which the sensing structure is located outside the storage compartment, the method including recording a first measurement when the sensing element is in a first position in which the sensing structure of the sensing element is positioned outside of the storage compartment and exposed to the process medium, moving the sensing element from the first position to a second position in which the sensing structure of the sensing element is positioned within or otherwise exposed to the storage compartment, and recording a second measurement when the sensing element is in the second position. The method can additionally include, prior to recording the first measurement when the sensing element is in the first position recording an initial measurement when the sensing element is in an initial position in which the sensing structure of the sensing element is positioned within the storage compartment and exposed to the storage solution, and longitudinally translating the sensing element from the initial position to the first position.

[0012] In another embodiment, a single-use bioreactor component is provided, including a process chamber configured to retain a process medium within an interior of the chamber, a storage compartment secured relative to the chamber, the storage compartment including an aperture extending between an interior chamber of the storage compartment and the process chamber, the storage compartment including a storage and calibration medium within the interior chamber of the storage compartment, a sensing structure extending through at least a portion of the storage compartment and into the interior of the process chamber, the sensing structure including a sensing surface exposed to the storage and calibration medium within the storage compartment, and a

sealing structure disposed adjacent or within the aperture extending between an interior chamber of the storage compartment and the process chamber, the sealing structure cooperating with an inactive portion of the sensing structure to form a seal inhibiting flow of the storage and calibration medium through the aperture,

[0013] The interior of the process chamber and the interior chamber of the storage chamber can form part of a sealed and sterilized portion of the single-use bioreactor component. The process chamber can include a single-use bioreactor bag. The process chamber can include a fluid channel configured to be placed in communication with a bioreactor chamber. The sensing structure can be configured to be moved between a first position in which the sensing surface is exposed to the storage and calibration medium within the storage compartment, and a second position in which the sensing surface is exposed to the interior of the process chamber, and the sealing structure can be configured to maintain the seal inhibiting flow of the storage and calibration medium through the aperture during movement of the sensing structure between the first position and the second position. A shape of the surface of the portion of the sensing element in contact with the sealing element can remain substantially constant during movement of the sensing element from the first position to the second position. The single-use bioreactor component can additionally include at least one sterile port in communication with the interior chamber of the storage compartment to allow access to the storage and calibration medium without compromising the sterility of the single-use bioreactor component.

[0014] In another embodiment, a single-use bioreactor component is provided, including a process compartment configured to retain a process medium therein, a storage compartment including an aperture extending therethrough, the storage compartment containing a calibration medium, a sensing structure, where a first portion of the sensing structure is in fluid communication with the process compartment, and where a second portion of the sensing structure is in fluid communication with the storage compartment, the second portion of the sensing structure including a sensing surface, and a sealing structure disposed adjacent or within the aperture in the storage compartment, the sealing structure cooperating with a portion of the sensing structure to form a seal inhibiting flow of the calibration medium through the aperture.

[0015] The sensing structure can be configured to be moved between a first position in which the first portion of the sensing structure is in fluid communication with the process compartment, and a second position in which at least part of the second portion of the sensing structure is in fluid communication with the storage compartment to expose the sensing surface to the process compartment. The sealing structure can be configured to maintain the seal inhibiting flow of the storage and calibration medium through the aperture during movement of the sensing structure between the first position and the second position. The sensing structure can be rotated between the first position and the second position. The sensing structure can be translated between the first position and the second position. A surface profile of the portion of the sensing element in contact with the sealing element can remain substantially constant during movement of the sensing structure from the first position to the second position.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0016] FIG. 1 is a side cross-sectional view schematically illustrating an embodiment of a pH sensing element.

[0017] FIG. 2 is a side cross-sectional view schematically illustrating an embodiment of a pH sensing element including a sensing structure located at a point located away from the end of the structure.

[0018] FIG. 3A is a side cross-sectional view schematically illustrating an embodiment of a sensor

structure including a sensing element such as the sensing element of FIG. 2 and a storage compartment containing a calibration solution.

[0019] FIG. 3B is a side cross-sectional view schematically illustrating the sensor structure of FIG. 3A, with the sensing element displaced to expose the sensing structure.

[0020] FIG. 4A is a side cross-sectional view schematically illustrating the sensor structure of FIG. 3A, shown in a sealed position relative to media to be tested.

[0021] FIG. 4B is a side cross-sectional view of the sensor structure in FIG. 4A, shown in an extended position in which the sensing structure of the sensing element is exposed to the media to be tested.

[0022] FIG. 5A is a side cross-sectional view schematically illustrating an embodiment of a sensor structure including a dual-chamber storage/calibration compartment, with the sensing structure of the sensing element located in the upper chamber.

[0023] FIG. 5B is a side cross-sectional view of the sensor structure of FIG. 5A, with the sensing structure of the sensing element located in the lower chamber.

[0024] FIG. 5C is a side cross-sectional view of the sensor structure of FIG. 5A, with the sensing structure of the sensing element exposed to the exterior of the storage/calibration compartment.

[0025] FIG. 6 is a side cross-sectional view schematically illustrating an embodiment of a storage compartment configured to retain therein a pair of sensing elements oriented parallel to one another.

[0026] FIG. 7 is a side cross-sectional view schematically illustrating an embodiment of a sensor structure including a sensing element such as the sensing element of FIG. 2 and a storage compartment including two ports allowing access to the storage medium inside the storage compartment.

[0027] FIG. 8 is a side cross-sectional view schematically illustrating an embodiment of a sensor structure including a sensing element such as the sensing element of FIG. 2 and a storage compartment, where the storage compartment is disposed adjacent a portion of a fluid path.

[0028] FIG. 9A is a perspective view schematically illustrating another embodiment of a sensing element. FIG. 9B is a side view schematically illustrating the sensing element of FIG. 9A.

[0029] FIG. 10A is a side view schematically illustrating an embodiment of a sensor structure including the sensing element of FIG. 9A, shown in a position in which the sensing surface is exposed to a storage/calibration medium.

[0030] FIG. 10B is a cross-sectional view of the sensor structure of FIG. 10A, taken along the line 10B-10B of FIG. 10A.

[0031] FIG. 10C is a side view of the sensor structure of FIG. 10A, with the sensing element moved to a position in which the sensing surface can be exposed to a process medium.

[0032] FIG. 11A is a side view of another embodiment of a sensor structure including a sensing element such as the sensing element of FIG. 2 and a storage compartment containing a calibration solution, shown inserted into a tube port. FIG. 11B is a perspective view of the sensor structure of FIG. 11A.

[0033] FIG. 11C is a perspective view of an embodiment in which a supplemental securement device is used to secure the sensor structure of FIG. 11A relative to the tube port.

[0034] FIGS. 12A and 12B are cutaway figures which illustrate the internal components of the sensor structure of FIG. 11A in a retracted and extended configuration, respectively.

[0035] FIG. 13A is a side view of another embodiment of a sensor structure including a sensing element such as the sensing element of FIG. 2 and a storage compartment containing a storage solution, configured to be inserted into a tube port. FIG. 13B is a side view of the sensor of FIG. 13A, shown in an extended position.

[0036] FIG. 14A is a cross-sectional perspective view of the sensor structure of FIG. 13A, shown in a retracted position. FIG. 14B is a cross-sectional perspective view of the sensor structure of FIG. 13A, shown in an extended position.

[0037] FIG. 15 is a top cross-sectional view schematically illustrating an embodiment of a sensor structure including a sensing element which can be rotated to expose a sensing surface to a process medium.

[0038] FIG. 16A is a perspective view of another embodiment of a sensor structure including a sensing element configured for use in a flow-through arrangement and comprising a storage compartment containing a calibration solution.

[0039] FIG. 16B is a side cross-sectional view of the sensor structure of FIG. 16A, with the sensor shown in a position in which the sensing element is exposed to calibration solution. FIG. 16C is a side cross-sectional view of the sensor structure of FIG. 16A, with the sensor shown in a position in which the sensing element is exposed to an inline flow-cell chamber.

[0040] FIGS. 17A and 17B are perspective view of another embodiment of a sensor structure including a sensing element configured for use in a flow-through arrangement and comprising a storage compartment containing a storage solution. FIG. 17C is a top plan view of the sensor structure of FIG. 17A.

[0041] FIG. 17D is a side cross-sectional view of the sensor structure of FIG. 17A, taken along the line A-A of FIG. 17C, with the sensor shown in a position in which the sensing element is exposed to an inline flow-cell chamber.

[0042] FIG. 17E is another side cross-sectional view of the sensor structure of FIG. 17A in the same position as FIG. 17D, taken along the line A-A of FIG. 17C, with the sensor shown in a position in which the sensing element is exposed to an inline flow-cell chamber, where the pressure within the inline flow-cell chamber causes deformation of a pressure equalization diaphragm.

DETAILED DESCRIPTION

[0043] FIG. 1 is a side cross-sectional view schematically illustrating a pH sensing element. The sensing element **100**, which may be a pH glass electrode, includes a body **102** having a half-cell element lead **104** and an internal electrolyte **106** retained within a hollow space within the body **102**, and sealed in place by a seal **108**. The sensing element **100** may also include or be in electrical communication with a reference electrode (not shown).

[0044] The distal end of the sensing element **100** includes a pH sensing glass electrode **110**, which serves as a sensing surface of the sensing element **100**. In some embodiments, this glass electrode **110** can be formed by being blown into a bulb shape at the end of the electrode stem glass tubing. By immersing the sensing element into a process medium or other medium to be measured, such that the sensing surface of the sensing element is immersed in the process medium, a voltage indicative of the pH of the process medium can be measured.

[0045] In some embodiments, a measurement of a process medium retained in a bioreactor can be made. In some embodiments, a bioreactor can include rigid walls, and a sensor can be configured such that a sensing element can be inserted through a port in the rigid wall of the bioreactor, with the rigidity of the bioreactor wall providing mechanical support for a variety of different structures or mechanisms used to selectively expose a probe to the process medium therein.

[0046] In other embodiments, however, the bioreactor can include a bag or other flexible structure, which is filled with and retains the process medium. Such a flexible bioreactor may itself be seated within a rigid retaining vessel, but as the walls of the actual containment vessel retaining the process medium are flexible, probes and other components which are configured to be insertable through or otherwise extend through the wall of the flexible bioreactor.

[0047] For example, such components may be configured to be insertable through reinforced ports in the flexible bioreactor wall, such that the sterility and integrity of the flexible bioreactor are not compromised during the insertion process. In some embodiments, sensors may be built into the flexible bioreactor bag prior to the bioreactor being sterilized or filled with a process medium, or otherwise installed prior to the flexible bioreactor being sterilized. Other components, such as agitators, may be similarly insertable through ports in the flexible bioreactor, or may be provided within the bioreactor prior to sterilization and/or filling of the bioreactor with sterile components or

media. Because of manner in which a flexible bioreactor such as a flexible single-use bioreactor are manufactured, the sensor or other components of the single-use bioreactor may not be easily accessible to the end user for the purposes of calibration or performance verification, as they cannot be removed or retracted without breaching the sterile barrier.

[0048] In some embodiments, a sensor can include a storage compartment or chamber surrounding at least a portion of the sensing element therein, where the sensing surface at the distal end of a sensing element is stored within a storage medium. Storage of the sensing surface of the sensing element, along with other components of the sensor such as a reference electrode, may be used to enable deployment of the sensor on-demand, without the need to wet the sensing surface for a period of time before measurements can be taken. In some embodiments, the storage medium may also be used as a calibration solution, by using the sensor to take a measurement of the known pH of the storage medium prior to deployment of the sensing element into the process medium. This can allow calibration of the sensor even when the sensor is stored within the sealed storage compartment, and inaccessible to the end user. In some embodiments, a significant period of time may elapse between the time at which the sensor is sealed into or relative to the sterile environment of a single-use bioreactor bag or component to be used with such a single-use bioreactor bag, sometimes on the order of several years. On-site calibration prior to use of the sensor can be needed to ensure that an accurate measurement can be obtained using the sensor.

[0049] When a measurement of the process medium is desired, the sensing element can be pushed into the process medium, immersing the sensing surface and reference electrode of the sensor into the process medium. In doing so, because the sensing surface of the sensing element is located at the distal end of the sensing element, the storage solution is exposed to the process medium, so that any fluid remaining in the storage chamber is intermixed with the process medium. As the storage chamber can be substantially smaller than the volume of the process medium, the storage medium will be dispersed into the process medium, and the fluid remaining within the storage chamber, if any, will be substantially the same composition and pH of the process medium.

[0050] In some embodiments, an alternative sensing element design may be used, and the alternative sensing element design may enable a variety of different single-use sensor designs. FIG. 2 is a side cross-sectional view schematically illustrating a pH sensing element including a sensing structure located at a point located away from the end of the structure. The sensing element **200** is similar to the sensing element **100** of FIG. 1, including a body **202** having a hollow space therein, in which a half-cell element lead **204** and an internal electrolyte **206** are located, and a seal **208** retained those components within that hollow space. However, the sensing element **200** differs in that the sensing surface **210**, which as discussed above may be a glass pH electrode, is located at a point away from the very distal end **218** of the sensing element **200**.

[0051] In particular, it can be seen that the sensing element **200** includes a proximal portion **212**, whose outer surface does not contain a sensing surface **210**, as well as a distal portion **214** which also does not contain a sensing surface **210**. The sections of the sensing element **200** which do not contain a sensing surface **210**, liquid junction, or similar component, may be referred to herein as inactive portions of the sensing element. The sensing surface **210** may comprise, for example, a cylindrical outer section of the body **202** of the sensing element **200**, but need not extend around the entire outer perimeter of the body **202**. For example, in some embodiments, the sensing surface **210** may be a section of a glass pH electrode or other suitable sensing surface in any desired shape.

[0052] In other embodiments, the sensing surface **210** may comprise glass, metal, electronic components, or any other suitable sensing structure. In some embodiments, the sensing surface **210** may comprise semiconductor components, such as thermistors and resistors, or may comprise integrated circuits such as ion-sensitive field-effect transistors (ISFETs). The sensing element **200** may be a part of any sensor, including sensors that reference voltage, current, capacitance, resistance, frequency, or luminescence. Although many embodiments herein are described in the context of pH sensors which can be used with single-use flexible bioreactor bags, embodiments of

sensing elements and other components described herein can also be used in a wide range of other sensor types and applications.

[0053] The body **202** can be any suitable shape. However, in some embodiments, the body **202** may include a section of substantially constant cross-section extending at least from a point proximal the proximal end of the sensing surface **210**, within the proximal section **212** of the sensing element **200**, to a point distal the distal end of the sensing surface **210**, within the distal section **214**. When viewed in cross-section, it can be seen that the outer surface of the sensing surface **210** is substantially coplanar with the adjacent proximal and distal sections **212** and **214** of the sensing element **200**. As described in greater detail below, such a sensing element **200** can be translated in the direction of its longitudinal axis, relative to a storage chamber, while minimizing fluid flow into or out of the storage chamber.

[0054] A sensor including the sensing element **200** may also include additional components not specifically illustrated in FIG. 2. For example, the sensor may include a reference electrode which may in some embodiments be integrated within the structure of the sensing element **200** (see, for example, FIGS. 4A and 4B). In other embodiments, described in more detail with respect to FIG. 6, a reference electrode may be located within a separate structure, which may in some embodiments extend along a parallel longitudinal axis to the longitudinal axis of the sensing element **200**.

[0055] FIG. 3A is a side cross-sectional view schematically illustrating a sensor structure including a sensing element such as the sensing element of FIG. 2 and a storage compartment containing a calibration medium. In FIG. 3A, the sensing element **200** is positioned such that it extends through a storage compartment **300** having an internal storage chamber **320** filled with a material which serves as both a storage medium and a calibration medium **322**. In some embodiments, the storage/calibration medium **322** may comprise a fluid, while in other embodiment, other forms of storage/calibration media may be used. For example, if the sensing element comprises a dissolved oxygen (DO) sensor, the storage/calibration medium may comprise a gas.

[0056] In particular, the sensing element **200** extends through both a proximal aperture of the storage compartment **300** having a proximal sealing element **310a** positioned therein, and a distal aperture of the storage compartment **300** having a distal sealing element **310b** positioned therein. The sensing element **200** extends along a longitudinal axis which passes through the centers of the proximal and distal apertures of the storage compartment **300**.

[0057] In the position illustrated in FIG. 3A, the sensing element **200** of the probe is shown in a retracted position, in which the sensing surface **210** of the sensing element **200** is disposed within the storage compartment **300** and immersed in the storage/calibration medium **322**. Because the sensing surface **210** is not located at the distal end **218** of the sensing element **200**, the sensing element **200** includes an inactive distal portion **214** which can be exposed to a process medium or any other material without affecting the voltage (or other information) provided by the sensing element **200**. In addition, because the inactive distal portion **214** does not include a sensing surface **210**, the sensing element can be stored with part of the inactive distal portion **214** exposed, without affecting the sensing element **200** or requiring advance preparation before the sensing element **200** can be used in a measurement.

[0058] In particular, it can be seen in FIG. 3A that the inactive distal portion **214** interacts with the distal scaling element **310b** to form part of the boundary encapsulating the storage/calibration medium **322** within the internal storage chamber **320** of the storage compartment **300**. This is in contrast to the types of storage configurations required by the use of a sensing element such as the sensing element **100** of FIG. 1, having a sensing surface at the distal tip. If the sensing surface were at the distal end, storage of the sensing element with its distal end exposed would expose an active section of the sensing element to the exterior of the storage chamber, such that it would not be exposed to the storage medium. This could have a detrimental effect on the operation of the sensing element. In addition, more complex and mechanisms would be required to allow the sensing surface to be extended into the process medium to be tested, such as piercing a seal, or otherwise

placing the interior of a storage chamber in fluid communication with the process medium. Such mechanisms would have irreversible effects on at least the composition of the fluid within the storage chamber, either by draining the storage chamber or allowing the storage medium to intermix with the process medium.

[0059] In contrast, the configuration of FIG. 3A allows the sensing element **200** to be extended into the process medium, without placing the internal storage chamber **320** in fluid communication with the exterior of the storage compartment **300**. FIG. 3B is a side cross-sectional view schematically illustrating the sensor structure of FIG. 3A, with the sensing element displaced to expose the sensing structure. In the position shown in FIG. 3B, the sensing element **200** has been longitudinally translated along the longitudinal axis of the sensing structure, such that the sensing surface **210** is now located outside of the sensing compartment **300**. The proximal portion of the sensing element **200** now interacts with the distal sealing element **310b** to form part of the boundary encapsulating the storage/calibration medium **322** within the internal storage chamber **320** of the storage compartment **300**.

[0060] In some embodiments, the proximal and distal sealing elements **310a** and **310b** may be O-rings or any other suitable gasket or sealing element which maintains a substantially fluid tight seal even when the sealing element is being translated therethrough. The tolerance of the O-rings or other sealing element allows maintenance of the fluid seal even though the cross-sectional shape of the sensing element **200** may vary somewhat over the length of the sensing element **200**.

[0061] During the translation of the sensing element **200** through the distal sealing element **310b**, the seal is maintained, due to the outer cross-sectional area of the portion of the sensing element **200** in contact with the distal sealing element **310b** being substantially constant, within the tolerance of the distal sealing element **310b**. Even if some small amount of fluid is pulled out along with the exposed section of the sensing element **200**, for example due to irregularities in the shape of the outer surface, the total volume of fluid exchange between the interior and the exterior of the storage compartment **300** may be minimal, and significantly less than embodiments in which the storage compartment is drained or completely exposed when the sensing element is extended. Thus, the volume of storage/calibration medium **322** pulled out of the storage compartment **300** may be less than substantially the entire volume of the storage compartment **300**, in contrast to single use sensor designs in which the distal end of the sensing element is an active portion of the sensing element. In embodiments in which the interior of the storage compartment is exposed to the process medium, nearly all of the storage medium flows out of the storage compartment **300** due to draining or intermixing with the process medium, the volume of which can be substantially larger than the volume of the storage medium.

[0062] In contrast, through the use of media-retaining storage compartments as described herein, a greater amount of the storage/calibration medium can be retained after the sensor is extended (and retracted) into the storage medium. For example, more than 10% of the storage/calibration medium may be retained in the storage compartment, more than 30% of the storage/calibration medium may be retained in the storage compartment, more than 50% of the storage/calibration medium may be retained in the storage compartment, more than 70% of the storage/calibration medium may be retained in the storage compartment, more than 90% of the storage/calibration medium may be retained in the storage compartment, more than 95% of the storage/calibration medium may be retained in the storage compartment, more than 97% of the storage/calibration medium may be retained in the storage compartment, more than 98% of the storage/calibration medium may be retained in the storage compartment, or more than more than 99% of the storage/calibration medium may be retained in the storage compartment.

[0063] The sensor structure of FIG. 3A can be integrated into or otherwise installed in a bioreactor such as a flexible single-use bioreactor bag. FIG. 4A is a side cross-sectional view schematically illustrating the sensor structure of FIG. 3A, shown in a sealed position relative to media to be tested. It can be seen that the proximal side of the storage compartment **300** is attached to,

integrated with, or otherwise secured relative to the flexible wall **400** of the bioreactor, such that the storage compartment **300** is located on the interior of the bioreactor, and extends into the process medium **410**. In other embodiments, however, the storage compartment **300** may be located at least partially outside of the wall **400** of the bioreactor, or entirely outside the wall of the bioreactor, and a wide variety of suitable configurations may be used.

[0064] When the sensing element is in the retracted position of FIG. 4A, the distal sealing element **310b** maintains a fluid-tight seal between the storage/calibration medium **322** and the process medium **410**. The composition of the storage/calibration medium **322** remains constant and the pH remains at a known, constant value. At some point prior to extension of the sensing element **420** into the process medium **410**, a validation or calibration process may be performed by measuring the voltage from the sensing element **200** to confirm that it is consistent with the expected reading, based on the known pH of the storage/calibration medium **322**.

[0065] It can also be seen in FIG. 4A that the sensing element **200** includes an integrated reference electrode as part of the single structure. The sensing element **200** includes an internal wall separating a first internal region of the body **202** from a second internal region. The first internal region includes the half-cell element lead **204** and a volume of internal electrolyte **206** in fluid communication with the sensing surface **210**, while the second internal region includes a half-cell element lead **264** and a second volume of internal electrolyte **266** in fluid communication with a liquid junction **260**. When in the position shown in FIG. 4A, both the sensing surface **210** and the liquid junction **260** are in contact with the storage/calibration medium **322**.

[0066] The sensing element **200** may be moved in the longitudinal direction to the position shown in FIG. 4B. During this process, the distal sealing element **310b** maintains a fluid seal with the constant-diameter section of the sensing element **200**, preventing or minimizing fluid exchange between the storage/calibration medium **322** and the process medium **410**. When in the position shown in FIG. 4B, both the sensing surface **210** and the liquid junction **260** are in contact with the process medium **410**, as the length of travel is sufficient that both the sensing surface **210** and the liquid junction **260** pass through the sealing element. To maintain the fluid-tight seal, the section of substantially constant cross-sectional area includes the section of the sensing element **200** which includes both the sensing surface **210** and the liquid junction **260**. When in the extended position, the pH of the process medium **410** may be measured by measuring the voltage from the sensing element **200**, when the sensing surface **210** and the liquid junction **260** are immersed in the process medium **410**.

[0067] Once the pH of the process medium **410** is measured, the sensing element **200** can then be retracted into the storage compartment **300**. The distal scaling element **310b** again operates to prevent or minimize fluid exchange between the storage/calibration medium **322** and the process medium **410** by maintaining a fluid-tight seal during the retraction. The shape and configuration of the sensing element **200** allow the storage/calibration medium **322** to be retained within the storage compartment **300** even after the extension and retraction of the sensing element **200**. In contrast to other designs in which the storage medium is not retained, or mixes with the process medium, the sensing surface **210** of the sensing element **210** is retained within a storage/calibration medium **322** of known composition and pH, due to the lack of significant mixing of the storage/calibration medium **322** with the process medium **410**. This enables a post-measurement calibration or validation process, in which the voltage from the sensing element **200** is measured to confirm that it is consistent with an expected reading, based on the known pH of the storage/calibration medium **322**, to confirm that the probe is operating correctly. This can be done in a non-destructive fashion, without cutting into the flexible wall **400** or otherwise removing the sensing element **200** from the bioreactor.

[0068] By inhibiting fluid flow between the storage/calibration medium **322** and the process medium **410**, a wider range of possible compositions of the storage/calibration medium **322** may be possible. If a storage compartment is designed such that all of the storage medium contained

therein will be mixed with the process medium, the composition of the storage medium may be chosen so that it will have a pH near 7.0 at room temperature, so as to have a minimal effect on the pH or composition of the process medium. If, however, the storage/calibration medium **322** can be retained within the storage compartment, with minimal if any mixing with the process medium, storage/calibration media with a wider range of possible compositions and pH may be used. For example, in one embodiment, a storage/calibration medium **322** with a pH of roughly 4.0 at room temperature may be used. By providing a larger difference between the pH of the storage/calibration medium **322** and the expected pH of the process medium **410**, an error in the operation of the sensing element will be more apparent, as the measured voltage will differ from the expected voltage by a larger amount.

[0069] In other embodiments, storage/calibration media having a pH of 4.01, 6.86, 9.18, or 10.05 at room temperature may be used. However, a wide variety of other pH ranges may also be suitable as storage/calibration media. In some embodiments, the pH at room temperature may be between 0 and 14, between 1 and 13, between 3 and 12, between 4 and 10.5, between 5 and 10.5, or between 6 and 10.5. In some embodiments, the pH at room temperature may be less than 6.5, less than 6.0, less than 5.0, or less than 4.0.

[0070] In embodiments in which the sensing structure comprises a type of sensor other than a pH sensor, the calibration medium may be chosen based on the property to be measured by the sensor. As discussed above, the calibration medium may comprise a gas or other material.

[0071] Even in the case of a smart sensor, in which the calibration can be performed prior to sterilization and subsequent installation into a flexible bioreactor bag, and the calibration data stored in a memory circuit of the smart sensor, the use of the storage medium as a calibration medium can still provide a verification of the continued functionality of the smart sensor, as a measurement sufficiently different from the known pH of the storage medium can provide an indication that the sensor has failed or is otherwise not providing an accurate measurement of the pH to which the sensing surface is exposed. Because this storage solution is maintained in substantially its original state, with minimal if any exposure to the process medium, this verification or failure check can also be performed after the sensing element is retracted back into the storage chamber. If the pH measurement of the process medium is different from an expected measurement, the retraction and subsequent measurement of the sensing element of the probe when exposed to the storage solution can provide a rapid and non-destructive check or verification of the operation of the measurement probe while the process is still ongoing. Because the calibration medium is retained in the storage compartment, the sensing element can be moved to a medium with known pH without the need to compromise the sterility of the ongoing process by physically removing the engaged probe structure from the flexible bioreactor and compromising the sterility of the process medium.

[0072] In some embodiments, the shape of the sensing element can be used in conjunction with a dual-chambered storage compartment to provide two-point on-site calibration of a sensor, or two-point verification. FIG. 5A is a side cross-sectional view schematically illustrating a sensor structure including a dual-chamber storage/calibration compartment, with the sensing structure of the sensing element located in the upper chamber. The storage compartment **500** is similar to the storage compartment **300** of FIG. 3A, but differs in that it includes an internal wall separating a distal chamber **520b** from a proximal chamber **520a**. The sensing element **200** cooperates with an internal sealing element **510c** to maintain a seal between the proximal and distal chambers **520a** and **520b**. Because this internal seal will be maintained during translation of the sensing element **200** through the storage compartment **500**, with minimal fluid flow between the chambers, the proximal chamber **520b** may retain a storage/calibration medium **522a** different from the storage/calibration medium **522b** in the distal chamber **520b**. In some embodiments, one of the chambers may include a medium which functions only as a calibration medium, with the sensing surface **210** of the sensing element being stored in the other of the two chambers for extended

periods of time.

[0073] When the pH of the storage/calibration medium **522a** differs from the pH storage calibration medium **522b**, a two-point validation or calibration process may be performed prior to and/or after measurement of a process medium. The voltage of the sensing element **200** may be measured when the sensing surface **210** is immersed in the storage/calibration medium **522a**.

[0074] The sensing element **210** may then be translated in the distal direction. FIG. 5B is a side cross-sectional view of the sensor structure of FIG. 5A, with the sensing structure of the sensing element located in the lower chamber. The voltage of the sensing element **200** may also be measured when the sensing surface **210** is immersed in the storage/calibration medium **522b**. The measured voltage when the sensing surface **210** is exposed to the storage/calibration media **522a** and **522b** can be compared with the expected voltages at the known pH values of the storage/calibration media **522a** and **522b**, and used to verify or calibrate the sensing element **200**.

[0075] Once done, the sensing element **200** may then be extended into a process medium for testing and used for measurement and control of the process. FIG. 5C is a side cross-sectional view of the sensor structure of FIG. 5A, with the sensing structure of the sensing element exposed to the exterior of the storage/calibration compartment. After measurement of the process medium, the sensing element may then be retracted through both chambers **520a** and **520b**, and measurements may be taken in each chamber as part of a post-measurement validation process.

[0076] As discussed elsewhere herein, the sensing structure may also include additional components not specifically illustrated in the figures, such as a reference electrode. FIG. 6 is a side cross-sectional view schematically illustrating a storage compartment configured to retain therein a pair of sensing elements oriented parallel to one another. The storage compartment **600** differs from the storage compartment **300** of FIG. 3A in that the storage compartment **600** includes a pair of proximal sealing elements **610a** and **640a** and a pair of distal sealing elements **610b** and **640b**. The sealing elements **610a** and **610b** are dimensioned and spaced to receive the sensing element **200**, while the sealing elements **610b** and **610b** are dimensioned and spaced to receive a separate sensing element **650**, which may serve as the reference electrode for a probe.

[0077] The reference half-cell element **650** includes a liquid junction **660**, and can be configured to move along with the sensing element **200** such that when the sensing surface **210** is exposed to the storage/calibration medium **322**, the liquid junction **660** is as well. Similarly, when the sensing surface **210** is exposed to a process medium **322**, the liquid junction **660** will also be exposed to the process medium. A section of substantially constant cross-sectional area extending to either side of the sensing surface **600** allows the sealing element **610b** to maintain a fluid-tight seal during translation of the reference half-cell element **650** therethrough.

[0078] Although the embodiments described herein are primarily described in the context of pH sensors in conjunction with bioreactors, the features described herein can be utilized in conjunction with other types of sensors, and in other contexts. For example, in addition to use with bioreactor bags, or tubing or other conduits in fluid communication with bioreactor bags, the sensing elements and associated components may be used with or integrated into a wide variety of other elements in a process flow. These elements may be flexible bags or other containers used in media preparation, upstream of a cell culture, as well as in various purification steps downstream of a cell culture. Similarly, embodiments may be used in any other suitable application, in conjunction with any suitable type of sensor. For example, the storage compartment and sensing element geometry can be used to facilitate on-site calibration during, for example, field testing of pH or other measurements, with the ability to retract the measurement probe into a storage compartment that protects the probe and allows for calibration or verification of the probe operation before or after tests.

[0079] In some embodiments, a storage compartment can include port or other opening to replace, alter, or otherwise interact with the storage/calibration medium. FIG. 7 is a side cross-sectional view schematically illustrating a sensor structure including a sensing element such as the sensing

element of FIG. 2 and a storage compartment including two ports allowing access to the storage medium inside the storage compartment. The storage compartment **700** includes a first port **780a**, which may serve as an inlet port, extending through an aperture **770a** in the wall of the storage compartment **700**, and a second port **780b**, which may serve as an outlet port, extending through an aperture **770b** in the wall of the storage compartment **700**. The ports **780a** and **780b** may include filters, which may in some embodiments be submicron filters. The ports **780a** and **780b** allow access to the storage/calibration medium **722** within the storage compartment **700** without compromising the sterility of the storage compartment **700**. This can be used to replace, refill, or otherwise alter the volume or composition of the storage/calibration medium **722** within the storage compartment **700**.

[0080] In certain embodiments discussed herein, the operation of a sensing element in conjunction with a media-preserving storage and calibration chamber is discussed in the context of extending the sensing element into a flexible bioreactor bag or similar process container to access the process medium. In other embodiments, however, the sensing element may be used in conjunction with a tube or other component which is in fluid communication with the process container, or can be selectively placed in fluid communication with the process container. In some embodiments, the sensing element can be extended into a cavity through which process medium or other medium to be tested is flowing.

[0081] FIG. 8 is a side cross-sectional view schematically illustrating a sensor structure including a sensing element such as the sensing element of FIG. 2 and a storage compartment, where the storage compartment is disposed adjacent a portion of a fluid path. In FIG. 8, the storage compartment **300** is located adjacent a fluid or gas conduit **800**, such that the sensing element **200** can extend into the conduit **800** and expose the sensing surface **210** (and liquid junction **260**, if integrated within the sensing element **200**) into the medium **822** within the conduit **800**. In some embodiments, the medium **822** may be flowing through the conduit **800** during at least part of this process.

[0082] In the illustrated embodiment, the conduit **800** includes a section **820** having a larger cross-sectional area than adjacent sections **880** of the conduit **800**. Such a configuration can be used when the cross-sectional area of the conduit **800** is small enough relative to the size of the exposed portion of the sensing element **200** that the sensing element **200** could not extend a sufficient distance into the conduit **800** to expose the sensing surface **210** and liquid junction **260**, or would significantly occlude the flow of the medium **822** through the conduit **800**. In embodiments in which the medium **822** is flowing through the conduit **800**, the sensing element **200** may remain in an extended position to measure a property of the medium **822** at multiple points in time. Multiple measurements over a period of time may also be made in any of the embodiments discussed herein, such as to measure the progress of a process over time.

[0083] In other embodiments, the sensing element need not be cylindrical, but may be any suitable shape. FIG. 9A is a perspective view schematically illustrating another embodiment of a sensing element. FIG. 9B is a side view schematically illustrating the sensing element of FIG. 9A. The sensing element **900** includes a planar side **902**, and a sensing surface **910** located on or in the planar side **902**. In the illustrated embodiment, the sensing element **900** is in the shape of a rectangular prism, but in other embodiments, any other suitable shape may be used. The side having the sensing surface **910** need not be planar, but may be any suitable shape, as described in greater detail below. The sensing element **900** may also include a half-cell element lead and an internal electrolyte, as discussed elsewhere herein, and may also include an integrated reference electrode, which may include a liquid junction adjacent the sensing surface **910**.

[0084] FIG. 10A is a side cross-sectional view schematically illustrating a sensor structure including the sensing element of FIG. 9A, shown in a position in which the sensing structure is exposed to a storage/calibration medium. FIG. 10B is a cross-sectional view of the sensor structure of FIG. 10A, taken along the line **10B-10B** of FIG. 10A. The sensor structure **1000** includes a pair

of apertures **1012a** and **1012b**, surrounded by sealing elements **1010a** and **1010b**, respectively. The sealing elements may comprise O-rings or other gaskets, or any other suitable sealing structure. One aperture is in fluid communication with a storage compartment **1020** containing a storage medium **1022**, which may also serve as a calibration medium. The other aperture is in fluid communication with an area which may be filled with or otherwise exposed to a process medium to be tested. The planar side **902** of the sensing element cooperates with the sealing element **1010a** to retain the storage/calibration medium **1022** within the storage compartment **1020**. In the position shown in FIG. **10A**, the sensing surface **910** of the sensing element **900** is exposed to the storage/calibration medium in the storage compartment **1020**.

[0085] FIG. **10C** is a side view of the sensor structure of FIG. **10A**, with the sensing element moved to a position in which the sensing surface can be exposed to a process medium. The sensing element **900** is translated in a direction parallel to the planar side **902**, such that the planar side **902** slides along the sealing elements **1010a** and **1010b** until the sensing surface **910** is aligned with the aperture **1012b**, allowing exposure of the sensing surface **910** to a process medium to be tested.

[0086] FIG. **11A** is a side view of another embodiment of a sensor structure including a sensing element such as the sensing element of FIG. **2** and a storage compartment containing a storage solution, shown inserted into a tube port. FIG. **11B** is a perspective view of the sensor structure of FIG. **11A**.

[0087] The sensor structure **1500** may be a single-use sensor such as a single-use pH sensor, and includes a sensor housing **1502** which includes a storage compartment **1540** containing a storage solution **1542**. The sensor housing **1502** can be secured relative to a tube port **1400** as shown, or other suitable structure. The sensor structure **1500** also includes a movable component **1504** which is longitudinally translatable relative to the sensor housing **1502**, and which supports a sensing element **1520** such as the sensing element **200** of FIG. **2**.

[0088] A scaling element such as an external gasket **1528** or O-ring cooperates with the internal surface of the tube port **1400** to maintain the integrity of the bioreactor bag in which the tube port **1400** is installed. To illustrate the fit of sensor structure **1500** within tube port **1400**, FIG. **11A** shows the tube port **1400** in partial cutaway view, whereas FIG. **11B** shows the external surface of the tube port **1500**. The external gasket **1528** is located between the sensor housing **1502** and the tube port **1400**, and does not extend through the interior of the storage compartment **1540** or contact the storage solution **1542** inside. A connector **1580** extending from the proximal end of the sensor structure **1500** allows connections to be made with an external instrument or system.

[0089] Translation of the movable component **1504** of the sensor structure **1500** allows the sensing element **1520** to be translated moved from a first position in which the sensing surface **1522** of the sensing element **1520** is retained within the storage compartment **1540** and exposed to the storage solution **1542**. The sensing element **1520** can be moved to a second position in which the sensing surface **1522** has been translated through the distal internal gasket near the distal tip **1510** of the sensor housing **1502**, allowing exposure of the sensing surface **1522** to a process medium.

[0090] Control over the longitudinal translation of the movable component **1504** and the sensing element **1520** with respect to the sensor housing **1502** can be provided through the use of an outwardly extending bolt **1552** or other feature which is retained within a longitudinally-extending aperture **1590** in the sensor housing **1502**. In the illustrated embodiment, the aperture **1590** includes a distal wider region **1592a** and a proximal wider region **1592b** connected to one another by a narrower longitudinal channel **1594**. The aperture **1590** can be dimensioned, in conjunction with other components and features of the sensor structure **1500**, to define or constrain the manner in which the movable component **1504** can be moved relative to the sensor housing **1502**.

[0091] In one embodiment, the bolt **1552** may have a shape which varies over the height of the bolt, and may be resiliently supported by a cantilevered portion of the movable component. In particular, an upper section of the bolt **1552** may have a narrower section, allowing it to be translatable along the narrower longitudinal channel **1594** when the bolt **1552** is pressed inwards.

When the bolt is no longer pressed inwards, it will flex back outwards, and the thicker lower section of the bolt **1552** will retain the bolt in place within one of the wider regions **1592a** or **1592b**. Outwardly extending grips or wings **1554** can assist with translation of the movable component of the sensor **1500** relative to the housing, and may be movable through longitudinal channels in the sensor housing **1502**.

[0092] Other configurations are possible, as well. In another embodiment, the bolt **1552** or similar structure may include a rotatable section, such that the bolt must be rotated to a particular position to be translatable along the narrower longitudinal channel **1594**, and can then be rotated back once in place in one of the wider regions **1592a** or **1592b** to retain the movable component of the sensor **1500** relative to the sensor housing **1502**.

[0093] FIG. **11C** is a perspective view of an embodiment in which a supplemental securement device is used to secure the single-use sensor relative to the tube port. It can be seen in FIG. **11C** that a length of tubing **1450** extends over the point at which the proximal end of the tube port abuts a facing surface of the sensor housing **1502**. A first compressive member **1442** is located proximal the flared proximal portion **1530** of the sensor housing **1502** and a second compressive member **1444** is located distal the flared portion **1430** of the tube port **1400** which abuts the flared portion **1530** of the sensor housing **1502**. In some embodiments, the compressive members **1442** and **1444** comprise zip ties, bands, or similar structures.

[0094] The compressive members **1442** and **1444** crimp the outer edges of the tubing **1450** and cooperate with the flared sections of the collar portions **1430** and **1530** to prevent the single use sensor **1500** from being removed from the tube port **1400**. Other suitable retention methods can also be used, including snap fit or clamshell type devices which can fit over the abutting portions of the sensor **1500** and the tube port **1400**. At least a portion of the tubing **1450** may be translucent or transparent to facilitate detection of leaks between the tube port **1400** and the sensor **1500**.

[0095] FIGS. **12A** and **12B** are cutaway figures which illustrate the internal components of the sensor structure of FIGS. **11A** to **11C** in both a retracted and extended configuration. In FIG. **12A**, it can be seen that the distal tip **1510** of the sensor housing **1502** has a smaller cross-sectional area than the remainder of the sensor housing **1502**, and that the distal internal gasket **1512** is secured within the region of smaller cross sectional size. By reducing the cross-sectional size of the sensor housing **1502** at the distal tip **1510**, the smaller distal internal gasket **1512** can be used to maintain a seal without the need to form a thicker section of the sensor housing wall. In other embodiments, however, the thickness of the wall of the sensor housing near the distal tip **1510** may be increase to provide a similarly-shaped interior space, with a wider outer cross-sectional shape. In addition, the size of the seal formed between the distal internal gasket **1512** and the sidewall of the sensing element **1520** is reduced, decreasing the possibility or the amount of leakage of storage solution **1542** from the storage chamber **1540**.

[0096] It can also be seen that when the movable component **1504** is in the retracted position, the tip of the sensing element **1520** is pulled back within the space between the distal internal gasket **1512** and the edge of the distal tip **1510** of the sensor housing **1502**, which may provide additional protection against damage to the sensor element and possible disruption of the seal between the distal internal gasket and the sensor element. In some embodiments, a protective structure such as a bumper or guard pins could overlie at least a portion of the tip of the sensing element. The use of a blunt protective structure can avoid perforation of a bioreactor bag in a folded position.

[0097] The proximal end of the storage compartment **1540** is defined by a plug **1560** including a proximal internal gasket **1562** which cooperates with the internal sidewall of the sensor housing **1502** to retain the storage solution **1542** within the storage compartment **1540**. A passage extending through the plug **1560**, which may include an internal gasket (not shown) allows a plunger **1564** supporting and retaining the sensing element **1520** to be translated longitudinally through the plug **1560** as the movable component **1504** is moved.

[0098] As can be seen in FIG. **12B**, when the sensing element **1520** is in an extended position, a

portion of the plunger **1564** which was originally located proximal of the plug **1560** is now extending into and in contact with the interior of the storage compartment **1540** and exposed to the storage solution **1542**. In order to maintain the sterility of the storage chamber **1540**, a bellows structure **1570** located proximal of the plug **1560** define a sterile and compressible area within which a proximal portion of the plunger **1564** is retained when the sensing element **1520** is in an unextended or retracted position.

[0099] In some embodiments, the sensing element may be a part of a smart sensor or similar structure, which includes, among other components, a memory circuit. In some embodiments, this memory can also be used to validate the operational history of such a smart sensor. Inadvertent or mistimed movement of the movable element of such a smart sensor that results in retraction of the sensing surface from the process media during the process can compromise the integrity of the sensor measurement and can affect the operation or outcome of a bioprocess with which the sensor is used.

[0100] In some embodiments, where feedback from a pH or similar sensor is used to manage a bioprocess, early or delayed exposure of the sensing surface to the process medium can cause the bioprocess to be incorrectly controlled. If a problem occurs with a bioreactor run, it may be necessary to demonstrate the root cause of this issue. By monitoring or recording indications that the sensing element was extended, the operational history of such a sensor can be monitored and preserved.

[0101] In some embodiments, the sensor can include a mechanism for detecting movement of the sensing element or another movable component of the sensor relative to the sensor housing. In one embodiment, this movement detection mechanism may include a mechanical contact, a proximity switch, or any other suitable mechanism for detecting or providing an indication of the relative position of a component of the sensor.

[0102] In some particular embodiments, movement of the movable component away from a particular position may be detected, while in other embodiments, movement to a particular position or past a particular position may be detected. In some embodiments, multiple detection mechanisms may be included, such as a first detection mechanism configured to detect movement of a component to or away from a first position, and a second detection mechanism configured to detect movement of the component to or away from a second position.

[0103] In an embodiment of a sensor structure such as the sensor structure of FIGS. **11A-12B**, movement of the sensing element **1520** can be detected via one or more movement detection mechanisms. These movement detection mechanisms need not be located on or adjacent the sensing element itself, but may instead be located, in some embodiments, proximal of the entire sensing element **1520**. For example, the detection sensors may be supported by or adjacent another portion of the movable component **1504**, as the attachment of the sensing element **1520** to movable component **1504** means that there is a direct correlation between translation of the movable component **1504** and translation of the sensing element **1520** supported by the movable component **1504**. Thus the movement and position of the sensing element **1520** can be indirectly but precisely monitored by monitoring the movement or position of another portion of movable component **1504**.

[0104] Upon detection of movement indicative that the sensing element has been moved relative to the sensor housing, time-stamped information relating to the movement of the sensing element may be written to or otherwise recorded in the memory of the smart sensor. In an embodiment in which the smart sensor is connected to or otherwise in communication with an external instrument, such information may be transmitted to the external instrument or system, where it can be stored in the memory of the external instrument or device. In some embodiments, even a sensor without an included memory can include movement detection mechanisms available to be used by an external instrument to detect and record movement of the sensing element when the sensor is connected to the external instrument. In this way, a log or other record can be generated, indicative of the

movement of the sensing element and the times at which that movement occurred.

[0105] In embodiments in which the sensor structure is gamma ray sterilized, the exposure to gamma radiation may place constraints on the type of circuitry which can be included in the sensor structure itself. In one embodiment, the sensor structure may include a robust memory chip capable of withstanding gamma radiation, as well as a movement detection mechanism which can be utilized in conjunction with a connected external instrument or other connected instrumentation, such as galvanic contacts which are closed when the sensor is in a particular position. The connected instrument can detect movement of a component of the sensor structure to or away from a given position, and record timestamped information regarding this movement to the memory chip within the sensor structure. In such an embodiment, an event log can be maintained within the robust memory chip included in the sensor structure.

[0106] In some embodiments, the connected instrumentation may include a dongle or other component which can be attached to the connector after the bioreactor bag is set up, and which includes circuitry which is configured to operate in connection with a hardened memory chip and one or more movement detection mechanisms to record to the hardened memory chip information relating to detected movement. By including this circuitry in a supplemental component, the circuitry in the supplemental component need not be made sufficiently robust to withstand the gamma ray sterilization process. The supplemental component can in some embodiments remain in place when a connection is made to other external instrumentation, such as by connecting the external instrumentation and the supplemental component in series.

[0107] In some embodiments, the detection of motion by an external instrument need not be contemporaneous with the occurrence of the motion. For example, in some embodiments, the movement detection mechanism may include a circuit and/or a mechanical component which can be tripped or otherwise altered by movement of a component of the sensor relative to the sensor housing. Such a circuit and/or component may be altered in a manner which can be detected by an external instrument, or directly observed by a user. This alteration may in some embodiments provide an indication of the time at which the movement occurred.

[0108] In some devices, a mechanical interlock or similar feature can be used to prevent retraction of a sensing element without operator assistance, to prevent inadvertent termination of process media sensing. Detecting and recording information relating to the timing movement of the sensing element can provide additional protection beyond or in addition to protection provided by a mechanical interlock. The movement record thus generated can be helpful in documenting both abnormal and successful bioreactor runs. This tracking can also provide an additional check as to the proper handling and sterility of a single-use sensor before use.

[0109] In some embodiments, the sensor output may also be used to provide an indication of movement of the sensing surface in or out of the storage compartment. If the sensor output is continually or periodically monitored, the smart sensor can detect a deviation from the sensor output corresponding to immersion in the storage medium, and can record, for example, a timestamp or similar information indicative of the insertion time of the sensor. This sensor exposure timestamp or similar information can provide another record of the process timeline.

[0110] In some embodiments, the storage solution is a reference solution, such as the reference solution used in the sensing element itself. In other embodiments, the storage solution may be a pH buffered storage solution. Because the storage medium is a sealed compartment, the pH and other characteristics of the storage medium will remain constant while the sensing element is retained within the storage and calibration chamber. At the point of time at which the sensing element is pushed into the process medium, the sensing surface and reference electrode of the sensor are immersed in the process medium, which will have characteristics different than the characteristics of the storage medium. Upon exposure to the process medium, the sensor output will deviate from the substantially constant sensor output which resulted from immersion in the storage medium.

[0111] This deviation from the constant sensor output while immersed in the storage medium

provides an indication that the sensor has been inserted into the process medium, or that the storage medium has become compromised, and can be used to provide additional validation of both the integrity of the storage compartment and of the time at which the sensor was first extended into the process medium. Because the storage medium will in many embodiments have characteristics which are substantially different from the process medium, retraction of the sensing element into the storage medium can also be detected by a return of the sensor output to a sensor output similar to the substantially constant sensor output which resulted from immersion in the storage medium. [0112] FIG. 13A is a side view of another embodiment of a sensor structure including a sensing element such as the sensing element of FIG. 2 and a storage compartment containing a storage solution, configured to be inserted into a tube port. FIG. 13B is a side view of the sensor of FIG. 13A, shown in an extended position. FIG. 14A is a cross-sectional perspective view of the sensor structure of FIG. 13A, shown in a retracted position. FIG. 14B is a cross-sectional perspective view of the sensor structure of FIG. 13A, shown in an extended position.

[0113] The sensor structure 1700 is similar to sensor structure 1500 in certain aspects, and like sensor structure 1500, the sensor structure 1700 may be a single-use sensor such as a single-use pH sensor, including a sensor housing 1702 which includes a storage compartment 1740 containing a storage solution. The sensor housing 1502 can be secured relative to a tube port 1400 as shown, or other suitable structure. The sensor structure 1700 includes a movable component which is longitudinally translatable relative to the sensor housing 1702.

[0114] The movable component supports a sensing element 1720 having a sensing surface 1722 such as the sensing element 200 of FIG. 2. One or more external gaskets or O-rings can be used to cooperate with the internal surface of a tube port to maintain the integrity of the bioreactor bag in which the tube port is installed, as described below.

[0115] A connector 1780 extends from the proximal end of the sensor structure 1700. The connector 1780 differs from the connector 1580 of the sensor structure 1500 in that the connector 1780 includes a length of cabling 1782 extending between the proximal end of the sensing element 1720 and the connector interface 1784 at the proximal end of the connector 1780. In some embodiments, a sensor structure 1700 may be provided with only the connected cabling 1782, and a desired connector interface for use with a particular external instrument or system may be attached at a later point in time.

[0116] The interface mechanism for translating the movable component of the sensor structure 1700 also differs from that of the sensor structure 1500. As can be seen, the interface mechanism of sensor structure 1700 includes a throw lever 1790, comprising a generally U-shaped handle operably coupled at the end of both arms to the upper housing section 1792, which in the illustrated embodiment serves as the movable component of the sensor structure 1792 and supports the sensing element 1720 near the proximal end of the sensing element 1720. The throw lever 1790 may facilitate operation of the sensor structure 1700 while a user is wearing gloves, or when there are other impediments to interaction with the sensor structure.

[0117] The throw lever 1790 is movable between a first position, shown in FIG. 12A, in which the throw lever 1790 lies against or adjacent a proximal section of the upper housing section 1792, and a second position, shown in FIG. 12B, in which the throw lever 1790 lies against or adjacent a distal section of the upper housing section 1792. The throw lever 1790 is operably coupled via a suitable mechanical linkage, cam surfaces, or another suitable mechanical arrangement to the movable component of the sensor structure 1700. Raised features 1794 on the surface of the upper housing section 1792 may cooperate with the throw lever 1790 to provide some resistance against inadvertent movement away from a desired position of the throw lever 1790.

[0118] The shape of the upper housing section 1792, and in particular the generally cylindrical sidewall section of the upper housing section 1792 underlying the throw lever 1790, cooperates with the shape of the throw lever 1790 to constrain the positions to which the throw lever 1790 can be moved. Because the throw lever 1790 is operably coupled to the movable component of the

sensor structure **1700**, constraint on the travel range of the throw lever **1790** constrains the longitudinal translation of the movable component, which in turn constrains the longitudinal translation of the supported sensing element **1720**.

[0119] The shape of the distal section of the sensor housing **1702** also differs from the shape of the distal section of the sensor housing **1502** of the sensor structure **1500**. In contrast to the sensor housing **1502**, which includes a single flared section **1530** of the sensor housing **1502**, the sensor housing **1702** includes a proximal flared section **1730** having a distal surface **1732** which can abut a proximal surface of a tube port, but also includes a ridged section **1734** formed from a resilient material such as silicone rubber and having ridges of increasingly larger diameter in the proximal direction. The flexible ridged section can abut an internal surface of a tube port to ensure a fluid seal will be formed despite variations in the internal cross-sectional size of the tube port, or imperfections in the interior surface of the tube port.

[0120] In other embodiments, movement of the sensing element to selectively expose the sensing surface to the process medium and to the storage/calibration medium may include rotation of the sensing element, in addition to or in place of translation of the sensing element in a given direction. FIG. **15** is a top cross-sectional view schematically illustrating a sensor structure including a sensing element which can be rotated to expose an active portion of the sensing surface to a process medium. The sensor structure includes a cylindrical sensing element **1200** including a sensing surface **1210** which does not extend around the entire circumference of the sensing element **1200**. The sensing element **1200** can also include a half-cell element lead and an internal electrolyte, as discussed elsewhere herein, and may also include an integrated reference electrode. In some embodiments, the sensing surface **1210** extends around less than half the circumference of the sensing surface **1200**, although in other embodiments it can extend around substantially less than half the circumference of the sensing element **1200**, as shown in FIG. **15**.

[0121] The surface of the sensing element **1200** is in contact with a first sealing element **1212a** and a second sealing element **1212b**. The first sealing element **1212a** cooperates with the surface of the sensing element **1200** to seal a storage compartment **1220** containing a storage/calibration medium **1222**. The second sealing element extends around an aperture in fluid communication with a space **1290** which can be filled with or otherwise exposed to a process medium. By rotating the sensing element **1200** relative to the scaling elements **1212a** and **1212b**, the sensing surface **1210** of the sensing element **1200** can be moved between a first position in which it is in fluid communication with the storage/calibration medium **1222** of the storage compartment **1120**, and a second position in which the sensing surface **1210** is circumscribed by the second sealing element **1212b** to allow the sensing surface **1210** to be exposed to the process medium in the space **1290**.

[0122] Regardless of the direction of rotation or translation of the sensing element, a fluid-tight seal can be maintained during movement of the sensing element as long as the portion of the sensing element in contact with a sealing element has a substantially constant shape. The portions of the sensing element which will not contact the sealing element need not have a substantially constant shape. Thus, portions of the sensing element **200** of FIG. **2** which are located sufficiently proximal or distal the sensing surface (or other portions which will contact a sealing element) can have a varying cross-sectional shape. Similarly, only a portion of the sensing element **1200** of FIG. **15** may have an outer surface in the shape of a circular arc, while the other surfaces may be any suitable shape, so long as the sealing elements do not contact those portions of the sensing element during movement of the sensing element. Similarly, a sealing element may be configured to maintain a substantially fluid-tight seal when in contact with a portion of a sensing element with a surface having a particular surface profile or shape. As long as the profile of the portion of the sensing element contacting the fluid-tight seal has a substantially constant surface profile or shape, the substantially fluid-tight seal can be maintained during translation and/or rotation of the sensing element, due to the sealing element cooperating with the surface of the sealing element.

[0123] Mechanical stops or other movement-constraining structures or devices may be included to

prevent the sensing element from being translated to a position where the shape of the section of the sensing element in contact with the sealing element changes. In addition, some variance in shape may be tolerated due to the tolerance of the sealing element.

[0124] FIG. **16A** is a perspective view of another embodiment of a sensor structure including a sensing element configured for use in a flow-through arrangement and comprising a storage compartment containing a storage solution. FIG. **16B** is a side cross-sectional view of the sensor structure of FIG. **16A**, with the sensor shown in a position in which the sensing element is exposed to storage solution. FIG. **16C** is a side cross-sectional view of the sensor structure of FIG. **16A**, with the sensor shown in a position in which the sensing element is exposed to an inline flow-cell chamber.

[0125] The sensor structure **2200** comprises a rotatable sensor drum **2220** secured within a sensor housing **2202**. The sensor housing **2202** comprises an inlet **2212** and an outlet **2214**. The inlet **2212** and the outlet **2214** are in fluid communication with one another via the inline flow-cell chamber **2210**, which includes an upper aperture adjacent the facing lower surface of the rotatable sensor drum **2220**. Although referred to as an inlet **2212** and an outlet **2214**, the flow direction into and out of the inline flow-cell chamber **2210** may in some embodiments go in either direction

[0126] The sensor structure **2200** includes a connector **2280** extending upwards from the rotatable sensor drum **2200**. This connector **2280** can be used to place the sensor structure in communication with an external instrument or other system. In the illustrated embodiment, the connector **2290** is offset from an axis of rotation of the rotatable sensor drum **2220** but in other embodiment, the connector **2280** may be aligned with the axis of rotation of the rotatable sensor drum **2220**.

[0127] The rotatable sensor drum **2220** in the illustrated embodiment includes a wider lower portion **2222** of larger cross-sectional area than a narrower upper neck portion **2224**. A collar **2204** secured to the sensor housing **2202** and having a central aperture that is substantially equal in cross-sectional size to the cross-sectional size of the upper neck region **2224** and smaller than the cross-sectional size of the lower portion **2222** of the sensor drum **2220** retains the rotatable sensor drum **2220** in place. Because the central aperture of the collar **2204** is aligned with the axis of rotation of the sensor drum **2220**, and because the portions of the sensor drum retained within the sensor housing **2204** are rotationally symmetric, the sensor drum **2220** can be rotated within the sensor housing **2202**. In the illustrated embodiment, a collar gasket **2208** provides a seal below the threaded connections between the collar **2204** and the sensor housing **2202**.

[0128] In the illustrated embodiment, an outwardly extending lever **2270** is attached to the sensor drum **2220** to facilitate rotation of the sensor drum **2220**. In other embodiments, the sensor drum may be rotated without the lever **2270**, or another suitable mechanism may be provided to facilitate rotation of the sensor drum, such as mechanical features which may be gripped by a user, or which may engage another mechanism used to rotate the sensor drum **2220**.

[0129] The lever **2270** cooperates with other features of the sensor housing **2202** to constrain rotation of the sensor drum. In the illustrated implementation, the sensor housing **2202** comprises a raised wall **2280** extending around a portion of the sensor housing **2202** and extending into the swept area of the lever **2270**. In the illustrated embodiment, the lateral edges of the wall **2280** are complementary with the shape of the lever **2270** such that the wall **2280** defines a first rotational position of the sensor drum **2220** when the lever **2270** is in contact with a first lateral edge **2282** of the wall **2280** and a second rotational position of the sensor drum **2220** when the lever **2270** is in contact with a second lateral edge **2284** of the wall **2280**.

[0130] One or more pins **2286** can be used to constrain movement of the lever **2270**, such as retaining the lever **2270** in one of the first or second positions adjacent a lateral edge of the wall **2280**. The pins **2286** may be removable or may be spring loaded or otherwise biased into the swept area of the lever **2270**, and movable out of the swept area to allow the lever **2270** to pass thereby when desired.

[0131] FIG. **16B** is a cross-sectional view illustrating the sensor structure **2200** in a first

configuration, where the sensor drum **2220** is in a first position. In the first position, the flat sensing surface **2230** generally flush with the base **2228** of the rotatable sensor drum **2220** and exposed at the base **2228** of the rotatable sensor drum **2220** is aligned with a storage and/or calibration chamber **2240** including a storage medium **2240** to which the flat sensing surface **2230** is exposed when the sensor structure is in the first configuration. The flat sensing surface **2230** serves as the sensing surface of the sensor structure **2200**, allowing calibration of the sensor structure **2200** when the sensor structure **2200** is in this first calibration.

[0132] The sensor drum **2220** also contains the remainder of the sensing element of the sensor structure **2200**. Unlike the sensing element of FIG. 2, for example, the flat sensing surface **2320** of the sensor **2232**, a combination pH electrode. An internal chamber within the sensor drum **2220** contains a reference solution **2234** to which the reference electrode of the sensor **2232** of the sensing element is exposed. An electrode gasket **2236** surrounding the flat sensing surface **2230** prevents leakage of the reference solution **2234** through the base **2228** of the sensor drum **2220** and an internal gasket **2238** prevents leakage of the reference solution **2234** between other components of the sensor drum **2220** joined together to define the internal chamber of the sensor drum **2220**.

[0133] The portion of the base **2228** overlying the inline flow-cell chamber **2210** cooperates with the portion of the sensor housing **2204** surrounding the inline flow-cell chamber **2210** and with the outlet gasket **2218** to allow process media flowing through the inline flow-cell chamber **2210** to pass through the inline flow-cell chamber **2210** without interference or leakage.

[0134] In FIG. 16C, the sensor drum has been rotated to expose the flat sensing surface **2230** to the inline flow-cell chamber **2210**, placing the sensing surface of the sensing element of the sensor structure **2200** in fluid communication with the inline flow-cell chamber **2210**, in a second configuration of the sensor structure **2220**. The base **2228** of the sensor drum **2220** seals the storage medium **2242** within the storage compartment **2240** when the sensor component **2200** is in this second configuration.

[0135] As discussed above, rotation of the sensor drum from the first position to the second position may include moving the lever **2270** from a first position in which it abuts a first lateral end of the wall **2280** to a second position in which it abuts the second lateral end of the wall **2280**. The wall **2280** may thus define the complete travel range of the sensor drum **2220**, with the first and second positions of the sensor drum corresponding to the edges of this maximum travel range.

[0136] The relative positioning between the storage chamber **2240** and the inline flow-cell chamber **2210** may correspond to the arc defined by the wall **2280**. The storage chamber **2240** and the inline flow-cell chamber **2210** are located substantially the same distance laterally outward of the axis of rotation of the sensor drum **2220**, so that the flat sensing surface **2230** can be selectively exposed, through rotation of the sensor drum **2220**, to both the storage chamber **2240** and the inline flow-cell chamber **2210**.

[0137] In the illustrated embodiment, the travel range of the sensor drum is roughly 180 degrees, and the storage chamber **2240** and the inline flow-cell chamber **2210** are located on opposite sides of the axis of rotation of the sensor drum **2220**. In an embodiment in which the storage chamber **2240** and the inline flow-cell chamber **2210** are located at some other angle to one another, the shape of wall **2280** may be adjusted so that it defines a matching arc. In some embodiments, the entire wall **2280** need not be included, as long as features defining stops for the rotation of the sensor drum are included.

[0138] Note that, although the figures depict the sensor structure **2200** in an orientation in which the axis of rotation of the sensor drum **2220** is vertical, the sensor structure **2220** can in use be oriented in a position such as a position in which the axis of rotation of the sensor drum **2220** is horizontal or canted at another angle to the vertical. In such a horizontal configuration, for example, contact between the storage medium **2242** within the storage compartment **2240** and the flat sensing surface **2230** can be ensured.

[0139] In an embodiment in which a movement detection mechanism is included in the sensor

structure, the movement detection mechanism may be supported by or attached to at least one of the lever or wall. Like the 1:1 translation of a longitudinally translatable component supporting the sensor element, the angular rotation of the lever will correspond to identical angular rotation of the sensor drum and the included sensing surface, and detection of rotational movement anywhere on the sensor drum or attached structures will correspond to rotational movement of the sensor drum. [0140] FIGS. 17A and 17B are perspective view of another embodiment of a sensor structure including a sensing element configured for use in a flow-through arrangement and comprising a storage compartment containing a storage solution. FIG. 17C is a top plan view of the sensor structure of FIG. 17A. 17D is a side cross-sectional view of the sensor structure of FIG. 17A, with the sensor shown in a position in which the sensing element is exposed to an inline flow-cell chamber. FIG. 17E is another side cross-sectional view of the sensor structure of FIG. 17A in the same position as FIG. 17D, with the sensor shown in a position in which the sensing element is exposed to an inline flow-cell chamber, where the pressure within the inline flow-cell chamber causes deformation of a pressure equalization diaphragm.

[0141] In some embodiments, an inline flow sensor can be exposed to significant pressure within the inline flow-cell chamber. If the pressure within the flow-cell chamber is significantly higher than the surrounding pressure, or the pressure of surrounding chambers, this pressure differential can compromise both the sterility and the sanitation of the flow-through sensor structure. The sensor structure may include structures such as a ceramic wicks which electrically connect the reference solution to the process solution within the inline flow-cell chamber. When the inline flow-cell chamber is at a pressure significantly higher than the reference solution chamber, this pressure differential can affect the operation of the sensor structure. In particular, such a pressure differential can cause the process solution to backflow through the ceramic wicks into the reference solution. This can cause drift of pH measurements due to a change in properties of the reference solution, and can affect the sterility and sanitation of the flow through sensor.

[0142] FIGS. 17A and 17B are perspectives view of another embodiment of a sensor structure including a sensing element configured for use in a flow-through arrangement and comprising a storage compartment containing a storage solution, with a pressure equalization mechanism in fluid communication with the inline flow-cell chamber. The sensor structure **2300**, like the sensor structure **2200** of FIG. 16A, comprises a rotatable sensor drum **2320** secured within a sensor housing **2302**, with the sensor housing **2302** comprising an inlet **2312** and an outlet **2314**. The inlet **2312** and the outlet **2314** are in fluid communication with one another via the inline flow-cell chamber **2310**, which includes an upper aperture adjacent the facing lower surface of the rotatable sensor drum **2220**. Although referred to as an inlet **2312** and an outlet **2314**, the flow direction into and out of the inline flow-cell chamber **2310** may in some embodiments go in either direction

[0143] The sensor structure **2300** includes a connector **2390** extending upwards from the rotatable sensor drum **2320**. This connector **2390** can be used to place the sensor structure in communication with an external instrument or other system. In the illustrated embodiment, the connector **2390** includes a flexible cord **2392** with a plug **2394** at its distal tip. As discussed above, the connector **2390** may include a robust memory chip capable of withstanding gamma radiation, which can be utilized in conjunction with a connected external instrument or other connected instrumentation, to provide smart probe functionality to the sensor structure **2300**. As can be seen in FIG. 17D, the robust memory chip **2396** can be disposed within the plug **2394** at the end of the connector **2390**, although in other embodiments such a memory chip can be located elsewhere within or adjacent the sensor structure **2300**.

[0144] For example, the gamma-hardened chip may include calibration information such as the pH of the storage solution, or other information regarding the sensor structure **2300**, such as the date of manufacture. Because such a robust memory chip may be able to withstand gamma irradiation, the entire sensor structure can be gamma irradiated while still providing smart probe functionality out of the box. In addition, a connected instrument can record timestamped information regarding the

use of the sensor structure, to provide an event log within the robust memory chip for the purposes of validation.

[0145] In the illustrated embodiment, an outwardly extending lever **2370** extending upwardly from the sensor drum **2320** can be used to facilitate rotation of the sensor drum **2320**. In the illustrated embodiment, the lever **2370** can be moved from a first position in which the sensing surface **2330** of the sensor **2332** is placed in fluid communication with the inline flow-cell chamber **2310**, as show in FIGS. **17A-17E**, to a second position in which the sensing surface **2330** of the sensor **2332** is placed in fluid communication with the storage and/or calibration chamber **2240** including a storage medium **2242**. In the illustrated embodiment, the lever **2370** can be used to rotate the sensor drum **2320** be moved roughly 90° to move between the first and second positions. Markings on the exterior of the sensor structure **2300** can be used to indicate the current configuration of the sensor structure **2300** and the manner in which it can be changed to a different configuration.

[0146] In FIG. **17D**, it can be seen that a pressure equalization mechanism is located within the sensor structure and in fluid communication with the inline flow-cell chamber **2310**. In the illustrated embodiment, the pressure equalization mechanism includes a pressure equalization membrane **2316** disposed between the inline flow-cell chamber **2310** and the reference solution chamber storing the reference solution **2334**, although in other embodiments other pressure equalization mechanisms may be used. In FIG. **17E**, the sensor structure **2300** is shown in a state in which the pressure within the inline flow-cell chamber is substantially higher than the external pressure. When such a pressure differential exists, the membrane **2316** deforms outward as shown, increasing the volume of the inline flow-cell chamber to relieve the pressure differential. By providing a component of the sensor structure **2300** which can be comparatively readily deformable, pressure differential between the inline flow-cell chamber **2320** and the chamber comprising the reference solution **2334** can be minimized or eliminated. In doing so, backflow of the process solution under pressure into the reference solution **2334** can be prevented.

[0147] The pressure equalization mechanism may provide a volumetric displacement chosen based on a variety of factors. Depending on, for example, the rigidity of the tubing or the rigidity of other components of the sensor structure **2300**, the design of the pressure equalization mechanism may be selected to provide a volumetric change under pressure which is greater if the tubing to which the sensor structure **2300** will be attached is more rigid. If the tubing is more flexible, and can itself safely deform in response to increased pressure, a smaller amount of volumetric change may be provided by the pressure equalization mechanism. The size of the pressure equalization mechanism, as well as the flexibility of the pressure equalization mechanism, will affect the amount of volumetric change provided by the pressure equalization mechanism when under pressure. In some embodiments, the pressure equalization mechanism may be designed to maintain the integrity of the internal gaskets under a pressure differential of 70 psi, although other embodiments may be designed with larger or smaller pressure differential thresholds.

[0148] The amount of deformation induced in the pressure equalization membrane during pressure equalization may be dependent not only on the pressure differential, but on the deformability of gaskets or other components of the sensor structure **2300** as well as the state of the reference solution chamber storing the reference solution **2334**, such as the amount of air, if any, within the chamber.

[0149] In addition to providing pressure compensation during use of the sensor structure **2300**, the pressure equalization membrane **2316** may also compensate for temperature variation in the reference solution **2334** during storage of the sensor structure **2300**, such that a pressure differential between the reference solution chamber storing the reference solution **2334** and the exterior of the sensor structure **2300** can be reduced or eliminated during storage of the sensor structure **2300**.

[0150] It can also be seen in FIGS. **17D** and **17E** that, in contrast to the O-rings used in the illustrated embodiment of FIGS. **16A-16C**, the sensor structure **2300** includes alternative sealing structures in the form of cup seals **2388** between the sensor drum **2320** and the facing internal

surface of the sensor structure **2300**. In contrast to an O-ring, a cup seal can provide less frictional resistance to rotation of the sensor drum **2320** relative to the remainder of the sensor structure **2300**, facilitating the movement of the sensor structure **2300** between the first position and the second position, while maintaining a seal. In other embodiments, V-rings may be used in place of or in addition to such O-rings or cup seals.

[0151] In some embodiments, some or all aspects of operation of the sensor structures described herein may be automated. A connected instrument or other automation system may be placed in communication with the sensor or a mechanism coupled to the sensor in order to control the sensor. This communication may be a direct connection, or may utilize a standardized communications protocol, such as Ethernet or Modbus.

[0152] In some embodiments, an actuation mechanism may be connected to the sensor or included within the sensor to move or rotate a component of the sensor structure, such as a rotatable sensor drum, between a first position and a second position, and back to the first position. The actuation mechanism may include a servo motor, stepper motor, or any other suitable mechanism for causing movement of the sensor structure component relative to other components of the sensor structure. In some embodiments, the actuation mechanism may be a distinct mechanism which can be mechanically coupled or connected to a lever or another component of the sensor structure to move a component of the sensor structure.

[0153] In some embodiments, automation of the operation of some or all aspects of the sensor structures described herein may allow installation and operation without the need for subsequent or periodic user contact with the sensor structure. Automation may also allow centralized control of a plurality of sensor structures, whether via an automation system, and/or remote user control.

[0154] In the foregoing description, specific details are given to provide a thorough understanding of the examples. However, it will be understood by one of ordinary skill in the art that the examples may be practiced without these specific details. Certain embodiments that are described separately herein can be combined in a single embodiment, and the features described with reference to a given embodiment also can be implemented in multiple embodiments separately or in any suitable subcombination. In some examples, certain structures and techniques may be shown in greater detail than other structures or techniques to further explain the examples.

[0155] The previous description of the disclosed embodiments is provided to enable any person skilled in the art to make or use the present invention. Various modifications to these embodiments will be readily apparent to those skilled in the art, and the generic principles defined herein may be applied to other embodiments without departing from the spirit or scope of the invention. Thus, the present invention is not intended to be limited to the embodiments shown herein but is to be accorded the widest scope consistent with the principles and novel features disclosed herein.

Claims

1. A sensor structure, comprising: a sensor housing; a inline flow chamber configured to allow a process medium to flow therethrough; a storage compartment configured to retain a storage medium therein; a sensing element retained at least partially within the sensor housing, the sensing element comprising a sensing surface, and reversibly rotatable relative to the sensor housing between a first position and a second position to selectively place the sensing element in fluid communication with one of the inline flow chamber and the storage compartment; and a sealing element circumscribing the storage compartment and configured to engage a facing surface of the sensing element to provide a seal inhibiting fluid flow out of the storage compartment during rotation of the sensing element between the first and second positions.
2. The sensor structure of claim 1, wherein the sensing element comprises a pH sensor
3. The sensor structure of claim 2, wherein the sensing surface comprises a glass pH electrode substantially flush with a facing surface of the sensing element.

- 4.** The sensor structure of claim 1, wherein each of the sensing surface, the inline flow chamber, and the storage compartment are located substantially the same radial distance from an axis of rotation of the sensing element, such that rotating the sensing element between the first position and the second position does not displace a substantial amount of the storage solution from the storage compartment.
 - 5.** The sensor structure of claim 1, wherein the sealing element comprises one of a cup seal, a V-ring, and an O-ring.
 - 6.** The sensor structure of claim 1, wherein the sensing structure is in electrical communication with a reference electrode.
 - 7.** The sensor structure of claim 1, wherein the storage medium has a known pH and serves as a calibration medium for the sensing element.
 - 8.** The sensor structure of claim 1, wherein rotating the sensing element between the first position and the second position does not expose the interior of the storage compartment.
 - 9.** The sensor structure of claim 1, additionally comprising a reference chamber comprising reference solution for the sensing element, wherein the reference solution is in fluid communication with a reference electrode in electrical communication with a sensing electrode.
 - 10.** The sensor structure of claim 1, additionally comprising a movement detection mechanism configured to detect movement of the sensing element relative to the storage compartment.
 - 11.** The sensor structure of claim 10, wherein the movement detection mechanism is configured to provide an indication of the time at which the detected movement occurred.
 - 12.** The sensor structure of claim 10, additionally comprising a memory chip configured to record a timestamp of movement of the sensor drum relative to the storage compartment.
 - 13.** The sensor structure of claim 10, wherein the movement detection mechanism comprises at least one of a proximity switch or a mechanical contact.
 - 14.** The sensor structure of claim 10, wherein the movement detection mechanism is configured such that the state of the movement detection mechanism can be detected by connected instrumentation, and the memory chip is configured to be written to by the connected instrumentation.
-