

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12397208
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Kirtley; Daniel C. et al.

Golf bags, golf bag tops and methods to manufacture golf bags and golf bag tops

Abstract

Exemplary embodiments of golf bags, golf bag tops, and methods to manufacture golf bags and golf bag tops are generally described herein. In one example, a golf bag top may include a club divider portion and a handle portion. A club fastener portion may extend from the handle portion and may receive a golf club shaft. A magnetic portion in the club fastener portion may magnetically attract the shaft. A magnet cover portion may be coupled to the club fastener portion and may include a flap portion entirely or partially covering the magnetic portion that would otherwise directly contact the shaft. The flap portion may provide physical separation between the magnetic portion and the shaft without prohibiting magnetic attraction therebetween. Other embodiments may be described and claimed.

Inventors:	Kirtley; Daniel C. (Tempe, AZ), Pacha; Duane E. (Chandler, AZ)
Applicant:	PARSONS XTREME GOLF, LLC (Scottsdale, AZ)
Family ID:	1000008777992
Assignee:	PARSONS XTREME GOLF, LLC (Scottsdale, AZ)
Appl. No.:	17/668533
Filed:	February 10, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20220266104 A1	Aug. 25, 2022

Related U.S. Application Data

continuation parent-doc US 16216736 20181211 US 11065516 20210720 child-doc US 17348991
continuation-in-part parent-doc US 17348991 20210616 US 11806593 child-doc US 17668533

Publication Classification

Int. Cl.: **A63B55/40** (20150101)

U.S. Cl.:

CPC **A63B55/40** (20151001); A63B2209/08 (20130101)

Field of Classification Search

CPC: A63B (55/40); A63B (2209/08)

USPC: 206/315.6

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4881638	12/1988	Cho	N/A	N/A
4932523	12/1989	Yamazoe	206/315.6	A63B 60/64
5176253	12/1992	Perrin et al.	N/A	N/A
5860520	12/1998	Tang	N/A	N/A
6145660	12/1999	Chou	206/315.6	A63B 55/40
6375004	12/2001	Tuerschmann et al.	N/A	N/A
6877604	12/2004	Pratt et al.	N/A	N/A
D513876	12/2005	Solheim et al.	N/A	N/A
D513877	12/2005	Solheim et al.	N/A	N/A
D513878	12/2005	Anderson et al.	N/A	N/A
D520752	12/2005	Solheim et al.	N/A	N/A
D522754	12/2005	Anderson	N/A	N/A
D530922	12/2005	Anderson	N/A	N/A
7124886	12/2005	Heidenreich	N/A	N/A
D538042	12/2006	Suggs	N/A	N/A
D544210	12/2006	McGuire et al.	N/A	N/A
D557501	12/2006	Suggs et al.	N/A	N/A
D557502	12/2006	Quartarone et al.	N/A	N/A
D577916	12/2007	Quartarone et al.	N/A	N/A
D580656	12/2007	Quartarone et al.	N/A	N/A
D613063	12/2009	Quartarone, III et al.	N/A	N/A
D613064	12/2009	Quartarone, III et al.	N/A	N/A
D613065	12/2009	McGuire et al.	N/A	N/A
D613066	12/2009	McGuire et al.	N/A	N/A
7905349	12/2010	Campbell	N/A	N/A
D636596	12/2010	McGuire	N/A	N/A
D649353	12/2010	Loudenslager et al.	N/A	N/A
D649354	12/2010	Loudenslager et al.	N/A	N/A

D649355	12/2010	Loudenslager et al.	N/A	N/A
D649356	12/2010	Loudenslager et al.	N/A	N/A
D669266	12/2011	Loudenslager et al.	N/A	N/A
8752798	12/2013	Loudenslager	N/A	N/A
D713148	12/2013	Bruce	N/A	N/A
D715055	12/2013	Bruce et al.	N/A	N/A
D718534	12/2013	Bruce	N/A	N/A
8910785	12/2013	Loudenslager	N/A	N/A
9421608	12/2015	Loudenslager et al.	N/A	N/A
11065516	12/2020	Pacha	N/A	A63B 55/40
2003/0116456	12/2002	Ueno	206/315.6	A63B 55/00
2008/0169210	12/2007	Heidenreich	N/A	N/A
2010/0320106	12/2009	McGuire	N/A	N/A
2012/0111747	12/2011	Reimers	N/A	N/A
2017/0021241	12/2016	Pelz	N/A	N/A

Primary Examiner: Weaver; Sue A

Background/Summary

CROSS REFERENCE (1) This application is a continuation-in-part of U.S. patent application Ser. No. 17/348,991, filed Jun. 16, 2021, now U.S. Pat. No. 11,806,593, which is a continuation of U.S. patent application Ser. No. 16/216,736, filed Dec. 11, 2018, now U.S. Pat. No. 11,065,516, which claims the benefit of U.S. Provisional Application No. 62/607,387, filed Dec. 19, 2017.

COPYRIGHT AUTHORIZATION

(1) The present disclosure may be subject to copyright protection. The copyright owner has no objection to the facsimile reproduction by anyone of the present disclosure and its related documents, as they appear in the Patent and Trademark Office patent files or records, but otherwise reserves all applicable copyrights.

(2) This application claims the benefit of U.S. Provisional Application No. 63/151,154, filed Feb. 19, 2021.

(3) The disclosures of the referenced applications are incorporated herein by reference.

FIELD

(4) The present disclosure generally relates to golf equipment, and more particularly, to golf bags, golf bag tops, and methods to manufacture golf bags and golf bag tops.

BACKGROUND

(5) Golf bags may be used to carry golf clubs and accessories. Some golf bags may be tube-shaped to hold a set of golf clubs and include one or more pockets for holding balls, tees, gloves, rain gear, and other golf related equipment and accessories. The open top portion of a golf bag may be divided into a number of slots to allow an individual to organize and sort the golf clubs.

Accordingly, an individual may organize his or her golf clubs based on available slots provided in the open top portion of the golf bag.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 depicts a side view of a golf bag with a golf bag top according to an exemplary

embodiment of the apparatus, methods, and articles of manufacture described herein.

(2) FIG. 2 depicts a top perspective view of a golf bag top according to an exemplary embodiment of the apparatus, methods, and articles of manufacture described herein.

(3) FIG. 3 depicts a bottom perspective view of the golf bag top of FIG. 2.

(4) FIG. 4 depicts a front view of the golf bag top of FIG. 2.

(5) FIG. 5 depicts a rear view of the golf bag top of FIG. 2.

(6) FIG. 6 depicts a top view of the golf bag top of FIG. 2.

(7) FIG. 7 depicts a bottom view of the golf bag top of FIG. 2.

(8) FIG. 8 depicts a right-side view of the golf bag top of FIG. 2.

(9) FIG. 9 depicts a left-side view of the golf bag top of FIG. 2.

(10) FIG. 10 depicts a top perspective view of a magnet cover according to an exemplary embodiment of the apparatus, methods, and articles of manufacture described herein.

(11) FIG. 11 depicts a bottom perspective view of the magnet cover of FIG. 10.

(12) FIG. 12 depicts a bottom view of a golf bag top according to an exemplary embodiment of the apparatus, methods, and articles of manufacture described herein.

(13) FIG. 13 depicts a bottom view of the golf bag top of FIG. 12 with the magnet cover of FIG. 10 installed thereon.

(14) FIG. 14 depicts a side view of a golf bag with the golf bag top of FIG. 12 and the magnet cover of FIG. 10 installed thereon.

(15) FIG. 15 depicts a top view of a golf bag top according to an exemplary embodiment of the apparatus, methods, and articles of manufacture described herein.

(16) FIG. 16 depicts a top view of a golf bag top according to an exemplary embodiment of the apparatus, methods, and articles of manufacture described herein.

(17) FIG. 17 depicts a top view of a golf bag top according to an exemplary embodiment of the apparatus, methods, and articles of manufacture described herein.

(18) FIG. 18 depicts a top view of a golf bag top according to an exemplary embodiment of the apparatus, methods, and articles of manufacture described herein.

(19) FIG. 19 depicts a front view of a golf bag top according to an exemplary embodiment of the apparatus, methods, and articles of manufacture described herein.

(20) FIG. 20 depicts a top view of the golf bag top of FIG. 19.

(21) FIG. 21 depicts a front view of a golf bag top according to an exemplary embodiment of the apparatus, methods, and articles of manufacture described herein.

(22) FIG. 22 depicts a top view of the golf bag top of FIG. 21.

(23) For simplicity and clarity of illustration, the drawing figures illustrate the general manner of construction, and descriptions and details of well-known features and techniques may be omitted to avoid unnecessarily obscuring the present disclosure. Additionally, elements in the drawing figures may not be depicted to scale. For example, the dimensions of some of the elements in the figures may be exaggerated relative to other elements to help improve understanding of embodiments of the present disclosure.

DESCRIPTION

(24) In general, golf bag tops and methods to manufacture golf bag tops are described herein. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

(25) In the example of FIG. 1, a golf bag **100** may include a body portion **110** having a top portion **120**, a bottom portion **130**, and a first housing portion **140** extending between the top portion **120** and the bottom portion **130**. The first housing portion **140** may define a chamber portion **142** for holding and maintaining one or more golf clubs (e.g., one generally shown as **144**) inside the body portion **110**. Each of the one or more golf clubs may be any type of golf club such as, but not limited to, an iron-type golf club, a wood-type golf club, a hybrid-type golf club, or a putter-type golf club. Additionally, the golf club **144** may be part of a set of golf clubs. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

(26) The golf bag **100** may include a second housing portion **150** located outside of the first housing portion **140**. As described in detail below, the second housing portion **150** may enable one or more golf clubs (e.g., one generally shown as **400**) to be prominently displayed and stored separately from any golf clubs stored in the first housing portion **140**. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

(27) The golf bag **100** may include one or more strap portions (not shown) so that an individual can lift and/or carry the golf bag **100**. The golf bag **100** may include one or more golf bag handles (e.g., one generally shown as **160**) on the body portion **110** between the top portion **120** and the bottom portion **130**. The golf bag **100** may include one or more pockets (e.g., generally shown as **170**) for carrying various items such as golf balls, golf tees, apparel, shoes, and/or other accessories. The pocket **170** may be accessible by any suitable types of closure (e.g., a zipper, hook and loop fastener, snap, etc.). The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

(28) In one example, as shown in FIGS. **1-9**, the golf bag **100** may also include a golf bag top (e.g., described and shown as a club divider portion **200**) located at or proximate to the top portion **120**. The club divider portion **200** may have a shape, curvature, contour, and/or other physical characteristics as shown in the example of FIGS. **2-9** so as to fit on or inside the body portion **110** at or proximate to the top portion **120**. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

(29) The club divider portion **200** may include a divider body portion. The divider body portion may have a perimeter portion **210** having a first side **212** and a second side **214**. The first side **212** may have an inner wall and an outer wall. The second side **214** may have an inner wall and an outer wall. As illustrated in FIG. **2**, for example, the first side **212** and the second side **214** may correspond respectively to a left side and a right side of the perimeter portion **210**. As shown in the example of FIGS. **2-9**, the club divider portion **200** may include one or more interconnected rib portions **230** that may connect to the inner wall(s) of the perimeter portion **210** to define a plurality of openings **220** through which the one or more golf clubs **144** can be inserted into the first housing portion **140** of the golf bag **100**. While the figures may depict a particular number of rib portions **230**, the apparatus, methods, and article of manufacture described herein may include more or fewer rib portions (e.g., one rib portion or four rib portions). The rib portions **230** may each extend laterally between the first side **212** and the second side **214** and may be approximately parallel or nonparallel with each other. Additionally, the rib portions **230** may be interconnected by a spine portion **232** extending longitudinally between the rib portions **230**. Although the above example may include the spine portion **232**, the apparatus, methods, and articles of manufacture described herein may not include the spine portion **232** to interconnect the rib portions **230**. In one example, the club divider portion **200** may include six openings, through which one or more golf clubs **144** may be inserted into the first housing portion **140**. While the above example may describe a particular number of openings defined by the rib portion(s) **230**, the apparatus, methods, and article of manufacture described herein may include more or fewer openings (e.g., one opening or eight openings). By providing a plurality of openings **220**, a set of golf clubs may be separated into different groups to allow an individual to organize the golf clubs in a certain manner. Alternatively, the club divider portion **200** may not include any rib portions **230** and may be, for example, a single opening configured to receive one or more golf clubs. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

(30) The golf bag **100** may include a handle portion **300** coupled to the perimeter portion **210** of the club divider portion **200**. In one example, the handle portion **300** may be a separate piece coupled to the club divider portion **200** via any suitable manufacturing method or process (e.g., adhered with epoxy, fastened with screws or threaded fasteners, or any combination thereof). In another example, the handle portion **300** and the club divider portion **200** may be a unitary piece (e.g., the handle portion **300** may be an integral piece of the club divider portion **200**). The handle portion

300 may be coupled at one end to the first side **212** of the perimeter portion **210**, extend outward and around a front portion of the perimeter portion **210**, and be coupled at another end to the second side **214** of the perimeter portion **210**. Accordingly, the handle portion **300** may extend outside of the perimeter portion **210** and may be spaced apart from the perimeter portion **210** to define a handle opening **310**. In use, an individual may insert their hand through the handle opening **310** and then wrap their fingers around the handle portion **300** to use the handle portion **300** to lift and/or carry the golf bag **100**. In some examples, the handle portion **300** may include texturing to improve grip. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

(31) The handle portion **300** may include a club fastener portion **320** configured to engage a first shaft portion **410** of the golf club **400**. The club fastener portion **320** may be located at or proximate to either the first side **212** or the second side **214** of the perimeter portion **210**. The golf bag **100** may include a base portion **180** located at or proximate to the bottom portion **130** and configured to engage a second shaft portion **420** of the golf club **400**. The club fastener portion **320** and the base portion **180** may engage the golf club **400** at two spaced apart portions (e.g., the first shaft portion **410** and the second shaft portion **420**) to fasten or hold the golf club **400** in an inverted position. In one example, as shown in FIG. 1, the base portion **180** may be a pocket configured to receive the second shaft portion **420** of the golf club **400**. In another example (not shown), the base portion **180** may be a sleeve portion, a tube portion, a platform portion, a cup-shaped portion, a channel portion, or any other receiving means configured to receive and hold the second shaft portion **420** of the golf club **400**. It should be understood that any suitable type of receiving means may be utilized. The club fastener portion **320** and the base portion **180** may define the second housing portion **150** for housing one or more golf clubs. In the example of FIG. 1, the second housing portion **150** is shown to house one golf club **400**. The second housing portion **150** may separate and externally store and/or display a single golf club of a set of golf clubs stored in the first housing portion **140**. In one example, the second housing portion **150** may hold a putter-type golf club. In another example (not shown), the second housing portion **150** may include multiple club fastener portions (not shown) that cooperate with the base portion **180** or several base portions (not shown) to house more than one golf club. Alternatively, the base portion **180** may include one or more rib portions to provide two or more separate openings, channels, chambers, or compartments. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

(32) The first housing portion **140** may define the chamber portion **142** and/or other interior space of the golf bag **100** to hold one or more golf clubs. When a golf club is received in the first housing portion **140**, the golf club **400** may have an exposed club length **520** that extends above the top portion **120**. The exposed club length **520** of the golf club **144** may include a golf club head and a shaft portion of the golf club **144**. During play, an individual can view the exposed club length **520** of the golf club **144** including at least the golf club head to visually differentiate the golf club from any other golf club(s) contained by the first housing portion **140**. The first housing portion **140** may extend between the top portion **120** and the bottom portion **130**. The first housing portion **140** may extend from the top portion **120** to the bottom portion **130**. The first housing portion **140** may have a height **500** that is greater than a percentage of a length of one or more golf clubs contained by the first housing portion **140**. In one example, the height **500** of the first housing portion **140** may be greater than 50% of a maximum club length **510** of the golf club **144**. In another example, the height **500** of the first housing portion **140** may be greater than 60% of the maximum club length **510** of the golf club **144**. In yet another example, the height **500** of the first housing portion **140** may be greater than 70% of the maximum club length **510** of the golf club **144**. In yet another example still, the height **500** of the first housing portion **140** may be greater than 80% of the maximum club length **510** of the golf club **144**. Accordingly, the chamber portion **142** may be an elongated and substantially enclosed hollow internal space of the golf bag **100** for surrounding

more than 50% of the club length of one or more golf clubs. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

(33) The second housing portion **150** have a height that may be defined by summing a height **530** of the club fastener portion **320** and a height **540** of the base portion **180**. The height of the second housing portion **150** may be less than or equal to a percentage of a maximum club length of one or more golf clubs housed by the second housing portion **150**. For example, the height of the second housing portion **150** may be less than or equal to 50% of a maximum club length **550** of the golf club **400**. In another example, the height of the second housing portion **150** may be less than or equal to 60% of the maximum club length **550** of the golf club **400**. In another example, the height of the second housing portion **150** may be less than or equal to 70% of the maximum club length **550** of the golf club **400**. In another example, the height of the second housing portion **150** may be less than or equal to 80% of the maximum club length **550** of the golf club **400**. While the above examples may describe particular percentages, the apparatus, methods, and articles of manufacture described herein may include the second housing portion **150** having a height to engage a greater percentage or a lesser percentage of the maximum club length **550** of the golf club **400**.

Accordingly, when the golf club **400** is stored or held in the second housing portion **150**, a portion of the maximum club length **550** of the golf club **400** may be exposed. More specifically, a portion of the golf club **400** other than the first shaft portion **410** and the second shaft portion **420** of the golf club **400** may be exposed. Thus, for a particular golf club, more than 50% of its maximum club length may be housed by the first housing portion **140**. When the same club is instead housed by the second housing portion **150**, less than or equal to 50% of its maximum club length may be housed by the second housing portion **150**. As a result, the golf club **144** housed by the first housing portion **140** may have less exposed length than the golf club **400** housed by the second housing portion **150**. Advantageously, by having more exposed length, the golf club **400** secured by the second housing portion **150** may be more prominently displayed than the golf club **144** stored in the first housing portion **140**. Additionally, the golf club **400** may be easily handled due to more exposed surface area in which to grab the golf club **400** and remove the golf club from the second housing portion **150**. What's more, the second housing portion **150** may be located frontward on the golf bag **100** such that the golf club **400** is readily accessible during play when the golf bag **100** is secured to a golf cart or placed on the ground. Accordingly, an individual may elect to use the second housing portion **150** to secure his or her most frequently used golf club and/or to prominently display his or her favorite golf club. The foregoing features are not available in present golf bags. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

(34) The club fastener portion **320** may include any suitable type of fastening mechanism configured to engage and hold a shaft **440** of the golf club **400** (e.g., via the first shaft portion **410**). In the example shown in FIGS. 1-9, the club fastener portion **320** may include a U-shaped portion **330**. The U-shaped portion **330** may have a first arm portion **331**, a second arm portion **333**, and an arcuate portion **334** connecting the first arm portion **331** to the second arm portion **333**. The U-shaped portion **330** may define a space **332**. The U-shaped portion may have a mouth portion **337** that provides access to the space **332**. The space **332** may have a width that is greater than or equal to an outer diameter of the shaft **440** of the golf club **400**. In one example, the outer diameter of the shaft **440** at or proximate to a grip portion **455** (e.g., butt end of the shaft **440**) may be in a range of 0.58 inch to 0.64 inch. The outer diameter of the shaft **440** at or proximate to the club head of the golf club **400** (e.g., tip end of the shaft **440**) may be in a range 0.335 inch to 0.37 inch. The diameter of the shaft **440** may taper between the butt end of the shaft and the opposing end of the shaft that is connected to the golf club head. While the above examples may describe particular outer diameters, the apparatus, methods, and articles of manufacture described herein may include shafts with greater or smaller diameters. Accordingly, the first shaft portion **410** or other shaft portion of the golf club **400** may be inserted into the U-shaped portion **330**. To hold the first shaft

portion **410** of the golf club **400** in the U-shaped portion **330**, the club fastener portion **320** may include a magnetic portion **340** located inside the U-shaped portion **330**. Accordingly, the first shaft portion **410** or other shaft portion of the golf club **400** may be magnetically attracted to the magnetic portion **340** and thereby secure the shaft within the space **332** of the U-shaped portion **330**. Referring to FIGS. **3**, **4**, and **7**, for example, the magnetic portion **340** may be inserted inside a cavity **350** in the bottom portion of the club fastener portion **320**. The cavity **350** may be located on an underside **321** of the club fastener portion **320**. The cavity **350** may be open to the space **332** defined by the U-shaped portion **330** such that an outer portion **360** of the magnetic portion **340** is exposed to the space **332** and is free to contact the first shaft portion **410** of the golf club **400**. The magnetic portion **340** may be sized and shaped to complement the cavity **350** so as to allow the magnetic portion **340** to be easily received inside the cavity **350** and secured thereto via a friction fit, an adhesive, or a fastener. The magnetic portion **340** may entirely or partially occupy the cavity **350**. In other examples, the magnetic portion **340** may have a circular cross section, a square cross section, a rectangular cross section, or any other suitable shape to engage the shaft **440** of the golf club **400**. The magnetic portion **340** may be removable and replaceable with a magnetic portion having a weaker or stronger magnetic attraction, thereby allowing an individual to adjust the amount of magnetic attraction between the club fastener portion **320** and the shaft **440** to match personal preference and use. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

(35) While the above examples may describe the magnetic portion **340** as a separate piece, the magnetic portion **340** may be an integral portion of the club fastener portion **320**. In one example, the club fastener portion **320** may be made of or include material(s) with magnetic properties to engage and secure a shaft of the golf club **400** (i.e., the shaft may be made of metal material(s)). Alternatively, the club fastener portion **320** may include the U-shaped portion without the magnetic portion **340** and engage the shaft **440** of the golf club **400** with a mechanical lock only. Further, while the figures may depict the club fastener portion **320** as a portion of the handle portion **300**, the club fastener portion **320** may extend directly from the club divider portion **200** (e.g., extend from the perimeter portion **210**) or from any other portion of the golf bag **100**. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

(36) An individual may easily store and retrieve a golf club from the second housing portion **150**. For example, the second shaft portion **420** of the golf club **400** may be inserted into the base portion **180** and then the golf club **400** may be guided toward the club fastener portion **320** in a substantially horizontal direction of insertion so that the first shaft portion **410** of the golf club **400** is received in the U-shaped portion **330** and held in place by the magnetic portion **340**. To remove the golf club **400** from the second housing portion **150**, the golf club **400** may be pulled away from the club fastener portion **320** in a substantially horizontal direction of removal and with sufficient force to disengage the first shaft portion **410** of the golf club **400** from the magnetic portion **340**. The second shaft portion **420** may be removed from the base portion **180** by lifting the golf club **400** in an upward direction. As described herein, the handle portion **300** extends outward and around a part of the perimeter portion **210**. Accordingly, the outward location of the handle portion **300** relative to the top portion **120** of the body portion **110** separately locates the golf club **400** from other golf clubs and allows for easy access and use by the individual. In one example, the second housing portion **150** may be used to separate a putter-type golf club from the iron-type golf club(s), the wood-type golf club(s), the hybrid-type golf club(s), or the wedge-type golf club(s) stored in the first housing portion **140**. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

(37) In one example, as shown in FIG. **1**, the base portion **180** may include an external pocket **182** of the golf bag **100**. The external pocket **182** may be located at or near the bottom portion **130**. The external pocket **182** may include an opening **184**, through which the second shaft portion **420** or other portion of the golf club **400** may be inserted. The opening **184** may be freely accessible or

accessed via a closure (e.g., zipper, Velcro®, button, etc.). In one example, as shown in FIG. 1, the club fastener portion **320** may engage the first shaft portion **410** of the golf club **400**, which may be a portion of the shaft **440** of the golf club **400** that is closer to a golf club head **450** than to the grip portion **455** of the golf club **400**. The external pocket **182** may receive the second shaft portion **420** of the golf club **400**, which may be a portion of the shaft **440** of the golf club **400** that includes the grip portion **455**. In one example, as shown in FIG. 1, the height **540** of the base portion **180** may be greater than or equal to a maximum length **560** of the grip portion **455** of the golf club **400**. In one example, the maximum length **560** of the grip portion **455** may be 10 inches. Although the above example describes a particular length of the grip portion **455**, the apparatus, methods, and articles of manufacture described herein may include grip portions with greater or shorter lengths. Additionally, the height **540** of the base portion **180** may be less than or equal to 50% of the maximum club length **550** of the golf club **400**. In another example (not shown), the height **540** of the base portion **180** may be less than the maximum length **560** of the grip portion **455** of the golf club **400**. In one example, the particular height **540** of the base portion **180** may be determined based on an individual's desire to shield the grip portion **455** or to prominently display the grip portion **455**. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

(38) The maximum club length **550** of the golf club **400** may vary based on the type of golf club and/or an individual's preference (e.g., in the range of 30 inches to 60 inches). In one example, the maximum club length **550** of a driver-type golf club may be in a range of 45 inches to 60 inches. In another example, the maximum club length **550** of a fairway wood-type golf club may be in a range of 43 inches to 45 inches. In yet another example, the maximum club length **550** of a hybrid-type golf club may be in a range of 42 inches to 44 inches. The maximum club length **550** of an iron-type golf club may be in a range of 36 inches to 41 inches. The maximum club length **550** of a wedge-type golf club may be in a range of 35 inches to 37 inches. The maximum club length **550** of a putter-type golf club may be in a range of 32 inches to 36 inches. In one example, the maximum club length **550** of the golf club **400** may be limited by a governing body of golf such as, but not limited to, the United States Golf Association (USGA). At present, the USGA requires the club length of a golf club to be at least 18 inches and, with the exception of putters, no more than 48 inches. With respect to the present disclosure, the “maximum club length” of a particular club may correspond to a straight-line measurement taken down the shaft beginning from the top of the grip portion to where the golf club meets the ground while the golf club is at an address position. While the above examples may describe particular lengths of certain types of golf clubs, the apparatus, methods, and articles of manufacture described herein may include golf clubs with greater or shorter club lengths. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

(39) In one example, as shown in FIG. 1, the base portion **180** may be located more forward than the club fastener portion **320**. In other words, the base portion **180** may be horizontally offset relative to the club fastener portion **320**. Further, the pocket **182** of the base portion **180** and the U-shaped portion **330** of the club fastener portion **320** may be generally located on the same vertical plane or substantially on the same vertical plane. In this way, the golf club **400** may be held in an upright position with a slight tilt toward the first housing portion **140**, as shown in FIG. 1. In another example (not shown), the base portion **180** and the club fastener portion **320** may have no horizontal offset therebetween such that the golf club **400** may be held in an upright orientation with no tilt. When the grip portion **455** of the golf club **400** is inserted into the pocket **182** and then the first shaft portion **410** of the golf club **400** is moved toward the magnetic portion **240**, the pocket **182** may guide the shaft **440** of the golf club **400** toward the U-shaped portion **330** with minimal or no lateral pivot. In other words, the second shaft portion **420** that is engaged inside the pocket **182** may be encouraged to move inside the pocket **182** toward the U-shaped portion **330** while the pocket **182** prevents or substantially prevents any lateral pivot of the golf club **400**.

Additionally, the golf club **400** may tend to pivot toward the magnetic portion **340** due to the noted horizontal offset between the pocket **182** and the club fastener portion **320**. Accordingly, when an individual inserts the second shaft portion **420** of the golf club **400** into the pocket **182**, the golf club **400** may pivot toward the club fastener portion **320**, enter the U-shaped portion **330**, and engage the magnetic portion **340** with minimal effort from the individual. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

(40) The golf bag **100** may be manufactured by any suitable manufacturing method and with any suitable materials. The golf bag **100** may include a rigid frame or shell that may be covered in soft materials such as leather, canvas, nylon, plastic, metal, composite materials, and/or other materials. The golf bag **100** may include any number of rings, clips, clamps, etc., to allow attachment of various straps and/or accessories. The golf bag **100** may include one or more pockets. The base portion **180** may be configured (i.e., sized, shaped, etc.) to engage the second shaft portion **420** of the golf club **400** and positioned to be aligned (e.g., vertical planar alignment) with the U-shaped portion **330** as described herein. The base portion **180** may include an elastic material or be generally elastic to grip the second shaft portion **420** of the golf club **400**. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

(41) In one example, the club divider portion **200** may be manufactured from rigid plastic materials via injection molding. The perimeter portion **210**, the rib portions **230**, and the spine portion **232** may be manufactured as a unitary piece via injection molding. In another example, the rib portions **230** and the spine portion **232** may be separately manufactured and then joined to the perimeter portion **210**. In one example, the handle portion **300** may be separately manufactured by injection molding or other plastic manufacturing methods and attached to the perimeter portion **210**. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

(42) The magnetic portion **340** may be attached inside the cavity **350** of club fastener portion **320**. The magnetic portion **340** may be attached inside the cavity **350** of club fastener portion **320** by way of friction and/or an adhesive. In another example, where the magnetic portion **340** is embedded in the club fastener portion **320**, the club fastener portion may be injection molded around the magnetic portion, thereby partially or entirely encapsulating the magnetic portion. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

(43) The club divider portion **200** may be manufactured from any suitable type of plastic materials, metal, metal alloy, composite material, wood, and/or any other material. In one example, the club divider portion **200** may be attached to the body portion **110** of the golf bag **100** by rivets. In another example, the club divider portion **200** may be attached to the body portion **110** of the golf bag **100** by threaded fasteners. In another example, the club divider portion **200** may be attached to the body portion **110** of the golf bag **100** by an adhesive. In another example, the club divider portion **200** may be attached to the body portion **110** of the golf bag **100** by screws. In another example, the club divider portion **200** may be attached to the body portion **110** of the golf bag **100** by an interference fit. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

(44) As shown in FIG. 6, a first end of the handle portion **300** may be coupled to a first outer wall of the first side **212** of the perimeter portion **210**, and a second end of the handle portion **300** may be coupled to a second outer wall of the second side **214** of the perimeter portion **210**. Between the first end and the second end of the handle portion **300**, the handle portion **300** may extend outward and around a portion of the perimeter portion **210**. Accordingly, part of the handle portion **300** may extend outside of and be spaced apart from the perimeter portion **210**. Likewise, the club fastener portion **320** may be located outside of and be spaced apart from the perimeter portion **210**, as shown in FIG. 6. The club fastener portion **320** may be spaced apart from an exterior material of the first housing portion **140**. Spacing the club fastener portion **320** outward and away from the perimeter portion **210** and the first housing portion **140** may prevent the golf club shaft **440** from rubbing on an exterior surface of the golf bag **100** during travel (e.g., in a motorized golf cart or

pull cart) and causing unwanted wear to the golf bag **100** or golf club shaft **440**. In one example, the U-shaped portion **330** may be spaced apart from the perimeter portion **210** by at least 0.5 inch (12.7 mm). In another example, the U-shaped portion **330** may be spaced apart from the perimeter portion **210** by at least 1 inch (25.4 mm). In another example, the U-shaped portion **330** may be spaced apart from the perimeter portion **210** by at least 2 inches (25.4 mm). In yet another example, the U-shaped portion **330** may be spaced apart from the perimeter portion **210** by at least one shaft diameter. In yet another example, the U-shaped portion **330** may be spaced apart from the perimeter portion **210** by at least two shaft diameters. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

(45) The golf bag top or the club divider portion **200** may be used for any type of golf bag and may not be limited for use with any of the golf bags described herein. The club divider portion **200** may be manufactured to fit any type and size of golf bag. The golf bag top or the club divider portion **200** may then be attached at or near the top portion of a golf bag to provide the functions discussed herein in combination with one more pockets (i.e., base portion) of the golf bag at or near the bottom portion of the golf bag. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

(46) The club fastener portion **320** may be an integral part of the handle portion **300**, as shown in FIG. 6. Consequently, the presence and purpose of the club fastener portion **320** may not be readily apparent to an individual. To identify the club fastener portion **320** and alert the individual of its presence, the club fastener portion **320** may be a different color than a color of the handle portion **300**. The magnet cover portion **600** may be a different color (e.g., red) than the color of the handle portion **300** (e.g., black). Adding a dissimilar color to the club fastener portion **320** and/or magnet cover portion **600** may draw attention to those features and enhance the objective of prominently displaying an individual's favorite golf club outside the first housing portion **140**. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

(47) Although the club fastener portion **320** is shown as an integral part of the handle portion **300**, this is not limiting. In another example, the club fastener portion **320** may be located on and attached to an exterior surface of the first housing portion **140**. In another example, the club fastener portion **320** may be a removable club fastener portion that is configured to attach to an exterior surface of the golf bag. In yet another example, the club fastener feature may include a first removable club fastener portion attachable to an upper portion of the first housing portion **140** and a second removable club fastener attachable to a lower portion of the first housing portion **140**. In yet another example, the club fastener feature may include a first removable club fastener portion attachable to a top portion **120** of the first housing portion **140** and a second removable club fastener attachable to the bottom portion **130** of the golf bag **100**. The removable club fasteners may attach to the golf bag **100** or any golf bag with fasteners, magnets, adhesives, or any other suitable technique. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

(48) In one example, as illustrated in FIGS. 10 and 11, a magnet cover portion **600** is shown adapted to cover the magnetic portion **340**. The magnet cover portion **600** may have a body portion **610** having a top portion **620** and a bottom portion **630**. The magnet cover portion **600** may have a tongue-shaped flap portion **640** extending from the body portion **610** at or proximate a first end **650** of the body portion **610**. The flap portion **640** may be configured to entirely or partially cover the outer portion **360** of the magnetic portion **340** that is exposed to the space **332** defined by the U-shaped portion **330** of the club fastener portion **320**. The flap portion **640** may be cantilevered from the first end **650** and may extend orthogonally or substantially orthogonally relative to the top portion **620** of the body portion **610**, as shown in FIG. 10. In one example, the body portion **610** may be made from a first material (e.g., polycarbonate), and the flap portion **640** may be made from a second material (e.g., thermoplastic elastomer) that is softer and more elastic than the first material. In another example, the body portion **610** and the flap portion **640** may be made from the

same material. The body portion **610** and the flap portion **640** may be a unitary piece. Alternately, the body portion **610** and the flap portion **640** may be separate pieces joined together to form the magnet cover portion **600**. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

(49) The magnet cover portion **600** may protect the shaft from being scratched or marred by the magnetic portion. The magnet cover portion **600** may attenuate sound produced when inserting the shaft into the club fastener portion **320**. Accordingly, the magnet cover portion **600** may be made from a softer material (i.e., having a lower material hardness value) than the ferromagnetic material of the magnetic portion **340**. In one example, the magnet cover portion **600** may be made from a synthetic material such as plastic or carbon fiber. In another example, the magnet cover portion **600** may be made from a natural material such as wood, leather, rubber, or cork. In yet another example, the flap portion **640** of the magnet cover portion **600** may be made of a conformable material that can be adapted to receive a range of shaft diameters. The magnet cover portion **600** may experience wear over time and, therefore, may be removable and replaceable. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

(50) The magnet cover portion **600** may include one or more locating features to aid installation and alignment of the magnet cover portion **600**. Examples of locating features include, but are not limited to, bosses, shims, pockets, depressions, locating pins, and threaded holes. The magnet cover portion **600** may include one or more bosses exemplarily shown as a first boss **660** and a second boss **665** in FIGS. **10** and **11**. In one example, the first boss **660** and second boss **665** may protrude from a top surface **621** of the top portion **620** and may extend in the same or substantially the same direction as the flap portion **640**. The first boss **660** and second boss **665** may be located at or proximate to a second end **670** of the body portion **610**. In the illustrated example, the first boss **660** and second boss **665** may be spaced apart in a lateral direction across the top portion **620**. Alternatively, the first boss **660** and second boss **665** may be spaced apart in a longitudinal direction or other directions across the top portion **620**. The first boss **660** and second boss **665** may be connected to or separated from a shim portion **680** located on the top portion **620**. In one example, the shim portion **680** may be located between the flap portion **640** and the first and second bosses **660** and **665**. The shim portion **680** may be configured to fit inside the cavity **350** on the underside **321** of the club fastener portion **320** and may abut the magnetic portion **340** housed inside the cavity **350**. The shim portion **680** may have a constant or variable height relative to the top surface **621** of the top portion **620**. In one example, the shim portion **680** may have a tapered height. In the illustrated example, the shim portion **680** may gradually increase in height in a direction toward the first and second bosses **660** and **665**. A through-hole **690** may be formed through the body portion **610** proximate to the second end **670**. The through-hole **690** may be located equidistant from the first and second bosses **660** and **665**. The through-hole **690** may be located closer to the second end **670** than the first and second bosses **660** and **665**. A recess **695** may be provided on the bottom portion **630** to allow a threaded fastener **691** to be inserted through the through-hole **690** and a head of the fastener to be flush with a bottom surface **631** of the bottom portion **630**, as shown in FIG. **13**. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

(51) In FIGS. **12-14**, and with continued reference to the magnet cover portion **600** of FIGS. **10** and **11**, an alternative example of the club divider portion **200** is shown. Except for the features described below, the club divider portion **200** may be similar to that shown in FIGS. **1-9**. In the illustrated example, the club fastener portion **320** of the handle portion **300** may include one or more locating features to aid installation and alignment of the magnet cover portion **600**. Examples of locating features may include, but are not limited to, bosses, shims, pockets, depressions, locating pins, and threaded holes. The club fastener portion **320** may include a depression **700** on the underside **321** of the club fastener portion **320** and at least partially surrounding the cavity **350** opening. The depression **700** may be configured to fit the magnet cover portion **600** such that the

body portion **610** of the magnet cover portion **600** sits flush with the underside **321** of the club fastener portion **320**. The depression **700** may include a first locating hole **710** positionally aligned with the first boss **660** of the magnet cover portion **600** and configured to receive the first boss **660** therein. The depression **700** may include a second locating hole **715** positionally aligned with the second boss **665** of the magnet cover portion **600** and configured to receive the second boss **465** therein. The depression **700** may include a threaded hole **720** positionally aligned with the through-hole **690** of the magnet cover portion **600** and configured to receive a threaded fastener **691** inserted through the through-hole **690** to secure the magnet cover portion **600** to the club fastener portion **320**, as shown in FIG. 13. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

(52) As illustrated in the example depicted in FIGS. 10-14, the magnet cover portion **600** may be placed inside the depression **700** such that the first and second bosses **660** and **665** are received inside the corresponding first and second locating holes **710** and **715** and the shim portion **680** is received inside the cavity **350** on the underside **321** of the club fastener portion **320**. A threaded fastener **691** may be inserted through the through-hole **690** and coupled to the threaded hole **720** to secure the magnet cover portion **600** to the club fastener portion **320**, as shown in FIG. 13. In another example, the magnet cover portion **600** may be glued in place using an adhesive in lieu of a fastener. In another example, the shim portion **680** may be made from a metal material and the magnet cover portion **600** may be secured in place via a magnetic attraction between the shim portion **680** and the magnetic portion **340** housed inside the cavity **350** on the underside **321** of the club fastener portion **320**. Securing the magnet cover portion **600** to the club fastener portion **320** may result in the outer portion **360** of the magnetic portion **340** being entirely or partially covered by the flap portion **640** of the magnet cover portion **600**. Accordingly, the first boss **660**, the second boss **665**, and the shim portion **680** may collectively function to align the flap portion **640** with the outer portion **360** of the magnetic portion **340**. In another example, the shim portion **680** may be omitted if the cavity **350** is entirely occupied by the magnetic portion **340**. In another example, the magnet cover portion **600** may include only the flap portion **640** (i.e., without any other parts) and may be attached to the magnetic portion **340** with an adhesive or a bonding agent. In operation, the flap portion **640** may serve as a physical barrier. The flap portion **640** may physically separate and prevent direct contact between the magnetic portion **340** and the first shaft portion **410** engaged to the club fastener portion **320** without prohibiting magnetic attraction therebetween, as shown in FIG. 14. By constructing the flap portion **640** from a softer material than the ferromagnetic material of the magnetic portion **340**, the flap portion **640** may be less abrasive than the magnetic portion **340**, and as a result, when the shaft **440** is engaged by the club fastener portion **320** and contacts the flap portion **640**, the shaft is less likely to be marred during transport than if it was otherwise directly contacting the magnetic portion **340**. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

(53) In the example shown in FIG. 4, the magnetic portion **340** may be visible after it is installed in the cavity of the club fastener portion **320**. Installation of the magnet cover portion **600** may prevent direct contact between the shaft **440** of the golf club **400** and the magnetic portion **340** and thereby protect the shaft from abrasion. In other examples, the magnetic portion **340** may be located within the club fastener portion **320** and be separated from the shaft **440** by a portion of the club fastener portion **320**, thereby preventing direct contact between the shaft **440** and magnetic portion **340** and protecting the shaft. For example, as shown in FIG. 15, the magnetic portion **340** may be located at or proximate to the arcuate portion **334** of the U-shaped portion. In another example, as shown in FIG. 16, the magnetic portion **340** may be located at or proximate to the first arm portion **331** of the U-shaped portion **330**. In another example, as shown in FIG. 17, the magnetic portion **340** may be located at or proximate to the second arm portion **333** of the U-shaped portion **330**. Except for the location of the magnetic portion **340**, the alternative examples of the club divider portion shown in FIGS. 15-17 may be similar to the club divider portion **200**

shown in FIGS. 1-9. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

(54) Although club fastener portions **320** with magnetic portions **340** are shown and described in FIGS. 1-14, the club fastener portion **320** may include any suitable type of club fastening means, with or without a magnetic portion, configured to hold a shaft **440** of the golf club **400** (e.g., via the first shaft portion **410**). The club fastening means may be configured to retain a shaft **440** of the golf club **400** at a fastening location outside of the first housing portion **140** and proximate to the top portion **120** of the golf bag **100**. In some examples, the club fastening means may include a magnetic portion, a clamp, a spring-loaded claw, a detent, a latch, a flap, a plurality of bristles, or a combination thereof. It should be understood that any suitable type of club fastening means may be utilized. The club fastening means may be configured to receive the shaft **440** from a substantially horizontal direction of insertion, rather than a vertical direction of insertion, to permit use in confined spaces, such as when the golf bag **100** is positioned in a golf cart with a roof. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

(55) As illustrated in the example of FIG. 18, the fastener portion **320** of the club divider portion **200** may include a detent **335**. The detent **335** may be located on a surface of the U-shaped portion **330**. In one example, the detent **335** may be made of a relatively soft material (e.g., thermoplastic elastomer) that compresses while the shaft **440** is being forced past the detent into the space **332** and then resumes its original shape after the shaft has passed, thereby serving to retain the shaft within the space **332**. In another example, the detent **335** may be a spring-loaded detent that retracts into the arm portion while the shaft **440** is being forced past the detent into the space **332** and then resumes its original position after the shaft has passed, thereby serving to retain the shaft within the space **332**. The detent may be located at any location on the U-shaped portion **330**. In one example, the detent **335** may be located on the first arm portion **331**, as shown in FIG. 18. In another example, the detent may be located on the second arm portion **333**. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

(56) As illustrated in the example of FIGS. 19 and 20, the fastener portion **320** of the club divider portion **200** may include a flap **336**. The flap **336** may be located at or proximate to the mouth portion **337** of the U-shaped portion **330**. The flap **336** may have a first end that is attached to the U-shaped portion **330** and a second end that is free. The flap **336** may be hinged or pivotally attached at the first end to the U-shaped portion **330** with one or more resistance devices such as a torsional spring or an elastomer that may provide resistance when the flap **336** is pivoted.

Alternatively, the flap **336** may be fixedly attached at the first end and constructed from a flexible material that provides pending resistance. Accordingly, the flap **336** may resist any pivoting or bending. In one example, as shown in FIGS. 19 and 20, the flap **336** may be attached to the first arm portion **331**. In another example, the flap **336** may be attached to the second arm portion **333**. The flap **336** may be configured to swing or bend inward when the shaft **440** is being forced into the space **332** of the U-shaped portion **330** and then close when the shaft has passed the flap, thereby retaining the shaft within the space **332** due to the pivoting or bending resistance provided by the flap **336** as described herein. The flap **336** may be configured to swing or bend outward when the shaft **440** is being removed from the club fastener portion. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

(57) As illustrated in the example of FIGS. 21 and 22, the fastener portion **320** of the club divider portion **200** may include a plurality of bristles **338**. The plurality of bristles **338** may be located at or proximate to the mouth portion **337** of the U-shaped portion. The plurality of bristles **338** may be configured to deflect when the shaft **440** is being forced into the space **332** of the U-shaped portion **330** and then return to their original positions after the shaft has passed. The bristles **338** may be elastic and yet have sufficient rigidity to maintain the shaft within the space **332**. In one example, the plurality of bristles may extend from the first arm portion **331**. In another example, the plurality of bristles may extend from the second arm portion **333**. In yet another example, as shown in FIGS.

21 and 22, the plurality of bristles 338 may include a first plurality of bristles extending from the first arm portion 331 and a second plurality of bristles extending from the second arm portion 333. The apparatus, methods, and articles of manufacture described herein are not limited in this regard. (58) Although a particular order of actions may be described herein with respect to one or more processes, these actions may be performed in other temporal sequences. Further, two or more actions in any of the processes described herein may be performed sequentially, concurrently, or simultaneously.

(59) A numerical range defined using the word “between” includes numerical values at both end points of the numerical range. A spatial range defined using the word “between” includes any point within the spatial range and the boundaries of the spatial range. A location expressed relative to two spaced apart or overlapping elements using the word “between” includes (i) any space between the elements, (ii) a portion of each element, and/or (iii) the boundaries of each element.

(60) The terms “and” and “or” may have both conjunctive and disjunctive meanings. The terms “a” and “an” are defined as one or more unless this disclosure indicates otherwise. The term “coupled”, and any variation thereof refer to directly or indirectly connecting two or more elements chemically, mechanically, and/or otherwise. The phrase “removably connected” is defined such that two elements that are “removably connected” may be separated from each other without breaking or destroying the utility of either element.

(61) The term “substantially” when used to describe a characteristic, parameter, property, or value of an element may represent deviations or variations that do not diminish the characteristic, parameter, property, or value that the element may be intended to provide. Deviations or variations in a characteristic, parameter, property, or value of an element may be based on, for example, tolerances, measurement errors, measurement accuracy limitations and other factors. The term “proximate” is synonymous with terms such as “adjacent,” “close,” “immediate,” “nearby”, “neighboring”, etc., and such terms may be used interchangeably as appearing in this disclosure.

(62) The apparatus, methods, and articles of manufacture described herein may be implemented in a variety of embodiments, and the foregoing description of some of these embodiments does not necessarily represent a complete description of all possible embodiments. Instead, the description of the drawings, and the drawings themselves, disclose at least one embodiment, and may disclosure alternative embodiments.

(63) As the rules of golf may change from time to time (e.g., new regulations may be adopted or old rules may be eliminated or modified by golf standard organizations and/or governing bodies such as the United States Golf Association (USGA), the Royal and Ancient Golf Club of St. Andrews (R&A), etc.), golf equipment related to the apparatus, methods, and articles of manufacture described herein may be conforming or non-conforming to the rules of golf at any particular time. Accordingly, golf equipment related to the apparatus, methods, and articles of manufacture described herein may be advertised, offered for sale, and/or sold as conforming or non-conforming golf equipment. The apparatus, methods, and articles of manufacture described herein are not limited in this regard.

(64) Although certain example apparatus, methods, and articles of manufacture have been described herein, the scope of coverage of this disclosure is not limited thereto. On the contrary, this disclosure covers all apparatus, methods, and articles of articles of manufacture fairly falling within the scope of the appended claims either literally or under the doctrine of equivalents.

Claims

1. A golf bag top comprising: a club divider portion having a perimeter portion and one or more rib portions extending from a first inner wall of the perimeter portion to a second inner wall of the perimeter portion to define a plurality of openings; a handle portion extending from a first outer wall of the club divider portion to a second outer wall of the club divider portion, the handle

portion extending beyond the perimeter portion of the club divider portion to define a handle opening between the handle portion and the club divider portion; a club fastener portion extending from the handle portion, the club fastener portion comprising: a U-shaped portion defining a space configured to receive a shaft of a golf club; a cavity in a bottom portion of the club fastener portion; a magnetic portion within the cavity; and a depression in the bottom portion of the club fastener portion; and a magnet cover portion comprising: a body portion configured to fit the depression; and a flap portion extending from the body portion and positioned between the magnetic portion and the space defined by the U-shaped portion, wherein the flap portion is configured to separate the magnetic portion and the shaft, and wherein the magnetic portion is configured to magnetically attract the shaft against the flap portion.

2. A golf bag top as defined in claim 1, wherein the depression comprises a locating hole, wherein the magnet cover portion comprises a boss extending from the body portion, and wherein the boss is received in the locating hole.

3. A golf bag top as defined in claim 1, wherein the depression comprises a first locating hole and a second locating hole, wherein the magnet cover portion comprises a first boss extending from the body portion and a second boss extending from the body portion, and wherein the first boss is received in the first locating hole and the second boss is received in the second locating hole.

4. A golf bag top as defined in claim 1, wherein the body portion includes a shim portion configured to fit in the cavity and a boss portion configured to fit in a locating hole in the depression, and wherein the shim portion and the boss portion collectively align the flap portion with the magnetic portion.

5. A golf bag top as defined in claim 1, wherein the club divider portion comprises a spine portion that interconnects the one or more rib portions to define the plurality of openings.

6. A golf bag top as defined in claim 1 further comprising a through-hole in the body portion of the magnet cover portion, a threaded hole in the depression, and a threaded fastener inserted through the through-hole and threaded into the threaded hole to fasten the magnet cover portion to the club fastener portion.

7. A golf bag top as defined in claim 1, wherein the U-shaped portion is spaced apart from the club divider portion by at least one shaft diameter.

8. A golf bag top comprising: a club divider portion having a perimeter portion; a handle portion attached to the club divider portion and extending beyond the perimeter portion; and a club fastener portion coupled to the handle portion, the club fastener portion configured to hold a shaft of a golf club, the club fastener portion comprising: a cavity in a bottom portion of the club fastener portion; and a magnetic portion within the cavity; and a magnet cover portion coupled to the club fastener portion and including a flap portion partially or entirely covering a portion of the magnetic portion, wherein the flap portion is between the magnetic portion and the shaft, and wherein the magnetic portion is configured to magnetically attract the shaft.

9. A golf bag top as defined in claim 8, wherein the club fastener portion comprises a U-shaped portion having a first arm portion, a second arm portion, and an arcuate portion connecting the first arm portion to the second arm portion, wherein the cavity is located in the U-shaped portion.

10. A golf bag top as defined in claim 8, wherein the magnet cover portion comprises a shim portion made of a metal material configured to fit within the cavity and be magnetically attracted to the magnetic portion to couple the magnet cover portion to the club fastener portion.

11. A golf bag top as defined in claim 8, wherein the club fastener portion comprises a U-shaped portion defining a space having a width that is greater than or equal to a maximum outer diameter of the shaft.

12. A golf bag top as defined in claim 8, wherein the magnet cover portion comprises a body portion comprising a first material, and the flap portion comprises a second material that is softer than the first material and softer than a ferromagnetic material of the magnetic portion.

13. A golf bag top as defined in claim 8, wherein the flap portion is a tongue-shaped flap portion.

14. A golf bag top comprising: a club divider portion having a plurality of openings configured to receive one or more golf club shafts; a handle portion for carrying a golf bag, the handle portion being attached to the club divider portion; a club fastener portion integrated into the handle portion, the club fastener portion configured to receive a shaft of a golf club, the club fastener portion comprising a magnetic portion configured to magnetically attract the shaft; and a magnet cover portion coupled to the club fastener portion, the magnet cover portion comprising a body portion and a flap portion extending from the body portion, the flap portion covering at least a portion of the magnetic portion, wherein the flap portion is located between the magnetic portion and the shaft, and wherein the flap portion physically separates the magnetic portion and the shaft without prohibiting magnetic attraction between the magnetic portion and the shaft.
 15. A golf bag top as defined in claim 14 further comprising one or more locating features on the magnet cover portion to aid installation onto the club fastener portion.
 16. A golf bag top as defined in claim 14 further comprising a first locating feature in a bottom side of the club fastener portion and a second locating feature extending from the body portion, wherein the first locating feature receives the second locating feature.
 17. A golf bag top as defined in claim 14 further comprising a cavity in the club fastener portion, the magnetic portion located in the cavity.
 18. A golf bag top as defined in claim 14, wherein the handle portion has a first color, and the magnet cover portion has a second color that is different from the first color.
 19. A golf bag top as defined in claim 14, wherein the club fastener portion comprises a depression, and wherein the body portion of the magnet cover portion fits in the depression and is flush with an exterior surface of the club fastener portion.
 20. A golf bag top as defined in claim 14 further comprising: a cavity in the club fastener portion, the magnetic portion located in the cavity; and a shim portion extending from a top portion of the body portion, the shim portion configured to extend into the cavity and abut the magnetic portion.
-