

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12397326
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Suzuki; Kei et al.

Substrate processing method and substrate processing apparatus

Abstract

A substrate processing method is provided, which includes: a sulfuric acid immersing step of immersing a plurality of substrates in a sulfuric acid-containing liquid within a sulfuric acid vessel; a transporting step of taking out the substrates from the sulfuric acid vessel and transporting the substrates to an ozone gas treatment unit; and an ozone exposing step of exposing the substrates transported to the ozone gas treatment unit to an ozone-containing gas. The ozone gas treatment unit may include a gas treatment chamber which accommodates the substrates. The ozone exposing step may include the step of placing the substrates taken out of the sulfuric acid vessel in a treatment space within the gas treatment chamber to expose the substrates to the ozone-containing gas.

Inventors:	Suzuki; Kei (Kyoto, JP), Inaba; Masaki (Kyoto, JP)
Applicant:	SCREEN Holdings Co., Ltd. (Kyoto, JP)
Family ID:	1000008777893
Assignee:	SCREEN Holdings Co., Ltd. (Kyoto, JP)
Appl. No.:	18/601642
Filed:	March 11, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240216960 A1	Jul. 04, 2024

Foreign Application Priority Data

JP	2021-155177	Sep. 24, 2021
----	-------------	---------------

Related U.S. Application Data

Publication Classification

Int. Cl.: **H01L21/67** (20060101); **B08B3/08** (20060101); **B08B5/00** (20060101); **B08B13/00** (20060101); **H01L21/677** (20060101)

U.S. Cl.:

CPC **B08B3/08** (20130101); **B08B5/00** (20130101); **B08B13/00** (20130101); **H01L21/67057** (20130101); **H01L21/67757** (20130101); H01L21/67109 (20130101)

Field of Classification Search

CPC: B08B (3/08); B08B (5/00); B08B (13/00); H01L (21/67109); H01L (21/67742); H01L (21/67757); H01L (21/67057)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5603777	12/1996	Ohashi	414/940	H01L 21/67712
2001/0004898	12/2000	Kamikawa	N/A	N/A
2001/0038089	12/2000	Levenson et al.	N/A	N/A
2002/0017315	12/2001	Kamikawa	134/61	B08B 3/08
2004/0063319	12/2003	Toshima	N/A	N/A
2005/0217793	12/2004	Hasegawa et al.	N/A	N/A
2006/0024213	12/2005	Arai	N/A	N/A
2010/0095981	12/2009	Kamikawa	134/3	H01L 21/67028
2010/0218791	12/2009	Tanaka et al.	N/A	N/A
2011/0130009	12/2010	Kumnig et al.	N/A	N/A
2011/0139192	12/2010	Koide	N/A	N/A
2012/0006726	12/2011	Kusuhara	414/801	B28D 5/0082
2013/0233351	12/2012	Brown	N/A	N/A
2014/0045339	12/2013	Iwata et al.	N/A	N/A
2014/0130367	12/2013	Yonekawa	N/A	N/A
2017/0018423	12/2016	Starrs	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
61100937	12/1985	JP	H01L 21/3046
H04-11308	12/1991	JP	N/A
H05152203	12/1992	JP	N/A
2004-134810	12/2003	JP	N/A
20230019312	12/2022	KR	N/A
201409188	12/2013	TW	N/A

OTHER PUBLICATIONS

Machine translation of JP-61100937-A (Year: 1986). cited by examiner

Primary Examiner: Bergner; Erin F

Attorney, Agent or Firm: OSTROLENK FABER LLP

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS (1) This Divisional Patent application claims priority to U.S. patent application Ser. No. 17/892,500, filed Aug. 22, 2022, which claims the priority benefit of Japanese Patent Application No. 2021-155177 filed on Sep. 24, 2021, the disclosure of which is entirely incorporated herein by reference.

BACKGROUND OF THE INVENTION**1. Field of the Invention**

(1) The present invention relates to a substrate processing method for processing a substrate, and to a substrate processing apparatus for processing a substrate. Exemplary substrates to be processed include semiconductor wafers, substrates for FPDs (Flat Panel Displays) such as liquid crystal display devices and organic EL (electroluminescence) display devices, substrates for optical disks, substrates for magnetic disks, substrates for magneto-optical disks, substrates for photomasks, ceramic substrates, and substrates for solar cells.

2. Description of the Related Art

(2) In a substrate processing apparatus disclosed in US2014/0045339A1, ozone gas is supplied to sulfuric acid and dissolved in the sulfuric acid in piping, whereby sulfuric acid/ozone is provided. By mixing the sulfuric acid and the ozone together, peroxodisulfuric acid (S.sub.2O.sub.8.sup.2-) is generated as an active species (etchant).

(3) In the substrate processing apparatus of US2014/0045339A1, the sulfuric acid/ozone flows through a sulfuric acid/ozone supply pipe into a water mixing portion to be mixed with water, whereby a sulfuric acid/ozone/water mixture liquid is generated. While a substrate is rotated, the sulfuric acid/ozone/water mixture liquid is spouted toward the substrate from a sulfuric acid/ozone/water nozzle to be supplied onto a surface of the substrate, whereby a resist is removed from the surface of the substrate.

SUMMARY OF THE INVENTION

(4) In the substrate processing apparatus disclosed in US2014/0045339A1, the temperature of the sulfuric acid/ozone/water mixture liquid is increased, as compared with the temperature of the sulfuric acid/ozone before the mixing, by dilution heat generated when the sulfuric acid/ozone is mixed with the water. Therefore, even if the sulfuric acid/ozone to be mixed with the water has a relatively low temperature, the sulfuric acid/ozone/water mixture liquid to be supplied to the surface of the substrate has a temperature necessary for the removal of the resist. Further, where the sulfuric acid/ozone to be mixed has a relatively low temperature, a greater amount of the ozone gas can be dissolved in the sulfuric acid/ozone before the mixing.

(5) In the apparatus of US2014/0045339A1, however, the concentration of the peroxodisulfuric acid having an oxidative power is liable to be reduced by mixing the sulfuric acid/ozone with the water. Therefore, it may be impossible to provide a sufficient oxidative power.

(6) An embodiment of the present invention provides a substrate processing method and a substrate processing apparatus which are capable of speedily and sufficiently removing an organic film such

as of a resist from a substrate.

(7) The embodiment of the present invention provides a substrate processing method, which includes: a sulfuric acid immersing step of immersing a plurality of substrates in a sulfuric acid-containing liquid within a sulfuric acid vessel; a transporting step of taking out the substrates from the sulfuric acid vessel and transporting the substrates to an ozone gas treatment unit; and an ozone exposing step of exposing the substrates transported to the ozone gas treatment unit to an ozone-containing gas.

(8) According to the method, the substrates immersed in the sulfuric acid-containing liquid at a time are exposed to the ozone-containing gas by the ozone gas treatment unit. Thus, ozone contained in the ozone-containing gas is dissolved in the sulfuric acid-containing liquid adhering to the substrates taken out of the sulfuric acid-containing liquid, whereby peroxodisulfuric acid is generated in the adhering sulfuric acid-containing liquid.

(9) As a result, organic films such as of a resist can be speedily and sufficiently removed from the substrates.

(10) The ozone-containing gas contains gaseous ozone (ozone gas), and the sulfuric acid-containing liquid contains sulfuric acid. The sulfuric acid-containing liquid is, for example, a sulfuric acid aqueous solution.

(11) In the embodiment of the present invention, the ozone gas treatment unit includes a gas treatment chamber which accommodates the substrates. The ozone exposing step includes the step of placing the substrates taken out of the sulfuric acid vessel in a treatment space within the gas treatment chamber to expose the substrates to the ozone-containing gas.

(12) According to the method, the substrates are generally simultaneously exposed to the ozone-containing gas in the treatment space. Therefore, the organic films can be more speedily and sufficiently removed from the substrates.

(13) In the embodiment of the present invention, the ozone exposing step includes the step of supplying the ozone-containing gas into the treatment space from a plurality of supply orifices which open in a wall defining the treatment space, and exhausting the treatment space through a plurality of exhaust orifices which open in the wall, whereby the substrates placed in the treatment space is exposed to the ozone-containing gas.

(14) According to the method, the ozone-containing gas is supplied into the treatment space from the supply orifices which open in the wall defining the treatment space, and the treatment space is exhausted through the exhaust orifices which open in the wall. Therefore, even if ozone in an atmosphere in contact with the sulfuric acid-containing liquid on the substrates is dissolved in the sulfuric acid-containing liquid to be thereby consumed, ozone is supplied to the atmosphere in contact with the sulfuric acid-containing liquid adhering to the substrates by supplying the ozone-containing gas into the treatment space. Therefore, the concentration of the ozone in the atmosphere in contact with the sulfuric acid-containing liquid on the substrates can be maintained at a sufficiently high level. Thus, the peroxodisulfuric acid can be generated in the sulfuric acid-containing liquid on the substrates.

(15) In the embodiment of the present invention, the supply orifices are arranged in a plurality of supply orifice rows juxtaposed in a predetermined arrangement direction in the gas treatment chamber. Each of the supply orifice rows may include a plurality of the supply orifices. The ozone exposing step includes the step of placing the substrates in the treatment space so that the substrates are arranged in the arrangement direction and located between respective adjacent pairs of the supply orifice rows.

(16) According to the method, the ozone-containing gas is supplied from the supply orifice rows between respective adjacent pairs of the substrates. Therefore, the ozone can be sufficiently supplied into the atmosphere in contact with the sulfuric acid-containing liquid on the substrates, and can be sufficiently dissolved in the sulfuric acid-containing liquid on the substrates. As a result, it is possible to suppress the uneven removal of the organic films from the substrates.

(17) In the embodiment of the present invention, the sulfuric acid immersing step includes a vertical immersing step of immersing the substrates in the sulfuric acid-containing liquid within the sulfuric acid vessel while holding the substrates in a vertical attitude. The substrate processing method further includes an attitude changing step of changing the attitude of the substrates taken out of the sulfuric acid vessel from the vertical attitude to a horizontal attitude. The ozone exposing step includes a horizontal exposing step of exposing the substrates to the ozone-containing gas while holding the substrates in the horizontal attitude.

(18) According to the method, the substrates held in the vertical attitude can be immersed in the sulfuric acid-containing liquid. Therefore, the substrates can be generally simultaneously immersed in the sulfuric acid-containing liquid. According to the method, the substrates are exposed to the ozone-containing gas after the attitude of the substrates is changed from the vertical attitude to the horizontal attitude. Therefore, the thickness variations of the sulfuric acid-containing liquid at different positions on each of the substrates can be suppressed, which may otherwise occur when the sulfuric acid-containing liquid adhering to the substrates held in the vertical attitude moves down by gravity. This suppresses the uneven removal of the organic film at different positions on each of the substrates.

(19) In the embodiment of the present invention, the substrate processing method further includes a substrate rotating step of rotating the substrates held in the horizontal attitude about a vertical axis extending through the centers of the substrates before the exposure of the substrates to the ozone-containing gas in the ozone exposing step after the attitude changing step.

(20) Therefore, an excess amount of the sulfuric acid-containing liquid can be removed from the substrates, thereby improving the thickness evenness of the sulfuric acid-containing liquid at different positions on each of the substrates. This improves the evenness of the ozone concentration of the sulfuric acid-containing liquid at different positions on each of the substrates. As a result, it is possible to suppress the uneven removal of the organic film at different positions on each of the substrates.

(21) In the embodiment of the present invention, the treatment space is located just above the sulfuric acid vessel. The transporting step includes the step of lifting the substrates from the sulfuric acid vessel to place the substrates in the treatment space.

(22) According to the method, the substrates are lifted from the sulfuric acid vessel by the unidirectional movement to be thereby moved from the sulfuric acid vessel to the treatment space. Therefore, the substrates can be speedily exposed to the ozone-containing gas after the sulfuric acid-containing liquid is applied to the substrates. Therefore, the organic films can be speedily removed from the substrates.

(23) Another embodiment of the present invention provides a substrate processing apparatus, which includes: a sulfuric acid vessel which retains a sulfuric acid-containing liquid and is configured so that a plurality of substrates can be immersed in the sulfuric acid-containing liquid; an ozone gas treatment unit in which the substrates are exposed to an ozone-containing gas; and a transport unit which transports the substrates between the sulfuric acid vessel and the ozone gas treatment unit.

(24) According to the apparatus, the substrates simultaneously immersed in the sulfuric acid-containing liquid are exposed to the ozone-containing gas by the ozone gas treatment unit. Thus, ozone contained in the ozone-containing gas is dissolved in the sulfuric acid-containing liquid adhering to the substrates taken out of the sulfuric acid-containing liquid, whereby peroxodisulfuric acid is generated in the sulfuric acid-containing liquid adhering to the substrates.

(25) As a result, organic films such as of a resist can be speedily and sufficiently removed from the substrates.

(26) In the embodiment of the present invention, the ozone gas treatment unit includes a gas treatment chamber having a treatment space capable of accommodating the substrates for exposing the substrates accommodated in the treatment space to the ozone-containing gas.

(27) According to the apparatus, the substrates can be generally simultaneously exposed to the

ozone-containing gas in the treatment space. Therefore, the organic films can be more speedily and sufficiently removed from the substrates.

(28) In the another embodiment of the present invention, the gas treatment chamber includes a wall defining the treatment space, a plurality of supply orifices which open in the wall for supplying the ozone-containing gas into the treatment space, and a plurality of exhaust orifices which open in the wall for exhausting the treatment space.

(29) According to the apparatus, the ozone-containing gas is supplied into the treatment space from the supply orifices which open in the wall defining the treatment space, and expelled from the treatment space through the exhaust orifices which open in the wall. Therefore, even if ozone in an atmosphere in contact with the sulfuric acid-containing liquid on the substrates is dissolved in the sulfuric acid-containing liquid to be thereby consumed, ozone is supplied to the atmosphere in contact with the sulfuric acid-containing liquid adhering to the substrates by supplying the ozone-containing gas into the treatment space. Therefore, the concentration of the ozone in the atmosphere in contact with the sulfuric acid-containing liquid on the substrates can be maintained at a sufficiently high level. This makes it possible to sufficiently generate the peroxodisulfuric acid in the sulfuric acid-containing liquid on the substrates.

(30) In the another embodiment of the present invention, the supply orifices are arranged in a plurality of supply orifice rows juxtaposed in a predetermined arrangement direction in the gas treatment chamber. Each of the supply orifice rows may include a plurality of the supply orifices. The transport unit supports the substrates so as to arrange the substrates in the arrangement direction, and transports the substrates into the gas treatment chamber so that the substrates are located between respective adjacent pairs of the supply orifice rows.

(31) According to the apparatus, the transport unit transports the substrates into the treatment space so as to locate the substrates between respective adjacent pairs of the supply orifice rows. Therefore, the ozone-containing gas can be supplied from the supply orifice rows between respective adjacent pairs of the substrates. This makes it possible to sufficiently supply the ozone into the atmosphere in contact with the sulfuric acid-containing liquid on the substrates, whereby the ozone can be sufficiently dissolved in the sulfuric acid-containing liquid on the substrates. As a result, it is possible to suppress the uneven removal of the organic films from the substrates.

(32) In the another embodiment of the present invention, the sulfuric acid vessel is configured so that the substrates can be immersed in the sulfuric acid-containing liquid while being held in a vertical attitude. The treatment space is configured so that the substrates can be accommodated therein while being held in a horizontal attitude. The transport unit includes an attitude changing mechanism which changes the attitude of the substrates between the vertical attitude and the horizontal attitude.

(33) According to the apparatus, the substrates held in the vertical attitude can be immersed in the sulfuric acid-containing liquid. Therefore, the substrates can be generally simultaneously immersed in the sulfuric acid-containing liquid. Further, where the substrates are transported to the gas treatment chamber after the attitude of the substrates is changed from the vertical attitude to the horizontal attitude by the attitude changing mechanism of the transport unit, the substrates held in the horizontal attitude can be exposed to the ozone-containing gas. Therefore, the thickness variations of the sulfuric acid-containing liquid at different positions on each of the substrates can be suppressed, which may otherwise occur when the sulfuric acid-containing liquid adhering to the substrates held in the vertical attitude moves down by gravity. This suppresses the uneven removal of the organic film at different positions on each of the substrates.

(34) In the another embodiment of the present invention, the transport unit includes a transport robot having a lifter which supports the substrates. The attitude changing mechanism transforms the lifter to change the attitude of the substrates between the vertical attitude and the horizontal attitude.

(35) According to the apparatus, after the substrates held in the vertical attitude are immersed in the

sulfuric acid-containing liquid within the sulfuric acid vessel, the attitude of the substrates can be changed from the vertical attitude to the horizontal attitude by transforming the lifter of the transport robot. Then, the substrates held in the horizontal attitude can be exposed to the ozone-containing gas in the gas treatment chamber. Thus, the substrates can be transported from the sulfuric acid vessel to the gas treatment chamber with the attitude thereof changed by using the single robot. Without the need for transferring the substrates between different robots, the organic films can be speedily removed from the substrates.

(36) In the another embodiment of the present invention, the treatment space is located just above the sulfuric acid vessel. The transport unit is movable up and down while supporting the substrates so as to transport the substrates between the gas treatment chamber and the sulfuric acid vessel.

(37) According to the apparatus, the transport unit is moved up and down while supporting the substrates, whereby the substrates are transported between the gas treatment chamber and the sulfuric acid vessel. Therefore, the substrates are lifted from the sulfuric acid vessel by the unidirectional movement to be thereby moved from the sulfuric acid vessel to the treatment space. Thus, the substrates can be speedily exposed to the ozone-containing gas after the sulfuric acid-containing liquid is applied to the substrates. This makes it possible to speedily remove the organic films from the substrates.

(38) In the another embodiment of the present invention, the substrate processing apparatus further includes a cover member which covers and uncovers the sulfuric acid vessel to separate the inside of the sulfuric acid vessel and the treatment space from each other. This substantially prevents the ozone-containing gas from being dissolved in the sulfuric acid-containing liquid retained in the sulfuric acid vessel. Therefore, substrates to be next subjected to the substrate treatment are substantially prevented from being removed of organic films before the start of the supply of the ozone-containing gas into the treatment space. This suppresses variations in peroxodisulfuric acid treatment period.

(39) In the another embodiment of the present invention, the transport unit includes a first transport robot which transports the substrates held in the vertical attitude to the sulfuric acid vessel, a second transport robot which transports the substrates held in the horizontal attitude to the gas treatment chamber, and a main transport robot which transports the substrates between the first transport robot and the second transport robot. The attitude changing mechanism changes the attitude of the substrates transported by the main transport robot between the horizontal attitude and the vertical attitude.

(40) According to the apparatus, the transportation of the substrates to the sulfuric acid vessel, the transportation of the substrates to the gas treatment chamber, and the change of the attitude of the substrates are achieved by the different robots. This makes the structures of the respective robots less complicated.

(41) In the another embodiment of the present invention, the second transport robot transports the substrates held in the horizontal attitude to the gas treatment chamber, and rotates the substrates held in the horizontal attitude about a vertical axis extending through the centers of the substrates in the gas treatment chamber.

(42) According to the apparatus, an excess amount of the sulfuric acid-containing liquid can be removed from the substrates by rotating the substrates in the gas treatment chamber. Since the sulfuric acid-containing liquid is removed by the rotation of the substrates, it is possible to improve the thickness evenness of the sulfuric acid-containing liquid at different positions on each of the substrates. This improves the evenness of the ozone concentration of the sulfuric acid-containing liquid at different positions on each of the substrates. As a result, it is possible to suppress the uneven removal of the organic film at different positions on each of the substrates.

(43) In the another embodiment of the present invention, the substrate processing apparatus further includes a heating chamber in which the substrates are heated. The transport unit further includes a third transport robot which transports the substrates held in the horizontal attitude into the heating

chamber and rotates the substrates held in the horizontal attitude about the vertical axis extending through the centers of the substrates in the heating chamber. The main transport robot transports the substrates among the sulfuric acid vessel, the gas treatment chamber and the heating chamber.

(44) According to the apparatus, an excess amount of the sulfuric acid-containing liquid can be removed from the substrates by rotating the substrates in the heating chamber. Since the sulfuric acid-containing liquid is removed by the rotation of the substrates, it is possible to improve the thickness evenness of the sulfuric acid-containing liquid at different positions on each of the substrates.

(45) Since the excess amount of the sulfuric acid-containing liquid is removed from the substrates in the heating chamber, it is possible to heat the substrates while removing the sulfuric acid-containing liquid. Where the heated substrates are transported into the gas treatment chamber via the main transport robot and the second transport robot, the substrates can be exposed to the ozone-containing gas after being removed of the excess amount of the sulfuric acid-containing liquid and heated. This makes it possible to enhance the activity of the peroxodisulfuric acid while improving the evenness of the ozone concentration of the sulfuric acid-containing liquid at different positions on each of the substrates. As a result, it is possible to further suppress the uneven removal of the organic film at different positions on each of the substrates.

(46) The foregoing and other objects, features, and effects of the present invention will become more apparent from the following description of embodiments with reference to the attached drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a schematic plan view showing the layout of a substrate processing apparatus according to a first embodiment of the present invention.

(2) FIG. 2 is a schematic elevational view showing the structures of major portions of the substrate processing apparatus by way of example.

(3) FIG. 3 is a sectional view for describing the structure of an auxiliary transport robot provided in the substrate processing apparatus by way of example.

(4) FIG. 4 is a block diagram for describing the electrical configuration of the substrate processing apparatus by way of example.

(5) FIG. 5 is a flow chart for describing an exemplary substrate treatment to be performed by the substrate processing apparatus.

(6) FIGS. 6A to 6C are schematic diagrams for describing how the substrate processing apparatus performs the substrate treatment.

(7) FIG. 7 is a diagram of a wall of a gas treatment chamber as seen from a treatment space of the gas treatment chamber when a lifter is located at a gas treatment position.

(8) FIG. 8 is a flow chart for describing another exemplary substrate treatment.

(9) FIG. 9 is an elevational view of major portions of a substrate processing apparatus according to a first modification of the first embodiment.

(10) FIGS. 10A to 10C are schematic diagrams for describing how the substrate processing apparatus of the first modification performs the substrate treatment.

(11) FIG. 11 is an elevational view of major portions of a substrate processing apparatus according to a second modification of the first embodiment.

(12) FIGS. 12A and 12B are schematic diagrams showing the structure of a first auxiliary transport robot provided in a substrate processing apparatus according to a second embodiment by way of example, specifically illustrating a state in which a lifter supports a single batch of substrates in a vertical attitude and a state in which the lifter supports the single batch of substrates in a horizontal

attitude, respectively.

(13) FIGS. **13A** to **13C** are schematic diagrams for describing how the substrate processing apparatus of the second embodiment performs the substrate treatment.

(14) FIG. **14** is a diagram of a wall of a gas treatment chamber as seen from a treatment space of the gas treatment chamber when the lifter is located at a gas treatment position in the substrate treatment according to the second embodiment.

(15) FIG. **15** is a schematic diagram for describing a substrate processing apparatus according to a modification of the second embodiment.

(16) FIG. **16** is an elevational view showing the structures of major portions of a substrate processing apparatus according to a third embodiment by way of example.

(17) FIG. **17A** is a schematic diagram showing the structure of a main transport robot provided in the substrate processing apparatus of the third embodiment by way of example, and FIG. **17B** is a sectional view taken along a line XVIIIB-XVIIIB in FIG. **17A**.

(18) FIGS. **18A** to **18E** are schematic diagrams for describing how the substrate processing apparatus of the third embodiment performs the substrate treatment.

(19) FIG. **19** is an elevational view of major portions of a substrate processing apparatus according to a first modification of the third embodiment.

(20) FIGS. **20A** and **20B** are schematic diagrams for describing how the substrate processing apparatus of the first modification of the third embodiment performs a substrate treatment.

(21) FIG. **21** is a flow chart for describing the substrate treatment to be performed by the substrate processing apparatus of the first modification of the third embodiment by way of example.

(22) FIG. **22** is an elevational view of major portions of a substrate processing apparatus according to a second modification of the third embodiment.

(23) FIG. **23** is a schematic diagram for describing the structure of a single-substrate treatment unit provided in the substrate processing apparatus by way of example.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Construction of Substrate Processing Apparatus According to First Embodiment

(24) FIG. **1** is a schematic plan view showing the layout of a substrate processing apparatus **1** according to a first embodiment of the present invention.

(25) The substrate processing apparatus **1** is a batch type apparatus adapted to treat a plurality of substrates **W** in batch. The substrate processing apparatus **1** includes load ports **LP** to which carriers **C** each containing disk-shaped substrates **W** such as semiconductor wafers are transported, a plurality of treatment units **2** in which substrates **W** transported from the load ports **LP** are treated with a treatment fluid, a transport unit **3** which transports the substrates **W** between the load ports **LP** and the treatment units **2**, and a controller **4** which controls the substrate processing apparatus **1**.
(26) As will be detailed later, examples of the treatment fluid include treatment liquid and treatment gas. Examples of the treatment liquid include a chemical liquid, a rinse liquid, a sulfuric acid-containing liquid, and a hydrophilizing liquid. Examples of the treatment gas include an ozone-containing gas, a displacement gas, and a heating gas.

(27) The treatment units **2** include a plurality of batch type liquid treatment units each adapted to treat the substrates **W** with the treatment liquid, and a batch type gas treatment unit adapted to treat the substrates **W** with the treatment gas.

(28) The liquid treatment units include a sulfuric acid treatment unit **5** in which the substrates **W** are treated with the sulfuric acid-containing liquid, a first rinsing unit **7** in which the substrates **W** are rinsed with the rinse liquid, a chemical liquid treatment unit **8** in which the substrates **W** are treated with the chemical liquid, and a second rinsing unit **9** in which the substrates **W** are rinsed with the rinse liquid. The gas treatment unit includes an ozone gas treatment unit **6** in which the substrates **W** are treated with the ozone-containing gas.

(29) The sulfuric acid-containing liquid is, for example, a sulfuric acid aqueous solution. The sulfuric acid aqueous solution contains sulfuric acid (H_2SO_4) and water (H_2O). The

sulfuric acid aqueous solution is, for example, dilute sulfuric acid or concentrated sulfuric acid. The sulfuric acid-containing liquid may contain a substance other than sulfuric acid and water. The sulfuric acid-containing liquid may be prepared by mixing sulfuric acid and water such as DIW (deionized water).

(30) The ozone-containing gas may be ozone gas or may be a gas mixture of ozone gas and a gas other than the ozone gas. An example of the gas other than the ozone gas is an inert gas. The inert gas to be contained in the ozone-containing gas may be, for example, nitrogen gas, a noble gas, or a gas mixture of the nitrogen gas and the noble gas. An example of the noble gas is argon gas. Examples of the displacement gas include an inert gas, air, and a gas mixture of the inert gas and air.

(31) The rinse liquid is not limited to the DIW, but may be DIW, carbonated water, electrolyzed ion water, hydrochloric acid water having a dilute concentration (e.g., not lower than 1 ppm and not higher than 100 ppm), ammonia water having a dilute concentration (e.g., not lower than 1 ppm and not higher than 100 ppm), or reduced water (hydrogen water). The rinse liquid to be used in the first rinsing unit **7** and the rinse liquid to be used in the second rinsing unit **9** may be different from each other.

(32) Examples of the chemical liquid include an ammonia/hydrogen peroxide mixture (APM liquid) and hydrofluoric acid.

(33) The substrates **W** to be treated by the substrate processing apparatus **1** are, for example, substrates each having an organic film such as of a resist exposed on a major surface thereof.

(34) The transport unit **3** includes a carrier transport device **15** which transports the carriers **C** between the load ports **LP** and the treatment units **2** and is capable of accommodating the carriers **C**, and an attitude changing robot **16** which loads and unloads the substrates **W** with respect to the carriers **C** held by the carrier transport device **15** and changes the attitude of the substrates **W** between a horizontal attitude and a vertical attitude.

(35) The expression “to change the attitude of the substrates **W** between the vertical attitude and the horizontal attitude” means that the attitude of the substrates **W** can be changed from the vertical attitude to the horizontal attitude, and that the attitude of the substrates **W** can be changed from the horizontal attitude to the vertical attitude.

(36) The term “horizontal attitude” means an attitude such that the major surfaces of the substrates **W** are horizontal. The term “vertical attitude” means an attitude such that the major surfaces of the substrates **W** are vertical. The vertical attitude may also be referred to as upright attitude.

(37) The attitude changing robot **16** performs, in addition to the attitude changing operation, a batching operation for forming a single batch from a plurality of substrates **W** (e.g., 50 substrates **W**) taken out of a plurality of carriers **C**, and an unbatching operation for placing the substrates **W** of the single batch dividedly in a plurality of carriers **C**.

(38) The transport unit **3** further includes a main transport robot **17** which transports the single batch of substrates **W** between the attitude changing robot **16** and the treatment units **2**, and a plurality of auxiliary transport robots **18** which each transport the single batch of substrates **W** between the main transport robot **17** and the treatment units **2**.

(39) The auxiliary transport robots **18** include a first auxiliary transport robot **18A** which transports the single batch of substrates **W** among the sulfuric acid treatment unit **5**, the ozone gas treatment unit **6**, and the first rinsing unit **7**, and a second auxiliary transport robot **18B** which transports the substrates **W** between the chemical liquid treatment unit **8** and the second rinsing unit **9**.

(40) The main transport robot **17** receives the single batch of substrates **W** from the attitude changing robot **16**. The main transport robot **17** transfers the single batch of substrates **W** received from the attitude changing robot **16** to the first auxiliary transport robot **18A** or the second auxiliary transport robot **18B**, and receives the single batch of substrates **W** supported by the first auxiliary transport robot **18A** or the second auxiliary transport robot **18B**.

(41) The treatment units **2** further include a drying unit **10** which dries the substrates **W**, and a

cleaning unit **11** which cleans the main transport robot **17**. The main transport robot **17** is further capable of transporting the single batch of substrates **W** to the drying unit **10**.

(42) The first auxiliary transport robot **18A** transports the single batch of substrates **W** received from the main transport robot **17** among the sulfuric acid treatment unit **5**, the ozone gas treatment unit **6** and the first rinsing unit **7**. Similarly, the second auxiliary transport robot **18B** transports the single batch of substrates **W** received from the main transport robot **17** between the chemical liquid treatment unit **8** and the second rinsing unit **9**.

(43) FIG. **2** is a schematic elevational view for describing the structures of major portions of the substrate processing apparatus **1** by way of example.

(44) The sulfuric acid treatment unit **5** includes a sulfuric acid vessel **20** which retains the sulfuric acid-containing liquid in which the single batch of substrates **W** is immersed, and a sulfuric acid treatment chamber **21** which accommodates the sulfuric acid vessel **20**. The sulfuric acid vessel **20** is open upward, and the sulfuric acid treatment chamber **21** has an openable/closable upper end portion **21a**.

(45) The first rinsing unit **7** includes a rinse liquid vessel **30** which retains the rinse liquid in which the single batch of substrates **W** is immersed, and a rinsing chamber **31** which accommodates the rinse liquid vessel **30**. The rinse liquid vessel **30** is open upward, and the rinsing chamber **31** has an openable/closable upper end portion **31a**.

(46) The ozone gas treatment unit **6** includes a gas treatment chamber **40** in which the single batch of substrates **W** is exposed to the ozone-containing gas. The gas treatment chamber **40** has a treatment space **40a** in which the single batch of substrates **W** can be accommodated. In the gas treatment chamber **40**, the single batch of substrates **W** accommodated in the treatment space **40a** is exposed to the ozone-containing gas.

(47) The ozone gas treatment unit **6** includes an ozone supply flow path **41** which supplies the ozone-containing gas to the gas treatment chamber **40**, an ozone gas valve **42** which opens and closes the ozone supply flow path **41**, a displacement gas supply flow path **43** which supplies the displacement gas to the gas treatment chamber **40**, a displacement gas valve **44** which opens and closes the displacement gas supply flow path **43**, an exhaust flow path **45** through which the internal atmosphere of the gas treatment chamber **40** is expelled, and an exhaust valve **46** which opens and closes the exhaust flow path **45**.

(48) Though not shown, the ozone gas valve **42** includes a valve body having a valve seat provided therein, a valve member which opens and closes the valve seat, and an actuator which moves the valve member between an open position and a closed position. The other valves each have the same structure.

(49) The ozone supply flow path **41** is defined, for example, by a pipe. The displacement gas supply flow path **43** is defined, for example, by a pipe. The exhaust flow path **45** is defined, for example, by a pipe.

(50) The ozone gas treatment unit **6** includes an ozone flow path heater **47** which heats the ozone-containing gas in the ozone supply flow path **41**. The ozone gas treatment unit **6** may include an ozone treatment chamber heater (not shown) which heats the gas treatment chamber **40**. The ozone flow path heater **47** and the ozone treatment chamber heater are exemplary ozone heating units which heat the ozone-containing gas in the ozone supply flow path **41** and/or the ozone-containing gas in the gas treatment chamber **40**.

(51) The gas treatment chamber **40** has walls **48** defining the treatment space **40a**. The walls **48** include an openable/closable upper wall **48u**, a bottom wall **48b**, and a side wall **48s** connecting the upper wall **48u** and the bottom wall **48b**. The upper wall **48u** is openable and closable. The side wall **48s** is polygonal or arcuate as seen in plan.

(52) The gas treatment chamber **40** has a plurality of supply orifices **49A** which open in the side wall **48s** for supplying the ozone-containing gas from the ozone supply flow path **41** into the treatment space **40a**, and a plurality of exhaust orifices **49B** which open in the side wall **48s** for

expelling the internal atmosphere of the treatment space **40a**. On the side wall **48s**, the supply orifices **49A** are opposed to the exhaust orifices **49B**. The supply orifices **49A** are also capable of supplying the displacement gas from the displacement gas supply flow path **43** into the treatment space **40a**. The supply orifices **49A** are provided in the same number as the exhaust orifices **49B**. The supply orifices **49A** and the exhaust orifices **49B** are, for example, round holes (see FIG. 7 to be described later).

(53) The first auxiliary transport robot **18A** transports the single batch of substrates **W** while holding the single batch of substrates **W** in the vertical attitude. The first auxiliary transport robot **18A** is capable of transporting the single batch of substrates **W** to the sulfuric acid vessel **20** of the sulfuric acid treatment unit **5** and immersing the single batch of substrates **W** held in the vertical attitude in the sulfuric acid-containing liquid within the sulfuric acid vessel **20**. The first auxiliary transport robot **18A** is further capable of transporting the single batch of substrates **W** into the gas treatment chamber **40** of the ozone gas treatment unit **6** and placing the single batch of substrates **W** held in the vertical attitude in the treatment space **40a** of the gas treatment chamber **40**. The first auxiliary transport robot **18A** is further capable of transporting the single batch of substrates **W** into the rinse liquid vessel **30** of the first rinsing unit **7** and immersing the single batch of substrates **W** held in the vertical attitude in the rinse liquid within the rinse liquid vessel **30**.

Structure of First Auxiliary Transport Robot

(54) FIG. 3 is a sectional view for describing the structure of the first auxiliary transport robot **18A** provided in the substrate processing apparatus **1** by way of example.

(55) The first auxiliary transport robot **18A** includes a lifter **50** which supports the single batch of substrates **W**, a lifting mechanism **51** which moves up and down the lifter **50**, and a sliding mechanism **52** which horizontally moves (slides) the lifter **50**.

(56) The lifting mechanism **51** includes a lifting actuator (not shown) which generates a driving force for moving up and down the lifter **50**. The lifting actuator is, for example, an electric motor or an air cylinder. The lifting mechanism **51** may include a power transmission mechanism (not shown) which transmits the driving force of the lifting actuator to the lifter **50**. The power transmission mechanism includes at least one of a ball screw mechanism and a rack-and-pinion mechanism, for example.

(57) The sliding mechanism **52** includes a sliding actuator (not shown) which generates a driving force for horizontally moving the lifter **50**. The sliding actuator is, for example, an electric motor or an air cylinder. The sliding mechanism **52** may include a power transmission mechanism (not shown) which transmits the driving force of the sliding actuator to the lifter **50**.

(58) The lifter **50** is not particularly limited but, for example, has the following structure. The lifter **50** includes a plurality of support portions **53** (e.g., three support portions **53**) (also see FIG. 2) which support the single batch of substrates **W** from below, and a connection portion **54** which connects the support portions **53** to each other at one-side ends thereof.

(59) The support portions **53** each have support grooves **55** of the same number as that of the substrates **W** to be supported. In FIG. 3, only the support grooves **55** of a middle one of the three support portions **53** are shown. In each of the support portions **53**, the support grooves **55** are provided equidistantly in an arrangement direction (horizontal direction) in which the substrates **W** in the single batch are arranged. Peripheral edge portions of the substrates **W** are respectively held in the support grooves **55** located at the corresponding positions with respect to the arrangement direction. Therefore, the lifter **50** is capable of moving up and down the single batch of substrates **W** while maintaining the single batch of substrates **W** in the vertical attitude.

(60) Referring to FIG. 2, the lifter **50** of the first auxiliary transport robot **18A** is horizontally movable above the gas treatment chamber **40**, the sulfuric acid treatment chamber **21**, and the rinsing chamber **31**. The lifter **50** of the first auxiliary transport robot **18A** can be horizontally moved among a first upper position just above the sulfuric acid treatment chamber **21**, a second upper position just above the gas treatment chamber **40**, and a third upper position just above the

rinsing chamber **31** by the sliding mechanism **52**.

(61) The lifter **50** of the first auxiliary transport robot **18A** can be moved up and down between the first upper position and a sulfuric acid treatment position where the single batch of substrates **W** is immersed in the sulfuric acid-containing liquid within the sulfuric acid vessel **20** by the lifting mechanism **51**. The lifter **50** of the first auxiliary transport robot **18A** can be moved up and down between the second upper position and a gas treatment position where the single batch of substrates **W** is placed in the treatment space **40a** by the lifting mechanism **51**. The lifter **50** of the first auxiliary transport robot **18A** can be moved up and down between the third upper position and a rinsing position where the single batch of substrates **W** is immersed in the rinse liquid within the rinse liquid vessel **30** by the lifting mechanism **51**.

(62) The sulfuric acid treatment position is such that the upper edge portions of the substrates **W** supported in the vertical attitude are located below the liquid surface of the sulfuric acid-containing liquid in the sulfuric acid vessel **20**. The rinsing position is such that the upper edge portions of the substrates **W** supported in the vertical attitude are located below the liquid surface of the rinse liquid in the rinse liquid vessel **30**.

Electrical Configuration of Substrate Processing Apparatus

(63) FIG. **4** is a block diagram for describing the electrical configuration of the substrate processing apparatus **1** by way of example.

(64) The controller **4** includes a microcomputer, and controls control objects provided in the substrate processing apparatus **1** according to a predetermined program. More specifically, the controller **4** includes a processor (CPU) **4A** and a memory **4B** which stores the program. The controller **4** is configured so that the processor **4A** executes the program to perform various control operations for a substrate treatment.

(65) Particularly, the controller **4** controls the operations of the carrier transport device **15**, the attitude changing robot **16**, the main transport robot **17**, the auxiliary transport robots **18**, the treatment units **2**, and the like. The controller **4** further controls the valves and the heaters provided in the treatment units **2**.

Exemplary Substrate Treatment

(66) FIG. **5** is a flow chart for describing an example of the substrate treatment to be performed by the substrate processing apparatus **1**. FIGS. **6A** to **6C** are schematic diagrams for describing how the substrate processing apparatus **1** performs the substrate treatment.

(67) In the substrate treatment, the substrate processing apparatus **1** performs, for example, a sulfuric acid immersing step (Step **S1**), an ozone exposing step (Step **S2**), a rinsing step (Step **S3**) and a drying step (Step **S4**) as shown in FIG. **5**. The substrate treatment will hereinafter be described in detail mainly with reference to FIGS. **1**, **2** and **5**. As required, reference will be made to FIGS. **6A** to **6C**.

(68) The main transport robot **17** receives a single batch of substrates **W** from the attitude changing robot **16**. The main transport robot **17** transfers the single batch of substrates **W** received from the attitude changing robot **16** to the first auxiliary transport robot **18A**. The single batch of substrates **W** is supported by the lifter **50** of the first auxiliary transport robot **18A**.

(69) After the first auxiliary transport robot **18A** receives the single batch of substrates **W** from the main transport robot **17**, the lifter **50** is moved to the first upper position (indicated by a two-dot-and-dash line in FIG. **6A**). The lifter **50** may receive the single batch of substrates **W** from the main transport robot **17** at the first upper position.

(70) The lifter **50** is moved down from the first upper position (indicated by the two-dot-and-dash line in FIG. **6A**) toward the sulfuric acid treatment position (indicated by a solid line in FIG. **6A**) while supporting the single batch of substrates **W** in the vertical attitude. Thus, as shown in FIG. **6A**, the single batch of substrates **W** is immersed in the sulfuric acid-containing liquid within the sulfuric acid vessel **20** while being held in the vertical attitude (sulfuric acid immersing step: Step **S1**).

(71) Thereafter, the lifter **50** is moved up toward the first upper position, whereby the single batch of substrates **W** is taken out from the sulfuric acid-containing liquid in the sulfuric acid vessel **20**. The lifter **50** is moved to the second upper position (indicated by a two-dot-and-dash line in FIG. **6B**) through the first upper position. Then, the lifter **50** is moved down from the second upper position to the gas treatment position (indicated by a solid line in FIG. **6B**). In this manner, a first transporting step (transporting step) is performed to take out the single batch of substrates **W** from the sulfuric acid vessel **20** and then transport the single batch of substrates **W** to the gas treatment chamber **40**.

(72) With the lifter **50** located at the gas treatment position, the ozone gas valve **42** and the exhaust valve **46** are opened. Thus, the internal atmosphere of the treatment space **40a** is expelled from the gas treatment chamber **40**, and the ozone-containing gas is supplied into the treatment space **40a**. By thus supplying the ozone-containing gas into the treatment space **40a**, the single batch of substrates **W** to which the sulfuric acid-containing liquid adheres is exposed to the ozone-containing gas (ozone exposing step: Step **S2** (vertical exposing step)).

(73) When the substrates **W** to which the sulfuric acid-containing liquid adheres are exposed to the ozone-containing gas, the ozone in the ozone-containing gas is dissolved in the adhering sulfuric acid-containing liquid, whereby peroxodisulfuric acid is generated in the adhering sulfuric acid-containing liquid. The peroxodisulfuric acid makes it possible to dissolve organic films exposed from the substrates **W** in the sulfuric acid-containing liquid. Parts of the organic films are not completely dissolved in the sulfuric acid-containing liquid, but are often separated from upper surfaces of the substrates **W**.

(74) By supplying the ozone-containing gas into the treatment space **40a**, the internal atmosphere of the treatment space **40a** is preferably replaced with the ozone-containing gas, whereby the treatment space **40a** is filled with the ozone-containing gas (ozone-containing gas filling step). With the treatment space **40a** filled with the ozone-containing gas, the peroxodisulfuric acid can be speedily and sufficiently generated in the sulfuric acid-containing liquid.

(75) The temperature of the ozone-containing gas is preferably, for example, in a range of not lower than 50° C. and not higher than 270° C. The temperature of the ozone-containing gas is preferably in a range of not lower than 50° C. and not higher than 270° C., more preferably in a range of not lower than 80° C. and not higher than 170° C. This enhances the activity of the peroxodisulfuric acid, making it possible to speedily remove the organic films.

(76) In the gas treatment chamber **40**, as shown in FIG. **7**, the supply orifices **49A** are arranged in a plurality of supply orifice rows **49AL** juxtaposed in a first arrangement direction **D1** (horizontally). More specifically, the supply orifice rows **49AL** each include a plurality of supply orifices **49A** aligned in a predetermined row direction (vertically in this example). The first arrangement direction **D1** intersects the row direction (orthogonally in this example). The substrates **W** in the single batch supported by the lifter **50** are arranged horizontally. The arrangement pitch **P1** of the substrates **W** in the single batch is equal to the arrangement pitch **P2** of the supply orifice rows **49AL**. When the lifter **50** supports the single batch of substrates **W** in the vertical attitude and, in this state, is located at the gas treatment position, the substrates **W** are located between respective adjacent pairs of the supply orifice rows **49AL** as seen in a horizontal direction parallel to the major surfaces of the substrates **W**.

(77) In FIG. **7**, the reference character “**49A**” for the supply orifices and the reference character “**49B**” for the exhaust orifices are both shown for convenience of description. The exhaust orifices **49B** are provided in the same arrangement as the supply orifices **49A**. In the gas treatment chamber **40**, the exhaust orifices **49B** are arranged in a plurality of exhaust orifice rows **49BL** juxtaposed at the same arrangement pitch **P2** as the supply orifice rows **49AL** in the first arrangement direction **D1** (horizontally). The exhaust orifice rows **49BL** each include a plurality of exhaust orifices **49B** aligned in a predetermined row direction (vertically in this embodiment). The first arrangement direction **D1** intersects the row direction (orthogonally in this example). When the lifter **50**

supports the single batch of substrates W in the vertical attitude and, in this state, is located at the gas treatment position, the substrates W are located between respective adjacent pairs of the exhaust orifice rows **49BL** as seen in a horizontal direction parallel to the major surfaces of the substrates W.

(78) Thereafter, the lifter **50** is moved up toward the second upper position, whereby the single batch of substrates W is taken out from the gas treatment chamber **40**. The lifter **50** is moved to the third upper position (indicated by a two-dot-and-dash line in FIG. **6C**) through the second upper position. Then, the lifter **50** is moved down from the third upper position toward the rinsing position (indicated by a solid line in FIG. **6C**). Thus, as shown in FIG. **6C**, the single batch of substrates W is immersed in the rinse liquid within the rinse liquid vessel **30** (rinsing step: Step **S3**). In this manner, a second transporting step is performed to take out the single batch of substrates W from the gas treatment chamber **40** and then transport the single batch of substrates W into the rinse liquid vessel **30**.

(79) By thus immersing the single batch of substrates W in the rinse liquid within the rinse liquid vessel **30**, the single batch of substrates W is rinsed. Specifically, the sulfuric acid-containing liquid in which the organic films are dissolved and the organic films separated from the substrates W are removed from the substrates W.

(80) After the single batch of substrates W is taken out from the gas treatment chamber **40**, the ozone gas valve **42** is closed, and the displacement gas valve **44** is opened. Thus, the displacement gas is supplied into the treatment space **40a** of the gas treatment chamber **40**, whereby the internal atmosphere of the treatment space **40a** is replaced with the displacement gas. In this manner, the ozone-containing gas is expelled from the treatment space **40a** (ozone expelling step).

(81) Thereafter, the lifter **50** is moved up toward the third upper position. Thus, the single batch of substrates W is taken out from the rinse liquid in the rinse liquid vessel **30**. With the lifter **50** located at the third upper position, the first auxiliary transport robot **18A** transfers the single batch of substrates W to the main transport robot **17**. The main transport robot **17** transports the single batch of substrates W received from the first auxiliary transport robot **18A** to the drying unit **10**. (82) In the drying unit **10**, the single batch of substrates W is dried by a reduced pressure drying method or the like (drying step: Step **S4**). Thereafter, the main transport robot **17** transfers the single batch of substrates W to the attitude changing robot **16**. The attitude changing robot **16** changes the attitude of the single batch of substrates W received from the main transport robot **17** from the vertical attitude to the horizontal attitude, and then places the substrates W of the single batch in a plurality of carriers C held in the carrier transport device **15**. This operation sequence is repeated, whereby a plurality of substrates W transported into the substrate processing apparatus **1** are treated.

(83) According to the first embodiment, the single batch of substrates W can be immersed in the sulfuric acid-containing liquid while being held in the vertical attitude. Therefore, the substrates W can be generally simultaneously immersed in the sulfuric acid-containing liquid. The single batch of substrates W immersed in the sulfuric acid-containing liquid at a time is exposed to the ozone-containing gas in the ozone gas treatment unit **6**. Thus, the ozone in the ozone-containing gas is dissolved in the sulfuric acid-containing liquid adhering to the substrates W in the single batch taken out from the sulfuric acid-containing liquid, whereby the peroxodisulfuric acid can be generated in the adhering sulfuric acid-containing liquid. As a result, the organic films can be speedily and sufficiently removed from the major surfaces of the substrates W in the single batch.

(84) According to the first embodiment, the single batch of substrates W taken out from the sulfuric acid vessel **20** is placed in the treatment space **40a** of the gas treatment chamber **40**. Thus, the substrates W in the single batch can be generally simultaneously exposed to the ozone-containing gas. Therefore, the organic films can be more speedily and sufficiently removed from the major surfaces of the substrates W in the single batch.

(85) According to the first embodiment, the ozone-containing gas is supplied from the supply

orifices **49A** into the treatment space **40a**, and is expelled from the treatment space **40a** through the exhaust orifices **49B**, whereby the single batch of substrates **W** can be exposed to the ozone-containing gas. Therefore, even if ozone in the atmosphere in contact with the sulfuric acid-containing liquid on the substrates **W** is dissolved in the sulfuric acid-containing liquid to be thereby consumed, ozone is supplied to the atmosphere in contact with the sulfuric acid-containing liquid adhering to the substrates **W** by supplying the ozone-containing gas into the treatment space **40a**. Therefore, the ozone concentration of the atmosphere in contact with the sulfuric acid-containing liquid on the substrates **W** can be maintained at a sufficiently high level. This makes it possible to generate the peroxodisulfuric acid in the sulfuric acid-containing liquid on the substrates **W**.

(86) In the gas treatment chamber **40**, the supply orifice rows **49AL** are juxtaposed in the first arrangement direction **D1**. The substrates **W** in the single batch are supported by the lifter **50** so as to be arranged in the first arrangement direction **D1**. The single batch of substrates **W** is placed in the treatment space **40a** so that the substrates **W** are located between respective adjacent pairs of the supply orifice rows **49AL**. Therefore, the ozone-containing gas from the supply orifice rows **49AL** can be supplied between respective adjacent pairs of the substrates **W**. Thus, the ozone can be sufficiently supplied into the atmosphere in contact with the sulfuric acid-containing liquid on the substrates **W**, and sufficiently dissolved in the sulfuric acid-containing liquid on the substrates **W**. As a result, it is possible to suppress the uneven removal of the organic films from the substrates **W**.

(87) Before the sulfuric acid immersing step (Step **S1**), the single batch of substrates **W** may be loaded into the gas treatment chamber **40** and exposed to the ozone-containing gas to be thereby hydrophilized. That is, as shown in FIG. **8**, the substrate treatment may further include a hydrophilizing step (Step **S5**) to be performed before the sulfuric acid immersing step (Step **S1**). In the substrate treatment, the single batch of substrates **W** is exposed to the ozone-containing gas before and after being immersed in the sulfuric acid-containing liquid. By performing the substrate treatment as shown in FIG. **8**, the single batch of substrates **W** is hydrophilized before being immersed in the sulfuric acid-containing liquid.

(88) This improves the wettability of the substrates **W**, so that the sulfuric acid-containing liquid can easily adhere to the substrates **W**. Therefore, the sulfuric acid-containing liquid can be thinly spread over the entire major surfaces of the substrates **W**. In the ozone exposing step, the ozone can easily reach the major surfaces of the substrates **W**, making it possible to speedily and sufficiently remove the organic films from the major surfaces of the substrates **W**.

First Modification of First Embodiment

(89) Next, a first modification of the substrate processing apparatus **1** will be described.

(90) FIG. **9** is an elevational view of major portions of the substrate processing apparatus **1** according to the first modification of the first embodiment.

(91) In the first modification, the sulfuric acid treatment chamber **21** is not provided, but the sulfuric acid vessel **20** is disposed in the gas treatment chamber **40**. In the gas treatment chamber **40**, the treatment space **40a** is located just above the sulfuric acid vessel **20**.

(92) The first auxiliary transport robot **18A** is movable up and down while supporting the substrates **W** so as to transport the substrates **W** between the treatment space **40a** and the sulfuric acid vessel **20**. The sulfuric acid treatment unit **5** does not have the sulfuric acid treatment chamber **21**, but includes a cover member **22** which covers and uncovers the sulfuric acid vessel **20** to separate the inside of the sulfuric acid vessel **20** and the treatment space **40a** from each other. In the first modification, the treatment space **40a** is defined by the side wall **48s**, the upper wall **48u** and the cover member **22**. The cover member **22** is driven by a cover driving mechanism such as a motor (not shown) to cover and uncover the sulfuric acid vessel **20**.

(93) The lifter **50** of the first auxiliary transport robot **18A** is horizontally movable above the gas treatment chamber **40** and the rinsing chamber **31**. The lifter **50** can be horizontally moved between the second upper position just above the gas treatment chamber **40** and the third upper position just

above the rinsing chamber 31 by the sliding mechanism 52. The lifter 50 can be moved up and down among the sulfuric acid treatment position, the gas treatment position and the second upper position by the lifting mechanism 51. The lifter 50 can be moved up and down between the rinsing position and the third upper position by the lifting mechanism 51.

(94) FIGS. 10A to 10C are schematic diagrams for describing how the substrate processing apparatus 1 of the first modification performs the substrate treatment.

(95) The substrate processing apparatus 1 of the first modification is capable of performing the substrate treatment shown in FIG. 5, but performs the substrate treatment by a different procedure from that shown in FIGS. 6A to 6C. Differences will hereinafter be mainly described.

(96) In the substrate treatment according to the first modification, the lifter 50 receives the single batch of substrates W from the main transport robot 17, and then is moved to the second upper position (indicated by a two-dot-and-dash line in FIG. 10A). The lifter 50 is moved down toward the sulfuric acid treatment position (indicated by a solid line in FIG. 10A) while supporting the single batch of substrates W. Thus, as shown in FIG. 10A, the single batch of substrates W is immersed in the sulfuric acid-containing liquid within the sulfuric acid vessel 20 (sulfuric acid immersing step: Step S1 in FIG. 5). The cover member 22 is opened before the lifter 50 is moved into the sulfuric acid vessel 20.

(97) Thereafter, the lifter 50 is moved upward, whereby the single batch of substrates W is taken out from the sulfuric acid-containing liquid in the sulfuric acid vessel 20. The lifter 50 is moved up from the sulfuric acid treatment position (indicated by a two-dot-and-dash line in FIG. 10B) to the gas treatment position (indicated by a solid line in FIG. 10B). Thus, the single batch of substrates W is lifted from the sulfuric acid vessel 20 to be thereby placed in the treatment space 40a (first transporting step). After the lifter 50 is retracted from the sulfuric acid vessel 20, the cover member 22 is closed.

(98) With the lifter 50 located at the gas treatment position, the ozone gas valve 42 and the exhaust valve 46 are opened. Thus, the internal atmosphere of the treatment space 40a is expelled from the gas treatment chamber 40, and the ozone-containing gas is supplied into the treatment space 40a. By thus supplying the ozone-containing gas into the treatment space 40a, therefore, the single batch of substrates W to which the sulfuric acid-containing liquid adheres is exposed to the ozone-containing gas (ozone exposing step: Step S2 in FIG. 5).

(99) The substrates W to which the sulfuric acid-containing liquid adheres are thus exposed to the ozone-containing gas, whereby the ozone in the ozone-containing gas is dissolved in the sulfuric acid-containing liquid adhering to the substrates W. Thus, the peroxodisulfuric acid is generated in the sulfuric acid-containing liquid adhering to the substrates W in the single batch. The peroxodisulfuric acid makes it possible to dissolve the organic films exposed from the substrates W in the sulfuric acid-containing liquid. Parts of the organic films are not completely dissolved in the sulfuric acid-containing liquid, but are often separated from the upper surfaces of the substrates W.

(100) By supplying the ozone-containing gas into the treatment space 40a, the internal atmosphere of the treatment space 40a is preferably replaced with the ozone-containing gas, whereby the treatment space 40a is filled with the ozone-containing gas (ozone-containing gas filling step). In the first modification, when the lifter 50 is located at the gas treatment position, the substrates W are located between respective adjacent pairs of the supply orifice rows 49AL (see FIG. 7).

(101) Thereafter, the lifter 50 is moved up toward the second upper position, whereby the single batch of substrates W is taken out from the gas treatment chamber 40. The lifter 50 is moved to the third upper position (indicated by a two-dot-and-dash line in FIG. 10C) through the second upper position. Then, the lifter 50 is moved down toward the rinsing position (indicated by a solid line in FIG. 10C) from the third upper position. Thus, as shown in FIG. 10C, the single batch of substrates W is immersed in the rinse liquid within the rinse liquid vessel 30 (rinsing step: Step S3 in FIG. 5). In this manner, the second transporting step is performed to take out the single batch of substrates W from the gas treatment chamber 40 and then transport the single batch of substrates W to the

rinse liquid vessel **30**.

(102) By thus immersing the single batch of substrates **W** in the rinse liquid within the rinse liquid vessel **30**, the single batch of substrates **W** is rinsed. More specifically, the sulfuric acid-containing liquid in which the organic films are dissolved and the organic films separated from the substrates **W** are removed from the substrates **W**.

(103) After the single batch of substrates **W** is taken out from the gas treatment chamber **40**, the ozone gas valve **42** is closed and the displacement gas valve **44** is opened. Thus, the displacement gas is supplied into the treatment space **40a** of the gas treatment chamber **40**, whereby the internal atmosphere of the treatment space **40a** is replaced with the displacement gas. Thus, the ozone-containing gas is expelled from the treatment space **40a**.

(104) Thereafter, the drying step (Step **S4**) is performed in the same manner as in the substrate treatment procedure shown in FIGS. **6A** to **6C**.

(105) According to the first modification of the first embodiment, the single batch of substrates **W** is lifted from the sulfuric acid vessel **20** by the unidirectional movement to be thereby moved from the sulfuric acid vessel **20** into the treatment space **40a**. Therefore, the single batch of substrates **W** can be speedily exposed to the ozone-containing gas after the sulfuric acid-containing liquid is applied to the single batch of substrates **W**. Thus, the organic films can be speedily removed from the major surfaces of the substrates **W** in the single batch.

(106) The inside of the sulfuric acid vessel **20** and the treatment space **40a** are separated from each other by the cover member **22** which covers and uncovers the sulfuric acid vessel **20**. Thus, the ozone-containing gas is substantially prevented from being dissolved in the sulfuric acid-containing liquid retained in the sulfuric acid vessel **20**. In the substrate treatment of the next batch of substrates **W**, therefore, the removal of the organic films from the substrates **W** can be suppressed before the start of the supply of the ozone-containing gas into the treatment space **40a**. This suppresses variations in peroxodisulfuric acid treatment period from batch to batch.

Second Modification of First Embodiment

(107) Next, a second modification of the substrate processing apparatus **1** will be described.

(108) FIG. **11** is an elevational view of major portions of the substrate processing apparatus **1** of the second modification of the first embodiment.

(109) In the second modification, the substrate processing apparatus **1** further includes a hydrophilizing unit **12** which treats the single batch of substrates **W** with a hydrophilizing liquid. The hydrophilizing liquid is, for example, ozone water.

(110) The hydrophilizing unit **12** includes a hydrophilizing liquid vessel **60** which retains the hydrophilizing liquid in which the single batch of substrates **W** is immersed, and a hydrophilizing chamber **61** which accommodates the hydrophilizing liquid vessel **60**. The hydrophilizing liquid vessel **60** is open upward, and the hydrophilizing chamber **61** has an openable/closable upper end portion **61a**.

(111) The lifter **50** of the first auxiliary transport robot **18A** is horizontally movable above the gas treatment chamber **40**, the sulfuric acid treatment chamber **21**, the rinsing chamber **31** and the hydrophilizing chamber **61**. The lifter **50** can be moved among the first upper position, the second upper position, the third upper position, and a fourth upper position just above the hydrophilizing chamber **61** by the sliding mechanism **52**.

(112) The substrate processing apparatus **1** of the second modification is capable of performing the substrate treatment shown in FIG. **5**. The substrate processing apparatus **1** of the second modification is also capable of performing the substrate treatment shown in FIG. **8**.

(113) Where the substrate treatment shown in FIG. **8** is performed, the first auxiliary transport robot **18A** receives the single batch of substrates **W** from the main transport robot **17**, and then the lifter **50** is moved to the fourth upper position. The lifter **50** is moved down toward a hydrophilizing position while supporting the single batch of substrates **W**. Thus, the single batch of substrates **W** is immersed in the hydrophilizing liquid within the hydrophilizing liquid vessel **60**

(hydrophilizing step: Step S5).

(114) Thereafter, the single batch of substrates W is taken out from the hydrophilizing liquid vessel **60**, and a process sequence from the sulfuric acid immersing step (Step S1) to the drying step (Step S4) is performed in the same manner as in the substrate treatment procedure shown in FIGS. 6A to 6C.

(115) According to the second modification of the first embodiment, the single batch of substrates W can be hydrophilized before being immersed in the sulfuric acid-containing liquid. This improves the wettability of the substrates W, so that the sulfuric acid-containing liquid can easily adhere to the substrates W. Therefore, the sulfuric acid-containing liquid can be thinly spread over the entire major surfaces of the substrates W. In the ozone exposing step, therefore, the ozone can easily reach the major surfaces of the substrates W, making it possible to speedily and sufficiently remove the organic films from the substrates W.

Structure of Substrate Processing Apparatus According to Second Embodiment

(116) Next, a substrate processing apparatus **1A** according to a second embodiment will be described by way of example. FIGS. 12A and 12B are schematic diagrams showing the structure of a first auxiliary transport robot **18A** provided in the substrate processing apparatus **1A** of the second embodiment by way of example. In FIGS. 12A and 12B, components equivalent to those shown in FIGS. 1 to 11 will be denoted by the same reference characters as in FIGS. 1 to 11, and duplicate description will be omitted. The same applies to FIGS. 13A to 15.

(117) The substrate processing apparatus **1A** of the second embodiment mainly differs from the substrate processing apparatus **1** of the first embodiment in that the lifter **50** of the first auxiliary transport robot **18A** is transformable so as to change the attitude of the single batch of substrates W between the vertical attitude and the horizontal attitude.

(118) According to the second embodiment, the lifter **50** of the first auxiliary transport robot **18A** includes a holding portion **56** which supports the single batch of substrates W by holding the peripheries of the substrates W, a rotary support shaft **57** which turns the holding portion **56**, and a connection portion **58** which is connected to the holding portion **56** via the rotary support shaft **57** to transmit the powers of the lifting mechanism **51** and the sliding mechanism **52**.

(119) The first auxiliary transport robot **18A** includes an attitude changing mechanism **70** which changes the attitude of the single batch of substrates W between the vertical attitude and the horizontal attitude. The attitude changing mechanism **70** turns the holding portion **56** about the horizontal rotary support shaft **57** to transform the lifter **50**. The rotary support shaft **57** and the holding portion **56** constitute an attitude converting structure which converts the attitude of the single batch of substrates W held thereby between the vertical attitude and the horizontal attitude. The attitude converting structure is driven by the attitude changing mechanism **70**. FIG. 12A shows a first support state in which the lifter **50** supports the single batch of substrates W in the vertical attitude, and FIG. 12B shows a second support state in which the lifter **50** supports the single batch of substrates W in the horizontal attitude.

(120) The attitude changing mechanism **70** includes, for example, an actuator such as an electric motor which turns the rotary support shaft **57** about its center axis **A1**.

Exemplary Substrate Treatment According to Second Embodiment

(121) FIGS. 13A to 13C are schematic diagrams for describing how the substrate processing apparatus **1A** of the second embodiment performs the substrate treatment.

(122) The substrate processing apparatus **1A** of the second embodiment is capable of performing the substrate treatment shown in FIG. 5, but performs the substrate treatment by a different procedure from that shown in FIGS. 6A to 6C. Differences will hereinafter be mainly described.

(123) After the first auxiliary transport robot **18A** receives the single batch of substrates W from the main transport robot **17**, the lifter **50** is moved to the first upper position (indicated by a two-dot-and-dash line in FIG. 13A). The first auxiliary transport robot **18A** may receive the single batch of substrates W from the main transport robot **17** when the lifter **50** is located at the first upper

position.

(124) In the first support state, the lifter **50** is moved down from the first upper position toward the sulfuric acid treatment position (indicated by a solid line in FIG. **13A**). Thus, as shown in FIG. **13A**, the single batch of substrates **W** is immersed in the sulfuric acid-containing liquid within the sulfuric acid vessel **20** while being held in the vertical attitude (sulfuric acid immersing step: Step **S1** shown in FIG. **5**).

(125) Thereafter, the lifter **50** is moved up toward the first upper position, whereby the single batch of substrates **W** is taken out from the sulfuric acid-containing liquid in the sulfuric acid vessel **20**. The lifter **50** is moved to the second upper position (indicated by a two-dot-and-dash line in FIG. **13B**) through the first upper position. Then, the attitude changing mechanism **70** changes the state of the lifter **50** from the first support state to the second support state. Thus, the attitude of the single batch of substrates **W** is changed from the vertical attitude to the horizontal attitude (first attitude changing step).

(126) Then, the lifter **50** is moved down from the second upper position toward the gas treatment position (indicated by a solid line in FIG. **13B**) to be located at the gas treatment position. With the lifter **50** located at the gas treatment position, the ozone gas valve **42** and the exhaust valve **46** are opened. Thus, the internal atmosphere of the treatment space **40a** is expelled from the gas treatment chamber **40**, and the ozone-containing gas is supplied into the treatment space **40a**. By thus supplying the ozone-containing gas into the treatment space **40a**, the single batch of substrates **W** to which the sulfuric acid-containing liquid adheres is exposed to the ozone-containing gas while being held in the horizontal attitude (ozone exposing step: Step **S2** shown in FIG. **5** (horizontal exposing step)).

(127) The first attitude changing step may be performed before the supply of the ozone-containing gas into the treatment space **40a** is started after the lifter **50** is located at the gas treatment position.

(128) By supplying the ozone-containing gas into the treatment space **40a**, the internal atmosphere of the treatment space **40a** is preferably replaced with the ozone-containing gas, whereby the treatment space **40a** is filled with the ozone-containing gas (ozone-containing gas filling step). With the treatment space **40a** filled with the ozone-containing gas, the peroxodisulfuric acid can be speedily and sufficiently generated in the sulfuric acid-containing liquid.

(129) In the gas treatment chamber **40**, as shown in FIG. **14**, the supply orifices **49A** are arranged in a plurality of supply orifice rows **49AL** juxtaposed in a second arrangement direction **D2** (vertically). The supply orifice rows **49AL** each include a plurality of supply orifices **49A** aligned in a predetermined row direction (horizontally in this example), and the second arrangement direction **D2** intersects the row direction (orthogonally in this example). The substrates **W** in the single batch supported by the lifter **50** are arranged vertically. When the lifter **50** supports the single batch of substrates **W** in the horizontal attitude and, in this state, is located at the gas treatment position, the substrates **W** are located between respective adjacent pairs of the supply orifice rows **49AL** as seen in a horizontal direction parallel to the major surfaces of the substrates **W**.

(130) In FIG. **14**, the reference character “**49A**” for the supply orifices and the reference character “**49B**” for the exhaust orifices are both shown for convenience of description. The exhaust orifices **49B** are provided in the same arrangement as the supply orifices **49A**. In the gas treatment chamber **40**, the exhaust orifices **49B** are arranged in a plurality of exhaust orifice rows **49BL** juxtaposed in the second arrangement direction **D2** (vertically). The exhaust orifice rows **49BL** each include a plurality of exhaust orifices **49B** aligned in the predetermined row direction (horizontally in this embodiment). The second arrangement direction **D2** intersects the row direction (orthogonally in this example). When the lifter **50** supports the single batch of substrates **W** in the horizontal attitude and, in this state, is located at the gas treatment position, the substrates **W** are located between respective adjacent pairs of the exhaust orifice rows **49BL** as seen in a horizontal direction parallel to the major surfaces of the substrates **W**.

(131) Thereafter, the lifter **50** is moved up toward the second upper position, whereby the single

batch of substrates W is taken out from the gas treatment chamber **40**. The lifter **50** is moved to the third upper position (indicated by a two-dot-and-dash line in FIG. **13C**) through the second upper position. Then, the attitude changing mechanism **70** changes the state of the lifter **50** from the second support state to the first support state. Thus, the attitude of the single batch of substrates W is changed from the horizontal attitude to the vertical attitude (second attitude changing step).

(132) Then, the lifter **50** is moved down from the third upper position toward the rinsing position (indicated by a solid line in FIG. **13C**). Thus, as shown in FIG. **13C**, the single batch of substrates W is immersed in the rinse liquid within the rinse liquid vessel **30** while being held in the vertical attitude (rinsing step: Step S3). In this manner, the second transporting step is performed to take out the single batch of substrates W from the gas treatment chamber **40** and then transport the single batch of substrates W into the rinse liquid vessel **30**.

(133) By thus immersing the single batch of substrates W in the rinse liquid within the rinse liquid vessel **30**, the single batch of substrates W is rinsed. More specifically, the sulfuric acid-containing liquid in which the organic films are dissolved and the organic films separated from the substrates W are removed from the substrates W.

(134) After the single batch of substrates W is taken out from the gas treatment chamber **40**, the ozone gas valve **42** is closed, and the displacement gas valve **44** is opened. Thus, the displacement gas is supplied into the treatment space **40a** in the gas treatment chamber **40**, whereby the internal atmosphere of the treatment space **40a** is replaced with the displacement gas. In this manner, the ozone-containing gas is expelled from the treatment space **40a** (ozone expelling step).

(135) Thereafter, the first auxiliary transport robot **18A** transfers the single batch of substrates W to the main transport robot **17**. The main transport robot **17** transports the single batch of substrates W received from the first auxiliary transport robot **18A** to the drying unit **10**. Thereafter, the single batch of substrates W is dried, and the substrates W in the single batch are consequently placed in a plurality of carriers.

(136) According to the second embodiment, the single batch of substrates W can be immersed in the sulfuric acid-containing liquid while being held in the vertical attitude. Therefore, the substrates W in the single batch can be generally simultaneously immersed in the sulfuric acid-containing liquid. The single batch of substrates W taken out from the sulfuric acid vessel **20** is placed in the treatment space **40a**, whereby the substrates W in the single batch can be simultaneously exposed to the ozone-containing gas. Therefore, the organic films can be more speedily and sufficiently removed from the substrates W.

(137) Before the single batch of substrates W is exposed to the ozone-containing gas, the attitude of the single batch of substrates W is changed from the vertical attitude to the horizontal attitude. Therefore, the thickness variations of the sulfuric acid-containing liquid at different positions on each of the substrates W can be suppressed, which may otherwise occur when the sulfuric acid-containing liquid moves down along the substrates W by gravity. This suppresses the uneven removal of the organic film at different positions on the major surface of each of the substrates W.

(138) According to the second embodiment, the attitude changing mechanism **70** transforms the lifter **50**, whereby the attitude of the single batch of substrates W is changed between the vertical attitude and the horizontal attitude. More specifically, the lifter **50** includes the attitude converting structure which is capable of converting the attitude of the single batch of substrates W held thereby between the vertical attitude and the horizontal attitude, and the attitude converting structure is driven by the attitude changing mechanism **70**.

(139) Therefore, after the single batch of substrates W is immersed in the sulfuric acid-containing liquid within the sulfuric acid vessel **20** while being held in the vertical attitude, the attitude of the single batch of substrates W can be changed from the vertical attitude to the horizontal attitude by transforming the lifter **50** of the first auxiliary transport robot **18A** (transport robot). Then, the single batch of substrates W can be exposed to the ozone-containing gas in the gas treatment chamber **40** while being held in the horizontal attitude. Thus, with the use of the single robot (first

auxiliary transport robot **18A**), the attitude of the single batch of substrates **W** can be changed, and the single batch of substrates **W** can be transported from the sulfuric acid vessel **20** to the gas treatment chamber **40**. Since the transfer of the substrates **W** between robots can be obviated, the organic films can be speedily removed from the substrates **W**.

(140) According to the second embodiment, the ozone-containing gas is supplied into the treatment space **40a** through the supply orifices **49A** and expelled from the treatment space **40a** through the exhaust orifices **49B**, whereby the single batch of substrates **W** can be exposed to the ozone-containing gas. Therefore, even if ozone in the atmosphere in contact with the sulfuric acid-containing liquid on the substrates **W** is dissolved in the sulfuric acid-containing liquid to be thereby consumed, ozone is supplied to the atmosphere in contact with the sulfuric acid-containing liquid adhering to the substrates **W** by supplying the ozone-containing gas into the treatment space **40a**. Therefore, the ozone concentration of the atmosphere in contact with the sulfuric acid-containing liquid on the substrates **W** can be maintained at a sufficiently high level. This makes it possible to generate the peroxodisulfuric acid in the sulfuric acid-containing liquid on the substrates **W**.

(141) In the gas treatment chamber **40**, the supply orifice rows **49AL** are juxtaposed in the second arrangement direction **D2**. The substrates **W** in the single batch are supported by the lifter **50** so as to be arranged in the second arrangement direction **D2**. The single batch of substrates **W** is placed in the treatment space **40a** so that the substrates **W** are located between respective adjacent pairs of the supply orifice rows **49AL**. Therefore, the ozone-containing gas from the supply orifice rows **49AL** can be supplied between respective adjacent pairs of the substrates **W**. Therefore, the ozone can be sufficiently supplied into the atmosphere in contact with the sulfuric acid-containing liquid on the substrates **W**, and sufficiently dissolved in the sulfuric acid-containing liquid on the substrates **W**. As a result, it is possible to suppress the uneven removal of the organic films from the substrates **W**.

Substrate Processing Apparatus According to Modification of Second Embodiment

(142) FIG. **15** is a schematic diagram for describing a substrate processing apparatus **1A** according to a modification of the second embodiment.

(143) In the substrate processing apparatus **1A** of the modification of the second embodiment, the sulfuric acid treatment chamber **21** is not provided, but the sulfuric acid vessel **20** is provided in the gas treatment chamber **40** as in the substrate processing apparatus **1** of the first modification of the first embodiment (see FIG. **9**). In the gas treatment chamber **40**, the treatment space **40a** is located just above the sulfuric acid vessel **20**.

(144) The substrate processing apparatus **1A** of the modification of the second embodiment is capable of performing the substrate treatment in substantially the same manner as the substrate processing apparatus **1** of the modification of the first embodiment (see FIGS. **10A** to **10C**). That is, the single batch of substrates **W** held in the vertical attitude is immersed in the sulfuric acid-containing liquid within the sulfuric acid vessel **20**, and then lifted from the sulfuric acid vessel **20** to be thereby placed in the treatment space **40a** (first transporting step).

(145) However, the state of the lifter **50** is changed from the first support state to the second support state by the attitude changing mechanism **70** after the single batch of substrates **W** is taken out from the sulfuric acid vessel **20** before the single batch of substrates **W** is exposed to the ozone-containing gas. Thus, the attitude of the single batch of substrates **W** is changed from the vertical attitude to the horizontal attitude (first attitude changing step).

(146) The first attitude changing step may be performed after the single batch of substrates **W** is taken out from the sulfuric acid vessel **20** before the single batch of substrates **W** is placed in the treatment space **40a**. Alternatively, the first attitude changing step may be performed after the lifter **50** is placed at the gas treatment position before the supply of the ozone-containing gas into the treatment space **40a** is started.

(147) According to the modification of the second embodiment, the single batch of substrates **W** is

lifted from the sulfuric acid vessel **20** by the unidirectional movement to be thereby moved from the sulfuric acid vessel **20** into the treatment space **40a**. Therefore, the single batch of substrates **W** can be speedily exposed to the ozone-containing gas after the sulfuric acid-containing liquid is applied to the single batch of substrates **W**. Thus, the organic films can be speedily removed from the substrates **W**.

(148) The inside of the sulfuric acid vessel **20** and the treatment space **40a** are separated from each other by the cover member **22** which covers and uncovers the sulfuric acid vessel **20**. Thus, the ozone-containing gas is substantially prevented from being dissolved in the sulfuric acid-containing liquid retained in the sulfuric acid vessel **20**. In the substrate treatment of the next batch of substrates **W**, therefore, the removal of the organic films from the substrates **W** can be suppressed before the start of the supply of the ozone-containing gas into the treatment space **40a**. This suppresses variations in peroxodisulfuric acid treatment period from batch to batch.

Structure of Substrate Processing Apparatus According to Third Embodiment

(149) Next, the structure of a substrate processing apparatus **1B** according to a third embodiment will be described by way of example. FIG. **16** is an elevational view of major portions of the substrate processing apparatus **1B** of the third embodiment. In FIG. **16**, components equivalent to those shown in FIGS. **1** to **15** will be denoted by the same reference characters as in FIGS. **1** to **15**, and duplicate description will be omitted. The same applies to FIGS. **17A** to **22**.

(150) The substrate processing apparatus **1B** of the third embodiment mainly differs from the substrate processing apparatus **1** of the first embodiment in that a hand **80** of the main transport robot **17** is transformable so as to change the attitude of the single batch of substrates **W** between the vertical attitude and the horizontal attitude. Further, a plurality of lift transport robots **19** are provided for the respective treatment units **2** instead of the auxiliary transport robots **18**.

(151) Specifically, the lift transport robots **19** include a first lift transport robot **19A** which transports the single batch of substrates **W** between the main transport robot **17** and the sulfuric acid treatment unit **5**, a second lift transport robot **19B** which transports the single batch of substrates **W** between the main transport robot **17** and the ozone gas treatment unit **6**, and a third lift transport robot **19C** which transports the single batch of substrates **W** between the main transport robot **17** and the first rinsing unit **7**. The first lift transport robot **19A** is an example of the first transport robot, and the second lift transport robot **19B** is an example of the second transport robot.

(152) Though not shown, the lift transport robots **19** may include another lift transport robot which transports the single batch of substrates **W** between the main transport robot **17** and the chemical liquid treatment unit **8**, and further another lift transport robot which transports the single batch of substrates **W** between the main transport robot **17** and the second rinsing unit **9**.

(153) The lift transport robots **19** each have substantially the same structure as the first auxiliary transport robot **18A** shown, for example, in FIG. **3**. However, the sliding mechanism **52** (see FIG. **3**) is not provided in any of the lift transport robots **19**.

(154) Further, the lifter **50** of the second lift transport robot **19B** has a structure such as to support the single batch of substrates **W** in the horizontal attitude. The lifter **50** of the second lift transport robot **19B** is not particularly limited but, for example, has the following structure. The lifter **50** includes, for example, a plurality of periphery support portions **88** (e.g., periphery support portions **88** of the same number as that of the substrates **W** to be supported) which support the respective substrates **W** from below (also see FIG. **18A** and the like to be described later), and a connection portion **89** which connects the periphery support portions **88** to each other.

(155) The lifter **50** of the first lift transport robot **19A** will hereinafter be referred to as first lifter **50A**, and the lifter **50** of the second lift transport robot **19B** will hereinafter be referred to as second lifter **50B**. Further, the lifter **50** of the third lift transport robot **19C** will hereinafter be referred to as third lifter **50C**. The first lifter **50A** and the third lifter **50C** are each configured so as to support the single batch of substrates **W** in the vertical attitude.

(156) The first lifter **50A** can be moved up and down between the sulfuric acid treatment position and the first upper position by the lifting mechanism **51** of the first lift transport robot **19A**. The second lifter **50B** can be moved up and down between the gas treatment position and the second upper position by the lifting mechanism **51** of the second lift transport robot **19B**. The third lifter **50C** can be moved up and down between the rinsing position and the third upper position by the lifting mechanism **51** of the third lift transport robot **19C**.

Structure of Main Transport Robot According to Third Embodiment

(157) FIG. **17A** is a schematic diagram showing the structure of the main transport robot **17** according to the third embodiment by way of example, and FIG. **17B** is a sectional view taken along a line XVIIB-XVIIB in FIG. **17A**.

(158) The main transport robot **17** is not particularly limited but, for example, has the following structure.

(159) The main transport robot **17** includes a hand **80** capable of holding (supporting) the single batch of substrates **W**, and a slide rail **83** which supports the hand **80** slidably.

(160) The main transport robot **17** further includes a hand driving mechanism **84** which moves (slides) the hand **80** horizontally along the slide rail **83**. The hand **80** is horizontally moved among a first transfer position (indicated by a solid line in FIG. **18A**, **18B** to be described later) where the hand **80** can transfer the single batch of substrates **W** with respect to the first lifter **50A** located at the first upper position, a second transfer position (indicated by a solid line in FIG. **18C**, **18D** to be described later) where the hand **80** can transfer the single batch of substrates **W** with respect to the second lifter **50B** located at the second upper position, and a third transfer position (indicated by a solid line in FIG. **18E** to be described later) where the hand **80** can transfer the single batch of substrates **W** with respect to the third lifter **50C** located at the third upper position.

(161) The hand **80** has a holding portion **85** which holds the single batch of substrates **W**, a pair of grasping portions **86** which grasp the substrates **W** held by the holding portion **85**, a first connection shaft **81** horizontally extending and connected to the holding portion **85**, and a second connection shaft **82** vertically extending and connected to the first connection shaft **81**.

(162) The pair of grasping portions **86** are opposed to each other, and are brought into contact with the peripheries of the substrates **W** from opposite sides of the substrates **W** to grasp the substrates **W**. The pair of grasping portions **86** are moved toward each other to grasp the single batch of substrates **W**, and are moved away from each other to release the single batch of substrates **W**.

(163) As shown in FIG. **17B**, the holding portion **85** has a plurality of holding grooves **87** for holding the substrates **W**. The holding portion **85** is capable of holding substrates **W** of the same number as that of the holding grooves **87**. The grasping portions **86** may each have a roughness (not shown) so that the peripheries of the substrates **W** can be easily grasped.

(164) The main transport robot **17** includes an attitude changing mechanism **71** which transforms the hand **80** to change the attitude of the single batch of substrates **W**. The attitude changing mechanism **71** includes a first rotating mechanism **72** which rotates the first connection shaft **81** about its center axis **A2**, and a second rotating mechanism **73** which rotates the second connection shaft **82** about its center axis **A3**.

(165) The hand **80** is transformed by the first rotating mechanism **72** and the second rotating mechanism **73** while holding the single batch of substrates **W**, whereby the state of the hand **80** is switched between a first holding state (see FIG. **18A** to be described later) in which the hand **80** holds the single batch of substrates **W** in the vertical attitude and a second holding state (see FIG. **18D** to be described later) in which the hand **80** holds the single batch of substrates **W** in the horizontal attitude. Thus, the attitude of the single batch of substrates **W** can be changed between the horizontal attitude and the vertical attitude.

Exemplary Substrate Treatment According to Third Embodiment

(166) FIGS. **18A** to **18E** are schematic diagrams for describing how the substrate processing apparatus **1B** of the third embodiment performs the substrate treatment.

(167) The substrate processing apparatus **1B** of the third embodiment is capable of performing the substrate treatment shown in FIG. **5**, but performs the substrate treatment by a different procedure from that shown in FIGS. **6A** to **6C**. Differences will hereinafter be mainly described.

(168) The main transport robot **17** receives the single batch of substrates **W** from the attitude changing robot **16**, and is moved to the first transfer position. The main transport robot **17** transfers the single batch of substrates **W** to the first lift transport robot **19A** while assuming the first holding state. The attitude of the substrates **W** to be transferred to the first lift transport robot **19A** is the vertical attitude.

(169) The first lifter **50A** of the first lift transport robot **19A** is located at the first upper position (indicated by a two-dot-and-dash line in FIG. **18A**) and, in this state, receives the single batch of substrates **W**. The single batch of substrates **W** are supported by the first lifter **50A** of the first lift transport robot **19A**.

(170) The first lifter **50A** is moved down from the first upper position toward the sulfuric acid treatment position while supporting the single batch of substrates **W**. Thus, as shown in FIG. **18A**, the single batch of substrates **W** is immersed in the sulfuric acid-containing liquid within the sulfuric acid vessel **20** while being held in the vertical attitude (sulfuric acid immersing step: Step **S1**).

(171) Thereafter, the first lifter **50A** is moved up toward the first upper position, whereby the single batch of substrates **W** is taken out from the sulfuric acid-containing liquid in the sulfuric acid vessel **20**. As shown in FIG. **18B**, the hand **80** of the main transport robot **17** receives the single batch of substrates **W** from the first lifter **50A** located at the first upper position.

(172) The hand **80** of the main transport robot **17** is moved to the second transfer position after receiving the single batch of substrates **W** from the first lifter **50A**. As shown in FIG. **18C**, the state of the hand **80** of the main transport robot **17** is changed to the second holding state by the attitude changing mechanism **71**, whereby the attitude of the single batch of substrates **W** held by the hand **80** is changed from the vertical attitude to the horizontal attitude (first attitude changing step).

(173) The attitude of the single batch of substrates **W** may be changed when the hand **80** is located at the first transfer position, or may be changed when the hand **80** is located at the second transfer position. Alternatively, the attitude of the single batch of substrates **W** may be changed at a predetermined time point when the hand **80** is on the way from the first transfer position to the second transfer position.

(174) As shown in FIG. **18C**, the second lifter **50B** located at the second upper position receives the single batch of substrates **W** held in the horizontal attitude from the main transport robot **17** located at the second transfer position. Thereafter, the second lifter **50B** is moved from the second upper position (indicated by a two-dot-and-dash line in FIG. **18D**) toward the gas treatment position (indicated by a solid line in FIG. **18D**).

(175) With the second lifter **50B** located at the gas treatment position, the ozone gas valve **42** and the exhaust valve **46** are opened. Thus, the internal atmosphere of the treatment space **40a** is expelled from the gas treatment chamber **40**, and the ozone-containing gas is supplied into the treatment space **40a**. By thus supplying the ozone-containing gas into the treatment space **40a**, as shown in FIG. **18D**, the single batch of substrates **W** held in the horizontal attitude is exposed to the ozone-containing gas (ozone exposing step: Step **S2** shown in FIG. **5** (horizontal exposing step)).

(176) The single batch of substrates **W** to which the sulfuric acid-containing liquid adheres is exposed to the ozone-containing gas, whereby the ozone in the ozone-containing gas is dissolved in the sulfuric acid-containing liquid adhering to the substrates **W**, and the peroxodisulfuric acid is generated in the sulfuric acid-containing liquid adhering to the substrates **W**. The peroxodisulfuric acid makes it possible to dissolve the organic films exposed from the substrates **W** in the sulfuric acid-containing liquid. Parts of the organic films are not completely dissolved in the sulfuric acid-containing liquid, but are often separated from the upper surfaces of the substrates **W**.

(177) By supplying the ozone-containing gas into the treatment space **40a**, the internal atmosphere

of the treatment space **40a** is preferably replaced with the ozone-containing gas, whereby the treatment space **40a** is filled with the ozone-containing gas (ozone-containing gas filling step). With the treatment space **40a** filled with the ozone-containing gas, the peroxodisulfuric acid can be speedily and sufficiently generated in the sulfuric acid-containing liquid.

(178) Where the second lifter **50B** supports the single batch of substrates **W** in the horizontal attitude and, in this state, is located at the gas treatment position, a positional relationship of the single batch of substrates **W** with respect to the supply orifice rows **49AL** and the exhaust orifice rows **49BL** is the same as in the second embodiment (see FIG. **14**).

(179) Thereafter, the second lifter **50B** is moved up toward the second upper position, whereby the single batch of substrates **W** is taken out from the gas treatment chamber **40**. The hand **80** of the main transport robot **17** receives the single batch of substrates **W** from the second lifter **50B** located at the second upper position.

(180) The hand **80** of the main transport robot **17** is moved to the third transfer position after receiving the single batch of substrates **W** from the second lifter **50B**. As shown in FIG. **18E**, the state of the hand **80** of the main transport robot **17** is changed to the first holding state by the attitude changing mechanism **71**, whereby the attitude of the single batch of substrates **W** held by the hand **80** is changed from the horizontal attitude to the vertical attitude (second attitude changing step).

(181) The attitude of the single batch of substrates **W** may be changed when the hand **80** is located at the second transfer position, or may be changed when the hand **80** is located at the third transfer position. Alternatively, the attitude of the single batch of substrates **W** may be changed at a predetermined time point when the hand **80** is on the way from the second transfer position to the third transfer position.

(182) As shown in FIG. **18E**, the third lifter **50C** located at the third upper position receives the single batch of substrates **W** held in the vertical attitude from the main transport robot **17** located at the third transfer position. Thereafter, the third lifter **50C** is moved down from the third upper position toward the rinsing position. Thus, the single batch of substrates **W** held in the vertical attitude is immersed in the rinse liquid within the rinse liquid vessel **30** (rinsing step: Step **S3**).

(183) By thus immersing the single batch of substrates **W** in the rinse liquid within the rinse liquid vessel **30**, the single batch of substrates **W** is rinsed. Specifically, the sulfuric acid-containing liquid in which the organic films are dissolved and the organic films separated from the substrates **W** are removed from the substrates **W**.

(184) After the single batch of substrates **W** is taken out from the gas treatment chamber **40**, the ozone gas valve **42** is closed and the displacement gas valve **44** is opened. Thus, the displacement gas is supplied into the treatment space **40a** in the gas treatment chamber **40**, whereby the internal atmosphere of the treatment space **40a** is replaced with the displacement gas. Thus, the ozone-containing gas is expelled from the treatment space **40a**.

(185) Thereafter, the third lift transport robot **19C** transfers the single batch of substrates **W** to the main transport robot **17**. The main transport robot **17** transports the single batch of substrates **W** received from the third lift transport robot **19C** to the drying unit **10**.

(186) The third embodiment provides the same effects as the second embodiment.

(187) According to the third embodiment, the transport unit **3** includes the first lift transport robot **19A** (first transport robot), the second lift transport robot **19B** (second transport robot), and the main transport robot **17** which transports the single batch of substrates **W** between the first lift transport robot **19A** and the second lift transport robot **19B**. The attitude changing mechanism **71** changes the attitude of the single batch of substrates **W** transported by the main transport robot **17** between the horizontal attitude and the vertical attitude.

(188) Therefore, the transportation of the single batch of substrates **W** to the sulfuric acid vessel **20**, the transportation of the single batch of substrates **W** to the gas treatment chamber **40**, and the change of the attitude of the single batch of substrates **W** are respectively achieved by the different

robots. This makes the structures of the respective robots less complicated.

Substrate Processing Apparatus According to First Modification of Third Embodiment

(189) FIG. **19** is an elevational view of major portions of a substrate processing apparatus **1B** according to a first modification of the third embodiment.

(190) In the first modification of the third embodiment, the second lift transport robot **19B** transports the single batch of substrates **W** held in the horizontal attitude to the gas treatment chamber **40**, and rotates the single batch of substrates **W** held in the horizontal attitude about a vertical axis **A4** extending through the centers of the substrates **W** in the single batch in the gas treatment chamber **40**.

(191) Specifically, the second lift transport robot **19B** includes a substrate rotating mechanism **90** which rotates the second lifter **50B** about the vertical axis **A4**, a lift rail **91** which supports the substrate rotating mechanism **90** and the second lifter **50B** in a liftable manner, and a lift driving mechanism **92** which moves up and down the second lifter **50B** and the substrate rotating mechanism **90** along the lift rail **91**.

(192) In the first modification of the third embodiment, the second lifter **50B** of the second lift transport robot **19B** is not particularly limited but, for example, has the following structure. The second lifter **50B** includes, for example, a periphery holding portion **96** which holds the peripheries of the substrates **W**, and a connection portion **97** which connects the lift rail **91** to the periphery holding portion **96**.

(193) Further, the ozone gas treatment unit **6** includes a displacement gas flow path heater **93** which heats the displacement gas in the displacement gas supply flow path **43**.

(194) The temperature of the displacement gas is preferably, for example, in a range of not lower than 50° C. and not higher than 270° C. The temperature of the displacement gas is preferably in a range of not lower than 50° C. and not higher than 270° C., more preferably not lower than 80° C. and not higher than 170° C.

(195) FIGS. **20A** and **20B** are schematic diagrams for describing how the substrate processing apparatus **1B** of the first modification of the third embodiment performs the substrate treatment. FIG. **21** is a flow chart for describing the substrate treatment to be performed by the substrate processing apparatus **1B** of the first modification of the third embodiment by way of example.

(196) The substrate processing apparatus **1B** of the first modification of the third embodiment is capable of performing the substrate treatment by substantially the same procedure as in the third embodiment shown in FIGS. **18A** to **18E**. Differences from the substrate treatment procedure shown in FIGS. **18A** to **18E** will hereinafter be mainly described.

(197) As shown in FIG. **21**, the substrate processing apparatus **1B** of the first modification of the third embodiment performs a substrate rotating step (Step **S6**) before the start of the ozone exposing step (Step **S2**) after the sulfuric acid immersing step (Step **S1**). This will be detailed below.

(198) In the substrate treatment according to the first modification of the third embodiment, the single batch of substrates **W** is immersed in the sulfuric acid-containing liquid, and then transferred from the first lifter **50A** to the main transport robot **17**, as in the substrate treatment according to the third embodiment. Thereafter, as shown in FIG. **20A**, the second lifter **50B** located at the second upper position receives the single batch of substrates **W** held in the horizontal attitude from the main transport robot **17** located at the second transfer position in the second holding state. Then, the second lifter **50B** is moved from the second upper position (see FIG. **20A**) toward the gas treatment position (indicated by a solid line in FIG. **20B**).

(199) The second lifter **50B** is rotated about the vertical axis **A4** while being located at the gas treatment position. Thus, the single batch of substrates **W** is rotated together with the second lifter **50B** (substrate rotating step: Step **S6** shown in FIG. **21**). Thus, the sulfuric acid-containing liquid is partly scattered around the substrates **W**, whereby liquid films of the sulfuric acid-containing liquid adhering to the major surfaces of the respective substrates **W** are thinned (sulfuric acid film

thinning step).

(200) After the rotation of at least the single batch of substrates W is started, the ozone gas valve **42** and the exhaust valve **46** are opened. Thus, the internal atmosphere of the treatment space **40a** is expelled from the gas treatment chamber **40**, and the ozone-containing gas is supplied into the treatment space **40a**. By thus supplying the ozone-containing gas into the treatment space **40a**, as shown in FIG. **20B**, the single batch of substrates W held in the horizontal attitude is exposed to the ozone-containing gas (ozone exposing step: Step S2 shown in FIG. **21**). During the supply of the ozone-containing gas, the single batch of substrates W may be rotated, or the rotation of the single batch of substrates W may be stopped.

(201) After the single batch of substrates W is exposed to the ozone-containing gas, the second lifter **50B** is moved to the second upper position with the rotation thereof stopped. Thereafter, the single batch of substrates W is transferred to the main transport robot **17**, and the rinsing step (Step S3 shown in FIG. **21**) and the drying step (Step S4 shown in FIG. **21**) are performed.

(202) According to the first modification of the third embodiment, the single batch of substrates W is rotated about the vertical axis A4 before being exposed to the ozone-containing gas in the ozone exposing step after the attitude changing step.

(203) Therefore, an excess amount of the sulfuric acid-containing liquid can be removed from the substrates W, thereby improving the thickness evenness of the sulfuric acid-containing liquid at different positions on each of the substrates. This improves the evenness of the ozone concentration of the sulfuric acid-containing liquid at different positions on each of the substrates. As a result, it is possible to suppress the uneven removal of the organic film at different positions on each of the substrates.

(204) Unlike in the first modification, the displacement gas may be supplied into the treatment space **40a** to heat the single batch of substrates W before the ozone-containing gas is supplied into the treatment space **40a** after the start of the rotation of the single batch of substrates W. By entirely heating the single batch of substrates W with the displacement gas before the supply of the ozone-containing gas, the activity of the peroxodisulfuric acid can be evenly improved. This makes it possible to suppress the uneven removal of the organic films from the substrates W.

Substrate Processing Apparatus According to Second Modification of Third Embodiment

(205) FIG. **22** is an elevational view of major portions of a substrate processing apparatus **1B** according to a second modification of the third embodiment.

(206) Unlike the substrate processing apparatus **1B** shown in FIG. **16**, the substrate processing apparatus **1B** of the second modification of the third embodiment further includes a heating unit **13** which heats the single batch of substrates W while rotating the single batch of substrates W.

(207) The heating unit **13** includes a heating chamber **100** having a heating space **100a** which is capable of accommodating the single batch of substrates W. The heating chamber **100** has an openable/closable upper end portion **100b**. The heating unit **13** includes a heating gas supply flow path **101** which supplies the heating gas into the heating chamber **100**, a heating gas valve **102** which opens and closes the heating gas supply flow path **101**, a heating gas exhaust flow path **103** through which the internal atmosphere of the heating chamber **100** is expelled, and a heating gas exhaust valve **104** which opens and closes the heating gas exhaust flow path **103**.

(208) The heating gas is, for example, an inert gas. The temperature of the heating gas is preferably, for example, in a range of not lower than 50° C. and not higher than 270° C. The temperature of the heating gas is preferably in a range of not lower than 50° C. and not higher than 270° C., more preferably not lower than 80° C. and not higher than 170° C.

(209) The substrate processing apparatus **1B** further includes a fourth lift transport robot **19D** which transports the single batch of substrates W between the main transport robot **17** and the heating unit **13**. The fourth lift transport robot **19D** is an example of the third transport robot. The fourth lift transport robot **19D** has, for example, substantially the same structure as the first auxiliary transport robot **18A** shown in FIG. **3**.

(210) However, the fourth lift transport robot **19D** does not have the sliding mechanism **52**. Further, the fourth lift transport robot **19D** is configured so as to support the single batch of substrates **W** in the horizontal attitude.

(211) The fourth lift transport robot **19D** includes a fourth lifter **50D**, a substrate rotating mechanism **105** which rotates the fourth lifter **50D** about a vertical axis **A5**, a lift rail **106** which supports the substrate rotating mechanism **105** and the fourth lifter **50D** in a liftable manner, and a lift driving mechanism **107** which moves the fourth lifter **50D** and the substrate rotating mechanism **105** along the lift rail **106**.

(212) The fourth lifter **50D** of the fourth lift transport robot **19D** is not particularly limited but, for example, has the following structure. The fourth lifter **50D** includes, for example, a periphery holding portion **108** which holds the peripheries of the substrates **W**, and a connection portion **109** which connects the periphery holding portion **108** to the lift rail **106**. The fourth lifter **50D** of the fourth lift transport robot **19D** is movable up and down between a fifth upper position just above the heating unit **13** and a heating position where the single batch of substrates **W** is accommodated in the heating space **100a**.

(213) The fourth lift transport robot **19D** transports the single batch of substrates **W** held in the horizontal attitude to the heating chamber **100**, and rotates the single batch of substrates **W** held in the horizontal attitude about the vertical axis **A5** extending through the centers of the substrates **W** in the heating chamber **100**.

(214) In the second modification of the third embodiment, the hand **80** of the main transport robot **17** is movable to a fourth transfer position where the hand **80** can transfer the single batch of substrates **W** with respect to the fourth lifter **50D** located at the fifth upper position.

(215) In the second modification of the third embodiment, the substrate treatment shown in FIG. **21** can be performed. That is, the substrate processing apparatus **1B** of the second modification of the third embodiment performs the substrate rotating step (Step **S6**) before the ozone exposing step (Step **S2**) is started after the sulfuric acid immersing step (Step **S1**). This will be detailed below.

(216) In the substrate treatment of the second modification of the third embodiment, the single batch of substrates **W** is immersed in the sulfuric acid-containing liquid, and then transferred from the first lifter **50A** to the main transport robot **17** as in the substrate treatment of the third embodiment. Thereafter, the fourth lifter **50D** located at the fifth upper position receives the single batch of substrates **W** held in the horizontal attitude from the main transport robot **17** located at the fourth transfer position. Then, the fourth lifter **50D** is moved from the fifth upper position toward the heating position.

(217) The fourth lifter **50D** is rotated about the vertical axis **A5** while being located at the heating position. Thus, the single batch of substrates **W** is rotated together with the fourth lifter **50D** (substrate rotating step: Step **S6**). Thus, the sulfuric acid-containing liquid is partly scattered around the substrates **W**, whereby liquid films of the sulfuric acid-containing liquid adhering to the major surfaces of the substrates **W** are thinned (sulfuric acid film thinning step).

(218) Simultaneously with or after the start of the rotation of the single batch of substrates **W**, the heating gas valve **102** and the heating gas exhaust valve **104** are opened. Thus, the internal atmosphere of the heating space **100a** is expelled from the heating chamber **100**, and the heating gas is supplied into the heating space **100a**. By thus supplying the heating gas into the heating space **100a**, the single batch of substrates **W** held in the horizontal attitude is heated (heating/rotating step).

(219) Thereafter, the single batch of substrates **W** is transferred from the fourth lifter **50D** to the main transport robot **17**. Then, the ozone exposing step (Step **S2** in FIG. **21**), the rinsing step (Step **S3** in FIG. **21**) and the drying step (Step **S4** in FIG. **21**) are performed.

(220) According to the second modification of the third embodiment, the single batch of substrates **W** is rotated in the heating chamber **100**, whereby an excess amount of the sulfuric acid-containing liquid can be removed from the substrates **W**. Where the excess amount of the sulfuric acid-

containing liquid is thus removed by the rotation of the substrates W, it is possible to improve the thickness evenness of the sulfuric acid-containing liquid at different positions on each of the substrates W.

(221) Since the excess amount of the sulfuric acid-containing liquid is removed from the substrates W in the heating chamber **100**, it is possible to heat the single batch of substrates W while removing the sulfuric acid-containing liquid. Where the single batch of substrates W thus heated is transported into the gas treatment chamber **40** via the main transport robot **17** and the second lift transport robot **19B**, the single batch of substrates W removed of the excess amount of the sulfuric acid-containing liquid and heated can be exposed to the ozone-containing gas. This makes it possible to improve the evenness of the ozone concentration of the sulfuric acid-containing liquid at different positions on each of the substrates W while enhancing the activity of the peroxodisulfuric acid. As a result, it is possible to further suppress the uneven removal of the organic film at different positions on each of the substrates W.

(222) Unlike in the second modification, the heating chamber **100** may be sufficiently heated by opening the heating gas valve **102** and the heating gas exhaust valve **104** before the start of the rotation of the single batch of substrates W.

Other Embodiments

(223) The present invention is not limited to the embodiments described above, but may be embodied in some other ways. Other embodiments will be described below by way of example.

(224) (1) The treatment units **2** may include a single-substrate treatment unit **110** which is adapted to treat the substrates W one by one as shown in FIG. **23**. Specifically, the single-substrate treatment unit **110** includes a spin chuck **111**, a treatment cup **112**, a heater **113**, an ozone-containing gas nozzle **114**, a rinse liquid nozzle **115**, and a chamber **116**.

(225) The spin chuck **111** rotates a substrate W about a vertical axis A6 extending through the center of the substrate W, while holding the substrate W in the horizontal attitude. The treatment cup **112** surrounds the spin chuck **111** to receive a treatment liquid scattered from the substrate W. The heater **113** heats the substrate W held by the spin chuck **111**. The ozone-containing gas nozzle **114** supplies an ozone-containing gas toward the substrate W. The rinse liquid nozzle **115** supplies a rinse liquid toward the substrates W.

(226) After the single batch of substrates W is immersed in the sulfuric acid-containing liquid within the sulfuric acid vessel **20**, one of the substrates W in the single batch is transported into the single-substrate treatment unit **110** (transporting step). The substrate W transported into the single-substrate treatment unit **110** is rotated by the spin chuck **111**, and heated by the heater **113** (substrate rotating step). Thereafter, the ozone-containing gas is spouted from the ozone-containing gas nozzle **114**, whereby the substrate W to which the sulfuric acid-containing liquid adheres is exposed to the ozone-containing gas (ozone exposing step). The single-substrate treatment unit **110** is an example of the ozone gas treatment unit.

(227) Thereafter, the rinse liquid is spouted from the rinse liquid nozzle **115**, whereby the substrate W is rinsed. Then, the substrate W is rotated at a higher speed by the spin chuck **111**, whereby the substrate W is dried (drying step).

(228) Where a plurality of single-substrate treatment units **110** are provided, all the substrates W in the single batch can be speedily exposed to the ozone-containing gas after being immersed in the sulfuric acid-containing liquid.

(229) (2) A heater **120** (indicated by a two-dot-and-dash line in FIG. **2**) which heats the sulfuric acid-containing liquid retained in the sulfuric acid vessel **20** may be provided in the sulfuric acid vessel **20**. For example, the temperature of the sulfuric acid-containing liquid is preferably not lower than 150° C. By thus heating the sulfuric acid-containing liquid by means of the heater **120**, the activity of the peroxodisulfuric acid can be enhanced, making it possible to speedily remove the organic films. A heater which heats the sulfuric acid-containing liquid in the piping for supplying the sulfuric acid-containing liquid to the sulfuric acid vessel **20** may be provided instead of the

heater **120**. The sulfuric acid-containing liquid used in the sulfuric acid vessel **20** may be drained from the sulfuric acid vessel **20** to be reused.

(230) (3) In the first modification of the first embodiment and the modification of the second embodiment, the sulfuric acid vessel **20** is provided in the gas treatment chamber **40**. Alternatively, the sulfuric acid vessel **20** may be accommodated in the sulfuric acid treatment chamber **21**, and the gas treatment chamber **40** may be disposed just above the sulfuric acid treatment chamber **21**.

(231) (4) Where the mechanism for changing the attitude of the substrates **W** is provided in neither the lifter **50** nor the hand **80**, the attitude of the single batch of substrates **W** may be changed from the vertical attitude to the horizontal attitude by the attitude changing robot **16** after the sulfuric acid immersing step. Similarly, the attitude of the single batch of substrates **W** may be changed from the horizontal attitude to the vertical attitude by the attitude changing robot **16** after the ozone exposing step.

(232) With the use of the substrate processing apparatus **1A** described above, the sulfuric acid immersing step, the ozone exposing step and the rinsing step can be performed with the attitude of the single batch of substrates **W** maintained in the horizontal attitude.

(233) (5) The treatment space **40a** may be filled with the ozone-containing gas, before the single batch of substrates **W** is transported into the ozone gas treatment unit **6**. In this case, the single batch of substrates **W** can be exposed to the ozone-containing gas by transporting the single batch of substrates **W** into the ozone gas treatment unit **6**. What is important is that the single batch of substrates **W** transported into the ozone gas treatment unit **6** is exposed to the ozone-containing gas. That is, the supply of the ozone-containing gas into the treatment space **40a** may be started before the single batch of substrates **W** is placed in the treatment space **40a**, or may be started after the single batch of substrates **W** is placed in the treatment space **40a**.

(234) (6) In the embodiments described above, the controller **4** controls the entire substrate processing apparatus **1**. Alternatively, controllers which control the respective components of the substrate processing apparatus **1** may be provided separately at different positions. Further, the controller **4** is not necessarily required to directly control the respective components, but signals outputted from the controller **4** may be received by slave controllers which control the respective components of the substrate processing apparatus **1**.

(235) (7) In the embodiments described above, the terms “horizontal” and “vertical” are not required to be used in the strict sense of these terms, but are intended to permit deviations in production accuracy, installation accuracy and the like.

(236) (8) The components of the substrate processing apparatuses are each schematically illustrated in the form of block, but the shapes, the sizes and the positional relationships of the blocks do not show the actual shapes, the actual sizes and the actual positional relationships of the respective components.

(237) While the embodiments of the present invention have been described in detail, these embodiments are merely specific examples that are illustrative of the technical principles of the present invention but not limitative of the invention. The spirit and scope of the present invention are limited only by the appended claims.

Claims

1. A substrate processing apparatus comprising: a sulfuric acid vessel which retains a sulfuric acid-containing liquid and is configured so that a plurality of substrates can be immersed in the sulfuric acid-containing liquid; an ozone gas treatment unit in which the plurality of substrates are exposed to an ozone-containing gas; and a transport unit which transports the plurality of substrates between the sulfuric acid vessel and the ozone gas treatment unit, wherein the ozone gas treatment unit comprises a gas treatment chamber having a treatment space capable of accommodating the plurality of substrates for exposing the plurality of substrates accommodated in the treatment space

to the ozone-containing gas, the gas treatment chamber comprises a pair of walls opposing each other and defining the treatment space, a plurality of supply orifices which open in one of the pair of walls for supplying the ozone-containing gas into the treatment space, and a plurality of exhaust orifices which open in the other of the pair of walls for exhausting the treatment space, and the plurality of supply orifices and the plurality of exhaust orifices are opposed to each other such that the plurality of supply orifices discharge the ozone-containing gas toward the plurality of exhaust orifices.

2. The substrate processing apparatus according to claim 1, wherein the plurality of supply orifices are arranged in a plurality of supply orifice rows juxtaposed in a predetermined arrangement direction in the gas treatment chamber, wherein the transport unit supports the plurality of substrates so as to arrange the plurality of substrates in the arrangement direction, and transports the plurality of substrates into the gas treatment chamber so that the plurality of substrates are located between respective adjacent pairs of the supply orifice rows.

3. The substrate processing apparatus according to claim 1, wherein the sulfuric acid vessel is configured so that the plurality of substrates can be immersed in the sulfuric acid-containing liquid while being held in a vertical attitude, wherein the treatment space is configured so that the plurality of substrates can be accommodated therein while being held in a horizontal attitude, wherein the transport unit comprises an attitude changing mechanism which changes attitude of the plurality of substrates between the vertical attitude and the horizontal attitude.

4. The substrate processing apparatus according to claim 3, wherein the transport unit comprises a transport robot having a lifter which supports the plurality of substrates for transporting the plurality of substrates between the sulfuric acid vessel and the gas treatment chamber, wherein the attitude changing mechanism transforms the lifter to change the attitude of the plurality of substrates between the vertical attitude and the horizontal attitude.

5. The substrate processing apparatus according to claim 1, wherein the treatment space is located just above the sulfuric acid vessel, wherein the transport unit is movable up and down while supporting the plurality of substrates so as to transport the plurality of substrates between the gas treatment chamber and the sulfuric acid vessel.

6. The substrate processing apparatus according to claim 5, further comprising a cover member which covers and uncovers the sulfuric acid vessel to separate inside of the sulfuric acid vessel and the treatment space from each other.

7. The substrate processing apparatus according to claim 3, wherein the transport unit comprises a first transport robot which transports the plurality of substrates held in the vertical attitude to the sulfuric acid vessel, a second transport robot which transports the plurality of substrates held in the horizontal attitude to the gas treatment chamber, and a main transport robot which transports the plurality of substrates between the first transport robot and the second transport robot, wherein the attitude changing mechanism changes attitude of the plurality of substrates transported by the main transport robot between the horizontal attitude and the vertical attitude.

8. The substrate processing apparatus according to claim 7, wherein the second transport robot transports the plurality of substrates held in the horizontal attitude to the gas treatment chamber, and rotates the plurality of substrates held in the horizontal attitude about a vertical axis extending through centers of the plurality of substrates in the gas treatment chamber.

9. The substrate processing apparatus according to claim 7, further comprising a heating chamber in which the plurality of substrates are heated, wherein the transport unit further comprises a third transport robot which transports the plurality of substrates held in the horizontal attitude into the heating chamber and rotates the plurality of substrates held in the horizontal attitude about a vertical axis extending through centers of the plurality of substrates in the heating chamber, wherein the main transport robot transports the plurality of substrates among the sulfuric acid vessel, the gas treatment chamber and the heating chamber.

10. A substrate processing apparatus comprising: a sulfuric acid vessel which retains a sulfuric

acid-containing liquid and is configured so that a plurality of substrates can be immersed in the sulfuric acid-containing liquid; an ozone gas treatment unit in which the plurality of substrates are exposed to an ozone-containing gas; a transport unit which transports the plurality of substrates between the sulfuric acid vessel and the ozone gas treatment unit; and a heating chamber in which the plurality of substrates are heated, wherein the ozone gas treatment unit comprises a gas treatment chamber having a treatment space capable of accommodating the plurality of substrates for exposing the plurality of substrates accommodated in the treatment space to the ozone-containing gas, the sulfuric acid vessel is configured so that the plurality of substrates can be immersed in the sulfuric acid-containing liquid while being held in a vertical attitude, the treatment space is configured so that the plurality of substrates can be accommodated therein while being held in a horizontal attitude, the transport unit comprises an attitude changing mechanism which changes attitude of the plurality of substrates between the vertical attitude and the horizontal attitude, the transport unit comprises a first transport robot which transports the plurality of substrates held in the vertical attitude to the sulfuric acid vessel, a second transport robot which transports the plurality of substrates held in the horizontal attitude to the gas treatment chamber, and a main transport robot which transports the plurality of substrates between the first transport robot and the second transport robot, the attitude changing mechanism changes attitude of the plurality of substrates transported by the main transport robot between the horizontal attitude and the vertical attitude, the transport unit further comprises a third transport robot which transports the plurality of substrates held in the horizontal attitude into the heating chamber and rotates the plurality of substrates held in the horizontal attitude about a vertical axis extending through centers of the plurality of substrates in the heating chamber, and the main transport robot transports the plurality of substrates among the sulfuric acid vessel, the gas treatment chamber and the heating chamber.
