

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12397987
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Conrad; Wayne Ernest

Dust and allergen control for surface cleaning apparatus

Abstract

A system comprising a vacuum cleaner and an apparatus for receiving dirt from a dirt collection region of the vacuum cleaner. The apparatus has an air flow passage from an inlet port to a clean air outlet, wherein the dirt collection region of the vacuum cleaner is positionable in air flow communication with the inlet port. In an emptying mode of operation, a motor and fan assembly of the system produces a flow of air that conveys dirt from the dirt collection region of the vacuum cleaner to the air treatment member of the apparatus. The vacuum cleaner is docked with the apparatus by a user moving the dirt collection region in a downward direction to a position in which, during the emptying mode of operation, the flow of air conveys the dirt from the dirt collection region of the vacuum cleaner downwardly to the air treatment member of the apparatus.

Inventors:	Conrad; Wayne Ernest (Hampton, CA)
Applicant:	Omachron Intellectual Property Inc. (Hampton, CA)
Family ID:	1000008777956
Assignee:	Omachron Intellectual Property Inc. (Hampton, CA)
Appl. No.:	18/109751
Filed:	February 14, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230286739 A1	Sep. 14, 2023

Related U.S. Application Data

continuation parent-doc US 16584013 20190926 PENDING child-doc US 18109751
continuation parent-doc US 15393003 20161228 US 10464746 20191105 child-doc US 16584013

Publication Classification

Int. Cl.: **B65F1/14** (20060101); **A47L9/10** (20060101); **A47L9/12** (20060101); **A47L9/16** (20060101); **B65F1/10** (20060101); **B65F1/16** (20060101)

U.S. Cl.:

CPC **B65F1/14** (20130101); **A47L9/106** (20130101); **A47L9/12** (20130101); **A47L9/16** (20130101); **A47L9/1683** (20130101); **B65F1/105** (20130101); **B65F1/1607** (20130101); **B65F2210/129** (20130101)

Field of Classification Search

CPC: B65F (1/14); B65F (1/105); B65F (1/1607); B65F (1/127); B65F (1/16); B65F (2210/129); B65F (7/00); B65F (7/005); A47L (9/106); A47L (9/12); A47L (9/16); A47L (9/1683); A47L (9/2873); A47L (2201/02); A47L (2201/024); A47L (7/0047); A47L (7/0057); A47L (7/0066); A47L (7/0052); A47L (5/38)

USPC: 15/310

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2013498	12/1934	McConaughy	N/A	N/A
2602417	12/1951	Medcalf	N/A	N/A
3724179	12/1972	Leinfelt	N/A	N/A
RE28201	12/1973	Hughes	N/A	N/A
4360947	12/1981	DeCosa	15/352	A47L 7/0071
4497308	12/1984	Johnson	110/165R	F23J 1/04
4571250	12/1985	Irmscher	141/93	B65F 1/10
4598838	12/1985	Zakrajsek	N/A	N/A
RE32257	12/1985	Dyson	N/A	N/A
4704764	12/1986	Metelko, Jr.	15/301	B65F 1/10
5267371	12/1992	Soler et al.	N/A	N/A
5358290	12/1993	Fleet et al.	N/A	N/A
5606769	12/1996	Tomasiak et al.	N/A	N/A
5787545	12/1997	Colens	N/A	N/A
5974625	12/1998	Garner	N/A	N/A
6071322	12/1999	Hulthen	N/A	N/A
6098244	12/1999	Conrad et al.	N/A	N/A
6099661	12/1999	Conrad	N/A	N/A
6101672	12/1999	Conrad et al.	N/A	N/A
6123779	12/1999	Conrad et al.	N/A	N/A
6129213	12/1999	Edwards	N/A	N/A
6129775	12/1999	Conrad et al.	N/A	N/A
6135708	12/1999	Conrad et al.	N/A	N/A
6168716	12/2000	Conrad et al.	N/A	N/A

6170119	12/2000	Conrad et al.	N/A	N/A
6173474	12/2000	Conrad	N/A	N/A
6174127	12/2000	Conrad et al.	N/A	N/A
6183641	12/2000	Conrad et al.	N/A	N/A
6224325	12/2000	Conrad et al.	N/A	N/A
6231645	12/2000	Conrad et al.	N/A	N/A
6238177	12/2000	Conrad et al.	N/A	N/A
6243917	12/2000	Conrad	N/A	N/A
6251296	12/2000	Conrad et al.	N/A	N/A
6261052	12/2000	Conrad et al.	N/A	N/A
6261379	12/2000	Conrad et al.	N/A	N/A
6280143	12/2000	Parker et al.	N/A	N/A
6307358	12/2000	Conrad	N/A	N/A
6312594	12/2000	Conrad et al.	N/A	N/A
6328527	12/2000	Conrad et al.	N/A	N/A
6332551	12/2000	Copeland	N/A	N/A
6334234	12/2001	Conrad et al.	N/A	N/A
6344064	12/2001	Conrad	N/A	N/A
6389329	12/2001	Colens	N/A	N/A
6406505	12/2001	Oh et al.	N/A	N/A
6440197	12/2001	Conrad et al.	N/A	N/A
6457205	12/2001	Conrad	N/A	N/A
6467124	12/2001	Small	N/A	N/A
6533834	12/2002	Conrad et al.	N/A	N/A
6599340	12/2002	Conrad et al.	N/A	N/A
6782585	12/2003	Conrad et al.	N/A	N/A
7053578	12/2005	Diehl et al.	N/A	N/A
7174602	12/2006	Foral	N/A	N/A
7329294	12/2007	Conrad	N/A	N/A
7386916	12/2007	Bone	55/299	A47L 9/2884
7488362	12/2008	Jeong et al.	N/A	N/A
7740675	12/2009	Conrad	N/A	N/A
7749293	12/2009	Conrad	N/A	N/A
7752706	12/2009	Goodger	N/A	N/A
7776120	12/2009	Conrad	N/A	N/A
7803207	12/2009	Conrad	N/A	N/A
7811345	12/2009	Conrad	N/A	N/A
7867308	12/2010	Conrad	N/A	N/A
7887612	12/2010	Conrad	N/A	N/A
7941895	12/2010	Conrad	N/A	N/A
7962996	12/2010	Mondello	N/A	N/A
8070006	12/2010	Austin et al.	N/A	N/A
8100999	12/2011	Ashbee et al.	N/A	N/A
8127398	12/2011	Conrad	N/A	N/A
8146201	12/2011	Conrad	N/A	N/A
8151407	12/2011	Conrad	N/A	N/A
8176596	12/2011	Conrad	N/A	N/A
8192515	12/2011	Conrad	N/A	N/A
8292979	12/2011	Conrad	N/A	N/A

8296900	12/2011	Conrad	N/A	N/A
8349428	12/2012	Conrad	N/A	N/A
8370993	12/2012	Conrad	N/A	N/A
8375508	12/2012	Conrad	N/A	N/A
8388900	12/2012	Benedek et al.	N/A	N/A
8444731	12/2012	Gomiciaga- Pereda et al.	N/A	N/A
8448291	12/2012	Conrad	N/A	N/A
8479358	12/2012	Conrad	N/A	N/A
8486170	12/2012	Conrad et al.	N/A	N/A
8510907	12/2012	Conrad	N/A	N/A
8533904	12/2012	Conrad	N/A	N/A
8561257	12/2012	Conrad	N/A	N/A
8567005	12/2012	Conrad	N/A	N/A
8572799	12/2012	Won et al.	N/A	N/A
8578550	12/2012	Conrad	N/A	N/A
8578553	12/2012	Conrad	N/A	N/A
8590102	12/2012	Conrad	N/A	N/A
8607407	12/2012	Conrad	N/A	N/A
8621709	12/2013	Conrad	N/A	N/A
8640304	12/2013	Conrad	N/A	N/A
8646147	12/2013	Conrad	N/A	N/A
8659184	12/2013	Conrad	N/A	N/A
8677554	12/2013	Conrad	N/A	N/A
8677558	12/2013	Conrad	N/A	N/A
8713751	12/2013	Conrad	N/A	N/A
8732892	12/2013	Laliberte et al.	N/A	N/A
8813305	12/2013	Conrad	N/A	N/A
8834209	12/2013	Conrad	N/A	N/A
8869344	12/2013	Conrad	N/A	N/A
8869345	12/2013	Conrad	N/A	N/A
8869348	12/2013	Conrad	N/A	N/A
8875340	12/2013	Conrad	N/A	N/A
8875342	12/2013	Conrad	N/A	N/A
8984708	12/2014	Kuhe et al.	N/A	N/A
9027198	12/2014	Conrad	N/A	N/A
9027203	12/2014	Conrad et al.	N/A	N/A
9066642	12/2014	Conrad	N/A	N/A
9119513	12/2014	Conrad	N/A	N/A
9161666	12/2014	Conrad	N/A	N/A
9161669	12/2014	Conrad	N/A	N/A
9167944	12/2014	Conrad	N/A	N/A
9204769	12/2014	Conrad	N/A	N/A
9204773	12/2014	Conrad	N/A	N/A
9215960	12/2014	Conrad	N/A	N/A
9226633	12/2015	Conrad et al.	N/A	N/A
9227151	12/2015	Conrad	N/A	N/A
9227201	12/2015	Conrad	N/A	N/A
9232881	12/2015	Conrad	N/A	N/A
9238235	12/2015	Conrad	N/A	N/A

9271618	12/2015	Mantyla et al.	N/A	N/A
9295995	12/2015	Conrad	N/A	N/A
9314138	12/2015	Conrad	N/A	N/A
9314139	12/2015	Conrad et al.	N/A	N/A
9315308	12/2015	Audet et al.	N/A	N/A
9320401	12/2015	Conrad	N/A	N/A
9326652	12/2015	Conrad	N/A	N/A
9364127	12/2015	Conrad	N/A	N/A
9427122	12/2015	Conrad et al.	N/A	N/A
9427126	12/2015	Conrad	N/A	N/A
9433332	12/2015	Conrad	N/A	N/A
9451852	12/2015	Conrad	N/A	N/A
9451855	12/2015	Conrad	N/A	N/A
9456721	12/2015	Conrad	N/A	N/A
9462920	12/2015	Morin et al.	N/A	N/A
9492045	12/2015	Conrad	N/A	N/A
9492048	12/2015	Won et al.	N/A	N/A
9526394	12/2015	Conrad	N/A	N/A
9572463	12/2016	Conrad	N/A	N/A
9591952	12/2016	Conrad	N/A	N/A
9591958	12/2016	Conrad	N/A	N/A
9775484	12/2016	Conrad	N/A	N/A
9788698	12/2016	Morin et al.	N/A	N/A
9801513	12/2016	Conrad et al.	N/A	N/A
9820621	12/2016	Conrad et al.	N/A	N/A
9888818	12/2017	Kuhe et al.	N/A	N/A
9924846	12/2017	Morin et al.	N/A	N/A
10076183	12/2017	Conrad et al.	N/A	N/A
10149587	12/2017	Conrad et al.	N/A	N/A
10159393	12/2017	Conrad	N/A	N/A
10201260	12/2018	Conrad et al.	N/A	N/A
10251519	12/2018	Conrad	N/A	N/A
10357136	12/2018	Conrad	N/A	N/A
10464746	12/2018	Conrad	N/A	N/A
10537219	12/2019	Conrad et al.	N/A	N/A
10568477	12/2019	Conrad	N/A	N/A
10729294	12/2019	Conrad et al.	N/A	N/A
11285495	12/2021	Conrad	N/A	N/A
11478117	12/2021	Conrad et al.	N/A	N/A
11534041	12/2021	Conrad	N/A	N/A
11534043	12/2021	Conrad	N/A	N/A
11571097	12/2022	Conrad	N/A	N/A
11793374	12/2022	Conrad	N/A	N/A
11857142	12/2023	Conrad	N/A	N/A
11950745	12/2023	Conrad et al.	N/A	N/A
2001/0027587	12/2000	Conrad et al.	N/A	N/A
2002/0162188	12/2001	Harmen	N/A	N/A
2003/0201754	12/2002	Conrad	N/A	N/A
2004/0093837	12/2003	Mauffette et al.	N/A	N/A
2004/0112022	12/2003	Vuijk	N/A	N/A

2004/0216266	12/2003	Conrad	N/A	N/A
2006/0137304	12/2005	Jeong et al.	N/A	N/A
2006/0156508	12/2005	Khalil	N/A	N/A
2006/0175336	12/2005	Wang	220/495.04	B65F 1/163
2006/0191099	12/2005	Fry et al.	N/A	N/A
2006/0196004	12/2005	Conrad	N/A	N/A
2006/0278087	12/2005	Sepke et al.	N/A	N/A
2007/0271724	12/2006	Hakan et al.	N/A	N/A
2007/0294858	12/2006	Murphy	N/A	N/A
2008/0040883	12/2007	Beskow et al.	N/A	N/A
2008/0172992	12/2007	Conrad	N/A	N/A
2008/0178416	12/2007	Conrad	N/A	N/A
2008/0178418	12/2007	Conrad	N/A	N/A
2008/0179133	12/2007	Conrad	N/A	N/A
2008/0189898	12/2007	Hughes	N/A	N/A
2008/0196366	12/2007	Conrad	N/A	N/A
2008/0216281	12/2007	Conrad	N/A	N/A
2008/0256744	12/2007	Rowntreer et al.	N/A	N/A
2010/0175217	12/2009	Conrad	N/A	N/A
2010/0229322	12/2009	Conrad	N/A	N/A
2010/0229323	12/2009	Conrad	N/A	N/A
2010/0229325	12/2009	Conrad	N/A	N/A
2010/0229326	12/2009	Conrad	N/A	N/A
2010/0229334	12/2009	Conrad	N/A	N/A
2010/0229335	12/2009	Conrad	N/A	N/A
2010/0251507	12/2009	Conrad	N/A	N/A
2010/0301147	12/2009	Harkess et al.	N/A	N/A
2011/0119860	12/2010	Marcil et al.	N/A	N/A
2011/0219567	12/2010	Conrad	N/A	N/A
2011/0219570	12/2010	Conrad	N/A	N/A
2011/0219579	12/2010	Conrad	N/A	N/A
2012/0011677	12/2011	Jung et al.	N/A	N/A
2012/0030895	12/2011	Chong et al.	N/A	N/A
2013/0007984	12/2012	Liu	15/353	A47L 9/248
2013/0031744	12/2012	Ota	N/A	N/A
2013/0305481	12/2012	Jung et al.	N/A	N/A
2014/0017777	12/2013	Wright et al.	N/A	N/A
2014/0059797	12/2013	Kim et al.	N/A	N/A
2014/0237768	12/2013	Conrad	N/A	N/A
2014/0366314	12/2013	Conrad	N/A	N/A
2016/0367094	12/2015	Conrad	N/A	N/A
2018/0022543	12/2017	Jokinen	N/A	N/A
2018/0064303	12/2017	Meggle et al.	N/A	N/A
2018/0078104	12/2017	Register et al.	N/A	N/A
2020/0315419	12/2019	Sato et al.	N/A	N/A
2022/0151446	12/2021	Conrad et al.	N/A	N/A
2024/0138634	12/2023	Conrad	N/A	N/A
2024/0180373	12/2023	Conrad et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2275675	12/1998	CA	N/A
2288544	12/1999	CA	N/A
2258416	12/1999	CA	N/A
2258419	12/1999	CA	N/A
2258421	12/1999	CA	N/A
2258422	12/1999	CA	N/A
2258423	12/1999	CA	N/A
2258426	12/1999	CA	N/A
2330801	12/2000	CA	N/A
2338193	12/2001	CA	N/A
2339514	12/2001	CA	N/A
2342673	12/2001	CA	N/A
2342993	12/2001	CA	N/A
2658014	12/2009	CA	N/A
2658022	12/2009	CA	N/A
2658160	12/2009	CA	N/A
2658366	12/2009	CA	N/A
2658397	12/2009	CA	N/A
2658497	12/2009	CA	N/A
2658643	12/2009	CA	N/A
2658644	12/2009	CA	N/A
1336154	12/2001	CN	N/A
101015436	12/2006	CN	N/A
101095604	12/2007	CN	N/A
101288572	12/2007	CN	N/A
101489453	12/2008	CN	N/A
101489455	12/2008	CN	N/A
101489457	12/2008	CN	N/A
101489461	12/2008	CN	N/A
101657133	12/2009	CN	N/A
102188208	12/2010	CN	N/A
102256523	12/2010	CN	N/A
202173358	12/2011	CN	N/A
60201666	12/2005	DE	N/A
60211663	12/2006	DE	N/A
112006003479	12/2007	DE	N/A
112007001314	12/2008	DE	N/A
112007003039	12/2008	DE	N/A
112007003052	12/2009	DE	N/A
112010001135	12/2011	DE	N/A
102012100047	12/2012	DE	N/A
102012110765	12/2013	DE	N/A
1243218	12/2009	EP	N/A
2003180587	12/2002	JP	N/A
2009261501	12/2008	JP	N/A
2010081968	12/2009	JP	N/A

2014180647	12/2013	JP	N/A
10-20050091821	12/2004	KR	N/A
10-20050091824	12/2004	KR	N/A
10-20050091826	12/2004	KR	N/A
10-20050091829	12/2004	KR	N/A
10-20050091830	12/2004	KR	N/A
10-20050091833	12/2004	KR	N/A
10-20050091834	12/2004	KR	N/A
10-20050091835	12/2004	KR	N/A
10-20050091836	12/2004	KR	N/A
10-20050091837	12/2004	KR	N/A
10-20050091838	12/2004	KR	N/A
10-20060008365	12/2005	KR	N/A
1020070012109	12/2006	KR	N/A
0010718	12/1999	WO	N/A
2008135708	12/2007	WO	N/A
2010102396	12/2009	WO	N/A
2012116956	12/2011	WO	N/A
2016040601	12/2015	WO	N/A

OTHER PUBLICATIONS

NPL1, How To Empty Dirt and Dust Container Shark Navigator Vacuum, YouTube, Available Oct. 11, 2014. <https://www.youtube.com/watch?v=SPe1M0M43IY> (Year: 2014). cited by examiner

English translation of CN202173358, as published on Mar. 28, 2012. cited by applicant

English translation of CN102256523, as published on Nov. 23, 2011. cited by applicant

English translation of CN102188208, as published on Sep. 21, 2011. cited by applicant

English translation of CN101657133, as published on Feb. 24, 2010. cited by applicant

English translation of CN 101489461, as published on Jul. 22, 2009. cited by applicant

English translation of CN101489457, as published on Jul. 22, 2009. cited by applicant

English translation of CN101489455, as published on Jul. 22, 2017. cited by applicant

English translation of CN101489453, as published on Jul. 22, 2009. cited by applicant

English translation of CN101288572, as published on Oct. 22, 2008. cited by applicant

English translation of CN101095604, as published on Jan. 2, 2008. cited by applicant

English translation of CN101015436, as published on Aug. 15, 2007. cited by applicant

English translation of CN1336154, as published on Feb. 20, 2002. cited by applicant

English translation of DE112010001135, as published on Aug. 2, 2012. cited by applicant

English translation of DE112007003052, as published on Jan. 14, 2010. cited by applicant

English translation of DE112007003039, as published on Oct. 29, 2009. cited by applicant

English translation of DE112007001314, as published on Apr. 23, 2009. cited by applicant

English translation of DE112006003479, as published on Dec. 18, 2008. cited by applicant

English translation of DE102012110765, as published on May 15, 2014. cited by applicant

English translation of DE60211663, as published on May 10, 2007. cited by applicant

English translation of DE60201666, as published on Jun. 1, 2006. cited by applicant

English translation of JP2010081968, as published on Apr. 15, 2010. cited by applicant

English translation of JP2009261501, as published on Nov. 12, 2009. cited by applicant

English translation of KR20050091821, as published on Sep. 15, 2005. cited by applicant

English translation of KR20050091824, as published on Sep. 15, 2005. cited by applicant

English translation of KR20050091826, as published on Sep. 15, 2005. cited by applicant

English translation of KR20050091829, as published on Sep. 15, 2005. cited by applicant

English translation of KR20050091830, as published on Sep. 15, 2005. cited by applicant

English translation of KR20050091833, as published on Sep. 15, 2005. cited by applicant
English translation of KR20050091834, as published on Sep. 15, 2005. cited by applicant
English translation of KR20050091835, as published on Sep. 15, 2005. cited by applicant
English translation of KR20050091836, as published on Sep. 15, 2005. cited by applicant
English translation of KR20050091837, as published on Sep. 15, 2005. cited by applicant
English translation of KR20050091838, as published on Sep. 15, 2005. cited by applicant
English translation of KR 20060008365. as published on Jan. 26, 2006. cited by applicant
International Search Report and Written Opinion dated Feb. 13, 2018. cited by applicant
English machine translation of the Abstract of JP2014180647, published on Sep. 29, 2014. cited by applicant
English machine translation of KR1020070012109, published on Jan. 25, 2007. cited by applicant
English machine translation of JP2003180587, published on Jul. 2, 2003. cited by applicant
English machine translation of EP1243218, published on May 19, 2010. cited by applicant
U.S. Appl. No. 09/343,479, filed Jun. 30, 1999. cited by applicant

Primary Examiner: Posigian; David S

Assistant Examiner: Gump; Michael A

Attorney, Agent or Firm: SMART & BIGGAR LP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of co-pending U.S. patent application Ser. No. 16/584,013, filed on Sep. 26, 2019, which itself is a continuation of Ser. No. 15/393,003, filed on Dec. 28, 2016 and issued as U.S. Pat. No. 10,464,746, the entirety of which is hereby incorporated by reference.

FIELD

(1) This disclosure relates generally to dust and allergen control for surface cleaning apparatus, and more specifically to systems and methods for constraining dust and other allergens during transfer of material collected by a surface cleaning apparatus to a garbage can or other waste receptacle.

INTRODUCTION

(2) Various types of surface cleaning apparatus are known, including upright surface cleaning apparatus, canister surface cleaning apparatus, stick surface cleaning apparatus, hand surface cleaning apparatus and central vacuum systems.

(3) Surface cleaning apparatus that use one or more cleaning stages (e.g. cyclonic cleaning stages) to remove particulate matter (e.g. dust and dirt) from an airstream are known. Frequently, a second cleaning stage, which may e.g. comprise a plurality of cyclones in parallel, is provided downstream of a first cleaning stage to remove particulate matter from the airstream exiting the first cleaning stage, e.g. by promoting the dis-entrainment of smaller particles from the airflow.

(4) Particulate matter separated from an airstream by a cyclonic cleaning stage is frequently collected in one or more dirt collection chambers. Often, these collection chambers are removable from the surface cleaning apparatus, either on their own or as part of a removable cyclone assembly. Providing a detachable dirt collection chamber and/or cyclone assembly may allow a user to carry the collection chamber and its contents—e.g. to a refuse container, which may also be referred to as a garbage can, for emptying-without needing to carry or move the rest of the surface cleaning apparatus.

(5) Typically, a dirt collection chamber is openable for accessing the interior of the dirt collection

chamber, e.g. for emptying or cleaning. For example, the collection chamber may have one or more openable portions that are moveably connected to (e.g., pivotally) or removable from the collection chamber. Alternatively, or additionally, a cyclone assembly in which the collection chamber is provided may have one or more openable portions that e.g. provide access to an interior of a cyclone chamber.

(6) Surface cleaning apparatus that collect particulate matter in an openable dirt collection chamber—which may be characterized as ‘bagless’ vacuum cleaners—may have one or more advantages as compared to surface cleaning apparatus in which particulate matter is collected in a bag or other non-openable collection vessel. For example, the effective suction provided at e.g. a dirty air inlet of the surface cleaning apparatus may be relatively constant, regardless of the amount of particulate matter in the dirt collection chamber.

(7) However, dirt collected in an openable dirt collection chamber has to be transferred to a garbage can or the like to empty the openable dirt collection chamber.

SUMMARY

(8) The following introduction is provided to introduce the reader to the more detailed discussion to follow. The introduction is not intended to limit or define any claimed or as yet unclaimed invention. One or more inventions may reside in any combination or sub-combination of the elements or process steps disclosed in any part of this document including its claims and figures.

(9) In accordance with a first aspect of this disclosure, a lid for a refuse container may have an openable port that allows access to the interior of the refuse container without removing the lid from the refuse container. By positioning a dirt collection region of a surface cleaning apparatus in the port, the contents of the dirt collection region may be emptied into the refuse container without removing the lid. In such an arrangement, the lid may inhibit or prevent dust, allergens, or other particulate matter from escaping the interior of the refuse container while the particulate matter is being transferred from the dirt collection region to the refuse container.

(10) For example, a surface cleaning apparatus may have a dirt collection region or chamber that is removable from the surface cleaning apparatus, either by itself or as part of a removable air treatment assembly, such as a removable cyclone assembly. A user may detach and carry such a dirt collection region to a refuse container for emptying or may carry the entire surface cleaning apparatus, such as a hand surface cleaning apparatus to the refuse container. If the dirt collection region is then opened above or in an open refuse container (e.g. a refuse container whose lid has been removed), then the contents will fall out due to gravity. However, lighter particulate matter may be entrained in air flow currents and may form a fine dust plume and/or may be carried to the floor adjacent the refuse container. In accordance with this aspect, a user may position the dirt collection region in an opened port of a lid of the refuse wherein the port is configured to inhibit or prevent dust, allergens, or other particulate matter from escaping the interior of the refuse container. For example, the port may be sized to be slightly larger than the dirt collection region, thereby providing a smaller annular gap between the lid and the dirt collection region, thereby reducing the likelihood that dust, allergens, or other particulate matter will escape from the interior of the refuse container. Alternatively, or in addition, the port may be provided with a gasket, or may be configured to close around the dirt collection container to inhibit or prevent dust, allergens, or other particulate matter from escaping the interior of the refuse container.

(11) In accordance with this broad aspect, there is provided a lid for a refuse container, the lid moveable between a closed position in which the lid overlies an open upper end of the refuse container and an open position in which the refuse container may be emptied, the lid having an openable port operable between a closed position in which the lid closes the upper end of the refuse container and an open position in which a dirt collection region of an air treatment member of a surface cleaning apparatus is positioned in the port.

(12) In some embodiments, in the open position, the lid may close around the dirt collection region.

(13) In some embodiments, in the open position, the port may be sized to close around the dirt

collection region whereby the refuse container is at least substantially sealed.

(14) In some embodiments, the lid may comprise at least one moveable member which closes the port when the port is in the closed position and which is positioned adjacent a portion of the surface cleaning apparatus when the port is in the open position and the portion of the surface cleaning apparatus is positioned in the port with the dirt collection region overlying a bottom of the refuse container.

(15) In some embodiments, the lid may comprise at least one moveable member which closes the port when the port is in the closed position and which abuts a portion of the surface cleaning apparatus when the port is in the open position and the portion of the surface cleaning apparatus is positioned in the port with the dirt collection region overlying a bottom of the refuse container.

(16) In some embodiments, the lid may comprise at least one moveable member which closes the port when the port is in the closed position and which deflects inwardly into the refuse container when the port is in the open position.

(17) In some embodiments, the at least one moveable member may be biased to the closed position.

(18) In some embodiments, the at least one moveable member may comprise a plurality of sections each of which has an outer end that is located at a perimeter of the openable port and an inner end wherein, in the closed position, the sections close the port and, in the open position, at least a portion of the sections extend into the refuse container.

(19) In some embodiments, the sections may be integrally formed as part of the lid.

(20) In some embodiments, the lid may be formed of a resilient material.

(21) In some embodiments, the dirt collection region may have an openable door and a door actuator and the lid may further comprise a lid actuator that is drivingly connected to the door actuator when the dirt collection region is positioned in the port.

(22) In some embodiments the lid may further comprise a suction motor having a suction motor inlet end and a suction motor outlet end wherein, when the lid is in the closed position, the suction motor inlet end is in air flow communication with an interior volume of the refuse container and the suction motor outlet end is in air flow communication with the ambient atmosphere exterior to the refuse container.

(23) Also in accordance with this broad aspect, there is also provided a garbage can comprising a container defining an interior volume and a lid moveable between a closed position in which the lid overlies an open upper end of the container and an open position in which the container may be emptied, the lid having an openable port operable between a closed position in which the lid closes the upper end of the container and an open position in which a dirt collection region of a surface cleaning apparatus is positioned in the port.

(24) In some embodiments, in the open position, the lid may close around the dirt collection region.

(25) In some embodiments, in the open position, the port may be sized to close around the dirt collection region whereby the container is at least substantially sealed.

(26) In some embodiments, the lid may comprise at least one moveable member which closes the port when the port is in the closed position and which is positioned adjacent a portion of the surface cleaning apparatus when the port is in the open position and the portion of the surface cleaning apparatus is positioned in the port with the dirt collection region overlying a bottom of the refuse container.

(27) In some embodiments, the lid may comprise at least one moveable member which closes the port when the port is in the closed position and which abuts a portion of the surface cleaning apparatus when the port is in the open position and the portion of the surface cleaning apparatus is positioned in the port with the dirt collection region overlying a bottom of the refuse container.

(28) In some embodiments, the lid may comprise at least one moveable member which closes the port when the port is in the closed position and which deflects inwardly into the container when the port is in the open position.

(29) In some embodiments, the at least one moveable member may be biased to the closed position.

(30) In some embodiments, the at least one moveable member may comprise a plurality of sections each of which has an outer end that is located at a perimeter of the openable port and an inner end wherein, in the closed position, the sections close the port and, in the open position, at least a portion of the sections extends into the container.

(31) In some embodiments, the sections may be integrally formed as part of the lid.

(32) In some embodiments, the lid may be formed of a resilient material.

(33) In some embodiments, the dirt collection region may have an openable door and a door actuator and the lid may further comprise a lid actuator that is drivingly connected to the door actuator when the dirt collection region is positioned in the port.

(34) In some embodiments, the garbage can may further comprise a suction motor having a suction motor inlet end in air flow communication with the interior volume of the container and a suction motor outlet end is in air flow communication with the ambient atmosphere exterior to the container.

(35) In accordance with a second aspect of this disclosure, a refuse container may be provided with a suction source to draw air from the interior volume of the container, which may reduce the air pressure within the refuse container. By drawing air from the interior volume of the container some, a substantial amount of, or substantially all of the dust, allergens, or other fine particulate matter dispersed into the air in the interior volume of the container, e.g., while particulate matter is being transferred from a dirt collection region of a surface cleaning apparatus through an opening of a refuse container (e.g., an open top of the refuse container), may be drawn from the interior volume towards the suction source or may be inhibited or prevented from escaping the interior of the refuse container through the opening and thereby remain in the interior volume to settle into the refuse container. Also, fine particulate matter which may be dispersed into the air above the interior volume of the refuse container upon emptying the dirt collection region may be drawn into the interior of the refuse container and may be drawn towards the suction source.

(36) For example, a surface cleaning apparatus may have a dirt collection region or chamber that is removable from the surface cleaning apparatus, either by itself or as part of a removable air treatment assembly, such as a removable cyclone assembly. A user may detach and carry such a dirt collection region to a refuse container for emptying, and open the dirt collection region above or in an open refuse container (e.g. a refuse container whose lid has been removed), whereby gravity transfers at least some of the contents of the dirt collection region to the interior of the refuse container. However, opening the dirt collection region for emptying may result in a cloud or plume of fine dust or other particles billowing outwards from the opening of the dirt collection region and/or from the container into which the dirt collection region is being emptied. The particles in such a plume or cloud may be dispersed during the emptying process, resulting in a less than complete transfer from the dirt collection region to the interior of the refuse container. This may be considered undesirable by a user, particularly if the plume or cloud contains dust or other allergens to which the user is sensitive.

(37) By providing a suction source to draw air from the interior volume of the refuse container, some or all of a plume of fine dust or other particles generated during the emptying of a dirt collection region of a surface cleaning apparatus may be drawn into the interior of the refuse container, which may result in a more controlled transfer of the contents of the dirt collection region to the refuse container.

(38) In accordance with this second aspect, there is provided a garbage can comprising a container defining an interior volume and a lid moveable between a closed position and an open position and a suction motor having a suction motor inlet end in air flow communication with the interior volume of the container and a suction motor outlet end in air flow communication with the ambient atmosphere exterior to the container.

(39) In some embodiments, the suction source may be provided on the lid.

(40) In some embodiments, the suction source may be removably mounted to the lid.

- (41) In some embodiments, the suction source may be attached to the container.
- (42) In some embodiments, the suction source may be removably mounted to the container.
- (43) In some embodiments, the garbage can may further comprise an air flow path extending from the interior volume to a clean air outlet, the air flow path including the suction motor and an air treatment member.
- (44) In some embodiments, the air treatment member may comprise a cyclone.
- (45) In some embodiments, the garbage may further comprise a pre-motor filter positioned in the air flow path upstream of the suction motor.
- (46) In some embodiments, the garbage may further comprise a dust control member providing a dust control agent comprising one or more of a liquid mist, positive ions, and negative ions to the interior volume.
- (47) In some embodiments, the dust control agent may be provided when dirt is introduced to the interior volume.
- (48) In some embodiments, the dust control agent may be automatically provided when dirt is introduced to the interior volume.
- (49) In accordance with this second aspect of this disclosure, a lid for a refuse container may be provided with a suction source to draw in air from an area proximate the opening of the container. By drawing air from the region near the opening of the container, dust, allergens, or other fine particulate matter dispersed in the air above or in the interior volume of the container—e.g. while particulate matter is being transferred from a dirt collection region of a surface cleaning apparatus to the refuse container—may be drawn into the interior of the refuse container, or inhibited or prevented from escaping the interior of the refuse container.
- (50) In accordance with this second broad aspect, there is provided a lid for a refuse container, the lid moveable between a closed position in which the lid overlies an open upper end of the refuse container and an open position in which the refuse container may be emptied wherein, when the lid is in the closed position, the suction motor inlet end is in air flow communication with an interior volume of the refuse container and the suction motor outlet end is in air flow communication with the ambient atmosphere exterior to the refuse container.
- (51) In some embodiments, the suction source may be removably mounted to the lid.
- (52) In some embodiments, the lid may further comprise an air flow path extending from the interior volume to a clean air outlet, the air flow path including the suction motor and an air treatment member.
- (53) In some embodiments, the air treatment member may comprise a cyclone.
- (54) In some embodiments, the lid may further comprise a pre-motor filter positioned in the air flow path upstream of the suction motor.
- (55) In some embodiments, the lid may further comprise a dust control member providing a dust control agent comprising one or more of a liquid mist, positive ions and negative ions to the interior volume.
- (56) In some embodiments, the dust control agent may be provided when dirt is introduced to the interior volume.
- (57) In some embodiments, the dust control agent may be automatically provided when dirt is introduced to the interior volume.
- (58) In accordance with a third aspect of this disclosure, a cyclone assembly of a surface cleaning apparatus may have a flexible closure member for enclosing an upper end of a refuse container. By deploying the flexible closure member about the refuse container prior to opening a dirt collection region of the cyclone assembly, an enclosed volume may be provided between an openable door of the dirt collection region and the interior of the refuse container. In such an arrangement, the closure member may inhibit or prevent dust, allergens, or other particulate matter from escaping the interior of the refuse container while this particulate matter is being transferred from the dirt collection region to the refuse container.

(59) For example, a surface cleaning apparatus may have a cyclone assembly that is removable from the surface cleaning apparatus as a unit, and such a cyclone assembly may include a dirt collection region or chamber. A user may detach and carry such a cyclone assembly to a refuse container for emptying. Instead of opening the dirt collection region in the open above a refuse container or in an open refuse container and relying on gravity to transfer the contents of the dirt collection region to the interior of the refuse container, the flexible closure member may be deployed about an upper end of the refuse container before opening the dirt collection region, which may result in a more controlled transfer of the contents of the dirt collection region to the refuse container. In particular, lighter collected matter which may be entrained in the air when the dirt collection region is opened may be contained within a closed or generally closed volume and may therefore be isolated or substantially isolated for air currents which may create a fine dust plume or, if such a plume forms, it will be within the interior of the hood and therefore the plume will be contained.

(60) In accordance with this third aspect, there is provided a cyclone bin assembly for a surface cleaning apparatus, the cyclone bin assembly comprising: a dirt collection region for a cyclone, the dirt collection region having an openable door; and, a flexible closure member moveable to a deployed position wherein a first portion of the closure member is provided on the cyclone bin assembly and a second portion of the closure member closes the upper end of a refuse container, whereby when the closure member is in the deployed position, a closed volume is provided which includes an interior volume of the refuse container and the openable door is located in the closed volume.

(61) In some embodiments, the flexible closure member may be mounted to an exterior surface of the cyclone bin assembly.

(62) In some embodiments, the flexible closure member may be air impermeable.

(63) In some embodiments, the closure member may be removably mountable to the cyclone bin assembly.

(64) In some embodiments, the closure member may be moveable to a retracted position in which the second portion of the closure member is retracted and secured to the cyclone bin assembly.

(65) In some embodiments, the second portion of the closure member may have a securing member which retains the second portion on the refuse container when the flexible closure member is in the deployed position.

(66) In some embodiments, the securing member may comprise at least one of a resilient member and a drawstring.

(67) In some embodiments, the flexible closure member may comprise a hood.

(68) In some embodiments, the cyclone bin assembly may further comprise an actuator for the openable door and, when the flexible closure member is in the deployed position, the actuator is exterior to the closed volume.

(69) In accordance with this third aspect, there is also provided a dirt collection system comprising: a cyclone bin assembly comprising: a dirt collection region for a cyclone, the dirt collection region having an openable door; and, a flexible closure member moveable to a deployed position wherein a first portion of the closure member is provided on the cyclone bin assembly and a second portion of the closure member closes the upper end of a refuse container, whereby when the closure member is in the deployed position, a closed volume is provided which includes an interior volume of the refuse container and the openable door is located in the closed volume; and, a refuse container comprising a suction motor having a suction motor inlet end in air flow communication with the interior volume of the refuse container and a suction motor outlet end in air flow communication with the ambient atmosphere exterior to the refuse container.

(70) In accordance with this third aspect, there is also provided a dirt collection apparatus comprising: a dirt collection region having an openable door; and, a flexible closure member moveable to a deployed position wherein a first portion of the closure member is provided on the

dirt collection apparatus and a second portion of the closure member closes the upper end of a refuse container, whereby when the closure member is in the closed position, a closed volume is provided which includes an interior volume of the refuse container and the openable door is located in the closed volume.

(71) In some embodiments, the flexible closure member may be mounted to an exterior surface of the dirt collection apparatus.

(72) In some embodiments, the flexible closure member may be air impermeable.

(73) In some embodiments, the closure member may be removably mountable to the cyclone bin assembly.

(74) In some embodiments, the closure member may be moveable to a retracted position in which the second portion of the closure member is retracted and secured to the dirt collection apparatus.

(75) In some embodiments, the second portion of the closure member may have a securing member which retains the second portion on the refuse container when the flexible closure member is in the deployed position.

(76) In some embodiments, the securing member may comprise at least one of a resilient member and a drawstring.

(77) In some embodiments, the flexible closure member may comprise a hood.

(78) In some embodiments, the dirt collection apparatus may further comprise an actuator for the openable door and, when the flexible closure member is in the deployed position, the actuator is exterior to the closed volume.

(79) In accordance with this third aspect, there is also provided a dirt collection system comprising: a dirt collection apparatus comprising: a dirt collection region having an openable door; and, a flexible closure member moveable to a deployed position wherein a first portion of the closure member is provided on the dirt collection apparatus and a second portion of the closure member closes the upper end of a refuse container, whereby when the closure member is in the closed position, a closed volume is provided which includes an interior volume of the refuse container and the openable door is located in the closed volume; and, a refuse container comprising a suction motor having a suction motor inlet end in air flow communication with the interior volume of the refuse container and a suction motor outlet end in air flow communication with the ambient atmosphere exterior to the refuse container.

(80) In accordance with a fourth aspect of this disclosure, a refuse container may be provided with a dust control system to provide a dust control agent towards the interior volume of the refuse container, and/or towards an area above the interior volume of the refuse container, e.g., below a dirt emptying outlet of a dirt collection region of a surface treatment apparatus. By providing a dust control agent into or above the interior volume of the container, the dispersal of dust, allergens, or other fine particulate matter into the air, e.g. while particulate matter is being transferred from a dirt collection region of a surface cleaning apparatus to the refuse container, may be inhibited or prevented. For example, by wetting the particulate matter, the particulate matter will be heavier and less likely to form a dust plume. Alternatively, the particulate matter may acquire a charge during the passage through a cyclone. By at least partially neutralizing any such a charge that the particulate matter may acquire, the particulate matter will be less likely to spread out and form a dust plume when the particulate matter exits a dirt collection region.

(81) Alternatively, or additionally, the refuse container may be provided with a treatment applicator to provide a treatment agent (e.g. a deodorizing agent, a disinfecting agent, a sanitizing agent) to an interior volume of the refuse container. By providing such a treatment agent, one or more negative aspects of dust, allergens, or other particulate matter located in the interior volume of the container, e.g. unpleasant odor, possible bacterial or microbial growth, may be inhibited or eliminated.

(82) Also in accordance with this fourth aspect, a surface treatment apparatus may be provided with a dust control system to provide a dust control agent towards an openable door of a dirt collection region of the surface cleaning apparatus, and/or towards an area proximate the openable door. By

providing a dust control agent towards an openable door of a dirt collection region, the dispersal of dust, allergens, or other fine particulate matter into the air when the openable door is opened, e.g. while particulate matter is being transferred from the dirt collection region to a refuse container, may be inhibited or prevented.

(83) Alternatively, or additionally, the surface treatment apparatus may be provided with a treatment applicator to provide a treatment agent (e.g. a deodorizing agent, a disinfecting agent, a sanitizing agent) to an interior volume of an air treatment member of the surface treatment apparatus (e.g. a dirt collection region). By providing such a treatment agent, one or more negative aspects of dust, allergens, or other particulate matter located in the interior volume of the air treatment member, e.g. unpleasant odor, possible bacterial or microbial growth, may be inhibited or eliminated.

(84) In accordance with this fourth aspect, there is provided an apparatus comprising one or more of a surface treatment apparatus having an air treatment member and a refuse container wherein at least one of the surface treatment apparatus and the refuse container comprises one or more of: a) a dust control member providing a dust control agent comprising one or more of a liquid mist, positive ions, and negative ions to an area below a dirt emptying outlet of a dirt collection region of the surface treatment apparatus; and, b) a treatment applicator providing a treatment agent comprising one or more of a deodorizing agent, a disinfecting agent, and a sanitizing agent to an interior volume of the air treatment member and an interior volume of the refuse container.

(85) In some embodiments, the one of the surface treatment apparatus and the refuse container may comprise both the dust control member and the treatment applicator.

(86) In some embodiments, the dust control member may comprise one or more nozzles directed to the area below the dirt emptying outlet of the dirt collection region of the surface treatment apparatus.

(87) In some embodiments, the nozzles may introduce the dust control agent to a location below the dirt emptying outlet and above the bottom of the refuse container.

(88) In some embodiments, the apparatus may further comprise a hood which, when the dirt emptying outlet is open and the hood is in a deployed position, a closed volume is provided that includes the interior volume of the refuse container and an interior volume of the dirt collection region and the nozzles introduce the dust control agent into the closed volume.

(89) In some embodiments, the surface cleaning apparatus may comprise a dirt separation member having the dirt emptying outlet and the nozzles are located around at least part of the perimeter of the dirt separation member.

(90) In some embodiments, the nozzles may be provided on the refuse container.

(91) In some embodiments, the dust control member may be automatically actuated when the dirt emptying outlet is opened.

(92) In some embodiments, the dust control member may be automatically actuated prior to the dirt emptying outlet being opened.

(93) In some embodiments, the one of the surface treatment apparatus and the refuse container which has the dust control member may further comprise a dust control agent reservoir.

(94) In some embodiments, the refuse container may further comprise a suction motor having a suction motor inlet end in air flow communication with the interior volume of the refuse container and a suction motor outlet end in air flow communication with the ambient atmosphere exterior to the refuse container.

(95) In some embodiments, the apparatus may further comprise an air flow path extending from the interior volume to a clean air outlet, the air flow path including the suction motor and a refuse container air treatment member.

(96) In some embodiments, the refuse container air treatment member may comprise a cyclone.

(97) In some embodiments, the apparatus may further comprise a pre-motor filter positioned in the air flow path upstream of the suction motor.

(98) In some embodiments, the treatment agent may comprise one or more of ozone, UV light, and hydrogen peroxide.

(99) In some embodiments, the treatment agent may comprise ozone and the refuse container further comprises an air flow path extending from the interior volume of the refuse container to a clean air outlet, the air flow path including the suction motor and an ozone destructor material.

(100) In some embodiments, the apparatus may further comprise a hood which, when the dirt emptying outlet is open and the hood is in a deployed position, a closed volume is provided that includes the interior volume of the refuse container and an interior volume of the dirt collection region and the treatment agent is introduced into the closed volume.

(101) In some embodiments, the treatment agent may be provided at pre-set intervals.

(102) In some embodiments, the treatment agent may be provided after a pre-set number of uses of the surface cleaning apparatus.

(103) In some embodiments, the treatment agent may be provided by manual activation.

(104) In some embodiments, the treatment agent may be provided subsequent to emptying of the dirt collection region.

(105) In accordance with a fifth aspect of this disclosure, a surface cleaning apparatus may be configured to selectively draw air from a dirt collection region of the surface cleaning apparatus, such that air pressure in the dirt collection region may be reduced below the pressure of the ambient atmosphere when an openable door of the dirt collection region is in an open position. By drawing air from the interior volume of the dirt collection region, the dispersal of dust, allergens, or other fine particulate matter into the air when the openable door is opened, e.g. while particulate matter is being transferred from the dirt collection region to a refuse container, may be inhibited or prevented. For example, air may be drawn directly from a dirt chamber and/or from a cyclone which is in air flow communication with a dirt chamber via a cyclone chamber dirt outlet. The air may be drawn towards a suction motor and may be filtered before and/or after passage by or through the suction motor. The suction motor may be the same suction motor as used to clean a surface and/or a separate suction motor.

(106) For example, a surface cleaning apparatus may have a cyclone assembly that includes a dirt collection region or chamber having an openable door. A user may position such a cyclone assembly above a refuse container for emptying. Prior to or while or after opening the door of the dirt collection region, the air pressure in the dirt collection region may be reduced to below that of the ambient air, which may result in a net inflow of air into the dirt collection region, thereby drawing finer dust, allergens, or other fine particulate matter towards the dirt collection region and/or maintaining finer dust, allergens, or other fine particulate matter in the dirt collection region. Accordingly, emptying of the dirt collection region may result in no dust plume, or a reduced dust plume, being formed in the air which may fall outside a refuse container. For example, larger dirt particles collected in the dirt collection region may be directed by gravity to the interior of the refuse container, while some or all of the finer dust or other smaller particles that may have otherwise formed a cloud or plume billowing outwards from the opening of the dirt collection region may be drawn towards the opening of the dirt collection region.

(107) In accordance with this fifth aspect, there is provided a surface cleaning apparatus comprising: a) an air flow path extending from a dirty air inlet to a clean air outlet and comprising a main air treatment member having a dirt collection region having an openable door; and, b) a main suction motor provided in the air flow path, wherein the dirt collection region is exposed to sub-atmospheric pressure when the openable door is in an open position.

(108) In some embodiments, the dirt collection region may be automatically exposed to sub-atmospheric pressure when the openable door is opened.

(109) In some embodiments, the dirt collection region may be automatically exposed to sub-atmospheric pressure prior to the openable door opening.

(110) In some embodiments, the main suction motor may be utilized to provide the sub-

atmospheric pressure to the dirt collection chamber.

(111) In some embodiments, the main suction motor may be operable in a cleaning mode in which the main suction motor is used to draw air from the dirty air inlet, through the main air treatment member to the clean air outlet and an emptying mode in which the main suction motor is utilized to provide the sub-atmospheric pressure to the dirt collection chamber and the main suction motor is operated at a lower power level during the emptying mode.

(112) In some embodiments, the main suction motor may produce sufficient suction to create an air flow of 0.1 Cubic Feet per Minute (CFM) to 1.5 CFM per square inch of opening area during the emptying mode, preferably 0.25 CFM to 1.25 CFM per square inch of opening during the emptying mode and more preferably 0.50 CFM to 1.00 CFM per square inch of opening area during the emptying mode.

(113) In some embodiments, the main suction motor may be operable in a cleaning mode in which the main suction motor is used to draw air from the dirty air inlet, through the main air treatment member to the clean air outlet and an emptying mode in which the main suction motor is utilized to provide the sub-atmospheric pressure to the dirt collection chamber, wherein a first pre-motor filter is positioned in a main downstream portion of the air flow path from the main air treatment member to the main suction motor during the cleaning mode and an alternate air treatment member is provided in an alternate downstream air flow path from the main air treatment member to the main suction motor during the emptying mode.

(114) In some embodiments, the surface cleaning apparatus may further comprise a main closure member associated with the main downstream portion of the air flow path and an alternate closure member associated with the alternate downstream air flow path, each of the main closure member and the alternate closure member moveable between an open position and a closed position wherein, during the cleaning mode, the main closure member is open and the alternate closure member is closed whereby the main suction motor is in air flow communication with the main air treatment member via the main downstream portion of the air flow path and in the emptying mode the main closure member is closed and the alternate closure member is open whereby the main suction motor is in air flow communication with the main air treatment member via the alternate downstream air flow path.

(115) In some embodiments, the alternate air treatment member may comprise a filter.

(116) In some embodiments, the surface cleaning apparatus may further comprise an emptying mode suction motor which provides the sub-atmospheric pressure to the dirt collection chamber.

(117) In some embodiments, the emptying mode suction motor may produce a sub-atmospheric pressure less than a pressure in the main air treatment member during operation of the main suction motor.

(118) In some embodiments, the main suction motor may produce sufficient suction to create an air flow of 0.1 CFM to 1.5 CFM per square inch of opening area during the emptying mode, preferably 0.25 CFM to 1.25 CFM per square inch of opening during the emptying mode and more preferably 0.50 CFM to 1.00 CFM per square inch of opening area during the emptying mode.

(119) In some embodiments, a portion of the air flow path may connect the emptying mode suction motor in air flow communication with the dirt collection region during an emptying mode of the dirt collection region.

(120) In some embodiments, the portion of the air flow path may be positioned upstream of the main air treatment member.

(121) In some embodiments, an emptying mode air treatment member may be positioned in the portion of the air flow path.

(122) In some embodiments, the surface cleaning apparatus may comprise a main closure member associated with the portion of the air flow path the main closure member being moveable between an open position and a closed position wherein, during the cleaning mode, the main closure member is closed whereby air travels from the dirty air inlet to the main air treatment member

without contacting the emptying mode air treatment member and, in the emptying mode the main closure member is opened whereby air travels from the main air treatment member and through the emptying mode air treatment member.

(123) In some embodiments, the emptying mode air treatment member may comprise a filter.

(124) In some embodiments, the main air treatment member may comprise a cyclone.

(125) In some embodiments, the dirt collection region may comprise a dirt collection chamber exterior to the cyclone.

(126) It will be appreciated by a person skilled in the art that an apparatus or method disclosed herein may embody any one or more of the features contained herein and that the features may be used in any particular combination or sub-combination.

(127) These and other aspects and features of various embodiments will be described in greater detail below.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) For a better understanding of the described embodiments and to show more clearly how they may be carried into effect, reference will now be made, by way of example, to the accompanying drawings in which:

(2) FIG. 1 is a perspective view of a container and a lid having an openable port in accordance with one embodiment;

(3) FIG. 2 is a perspective view of the container and lid of FIG. 1 with the lid in an open position and overlying the open interior of the container;

(4) FIG. 3 is a top view of the lid of FIG. 1, with the openable port in a closed position;

(5) FIG. 4 is a top view of the lid of FIG. 1, with the openable port in an open position;

(6) FIG. 5 is a cross section view of the container and lid of FIG. 1, taken along line 5-5, with the openable port in a closed position;

(7) FIG. 6 is a cross section view of the container and lid of FIG. 5, with a cyclone dirt bin positioned in the openable port, the cyclone dirt bin being in a closed configuration;

(8) FIG. 7 is a cross section view of the container and lid of FIG. 5, with a cyclone dirt bin positioned in the openable port, the cyclone dirt bin being in an open configuration;

(9) FIG. 8 is a top view of the lid of FIG. 1, with a cyclone dirt bin positioned in the openable port;

(10) FIG. 9 is a cross section view of a container and lid according to another embodiment, with a lid actuator drivingly connected to a door actuator of a cyclone dirt bin positioned in an openable port of the lid;

(11) FIG. 10 is a perspective view of a container, a first lid having an open port, a second lid in a removed position, and a suction source in accordance with one embodiment;

(12) FIG. 11 is a cross section view of the container and first lid of FIG. 10, taken along line 11-11, with a cyclone dirt bin positioned above the container, the cyclone dirt bin being in a closed configuration;

(13) FIG. 12 is a cross section view of the container and first lid of FIG. 11, with the cyclone dirt bin in an open configuration, and with the suction source drawing air from the interior volume of the container;

(14) FIG. 13A is a cross section view of a container, a first lid having an open port and a suction source, and a second lid in a removed position in accordance with another embodiment;

(15) FIG. 13B is a cross section view of the first lid and suction source of FIG. 13A;

(16) FIG. 14 is a perspective view of a container, a first lid having an open port, and a cyclone bin assembly having a deployable closure member in accordance with one embodiment;

(17) FIG. 15 is a cross section view of a container, a first lid having an open port, and a cyclone bin

assembly having a deployable closure member in accordance with another embodiment, the cyclone bin assembly being in a closed configuration;

(18) FIG. **16** is a cross section view of the container, first lid, cyclone bin assembly, and deployable closure member of FIG. **15**, with the cyclone bin assembly in an open configuration;

(19) FIG. **17** is a cross section view of a container, a first lid having an open port, a cyclone bin assembly having a deployable closure member in accordance with another embodiment, the cyclone bin assembly being in an open configuration;

(20) FIG. **18** is a perspective view of a container and a first lid having an open port and a dust control member providing a dust control agent according to one embodiment;

(21) FIG. **19** is a bottom view of the lid of FIG. **18**;

(22) FIG. **20** is a cross section view of a container and first lid having an open port according to another embodiment, with the lid having first and second dust control members for providing dust control agents, with a cyclone dirt bin positioned above the container, the cyclone dirt bin being in a closed configuration;

(23) FIG. **21** is a cross section view of the container and first lid of FIG. **20**, with the cyclone dirt bin in an open configuration, and with the first and second dust control members providing dust control agents;

(24) FIG. **22** is a perspective view of a cyclone bin assembly having a dust control member for providing a dust control agent according to one embodiment;

(25) FIG. **23** is a cross section view of a cyclone bin assembly having a dust control member for providing a dust control agent according to another embodiment, the cyclone dirt bin being in a closed configuration;

(26) FIG. **24** is a cross section view of the cyclone bin assembly of FIG. **23**, with the cyclone dirt bin in an open configuration, and with the dust control member providing a dust control agent;

(27) FIG. **25** is a cross section view of a cyclone bin assembly having a dust control member for providing a dust control agent according to another embodiment, the dust control member being configured to automatically provide a dust control agent when an openable door of a dirt collection region is opened;

(28) FIG. **26** is a cross section view of a cyclone bin assembly having a dust control member for providing a dust control agent according to another embodiment, the dust control member being configured to automatically provide a dust control agent and subsequently open an openable door of a dirt collection region;

(29) FIG. **27** is a cross section view of a container, a lid, and a suction source according to another embodiment, with an ozone gas emitter provided on an interior wall of the container, and with a UV light source provided on the lid;

(30) FIG. **28** is a cross section view of cyclone bin assembly according to another embodiment, with a UV light source and an ozone gas emitter provided in the dirt collection region, and with a suction source and ozone destructor material;

(31) FIG. **29** is a schematic cross-section view of a cyclone bin assembly according to another embodiment, with conduit and a valve to direct suction from a suction source for selectively drawing air out of the cyclone bin assembly via the cyclone dirty air inlet or via the cyclone air outlet, with an openable door of a dirt collection region being in a closed configuration, and with the suction source drawing air out of the cyclone bin assembly via the cyclone air outlet;

(32) FIG. **30** is a schematic cross-section view of the cyclone bin assembly of FIG. **29**, with the openable door in an open configuration, and with the suction source drawing air out of the cyclone bin assembly via the cyclone dirty air inlet;

(33) FIG. **31** is a schematic cross-section view of a cyclone bin assembly according to another embodiment, with an auxiliary suction source for drawing air out of the cyclone bin assembly via the cyclone dirty air inlet, with an openable door of a dirt collection region being in a closed configuration, and with the suction source drawing air out of the cyclone bin assembly via the

cyclone air outlet; and

(34) FIG. 32 is a schematic cross-section view of a cyclone bin assembly according to another embodiment, with a valve to direct suction from a suction source for selectively drawing air out of the cyclone bin assembly via the cyclone air outlet and an auxiliary cyclone air outlet proximate the cyclone dirty air inlet, with an openable door of a dirt collection region being in an open configuration, and with the suction source drawing air out of the cyclone bin assembly via the auxiliary cyclone air outlet.

(35) The drawings included herewith are for illustrating various examples of articles, methods, and apparatuses of the teaching of the present specification and are not intended to limit the scope of what is taught in any way.

DESCRIPTION OF EXAMPLE EMBODIMENTS

(36) Various apparatuses, methods and compositions are described below to provide an example of an embodiment of each claimed invention. No embodiment described below limits any claimed invention and any claimed invention may cover apparatuses and methods that differ from those described below. The claimed inventions are not limited to apparatuses, methods and compositions having all of the features of any one apparatus, method or composition described below or to features common to multiple or all of the apparatuses, methods or compositions described below. It is possible that an apparatus, method or composition described below is not an embodiment of any claimed invention. Any invention disclosed in an apparatus, method or composition described below that is not claimed in this document may be the subject matter of another protective instrument, for example, a continuing patent application, and the applicant(s), inventor(s) and/or owner(s) do not intend to abandon, disclaim, or dedicate to the public any such invention by its disclosure in this document.

(37) Furthermore, it will be appreciated that for simplicity and clarity of illustration, where considered appropriate, reference numerals may be repeated among the figures to indicate corresponding or analogous elements. In addition, numerous specific details are set forth in order to provide a thorough understanding of the example embodiments described herein. However, it will be understood by those of ordinary skill in the art that the example embodiments described herein may be practiced without these specific details. In other instances, well-known methods, procedures, and components have not been described in detail so as not to obscure the example embodiments described herein. Also, the description is not to be considered as limiting the scope of the example embodiments described herein.

(38) The terms “an embodiment,” “embodiment,” “embodiments,” “the embodiment,” “the embodiments,” “one or more embodiments,” “some embodiments,” and “one embodiment” mean “one or more (but not all) embodiments of the present invention(s),” unless expressly specified otherwise.

(39) The terms “including,” “comprising,” and variations thereof mean “including but not limited to,” unless expressly specified otherwise. A listing of items does not imply that any or all of the items are mutually exclusive, unless expressly specified otherwise. The terms “a,” “an,” and “the” mean “one or more,” unless expressly specified otherwise.

(40) In the examples discussed herein, the dirt collection region (or dirt collection chamber) from which dust, allergens, or other particulate matter may be transferred to a refuse container or other receptacle may be associated with any suitable type of surface cleaning apparatus, such as an upright vacuum cleaner, a canister type vacuum cleaner, a hand vacuum cleaner, a stick vacuum cleaner, a wet-dry type vacuum cleaner, a carpet extractor, and the like.

(41) The flowing is a general description of a garbage can which may be used with any aspect of this disclosure.

(42) Referring to FIGS. 1-8, a container 20 and a lid 100 are shown generally and collectively as 10. Container 20 may be referred to as a refuse container, and the container 20 and lid 100 may be referred to collectively as a garbage can. The container 20 includes an upper end 24 and a closed

lower end **22**, and a sidewall **26** extending between the lower and upper ends **22**, **24**. Sidewall **26** and lower end **22** define an interior volume **28** of the container **20**. The lid **100** is configured to rest on or engage with the upper end **24** of container **20**, such that the lid overlies all or substantially all of upper end **24**. In such a closed configuration, lid **100** inhibits or prevents access to the interior volume **28** of container **20**. Lid **100** is preferably removable from refuse container **20**, to e.g. facilitate emptying of the container. It will be appreciated that container **20** and a lid **100** may be of any configuration known in the art and may be lockingly secured to each other by any means known in the art.

(43) In the examples discussed herein, dust, allergens, or other particulate matter are described as being transferred into interior volume **28** of refuse container **20**. It will be appreciated that a secondary container, such as a refuse or garbage bag (e.g. a plastic or paper container, which may be characterized as a disposable container) may be removably positioned in refuse container **20**, e.g. lining all or substantially all of the interior volume **28**. For example, an upper portion of a secondary container may be positioned between container **20** and lid **100**, with a lower portion of the secondary container positioned adjacent or in abutment with lower end **22** of container **20**. In such an arrangement, refuse deposited into the container **20** is actually deposited into the secondary container, and the secondary container may be periodically removed from container **20** to transfer the collected refuse to e.g. a larger household refuse container, such as a container from which a municipality or other service provider may collect refuse for transport to a landfill, an incinerator, and the like.

(44) As exemplified in FIGS. **1-8**, lid **100** has an upper surface **104** and a lower surface **102**. The lower surface **102** is configured to overlie upper end **24** of container **20**, in order to substantially or entirely enclose interior volume **28** of container **20**. For example, as exemplified in FIG. **5**, lower surface **102** may have a channel **108** that is dimensioned to overlie and engage with the sidewall **26** at the upper end **24** of container **20**. Alternatively, the lower surface **102** and/or the upper end **24** may be provided in another configuration for cooperative engagement, for example upper end **24** may have a channel in the top surface of sidewall **26** and lower surface **102** may have a one or more downwardly extending projections for engaging such a channel.

(45) In some of the embodiment disclosed herein, the lid may include an operating component and/or part of a fluid flow passage and/or an ion emitter. In such a case, a two part lid system may be used. In such a case, as exemplified in FIG. **10**, the lid for the container **20** may comprise a first lid **100** and a second lid **5**. In FIG. **10**, a second or upper lid **5** is also shown in a removed position. Upper lid **5** is configured to rest on or engage with the upper surface **104** of lid **100**, such that the second lid **5** overlies all or substantially all of port **110**. Lid **5** is preferably removable from lid **100**. In the illustrated embodiment, lid **5** has a handle **7**, although such a handle may not be provided in alternative embodiments.

(46) In some embodiments, second or upper lid **5** may also be configured to rest on or engage with the upper end **24** of container **20**, such that the lid overlies all or substantially all of upper end **24**. For example, second lid **5** and container **20** may have been purchased or otherwise acquired as a set, and first or inner lid **100** may be configured to act as a retrofit or to otherwise provide some or all of the dust control features and/or functionality as disclosed herein.

(47) An advantage of using a second lid **5** is that an operating component and/or part of a fluid flow passage and/or an ion emitter need not be provided with container **20**. Instead, they may be provided in or on or as part of the lid. When the container is to be emptied, first lid **100** may be removed and second lid **5** used to close container **20**. Container **20** may then be taken to the end of a driveway to be emptied by a municipal garbage service without concern that an operating component and/or part of a fluid flow passage and/or an ion emitter may be damaged by workers when emptying container **20**.

(48) Refuse Container Lid Having an Openable Port

(49) The following is a general description of a lid for a refuse container having an openable port

and other features set out herein that may be used by itself or in combination with one or more embodiments disclosed herein, including one or more of a refuse container having a suction source, a cyclone bin assembly having a deployable closure member, dust control systems for refuse containers or surface treatment apparatus, and dust treatment systems for refuse containers or surface treatment apparatus. The following description contains various features of a lid for a refuse container having an openable port that may be used individually or in any combination or sub-combination.

(50) In accordance with this aspect, lid **100** has an aperture or port **110** extending between upper surface **104** and lower surface **102**. Port **110** is operable between a closed position in which particulate matter (e.g. dirt, dust, allergens, and the like) is inhibited or preferably prevented from passing through port **110**, and an open position. Preferably, a closure member of port **110** is biased towards the closed position. It will be appreciated that port **110** may occupy part or all of lid **100** other than the portion of lid that seats on refuse container **20**. It will be appreciated that

(51) In the illustrated example, a number of moveable members or flanges **120** are provided on the interior perimeter of port **110**. Each moveable flange **120** extends inwardly from an outer end **122** towards an inner end **124** located at or proximate the center of port **110**, and the members **120** are dimensioned such that when the members are each substantially parallel to lid **100**, the aperture or port **110** is substantially or preferably completely closed by the flanges **120**. Preferably, flanges **120** are flexible, and may be resiliently biased towards a closed position, e.g., a position in which the members are substantially parallel to the remainder of the horizontally extending portion of lid **100**.

(52) Alternatively, the moveable members or flanges may be of any other suitable configuration, including, for example a configuration in which the members open like an iris, a sliding panel or the like.

(53) Moveable members or flanges **120** may be secured to lid **100** using any suitable method, such as using one or more mechanical fasteners, an adhesive, or the like. Alternatively, the lid **100** and flanges **120** may be integrally formed, e.g. via injection molding.

(54) The operation of lid **100** in controlling dust, allergens, and other particulate matter when emptying a dirt collection region of a surface cleaning apparatus will now be discussed with reference to FIGS. 5-8.

(55) In FIG. 5, lid **100** is resting on and overlying upper end **24** of container **20**. Flanges **120** are substantially parallel to lid **100**, cooperatively closing port **110** in lid **100**.

(56) In FIGS. 6 and 8, a cyclone bin assembly **30** for a surface cleaning apparatus has been positioned in port **110**. Cyclone bin assembly **30** includes an air treatment member, in this case a cyclone **31**, and a dirt collection region **38** for collecting particulate matter dis-entrained from a dirty airflow by cyclone **31**. A handle **33** is provided at an upper end **34** of the cyclone bin assembly. Cyclone bin assembly **30** has an openable lower end **32** releasably secured by a door closure member **37**. A door release switch or actuator **35** is positioned external to the garbage can so it is operable by a user when the cyclone bin assembly **30** has been inserted into port **110** into an emptying position. Switch **35** is operatively connected to door closure member **37**. As exemplified, switch **35** is provided adjacent handle **33** and is drivingly coupled to door closure member **37** via door actuator **39**. It will be appreciated that switch **35** may be operatively connected to door closure member **37** by any other mechanical drive member or may be electrically connected thereto or wirelessly operatively connected thereto.

(57) In the illustrated embodiment, inserting cyclone bin assembly **30** in port **110** results in flanges **120** being deflected towards the lower end **22** of container **20** by contact with the cyclone bin assembly **30**. At least the inner ends **124** of each flange **120** are displaced into the interior volume **28** of container **20**. Preferably, flanges **120** are configured such that at least a portion of each inner end **124** remains in contact or proximate an outer sidewall **36** of cyclone bin assembly **30**, thereby forming at least a substantial if not a complete seal about cyclone bin assembly **30**, to inhibit or prevent dust, allergens, and other particulate matter from exiting container **20**. Optionally, if port

110 is sized to be slightly larger in diameter than the cyclone bin assembly or the dirt collection region inserted into port **110**, then flanges **120** may contact most of the perimeter of the cyclone bin assembly or the dirt collection region.

(58) In FIG. 7, openable lower end **32** of cyclone bin assembly **30** has been moved into an open position. For example, door release switch **35** may have been deflected or rotated (e.g. by a user's thumb), resulting in a deflection or rotation of door closure member **37**, whereby openable lower end **32** was released and moved to an open position, e.g. due to gravity or one or more biasing members (not shown).

(59) As discussed previously with reference to FIG. 6, lid **100** and the substantial if not complete seal provided by flanges **120** about the outer sidewall **36** of cyclone bin assembly **30** may act to inhibit or prevent dust, allergens, and other particulate matter from exiting container **20** during transfer of such particles from dirt collection region **38** to the interior volume **28** of container **20**.

(60) FIG. 9 exemplifies an alternative embodiment of a lid, referred to generally as **100'**, with an alternative design of cyclone bin assembly **30'** positioned in port **110** of lid **100'**. The embodiment of lid **100'** shown in FIG. 9 includes a lid actuator for actuating a door closure member of a cyclone bin assembly when the cyclone bin assembly has been positioned in port **110** of lid **100'**, but is otherwise similar to lid **100** shown in FIG. 7.

(61) In the example cyclone bin assembly **30'** shown in FIG. 9, a door release switch need not be provided proximate the upper end of the cyclone bin assembly. Instead, the door closure member **37'** may be configured to be moved, e.g., deflected or rotated once the cyclone bin assembly has been inserted into port **110**, thereby releasing openable lower end **32** into a closed or essentially closed volume. Otherwise, the example cyclone bin assembly **30'** shown in FIG. 9 is similar to cyclone bin assembly **30** shown in FIG. 7.

(62) As exemplified in FIG. 9, when cyclone bin assembly **30'** is positioned in port **110**, flanges **120** are configured such that at least a portion of each inner end **124** remains in contact or proximate an outer sidewall **36** of cyclone bin assembly **30'**, thereby forming at least a substantial if not a complete seal about cyclone bin assembly **30'**, to inhibit or prevent dust, allergens, and other particulate matter from exiting container **20**. However, in this illustrated configuration the door closure member **37'** is positioned below flanges **120**, which may inhibit or prevent a user from releasing openable lower end **32** when cyclone bin assembly **30'** is positioned in port **110**. To address this potential issue, lid **100'** is provided with a lid actuator **130**.

(63) Lid actuator **130** has an upper end **132** operable by a user from the exterior of the refuse container. As exemplified, lid actuator **130** projects upwardly from, e.g., top surface **104** of lid **100'**, and a lower end **134** is positioned in the interior volume **28** and below the lower surface **102** of lid **100'**. In the illustrated example, lid actuator is pivotally secured to lid **100'** by a shaft or other pivoting coupling **136**. In this arrangement, the upper end **132** of lid actuator **130** may be manipulated by a user to cause the lower end **134** to drivingly engage and thereby actuate the door closure member **37'** of cyclone bin assembly **30'** to release openable lower end **32** when the bin assembly has been positioned in port **110**.

(64) Alternatively, the lid actuator may be of any other suitable configuration, including, for example a configuration in which the actuator is provided in a sidewall of the garbage can and inwardly slideable to actuate door closure member **37'**.

(65) It will be appreciated that in this aspect, and other aspects, of this disclosure cyclone bin assembly **30** may be of any design and may be an air treatment member of any type and need not be cyclonic. Further, instead of inserting part or all of an air treatment member (such as cyclone bin assembly **30**) into port **110**, the dirt collection region may comprise a dirt collection chamber that is external to the air treatment member, e.g., a cyclone chamber, and the dirt collection region may be removed from the rest of the air treatment member and part of all of it may be inserted into port **110** in order to empty the dirt collection chamber.

(66) Refuse Container with Sub-Atmospheric Pressure Mode

(67) The following is a general description of a refuse container having a suction source and other features set out herein that may be used by itself or in combination with one or more embodiments disclosed herein, including one or more of a lid for a refuse container having an openable port, dust control systems for refuse containers or surface treatment apparatus, and dust treatment systems for refuse containers or surface treatment apparatus. The following description contains various features of a refuse container having a suction source which may be used individually or in any combination or sub-combination.

(68) In accordance with this aspect, a sub atmospheric is used to inhibit, substantially prevent or essentially prevent a dust plume of lighter dirt particles forming in the ambient air when the dirt collection region is emptied. For example, a suction motor may be used to draw air from the interior of a refuse container or the ambient air above or immediately above the refuse container. This will create a flow of air, e.g., into the refuse container if the suction motor is in communication with the interior of the refuse container, or into one or more inlet ports if the suction motor is in communication with the air above the refuse container, which may partially or substantially entrain the lighter dust that would otherwise form a dust plume. Accordingly, a smaller dust plume or essentially no dust plume may be formed.

(69) In the examples illustrated in FIGS. **10-12**, a suction source, referred to generally as **220**, is provided on the refuse container and may be permanently mounted thereto or may be removable mounted. In the latter case, the suction source may be removed before a garbage can is taken to, e.g., the end of a drive way to be emptied into a garbage truck. By providing a suction source to draw air from the interior volume of the refuse container, some or all of a plume of fine dust or other particles generated during the emptying of a dirt collection region of a surface cleaning apparatus may be drawn into the interior of the refuse container, which may result in a more controlled transfer of the contents of the dirt collection region to the refuse container. By making the suction source **220** removable, damage to suction source **220** may be avoided when the garbage can is emptied.

(70) Suction source **220** includes a suction motor **206** drivingly connected to a suction fan **204** for drawing air from the interior volume **28** of container **20**, either directly or via an optional air treatment member **210**. An optional pre-motor filter **202** is shown upstream of suction motor **206**, and an optional post-motor filter **208** is shown downstream of suction motor **206** and upstream of a clean air outlet. It will be appreciated that one or both of these filters may not be provided in alternative embodiments.

(71) In the illustrated configuration, an upstream or inlet end of suction source **220** is in airflow communication with the interior volume **28** via an inlet **212** provided in the sidewall **26** of container **20**. An optional air treatment member **210** is provided downstream of inlet **212**. In the illustrated example, air treatment member **210** is a cyclonic air treatment member, and has a cyclone **211** in fluid communication with the interior volume **28** of container **20** via inlet **212**. A dirt collection region **218** is provided to collect particles dis-entrained from air drawn through inlet **212** by cyclone **211**. Air treatment member **210** also has an outlet **214** in fluid communication with suction fan **204**. Alternatively, or additionally, the air treatment member may comprise a bag, a filter, an additional cyclonic cleaning stage and/or other air treatment known in the art.

(72) In the illustrated examples, inlet **212** is provided proximate the upper end **24** of container **20**. Alternatively, inlet **212** may be provided proximate the lower end **22** of container **20**, or between the upper and lower ends **24**, **22**.

(73) Also, in the illustrated examples a single inlet **212** is provided. Alternatively, two or more inlets **212** may be provided. In some embodiments, a manifold may be provided between two or more inlets **212** and the suction fan **204**. For example, two or more inlets **212** may converge at or before the inlet to optional air treatment member **210**.

(74) The operation of suction source **220** in controlling dust, allergens, and other particulate matter when emptying a dirt collection region of a surface cleaning apparatus will now be discussed with

reference to FIGS. **11** and **12**.

(75) In FIG. **11**, a cyclone bin assembly **30'** for a surface cleaning apparatus has been positioned above port **110**. For example, a user may have detached and carried such a dirt collection region to such a position. Alternatively, if the surface cleaning apparatus is a hand vacuum cleaner, then the entire hand vacuum cleaner may be so positioned. Cyclone bin assembly **30'** includes a dirt collection region **38** for collecting particulate matter dis-entrained from a dirty airflow by an air treatment member, in this case a cyclone **31**.

(76) In FIG. **12**, openable lower end **32** of cyclone bin assembly **30'** has been moved into an open position. For example, a user may have opened the dirt collection region, with the expectation that gravity would transfer at least the bulk of the contents of the dirt collection region to the interior of the refuse container. For example, door closure member **37'** may have been deflected or rotated (e.g. by a user's thumb), whereby openable lower end **32** was released and moved to an open position, e.g. due to gravity or, as shown in FIG. **12**, by one or more biasing members **40**.

(77) As discussed previously, opening the dirt collection region **38** for emptying often results in a cloud or plume of fine dust or other particles billowing outwards from the opening of the dirt collection region and/or from the container **20** into which the dirt collection region is being emptied. The particles in such a plume or cloud may be dispersed during the emptying process, resulting in a less than complete transfer from the dirt collection region **38** to the interior **28** of the refuse container **20**. This may be considered undesirable by a user, particularly if the plume or cloud contains dust or other allergens to which the user is sensitive.

(78) To address this potential issue, in FIG. **12** suction motor **206** has been actuated to drive suction fan **204**, resulting in an airflow from the interior volume **28** of container **20**, through inlet **212** and optional air treatment member **210**, and through post-motor filter **208** to an area exterior of the container **20**. Advantageously, this may result in some or all of any particles dispersed in a plume or cloud following the opening of dirt collection region **38** being drawn into the interior volume **28** of container **20** and/or into air treatment member **210**. Accordingly, the amount of dust, allergens, or other fine particulate matter that is 'lost' (i.e. is not transferred to container **20** or to air treatment member **210**) during the emptying of dirt collection region **38** into container **20** may be reduced or eliminated.

(79) FIGS. **13A** and **13B** illustrate an alternative embodiment in which a suction source **220** is provided on the first or inner lid **100** for a refuse container **20**. In the illustrated example, suction source **220** includes a suction motor **206** drivably connected to a suction fan **204** for drawing air from inlets **112** located about the perimeter of port **110** in lid **100**. A pre-motor filter **202** and a post-motor filter **208** are also shown upstream and downstream, respectively, of suction motor **206**, although it will be appreciated that one or both of these filters may not be provided in alternative embodiments.

(80) In FIG. **13A**, a second or upper lid **5** is also shown in a removed position. Upper lid **5** is configured to rest on or engage with the upper surface **104** of lid **100**, such that the second lid **5** overlies all or substantially all of port **110**.

(81) In the illustrated configuration, inlets **112** are provided on an inner surface of port **110** between the upper surface **104** and a lower surface **102** of lid **100**. An optional air treatment member **210** is provided downstream of inlets **112**. In the illustrated example, air treatment member **210** includes a vacuum bag **213** for collecting particles from a dirty airflow into the bag, as is known in the art. Air treatment member **210** is in fluid communication with a conduit **115** that is downstream of an annular manifold **114** provided about port **110**. Downstream portions of inlets **112** are connected to manifold **114**, providing a fluid flow path from inlets **112** to air treatment member **210**. Air treatment member **210** also has an outlet **214** in fluid communication with suction fan **204**. Alternatively, the air treatment member can comprise a cyclone, a filter, an additional cyclonic cleaning stage and/or other air treatment known in the art.

(82) In the illustrated example, inlets **112** are provided on an inner surface of port **110**.

Alternatively, inlets **112** may be provided on the lower surface **102** of lid **100**, or on the upper surface **104** and may optionally extend above upper surface **104**.

(83) Also, in the illustrated example two inlets **112** are provided. Alternatively, three or more inlets **112** may be provided, or a single inlet **112** may be provided.

(84) Also, in the illustrated example, an annular manifold **114** is provided between inlets **112** and the air treatment member **210**. Alternatively, each inlet **112** may be provided with a dedicated conduit to optional air treatment member **210**.

(85) Also, as illustrated in FIG. **13B**, suction source **200** is provided on lid **100**. For example, second lid **5** and container **20** (as shown in FIG. **13A**) may have been purchased or otherwise acquired as a set, and first or inner lid **110** shown in FIG. **13B** may be acquired as an option or a retrofit (e.g. acquired separately) to provide the suction source to effect a more controlled transfer of the contents of the dirt collection region to the refuse container. Suction source **200** may be secured to lid **100** in any suitable manner. For example, suction source **200** and/or optional air treatment member **210** may be removably mounted to lid **100**, e.g. an upper end of conduit **115** may be threaded to provide for rotational engagement and disengagement with corresponding threads in lid **100**. Alternatively, suction source **200** and/or optional air treatment member **210** may be non-removably (e.g. integrally formed with) mounted to lid **100**.

(86) Also, in the illustrated examples, suction source **200** is provided on lid **100**. Alternatively, suction source **200** may be provided on the exterior of container **20**. Suction source **200** may be secured to container **20** in any suitable manner. For example, suction source **200** and/or optional air treatment member **210** may be removably mounted to container **20**. Alternatively, suction source **200** and/or optional air treatment member **210** may be non-removably (e.g. integrally formed with) mounted to container **20**.

(87) Also, in the illustrated examples, suction source **200** is configured to be positioned on the exterior of container **20**. Alternatively, suction source **200** and/or optional air treatment member **210** may be positioned (e.g. removably or non-removably) in the interior of container **20**.

(88) It will be appreciated that the lid may include the openable port of the aspect discussed previously and the air may be drawn for a substantially sealed interior **28** of container **20**.

(89) Alternatively or in addition, it will be appreciated that the suction source may be actuated prior to, upon or subsequent to the opening of the dirt collection region. For example, if port **110** is provided with flanges, then the suction source may be actuated when the flanges commence deflection upon opening of the port. Alternatively, a sensor, e.g., an infra-red (IR) sensor, may be provided to actuate the suction source when the dirt collection region is brought proximate to or into the container **20**.

(90) Cyclone Bin Assembly with Deployable Closure Member

(91) The following is a general description of a cyclone bin assembly having a deployable closure member and other features set out herein that may be used by itself or in combination with one or more embodiments disclosed herein, including one or more of a lid for a refuse container having an openable port, dust control systems for refuse containers or surface treatment apparatus, dust treatment systems for refuse containers or surface treatment apparatus, and a refuse container having a suction source. The following description contains various features of a cyclone bin assembly having a deployable closure member that may be used individually or in any combination or sub-combination.

(92) In accordance with this aspect, a flexible closure member or hood is provided to create a closed or substantially closed volume between the interior of container **20** and the openable portion of the dirt collection region. Accordingly, when the dirt collection region is opened, even if the finer dirt creates a plume or cloud, the plume or cloud is contained or substantially contained thereby reducing or preventing the loss of finer particulate matter upon emptying the dirt collection region.

(93) As exemplified in FIGS. **14-17**, a flexible closure member **300** is shown in association with a

cyclone bin assembly for a surface cleaning apparatus. In the example shown in FIGS. 14 and 17, cyclone bin assembly **30'** includes an air treatment member, in this case a cyclone **31**, and a dirt collection region **38** for collecting particulate matter dis-entrained from a dirty airflow by cyclone **31**. A handle **33** is provided at an upper end **34** of the cyclone bin assembly. Cyclone bin assembly **30'** has an openable lower end **32** releasably secured by a door closure member **37'**. It will be appreciated that, as discussed previously, any air treatment member and openable dirt collection region known in the surface cleaning arts may be used.

(94) As exemplified, flexible closure member **300** is mounted on or secured to an outer sidewall **36** (i.e. an exterior surface) of cyclone bin assembly **30'**. In the illustrated example, a first or upper end **304** is secured to sidewall **36**. An optional shroud **308** is provided about the sidewall **36**. Shroud **308** may assist in retaining or gathering flexible closure member **300** when it is in a retracted position. It will be appreciated that flexible closure member **300** may be permanently mounted or removably mounted to any portion of the dirt collection region, air treatment member, or surface cleaning apparatus.

(95) Flexible closure member **300** comprises a pliant, flexible material, and may be provided as a single piece construction (e.g. having an annular or conical shape), or may alternatively be provided as two or more panels of material.

(96) Preferably, flexible closure member **300** comprises at least one of a plastic material (e.g. a polyethylene film, a bioplastic film, and the like) and a natural fabric (e.g. cotton, hemp, and the like). In one or more preferred embodiments, flexible closure member **300** may be made from a substantially or completely air-impermeable material.

(97) Flexible closure member **300** is preferably transparent or translucent, although it will be appreciated that all or a portion of flexible closure member **300** may be opaque.

(98) Flexible closure member **300** preferably has a length sufficient to permit a user to hold, e.g., bin assembly **30'** while standing upright, while flexible closure member is secured to container **20** and while emptying the dirt collection region.

(99) As exemplified in FIG. 15, a securing member **306** may be provided at or proximate a second or lower end **302** of flexible closure member **300**. Securing member **306** is configured to assist in retaining the lower end **302** of flexible closure member **300** in a position where the flexible closure member encloses upper end **24** of refuse container **20**.

(100) In a preferred embodiment, securing member **306** may comprise an elongate elastic member extending about all or a portion of a perimeter of lower end **302** of flexible closure member **300**. In such an arrangement, securing member **306** may assist in providing a partial or complete seal between lower end **302** of flexible closure member **300** and sidewall **26** of refuse container **20**. Preferably, such an elastic member has sufficient elasticity so as to be stretched from a length approximately equal to the circumference of an outer perimeter of the cyclone bin assembly, to a length approximately equal to a circumference of an outer perimeter of a refuse container **20** or of a lid **100**.

(101) In another preferred embodiment, securing member **306** may comprise a drawstring extending about all or a portion of a perimeter of lower end **302** of flexible closure member **300**. Preferably, such a drawstring can be extended to a length approximately equal to a circumference of an outer perimeter of a refuse container **20** or of a lid **100**, and retracted to a second length approximately equal to the circumference of an outer perimeter of the cyclone bin assembly.

(102) For example, in a retracted position (not shown), lower end **302** of flexible closure member **300** may be gathered or otherwise positioned under shroud **308**, such that all or substantially all of flexible closure member **300** is positioned between shroud **308** and sidewall **36**. Preferably, in such a position securing member **306** may be used to secure lower end **302** to the cyclone bin assembly (e.g. to sidewall **36**).

(103) In another preferred embodiment, flexible closure member **300** may itself be sufficiently resilient or elastic such that a securing member **306** is not required.

(104) Alternatively, or in addition, container **20** may be provided with a locking member to which the lower end of flexible closure member **300** is releasably attachable. For example, the lower end of flexible closure member **300** and the garbage can may have male and female interengageable hook and loop fasteners.

(105) The operation of flexible closure member **300** in controlling dust, allergens, and other particulate matter when emptying a dirt collection region of a surface cleaning apparatus will now be discussed with reference to FIGS. **15** and **16**.

(106) In FIG. **15**, a cyclone bin assembly **30** for a surface cleaning apparatus has been positioned above port **110** of container **20** or may be above an open top of container **20**. For example, a user may have detached and carried the cyclone bin assembly to such a position. Cyclone bin assembly **30** includes a dirt collection region **38** for collecting particulate matter dis-entrained from a dirty airflow by an air treatment member, in this case a cyclone **31**.

(107) Also, in FIG. **15** flexible closure member **300** has been moved to a deployed position, in which lower end **302** has been positioned around upper portion **24** of container **20**, and optionally retained in such a position by optional securing member **306**. As a result, an enclosed volume **310** (i.e. a closed volume) defined by flexible closure member **300** extends between the upper end **304** of flexible closure member **300** and includes the interior volume **28** of container **20**. Notably, openable lower end **32** of cyclone bin assembly **30** is positioned within enclosed volume **310**.

(108) In FIG. **16**, openable lower end **32** of cyclone bin assembly **30** has been moved into an open position. For example, a user may have opened the dirt collection region, with the expectation that gravity would transfer at least the bulk of the contents of the dirt collection region to the interior of the refuse container. For example, door release switch **35** may have been deflected or rotated (e.g. by a user's thumb), resulting in a deflection or rotation of door closure member **37**, whereby openable lower end **32** was released and moved to an open position, e.g. due to gravity or one or more biasing members (not shown).

(109) As discussed previously, opening the dirt collection region **38** for emptying often results in a cloud or plume of fine dust or other particles billowing outwards from the opening of the dirt collection region and/or from the container **20** into which the dirt collection region is being emptied. The particles in such a plume or cloud may be dispersed during the emptying process, resulting in a less than complete transfer from the dirt collection region **38** to the interior **28** of the refuse container **20**. This may be considered undesirable by a user, particularly if the plume or cloud contains dust or other allergens to which the user is sensitive.

(110) Advantageously, in the configuration illustrated in FIG. **16**, flexible closure member **300** may act to direct some or all of any particles dispersed in a plume or cloud following the opening of dirt collection region **38** towards the interior volume **28** of container **20**. Accordingly, the amount of dust, allergens, or other fine particulate matter that is dispersed during the emptying of dirt collection region **38** into container **20** may be reduced or eliminated.

(111) As discussed previously, the actuator to open the dirt collection region may be located so that it may be actuated when flexible closure member is deployed, e.g., it is located at a position exterior to enclosed volume **310**. Accordingly, as exemplified in FIGS. **15** and **16**, cyclone bin assembly **30** is provided with a door release switch **35** (positioned adjacent handle **33**) that is operatively coupled to door closure member **37** via door actuator **39**. In such a configuration, i.e. in which the actuator **35** for the openable door **32** is exterior to the closed volume **310** when the flexible closure member **300** is in the deployed position, the opening of openable door **32** may be relatively straightforward for a user. Any mechanism discussed herein may Alternatively be used.

(112) FIG. **17** illustrates an alternative embodiment of a refuse container **20**, with an alternative design of cyclone bin assembly **30'**. In the example cyclone bin assembly **30'** shown in FIG. **17**, a door release switch is not provided proximate the upper end of the cyclone bin assembly. Instead, the door closure member **37'** is configured to be deflected or rotated directly, thereby releasing openable lower end **32**.

(113) As shown in FIG. 17, when lower end 32 of cyclone bin assembly 30' is positioned in interior volume 28 of container 20, and the flexible closure member 300 has been deployed about the upper end 24 of container 20, the door closure member 37' is positioned in the interior volume 310 provided by flexible closure member 300. In this illustrated configuration, the flexible closure member 300 may inhibit or prevent a user from releasing openable lower end 32. To address this potential issue, container 20 is provided with a release actuator 130'.

(114) Release actuator 130' has a first portion 132' projecting generally outwardly from sidewall 26 of container 20, and a second portion 134' positioned in the interior volume 28. In the illustrated example, release actuator 130' is positioned in an annular opening in sidewall 26 such that the actuator may be translated inwardly or outwardly with respect to container 20. Preferably, a spring 138 or other biasing member is provided to bias the release actuator 130' towards a position in which the second portion 134' remains in interior volume 28, and in which first portion 132' remains exterior to container 20. In this arrangement, the first portion 132' of actuator 130' may be manipulated by a user to cause the second portion 134' to extend inwardly to drivingly engage and thereby actuate the door closure member 37' of cyclone bin assembly 30' to release openable lower end 32 when the flexible closure member 300 is in a deployed position. It will be appreciated that release actuator 130' may have any configuration and may be rotatable, translatable or otherwise moveably mounted. Also, release actuator 130' may communicate wirelessly with door closure member 37'.

(115) It will be appreciated that any embodiment of this aspect may be used advantageously with an embodiment which creates a sub atmospheric pressure in interior volume 28 and/or interior volume 310.

(116) Dust Control and/or Treatment for Refuse Container or Surface Treatment Apparatus

(117) The following is a general description of dust control and dust treatment systems for a refuse container or for a surface treatment apparatus and other features set out herein that may be used by itself or in combination with one or more embodiments disclosed herein, including one or more of a lid for a refuse container having an openable port, a refuse container having a suction source, a cyclone bin assembly having a deployable closure member, and a dirt collection region of a surface treatment apparatus having a sub-atmospheric pressure mode. The following description contains various features of dust control and dust treatment systems that may be used individually or in any combination or sub-combination.

(118) In accordance with this aspect, a dust control system is provided for selectively directing a dust control agent towards an area in and/or above the interior volume of the refuse container, e.g. below a dirt emptying outlet of a dirt collection region of a surface treatment apparatus. By providing a dust control agent above the interior volume of the container, the dispersal of dust, allergens, or other fine particulate matter into the air, e.g. while particulate matter is being transferred from a dirt collection region of a surface cleaning apparatus to the refuse container, may be inhibited or prevented, which may result in a more controlled transfer of the contents of the dirt collection region to the refuse container. Alternatively, or additionally, the dust control system may be configured to selectively direct a dust control agent towards the interior volume of the refuse container.

(119) Alternatively or in addition, in accordance with this aspect a dust treatment system is provided for selectively directing a dust treatment agent to, e.g., the interior volume of the refuse container and/or a dirt collection region and/or an air treatment member such as a cyclone chamber. Dust, dirt, and other refuse collected in the refuse container may result in the growth of undesirable organisms. Such organisms may have a negative effect of the air quality surrounding container 20. Accordingly, a refuse container 20 may include one or more treatment applicators that provide one or more treatment agents (e.g. disinfecting, sanitizing, and/or deodorizing agents) in the interior volume 28 to reduce or eliminate organisms and/or other odor sources in the interior volume of the container. Disinfecting agents may be any element or emission that may reduce or inhibit growth of

organisms in interior volume **28**, or that are harmful or lethal to organisms that may grow in interior volume **28**. Examples include ultra-violet (UV) light, ozone (O.sub.3), and hydrogen peroxide (H.sub.2O.sub.2). An advantage of this design is that it may reduce or eliminate potentially harmful organisms (e.g. allergens), or reduce or eliminate odors emanating from the collected refuse.

(120) As exemplified in FIGS. **18** and **19**, the dust control system includes a plurality of nozzles **410** for dispersing a liquid, e.g. water, into the air in the form of, e.g., a mist or other dispersion. Nozzles **410** may be provided on an inner surface of port **110** between the upper surface **104** and a lower surface **102** of lid **100**. As exemplified in FIG. **19**, the nozzles **410** are in fluid communication via conduit **422** with a fluid pump **430** that is itself in fluid communication with a reservoir **420**. Reservoir **420** is configured to store a liquid to be dispersed (e.g. water).

(121) It will be appreciated that the liquid, e.g., water, may be dispersed using any means known in the arts, such as an ultrasonic nebulizer or the like.

(122) In the illustrated example, nozzles **410** are provided on an inner surface of port **110**. Alternatively, or additionally, nozzles **410** may be provided on the upper surface **104** of lid **100**, or on the lower surface **102**, or on container **20** itself.

(123) Also, in the illustrated example four nozzles **410** are provided. Alternatively, five or more nozzles **410** may be provided, or three or two or only one nozzle **410** may be provided.

(124) Also, in the illustrated example, nozzles **410** are connected in series using conduit **422**. Alternatively, each nozzle **410** may be provided with a dedicated conduit to pump **430**.

(125) It will be appreciated that the dust control system may be actuated in a number of ways and any method discussed herein for actuating a suction motor to produce sub atmospheric pressure may be used.

(126) For example, in the configuration illustrated in FIG. **18**, a first dust control system actuator **404**, in this example a depressible button, is provided on upper surface **104** of lid **100**. Pump **430** may be configured to direct fluid from reservoir **420** to nozzles **410** in response to actuator **404** being depressed. Alternatively, pump **430** may be configured to direct fluid to nozzles **410** after a pre-determined delay period following the depression of button **404**.

(127) Alternatively, or in addition, a second dust control system actuator **402**, a sensor such as an infra-red (IR) sensor, may be provided, e.g., on an inner surface of port **110** between the upper surface **104** and a lower surface **102** of lid **100**. IR sensor **402** is preferably configured to detect when an object (e.g. a dirt collection region of a surface cleaning apparatus) is positioned in port **110**. Pump **430** may be configured to direct fluid from reservoir **420** to nozzles **410** in response to actuator **402** determining an object is positioned in port **110**. Alternatively, pump **430** may be configured to direct fluid to nozzles **410** after a pre-determined delay period following the detection of an object by sensor **402**.

(128) In the configuration exemplified in FIGS. **18** and **19**, the dust control system includes one or more nozzles for dispersing water or other liquids into the air in the form of a mist or other dispersion. Alternatively, or additionally, the dust control system may include one or more ion emitters for selectively dispersing negative (and/or positive) ions in to the air. In operation, contacting the particulate matter with liquid will increase the weight of the particulate matter, including some or all of the finer particulate matter. This will increase the weight of the particulate matter and thereby reduce the likelihood of a plume or cloud forming. Similarly, particulate matter may become charged upon passage through a surface cleaning apparatus, e.g., a cyclone chamber. Exposing the particulate matter with oppositely charged ions will decrease the charge state of the particulate matter, including some or all of the finer particulate matter. This will reduce the tendency of the charged particulate matter to disperse and thereby reduce the likelihood of a plume or cloud forming.

(129) In the configuration exemplified in FIGS. **20** and **21**, the dust control system also includes a plurality of ion emitters **460** for imparting a negative (and/or positive) charge. Emitters **460** are

provided on, e.g., an inner surface of port **110** between the upper surface **104** and a lower surface **102** of lid **100**. As illustrated in FIG. **20**, the emitters **460** are coupled to a, e.g., power source and control electronics **450** for providing the voltage to impart the charge.

(130) In the illustrated example, emitters **460** are provided on an inner surface of port **110**.

Alternatively, or additionally, emitters **460** may be provided on the upper surface **104** of lid **100**, or on the lower surface **102**, or on container **20** itself.

(131) Also, in the illustrated example a group of six emitters **460** is provided. It will be appreciated that more or fewer groups of more or fewer emitters **460** may be provided in alternative embodiments.

(132) The operation of the dust control system in controlling dust, allergens, and other particulate matter when emptying a dirt collection region of a surface cleaning apparatus will now be discussed with reference to FIGS. **20** and **21**.

(133) In FIG. **20**, a cyclone bin assembly **30** for a surface cleaning apparatus has been positioned above port **110**. For example, a user may have detached and carried such a dirt collection region to such a position. Cyclone bin assembly **30** includes a dirt collection region **38** for collecting particulate matter dis-entrained from a dirty airflow by an air treatment member, in this case a cyclone **31**.

(134) In FIG. **21**, openable lower end **32** of cyclone bin assembly **30** has been moved into an open position. For example, a user may have opened the dirt collection region, with the expectation that gravity would transfer at least the bulk of the contents of the dirt collection region to the interior of the refuse container. For example, door release switch **35** may have been deflected or rotated (e.g. by a user's thumb), resulting in a deflection or rotation of door closure member **37**, whereby openable lower end **32** was released and moved to an open position, e.g. due to gravity or one or more biasing members (not shown).

(135) As discussed previously, opening the dirt collection region **38** for emptying often results in a cloud or plume of fine dust or other particles billowing outwards from the opening of the dirt collection region and/or from the container **20** into which the dirt collection region is being emptied. The particles in such a plume or cloud may be dispersed during the emptying process, resulting in a less than complete transfer from the dirt collection region **38** to the interior **28** of the refuse container **20**. This may be considered undesirable by a user, particularly if the plume or cloud contains dust or other allergens to which the user is sensitive.

(136) To address this potential issue, in FIG. **21** pump **430** has been actuated to direct a liquid, e.g., water, to nozzles **410**, resulting in a spray or mist of water particles being dispersed in the region above port **110** (i.e. the area or region below the outlet of the dirt collection region **38** in the illustrated example). Advantageously, this may result in some or all of any particles dispersed in a plume or cloud following the opening of dirt collection region **38** being 'wetted' by the dispersed water droplets, and thereafter drawn into the interior volume **28** of container **20** by gravity.

(137) Also, in FIG. **21** control electronics **450** have been actuated to cause ion emitters **460** to emit, e.g., negatively charged particles, resulting in a negative ions being dispersed in the region above port **110**. Advantageously, this may result in some or all of the charged particulate matter being neutralized. This results in the particulate matter having a lesser tendency to disperse following the opening of dirt collection region **38** and thereby a lower likelihood of a plume being formed or a smaller plume being formed.

(138) Accordingly, the amount of dust, allergens, or other fine particulate matter that is 'lost' (i.e. is not transferred to container **20**) during the emptying of dirt collection region **38** into container **20** may be reduced or eliminated.

(139) In the examples illustrated in FIGS. **18-21**, a dust control system is provided in association with a refuse container and/or with a lid for a refuse container. Alternatively, or in addition, a dust control system may be provided in association with a surface cleaning apparatus, or a portion thereof such as an air treatment member (which may be characterized as a dirt separation member)

and/or a dirt collection region. Accordingly, the dust control system may be configured to selectively direct a dust control agent towards the interior volume of the dirt collection region and/or a region below the openable portion of a dirt collection region.

(140) As exemplified in in FIGS. 22-24, the dust control system includes a plurality of nozzles **410** for dispersing a liquid, e.g. water, into the air in the form of a mist or other dispersion. Nozzles **410** are provided on an outer surface of sidewall **36** between the upper end **34** and lower end **32** of bin assembly **30**. As illustrated in FIG. 23, the nozzles **410** are in fluid communication with a reservoir **420**. Reservoir **420** is configured to store a liquid to be dispersed (e.g. water).

(141) In the illustrated example, four nozzles **410** are shown. Alternatively, five or more nozzles **410** may be provided, or three or two or only one nozzle **410** may be provided.

(142) The operation of the dust control system in controlling dust, allergens, and other particulate matter when emptying a dirt collection region of a surface cleaning apparatus will now be discussed with reference to FIGS. 23 and 24.

(143) In FIG. 23, openable end or door **32** for dirt collection region **38** is in a closed position, and particulate matter dis-entrained from a dirty airflow by an air treatment member, in this case a cyclone **31**, has been collected in the dirt collection region **38**.

(144) In FIG. 24, openable lower end **32** has been moved into an open position. For example, a user may have opened the dirt collection region, with the expectation that gravity would transfer at least the bulk of the contents of the dirt collection region to e.g. the interior of a refuse container. For example, door closure member **37'** may have been deflected or rotated (e.g. by a user's thumb), whereby openable lower end **32** was released and moved to an open position, e.g. due to gravity or one or more biasing members (not shown).

(145) Also, in FIG. 24 a pump has been actuated to direct liquid, e.g., water, to nozzles **410**, resulting in a spray or mist of water particles being dispersed in the region around the opening of dirt collection region **38**. As discussed previously, opening the dirt collection region **38** for emptying often results in a cloud or plume of fine dust or other particles billowing outwards from the opening of the dirt collection region. Advantageously, the dispersal of water particles in the region around the opening of dirt collection region **38** may result in some or all of any particles dispersed in a plume or cloud following the opening of dirt collection region **38** being 'wetted' by the dispersed water droplets, and thereafter drawn into e.g. the interior volume **28** of a refuse container by gravity.

(146) Accordingly, the amount of dust, allergens, or other fine particulate matter that is dispersed into the air during the emptying of dirt collection region **38** may be reduced or eliminated.

(147) The dust control system provided with a cyclone bin assembly may be actuated in a number of ways and may be actuated using any method of actuation discussed herein. For example, a manual dust control system actuator, e.g. a depressible button, may be provided. Fluid pump may be configured to direct fluid from reservoir **420** to nozzles **410** in response to such an actuator being depressed. Alternatively, it may be actuated by the opening of the dirt collection region.

(148) For example, in the configuration illustrated in FIG. 25, at least a portion of bellows-type pump **430** is positioned between door closure member **37'** and sidewall **36** of the cyclone bin assembly. In this arrangement, pump **430** may be actuated substantially concurrently with the deflection or rotation of door closure member **37'** (e.g. by a user's thumb), whereby a spray or mist of water particles being dispersed from nozzles **410** substantially concurrently with the opening of openable lower end **32**. In other words, in such an arrangement pump **430** is configured to direct fluid from reservoir **420** to nozzles **410** in response to door closure member **37'** being actuated.

(149) Alternatively, in the configuration illustrated in FIG. 26, a door release switch **35** provided adjacent handle **33** is operatively coupled to door closure member **37** via door actuator **39**. In this example, a piston-type pump **430** is provided at the base of door actuator **39**, such that downward travel of door actuator **39** results in a spray or mist of water particles being dispersed from nozzles **410**. Also, a secondary door actuator **371** is provided at the base of the cylinder of the piston-type

pump **430**. In this configuration, further downward travel of door actuator **39**—i.e. after pump **430** has been actuated—results in contact and downward travel of secondary door actuator **371**, thereby resulting in a deflection of door closure member **37**, whereby openable lower end **32** is released. In other words, in such an arrangement pump **430** is configured to direct fluid from reservoir **420** to nozzles **410** prior to door closure member **37'** being actuated. Or, put another way, in such an arrangement openable lower end **32** is configured to automatically open after a spray or mist of water particles has been dispersed from nozzles **410**.

(150) FIGS. **27** and **28** exemplify the use of a dust treatment agent.

(151) As exemplified in FIG. **27**, the dust treatment system includes a UV light emitter **510** that selectively emits UV light into interior volume **28** of container **20**, and an ozone gas emitter **520** that selectively emits ozone gas into interior volume **28** of container **20**. It will be appreciated that only one treatment member may be used.

(152) In some embodiments, a manual actuator (e.g. a depressible button) may be provided to selectively actuate the dust treatment system to provide one or more treatment agents (e.g. UV light, ozone gas) into interior volume **28** of container **20**. For example, the UV light emitter **510** may be configured such that, in response to depression of the manual actuator, it emits UV light for a pre-set period of time (e.g. 90 seconds). Similarly, the ozone gas emitter **520** may be configured such that, in response to depression of the manual actuator, it emits ozone gas for a pre-set period of time (e.g. 90 seconds). Alternatively, or additionally, the dust treatment system may be configured such that one or more treatment agents (e.g. UV light, ozone gas) are provided into interior volume **28** of container **20** at pre-set intervals (e.g. every 24 hours) without requiring manual actuation, and/or upon emptying a dirt collection region and/or a preset time after a dirt collection region is emptied into the refuse container.

(153) Ozone gas may be effective for purifying and/or deodorizing refuse collected in container **20**. However, ozone gas may be also harmful if inhaled by humans or other animals. In an effort to minimize one or more risks associated with emitting ozone gas, some embodiments that include an ozone gas emitter **520** may also include an ozone destructor material for breaking down some or all of the emitted ozone.

(154) For example, as illustrated in FIG. **27**, a suction source **220** that includes a suction motor **206** drivingly connected to a suction fan **204** may be provided for drawing air (including emitted ozone) from the interior volume **28** of container **20** via an inlet **212** and across an ozone destructor material **530**. The ozone destructor material **530** may be any material that can remove ozone gas from the air flow by adsorption or conversion to one or more other molecules. Examples include activated carbon or an ozone catalyst that converts ozone (O.sub.3) to oxygen (O.sub.2). An advantage of this design is that some or all of the ozone gas emitted into interior volume **28** to counteract organisms in container **20** may be removed before the air flow is discharged from container **20**. This may allow a container **20** including ozone gas emitter **520** to be safely employed in, e.g. residential spaces.

(155) In the example illustrated in FIG. **27**, a dust treatment system is provided in association with a refuse container and/or with a lid for a refuse container. Alternatively, a dust treatment system may be provided in association with an air treatment member such as a cyclone bin assembly. As exemplified in FIG. **28**, a cyclone bin assembly **30** for a surface cleaning apparatus has a dust treatment system for selectively introducing a dust treatment agent into a dirt collection region of a surface treatment apparatus. By providing one or more disinfecting agents, e.g. ultra-violet (UV) light, ozone (O.sub.3), and hydrogen peroxide (H.sub.2O.sub.2), into a dirt collection region, growth of undesirable organisms present in dust, dirt, and/or other refuse collected in the dirt collection region may be reduced or eliminated.

(156) In the configuration illustrated in FIG. **28**, the dust treatment system includes a UV light emitter **510** that emits UV light into dirt collection region **38** of cyclone bin assembly **30**, and an ozone gas emitter **520** that selectively emits ozone gas into dirt collection region **38**. It will be

appreciated that only one treatment member may be used.

(157) In some embodiments, a manual actuator (e.g. a depressible button) may be provided to selectively actuate the dust treatment system to provide one or more treatment agents (e.g. UV light, ozone gas) into dirt collection region **38** of cyclone bin assembly **30**. For example, the UV light emitter **510** may be configured such that, in response to depression of the manual actuator, it emits UV light for a pre-set period of time (e.g. 90 seconds). Similarly, the ozone gas emitter **520** may be configured such that, in response to depression of the manual actuator, it emits ozone gas for a pre-set period of time (e.g. 90 seconds). Alternatively, or additionally, the dust treatment system may be configured such that one or more treatment agents are provided into interior volume **28** of container **20** at pre-set intervals (e.g. every 24 hours) without requiring manual actuation. Alternatively, or additionally, the dust treatment system may be configured such that one or more treatment agents are provided into interior volume **28** of container **20** after a pre-set number of uses of the surface cleaning apparatus (e.g. following 5 on/off cycles of the main suction motor of the surface cleaning apparatus). Alternatively, or additionally, the dust treatment system may be configured such that one or more treatment agents are provided into interior volume **28** of container **20** subsequent to emptying of the dirt collection region (e.g. in response openable door **32** being closed).

(158) In an effort to minimize one or more risks associated with emitting ozone gas, the example illustrated in FIG. **28** includes a suction source **220** that includes a suction motor **206** drivingly connected to a suction fan **204** for drawing air (including emitted ozone) from dirt collection region **38** via an inlet **532** and across an ozone destructor material **530**. As discussed above, ozone destructor material **530** may be any material that can remove ozone gas from the air flow by adsorption or conversion to one or more other molecules. Examples include activated carbon or an ozone catalyst that converts ozone (O.sub.3) to oxygen (O.sub.2). An advantage of this design is that some or all of the ozone gas emitted into dirt collection region **38** of cyclone bin assembly **30** may be drawn across an ozone destructor material before being otherwise exhausted into the ambient atmosphere (e.g. by opening openable door **32**). This may allow a cyclone bin assembly **30** including ozone gas emitter **520** to be safely employed in, e.g. residential spaces.

(159) Sub-Atmospheric Pressure Mode for Dirt Collection Region of a Surface Treatment Apparatus

(160) The following is a general description of a dirt collection region of a surface treatment apparatus having a sub-atmospheric pressure mode and other features set out herein that may be used by itself or in combination with one or more embodiments disclosed herein, including one or more of a lid for a refuse container having an openable port, a refuse container having a suction source, a cyclone bin assembly having a deployable closure member, dust control systems for refuse containers or surface treatment apparatus, and dust treatment systems for refuse containers or surface treatment apparatus. The following description contains various features of a dirt collection region of a surface treatment apparatus having a sub-atmospheric pressure mode that may be used individually or in any combination or sub-combination.

(161) In accordance with this aspect, sub atmospheric pressure is provided in an air treatment member or a portion thereof, e.g., a dirt collection region, to draw finer particulate matter into the surface cleaning apparatus. An advantage of this aspect is that a reduced amount of finer particulate matter may be released when the dirt collection region is opened and therefore a smaller plume may be formed upon emptying the dirt collection region.

(162) It will be appreciated that the sub atmospheric pressure may be produced by the suction motor (which may be referred to as a main suction motor) used to draw air from a dirty air inlet when a surface cleaning apparatus is used to clean a surface (i.e., a cleaning mode). In such a case, the main suction motor may be operated at a lower power level to produce a reduced level of suction during an emptying operation (i.e., an emptying mode). For example, the main suction motor may be configured to produce sufficient suction to create an air flow of 0.1 CFM to 1.5 CFM

per square inch of opening area during the emptying mode, preferably 0.25 CFM to 1.25 CFM per square inch of opening during the emptying mode and more preferably 0.50 CFM to 1.00 CFM per square inch of opening area during the emptying mode. Alternatively, or in addition, dilution air may be drawn from outside the air treatment member, such as by opening a vent hole, between the main suction motor and the air treatment member during the emptying mode. An advantage of this latter approach is that the suction motor may be operated at the same power level during both cleaning and emptying.

(163) Alternatively, or in addition, the sub atmospheric pressure may be produced during the emptying mode by an alternate suction motor for use during a cleaning cyclone, i.e., an emptying mode suction motor. An advantage of this design is that a smaller, and therefore lighter, suction motor and fan assembly may be used. Such a suction motor may be removable with the dirt collection region (e.g., part of a removable cyclone bin assembly or dirt collection region), thereby permitting a removable dirt collection to be used in conjunction with this aspect.

(164) It will be appreciated that the suction motor, whichever is used, may be actuated prior to, upon, or subsequent to opening the dirt collection region for emptying. For example, one or more sensors configured to detect when an openable door of the dirt collection region is opened may be provided to automatically actuate whichever suction motor is to be used during the emptying mode in response to the openable door being opened.

(165) It will also be appreciated that the air which is drawn from the air treatment member during an emptying operation (i.e., the emptying mode) may also be treated to remove particulate matter. Any air treatment member may be used. For example, the air may be drawn through a cyclone and/or an alternate or emptying mode pre-motor filter.

(166) As exemplified in FIGS. **29-32**, a cyclone bin assembly (a main air treatment member) is shown schematically coupled to a suction system of surface cleaning apparatus. In the illustrated schematics, cyclone bin assembly **30** includes a cyclone **31**, and a dirt collection region **38** in communication with cyclone **31** via cyclone dirt outlet **633** for collecting particulate matter dis-entrained from a dirty airflow by cyclone **31**. Cyclone bin assembly **30** has an openable lower end **32** releasably secured by a door closure member **37'**. It will be appreciated that any air treatment member may be used as the main air treatment member.

(167) Referring to FIG. **29**, in operation dirty air (e.g. an airflow with entrained particulate matter) enters a dirty air inlet **602** of the surface cleaning apparatus and is drawn through a conduit **610** to a cyclone dirty air inlet **632**. After circulating in cyclone **31**, and thereby dis-entraining particles contained therein, the air passes through cyclone air outlet **634** and is drawn through a conduit **620** by a suction fan **204** drivingly connected to a main suction motor **206** and exhausted from a clean air outlet **604** of the surface cleaning apparatus. In the illustrated example, an optional main or first pre-motor filter **202** and an optional main or first post-motor filter **208** are also shown upstream and downstream, respectively, of suction motor **206**, although it will be appreciated that one or both of these filters may not be provided in alternative embodiments. Any known surface cleaning apparatus with any known cyclone assembly or other air treatment member may be used.

(168) As discussed previously, opening the dirt collection region **38** for emptying often results in a cloud or plume of fine dust or other particles billowing outwards from the opening of the dirt collection region. The particles in such a plume or cloud may be dispersed during the emptying process, resulting in a less than complete transfer from the dirt collection region **38** to e.g. a refuse container. This may be considered undesirable by a user, particularly if the plume or cloud contains dust or other allergens to which the user is sensitive.

(169) As exemplified in FIGS. **29** and **30**, the main suction motor used during a cleaning operation is used to create the sub atmospheric pressure during emptying of the dirt collection region (e.g. when the openable door is in an open position). The suction motor may be connected to draw air from the cyclone by any method and may use the cyclone air outlet. As exemplified, a bypass conduit **612**, which functions as an alternate downstream air flow path, and valves **640a**, **640b** are

provided. For example, in the configuration shown in FIG. 30, main suction fan **204** and main suction motor **206** are shown being used to draw air from cyclone air inlet **632** via conduit **612**, resulting in an airflow from the dirt collection region **38** via cyclone dirt outlet **633** and cyclone **31**, through conduit **612** and an optional auxiliary or emptying mode backflow pre-motor filter **650**, and through post-motor filter **208** to an area exterior of the air treatment member. Advantageously, this may result in some or all of any particles that might otherwise be dispersed in a plume or cloud following the opening of dirt collection region **38** being drawn back into auxiliary backflow filter **650**. Accordingly, the amount of dust, allergens, or other fine particulate matter that is 'lost' (e.g. is not transferred to a refuse container) during the emptying of dirt collection region **38** may be reduced or eliminated. In an alternate embodiment as exemplified in FIG. 32, it will be appreciated that the alternate downstream air flow path may extend from the main air treatment member (cyclone **31** as exemplified) to the main suction motor **206** and bypass the main pre-motor filter **202**. In such a case, auxiliary backflow pre-motor filter **650** may be the only filter upstream of suction motor **206**.

(170) It will be appreciated that in some embodiments, suction motor **206** may be operated at reduced power when drawing air from cyclone air inlet **632**. An advantage of such a configuration is that only very fine dust or other particles may be drawn towards auxiliary backflow filter **650**, while larger particles may be relatively unaffected by the reduced airflow. For example, when openable lower end **32** of cyclone bin assembly **30** has been moved into an open position, larger dirt particles collected in the dirt collection region may be directed by gravity to the interior of a refuse container over which the cyclone bin assembly **30** is positioned.

(171) In the examples illustrated in FIGS. 29 and 30, the same suction source used during normal operation of the surface cleaning apparatus is used to drawing air from cyclone air inlet **632** during emptying of the dirt collection region **38**. Alternatively, an auxiliary or emptying mode suction source may be provided to draw air from the cyclone, such as from cyclone air inlet **632**.

(172) For example, as illustrated in FIG. 31, a main suction source **220a**, which may be referred to as a main suction motor or a main suction motor and fan assembly, may be provided downstream of cyclone air outlet **634** for drawing air through cyclone **31** during normal operation of the surface cleaning apparatus (the cleaning mode). For example, suction fan **204a** may be used to induce an airflow from dirty air inlet **602** through cyclone air inlet **632**, around cyclone **31**, through cyclone air outlet **634**, and exiting from clean air outlet **604a** of the surface cleaning apparatus.

(173) During emptying of the dirt collection region (the emptying mode), emptying mode suction fan **204b** and emptying mode suction motor **206b** may be used to draw air from cyclone air inlet **632** via conduit **612**, resulting in an airflow from the dirt collection region **38** via cyclone dirt outlet **633** and cyclone **31**, through conduit **612** and optional auxiliary backflow filter **650**, and through post-motor filter **208b** to an auxiliary clean air outlet **604b**. Advantageously, this may result in some or all of any particles dispersed in a plume or cloud following the opening of dirt collection region **38** being drawn back into auxiliary backflow filter **650**.

(174) It will be appreciated that the air flow path through which air travels during the emptying mode (the alternate downstream air flow path), whichever suction motor is used, may be closed during the cleaning mode and opened during an emptying mode. Similarly, the flow path from the main air treatment member to the main suction motor (a main downstream portion of the air flow path) is open during the cleaning mode and may be closed during the emptying mode. A main closure member may be associated with the main downstream portion of the air flow path and an alternate closure member may be associated with the alternate downstream air flow path. These closure members may be provided at the inlets to these air flow paths and may be any closure member such as a valve, a sliding closure panel, or the like.

(175) For example, as exemplified in FIG. 32, a valve **640c** is provided to selectively direct suction from a main suction source **220** to either cyclone air outlet **634** (for drawing air through cyclone **31** during normal operation of the surface cleaning apparatus) or to bypass inlet **636** (for drawing air

from dirt collection region **38** via cyclone **31** during emptying). Valve **640c** may be a sliding panel which selectively blocks the outlet of main pre-motor filter **202** and alternate pre-motor filter **650**. Accordingly, a single closure member may be used.

(176) Accordingly, during a cleaning operation, valve **640c** may direct an airflow generated by main suction fan **204** to induce an airflow from dirty air inlet **602** through cyclone air inlet **632**, around cyclone **31**, through cyclone air outlet **634**, through pre-motor filter **202**, past the suction motor, across post-motor filter **208**, and exiting from clean air outlet **604** of the surface cleaning apparatus.

(177) During emptying of the dirt collection region, valve **640c** (in the position shown in FIG. **32**) may direct an airflow generated by suction fan **204** to induce an airflow from the dirt collection region **38** via cyclone dirt outlet **633** and cyclone **31**, and through an auxiliary cleaning cyclone air outlet through cleaning cycle pre-motor filter **650**, past the suction motor and through post-motor filter **208** to clean air outlet **604**. This may result in some or all of any particles dispersed in a plume or cloud following the opening of dirt collection region **38** being drawn back into auxiliary pre-motor filter **650**. As the dirt that may be entrained by a pre-motor filter may differ between a cleaning operation and an emptying operation, (e.g., it may be finer during a cleaning operation) each pre-motor filter **202** and **650** may be designed to collect dirt having a different particle size distribution. An advantage of this design is that the main pre-motor filter **202** is not used in an emptying mode and therefore the pre-motor filter may operate for a longer period of time without requiring cleaning or replacement.

(178) In an alternate embodiment, a separate closure member may be used for each flow path. Accordingly, for example, in the embodiment of FIG. **31**, a main closure member **640c** may be used to close the cyclone air outlet during an emptying mode and an alternate closure member **640d** may be used to close the alternate downstream air flow path **612** during a cleaning mode.

(179) As noted above, it will be appreciated that in some embodiments, suction motor **206** may be operated at reduced power during an emptying operation so that only very fine dust or other particles may be drawn towards auxiliary pre-motor filter **650**, while larger particles may be relatively unaffected by the reduced airflow.

(180) As used herein, the wording “and/or” is intended to represent an inclusive—or. That is, “X and/or Y” is intended to mean X or Y or both, for example. As a further example, “X, Y, and/or Z” is intended to mean X or Y or Z or any combination thereof.

(181) While the above description describes features of example embodiments, it will be appreciated that some features and/or functions of the described embodiments are susceptible to modification without departing from the spirit and principles of operation of the described embodiments. For example, the various characteristics which are described by means of the represented embodiments or examples may be selectively combined with each other. Accordingly, what has been described above is intended to be illustrative of the claimed concept and non-limiting. It will be understood by persons skilled in the art that other variants and modifications may be made without departing from the scope of the invention as defined in the claims appended hereto. The scope of the claims should not be limited by the preferred embodiments and examples, but should be given the broadest interpretation consistent with the description as a whole.

Claims

1. A system comprising a vacuum cleaner comprising a dirt collection region and an apparatus for receiving dirt from the dirt collection region of the vacuum cleaner, the dirt collection region having an openable door, a closure member securing the openable door in a closed position, and a biasing member biasing the openable door to move between an open position in which dirt is emptyable from the dirt collection region and the closed position, the apparatus comprising: (a) an air flow passage from an inlet port to a clean air outlet; (b) an air treatment member positioned in

the air flow passage downstream from the inlet port, the air treatment member comprising an openable portion and a stationary portion, the stationary portion comprising an upper end, a lower end, and an interior volume that extends from the upper end to the lower end, the interior volume comprising an apparatus dirt collection region; and (c) a release actuator which engages a portion of the vacuum cleaner whereby the closure member is moved to an unlocked position in which the closure member is disengaged from the openable door and the openable door is moveable to the open position, wherein the dirt collection region of the vacuum cleaner is removably positionable in air flow communication with the inlet port whereupon, when the dirt collection region of the vacuum cleaner is docked with the apparatus and the system is in an emptying mode of operation, a motor and fan assembly of the system produces a flow of air that conveys dirt from the dirt collection region of the vacuum cleaner to the air treatment member of the apparatus.

2. The system of claim 1 wherein, when the apparatus is standing on a floor in a use position, the floor in the use position, the apparatus has an upper end which has the inlet port.

3. The system of claim 1 wherein, when the dirt collection region of the vacuum cleaner is docked with the apparatus, the openable door of the dirt collection region of the vacuum cleaner is aligned with the inlet port.

4. The system of claim 1 wherein, during the emptying mode of operation, the openable door of the dirt collection region of the vacuum cleaner is positioned in the apparatus.

5. The system of claim 1 wherein, when the dirt collection region of the vacuum cleaner is docked with the apparatus, a portion of the dirt collection region of the vacuum cleaner is positioned in the apparatus.

6. The system of claim 1 wherein a garbage bag is removably positionable in the apparatus.

7. The system of claim 1, wherein, when the apparatus is standing on a floor in a use position, the inlet port faces upwardly.

8. The system of claim 1 wherein, when the apparatus is standing on a floor in a use position, the inlet port is provided in an upwardly facing surface of the apparatus.

9. The system of claim 1 wherein the dirt collection region of the vacuum cleaner is a dirt collection region of a hand vacuum cleaner.

10. The system of claim 1 wherein the air treatment member has an outlet port and, when the apparatus is standing on a floor, the air treatment member of the apparatus has a bottom wall, an upper wall and an upwardly extending sidewall, the outlet port of the air treatment member of the apparatus being provided in the upwardly extending sidewall of the air treatment member of the apparatus.

11. A system comprising a vacuum cleaner comprising a dirt collection region and an apparatus for receiving dirt from the dirt collection region of the vacuum cleaner, the dirt collection region having an openable door, a lock securing the openable door in a closed position, and a biasing member biasing the openable door to move between an open position in which dirt is emptyable from the dirt collection region and the closed position, the apparatus comprising: (a) an air flow passage from an inlet port to a clean air outlet wherein, when the apparatus is standing on a floor in a use position, the inlet port is provided in an upwardly facing surface of the apparatus and the inlet port comprises a majority of the upwardly facing surface; (b) a container positioned in the air flow passage downstream from the inlet port, the container having an openable portion that is moveable with respect to a remainder of the container and an interior volume into which dirt from the dirt collection region is transferrable by air flow produced by a motor and fan assembly of the system; and (c) a release actuator which disengages the lock from the openable door whereby the openable door is moveable to the open position.

12. The system of claim 11 wherein, when the dirt collection region is positioned in air flow communication with the inlet port during an emptying mode of operation, the openable door of the dirt collection region is receivable in the apparatus.

13. The system of claim 11 wherein, when the dirt collection region is positioned in air flow

communication with the inlet port and the motor and fan assembly is actuated, air travels downwardly from the dirt collection region into the container.

14. The system of claim 11 wherein, when the dirt collection region is positioned in air flow communication with the inlet port and the apparatus is free standing on the floor in the use position, the dirt collection region is supportable by the apparatus such that the dirt collection region is positioned at an elevation above the floor.

15. The system of claim 11 wherein the dirt collection region comprises an end wall and the end wall comprises the openable door of the dirt collection region and, during an emptying mode of operation, the openable door is positioned in the apparatus.

16. The system of claim 11 wherein, when the apparatus is standing on the floor in the use position, an upper end of the apparatus comprises an annular housing having the inlet port.

17. The system of claim 11 wherein, when the apparatus is standing on the floor in the use position, an upper end of the apparatus has the inlet port into which the dirt collection region is downwardly slideably engageable by a user.

18. The system of claim 11 wherein, when the apparatus is standing on the floor in the use position, the dirt collection region is downwardly slideably engageable by a user to a position in which the dirt collection region is docked with the apparatus.

19. The system of claim 11 wherein an upper end of the apparatus has an opening which engages the dirt collection region when the dirt collection region is moved by a user in a downward direction to a position in which the openable door of the dirt collection region of the vacuum cleaner is aligned with the inlet port.

20. The system of claim 11 wherein the dirt collection region is a dirt collection region of a hand vacuum cleaner.
