

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12399419
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Vitale; Nicholas et al.

Camera and camera mount

Abstract

An electronic device includes a body, electronic components contained in the body, and two finger members. The two finger members movable relative to the body between an extended state and a collapsed state. In the extended state, the two finger members extend outward from the body for receipt by a mount of an external support. In the collapsed state, the two finger members are collapsed toward the body. In the extended state, the two finger members may extend parallel with each other for receipt in parallel slots of the mount of the external support.

Inventors:	Vitale; Nicholas (Foster City, CA), Muhlenkamp, IV; John George (Brisbane, CA), Nguyen; Huy Phuong (Alpine, UT), Marroquin; Marco (San Mateo, CA), Woodman; Nicholas D. (Big Sky, MT), Crow; Kielan C. (San Mateo, CA)
Applicant:	GoPro, Inc. (San Mateo, CA)
Family ID:	1000008777988
Assignee:	GoPro, Inc. (San Mateo, CA)
Appl. No.:	18/127865
Filed:	March 29, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230236481 A1	Jul. 27, 2023

Related U.S. Application Data

continuation parent-doc US 17181163 20210222 US 11662651 child-doc US 18127865
continuation parent-doc US 16697947 20191127 US 10928711 20210223 child-doc US 17181163
continuation-in-part parent-doc WO PCT/US2019/045281 20190806 PENDING child-doc US 16697947
us-provisional-application US 62881023 20190731
us-provisional-application US 62868099 20190628
us-provisional-application US 62786059 20181228
us-provisional-application US 62715794 20180807

Publication Classification

Int. Cl.:	G03B17/56 (20210101); F16M11/12 (20060101); G03B17/08 (20210101); H04N23/55 (20230101)
U.S. Cl.:	
CPC	G03B17/561 (20130101); F16M11/121 (20130101); G03B17/08 (20130101); H04N23/55 (20230101);

Field of Classification Search

CPC:	G03B (17/561); F16M (13/00)
------	-----------------------------

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
1467556	12/1922	Nagel	N/A	N/A
1612277	12/1925	Leo	N/A	N/A
D118296	12/1938	Tuomey	N/A	N/A
2651981	12/1952	Calhoun	N/A	N/A
2890067	12/1958	Morin	N/A	N/A
2962251	12/1959	Nikolaus	N/A	N/A
3073227	12/1962	Richard	N/A	N/A

3508482	12/1969	Taylor	N/A	N/A
D219768	12/1970	Conwill	N/A	N/A
3762797	12/1972	Heller	N/A	N/A
3776649	12/1972	Kemezys	N/A	N/A
3860937	12/1974	Wolfe	N/A	N/A
D243655	12/1976	Matousek	N/A	N/A
4025930	12/1976	Wolff	N/A	N/A
4091402	12/1977	Siegel	N/A	N/A
4208028	12/1979	Brown	N/A	N/A
4417796	12/1982	Sugiura	N/A	N/A
D272392	12/1983	Bigelow	N/A	N/A
4573239	12/1985	Valenti	N/A	N/A
4646141	12/1986	Timmermans	N/A	N/A
4733259	12/1987	Ng	N/A	N/A
4763151	12/1987	Klinger	N/A	N/A
4837817	12/1988	Maemori	N/A	N/A
4864335	12/1988	Corrales	N/A	N/A
4887161	12/1988	Watanabe	N/A	N/A
4888795	12/1988	Ando	N/A	N/A
4953030	12/1989	Seo	N/A	N/A
5021813	12/1990	Corrales	N/A	N/A
5092458	12/1991	Yokoyama	N/A	N/A
5244326	12/1992	Henriksen	N/A	N/A
5294988	12/1993	Wakabayashi	N/A	N/A
5327265	12/1993	McDonald	N/A	N/A
5336086	12/1993	Simmen	N/A	N/A
5400234	12/1994	Yu	N/A	N/A
5429466	12/1994	Nagayama	N/A	N/A
D363562	12/1994	Schildt	N/A	N/A
5485357	12/1995	Zolninger	N/A	N/A
5486852	12/1995	Arai	N/A	N/A
5505424	12/1995	Niemann	N/A	N/A
D373947	12/1995	Parduhn	N/A	N/A
5563661	12/1995	Takahashi	N/A	N/A
5627587	12/1996	Murata	N/A	N/A
5657081	12/1996	Kurahashi	N/A	N/A
5661823	12/1996	Yamauchi	N/A	N/A
D391217	12/1997	Pingel	N/A	N/A
5726708	12/1997	Sakai	N/A	N/A
5729289	12/1997	Etoh	N/A	N/A
5769370	12/1997	Ashjaee	N/A	N/A
5775558	12/1997	Montalbano	N/A	N/A
5805219	12/1997	Ejima	N/A	N/A
5808663	12/1997	Okaya	N/A	N/A
5842069	12/1997	Konno	N/A	N/A
5887375	12/1998	Watson	N/A	N/A
5926218	12/1998	Smith	N/A	N/A
5938492	12/1998	Carlini	N/A	N/A
5946501	12/1998	Hayakawa	N/A	N/A
5969750	12/1998	Hsieh	N/A	N/A
5978609	12/1998	Aoki	N/A	N/A
5995373	12/1998	Nagai	439/31	G06F 1/1681
D418044	12/1998	Schoeneweis	N/A	N/A
6034728	12/1999	Arena	N/A	N/A
6035147	12/1999	Kurosawa	N/A	N/A
6042080	12/1999	Shepherd	N/A	N/A
6104887	12/1999	Hamasaki	N/A	N/A
6118929	12/1999	Kawamura	N/A	N/A
6128441	12/1999	Kamata	N/A	N/A
6138826	12/1999	Kanamori	N/A	N/A
D437772	12/2000	Erwin	N/A	N/A
D441386	12/2000	Yamazaki	N/A	N/A
D442982	12/2000	Adachi	N/A	N/A
6315180	12/2000	Watkins	N/A	N/A
6332146	12/2000	Jebens	N/A	N/A
6360928	12/2001	Russo	N/A	N/A
D460474	12/2001	Gotham, Sr.	N/A	N/A
D462893	12/2001	Sung	N/A	N/A
6480671	12/2001	Takahashi	N/A	N/A
6483542	12/2001	Morinaga	N/A	N/A
D467605	12/2001	Dordick	N/A	N/A
6530784	12/2002	Yim	N/A	N/A
6583809	12/2002	Fujiwara	N/A	N/A
6637904	12/2002	Hernandez	N/A	N/A
6654235	12/2002	Imsand	N/A	N/A

D483789	12/2002	Dordick	N/A	N/A
6727954	12/2003	Okado	N/A	N/A
6741287	12/2003	Fuchimukai	N/A	N/A
D491968	12/2003	Isshiki	N/A	N/A
D492893	12/2003	Oddsens, Jr.	N/A	N/A
D494450	12/2003	Schultz	N/A	N/A
6809759	12/2003	Chiang	N/A	N/A
D504904	12/2004	Nagai	N/A	N/A
6955484	12/2004	Woodman	N/A	N/A
D511960	12/2004	Ogino	N/A	N/A
D515121	12/2005	Bleau	N/A	N/A
D515613	12/2005	Holmes	N/A	N/A
D515910	12/2005	Gates	N/A	N/A
7011460	12/2005	Todd	N/A	N/A
7060921	12/2005	Kubo	N/A	N/A
7077582	12/2005	Johnson	N/A	N/A
7129981	12/2005	Berstis	N/A	N/A
7185862	12/2006	Yang	N/A	N/A
7196722	12/2006	White	N/A	N/A
7226261	12/2006	Bristol	N/A	N/A
D551969	12/2006	Aurilio	N/A	N/A
7285879	12/2006	Osaka	N/A	N/A
D555699	12/2006	Oh	N/A	N/A
7295388	12/2006	Shyu	N/A	N/A
D559083	12/2007	Brassard	N/A	N/A
7327396	12/2007	Schultz	N/A	N/A
7337403	12/2007	Pavley	N/A	N/A
7362352	12/2007	Ueyama	N/A	N/A
7379664	12/2007	Marcus	N/A	N/A
D571188	12/2007	Brassard	N/A	N/A
D576486	12/2007	Koza	N/A	N/A
D577729	12/2007	Derry	N/A	N/A
D577731	12/2007	Altonji	N/A	N/A
7440693	12/2007	Kouchi	N/A	N/A
D581255	12/2007	Calvin	N/A	N/A
D582955	12/2007	Sekine	N/A	N/A
7463304	12/2007	Murray	N/A	N/A
7464215	12/2007	Kawai	N/A	N/A
7494290	12/2008	Kim	N/A	N/A
7496293	12/2008	Shamir	N/A	N/A
7508420	12/2008	Kitajima	N/A	N/A
D591325	12/2008	Dordick	N/A	N/A
7537399	12/2008	Mayumi	N/A	N/A
7543327	12/2008	Kaplinsky	N/A	N/A
D596217	12/2008	Kim	N/A	N/A
D596658	12/2008	Dordick	N/A	N/A
7612821	12/2008	Hsia	N/A	N/A
7613386	12/2008	Shimamura	N/A	N/A
7643056	12/2009	Silsby	N/A	N/A
7656294	12/2009	Boss	N/A	N/A
7663666	12/2009	Kawai	N/A	N/A
7671886	12/2009	Sawada	N/A	N/A
7674081	12/2009	Selle	N/A	N/A
D616286	12/2009	Foresman	N/A	N/A
D616480	12/2009	Ookawa	N/A	N/A
D616742	12/2009	Lymn	N/A	N/A
7728905	12/2009	Tanaka	N/A	N/A
7752732	12/2009	Brown	N/A	N/A
7801425	12/2009	Fantone	N/A	N/A
D625750	12/2009	Dittmer	N/A	N/A
7823771	12/2009	Sawachi	N/A	N/A
D635445	12/2010	Foresman	N/A	N/A
D640304	12/2010	Green	N/A	N/A
8013932	12/2010	Chan	N/A	N/A
8014656	12/2010	Woodman	N/A	N/A
8026945	12/2010	Garoutte	N/A	N/A
D646313	12/2010	Woodman	N/A	N/A
8031222	12/2010	Crinon	N/A	N/A
D657808	12/2011	Woodman	N/A	N/A
8150248	12/2011	Woodman	N/A	N/A
8194145	12/2011	Lee	N/A	N/A
8194174	12/2011	Roskowski	N/A	N/A
8199251	12/2011	Woodman	N/A	N/A
8218025	12/2011	Yonaha	N/A	N/A
8235635	12/2011	Brown	N/A	N/A

8267361	12/2011	Dordick	N/A	N/A
8300107	12/2011	Strandwitz	N/A	N/A
D671394	12/2011	Derry	N/A	N/A
8325270	12/2011	Woodman	N/A	N/A
8328055	12/2011	Snyder	N/A	N/A
D675242	12/2012	O'Donnell	N/A	N/A
8348214	12/2012	Vogt	N/A	N/A
8356948	12/2012	Onishi	N/A	N/A
8368748	12/2012	Ho	N/A	N/A
8371729	12/2012	Sharrah	N/A	N/A
D679576	12/2012	Paul	N/A	N/A
D680097	12/2012	Davies	N/A	N/A
D683207	12/2012	Papadopoulos	N/A	N/A
8467675	12/2012	Chen	N/A	N/A
8485910	12/2012	Selle	N/A	N/A
D690280	12/2012	Schul	N/A	N/A
8542308	12/2012	Ozawa	N/A	N/A
8544643	12/2012	Yim	N/A	N/A
8638392	12/2013	Woodman	N/A	N/A
D699276	12/2013	Samuels	N/A	N/A
D699277	12/2013	Samuels	N/A	N/A
D700166	12/2013	Petersen	N/A	N/A
D701840	12/2013	Kazakia	N/A	N/A
D702276	12/2013	Woodman	N/A	N/A
8727642	12/2013	Tse	N/A	N/A
8743277	12/2013	Matsuzawa	N/A	N/A
8749966	12/2013	Boudreau	N/A	N/A
8792003	12/2013	Nakamura	N/A	N/A
8807849	12/2013	Apter	N/A	N/A
D713868	12/2013	Yang	N/A	N/A
8825124	12/2013	Davies	N/A	N/A
8827219	12/2013	Kessler	N/A	N/A
8830326	12/2013	Kitagawa	N/A	N/A
8837928	12/2013	Clearman	N/A	N/A
8870475	12/2013	Bennett	N/A	N/A
D718617	12/2013	Taylor	N/A	N/A
8917496	12/2013	Richardson	N/A	N/A
D722864	12/2014	Greenthal	N/A	N/A
D724637	12/2014	Samuels	N/A	N/A
D724638	12/2014	Samuels	N/A	N/A
8970689	12/2014	Campbell	N/A	N/A
8992102	12/2014	Samuels	N/A	N/A
D727387	12/2014	Hasegawa	N/A	N/A
D727991	12/2014	Hasegawa	N/A	N/A
9004783	12/2014	Woodman	N/A	N/A
9014766	12/2014	Hu	N/A	N/A
D729059	12/2014	Taylor	N/A	N/A
D729761	12/2014	Hu	N/A	N/A
D729762	12/2014	Hu	N/A	N/A
D730423	12/2014	Vandenbussche	N/A	N/A
9033596	12/2014	Samuels	N/A	N/A
D732593	12/2014	Woodman	N/A	N/A
D732933	12/2014	Jansen	N/A	N/A
9097962	12/2014	Johnson, Sr.	N/A	N/A
9122133	12/2014	Bennett	N/A	N/A
9152019	12/2014	Kintner	N/A	N/A
9161110	12/2014	Patsis	N/A	N/A
9204022	12/2014	Campbell	N/A	N/A
9204710	12/2014	Burns	N/A	N/A
9229299	12/2015	Morlon	N/A	N/A
9243737	12/2015	Hida	N/A	N/A
9243739	12/2015	Peters	N/A	N/A
9244337	12/2015	Weihe	N/A	N/A
D749164	12/2015	Raccah	N/A	N/A
9268200	12/2015	Clearman	N/A	N/A
9268201	12/2015	Montgomery	N/A	N/A
D750687	12/2015	Samuels	N/A	N/A
9282226	12/2015	Samuels	N/A	N/A
9297616	12/2015	Daniel	N/A	N/A
9297640	12/2015	Tassakos	N/A	N/A
9300345	12/2015	Johnson	N/A	N/A
D754238	12/2015	Woodman	N/A	N/A
9357115	12/2015	Campbell	N/A	N/A
9360742	12/2015	Harrison	N/A	N/A
9372383	12/2015	Johnson	N/A	N/A

9377672	12/2015	Clearman	N/A	N/A
9395031	12/2015	Clearman	N/A	F16M 13/00
9395603	12/2015	Achenbach	N/A	N/A
D762536	12/2015	Wurzer	N/A	N/A
D764566	12/2015	Bennett	N/A	N/A
D764567	12/2015	Bennett	N/A	N/A
9423673	12/2015	Clearman	N/A	N/A
9426341	12/2015	Baldrige	N/A	N/A
9507245	12/2015	Druker	N/A	N/A
9513535	12/2015	Bennett	N/A	N/A
9521302	12/2015	Samuels	N/A	N/A
D776746	12/2016	Bennett	N/A	N/A
D777240	12/2016	Costa	N/A	N/A
9551915	12/2016	Clearman	N/A	N/A
D780249	12/2016	Ramsthaler	N/A	N/A
9588407	12/2016	Harrison	N/A	N/A
9596388	12/2016	Woodman	N/A	N/A
9622556	12/2016	Fathollahi	N/A	N/A
9625791	12/2016	Harrison	N/A	N/A
9628681	12/2016	Clearman	N/A	N/A
9635226	12/2016	Samuels	N/A	N/A
9661197	12/2016	Clearman	N/A	N/A
9681029	12/2016	Harrison	N/A	N/A
9699360	12/2016	Woodman	N/A	N/A
D795061	12/2016	Bacallao	N/A	N/A
9736376	12/2016	Holway	N/A	N/A
9763548	12/2016	Theising	N/A	N/A
9772542	12/2016	Clearman	N/A	N/A
D799953	12/2016	Papafagos	N/A	N/A
D800205	12/2016	Harrison	N/A	N/A
D800822	12/2016	Costa	N/A	N/A
9823549	12/2016	Miyashita	N/A	N/A
9829772	12/2016	Harrison	N/A	N/A
9851622	12/2016	Song	N/A	N/A
9864257	12/2017	Wroblewski	N/A	N/A
9880451	12/2017	Clearman	N/A	N/A
D811335	12/2017	Weng	N/A	N/A
9904148	12/2017	Druker	N/A	N/A
9915855	12/2017	Miyashita	N/A	N/A
9926029	12/2017	Rucker	N/A	N/A
9930231	12/2017	Clearman	N/A	N/A
D818517	12/2017	Szarawarski	N/A	N/A
10025166	12/2017	Clearman	N/A	N/A
10094513	12/2017	Bennett	N/A	N/A
D837623	12/2018	Powers	N/A	N/A
D839946	12/2018	De Vries	N/A	N/A
D840795	12/2018	Tribbett	N/A	N/A
D841721	12/2018	Muhlenkamp, IV	N/A	N/A
D847609	12/2018	Ng	N/A	N/A
10306115	12/2018	Samuels	N/A	N/A
10356291	12/2018	Woodman	N/A	N/A
10416538	12/2018	Clearman	N/A	N/A
10511750	12/2018	Clearman	N/A	N/A
D873833	12/2019	Leimer	N/A	N/A
10539858	12/2019	Clearman	N/A	N/A
10547769	12/2019	Harrison	N/A	N/A
D874248	12/2019	Stekr	N/A	N/A
D879762	12/2019	Luo	N/A	N/A
D894256	12/2019	Vitale	N/A	N/A
D905786	12/2019	Vitale	N/A	N/A
10928711	12/2020	Vitale	N/A	N/A
D947357	12/2021	Chen	N/A	N/A
D989164	12/2022	Bergman	N/A	N/A
D989165	12/2022	Vitale	N/A	N/A
D990546	12/2022	Harrison	N/A	N/A
D1003979	12/2022	Alberstein	N/A	N/A
2001/0017339	12/2000	Brotz	N/A	N/A
2001/0043281	12/2000	Onuki	N/A	N/A
2002/0005907	12/2001	Alten	N/A	N/A
2002/0046218	12/2001	Gilbert	N/A	N/A
2002/0101534	12/2001	Liu	N/A	N/A
2002/0178116	12/2001	Yamasaki	N/A	N/A
2003/0035052	12/2002	Baron	N/A	N/A
2003/0085244	12/2002	Parsons	N/A	N/A
2003/0104806	12/2002	Ruef	N/A	N/A

2003/0115662	12/2002	Dobbie	N/A	N/A
2003/0156212	12/2002	Kingetsu	N/A	N/A
2003/0179306	12/2002	Lee	N/A	N/A
2004/0066457	12/2003	Silverstein	N/A	N/A
2004/0076415	12/2003	Da	N/A	N/A
2004/0095506	12/2003	Scott	N/A	N/A
2004/0201745	12/2003	Wess	N/A	N/A
2004/0212687	12/2003	Patwari	N/A	N/A
2004/0223752	12/2003	Ghanouni	N/A	N/A
2005/0025472	12/2004	Sugita	N/A	N/A
2005/0041966	12/2004	Johnson	N/A	N/A
2005/0122424	12/2004	Overstreet	N/A	N/A
2005/0190263	12/2004	Monroe	N/A	N/A
2005/0265711	12/2004	Heibel	N/A	N/A
2006/0007551	12/2005	Sakurai	N/A	N/A
2006/0015664	12/2005	Zhang	N/A	N/A
2006/0022108	12/2005	Kuga	N/A	N/A
2006/0061663	12/2005	Park	N/A	N/A
2006/0066753	12/2005	Gennetten	N/A	N/A
2006/0072020	12/2005	McCutchen	N/A	N/A
2006/0098966	12/2005	Takahashi	N/A	N/A
2006/0139459	12/2005	Zhong	N/A	N/A
2006/0177215	12/2005	Johnson	N/A	N/A
2006/0257137	12/2005	Fromm	N/A	N/A
2006/0262365	12/2005	Imao	N/A	N/A
2006/0274157	12/2005	Levien	N/A	N/A
2006/0274493	12/2005	Richardson	N/A	N/A
2007/0024734	12/2006	Headley	N/A	N/A
2007/0025711	12/2006	Marcus	N/A	N/A
2007/0053680	12/2006	Fromm	N/A	N/A
2007/0071423	12/2006	Fantone	N/A	N/A
2007/0077062	12/2006	Senba	N/A	N/A
2007/0109417	12/2006	Hyttfors	N/A	N/A
2007/0126883	12/2006	Ishige	N/A	N/A
2007/0140686	12/2006	Misawa	N/A	N/A
2007/0154254	12/2006	Bevirt	N/A	N/A
2007/0242134	12/2006	Zernov	N/A	N/A
2007/0244634	12/2006	Koch	N/A	N/A
2007/0268382	12/2006	Shiomi	N/A	N/A
2007/0268588	12/2006	Elias	N/A	N/A
2008/0011344	12/2007	Barker	N/A	N/A
2008/0023607	12/2007	Barker	N/A	N/A
2008/0063392	12/2007	Ahn	N/A	N/A
2008/0072163	12/2007	Teng	N/A	N/A
2008/0074487	12/2007	Ryckman	N/A	N/A
2008/0100712	12/2007	Hayes	N/A	N/A
2008/0107414	12/2007	Showalter	N/A	N/A
2008/0117328	12/2007	Daoud	N/A	N/A
2008/0122958	12/2007	Huseth	N/A	N/A
2008/0180537	12/2007	Weinberg	N/A	N/A
2008/0237414	12/2007	Lien	N/A	N/A
2008/0248703	12/2007	Russell	N/A	N/A
2008/0266389	12/2007	DeWind	N/A	N/A
2008/0267613	12/2007	Darrow	N/A	N/A
2008/0316327	12/2007	Steinberg	N/A	N/A
2008/0316734	12/2007	Spartano	N/A	N/A
2009/0003821	12/2008	Son	N/A	N/A
2009/0032420	12/2008	Zenzai	N/A	N/A
2009/0059064	12/2008	Terakado	N/A	N/A
2009/0109286	12/2008	Ennis	N/A	N/A
2009/0110380	12/2008	Fantone	N/A	N/A
2009/0111543	12/2008	Tai	N/A	N/A
2009/0173863	12/2008	Crown	N/A	N/A
2009/0206077	12/2008	Melmon	N/A	N/A
2009/0283184	12/2008	Han	N/A	N/A
2009/0321483	12/2008	Froloff	N/A	N/A
2010/0060747	12/2009	Woodman	N/A	N/A
2010/0061711	12/2009	Woodman	N/A	N/A
2010/0079607	12/2009	Won	N/A	N/A
2010/0118158	12/2009	Boland	N/A	N/A
2010/0141762	12/2009	Siann	N/A	N/A
2010/0205537	12/2009	Knighton	N/A	N/A
2010/0220188	12/2009	Renkis	N/A	N/A
2010/0229450	12/2009	Becker	N/A	N/A
2010/0246669	12/2009	Harel	N/A	N/A

2010/0252188	12/2009	Inanami	N/A	N/A
2010/0253832	12/2009	Duparre	N/A	N/A
2010/0266273	12/2009	Wood	N/A	N/A
2010/0283843	12/2009	Cai	N/A	N/A
2010/0289904	12/2009	Zhang	N/A	N/A
2010/0299814	12/2009	Celona	N/A	N/A
2010/0333155	12/2009	Royall	N/A	N/A
2011/0001834	12/2010	Herrell	N/A	N/A
2011/0042530	12/2010	Phillips	N/A	N/A
2011/0064401	12/2010	Desorbo	N/A	N/A
2011/0067322	12/2010	Taschek	N/A	N/A
2011/0129210	12/2010	McGucken	N/A	N/A
2011/0138673	12/2010	Deros	N/A	N/A
2011/0147245	12/2010	Yim	N/A	N/A
2011/0211820	12/2010	Yim	N/A	N/A
2011/0216195	12/2010	Tanaka	N/A	N/A
2011/0224798	12/2010	Caillouette	N/A	N/A
2011/0252188	12/2010	Weingarten	N/A	N/A
2011/0260022	12/2010	Lin	N/A	N/A
2011/0297578	12/2010	Stiehl	N/A	N/A
2011/0298970	12/2010	Shinohara	N/A	N/A
2011/0317065	12/2010	Lin	N/A	N/A
2012/0017922	12/2011	Hirshberg	N/A	N/A
2012/0043236	12/2011	Szucs	N/A	N/A
2012/0070223	12/2011	Wimberley	N/A	N/A
2012/0099849	12/2011	Onishi	N/A	N/A
2012/0120236	12/2011	Xiao	N/A	N/A
2012/0133758	12/2011	Foss	N/A	N/A
2012/0195585	12/2011	Wagner	N/A	N/A
2012/0224078	12/2011	Woodman	N/A	N/A
2012/0228346	12/2011	Huang	224/218	A45F 5/00
2012/0240444	12/2011	Russell	N/A	N/A
2012/0242785	12/2011	Sasagawa	N/A	N/A
2012/0242786	12/2011	Sasagawa	N/A	N/A
2012/0262618	12/2011	Weakly	N/A	N/A
2012/0288269	12/2011	Jensen	N/A	N/A
2012/0312309	12/2011	Zimmerman	N/A	N/A
2012/0315813	12/2011	Rossini	N/A	N/A
2012/0324682	12/2011	Ballentine	N/A	N/A
2013/0029515	12/2012	Lin	N/A	N/A
2013/0057758	12/2012	Woodman	N/A	N/A
2013/0082963	12/2012	Chu	N/A	N/A
2013/0107111	12/2012	Campbell	N/A	N/A
2013/0127309	12/2012	Wyner	N/A	N/A
2013/0148951	12/2012	Zhang	N/A	N/A
2013/0170823	12/2012	McDonald	N/A	N/A
2013/0184033	12/2012	Willenborg	N/A	N/A
2013/0186310	12/2012	Lymberis	N/A	N/A
2013/0250134	12/2012	McCauley	N/A	N/A
2013/0263865	12/2012	Khast	N/A	N/A
2013/0306689	12/2012	Johnson	N/A	N/A
2013/0315577	12/2012	Clark	N/A	N/A
2013/0324189	12/2012	Katis	N/A	N/A
2013/0331976	12/2012	Freeman	N/A	N/A
2014/0016922	12/2013	Greenthal	N/A	N/A
2014/0027591	12/2013	Fountain	N/A	N/A
2014/0028484	12/2013	Ho	N/A	N/A
2014/0036420	12/2013	Chen	N/A	N/A
2014/0050468	12/2013	Henry	N/A	N/A
2014/0060582	12/2013	Hartranft	N/A	N/A
2014/0066144	12/2013	Hong	N/A	N/A
2014/0069824	12/2013	Kalashnikov	N/A	N/A
2014/0090205	12/2013	Sarnowski	N/A	N/A
2014/0098241	12/2013	Stout	N/A	N/A
2014/0099093	12/2013	Johnson	N/A	N/A
2014/0104447	12/2013	Woodman	N/A	N/A
2014/0105589	12/2013	Samuels	N/A	N/A
2014/0190841	12/2013	Nash	N/A	N/A
2014/0226268	12/2013	ONeill et al.	N/A	N/A
2014/0231475	12/2013	Donnelly	N/A	N/A
2014/0252188	12/2013	Webster	N/A	N/A
2014/0267894	12/2013	Campbell	N/A	N/A
2014/0310915	12/2013	Tung	N/A	N/A
2014/0321843	12/2013	Hulse	N/A	N/A
2014/0353178	12/2013	Kim	N/A	N/A

2015/0030320	12/2014	Clearman	N/A	N/A
2015/0040917	12/2014	Gottsch	N/A	N/A
2015/0078737	12/2014	Albonico	N/A	N/A
2015/0122849	12/2014	Jones	N/A	N/A
2015/0130998	12/2014	Campbell	N/A	N/A
2015/0136620	12/2014	Williams	N/A	N/A
2015/0143618	12/2014	Pereira	N/A	N/A
2015/0171404	12/2014	Kwon	N/A	N/A
2015/0177597	12/2014	Harrison	N/A	N/A
2015/0180527	12/2014	Fathollahi	N/A	N/A
2015/0192841	12/2014	Bennett	N/A	N/A
2015/0195436	12/2014	Samuels	N/A	N/A
2015/0201113	12/2014	Wood	N/A	N/A
2015/0234258	12/2014	Hida	N/A	N/A
2015/0253651	12/2014	Russell	N/A	N/A
2015/0264226	12/2014	Gafni	N/A	N/A
2015/0286115	12/2014	Koch	N/A	N/A
2015/0286117	12/2014	Sung	N/A	N/A
2015/0288892	12/2014	Frank	N/A	N/A
2015/0305518	12/2014	Galant	N/A	N/A
2015/0312446	12/2014	Blackman	N/A	N/A
2015/0316205	12/2014	Bennett	224/181	G03B 17/563
2015/0323856	12/2014	Nordhaug	N/A	N/A
2015/0332129	12/2014	Murphy	N/A	N/A
2015/0346588	12/2014	Hudson	N/A	N/A
2015/0366093	12/2014	Battista	N/A	N/A
2015/0372705	12/2014	Fiorentino	N/A	N/A
2016/0077409	12/2015	Samuels	N/A	N/A
2016/0100083	12/2015	Harrison	N/A	N/A
2016/0119516	12/2015	Clearman	N/A	N/A
2016/0131963	12/2015	Clearman	N/A	N/A
2016/0131964	12/2015	Basulto	N/A	N/A
2016/0134788	12/2015	Clearman	N/A	N/A
2016/0139494	12/2015	Tien	N/A	N/A
2016/0186919	12/2015	Zhao	N/A	N/A
2016/0209733	12/2015	Akai	N/A	N/A
2016/0216597	12/2015	Lim	N/A	N/A
2016/0219202	12/2015	Barros	N/A	N/A
2016/0269629	12/2015	Martin	N/A	N/A
2016/0309064	12/2015	Woodman	N/A	N/A
2016/0330352	12/2015	Samuels	N/A	N/A
2016/0355121	12/2015	Gertsma	N/A	N/A
2016/0373623	12/2015	Woodman	N/A	N/A
2017/0050794	12/2016	Clark	N/A	N/A
2017/0059967	12/2016	Harrison	N/A	N/A
2017/0060184	12/2016	Ranetkins	N/A	N/A
2017/0090273	12/2016	Clearman	N/A	N/A
2017/0108759	12/2016	Clearman	N/A	N/A
2017/0142300	12/2016	Rice	N/A	N/A
2017/0176843	12/2016	Yamakose	N/A	G03B 17/04
2017/0223238	12/2016	Clearman	N/A	N/A
2017/0235213	12/2016	Clearman	N/A	N/A
2017/0255082	12/2016	Song	N/A	N/A
2017/0272626	12/2016	Harrison	N/A	N/A
2017/0289413	12/2016	Samuels	N/A	N/A
2017/0306672	12/2016	Romero Contreras et al.	N/A	N/A
2017/0324890	12/2016	Moskovchenko	N/A	N/A
2017/0339319	12/2016	Woodman	N/A	N/A
2018/0059514	12/2017	Druker	N/A	N/A
2018/0095343	12/2017	Wroblewski	N/A	N/A
2018/0136546	12/2017	Clearman	N/A	N/A
2018/0157153	12/2017	Clearman	N/A	N/A
2018/0220050	12/2017	Clearman	N/A	N/A
2019/0025675	12/2018	Druker	N/A	N/A
2019/0238729	12/2018	Samuels	N/A	N/A
2019/0258142	12/2018	Liu	N/A	N/A
2019/0281197	12/2018	Woodman	N/A	N/A
2019/0342473	12/2018	Clearman	N/A	N/A
2019/0342474	12/2018	Woodman	N/A	N/A
2019/0369466	12/2018	Clearman	N/A	N/A
2020/0159091	12/2019	Vitale	N/A	N/A
2021/0173288	12/2020	Vitale	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No. Application Date Country CPC

3468747D	12/2004	CN	N/A
1740899	12/2005	CN	N/A
100432830	12/2007	CN	N/A
201796220	12/2010	CN	N/A
301786205	12/2011	CN	N/A
202353622	12/2011	CN	N/A
302436013	12/2012	CN	N/A
302579018	12/2012	CN	N/A
302748860	12/2013	CN	N/A
302790142	12/2013	CN	N/A
303181818	12/2014	CN	N/A
303248953	12/2014	CN	N/A
104871082	12/2014	CN	N/A
105474089	12/2015	CN	N/A
303775763	12/2015	CN	N/A
106164768	12/2015	CN	N/A
303907057	12/2015	CN	N/A
303988503	12/2015	CN	N/A
106516141	12/2016	CN	N/A
304130943	12/2016	CN	N/A
304232547	12/2016	CN	N/A
206579852	12/2016	CN	N/A
304363793	12/2016	CN	N/A
304461932	12/2017	CN	N/A
304723510	12/2017	CN	N/A
109375454	12/2018	CN	N/A
110426910	12/2018	CN	N/A
305434602	12/2018	CN	N/A
305689289	12/2019	CN	N/A
111120817	12/2019	CN	N/A
305905490	12/2019	CN	N/A
211375284	12/2019	CN	N/A
306285361	12/2020	CN	N/A
202005004068	12/2004	DE	N/A
202013005239	12/2012	DE	N/A
202014011346	12/2018	DE	N/A
0845399	12/1997	EP	N/A
1160499	12/2000	EP	N/A
1653423	12/2005	EP	N/A
2464096	12/2011	EP	N/A
2906993	12/2014	EP	N/A
3025193	12/2015	EP	N/A
3092527	12/2015	EP	N/A
2018929	12/1978	GB	N/A
2363028	12/2000	GB	N/A
6006189	12/2016	GB	N/A
H05304625	12/1992	JP	N/A
2002006381	12/2001	JP	N/A
2003029330	12/2002	JP	N/A
2003330090	12/2002	JP	N/A
2004080256	12/2003	JP	N/A
2004221775	12/2003	JP	N/A
2005142671	12/2004	JP	N/A
D1265949	12/2005	JP	N/A
2007003648	12/2006	JP	N/A
2008109364	12/2007	JP	N/A
2008158143	12/2007	JP	N/A
D1400935	12/2009	JP	N/A
2011193209	12/2010	JP	N/A
2014191189	12/2013	JP	N/A
2004023795	12/2003	WO	N/A
2004081713	12/2003	WO	N/A
2005096760	12/2004	WO	N/A
2005098304	12/2004	WO	N/A
2007128317	12/2006	WO	N/A
2007130146	12/2006	WO	N/A
2010005975	12/2009	WO	N/A
2010005976	12/2009	WO	N/A
2013067340	12/2012	WO	N/A
2014062360	12/2013	WO	N/A
2015013054	12/2014	WO	N/A
2015102888	12/2014	WO	N/A
2016053472	12/2015	WO	N/A
2016064468	12/2015	WO	N/A
2016073188	12/2015	WO	N/A

YouTube video clip entitled "Customizable GoPro Cage—Go Tough Sharkcage Unboxing Video," uploaded on Dec. 17, 2014 by user "Fotodiox Inc". Retrieved v=x4lij96EtYA > (Year: 2014). cited by examiner

Day of the (most recent) update in DPMAregister' (German Patent and Trademark Office) Jul. 5, 2014 (Jul. 5, 2014), 19 Pages, [ONLINE] retrieved from DPM<URL:https://register.dpma.de/DPMAREgister/pat/register/PAT2020130052392_2015-10-137AKZ=2020130052392&VIEW=pdf>, (used to establish publication directly above). cited by applicant

GoPro Hero 3 Sports Wrist Camera Review, PaddleDogNation, 2006, 6 pages, [Online] [Retrieved on Aug. 8, 2007] Retrieved from the Internet <URL:http://ro3Ca...>. cited by applicant

Tekkno Trading Project—Brandnews, NSP, Jan. 2008, p. 59. cited by applicant

"WoCase 360 Degree Panoramic Swiveling Glove Mount Hand Mount (Compatible with left handed) for GoPro HERO4 HERO3+3 2 1 Cameras (Rotary Mo 2013, 8 pages, [online] [retrieved on Feb. 22, 2020] Retrieved from the internet <URL:http://www.amazon.com/WoCase-Panoramic-Swiveling-Compatible-C ie=UTF8&dplID=51%2BoLD9jb2L&dplSrc=sims&preST=_AC_UL160_SR160%2C160_&refRID=097XMG8E8BDXQAJRSS0D>. cited by applicant

Canon, 'Wireless file Transmitter WFT-EF E,' 2009, 132 pages, [Online] [Retrieved on Feb. 11, 2015] Retrieved from the Internet<URL:http://shuttersnitch.co applicant

Cheesycam.com, 'Remote LCD Live View + Remote Shutter for DSLR Video—Exciting!,' Jul. 16, 2010, 12 pages, [Online] [Retrieved on Feb. 11, 2015] Re lcd-live-view-for-dslr-video-exciting/>. cited by applicant

Chinese Office Action dated May 30, 2018 for CN Application No. 201480072371.9, (6 pages). cited by applicant

Design U.S. Appl. No. 29/661,818, filed Aug. 31, 2018, Huy Phuong Nguyen et al., 79 pages. cited by applicant

Design U.S. Appl. No. 29/661,819, filed Aug. 31, 2018, Vitale et al., 80 pages. cited by applicant

Design U.S. Appl. No. 29/681,087, filed Feb. 22, 2019, Vitale et al., 41 pages. cited by applicant

Design U.S. Appl. No. 29/694,559, filed Jun. 11, 2019, Coster et al., 28 pages. cited by applicant

Design U.S. Appl. No. 29/706,013, filed Sep. 17, 2019, Muhlenkamp et al., 97 pages. cited by applicant

Double male GoPro bar by eliotg Thingiverse. [online] Published on Jan. 16, 2016. Retrieved from URL:https://www.thingiverse.com/thing: 1273246 (2 page European Search Report for European Patent Application No. EP 14876907.8, Jan. 10, 2017, 8 Pages. cited by applicant

Fantaseal Action Camera Bike Mount Aluminum Alloy 2-Rail Saddle Bike Seat Mount for GoPro Pro Seat Rail Mount GoPro Bike Mount GoPro Bicycle Sea DBPOWER-BK. Online, published date unknown. Retrieved on May 23, 2018 from URL: https://www.amazon.com/fantaseal-Action-Camera-Bi (1 page). ci File Inspection—DE 20 2013 005 239.2, (MAAS) Retrieved on Oct. 13, 2015 (Oct. 13, 2015) entire document, 4 Pages, [ONLINE] retrieved from DPMAreg<URL:https://register.dpma.de/DPMAREgister/pat/PatAkteneinsicht?akz=2020130052392>. cited by applicant

Guarnera, M. et al., 'Manet: Possible Applications with PDA in Wireless Imaging Environment', IEEE International Symposium, Sep. 2002, vol. 7, pp. 239 http://web.archive.org/web/20190503083635/http://www.fvshare.com:80/en/vitag Note—wayback machine link may take extra time to load pictures May 3, https://www.amazon.com/Adjust-Straight-Joints-HSU-Direction/dp/B01IQPD9DU/ref=sr_1_1?keywords=long+and+short+straight+joint+tripod+mount+ada retrieved Feb. 22, 2020, 9 pages. cited by applicant

https://www.amazon.com/Fotasy-Aluminum-Folding-Release-Cameras/dp/B0058FJHR4/ref=sr_1_8?keywords=z+tripod+mount&qid=1582047698&sr=8-8, https://www.amazon.com/Tripod-Pistol-Cameras-Weighing-2-5lbs/dp/B0739YGN9M/ref=sr_1_1?keywords=Handheld+Grip+Mini+Tripod+Stand+for+DC+ Retrieved Feb. 22, 2020, 9 pages. cited by applicant

https://www.youtube.com/watch?v=sOfMcPM5Xg4 (@7:08 mark), retrieved Feb. 22, 2020. NO pdf attached. please see video at link. cited by applicant

Huang, J., "Part 19—Oct. 21: Interbike Bits and Baubles," Interbike Show, Las Vegas, Nevada, USA, Sep. 22-26, 2008, Cyclingnews.com, [Online] [Retrieved Internet<URL:http://www.cyclingnews.com/tech/2008/shows/interbike08/?i- d=result...>. 3 pages. cited by applicant

I Phone X Outfitting it for Adventure. [online] Published on Nov. 29, 2017. Retrieved from URL: https://explore.globalcreations.com/reviews/tools/outfitting Instagram Account for "mygomount", First post uploaded on Mar. 19, 2017, 3 Pages, [online] Retrieved on Jul. 25, 2017] Retrieved from the internet <URL:h applicant

International Preliminary Report on Patentability for App. No. PCT/US2019/045281, dated Feb. 18, 2021, 7 pages. cited by applicant

International Search Report and Written Opinion for Application No. PCT/US2019/045281, date of mailing Oct. 24, 2019, 10 pages. cited by applicant

International Search Report and Written Opinion for International Application No. PCT/US2014/046552, Aug. 18, 2014, 7 pages. cited by applicant

ION USA, 'Wi-Fi PODZ,' Date Unknown, 2 pages. [Online] [Retrieved Oct. 11, 2016] Retrieved from the internet <https://usa.ioncamera.com/shop/wi-fi-pod JP-05304625 A, 1993, 5 pages, (Machine Translation available from JPO website), [Online]. [Retrieved Dec. 14, 2014], Retrieved from the Internet <http://do u=http%3A%2F%2Fdossier1%...>. cited by applicant

JP5-304625 English Machine Translation available from JPO website. 2016. 7 pages. cited by applicant

Non-Final Rejection for U.S. Appl. No. 13/665,594 mailed Mar. 29, 2013, 25 Pages. cited by applicant

Non-Final Rejection for U.S. Appl. No. 12/498,890 mailed Aug. 30, 2011, 31 Pages. cited by applicant

Norouznezhad, E. et al. "A High Resolution Smart Camera with GigE Vision Extension for Surveillance Applications," Second ACM/IEEE International Conf applicant

Office Action for U.S. Patent Application No. U.S. Appl. No. 14/521,458, Feb. 25, 2016, 13 Pages. cited by applicant

Office Action for U.S. Patent Application No. U.S. Appl. No. 14/521,458, Jul. 28, 2015, 12 Pages. cited by applicant

PCT International Search Report and Written Opinion for PCT/US15/43958, Nov. 9, 2015, 14 Pages. cited by applicant

PCT International Search Report and Written Opinion for PCT/US15/45403, Nov. 19, 2015, 12 Pages. cited by applicant

PCT International Search Report and Written Opinion for PCT/US15/56478, Jan. 15, 2016, 9 Pages. cited by applicant

PCT International Search Report and Written Opinion for PCT/US2014/058465, Dec. 23, 2014, 17 pages. cited by applicant

PCT International Search Report and Written Opinion for PCT/US2014/070655, Apr. 29, 2015, 13 Pages. cited by applicant

PCT International Search Report and Written Opinion for PCT/US2015/028377, Jul. 24, 2015, 16 Pages. cited by applicant

PCT International Search Report and Written Opinion, PCT Application No. PCT/US2009/049821, Sep. 3, 2009, 8 pages. cited by applicant

PCT International Search Report and Written Opinion, PCT/US2012/063304, Jan. 22, 2013, 7 Pages. cited by applicant

PCT International Search Report for Written Opinion for PCT/US2013/062061, Mar. 3, 2014, 15 Pages. cited by applicant

Pro Camera Bracket Integrated Mount. Online, published date unknown. Retrieved on May 23, 2018 from URL: https://www.annaincycling.conn/pro-camera-prac0129/p612468 (1 page). cited by applicant

Pro Standard, "The Grill Mount Multi-Function Mouth Mount," Date unknown, 8 Pages, [online] [Retrieved on Jul. 25, 2017] Retrieved from the internet <U standard/products/the-grill-mount?variant=7683423299>. cited by applicant

Re-Fuel, '24hr Action Pack Battery for GoPro Hero4, Hero3+ & Hero3,' Date Unknown, 5 pages. [Online] [Retrieved Oct. 11, 2016] Retrieved from the inter pack.html>. cited by applicant

Spypoint Xcel Action Camera Adhesive Mount XHD-AM. Online, published date unknown. Retrieved on May 14, 2020 from URL: https://www.opticsplane page. cited by applicant

Sun, X. et al. "Region of Interest Extraction and Virtual Camera Control Based on Panoramic Video Capturing," IEEE Transactions on Multimedia, 2005, pp. Sewing Machine Table Folding Flip Hinge, Uxcell store, Amazon, https://www.amazon.com/uxcell-Sewing-Machine-Folding-Plating /dp/B07GQVB98L, Aug Supplementary European Search Report for European Patent Application No. EP 14829354, Aug. 16, 2016, 6 Pages. cited by applicant

The Telesin Tripod Mount Adapter, Telesin Tripod Mount Adapter for GoPro Hero 11/10/9/8/Max—telesinstore. cited by applicant
U.S. Appl. No. 16/697,947, filed Nov. 27, 2019, Vitale et al., 77 pages. cited by applicant
United States Advisory Action, U.S. Appl. No. 14/521,458, Aug. 12, 2016, 2 pages. cited by applicant
United States Advisory Action, U.S. Appl. No. 14/521,458, Jun. 20, 2016, 4 pages. cited by applicant
United States Advisory Action, U.S. Appl. No. 14/947,766, Aug. 29, 2016, 3 pages. cited by applicant
United States Office Action for U.S. Appl. No. 14/148,536, Jul. 9, 2014, 9 pages. cited by applicant
United States Office Action for U.S. Appl. No. 14/536,683, Dec. 18, 2014, 14 Pages. cited by applicant
United States Office Action for U.S. Appl. No. 14/536,683, Jun. 9, 2015, 16 pages. cited by applicant
United States Office Action for U.S. Appl. No. 14/536,683, Sep. 21, 2015, 15 Pages. cited by applicant
United States Office Action for U.S. Appl. No. 13/666,807, Oct. 6, 2014, 11 pages. cited by applicant
United States Office Action for U.S. Appl. No. 14/149,502, Jul. 9, 2014, 8 pages. cited by applicant
United States Office Action for U.S. Appl. No. 14/495,673, Jan. 28, 2015, 16 pages. cited by applicant
United States Office Action for U.S. Appl. No. 14/495,673, Mar. 24, 2015, 15 pages. cited by applicant
United States Office Action for U.S. Appl. No. 14/495,673, Nov. 7, 2014, 16 pages. cited by applicant
United States Office Action for U.S. Appl. No. 14/604,118, Apr. 14, 2015, 11 pages. cited by applicant
United States Office Action, U.S. Appl. No. 14/459,650, Jun. 10, 2015, 7 pages. cited by applicant
United States Office Action, U.S. Appl. No. 14/132,554, Apr. 24, 2015, 13 pages. cited by applicant
United States Office Action, U.S. Appl. No. 14/132,554, Dec. 3, 2015, 28 pages. cited by applicant
United States Office Action, U.S. Appl. No. 14/132,554, Feb. 26, 2016, 31 pages. cited by applicant
United States Office Action, U.S. Appl. No. 14/854,040, Feb. 4, 2016, 7 pages. cited by applicant
United States Office Action, U.S. Appl. No. 14/521,458, Feb. 25, 2016, 13 pages. cited by applicant
United States Office Action, U.S. Appl. No. 14/521,458, Jul. 28, 2015, 12 pages. cited by applicant
United States Office Action, U.S. Appl. No. 14/521,458, Sep. 20, 2016, 16 pages. cited by applicant
United States Office Action, U.S. Appl. No. 14/606,018, Dec. 2, 2016, 19 pages. cited by applicant
United States Office Action, U.S. Appl. No. 14/606,018, Jan. 13, 2016, 16 pages. cited by applicant
United States Office Action, U.S. Appl. No. 14/606,018, Jul. 15, 2016, 21 pages. cited by applicant
United States Office Action, U.S. Appl. No. 14/606,018, Jun. 2, 2016, 19 pages. cited by applicant
United States Office Action, U.S. Appl. No. 14/947,766, Apr. 21, 2016, 13 pages. cited by applicant
United States Office Action, U.S. Appl. No. 14/947,766, Aug. 16, 2016, 6 pages. cited by applicant
United States Office Action, U.S. Appl. No. 14/947,766, Nov. 9, 2016, 11 pages. cited by applicant
United States Office Action, U.S. Appl. No. 15/180,535, Jan. 17, 2017, 12 pages. cited by applicant
United States Office Action, U.S. Appl. No. 15/187,708, Oct. 7, 2016, 13 pages. cited by applicant
Vilta-G-Freevision Intelligent Technology, URL: <http://www.fvshare.com/en/vitag>, retrieved on Feb. 22, 2020, 8 pages. cited by applicant
Vixen Polaris Star Tracker Review. [online] Published date Mar. 22, 2013. Retrieved on Oct. 25, 2016 from <URL: <https://www.ephotozine.com/article/vixen>>
applicant
Volk, W., 'Go Pro's Digital Hero Camera,' Divester, Posted Dec. 5, 2008, [Online] [Retrieved on Sep. 16, 2009] Retrieved from the Internet <URL: <http://www>>
pages. cited by applicant
Yourdealer, 'Aputure Gigtube Digital Screen Remote Viewfinder gives you more remote control with most DSLRs,' 2009 Deals-World.com, Apr. 11, 2010, 3
the Internet <URL: <http://www.deals-world.com/deals/2010/04/11/aputure-gigtube-digital-screen-remote-viewfinder-gives-you-more-remote-control-with-most>>
Youtube.com, Video for 'The Air Pro Wi-Fi Podz,' Aug. 18, 2014, 1 page, [Online] [Retrieved Oct. 11, 2016] Can be retrieved from the internet <URL: <https://>>
applicant
Youtube.com, Video for 'The WiFi PODZ Tutorial,' Jun. 15, 2012, 2 pages. [Online] [Retrieved Oct. 11, 2016] Can be retrieved from the internet <URL: <https://>>
applicant
Extended European Search Report issued in App. No. EP24164959, dated May 27, 2024, 7 pages. cited by applicant
Insta360 GO 3 Pivot Stand, Insta360 Store, <https://store.insta360.com/product/go-3-pivot-stand>, 5 pages printed Apr. 19, 2024. cited by applicant
Insta360 GO 3 Quick Release Mount, insta360.com, <https://store.insta360.com/product/go-3-quick-release-mount>, 6 pages, printed Apr. 19, 2024. cited by applicant
Ulanzi Mount 1 (Ulanzi Mount 1), Ulanzi Falcam GoPro Mount to DJI Action Mount Magnetic Base 3234, <https://www.ulanzi.com/products/falcam-gopro-mount-to-dji-action-mount-magnetic-base-3234>,
currency=USD&variant=43790033617117&utm_medium=cpc&utm_source=google&utm_campaign=Google%20Shopping&stkn=100b30dffd7&gad_source=1&gclid=CjwKAEjYwposKpfiMltKxjimpkwSGC32ksaAugHEALw_wcB, Retrieved from Internet Mar. 26, 2024. cited by applicant
Ulanzi Mount 2 (Ulanzi Mount 2), Ulanzi Falcam F22 GoPro Mount to DJI Action Mount Magnetic Base 3235, <https://www.ulanzi.com/products/falcam-f22-go-pro-mount-to-dji-action-mount-magnetic-base-3235>,
Retrieved from Internet Mar. 26, 2024. cited by applicant
Ulanzi Mount 3 (Ulanzi Mount 3), Ulanzi Go-Quick II Magnetic Quick Release 1/4" Screw Adapter Mount Set C045GBB1, <https://www.ulanzi.com/products/go-quick-ii-magnetic-quick-release-1-4-screw-adapter-mount-set-c045gbb1>, Retrieved from Internet Mar. 26, 2024. cited by applicant
Ulanzi Mount 4 (Ulanzi Mount 4) Ulanzi Go Quick II Quick Release Basic Set, <https://www.ulanzi.com/products/ulanzi-go-quick-ii-quick-release-basic-set>,
HSU HGP235 Amazon product listing at <https://www.amazon.com/HSU-Replacement-Folding-Compatible-Connector/dp/B08R2XP8DW>, accessed Nov. 15,

Primary Examiner: Reisner; Noam

Attorney, Agent or Firm: Young Basile Hanlon & MacFarlane, P.C.

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION(S) (1) This application is a continuation of U.S. application Ser. No. 17/181,163, filed Feb. 22, 2021, which is a continuation of U.S. application Ser. No. 16/697,947, filed Nov. 27, 2019, now U.S. Pat. No. 10,928,711, which is a continuation-in-part of PCT Application No. PCT/US2019/045281, filed Aug. 6, 2019, which claims priority to and the benefit of U.S. Provisional Application No. 62/881,023, filed Jul. 31, 2019, U.S. Provisional Application No. 62/868,099, filed Jun. 28, 2019, U.S. Provisional Application No. 62/786,059, filed Dec. 28, 2018, and U.S. Provisional Application No. 62/715,794, filed Aug. 7, 2018, the entire disclosures of which are hereby incorporated by reference.

TECHNICAL FIELD

(1) This disclosure relates to electronic devices and, in particular, mounting systems for cameras.

SUMMARY

(2) Disclosed herein are implementations of electronic devices and mounts thereof.

(3) In one implementation, an electronic device includes a body, electronic components contained in the body, and two finger members. The two

finger members are movable relative to the body between an extended state and a collapsed state. In the extended state, the two finger members extend outward from the body for receipt by a mount of an external support. In the collapsed state, the two finger members are collapsed toward the body. In the extended state, the two finger members may extend parallel with each other for receipt in parallel slots of the mount of the external support.

(4) In one implementation, a mount for an electronic device includes a base and two finger members. The base is configured to couple to the electronic device. The two finger members are movable relative to the base between an extended state and a collapsed state. In the extended state, the two finger members extend parallel with each other to be insertable into parallel slots a support mount of an external support. In the collapsed state, the two finger members are biased away from each other.

(5) In one implementation, a mount for a camera includes two protrusions and a base. The two protrusions each include opposed planar surfaces that define a thickness of the protrusion, which is less than a width and a length of the protrusion. The protrusions are rotatably coupled to the base. The two protrusions are movable relative to the base between respective extended positions and collapsed positions. When the two protrusions are in the extended positions, the two protrusions extend parallel with each other in a common direction to define a slot therebetween.

(6) In an implementation, a camera mount includes two finger members that are coupleable to a camera. Each of the two finger members includes opposed planar surfaces that are parallel with and define a thickness of thereof and an aperture extending through the thickness. The two finger members are rotatable relative to the camera about different respective axes of rotation between respective extended positions and respective collapsed positions. When the finger members are in the respective extended positions, the camera mount is in an extended state with the finger members extending parallel with each other in a common direction and the apertures being coaxial with each other. When the finger members are in the respective collapsed positions, the camera mount is in a collapsed state. A camera may include a body, a lens coupled to the body, and the mount coupled to the body.

(7) In an implementation, a camera includes a body, electronic components contained in the body and including an image sensor, and two finger members coupled to and movable relative to the body between an extended state and a non-extended state. In the extended state, the two finger members extend away from the body for receipt by a mount of an external support. In the non-extended state, the two finger members are biased toward the body relative to the extended state.

(8) The camera may further include a mount assembly that includes a base and the two finger members rotatably coupled to the base. The base may be removably coupled to the body with the two finger members being coupled to the body of the camera by the base of the mount assembly. The two finger members may each include opposed planar surfaces that define a thickness thereof with the thickness being less than a width and a length thereof. The two finger members may be rotatable relative to the body about different axes to move between the extended state and the non-extended state. The two finger members may rotate toward each other when moving from the non-extended state to the extended state. In the extended state, the finger members may be parallel and extend in a common direction away from the body. In the non-extended state, the finger members may be parallel and extend in opposite directions. The two finger members may be retainable in each of the extended state and the non-extended state. In the non-extended state, each of the finger members may be contained substantially within a recess of the body. In the extended state, each of the finger members may protrude outward from the recess.

(9) In an implementation, a mount for a camera includes a base configured to couple to the camera, and two fingers that are movable relative to the base between an extended state and a non-extended state. In the extended state, the two fingers extend parallel with each other to be insertable into parallel slots of a support mount of an external support. In the non-extended state, the two fingers are biased away from each other as compared to the extended state. The two fingers may be rotatable relative to the base about parallel axes independent of each other. The mount may retain the fingers frictionally in the extended state and magnetically in the non-extended state. The two fingers may each include opposed planar surfaces that define a thickness thereof and an aperture extending through the thickness with the thickness being less than a width and a length thereof.

(10) In an implementation, a mount for a camera includes two protrusions and a base. Each of the protrusions includes opposed planar surfaces that define a thickness of the protrusion and an aperture extending through the thickness with thickness being less than a width and a length of the protrusion. The protrusions are coupled to the base and rotatable between respective first positions and respective second positions. When the two protrusions are in the respective first positions, the two protrusions extend parallel with each other in a common direction to define a slot therebetween.

(11) In an implementation, a camera mount includes a finger member that is coupleable to a camera. The finger member includes a proximal portion, a distal portion, an axis of rotation, and an aperture. The distal portion extends from the proximal portion and includes opposed planar surfaces that are parallel with each other and define a thickness thereof. The axis of rotation extends through the proximal portion and about which the finger member is rotatable relative to the camera when coupled thereto. The aperture extends through the distal portion. An end of the distal portion is rounded about the aperture and includes a finger pick for a user to rotate the finger member about the axis of rotation.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The disclosure is best understood from the following detailed description when read in conjunction with the accompanying drawings. It is emphasized that, according to common practice, the various features of the drawings are not to-scale. On the contrary, the dimensions of the various features are arbitrarily expanded or reduced for clarity.
- (2) FIGS. 1A-C are perspective views of an example of an image capture device.
- (3) FIGS. 2A-B are perspective views of another example of an image capture device.
- (4) FIG. 2C is a cross-sectional view of the image capture device of FIGS. 2A-B.
- (5) FIGS. 3A-B are block diagrams of examples of image capture systems.
- (6) FIG. 4A is a bottom perspective view of a camera having a mount coupled to an external mount.
- (7) FIG. 4B is a bottom perspective view of the camera of FIG. 1 with the mount in an extended state.
- (8) FIG. 4C is a bottom perspective view of the camera of FIG. 1 with the mount in a collapsed state.
- (9) FIG. 4D is a bottom perspective view of the camera of FIG. 1 without the mount.
- (10) FIG. 5 is an upper perspective view of the external mount of FIG. 4A.
- (11) FIG. 6 is a partial side view of the external mount.
- (12) FIG. 7 is an upper perspective view of the mount in the collapsed state.
- (13) FIG. 8 is an upper perspective view of the mount in the extended state.
- (14) FIG. 9A is a cross-sectional view of the camera taken along line 9-9 in FIG. 4C.
- (15) FIG. 9B is the cross-sectional view of the camera taken along line 9-9 in FIG. 4C without the mount.
- (16) FIG. 9C is a cross-sectional view of a variation of the camera taken along line 9-9 in FIG. 4C.
- (17) FIG. 9D is the cross-sectional view of the variation of the camera of FIG. 9C.
- (18) FIG. 10A is an upside down, bottom perspective, cross-sectional view of a camera having another embodiment of a mount.
- (19) FIG. 10B is an upside down, bottom perspective, exploded view of the mount of FIG. 10B.
- (20) FIG. 10C is an upside down, bottom perspective, cross-sectional view of the camera with the mount of FIG. 10A in an extended and connected state.

(21) FIG. **10D** is an upside down, bottom perspective, cross-sectional view of the camera with the mount of FIG. **10B** in an extended and disconnected state.

(22) FIG. **11** is a partial, upside down view of the mount having a retention mechanism.

(23) FIG. **12** is a partial view of the mount having another retention mechanism.

(24) FIG. **13** is a partial view of the mount having another retention mechanism.

(25) FIG. **14** is a partial view of the mount having another retention mechanism.

(26) FIG. **15** is a partial view of the mount having another retention mechanism.

(27) FIG. **16** is a partial view of the mount having another retention mechanism.

(28) FIG. **17** is a partial view of the mount having another retention mechanism.

(29) FIG. **18A** is a bottom perspective view of another embodiment of a mount in a collapsed state.

(30) FIG. **18B** is a bottom perspective view of the mount of FIG. **18A** in an extended state.

(31) FIG. **18C** is a bottom perspective, exploded view of the mount of FIG. **18A** in the extended state.

(32) FIG. **18D** is a top perspective, partial exploded view of the mount of FIG. **18A** in the collapsed state.

(33) FIG. **18E** is a simplified cross-sectional view of the mount taken along line **18E-18E** in FIG. **18D**.

(34) FIG. **18F** is a bottom perspective view of a variation of the mount of FIG. **18A**.

(35) FIG. **18G** is a bottom perspective view of a base of the variation of the mount of FIG. **18F**.

(36) FIG. **19** is a schematic view of a housing with a mount.

(37) FIG. **20A** is a side view of the camera of FIG. **4A** with a housing.

(38) FIG. **20B** is a bottom view of the camera of FIG. **4A** with the housing of FIG. **20A**.

(39) FIG. **21** is a bottom view of a variation of the housing of FIG. **20A**.

DETAILED DESCRIPTION

(40) Disclosed herein are embodiments of electronic devices (e.g., cameras) and mounts therefor, which are configured to connect to an external mount for supporting the electronic device. FIGS. **1A-C** are perspective views of an example of an image capture device **100**. The image capture device **100** may include a body **102** having a lens **104** structured on a front surface of the body **102**, various indicators on the front of the surface of the body **102** (such as LEDs, displays, and the like), various input mechanisms (such as buttons, switches, and touch-screen mechanisms), and electronics (e.g., imaging electronics, power electronics, etc.) internal to the body **102** for capturing images via the lens **104** and/or performing other functions. The image capture device **100** may be configured to capture images and video and to store captured images and video for subsequent display or playback.

(41) The image capture device **100** may include various indicators, including LED lights **106** and LCD display **108**. The image capture device **100** may also include buttons **110** configured to allow a user of the image capture device **100** to interact with the image capture device **100**, to turn the image capture device **100** on, to operate latches or hinges associated with doors of the image capture device **100**, and/or to otherwise configure the operating mode of the image capture device **100**. The image capture device **100** may also include a microphone **112** configured to receive and record audio signals in conjunction with recording video.

(42) The image capture device **100** may include an I/O interface **114** (e.g., hidden as indicated using dotted lines). As best shown in FIG. **1B**, the I/O interface **114** can be covered and sealed by a removable door **115** of the image capture device **100**. The removable door **115** can be secured, for example, using a latch mechanism **115a** (e.g., hidden as indicated using dotted lines) that is opened by engaging the associated button **110** as shown.

(43) The removable door **115** can also be secured to the image capture device **100** using a hinge mechanism **115b**, allowing the removable door **115** to pivot between an open position allowing access to the I/O interface **114** and a closed position blocking access to the I/O interface **114**. The removable door **115** can also have a removed position (not shown) where the entire removable door **115** is separated from the image capture device **100**, that is, where both the latch mechanism **115a** and the hinge mechanism **115b** allow the removable door **115** to be removed from the image capture device **100**.

(44) The image capture device **100** may also include another microphone integrated into the body **102** or housing. The front surface of the image capture device **100** may include two drainage ports as part of a drainage channel. The image capture device **100** may include an interactive display **120** that allows for interaction with the image capture device **100** while simultaneously displaying information on a surface of the image capture device **100**. As illustrated, the image capture device **100** may include the lens **104** that is configured to receive light incident upon the lens **104** and to direct received light onto an image sensor internal to the lens **104**.

(45) The image capture device **100** of FIGS. **1A-C** includes an exterior that encompasses and protects internal electronics. In the present example, the exterior includes six surfaces (i.e. a front face, a left face, a right face, a back face, a top face, and a bottom face) that form a rectangular cuboid. Furthermore, both the front and rear surfaces of the image capture device **100** are rectangular. In other embodiments, the exterior may have a different shape. The image capture device **100** may be made of a rigid material such as plastic, aluminum, steel, or fiberglass. The image capture device **100** may include features other than those described here. For example, the image capture device **100** may include additional buttons or different interface features, such as interchangeable lenses, cold shoes and hot shoes that can add functional features to the image capture device **100**, etc.

(46) The image capture device **100** may include various types of image sensors, such as a charge-coupled device (CCD) sensors, active pixel sensors (APS), complementary metal-oxide-semiconductor (CMOS) sensors, N-type metal-oxide-semiconductor (NMOS) sensors, and/or any other image sensor or combination of image sensors.

(47) Although not illustrated, in various embodiments, the image capture device **100** may include other additional electrical components (e.g., an image processor, camera SoC (system-on-chip), etc.), which may be included on one or more circuit boards within the body **102** of the image capture device **100**.

(48) The image capture device **100** may interface with or communicate with an external device, such as an external user interface device, via a wired or wireless computing communication link (e.g., the I/O interface **114**). The user interface device may, for example, be the personal computing device **360** described below with respect to FIG. **3B**. Any number of computing communication links may be used. The computing communication link may be a direct computing communication link or an indirect computing communication link, such as a link including another device or a network, such as the internet, may be used.

(49) In some implementations, the computing communication link may be a Wi-Fi link, an infrared link, a Bluetooth (BT) link, a cellular link, a ZigBee link, a near field communications (NFC) link, such as an ISO/IEC 20643 protocol link, an Advanced Network Technology interoperability (ANT+) link, and/or any other wireless communications link or combination of links.

(50) In some implementations, the computing communication link may be an HDMI link, a USB link, a digital video interface link, a display port interface link, such as a Video Electronics Standards Association (VESA) digital display interface link, an Ethernet link, a Thunderbolt link, and/or other wired computing communication link.

(51) The image capture device **100** may transmit images, such as panoramic images, or portions thereof, to the user interface device (not shown) via the computing communication link, and the user interface device may store, process, display, or a combination thereof the panoramic images.

(52) The user interface device may be a computing device, such as a smartphone, a tablet computer, a phablet, a smart watch, a portable computer, and/or another device or combination of devices configured to receive user input, communicate information with the image capture device **100** via the computing communication link, or receive user input and communicate information with the image capture device **100** via the computing

communication link **22**.

(53) The user interface device may display, or otherwise present, content, such as images or video, acquired by the image capture device **100**. For example, a display of the user interface device may be a viewport into the three-dimensional space represented by the panoramic images or video captured or created by the image capture device **100**.

(54) The user interface device may communicate information, such as metadata, to the image capture device **100**. For example, the user interface device may send orientation information of the user interface device with respect to a defined coordinate system to the image capture device **100**, such that the image capture device **100** may determine an orientation of the user interface device relative to the image capture device **100**.

(55) Based on the determined orientation, the image capture device **100** may identify a portion of the panoramic images or video captured by the image capture device **100** for the image capture device **100** to send to the user interface device for presentation as the viewport. In some implementations, based on the determined orientation, the image capture device **100** may determine the location of the user interface device and/or the dimensions for viewing of a portion of the panoramic images or video.

(56) The user interface device may implement or execute one or more applications to manage or control the image capture device **100**. For example, the user interface device may include an application for controlling camera configuration, video acquisition, video display, or any other configurable or controllable aspect of the image capture device **100**.

(57) The user interface device, such as via an application, may generate and share, such as via a cloud-based or social media service, one or more images, or short video clips, such as in response to user input. In some implementations, the user interface device, such as via an application, may remotely control the image capture device **100** such as in response to user input.

(58) The user interface device, such as via an application, may display unprocessed or minimally processed images or video captured by the image capture device **100** contemporaneously with capturing the images or video by the image capture device **100**, such as for shot framing, which may be referred to herein as a live preview, and which may be performed in response to user input. In some implementations, the user interface device, such as via an application, may mark one or more key moments contemporaneously with capturing the images or video by the image capture device **100**, such as with a tag, such as in response to user input.

(59) The user interface device, such as via an application, may display, or otherwise present, marks or tags associated with images or video, such as in response to user input. For example, marks may be presented in a camera roll application for location review and/or playback of video highlights.

(60) The user interface device, such as via an application, may wirelessly control camera software, hardware, or both. For example, the user interface device may include a web-based graphical interface accessible by a user for selecting a live or previously recorded video stream from the image capture device **100** for display on the user interface device.

(61) The user interface device may receive information indicating a user setting, such as an image resolution setting (e.g., 3840 pixels by 2160 pixels), a frame rate setting (e.g., 60 frames per second (fps)), a location setting, and/or a context setting, which may indicate an activity, such as mountain biking, in response to user input, and may communicate the settings, or related information, to the image capture device **100**.

(62) FIGS. 2A-B illustrate another example of an image capture device **200**. The image capture device **200** includes a body **202** and two camera lenses **204**, **206** disposed on opposing surfaces of the body **202**, for example, in a back-to-back or Janus configuration.

(63) The image capture device may include electronics (e.g., imaging electronics, power electronics, etc.) internal to the body **202** for capturing images via the lenses **204**, **206** and/or performing other functions. The image capture device may include various indicators such as an LED light **212** and an LCD display **214**.

(64) The image capture device **200** may include various input mechanisms such as buttons, switches, and touchscreen mechanisms. For example, the image capture device **200** may include buttons **216** configured to allow a user of the image capture device **200** to interact with the image capture device **200**, to turn the image capture device **200** on, and to otherwise configure the operating mode of the image capture device **200**. In an implementation, the image capture device **200** includes a shutter button and a mode button. It should be appreciated, however, that, in alternate embodiments, the image capture device **200** may include additional buttons to support and/or control additional functionality.

(65) The image capture device **200** may also include one or more microphones **218** configured to receive and record audio signals (e.g., voice or other audio commands) in conjunction with recording video.

(66) The image capture device **200** may include an I/O interface **220** and an interactive display **222** that allows for interaction with the image capture device **200** while simultaneously displaying information on a surface of the image capture device **200**.

(67) The image capture device **200** may be made of a rigid material such as plastic, aluminum, steel, or fiberglass. In some embodiments, the image capture device **200** described herein includes features other than those described. For example, instead of the I/O interface **220** and the interactive display **222**, the image capture device **200** may include additional interfaces or different interface features. For example, the image capture device **200** may include additional buttons or different interface features, such as interchangeable lenses, cold shoes and hot shoes that can add functional features to the image capture device **200**, etc.

(68) FIG. 2C is a cross-sectional view of the image capture device **200** of FIGS. 2A-B. The image capture device **200** is configured to capture spherical images, and accordingly, includes a first image capture device **224** and a second image capture device **226**. The first image capture device **224** defines a first field-of-view **228** as shown in FIG. 2C and includes the lens **204** that receives and directs light onto a first image sensor **230**.

(69) Similarly, the second image capture device **226** defines a second field-of-view **232** as shown in FIG. 2C and includes the lens **206** that receives and directs light onto a second image sensor **234**. To facilitate the capture of spherical images, the image capture devices **224**, **226** (and related components) may be arranged in a back-to-back (Janus) configuration such that the lenses **204**, **206** face in generally opposite directions.

(70) The fields-of-view **228**, **232** of the lenses **204**, **206** are shown above and below boundaries **236**, **238**, respectively. Behind the first lens **204**, the first image sensor **230** may capture a first hyper-hemispherical image plane from light entering the first lens **204**, and behind the second lens **206**, the second image sensor **234** may capture a second hyper-hemispherical image plane from light entering the second lens **206**.

(71) One or more areas, such as blind spots **240**, **242** may be outside of the fields-of-view **228**, **232** of the lenses **204**, **206** so as to define a “dead zone.” In the dead zone, light may be obscured from the lenses **204**, **206** and the corresponding image sensors **230**, **234**, and content in the blind spots **240**, **242** may be omitted from capture. In some implementations, the image capture devices **224**, **226** may be configured to minimize the blind spots **240**, **242**.

(72) The fields-of-view **228**, **232** may overlap. Stitch points **244**, **246**, proximal to the image capture device **200**, at which the fields-of-view **228**, **232** overlap may be referred to herein as overlap points or stitch points. Content captured by the respective lenses **204**, **206**, distal to the stitch points **244**, **246**, may overlap.

(73) Images contemporaneously captured by the respective image sensors **230**, **234** may be combined to form a combined image. Combining the respective images may include correlating the overlapping regions captured by the respective image sensors **230**, **234**, aligning the captured fields-of-view **228**, **232**, and stitching the images together to form a cohesive combined image.

(74) A slight change in the alignment, such as position and/or tilt, of the lenses **204**, **206**, the image sensors **230**, **234**, or both, may change the relative positions of their respective fields-of-view **228**, **232** and the locations of the stitch points **244**, **246**. A change in alignment may affect the size of the blind spots **240**, **242**, which may include changing the size of the blind spots **240**, **242** unequally.

(75) Incomplete or inaccurate information indicating the alignment of the image capture devices **224**, **226**, such as the locations of the stitch points **244**, **246**, may decrease the accuracy, efficiency, or both of generating a combined image. In some implementations, the image capture device **200** may maintain information indicating the location and orientation of the lenses **204**, **206** and the image sensors **230**, **234** such that the fields-of-view **228**, **232**, stitch points **244**, **246**, or both may be accurately determined, which may improve the accuracy, efficiency, or both of generating a

combined image.

(76) The lenses **204**, **206** may be laterally offset from each other, may be off-center from a central axis of the image capture device **200**, or may be laterally offset and off-center from the central axis. As compared to image capture devices with back-to-back lenses, such as lenses aligned along the same axis, image capture devices including laterally offset lenses may include substantially reduced thickness relative to the lengths of the lens barrels securing the lenses. For example, the overall thickness of the image capture device **200** may be close to the length of a single lens barrel as opposed to twice the length of a single lens barrel as in a back-to-back configuration. Reducing the lateral distance between the lenses **204**, **206** may improve the overlap in the fields-of-view **228**, **232**.

(77) Images or frames captured by the image capture devices **224**, **226** may be combined, merged, or stitched together to produce a combined image, such as a spherical or panoramic image, which may be an equirectangular planar image. In some implementations, generating a combined image may include three-dimensional, or spatiotemporal, noise reduction (3DNR). In some implementations, pixels along the stitch boundary may be matched accurately to minimize boundary discontinuities.

(78) FIGS. **3A-B** are block diagrams of examples of image capture systems.

(79) Referring first to FIG. **3A**, an image capture system **300** is shown. The image capture system **300** includes an image capture device **310** (e.g., a camera or a drone), which may, for example, be the image capture device **200** shown in FIGS. **2A-C**.

(80) The image capture device **310** includes a processing apparatus **312** that is configured to receive a first image from a first image sensor **314** and receive a second image from a second image sensor **316**. The image capture device **310** includes a communications interface **318** for transferring images to other devices. The image capture device **310** includes a user interface **320** to allow a user to control image capture functions and/or view images. The image capture device **310** includes a battery **322** for powering the image capture device **310**. The components of the image capture device **310** may communicate with each other via the bus **324**.

(81) The processing apparatus **312** may be configured to perform image signal processing (e.g., filtering, tone mapping, stitching, and/or encoding) to generate output images based on image data from the image sensors **314** and **316**. The processing apparatus **312** may include one or more processors having single or multiple processing cores. The processing apparatus **312** may include memory, such as a random-access memory device (RAM), flash memory, or another suitable type of storage device such as a non-transitory computer-readable memory. The memory of the processing apparatus **312** may include executable instructions and data that can be accessed by one or more processors of the processing apparatus **312**.

(82) For example, the processing apparatus **312** may include one or more dynamic random access memory (DRAM) modules, such as double data rate synchronous dynamic random-access memory (DDR SDRAM). In some implementations, the processing apparatus **312** may include a digital signal processor (DSP). In some implementations, the processing apparatus **312** may include an application specific integrated circuit (ASIC). For example, the processing apparatus **312** may include a custom image signal processor.

(83) The first image sensor **314** and the second image sensor **316** may be configured to detect light of a certain spectrum (e.g., the visible spectrum or the infrared spectrum) and convey information constituting an image as electrical signals (e.g., analog or digital signals). For example, the image sensors **314** and **316** may include CCDs or active pixel sensors in a CMOS. The image sensors **314** and **316** may detect light incident through a respective lens (e.g., a fisheye lens). In some implementations, the image sensors **314** and **316** include digital-to-analog converters. In some implementations, the image sensors **314** and **316** are held in a fixed orientation with respective fields of view that overlap.

(84) The communications interface **318** may enable communications with a personal computing device (e.g., a smartphone, a tablet, a laptop computer, or a desktop computer). For example, the communications interface **318** may be used to receive commands controlling image capture and processing in the image capture device **310**. For example, the communications interface **318** may be used to transfer image data to a personal computing device. For example, the communications interface **318** may include a wired interface, such as a high-definition multimedia interface (HDMI), a universal serial bus (USB) interface, or a FireWire interface. For example, the communications interface **318** may include a wireless interface, such as a Bluetooth interface, a ZigBee interface, and/or a Wi-Fi interface.

(85) The user interface **320** may include an LCD display for presenting images and/or messages to a user. For example, the user interface **320** may include a button or switch enabling a person to manually turn the image capture device **310** on and off. For example, the user interface **320** may include a shutter button for snapping pictures.

(86) The battery **322** may power the image capture device **310** and/or its peripherals. For example, the battery **322** may be charged wirelessly or through a micro-USB interface.

(87) Referring to FIG. **3B**, another image capture system **330** is shown. The image capture system **330** includes an image capture device **340** and a personal computing device **360** that communicate via a communications link **350**. The image capture device **340** may, for example, be the image capture device **100** shown in FIGS. **1A-C**. The personal computing device **360** may, for example, be the user interface device described with respect to FIGS. **1A-C**.

(88) The image capture device **340** includes an image sensor **342** that is configured to capture images. The image capture device **340** includes a communications interface **344** configured to transfer images via the communication link **350** to the personal computing device **360**.

(89) The personal computing device **360** includes a processing apparatus **362** that is configured to receive, using a communications interface **366**, images from the image sensor **342**. The processing apparatus **362** may be configured to perform image signal processing (e.g., filtering, tone mapping, stitching, and/or encoding) to generate output images based on image data from the image sensor **342**.

(90) The image sensor **342** is configured to detect light of a certain spectrum (e.g., the visible spectrum or the infrared spectrum) and convey information constituting an image as electrical signals (e.g., analog or digital signals). For example, the image sensor **342** may include CCDs or active pixel sensors in a CMOS. The image sensor **342** may detect light incident through a respective lens (e.g., a fisheye lens). In some implementations, the image sensor **342** includes digital-to-analog converters. Image signals from the image sensor **342** may be passed to other components of the image capture device **340** via a bus **346**.

(91) The communications link **350** may be a wired communications link or a wireless communications link. The communications interface **344** and the communications interface **366** may enable communications over the communications link **350**. For example, the communications interface **344** and the communications interface **366** may include an HDMI port or other interface, a USB port or other interface, a FireWire interface, a Bluetooth interface, a ZigBee interface, and/or a Wi-Fi interface. For example, the communications interface **344** and the communications interface **366** may be used to transfer image data from the image capture device **340** to the personal computing device **360** for image signal processing (e.g., filtering, tone mapping, stitching, and/or encoding) to generate output images based on image data from the image sensor **342**.

(92) The processing apparatus **362** may include one or more processors having single or multiple processing cores. The processing apparatus **362** may include memory, such as RAM, flash memory, or another suitable type of storage device such as a non-transitory computer-readable memory. The memory of the processing apparatus **362** may include executable instructions and data that can be accessed by one or more processors of the processing apparatus **362**. For example, the processing apparatus **362** may include one or more DRAM modules, such as DDR SDRAM.

(93) In some implementations, the processing apparatus **362** may include a DSP. In some implementations, the processing apparatus **362** may include an integrated circuit, for example, an ASIC. For example, the processing apparatus **362** may include a custom image signal processor. The processing apparatus **362** may exchange data (e.g., image data) with other components of the personal computing device **360** via a bus **368**.

(94) The personal computing device **360** may include a user interface **364**. For example, the user interface **364** may include a touchscreen display for presenting images and/or messages to a user and receiving commands from a user. For example, the user interface **364** may include a button or switch enabling a person to manually turn the personal computing device **360** on and off. In some implementations, commands (e.g., start recording video, stop recording video, or capture photo) received via the user interface **364** may be passed on to the image capture device **340** via the

communications link 350.

(95) Referring to FIGS. 4A-6, a camera 400, such as one of the image capture device 100, the image capture device 200, or a variation thereof, includes a body 410 and a mount 420 by which the camera 400 is coupled to another mount 442 of an external support 440. The mount 420 of the camera 400 is referred to herein as the device mount 420, but may also be referred to as a camera mount when used with a camera. The other mount 442 of the external support 440 is referred to herein as the support mount 442. Cooperatively, the device mount 420 and the support mount 442 may be referred to as a mounting system. Instead of a camera 400, another type of electronic device may be similarly configured with the device mount 420 described herein, such an output device (e.g., an electronic display, or speaker), an input device (e.g., a microphone), a control device (e.g., a remote control), a peripheral device (e.g., a battery, or communications interface, hub, or dock with which other devices are in communication), which may or may not be associate with the camera 400 or another image capture device. The external support 440 may be a tripod (as shown), or another type of mounting device, such as a bar mount (e.g., for handle bars of a bicycle), an elongated arm (e.g., a “selfie stick”), or a helmet mount. The device mount 420 may also be referred to as a mount assembly.

(96) The camera 400 includes one or more lenses 412 facing outward from the body 410 and electronic components suitable for capturing images contained therein (e.g., image sensor, image processor, memory, and/or power storage, such as a battery). For example, the camera 400 may be configured similar to the image capture device 100 as is shown (i.e., having only one lens 412) or as the image capture device 200 (i.e., having two of the lenses 412). The body 410 may, for example, be a housing that contains the electronic components therein and may be waterproof. The body 410 may, as shown, have a rectilinear shape having a bottom side 410a, an upper side opposite the bottom side 410a (not labeled in FIG. 4A), a front side 410b, a rear side opposite the front side 410b (not labeled in FIG. 4A), a right side 410c, and a left side opposite the right side 410c (not labeled in FIG. 4A). The one or more lenses 412 face outward, for example, from the front side 410b and/or the rear side. As is shown, the one or more lenses 412 are statically positioned and oriented relative to the body 410. For example, while the lenses 412 may be removable from the body 410, the one or more lenses 412 do not move relative to the various sides of the body 410 during normal operation. The body 410 may have any other suitable shape, such as having a rounded or irregular shape.

(97) Referring additionally to FIGS. 5 and 6, the device mount 420 and the support mount 442 include interlocking fingers by which the device mount 420 and the support mount 442 couple to each other. The support mount 442 includes three finger members 444 that define two parallel slots 446 therebetween, which receive finger members 422 of the device mount 420 corresponding thereto. The support mount 442 may also be referred to as a three-finger mount, while the device mount 420 may also be referred to as a two-finger mount. As discussed in further detail below, the finger members 422 of the device mount 420 are thin, flat planar structures having opposed planar faces that define a thickness thereof that is less than a width and a length thereof (e.g., less than one quarter of the width and/or the length). The finger members 444 of the support mount 442 define the parallel slots 446 with corresponding dimensions for interfitment (e.g., receipt) therein of the finger members 422 of the device mount 420. The finger members 422, 444 may also be referred to as fingers, arms, protrusions, planar protrusions, or members.

(98) Referring first to the support mount 442 of the external support 440, the three finger members 444 include a first outer finger member 444a, a second outer finger member 444b, and a central finger member 444c that is positioned between the first outer finger member 444a and the second outer finger member 444b. The central finger member 444c includes two planar surfaces 444c' that are parallel with and face away from each other and which may be referred to as opposed planar surfaces. The central finger member 444c has a thickness that is measured between and perpendicular to the two planar surfaces 444c' thereof.

(99) The first outer finger member 444a includes a planar surface 444a' that faces and is parallel with one of the two planar surfaces 444c' of the central finger member 444c. A first of the slots 446 is defined between the planar surface 444a' of the first outer finger member 444a and a first of the planar surfaces 444c' of the central finger member 444c. The first slot 446 has a width that is measured between and perpendicular to the planar surface 444a' of the first outer finger member 444a and the first planar surface 444c' of the central finger member 444c.

(100) The second outer finger member 444b includes a planar surface 444b' that faces and is parallel with a second of the two planar surfaces 444c' of the central finger member 444c. The planar surface 444b' of the second outer finger member 444b is also parallel with the first of the two planar surfaces 444c' of the central finger member 444c and the planar surface 444a' of the first outer finger member 444a. A second of the slots 446 is defined between the planar surface 444b' of the second outer finger member 444b and the second of the planar surfaces 444c' of the central finger member 444c. The second slot 446 has a width that is measured between and perpendicular to the planar surface 444b' of the second outer finger member 444b and the second planar surface 444c' of the central finger member 444c. The widths of the two slots 446 are the same. The three finger members 444 may be an integrally formed structure, such as being an injection molded plastic structure or a machined metal structure. The finger members 444 may also terminate at a common height (e.g., having rounded ends) and/or have a common width.

(101) The support mount 442 also includes a shaft 448, which functions to retain the device mount 420 of the camera 400 to the support mount 442. The three finger members 444 include apertures (not labeled) that are aligned with each other and through which the shaft 448 is positioned. The shaft 448 extends perpendicular to the finger members 444 and the slots 446. The shaft 448 is removable from the support mount 442, for example, being a threaded shaft (e.g., a thumb screw) having a threaded end that is received by a nut 450 of the support mount 442.

(102) Referring to FIGS. 4B-4D, the device mount 420 is reconfigurable (e.g., is collapsible, movable, or foldable) between a first configuration and a second configuration. In the first configuration (shown in FIG. 4B), the device mount 420 is arranged for being coupled to the support mount 442 of the external support 440 and, in particular, extends away from the body 410 for receipt by the support mount 442. The first configuration may also be referred to as an extended, protruding, unfolded, deployed, or mounting state or configuration. In the second configuration (shown in FIG. 4C), the device mount 420 is collapsed toward the body 410, for example, to use the camera 400 without the external support 440. In the second configuration, the device mount 420 is collapsed toward the body 410, such that the camera 400 is more compact than in the extended state, for example, such that the camera 400 has a lesser height when the device mount 420 is collapsed than when extended. In the collapsed state, the device mount may be configured to not be receivable (e.g., not be fully receivable) by the support mount 442 of the external support 440 for retention thereto (e.g., with the shaft 448). The second configuration may also be referred to as a collapsed, recessed, folded, non-deployed, non-extended, or non-mounting state or configuration. The device mount 420 is also removable from the body 410 (shown in FIG. 4D), or may alternatively be permanently coupled thereto.

(103) Referring additionally to FIGS. 7-8, the device mount 420 generally includes the two finger members 422, referenced above, and a base 424. The two finger members 422 correspond to the two slots 446 of the support mount 442 and, when the device mount 420 is in the extended state, are insertable into the slots 446 of the support mount 442.

(104) The finger members 422 are coupled to and movable relative to the base 424. As shown, the finger members 422 rotate relative to the base 424 between respective extended positions (shown in FIG. 8; see also FIG. 4B) and collapsed positions (shown in FIG. 7; see also FIG. 4C). For example, as shown, the finger members 422 are coupled to a side of the body 410 of the camera 400 (e.g., to the bottom side 410a via the base 424) and extend away from the side in the extended positions and extend along the side in the collapsed positions. As shown and further discussed below, the axes about which the finger members 422 rotate may have a fixed orientation relative to the body 410 (e.g., the sides thereof and/or the lens 412) when coupled to the body 410. For example, the finger members 422 may rotate substantially 90 degrees between the extended and collapsed positions and/or in opposite directions from each other (e.g., as indicated by the arrows in FIG. 8). The finger members 422 may rotate independent of each other, for example, such that one of the finger members 422 may be in the extended position, while the other of the finger members 422 may simultaneously be in the collapsed position. The base 424 is in turn coupled to the camera 400 along the bottom side 410a of the body 410, such that the finger members 422 are also rotatable relative to the body 410. When the finger members 422 are in the respective extended positions, the device mount 420 is in the first or extended state, and when finger members 422 are in the respective collapsed positions, the device mount 420 is in the

second or collapsed state. In the extended positions, the finger members 422 extend parallel with each other in a common direction, for example, with the planar surfaces 422a of the two finger members 422 being parallel with each other. As is shown, in the extended state, the finger members 422 extend from the bottom side 410a and away from the body 410 of the camera 400, such as downward therefrom and/or generally perpendicular to the direction in which the lens 412 faces (e.g., an optical axis thereof). In the extended state, the finger members 422 are simultaneously receivable in the slots 446 (i.e., between the finger members 444) of the support mount.

(105) In the collapsed positions, the finger members 422 extend away from each other. For example, the finger members 422 may extend away from each other in parallel, for example, with the planar surfaces 422a of the two finger members 422 being parallel with each other and/or in a common plane (e.g., with the one of the planar surfaces 422a of each of the two finger members 422 being coplanar). When either of the finger members 422 is in the collapsed position, the finger members 422 are not simultaneously receivable in the slots 446 of the support mount. In other embodiments, the base 424 may be omitted with the finger members 422 being coupled directly to the body 410 of the camera 400, or otherwise coupled to the body 410 of the camera (e.g., with the hinge pins 428 directly engaging the body 410 of the camera 400). As compared to the extended state or positions, the finger members 422 are biased away from each other and/or toward (e.g., are closer to) the body 410 of the camera 400 when in the collapsed state or positions.

(106) The two finger members 422 are flat, elongated members configured to be received in one of the slots 446 of the support mount 442 of the external support 440. Each finger member 422 includes a proximal portion 422b and a distal portion 422c having two planar surfaces 422a (e.g., opposed planar surfaces). The proximal portion 422b is proximal to and rotatably coupled to the base 424. The distal portion 422c extends from the proximal portion 422b and is configured to be inserted into one of the slots 446 of the external support 440. As each finger member 422 is rotated from the extended position to the collapsed position, the distal portion 422c is moved toward the body 410. As the two finger members 422 are rotated from the respective extended positions to the collapsed positions, the distal portions 422c of the two finger members are moved away from each other. The distal portion 422c may have an end shape that is rounded (e.g., semi-circular) to facilitate pivoting of the finger members 422 when coupled to the support mount 442 (e.g., about the shaft 448).

(107) The two planar surfaces 422a of the distal portion 422c of each finger member 422 are parallel with and face away from each other. The distal portion 422c of the finger member 422 has a thickness that is measured between and perpendicular to the two planar surfaces 422a thereof. The thickness of distal portion 422c of each finger member 422 is approximately equal to the width of each slot 446 of the external support 440 into which the finger member 422 is received. As a result, the planar surfaces 422a of the finger members 422 engage the planar surfaces 444a', 444b', and 444c' of the finger members 444, which may create friction therebetween to hinder movement of the device mount 420 of the camera 400 relative to the external support 440. The thicknesses of the distal portions 422c of the two finger members 422 are the same as each other, for example, such that either finger member 422 of the device mount 420 may be inserted into either of the slots 446 of the support mount 442.

(108) When the finger members 422 are in the respective extended positions, one of the planar surfaces 422a of each of the finger members 422 (i.e., those of the planar surfaces 422a that face away from the body 410 in the collapsed positions) are parallel with each other and spaced apart facing each other to define a slot 426 in which the central finger member 444c of the external support 440 is receivable. For example, as is shown, in the extended state, the planar surfaces 422a of the finger members 422 extend away from the body 410 of the camera 400, such as downward therefrom and/or generally perpendicular to a direction in which the lens 412 faces (e.g., forward direction). A width of the slot 426 of the device mount 420 is measured between and perpendicular to the two planar surfaces 422a of the two finger members 422 facing each other in the extended states. The width of the slot 426 of the device mount 420 is approximately equal to the thickness of the central finger member 444c of the external support 440 for receipt thereof. The width of the slot 426 of the device mount 420 may, as shown, also be approximately equal to the thickness of the two finger members 422 (e.g., within 35%, 25%, 15%, or 10% of the thickness thereof).

(109) The finger members 422 additionally include apertures 429 extending therethrough (e.g., through the planar surfaces 422a thereof), which are configured to receive the shaft 448 of the support mount 442 therethrough. When the device mount 420 is inserted into the support mount 442 (i.e., with the finger members 422 inserted into the slots 446), the shaft 448 may be inserted through the apertures 429 of the finger members 422 and the apertures (not shown) of the support mount 442, so as to retain the device mount 420 to the support mount 442. The camera 400 may, thereby, be coupled and retained to the external support 440. Furthermore, the shaft 448 may be tightened (e.g., into the nut 450), so as to press the finger members 422 of the device mount 420 and the finger members 444 of the support mount 442 against each other to increase friction therebetween.

(110) The finger members 422 may, for example, be made of a metal material (e.g., aluminum, steel) according to any suitable manufacturing process or combination of processes (e.g., casting and/or machining). Alternatively, the finger members 422 may be made of a polymer (e.g., injection molded plastic), composite (e.g., glass-filled nylon), or combination of metal and polymer materials (e.g., a metal inner structure hingedly coupled to the base 424 and overmolded or otherwise covered with a polymer (e.g., plastic or elastomer). In some examples, the finger members 422 are formed of a metal material (e.g., machine aluminum) that is coated with one or more additional layers (e.g., metal plating, polymer coatings, phobic coatings, paint or color, anodizing, physical vapor deposited materials, among others). The additional layers coating the metal material of the finger members 422 may, for example, provide desired friction with the support mount 442 and/or desired aesthetics (e.g., color). In one example, the finger member 422 may be formed of aluminum and coated with a physical vapor deposition and a phobic (e.g., anti-fingerprint coating). When using a polymer, composite, or combination of materials, the polymer material may insulate the planar surfaces 422a from heat conducted from the body 410 to the base 424.

(111) As referenced above, the two finger members 422 are rotatably coupled to the base 424, which is in turn coupled to the camera 400 along the bottom side 410a of the body 410. For example, referring to FIG. 7, the base 424 may generally include a central portion 424a that is rotatably coupled to the two finger members 422, and two outer portions 424b that extend outward from the central portion 424a and are coupled to or otherwise interface with the body 410 of the camera 400. The central portion 424a and the outer portions 424b may form a unitary structure, for example, formed of metal (e.g., aluminum), polymer (e.g., injection molded plastic), composite, or combination of metal and polymer materials, or may be formed of multiple components that are coupled together.

(112) The finger members 422 are rotatable relative to the base 424, for example, about different axes of rotation that may, for example, be parallel (as shown), intersecting, or skew. As shown, when the finger members 422 are coupled to the body 410, such as when the device mount 420 is coupled to the body 410, the axes of rotation of the finger members 422 may be statically oriented relative to the body 410 and/or the one or more lenses 412 of the camera 400. For example, while device mount 420 may be removable and the finger members 422 are able to rotate between the extended and collapsed positions, the axes of rotation do not move relative to the body 410. For example, as shown, the axes of rotation of the finger members 422 may extend (e.g., are oriented) in a forward-rearward direction and/or extend generally in a common direction in which the one or more lenses 412 face (e.g., being parallel with optical axes of the one or more lenses 412). For example, as shown, when the two finger members 422 are moved from the extended position to the retracted position, one of the finger members 422 (e.g., a right finger member) rotates toward the right side 410d of the body 410 of the camera 400 and the other of the finger members 422 (e.g., a left finger member) rotates toward the left side 410e of the body 410 of the camera 400. To distinguish between the different axes of rotation of the finger members 422, the axes of rotation may be referred to, for example, as respective axes, different respective axes, parallel axes, first and second axes, or right and left axes.

(113) Each of the finger members 422 is coupled to the base 424, such as with a hinge pin 428. The hinge pin 428 extends through the proximal portion 422b of the finger member 422 (e.g., through a bore thereof) and the central portion 424a of the base 424. As shown, each hinge pin 428 may form the axis of rotation of the finger member 422 coupled thereto. Each hinge pin 428 may have a static position relative to the body 410 and/or the one or more lenses 412. For example, while device mount 420 may be removable from the camera 400 and the finger members 422 are able to rotate between the extended and collapsed positions, the hinge pins 428 may rotate relative to the body 410 but do not change position (e.g., in the axial or

radial directions relative to the hinge pin **428**), such that the axes of rotation remain in static orientation relative to the body **410**. The proximal portion **422b** of the finger member **422** may, for example, receive therein part of the central portion **424a** of the base **424**. For example, the proximal portion **422b** of the finger member **422** may include end segments **422b'** that are spaced apart to form a recess (e.g., a slot or gap) in which is received an outwardly-extending segment **424a'** of the central portion **424a** of the base **424** and through which the axes of rotation extend. As shown, the hinge pin **428** and, thereby, the axis of rotation of each finger member **422** is generally perpendicular to the direction that the apertures **429** extend through the finger member **422**. The proximal portion **422b** (e.g., the end segments **422b'**) may be rounded about the hinge pin **428** (e.g., the axis thereof). The end of the distal portion **422c** may be rounded about the aperture **429** (e.g., an axis thereof). As a result, the end of the proximal portion **422b** may be rounded about an axis that is perpendicular to the aperture **429** and/or the end of the distal portion **422c** may be rounded about an axis that is perpendicular to the hinge pin **428** (e.g., the axis about which the finger member **422** rotates). Further, the radius of the end of the distal portion **422c** may be larger than the radius of the end of the proximal portion **422b** or otherwise larger than a distance from the axis of rotation to the surface of the end of the proximal portion **422b** (e.g., being at least three, four, or five times greater than).

(114) The outwardly-extending segments **424a'** of the central portion **424a** of the base **424** extend laterally outward (e.g., left and right) from a central segment **424a''** of the central portion **424a** of the base **424**. For example, as shown, the outwardly-extending segments **424a'** and the central segment **424a''** may cooperatively form a cross-shape, such as with the outwardly-extending segments **424a'** of the central portion **424a** having a width (i.e., measured front to back) that is less than a width of the central segment **424a''**. Further, slots may be defined between central segment **424a''** and the outer portion **424b** in which the end segments **422b'** of the finger member **422** are positioned, which may result in no portion of the base **424** being positioned between the proximal portions **422b** of the finger member **422** and the body **410** of the camera **400**. A sum of widths of the end segments **422b'** of the finger members **422** and the width of the outwardly-extending segments **424a'** may be approximately equal to a width of the central segment **424a''**.

(115) Alternatively, as shown in FIGS. **18A-18E**, the base **424** may be configured to be arranged between the proximal portions **422b** of the finger members **422** and the external housing **419**. For example, the base **424** may not define slots between the central segment **424a''** of the central portion **424a** and the outer portion **424b** of the base **424** (e.g., with the base **424** having a generally constant thickness and/or width). For example, as described in further detail below with respect to FIGS. **18A-18E**, the base **424** may instead include a generally planar portion of generally constant thickness and a cross-shaped portion (e.g., similar to that formed by the outwardly-extending segments **424a'** and the central segment **424a''** extending downward therefrom).

(116) Further, the proximal portion **422b** of the finger members **422** (e.g., the end segments **422b'** thereof) may have a thickness (e.g., measured top to bottom in the collapsed state) that is approximately equal to a thickness of the central portion **424a** of the base **424** (e.g., outwardly-extending segments **424a'** and/or the central segment **424a''** thereof). The thickness of the distal portion **422c** (i.e., between the planar surfaces **422a**) is less than the thickness of the end segments **422b'** of the finger member **422**. A sum of the thicknesses of the distal portion **422c** of the finger member **422** and the outer portion **424b** of the base **424** (e.g., measured top to bottom in the collapsed state) may be approximately equal to the thickness of the end segments **422b'** of the finger member **422**, the outwardly-extending segments **424a'**, and/or the central segment **424a''** of the central portion **424a**.

(117) When in the extended state, the finger members **422** (e.g., the proximal portion **422b** and/or one of the planar surfaces **422a** thereof) may abut the central portion **424a** of the base **424** (e.g., the central segment **424a''**) to prevent further rotation toward each other. As a result, the finger members **422** are also prevented from further rotation by the central portions **424a** relative to the body **410** (e.g., relative to the bottom side **410a** thereof). The finger members **422**, thereby, remain spaced apart to define the slot **426** of the device mount **420** between the finger members **422**. When in the extended state, the apertures **429** of the finger members **422** share a common axis (e.g., of the shaft **448**), which may extend perpendicular to both axes of rotation of the finger members **422** and may also be spaced below the bottom side **410a** of the body **410**. When in the collapsed state, the apertures **429** have different axes, which may be parallel with each other and perpendicular to both axes of rotation of the finger members **422**.

(118) When in the collapsed state, the finger members **422** abut the outer portions **424b** of the base **424**. A sum of a thickness of the distal portion **422c** of the finger member **422** and the outer portion **424b** of the base **424** may be approximately equal to the thickness of the proximal portion **422b** of the finger member **422** and/or the central portion **424a** of the base **424**. When in the collapsed state, those planar surfaces **422a** of the two finger members **422** that define the slot **426** face away from the body **410** and may be coplanar with each other. Further, when in the collapsed state, the apertures **429** of the finger members **422** have different axes that, for example, are parallel and spaced apart from each other (e.g., extending through the bottom side **410a** and the top side of the body **410** of the camera **400**).

(119) While the proximal portion **422b** (e.g., the end segments **422b'**) have a thickness that is greater than the distal portion **422c**, in other configurations, the finger member **422** may be configured differently, such as having a generally constant thickness and/or being substantially planar (e.g., with planar parallel surfaces), as is illustrated with the finger members **10A-10D** and **18A-18E**.

(120) Referring again to FIGS. **4B-4D**, the base **424** is coupled to the camera **400** at the bottom side **410a** thereof. For example, referring to FIG. **4D**, the bottom side **410a** of the body **410** may define a recess **414** in which is received the base **424** of the device mount **420**. As is shown, when the device mount **420** is coupled to the body **410**, the device mount **420** and, in particular, the base **424** is statically positioned and oriented relative to the body **410**. For example, while device mount **420** may be removable and the finger members **422** are able to rotate between the extended and collapsed positions, the base **424** does not move relative to the body **410**. As a result, the axes of rotation of the finger members **422** and/or the hinge pins **428** are in a static orientation relative to the body **410** of the camera **400** and/or the lenses **412** (e.g., being held in the fixed orientation by the base **424**). Furthermore, as is also shown, the axes of rotation of the finger members **422** may extend through the recess **414** of the body **410** of the camera **400** and/or the hinge pins **428** may be positioned entirely with the recess **414** of the body **410** of the camera **400**.

(121) The base **424** is receivable by the recess **414** in a direction generally opposed to the side to which the base **424** is coupled (e.g., being received upward into the recess **414** on the bottom side **410a** of the body **410** of the camera **400**). The recess **414** may also receive the finger members **422**, wholly or partially, in the collapsed positions. For example, as shown in FIG. **4C** and additionally in FIGS. **9A-9D**, the finger members **422** may not protrude from the recess **414** when in the collapsed state (e.g., are flush with or preferably recessed relative to surrounding surfaces of the bottom side **410a**). With the device mount **420** being recessed relative to the surrounding surfaces of the bottom side **410a** of the body **410** of the camera **400**, the bottom side **410a** may define a flat surface that allows the camera **400** to rest in a stable manner on a flat support surface (e.g., a table).

(122) The recess **414** may have multiple depths for receipt of the base **424** of the device mount **420** and for receipt of the finger members **422** when in the collapsed state. For example, the recess **414** may have an inner region **414a** and an outer region **414b**, the inner region **414a** being positioned inward (e.g., laterally and vertically) of the outer region **414b** relative to the body **410**. The inner region **414a** of the recess **414** has a depth relative to the surrounding surfaces of the bottom side **410a** that is greater than a depth of the outer region **414b** of the recess **414**.

(123) The base **424** of the device mount **420** is received in the inner region **414a** of the recess **414**. The finger members **422** of the device mount **420** are received in the outer region **414b** of the recess **414** when in the collapsed state. For example, the thickness of the finger members **422** (e.g., of the distal portion **422c**) may be approximately the same as, or preferably less than, the depth of the outer region **414b** of the recess **414**. An overall thickness of the device mount **420** formed cooperatively by the thickness of the outer portion **424b** of the base **424** and the thickness of the finger members **422** (e.g., the distal portion **422c** between the planar surfaces **422a**) may be approximately equal to or preferably less than (as shown in FIGS. **9A-9D**) the depth of the inner region **414a** of the recess **414**. Further, the thickness of the finger members **422** (e.g., of the distal portion **422c** between the planar surfaces **422a**) may be approximately equal to or preferably less than (as shown in FIGS. **9A-9D**) the depth of the outer region **414b** of the recess **414**.

(124) As referenced above, the outer portions **424b** of the base **424** extend outward from the central portion **424a**. As a result, the base **424** may be

considered elongated. For example, the base **424** may have a length (e.g., measured left-to-right relative to the body **410**), which extends at least a majority (e.g., greater than 75%) of an overall length of the device mount **420** (e.g., measured between ends of the distal portions **422c** of the finger members **422**). For example, as shown, the base **424** may be sufficiently long to overlap the apertures **429** of the finger members **422**. By being elongated, the base **424** may distribute loading from the device mount **420** to the camera **400** (e.g., to the body **410** or an internal structure thereof, such as a chassis) over a large area. For example, as shown, the outer portions **424b** of the base **424** may be connected to the body **410** with fasteners (e.g., screws) at outer ends of the device mount **420** (e.g., two of the fasteners **417** on each of the left and right ends). Alternatively, the length of the base **424** may be shorter, for example, less than half the overall length of the device mount **420**, or sufficiently short to not overlap the apertures of the finger members **422** (see, e.g., FIGS. **18A-18E**).

(125) The finger members **422**, when in the collapsed positions, may block access to the fasteners (e.g., cover the fasteners). As a result, the device mount **420** may not be removable from the body **410** when the finger members **422** are in the collapsed state.

(126) The overall length of the device mount **420** may be slightly less than a length of the outer region **414b** of the recess **414**. By having a shorter length, ends of the distal portions **422c** of the finger members **422** may be accessible within the recess **414** for a user to fold the finger members **422** outward from the collapsed state to the extended state. The distal portions **422c** of the finger members **422** may further include indentations **422d** (e.g., finger picks) on the ends thereof, which allow the user to pull the finger members **422** out of the recess **414** into the extended positions. Alternatively, the recess **414** may omit one or both ends thereof providing unrestricted access to the ends (e.g., the indentations **422d**) of the finger members **422**.

(127) Referring to the cross-sectional view FIGS. **9A-9B**, the device mount **420** is configured to couple to a chassis **418** of the body **410** of the camera **400**. The body **410** includes the chassis **418**, which is a generally rigid structure to which the internal components of the camera **400** (e.g., the electronics, battery, etc., such as the processing apparatus **312**, image sensors **314**, **316**, etc.) are coupled, and an external housing **419** that contains the chassis **418** and the electronic components. For example, the external housing **419** may include one or more components formed of one or more polymer materials (e.g., elastomer overmolded to plastic) that define a compartment **416** that is waterproof, so as to protect the electronics therein. For example, the external housing **419** may include two external housing components that are coupled to each other with a seal therebetween and which define a waterproof cavity therein. Any apertures in the external housing components, such as for any input/output (I/O) components (e.g., microphones, speakers, displays, power, etc.) are sealed. The chassis **418** is formed of a metal material (e.g., one or more cast aluminum components) and also functions as a heat sink to conduct heat away from the electronic components. The chassis **418** is stiffer than the external housing **419**. In a variation of the body **410**, the compartment **416** is not waterproof.

(128) The chassis **418** includes a bottom segment **418a** at the bottom side **410a** of the body **410** and an upright segment **418b** (e.g., front or rear) extending upward from the bottom segment **418a** at the front side **410b** or the rear side of the body **410**. For example, the chassis **418** may be generally L-shaped. The bottom segment **418a** sufficiently spans the thickness and/or the width of the camera **400** for being coupled to the device mount **420**, such as a majority of the thickness and/or the width of the camera **400**. In the case of the device mount **1820**, the bottom segment **418a** may instead span less than a majority of the width of the camera **400**. The upright segment **418b** may span a majority of the width and/or height of the camera **400** (e.g., having a forward surface area that is greater than a majority of the surface area on the front side of the camera **400**). The external housing **419** similarly includes a bottom segment **419a** at the bottom side **410a** of the body **410** and outward of the bottom segment **418a** of the chassis **418**, as well as a front segment **419b** at the front side **410b** of the body **410** and outward of the upright segment **418b** of the chassis **418**. The bottom segment **419a** of the external housing **419** defines the recess **414** and, further, allows the fasteners **417** (e.g., screws) to couple the base **424** of the device mount **420** directly to the chassis **418**. For example, the bottom segment **418a** of the chassis **418** includes four screw holes **418a'** that threadably receive the fasteners **417**, while the bottom segment **419a** of the external housing **419** includes four corresponding through holes **419a'** (labeled in FIG. **6**) through which the fasteners **417** extend. Seals **415** (e.g., O-rings) extend around the screw holes **418a'** and the through holes **419a'** and are positioned (e.g., compressed) between the chassis **418** and the external housing **419** to prevent water leakage therebetween. Further, the screw holes **418a'** are blind screw holes or are otherwise sealed, such that water does not leak through the screw holes **418a'** themselves into body **410**. The screw holes **418a'** may engage the fasteners **417** over an axial length of, for example, above approximately 0.8 mm (e.g., above 1.0 mm) and below 3 mm (e.g., below 2 mm), such as approximately 1.2 mm or approximately 1.5 mm.

(129) As referenced above, when the finger members **422** of the device mount **420** are in the collapsed positions, the fasteners **417** are covered, such that the fasteners **417** are not accessible and the device mount **420** is not removable from the camera **400**. When the finger members **422** are moved to the extended positions, the fasteners **417** are uncovered and accessible with a suitable tool (e.g., a screw driver) and the device mount **420** is, thereby, removable from the camera **400**.

(130) Referring to FIGS. **9C-9D**, a variation of the body **410** includes a chassis **918** and a housing component **919** that cooperatively define a compartment **916** in which the various electronic components are positioned. Thus, rather than the chassis **918** being positioned within the compartment **416** as is the chassis **418**, the chassis **918** forms a surface that itself defines an interior surface of the compartment **916**. Any apertures in the chassis **918** and the housing component **919** (e.g., for I/O components) are sealed to ensure that the compartment **916** is waterproof. In a variation, the compartment **916** is not waterproof.

(131) The chassis **918** generally includes a lower segment **918a** and an upright segment **918a** (e.g., a front or rear segment or portion) extending upward therefrom. For example, the chassis **918** may be generally L-shaped. The lower segment **918a** sufficiently spans the thickness and/or the width of the camera **400** for being coupled to the device mount **420**, such as a majority of the thickness and/or the width of the camera **400**. In the case of the device mount **1820**, the lower segment **918a** may span less than a majority of the width of the camera **400**. The upright segment **918b** may span a majority of the width and/or the height of the camera **400** (e.g., having a surface area that is greater than a majority of the surface area on the corresponding side of the camera **400**). A cover **919a** may be positioned over and/or cover from view the upright segment **918a**, for example, having the same or complementary aesthetic and/or tactile properties as the housing component **919**.

(132) The chassis **918** and the housing component **919** are coupled to each other with a peripheral seal **917** therebetween, such as a gasket. The lower segment **918a** is positioned outside the compartment **916**, for example, being positioned below peripheral seal **917** and extending between the housing component **919** and the device mount **420** coupled thereto. With the lower segment **919b** positioned outside the compartment **916**, the device mount **420** may be coupled to the chassis **918** (i.e., the lower segment **918b** thereof) without further waterproofing (e.g., without the seals **415** shown in FIGS. **9A-9B**). For example, the chassis **918** may include screw holes **918a'** in the lower segment **919**, thereof, which receive the threaded fasteners **417**. The screw holes **918a'**, being in the lower segment **919b** that is outside the compartment **916**, may be open holes (e.g., apertures). The screw holes **918a'** may engage the fasteners **417** over an axial length of, for example, above approximately 0.8 mm (e.g., above 1.0 mm) and below 3 mm (e.g., below 2 mm), such as approximately 1.2 mm or approximately 1.5 mm.

(133) Referring to FIGS. **10A-10D**, a variation of the device mount **1020** is removable from a variation of the camera **1000** without a tool. The camera **1000** is configured similar to the camera **400** but is configured to couple to the device mount **1020** by including a stud **1016** that engages a spring clip **1027** of the device mount **1020**. The stud **1016** includes a base **1016a** (e.g., a plate) and a boss **1016b** coupled thereto and protruding therefrom. The base **1016a** is coupled to the bottom side **410a** of the camera **1000**, for example, being embedded in material forming the bottom segment **419a** of the external housing **419**. Alternatively, the base **1016a** may be coupled to the chassis **418**, for example, in the manner by which the base **424** is coupled to the chassis **418** (e.g., with fasteners **417**, such as threaded screws). The bottom segment **419a** of external housing defines a recess **414** in which the device mount **1020** is received, including an inner region **414a** for receiving the base **1016a**, which is deeper than an outer region **414b** of the recess **414** for receiving the finger members **1022**.

(134) The boss **1016b** of the stud **1016** has an outer surface with a generally constant diameter and includes opposed slots **1016c** recessed into the

outer surface. In an axial region that includes the slots **1016c**, the boss **1016b** has a variable diameter that increases circumferentially from a minimum diameter in the opposed slots **1016c** to a maximum diameter (e.g., the generally constant diameter) at positions between the slots **1016c** (e.g., rotated 90 degrees).

(135) The device mount **1020** includes finger members **1022**, a base **1024**, and a spring clip **1027**. The finger members **1022** are pivotally coupled to the base **1024** in substantially the same manner as the finger members **422** (e.g., within hinge pins extending therethrough). The base **1024** is a tubular member having an inner surface with a generally constant diameter that is larger than the diameter of the outer surface of the boss **1016b** and having an outer surface with a generally constant diameter that is smaller than a dimension (e.g., diameter) of the inner region **414a** of the recess **414**. The base **1024** additionally includes slots **1024a** that are opposed to each other and extend radially outward into the inner surface of the base **1024** (e.g., being an aperture extending entirely through the wall thereof).

(136) The spring clip **1027** is configured to releasably couple the base **1024** to the boss **1016b** of the camera **1000**. In particular, the spring clip **1027** is configured to be received by both the slots **1016c** of the boss **1016b** and the slots **1024a** of the base **1024**. The spring clip **1027** is a generally ring-shaped member having an end portion (e.g., a lower end) with flanges **1027a** that are positioned within the slots **1024a** of the base **1024** and which are receivable by the slots **1016c** of the boss **1016b**. A central portion of the spring clip **1027** extends axially between (e.g., along) the inner surface of the base **1024** and the outer surface of the boss **1016b**, and another end portion (e.g., an upper end) of the spring clip **1027** extends radially outward between an axial end of the base **1024** and the base **1016a** of the stud **1016**.

(137) In FIGS. **10A** and **10C**, the device mount **1020** is coupled to and retained on the stud **1016** of the camera **400**, which may be referred to as a connected state. In particular, the flanges **1027a** of the spring clip **1027** are positioned in both the slots **1016c** of the stud **1016** (protruding radially inward therein) and the slots **1024a** of the base **1024** (protruding radially outward therein), so as to prevent relative axial movement between the stud **1016** (i.e., the camera **1000**) and the base **1024** (i.e., the device mount **1020**).

(138) In FIG. **10D**, the device mount **1020** is axially removable from the stud **1016**, which may be referred to as a disconnected or disconnectable state. More particularly, the device mount **1020** is rotated by 90 degrees relative to the stud **1016** in the connected state, such that the flanges **1027a** of the spring clip **1027** are not aligned with the slots **1016c** of the boss **1016b** but are instead aligned with those regions therebetween in which the outer surface of the boss **1016a** has the maximum diameter. In the disconnected state, the finger members **1022** are in the extended state (discussed above with the respect to the finger members **422**) and rotated 90 degrees relative to the outer region **414b** of the recess **414**. As the base **1024** of the device mount **1020** is received on the stud **1016** of the camera **400**, the boss **1016b** presses the flanges **1027a** of the spring clip **1027** outward further into the slots **1024c** of the base. The device mount **1020** is subsequently rotated by 90 degrees into the connected state (e.g., by a user grasping the finger members **1022**), such that the flanges **1027a** of the spring clip **1027** bias inward (e.g., spring inward) for receipt into the slots **1016c** on the boss **1016b**. The finger members **1022** may then be pivoted into the outer region **414b** of the recess **414** into the collapsed state.

(139) To remove the device mount **1020**, the finger members **1022** are pivoted out of the recess **414**, and the device mount **1020** is rotated by 90 degrees, such that the flanges **1027a** of the spring clip **1027** are rotated out of the slots **1016c** of the boss **1016b** and biased outward as the diameter of the outer surface of the boss **1016b** engaged thereby increases. The device mount **1020** may then be removed axially from the boss **1016b** of the stud **1016**, since the flanges **1027a** of the spring clip **1027** are no longer retained in the slots **1016c** of the boss **1016b**.

(140) Referring to FIG. **5** and FIGS. **11-17** the camera **400** and the device mount **420**, or variations thereof, may be configured to hold (e.g., retain or maintain) the two finger members **422** in the extended state and/or in the collapsed state. For example, as shown in FIG. **4C**, the finger members **422** may form an interference fit with the recess **414**. For example, outer surfaces of the finger members **422** (e.g., those extending between the planar surface **422a** thereof) may engage inner surfaces of the bottom side **410a** of the body **410**, which define the recess **414**, such that friction therebetween retains the finger members **422** in the recess (i.e., in the collapsed position).

(141) As shown in FIGS. **11-17**, the device mount **420** may include one or more retention mechanisms by which the finger member **422** is held in the extended position or the collapsed position relative to the base **424**. In an example shown in FIG. **11**, a spring **1130** (e.g., a torsion spring) biases one of the finger members **422** about the axis of rotation into the extended state. For example, the spring **1130** may bias the finger members **422** against the central segment **424a''** of the central portion **424a** of the base **424** into the extended state (shown in solid lines) from the collapsed state (shown in dashed lines). The spring **1130** may alternatively normally bias the finger member **422** to the collapsed state. The retention mechanism may also be referred to as retainers and components thereof may be referred to as retaining components.

(142) As shown in FIG. **12**, a retention mechanism is configured as a latch **1232** that retains the finger member **422** in the collapsed state. For example, the latch **1232** includes a sprung protrusion **1232a** on an edge of the finger member **422**, which engages and is received by a detent **1232b** in the body **410** (e.g., in the recess **414** of the body **410** as shown). The sprung protrusion **1232a** may itself be elastic (e.g., being formed of an elastomer) or may include a biasing spring that presses the sprung protrusion **1232a** into the detent **1232b**. As the user forces the finger member **422** to move between the collapsed and extended states, the structure surrounding and defining the detent **1232b** applies a lateral force (e.g., generally parallel with the axis of rotation) against the sprung protrusion **1232a**, thereby biasing the sprung protrusion **1232a** out of the detent **1232b** for release thereof and of the finger member **422**. The sprung protrusion **1232a** and the detent **1232b** may be arranged in an opposite configuration with the sprung member **1232a** as part of the body **410** of the electronic device and the detent **1232b** on the finger member **422**. In a further alternative, the latch **1232** may include a latch release interface, such as a button, that may be pressed by the user to release the finger member **422** for movement.

(143) In another example shown in FIG. **13**, the proximal portion **422b** of the finger member **422** may engage detents in the base **424** the extended and/or collapsed states (both as shown). The finger member **422** includes a sprung protrusion **1334** that moves longitudinally (e.g., generally parallel with the finger member **422**). The base **424** includes two detents **1336a**, **1336b** in the central portion **424a** and the outer portion **424b**, respectively, which receive and hold the sprung protrusion **1334a** and, thereby, the finger member **422** in the collapsed and the extended positions, respectively.

(144) In another example shown in FIG. **14**, the finger member **422** is retained in the collapsed position magnetically. For example, the finger member **422** includes a magnetic component **1438** (e.g., a permanent magnet or an attractor plate), while the base **424** includes another magnetic component **1440** attracted thereby (e.g., an attractor plate or a permanent magnet). The base **424** may itself form the other magnetic component **1440** (e.g., being formed of steel or other ferromagnetic material). The magnetic component **1438** may instead be incorporated into the body **410** (e.g., in the external housing **419** and/or the chassis **418** therein). The magnetic components **1438** or **1440** may, for example, be a permanent magnet formed of a suitable material, such as those described for the magnetic feature **1822h** described below. The magnetic components **1438**, **1440** magnetically couple to each other with a desired force (e.g., an opening force) to retain the finger member **422** in the collapsed position, while still allowing the finger member **422** to be moved easily by the user to the extended position. For example, the for example, magnetic components **1438**, **1440** may magnetically couple to each other to require an opening force the finger member **422** of above 0.5 N (e.g., above 1.0 N or above 1.5 N) and below 5 N (e.g., below 4 N, or below 3 N), such as between approximately 1.5 and 2.5N (e.g., approximately 2 N), which may be measured at the distal portion **422c** of the finger member **422** (e.g., at the finger pick) or the location of the magnetic component **438**.

(145) In another example shown in FIG. **15**, the finger member **422** is retained in the collapsed and extend positions with an over-center device **1542**. The over-center device **1542** includes sprung surface that engages the proximal portion **422b** of the finger member **422** (e.g., a protrusion **1540** thereof). The sprung surface is biased generally toward the pivot axis to apply spring force to the proximal portion **422b** of the finger member **422**, which generates torque about the pivot axis that biases the distal portion **422c** into either the collapsed or extended position. As the finger member **422** is pivoted between the collapsed and extended positions and crosses a mid-point in the angular range of travel, the torque generated by the spring force changes direction so as to bias the finger member **422** toward the other of the collapsed or extended position.

(146) As illustrated schematically, the over-center device **1542** includes a spring surface **1542a** that is normally biased by a spring **1542b** toward the

pivot axis. The spring surface **1542a** may be a plate member, while the spring **1542b** may be a coil spring that applies force between the base **424** and the plate member. Alternatively, the spring surface **1542a** and the spring **1542b** may be cooperatively formed by a single spring element (e.g., a flat torsion spring).

(147) In another example shown in FIG. **16**, movement of one of the finger members **422** causes movement of the other finger member **422**. As illustrated, a right finger member **422R** and a left finger member **422L** include proximal portions **1622b** that overlap each other. As the user moves one of the finger members **422**, the proximal portions **422b** engage each other such that the other of the finger members **422** moves.

(148) In another example shown in FIG. **17**, the finger member **422** is retained in the collapsed, extended, and/or intermediate positions frictionally. For example, the finger member **422** includes the hinge pin **428**. The finger member **422** and the hinge pin **428** are rotationally fixed, for example, with the hinge pin **428** being tightly received by the proximal portion **422b** of the finger member **422** (e.g., being press-fit into apertures thereof). The hinge pin **428** is in turn frictionally engaged with the base **424** to prevent rotation therebetween. For example, the friction between the hinge pin **428** and the base **424** may be sufficient to prevent rotation of the finger member **422** relative to the base **424** due to the force of gravity.

(149) The friction between the hinge pin **428** and the base **424** may be provided by a friction pad **1730** (e.g., a friction component). For example, the hinge pin **428** may be received by and rotate within apertures of the base **424** (not shown), while the friction pad **1730** presses against the hinge pin **428** in a radial direction to generate friction therebetween. The friction pad **1730** may also press the hinge pin **428** against the base **424** (e.g., those portions defining the apertures in which the hinge pin **428** is received), such that additional friction is generated between the hinge pin **428** and the base **424**. The friction pad **1730** may, for example, be an elastic material (e.g., an elastomer, such as rubber, or other polymer). Instead or additionally, the proximal portion **422b** (e.g., an end thereof) may be frictionally engaged, such as with friction pad similar to the friction pad **1730** or portion of the body **410** of the camera **400** engaging the end thereof, for example, with the end have a rounded surface concentric with the axis of rotation (e.g., of the hinge pin **428**).

(150) It should be noted that the retention mechanisms disclosed in FIGS. **11-17** may be used in any suitable combinations with each other. For example, the spring **1130** of FIG. **11** may be used in combination with the latch **1232** of FIG. **12** or the magnetic components **1438**, **1440** of FIG. **14**. In another example, the finger member **422** may be retained both frictionally (e.g., as describe with respect to FIG. **17**) and magnetically (e.g., described with respect to FIG. **14**).

(151) Referring to FIGS. **18A-18E**, a variation of the device mount **1820** is includes two finger members **1822**, a base **1824**, and hinge pins **1826**.

(152) The finger members **1822** may have a substantially planar configuration with opposed planar surfaces **1822a** that extend parallel with each other from a proximal end **1822b** to a distal end **1822c** thereof (e.g., similar to the finger member **1022**). As with the finger member **422**, the finger member **1822** includes an aperture **1822d** that extends therethrough (e.g., in a normal direction to the planar surfaces **1822a**). The aperture **1822d** is for receiving the shaft **448** for coupling the device mount **1820** to the support mount **442**. The finger members **1822**, when extended, are inserted into the slots **446** of the support mount **442**, while the shaft **448** is inserted through the apertures **1822d** of the finger member **1822** and the apertures (not shown) of the support mount **442**.

(153) The distal end **1822c** of the finger member **1822** may be rounded, for example, having a semicircular cross-sectional shape about the aperture **1822d** to permit rotation of the finger member **1822** when coupled to the support mount **442**. The distal end **1822c** of the finger member **1822** may include an indentation **1822g**, which forms a finger pick to facilitate the user removing the finger member **1822** from a recess of the external housing **419** of the camera **400** in which the device mount **1820** is positioned and for rotating the finger member **1822** (see FIG. **18E**).

(154) The proximal end **1822b** of the finger member **1822** includes end segments **1822b'** that are spaced apart to form a recess **1822e** (e.g., a gap or slot) in which is received a hinge portion of the base **1824** as described below. The proximal end **1822b** further includes apertures **1822f** extending through the end segments **1822b'** in each of which is received one of the hinge pins **1826**. The apertures **1822f** and the hinge pin **1826** are configured to be rotationally fixed to each other (e.g., to rotate with each other), for example, with the hinge pin **1826** being press-fit into the apertures **1822f**. The proximal end **1822b** of the finger member **1822** may be rounded (e.g., being semi-circular in cross-section along the axis of the hinge pin **1826**) to permit rotation, while being in close proximity to other structures (e.g., the base **1824**).

(155) The base **1824** generally includes a coupling portion **1824a** (e.g., plate portion) and a hinge portion **1824b**. The coupling portion **1824a** is configured to couple to the camera **400**. As shown, the coupling portion **1824a** is a generally planar structure having apertures **1824c** through which fasteners (not shown; see, e.g., fasteners **417**) extend to couple the base **1824** to the camera **400** (e.g., similar to the base **424** of the device mount **420**). The base **1824** may have a length that is relatively short as compared to the base **424**, for example, being positioned between the apertures **1822d** (e.g., not overlapping the apertures **1822d**) of the finger members **1822** when in the collapsed position. As shown in FIG. **18E**, the base **1824** may be received in the recess **414** of the external housing **419** of the camera **400**. As a result, the finger members **1822** may be flush against or otherwise contact the external housing **419** when in the collapsed position. Furthermore, as also shown in FIG. **18E**, the finger members **1822** and the base **1824** may be slightly recessed relative to the external housing **419**, such that when the finger members **1822** are collapsed, the camera **400** may rest stably on a surface without the interference from the finger members **1822** engaging the surface.

(156) The hinge portion **1824b** protrudes from the coupling portion **1824a** for the finger members **1822** to hingedly couple thereto. The hinge portion **1824b** generally includes a central segment **1824b'** and two outwardly extending segments **1824b''**. Each of the two outwardly extending segments **1824b''** is received by the recess **1822e** of one of the finger members **1822** and includes an aperture **1824c** for receiving the hinge pin **1826** therein. The aperture **1824c** and the hinge pin **1826** are cooperatively configured to permit the finger member **1822** to rotate about an axis formed thereby (e.g., about the hinge portion **1824b** of the base **1824**).

(157) The central segment **1824b'** is positioned between the two outwardly extending segments **1824b''** and the finger members **1822**. As the finger members **1822** are rotated from the collapsed positions to the extended positions, the central segment **1824b'** may engage the finger members **1822** (e.g., the planar surfaces **1822a** thereof) to maintain proper spacing between the finger members **1822** for receipt thereof into the slots **446** of the support mount **442** and to receive the central finger member **444c** of the support mount **442** therebetween.

(158) To facilitate coupling of the finger members **1822** to the base **1824**, the base **1824** may include a base member **1824e** and a base cap **1824f**. The base member **1824e** is a structure that forms the coupling portion **1824a** and first part of the hinge portion **1824b**, while the base cap **1824f** forms a remaining part of the hinge portion **1824b**. More particularly, the base member **1824e** and the base cap **1824f** cooperatively define the apertures **1824c**, for example, each forming a semi-circular half thereof. Thus, to assemble the device mount **1820**, the hinge pins **1826** are coupled to the finger members **1822** (e.g., being press fit therein), the hinge pins **1826** are placed in the semi-circular half of the aperture formed by the base member **1824e** of the base **1824**, and the base cap **1824f** is then coupled to the base member **1824e**, capturing the hinge pins **1826** therebetween. The base cap **1824f** may be coupled to the base member **1824e**, for example, with fasteners. In one embodiment, the base member **1824e** is formed of a metal material (e.g., steel or other ferromagnetic material or aluminum), while the base cap **1824f** is formed of metal, plastic, or other polymer material. The base cap **1824f** being formed of plastic or other polymer may be advantageous by being a heat insulator, so as to hinder conduction of heat generated by the camera **400** to an exposed surface of the camera **400**.

(159) Alternatively, the base **1824** may be a unitary structure with the hinge pins **1826** being received axially by the apertures **1824c**. For example, as shown in FIGS. **18F-18G**, a base **1824'** and a base member **1824e'** thereof, which are variations of the base **1824** and the base member **1824e**, may itself define the apertures **1824c** in which are positioned the hinge pins **1826** (i.e., without the base cap **1824f**). For example, the hinge pins **1826** may be inserted axially through the apertures **1822f** of each of the finger members **1822** of the aperture **1824c** of the base member **1824e'** of the base **1824**, so as to couple the finger members **1822** to the base member **1824e'**. An outer surface of the base member **1824e'** may be exposed, such that heat is conducted from the chassis (e.g., the chassis **418** or **918**) of the body **410** of the camera **400** to the surface of the base member **1824e'** (e.g., by the metal structure formed thereby). Alternatively, an insulative cap (not shown) or other heat insulative layer or material, which may not function to

retain the hinge pins **1826** to the base **1824e'**, may be coupled to the base member **1824c'** to insulate heat conducted through the base member **1824e'**.

(160) As shown and described above with respect to the device mount **420**, when the device mount **1820** is coupled to the camera **400**, the axes of rotation of the finger members **1822** may be in a static orientation (e.g., fixed orientation) relative to the body **410** of the camera **400** (e.g., relative to the sides thereof and/or the lens **412**, such as extending forward and backward) and/or passing through the recess **414** of the body **410** of the camera **400**. For example, as shown, the hinge pins **1826** may be held in a static position and/or be positioned entirely within the recess **414** of the body **410** of the camera **400**, for example, being held in the static position by the base **1824** that is statically coupled to the body **410** of the camera **400**. It should be noted that while the hinge pins **1826** are in static positions, the hinge pins **1826** themselves may rotate (e.g., with the finger members **1822**), while axes of the hinge pins **1826** (e.g., the axes of rotation of the finger members **1822**) remain in static orientation relative to the body **410**.

(161) The device mount **1820** may additionally be configured to hold the finger members **1822** in the extended and/or collapsed states magnetically and/or fictionally. For example, the finger members **1822** may be held frictionally in the extended state, and may be held magnetically in the collapsed state.

(162) The device mount **1820** frictionally maintains the finger members **1822** in the extended state generally described above with respect to FIG. 17. In particular, the device mount **1820** includes a friction pad **1828**, which may be considered part of the base **1824**. The friction pad **1828** presses against one or both of the hinge pins **1826** to generate friction therebetween for holding one or both of the finger members **1822** in the extended position. The friction pad **1828** may further press the hinge pins **1826** against the base **1824** (e.g., the hinge portion **1824b**, which may be formed by the base cap **1824f**) to generate friction therebetween for holding one or both of the finger members **1822** in the extended position. The friction between the base **1824** (e.g., the friction pad **1828** and/or the hinge portion **1824b**) and each hinge pin **1826** is sufficient to at least overcome the force of gravity acting on the finger members **1822** to maintain the finger member **1822** in the extended position.

(163) As illustrated in FIGS. 18D and 18E, the hinge pins **1826** are pressed between the friction pad **1828** and the hinge portion **1824b** of the base **1824** (e.g., against the surface defining the aperture **1824c**, such as the base cap **1824f**). As shown, the base **1824** defines a cavity **1824g** (e.g., a recess) through which the hinge pins **1826** extend and in which the friction pad **1828** is positioned against the hinge pins **1826**. The cavity **1824g** has a depth, which is less than the cumulative height of the friction pad **1828** and the hinge pins **1826**, such that the friction pad **1828** is compressed by the hinge pins **1826**. As shown in FIG. 18D, the cavity **1824g** has an upper opening from which the friction pad **1828** protrudes, so as to engage a surface of the external housing **419** of the camera **400** (see FIG. 18E). Alternatively, the cavity **1824g** may be closed at an upper end (e.g., the coupling portion **1824a** being continuous), while the friction pad **1828** is received by a lower opening that is enclosed by the base cap **1824f**.

(164) The device mount **1820** magnetically maintains the finger members **1822** in the collapsed state as generally described above with respect to FIG. 14. In particular, the finger member **1822** includes a magnetic feature **1822h**, which forms a magnetic coupling with the base **1824**. As shown, the magnetic feature **1822h** is arranged between the hinge pin **1826** and the aperture **1822d** of the finger member **1822**. The magnetic feature **1822h** may, for example, be a permanent magnet that is embedded into the material forming the finger member **1822**, for example, to be flush with or recessed relative to the planar surface **1822a** nearest the base **1824**. For example, as described above with respect to the finger member **422**, the material forming the finger member **1822** may be aluminum, which may be further coated with other materials (e.g., vapor deposited material, phobic coating, etc.). The permanent magnet may be any suitable type of permanent magnet, such as a rare earth magnet. In one particular example, the permanent magnet that forms the magnetic feature **1822h** of the finger members **1822** may be a samarium cobalt magnet, which may have superior resistance to corrosion as compared to magnets formed of other materials (e.g., neodymium magnets) and may be advantageous for use of the device mount **1820** in high moisture environments, as is contemplated. Further any coating of the finger member **1822** (e.g., those described above for the finger member **422**) may further protect the magnetic feature **1822h** from corrosion by serving as a moisture (e.g., water) barrier that prevents or limits contact with the magnetic feature **1822h** itself.

(165) The base **1824** has a length sufficient to overlap the magnetic feature **1822h** and, as referenced above, may be made of steel, another ferromagnetic material, or may include a permanent magnet of suitable orientation to form a magnetic coupling with the magnetic feature **1822h**. Alternatively, the magnetic feature **1822h** of the finger member **1822** may be an attractor plate or otherwise include a ferromagnetic material, while the base **1824** includes a permanent magnet that forms the magnetic coupling with the magnetic feature **1822h**. As described above with respect to the finger member **422** and the magnetic components **1438**, **1440**, the magnetic feature **1822h** is configured to provide sufficient force (e.g., the opening force) to retain the finger member **1822** in the collapsed position, while still allowing the finger member **1822** to be easily (e.g., comfortably) moved by the user to the extended positions, such as by having an opening force of above 0.5 N (e.g., above 1.0 N or above 1.5 N) and below 5 N (e.g., below 4 N, or below 3 N), such as between approximately 1.5 and 2.5 N (e.g., approximately 2 N), which may be measured at the distal portion of the finger member **1822** (e.g., at the finger pick) or the location of the magnetic feature **1822h**.

(166) As a further alternative, the magnetic feature **1822h** of the finger member **1822** may instead magnetically couple to the camera **400**, which includes a complementary magnetic feature for forming a magnetic coupling therewith.

(167) Referring to FIG. 19, in addition to each of the device mount **420** and the variations thereof (e.g., **1020**, **1820**, and variations thereof) being coupleable to a camera **400**, the device mount **420** may instead or additionally be coupleable to or integrated with a detachable housing **1990** that is adapted to releasably contain a camera therein. Thus, the detachable housing **1990** (or **2090** below) may be considered to form the device mount **420**, **1020**, **1820**, or variations thereof. The detachable housing **1990** (e.g., an open frame or waterproof housing) is configured to couple to the device mount **420** or variations thereof (e.g., the device mount **1820** as shown), or may otherwise include the finger members **422** (or others) that are rotatably coupled thereto. The detachable housing **1990** is configured to couple to or otherwise contain a camera **400** therein, or other image capture device or system **100**, **200**, **300** therein. As referenced above, the detachable housing **1990** may be a waterproof housing, which includes an outer housing structure that defines a receptacle **1992** for containing the camera **400** therein. For example, the outer housing structure may tightly engage the camera **400** therein, so as to couple the detachable housing **1990** to the camera **400**. Alternatively, the detachable housing **1990** may be a frame having one or more open sides to the receptacle **1992**. For example, the frame may have an open front face and/or an open rear face that allow a substantial majority of a front side and/or a rear side, respectively of the camera mounted therein to be exposed. Such a frame may be coupled to the camera, for example, by being clamped around left, top, right, and bottom sides of the camera and/or engaging edges of the front and/or rear sides of the camera. The combination of the camera (e.g., **400**), the detachable housing (e.g., **1990**), and the device mount may be referred to cooperatively as a camera system.

(168) The outer housing structure **1991** may further include a recess **1994** in which the device mount **1820** (as shown) is positioned and that may be configured substantially similar to the recess **414**. For example, the finger members **422** may be substantially contained in the recess in the collapsed state (e.g., being flush or recessed relative to the surrounding surfaces of the outer housing structure **1991**) and extend therefrom in the extended state.

(169) Referring to FIGS. 20A-20B, a housing **2090** is provided for the camera **400** having the device mount **420** and which allows for simultaneous use of the device mount **420**, **1020**, **1820** and the housing **2090** with the camera **400**. More particularly, the housing **2090** includes an outer housing structure that defines a receptacle (shown; not labeled) for receiving the camera **400** therein and may tightly engage outer surfaces of the camera **400** or otherwise couple to the camera **400**. The housing **2090** includes one or more apertures **2092** on a bottom surface **2093** thereof, which allow the finger members **422** (or variations thereof, such as the finger members **1022** or **1822**) to protrude through the bottom surface **2093** of the housing **2090** for coupling to the external support **440** (or variation thereof). In one example, the aperture **2092** permits the finger members **422** to be moved (e.g., to be rotated) between the extended and retracted states thereof. For example, as shown in FIG. 20B, the aperture **2092** has a length and a width that are greater than the length and width of the device mount **420** in the extended state (e.g., the cooperative width of the finger members **422**). Alternatively, as shown in FIG. 21, a housing **2190** is otherwise configured similar to the housing **2090**, but instead of the aperture **2092**, instead

includes an aperture 2192 that permits the finger members 422 (or variations thereof, such as the finger members 1022 or 1822) to protrude therethrough, while inhibiting movement of the finger members 422 (e.g., rotation thereof) between the extended and retracted states thereof. For example. The aperture has a width that is greater than the distance between the planar surfaces 422a of the finger members 422 in the extended state but less than the width of the device mount 420 in the extended state (e.g., the cooperative width of the finger members 422).

(170) While the disclosure has been described in connection with certain embodiments, it is to be understood that the disclosure is not to be limited to the disclosed embodiments but, on the contrary, is intended to cover various modifications and equivalent arrangements included within the scope of the appended claims, which scope is to be accorded the broadest interpretation so as to encompass all such modifications and equivalent structures as is permitted under the law.

(171) In addition to the foregoing, the following embodiments are contemplated by the present application:

(172) 1. A camera mount comprising: two finger members coupleable to a camera, each of the two finger members having opposed planar surfaces that are parallel with and define a thickness of thereof and an aperture extending through the thickness; characterized in that: the two finger members are rotatable relative to the camera about different respective axes of rotation between respective extended positions and respective collapsed positions; wherein when the finger members are in the respective extended positions, the camera mount is in an extended state with the finger members extending parallel with each other in a common direction and the apertures being coaxial with each other; and wherein when the finger members are in the respective collapsed positions, the camera mount is in a collapsed state.

(173) 2. The camera mount according to Embodiment 1, wherein when the camera mount is in the extended state, the finger members are spaced apart to define a slot of the camera mount therebetween.

(174) 3. The camera mount according to Embodiment 2, wherein the slot has a width that is approximately equal to the thickness of each of the two finger members.

(175) 4. The camera mount according to any of embodiments 1-3, wherein when the camera mount is in the extended state, the two finger members are insertable into parallel slots of a support mount.

(176) 5. The camera mount according to Embodiment 4, wherein a central finger member of the support mount is receivable in the slot of the camera mount.

(177) 6. The camera mount according to any of embodiments 1-5, wherein when the camera mount is in the collapsed state, the finger members extend away from each other.

(178) 7. The camera mount according to Embodiment 6, wherein when the camera mount is in the collapsed state, the finger members extend away from each other in parallel.

(179) 8. The camera mount according to any of embodiments 6-7, wherein when the camera mount is in the collapsed state, the two finger members are not simultaneously receivable in parallel slots of a support mount.

(180) 9. The camera mount according to any of embodiments 1-8, wherein as the two finger members are rotated from the respective extended positions to the respective collapsed positions, distal portions of the two finger members are moved away from each other.

(181) 10. The camera mount according to Embodiment 9, wherein as the two finger members are rotated from the respective extended positions to the respective collapsed positions, the distal portions of the two finger members are moved toward a body of the camera to which the camera mount is coupled.

(182) 11. The camera mount according to any of embodiments 1-10, wherein each of the two finger members includes a proximal portion and a distal portion, the axis of rotation thereof extends through the proximal portion, and the aperture extends through the distal portion.

(183) 12. The camera mount according to Embodiment 11, wherein the proximal portion is rounded about the axis of rotation thereof.

(184) 13. The camera mount according to any of embodiments 11-12, wherein the distal portion is rounded about the aperture.

(185) 14. The camera mount according to any of embodiments 1-13, wherein the two finger members are retainable at least one of the respective extended positions or the respective collapsed positions.

(186) 15. The camera mount according to Embodiment 14, wherein the two finger members are retainable one or more of magnetically or fictionally.

(187) 16. The camera mount according to any of embodiments 14-15, wherein the two finger members are retainable frictionally in the respective extended positions.

(188) 17. The camera mount according to any of embodiments 14-16, wherein the two finger members are retainable magnetically in the respective collapsed positions.

(189) 18. The camera mount according to Embodiment 17, wherein each of the two finger members includes a magnetic component.

(190) 19. The camera mount according to any of embodiments 1-18, further comprising a base; wherein the two finger members are coupled to the base and rotate relative to the base between the respective extended positions and the respective collapsed positions.

(191) 20. The camera mount according to Embodiment 19, wherein the base is coupleable to the camera, such that the two finger members are in turn coupleable and rotatable relative to the camera.

(192) 21. The camera mount according to Embodiment 20, wherein the camera mount is in the collapsed state, the camera mount is not removable from the camera.

(193) 22. The camera mount according to any of embodiments 1-18, further comprising a housing structure that defines a receptacle for containing the camera and is coupleable to the camera, wherein the two finger members are rotatably coupled to the housing structure, such that the two finger members are in turn coupleable and rotatable relative to the camera.

(194) 23. The camera mount according to Embodiment 22, wherein the housing structure includes a recess, the two finger members are substantially contained in the recess when the camera mount is in the collapsed state, and the two finger members extend from the recess when the camera mount is in the extended state.

(195) 24. The camera mount according to any of embodiments 22-23, wherein the receptacle is waterproof.

(196) 25. The camera mount according to any of embodiments 22-23, wherein the housing structure is a frame having one or more open sides allowing a substantial majority of a side of the camera in the receptacle to be exposed.

(197) 26. A camera comprising: a body; a lens coupled to the body; and the camera mount according to any of embodiments 1-21 coupled to the body.

(198) 27. The camera according to Embodiment 26, wherein the body defines a recess that receives the finger members when the finger members are in the respective collapsed positions.

(199) 28. The camera according to Embodiment 27, wherein the camera mount includes a base, the two finger members are coupled to the base and rotate relative to the base between the respective extended positions and the respective collapsed positions, and the base is coupled to the camera, such that the two finger members are in turn coupled and rotatable relative to the camera.

(200) 29. The camera according to Embodiment 28, wherein the camera includes a bottom side that defines the recess, and when the finger members are in the respective collapsed positions, the finger members are recessed relative to surrounding surfaces of the bottom side.

(201) 30. The camera according to Embodiment 29, wherein the base is receivable in the recess in a direction generally opposed to the bottom side.

(202) 31. The camera according to Embodiment 26, further comprising internal components that include an image sensor, wherein the body includes a chassis that is formed of a metal material and is a generally rigid structure to which the internal components of the camera are coupled, and the camera mount is coupled to the chassis.

(203) 32. The camera according to Embodiment 31, wherein the chassis includes a bottom segment at a bottom side of the camera and an upright

segment extending upward from the bottom segment.
(204) 33. The camera according to Embodiment 32, wherein the camera mount is coupled to the bottom segment with threaded screws.
(205) 34. The camera according to Embodiment 32, further comprising an external housing that defines a compartment that is waterproof and that contains the chassis.
(206) 35. The camera according to Embodiment 34, wherein the external housing is formed of a polymer material.
(207) 36. The camera according to Embodiment 32, further comprising an external housing component, wherein the chassis and the external housing component cooperatively define a cavity that is waterproof and in which the image sensor is positioned.
(208) 37. The camera according to Embodiment 36, wherein the bottom segment is positioned outside the cavity.

Claims

1. A camera mount for a camera, the camera mount comprising: a base directly connectable to the camera, wherein the base includes: a coupling portion configured to couple to the camera, wherein the coupling portion includes: a plate; and a raised base member extending from the plate and defining an exterior surface; and a hinge portion extending laterally outward from the raised base member and defining outwardly extending segments with apertures; and first and second finger members rotatably coupled to the hinge portion about pivot axes extending in parallel relation to the exterior surface, the first and second finger members configured to interface with an accessory such that the accessory is connectable to the camera via the camera mount.
 2. The camera mount of claim 1, wherein the camera mount is reconfigurable between a collapsed configuration, in which exterior surfaces of the first and second fingers members extend in parallel relation to the exterior surface of the raised base member, and an expanded configuration, in which the exterior surfaces of the first and second fingers members extend in non-parallel relation to the exterior surface of the raised base member.
 3. The camera mount of claim 2, wherein the first and second finger members include: proximal ends defining recesses configured to receive the hinge portion such that the hinge portion extends into the first and second finger members; and distal ends defining indentations configured for manual engagement by a user to facilitate reconfiguration of the camera mount from the collapsed configuration into the expanded configuration.
 4. The camera mount of claim 1, wherein the coupling portion and the hinge portion are configured such that the base includes a cruciform configuration.
 5. The camera mount of claim 4, wherein the raised base member extends vertically from the plate.
 6. The camera mount of claim 5, wherein the outwardly extending segments extend from the raised base member in orthogonal relation to the pivot axes.
 7. The camera mount of claim 5, wherein the apertures are configured to receive hinge pins such that the hinge pins extend from the pair of outwardly extending segments and into the first and second fingers members to thereby pivotably connect the first and second finger members to the hinge portion.
 8. The camera mount of claim 7, wherein the hinge pins are press fit into the first and second finger members.
 9. The camera mount of claim 1, wherein the camera mount is configured to removably receive a threaded shaft on the accessory.
 10. The camera mount of claim 1, wherein the plate includes a polygonal cross-sectional configuration defining four corner sections, the plate including an opening in each corner section configured to receive a mechanical fastener to thereby connect the camera mount to the camera.
 11. A camera mount for a camera, the camera mount comprising: a base directly connectable to the camera, wherein the base includes: a coupling portion including: a plate with a rectangular cross-sectional configuration defining four corner sections, wherein each corner section includes an opening configured to receive a mechanical fastener to thereby connect the camera mount to the camera; and a raised base member extending from the plate; and a hinge portion extending laterally outward from the raised base member and defining a pair of outwardly extending segments with apertures, whereby the base includes a cruciform configuration; and first and second finger members pivotably connected to the hinge portion such that the camera mount is reconfigurable between a collapsed configuration and an expanded configuration, wherein the first and second finger members include: proximal ends defining recesses configured to receive the outwardly extending segments such that the hinge portion extends into the first and second finger members; and distal ends defining indentations configured for manual engagement by a user to facilitate reconfiguration of the camera mount from the collapsed configuration into the expanded configuration.
 12. The camera mount of claim 11, wherein the first and second finger members include linear sidewalls connected by an arcuate end wall.
 13. The camera mount of claim 11, further comprising hinge pins extending into the apertures and the first and second finger members so as to define pivot axes for the first and second finger members.
 14. The camera mount of claim 13, wherein the camera mount is configured to interface with an accessory such that the accessory is connectable to the camera via the camera mount.
 15. The camera mount of claim 14, wherein the camera mount is configured to removably receive a threaded shaft on the accessory such that the threaded shaft is oriented in transverse relation to the pivot axes.
 16. A camera mount for a camera, the camera mount comprising: a base directly connectable to the camera, wherein the base includes: a coupling portion including: a plate with a polygonal cross-sectional configuration defining four corner sections, wherein each corner section includes an opening configured to receive a mechanical fastener to thereby connect the camera mount to the camera; and a raised base member extending from the plate; and a hinge portion extending laterally outward from the raised base member and defining outwardly extending segments with apertures; and first and second finger members pivotably connected to the hinge portion by hinge pins extending into the apertures such that the camera mount is reconfigurable between a collapsed configuration and an expanded configuration, wherein the hinge portion extends into the first and second finger members such that the hinge pins extend from the hinge portion and into the first and second finger members.
 17. The camera mount of claim 16, wherein the hinge pins are press fit into the first and second finger members.
 18. The camera mount of claim 16, wherein the camera mount is configured to interface with an accessory such that the accessory is connectable to the camera via the camera mount.
 19. The camera mount of claim 18, wherein the camera mount provides a threaded interface configured to facilitate removable connection of the accessory to the camera mount.
 20. The camera mount of claim 18, wherein the camera mount is configured to removably receive a threaded shaft on the accessory such that the threaded shaft is oriented in transverse relation to the hinge pins.
-