

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent

12400143

Kind Code

B2

Date of Patent

August 26, 2025

Inventor(s)

Dang; Qingqing et al.

Model development tool to train, evaluate and predict with deep learning by selecting functions

Abstract

Embodiments of the present disclosure provide a method and apparatus of training a model, an electronic device, a storage medium and a development system, which relate to a field of deep learning. The method may include calling a training preparation component to set at least a loss function and an optimization function for training the model, in response to determining that a training preparation instruction is received. The method further includes calling a training component to set a first data reading component, in response to determining that a training instruction is received. The first data reading component is configured to load a training data set for training the model. In addition, the method may further include training the model based on the training data set from the first data reading component, by using the loss function and the optimization function through the training component.

Inventors: Dang; Qingqing (Beijing, CN), Deng; Kaipeng (Beijing, CN), Jiang; Lielin (Beijing, CN), Guo; Sheng (Beijing, CN), Hu; Xiaoguang (Beijing, CN), Zhang; Chunyu (Beijing, CN), Ma; Yanjun (Beijing, CN), Wu; Tian (Beijing, CN), Wang; Haifeng (Beijing, CN)

Applicant: Beijing Baidu Netcom Science Technology Co., Ltd. (Beijing, CN)

Family ID: 1000008777940

Assignee: BEIJING BAIDU NETCOM SCIENCE TECHNOLOGY CO., LTD. (Beijing, CN)

Appl. No.: 17/480292

Filed: September 21, 2021

Prior Publication Data

Document Identifier

US 20220004930 A1

Publication Date

Jan. 06, 2022

Foreign Application Priority Data

CN

202011247471.4

Nov. 10, 2020

Publication Classification

Int. Cl.: G06N20/00 (20190101); G06F18/21 (20230101); G06F18/23 (20230101)

U.S. Cl.:

CPC G06N20/00 (20190101); G06F18/217 (20230101); G06F18/23 (20230101);

Field of Classification Search

CPC: G06N (20/00); G06N (3/08); G06N (3/04); G06F (18/217); G06F (18/23)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
9367428	12/2015	Rhee et al.	N/A	N/A
2015/0106794	12/2014	Rhee et al.	N/A	N/A
2017/0061329	12/2016	Kobayashi et al.	N/A	N/A
2019/0095790	12/2018	Ling et al.	N/A	N/A
2019/0228495	12/2018	Tremblay	N/A	B25J 9/1661
2020/0085382	12/2019	Taerum et al.	N/A	N/A
2020/0367074	12/2019	Zhang	N/A	G06F 9/542
2022/0164703	12/2021	Tezuka et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
107392307	12/2016	CN	N/A
108021395	12/2017	CN	N/A
110121180	12/2018	CN	N/A
110135524	12/2018	CN	N/A
111310934	12/2019	CN	N/A
2016-533570	12/2015	JP	N/A
2017-049677	12/2016	JP	N/A
2019-061664	12/2018	JP	N/A
2019-139468	12/2018	JP	N/A
2020/203061	12/2019	WO	N/A

OTHER PUBLICATIONS

“Ryan et al. Plan-Structured Deep Neural Network Models for Query Performance Prediction, 2019” (Year: 2019). cited by examiner

Official Communication issued in corresponding European Patent Application No. 21198055.2, mailed on Mar. 25, 2022. cited by applicant

Official Communication issued in corresponding Chinese Patent Application No. 202011247471.4, mailed on Jul. 21, 2021. cited by applicant

Primary Examiner: Afshar; Kamran

Assistant Examiner: Hales; Brian J

Attorney, Agent or Firm: Keating & Bennett, LLP

Background/Summary

CROSS REFERENCE TO RELATED APPLICATION(S)

(1) This application claims the priority of the Chinese patent application 202011247471.4 filed on Nov. 10, 2020, the content of which is hereby used for reference.

TECHNICAL FIELD

(2) Embodiments of the present disclosure mainly relate to a field of deep learning, and in particular to a method and apparatus of training a model, an electronic device, a computer-readable

storage medium, and a development system of training a model.

BACKGROUND

(3) With a rapid development of artificial intelligence technology, deep learning technology has become a key technology in a field of artificial intelligence. Deep learning framework development system enables a developer to build, train or evaluate customized neural networks by using functional components provided in the system, so that the customized neural networks may be applied to natural language processing, image recognition, speech recognition, and so on. In order to facilitate development, a large number of application programming interfaces (APIs) are designed in the deep learning framework development system. For example, for a senior developer, the deep learning framework development system generally includes a low-level API that may be flexibly applied in implementation of a complex scene model, and for a junior developer, the deep learning framework development system generally includes a high-level API that follows a fixed pattern. However, a model construction of the high-level API is not completely consistent with that of the low-level API. This results in that a large amount of codes are needed if the low-level API needs to be applied in an application and a transformation of the high-level API, which raises the bar of system development.

SUMMARY

(4) According to exemplary embodiments of the present disclosure, there is provided a solution for training a model.

(5) In a first aspect of the present disclosure, there is provided a method of training a model, including: calling a training preparation component to set at least a loss function and an optimization function, in response to determining that a training preparation instruction is received, wherein the loss function and the optimization function are called to train the model; calling a training component to set a first data reading component, in response to determining that a training instruction is received, wherein the first data reading component is configured to load a training data set for training the model; and training the model based on the training data set from the first data reading component, by using the loss function and the optimization function through the training component.

(6) In a second aspect of the present disclosure, there is provided an apparatus of training a model, including: a training preparation component calling module configured to call a training preparation component to set at least a loss function and an optimization function, in response to determining that a training preparation instruction is received, wherein the loss function and the optimization function are called to train the model; a training component calling module configured to call a training component to set a first data reading component, in response to determining that a training instruction is received, wherein the first data reading component is configured to load a training data set for training the model; and a training execution module configured to train the model based on the training data set from the first data reading component, by using the loss function and the optimization function through the training component.

(7) In a third aspect of the present disclosure, there is provided a development system of training a model, including: a training preparation component configured to set at least a loss function and an optimization function in response to a training preparation instruction, wherein the loss function and the optimization function are called to train the model; and a training component configured to: set a first data reading component in response to a training instruction, wherein the first data reading component is configured to load a training data set for training the model; and train the model based on the training data set from the first data reading component, by using the loss function set and the optimization function set.

(8) In a fourth aspect of the present disclosure, there is provided an electronic device, including: one or more processors; and a storage device for storing one or more programs, wherein the one or more programs, when executed by the one or more processors, cause the one or more processors to implement the method according to the first aspect of the present disclosure.

- (9) According to a fifth aspect of the present disclosure, there is provided a computer-readable storage medium having a computer program stored thereon, wherein the computer program, when executed by a processor, causes the processor to implement the method according to the first aspect of the present disclosure.
- (10) In a sixth aspect of the present disclosure, there is provided a computer program product containing computer program instructions, wherein the computer program instructions are executable by a processor to implement the method according to the first aspect of the present disclosure.
- (11) It should be understood that content described in this section is not intended to limit key or important features in the embodiments of the present disclosure, nor is it intended to limit the scope of the present disclosure. Other features of the present disclosure will be easily understood through the following description.
-

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The above and other features, advantages and aspects of the embodiments of the present disclosure will become more apparent in combination with the drawings and with reference to the following detailed description. In the drawings, same or similar reference numerals indicate same or similar elements.
- (2) FIG. 1 shows a schematic diagram of an example environment in which various embodiments of the present disclosure may be implemented.
- (3) FIG. 2 shows a schematic diagram of a development system architecture for training a model according to the embodiments of the present disclosure.
- (4) FIG. 3 shows a flowchart of a process of training a model according to the embodiments of the present disclosure.
- (5) FIG. 4 shows a schematic diagram of data distribution in parallel training with a plurality of computing devices according to the embodiments of the present disclosure.
- (6) FIG. 5 shows a block diagram of an apparatus of training a model according to the embodiments of the present disclosure.
- (7) FIG. 6 shows a block diagram of a computing device for implementing the various embodiments of the present disclosure.

DETAILED DESCRIPTION OF EMBODIMENTS

- (8) Hereinafter, embodiments of the present disclosure will be described in more detail with reference to the drawings. Although some embodiments of the present disclosure are shown in the drawings, it should be understood that the present disclosure may be implemented in various forms and should not be construed as being limited to the embodiments set forth herein. On the contrary, these embodiments are provided for a more thorough and complete understanding of the present disclosure. It should be understood that the drawings and the embodiments of the present disclosure are only used for exemplary purposes and are not used to limit the protection scope of the present disclosure.
- (9) In the description of the embodiments of the present disclosure, the term “including” and similar terms should be understood as open-ended inclusion, that is, “including but not limited to.” The term “based on” should be understood as “at least partially based on.” The term “an embodiment,” “one embodiment” or “this embodiment” should be understood as “at least one embodiment.” The terms “first,” “second” and the like may refer to different or same objects.
- (10) The following may also include other explicit and implicit definitions.
- (11) As mentioned above, in order to improve a usability of a high-level API and reduce a code amount of algorithms implemented by the high-level API, it is necessary to provide an optimized

development system of training a model as well as a method and apparatus of training a model based on the development system. In addition, in current mainstream methods of training a model, training data generally needs to be processed in parallel through a plurality of computing devices (that is, computing nodes dedicated to model training, such as CPU or GPU, etc.) so as to achieve parallel training. However, in a traditional high-level API, different codes need to be input separately to set a single computing device or a plurality of computing devices for processing data, which further increases the code amount. Therefore, in a design of the high-level API, this aspect needs to be taken into account to reduce the code amount.

(12) According to the embodiments of the present disclosure, a model training solution is proposed. For example, in the design of the high-level API, a call path between a relevant component in the high-level API and that in the low-level API may be created, so that low-level API codes such as a loss function, a measurement function, an optimization function, etc., may be completely reused. After receiving a relevant instruction from a developer or other users, the development system may directly call a high-level API component associated with the instruction, and the high-level API component may automatically call the low-level API used to execute the instruction. In this way, compared with the traditional high-level API, the amount of codes that the developer needs to input is significantly reduced. Since the high-level API supports the user to define or select the low-level API such as the loss function and the measurement function, the high-level API in the present disclosure is more flexible and practical than the traditional high-level API.

(13) In addition, the method of training the model in the present disclosure may also solve a problem of failure of parallel processing with a plurality of computing devices due to a lack of data to be processed on an individual computing device by automatically completing data and optionally setting a respective mask, and may solve a problem of automatic aggregation of an evaluation result by firstly aggregating data after parallel processing and then calculating the evaluation result.

(14) The embodiments of the present disclosure will be described in detail below with reference to the drawings. FIG. 1 shows a schematic diagram of an example environment **100** in which various embodiments of the present disclosure may be implemented. As shown in FIG. 1, the example environment **100** includes a user instruction **110** for training a model, a development system **120**, and a model **130**.

(15) As shown in FIG. 1, the development system **120** is suspended until the user instruction **110** is input by the user. In some embodiments, the user instruction **110** is a code typed by the developer. Alternatively or additionally, the user instruction **110** may also be an instruction key for a junior developer or even a beginner. For example, when the beginner wants to select a specific function (for example, an optimization function) required for training the model, the beginner may select a training preparation component on an initial development interface, and select an optimization function, such as Adam optimizer, in a next level of the training preparation component. In some embodiments, the development system **120** may be located in, including but not limited to a personal computer, a server computer, a handheld or laptop device, a mobile device (such as a mobile phone, a personal digital assistant (PDA), a media player), a multiprocessor system, a consumer electronic product, a small computer, a large computer, a distributed computing environment including any one of the systems or devices described above, or the like.

(16) When the development system **120** receives the user instruction **110** from the developer, the development system **120** may automatically call a components associated with the user instruction **110**. As an example, the development system **120** may call a training preparation component to define relevant functions required to train the model **130**. As another example, the development system **120** may call a training component to define a data reading component required to read the training data. Thus, the model may be automatically trained based on the training data selected and the relevant functions.

(17) FIG. 2 shows a schematic diagram of a development system **200** of training the model according to the embodiments of the present disclosure. As shown in FIG. 2, the development

system **200** includes a high-level API **210**. The high-level API **210** includes at least a training preparation component **211** and a training component **212**. After receiving a training preparation instruction from the developer, the training preparation component **211** may set a loss function **201** and an optimization function **205** for training the model **130**. It should be understood that the training preparation component **211** may be used to define the optimization function, the loss function, the measurement function, the training data set, etc. required for training the model **130**. After receiving a training instruction from the developer, the training component **212** may set a data reading component **207** so as to load training data **209** for training the model **130** (that is, a training data set). That is to say, the training component **212** may be used to set a cycle iteration process, a number of training rounds and a process of reading the training data required for training the model **130**. After relevant parameters for training are set, the training component **212** is configured to train the model **130** based on the training data **209** from the data reading component **207**, by using the loss function **201** set and the optimization function **205** set.

(18) In some embodiments, the training preparation component **211** may further set a measurement function **203**, and the high-level API **210** may further include an evaluation component. The evaluation component (not shown) may set the data reading component **207** based on an evaluation instruction. The data reading component **207** is configured to load evaluation data different from the training data **209** (that is, an evaluation data set). That is to say, the evaluation component may evaluate the model **130** based on a difference between an output of the model **130** (that is, a prediction result) and a labeled result in the evaluation data set. For example, the evaluation component may evaluate the model **130** based on the evaluation data set from the data reading component **207**, by using the model **130** trained, the loss function **201** and the measurement function **203**.

(19) In some embodiments, the high-level API **210** may further includes a prediction component used to set the data reading component **207** so as to load a prediction data set different from the training data **209**. For example, the prediction component may determine a prediction result of the prediction data set from the data reading component **207** by using the model **130** trained.

(20) As shown in FIG. 2, the development system **200** may include several low-level APIs, such as the loss function **201**, the measurement function **203**, the optimization function **205**, the data reading component **207**, and the training data **209**. As an example, the loss function **201**, the measurement function **203**, the optimization function **205** and the data reading component **207** are all the low-level APIs in the development system of training the model. For example, the data reading component **207** may be used to read the training data **209** and input an input portion of the training data **209** to the model **103**. An output of the model is the prediction result. The loss function **201** may be used to compare the prediction result with the labeled result in the training data **209** so as to obtain the difference. The optimization function **205** may be used to optimize the parameters of the model **103** so as to reduce the difference. The above process is repeated until the parameters of the model **103** converge.

(21) It should be understood that the data reading component(s) **207** called by the components mentioned above may be a same data reading component used to perform different tasks at different times, or may be different data reading components. For example, when a user instruction for training is received, the data reading component **207** may retrieve the training data **209**; when a user instruction for evaluation is received, the data reading component **207** may retrieve the evaluation data; and when a user instruction for prediction is received, the data reading component **207** may retrieve the prediction data.

(22) The technical solutions described above are only for example, and do not limit the present disclosure. It should be understood that the entire development system **200** may also be arranged in other ways and connection relationships. In order to explain the principle of the above solutions more clearly, a process of training the model will be described below in more detail with reference to FIG. 3.

(23) FIG. 3 shows a flowchart of a process of training a model according to the embodiments of the present disclosure. In some embodiments, a method **300** may be implemented in the development system **120** shown in FIG. 1. A process **300** of training a model according to the embodiments of the present disclosure will be described below with reference to FIG. 3. For ease of understanding, specific data mentioned below are all exemplary and are not used to limit the protection scope of the present disclosure.

(24) In order to more clearly introduce the solutions of the present disclosure, a dataset-based model training is illustrated with reference to FIG. 3 by way of example in describing a specific process of training the model. It should be understood that model training development solutions in the present disclosure are also applicable to other development system frameworks. After the developer sets a format of input training data and a network structure of the model to be trained, the process **300** of training the model begins.

(25) In step **302**, the development system **120** may detect in real time whether a user instruction is input or not. When it is determined that the user instruction **110** such as the training preparation instruction is received, the development system **120** automatically calls the training preparation component **211** to set at least the loss function **201** and the optimization function **205** for training the model **130**. It should be understood that the “component” and “function” mentioned here are actually the application programming interface APIs mentioned above.

(26) In step **304**, the development system **120** may continue to detect whether a user instruction is input or not. When it is determined that the user instruction **110** such as the training instruction is received, the development system **120** automatically calls the training component **212** to set the data reading component **207**. Here, the data reading component **207** is configured to load the training data **209** for training the model **130** (that is, the training data set). In some embodiments, the training component **212** may include a call path for the loss function **201**, a call path for the optimization function **205**, and a call path for the data reading component **207**.

(27) It should be understood that when the model **130** is trained based on the training data **209**, due to a large amount of the training data **209**, the training is usually performed by parallel processing with a plurality of computing devices, so as to reduce training time. However, when the training data **209** is allocated to the plurality of computing devices, there may be a lack of data to be processed on a certain computing device. For example, if the training data set contains 10 data, and four computing devices are used for parallel processing, there may be a problem of missing data on two computing devices, resulting in the failure of parallel training with the plurality of computing devices.

(28) Therefore, the problem of missing data may be solved automatically through the following process. For a clear description, this process is described with reference to FIG. 4. FIG. 4 shows a schematic diagram of an interior of the data reading component **400** for data distribution in parallel training with a plurality of computing devices according to the embodiments of the present disclosure. As shown in FIG. 4, a large amount of training data **209** is loaded in the data reading component **400**. The training data **209** contains at least a first batch **410** and a last batch **420** (intermediate batches are not shown). Each batch of training data **209** is divided into a plurality of groups to be loaded into the plurality of computing devices for parallel execution of, for example, the following training process.

(29) Firstly, the development system **120** may acquire a number of the computing devices for the parallel processing of the training data **209**, that is 4. It should be understood that the type and number of the computing devices may be set in the training preparation component **211**, or the developer may directly enter codes to make a simple setting. Therefore, the development system **120** may then determine the number of the computing devices based on the setting. After that, the development system **120** may group the training data set based on the number, as shown in FIG. 4, so that the data in the training data set is arranged in the data reading component **207**. Further, positions in the data reading component **207** where the training data is missing, that is, vacancy **421**

and vacancy **422**, may also be determined. Finally, the development system **120** may fill these positions with predetermined data. As an example, the development system **120** may fill the vacancy **421** and the vacancy **422** with any data in the training data set. For example, a first data in the data set may be copied and filled into the vacancy **421**, and a second data in the data set may be copied and filled into the vacancy **422**. With similar processing, the training data **209** may be input into the computing devices so as to train the model **130** in a subsequent process.

(30) In step **306**, the development system **120** may train the model **130** based on the training data **209** from the data reading component **207**, by using the loss function **201** and the optimization function **205** through the training component **212**. It should be understood that since the training component **212** includes the call path for the loss function **201**, the call path for the optimization function **205** and the call path for the data reading component **207**, the training component **212** may automatically call the data reading component **207** to read the training data **209**. In addition, the input portion of the training data **209** is input to the model **103**, and the output of the model **103** is the prediction result. Therefore, the training component **212** may automatically call the loss function **201** to compare the prediction result with the labeled result in the training data **209**, so as to obtain the difference. Furthermore, based on the difference, the training component **212** may automatically call the optimization function **205** to optimize the parameters of the model **103**. A two-layer loop program has been constructed in the training component **212** to perform the above process cyclically until the parameters of the model **103** converge or a predetermined number of iterations are reached. In this way, the present disclosure enables the developer to train the model flexibly only by inputting a few lines of code, which greatly saves developer's research and development costs.

(31) A process of evaluating the model **130** will be described in detail below.

(32) Similar to the process **302**, the development system **120** may further automatically call the training preparation component **211**, based on the user instruction **110** from the developer, to set the measurement function **203** for evaluating the model **130** (that is, a character segment about "evaluation" in the code input by the developer). In this way, the developer may select and set the functions required to evaluate the model **130** only by entering a few lines of code.

(33) Similar to the process **304**, the development system **120** may further automatically call the evaluation component, based on the user instruction **110** (here is the evaluation instruction) from the developer, to set the data reading component **207**. Here, the data reading component **207** is configured to load the evaluation data different from the training data **209** (that is, the evaluation data set). The evaluation data set may be input to the model **130** to evaluate the model **130**. In some embodiments, the training component may include a call path for the loss function **201**, a call path for the measurement function **203**, and a call path for the data reading component **207**.

(34) Similar to the process **306**, the development system **120** may evaluate the model **130** based on the evaluation data set from the data reading component **207**, by using the model **130** trained, the loss function **201** and the measurement function **203** through the evaluation component. For example, a recall rate and an accuracy rate of the model **130** may be calculated. In this way, the present disclosure enables the developer to evaluate the model flexibly only by inputting a few lines of code.

(35) The process of automatically solving the problem of missing data is described above with reference to FIG. **4**. It should be understood that this process is only for the training of the model. Because the training data set usually contains a large amount of data, the process of training the model may not have too high requirements on the training data. Therefore, the training data filled in the vacancies **421** and **422** may also be used to train the model **130**. However, if the model **130** is evaluated by parallel execution with a plurality of computing devices, the training data filled in the vacancies **421** and **422** may affect the evaluation result. Therefore, this case may be automatically handled in the following way.

(36) Firstly, the development system **120** may acquire a number of the computing devices for

parallel processing of the evaluation data, that is 4, for example. Then, the development system **120** may group the evaluation data based on the number, as shown in FIG. **4**, so that the data in the evaluation data set is arranged in the data reading component **207**. Positions in the data reading component **207** where the evaluation data is missing, that is, vacancy **421** and vacancy **422**, may also be determined. After that, the development system **120** may fill these positions with predetermined data. As an example, the development system **120** may fill the vacancies **421**, **422** with any data in the evaluation data set. For example, a first data in the data set may be copied and filled into the vacancy **421**, and a second data in the data set may be copied and filled into the vacancy **422**. Thus, similar to the manner described above, each batch in the filled data set may be used for the parallel processing with the plurality of computing devices. That is, the evaluation result for the model **130** may be determined based on the filled evaluation data set by using the model **130** trained, the loss function **201** set and the measurement function **203** set.

(37) For the evaluation result determined, the evaluation result of the evaluation data filled in the vacancies **421** and **422** is not expected. Therefore, the development system **120** may minimize a weight of an invalid evaluation result associated with the position where the evaluation data is missing in the evaluation result, so as to remove the invalid evaluation result. For example, the weight of the evaluation result associated with the position where the evaluation data is missing may be set to zero, and a weight of other positions may be set to one, so that the result is masked. In addition, the development system **120** may be further configured to automatically aggregate the evaluation result. For example, the development system **120** may call the training component to firstly aggregate the prediction result output from the model, and then calculate the evaluation result through the measurement function **203**. Thus, the developer may aggregate the evaluation result without entering additional codes. In this way, either a processing with a single computing device or a parallel processing with a plurality of computing devices may be implemented in the development system **120** of the present disclosure, and the amount of input code is significantly reduced.

(38) In addition, in some embodiments, in addition to functions of training and evaluation described above, the development system **120** may be further configured to predict the output of the model **130** based on the user instruction **110**. For example, the development system **120** may call the prediction component to set the data reading component **207**, after the prediction instruction is receiving. The data reading component **207** is configured to load the prediction data different from the training data **209**. The prediction data here differs from the training data **209** and the evaluation data in that both the training data **209** and the evaluation data are labeled data (that is, both contain the input data entering the model **130** and the labeled result), while the prediction data is unlabeled data (that is, the prediction data only contains the input data entering the model **130**). Then, the development system **120** may determine the prediction result of the prediction data set from the data reading component **207** by using the model **130** trained, through the prediction component. When the developer needs to view the prediction result of specific data or a group of data, a function of prediction may be realized conveniently only by inputting a few lines of code, which significantly saves research and development resources.

(39) Through the embodiments described above, the solution of training the model, the solution of evaluating the model and the solution of predicting the model of the present disclosure may realize a reduction of the input of codes. Training a model based on the traditional high-level API generally needs tens of lines or even more codes. Compared with this, the solution of training the model, the solution of evaluating the model and the solution of predicting the model of the present disclosure only need a few lines of codes in total, so that the developer's research and development resources and time costs are significantly saved. In addition, in a case of the parallel training with a plurality of computing devices, the solutions of the embodiments of the present disclosure do not need to input additional codes, or the input codes are significantly reduced.

(40) FIG. **5** shows a block diagram of an apparatus **500** of training a model according to the

embodiments of the present disclosure. As shown in FIG. 5, the apparatus **500** may include a training preparation component calling module **502**, a training component calling module **504**, and a training execution module **506**. The training preparation component calling module **502** is configured to call a training preparation component to set at least a loss function and an optimization function, in response to determining that a training preparation instruction is received. The loss function and the optimization function are called to train the model. The training component calling module **504** is configured to call a training component to set a first data reading component, in response to determining that a training instruction is received. The first data reading component is configured to load a training data set for training the model. The training execution module **506** is configured to train the model based on the training data set from the first data reading component, by using the loss function and the optimization function through the training component.

(41) In some embodiments, the training preparation component calling module **502** may be further configured to call the training preparation component to set a measurement function. The apparatus **500** may further include an evaluation component calling module and an evaluation execution module. The evaluation component calling module is configured to call an evaluation component to set a second data reading component, in response to determining that an evaluation instruction is received. The second data reading component is configured to load an evaluation data set different from the training data set. The evaluation execution module is configured to evaluate the model based on the evaluation data set from the second data reading component, by using the model trained, the loss function and the measurement function through the evaluation component.

(42) In some embodiments, the apparatus **500** may further include a prediction component calling module and a prediction result determination module. The prediction component calling module is configured to call a prediction component to set a third data reading component, in response to determining that a prediction instruction is received. The third data reading component is configured to load a prediction data set different from the training data set. The prediction result determination module is configured to determine a prediction result of the prediction data set from the third data reading component, by using the model trained through the prediction component.

(43) In some embodiments, the apparatus **500** may further include a number acquisition module, a training data arrangement module, a position determination module, and a filling module. The number acquisition module is configured to acquire a number of computing devices for parallel processing of the training data set. The training data arrangement module is configured to group the training data set based on the number, so that training data in the training data set is arranged in the first data reading component. The position determination module is configured to determine a position in the first data reading component where the training data is missing. The filling module is configured to fill the position with predetermined data.

(44) In some embodiments, the apparatus **500** may further include a number acquisition module, a training data arrangement module, a position determination module, and a filling module. The number acquisition module is configured to acquire a number of computing devices for parallel processing of the evaluation data set. The training data arrangement module is configured to group the evaluation data set based on the number, so that evaluation data in the evaluation data set is arranged in the second data reading component. The position determination module is configured to determine a position in the second data reading component where the evaluation data is missing. The filling module is configured to fill the position with predetermined data, so as to form a filled evaluation data set.

(45) In some embodiments, the apparatus **500** may further include a prediction result determination module and a weight minimization module. The prediction result determination module is configured to determine an evaluation result for the model based on the filled evaluation data set, by using the model trained, the loss function set and the measurement function set. The weight minimization module is configured to minimize a weight of an invalid evaluation result in the

evaluation result, so as to remove the invalid evaluation result. The invalid evaluation result is associated with the position where the evaluation data is missing.

(46) In some embodiments, the training component includes a call path for the loss function, a call path for the optimization function and a call path for the first data reading component.

(47) In some embodiments, the evaluation component includes a call path for the loss function, a call path for the measurement function and a call path for the second data reading component.

(48) FIG. 6 shows a block diagram of a computing device 600 for implementing the various embodiments of the present disclosure. The computing device 600 may be used to implement the development system 120 in FIG. 1. As shown, the computing device 600 includes a central processing unit (CPU) 601, which may perform various appropriate actions and processing based on computer program instructions stored in a read-only memory (ROM) 602 or computer program instructions loaded from a storage unit 608 into a random access memory (RAM) 603. Various programs and data required for operations of the computing device 600 may also be stored in the RAM 603. The CPU 601, the ROM 602 and the RAM 603 are connected to each other through a bus 604. An input/output (I/O) interface 605 is also connected to the bus 604.

(49) Various components in the computing device 600, including an input unit 606 such as a keyboard, a mouse, etc., an output unit 607 such as various types of displays, speakers, etc., a storage unit 608 such as a magnetic disk, an optical disk, etc., and a communication unit 609 such as a network card, a modem, a wireless communication transceiver, etc., are connected to the I/O interface 605. The communication unit 609 allows the computing device 600 to exchange information/data with other devices through a computer network such as the Internet and/or various telecommunication networks.

(50) The processing unit 601 performs the various methods and processes described above, such as the process 300. For example, in some embodiments, the process 300 may be implemented as a computer software program that is tangibly contained on a machine-readable medium such as the storage unit 608. In some embodiments, part or all of a computer program may be loaded and/or installed on the computing device 600 via the ROM 602 and/or the communication unit 609. When the computer program is loaded into the RAM 603 and executed by the CPU 601, one or more steps of the process 300 described above may be performed. Alternatively, in other embodiments, the CPU 601 may be configured to perform the process 300 in any other appropriate way (for example, by means of firmware).

(51) The functions described above may be performed at least partially by one or more hardware logic components. For example, without limitation, exemplary types of the hardware logic components that may be used include: field programmable gate array (FPGA), application specific integrated circuit (ASIC), application specific standard product (ASSP), system on chip (SOC), complex programmable logic device (CPLD), etc.

(52) Program codes for implementing the method of the present disclosure may be written in a programming language or any combination of a plurality of programming languages. These program codes may be provided to a processor or a controller of a general-purpose computer, a special-purpose computer, or other programmable data processing devices, so that when the program codes are executed by the processor or the controller, the functions/operations specified in the flowchart and/or the block diagram may be implemented. The program codes may be executed completely on a machine, partly on the machine, partly on the machine and partly on a remote machine as an independent software package, or completely on the remote machine or a server.

(53) In the context of the present disclosure, the machine readable medium may be a tangible medium that may contain or store programs for use by or in combination with an instruction execution system, device or apparatus. The machine-readable medium may be a machine-readable signal medium or a machine-readable storage medium. The machine-readable medium may include, but not be limited to an electronic, magnetic, optical, electromagnetic, infrared or semiconductor system, device or apparatus, or any suitable combination of the above. More

specific examples of the machine-readable storage medium may include electrical a connection based on one or more wires, a portable computer disk, a hard disk, a random access memory (RAM), a read-only memory (ROM), an erasable programmable read-only memory (EPROM or flash memory), an optical fiber, a portable compact disk read-only memory (CD-ROM), an optical storage device, a magnetic storage device, or any suitable combination of the above.

(54) In addition, although the operations are described in a specific order, it should be understood that such operations are required to be performed in the specific order shown or in a sequential order, or that all the operations illustrated should be performed to achieve a desired result. Under certain circumstances, multitasking and parallel processing may be advantageous. Similarly, although some specific implementation details are included in the above discussion, these should not be interpreted as limiting the scope of the present disclosure. Some features described in the context of separate embodiments may also be implemented in combination in a single implementation. Conversely, the various features described in the context of a single implementation may also be implemented in a plurality of implementations individually or in any suitable sub-combination.

(55) Although the subject matter has been described in language specific to structural features and/or method logical actions, it should be understood that the subject matter defined in the appended claims is not necessarily limited to the specific features or actions described above. On the contrary, the specific features and actions described above are merely exemplary forms of implementing the claims.

Claims

1. A computer-implemented method of training a model, comprising: calling a training preparation application programming interface (API) to set at least a loss function and an optimization function, in response to determining that a training preparation instruction is received, wherein the loss function and the optimization function are called to train the model; calling a training API to set a first data reading API, in response to determining that a training instruction is received, wherein the first data reading API is configured to load a training data set for training the model, wherein the training API comprises a call path for the loss function, a call path for the optimization function, and a call path for the first data reading API, to reuse low-level API codes of the loss function, low-level API codes of the optimization function and low-level API codes of the first data reading API; acquiring a number of a plurality of computing devices for parallel processing of the training data set; grouping the training data set based on the number, so that training data in the training data set is arranged in the first data reading API; determining a position in the first data reading API where the training data is missing; filling the position with predetermined data; and training the model based on the training data set from the first data reading API after the filling, by using the loss function and the optimization function through the training API, wherein the loss function is used for comparing a prediction result output by the model with a labeled result in the training data set so as to obtain a difference, the optimization function is used for optimizing parameters of the model, and the loss function and the optimization function are configured to perform the comparing and the optimizing repeatedly until the parameters of the model converge.
2. The method of claim 1, further comprising: calling the training preparation API to set a measurement function; calling an evaluation API to set a second data reading API, in response to determining that an evaluation instruction is received, wherein the second data reading API is configured to load an evaluation data set different from the training data set; and evaluating the model based on the evaluation data set from the second data reading API, by using the model trained, the loss function and the measurement function through the evaluation API.
3. The method of claim 1, further comprising: calling a prediction API to set a third data reading API, in response to determining that a prediction instruction is received, wherein the third data

reading API is configured to load a prediction data set different from the training data set; and determining a prediction result of the prediction data set from the third data reading API, by using the model trained through the prediction API.

4. The method of claim 2, further comprising: acquiring a number of a plurality of computing devices for parallel processing of the evaluation data set; grouping the evaluation data set based on the number, so that evaluation data in the evaluation data set is arranged in the second data reading API; determining a position in the second data reading API where the evaluation data is missing; and filling the position with predetermined data, so as to form a filled evaluation data set.

5. The method of claim 4, further comprising: determining an evaluation result for the model based on the filled evaluation data set, by using the model trained, the loss function set and the measurement function set; and minimizing a weight of an invalid evaluation result in the evaluation result, so as to remove the invalid evaluation result, wherein the invalid evaluation result is associated with the position where the evaluation data is missing.

6. The method of claim 2, wherein the evaluation API comprises a call path for the loss function, a call path for the measurement function, and a call path for the second data reading API.

7. A non-transitory computer-readable storage medium having a computer program stored thereon, wherein the computer program, when executed by a processor, causes the processor to implement the method of claim 1.

8. An electronic device, comprising: one or more processors; and a storage device for storing one or more programs, wherein the one or more programs, when executed by the one or more processors, cause the one or more processors to implement operations of training a model, comprising: calling a training preparation application programming interface (API) to set at least a loss function and an optimization function, in response to determining that a training preparation instruction is received, wherein the loss function and the optimization function are called to train the model; calling a training API to set a first data reading API, in response to determining that a training instruction is received, wherein the first data reading API is configured to load a training data set for training the model, wherein the training API comprises a call path for the loss function, a call path for the optimization function, and a call path for the first data reading API, to reuse low-level API codes of the loss function, low-level API codes of the optimization function and low-level API codes of the first data reading API; acquiring a number of a plurality of computing devices for parallel processing of the training data set; grouping the training data set based on the number, so that training data in the training data set is arranged in the first data reading API; determining a position in the first data reading API where the training data is missing; filling the position with predetermined data; and training the model based on the training data set from the first data reading API after the filling, by using the loss function and the optimization function through the training API wherein the loss function is used for comparing a prediction result output by the model with a labeled result in the training data set so as to obtain a difference, the optimization function is used for optimizing parameters of the model, and the loss function and the optimization function are configured to perform the comparing and the optimizing repeatedly until the parameters of the model converge.

9. The electronic device of claim 8, wherein the one or more processors are further configured to implement operations of: calling the training preparation API to set a measurement function; calling an evaluation API to set a second data reading API, in response to determining that an evaluation instruction is received, wherein the second data reading API is configured to load an evaluation data set different from the training data set; and evaluating the model based on the evaluation data set from the second data reading API, by using the model trained, the loss function and the measurement function through the evaluation API.

10. The electronic device of claim 8, wherein the one or more processors are further configured to implement operations of: calling a prediction API to set a third data reading API, in response to determining that a prediction instruction is received, wherein the third data reading API is

configured to load a prediction data set different from the training data set; and determining a prediction result of the prediction data set from the third data reading API, by using the model trained through the prediction API.

11. The electronic device of claim 9, wherein the one or more processors are further configured to implement operations of: acquiring a number of a plurality of computing devices for parallel processing of the evaluation data set; grouping the evaluation data set based on the number, so that evaluation data in the evaluation data set is arranged in the second data reading API; determining a position in the second data reading API where the evaluation data is missing; and filling the position with predetermined data, so as to form a filled evaluation data set.

12. The electronic device of claim 11, wherein the one or more processors are further configured to implement operations of: determining an evaluation result for the model based on the filled evaluation data set, by using the model trained, the loss function set and the measurement function set; and minimizing a weight of an invalid evaluation result in the evaluation result, so as to remove the invalid evaluation result, wherein the invalid evaluation result is associated with the position where the evaluation data is missing.

13. The electronic device of claim 9, wherein the evaluation API comprises a call path for the loss function, a call path for the measurement function, and a call path for the second data reading API.
