

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12402496
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Kobayashi; Hidetomo et al.

Display device

Abstract

A display device with high resolution is provided. A display device with low power consumption is provided. A display device with high luminance is provided. A display device with a high aperture ratio is provided. The display device includes a first wiring, a second wiring, a third wiring, and a pixel electrode. The first wiring extends in a first direction and is supplied with a source signal. The second wiring extends in a second direction intersecting the first direction and is supplied with a gate signal. The third wiring is supplied with a constant potential. The first wiring and the pixel electrode overlap with each other with the third wiring therebetween.

Inventors: Kobayashi; Hidetomo (Isehara, JP), Shishido; Hideaki (Atsugi, JP), Katsui; Shuichi (Atsugi, JP)

Applicant: Semiconductor Energy Laboratory Co., Ltd. (Atsugi, JP)

Family ID: 1000008777917

Assignee: Semiconductor Energy Laboratory Co., Ltd. (Atsugi, JP)

Appl. No.: 17/555671

Filed: December 20, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20220208939 A1	Jun. 30, 2022

Foreign Application Priority Data

JP	2020-214950	Dec. 24, 2020
JP	2021-158140	Sep. 28, 2021

Publication Classification

Int. Cl.: H01L27/32 (20060101); H10D30/67 (20250101); H10K59/131 (20230101)

U.S. Cl.:

CPC H10K59/131 (20230201); H10D30/6713 (20250101); H10D30/6743 (20250101); H10D30/6757 (20250101);

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6462723	12/2001	Yamazaki et al.	N/A	N/A
6952023	12/2004	Yamazaki	257/E29.283	H01L 27/1288
7199768	12/2006	Ono et al.	N/A	N/A
7317429	12/2007	Shirasaki et al.	N/A	N/A
7369075	12/2007	Ishii et al.	N/A	N/A
7674650	12/2009	Akimoto et al.	N/A	N/A
8067775	12/2010	Miyairi et al.	N/A	N/A
8106400	12/2011	Miyairi et al.	N/A	N/A
8212488	12/2011	Osame et al.	N/A	N/A
8737109	12/2013	Yamazaki et al.	N/A	N/A
9047836	12/2014	Koyama	N/A	N/A
9536904	12/2016	Miyake et al.	N/A	N/A
2002/0113546	12/2001	Seo et al.	N/A	N/A
2005/0030265	12/2004	Miyagawa	N/A	N/A
2008/0225061	12/2007	Kimura et al.	N/A	N/A
2010/0032679	12/2009	Kawae et al.	N/A	N/A
2010/0096654	12/2009	Godo	N/A	N/A
2010/0117072	12/2009	Ofuji et al.	N/A	N/A
2011/0031496	12/2010	Yamazaki et al.	N/A	N/A
2011/0031499	12/2010	Kimura	257/E29.296	H01L 27/1251
2011/0057187	12/2010	Sakakura et al.	N/A	N/A
2011/0062434	12/2010	Eguchi et al.	N/A	N/A
2011/0108837	12/2010	Yamazaki et al.	N/A	N/A
2011/0133181	12/2010	Yamazaki	N/A	N/A
2011/0210324	12/2010	Sakakura et al.	N/A	N/A
2011/0210355	12/2010	Yamazaki et al.	N/A	N/A
2012/0007084	12/2011	Park et al.	N/A	N/A
2013/0021316	12/2012	Inoue et al.	N/A	N/A
2013/0063413	12/2012	Miyake	N/A	N/A
2013/0069068	12/2012	Miyake	N/A	N/A
2013/0207102	12/2012	Miyake et al.	N/A	N/A
2014/0168194	12/2013	Kong et al.	N/A	N/A
2015/0171156	12/2014	Miyake	N/A	N/A
2015/0187276	12/2014	Shim et al.	N/A	N/A

2016/0260373	12/2015	Miyake	N/A	N/A
2016/0300900	12/2015	Miyake	N/A	N/A
2016/0329392	12/2015	Miyake	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2002-324673	12/2001	JP	N/A
4429576	12/2009	JP	N/A

Primary Examiner: Pham; Long

Attorney, Agent or Firm: Robinson Intellectual Property Law Office, P.C.

Background/Summary

BACKGROUND OF THE INVENTION

1. Field of the Invention

(1) One embodiment of the present invention relates to a display device. One embodiment of the present invention relates to an electronic device including a display device.

(2) Note that one embodiment of the present invention is not limited to the above technical field. Examples of the technical field of one embodiment of the present invention disclosed in this specification and the like include a semiconductor device, a display device, a light-emitting apparatus, a power storage device, a memory device, an electronic device, a lighting device, an input device, an input/output device, a driving method thereof, and a manufacturing method thereof. A semiconductor device refers to a device that can function by utilizing semiconductor characteristics in general.

2. Description of the Related Art

(3) In recent years, the resolution of a display panel has been increased. As a device that requires a high-resolution display panel, a device for virtual reality (VR) or augmented reality (AR) has been actively developed in recent years.

(4) Examples of the display device that can be used for a display panel include, typically, a liquid crystal display device, a light-emitting apparatus including a light-emitting element such as an organic electroluminescent (EL) element or a light-emitting diode (LED), and electronic paper performing display by an electrophoretic method or the like.

(5) An organic EL element generally has a structure in which a layer containing a light-emitting organic compound is provided between a pair of electrodes. By voltage application to this element, the light-emitting organic compound can emit light. A display device including such an organic EL element needs no backlight which is necessary for a liquid crystal display device and the like and thus can have advantages such as thin, lightweight, high contrast, and low power consumption. Patent Document 1, for example, discloses an example of a display device using an organic EL element.

REFERENCE

(6) [Patent Document 1] Japanese Published Patent Application No. 2002-324673

SUMMARY OF THE INVENTION

(7) The above-described wearable device for VR or AR needs to be provided with a focus adjustment lens between eyes and the display panel. Since part of the screen is enlarged by the lens, low resolution of the display panel might cause a problem of weak sense of reality and immersion.

(8) In addition, in the case of a battery-driven device, the power consumption of the display panel needs to be reduced in order that the continuous use time can be prolonged. In particular, a

transmissive type device for AR is required to have high luminance because an image is displayed to be overlaid on external light.

(9) An object of one embodiment of the present invention is to provide a display device with high resolution. An object of one embodiment of the present invention is to provide a display device with low power consumption. An object of one embodiment of the present invention is to provide a display device with high luminance. An object of one embodiment of the present invention is to provide a display device with a high aperture ratio. An object of one embodiment of the present invention is to provide a highly reliable display device.

(10) An object of one embodiment of the present invention is to provide a novel display device, a novel display module, or a novel electronic device. An object of one embodiment of the present invention is to provide a method for manufacturing the display device with high yield. An object of one embodiment of the present invention is to reduce at least one of problems of the conventional technique.

(11) Note that the description of these objects does not preclude the existence of other objects. In one embodiment of the present invention, there is no need to achieve all these objects. Objects other than these can be derived from the description of the specification, the drawings, the claims, and the like.

(12) One embodiment of the present invention is a display device including a first wiring, a second wiring, a third wiring, and a pixel electrode. The first wiring extends in a first direction and is supplied with a source signal. The second wiring extends in a second direction intersecting the first direction and is supplied with a gate signal. The third wiring is supplied with a constant potential. The first wiring and the pixel electrode overlap with each other with the third wiring therebetween.

(13) Another embodiment of the present invention is a display device including a first wiring, a second wiring, a third wiring, a pixel electrode, a first transistor, and a second transistor. The first wiring extends in a first direction and is supplied with a source signal. The second wiring extends in a second direction intersecting the first direction and is supplied with a gate signal. The third wiring is supplied with a first potential. The first wiring and the pixel electrode overlap with each other with the third wiring therebetween. One of a source and a drain of the first transistor is electrically connected to the first wiring and a gate of the first transistor is electrically connected to the second wiring. One of a source and a drain of the second transistor is electrically connected to the pixel electrode and the other of the source and the drain of the second transistor is electrically connected to the third wiring. The first transistor and the second transistor each include a semiconductor layer in which current flows in the first direction.

(14) Another embodiment of the present invention is a display device including a first wiring, a second wiring, a third wiring, a pixel electrode, a first transistor, and a second transistor. The first wiring extends in a first direction and is supplied with a source signal. The second wiring extends in a second direction intersecting the first direction and is supplied with a gate signal. The third wiring is supplied with a first potential. The first wiring and the pixel electrode overlap with each other with the third wiring therebetween. One of a source and a drain of the first transistor is electrically connected to the first wiring and a gate of the first transistor is electrically connected to the second wiring. One of a source and a drain of the second transistor is electrically connected to the pixel electrode and the other of the source and the drain of the second transistor is electrically connected to the third wiring. The first transistor and the second transistor each comprise a semiconductor layer in which current flows in the second direction.

(15) In the above embodiment, a plurality of dummy layers is preferably included. At this time, it is preferable that the dummy layers each include the same semiconductor material as the semiconductor layer and each include a portion having substantially the same top surface shape as the semiconductor layer. Furthermore, it is preferable that the plurality of dummy layers and the semiconductor layer be arranged at a regular interval in the second direction or the first direction.

(16) In any of the above embodiments, a fourth wiring, a third transistor, and a fourth transistor are

preferably included. One of a source and a drain of the third transistor is electrically connected to the fourth wiring and the other of the source and the drain of the third transistor is electrically connected to a gate of the second transistor. One of a source and a drain of the fourth transistor is electrically connected to the fourth wiring and the other of the source and the drain of the fourth transistor is electrically connected to the pixel electrode. The fourth wiring is supplied with a second potential lower than the first potential

(17) In any of the above embodiments, a fifth transistor is preferably included. The fifth transistor is a transistor in which a channel is formed in silicon. The semiconductor layer contains one or both of indium and zinc. The first transistor and the second transistor are preferably provided above the fifth transistor.

(18) In any of the above embodiments, the third wiring preferably has a top surface shape in a form of lattice. At this time, a first portion extending in the first direction and a second portion extending in the second direction are preferably included. Furthermore, it is preferably that the pixel electrode and the first wiring overlap with each other with the first portion therebetween.

(19) In any of the above embodiments, the number of pixel electrodes is preferably two or more. A light-emitting region is provided over the pixel electrode. The light-emitting regions are arranged so that one of the light-emitting regions is surrounded by six of the light-emitting regions in a plan view.

(20) In the above embodiment, the light-emitting region preferably has a substantially hexagonal top surface shape. Furthermore, it is preferable that the light-emitting region have a top surface shape in which interior angles of two opposite corners of six corners are each larger than 120° and interior angles of the other four of the six corners are each smaller than 120° .

(21) Alternatively, in the above embodiment, the light-emitting region preferably has a substantially hexagonal top surface shape. Furthermore, it is preferable that the pixel electrode have a top surface shape in which six angles are each 120° , lengths of two opposite sides of six sides are equal to each other, and lengths of the other four sides are equal to one another.

(22) In any of the above embodiments, three adjacent light-emitting regions of the light-emitting regions are preferably positioned to be on vertices of an isosceles triangle.

(23) Another embodiment of the present invention is a display module including any of the display devices, and a connector or an integrated circuit.

(24) Another embodiment of the present invention is an electronic device including the above-described display module and at least one of an antenna, a battery, a housing, a camera, a speaker, a microphone, a touch sensor, and an operation button.

(25) According to one embodiment of the present invention, a display device with high resolution can be provided. A display device with low power consumption can be provided. A display device with high luminance can be provided. A display device with a high aperture ratio can be provided. A highly reliable display device can be provided.

(26) According to one embodiment of the present invention, a novel display device, a novel display module, a novel electronic device, or the like can be provided. A method for manufacturing the display device with high yield can be provided. At least one of problems of the conventional technique can be reduced.

(27) Note that the description of these effects does not preclude the existence of other effects. One embodiment of the present invention does not necessarily have all these effects. Effects other than these can be derived from the description of the specification, the drawings, the claims, and the like.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) In the accompanying drawings:

(2) FIGS. 1A to 1C each illustrate a structure example of a display device;

(3) FIG. 2 illustrates a structure example of a display device;

(4) FIGS. 3A to 3E each illustrate a structure example of a display device;

(5) FIGS. 4A to 4E each illustrate a structure example of a display device;

(6) FIGS. 5A to 5E each illustrate a structure example of a display device;

(7) FIGS. 6A to 6D illustrate a structure example of a display device;

(8) FIG. 7 illustrates a structure example of a display device;

(9) FIGS. 8A to 8F each illustrate a structure example of a display device;

(10) FIGS. 9A to 9F each illustrate a structure example of a display device;

(11) FIGS. 10A to 10D are circuit diagrams each illustrating a structure example of a display device;

(12) FIG. 11A to FIG. 11D are circuit diagrams each illustrating a structure example of a display device.

(13) FIG. 12 is a timing chart showing an example of a method for driving a display device;

(14) FIG. 13 illustrates a structure example of a display device;

(15) FIG. 14 illustrates a structure example of a display device;

(16) FIGS. 15A to 15D are circuit diagrams each illustrating a structure example of a protection circuit;

(17) FIG. 16 is a block diagram illustrating a structure example of a display device;

(18) FIG. 17 is a block diagram illustrating a structure example of a display device;

(19) FIG. 18 is a block diagram illustrating a structure example of a display device;

(20) FIGS. 19A and 19B are circuit diagrams illustrating a structure example of a display device.

(21) FIGS. 20A to 20C are a circuit diagram and schematic views illustrating structure examples of a display device;

(22) FIG. 21 is a block diagram illustrating a structure example of a display device;

(23) FIGS. 22A to 22C each illustrate a structure example of a light-emitting device;

(24) FIGS. 23A to 23C illustrate structure examples of a display device;

(25) FIGS. 24A and 24B illustrate a structure example of an electronic device;

(26) FIGS. 25A and 25B illustrate a structure example of an electronic device;

(27) FIG. 26 illustrates a structure example of a transistor of Example;

(28) FIGS. 27A and 27B show electrical characteristics of the transistor of Example;

(29) FIG. 28 is an optical micrograph of a display panel of Example in a manufacturing step; and

(30) FIG. 29 is a photograph of the display panel of Example that is displaying an image.

DETAILED DESCRIPTION OF THE INVENTION

(31) Embodiments will be described below with reference to the drawings. Note that the embodiments can be implemented with many different modes, and it will be readily understood by those skilled in the art that modes and details thereof can be changed in various ways without departing from the spirit and scope thereof. Therefore, the present invention should not be construed as being limited to the description of embodiments below.

(32) Note that in structures of the invention described below, the same portions or portions having similar functions are denoted by the same reference numerals in different drawings, and the description thereof is not repeated. The same hatching pattern is used for portions having similar functions, and the portions are not denoted by specific reference numerals in some cases.

(33) Note that in each drawing described in this specification, the size, the layer thickness, or the region of each component is exaggerated for clarity in some cases. Therefore, the size, the layer thickness, or the region is not limited to the illustrated scale.

(34) Note that in this specification and the like, ordinal numbers such as “first” and “second” are

- used in order to avoid confusion among components and do not limit the number of components.
- (35) Note that in this specification and the like, the expression “having substantially the same top surface shapes” means that at least outlines of stacked layers partly overlap with each other. For example, the case of patterning an upper layer and a lower layer with the use of the same or partially the same mask patterns is included in the expression. The expression “having substantially the same top surface shapes” also sometimes includes the case where the outlines do not completely overlap with each other; for instance, the edge of the upper layer may be positioned on the inner side or the outer side of the edge of the lower layer.
- (36) Note that the expressions indicating directions such as “over” and “under” are basically used to correspond to the directions of drawings. However, in some cases, the term “over” or “under” in the specification indicates a direction that does not correspond to the apparent direction in the drawings, for the purpose of easy description or the like. For example, when a stacked order (formation order) of a stacked body or the like is described, even in the case where a surface on which the stacked body is provided (e.g., a formation surface, a support surface, a bonding surface, or a planarization surface) is positioned above the stacked body in the drawings, the direction and the opposite direction are referred to as “under” and “over”, respectively, in some cases.
- (37) Note that in this specification, an EL layer means a layer containing at least a light-emitting substance (also referred to as a light-emitting layer) or a stack including the light-emitting layer provided between a pair of electrodes of a light-emitting element.
- (38) In this specification and the like, a display panel that is one embodiment of a display device has a function of displaying (outputting) an image or the like on (to) a display surface. Thus, the display panel is one embodiment of an output device.
- (39) In this specification and the like, a structure in which a connector such as a flexible printed circuit (FPC) or a tape carrier package (TCP) is attached to a substrate of a display panel, or a structure in which an integrated circuit (IC) is mounted on a substrate by a chip on glass (COG) method or the like is referred to as a display panel module or a display module, or simply referred to as a display panel or the like in some cases.

Embodiment 1

- (40) In this embodiment, a structure example of a display device of one embodiment of the present invention will be described.
- (41) One embodiment of the present invention is a display device that includes a plurality of pixels arranged in a matrix. The display device includes a plurality of source lines (first wirings) supplied with source signals (also referred to as video signals, data signals, or the like) and a plurality of gate lines (second wirings) supplied with gate signals (also referred to as scan signals or the like). The source lines extend in a first direction, and the gate lines extend in a second direction that intersects the first direction.
- (42) Each pixel is provided for the intersection portion of one source line and one gate line. The pixel includes one or more display elements and one or more transistors. The pixel includes a pixel electrode functioning as an electrode of the display element.
- (43) When electrical noise that is caused by a signal supplied to the source line, the gate line, or another wiring is transmitted to the pixel electrode, the potential of the pixel electrode might be changed and the gray level of the pixel might be deviated from the intended value. As a result, the display quality of an image displayed by the display device is impaired. In particular, the frequency of a signal input to the source line is higher than that of a signal input to the gate line and thus greatly affects the potential of the pixel electrode.
- (44) As a measure for reducing such electrical crosstalk between the source line and the pixel electrode, physically separating the pixel electrode from the source line is considered. In particular, it is effective for reducing the crosstalk to prevent the source line and the pixel electrode from overlapping with each other. However, such a method requires a reduction in the area of the pixel electrode, leading to a decrease in the aperture ratio (effective light-emitting area ratio) of the

display device.

(45) Thus, in one embodiment of the present invention, the source line and the pixel electrode overlap with each other with a wiring (a third wiring) supplied with a constant potential positioned therebetween. Accordingly, electrical noise from the source line is blocked by the third wiring, whereby the electrical noise can be inhibited from being transmitted to the pixel electrode. Therefore, it becomes possible to increase the area of the pixel electrode, thereby increasing the aperture ratio of the display device.

(46) The third wiring preferably supplies a constant potential to the pixel. For example, in the case where an organic EL element is used as the display element, the third wiring can also serve as a wiring that supplies an anode potential or a cathode potential to the organic EL element. In addition, the third wiring can also serve as a wiring that supplies a power supply potential (e.g., a high power supply potential (VDD) or a low power supply potential (VSS)) to the pixel.

(47) The third wiring can have a top surface shape in the form of stripes that extend in the first direction, in which the source lines extend. Furthermore, the third wiring may have a portion that extends in the second direction and may have a top surface shape in the form of lattice that includes a portion along the first direction and a portion along the second direction.

(48) Such a structure can inhibit the influence of the electrical crosstalk between the pixel electrode and the wirings including the source lines, whereby the pixel electrode and the wirings can be freely arranged to overlap with each other. Thus, a display device with extremely high resolution can be achieved. For example, it is possible to achieve a display device with a resolution higher than or equal to 1000 ppi, higher than or equal to 2000 ppi, higher than or equal to 3000 ppi, higher than or equal to 4000 ppi, or higher than or equal to 5000 ppi and lower than or equal to 30000 ppi, lower than or equal to 20000 ppi, or lower than or equal to 15000 ppi.

(49) More specific examples are described below with reference to drawings.

Structure Example 1

(50) FIG. 1A is a schematic perspective view illustrating a stacked-layer structure of one of subpixels of a display device **10**. The subpixel includes a pixel circuit **11**, a light-emitting element **12**, a wiring **21**, a wiring **22**, and a wiring **23**. The light-emitting element **12** includes a pixel electrode **24**.

(51) The wiring **21** functions as a source line and extends in a Y direction. The wiring **22** functions as a gate line and extends in an X direction. The wiring **23** is supplied with a constant potential and includes a portion extending in the Y direction.

(52) The light-emitting element **12** is provided in the inside of the pixel electrode **24**. As the light-emitting element **12**, for example, an electroluminescence element in which a layer containing a light-emitting substance (also referred to as an EL layer) is interposed between a pair of electrodes is suitably used. The electroluminescence element emits light when current flows between the pair of electrodes. In particular, an organic EL element in which the EL layer contains a light-emitting organic compound is preferably used.

(53) The pixel circuit **11** is a circuit for controlling a current that flows in the light-emitting element **12**. The pixel circuit **11** preferably includes at least one transistor.

(54) The pixel electrode **24** and the wiring **21** have a region where they overlap with each other in a plan view. Furthermore, the pixel electrode **24** and the wiring **21** overlap with each other with the wiring **23** positioned therebetween. Since the wiring **23** supplied with a constant potential is provided between the pixel electrode **24** and the wiring **21** in this manner, electrical noise due to the wiring **21** is blocked by the wiring **23** and inhibited from being transmitted to the pixel electrode **24** even when the pixel electrode **24** and the wiring **21** overlap with each other. Accordingly, the area of the pixel electrode **24** can be increased, and therefore, the light-emitting area of the light-emitting element **12** can be increased and the aperture ratio (effective light-emitting area ratio) of the display device **10** can be increased.

(55) Here, in this specification and the like, a plan view refers to a view from the display surface

side of the display device **10**.

(56) FIG. **1B** illustrates a display device **10X** that does not include the wiring **23**, as an example. In that case, deviation of the gray scale in the luminance of the light-emitting element **12** may occur when electrical noise from the wiring **21** is transmitted to the pixel electrode **24** positioned above the wiring **21** and the potential of the pixel electrode **24** changes.

(57) FIG. **1C** illustrates, as an example, a display device **10Y** in which the width of the pixel electrode **24** in the X direction is reduced so that the pixel electrode **24** does not overlap with the wiring **21**. In this case, although crosstalk due to electrical noise from the wiring **21** can be inhibited, the light-emitting area of the light-emitting element **12** is small, so that the aperture ratio of the display device **10** is reduced.

(58) As described above, the display device **10** of one embodiment of the present invention can have a high resolution and a high aperture ratio. Since the aperture ratio can be increased, the luminance can be increased and the power consumption can be reduced. Furthermore, a current required for a desired luminance can be reduced, so that a display device with low power consumption can be achieved.

Structure Example 2

(59) A more specific structure example of the pixel will be described below.

Structure Example 2-1

(60) FIG. **2** illustrates a schematic top view of a pixel **20** included in a display device **10A**. The pixel **20** includes a subpixel **20R**, a subpixel **20G**, and a subpixel **20B**. The display device **10A** includes a plurality of pixels **20** that are arranged periodically in the X and Y directions.

(61) The subpixel **20R** includes a light-emitting element **12R** emitting red light. The subpixel **20G** includes a light-emitting element **12G** emitting green light. The subpixel **20B** includes a light-emitting element **12B** emitting blue light.

(62) The light-emitting elements **12R**, **12G**, and **12B** may contain different light-emitting materials from each other, may each have a structure with a combination of a white light-emitting element and a color filter, or may each have a structure with a combination of a blue or violet light-emitting element and a color conversion material (e.g., quantum dots).

(63) FIGS. **3A** to **3E** each illustrate a schematic top view of a subpixel **20X**, one of the subpixels included in the pixel **20** illustrated in FIG. **2**. The subpixel **20X** can be used as any of the subpixels **20R**, **20G**, and **20B**. The light-emitting element is omitted here.

(64) FIG. **3B** illustrates an example of the top surface shape of the wiring **23**, in which the pixel electrode **24** illustrated in FIG. **3A** is shown only by its outline with dashed lines.

(65) The wiring **23** functions as a power supply line for the light-emitting element **12** and is supplied with a constant potential. In the case where the pixel electrode **24** functions as an anode, the wiring **23** is supplied with a high power supply potential; in the case where the pixel electrode **24** functions as a cathode, the wiring **23** is supplied with a low power supply potential.

(66) As illustrated in FIG. **3B**, it is preferable that the wiring **23** include not only a portion extending in the Y direction but also a portion extending in the X direction. Thus, the wiring **23** can have a top surface shape in the form of lattice, so that the electrical resistance can be lower than that in the case of a top surface shape in the form of stripes and the influence of voltage drop can be inhibited.

(67) In FIG. **3C**, the wiring **23** in FIG. **3B** is shown only by its outline with dashed lines. In FIG. **3C**, the same hatching pattern is used for the wiring **22** and a conductive layer formed by processing the same conductive film as the wiring **22**. Similarly, in FIG. **3C**, the same hatching pattern is used for the wiring **21** and a conductive layer formed by processing the same conductive film as the wiring **21**.

(68) In FIG. **3D**, the wiring **21** in FIG. **3C** and the conductive layer formed by processing the same conductive film as the wiring **21** are shown only by their outlines with dashed lines. In FIG. **3E**, the wiring **22** in FIG. **3D** and the conductive layer formed by processing the same conductive film as

the wiring **22** are shown only by their outlines with dashed lines.

(69) FIGS. **3C** and **3D** illustrate a transistor **30a** and a transistor **30b**. FIG. **3D** also illustrates a semiconductor layer **31a** included in the transistor **30a** and a semiconductor layer **31b** included in the transistor **30b**. The transistor **30a** functions as a selection transistor that controls selection/non-selection of the subpixel. The transistor **30b** functions as a driver transistor that controls a current flowing to the light-emitting element.

(70) Part of a gate of the transistor **30a** is composed of the wiring **22**, one of a source and a drain of the transistor **30a** is electrically connected to the wiring **21**, and the other of the source and the drain of the transistor **30a** is electrically connected to a gate of the transistor **30b**. One of a source and a drain of the transistor **30b** is electrically connected to the wiring **23**, and the other of the source and the drain of the transistor **30b** is electrically connected to the pixel electrode **24**.

(71) In the example described here, each top surface shape of the semiconductor layers **31a** and **31b** includes a pair of thick portions where contact portions are provided and a thin portion formed as a channel. The semiconductor layers of the two transistors are preferably formed to have substantially the same top surfaces shapes in this manner, in which case the electrical characteristic of the transistors can be uniform and designing is facilitated. Note that a transistor with desired electrical characteristics can be formed with a combination of semiconductor layers of the same pattern. For example, a plurality of semiconductor layers can be arranged in parallel and connected in one transistor so that the channel width of the transistor can be an integral multiple of that of the other transistor. Alternatively, a plurality of semiconductor layers can be arranged in serial and connected in one transistor, whereby the channel length of the transistor can be an integral multiple of that of the other transistor.

(72) In the display device **10A**, the semiconductor layer **31a** included in the transistor **30a** and the semiconductor layer **31b** included in the transistor **30b** are each placed so that current can flow in the Y direction, i.e., a direction parallel to the direction in which the wiring **21** extends. In other words, the transistors **30a** and **30b** are each placed so that the channel length direction thereof can be parallel to the Y direction and the channel width direction thereof can be parallel to the X direction. In this manner, the direction of current flow is preferably the same for the plurality of transistors included in the pixel, in which case variation of the electrical characteristics can be inhibited and designing can be facilitated.

(73) Here, as illustrated in FIG. **3D** and the like, a plurality of dummy layers **32** is preferably provided. The dummy layers **32** are formed by processing the same film as the semiconductor layers **31a** and **31b** and can have the same composition as the semiconductor layers **31a** and **31b**. In FIGS. **3A** to **3E**, different hatching patterns are used for the semiconductor layers **31a** and **31b** and the dummy layer **32** to differentiate the semiconductor layers **31a** and **31b** from the dummy layers **32**.

(74) A top surface of the dummy layer **32** has preferably the same shape as those of the semiconductor layers **31a** and **31b** or a shape in which the shapes of the top surfaces of the semiconductor layers **31a** and **31b** are periodically combined. In the display device **10A**, each of dummy layers **32** has a top surface shape that includes two or more thick portions and a thin portion(s) that connect adjacent thick portions in the Y direction. Every dummy layer **32** is provided so that the longitudinal direction thereof can be parallel to the Y direction. Furthermore, each of the dummy layers **32** is provided across a plurality of pixels lined in the Y direction.

(75) In this manner, when the dummy layers **32** are provided in a region where neither the semiconductor layer **31a** nor the semiconductor layer **31b** is provided, variations in processing shapes of the semiconductor layers **31a** and **31b** can be reduced, so that variations in the electrical characteristics of the transistors **30a** and **30b** can be reduced. Note that a dummy layer is provided in a vacant space for the purposes of stabilization of the manufacturing process, a reduction in the processing variation, and the like, and is basically not considered as a component of the circuit. For this reason, the dummy layer is electrically floating or supplied with a constant voltage. Note that a

dummy layer is preferably provided for a layer other than the semiconductor layer.

(76) The dummy layers **32** are preferably provided so as to be laid throughout the region where neither the semiconductor layer **31a** nor the semiconductor layer **31b** is provided, as much as possible. Although the display device **10A** is an example in which the dummy layers **32** are provided in a region other than the region where the wiring **21** provided, the dummy layers **32** may be provided to overlap with the wiring **21**.

(77) Note that although two transistors are provided in one subpixel in this example, one embodiment of the present invention is not limited thereto; three or more transistors may be provided. In that case, it is preferable that semiconductor layers of all the transistors provided in a subpixel have the same patterns and the directions of currents flowing in the semiconductor layers be the same as one another.

(78) The above is the description of Structure example 2-1.

(79) Structural examples that is partly different from the above structure example will be described below with reference to drawings. Note that portions similar to those described above are not described below in some cases. In the drawings shown below, the same reference numerals and the same hatching patterns are used for components having the same function and description thereof is omitted in some cases.

Structure Example 2-2

(80) FIGS. **4A** to **4E** are schematic top views of the subpixel **20X** included in a display device **10B**. The display device **10B** differs from the display device **10A** mainly in the orientations of the semiconductor layers **31a** and **31b** and the dummy layers **32**.

(81) The semiconductor layers **31a** and **31b** are each placed so that current flows in the X direction, i.e., a direction parallel to a direction in which the wiring **22** extends. In other words, the transistors **30a** and **30b** are each placed so that the channel length direction thereof is parallel to the X direction and the channel width direction thereof is parallel to the Y direction.

(82) The dummy layer **32** is placed so that the longitudinal direction thereof is parallel to the X direction. The dummy layer **32** is provided across a plurality of pixels lined in the X direction.

(83) Note that the display device **10B** is an example in which the dummy layer **32** includes a region overlapping with the wiring **21**.

Structure Example 2-3

(84) FIGS. **5A** to **5E** are schematic top views of the subpixel **20X** included in a display device **10C**. The display device **10C** differs from the display device **10A** mainly in including no dummy layer **32**.

(85) Note that the display device **10B** illustrated in Structure example 2-2 may have a structure including no dummy layer **32**, like the display device **10C**.

Structure Example 3

(86) A structure example of a display device different from Structural example 2 will be described below. Note that portions similar to those described above are denoted by the same reference numerals as those described above and are not described in some cases.

(87) [Example of Pixel Arrangement]

(88) FIG. **6A** is a schematic top view of part of a display device **10D**. FIG. **6A** illustrates an example of a way of arranging six light-emitting elements. A structure illustrated in FIG. **6A** is one unit, and units are arranged in the X and Y directions repeatedly in a pixel portion included in the display device **10D**.

(89) FIG. **6A** illustrates six pixel electrodes **24**, two light-emitting elements **12R**, two light-emitting elements **12G**, and two light-emitting elements **12B**. Regions where two subpixels **20R**, two subpixels **20G**, and two subpixels **20B** are provided are shown by dashed lines.

(90) Each of the light-emitting elements is placed in the inside of one of closest-packed hexagonal regions. Focusing on one of the light-emitting elements, the light-emitting element is placed so as to be surrounded by six light-emitting elements. In addition, the light-emitting elements are

arranged so that adjacent light-emitting elements have different colors. For example, focusing on the light-emitting element **12R**, the light-emitting element **12R** is surrounded by three light-emitting elements **12G** and three light-emitting elements **12B** that are alternately arranged.

(91) It is preferable that a light-emitting region of the light-emitting element also have a hexagonal top surface shape. It is preferable that the pixel electrode **24** also have a hexagonal top surface shape.

(92) FIGS. **6B** and **6C** each illustrate an example of the top surface shape of the light-emitting region of the light-emitting element **12**.

(93) In a light-emitting element **12X** illustrated in FIGS. **6B** and **6C**, a length between a pair of vertices positioned in the Y direction and a distance between a pair of sides extending in the Y direction are equal to each other and are each a length L. Therefore, the alignment pitch of pixels in the X direction can be the same as that in the Y direction. Note that in the case of a closest-packed arrangement of regular hexagons, it is difficult to make the arrangement pitches in the X and Y directions equal to each other; therefore, it is preferable not to use regular hexagons.

(94) In the light-emitting element **12X** illustrated in FIG. **6B**, interior angles (angles $\theta 1$) of the pair of vertices positioned in the Y direction are equal to each other, and interior angles (angles $\theta 2$) of the other four vertices are equal to each other. Here, the angle $\theta 1$ is larger than 120° , and the angle $\theta 2$ is smaller than 120° .

(95) In the light-emitting element **12X** illustrated in FIG. **6C**, all of the six interior angles are each 120° . In addition, the length of each of the pair of sides extending in the Y direction is shorter than each of the other sides.

(96) Actually, the vertices of the top surface of the light-emitting element **12X** are often rounded; therefore, the above-described angles and lengths of the sides are applied to a hexagonal figure similar to the light-emitting element **12X**.

(97) The shape of the light-emitting element **12X** has been described above. It is preferable that the pixel electrode have a similar shape also. At this time, the light-emitting region can be provided so as to overlap with the pixel electrode and be positioned in the inside side of the pixel electrode in a plan view.

(98) FIG. **6D** illustrates the positions of three adjacent light-emitting elements (the light-emitting elements **12R**, **12G**, and **12B**). As illustrated in FIG. **6D**, the three light-emitting elements are preferably arranged on the vertices of an isosceles triangle. At this time, in the isosceles triangle, the angle of the vertex positioned in the Y direction is preferably larger than each of the angles of the vertices at the ends of a side parallel to the X direction.

Structure Example 3-1

(99) Next, a more specific structure example of the pixel will be described.

(100) FIG. **7** illustrates a schematic top view of a display device **10E**. A region including 2×2 subpixels is shown in FIG. **7**. A subpixel **20G**, a subpixel **20B**, and two subpixels **20R** are shown in FIG. **7**.

(101) FIG. **8A** illustrates a schematic top view of a subpixel **20X**, one of the subpixels included in the display device **10E**. The subpixel **20X** can be used as any of the subpixels **20R**, **20G**, and **20B** in FIG. **7**. In FIG. **8A**, the pixel electrode **24** is shown only by its outline with dashed lines.

(102) FIGS. **8B** to **8F** illustrate the layout of layers that form the subpixel **20X**. FIG. **8B** illustrates a layer positioned closest to a formation surface, FIG. **8F** illustrates two layers closest to the pixel electrode **24**.

(103) FIG. **8B** illustrates a layer including the wiring **22** and a conductive layer that is obtained by processing the same conductive film as the wiring **22**. Part of them functions as one gate electrode (also referred to as a bottom gate electrode, a first gate electrode, or the like) of the transistor **30a** or **30b**.

(104) FIG. **8C** illustrates a layer including the semiconductor layers **31a** and **31b** and a plurality of dummy layers **32**. Although the channel length direction is parallel to the Y direction in FIG. **8C**,

the channel length direction may be parallel to the X direction in a manner similar to that in Structural example 2-2 described above.

(105) FIG. 8D illustrates a layer including a plurality of conductive layers 25. Part of the conductive layers 25 functions as the other gate electrode (also referred to as a top gate electrode, a second gate electrode, or the like) of the transistor 30a or 30b. In addition, a conductive layer 25 that is electrically floating may be provided as a dummy layer. With the dummy layer, variations in the processing shape of the conductive layer 25 and the like can be reduced.

(106) FIG. 8E illustrates a layer including the wiring 21 and a plurality of conductive layers obtained by processing the same conductive film as the wiring 21. Part of the plurality of conductive layers in FIG. 8E functions as one of a source electrode and a drain electrode of the transistor 30a or 30b. Part of the plurality of conductive layers in FIG. 8E functions as one electrode of a capacitor.

(107) FIG. 8F illustrates a layer that includes a conductive layer 27 and a layer that includes the wiring 23 positioned above the layer including the conductive layer 27 and a conductive film obtained by processing the same conductive film as the wiring 23. The pixel electrode 24 is provided above the wiring 23. Part of the conductive layer 27 functions as the other electrode of the capacitor. Part of the conductive layer obtained by processing the same conductive film as the wiring 23 functions as a relay wiring that electrically connects the pixel electrode 24 and the transistor 30b.

Structure Example 3-2

(108) The structure of the subpixel including two transistors has been described above, and a structure example of a subpixel including four transistors will be described below. In the description below, Structural example 3-1 and the like are referred to for portions similar to those described in Structural example 3-1 and the like, and description of the portions is omitted in some cases.

(109) FIGS. 9A to 9F illustrate a structure example of a display device 10F including the subpixel 20X with four transistors.

(110) The subpixel 20X includes the transistor 30a, the transistor 30b, a transistor 30c, and a transistor 30d.

(111) As illustrated in FIG. 9B, three gate lines (wirings 22a, 22b, and 22c) and a wiring 22d supplied with a constant potential are provided. Part of the wiring 22a functions as one of gate electrodes of the transistor 30a. Part of the wiring 22b functions as one of gate electrodes of the transistor 30c. Part of the wiring 22c functions as one of gate electrodes of the transistor 30d.

(112) As illustrated in FIG. 9C, a semiconductor layer 31c included in the transistor 30c and a semiconductor layer 31d included in the transistor 30d are placed so that current flows in the Y direction in a manner similar to that of the semiconductor layers 31a and 31b. The dummy layer 32 is provided in a space between the semiconductor layers so that the longitudinal direction of the dummy layer can be parallel to the Y direction. Although the channel length direction is parallel to the Y direction in FIG. 9C, the channel length direction may be parallel to the X direction in a manner similar to that in Structural example 2-2 described above.

(113) As illustrated in FIGS. 9B to 9D, the transistors 30a, 30b, 30c, and 30d are each a transistor including a pair of gate electrodes. Note that one or more of the four transistors may be transistors each including only one gate (single-gate transistors) and the other transistors may be transistors each including a pair of gates (dual-gate transistors).

(114) [Pixel Circuit]

(115) A structural example of a pixel circuit and an example of a driving method thereof, which are applicable to the display device of one embodiment of the present invention, will be described below.

(116) [Structure Example of Pixel Circuit]

(117) A pixel circuit PIX1 illustrated in FIG. 10A includes a transistor M1, a transistor M2, a

capacitor C1, and a light-emitting element EL. Wirings SL, GL, AL, and CL are electrically connected to the pixel circuit PIX1.

(118) A gate of the transistor M1 is electrically connected to the wiring GL, one of a source and a drain of the transistor M1 is electrically connected to the wiring SL, and the other of the source and the drain of the transistor M1 is electrically connected to a gate of the transistor M2 and one electrode of the capacitor C1. One of a source and a drain of the transistor M2 is electrically connected to the wiring AL and the other of the source and the drain of the transistor M2 is electrically connected to an anode of the light-emitting element EL. The other electrode of the capacitor C1 is electrically connected to the anode of the light-emitting element EL. A cathode of the light-emitting element EL is electrically connected to the wiring CL.

(119) The transistor M1 can be referred to as a selection transistor and functions as a switch for controlling selection/non-selection of the pixel. The transistor M2 can be referred to as a driver transistor and has a function of controlling a current flowing to the light-emitting element EL. The capacitor C1 functions as a storage capacitor and has a function of retaining a gate potential of the transistor M2. A capacitor such as a MIM capacitor may be used as the capacitor C1; alternatively, capacitance between wirings, a gate capacitance of the transistor, or the like may be used as the capacitor C1.

(120) The wiring SL is supplied with a source signal. The wiring GL is supplied with a gate signal. The wirings AL and CL are each supplied with a constant potential. In the light-emitting element EL, the anode side can have a high potential and the cathode side can have a lower potential than the anode side.

(121) The pixel circuit PIX2 illustrated in FIG. 10B has a structure in which a transistor M3 is added to the pixel circuit PIX1. In addition, a wiring V0 is electrically connected to the pixel circuit PIX2.

(122) A gate of the transistor M3 is electrically connected to the wiring GL, one of a source and a drain of the transistor M3 is electrically connected to the anode of the light-emitting element EL, and the other of the source and the drain of the transistor M3 is electrically connected to the wiring V0.

(123) The wiring V0 is supplied with a constant potential when data is written to the pixel circuit PIX2. Thus, a variation in the gate-source potential of the transistor M2 can be inhibited.

(124) A pixel circuit PIX3 illustrated in FIG. 10C is an example in the case where a transistor in which a pair of gates are electrically connected to each other is used as each of the transistors M1 and M2 of the pixel circuit PIX1. A pixel circuit PIX4 illustrated in FIG. 10D is an example in the case where such transistors are used in the pixel circuit PIX2. With these structures, a current that can flow through the transistor can be increased. Although the transistor in which the pair of gates are connected to each other is used as every transistor here, one embodiment of the present invention is not limited thereto. A transistor that includes a pair of gates electrically connected to different wirings may be used. When, for example, a transistor in which one of the gates is electrically connected to the source is used, the reliability can be increased.

(125) A pixel circuit PIX5 illustrated in FIG. 11A has a structure in which a transistor M4 is added to the pixel circuit PIX2. Three wirings (wirings GL1, GL2, and GL3) functioning as gate lines are electrically connected to the pixel circuit PIX5.

(126) A gate of the transistor M4 is electrically connected to the wiring GL3, one of a source and a drain of the transistor M4 is electrically connected to the gate of the transistor M2, and the other of the source and the drain of the transistor M4 is electrically connected to the wiring V0. The gate of the transistor M1 is electrically connected to the wiring GL1, and the gate of the transistor M3 is electrically connected to the wiring GL2.

(127) When the transistors M3 and M4 are turned on at the same time, the source and the gate of the transistor M2 have the same potential, so that the transistor M2 can be turned off. Thus, a current flowing to the light-emitting element EL can be blocked forcibly. Such a pixel circuit is

suitable for the case of using a display method in which a display period and an off period are alternately provided.

(128) A pixel circuit PIX6 illustrated in FIG. 11B is an example in the case where a capacitor C2 is added to the pixel circuit PIX5. The capacitor C2 functions as a storage capacitor.

(129) A pixel circuit PIX7 illustrated in FIG. 11C and a pixel circuit PIX8 illustrated in FIG. 11D are each an example in the case where a transistor including a pair of gates is used in the pixel circuit PIX5 or the pixel circuit PIX6. A transistor in which a pair of gates are electrically connected to each other is used as each of the transistors M1, M3, and M4, and a transistor in which one of gates is electrically connected to a source is used as the transistor M2.

(130) [Example of Driving Method]

(131) An example of a method for driving a display device in which the pixel circuit PIX5 is used will be described below. Note that a similar driving method can be applied to the pixel circuits PIX6, PIX7, and PIX8.

(132) FIG. 12 shows a timing chart of a method for driving the display device in which the pixel circuit PIX5 is used. Changes in the potentials of wirings GL1[k], GL2[k], and GL3[k] that are gate lines of the k-th row and changes in the potentials of wirings GL1[k+1], GL2[k+1], and GL3[k+1] that are gate lines of the k+1-th row are shown here. FIG. 12 also shows the timing of supplying a signal to the wiring SL functioning as a source line.

(133) In the example of the driving method described here, one horizontal period is divided into a lighting period and a non-lighting period. A horizontal period of the k-th row is shifted from a horizontal period of the k+1-th row by a selection period of the gate line.

(134) In the lighting period of the k-th row, first, the wirings GL1[k] and GL2[k] are supplied with a high-level potential and the wiring SL is supplied with a source signal. Thus, the transistors M1 and M3 are turned on, so that a potential corresponding to the source signal is written from the wiring SL to the gate of the transistor M2. After that, the wirings GL1[k] and GL2[k] are supplied with a low-level potential, so that the transistors M1 and M3 are turned off and the gate potential of the transistor M2 is retained.

(135) Subsequently, in a lighting period of the k+1-th row, data is written by operation similar to that described above.

(136) Next, the non-lighting period is described. In the non-lighting period of the k-th row, the wirings GL2[k] and GL3[k] are supplied with a high-level potential. Accordingly, the transistors M3 and M4 are turned on, and the source and the gate of the transistor M2 are supplied with the same potential, so that almost no current flows through the transistor M2. Therefore, the light-emitting element EL is turned off. As a result, all the subpixels that are positioned in the k-th row are turned off. The subpixels of the k-th row remain in the off state until the next lighting period.

(137) Subsequently, in a non-lighting period of the k+1-th row, all the subpixels of the k+1-th row are turned off in a manner similar to that described above.

(138) Such a driving method described above, in which the subpixels are not constantly on through one horizontal period and a non-lighting period is provided in one horizontal period, can be called duty driving. With duty driving, an afterimage phenomenon can be inhibited at the time of displaying moving images; therefore, a display device with high performance in displaying moving images can be achieved. Particularly in a VR device and the like, a reduction in an afterimage can reduce what is called VR sickness.

(139) In the duty driving, the proportion of the lighting period to one horizontal period can be called a duty cycle. For example, a duty cycle of 50% means that the lighting period and the non-lighting period have the same lengths. Note that the duty cycle can be set freely and can be adjusted appropriately within a range higher than 0% and lower than or equal to 100%, for example.

(140) The above is the description of the example of the driving method.

(141) [Example of Cross-Sectional Structure]

(142) Next, examples of a cross-sectional structure of a display device of one embodiment of the

present invention will be described.

(143) FIG. 13 is a schematic cross-sectional view of a display device **200A**. The display device **200A** includes, between a substrate **201** and a substrate **202**, a light-emitting element **250R**, a light-emitting element **250G**, a transistor **210**, a transistor **220**, a capacitor **240**, and the like.

(144) The transistor **210** is a transistor whose channel formation region is formed in the substrate **201**. As the substrate **201**, a semiconductor substrate such as a single crystal silicon substrate can be used, for example. The transistor **210** includes part of the substrate **201**, a conductive layer **211**, a low-resistance region **212**, an insulating layer **213**, an insulating layer **214**, and the like. The conductive layer **211** functions as a gate electrode. The insulating layer **213** is positioned between the substrate **201** and the conductive layer **211** and functions as a gate insulating layer. The low-resistance region **212** is a region where the substrate **201** is doped with an impurity, and functions as one of a source and a drain. The insulating layer **214** is provided to cover a side surface of the conductive layer **211** and functions as an insulating layer.

(145) An element isolation layer **215** is provided between two adjacent transistors **210** to be embedded in the substrate **201**.

(146) A wiring layer **203** is provided between the transistor **210** and the transistor **220**. The wiring layer **203** has a structure in which layers each including one or more wirings are stacked. Each of the layers includes a conductive layer **271**, and an interlayer insulating layer **273** is provided between the layers. Furthermore, the conductive layers **271** of different layers are electrically connected to one another with plugs **272** provided in the interlayer insulating layers **273**.

(147) The transistor **220** is provided over the wiring layer **203**. The transistor **220** contains a metal oxide (also referred to as an oxide semiconductor) in the semiconductor layer where a channel is formed.

(148) The transistor **220** includes a semiconductor layer **221**, an insulating layer **223**, a conductive layer **224**, a pair of conductive layers **225**, an insulating layer **226**, a conductive layer **227**, and the like.

(149) An insulating layer **231** is provided over the wiring layer **203**. The insulating layer **231** functions as a barrier layer that prevents diffusion of impurities such as water and hydrogen from the wiring layer **203** side into the transistor **220** and release of oxygen from the semiconductor layer **221** to the wiring layer **203** side. As insulating layer **231**, for example, a film in which hydrogen or oxygen is less likely to diffuse than in a silicon oxide film can be used. Examples of such a film include an aluminum oxide film, a hafnium oxide film, and a silicon nitride film.

(150) The conductive layer **227** is provided over the insulating layer **231**, and the insulating layer **226** is provided to cover the conductive layer **227**. The conductive layer **227** functions as a first gate electrode of the transistor **220**, and part of the insulating layer **226** functions as a first gate insulating layer. An oxide insulating film such as a silicon oxide film is preferably used as at least part of the insulating layer **226** that is in contact with the semiconductor layer **221**.

(151) The insulating layer **226** is provided over the semiconductor layer **221**. A metal oxide film having semiconductor characteristics (also referred to as an oxide semiconductor film) is preferably used as the semiconductor layer **221**.

(152) When the semiconductor layer **221** is an In-M-Zn oxide, as the atomic ratio of metal elements in a sputtering target used for deposition of the In-M-Zn oxide, In:M:Zn=1:1:1, In:M:Zn=1:1:1.2, In:M:Zn=1:1:3:2, In:M:Zn=1:3:4, In:M:Zn=1:3:6, In:M:Zn=2:2:1, In:M:Zn=2:1:3, In:M:Zn=3:1:2, In:M:Zn=4:2:3, In:M:Zn=4:2:4.1, In:M:Zn=5:1:3, In:M:Zn=5:1:6, In:M:Zn=5:1:7, In:M:Zn=5:1:8, In:M:Zn=6:1:6, In:M:Zn=5:2:5, or the like is given.

(153) The sputtering target preferably contains a polycrystalline oxide, in which case the semiconductor layer **221** having crystallinity is easily formed. Note that the atomic ratio in the deposited semiconductor layer **221** varies within the range of $\pm 40\%$ from any of the atomic ratios of the metal elements contained in the sputtering target. For example, in the case where the composition of the sputtering target used for the semiconductor layer **221** is In:Ga:Zn=4:2:4.1

[atomic ratio], the composition of the deposited semiconductor layer is in the neighborhood of In:Ga:Zn=4:2:3 [atomic ratio] in some cases.

(154) Note that when the atomic ratio is described as In:Ga:Zn=4:2:3 or as being in the neighborhood thereof, the case is included where the atomic proportion of Ga is greater than or equal to 1 and less than or equal to 3 and the atomic proportion of Zn is greater than or equal to 2 and less than or equal to 4 with the atomic proportion of In being 4. In addition, when the atomic ratio is described as In:Ga:Zn=5:1:6 or as being in the neighborhood thereof, the case is included where the atomic proportion of Ga is greater than 0.1 and less than or equal to 2 and the atomic proportion of Zn is greater than or equal to 5 and less than or equal to 7 with the atomic proportion of In being 5. Furthermore, when the atomic ratio is described as In:Ga:Zn=1:1:1 or as being in the neighborhood thereof, the case is included where the atomic proportion of Ga is greater than 0.1 and less than or equal to 2 and the atomic proportion of Zn is greater than 0.1 and less than or equal to 2 with the atomic proportion of In being 1.

(155) The energy gap of the semiconductor layer **221** is 2 eV or more, preferably 2.5 eV or more. Thus, with the use of a metal oxide having a wider energy gap than silicon, the off-state current of the transistor can be reduced.

(156) The semiconductor layer **221** preferably has a non-single-crystal structure. The non-single-crystal structure includes, for example, a CAAC structure which is described later, a polycrystalline structure, a microcrystalline structure, and an amorphous structure. Among the non-single-crystal structures, the amorphous structure has the highest density of defect states, whereas the CAAC structure has the lowest density of defect states.

(157) A c-axis aligned crystal (CAAC) will be described below. A CAAC refers to an example of a crystal structure.

(158) Note that the CAAC structure is a crystal structure of a thin film or the like that has a plurality of nanocrystals (crystal regions each of which has a maximum diameter of less than 10 nm). The nanocrystals each have c-axis alignment in a particular direction. The nanocrystals each have neither a-axis alignment nor b-axis alignment, and have continuous crystal connection without a grain boundary in the a-axis and b-axis directions. In particular, in a thin film having the CAAC structure, the c-axes of nanocrystals are likely to be aligned in the film thickness direction, the normal direction of the surface where the thin film is formed, or the normal direction of the surface of the thin film.

(159) A c-axis aligned crystal oxide semiconductor (CAAC-OS) is an oxide semiconductor with high crystallinity. On the other hand, in the CAAC-OS, a clear grain boundary cannot be observed; thus, a reduction in electron mobility due to the grain boundary is less likely to occur. Entry of impurities, formation of defects, or the like might decrease the crystallinity of an oxide semiconductor. This means that the CAAC-OS can be referred to as an oxide semiconductor having small amounts of impurities and defects (e.g., oxygen vacancies). Therefore, an oxide semiconductor including the CAAC-OS is physically stable. Accordingly, the oxide semiconductor including the CAAC-OS is resistant to heat and has high reliability.

(160) Here, in crystallography, a general way of choosing a unit cell formed with three axes (crystal axes) of the a-axis, the b-axis, and the c-axis is to choose a unit cell in which a unique axis is used as the c-axis. In particular, in the case of a crystal having a layered structure, a general way of choosing a unit cell is to choose a unit cell in which two axes parallel to the plane direction of a layer are used as the a-axis and the b-axis and an axis intersecting with the layer is used as the c-axis. Typical examples of such a crystal having a layered structure include graphite, which is classified as a hexagonal system. In a unit cell of graphite, the a-axis and the b-axis are parallel to the cleavage plane and the c-axis is orthogonal to the cleavage plane. For example, an InGaZnO₄ crystal having a YbFe₂O₄ type crystal structure, which is a layered structure, can be classified as a hexagonal system, and, in a unit cell thereof, the a-axis and the b-axis are parallel to the plane direction of the layer and the c-axis is orthogonal to the layer (i.e.,

orthogonal to the a-axis and the b-axis).

(161) In an image obtained with a TEM, crystal parts cannot be found clearly in an oxide semiconductor film having a microcrystalline structure (a microcrystalline oxide semiconductor film) in some cases. In most cases, a crystal part in the microcrystalline oxide semiconductor film is greater than or equal to 1 nm and less than or equal to 100 nm, or greater than or equal to 1 nm and less than or equal to 10 nm. A microcrystal with a size greater than or equal to 1 nm and less than or equal to 10 nm, or greater than or equal to 1 nm and less than or equal to 3 nm is specifically referred to as a nanocrystal (nc). An oxide semiconductor film including a nanocrystal is referred to as a nanocrystalline oxide semiconductor (nc-OS) film. In an image obtained with a TEM, a grain boundary cannot be found clearly in the nc-OS film in some cases.

(162) In the nc-OS film, a microscopic region (e.g., a region with a size greater than or equal to 1 nm and less than or equal to 10 nm, in particular, a region with a size greater than or equal to 1 nm and less than or equal to 3 nm) has a periodic atomic arrangement. There is no regularity of crystal orientation between different crystal parts in the nc-OS film. Hence, the orientation in the whole film is not observed. Accordingly, in some cases, the nc-OS film cannot be distinguished from an amorphous oxide semiconductor film depending on an analysis method. For example, when the nc-OS film is subjected to structural analysis by an out-of-plane method with an XRD apparatus using an X-ray having a diameter larger than the diameter of a crystal part, a peak indicating a crystal plane does not appear. Furthermore, a halo pattern is shown in a selected-area electron diffraction pattern of the nc-OS film obtained by using an electron beam having a probe diameter larger than the diameter of a crystal part (e.g., larger than or equal to 50 nm). Meanwhile, in some cases, a circular (ring-like) region with high luminance is observed in an electron diffraction pattern (also referred to as nanobeam electron diffraction pattern) of the nc-OS film, which is obtained using an electron beam with a probe diameter close to or smaller than the diameter of a crystal part (e.g., 1 nm or larger and 30 nm or smaller), and spots are observed in the ring-like region.

(163) The nc-OS film has a lower density of defect states than an amorphous oxide semiconductor film. Note that there is no regularity of crystal orientation between different crystal parts in the nc-OS film. Hence, the nc-OS film has a higher density of defect states than the CAAC-OS film. Thus, the nc-OS film has a higher carrier density and higher electron mobility than the CAAC-OS film in some cases. Accordingly, a transistor including the nc-OS film may have high field-effect mobility.

(164) The nc-OS film can be formed at a smaller oxygen flow rate ratio in deposition than the CAAC-OS film. The nc-OS film can also be formed at a lower substrate temperature in formation than the CAAC-OS film. For example, the nc-OS film can be deposited at a relatively low substrate temperature (e.g., 130° C. or lower) or without heating of the substrate; thus, the nc-OS film is suitable for the case of using a large glass substrate, a resin substrate, or the like, and productivity can be increased.

(165) An example of a crystal structure of a metal oxide is described. A metal oxide that is formed by a sputtering method using an In—Ga—Zn oxide target (atomic ratio of In:Ga:Zn=4:2:4.1) at a substrate temperature higher than or equal to 100° C. and lower than or equal to 130° C. is likely to have either the nc structure or the CAAC structure, or a structure in which both structures are mixed. In contrast, a metal oxide formed at a substrate temperature set at room temperature (R.T.) is likely to have the nc structure. Note that room temperature (R.T.) herein also refers to a temperature of the time when a substrate is not heated intentionally.

(166) The pair of conductive layers **225** is provided on and in contact with the semiconductor layer **221**, and functions as a source electrode and a drain electrode.

(167) An insulating layer **232** is provided to cover top and side surfaces of the pair of conductive layers **225**, a side surface of the semiconductor layer **221**, and the like, and an insulating layer **261** is provided over the insulating layer **232**. The insulating layer **232** functions as a barrier layer that prevents diffusion of impurities such as water and hydrogen from the interlayer insulating layer and the like into the semiconductor layer **221** and release of oxygen from the semiconductor layer **221**.

As the insulating layer **232**, an insulating film similar to the insulating layer **231** can be used.

(168) An opening reaching the semiconductor layer **221** is provided in the insulating layers **232** and **261**. The insulating layer **223** that is in contact with the side surfaces of the insulating layers **261** and **232**, the side surface of the conductive layer **225**, and the top surface of the semiconductor layer **221** and the conductive layer **224** over the insulating layer **223** are embedded in the opening. The conductive layer **224** functions as a second gate electrode, and the insulating layer **223** functions as a second gate insulating layer.

(169) The top surface of the conductive layer **224**, the top surface of the insulating layer **223**, and the top surface of the insulating layer **261** are planarized so that they are substantially level with each other, and an insulating layer **233** is provided to cover these layers. An opening portion is provided in the stacked-layer structure between the insulating layer **233** and the insulating layer **231**, and part of the insulating layer **233** is in contact with the insulating layer **231** in the opening portion. The insulating layer **261** functions as an interlayer insulating layer. The insulating layer **233** functions as a barrier layer that prevents diffusion of impurities such as water and hydrogen from layers above the insulating layer **233**. As the insulating layer **233**, an insulating film similar to the insulating layer **231** or the like can be used.

(170) The capacitor **240** is provided over the insulating layer **233**.

(171) The capacitor **240** includes a conductive layer **241**, a conductive layer **242**, and an insulating layer **243** between the conductive layers **241** and **242**. The conductive layer **241** functions as one electrode of the capacitor **240**, the conductive layer **242** functions as the other electrode of the capacitor **240**, and the insulating layer **243** functions as a dielectric of the capacitor **240**.

(172) An insulating layer **234** is provided to cover the capacitor **240**. As the insulating layer **234**, an insulating film similar to the insulating layer **231** can be used. An insulating layer **262** is provided over the insulating layer **231** with an interlayer insulating layer and a wiring positioned therebetween, and the light-emitting elements **250R** and **250G** are provided over the insulating layer **262**.

(173) The light-emitting element **250R** includes a conductive layer **251**, a conductive layer **252R**, an EL layer **253W**, a conductive layer **254**, and the like.

(174) The conductive layer **251** has a property of reflecting visible light, and the conductive layer **252R** has a property of transmitting visible light. The conductive layer **254** has a property of reflecting and transmitting visible light. The conductive layer **252R** functions as an optical adjustment layer for adjusting the optical path length between the conductive layer **251** and the conductive layer **254**. The thickness of the optical adjustment layer can differ between the light-emitting elements of different colors. The thickness of the conductive layer **252R** of the light-emitting element **250R** is different from the thickness of a conductive layer **252G** of the light-emitting element **250G**.

(175) An insulating layer **256** is provided to cover an end portion of the conductive layer **252R** and an end portion of the conductive layer **252G**.

(176) The EL layer **253W** and the conductive layer **254** are shared by a plurality of pixels. The EL layer **253W** includes a light-emitting layer that emits white light.

(177) A coloring layer **255R** is provided over the light-emitting element **250R** with an insulating layer **235** positioned therebetween. A coloring layer **255G** is provided over the light-emitting element **250G**. Note that part of a coloring layer **255B** is shown in FIG. 13.

(178) The coloring layer **255R** transmits red light, the coloring layer **255G** transmits green light, and the coloring layer **255B** transmits blue light, for example. This can increase the color purity of light from the light-emitting elements, so that a display device with higher display quality can be achieved. Furthermore, positional alignment of the light-emitting elements and the coloring layers is easier in the case where the coloring layers are formed over the insulating layer **235** than in the case where the coloring layers are formed on the substrate **202** side and then the substrates **201** and **202** are bonded to each other; therefore, a display device with extremely high resolution can be

achieved.

(179) A lens array **257** is provided over the coloring layers **255R** and **255G**. Light emitted from the light-emitting element **250R** is colored by the coloring layer **255R** and is emitted to the outside through the lens array **257**. The lens array **257** may be omitted if not needed.

(180) The display device **200A** includes the substrate **202** on the viewing side. The substrate **202** and the substrate **201** are bonded to each other. As the substrate **202**, a light-transmitting substrate such as a glass substrate, a quartz substrate, a sapphire substrate, or a plastic substrate can be used.

(181) With such a structure, a display device with extremely high resolution and high display quality can be achieved.

(182) FIG. **14** illustrates a schematic cross-sectional view of a display device **200B** with a structure partly different from that of the display device **200A**.

(183) The light-emitting element **250R** includes an EL layer **253R** that emits red light. The light-emitting element **250G** includes an EL layer **253G** that emits green light.

(184) In the example described here, the display device **200B** includes no coloring layer.

(185) In addition, the EL layer **253R** and the EL layer **253G** are processed so as not to be in contact with each other between adjacent two light-emitting elements. In other words, between the adjacent two light-emitting elements, an end portion of the EL layer **253R** and an end portion of the EL layer **253G** are provided to face each other over the insulating layer **256**. Although the EL layer **253R** and the EL layer **253G** may be formed separately by an evaporation method using a fine metal mask, they are each preferably processed finely by a photolithography method.

(186) The above is the description of the example of the cross-sectional structure.

(187) [Protection Circuit]

(188) A structure example of a protection circuit that can be used in the display device will be described below.

(189) Many source lines and gate lines are arranged in a matrix in an active matrix display device. Therefore, when electrostatic discharge (ESD) is generated in the source line or the gate line during a manufacturing process of the display device, an integration process of an electronic device, or the like, display defects are caused. Thus, a protection circuit for reducing the influence of ESD is preferably provided for the source lines and the gate lines.

(190) In addition, an inspection circuit, terminal, electrode, or the like for checking whether pixels drive normally is sometimes used in an inspection such as a pre-shipment inspection of a display device or a sampling inspection.

(191) FIG. **15A** illustrates a circuit **PC1** for inputting a potential input from a terminal **PRE** to a source line **SL**, as an example.

(192) The circuit **PC1** includes a transistor **Tr1**, a transistor **Tr2**, and a transistor **Tr3**. Each of the transistors includes a pair of gates. A gate positioned below the semiconductor layer is referred to as a back gate, and a gate positioned above the semiconductor layer is referred to as a top gate.

(193) A top gate of the transistor **Tr1** is electrically connected to a terminal **Sig**, a back gate of the transistor **Tr1** is electrically connected to a terminal **VBG1**, one of a source and a drain of the transistor **Tr1** is electrically connected to the source line **SL**, and the other thereof is electrically connected to the terminal **PRE**.

(194) The terminal **Sig** is supplied with a signal for controlling the transistor **Tr1**. The terminal **VBG1** is supplied with a bias potential. When the transistor **Tr1** is turned on, the wiring **SL** is supplied with the potential of the terminal **PRE**.

(195) Here, the transistors **Tr2** and **Tr3** are electrically connected to each other between the top gate of the transistor **Tr1** and the terminal **Sig**. The transistors **Tr2** and **Tr3** function as a protection circuit. The transistors **Tr2** and **Tr3** are each a diode-connected transistor. A terminal **VDD** is electrically connected to the transistor **Tr2**, and a terminal **VSS** is electrically connected to the transistor **Tr3**. A terminal **VBG2** is electrically connected to a back gate of the transistor **Tr2**, and a terminal **VBG3** is electrically connected to a back gate of the transistor **Tr3**.

- (196) A circuit PC2 illustrated in FIG. 15B is an example in the case where the number of terminals and the number of transistors are reduced compared with those in the circuit PC1.
- (197) The circuit PC2 includes the transistor Tr1. The top gate of the transistor Tr1 is electrically connected to the wiring SL, the back gate of the transistor Tr1 is electrically connected to the terminal Sig, one of the source and the drain of the transistor Tr1 is electrically connected to the terminal PRE, and the other thereof is electrically connected to the wiring SL.
- (198) In this manner, the terminal Sig supplied with a control signal is connected not to the top gate of the transistor Tr1 but to the back gate of the transistor Tr1, whereby the terminal Sig does not require any protection circuit and thus the circuit can be simplified. Note that the top gate and the back gate of the transistor Tr1 can be interchanged in some cases depending on the electrical characteristics of the transistor Tr1.
- (199) A circuit PC3 illustrated in FIG. 15C is an example in the case where two transistors, transistors Tr1a and Tr1b, are used instead of the transistor Tr1 in the circuit PC2. Back gates of the transistors Tr1a and Tr1b are electrically connected to the terminal Sig.
- (200) A circuit PC4 illustrated in FIG. 15D is an example in the case where terminals (a terminal Sig1 and a terminal Sig2) are connected to the transistor Tr1a and the transistor Tr1b, respectively.
- (201) With any of the structures illustrated in FIGS. 15B, 15C, and 15D, the number of terminals can be reduced greatly; therefore, a small display device can be achieved.
- (202) At least part of this embodiment can be implemented in appropriate combination with any of the other embodiments described in this specification.

Embodiment 2

- (203) In this embodiment, a display device and a display system that are embodiments of the present invention will be described.
- (204) <Structure Example of Display Device>
- (205) FIG. 16 is a block diagram schematically illustrating a structure example of a display device 510 that is the display device of one embodiment of the present invention. The display device 510 includes a layer 520 and a layer 530. The layer 530 can be stacked above the layer 520, for example. An interlayer insulator or a conductor for electrical connection between different layers can be provided between the layers 520 and 530.
- (206) For example, a transistor provided in the layer 520 can be a transistor in which a channel formation region includes silicon (also referred to as a Si transistor) and can be a transistor in which a channel formation region includes single crystal silicon. In particular, a transistor in which a channel formation region includes single crystal silicon is preferably used as the transistor provided in the layer 520, in which case the on-state current of the transistor can be high, so that a circuit included in the layer 520 can be driven at high speed. The Si transistor can be formed by minute processing with a channel length of 3 nm to 10 nm; therefore, the display device 510 can be provided with a CPU, an accelerator such as a GPU, an application processor, or the like.
- (207) A transistor provided in the layer 530 can be an OS transistor, for example. It is particularly preferable that a transistor in which a channel formation region includes an oxide containing at least one of indium, an element M (the element M is aluminum, gallium, yttrium, or tin), and zinc be used as the OS transistor. Such an OS transistor has a characteristic of an extremely low off-state current. Thus, it is preferable that the OS transistor be used as a transistor provided particularly in a pixel circuit included in a display portion, in which case analog data written to the pixel circuit can be retained for a long time.
- (208) A driver circuit 540 and a functional circuit 550 are provided in the layer 520. Since the Si transistor with a high on-state current is provided in the layer 520, the circuits included in the layer 520 can be driven at high speed.
- (209) A display portion 560 including a plurality of pixels 561 is provided in the layer 530. Pixel circuits 562R, 562G, and 562B that control emission of red light, green light, and blue light are provided in the pixels 561. The pixel circuits 562R, 562G, and 562B function as subpixels of the

pixels **561**. Since the pixel circuits **562R**, **562G**, and **562B** include OS transistors, analog data written to the pixel circuits can be retained for a long time. A backup circuit **582** is provided in each of the pixels **561** included in the layer **530**. The backup circuit is sometimes referred to as a memory circuit.

(210) The driver circuit **540** includes a gate line driver circuit, a source line driver circuit, and the like for driving the pixels **561** (the pixel circuits **562R**, **562G**, and **562B**) in the display portion **560**. The driver circuit **540** is provided not in the layer **530** where the display portion is provided but in the layer **520**, whereby an area occupied by the display portion in the layer **530** can be large. In addition, the driver circuit **540** may include a digital-to-analog (D/A) converter circuit, a low voltage differential signaling (LVDS) circuit functioning as an interface for receiving data such as image data from the outside of the display device **510**, or the like. The Si transistor of the layer **520** can have a high on-state current. The channel length, the channel width, or the like of the Si transistor may be varied in accordance with the operation speed of each circuit.

(211) The functional circuit **550** includes a processor (e.g., a CPU) used for arithmetic processing of data. A CPU includes a plurality of CPU cores. A CPU core includes a flip-flop. A flip-flop includes a plurality of scan flip-flops. Input/output of data of the scan flip-flops (backup data) is performed between a flip-flop **580** and the backup circuit **582**. FIG. **16** illustrates backup data BD as a data signal retained in the backup circuit **582**.

(212) For the backup circuit **582**, for example, a memory including an OS transistor is suitable. The use of an OS transistor with an extremely low off-state current in the backup circuit leads to advantages such as long-time retention of the voltage of analog data written to the backup circuit and very little power consumption for data retention. The backup circuit **582** including the OS transistor can be provided in the display portion **560** where the plurality of pixels **561** is provided. FIG. **16** illustrates a state where the backup circuit **582** is provided in each of the pixels **561**.

(213) The backup circuits **582** including the OS transistor and the layer **520** including the Si transistor can be stacked. The backup circuits **582** may be arranged in a matrix like the subpixels in the pixels **561**; alternatively, one backup circuit **582** may be provided for a plurality of pixels. That is, the backup circuits **582** can be arranged in the layer **530** without being limited by the arrangement of the pixels **561**. Therefore, the backup circuits **582** can be arranged without any increase in the circuit area while the degree of flexibility in the layout of the display portion or the circuits is enhanced, so that memory capacity of the backup circuits **582** required for arithmetic processing can be increased.

(214) <Structure Example of Pixel Circuit and Backup Circuit>

(215) FIG. **17** and FIG. **18** illustrate an example of the layout of the backup circuit **582** and the pixel circuits **562R**, **562G**, and **562B** functioning as the subpixels in the display portion **560**.

(216) FIG. **17** illustrates a structure in which the pixels **561** are arranged in a matrix in the display portion **560**. The pixels **561** each include the pixel circuits **562R**, **562G**, and **562B** and the backup circuit **582**. As described above, the backup circuit **582** and the pixel circuits **562R**, **562G**, and **562B** can be formed with OS transistors and thus can be placed in the same pixel.

(217) <Block Diagram of Display Device>

(218) FIG. **18** is a block diagram illustrating components included in the display device **510**. The display device includes the driver circuit **540**, the functional circuit **550**, and the display portion **560**.

(219) The driver circuit **540** includes a gate driver **541** and a source driver **542**, for example. The gate driver **541** has a function of driving a plurality of gate lines GL for outputting signals to the pixel circuits **562R**, **562G**, and **562B**. The source driver **542** has a function of driving a plurality of source lines SL for outputting signals to the pixel circuits **562R**, **562G**, and **562B**. The driver circuit **540** supplies voltage for performing display with the pixel circuits **562R**, **562G**, and **562B** to the pixel circuits **562R**, **562G**, and **562B** through a plurality of wirings.

(220) The functional circuit **550** includes a CPU **551**. The CPU **551** includes a CPU core **553**. The

CPU core **553** includes the flip-flop **580** for temporarily retaining data used for arithmetic processing. The flip-flop **580** includes a plurality of scan flip-flops **581**, and each of the scan flip-flops **581** is electrically connected to the backup circuit **582** provided in the display portion **560**. (221) The display portion **560** includes the plurality of pixels **561** each including the pixel circuits **562R**, **562G**, and **562B** and the backup circuit **582**. The backup circuit **582** is not necessarily placed in the pixel **561** that is a repeating unit, as described with reference to FIG. **17**. The backup circuit **582** can be placed freely in accordance with the shape of the display portion **560**, the shapes of the pixel circuits **562R**, **562G**, and **562B**, and the like.

(222) <Structure Example of Pixel Circuit>

(223) FIGS. **19A** and **19B** illustrate a structure example of a pixel circuit **562** that can be used as the pixel circuits **562R**, **562G**, and **562B** and a light-emitting element **570** connected to the pixel circuit **562**. FIG. **19A** illustrates connection between elements, and FIG. **19B** schematically illustrates the positional relationship of the driver circuit **540**, the pixel circuit **562**, and the light-emitting element **570**.

(224) In this specification and the like, the term “element” can be replaced with the term “device” in some cases. For example, a display element, a light-emitting element, and a liquid crystal element can be rephrased as a display device, a light-emitting device, and a liquid crystal device, respectively.

(225) The pixel circuit **562**, which is illustrated as an example in FIGS. **19A** and **19B**, includes a switch **SW21**, a switch **SW22**, a transistor **M21**, and a capacitor **C21**. The switch **SW21**, the switch **SW22**, and the transistor **M21** can be formed with OS transistors. Each of the OS transistors of the switch **SW21**, the switch **SW22**, and the transistor **M21** preferably includes both a gate electrode and a back gate electrode, in which case the back gate electrode and the gate electrode can be supplied with the same signals or different signals.

(226) The transistor **M21** includes the gate electrode electrically connected to the switch **SW21**, a first electrode electrically connected to the light-emitting element **570**, and a second electrode electrically connected to a wiring **ANO**. The wiring **ANO** supplies a potential for supplying current to the light-emitting element **570**.

(227) The switch **SW21** includes a first terminal electrically connected to the gate electrode of the transistor **M21** and a second terminal electrically connected to the source line **SL**. Furthermore, the switch **SW21** has a function of controlling its on/off state on the basis of the potential of a gate line **GL1**.

(228) The switch **SW22** includes a first terminal electrically connected to the wiring **V0** and a second terminal electrically connected to the light-emitting element **570**. In addition, the switch **SW22** has a function of controlling its on/off state on the basis of the potential of a gate line **GL2**. The wiring **V0** supplies a reference potential and outputs current flowing in the pixel circuit **562** to the driver circuit **540** or the functional circuit **550**.

(229) The capacitor **C21** includes a conductive film electrically connected to the gate electrode of the transistor **M21** and a conductive film electrically connected to the second terminal of the switch **SW22**.

(230) The light-emitting element **570** includes a first electrode electrically connected to the first electrode of the transistor **M21** and a second electrode electrically connected to a wiring **VCOM**. A potential for supplying current to the light-emitting element **570** is supplied to the wiring **VCOM**.

(231) Accordingly, the intensity of light emitted by the light-emitting element **570** can be controlled in accordance with an image signal supplied to the gate electrode of the transistor **M21**.

Furthermore, the amount of current flowing to the light-emitting element **570** can be increased by the reference potential of the wiring **V0** that is supplied through the switch **SW22**. Moreover, it is possible to estimate the amount of current flowing to the light-emitting element by monitoring the amount of current flowing to the wiring **V0** with an external circuit. Thus, a defect of a pixel or the like can be detected.

(232) In the structure illustrated as an example in FIG. 19B, the wirings electrically connecting the pixel circuit 562 and the driver circuit 540 can be made short, so that wiring resistance of the wirings can be small. Accordingly, data writing can be performed at high speed, and the display device 510 can be driven at high speed. Therefore, even when the number of pixels 561 included in the display device 510 is large, a sufficiently long frame period can be ensured and the pixel density of the display device 510 can be increased. In addition, the increased pixel density of the display device 510 can increase the definition of an image displayed by the display device 510. For example, the pixel density of the display device 510 can be 1000 ppi or higher, 5000 ppi or higher, or 7000 ppi or higher. Thus, the display device 510 can be, for example, a display device for VR or AR and can be suitably used in an electronic device with a short distance between the display portion and the user, such as an HMD.

(233) Although the gate line GL1, the gate line GL2, the wiring ANO, the wiring VCOM, the wiring V0, and the source line SL are supplied with signals from the driver circuit 540 below the pixel circuit 562 through the wirings in FIG. 19B, one embodiment of the present invention is not limited thereto. For example, wirings for supplying signals and voltages of the driver circuit 540 may be led to an outer region of the display portion 560 and electrically connected to the pixel circuits 562 arranged in a matrix in the layer 530. In this case, it is effective that the gate driver 541 included in the driver circuit 540 is provided in the layer 530. That is, the use of OS transistors as transistors of the gate driver 541 is effective. It is effective that part of the function of the source driver 542 included in the driver circuit 540 is provided in the layer 530. For example, it is effective that a demultiplexer distributing signals output by the source driver 542 to source lines is provided in the layer 530. The use of OS transistors as transistors of the demultiplexer is effective.

(234) <Structure Example of Display Correction System>

(235) The display system of one embodiment of the present invention may include a display correction system. The display correction system can reduce display defects based on defective pixels, such as bright spots or dark spots, by correcting a current $I_{\text{sub.EL}}$ flowing to the light-emitting elements 570.

(236) A circuit diagram in FIG. 20A illustrates part of the pixel circuit 562 illustrated in FIG. 19A. The amount of the current $I_{\text{sub.EL}}$ flowing to the light-emitting element 570 in a defective pixel causing a bright spot or a dark spot is extremely larger or smaller than that in a pixel that performs normal display.

(237) The CPU 551 periodically obtains data of a monitor current $I_{\text{sub.MONI}}$ that flows through a switch SW23. The amount of the monitor current $I_{\text{sub.MONI}}$ is converted into digital data that can be treated in the CPU 551 and arithmetic processing is performed in the CPU 551 with the digital data. A defective pixel is presumed by the arithmetic processing in the CPU 551, and correction is performed in the CPU 551 so that a display defect due to the defective pixel is less likely to be seen. For example, in the case where a pixel 561D illustrated in FIG. 20B is a defective pixel, the current $I_{\text{sub.EL}}$ that flows to the light-emitting element 570 of an adjacent pixel 561N is corrected.

(238) The amount of the correction can be estimated by executing arithmetic operation based on an artificial neural network such as a deep neural network (DNN), a convolutional neural network (CNN), a recurrent neural network (RNN), an autoencoder, a deep Boltzmann machine (DBM), or a deep belief network (DBN).

(239) With the above correction, the current $I_{\text{sub.EL}}$ flowing to the pixel 561N adjacent to the defective pixel is corrected to be a current $I_{\text{sub.EL_C}}$. When a composited pixel 561G of the defective pixel and the pixel 561N performs display, a display defect due to the defective pixel, such as a bright spot or a dark spot, can be less likely to be seen, leading to normal display.

(240) Note that during arithmetic operation by the display correction system, which is performed for correcting a current flowing to a pixel, data in the arithmetic operation can be retained as backup data. Therefore, the display correction system is particularly effective in arithmetic processing on an enormous amount of calculation, such as arithmetic operation based on an

artificial neural network. Note that it is also possible to reduce power consumption in addition to a reduction in display defects by making the CPU 551 function as an application processor and combining arithmetic operation with, for example, driving that makes a frame frequency changeable.

(241) <Modification Example of Display Device>

(242) FIG. 21 illustrates a modification example of the components included in the display device 510 described above.

(243) The structure of a block diagram of a display device 510A illustrated in FIG. 21 corresponds to the structure of the display device 510 in FIG. 18 in which an accelerator 552 is added to the functional circuit 550.

(244) In the case where arithmetic operation based on an artificial neural network is performed in the above-described display correction system, product-sum operation is repeatedly performed. The accelerator 552 functions as a dedicated arithmetic circuit to product-sum operation of an artificial neural network NN. In the arithmetic operation with the accelerator 552, the above-mentioned processing for correcting display defects or processing for correcting the outline of an image by upconversion of display data or the like can be performed, for example. During the arithmetic processing with the accelerator 552, it is possible to reduce the power consumption by power gating control on the CPU 551.

(245) At least part of any of the structure examples, the drawings corresponding thereto, and the like described in this embodiment can be implemented in combination with any of the other structure examples, the other drawings corresponding thereto, and the like as appropriate.

Embodiment 3

(246) In this embodiment, a light-emitting element (light-emitting device) that can be used in the display device of one embodiment of the present invention will be described.

(247) In this specification and the like, a device fabricated using a metal mask or a fine metal mask (FMM, a high-resolution metal mask) is referred to as a device with a metal mask (MM) structure in some cases. Also in this specification and the like, a device fabricated without using a metal mask or an FMM is referred to as a device with a metal maskless (MML) structure in some cases.

(248) Note that in this specification and the like, a structure in which light-emitting layers of light-emitting devices of different colors (here, blue (B), green (G), and red (R)) are separately formed or are colored separately is referred to as a side-by-side (SBS) structure in some cases. Furthermore, in this specification and the like, a light-emitting device capable of emitting white light is referred to as a white light-emitting device in some cases. Note that a white light-emitting device that is combined with coloring layers (e.g., color filters) can be a light-emitting device of full-color display.

(249) Light-emitting devices can be roughly classified into a light-emitting device with a single structure and a light-emitting device with a tandem structure. A light-emitting device with a single structure includes one light-emitting unit between a pair of electrodes, and the light-emitting unit preferably includes one or more light-emitting layers. To obtain white light emission, two or more light-emitting layers need to be selected so as to emit light of complementary colors. When, for example, the emission colors of first and second light-emitting layers are made complementary, the light-emitting device as a whole can emit white light. The same applies to a light-emitting device including three or more light-emitting layers.

(250) A light-emitting device with a tandem structure includes two or more light-emitting units between a pair of electrode, and each light-emitting unit preferably includes one or more light-emitting layers. To obtain white light emission, the structure is made so that light from light-emitting layers of the light-emitting units can be combined to be white light. Note that the structure that provides white light emission is similar to that in the case of the above-described single structure. In the light-emitting device with a tandem structure, it is preferable that an intermediate layer such as a charge-generation layer be provided between the plurality of light-emitting units.

(251) A light-emitting device with an SBS structure can have lower power consumption than the white light-emitting device (with a single structure or a tandem structure). In order to reduce power consumption, it is preferable to use a light-emitting device with an SBS structure. Meanwhile, since the manufacturing process of the white light-emitting device is simpler than that of the light-emitting device with an SBS structure, the white light-emitting device is preferable to reduce the manufacturing cost or increase the manufacturing yield.

(252) <Structure Example of Light-Emitting Element **570**>

(253) An EL layer **686** included in the light-emitting element **570** can be formed of a plurality of layers such as a layer **4420**, a light-emitting layer **4411**, and a layer **4430**, as illustrated in FIG. **22A**. The layer **4420** can include, for example, a layer containing a substance with a high electron-injection property (an electron-injection layer) and a layer containing a substance with a high electron-transport property (an electron-transport layer). The light-emitting layer **4411** contains a light-emitting compound, for example. The layer **4430** can include, for example, a layer containing a substance with a high hole-injection property (a hole-injection layer) and a layer containing a substance with a high hole-transport property (a hole-transport layer).

(254) The structure including the layer **4420**, the light-emitting layer **4411**, and the layer **4430**, which is provided between a pair of electrodes, can function as a single light-emitting unit, and the structure in FIG. **22A** is referred to as a single structure in this specification.

(255) Note that the structure in which a plurality of light-emitting layers (light-emitting layers **4411**, **4412**, and **4413**) is provided between the layer **4420** and the layer **4430** as illustrated in FIG. **22B** is another variation of the single structure.

(256) The structure in which a plurality of light-emitting units (El layers **686a** and **686b**) is connected in series with an intermediate layer (charge-generation layer) **4440** therebetween as illustrated in FIG. **22C** is referred to as a tandem structure in this specification. In this specification and the like, the structure illustrated in FIG. **22C** is referred to as a tandem structure; however, without being limited to this, a tandem structure may be referred to as a stack structure, for example. The tandem structure enables a light-emitting element capable of high luminance light emission.

(257) The emission color of the light-emitting element **570** can be changed to red, green, blue, cyan, magenta, yellow, white, or the like depending on the material of the EL layer **686**. When the light-emitting element **570** has a microcavity structure, the color purity can be further increased.

(258) In the light-emitting element that emits white light, the light-emitting layer preferably contains two or more kinds of light-emitting substances. To obtain white light emission, the two or more kinds of light-emitting substances are selected so as to emit light of complementary colors. For example, the emission colors of first and second light-emitting layers are complementary, so that the light-emitting element can emit white light as a whole. This can be applied to a light-emitting element including three or more light-emitting layers.

(259) The light-emitting layer preferably contains two or more selected from light-emitting substances that emit light of red (R), green (G), blue (B), yellow (Y), orange (O), and the like. Alternatively, the light-emitting layer preferably contains two or more light-emitting substances that emit light containing two or more of spectral components of R, G, and B.

(260) <Method for Forming Light-Emitting Element **570**>

(261) A method for forming the light-emitting element **570** provided over the pixel circuit **562** is described below.

(262) FIG. **23A** illustrates a schematic top view of the display device of one embodiment of the present invention. The display portion **560** includes a plurality of light-emitting elements **570R** exhibiting red, a plurality of light-emitting elements **570G** exhibiting green, and a plurality of light-emitting elements **570B** exhibiting blue. In FIG. **23A**, light-emitting regions of the light-emitting elements are denoted by R, G, and B to easily differentiate the light-emitting elements. Note that the structure of the display portion **560** illustrated in FIG. **23A** may be referred to as an SBS

structure. Although the structure illustrated in FIG. 23A has three colors of red (R), green (G), and blue (B), one embodiment of the present invention is not limited thereto. For example, the structure may have four or more colors.

(263) The light-emitting elements **570R**, the light-emitting elements **570G**, and the light-emitting elements **570B** are arranged in a matrix. FIG. 23A shows what is called a stripe arrangement, in which the light-emitting elements with the same color are arranged in one direction. Note that the arrangement method of the light-emitting elements is not limited thereto; another method such as a delta, zigzag, or PenTile arrangement may also be used.

(264) As the light-emitting elements **570R**, **570G**, and **570B**, an organic EL device such as an organic light-emitting diode (OLED) or a quantum-dot light-emitting diode (QLED) is preferably used. As a light-emitting substance included in the EL element, a substance emitting fluorescence (a fluorescent material), a substance emitting phosphorescence (a phosphorescent material), a substance exhibiting thermally activated delayed fluorescence (a thermally activated delayed fluorescent (TADF) material), an inorganic compound (e.g., a quantum dot material), or the like can be used.

(265) FIG. 23B is a schematic cross-sectional view taken along dashed-dotted line A1-A2 in FIG. 23A.

(266) FIG. 23B shows a cross section of the light-emitting elements **570R**, **570G**, and **570B**. The light-emitting elements **570R**, **570G**, and **570B** are each provided over a substrate **351** and include a conductor **672** functioning a pixel electrode and a conductor **688** functioning a common electrode.

(267) The light-emitting element **570R** includes an EL layer **686R** between the conductor **672** and the conductor **688**. The EL layer **686R** includes a light-emitting organic compound that emits light with intensity at least in a red wavelength range. An EL layer **686G** of the light-emitting element **570G** includes a light-emitting organic compound that emits light with intensity at least in a green wavelength range. An EL layer **686B** of the light-emitting element **570B** includes a light-emitting organic compound that emits light with intensity at least in a blue wavelength range.

(268) The EL layer **686R**, the EL layer **686G**, and the EL layer **686B** may each include one or more of an electron-injection layer, an electron-transport layer, a hole-injection layer, and a hole-transport layer in addition to the layer containing a light-emitting organic compound (the light-emitting layer).

(269) The conductor **672** is provided for each of the light-emitting elements. The conductor **688** is provided as a common layer to the light-emitting elements. A conductive film that transmits visible light is used for either the conductor **672** or the conductor **688**, and a reflective conductive film is used for the other. The light-transmitting conductor **672** and the reflective conductor **688** offer a bottom-emission display device whereas the reflective conductor **672** and the light-transmitting conductor **688** offer a top-emission display device. Note that when both the conductor **672** and the conductor **688** transmit light, a dual-emission display device can be obtained.

(270) An insulating layer **372** is provided to cover end portions of the conductor **672**. End portions of the insulating layer **372** are preferably tapered.

(271) The EL layer **686R**, the EL layer **686G**, and the EL layer **686B** each include a region in contact with a top surface of the conductor **672** and a region in contact with a surface of the insulating layer **372**. End portions of the EL layer **686R**, the EL layer **686G**, and the EL layer **686B** are positioned over the insulating layer **372**.

(272) As shown in FIG. 23B, there is a gap between the EL layers of two light-emitting elements with different colors. The EL layer **686R**, the EL layer **686G**, and the EL layer **686B** are thus preferably provided so as not to be in contact with each other. This favorably prevents unintentional light emission (also referred to as crosstalk) from being caused by current flowing through two adjacent EL layers. As a result, the contrast can be increased to achieve a display device with high display quality.

(273) The EL layer **686R**, the EL layer **686G**, and the EL layer **686B** can be formed separately by a vacuum evaporation method or the like using a shadow mask such as a metal mask. These layers may be formed separately by a photolithography method. The use of the photolithography method achieves a display device with high resolution, which is difficult to obtain in the case of using a metal mask.

(274) A protective layer **371** is provided over the conductor **688** so as to cover the light-emitting elements **570R**, **570G**, and **570B**. The protective layer **371** has a function of preventing diffusion of impurities such as water into each light-emitting element from the above.

(275) The protective layer **371** can have, for example, a single-layer structure or a stacked-layer structure at least including an inorganic insulating film. Examples of the inorganic insulating film include an oxide film or a nitride film such as a silicon oxide film, a silicon oxynitride film, a silicon nitride oxide film, a silicon nitride film, an aluminum oxide film, an aluminum oxynitride film, or a hafnium oxide film. Alternatively, a semiconductor material such as indium gallium oxide or indium gallium zinc oxide may be used for the protective layer **371**. The protective layer **371** may be formed by an ALD method, a CVD method, or a sputtering method. Although the protective layer **371** includes an inorganic insulating film in this example, one embodiment of the present invention is not limited thereto. The protective layer **371** may have a stacked-layer structure of an inorganic insulating film and an organic insulating film, for example.

(276) FIG. **23C** illustrates an example different from the above.

(277) In FIG. **23C**, a light-emitting element **570W** emitting white light is provided. The light-emitting element **570W** includes an EL layer **686W** emitting white light between the conductor **672** and the conductor **688**.

(278) The EL layer **686W** can have, for example, a stacked structure of two or more layers that are selected so as to emit light of complementary colors. It is also possible to use a stacked EL layer in which a charge-generation layer is provided between light-emitting layers.

(279) FIG. **23C** shows three light-emitting elements **570W** side by side. A coloring layer **364R** is provided above the left light-emitting element **570W**. The coloring layer **364R** functions as a band path filter that transmits red light. Similarly, a coloring layer **364G** that transmits green light is provided above the middle light-emitting element **570W**, and a coloring layer **364B** that transmits blue light is provided above the right light-emitting element **570W**. This enables the display device to display color images.

(280) The EL layer **686W** and the conductor **688** are each separated between adjacent two light-emitting elements **570W**. This favorably prevents unintentional light emission from being caused by current flowing through the EL layers **686W** of adjacent two light-emitting elements **570W**. Particularly when the EL layer **686W** is a stacked EL element in which a charge-generation layer is provided between two light-emitting layers, the effect of crosstalk is more significant as the resolution increases, i.e., as the distance between adjacent pixels decreases, leading to lower contrast. Thus, the above structure can achieve a display device having high resolution and contrast.

(281) The EL layer **686W** and the conductor **688** are preferably separated by a photolithography method. This can reduce the distance between light-emitting elements, achieving a display device with higher aperture ratio than that is formed using, for example, a shadow mask such as a metal mask.

(282) Note that in the case of a bottom-emission light-emitting element, the coloring layers may be provided between the conductor **672** and the substrate **351**.

(283) The above is the description of the light-emitting elements.

(284) At least part of this embodiment can be implemented in appropriate combination with any of the other embodiments described in this specification.

Embodiment 4

(285) In this embodiment, structure examples of an electronic device for which the display device

of one embodiment of the present invention is used will be described.

(286) The display device and the display module of one embodiment of the present invention can be applied to a display portion of an electronic device or the like having a display function. Examples of such an electronic device include a digital camera, a digital video camera, a digital photo frame, a mobile phone, a portable game machine, a portable information terminal, and an audio reproducing device, in addition to electronic devices with a relatively large screen, such as a television device, a laptop personal computer, a monitor device, digital signage, a pachinko machine, and a game machine.

(287) In particular, the display device and the display module of one embodiment of the present invention can have a high resolution, and thus can be favorably used for an electronic device having a relatively small display portion. As the display device and the display module, a watch-type or bracelet-type information terminal device (wearable device); and a wearable device worn on a head, such as a device for VR such as a head mounted display and a glasses-type device for AR can be given, for example.

(288) FIG. 24A is a perspective view of an electronic device **700** that is of a glasses type. The electronic device **700** includes a pair of display panels **701**, a pair of housings **702**, a pair of optical members **703**, a pair of temples **704**, and the like.

(289) The electronic device **700** can project an image displayed on the display panel **701** onto a display region **706** of the optical member **703**. Since the optical members **703** have a light-transmitting property, a user can see images displayed on the display regions **706**, which are superimposed on transmission images seen through the optical members **703**. Thus, the electronic device **700** is an electronic device capable of AR display.

(290) The housing **702** includes a camera **705** capable of taking an image of what lies in front thereof. Although not illustrated, one of the housings **702** is provided with a wireless receiver or a connector to which a cable can be connected, whereby a video signal or the like can be supplied to the housing **702**. Furthermore, when the housing **702** is provided with an acceleration sensor such as a gyroscope sensor, the orientation of the user's head can be detected and an image corresponding to the orientation can be displayed on the display region **706**. Moreover, the housing **702** is preferably provided with a battery, in which case charging can be performed with or without a wire.

(291) Next, a method for projecting an image on the display region **706** of the electronic device **700** is described with reference to FIG. 24B. The display panel **701**, a lens **711**, and a reflective plate **712** are provided in the housing **702**. A reflective surface **713** functioning as a half mirror is provided in a portion corresponding to the display region **706** of the optical member **703**.

(292) Light **715** emitted from the display panel **701** passes through the lens **711** and is reflected by the reflective plate **712** to the optical member **703** side. In the optical member **703**, the light **715** is fully reflected repeatedly by end surfaces of the optical member **703** and reaches the reflective surface **713**, whereby an image is projected on the reflective surface **713**. Accordingly, the user can see both the light **715** reflected by the reflective surface **713** and transmitted light **716** transmitted through the optical member **703** (including the reflective surface **713**).

(293) FIGS. 24A and 24B show an example in which the reflective plate **712** and the reflective surface **713** each have a curved surface. This can increase optical design flexibility and reduce the thickness of the optical member **703**, compared to the case where they have flat surfaces. Note that the reflective plate **712** and the reflective surface **713** may be flat.

(294) The reflective plate **712** can use a component having a mirror surface, and preferably has high reflectivity. As the reflective surface **713**, a half mirror utilizing reflection of a metal film may be used, but the use of prism utilizing total reflection or the like can increase the transmittance of the transmitted light **716**.

(295) Here, the housing **702** preferably includes a mechanism for adjusting the distance or angle between the lens **711** and the display panel **701**. This enables focus adjustment and zooming in/out

of image. One or both of the lens **711** and the display panel **701** are preferably configured to be movable in the optical-axis direction, for example.

(296) The housing **702** preferably includes a mechanism capable of adjusting the angle of the reflective plate **712**. The position of the display region **706** where images are displayed can be changed by changing the angle of the reflective plate **712**. Thus, the display region **706** can be placed at the most appropriate position in accordance with the position of the user's eye.

(297) The display device or the display module of one embodiment of the present invention can be used for the display panel **701**. Thus, the electronic device **700** can perform display with extremely high resolution.

(298) FIGS. **25A** and **25B** illustrate perspective views of an electronic device **750** that is of a goggle-type. FIG. **25A** is a perspective view illustrating the front surface, the top surface, and the left side surface of the electronic device **750**, and FIG. **25B** is a perspective view illustrating the back surface, the bottom surface, and the right side surface of the electronic device **750**.

(299) The electronic device **750** includes a pair of display panels **751**, a housing **752**, a pair of temples **754**, a cushion **755**, a pair of lenses **756**, and the like. The pair of display panels **751** is positioned to be seen through the lenses **756** inside the housing **752**.

(300) The electronic device **750** is an electronic device for VR. A user wearing the electronic device **750** can see an image displayed on the display panel **751** through the lens **756**. Furthermore, when the pair of display panels **751** displays different images, three-dimensional display using parallax can be performed.

(301) An input terminal **757** and an output terminal **758** are provided on the back side of the housing **752**. To the input terminal **757**, a cable for supplying a video signal from a video output device or the like, power for charging a battery provided in the housing **752**, or the like can be connected. The output terminal **758** can function as, for example, an audio output terminal to which earphones, headphones, or the like can be connected. Note that in the case where audio data can be output by wireless communication or sound is output from an external video output device, the audio output terminal is not necessarily provided.

(302) In addition, the housing **752** preferably includes a mechanism by which the left and right positions of the lens **756** and the display panel **751** can be adjusted to the optimal positions in accordance with the position of the user's eye. In addition, the housing **752** preferably includes a mechanism for adjusting focus by changing the distance between the lens **756** and the display panel **751**.

(303) The display device or the display module of one embodiment of the present invention can be used for the display panel **751**. Thus, the electronic device **750** can perform display with extremely high resolution. This enables a user to feel high sense of immersion.

(304) The cushion **755** is a portion in contact with the user's face (forehead, cheek, or the like). The cushion **755** is in close contact with the user's face, so that light leakage can be prevented, which increases the sense of immersion. A soft material is preferably used for the cushion **755** so that the cushion **755** is in close contact with the face of the user wearing the electronic device **750**. For example, a material such as rubber, silicone rubber, urethane, or sponge can be used. Furthermore, when a sponge or the like whose surface is covered with cloth, leather (natural leather or synthetic leather), or the like is used, a gap is unlikely to be generated between the user's face and the cushion **755**, whereby light leakage can be suitably prevented. Furthermore, using such a material is preferable because it has a soft texture and the user does not feel cold when wearing the device in a cold season, for example. The member in contact with user's skin, such as the cushion **755** or the temple **754**, is preferably detachable because cleaning or replacement can be easily performed.

(305) At least part of this embodiment can be implemented in combination with any of the other embodiments described in this specification as appropriate.

Example

(306) In this example, a display device of one embodiment of the present invention was fabricated.

The display device 10F illustrated in FIG. 9A in Embodiment 1 can be referred to for a pixel of the fabricated display device. FIG. 13 can be referred to for cross sectional structures of a transistor and a display element of the fabricated display device.

(307) First, the electrical characteristics of the transistor used in the display device are described. FIG. 26 illustrates a schematic perspective view of the transistor. The fabricated transistor has a trench-gate self-aligned (TGSA) structure formed with an LSI process node, in which a top gate electrode is formed to cover a channel of an oxide semiconductor (OS). Therefore, electric-field controllability by the top gate electrode is improved, and thus the structure is suitable for miniaturization.

(308) The transistor is a transistor in which an oxide semiconductor is used as a semiconductor where a channel is formed (OS transistor). The measured transistor has a channel length of approximately 200 nm and a channel width of approximately 60 nm.

(309) FIG. 27A shows Id-Vg characteristics. FIG. 27A shows two Id-Vg characteristics at drain voltages of 0.1 V and 1.2 V. In spite of being minute, the transistor exhibited normally-off characteristics as shown in FIG. 27A and its off-state current was lower than or equal to the lower detection limit (1×10^{-12} A) of the measurement device.

(310) FIG. 27B shows Id-Vd characteristics. FIG. 27B shows four Id-Vd characteristics at gate voltages of 0.5 V, 1.0 V, 1.5 V, and 2.0 V. In spite of being minute, the transistor exhibited high saturation as shown in FIG. 27B.

(311) The fabricated display panel had a structure in which silicon transistors, OS transistors, and OLED elements were stacked. FIG. 28 is an optical micrograph of a chip at a stage after a formation step of the silicon transistors. It can be found that a source driver, a digital-to-analog converter (DAC), a scan driver, an interface (IF), and the like are provided in a display region denoted by dashed lines. With a monolithic structure in which the silicon transistors, the OS transistors, and the OLED elements are stacked in this manner, a frame area can be reduced.

(312) The specifications of the fabricated panel are described. The size of the display region was a diagonal of 0.51 inches, the resolution was 1920×1920 pixels, the pixel size was 4.8 μm, the pixel density was 5291 ppi, the aperture ratio was 23.8%, and a color method with white tandem OLEDs and color filters was used. The light-emitting elements were top-emission light-emitting elements.

(313) Since white tandem elements are used as OLED elements, high voltage is required as compared with the case of using single elements. OS transistors with high withstand voltage are used as transistors of pixels in the display device of this example, and therefore, favorable display is possible with the white tandem elements.

(314) FIG. 29 is a photograph of the display device displaying an image. As shown in FIG. 29, favorable display was performed. It was also confirmed that the display device was capable of duty driving.

(315) This application is based on Japanese Patent Application Serial No. 2020-214950 filed with Japan Patent Office on Dec. 24, 2020 and Japanese Patent Application Serial No. 2021-158140 filed with Japan Patent Office on Sep. 28, 2021, the entire contents of which are hereby incorporated by reference.

Claims

1. A display device comprising: a first transistor; a second transistor; a first wiring configured to be supplied with a source signal; a second wiring configured to be supplied with a gate signal; a third wiring configured to be supplied with a constant potential; and a pixel electrode, wherein one of a source and a drain of the first transistor is electrically connected to the first wiring, wherein a gate of the first transistor is electrically connected to the second wiring, wherein one of a source and a drain of the second transistor is electrically connected to the pixel electrode, wherein the other of the source and the drain of the second transistor is electrically connected to the third wiring,

- wherein the first wiring extends in a first direction, wherein the second wiring extends in a second direction, wherein the second direction is a direction intersecting the first direction, wherein the first wiring and the pixel electrode overlap each other with the third wiring therebetween, and wherein each of the first transistor and the second transistor comprises a semiconductor layer in which current flows in the same direction.
2. The display device according to claim 1, wherein each of the first transistor and the second transistor comprises a semiconductor layer in which current flows in the first direction.
 3. The display device according to claim 1, wherein each of the first transistor and the second transistor comprises a semiconductor layer in which current flows in the second direction.
 4. The display device according to claim 1, further comprising a plurality of dummy layers, wherein the first transistor comprises a semiconductor layer, wherein each of the plurality of dummy layers comprises a semiconductor material same as the semiconductor layer of the first transistor, wherein each of the plurality of dummy layers comprises a portion having substantially the same top surface shape as the semiconductor layer of the first transistor, and wherein the plurality of dummy layers and the semiconductor layer are arranged at a regular interval in the second direction.
 5. The display device according to claim 1, further comprising a plurality of dummy layers, wherein the first transistor comprises a semiconductor layer, wherein each of the plurality of dummy layers comprises a semiconductor material same as the semiconductor layer of the first transistor, wherein each of the plurality of dummy layers comprises a portion having substantially the same top surface shape as the semiconductor layer of the first transistor, and wherein the plurality of dummy layers and the semiconductor layer are arranged at a regular interval in the first direction.
 6. The display device according to claim 1, further comprising: a fourth wiring; a third transistor; and a fourth transistor, wherein one of a source and a drain of the third transistor is electrically connected to the fourth wiring, wherein the other of the source and the drain of the third transistor is electrically connected to a gate of the second transistor, wherein one of a source and a drain of the fourth transistor is electrically connected to the fourth wiring, wherein the other of the source and the drain of the fourth transistor is electrically connected to the pixel electrode, wherein the third wiring is supplied with a first potential, wherein the fourth wiring is supplied with a second potential, and wherein the second potential is lower than the first potential.
 7. The display device according to claim 1, further comprising a third transistor, wherein the third transistor comprises silicon in a channel formation region, wherein the first transistor comprises indium or zinc, or both indium and zinc in a channel formation region, and wherein each of the first transistor and the second transistor is positioned over the third transistor.
 8. The display device according to claim 1, wherein the third wiring has a top surface shape in a form of lattice, wherein the third wiring comprises a first portion extending in the first direction and a second portion extending in the second direction, and wherein the pixel electrode and the first wiring overlap each other with the first portion therebetween.
 9. The display device according to claim 1, further comprising a plurality of light-emitting regions, wherein one of the plurality of light-emitting regions is surrounded by six of the plurality of light-emitting regions in a plan view.
 10. The display device according to claim 9, wherein the one of the plurality of light-emitting regions has a hexagonal shape in the plan view, wherein each of two interior angles of the hexagonal shape is larger than 120° , wherein each of the other four interior angles of the hexagonal shape is smaller than 120° , and wherein the two interior angles are positioned at the opposite corners to each other.
 11. The display device according to claim 9, wherein the one of the plurality of light-emitting regions has a hexagonal shape in the plan view, and wherein each of two interior angles of the hexagonal shape is larger than 120° .

12. The display device according to claim 9, wherein the plurality of light-emitting regions comprises adjacent three light-emitting regions, and wherein the adjacent three light-emitting regions are positioned to be on vertices of an isosceles triangle.
13. A display module comprising: the display device according to claim 1; and a connector or an integrated circuit.
14. An electronic device comprising: the display module according to claim 13; and at least one of an antenna, a battery, a housing, a camera, a speaker, a microphone, a touch sensor and an operation button.
15. A display device comprising: a first wiring configured to be supplied with a source signal; a second wiring configured to be supplied with a gate signal; a third wiring configured to be supplied with a constant potential; and a pixel electrode, wherein the first wiring extends in a first direction, wherein the second wiring extends in a second direction, wherein the second direction is a direction intersecting the first direction, wherein the first wiring and the pixel electrode overlap each other with the third wiring therebetween, wherein the third wiring has a top surface shape in a form of lattice, wherein the third wiring comprises a first portion extending in the first direction and a second portion extending in the second direction, and wherein the pixel electrode and the first wiring overlap each other with the first portion therebetween.
16. The display device according to claim 15, further comprising a first transistor and a second transistor, wherein one of a source and a drain of the first transistor is electrically connected to the first wiring, wherein a gate of the first transistor is electrically connected to the second wiring, wherein one of a source and a drain of the second transistor is electrically connected to the pixel electrode, wherein the other of the source and the drain of the second transistor is electrically connected to the third wiring.
17. The display device according to claim 16, further comprising a plurality of dummy layers, wherein the first transistor comprises a semiconductor layer, wherein each of the plurality of dummy layers comprises a semiconductor material same as the semiconductor layer of the first transistor, wherein each of the plurality of dummy layers comprises a portion having substantially the same top surface shape as the semiconductor layer of the first transistor, and wherein the plurality of dummy layers and the semiconductor layer are arranged at a regular interval in the second direction.
18. A display module comprising: the display device according to claim 15; and a connector or an integrated circuit.
19. An electronic device comprising: the display module according to claim 18; and at least one of an antenna, a battery, a housing, a camera, a speaker, a microphone, a touch sensor and an operation button.
-