



(12) **United States Patent**
Rentzelos et al.

(10) **Patent No.: US 12,404,862 B2**
(45) **Date of Patent: Sep. 2, 2025**

(54) **CONTAINMENT FOR FLUID HANDLING DEVICES, SUCH AS PUMPS, AND RELATED DEVICES, APPARATUS, SYSTEMS, AND METHODS**

6,264,440 B1 * 7/2001 Klein F04D 29/047
417/365
6,293,772 B1 9/2001 Brown
6,997,688 B1 * 2/2006 Klein F04D 29/126
417/420
7,572,115 B2 8/2009 Klein
7,707,720 B2 5/2010 Klein
8,770,945 B2 7/2014 Ozaki
9,133,847 B2 9/2015 Hijikata
9,592,326 B2 3/2017 Takatani
10,036,389 B2 7/2018 Li
10,428,822 B1 10/2019 Wang
(Continued)

(71) Applicant: **FLOWSERVE PTE. LTD.**

(72) Inventors: **Nick Rentzelos**, Northbrook, IL (US);
Stephen Ide, Nazareth, PA (US); **Collin Perle**, Plainfield, IL (US)

(73) Assignee: **Flowserve Pte. Ltd.**, Singapore (SG)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

FOREIGN PATENT DOCUMENTS

CN 111089060 A 5/2020
CN 212028076 11/2020
(Continued)

(21) Appl. No.: **18/140,597**

(22) Filed: **Apr. 27, 2023**

OTHER PUBLICATIONS

(65) **Prior Publication Data**

US 2024/0360833 A1 Oct. 31, 2024

International Search Report and Written Opinion for PCT/IB2024054008, Jul. 23, 2024, 10 pages.

Primary Examiner — Connor J Tremarche

(74) *Attorney, Agent, or Firm* — BKRIP LLC

(51) **Int. Cl.**
F04D 25/02 (2006.01)

(52) **U.S. Cl.**
CPC **F04D 25/026** (2013.01)

(58) **Field of Classification Search**
CPC F04D 25/026
See application file for complete search history.

(57) **ABSTRACT**


Intermediate drives may provide containment for fluid handling devices, such as pumps. Such intermediate drivees may one or more utilize magnetic drives to provide static barriers for mechanical devices. A fluid handling assembly may include a fluid handling device comprising a housing, a housing cavity, a fluid inlet, and a fluid outlet. An intermediate drive may be positioned and configured to transmit energy from a motor to the fluid handling device while providing a secondary containment area that is separate from the primary containment area provided by the fluid handling device.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,722,664 A * 2/1988 Wissman F04D 29/026
415/197
5,525,039 A 6/1996 Sieghartner
5,856,719 A 1/1999 De Armas
6,135,728 A 10/2000 Klein
6,234,748 B1 5/2001 Brown

19 Claims, 4 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

10,704,810	B2	7/2020	Snell	
10,830,240	B2	11/2020	Eschner	
2004/0013546	A1	1/2004	Klein	
2007/0110595	A1 *	5/2007	Sato	 F04D 13/0633
				417/423.12
2015/0270768	A1 *	9/2015	Sinnerud	 F03B 11/006
				310/104
2021/0246901	A1	8/2021	Eschner	
2022/0178381	A1 *	6/2022	De Raeve	 F04D 1/06

FOREIGN PATENT DOCUMENTS

IT	PD20120320	A1	4/2014
JP	S62267591	A	11/1987

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4

1

CONTAINMENT FOR FLUID HANDLING DEVICES, SUCH AS PUMPS, AND RELATED DEVICES, APPARATUS, SYSTEMS, AND METHODS

TECHNICAL FIELD

The present disclosure relates generally to containment assemblies and systems for mechanical or fluid handling devices, such as pumps, and, more particularly, to intermediate drives providing containment (e.g., secondary containment) utilizing one or more magnetic drives to provide static barriers for fluid handling devices that, for example, may be utilized with hazardous fluids and related assemblies, systems, and methods.

BACKGROUND

Magnetic-drive centrifugal pumps may be used to pump fluids, such as caustic and/or hazardous liquids and/or gases. A magnetic-drive pump features a pump shaft separated from a drive shaft by a containment shell. The drive shaft is arranged to rotate with one magnetic assembly, which is magnetically coupled to another magnetic assembly. The magnetic assemblies cooperate to apply torque to the pump shaft or an impeller to pump a fluid contained by the containment shell.

Although many magnetic-drive centrifugal pumps are generally reliable, the containment shell may leak or burst from the presence of one or more of the following factors: exposure to excessive heat, exposure to excessive hydraulic pressure, exposure to extreme hydraulic transients, long-term exposure to caustic or corrosive fluids, lack of proper pump maintenance, exposure to excessive particulate matter, and/or exceeding other operating limitations of the pump. If the pumped fluid is caustic or corrosive, the pumped fluid may erode the interior of the containment shell such that the integrity of the containment shell is degraded over time. If the pump is not properly maintained, excessive radial bearing wear may lead to rubbing or scraping mechanical contact between the impeller and the containment shell that damages the fluid containing capacity of the containment shell. Further, if particles in the pumped fluid accumulate or lodge between the containment shell and the impeller, the containment shell may become scratched, eroded or pitted; and hence, more vulnerable to chemical attack from the pumped fluid.

Leakage of the pumped fluid from an improperly maintained, misused or abused pump may be associated with health and safety risks because the pumped fluid may be hazardous, caustic, flammable, or toxic, for instance.

BRIEF SUMMARY

In some aspects, the techniques described herein relate to a pump assembly including: a pump including a pump housing, a housing cavity, a fluid inlet, and a fluid outlet, the pump defining a primary containment area; an intermediate drive positioned and configured to transmit energy from a motor to the pump, the intermediate drive defining a secondary containment area separate from the primary containment area; a non-metallic first static barrier providing a static seal between the housing cavity of the pump and the secondary containment area; a non-metallic second static barrier providing a static seal between the secondary containment area and a surrounding environment; a first magnetic drive for providing a magnetic coupling across the first

2

static barrier; and a second magnetic drive for providing a magnetic coupling across the second static barrier.

In some aspects, the techniques described herein relate to a fluid handling assembly including: a fluid handling device including a housing defining a housing cavity, a fluid inlet, and a fluid outlet, the fluid handling device defining a primary containment area; and an intermediate drive positioned and configured to transmit energy from a motor to the fluid handling device, the intermediate drive defining a secondary containment area separate from the primary containment area, the intermediate drive including: a modular housing including a drive end housing, an output end housing, and a central housing; a coupling to the fluid handling device positioned at the output end housing; a static barrier positioned at the drive end housing providing a static seal between the secondary containment area and a surrounding environment; a magnetic drive for providing a magnetic coupling with the motor across the static barrier positioned at the drive end housing; and a drive shaft coupled between the magnetic drive and the coupling to the fluid handling device, the central housing for supporting and positioning the drive shaft in the central housing with one or more bearings.

In some aspects, the techniques described herein relate to an intermediate drive including: a drive housing having a first end portion configured to couple to a fluid handling device and a second end portion configured to couple to a motor; a static barrier coupled to the drive housing and defining a containment area within the drive housing that is sealed with one or more static seals separating the containment area from a surrounding environment when the drive housing is coupled to a fluid handling device; a rotor including magnets positioned adjacent to the static barrier of the intermediate drive to be driven by the motor; a drive coupling mechanically coupled to the rotor, the drive coupling configured to apply force supplied by the motor via the intermediate drive to the fluid handling device; a drive shaft coupled between the rotor and the drive coupling; and a cartridge positioned in the drive housing for supporting and positioning the drive shaft in the drive housing with one or more bearings.

In some aspects, the techniques described herein relate to an intermediate drive including: a drive housing having a first end configured to couple to a fluid handling device and a second end configured to couple to a motor; a static barrier coupled to the drive housing and defining a containment area within the drive housing that is sealed with one or more static seals separating the containment area from a surrounding environment when the drive housing is coupled to a fluid handling device; and a drive assembly including: a rotor positioned on a first end of the drive assembly, the rotor including magnets positioned adjacent to the static barrier of the intermediate drive to be driven by the motor; and a drive coupling coupled to the rotor and positioned on a first end of the rotor assembly, the drive coupling configured to apply force supplied by the motor via the intermediate drive to the fluid handling device, wherein the intermediate drive supports the drive assembly using only a single bearing or wherein the intermediate drive supports the drive assembly without the use of bearings.

In some aspects, the techniques described herein relate to a method of driving a fluid handling device with an intermediate drive including a statically sealed secondary containment area, the method including: indirectly driving a first rotor of the intermediate drive via magnetic force applied through a first non-metallic static barrier, the first non-metallic static barrier being coupled to a drive housing

3

of the intermediate drive and defining a secondary containment area within the drive housing that is sealed from a surrounding environment; transferring force applied to the first rotor to a second rotor; and indirectly driving the fluid handling device with the second rotor via magnetic force applied through a second non-metallic static barrier.

In some aspects, the techniques described herein relate to a pump assembly comprising: a pump comprising a pump housing, a housing cavity, a fluid inlet, and a fluid outlet; an intermediate drive positioned and configured to transmit energy from a motor to the pump, the secondary drive comprising a secondary containment area; a non-metallic primary static barrier providing a static seal between the housing cavity of the pump and the secondary containment area; a non-metallic secondary static barrier providing a static seal between the secondary containment area and a surrounding environment; a first magnetic drive providing a magnetic coupling across the primary static barrier; and a second magnetic drive providing a magnetic coupling across the secondary static barrier.

In some aspects, the techniques described herein relate to an intermediate drive comprising: a drive housing having a first end configured to couple to a pump and a second end configured to couple to a motor; a non-metallic static barrier coupled to the drive housing and defining a secondary containment area within the drive housing that is sealed completely with static seals separating the secondary containment area from a surrounding environment when the drive housing is coupled to a pump; a first rotor of a first magnetic drive comprising magnets positioned to fit adjacent a non-metallic static barrier of a pump; and a second rotor mechanically coupled to the first rotor, the second rotor comprising magnets positioned adjacent the non-metallic static barrier of the intermediate drive.

In some aspects, the techniques described herein relate to a method of providing a statically sealed secondary containment area for a mechanical device, the method comprising: providing an intermediate drive comprising: a drive housing having a first end configured to couple to the mechanical device and a second end configured to couple to a motor; a non-metallic static barrier coupled to the drive housing and defining a secondary containment area within the drive housing that is sealed completely with static seals separating the secondary containment area from a surrounding environment when the drive housing is coupled to the mechanical device; a first magnetic drive comprising magnets positioned to fit adjacent a non-metallic static barrier of the mechanical device; and a second rotor mechanically coupled to the first rotor, the second rotor comprising magnets positioned adjacent the non-metallic static barrier of the intermediate drive; and coupling the first end of the drive housing to the mechanical device.

BRIEF DESCRIPTION OF THE DRAWINGS

While the specification concludes with claims particularly pointing out and distinctly claiming what are regarded as embodiments of the present disclosure, various features and advantages of embodiments of the disclosure may be more readily ascertained from the following description of example embodiments of the disclosure when read in conjunction with the accompanying drawings, in which:

FIG. 1 is a cross-sectional view of a centrifugal pump assembly with a magnetically-driven centrifugal pump and a magnetically-driven intermediate drive providing secondary containment for the centrifugal pump coupled to a motor, according to an embodiment of the present disclosure.

4

FIG. 2 is a cross-sectional view of a magnetically-driven intermediate drive with secondary containment having sealed bearings, according to an additional embodiment of the present disclosure.

FIG. 3 illustrates a partial cross-sectional view of a centrifugal pump assembly with a magnetically-driven centrifugal pump and a magnetically-driven intermediate drive providing secondary containment having a single bearing, according to an additional embodiment of the present disclosure.

FIG. 4 illustrates a partial cross-sectional view of a centrifugal pump assembly with a magnetically-driven centrifugal pump and a magnetically-driven intermediate drive providing secondary containment having an intermediate rotor assembly that is not supported by any bearings, according to an additional embodiment of the present disclosure.

DETAILED DESCRIPTION

The illustrations presented herein are not meant to be actual views of any particular pump assembly, intermediate drive, or component thereof, but are merely idealized representations employed to describe illustrative embodiments. The drawings are not necessarily to scale. Elements common between figures may retain the same numerical designation.

As used herein, relational terms, such as “first,” “second,” “top,” “bottom,” etc., are generally used for clarity and convenience in understanding the disclosure and accompanying drawings and do not connote or depend on any specific preference, orientation, or order, except where the context clearly indicates otherwise.

As used herein, the term “and/or” means and includes any and all combinations of one or more of the associated listed items.

As used herein, the term “substantially,” “approximately,” or “about” in reference to a given parameter means and includes to a degree that one skilled in the art would understand that the given parameter, property, or condition is met with a small degree of variance, such as within acceptable manufacturing tolerances. For example, a parameter that is substantially met may be at least 90% met, at least 95% met, at least 99% met, or even 100% met.

As used herein, the term “fluid” may mean and include fluids of any type and composition. Fluids may take a liquid form, a gaseous form, or combinations thereof, and, in some instances, may include some solid material (e.g., particulates, debris, etc.).

As discussed above, leakage of the pumped fluid from an improperly maintained, misused or abused pump may be associated with health and safety risks because the pumped fluid may be hazardous, caustic, flammable, or toxic, for instance. Even if the probability of a leak of containment shell is relatively low, a need exists for a secondary containment scheme for containing the pumped fluid in the event the containment shell leaks or bursts for any reason. Embodiments of the present disclosure may provide such containment that is secondary to one or more sealing features at a fluid handling device, such as, for example, a pump (e.g., that defines a primary containment).

Some embodiments of the present disclosure include a methods and apparatus for transmitting mechanical energy (e.g., force), rotationally and/or linearly, from an energy source (e.g., a motor) through a system of one or more magnetic drive couplings (e.g., one coupling, two couplings, three couplings, or more) to an energy consuming device (e.g., a mechanical or fluid handling device, such as, for

example, a pump) through an intermediate drive structure or system. The intermediate drive may act to couple (e.g., and transfer one or more forces between) a first wet end of a system (e.g., a pump) with a dry end of the system (e.g., a motor) while providing additional sealing (e.g., a secondary seal) to a primary seal of the wet end of the pump (e.g., one or more seals on the pump). Such a configuration may provide additional isolation of the dry end (e.g., the motor and associate components and/or operators) from the wet end. For example, in the event of a breach in the primary containment area, the secondary containment may act to at least partially isolate (e.g., entirely isolate) the drive motor from exposure to the pumped fluid and/or gas.

While embodiments of the disclosure may be useful for many applications, it may be particularly useful in applications where a dangerous environment (e.g., hazardous fluids comprising liquids and/or gases) needs to be isolated from the atmosphere and/or a biological life sustaining environment and/or two separate mutually incompatible biological life sustaining environments.

Some embodiments may utilize two magnetic-drive couplings that may be arranged to transmit rotary motion, although linear motion is also disclosed. A first magnetic-drive coupling located at the energy consuming device may utilize a primary containment element (e.g., a shell including a non-metallic material) to isolate the dangerous atmosphere and allow the magnetic coupling to transmit motion through the sealed shell (e.g., to a component to be driven, such as, for example, a pump). A second magnetic-drive coupling located at the energy source may also utilize a containment element (e.g., another shell including a non-metallic material) to define a secondary containment area between the primary containment area of the dangerous environment and the isolated environment. The second magnetic-drive coupling also transmits motion from the energy source through the sealed shell to the primary magnetic drive. The two magnetic drives may be connected by intermediate mechanical componentry inside the secondary containment area to enable transmission of mechanical energy (e.g., force) from the energy source to the energy consuming device.

In some embodiments, the intermediate drive may include a magnetic coupling at the motor while being coupled (e.g., directly or indirectly coupled) to the pump or other energy consuming device (e.g., another fluid handling device, pressure exchanger, mixer, etc.). As above, the intermediate drive may include indirect magnetic coupling at either end. In additional embodiments, the intermediate drive may include an indirect magnetic coupling at the motor and a direct coupling at the pump or other energy consuming device (e.g., directly coupled to a shaft of the pump where the primary containment is achieved through one or more dynamic shaft seals).

In some embodiments, the magnetic coupling or couplings may assist in centering and/or self-aligning a drive shaft of the system.

In some embodiments, the primary and secondary containment elements may reduce or eliminate the need for dynamic sealing (e.g., shaft seals) in the components of the drive assembly and may enable to use of static seals (e.g., the use of only static seals) for at least partially isolating the intermediate drive from a surrounding environment. For example, the intermediate drive may not require shaft seals on an input side (e.g., dry side) of intermediate drive that interfaces with a motor or other drive device.

As discussed herein, the containment area or areas may refer to a portion, region, and/or volume of an element,

assembly, device, and/or system that is at least partially isolated from an adjacent region and/or environment.

In some embodiments, the secondary containment area may be designed to have the same pressure and temperature parameters of the primary containment area, thus creating an intermediate isolated secondary containment chamber. This secondary containment chamber may be monitored for leakage of the dangerous atmosphere from the primary containment area. Accordingly, the monitoring system may be designed to warn operators of a leak from the primary containment area to the secondary containment area so that emergency action can be taken.

One example application of embodiments of the present disclosure is to drive a centrifugal chemical pump that may be utilized to pump various types of hazardous chemicals. Embodiments may also be utilized to drive other energy consuming devices, such as stirrers, reactors, propulsion systems, drive systems, compressors, and/or any system requiring separation of a hazardous environment from a surrounding environment. Embodiments may also be utilized to drive linear actuated devices such as valves and/or displacement pumps used in hazardous environments.

Some embodiments may utilize one or more sealed intermediate bearing, or no intermediate bearings, to allow transmission of energy between the input and output of the intermediate drive (e.g., between two magnetic drives). This may be advantageous as no ancillary heat exchange systems are needed to control internal temperatures of the mechanism.

In some embodiments, the intermediate drive may include one or more modular features that enable the intermediate drive to work with multiple types of upstream and/or downstream components (e.g., drives, pumps, exchangers, mixers, etc.). For example, the intermediate drive may include multiple housing components that can be interchanged and/or removed to interface with different componentry. Further, internal components of the intermediate drive be interchanged and/or removed depending on the desired application.

In some embodiments, the intermediate drive may be used as a retrofit to an existing system. For example, the intermediate drive may be used as a field retrofittable secondary containment upgrade. When implemented in a retrofit for a fluid handling device, such as a pump, the retrofit may not require opening the wetted areas of the pump casing and exposing the pumped fluid to atmosphere.

FIG. 1 illustrates a cross-sectional view of a centrifugal pump assembly 100 with a magnetically-driven centrifugal pump 102 and a magnetically-driven intermediate drive 104 providing secondary containment for the centrifugal pump 102 coupled to a motor 108, according to an embodiment of the present disclosure. As above, in additional embodiments, the pump 102 may be driven by other components, such as, for example, a dynamically sealed shaft.

The centrifugal pump 102 may include a pump housing 116, an impeller 118 (e.g., comprising a composite plastic, such as a fiber reinforced polymer), and a pump shaft 120. The pump housing 116 may include a housing cavity 122 having a fluid inlet 124, and a fluid outlet 126. The pump housing 116 may be comprised of a plurality of sections that may be cast, molded, and/or otherwise formed and connected together with fasteners and/or adhesives. The pump housing 116, one or more portions of which provides a barrier for a primary containment area 128 (e.g., wetted areas), may be formed from a corrosion-resistant material (e.g., a stainless steel, a polymer, a fiber-reinforced polymer, a composite, a ceramic, and/or a reinforced ceramic), and/or

the housing cavity **122** may be lined with a corrosion-resistant material (e.g., a fluoropolymer coating, such as, for example, ethylene tetrafluoroethylene (ETFE) or another polymer coating).

One end of the pump shaft **120** may be coupled to a primary static barrier **130**, which may be formed of a non-metallic material, that provides a static seal of the housing cavity **122** at one end of the pump housing **116**. Such non-metallic material for the primary static barrier **130** (or other such barriers discussed herein) may include, for example, a reinforced polymer and/or ceramic (e.g., fiber reinforced), a composite material, a polymer, a ceramic, combinations thereof, etc.

An annular portion of the impeller **118** may be positioned over the pump shaft **120** and radial bearings **134** may be positioned between the annular portion of the impeller **118** and the pump shaft **120** to facilitate the rotation of the impeller **118** about the pump shaft **120**. The pump shaft **120** may be coupled to the intermediate drive **104** via an indirect or direct coupling (e.g., via a magnetic coupling or via a direct mechanical coupling to the pump shaft **120**). For example, the annular portion of the impeller **118** may include one or more magnets **136** (e.g., encapsulated magnets) at a location proximate to a first side of the primary static barrier **130** positioned and configured to interact with one or more corresponding magnet **140** (e.g., encapsulated magnets) of a rotor **142** of a first magnetic drive **144** of the intermediate drive **104**, the magnets **140** being located proximate to an opposing second side of the primary static barrier **130** the intermediate drive **104** is coupled to the centrifugal pump **102**.

In additional embodiments that include a direct coupling, the drive shaft **152** may be directly coupled to the pump shaft **120** (e.g., where one or more of the drive shaft **152** and/or the pump shaft **120** may include a dynamic seal).

The intermediate drive **104** may include a drive housing **150**, a drive shaft **152**, and a secondary static barrier **154**. As above, the secondary static barrier **154** may comprise a non-metallic material may include, for example, a reinforced polymer and/or ceramic (e.g., fiber reinforced), a composite material, a polymer, a ceramic, combinations thereof, etc.

The drive housing **150** may be comprised of a number of sections including an input end housing **156**, an output end housing **158**, and a central housing **160** that may be cast, molded, and/or otherwise formed and connected together with fasteners and/or adhesives. At least the output end housing **158** and the central housing **160** of the drive housing **150**, which provide a barrier for a secondary containment area **162**, may be formed from a corrosion-resistant material, and/or may be lined with a corrosion-resistant material.

As above, the various components of the drive housing **150** may be modular (e.g., replaceable, interchangeable, removable) to accommodate use with a range of different input and/or output components. For example, one or more of the input end housing **156**, the output end housing **158**, and/or the central housing **160** may be interchanged and/or removed to accommodate different size and/or configurations of an output component (e.g., the pump **102**) and/or an input component (e.g., the motor **108**).

In some embodiments, the central housing **160** may include modular components (e.g., cartridge **161**) that interface with the shaft **152** extending through the central housing **150**. For example, the cartridge **161** may support and position one or more radial bearings **168** that support the shaft **152**. In embodiments where open bearings are used, the cartridge **161** may enable the supply of lubricating fluid

to the bearings **168** (e.g., through openings formed in lateral or radial sides of the cartridge **161**).

In embodiments where a reduced number of bearings are implemented or omitted (e.g., such as those discussed below), the cartridge **161** and/or the entire central housing **150** may be removed. For example, as depicted in FIG. 1, the central housing **160** may house the one or more radial bearings **168** (e.g., along with the cartridge **161**, when implemented) to support a central portion of the drive shaft **152** as the drive shaft **152** extends between the input end housing **156** and the output end housing **158**. In additional embodiments, such as those discussed below with reference to FIGS. 3 and 4, the central housing **160** may be omitted where one or more bearings are posited at an interface between the input end housing **156** and the output end housing **158** or where bearings and a drive shaft are entirely omitted.

The drive shaft **152** may have an output end mechanically coupled with the rotor **142** of the first magnetic drive **144** and an opposing input end mechanically coupled with a first rotor **164** of a second magnetic drive **166**. For example, the rotor **142** of the first magnetic drive **144** and the first rotor **164** of the second magnetic drive **166** may each include a keyed connected along with a mechanical coupling (e.g., a set screw, a flanged or tapered connection, etc.).

The one or more radial bearings **168** may be positioned between the drive housing **150** and the drive shaft **152** to secure the drive shaft **152** and facilitate the rotation of the drive shaft **152** relative to the drive housing **150**. In some embodiments, one or more rotary shaft seals may also be located between the drive shaft **152** and the drive housing **150** which may provide a dynamic seal between regions of the drive housing **150**, such as, for example, between the output end housing **158** and the central housing **160** and between the central housing **160** and the input end housing **156**.

In some embodiments, each radial bearing **168** may be an open bearing, as shown in FIG. 1. Accordingly, a cavity of the central housing **160** may include a fluid (e.g., an oil bath), which may lubricate and cool each radial bearing **168**. The rotary shaft seals may prevent oil from leaking from the central housing **160** into the input end housing **156** and the output end housing **158**. In additional embodiments, sealed radial bearings may be utilized, as will be discussed further herein with reference to FIGS. 2 and 3.

In some embodiments, one or more of the housings **156**, **158**, **160** may hold a fluid (e.g., oil) for cooling portions of the drive system.

As shown in FIG. 1, the output end housing **158** may be coupled to the pump housing **116** such that the primary static barrier **130** provides a static seal between the housing cavity **122** of the centrifugal pump **102** and the secondary containment area **162** of the intermediate drive **104**. Likewise, the secondary static barrier **154**, which may also be formed of a non-metallic material, may be positioned within the drive housing such that the secondary static barrier **154** provides a static seal of the secondary containment area **162** of the intermediate drive, such as between the central housing **160** and the output end housing **158** of the drive housing **150**. Seals such as static elastomer seals **172** and/or sealing adhesives may provide static seals between components defining the volume of the secondary containment area **162**. Accordingly, the secondary containment area **162** may be sealed completely with static seals and without any dynamic seals separating the secondary containment area **162** from the surrounding environment or from the primary containment area **128**.

The first rotor **164** of the second magnetic drive **166** may include one or more magnet **174** (e.g., encapsulated magnets) at a location proximate to a first side of the secondary static barrier **154** positioned and configured to interact with one or more corresponding magnet **176** (e.g., encapsulated magnets) of a second rotor **178** of the second magnetic drive **166**, the magnets **176** being located proximate to an opposing second side of the secondary static barrier **154**.

The second rotor **178** may include a coupling **180** configured to couple the second rotor **178** to an output shaft **182** of the motor **108** (e.g., an electric motor). Additionally, the input end housing **158** may include a coupling **184** (e.g., a mounting flange) configured to couple to a housing **186** of the motor **108**.

Although the first magnetic drive **144** and the second magnetic drive **166** are shown having nested annular portions, additional embodiments of the present disclosure may include alternative geometries and arrangements. For example, embodiments may include one or more magnetic drive having rotors with opposing planar faces with magnets that interact across a planar portion of a static barrier. Additionally, the arrangement of the magnetic drives may be reversed. For example, rather than the annular portion of the first rotor **164** being nested within the annular portion of the second rotor **178**, the first rotor **164** may have an annular portion with a larger diameter than that of the second rotor **178** and the annular portion of the second rotor **178** may be nested within the annular portion of the first rotor **164** and the orientation of the secondary static barrier **154** may be flipped 180 degrees with respect to the drive housing **150**.

The drive housing **150** may include one or more mounting bracket **188** configured to facilitate mounting of the intermediate drive **104** to a structure, and one or more hoisting ring **190** configured to facilitate hoisting of the intermediate drive **104** for installation and/or removal. The drive housing **150** may additionally include one or more ancillary connection port **192** that may be utilized to connect sensors (e.g., sensors to detect a leak from the primary containment area **128** to the secondary containment area **162**), and/or other systems to the intermediate drive **104**. An ancillary connection port **192** may be sealed with a plug if unused.

In operation, the motor **108** may impart a torque on the output shaft **182** of the motor and cause the output shaft **182** to rotate. As the second rotor **178** of the second magnetic drive **166** is coupled to the output shaft **182**, the second rotor **178** may also be caused to rotate by the motor **108**. The magnets **176** of the second rotor **178** may interact with the magnets **174** of the first rotor **164** via a magnetic field extending through the secondary static barrier **154**, and when the second rotor **178** rotates a torque may be applied to the first rotor **164** via the magnetic field, which may cause the first rotor **164** to rotate.

As the first rotor **164** of the second magnetic drive **166** is mechanically coupled to the rotor **142** of the first magnetic drive **144** via the drive shaft **152**, the rotation of the first rotor **164** of the second magnetic drive **166** may cause the rotor **142** of the first magnetic drive **144** to rotate. The magnets **140** of the rotor **142** may interact with the magnets **136** of the impeller **118** via a magnetic field extending through the primary static barrier **130**, and when the rotor **142** rotates a torque may be applied to the impeller **118** via the magnetic field, which may cause the impeller **118** to rotate. The rotation of the impeller **118** may impart a centrifugal force to fluid in the housing cavity **122** of the centrifugal pump **102**, which may cause fluid to be drawn into the centrifugal pump **102** via the fluid inlet **124** and to exit via the fluid outlet **126**.

In some embodiments, because one or more of the primary static barrier **130** and the secondary static barrier **154** are made from a non-metallic material, the moving magnetic fields of the first magnetic drive **144** and the second magnetic drive **166**, respectively, may not cause the induction of eddy currents in the primary static barrier **130** or the secondary static barrier **154**, which may improve efficiency and reduce heat and stress.

Additionally, since the intermediate drive **104** includes a secondary containment area **162** that is completely statically sealed (e.g., completely statically sealed without any dynamic seals providing a barrier between the secondary containment area **162** and the surrounding environment or the primary containment area **128**), a leak occurring from the primary containment area **128** into the secondary containment area **162**, such as from a device failure, may be safely contained in the secondary containment area **162**. The presence of fluid from the primary containment area **128** in the secondary containment area **162** may be detected by a sensor and alert an operator so that remedial action may be taken. Accordingly, a failure of a seal between the primary containment area **128** and the secondary containment area **162** may be remedied without the leakage of fluid from the primary containment area **128** into the surrounding environment.

FIG. 2 illustrates a cross-sectional view of a magnetically-driven intermediate drive **200** with secondary containment having sealed bearings **210**, according to an additional embodiment of the present disclosure.

The intermediate drive **200** may be configured to connect to a mechanical device, such as a centrifugal pump substantially identical to the centrifugal pump **102** (see FIG. 1).

The intermediate drive **200** may include a drive housing **250**, a drive shaft **252**, and a static barrier **254** that may be formed of a non-metallic material. The housing of the intermediate drive **200** may be comprised of a plurality of sections including an output end housing **258**, and a central housing **260** that may be cast, molded, or otherwise formed, and connected with fasteners and/or adhesives. The central housing **260** may be configured to connect to an input end housing substantially identical to the input end housing **156** (see FIG. 1). The output end housing **258** and the central housing **260** of the drive housing **250**, may provide a barrier for a secondary containment area **262**, and may be formed from a corrosion-resistant material (e.g., a stainless steel, a polymer, a reinforced polymer, a composite, a ceramic, and/or a reinforced ceramic) and/or may be lined with a corrosion-resistant material.

The drive shaft **252** may have an output end mechanically coupled with a rotor **242** of a first magnetic drive and an opposing input end mechanically coupled with a rotor **264** of a second magnetic drive. One or more radial bearing **210** may be positioned between the drive housing **250** and the drive shaft **252** to secure the drive shaft **252** and facilitate the rotation of the drive shaft **252** relative to the drive housing **250**.

Each bearing **210** may be a sealed bearing such that grease may be sealed within each bearing **210** that lubricates each respective bearing **210** for the life of the bearing **210**, eliminating the need for an oil bath and its subsystems.

When the output end housing **258** is coupled to a mechanical device (such as a centrifugal pump) a primary static barrier of the mechanical device may provide a static seal between mechanical device and the secondary containment area **262** of the intermediate drive **200**. Likewise, a secondary static barrier **254**, which may be formed of a non-metallic material, coupled to the drive housing **250** may

11

provide a static seal of the secondary containment area **262** of the intermediate drive **200**. Accordingly, the secondary containment area **262** may be sealed completely with static seals and without any dynamic seals separating the secondary containment area **262** from the surrounding environment or from a primary containment area.

FIG. **3** illustrates a partial cross-sectional view of a centrifugal pump assembly **300** with a magnetically-driven centrifugal pump **302** and a magnetically-driven intermediate drive **304** providing secondary containment for the centrifugal pump **302** having a single bearing **310**, according to an additional embodiment of the present disclosure.

The intermediate drive **304** may be configured to connect to a mechanical device, such as a centrifugal pump **302**, which may be substantially identical to the centrifugal pump **102** described with reference to FIG. **1**. The centrifugal pump **302** may include a primary static barrier **330**, which may be formed of a non-metallic material, that provides a static seal of a primary containment area of the centrifugal pump **302**.

The intermediate drive **304** may include a drive housing **350**, a drive shaft **352**, and a secondary static barrier **354**. The drive housing **350** may be comprised of a plurality of sections including an input end housing **356**, an output end housing **358**, and a central housing **360** that may be cast, molded, or otherwise formed, and connected with fasteners and/or adhesives. At least the output end housing **358** and the central housing **360** of the drive housing **350**, which provide a barrier for a secondary containment area **362**, may be formed from a corrosion-resistant material (e.g., a stainless steel, a polymer, a reinforced polymer, a composite, a ceramic, and/or a reinforced ceramic), and/or may be lined with a corrosion-resistant material.

The drive shaft **352** may have an output end mechanically coupled with the rotor **342** of the first magnetic drive **344** and an opposing input end mechanically coupled with a first rotor **364** of a second magnetic drive **366**. The rotor **342** may include magnets **340** that may be positioned proximate the primary static barrier **330** positioned and configured to interact with magnets of an impeller of the centrifugal pump **302**.

The drive housing **350** and the drive shaft **352** may be relatively short, such as in comparison to the drive housing **150** and drive shaft **152** described with reference to FIG. **1**. Accordingly, a single radial bearing **310** may be positioned between the drive housing **350** and the drive shaft **352** to secure the drive shaft **352** and facilitate the rotation of the drive shaft **352** relative to the drive housing **350**. The bearing **310** may be a sealed bearing such that grease may be sealed within the bearing **310** that lubricates the bearing **310** for the life of the bearing **310**. In some embodiments, the bearing **310** may be supported and positioned by a portion of the central housing **360** of the drive housing **350** (e.g., a laterally or radially extending structure of the central housing **360**).

The output end housing **358** may be coupled to the centrifugal pump **302** such that the primary static barrier **330** provides a static seal between the primary containment area of the centrifugal pump **302** and the secondary containment area **362** of the intermediate drive **304**. Likewise, a secondary static barrier **354**, which may be formed of a non-metallic material, may be positioned within the drive housing **350** such that the secondary static barrier **354** provides a static seal of the secondary containment area **362** of the intermediate drive **304**, such as between the central housing **360** and the output end housing **358** of the drive housing **350**. Seals such as static elastomer seals **372** and/or sealing adhesives may provide static seals between components

12

defining the volume of the secondary containment area **362**. Accordingly, the secondary containment area **362** may be sealed completely with static seals and without any dynamic seals separating the secondary containment area **362** from the surrounding environment or from the primary containment area of the centrifugal pump **302** (e.g., provided, in part, with the primary static barrier **330**).

The first rotor **364** of the second magnetic drive **366** may include magnets **374** at a location proximate to a first side of the secondary static barrier **354** positioned and configured to interact with corresponding magnets **378** of a second rotor **376** of the second magnetic drive **366**, the magnets **374** being located proximate to an opposing second side of the secondary static barrier **354**.

The second rotor **376** may include a coupling **380** configured to couple the second rotor **376** to an output shaft of a motor (e.g., an electric motor). Additionally, the input end housing **358** may include a coupling **384** (e.g., a mounting flange) configured to couple to a housing of a motor.

FIG. **4** illustrates a partial cross-sectional view of a centrifugal pump assembly **400** with a magnetically-driven centrifugal pump **402** and a magnetically-driven intermediate drive **404** providing secondary containment having an intermediate rotor or drive assembly **406** that is not supported by any bearings, according to an additional embodiment of the present disclosure.

The intermediate drive **404** may be configured to connect to a mechanical device, such as the centrifugal pump **402**, which may be substantially identical to the centrifugal pump **102** described with reference to FIG. **1**. The centrifugal pump **402** may include a primary static barrier **430**, which may be formed of a non-metallic material, that provides a static seal of a primary containment area of the pump **402**.

Similar to the intermediate drive **304**, the intermediate drive **404** may include a drive housing **450** and a secondary static barrier **454**. Rather than utilizing a drive shaft, however, a rotor **442** of a first magnetic drive **444** and a first rotor **464** of a second magnetic drive **466** may be mechanically coupled directly together without a drive shaft to form the intermediate rotor assembly **406**. Accordingly, the intermediate drive **404** may be relatively compact and have relatively few moving parts.

The rotor **442** of the first magnetic drive **444** may include magnets **440** positioned to interact with magnets of a rotor of the centrifugal pump **402** across the primary static barrier **430**. Likewise, the first rotor **464** of the second magnetic drive **466** may include magnets **474** that are positioned to interact with magnets **476** of a second rotor **478** of the second magnetic drive **466** across the secondary static barrier **454**. The interaction of the magnets **440** and the magnets of the centrifugal pump of the first magnetic drive **444** and the interaction of the magnets **474** and **476** of the second magnetic drive **466** may be positioned and configured to create a magnetic field that levitates the intermediate rotor assembly **406** within the drive housing **450** (e.g., substantially centers or self-aligns the intermediate rotor assembly **406** about an axis of rotational and/or linear movement), such that no bearings are needed to secure the intermediate rotor assembly **406** within the intermediate drive **404**.

Components of the intermediate drive **404**, such the rotors **442** and **464** of the intermediate rotor assembly **406** may be injection molded. Injection molding may facilitate the molding of components around the magnets. Additionally, injection molding of components of the intermediate rotor assembly **406** may allow for the intermediate rotor assembly **406** to be lightweight and precisely balanced, which may be

13

important since the intermediate rotor assembly **406** will be supported solely by the magnetic fields of the first magnetic drive **444** and the second magnetic drive **466**.

The remaining components of the intermediate drive **404** may be substantially identical to those of the intermediate drive **304** described with reference to FIG. 3.

Accordingly, although embodiments of the present disclosure may be described herein with reference to pumps, such as centrifugal pumps, it will be understood that additional mechanical devices, such as stirrers, reactors, propulsion systems, compressors, and/or drive systems may be utilized in conjunction with intermediate drive assemblies with secondary containment according to additional embodiments of the present disclosure.

Additionally, although embodiments of the present disclosure may be described with reference to motors as an energy source, such as electric motors, it will be understood that additional energy sources, including rotational energy sources and linear energy sources may be utilized in additional embodiments of the present disclosure.

Further, while embodiments of the present disclosure may be described with reference to pumping and/or processing hazardous fluids, embodiments of the present disclosure may be utilized for any number of additional applications or fluid handling devices/systems, such as marine propulsion systems (e.g., for deep sea underwater manned vehicles where leak detection and secondary leak containment would be desired), outer space applications (e.g., where protection of human life from loss of internal atmospheric conditions would be critical), energy recovery pump applications, actuators, medical devices, and/or consumer products (e.g., aquarium pumps, mixers, etc.).

While the present disclosure has been described herein with respect to certain illustrated embodiments, those of ordinary skill in the art will recognize and appreciate that it is not so limited. Rather, many additions, deletions, and modifications to the illustrated embodiments may be made without departing from the scope of the disclosure as hereinafter claimed, including legal equivalents thereof. In addition, features from one embodiment may be combined with features of another embodiment while still being encompassed within the scope of the disclosure as contemplated by the inventor.

What is claimed is:

1. A pump assembly comprising:

a pump comprising a pump housing, a housing cavity, a fluid inlet, and a fluid outlet, the pump defining a primary containment area;

an intermediate drive positioned and configured to transmit energy from a motor to the pump, the intermediate drive defining a secondary containment area separate from the primary containment area, the intermediate drive comprising a modular drive housing including an output end housing and a central housing;

a non-metallic first static barrier providing a static seal between the housing cavity of the pump and the secondary containment area, the first static barrier being positioned at least partially within the output end housing;

a non-metallic second static barrier providing a static seal between the secondary containment area and a surrounding environment, the second static barrier extending at least partially from the central housing;

a first magnetic drive for providing a magnetic coupling across the first static barrier;

a second magnetic drive for providing a magnetic coupling across the second static barrier; and

14

a drive shaft having an output end mechanically coupled to a rotor of the first magnetic drive and an opposing input end mechanically coupled to a rotor of the second magnetic drive, the drive shaft housed in the central housing with one or more radial bearings for supporting the drive shaft,

wherein the central housing includes a modular cartridge positioned in the central housing, the modular housing configured to enable supply of lubricating fluid to the one or more radial bearings, and

wherein the central housing and the drive shaft are configured to be removed from the intermediate drive such that the rotor of the first magnetic drive is directly coupled to the rotor of the second magnetic drive.

2. The pump assembly of claim 1, wherein at least one of the non-metallic first static barrier or the non-metallic second static barrier comprises at least one of a polymer, a reinforced polymer, a composite, a ceramic, or a reinforced ceramic.

3. The pump assembly of claim 1, wherein the modular cartridge is configured to enable supply of the lubricating fluid through openings formed in lateral or radial sides of the modular cartridge, the openings enabling communication between the modular cartridge and the central housing during use of the pump assembly.

4. The pump assembly of claim 1, wherein the central housing includes a removable, modular cartridge for supporting and positioning the one or more radial bearings and the drive shaft.

5. The pump assembly of claim 1, wherein each radial bearing of the one or more radial bearings is a sealed radial bearing.

6. The pump assembly of claim 1, wherein the drive shaft of the intermediate drive is supported by the one or more radial bearings comprising a single radial bearing, the single radial bearing supported and positioned by a portion of the central housing.

7. The pump assembly of claim 1, wherein one or more interior surfaces of the pump comprise a polymer coating.

8. The pump assembly of claim 1, wherein the rotor of the first magnetic drive is mechanically coupled to the rotor of the second magnetic drive to form an intermediate rotor assembly which is not supported by any bearings when the central housing is removed from the intermediate drive.

9. The pump assembly of claim 8, wherein the intermediate rotor assembly magnetically levitates.

10. The pump assembly of claim 1, wherein a portion of a housing of the intermediate drive that provides a barrier for the secondary containment area is formed from a corrosion-resistant material.

11. A method of driving a fluid handling device with the intermediate drive of claim 1 including the secondary containment area, the method comprising:

indirectly driving the rotor of the first magnetic drive via magnetic force applied through the non-metallic first static barrier;

transferring force applied to the rotor of the first magnetic drive to a second rotor; and

indirectly driving the fluid handling device with the rotor of the second magnetic drive via magnetic force applied through the non-metallic second static barrier.

12. The pump assembly of claim 1, wherein the modular drive housing further comprises a drive input end housing coupled to a portion of the pump.

15

13. A pump assembly comprising:
- a pump comprising a pump housing, a housing cavity, a fluid inlet, and a fluid outlet, the pump defining a primary containment area;
 - an intermediate drive positioned and configured to transmit energy from a motor to the pump, the intermediate drive defining a secondary containment area separate from the primary containment area, the intermediate drive comprising a modular drive housing including an output end housing and a central housing;
 - a non-metallic first static barrier providing a static seal between the housing cavity of the pump and the secondary containment area, the first static barrier being positioned at least partially within the output end housing;
 - a non-metallic second static barrier providing a static seal between the secondary containment area and a surrounding environment;
 - a first magnetic drive for providing a magnetic coupling across the first static barrier;
 - a second magnetic drive for providing a magnetic coupling across the second static barrier; and
 - a drive shaft having an output end mechanically coupled to a rotor of the first magnetic drive and an opposing input end mechanically coupled to a rotor of the second magnetic drive, the drive shaft housed in the central housing, wherein the central housing is configured to be removed from the intermediate drive such that the intermediate drive lacks one or more bearings housed in the central housing.
14. The pump assembly of claim 13, wherein the intermediate drive lacks the drive shaft when the central housing is removed from the intermediate drive.
15. The pump assembly of claim 13, wherein the intermediate drive comprises the drive shaft supported by the one or more bearings comprising a single radial bearing.
16. The pump assembly of claim 13, wherein the modular drive housing further comprises a drive input end housing coupled to a portion of the pump.
17. The pump assembly of claim 13, wherein the rotor of the first magnetic drive is configured to be directly coupled to the rotor of the second magnetic drive when the central housing is removed from the intermediate drive.
18. A pump assembly comprising:
- a pump comprising a pump housing, a housing cavity, a fluid inlet, and a fluid outlet, the pump defining a primary containment area; and
 - an intermediate drive comprising:
 - a modular housing including a drive end housing, an output end housing, and a central housing, the output end housing coupled to the pump and the drive end housing configured to couple to a motor;

16

- a static barrier coupled to the drive end housing and defining a containment area within the modular housing that is sealed with one or more static seals separating the containment area from a surrounding environment;
 - a rotor comprising magnets positioned adjacent to the static barrier of the intermediate drive to be driven by the motor;
 - a drive coupling mechanically coupled to the rotor, the drive coupling configured to apply force supplied by the motor via the intermediate drive to the pump;
 - a drive shaft coupled between the rotor and the drive coupling; and
 - a cartridge positioned in the central housing for supporting and positioning the drive shaft in the modular housing with one or more bearings, at least one of the central housing, the cartridge, the drive shaft, or the one or more bearings configured to be removed from the modular housing in order to reconfigure the intermediate drive for use with multiple pumps and/or motors, wherein the modular housing and the cartridge are configured to enable supply of lubricating fluid to the one or more bearings.
19. A pump assembly comprising:
- a pump comprising a pump housing, a housing cavity, a fluid inlet, and a fluid outlet, the pump defining a primary containment area; and
 - an intermediate drive comprising:
 - a drive housing having a first end configured to couple to a fluid handling device and a second end configured to couple to a motor;
 - a static barrier coupled to the drive housing and defining a containment area within the drive housing that is sealed with one or more static seals separating the containment area from a surrounding environment when the drive housing is coupled to a fluid handling device; and
 - a drive assembly comprising:
 - a rotor comprising magnets positioned adjacent to the static barrier of the intermediate drive to be driven by the motor; and
 - a drive coupling coupled to the rotor, the drive coupling configured to apply force supplied by the motor via the intermediate drive to the pump, wherein the intermediate drive is modular such that, in a first configuration, the intermediate drive is configured to support the drive assembly using only a single bearing and, in a second configuration, the intermediate drive is configured to support the drive assembly without use of bearings.

* * * * *