

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12404966
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Xu; Hao et al.

Display mounting support

Abstract

The present disclosure provides a display mounting support including a wall plate and at least one hanging assembly. The wall plate defines a hanging hook groove. The hanging assembly is hung into the hanging hook groove. Each hanging assembly includes a hanging hook member, a retractable mechanism and a display hanging member. The hanging hook member includes a hanging rod, a connecting rod and a hanging hook. The connecting rod is connected between the hanging rod and the hanging hook. The hanging hook includes a cantilever portion and a first concave structure. The retractable mechanism is connected between the hanging rod and the display hanging member. The display hanging member is configured to fix to a back of a display. The hanging hook of the hanging assembly is inserted into the hanging hook groove for hanging the display on the wall plate.

Inventors:	Xu; Hao (Hong Kong, CN), Wu; Linghui (Hong Kong, CN)
Applicant:	Xinadda (Hong Kong) Limited (Hong Kong, CN)
Family ID:	90708468
Assignee:	Xinadda (Hong Kong) Limited (Hong Kong, CN)
Appl. No.:	18/531161
Filed:	December 06, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20250067384 A1	Feb. 27, 2025

Foreign Application Priority Data

CN	202322303828.1	Aug. 26, 2023
----	----------------	---------------

Publication Classification

Int. Cl.: F16M11/04 (20060101); F16M11/10 (20060101)

U.S. Cl.:

CPC F16M11/048 (20130101); F16M11/046 (20130101); F16M11/10 (20130101);

Field of Classification Search

CPC: F16M (11/048); F16M (11/046); F16M (11/10)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
8322673	12/2011	Sculler	248/917	F16M 13/02
8456808	12/2012	Grey	361/679.01	F16M 11/10
10159345	12/2017	Hung	N/A	F16M 11/2085
2019/0017653	12/2018	Stifal	N/A	F16M 11/10
2020/0208774	12/2019	Pei	N/A	H05K 5/0204
2023/0184375	12/2022	Kolz	312/7.2	F16M 11/2014

Primary Examiner: McKinnon; Terrell L

Assistant Examiner: Tan; Ding Y

Attorney, Agent or Firm: IP Spring

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

(1) This application claims priority under 35 U.S.C. § 119 (a) to Chinese Patent Application No. 202322303828.1, filed Aug. 26, 2023, the entire disclosure of which is incorporated herein by reference.

TECHNICAL FIELD

(2) The present disclosure relates to technical fields of display mounting, and in particular relates to a display mounting support.

BACKGROUND

(3) Electronic devices such as flat panel televisions, displays and so on have been widely used due to their advantages such as high definition, large screen, light weight, and so on. In the prior art, flat panel televisions or displays are generally mounted on a wall using a wall mount, thereby saving space in a house. In order to adapt to different use scenarios, the existing display mounting support can also realize an adjustment for left-right rotation angle, specifically: the hanging hook of the display mounting support is widened in a front to back direction, so as to adjust a rotation angle of the display in a left-right direction. However, this method results in a large gap between the hanging hook and the wall plate of the display mounting support, which is easy to wobble, and the

use experience is reduced in quality.

SUMMARY

(4) For this purpose, the present disclosure proposes a display mounting support to solve at least one of the above mentioned technical problems.

(5) In order to solve the above mentioned technical problems, the technical solutions of the present disclosure are as follows.

(6) In a first aspect, the present disclosure provides a display mounting support including a wall plate and at least one hanging assembly. The wall plate includes a wall frame and a first guiding bar. The wall frame is configured to be mounted on a wall surface. The wall frame and the first guiding bar are connected to form a hanging hook groove. The hanging hook groove extends along a left-right direction of the display mounting support. The hanging assembly is hung into the hanging hook groove of the wall plate. Each hanging assembly includes a hanging hook member, a retractable mechanism and a display hanging member. The hanging hook member includes a hanging rod, a connecting rod and a hanging hook. The connecting rod is connected between one end of the hanging rod and one side of the hanging hook. The hanging hook includes a cantilever portion and a first concave structure. The cantilever portion is connected to one end of the connecting rod away from the hanging rod and towards the wall plate. The first concave structure includes a first plate portion and a second plate portion. The first plate portion and the second plate portion are disposed side by side on one side of the cantilever portion facing the wall plate and extending towards the hanging rod. Adjacent edges of the first plate portion and the second plate portion intersect with each other. The first concave structure is recessed when viewed from the wall plate. The retractable mechanism is connected between the hanging rod and the display hanging member. The display hanging member is configured to fix to a predetermined position on a back of a display. The hanging hook is inserted into the hanging hook groove for hanging the display on the wall plate.

(7) In combination with the first aspect, in some embodiments of the present disclosure, the connecting rod is hollow and open on a side facing the wall plate to form a receiving groove. The hanging hook member further includes a first supporting member. The first supporting member is received in the receiving groove. The first supporting member includes a first convex structure on a side facing the hanging hook. The first convex structure includes a third plate portion and a fourth plate portion. The third plate portion is adjacent to the first plate portion. The fourth plate portion is adjacent the second plate portion. Adjacent edges of the third plate portion and the fourth plate portion intersect with each other. The first convex structure is protruded when viewed from the wall plate. A minimum distance between the first convex structure and the first concave structure is greater than or equal to a thickness of the first guiding bar.

(8) In combination with the first aspect, in some embodiments of the present disclosure, the third plate portion and the second plate portion are parallel, and a distance between planes where each of the third plate portion and the second plate portion is located is greater than or equal to a thickness of the first guiding bar. The first plate portion and the fourth plate portion are parallel, and a distance between planes where each of the first plate portion and the fourth plate portion is located is greater than or equal to the thickness of the first guiding bar.

(9) In combination with the first aspect, in some embodiments of the present disclosure, the first concave structure is a V-shaped structure, and the first convex structure is correspondingly also a V-shaped structure.

(10) In combination with the first aspect, in some embodiments of the present disclosure, the first supporting member further includes a protruding portion. The protruding portion including a fifth plate portion and a sixth plate portion. Adjacent edges of the fifth plate portion and the sixth plate portion intersect with each other. The fifth plate portion is adjacent to and parallel to the first plate portion. The sixth plate portion is adjacent to and parallel to the second plate portion. When the first supporting member is received in the receiving groove, the fifth plate portion resists against

inside of the first plate portion, and the sixth plate portion resists against inside of the second plate portion.

(11) In combination with the first aspect, in some embodiments of the present disclosure, the wall plate further includes a second guiding bar, the wall frame and the second guiding bar are connected to form a locking hook groove. The locking hook groove extends along a left-right direction of the display mounting support. Opening of the locking hook groove and opening of the hanging hook groove are set back to back. The hanging assembly further includes a pull cord assembly. The pull cord assembly is connected to the other end of the hanging rod. The pull cord assembly includes a locking hook. The locking hook includes two cantilevers and a second concave structure. The second concave structure is connected between the two cantilevers. The second concave structure includes a seventh plate portion and an eighth plate portion. Adjacent edges of the seventh plate portion and the eighth plate portion intersect with each other. The second concave structure is recessed when viewed from the wall plate. The locking hook of the hanging assembly is inserted into the locking hook groove for locking the hanging assembly on the wall plate.

(12) In combination with the first aspect, in some embodiments of the present disclosure, the hanging rod is hollow inside, and, the other end of the hanging rod on the side facing the wall plate defines an opening. The pull cord assembly further includes a locking member, a shaft, a tension spring and a pull rope. The locking member is received inside the other end of the hanging rod and is partially exposed from the opening. The locking member includes a bottom wall, a first sidewall, a second sidewall and a locking hook. The first sidewall and the second sidewall are located opposite to each other. The locking hook is connected to sides of the first sidewall and the second sidewall adjacent the wall plate. The bottom wall is connected to bottom ends of the first sidewall, the second sidewall and the locking hook simultaneously. At least one of the first sidewall and the second sidewall defines a first limiting groove extending along a height direction of the display mounting support. The hanging rod defines a shaft hole correspondingly. The shaft passes through the first limiting groove and is fixed in the shaft hole. The tension spring is located in the locking member. One end of the tension spring is connected to the shaft, and the other end of the tension spring is fixed to the bottom wall of the locking member. The pull rope is located outside of the locking member, and is fixed to the bottom wall of the locking member.

(13) In combination with the first aspect, in some embodiments of the present disclosure, the pull cord assembly further includes a second supporting member. The second supporting member is located within the locking member. The second supporting member includes a second convex structure on a side of the second supporting member facing the locking hook. The second convex structure includes a ninth plate portion and a tenth plate portion. The ninth plate portion is adjacent to the seventh plate portion. The tenth plate portion is adjacent to the eighth plate portion. Adjacent edges of the ninth plate portion and the tenth plate portion intersect with each other. The second convex structure is protruded when being viewed from the wall plate. A minimum distance between the second convex structure and the second concave structure is greater than or equal to a thickness of the second guiding bar.

(14) In combination with the first aspect, in some embodiments of the present disclosure, the seventh plate portion and the tenth plate portion are parallel: a distance between planes where each of the seventh plate portion and the tenth plate portion is located is greater than or equal to a thickness of the second guiding bar: the eighth plate portion and the ninth plate portion are parallel, and a distance between planes where each of the eighth plate portion and the ninth plate portion is located is greater than or equal to the thickness of the second guiding bar.

(15) In combination with the first aspect, in some embodiments of the present disclosure, the second concave structure is a V-shaped structure, and the second convex structure is correspondingly also a V-shaped structure.

(16) In combination with the first aspect, in some embodiments of the present disclosure, the display mounting support further includes a height adjusting mechanism. The height adjusting

mechanism includes a first height adjusting member, a second height adjusting member, and a height adjusting bolt. The first height adjusting member is located within the receiving groove of the connecting rod and passes through the first supporting member. The second height adjusting member is located with the hanging rod. The first height adjusting member is connected with the second height adjusting member. The first height adjusting member defines a first bolt hole at a top of the first height adjusting member. A top plate of the connecting rod defines a second bolt hole. The height adjusting bolt passes through the first bolt hole and the second bolt hole so as to connect the first height adjusting member with the top plate of the connecting rod. The height adjusting bolt adjusts a relative position of the first height adjusting member and the second height adjusting member within the hanging hook member. The second height adjusting member is connected to the retractable mechanism.

(17) In combination with the first aspect, in some embodiments of the present disclosure, the retractable mechanism includes a first gear arm, a second gear arm, a third gear arm and a fourth gear arm. The first gear arm, the second gear arm, the third gear arm and the fourth gear arm are connected in a quadrilateral structure. Ends of the first gear arm and the second gear arm are connected by gear meshing and simultaneously pivotally connected to the hanging member. Ends of the third gear arm and the fourth gear arm are connected by gear meshing and simultaneously pivotally connected to the display hanging member. The first gear arm is pivotally connected to the third gear arm, and the second gear arm is pivotally connected to the fourth gear arm.

(18) In combination with the first aspect, in some embodiments of the present disclosure, the display mounting support further includes a tilt adjusting mechanism. The tilt adjusting mechanism includes a mounting member and an adjusting handle. The mounting member is secured to the hanging hook member. The mounting member includes a screw located on a sidewall thereof. The display hanging member further includes a lug portion located on a sidewall thereof. The lug portion defines an arcuate groove. The screw passes through the arcuate groove. The adjusting handle is threadedly connected with the screw. When the screw is located at different positions of the arcuate groove, the display hanging member has different front-to-rear tilting angles relative to the mounting member.

(19) A second aspect of the present disclosure provides a display mounting support including a wall plate and at least one hanging assembly. The wall plate including a wall frame and a first guiding bar. The wall frame is configured for fixing to a wall surface. The wall frame and the first guiding bar are connected to form a hanging hook groove. The hanging hook groove extends along a left-right direction of the display mounting support. The hanging assembly is hung into different positions of the hanging hook groove of the wall plate. Each hanging assembly includes a hanging hook member, a retractable mechanism and a display hanging member. The hanging hook member including a hanging rod, a connecting rod and a hanging hook. The connecting rod is connected between one end of the hanging rod and one side of the hanging hook. The connecting rod is hollow and open on a side facing the wall plate to form a receiving groove. The first supporting member is received in the receiving groove. The first supporting member includes a first convex structure on a side facing the hanging hook. The first convex structure includes a first plate portion and a second plate portion. Adjacent edges of the first plate portion and the second plate portion intersect with each other. The first convex structure is protruded when viewed from the wall plate. The retractable mechanism is connected between the hanging rod and the display hanging member. The display hanging member is configured to fix to a predetermined position on a back of a display. The hanging hook is inserted into the hanging hook groove for hanging the display on the wall plate.

(20) In combination with the second aspect, in some embodiments of the present disclosure, the hanging hook includes a cantilever portion and a first concave structure. The cantilever portion is connected to one end of the connecting rod away from the hanging rod and towards the wall plate. The first concave structure includes a third plate portion and a fourth plate portion. The third plate

portion and the fourth plate portion are disposed side by side on the side of the cantilever portion facing the wall plate and extending towards the hanging rod. Adjacent edges of the third plate portion and the fourth plate portion intersect with each other. The first concave structure is recessed when viewed from the wall plate. A minimum distance between the first convex structure and the first concave structure is greater than or equal to a thickness of the first guiding bar.

(21) In combination with the second aspect, in some embodiments of the present disclosure, the first concave structure is a V-shaped structure, and the first convex structure is correspondingly also a V-shaped structure.

(22) In combination with the second aspect, in some embodiments of the present disclosure, the first supporting member further includes a protruding portion. The protruding portion includes a fifth plate portion and a sixth plate portion. Adjacent edges of the fifth plate portion and the sixth plate portion intersect with each other. The fifth plate portion is adjacent to and parallel to the first plate portion. The sixth plate portion is adjacent to and parallel to the second plate portion. When the first supporting member is received in the receiving groove, the fifth plate portion resists against inside of the first plate portion, and the sixth plate portion resists against inside of the second plate portion.

(23) In combination with the second aspect, in some embodiments of the present disclosure, the wall plate further includes a second guiding bar. The wall frame and the second guiding bar are connected to form a locking hook groove. The locking hook groove extends along a left-right direction of the display mounting support. Opening of the locking hook groove and opening of the hanging hook groove are set back to back. The hanging assembly further includes a pull cord assembly. The pull cord assembly is connected to the other end of the hanging rod. The pull cord assembly includes a locking hook. The locking hook is inserted into the locking hook groove for locking the hanging assembly on the wall plate. The pull cord assembly further includes a second supporting member. The second supporting member is connected to one end of the hanging rod away from the hanging hook. The second supporting member includes a second convex structure on a side of the second supporting member facing the locking hook. The second convex structure includes a seventh plate portion and an eighth plate portion. Adjacent edges of the seventh plate portion and the eighth plate portion intersect with each other. The second convex structure is protruded when being viewed from the wall plate.

(24) In combination with the second aspect, in some embodiments of the present disclosure, the locking hook includes two cantilever arms and a second concave structure. The second concave structure is connected between the two cantilever arms. The second concave structure includes a ninth plate portion and a tenth plate portion. The ninth plate portion is adjacent to the seventh plate portion. The tenth plate portion is adjacent to the eighth plate portion. Adjacent edges of the ninth plate portion and the tenth plate portion intersect with each other. The second concave structure is recessed when being viewed from the wall plate.

(25) In combination with the second aspect, in some embodiments of the present disclosure, the second supporting member defines an inserting groove. The pull cord assembly includes a locking member. The locking member include an inserting portion and the locking hook. The locking hook is connected to one side of the inserting portion. The inserting portion is inserted into the inserting groove. The locking hook is located outside of the inserting groove, and spaced apart from the second convex structure of the second supporting member so as to form a snapping space for snapping into the locking hook groove.

(26) In combination with the second aspect, in some embodiments of the present disclosure, the second concave structure is V-shaped, and the second convex structure is correspondingly V-shaped.

(27) Compared with the prior art, the beneficial effect of the present disclosure is as follows:

(28) Compared with the prior art, the present disclosure adopts a hanging hook with a first concave structure or a first supporting member with a first concave structure, which can reduce a movement

gap of the hanging hook relative to the first guiding bar without affecting the adjustment of the left-right rotation angles, so that the display mounting support has a smaller movement gap between the hanging hook and the first guiding bar at any rotation angle within the adjustable range of the left-right rotation angles, avoiding problems such as wobbling or empty travel due to the large movement gap between the hanging hook and the first guiding bar.

Description

BRIEF DESCRIPTION OF THE ACCOMPANYING DRAWINGS

- (1) To describe the technology solutions in the embodiments of the present disclosure more clearly, the following briefly introduces the accompanying drawings required for describing the embodiments. Obviously, the accompanying drawings in the following description show merely at least one embodiment of the present disclosure, and those of ordinary skilled in the art may also obtain other drawings based on these drawings.
- (2) FIG. 1 illustrates a three-dimensional structural schematic view of a display mounting support 1 in accordance with an embodiment of the present disclosure.
- (3) FIG. 2 illustrates an exploded view of the display mounting support in an embodiment of the present disclosure.
- (4) FIG. 3 illustrates a three-dimensional structural schematic view of the hanging assembly from another view in accordance with an embodiment of the present disclosure.
- (5) FIG. 4 illustrates a partial enlarged view of FIG. 3 at IV.
- (6) FIG. 5 illustrates an exploded view of a hanging hook member of FIG. 3.
- (7) FIG. 6 illustrates a schematic view of a positional relationship between a hanging hook and a first guiding bar in the prior art.
- (8) FIG. 7 illustrates a schematic view of a positional relationship between a hanging hook and a first guiding bar in the prior art.
- (9) FIG. 8 illustrates a schematic view of a positional relationship between a hanging hook and a first guiding bar in accordance with an embodiment of the present disclosure.
- (10) FIG. 9A illustrates a schematic view of a display mounting support being adjusted to the right in accordance with an embodiment of the present disclosure.
- (11) FIG. 9B illustrates a schematic view of a positional relationship between the hanging hook and the first guiding bar in a first limit position in accordance with an embodiment of the present disclosure.
- (12) FIG. 10A illustrates a schematic view of the display mounting support in accordance with an embodiment of the present disclosure when the display mounting support is stretched forward.
- (13) FIG. 10B illustrates a schematic view of the display mounting support in accordance with an embodiment of the present disclosure when the display mounting support is retracted backward.
- (14) FIG. 10C illustrates a schematic view of a positional relationship between the hanging hook and the first guiding bar in an intermediate position in accordance with an embodiment of the present disclosure.
- (15) FIG. 11A illustrates a schematic view of the display mounting support being adjusted to the left in accordance with an embodiment of the present disclosure.
- (16) FIG. 11B illustrates a schematic view of a positional relationship between the hanging hook and the first guiding bar in a second limit position in accordance with an embodiment of the present disclosure.
- (17) FIG. 12 illustrates a partial enlarged view of FIG. 3 at XII.
- (18) FIG. 13 illustrates an exploded view of the hanging assembly in FIG. 2.
- (19) FIG. 14 illustrates a schematic view of height adjustment.
- (20) FIG. 15 illustrates a schematic view of partial assembly of the hanging assembly in FIG. 13.

(21) FIG. 16 illustrates a three-dimensional structural schematic view of the hanging assembly in accordance with another embodiment of the present disclosure.

(22) FIG. 17 illustrates a partial exploded view of the hanging assembly in FIG. 16.

(23) FIG. 18 illustrates a partial enlarged view of FIG. 17.

DETAILED DESCRIPTION OF ILLUSTRATED EMBODIMENTS

(24) Embodiments of the present disclosure are described in detail below. Examples of the embodiments are shown in the accompanying drawings. The same or similar labeling throughout denotes the same or similar elements or elements having the same or similar functions. The embodiments described below by reference to the accompanying drawings are exemplary and are intended to be configured to explain the present disclosure and are not to be construed as limiting the present disclosure.

(25) Furthermore, the terms “first” and “second” are used for descriptive purposes only and are not to be understood as indicating or implying relative importance or implicitly specifying the number of technical features indicated. Therefore, a feature defined with “first” or “second” may include one or more such features, either explicitly or implicitly. In the description of the present disclosure, “more than one” means two or more, unless otherwise expressly and specifically limited.

(26) In the present disclosure, unless otherwise expressly specified and limited, the terms “connected”, “fixed”, and so on are to be understood broadly, e.g., they may be fixedly connected, removably connected, or integrally connected: they may be mechanically connected or electrically connected: they may be directly connected or indirectly connected through an intermediate medium: they may be interconnected within two elements or an interactive relationship between two elements. For those of ordinary skill in the art, the specific meaning of the above terms in the present disclosure may be understood on a case-by-case basis.

(27) Referring to FIG. 1, FIG. 1 illustrates a three-dimensional structural schematic view of a display mounting support 1 in accordance with an embodiment of the present disclosure.

(28) For convenience of description, a front-back direction of the display mounting support 1 shown in FIG. 1 is defined as a Y-axis direction, i.e., a thickness direction, a left-right direction of the display mounting support 1 shown in FIG. 1 is defined as an X-axis direction, and a height direction of the display mounting support 1 shown in FIG. 1 is defined as a Z-axis direction. The orientation terms such as “top”, “bottom”, “left” and “right” mentioned in the description of the display mounting support 1 in embodiments of the present disclosure are based on the orientation shown in FIG. 1 of the accompanying drawings of the specification, with a positive direction of Z-axis as the “top”, a negative direction of Z-axis as the “bottom”, a negative direction of X-axis as the “left” and a positive direction of the X-axis as “right”, which does not constitute a limitation of the display mounting support 1 in an actual application scenario.

(29) As shown in FIG. 1, the display mounting support 1 includes a wall plate 11 and two hanging assemblies 12. The wall plate 11 is configured for being fixed on a wall. One side of each hanging assembly 12 is configured for hanging on the wall plate 11, and the other side of each hanging assembly 12 is configured for fixing on a display screen (not shown), so as to hang the display screen on the wall plate 11. Referring to FIG. 2, FIG. 2 illustrates an exploded view of the display mounting support 1 in an embodiment of the present disclosure. The wall plate 11 includes a wall frame 111 and a first guiding bar 112. The wall frame 111 and the first guiding bar 112 are connected to form a hanging hook groove 113. The hanging hook groove 113 extends along a left-right direction of the display mounting support 1. Each hanging assembly 12 includes a hanging hook member 121, a retractable mechanism 122, and a display hanging member 123. Referring to FIGS. 3 and 4 together, FIG. 3 illustrates a three-dimensional structural schematic view of the hanging assembly from another view in accordance with an embodiment of the present disclosure: FIG. 4 illustrates a partial enlarged view of FIG. 3 at IV; and FIG. 5 illustrates an exploded view of a hanging hook member 121 of FIG. 3. As shown in FIG. 5, the hanging hook member 121

includes a hanging rod **1211**, a connecting rod **1212**, and a hanging hook **1213**. The connecting rod **1212** is connected between one end of the hanging rod **1211** and one side of the hanging hook **1213**. The hanging hook **1213** includes a cantilever portion **12133** and a first concave structure **12130**. The cantilever portion **12133** is connected to one end of the connecting rod **1212** away from the hanging rod **1211** and towards the wall plate **11**. The first concave structure **12130** includes a first plate portion **12131** and a second plate portion **12132**. The first plate portion **12131** and the second plate portion **12132** are disposed side by side on the side of the cantilever portion **12133** facing the wall plate **11** and extending towards the hanging rod **1211**. Adjacent edges of the first plate portion **12131** and the second plate portion **12132** intersect with each other. The first concave structure **12130** is recessed when viewed from the wall plate **11**. Referring to FIG. 3, the retractable mechanism **122** is connected between the hanging rod **1211** and the display hanging member **123**. Referring again to FIG. 2, the display hanging member **123** is configured to fix to a predetermined position on a back of a display. The hanging hook **1213** of each of the two hanging assemblies **12** is inserted into the hanging hook groove **113** for hanging each of the two hanging assemblies **12** on the wall plate **11**. It can be understood that in other embodiments, the hanging assembly **12** may be one or more, without limitation herein.

(30) Referring to FIG. 6, in the prior art, in order to enable the display mounting support **1** to achieve left and right rotation, the hanging hook **1213** has a larger dimension L in the Y-axis direction, and in FIG. 6, the span of the hanging hook **1213** in the Y-axis direction is in an area labeled as dimension L in the figure, and furthermore, the hanging hook **1213** is in a shape of an inverted L when viewed from the X-axis direction, and the hanging hook **1213** is in a shape of a straight face when viewed from a negative direction of the Y-axis. When the hanging hook **1213** is in a parallel state relative to the first guiding bar **112**, there exists a movement gap G between the hanging hook **1213** and the first guiding bar **112**, and the movement gap G is large, which will lead to an empty travel when adjusting a left-right rotation angle or a forward-backward movement distance, affecting the experience. Similarly, when the hanging hook **1213** rotates counterclockwise or clockwise relative to the first guiding bar **112** but does not reach a limit position, there is a gap G between the hanging hook **1213** and the first guiding bar **112**, which will lead to an empty travel when adjusting a left-right rotation angle or a forward-backward movement distance, affecting the experience. Referring to FIG. 7, in the prior art, when the hanging hook **1213** is rotated counterclockwise to a limit position, one side of the hanging hook **1213** can be held against the first guiding bar **112**, and similarly, when the hanging hook **1213** is rotated clockwise to a limit position, the other side of the hanging hook **1213** can be held against the first guiding bar **112**. Therefore, a problem of the large movement gap between the hanging hook **1213** and the first guiding bar **112** in the prior art does not exist only when the hanging hook **1213** is rotated counterclockwise to the limit position or clockwise to the limit position. However, when the hanging hook **1213** is rotated relative to the first guiding bar **112** but not to the limit position, there exists the movement gap G between the hanging hook **1213** and the first guiding bar **112**, which can lead to the empty travel when adjusting the left-right rotation angles or the forward-backward movement distance, affecting the experience. In the present disclosure, please referring to FIG. 8, by adopting the hanging hook **1213** having the first concave structure **12130**, the size of the hanging hook **1213** in the Y-axis direction, i.e., the thickness direction, can be increased, and thus the movement gap of the hanging hook **1213** relative to the first guiding bar **112** can be reduced without affecting the adjustment of the left-right rotation angles, so that the display mounting support **1** has a smaller movement gap between the hanging hook **1213** and the first guiding bar **112** at any rotation angle within an adjustable range of the left-right rotation angle, and avoids problems such as wobbling or empty travel between the hanging hook **1213** and the first guiding bar **112** due to excessive movement gap.

(31) In some embodiments, referring again to FIG. 5, the connecting rod **1212** is hollow and open on a side facing the wall plate **11** to form a receiving groove **12121**. The hanging hook member **121**

also includes a first supporting member **1214**. The first supporting member **1214** is received in the receiving groove **12121**. The first supporting member **1214** includes a first convex structure **12140** on a side facing the hanging hook **1213**. The first convex structure **12140** includes a third plate portion **12141** and a fourth plate portion **12142**. The third plate portion **12141** is adjacent to the first plate portion **12131**, and the fourth plate portion **12142** is adjacent to the second plate portion **12132**. Adjacent edges of the third plate portion **12141** and the fourth plate portion **12142** intersect with each other. The first convex structure **12140**) and the first concave structure **12130** are disposed back to back. Referring to FIG. 9B, a minimum distance between the first convex structure **12140**) and the first concave structure **12130** is greater than or equal to a thickness of the first guiding bar **112**. In some embodiments, the difference between the minimum distance between the first convex structure **12140** and the first concave structure **12130** and the thickness of the first guiding bar **112** is within 0.0 to 1.5 mm. It can be understood that in other embodiments, a range of the difference may be adjusted according to practical needs.

(32) Therefore, in the present disclosure, by adding the first convex structure **12140**, the first convex structure **12140** and the first concave structure **12130** are located back to back, which can further narrow the movement gap between the hanging hook **1213** and the first guiding bar **112**, reduce wobbling of the hanging hook **1213** relative to the first guiding bar **112** without affecting the adjustment of the left-right rotation angles, and enhance the user experience.

(33) In some embodiments, the first supporting member **1214** is a plastic member. It can be understood that, in other embodiments, the first supporting member **1214** may also be a metal member, etc., and is not limited herein.

(34) In some embodiments, referring again to FIG. 4, the first concave structure **12130** and the first convex structure **12140** are both V-shaped. Correspondingly, the first plate portion **12131**, the second plate portion **12132**, the third plate portion **12141** and the fourth plate portion **12142** may be in a form of a planar plate. The third plate portion **12141** and the first plate portion **12131** together form a V-shaped angle between them. The second plate portion **12132** and the fourth plate portion **12142** together form a V-shaped angle between them. And, referring again to FIG. 9B, the third plate portion **12141** and the second plate portion **12132** are parallel, and a distance between the planes where each of the third plate portion **12141** and the second plate portion **12132** is located is greater than or equal to the thickness of the first guiding bar **112**. In this embodiment, the distance between the planes where each of the third plate portion **12141** and the second plate portion **12132** is located is slightly greater than the thickness of the first guiding bar **112**, and the difference between the distance between the planes where each of the third plate portion **12141** and the second plate portion **12132** is located and the thickness of the first guiding bar is 0.0 mm-1.5 mm, which is able to ensure that the hanging hook **1213** can be smoothly hung in the hanging hook groove **113**, i.e., the first guiding bar **112** can smoothly enter between the third plate portion **12141** and the second plate portion **12132**, while avoiding wobbling caused by excessive gaps between the third plate portion **12141** and the second plate portion **12132**. It can be understood that, in other embodiments, the range of the difference may be adjusted according to actual needs. The first plate portion **12131** and the fourth plate portion **12142** are parallel, and a distance between the planes where each of the first plate portion **12131** and the fourth plate portion **12142** is located is greater than or equal to the thickness of the first guiding bar **112**. In this embodiment, the distance between the planes where each of the first plate portion **12131** and the fourth plate portion **12142** is located is slightly greater than the thickness of the first guiding bar **112**, and the difference between the distance between the planes where each of the first plate portion **12131** and the fourth plate portion **12142** is located and the thickness of the first guiding bar **112** is 0.0 mm-1.5 mm, which is able to ensure that the hanging hook **1213** can be smoothly hung in the hanging hook groove **113**, i.e., the first guiding bar **112** can smoothly enter between the first plate portion **12131** and the fourth plate portion **12142**, while avoiding wobbling caused by excessive gaps between the first plate portion **12131** and the fourth plate portion **12142**. It can be understood that in other embodiments, the

range of the difference may be adjusted according to actual needs.

(35) Therefore, through the mutual cooperation of the third plate portion **12141** and the second plate portion **12132**, and the mutual cooperation of the first plate portion **12131** and the fourth plate portion **12142**, it is possible to further narrow the movement gap of the hanging hook **1213** relative to the first guiding bar **112**, which makes the hanging hook **1213** more reliable and stable when it is rotated to the limit position relative to the first guiding bar **112**.

(36) It can be understood that, in other embodiments, the first concave structure **12130**) and the first convex structure **12140** may be in a shape of a C-shape or a polygonal shape, etc., respectively, Correspondingly, the first plate portion **12131**, the second plate portion **12132**, the third plate portion **12141** and the fourth plate portion **12142** may be in a shape of a curved plate or a polygonal plate and will not be limited herein.

(37) Referring to FIGS. **9A** and **9B**, the retractable mechanisms **122** of the two hanging assemblies **12** may have different retractable lengths. When the display **2** is held by hand to be rotated to the right, the hanging hook **1213** is rotated counterclockwise relative to the first guiding bar **112**. When the hanging hook **1213** is rotated counterclockwise relative to the first guiding bar **112** to a first limit position, the second plate portion **12132** and the third plate portion **12141** rest against the opposite sides of the first guiding bar **112**, respectively. In this embodiment, the maximum angle at which the hanging hook **1213** rotates counterclockwise relative to the first guiding bar **112** is -15 degrees. It can be understood that, in other embodiments, the maximum angle at which the hanging hook **1213** rotates counterclockwise relative to the first guiding bar **112** may be adjusted according to actual needs.

(38) Referring to FIG. **10A**, FIG. **10B**, and FIG. **10C**, when the hanging hook **1213** is set in parallel relative to the first guiding bar **112**, the pointed corners of the first convex structure **12140** and the first concave structure **12130** are held against the first guiding bar **112** on opposite sides of the first guiding bar **112**. At this time, the rotation angle of the hanging hook **1213** relative to the first guiding bar **112** is 0 degrees. At this time, when the display **2** is pushed forward and backward, the first convex structure **12140**) and the first concave structure **12130** can be held against the opposite sides of the first guiding bar **112**, avoiding an empty travel when the display **2** is adjusting a forward and backward retractable distance.

(39) Referring to FIGS. **11A** and **11B**, when the display **2** is held by hand to be rotated to the left, the hanging hook **1213** is rotated clockwise relative to the first guiding bar **112**. When the hanging hook **1213** is rotated clockwise relative to the first guiding bar **112** to a second limit position, the first plate portion **12131** and the fourth plate portion **12142** rest against the opposite sides of the first guiding bar **112**, respectively. In this embodiment, the maximum angle at which the hanging hook **1213** rotates clockwise relative to the first guiding bar **112** is $+15$ degrees. It can be understood that, in other embodiments, the maximum angle at which the hanging hook **1213** rotates clockwise relative to the first guiding bar **112** may be adjusted according to actual needs.

(40) It can be understood that, in some embodiments, one of the first concave structure **12130** and the first convex structure **12140** may be omitted, e.g., either the first concave structure **12130** or the first convex structure **12140** may be omitted.

(41) In other embodiments, when the first concave structure **12130** is omitted, the angle of the first convex structure **12140** may be set smaller, making the first convex structure **12140**) be larger in the Y-axis direction so that even if only the first convex structure **12140** is included, the movement gap of the hanging hook **1213** within the hanging hook groove **113** can be minimized. In yet other embodiments, when the first convex structure **12140**) is omitted, the angle of the first concave structure **12130** may be set smaller, making the first concave structure **12130** be larger in the Y-axis direction so that even if only the first concave structure **12130** is included, the movement gap of the hanging hook **1213** within the hanging hook groove **113** can be minimized.

(42) In some embodiments, referring again to FIG. **5**, the first supporting member **12144** further includes a protruding portion **12143**. The protruding portion **12143** is located on a top end of the

first supporting member **12144**. The protruding portion **12143** protrudes from a side of the top end of the first supporting member **1214** facing the wall plate **11**. The protruding portion **12143** includes a supporting concave structure **12144**. The supporting concave structure **12144** includes a fifth plate portion **12145** and a sixth plate portion **12146**. Adjacent edges of the fifth plate portion **12145** and the sixth plate portion **12146** intersect with each other. The fifth plate portion **12145** is located adjacent to the first plate portion **12131**, and the sixth plate portion **12146** is adjacent to the second plate portion **12132**. The fifth plate portion **12145** is parallel to the first plate portion **12131** and resists against the inside of the first plate portion **12131**. The sixth plate portion **12146** is parallel to the second plate portion **12132** and resists against the inside of the second plate portion **12132**.

(43) Therefore, the fifth plate portion **12145** can support the first plate portion **12131**, and the sixth plate portion **12146** can support the second plate portion **12132**, thereby enhancing the overall structural strength of the hanging hook **1213**, and assisting in the positioning of the first supporting member **1214** within the receiving groove **12121**.

(44) In some embodiments, referring again to FIG. 5, the connecting rod **1212** includes a first side plate **12122**, a second side plate **12123**, a front plate **12124**, and a top plate **12125**. The first side plate **12122** and the second side plate **12123** are located opposite to each other. The front plate **12124** is connected to front ends of the first side plate **12122** and the second side plate **12123**, and the cantilever portions **12133** are two. The two cantilever portions **12133** are coplanar with the first side plate **12122** and the second side plate **12123**, respectively. The top plate **12125** is connected to the top ends of the first side plate **12122** and the second side plate **12123**, and the top ends of the two cantilever portions **12133**. The first side plate **12122**, the second side plate **12123**, the front plate **12124**, the top plate **12125**, the two cantilever portions **12133** cooperatively form the receiving groove **12121**.

(45) In some embodiments, when the first concave structure **12130** is V-shaped, a peripheral wall of the top plate **12125** adjacent the wall plate **11** is in a V-shape that corresponds to the V-shape of the first concave structure **12130** of the hanging hook **1213**. It can be understood that, in other embodiments, when the first concave structure **12130** is C-shaped or polygonal shaped, a peripheral wall of the top plate **12125** adjacent the wall plate **11** is in a C-shape or polygonal shape that corresponds to the C-shape or polygonal shape of the first concave structure **12130** of the hanging hook **1213**.

(46) In some embodiments, the first supporting member **1214** further includes a third side plate **12147** and a fourth side plate **12148**. The third side plate **12147** and the fourth side plate **12148** each has an L shape. The third side plate **12147** and the fourth side plate **12148** are located opposite to each other. The third side plate **12147** connects the third plate portion **12141** and the fifth plate portion **12145**. The fourth side plate **12148** connects the fourth plate portion **12142** and the sixth plate portion **12146**. The third side plate **12147** is located on an inner side of the first side plate **12122** and is parallel to the first side plate **12122**. The fourth side plate **12148** is located on an inner side of the second side plate **12123** and is parallel to the second side plate **12123**.

(47) Therefore, by the third side plate **12147** affixing to the first side plate **12122** and the fourth side plate **12148** affixing to the second side plate **12123**, which improves a positioning accuracy of the first supporting member **1214** within the receiving groove **12121**.

(48) In some embodiments, the third side plate **12147** and the fourth side plate **12148** also form an upper and lower through space for passage of other components.

(49) In some embodiments, referring again to FIG. 2, the wall plate **11** further includes a second guiding bar **114**. The wall frame **111** and the second guiding bar **114** are connected to form a locking hook groove **115**. The locking hook groove **115** extends along a left-right direction of the display mounting support **1**. Opening of the locking hook groove **115** and opening of the hanging hook groove **113** are set back to back. The hanging assembly **12** further includes a pull cord assembly **124**. The pull cord assembly **124** is connected to the other end of the hanging rod **1211**.

Referring again to FIG. 5, the pull cord assembly **124** includes a locking hook **1241**. When the hanging assembly **12** is hung into the hanging hook groove **113** through the hanging hook **1213**, the locking hook **1241** of the pull cord assembly **124** is used to securely and reliably fix the hanging assembly **12** to the wall plate **11** by the locking hook **1241** of the pull cord assembly **124** being snapped into the locking hook groove **115**.

(50) Specifically, the locking hook **1241** includes two cantilever arms **12413** and a second concave structure **12410**. The second concave structure **12410** is connected between the two cantilever arms **12413**. The second concave structure **12410** includes a seventh plate portion **12411** and an eighth plate portion **12412**. Adjacent edges of the seventh plate portion **12411** and the eighth plate portion **12412** intersect with each other. The second concave structure **12410** is recessed when viewed from the wall plate **11**.

(51) Therefore, compared to the locking hook with a shape of flat plate, by adopting the locking hook **1241** with the second concave structure **12410** in the present disclosure, a size of the locking hook **1241** in the Y-axis direction, i.e., in the thickness direction, can be increased, and therefore, the second concave structure **12410** can occupy more spaces of the locking hook groove **115** in the thickness direction, which reduces the movement gap between the locking hook **1241** and the second guiding bar **114**, so that the display mounting support **1** has a smaller movement gap between the locking hook **1241** and the second guiding bar **114** at any angle within the adjustable range of the left-right rotation angles, which can further avoid problems such as empty travel and wobbling caused by the gap between the locking hook **1241** and the second guiding bar **114** being too large.

(52) Referring to FIGS. 5 and 12, the pull cord assembly **124** further includes a locking member **1240**, a shaft **1242**, a tension spring **1243**, and a pull rope **1244**. The locking member **1240** is connected to the other end of the hanging rod **1211**. The locking member **1240** includes the locking hook **1241**. The locking **1241** is set corresponding to a position of the opening **1216**. In some embodiments, the hanging rod **1211** is hollow inside and a side of the other end of the hanging rod **1211** facing the wall plate **11** defines an opening **1216**. The locking member **1240** is received inside the other end of the hanging rod **1211** and is partially exposed from the opening **1216**. The locking member **1240** further includes a bottom wall **1245**, a first sidewall **1246** and a second sidewall **1247**. The first sidewall **1246** and the second sidewall **1247** are located opposite to each other. The locking hook **1241** is connected to sides of the first sidewall **1246** and the second sidewall **1247** adjacent to the wall plate **11**. The bottom wall **1245** is simultaneously connected to bottom ends of the first sidewall **1246**, the second sidewall **1247** and the locking hook **1241**. At least one of the first sidewall **1246** and the second sidewall **1247** of the locking member **1240** is slidably coupled to the other end of the hanging rod **1211** by the shaft **1242** to provide guidance for sliding of the locking member **1240** relative to the hanging rod **1211**. At least one of the first sidewall **1246** and the second sidewall **1247** defines a first limiting groove **1248** extending along a height direction of the display mounting support **1**. The hanging rod **1211** defines a shaft hole **1215** correspondingly. The shaft **1242** passes through the first limiting groove **1248** and is fixed in the shaft hole **1215**. In other embodiments, the first limiting groove **1248** may be defined on the hanging rod **1211**, and the shaft hole **1215** may be defined on at least one of the first sidewall **1246** and the second sidewall **1247**. The tension spring **1243** is located in the locking member **1240**, and one end of the tension spring **1243** is connected to the shaft **1242** and the other end of the tension spring **1243** is fixed to the bottom wall **1245** of the locking member **1240**. The pull rope **1244** is located outside of the locking member **1240**, and the pull rope **1244** is secured to the bottom wall **1245** of the locking member **1240**. It can be understood that the pull rope **1244** and the tension spring **1243** may be secured to different locations on the bottom wall **1245**, for example, the bottom wall **1245** includes a first post and a second post, the pull rope **1244** is coupled to the first post and the tension spring **1243** is coupled to the second post. In other embodiments, the bottom wall may include only one post, and the pull rope **1244** and the tension spring **1243** are both connected to the post.

(53) Therefore, when pulled downwardly by the pull rope **1244**, the locking member **1240** follows the pull rope **1244** downwardly within a travel allowed by the first limiting groove **1248**, the tension spring **1243** is stretched, and when the locking member **1240** is moved downwardly to a position where the locking hook **1241** is lower than a lower edge of the second guiding bar **114**, the locking hook **1241** can be removed from the locking hook groove **115**, the pull cord assembly **124** is unlocked, and the hanging assembly **12** as a whole can be removed from the wall plate **11**. Conversely, when the hanging assembly **12** needs to be mounted on the wall plate **11**, the hanging hook **1213** of the hanging assembly **12** is first snapped into the hanging hook groove **113**, and then the pull rope **1244** is pulled down such that the locking member **1240** follows the pull rope **1244** to move downwardly within the travel allowed by the first limiting groove **1248**, the tension spring **1243** is stretched, and when the locking member **1240** moves downwardly until the position of the locking hook **1241** is lower than the lower edge of the second guiding bar **114**, the pull cord assembly **124** is pushed toward the side close to the wall plate **11**, and the locking hook **1241** can enter the locking hook groove **115**, releasing the pull rope **1244**. The locking hook **1241** snaps to the locking hook groove **115** under the elastic restoring force of the tension spring **1243**, and the hanging assembly **12** can be mounted to the wall plate **11**.

(54) In some embodiments, the pull cord assembly **124** further includes a second supporting member **1249**. The second supporting member **1249** is located within the locking member **1240**. The second supporting member **1249** includes a second convex structure **12490** on a side of the second supporting member **1249** facing the locking hook **1241**. The second convex structure **12490** includes a ninth plate portion **12491** and a tenth plate portion **12492**. The ninth plate portion **12491** is adjacent to the seventh plate portion **12411**, and the tenth plate portion **12492** is adjacent to the eighth plate portion **12412**. Adjacent edges of the ninth plate portion **12491** and the tenth plate portion **12492** intersect with each other. The second convex structure **12490** is protruded when viewed from the wall plate **11**. A minimum distance between the second convex structure **12490** and the second concave structure **12410** is greater than or equal to the thickness of the second guiding bar **114**.

(55) Therefore, in the present disclosure, due to the addition of the second convex structure **12490**, the second convex structure **12490** and the second concave structure **12410** are set back to back, which can further reduce the movement gap of the locking hook **1241** relative to the second guiding bar **114**, and reduce wobbling of the locking hook **1241** relative to the second guiding bar **114** without affecting the adjustment of the left-right rotation angle, thereby enhancing the user experience.

(56) In some embodiments, the second supporting member **1249** is a plastic member. It can be understood that in other embodiments, the second supporting member **1249** may also be a metal member, etc., without limitation herein.

(57) In some embodiments, the second concave structure **12410** and the second convex structure **12490** are both V-shaped. Correspondingly, the ninth plate portion **12491**, the seventh plate portion **12411**, the tenth plate portion **12492**, and the eighth plate portion **12412** may be in the form of a planar plate. The ninth plate portion **12491** and the seventh plate portion **12411** together form a V-shaped angle. The tenth plate portion **12492** and the eighth plate portion **12412** together form a V-shaped angle. The seventh plate portion **12411** and the tenth plate portion **12492** are parallel, a distance between the planes where each of the seventh plate portion **12411** and the tenth plate portion **12492** is located is greater than or equal to a thickness of the second guiding bar **114**, and a difference between the distance between the planes where each of the seventh plate portion **12411** and the tenth plate portion **12492** and the thickness of the second guiding bar **114** is 0.0 mm to 1.5 mm. The eighth plate portion **12412** and the ninth plate portion **12491** are provided in parallel, a distance between the planes where each of the eighth plate portion **12412** and the ninth plate portion **12491** is located is greater than or equal to the thickness of the second guiding bar **114**, and the difference between the distance between the planes where each of the eighth plate portion

12412 and the ninth plate portion **12491** and the thickness of the second guiding bar **114** is 0.0 mm to 1.5 mm. It can be understood that, in other embodiments, a range of the difference may be adjusted according to the actual needs.

(58) Therefore, through the mutual cooperation of the seventh plate portion **12411** and the tenth plate portion **12492**, and the mutual cooperation of the eighth plate portion **12412** and the ninth plate portion **12491**, the movement gap of the locking hook **1241** relative to the second guiding bar **114** can be further narrowed, which makes the limit more reliable and stable when the locking hook **1241** is rotated to the limit position relative to the second guiding bar **114**.

(59) It can be understood that in other embodiments, the second concave structure **12410** and the second convex structure **12490** may be in a shape of a C-shape or a polygon, etc., respectively, and will not be limited herein.

(60) It can be understood that in some embodiments, one of the second convex structure **12490** and the second concave structure **12410** may be omitted, for example, the second convex structure **12490** or the second concave structure **12410** may be selectively omitted.

(61) In other embodiments, when the second concave structure **12410** is omitted, the angle of the second convex structure **12490** may be set smaller, allowing the second convex structure **12490** to have a larger size in the Y-axis direction, so that even if only the second convex structure **12490** is included, the movement gap of the locking hook **1241** within the locking hook groove **115** may be minimized. In yet other embodiments, when the second convex structure **12490** is omitted, the angle of the second concave structure **12410** may be set smaller, allowing the second concave structure **12410** to have a larger size in the Y-axis direction in the Y-axis direction, so that even if only the second concave structure **12410** is included, the movement gap of the locking hook **1241** within the locking hook groove **115** may be minimized.

(62) In some embodiments, the second supporting member **1249** further includes a fifth side plate **12493**, a sixth side plate **12494**, and a second front plate **12495**. The fifth side plate **12493** and the sixth side plate **12494** are located opposite to each other. The second front plate **12495** and the second convex structure **12490** are located opposite to each other. The fifth side plate **12493**, the sixth side plate **12494**, the second front plate **12495** and the second convex structure **12490** cooperatively form a rectangular space. The tension spring **1243** is located within the rectangular space. Correspondingly, the fifth side plate **12493** and the sixth side plate **12494** each defines a perforation **12496** corresponding to the position of the shaft hole **1215**. The shaft **1242** are threaded within the first limiting grooves **1248**, the shaft holes **1215** and the perforations **12496**.

(63) Therefore, the second supporting member **1249** is an enclosing structure with greater structural strength and better support.

(64) In some embodiments, referring to FIG. 13, the hanging assembly **12** further includes a height adjustment mechanism **125**. The height adjustment mechanism **125** is configured to adjust a height of the display **2**. Specifically, the height adjusting mechanism **125** includes a first height adjusting member **1251**, a second height adjusting member **1252**, and a height adjusting bolt **1253**. The first height adjusting member **1251** is received in the receiving groove **12121** of the connecting rod **1212** and passes through the first supporting member **1214**. The second height adjusting member **1252** is located within the hanging rod **1211**. The first height adjusting member **1251** is connected to the second height adjusting member **1252**. The first height adjusting member **1251** defines a first bolt hole **1254** at a top of the first height adjusting member **1251**. The top plate **12125** defines a second bolt hole **12129**. The height adjusting bolt **1253** passes through the first bolt hole **1254** and the second bolt hole **12129** to connect the first height adjusting member **1251** to the top plate **12125**. The height adjusting bolt **1253** adjusts the relative positions of the first height adjusting member **1251** and the second height adjusting member **1252** within the hanging hook member **121**. The second height adjusting member **1252** is connected to the retractable mechanism **122**.

(65) Referring to FIGS. 14 and 15, when the horizontal degree of the display **2** needs to be fine-tuned, the height adjustment bolt **1253** can be rotated using a tool **3** to adjust the height of the

height adjustment mechanism **125** as a whole relative to the hanging hook member **121**.

(66) Therefore, since the two hanging assemblies **12** each includes a height adjusting mechanism **125**, the two height adjusting mechanisms **125** can be adjusted separately, so as to adjust the horizontal degree of the display **2**. When the horizontal degree of the wall plate **11** mounted on the wall is not sufficient, the two hanging assemblies **12** can be fine-adjusted by using the two height adjusting mechanisms **125**, so that the display **2** reaches the required horizontal degree.

(67) In some embodiments, the first height adjustment member **1251** has a substantially U-shaped cross-section in the Y-axis direction. A size of the first height adjustment member **1251** in the Y-axis direction is smaller than that of the first supporting member **1214** in the Y-axis direction. A size of the first height adjustment member **1251** in the Y-axis direction is smaller than that of the second height adjustment member **1252** in the Y-axis direction. Both the hanging rod **1211** and the second height adjustment member **1252** have a substantially U-shaped cross-section in the Z-axis direction. The U-shaped structure of the second height adjustment member **1252** is located within the U-shaped structure of the hanging rod **1211**. The hanging rod **1211** and the second height adjustment member **1252** have substantially same sizes in the Y-axis direction.

(68) In some embodiments, the height adjustment mechanism **125** further includes a first guiding bolt **1255**. The first height adjustment member **1251** is connected to the second height adjustment member **1252** by the first guiding bolt **1255**. The hanging rod **1211** defines a second limiting groove **1219** corresponding to a position of the first guiding bolt **1255**. The second limiting groove **1219** extends along a Z-axis direction. The first guiding bolt **1255** is also threaded into the second limiting groove **1219**. The second limiting groove **1219** can limit a height adjustment travel of the height adjustment mechanism **125**, and can act as a guide for the movement in the height direction.

(69) In some embodiments, the second height adjustment member **1252** defines a third limiting groove **1218** on a bottom end thereof. The third limiting groove **1218** extends along the Z-axis direction. The height adjustment mechanism **125** further includes a second guiding bolt **1256**. The second guiding bolt **1256** is also threaded into the third limiting groove **1218**. The second height adjustment member **1252** is connected to the hanging rod **1211** by the second guiding bolt **1256**. Therefore, the ends of the second height adjustment member **1252** are limited and guided by the first guiding bolt **1255** and the second guiding bolt **1256**, respectively, for better travel stability.

(70) In some embodiments, referring again to FIG. **13**, the retractable mechanism **122** includes a first gear arm **1221**, a second gear arm **1222**, a third gear arm **1223**, and a fourth gear arm **1224**. The first gear arm **1221**, the second gear arm **1222**, the third gear arm **1223**, and the fourth gear arm **1224** are connected in a quadrilateral structure. Ends of the first gear arm **1221** and the second gear arm **1222** are connected by gear meshing and simultaneously pivotally connected to the second height adjustment member **1252**. Ends of the third gear arm **1223** and the fourth gear arm **1224** are connected by gear meshing and simultaneously pivotally connected to the display hanging member **123**. The first gear arm **1221** is pivotally connected to the third gear arm **1223**, and the second gear arm **1222** is pivotally connected to the fourth gear arm **1224**. In other embodiments, the retractable mechanism **122** is not limited to the above-described structure, but may also be other types of retractable mechanisms, which are not limited herein.

(71) Therefore, the retractable distance of the display mounting support **1** in the Y-axis direction can be adjusted by the retractable mechanism **122**.

(72) In this embodiment, when the display mounting support **1** includes the height adjustable mechanism **125**, ends of the first gear arm **1221** and the second gear arm **1222** are connected by gear meshing and simultaneously pivotally connected to the second height adjusting member **1252**. It can be understood that in other embodiments, the height adjustment mechanism **125** may be omitted, so that ends of the first gear arm **1221** and the second gear arm **1222** are connected by gear meshing and simultaneously pivotally connected to the hanging rod **1211**.

(73) In some embodiments, referring again to FIG. **13**, the display mounting support **1** further includes a tilt adjustment mechanism **126**. The tilt adjustment mechanism **126** includes a mounting

member **1261** and an adjustment handle **1263**. The mounting member **1261** is pivotally coupled to sides of the third gear arm **1223** and the fourth gear arm **1224** away from the wall plate **11**. The mounting member **1261** is substantially U-shaped with an opening facing the third gear arm **1223** and the fourth gear arm **1224**. The mounting member **1261** includes a screw: **1262** located on sidewall **1260** thereof. A central axis of the screw **1262** extends in the X-axis direction. The display hanging member **123** further includes a lug portion **1231** located on sidewall thereof. The lug portion **1231** defines an arcuate groove **1232**. The screw **1262** passes through the arcuate groove **1232**. The adjustment handle **1263** is threadedly connected to the screw: **1262**. When the screw: **1262** is located in different positions of the arcuate groove **1232**, the display hanging member **123** has different downward tilt angles or upward tilt angles relative to the mounting member **1261**. (74) Therefore, the downward tilt angles or upward tilt angles of the display **2** can be adjusted by the tilt adjustment mechanism **126**.

(75) In other embodiments, the tilt adjustment mechanism **126** may be omitted, and the display hanging member **123** is fixedly connected to a side of the retractable mechanism **122** away from the wall plate **11**.

(76) Referring to FIGS. **16**, **17**, and **18**, FIG. **16** illustrates a three-dimensional structural schematic view of the hanging assembly in accordance with another embodiment of the present disclosure: FIG. **17** illustrates a partial exploded view of the hanging assembly in FIG. **16**; FIG. **18** illustrates a partial enlarged view of FIG. **17**.

(77) In this embodiment, the pull rod assembly **124** includes a locking member **1240** and a second supporting member **1249**. The locking member **1240** includes the locking hook **1241**, but the second concave structure included in the locking hook **1241** may be omitted. The second supporting member **1249** defines an inserting groove **12497**. The inserting groove **12497** penetrates through the bottom surface of the second supporting member **1249** along the height direction. The locking member **1240** includes an inserting portion **12401** and the locking hook **1241**. The locking hook **1241** is connected to one side of the inserting portion **12401**. The inserting portion **12401** is inserted into the inserting groove **12497**. The locking hook **1241** is located outside of the inserting groove **12497** and is located opposite and spaced apart from the second convex structure **12490** of the second supporting member **1249** to form a snapping space for snapping into the locking hook groove **115**.

(78) Therefore, since the inserting groove **12497** is a groove extending in the height direction, the locking member **1240** can slide up and down within the inserting groove **12497** relative to the second supporting member **1249**. A pull rope **1244** may be attached to the locking member **1240**. The pull rope **1244** may pull the locking member **1240** downwardly, causing the locking member **1240** to disengage from the locking hook groove **115**.

(79) In some embodiments, a tab **12498** is formed at a bottom position of the second supporting member **1249**, and the inserting groove **12497** is also formed on the tab **12498**, which can increase a formation space of the inserting groove **12497**, so that there is more contact area between the inserting portion **12401** and the inserting groove **12497**, and improve the structural stability.

(80) In some embodiments, a guiding member is provided between the locking member **1240** and the second supporting member **1249**, the guiding member may provide a guiding effect on the up and down sliding of the locking member **1240** relative to the second supporting member **1249**. Obviously, the guiding member may be, but is not limited to, a guiding shaft and a guiding groove fit, and the guiding groove may be defined on at least one of the locking member **1240** and the second supporting member **1249**. In this embodiment, the guiding groove is defined on the inserting portion **12401**.

(81) In some embodiments, a reset spring is also located between the locking member **1240** and the second supporting member **1249**, the reset spring acts as a reset for downward movement of the locking member **1240** relative to the second supporting member **1249**.

(82) The above description of the technical solution of the subject matter of the present disclosure

as well as the corresponding details are described above, and it can be understood that the above description is only at least one embodiment of the technical solution of the subject matter of the present disclosure, and some of the details can also be omitted in its specific implementation.

(83) In addition, in at least one embodiment of the above present disclosure, there are multiple embodiments of the combination of implementation possibilities, various combination programs are limited to space will not be listed. The technical personnel in the field can freely combine the implementation of the above embodiments according to the needs of the specific implementation, in order to obtain a better application experience.

(84) In summary, it can be understood that the present disclosure has the above mentioned excellent characteristics, so that it can be used to enhance the effectiveness of the previous technology has not been practical, and become a very practical value of the product.

(85) The above is only a better example of the present disclosure, and is not intended to limit the present disclosure. Any modification, equivalent substitution or improvement made within the ideas and principles of the present disclosure shall be included in the scope of protection of the present disclosure.

Claims

1. A display mounting support, wherein the display mounting support comprises: a wall plate, wherein: the wall plate comprises a wall frame and a first guiding bar; the wall frame is configured to be mounted on a wall surface, the wall frame and the first guiding bar are connected to form a hanging hook groove, the hanging hook groove extends along a left-right direction of the display mounting support; and at least one hanging assembly, wherein: the at least one hanging assembly is hung into the hanging hook groove of the wall plate; each hanging assembly comprises a hanging hook member, a retractable mechanism and a display hanging member; the hanging hook member comprises a hanging rod, a connecting rod and a hanging hook; the connecting rod is connected between one end of the hanging rod and one side of the hanging hook; the hanging hook comprises a cantilever portion and a first concave structure; the cantilever portion is connected to one end of the connecting rod away from the hanging rod and towards the wall plate; the first concave structure comprises a first plate portion and a second plate portion; the first plate portion and the second plate portion are disposed side by side on one side of the cantilever portion facing the wall plate and extending towards the hanging rod; adjacent edges of the first plate portion and the second plate portion intersect with each other; the first concave structure is recessed when viewed from the wall plate; the retractable mechanism is connected between the hanging rod and the display hanging member; the display hanging member is configured to be connected to a predetermined position on a back of a display; and the hanging hook is inserted into the hanging hook groove for hanging the display on the wall plate.

2. The display mounting support according to claim 1, wherein: the connecting rod is hollow and open on a side facing the wall plate to form a receiving groove; the hanging hook member further comprises a first supporting member; the first supporting member is received in the receiving groove; the first supporting member comprises a first convex structure on a side facing the hanging hook; the first convex structure comprises a third plate portion and a fourth plate portion; the third plate portion is adjacent to the first plate portion; the fourth plate portion is adjacent the second plate portion; adjacent edges of the third plate portion and the fourth plate portion intersect with each other; the first convex structure is protruded when viewed from the wall plate; and a minimum distance between the first convex structure and the first concave structure is greater than or equal to a thickness of the first guiding bar.

3. The display mounting support according to claim 2, wherein: the third plate portion and the second plate portion are parallel, and a distance between planes where each of the third plate portion and the second plate portion is located is greater than or equal to a thickness of the first

guiding bar; the first plate portion and the fourth plate portion are parallel; and a distance between planes where each of the first plate portion and the fourth plate portion is located is greater than or equal to a thickness of the first guiding bar.

4. The display mounting support according to claim 2, wherein the first concave structure is a V-shaped structure, and the first convex structure is correspondingly also a V-shaped structure.

5. The display mounting support according to claim 2, wherein: the first supporting member further comprises a protruding portion; the protruding portion comprises a fifth plate portion and a sixth plate portion; adjacent edges of the fifth plate portion and the sixth plate portion intersect with each other; the fifth plate portion is adjacent to and parallel to the first plate portion; the sixth plate portion is adjacent to and parallel to the second plate portion; when the first supporting member is received in the receiving groove, the fifth plate portion resists against inside of the first plate portion; and the sixth plate portion resists against inside of the second plate portion.

6. The display mounting support according to claim 1, wherein: the wall plate further comprises a second guiding bar, the wall frame and the second guiding bar are connected to form a locking hook groove, the locking hook groove extends along a left-right direction of the display mounting support, opening of the locking hook groove and opening of the hanging hook groove are set back to back; the at least one hanging assembly further comprises a pull cord assembly, the pull cord assembly is connected to the other end of the hanging rod; the pull cord assembly comprises a locking hook, the locking hook comprises two cantilevers and a second concave structure; the second concave structure is connected between the two cantilevers; the second concave structure comprises a seventh plate portion and an eighth plate portion; adjacent edges of the seventh plate portion and the eighth plate portion intersect with each other; the second concave structure is recessed when viewed from the wall plate; and the locking hook of the at least one hanging assembly is inserted into the locking hook groove for locking the at least one hanging assembly on the wall plate.

7. The display mounting support according to claim 6, wherein: the hanging rod is hollow inside, and, a side of the other end of the hanging rod facing the wall plate defines an opening; the pull cord assembly further comprises a locking member, a shaft, a tension spring and a pull rope; the locking member is received inside the other end of the hanging rod and partially exposed from the opening; the locking member comprises a bottom wall, a first sidewall, a second sidewall and a locking hook; the first sidewall and the second sidewall are located opposite to each other; the locking hook is connected to sides of the first sidewall and the second sidewall adjacent the wall plate; the bottom wall is connected to bottom ends of the first sidewall, the second sidewall and the locking hook simultaneously; at least one of the first sidewall and the second sidewall defines a first limiting groove extending along a height direction of the display mounting support; the hanging rod defines a shaft hole correspondingly; the shaft passes through the first limiting groove and is fixed in the shaft hole; the tension spring is located in the locking member; one end of the tension spring is connected to the shaft, and the other end of the tension spring is fixed to the bottom wall of the locking member; and the pull rope is located outside of the locking member and is fixed to the bottom wall of the locking member.

8. The display mounting support according to claim 7, wherein: the pull cord assembly further comprises a second supporting member; the second supporting member is located within the locking member; the second supporting member comprises a second convex structure on a side of the second supporting member facing the locking hook; the second convex structure comprises a ninth plate portion and a tenth plate portion; the ninth plate portion is adjacent to the seventh plate portion; the tenth plate portion is adjacent to the eighth plate portion; adjacent edges of the ninth plate portion and the tenth plate portion intersect with each other; the second convex structure is protruded when being viewed from the wall plate; and a minimum distance between the second convex structure and the second concave structure is greater than or equal to a thickness of the second guiding bar.

9. The display mounting support according to claim 8, wherein: the seventh plate portion and the tenth plate portion are parallel; a distance between planes where each of the seventh plate portion and the tenth plate portion is located is greater than or equal to a thickness of the second guiding bar; the eighth plate portion and the ninth plate portion are parallel; and a distance between planes where each of the eighth plate portion and the ninth plate portion is located is greater than or equal to a thickness of the second guiding bar.

10. The display mounting support according to claim 8, wherein the second concave structure is a V-shaped structure, and the second convex structure is correspondingly also a V-shaped structure.

11. The display mounting support according to claim 2, wherein: the display mounting support further comprises a height adjusting mechanism; the height adjusting mechanism comprises a first height adjusting member, a second height adjusting member, and a height adjusting bolt; the first height adjusting member is located within the receiving groove of the connecting rod and passes through the first supporting member; the second height adjusting member is located with the hanging rod, the first height adjusting member is connected with the second height adjusting member; the first height adjusting member defines a first bolt hole at a top of the first height adjusting member; a top plate of the connecting rod defines a second bolt hole; the height adjusting bolt passes through the first bolt hole and the second bolt hole so as to connect the first height adjusting member with the top plate of the connecting rod; the height adjusting bolt adjusts a relative position of the first height adjusting member and the second height adjusting member within the hanging hook member; and the second height adjusting member is connected to the retractable mechanism.

12. The display mounting support according to claim 1, wherein: the retractable mechanism comprises a first gear arm, a second gear arm, a third gear arm and a fourth gear arm; the first gear arm, the second gear arm, the third gear arm and the fourth gear arm are connected in a quadrilateral structure; ends of the first gear arm and the second gear arm are connected by gear meshing and simultaneously pivotally connected to the at least one hanging member; ends of the third gear arm and the fourth gear arm are connected by gear meshing and simultaneously pivotally connected to the display hanging member; the first gear arm is pivotally connected to the third gear arm; and the second gear arm is pivotally connected to the fourth gear arm.

13. The display mounting support according to claim 1, wherein: the display mounting support further comprises a tilt adjusting mechanism; the tilt adjusting mechanism comprises a mounting member and an adjusting handle; the mounting member is secured to the hanging hook member; the mounting member comprises a screw located on a sidewall thereof; the display hanging member further comprises a lug portion located on a sidewall thereof; the lug portion defines an arcuate groove; the screw passes through the arcuate groove; the adjusting handle is threadedly connected with the screw; and when the screw is located at different positions of the arcuate groove, the display hanging member has different front-to-rear tilting angles relative to the mounting member.

14. A display mounting support, wherein the display mounting support comprises: a wall plate, wherein: the wall plate comprises a wall frame and a first guiding bar; the wall frame is configured for fixing to a wall surface; the wall frame and the first guiding bar are connected to form a hanging hook groove; and the hanging hook groove extends along a left-right direction of the display mounting support; and at least one hanging assembly, wherein: the at least one hanging assembly is hung into different positions of the hanging hook groove of the wall plate; each hanging assembly comprises a hanging hook member, a retractable mechanism and a display hanging member; the hanging hook member comprises a hanging rod, a connecting rod and a hanging hook; the connecting rod is connected between one end of the hanging rod and one side of the hanging hook; the connecting rod is hollow and open on a side facing the wall plate to form a receiving groove; a first supporting member is received in the receiving groove; the first supporting member comprises a first convex structure on a side facing the hanging hook; the first convex

structure comprises a first plate portion and a second plate portion; adjacent edges of the first plate portion and the second plate portion intersect with each other; the first convex structure is protruded when viewed from the wall plate; the retractable mechanism is connected between the hanging rod and the display hanging member; the display hanging member is configured to fix to a predetermined position on a back of a display; and the hanging hook is inserted into the hanging hook groove for hanging the display on the wall plate.

15. The display mounting support according to claim 14, wherein: the hanging hook comprises a cantilever portion and a first concave structure; the cantilever portion is connected to one end of the connecting rod away from the hanging rod and towards the wall plate; the first concave structure comprises a third plate portion and a fourth plate portion; the third plate portion and the fourth plate portion are disposed side by side on the side of the cantilever portion facing the wall plate and extending towards the hanging rod; adjacent edges of the third plate portion and the fourth plate portion intersect with each other; the first concave structure is recessed when viewed from the wall plate; and a minimum distance between the first convex structure and the first concave structure is greater than or equal to a thickness of the first guiding bar.

16. The display mounting support according to claim 15, wherein the first concave structure is a V-shaped structure, and the first convex structure is correspondingly also a V-shaped structure.

17. The display mounting support according to claim 14, wherein: the first supporting member further comprises a protruding portion; the protruding portion comprises a fifth plate portion and a sixth plate portion; adjacent edges of the fifth plate portion and the sixth plate portion intersect with each other; the fifth plate portion is adjacent to and parallel to the first plate portion; the sixth plate portion is adjacent to and parallel to the second plate portion; when the first supporting member is received in the receiving groove; the fifth plate portion resists against inside of the first plate portion; and the sixth plate portion resists against inside of the second plate portion.

18. The display mounting support according to claim 14, wherein: the wall plate further comprises a second guiding bar; the wall frame and the second guiding bar are connected to form a locking hook groove; the locking hook groove extends in a left-right direction along the display mounting support; opening of the locking hook groove and opening of the hanging hook groove are set back to back; the at least one hanging assembly further comprises a pull cord assembly; the pull cord assembly is connected to the other end of the hanging rod; the pull cord assembly comprises a locking hook; the locking hook is inserted into the locking hook groove for locking the at least one hanging assembly on the wall plate; the pull cord assembly further comprises a second supporting member; the second supporting member is located within a locking member; the second supporting member comprises a second convex structure on a side of the second supporting member facing the locking hook; the second convex structure comprises a seventh plate portion and an eighth plate portion; adjacent edges of the seventh plate portion and the eighth plate portion intersect with each other; and the second convex structure is protruded when being viewed from the wall plate.

19. The display mounting support according to claim 18, wherein: the locking hook comprises two cantilever arms and a second concave structure; the second concave structure is connected between the two cantilever arms; the second concave structure comprises a ninth plate portion and a tenth plate portion; the ninth plate portion is adjacent to the seventh plate portion; the tenth plate portion is adjacent to the eighth plate portion; adjacent edges of the ninth plate portion and the tenth plate portion intersect with each other; and the second concave structure is recessed when being viewed from the wall plate.

20. The display mounting support according to claim 18, wherein: the second supporting member defines an inserting groove; the pull cord assembly comprises a locking member; the locking member comprise an inserting portion and the locking hook; the locking hook is connected to one side of the inserting portion; the inserting portion is inserted into the inserting groove; and the locking hook is located outside of the inserting groove and is spaced apart from the second convex

structure of the second supporting member so as to form a snapping space for snapping into the locking hook groove.
