

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12405128
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Yamamoto; Shusuke et al.

Output device

Abstract

An output device, including: a memory; and a processor coupled to the memory, the processor configured to: acquire an objective that a user wishes to achieve after boarding a vehicle; and output a candidate site having a shortest total time among candidate sites that would enable the objective to be achieved, the total time including a predicted required time from a current location of the user and a predicted waiting time at a parking lot associated with the candidate site.

Inventors: Yamamoto; Shusuke (Tokyo, JP), Okazaki; Chikara (Gotemba, JP), Watatsu; Kohta (Nagoya, JP), Tanaka; Hideyuki (Nisshin, JP), Murase; Shinya (Nagoya, JP), Tatsumoto; Yuki (Seto, JP)

Applicant: TOYOTA JIDOSHA KABUSHIKI KAISHA (Toyota, JP)

Family ID: 90890082

Assignee: TOYOTA JIDOSHA KABUSHIKI KAISHA (Toyota, JP)

Appl. No.: 18/378802

Filed: October 11, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240151548 A1	May. 09, 2024

Foreign Application Priority Data

JP	2022-177458	Nov. 04, 2022
----	-------------	---------------

Publication Classification

Int. Cl.: G01C21/36 (20060101); G06V20/10 (20220101); G06V20/13 (20220101)

U.S. Cl.:

CPC **G01C21/3685** (20130101); **G01C21/3602** (20130101); **G01C21/3647** (20130101);
G06V20/13 (20220101); **G06V20/182** (20220101);

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2009/0177383	12/2008	Tertoolen	701/532	G01C 21/3682
2012/0056758	12/2011	Kuhlman	340/932.2	G08G 1/14
2014/0350853	12/2013	Proux	701/533	G01C 21/34
2017/0191848	12/2016	Jones	N/A	G01C 21/3484
2018/0150773	12/2017	Lee	N/A	G08G 1/143
2018/0301031	12/2017	Naamani	N/A	G01C 21/3685
2020/0400446	12/2019	Beaurepaire	N/A	G08G 1/144
2021/0082284	12/2020	Diehl	N/A	G08G 1/0112
2021/0312808	12/2020	Lee	N/A	E04H 6/422
2022/0150820	12/2021	Newman	N/A	H04W 48/20
2023/0045975	12/2022	Simpson	N/A	G08G 1/202
2023/0400312	12/2022	Beaurepaire	N/A	G06Q 50/40
2024/0151548	12/2023	Yamamoto	N/A	G06V 20/182

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
H09-120486	12/1996	JP	N/A
2001-147133	12/2000	JP	N/A
3654009	12/2004	JP	N/A
2022-009869	12/2021	JP	N/A

Primary Examiner: Girma; Fekadeselassie

Attorney, Agent or Firm: Oliff PLC

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION

(1) This application is based on and claims priority under 35 USC 119 from Japanese Patent Application No. 2022-177458 filed on Nov. 4, 2022, the disclosure of which is incorporated by reference herein.

BACKGROUND

Technical Field

(2) The present disclosure relates to an output device.

Related Art

(3) Japanese Patent Application Laid-open JP-A) No. 2022-009869 discloses an information providing system that predicts the degree of congestion in a parking lot associated with a destination at a predicted time of arrival of the vehicle at the destination, and outputs parking information including the prediction result relating to the degree of congestion and the waiting time at the parking lot.

(4) The information providing system disclosed in JP-A No. 2022-009869 has the problem that it is not possible to identify sites with the shortest total time, including the required time from a current location.

SUMMARY

(5) The present disclosure has been made in consideration of the above facts, and an object thereof is to provide an output device that enables a site to which the total time, including the required time from a current location, is shortest, to be identified.

Means for Solving the Problem

(6) An output device according to a first aspect includes an acquisition unit that acquires an objective that a user wishes to achieve after boarding a vehicle; and an output unit that outputs a candidate site having a shortest total time among candidate sites that would enable the objective to be achieved, the total time including a predicted required time from a current location of the user and a predicted waiting time at a parking lot associated with the candidate site.

(7) In the output device of the first aspect, the acquisition unit acquires the objective that the user wishes to achieve after boarding the vehicle, and the output unit outputs a candidate site having a shortest total time among candidate sites that would enable the objective to be achieved, the total time including a predicted required time from a current location of the user and a predicted waiting time at a parking lot associated with the candidate site. According to the output device of the first aspect, sites to which the total time, including the required time from the current location, is shortest can be identified.

(8) An output device according to a second aspect is the output device of the first aspect, in which the output unit outputs the candidate site having a shortest total time that is a total of the predicted required time, which is predicted from a satellite image capturing a road from the current location to the candidate site, and the predicted waiting time, which is predicted from a satellite image capturing the parking lot.

(9) According to the output device of the second aspect, even if devices such as sensors are not newly installed, sites to which the total time is shortest can be identified.

(10) An output device according to a third aspect is the output device of the second aspect, in which the acquisition unit acquires a target date on which the user wishes to achieve the objective; and the output unit outputs the candidate site having a shortest total time that is a total of the predicted required time, which is predicted from a satellite image capturing the road on a date that is relevant to the target date, and the predicted waiting time, which is predicted from a satellite image capturing the parking lot on a date that is relevant to the target date.

(11) According to the output device of the third aspect, compared to cases in which the predicted required time and predicted waiting time are not predicted based on satellite images recorded on dates associated with the target date, a total time predicted with high accuracy can be identified.

(12) An output device according to a fourth aspect is the output device of any one of the first aspect to the third aspect, in which, in a case in which there is a plurality of candidate sites having the shortest total time, the output unit outputs the candidate site for which the predicted waiting time is shortest among the candidate sites having the shortest total time.

(13) According to the output device of the fourth aspect, compared to a case in which a candidate site with the shortest total time and with the shortest predicted required time is output, congestion of the parking lot can be reduced.

(14) An output device according to a fifth aspect is the output device of any one of the first aspect to the fourth aspect, in which the acquisition unit acquires a destination of the vehicle, and

acquires, as the objective, a classification characterizing the destination.

(15) According to the output device of the fifth aspect, the objective that is intended to be achieved at the destination can be achieved at the candidate site with the shortest total time.

(16) According to the present disclosure, it is possible to identify sites to which the total time, including the required time from the current location, is shortest.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) An exemplary embodiment of the present disclosure will be described in detail based on the following figures, wherein:

(2) FIG. 1 is a diagram illustrating an exemplary schematic configuration of an output system according to an exemplary embodiment.

(3) FIG. 2 is a block diagram illustrating an exemplary hardware configuration of a vehicle according to an exemplary embodiment.

(4) FIG. 3 is a block diagram illustrating an exemplary hardware configuration of a center server according to an exemplary embodiment.

(5) FIG. 4 is a block diagram illustrating an exemplary functional configuration of a CPU in a center server according to an exemplary embodiment.

(6) FIG. 5 is a flow chart illustrating an exemplary flow of output processing according to an exemplary embodiment.

DETAILED DESCRIPTION

(7) As illustrated in FIG. 1, an output system **100** of the present exemplary embodiment is configured including a satellite server **10**, a vehicle **12**, and a center server **30**. The center server **30** is an example of an output device. The vehicle **12** further includes an onboard unit **20**. Note that the number of vehicles **12** included in the output system **100** is not limited to the number illustrated in FIG. 1. The satellite server **10**, the vehicle **12**, and the center server **30** are connected together through a network **CN1**.

(8) The satellite server **10** accumulates satellite images, these being terrestrial images captured from above by an artificial satellite, an aircraft, or the like. More specifically, the satellite server **10** associates and accumulates the satellite image, the date on which the satellite image was captured, and the location at which the satellite image was captured.

(9) FIG. 2 is a block diagram illustrating hardware configuration of devices installed in the vehicle **12** of the present exemplary embodiment. As illustrated in FIG. 2, the vehicle **12** of the present exemplary embodiment includes an onboard unit **20** and a global positioning system (GPS) device **22**.

(10) The GPS device **22** is a device that acquires position information that is a current location of the vehicle **12**.

(11) The onboard unit **20** is configured including a central processing unit (CPU) **20A**, read only memory (ROM) **20B**, random access memory (RAM) **20C**, storage **20D**, a wireless communication interface (I/F) **20E**, and an input/output I/F **20G**. The CPU **20A**, the ROM **20B**, the RAM **20C**, the storage **20D**, the wireless communication I/F **20E**, and the input/output I/F **20G** are connected so as to be capable of communicating with each other through a bus **201**.

(12) The CPU **20A** executes various programs and controls various units. Namely, the CPU **20A**, which is an example of a hardware processor, loads a program from the ROM **20B** or the storage **20D**, which correspond to a memory, and executes the program using the RAM **20C** as a workspace.

(13) The ROM **20B** holds various programs and various data. The RAM **20C** serves as a workspace to temporarily store programs and data. The storage **20D** serving as a storage unit is configured by

a hard disk drive (HDD) or a solid state drive (SSD), and holds various programs including an operating system, as well as various data.

(14) The wireless communication I/F **20E** is an interface for connecting to the network **CN1**.

(15) The input/output I/F **20G** is an interface for communicating with various devices installed in the vehicle **12**. An onboard unit **20** of the present exemplary embodiment is connected to a GPS device **22** via an input/output I/F **20G**. Note that the GPS device **22** may be directly connected to the bus **201**.

(16) (Center Server)

(17) As illustrated in FIG. **3**, the center server **30** is configured including a CPU **30A**, a ROM **30B**, a RAM **30C**, and a communication I/F **30G**. The CPU **30A**, the ROM **30B**, the RAM **30C**, and the communication I/F **30G** are connected so as to be capable of communicating with each other through an internal bus **30H**.

(18) The CPU **30A** executes various programs and controls various units. Namely, the CPU **30A**, which is an example of a hardware processor, loads a program from the ROM **30B**, which corresponds to a memory, and executes the program using the RAM **30C** as a workspace.

(19) The ROM **30B** holds various programs and various data. The RAM **30C** serves as a workspace to temporarily store programs and data.

(20) The ROM **30B** of the present exemplary embodiment holds an output program and a site database.

(21) The output program is a program for implementing various functionality possessed by the center server **30**.

(22) Sites on a map are stored in a site database as a site list, together with the classifications of the sites. The classification is information that outlines the site, such as a supermarket, a park, an amusement park, or a department store. The site database can be updated via the network **CN1**. Note that the site database may be acquired through the network **CN1**.

(23) A speed database holds the average speed of a vehicle traveling through a road section for each density (i.e., traffic density) of vehicles in the relevant road section. The speed database according to the present exemplary embodiment holds information such that the average speed decreases as the traffic density increases.

(24) The communication I/F **30G** is an interface for connecting to the network **CN1**.

(25) FIG. **4** is a block diagram illustrating an example of functional configuration of the CPU **30A**. As illustrated in FIG. **4**, the CPU **30A** includes an acquisition unit **300**, a prediction unit **310**, and an output unit **320**. The respective functional configuration is implemented by the CPU **30A** reading and executing the output program stored in the ROM **30B**.

(26) The acquisition unit **300** has a function of acquiring an objective that a user wishes to achieve by boarding the vehicle **12** (hereafter simply referred to as an “objective”). In the present exemplary embodiment, the acquisition unit **300** acquires a destination of the vehicle **12** (hereafter simply referred to as a “destination”) from the onboard unit **20** via the communication I/F **30G**. The acquisition unit **300** acquires the classification of the acquired destination as the objective. More specifically, the acquisition unit **300** acquires a classification stored in the site database in association with the acquired destination as the objective. For example, in a case in which the acquisition unit **300** acquires “A Supermarket B Store” as a destination from the onboard unit **20**, a classification (such as “Supermarket” or “A Supermarket”) stored in association with “A Supermarket B Store” in the site database is acquired as the objective.

(27) Moreover, the acquisition unit **300** acquires candidate sites that are capable of realizing the objective (hereafter, simply referred to as “candidate sites”). More specifically, the acquisition unit **300** acquires all the sites stored in the site database in association with the acquired objective as candidate sites. For example, in a case in which the acquisition unit **300** acquires “Supermarket” as the objective, in the site database, “A Supermarket B Store”, “A Supermarket C Store”, “A Supermarket D Store”, “X Supermarket B Store”, and “Y Supermarket C Store” stored in

association with “Supermarket” are acquired as candidate sites.

(28) Note that the acquisition unit **300** may acquire the objective directly instead of acquiring the destination. In this case, the acquisition unit **300** acquires an objective (such as a supermarket, a park, an amusement park, or a department store) from the onboard unit **20** via the communication I/F **30G**.

(29) Moreover, the acquisition unit **300** acquires the current location of the user (hereafter simply referred to as the “current location”) from the onboard unit **20** via the communication I/F **30G**. In the present exemplary embodiment, an occupant of the vehicle **12** is applied as a user. Accordingly, in the present exemplary embodiment, the current position acquired by the vehicle **12** via the GPS device **22** is applied as the current location. However, the present invention is not limited to this example. The current location may be position information of a user terminal such as a smartphone owned by the user, or a current location input by the user.

(30) Moreover, the acquisition unit **300** has a function of further acquiring a target date on which the user wishes to achieve the objective. In the present exemplary embodiment, the acquisition unit **300** acquires the target date from the onboard unit **20** via the communication I/F **30G**. However, the present invention is not limited to this example. The target date may be acquired from a user terminal such as a smartphone owned by the user.

(31) Then, the acquisition unit **300** acquires a satellite image in which a road from a current location to a candidate site (hereafter simply referred to as a “road”) is captured, and a satellite image in which a parking lot associated with a candidate site (hereafter simply referred to as a “parking lot”) has been captured, from the satellite server **10** via the communication I/F **30G**. Hereinafter, a satellite image capturing a road and a satellite image capturing a parking lot are collectively referred to as a “satellite image”.

(32) Note that the acquisition unit **300** acquires two satellite images capturing a parking lot. More specifically, the acquisition unit **300** acquires a satellite image capturing the parking lot, and a satellite image capturing the same parking lot after a predetermined time (such as 10 minutes or 30 minutes) has elapsed since the parking lot was captured.

(33) In the present exemplary embodiment, the acquisition unit **300** acquires from the satellite server **10** a satellite image captured on a date related to the target date. More specifically, the acquisition unit **300** acquires a satellite image captured on a date on which at least one of the day of the week or the time period is the same as the target date. The time period is, for example, one week before and after the same day and month as the target date. For example, in a case in which the target date is Aug. 15, 2023 (Tuesday), the acquisition unit **300** acquires at least one of a satellite image captured on a Tuesday or a satellite image captured from Aug. 8, 2022 to Aug. 22, 2022. Note that the timing may be two weeks before and after the same day as the target date, or one month before and after the same day as the target day. Further, the matter of which of a date on which the target date and the day of the week are the same, a date on which the target date and the time period are the same, or a date on which the target date, the day of the week, and the time period are the same is acquired by the acquisition unit **300** may be predetermined by a user, or may be predetermined by an administrator or the like of the center server **30**.

(34) Note that in a case in which the acquisition unit **300** does not acquire the target date, the acquisition unit **300** may acquire the most recent satellite image stored in the satellite server **10**.

(35) Moreover, the acquisition unit **300** may acquire a satellite image captured on a date on which at least one of the presence or absence of a holiday or the time period are the same as the target date. The presence or absence of a holiday means whether or not the day is a Saturday, a Sunday, or a national holiday. For example, in a case in which the target date is Aug. 15, 2023 (Tuesday), the target day is not a holiday. The acquisition unit **300** then acquires at least one of satellite images taken on Mondays, Tuesdays, Wednesdays, Thursdays, or Fridays, these being weekdays, or satellite images taken from Aug. 8, 2022, to Aug. 22, 2022.

(36) Moreover, in a case in which the user further acquires a target time at which the user wishes to

achieve the objective, the acquisition unit **300** acquires a satellite image captured during the same time of day as the acquired target time. The time of day is, for example, 30 minutes before and after the target time acquired by the acquisition unit **300**. For example, in a case in which the target time is 13:00, the acquisition unit **300** acquires satellite images captured from 12:30 to 13:30. Note that the time of day may be one hour before or after the target time acquired by the acquisition unit **300**, or three hours before or after the target time, or the like.

(37) In the present exemplary embodiment, the acquisition unit **300** transmits the current location, the candidate site, and the target date to the satellite server **10**. The satellite server **10** then transmits to the center server **30** the satellite images for each candidate site captured on a date associated with the target date. As a result, the acquisition unit **300** acquires satellite images for each candidate site captured on a date that is related to the target date. Note that in a case in which a road from a current location to a candidate site is captured across plural satellite images, the acquisition unit **300** acquires the plural satellite images.

(38) The prediction unit **310** predicts a predicted required time from a current location to a candidate site on a target date, and a predicted waiting time for a parking lot, based on the satellite images for each candidate site acquired by the acquisition unit **300**. Namely, the prediction unit **310** predicts a total time including the predicted required time and the predicted waiting time on the target date.

(39) More specifically, the prediction unit **310** extracts a region of a road from a current location to a candidate site from a satellite image in which a road has been captured. The prediction unit **310** then extracts the front and rear surfaces of vehicles from the extracted road region, and calculates the number of vehicles traveling on the road. Then, the prediction unit **310** calculates the density of vehicles by dividing the calculated number of vehicles by the area of the relevant road. The prediction unit **310** then reads from the speed database the average vehicle speed stored in association with the calculated vehicle density. The prediction unit **310** then predicts the predicted required time from the current location to the candidate site by dividing the length of the road by the read average speed of the vehicle.

(40) Note that the prediction method of the predicted required time is not limited to the example described above. For example, the prediction unit **310** may predict the predicted required time by inputting a satellite image acquired by the acquisition unit **300** in which the roads are captured into a required time prediction model that has learned the actual required time from one location to another, and a satellite image in which a road from the one location to the other is captured, as a data set.

(41) Alternatively, the prediction unit **310** may predict the predicted required time based on information collected by sensors installed at various points on the road, without using a satellite image in which the road has been captured. Moreover, the prediction unit **310** may predict the predicted required time based on the position information of plural vehicles **12** traveling on the road.

(42) Further, the prediction unit **310** extracts a region of a parking lot from the satellite image in which the parking lot has been captured. In the present exemplary embodiment, a parking lot adjacent to a candidate site is applied as the parking lot. The prediction unit **310** then extracts the front and rear surfaces of vehicles that are stationary in relation to the extracted parking lot region, and calculates the number of vehicles lined up in the parking lot. The prediction unit **310** then identifies the last vehicle of the vehicles lined up in the parking lot. Moreover, the prediction unit **310** calculates the number of vehicles newly lined up behind the last vehicle from a satellite image in which the same parking lot has been captured after a predetermined period of time has elapsed. The prediction unit **310** then divides the number of newly arrayed vehicles by the predetermined time period to calculate the number of vehicles that line up in the parking lot per unit time. Then, the prediction unit **310** predicts the predicted waiting time by dividing the number of vehicles lined up in the parking lot by the number of vehicles that line up in the parking lot per unit time, using

Little's law. Note that in a case in which the number of vehicles that line up in the parking lot is zero, the prediction unit **310** predicts the predicted waiting time as zero minutes.

(43) The prediction method of the predicted waiting time is not limited to the example described above. For example, the prediction unit **310** may predict the predicted waiting time by multiplying the average parking time of the parking lot by the number of vehicles lined up in the parking lot. In this case, the average parking time may be stored in advance in the site database, or may be calculated from plural satellite images in which the same parking lot is captured.

(44) Alternatively, the prediction unit **310** may predict the predicted waiting time by inputting a satellite image acquired by the acquisition unit **300** in which the parking lot has been captured into a waiting time prediction model that has learned the actual waiting time of a single parking lot and satellite images in which the single parking lot has been captured as a data set.

(45) Alternatively, the prediction unit **310** may predict the predicted waiting time based on information collected by a sensor installed at the entrance to or from the parking lot, without using a satellite image in which the parking lot has been captured. Moreover, the prediction unit **310** may predict the predicted waiting time based on the position information of vehicles **12** lined up at the parking lot.

(46) The output unit **320** has a function of outputting a candidate site for which the total of the predicted required time from the current location and the predicted waiting time at the parking lot is the shortest among the candidate sites. In the present exemplary embodiment, the output unit **320** outputs the candidate site with the shortest total time that is a total of the predicted required time predicted from the satellite images in which the road has been captured on the date associated with the target date and from the predicted waiting time predicted from the satellite images in which the parking lot has been captured on the date associated with the target date. Namely, the output unit **320** outputs the candidate site with the shortest total time predicted by the prediction unit **310**. In the present exemplary embodiment, the output unit **320** outputs the candidate site with the shortest total time to the onboard unit **20** via the communication I/F **30G**. However, the present invention is not limited to this example. The output unit **320** may output the candidate site with the shortest total time to a user terminal such as a smartphone owned by the user. In a case in which the center server **30** includes a display device, the output unit **320** may output a candidate spot with the shortest total time to the display device.

(47) Moreover, in the present exemplary embodiment, in a case in which there are plural candidate sites with the shortest total time, the output unit **320** has a function of outputting the candidate site with the shortest predicted waiting time out of the candidate sites with the shortest total time.

However, the present invention is not limited to this example. The output unit **320** may output the candidate site with the shortest predicted required time among the candidate sites with the shortest total time, or may output all the candidate sites with the shortest total time. In cases in which there are plural candidate sites with the shortest total time, the matter of which of the candidate site with the shortest predicted waiting time or the candidate site with the shortest predicted required time among the candidate sites with the shortest total time, or all the candidate sites with the shortest total time, is output by the output unit **320** may be predetermined by a user, or may be predetermined by an administrator or the like of the center server **30**.

(48) Next, explanation follows regarding a flow of output processing for outputting candidate sites with the shortest total time, with reference to FIG. 5. The output processing is performed by the CPU **30A** deploying the output program from the ROM **30B** to the RAM **30C**, and executing the output program in the RAM **30C**.

(49) At step **S100** in FIG. 5, the CPU **30A** waits until the current location is acquired from the onboard unit **20**. When the CPU **30A** acquires the current location (step **S100**: YES), the processing transitions to step **S101**.

(50) At step **S101**, the CPU **30A** waits until it acquires a destination from the onboard unit **20**. When the CPU **30A** acquires the destination (step **S101**: YES), the processing transitions to step

S102.

(51) At step **S102**, the CPU **30A** acquires the objective. More specifically, the CPU **30A** acquires a classification stored in the site database in association with the destination acquired at step **S101** as the objective.

(52) At step **S103**, the CPU **30A** acquires candidate sites. More specifically, the CPU **30A** acquires all the sites stored in the site database in association with the objective acquired at step **S102** as candidate sites.

(53) At step **S104**, the CPU **30A** waits until a target date is acquired from the onboard unit **20**. When the target date has been acquired (step **S104**: YES), the CPU **30A** transitions to step **S105**.

(54) At step **S105**, the CPU **30A** transmits the current location, the candidate site, and the target date to the satellite server **10**.

(55) At step **S106**, the CPU **30A** acquires, from the satellite server **10** and for each candidate site, a satellite image in which a road is captured on a date associated with a target date, and a satellite image in which a parking lot is captured. More specifically, the CPU **30A** acquires from the satellite server **10** a satellite image of a road and a satellite image of a parking lot captured on a date on which at least one of a day of the week or a time period is the same as the target date for each candidate site.

(56) At step **S107**, the CPU **30A** predicts the predicted required time for each candidate site. More specifically, the CPU **30A** predicts the predicted required time for each candidate site by dividing the length of the road by the average speed of vehicles calculated based on the satellite image in which the relevant road is captured.

(57) At step **S108**, the CPU **30A** predicts a predicted waiting time for each candidate site. More specifically, the CPU **30A** predicts the predicted waiting time by dividing the number of vehicles that line up in the parking lot calculated from the satellite image in which the parking lot is captured, by the number of vehicles lined up in the parking lot per unit time.

(58) At step **S109**, the CPU **30A** predicts the total time for each candidate site. More specifically, the CPU **30A** adds together the predicted required time predicted at step **S107** and the predicted waiting time predicted at step **S108**.

(59) At step **S110**, the CPU **30A** determines whether or not there are plural candidate sites with the shortest total time. In a case in which there are plural candidate sites with the shortest total time (step **S110**: YES), the CPU **30A** transitions to step **S111**. On the other hand, in a case in which there is one candidate site with the shortest total time (step **S110**: NO), the CPU **30A** transitions to step **S112**.

(60) At step **S111**, the CPU **30A** outputs to the onboard unit **20** the candidate site with the shortest predicted waiting time among the candidate sites with the shortest total time, and ends the present output processing.

(61) At step **S112**, the CPU **30A** outputs the candidate site with the shortest total time to the onboard unit **20**, and ends the present output processing.

(62) [Notes]

(63) Note that in the above exemplary embodiments, a center server **30** configured separately from the vehicle **12** is applied as the output device. However, the present invention is not limited to this example. A device incorporated in the vehicle **12** may be applied as an output device. Alternatively, a user terminal owned by a user may be applied instead of the vehicle **12**. In this case, a device built into the user terminal may be applied as the output device.

(64) Moreover, in the above exemplary embodiments, satellite images are accumulated in a satellite server **10** configured separately from the center server **30**. However, the present invention is not limited to this example. The satellite images may be stored in a storage device such as the ROM **30B** or the storage included in the center server **30**.

(65) Moreover, in the above exemplary embodiments, the center server **30** predicts the total time. However, the present invention is not limited to this example. Devices other than the center server

30 may predict the total time. In this case, the center server **30** outputs the candidate site to which the total time predicted by the devices other than the center server **30** is the shortest.

(66) Note that the processing executed by the CPU reading and executing software (a program) in the above exemplary embodiments may be executed by various types of processor other than a CPU. Such processors include programmable logic devices (PLD) that allow circuit configuration to be modified post-manufacture, such as a field-programmable gate array (FPGA), and dedicated electric circuits, these being processors including a circuit configuration custom-designed to execute specific processing, such as an application specific integrated circuit (ASIC). The processing described above may be executed by any one of these various types of processor, or by a combination of two or more of the same type or different types of processor (such as plural FPGAs, or a combination of a CPU and an FPGA). The hardware structure of these various types of processors is more specifically an electric circuit combining circuit elements such as semiconductor elements.

(67) Although explanation has been given regarding an aspect in which the respective programs are stored (installed) in advance in the ROM in the above exemplary embodiments, there is no limitation thereto. The program may be provided in a format recorded on a recording medium such as compact disc read only memory (CD-ROM), digital versatile disc read only memory (DVD-ROM), or universal serial bus (USB) memory. Alternatively, the programs may be provided in a format downloadable from an external device over a network.

(68) The flow of processing described in the above exemplary embodiments is also an example, and unnecessary steps may be deleted, new steps may be added, or the processing order may be rearranged within a range not departing from the spirit of the present invention.

(69) The configurations of the satellite server **10**, the vehicle **12**, and the center server **30** described in the above exemplary embodiments are examples, and may be modified according to circumstances within a range not departing from the spirit of the present invention.

Claims

1. An output device, comprising: a memory; and a processor coupled to the memory, the processor configured to: acquire an objective that a user wishes to achieve after boarding a vehicle; output a candidate site having a shortest total time among candidate sites that would enable the objective to be achieved, the total time including a predicted required time from a current location of the user and a predicted waiting time at a parking lot associated with the candidate site; and output the candidate site having a shortest total time that is a total of the predicted required time, which is predicted from a satellite image capturing a road from the current location to the candidate site, and the predicted waiting time, which is predicted from a satellite image capturing the parking lot.
2. An output device, comprising: a memory; and a processor coupled to the memory, the processor configured to: acquire an objective that a user wishes to achieve after boarding a vehicle; output a candidate site having a shortest total time among candidate sites that would enable the objective to be achieved, the total time including a predicted required time from a current location of the user and a predicted waiting time at a parking lot associated with the candidate site; output the candidate site having a shortest total time that is a total of the predicted required time, which is predicted from a satellite image capturing a road from the current location to the candidate site, and the predicted waiting time, which is predicted from a satellite image capturing the parking lot; acquire a target date on which the user wishes to achieve the objective; and output the candidate site having a shortest total time that is a total of the predicted required time, which is predicted from a satellite image capturing the road on a date that is relevant to the target date, and the predicted waiting time, which is predicted from a satellite image capturing the parking lot on a date that is relevant to the target date.
3. An output device, comprising: a memory; and a processor coupled to the memory, the processor

configured to: acquire an objective that a user wishes to achieve after boarding a vehicle; and output a candidate site having a shortest total time among candidate sites that would enable the objective to be achieved, the total time including a predicted required time from a current location of the user and a predicted waiting time at a parking lot associated with the candidate site, wherein, in a case in which there is a plurality of candidate sites having the shortest total time, the processor outputs the candidate site for which the predicted waiting time is shortest among the candidate sites having the shortest total time.

4. The output device of claim 1, wherein the processor acquires a destination of the vehicle, and acquires, as the objective, a classification characterizing the destination.
