

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12405282
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Tsai; Hong-I

Apparatus for detecting defects of reflective element

Abstract

An apparatus for detecting defects includes a first conveyor for transporting finished reflective elements; a 3D inspection zone including a second conveyor, a first robot for picking one reflective element and placing same on the second conveyor, two side-lit panels at either side of the second conveyor, and two first digital cameras each between the side-lit panels of the same side for taking 3D images of the reflective element and sending same to an image processor for detecting defects; a 2D inspection zone including a third conveyor for receiving the reflective element, a backlit panel at either side of the third conveyor, and two second digital cameras for taking 2D images of the reflective element and sending same to the image processor for detecting defects. There are further provided a microcontroller, a fourth conveyor, a fifth conveyor, and a second robot.

Inventors:	Tsai; Hong-I (Taoyuan, TW)
Applicant:	Tsai; Hong-I (Taoyuan, TW)
Family ID:	90360238
Assignee:	Taiwan Nano-Technology Application Corp (Taoyuan, TW)
Appl. No.:	18/386616
Filed:	November 03, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240103026 A1	Mar. 28, 2024

Publication Classification

Int. Cl.: G01N21/88 (20060101); G01N21/95 (20060101); G01N35/00 (20060101)

U.S. Cl.:

CPC **G01N35/0099** (20130101); **G01N21/8851** (20130101); **G01N21/95** (20130101);
G01N2021/9511 (20130101)

Field of Classification Search

CPC: G01N (21/8806); G01N (21/8851); G01N (21/95); G01N (2021/845); G01N (2021/9511)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
10937683	12/2020	Schlezingner	N/A	H01L 21/67715
2021/0018367	12/2020	Oguchi	N/A	G01J 3/0205

Primary Examiner: Pyo; Kevin K

Background/Summary

BACKGROUND OF THE INVENTION

1. Field of the Invention

(1) The invention relates to detecting apparatuses and more particularly to an apparatus for detecting defects of a reflective element in a manufacturing process of an interior rearview mirror for a vehicle.

2. Description of Related Art

(2) Typically, an employee may visually inspect a slightly convex surface of a randomly selected finished reflective element for defects (e.g., scratches, blobs and notches) in a manufacturing process of an interior rearview mirror for a vehicle. The passed reflective element will be mounted on a casing of the interior rearview mirror.

(3) However, the manual inspection is time consuming, labor intensive and unreliable.

(4) Thus, the need for improvement still exists.

SUMMARY OF THE INVENTION

(5) It is therefore one object of the invention to provide an apparatus for detecting defects of a reflective element comprising an apparatus for detecting defects, comprising a first conveyor for transporting a plurality of finished reflective elements; an image processor; a 3D inspection zone including a second conveyor disposed rearward of the first conveyor, a first robot for picking one of the finished reflective elements and placing same on the second conveyor, two spaced side-lit panels at either side of the second conveyor, and two first CCD-based digital cameras each disposed between the side-lit panels of the same side for taking 3D images of the finished reflective element moving on the second conveyor and sending the 3D images to the image processor for detecting defects of the finished reflective element; a 2D inspection zone including a third conveyor disposed rearward of the second conveyor for receiving the finished reflective element from the second conveyor, a backlit panel at either side of the third conveyor, and two second CCD-based digital cameras each disposed above the backlit panel for taking 2D images of the finished reflective element moving on the third conveyor and sending the 2D images to the image processor for detecting defects of the finished reflective element; a microcontroller for receiving data of the detected defects of the finished reflective element from the image processor and determining whether the finished reflective element has defects or not; a fourth conveyor disposed

rearward of the third conveyor; a fifth conveyor disposed rearward of the third conveyor and being parallel to the fourth conveyor; and a second robot controlled by the microcontroller for picking the finished reflective element moving on the third conveyor and either placing same on the fourth conveyor if the finished reflective element is defect free or placing same on the fifth conveyor if the finished reflective element has defects.

(6) The above and other objects, features and advantages of the invention will become apparent from the following detailed description taken with the accompanying drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a schematic top plan view of an apparatus for detecting defects of a reflective element in a manufacturing process of an interior rearview mirror for a vehicle according to the invention; and

(2) FIG. 2 is a schematic front elevation view of FIG. 1.

DETAILED DESCRIPTION OF THE INVENTION

(3) Referring to FIGS. 1 to 2, an apparatus 1 for detecting defects of a reflective element in a manufacturing process of an interior rearview mirror for a vehicle in accordance with the invention comprises a first conveyor 10 for transporting a plurality of finished reflective elements 100; an image processor 20; a three-dimensional (3D) inspection zone 30 including a second conveyor 31 disposed rearward of the first conveyor 10, a first robot (e.g., manipulating industrial robot) 32 for picking the finished reflective element 100 and placing same on the second conveyor 31, two spaced side-lit panels 33 at either side of the second conveyor 31, and two first charge-coupled device (CCD)-based digital cameras 34 each disposed between the side-lit panels 33 of the same side for taking 3D images of the finished reflective element 100 moving on the second conveyor 31 and sending the 3D images to the image processor 20 for detecting defects (e.g., scratches, blobs and notches) of the finished reflective element 100; a two-dimensional (2D) inspection zone 40 including a third conveyor 41 disposed rearward of the second conveyor 31 for receiving the finished reflective element 100 from the second conveyor 31, a backlit panel 42 at either side of the third conveyor 41, and two second CCD-based digital cameras 43 each disposed above the backlit panel 42 for taking 2D images of the finished reflective element 100 moving on the third conveyor 41 and sending the 2D images to the image processor 20 for detecting defects (e.g., scratches, blobs and notches) of the finished reflective element 100; a microcontroller 50 for receiving data of the detected defects of the finished reflective element 100 from the image processor 20 and determining whether the finished reflective element 100 has defects or not; a fourth conveyor 60 disposed rearward of the third conveyor 41; a fifth conveyor 70 disposed rearward of the third conveyor 41 and being parallel to the fourth conveyor 60; and a second robot 80 controlled by the microcontroller 50 for picking the finished reflective element 100 moving on the third conveyor 41 and either placing same on the fourth conveyor 60 if the finished reflective element 100 is defect free or placing same on the fifth conveyor 70 if the finished reflective element 100 has defects.

(4) Preferably, the image processor 20 performs a defect detection program on the 2D and 3D images to detect defects (e.g., scratches, blobs and notches) of the finished reflective element 100.

(5) Preferably, each of the fourth conveyor 60 and the fifth conveyor 70 transport the inspected finished reflective element 100 to a receptacle.

(6) While the invention has been described in terms of preferred embodiments, those skilled in the art will recognize that the invention can be practiced with modifications within the spirit and scope of the appended claims.

Claims

1. An apparatus for detecting defects, comprising: a first conveyor for transporting a plurality of finished reflective elements; an image processor; a 3D inspection zone including a second conveyor disposed rearward of the first conveyor, a first robot for picking one of the finished reflective elements and placing same on the second conveyor, two spaced side-lit panels at either side of the second conveyor, and two first CCD-based digital cameras each disposed between the side-lit panels of the same side for taking 3D images of the finished reflective element moving on the second conveyor and sending the 3D images to the image processor for detecting defects of the finished reflective element; a 2D inspection zone including a third conveyor disposed rearward of the second conveyor for receiving the finished reflective element from the second conveyor, a backlit panel at either side of the third conveyor, and two second CCD-based digital cameras each disposed above the backlit panel for taking 2D images of the finished reflective element moving on the third conveyor and sending the 2D images to the image processor for detecting defects of the finished reflective element; a microcontroller for receiving data of the detected defects of the finished reflective element from the image processor and determining whether the finished reflective element has defects or not; a fourth conveyor disposed rearward of the third conveyor; a fifth conveyor disposed rearward of the third conveyor and being parallel to the fourth conveyor; and a second robot controlled by the microcontroller for picking the finished reflective element moving on the third conveyor and either placing same on the fourth conveyor if the finished reflective element is defect free or placing same on the fifth conveyor if the finished reflective element has defects.
