

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12408047
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Castillo Lema; Jose

Management orchestrator for a content-centric network in a 6G network

Abstract

A management orchestrator for a content-centric network in a 6G network is described herein according to some aspects. For example, the management orchestrator can receive, from a client device, a request for a network function in the content-centric network executed by a plurality of network nodes in the 6G network. In response to receiving the request for the network function, the management orchestrator can identify a particular network node of the plurality of network nodes usable for executing the network function. The management orchestrator can then automatically deploy a named function via the particular network node. The named function can be used to execute the network function for the client device.

Inventors:	Castillo Lema; Jose (Sao Paulo, BR)
Applicant:	Red Hat, Inc. (Raleigh, NC)
Family ID:	91027753
Assignee:	Red Hat, Inc. (Raleigh, NC)
Appl. No.:	17/985750
Filed:	November 11, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20240163689 A1	May. 16, 2024

Publication Classification

Int. Cl.: H04W24/02 (20090101); H04L41/0895 (20220101)

U.S. Cl.:

Field of Classification Search**CPC:** H04W (24/00-04); H04L (41/08); H04L (41/0893-0895)**References Cited****U.S. PATENT DOCUMENTS**

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
10397132	12/2018	Xia et al.	N/A	N/A
11064321	12/2020	Jha	N/A	H04W 4/02
11115867	12/2020	Dowlatkhah et al.	N/A	N/A
11297555	12/2021	Dowlatkhah et al.	N/A	N/A
11381636	12/2021	Alam	N/A	G06N 3/045
11533316	12/2021	Smith	N/A	H04L 63/105
2021/0320988	12/2020	Zhang	N/A	H04W 40/24
2021/0328783	12/2020	Doshi	N/A	H04L 9/0861
2021/0328873	12/2020	Yeung et al.	N/A	N/A
2022/0158934	12/2021	Himayat	N/A	H04L 45/745
2023/0014064	12/2022	Cheruvu	N/A	H04L 63/101

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
112020003252	12/2021	DE	H04L 45/26

OTHER PUBLICATIONS

Castillo-Lema, José & Venancio Neto, Augusto & Silva, Flávio & Kofuji, Sergio. (2019). Network Function Virtualization in Content-Centric Networks. 31-37. cited by examiner

X. Marchal et al., “Leveraging NFV for the deployment of NDN: Application to HTTP traffic transport,” NOMS 2018—2018 IEEE/IFIP Network Operations and Management Symposium, Taipei, Taiwan, 2018. cited by examiner

Arumaithurai et al., “Exploiting ICN for Flexible Management of Software-Defined Networks,” ACM-ICN '14: Proceedings of the 1st ACM Conference on Information-Centric Networking, Sep. 24, 2014: pp. 107-116, <<https://doi.org/10.1145/2660129.2660147>>. cited by applicant

Clayman et al., “The Dynamic Placement of Virtual Network Functions,” 2014 IEEE Network Operations and Management Symposium (NOMS), 2014: pp. 1-9. cited by applicant

Diaz et al., “Towards an ICN-based architecture to enhanced mobility challenges over future heterogeneous mobile networks,” Universite Sorbonne, Institut Galilee, 2020: pp. 1-4. cited by applicant

Gürkan et al., “Convergence of ICN and MEC for 5G: Opportunities and Challenges,” IEEE Communications Standards Magazine, Dec. 2020: pp. 64-71. cited by applicant

Ravindran et al., “Towards Software Defined ICN based Edge-Cloud Services,” 2013 IEEE 2nd

Primary Examiner: Higa; Brendan Y

Attorney, Agent or Firm: Kilpatrick Townsend & Stockton LLP

Background/Summary

TECHNICAL FIELD

(1) The present disclosure relates generally to content-centric networks and, more particularly (although not necessarily exclusively), to a management orchestrator for a content-centric network in a 6G network.

BACKGROUND

(2) Network functions virtualization (NFV) allows network services and functions to be virtualized instead of being run on proprietary hardware. Network functions are playing an increasingly important role in modern networks, ranging from mobile networks, enterprise networks, to data-center networks. Network functions can improve the performance of a network (e.g., optimizers for Wide Area Networks, web proxies and video transcoders, or load balancers), enhance network security, or monitor network traffic. The need to perform additional processing of packets of a data flow in a network before the packets are delivered to a destination has become an integral part of providing Internet services. Such network functions include performing the modification of packet headers, discarding packets, collection of statistical information, or even modification of the payload (e.g., optimization and compression).

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a block diagram of an example of a management orchestrator for a content-centric network in a 6G network according to some examples of the present disclosure.
- (2) FIG. 2 is a block diagram of another example of a management orchestrator for a content-centric network in a 6G network according to some examples of the present disclosure.
- (3) FIG. 3 is a flowchart of a process for using a management orchestrator for a content-centric network in a 6G network according to some examples of the present disclosure.

DETAILED DESCRIPTION

(4) In recent years, extensive effort has been made to evolve and mature network functions virtualization (NFV) technologies over Internet Protocol (IP) networks. In IP networks, network functions have to be resident on the path of a flow for a packet. This may cause network traffic (such as packets) to be deviated from its “natural” IP shortest path to be instead routed through the network functions. Current routing protocols deployed in IP networks constrain how packets can be deviated from the shortest path. Additionally, network functions in IP networks are managed via a central controller, which can lead to computing performance penalties and scalability limitations. Thus, network functions used in IP networks are unable to take full advantage of the great flexibility offered by NFV. IP networks deliver packets to a particular destination based on an address in a header of the packet. In contrast, endpoints in content-centric networks (CCNs) communicate based on named data instead of IP addresses. CCNs are expected to be a fundamental construct of 6G networks, but little or no attempts have been made to incorporate network

functions into CCNs.

(5) Some examples of the present disclosure overcome one or more of the abovementioned problems by implementing a management orchestrator for network functions for CCNs within 6G networks. The management orchestrator can implement and use network services and network functions, such as Virtual Network Functions (VNFs) or Cloud Native Functions (CNFs). By using the Named Function Networking (NFN) paradigm, the management orchestrator can distribute network functions and services through network nodes via named functions. NFN decouples network traffic from location of data. For example, in NFN, named functions are distributed throughout the network and are called using their name, rather than their IP address. Client devices ask for a service from a network function by name. The management orchestrator can then automatically route the request to the closest network node that supports the named function for the network function. No registry or lookup is required, reducing latency in the network.

(6) Named functions are distinct from network functions. For example, “network function” is a generic term that refers to hardware or software that implements network services, and is typically implemented through virtual network functions. On the other hand, named functions extend the capability of a CCN from simply resolving data access by name to also supporting function definition by name. Network functions can be implemented through named functions distributed throughout network nodes in the CCN by the management orchestrator.

(7) The use of NFN can provide the flexibility to dynamically place network functions in the 6G network as needed and without the need of a central controller. The management orchestrator can provide a scalable and flexible framework that can perform automated deployment, management, monitoring, optimization, and lifecycle management of named functions over a CCN in a 6G network. Using the management orchestrator to manage named functions and their network functions can reduce computational resources, power usage, response times, and inter-node traffic of the 6G network. Network functions can therefore be deployed over commodity hardware, without the need of a central controller for performing service chaining.

(8) Additionally, in-network caching by network nodes can be performed. For example, a client device may issue an interest request for a particular network function. The management orchestrator may route the interest request through a first network node and then a second network node. The network function can be deployed on the second network node, and can fulfill the interest request by generating and transmitting a data packet back to the client device. The data packet can be transmitted from the second network node to the first network node, and from the first network node to the client device. The data packet can be cached by the first network node and the second network node. Later, a client device (e.g., the original client device or a separate client device) can issue the same interest request. Although the network function is deployed on the second network node, either the first network node or the second network node may fulfill the interest request using the cached data packet. In-network caching can speed up distribution of data between network nodes and client devices, and can also reduce traffic load on the server side.

(9) Illustrative examples are given to introduce the reader to the general subject matter discussed herein and are not intended to limit the scope of the disclosed concepts. The following sections describe various additional features and examples with reference to the drawings in which like numerals indicate like elements, and directional descriptions are used to describe the illustrative aspects, but, like the illustrative aspects, should not be used to limit the present disclosure.

(10) FIG. 1 is a block diagram of an example of a management orchestrator for a content-centric network (CCN) **102** in a 6G network **100** according to some examples of the present disclosure. The 6G network **100** can include a CCN **102** that is executed by hardware **106** that includes one or more network nodes **108a-b**. Examples of the network nodes **108a-b** can include routers, sensors, controllers, switches, modems, or other suitable node devices. The network nodes **108a-b** can deploy cloud named functions **114** requested by a client device **110**. Examples of the client device can include laptop computers, desktop computers, servers, mobile phones, tablets, or the like.

(11) The cloud named functions **114** can implement network functions **118** for the 6G network **100**, such as virtualized routers, firewalls, Wide Area Network (WAN) optimization, or the like. The network functions **118** can be virtual network functions or cloud native functions. The cloud named functions **114** are deployed and managed by the management orchestrator **104**. For example, the management orchestrator **104** can allocate hardware **106**, such as a particular network node **108**, for placing or configuring cloud named functions **114** in response to a request **112** from the client device **110**. One or more cloud named functions **114** can then be used to execute a network function **118**. In some examples, the management orchestrator **104** can chain cloud named functions **114** together, such as a first named function **116a** to a second named function **116b**, to implement a single network function **118**. The first named function **116a** and the second named function **116b** can be configured on a single network node, such as the second network node **108b**, or across multiple network nodes **108a-b**.

(12) The management orchestrator **104** can dynamically place cloud named functions **114** across the CCN **102** such that latency for the CCN **102** can be minimized. Additionally, the management orchestrator **104** can place cloud named functions **114** to be on-path for network flow of data packets **128**. This introduces minimal inference to network traffic and obviates the need for complicated forwarding rules in routers. After deployment of the cloud named functions **114**, the management orchestrator **104** can upgrade, release, reclaim hardware **106**, and perform any other lifecycle management operations with respect to the cloud named functions **114**.

(13) Rather than being called via their location on one of the network nodes **108a-b**, the cloud named functions **114** can be called by their name. For example, the client device **110** can transmit an interest request **122** for a data packet **128** from a network function **118** in the CCN **102** to the management orchestrator **104**. The interest request **122** can call for the network function by its content name **126**. The management orchestrator **104** can direct the interest request **122** to the closest network node, such as the first network node **108a**. The first network node **108a** may identify that the first network node **108a** does not execute the network function **118**. In response, the first network node **108a** can then identify another nearby network node that may execute the network function **118**. For example, the first network node **108a** may identify, based on the content name **126**, that the second network node **108b** may execute the network function **118**. Therefore, the first network node **108a** can transmit the interest request **122** to the second network node **108b**.

(14) In examples where the network function **118** is not deployed on the second network node **108b**, the second network node **108b** can transmit the interest request **122** to another network node, and the process can continue until the proper network node receives the interest request **122**. In other examples, the second network node **108b** can identify that the network function **118** is deployed on the second network node **108b** based on the content name **126**. The network function **118** can be implemented on the second network node **108b** via chained named functions **116a-b** having the content name **126**. The named functions **116a-b** can cause the network function **118** to fulfill the interest request **122**, thereby generating a data packet **128** for the client device **110**. The data packet **128** can then be transmitted back to the client device **110** in a reverse of the pathway **124** that the interest request **122** travelled to the second network node **108b**. For example, the interest request **122** was transmitted from the client device **110**, to the first network node **108a**, and then to the second network node **108b**. The data packet **128** can be transmitted on a reverse pathway from the second network node **108b**, to the first network node **108a**, and then to the client device **110**.

(15) In some examples, the data packet **128** may be cached by the network nodes **108a-b** as the data packet **128** is transmitted to the client device **110**. For example, after generating the data packet **128**, the second network node **108b** can store a cached data packet **129** for the interest request **122** and corresponding data packet **128**. Additionally, the first network node **108a** can also store the cached data packet **129** in response to receiving the data packet **128** for transmission to the client device **110**. Because the network nodes **108a-b** store the cached data packet **129**, future

identical interest requests for the network function **118** can be fulfilled using the cached data packet **129** in any network node **108** that first receives the interest request **122**. For example, the client device **110** may send a subsequent interest request **122** to the management orchestrator **104** that is identical to the original interest request **122**. The management orchestrator **104** can route the subsequent interest request **122** to the first network node **108a**. The first network node **108a** can fulfill the interest request **122** and generate the data packet **128** using the cached data packet **129**. Thus, the interest request **122** may not be transmitted to the second network node **108b** at all, and the network function **118** may not be needed to generate the data packet **128**. This can significantly reduce latency in the CCN **102**.

(16) Although FIG. **1** depicts a certain number and arrangement of components, this is for illustrative purposes and intended to be non-limiting. Other examples may include more components, fewer components, different components, or a different arrangement of the components shown in FIG. **1**. For example, although a single client device **110** is depicted as transmitting a request **112** for a new network function **118** and transmitting an interest request **122** for the data packet **128**, the request **112** and the interest request **122** may be transmitted by two separate client devices. Additionally, although the management orchestrator **103** for the CCN **102** is described as being within a 6G network, the components described herein may be implemented any subsequent generation of mobile network, such as 7G or 8G networks.

(17) FIG. **2** is a block diagram of another example of a management orchestrator **208** for a content-centric network **201** in a 6G network **200** according to some examples of the present disclosure. The 6G network **200** includes a processing device **202** communicatively coupled to a memory **204**. The processing device **202** can include one processing device or multiple processing devices. Non-limiting examples of the processing device **202** include a Field-Programmable Gate Array (FPGA), an application-specific integrated circuit (ASIC), a microprocessor, etc. The processing device **202** can execute instructions **206** stored in the memory **204** to perform the operations. In some examples, the instructions **206** can include processor-specific instructions generated by a compiler or an interpreter from code written in any suitable computer-programming language, such as C, C++, C #, etc.

(18) Memory **204** can include one memory device or multiple memory devices. The memory **204** can be non-volatile and may include any type of memory device that retains stored information when powered off. Non-limiting examples of the memory **204** include electrically erasable and programmable read-only memory (EEPROM), flash memory, or any other type of non-volatile memory. At least some of the memory **204** can include a non-transitory computer-readable medium from which the processing device **202** can read instructions **206**. A computer-readable medium can include electronic, optical, magnetic, or other storage devices capable of providing the processing device **202** with computer-readable instructions **206** or other program code. Examples of a computer-readable medium can include magnetic disks, memory chips, ROM, random-access memory RAM, an ASIC, a configured processor, optical storage, or any other medium from which a computer processor can read instructions **206**.

(19) The processing device **202** can execute instructions **206** to execute the management orchestrator **208** for the 6G network **200**. For example, the management orchestrator **208** can receive, from a client device **210**, a request **212** for a network function **218** in a content-centric network **201** executed by a plurality of network nodes **214** in the 6G network **200**. The processing device **202** can identify a particular network node **220** of the plurality of network nodes **214** usable for executing the network function **218** in response to receiving the request **212** for the network function **218**. Then, the processing device **202** can automatically deploy a named function **216** in the particular network node **220**. The processing device **202** can deploy the network function **218** for the client device **210** in the content-centric network **201** in the 6G network **200** using the named function **216**.

(20) FIG. **3** is a flowchart of a process for using a management orchestrator **208** for a content-

centric network **201** in a 6G network **200** according to some examples of the present disclosure. FIG. **3** is described with references to components in FIGS. **1-2**. Other examples can include more steps, fewer steps, different steps, or a different order of the steps than is depicted in FIG. **3**.

(21) At step **302**, the process **300** involves receiving, by the processing device **202** and from a client device **210**, a request **212** for a network function **218** in a content-centric network **201** executed by a plurality of network nodes **214** in a 6G network **200**. For example, the client device **210** may transmit the request **212** for a new network function **218** that is a firewall for data packets received by the client device **210**. The request **212** can be received by the management orchestrator **208**, which manages the plurality of network nodes **214** and any functions executing thereon.

(22) At step **304**, the process **300** involves, in response to receiving the request **212** for the network function **218**, identifying, by the processing device **202**, a particular network node **220** of the plurality of network nodes **214** usable for executing the network function **218**. For example, the processing device **202** can execute the management orchestrator **208** to identify a particular network node **220** that has available hardware and software resources necessary for executing a firewall for the client device **210**. In some examples, the management orchestrator **208** may identify a particular network node **220** that is relatively physically close to the client device **210**. This is because nodes that are closer to the client device **210** may cause less latency in the content-centric network **201** when executing the network function **218** for the client device **210**. The management orchestrator **208** may also determine the particular network node **220** based on a data packet flow for the client device **210**. For example, if data packets received by the client device originate from a first network node, travel to a second network node, and then travel to the client device, the management orchestrator **208** may identify the second network node as the particular node. In this way, data packets that will be inspected by the firewall will not be rerouted off of the typical data packet flow if the network function is deployed by the second network node.

(23) At step **306**, the process **300** involves automatically deploying, by the processing device **202**, a named function **216** via the particular network node **220**. The processing device **202** can execute the management orchestrator **208** to automatically deploy the named function **216** in response to identifying the particular network node **220**. The named function **216** is a function or service that can be called by name, rather than address or location. For example, the client device **210** may interact with the named function **216** by sending an interest request **122** to the management orchestrator **208** for the “firewall.” The management orchestrator **208** can direct the interest request **122** to a first network node that may or may not be executing the firewall. If the first network node is the particular network node **220** executing the firewall, the first network node can fulfill the interest request **122**. If the first network node is not executing the firewall, the first network node can transmit the interest request **122** to another nearby network node. This can continue until the interest request **122** is received by the particular network node **220** that is executing the network function **218** called “firewall.”

(24) In some examples, the processing device **202** can execute the management orchestrator **208** to automatically deploy more than one named function **216**. The management orchestrator **208** may do so when multiple named functions are needed to execute the network function **218** requested by the client device **210**. For example, the request **212** for a network function **218** from the client device **210** for a firewall may involve a firewall function for data packets from both directions. In such an example, the management orchestrator **208** may automatically deploy a first named function **116a** that is a firewall that can inspect data packets transmitted by the client device **210** and a second named function **116b** that is a firewall that inspects data packets received by the client device **210**. The first named function **116a** and the second named function **116b** may each be automatically deployed on the particular network node **220**. The management orchestrator **208** can then chain the first named function **116a** to the second named function **116b**.

(25) In some examples, instead of automatically deploying a new named function **216**, the management orchestrator **208** can identify existing named functions **216** that can execute the

network function **218** requested by the client device **210**. In one example, the management orchestrator **208** may identify an existing named function **216** executing a network function **218** that is a firewall, that fulfills the request **212** transmitted by the client device **210**. The management orchestrator **208** can then assign the named function **216** to the client device **210** for the firewall. In another example, the management orchestrator **208** may identify at least two named functions deployed on the particular network node **220** that can be used to execute the network function **218**. The management orchestrator **208** can then chain the at least two named functions together. The chained named functions can be used to fulfill the request **212** from the client device **210**.

(26) At step **308**, the process **300** involves executing, by the processing device **202** and using the named function **216**, the network function **218** for the client device **210** in the content-centric network **201** within the 6G network **200**. The named function **216** can implement the network function **218** requested by the client device **210**. For example, interest requests for the network function **218** can be transmitted using the name of the named function (e.g., “firewall”). In examples where the network function **218** is executed by chained named functions **116a-b**, the network function **218** may be called by any of the names of the chained named functions **116-ab**. The operation performed by the network function **218** may depend on the name of the named function **116** that is called. For example, a data packet received by the particular network node **220** may have an interest request **122** called “firewall—incoming.” This can indicate that the second named function **116b**, which is a firewall handling data packets received by the client device **210**, should execute the network function **218** to handle the interest request **122**. The second named function **116b** can execute the network function **218** to inspect the data packet and then to transmit the inspected data packet to the client device **210**.

(27) The foregoing description of certain examples, including illustrated examples, has been presented only for the purpose of illustration and description and is not intended to be exhaustive or to limit the disclosure to the precise forms disclosed. Numerous modifications, adaptations, and uses thereof will be apparent to those skilled in the art without departing from the scope of the disclosure.

Claims

1. A system comprising: a processing device; and a memory comprising instructions for causing the processing device to execute a management orchestrator for a 6G network to: receive, from a client device, a request for a network function in a content-centric network executed by a plurality of network nodes in the 6G network; in response to receiving the request for the network function, identify a particular network node of the plurality of network nodes usable for executing the network function; automatically deploy a named function via the particular network node; and execute, using the named function, the network function for the client device in the content-centric network within the 6G network.
2. The system of claim 1, wherein the memory is further executable by the processing device for causing the processing device to, subsequent to executing the network function for the client device: receive, at a first network node of the plurality of network nodes, an interest request for the network function from the client device, the interest request including a content name; identify, based on the content name, that the first network node does not execute the network function; in response to identifying that the first network node does not execute the network function, identify, based on the content name, a second network node of the plurality of network nodes to receive the interest request; and transmit the interest request to the second network node of the plurality of network nodes.
3. The system of claim 2, wherein the memory is further executable by the processing device for causing the processing device to, in response to transmitting the interest request to the second network node: identify, based on the content name, that the second network node executes the

network function, the network function being executed by the named function associated with the content name; fulfill, by the named function, the interest request for the network function to generate a data packet; and transmit the data packet to the client device.

4. The system of claim 3, wherein the memory is further executable by the processing device for causing the processing device to transmit the data packet to the client device by: transmitting the data packet from the second network node to the first network node; in response to transmitting the data packet from the second network node to the first network node, caching, by the first network node, the data packet; and transmitting the data packet from the first network node to the client device.

5. The system of claim 4, wherein the memory is further executable by the processing device for causing the processing device to: receive, by the first network node, a subsequent interest request for the network function; and in response to receiving the subsequent interest request, fulfill, by the first network node, the subsequent interest request using the cached data packet.

6. The system of claim 1, wherein the memory is further executable by the processing device for causing the management orchestrator to: identify at least two named functions deployed on the particular network node and usable for executing the network function; chain the at least two named functions; and execute the network function using the at least two named functions that are chained.

7. The system of claim 1, wherein the network function comprises a virtual network function or a cloud native function.

8. A method comprising: receiving, by a processing device executing a management orchestrator for a 6G network and from a client device, a request for a network function in a content-centric network executed by a plurality of network nodes in the 6G network; in response to receiving the request for the network function, identifying, by the management orchestrator, a particular network node of the plurality of network nodes usable for executing the network function; automatically deploying, by the management orchestrator, a named function via the particular network node; and executing, by the management orchestrator and using the named function, the network function for the client device in the content-centric network within the 6G network.

9. The method of claim 8, further comprising, subsequent to executing the network function for the client device: receiving, at a first network node of the plurality of network nodes, an interest request for the network function from the client device, the interest request including a content name; identifying, based on the content name, that the first network node does not execute the network function; in response to identifying that the first network node does not execute the network function, identifying, based on the content name, a second network node of the plurality of network nodes to receive the interest request; and transmitting the interest request to the second network node of the plurality of network nodes.

10. The method of claim 9, further comprising, in response to transmitting the interest request to the second network node: identifying, based on the content name, that the second network node executes the network function, the network function being executed by the named function associated with the content name; fulfilling, by the named function, the interest request for the network function to generate a data packet; and transmitting the data packet to the client device.

11. The method of claim 10, wherein transmitting the data packet to the client device further comprises: transmitting the data packet from the second network node to the first network node; in response to transmitting the data packet from the second network node to the first network node, caching, by the first network node, the data packet; and transmitting the data packet from the first network node to the client device.

12. The method of claim 11, further comprising: receiving, by the first network node, a subsequent interest request for the network function; and in response to receiving the subsequent interest request, fulfilling, by the first network node, the subsequent interest request using the cached data packet.

13. The method of claim 8, further comprising: identifying at least two named functions deployed on the particular network node and usable for executing the network function; chaining the at least two named functions; and executing the network function using the at least two named functions that are chained.

14. The method of claim 8, wherein the network function comprises a virtual network function or a cloud native function.

15. A non-transitory computer-readable medium comprising program code that is executable by a processing device for causing a management orchestrator for a 6G network to: receive, from a client device, a request for a network function in a content-centric network executed by a plurality of network nodes in the 6G network; in response to receiving the request for the network function, identify a particular network node of the plurality of network nodes usable for executing the network function; automatically deploy a named function via the particular network node; and execute, using the named function, the network function for the client device in the content-centric network within the 6G network.

16. The non-transitory computer-readable medium of claim 15, further comprising program code that is executable by the processing device for causing the processing device to, subsequent to executing the network function for the client device: receive, at a first network node of the plurality of network nodes, an interest request for the network function from the client device, the interest request including a content name; identify, based on the content name, that the first network node does not execute the network function; in response to identifying that the first network node does not execute the network function, identify, based on the content name, a second network node of the plurality of network nodes to receive the interest request; and transmit the interest request to the second network node of the plurality of network nodes.

17. The non-transitory computer-readable medium of claim 16, further comprising program code that is executable by the processing device for causing the processing device to, in response to transmitting the interest request to the second network node: identify, based on the content name, that the second network node executes the network function, the network function being executed by the named function associated with the content name; fulfill, by the named function, the interest request for the network function to generate a data packet; and transmit the data packet to the client device.

18. The non-transitory computer-readable medium of claim 17, further comprising program code is executable by the processing device for causing the processing device to transmit the data packet to the client device by: transmitting the data packet from the second network node to the first network node; in response to transmitting the data packet from the second network node to the first network node, caching, by the first network node, the data packet; and transmitting the data packet from the first network node to the client device.

19. The non-transitory computer-readable medium of claim 18, further comprising program code that is executable by the processing device for causing the processing device to: receive, by the first network node, a subsequent interest request for the network function; and in response to receiving the subsequent interest request, fulfill, by the first network node, the subsequent interest request using the cached data packet.

20. The non-transitory computer-readable medium of claim 15, further comprising program code that is executable by the processing device for causing the management orchestrator to: identify at least two named functions deployed on the particular network node and usable for executing the network function; chain the at least two named functions; and execute the network function using the at least two named functions that are chained.
