

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent
Kind Code
Date of Patent
Inventor(s)

12408082
B2
September 02, 2025
Lu; Kun et al.

Reducing network traffic associated with a throughput intensive communication over a wireless telecommunication network

Abstract

The system determines that an application running user equipment (UE) is requesting a throughput intensive communication over a network. The throughput intensive communication can require a predetermined downlink and uplink throughput. The system sends a first indication to the network, specifying to a base station of the network that the UE is requesting the throughput intensive communication. The base station determines whether it can provide the downlink throughput and the uplink throughput to the UE. Upon determining that the base station cannot provide the downlink or the uplink throughput to the UE, the base station sends a first message to the UE, indicating that the throughput intensive communication is of low quality. Upon receiving the first message, the UE waits for a predetermined criterion to be satisfied before attempting to engage in the throughput intensive communication, thereby reducing network traffic by eschewing sending repeated requests for the throughput intensive communication.

Inventors: Lu; Kun (Bellevue, WA), Gronstad; Egil (Bellevue, WA), Liu; Jun (Sammamish, WA), Zhang; Lin (Overland Park, KS)

Applicant: T-Mobile USA, Inc. (Bellevue, WA)

Family ID: 90470354

Assignee: T-Mobile USA, Inc. (Bellevue, WA)

Appl. No.: 17/958010

Filed: September 30, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20240114397 A1	Apr. 04, 2024

Publication Classification

Int. Cl.: H04W28/20 (20090101); H04W24/10 (20090101); H04W64/00 (20090101);
H04W76/10 (20180101)

U.S. Cl.:

CPC H04W28/20 (20130101); H04W24/10 (20130101); H04W64/00 (20130101);
H04W76/10 (20180201);

Field of Classification Search

CPC: H04W (28/20); H04W (76/10); H04W (24/10); H04W (64/00)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6996072	12/2005	Minborg	N/A	N/A
7286841	12/2006	Sun et al.	N/A	N/A
7299069	12/2006	Claussen	N/A	N/A
8184597	12/2011	Englund et al.	N/A	N/A
8289954	12/2011	Tenny et al.	N/A	N/A
8312337	12/2011	Park et al.	N/A	N/A
8331912	12/2011	Lundy et al.	N/A	N/A
8358629	12/2012	Grilli et al.	N/A	N/A
8493353	12/2012	Blanchflower et al.	N/A	N/A
8976677	12/2014	Novak et al.	N/A	N/A
9137844	12/2014	Kitazoe	N/A	N/A
9210618	12/2014	Chen et al.	N/A	N/A
9392533	12/2015	Vivanco et al.	N/A	N/A
9585037	12/2016	Davari et al.	N/A	N/A
9591679	12/2016	Bontu et al.	N/A	N/A
9609510	12/2016	Raleigh et al.	N/A	N/A
9635530	12/2016	Ayyalasomayajula et al.	N/A	N/A
9642147	12/2016	Barbieri et al.	N/A	N/A
9661602	12/2016	Annamalai et al.	N/A	N/A
9723651	12/2016	Ozturk et al.	N/A	N/A
9749884	12/2016	Cummings	N/A	N/A
9807651	12/2016	Mujtaba et al.	N/A	N/A
9860781	12/2017	Cui et al.	N/A	N/A
9876903	12/2017	Yerrabommanahalli et al.	N/A	N/A
9883384	12/2017	Lee et al.	N/A	N/A
9900443	12/2017	Pattabiraman et al.	N/A	N/A
9906996	12/2017	Lou et al.	N/A	N/A
9949314	12/2017	Zhao et al.	N/A	N/A
9967794	12/2017	Park et al.	N/A	N/A
10039013	12/2017	Periyasamy et al.	N/A	N/A
10111135	12/2017	Schwarzbauer et al.	N/A	N/A

10154470	12/2017	Edge et al.	N/A	N/A
10244448	12/2018	Chong et al.	N/A	N/A
10292055	12/2018	Carpenter et al.	N/A	N/A
10299211	12/2018	Shi et al.	N/A	N/A
10785155	12/2019	Damola et al.	N/A	N/A
10827338	12/2019	Bodapotula et al.	N/A	N/A
10863556	12/2019	Lau et al.	N/A	N/A
10999854	12/2020	Fu et al.	N/A	N/A
11006293	12/2020	Singh et al.	N/A	N/A
11019528	12/2020	Yang et al.	N/A	N/A
11026121	12/2020	Shih et al.	N/A	N/A
11038741	12/2020	Machou et al.	N/A	N/A
11044786	12/2020	Kuppelur et al.	N/A	N/A
11122471	12/2020	Chiang et al.	N/A	N/A
11178586	12/2020	Luo et al.	N/A	N/A
11202212	12/2020	Karanam	N/A	N/A
11206589	12/2020	Chen et al.	N/A	N/A
11272415	12/2021	Araujo et al.	N/A	N/A
11297513	12/2021	Agarwal et al.	N/A	N/A
11330653	12/2021	Paladugu et al.	N/A	N/A
11356857	12/2021	Vivanco et al.	N/A	N/A
11405971	12/2021	Jain et al.	N/A	N/A
11425659	12/2021	He et al.	N/A	N/A
11432201	12/2021	Kwok et al.	N/A	N/A
2005/0233733	12/2004	Roundtree et al.	N/A	N/A
2006/0142020	12/2005	Mueckenheim et al.	N/A	N/A
2006/0142021	12/2005	Mueckenheim et al.	N/A	N/A
2012/0020393	12/2011	Patil et al.	N/A	N/A
2012/0295617	12/2011	Anchan et al.	N/A	N/A
2013/0196647	12/2012	Raleigh et al.	N/A	N/A
2013/0223294	12/2012	Karjalainen et al.	N/A	N/A
2014/0254398	12/2013	Li	370/252	H04W 28/0846
2018/0227902	12/2017	Gholmieh	N/A	H04B 7/0413
2020/0187014	12/2019	Sevindik	N/A	N/A
2020/0322970	12/2019	Duet et al.	N/A	N/A
2020/0351792	12/2019	Ghelichi et al.	N/A	N/A
2021/0067945	12/2020	Liu et al.	N/A	N/A
2021/0250828	12/2020	Vaidya et al.	N/A	N/A
2021/0282125	12/2020	Pezeshki et al.	N/A	N/A
2021/0377866	12/2020	Kim et al.	N/A	N/A
2022/0167442	12/2021	Dong et al.	N/A	N/A
2022/0232605	12/2021	Kim et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
108605382	12/2017	CN	N/A
105376293	12/2019	CN	N/A
113196700	12/2020	CN	N/A
2070381	12/2011	EP	N/A

2801065	12/2013	EP	N/A
2813039	12/2013	EP	N/A
2826269	12/2014	EP	N/A
3209043	12/2016	EP	N/A
3308528	12/2017	EP	N/A
2795983	12/2018	EP	N/A
3501204	12/2018	EP	N/A
3180907	12/2019	EP	N/A
3840524	12/2020	EP	N/A
5528965	12/2013	JP	N/A
5922475	12/2015	JP	N/A
6606431	12/2018	JP	N/A
20200086729	12/2019	KR	N/A
20210019103	12/2020	KR	N/A
102412510	12/2021	KR	N/A
2011016173	12/2010	WO	N/A
2014116983	12/2013	WO	N/A
2015112108	12/2014	WO	N/A
2015155411	12/2014	WO	N/A
2015161519	12/2014	WO	N/A
2017133610	12/2016	WO	N/A
2018104834	12/2017	WO	N/A
2020148658	12/2019	WO	N/A
2020185949	12/2019	WO	N/A
2021162927	12/2020	WO	N/A
2021163394	12/2020	WO	N/A
2022152620	12/2021	WO	N/A
2022155431	12/2021	WO	N/A

Primary Examiner: Cosme; Natasha W

Attorney, Agent or Firm: Perkins Coie LLP

Background/Summary

BACKGROUND

(1) With the 5G wireless telecommunication network in full development and operational in over 72 countries worldwide in March 2022, extended reality (XR) powered by 5G is expected to become a popular application, which can change the way people are surfing the Internet—namely, from 2D surfing to 3D surfing. According to predictions, there will be over 100 million XR users by 2025 and 1 billion by 2030. XR applications are throughput intensive, and the 5G network may not be able to provide the needed bandwidth at all times. However, the UE might not know the status of the network and can keep trying to access XR services, which can congest the network and result in even worse user experience.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) Detailed descriptions of implementations of the present invention will be described and explained through the use of the accompanying drawings.
- (2) FIG. 1 is a diagram that illustrates a wireless telecommunication network in which aspects of the disclosed technology are incorporated.
- (3) FIG. 2 is a block diagram that illustrates an architecture including 5G core network functions (NFs) that can implement aspects of the present technology.
- (4) FIG. 3 shows different types of artificial realities.
- (5) FIG. 4 shows media streaming within the 5G network.
- (6) FIG. 5 shows extended reality communication within the 5G network.
- (7) FIG. 6 shows communication between UE and the base station.
- (8) FIG. 7 shows a single stream download extended reality communication model.
- (9) FIG. 8 is a flowchart of a method to reduce network traffic associated with throughput intensive communication over a 5G or higher generation wireless telecommunication network.
- (10) FIG. 9 is a flowchart of steps performed by a system to reduce network traffic associated with throughput intensive communication over a wireless telecommunication network.
- (11) FIG. 10 is a block diagram that illustrates an example of a computer system 1000 in which at least some operations described herein can be implemented.
- (12) The technologies described herein will become more apparent to those skilled in the art from studying the Detailed Description in conjunction with the drawings. Embodiments or implementations describing aspects of the invention are illustrated by way of example, and the same references can indicate similar elements. While the drawings depict various implementations for the purpose of illustration, those skilled in the art will recognize that alternative implementations can be employed without departing from the principles of the present technologies. Accordingly, while specific implementations are shown in the drawings, the technology is amenable to various modifications.

DETAILED DESCRIPTION

- (13) Disclosed here is a system and method to reduce network traffic associated with an extended reality communication over a 5G or higher generation wireless telecommunication network (“5G+ network”). The system can determine that an application associated with a mobile device is requesting an extended reality communication over the 5G or higher generation wireless telecommunication network. The extended reality communication includes real-and-virtual combined environments and human-machine interactions generated by computer technology and wearables. The desired downlink throughput associated with the extended reality communication is approximately above 20 megabits per second (Mbps). The desired uplink throughput associated with extended reality communication is approximately up to 10 Mbps.
- (14) The mobile device sends a first indication to the 5G+ wireless telecommunication network, requesting extended reality communication from a base station that forms part of the 5G+ network. The base station determines whether it can provide the needed downlink throughput and uplink throughput to the mobile device. The base station can make this determination based on a location of the UE, RF associated with the UE, number of UEs connected to the base station, available base station resources, buffer estimation, hybrid automatic repeat request (hybrid ARQ or HARQ) feedback, etc., as described below. Upon determining that the base station cannot provide the desired downlink and uplink throughput to the mobile device, the base station can send a message to the mobile device indicating that the extended reality communication is not available or will be of low-quality.
- (15) Upon receiving the message, the mobile device can wait for another message from the 5G+ network indicating that the extended reality communication is available, thereby reducing network traffic associated with an extended reality communication by eschewing sending repeated requests

for the extended reality communication.

(16) The description and associated drawings are illustrative examples and are not to be construed as limiting. This disclosure provides certain details for a thorough understanding and enabling description of these examples. One skilled in the relevant technology will understand, however, that the invention can be practiced without many of these details. Likewise, one skilled in the relevant technology will understand that the invention can include well-known structures or features that are not shown or described in detail, to avoid unnecessarily obscuring the descriptions of examples.

(17) Wireless Communications System

(18) FIG. 1 is a diagram that illustrates a wireless telecommunication network **100** (“network **100**”) in which aspects of the disclosed technology are incorporated. The network **100** includes base stations **102-1** through **102-4** (also referred to individually as “base station **102**” or collectively as “base stations **102**”). A base station is a type of network access node (NAN) that can also be referred to as a cell site, a base transceiver station, or a radio base station. The network **100** can include any combination of NANs including an access point, radio transceiver, gNodeB (gNB), NodeB, eNodeB (eNB), Home NodeB or Home eNodeB, or the like. In addition to being a wireless wide area network (WWAN) base station, a NAN can be a wireless local area network (WLAN) access point, such as an Institute of Electrical and Electronics Engineers (IEEE) 802.11 access point.

(19) The NANs of a network **100** formed by the network **100** also include wireless devices **104-1** through **104-7** (referred to individually as “wireless device **104**” or collectively as “wireless devices **104**”) and a core network **106**. The wireless devices **104-1** through **104-7** can correspond to or include network **100** entities capable of communication using various connectivity standards. For example, a 5G communication channel can use millimeter wave (mmW) access frequencies of 28 GHz or more. In some implementations, the wireless device **104** can operatively couple to a base station **102** over a long-term evolution/long-term evolution-advanced (LTE/LTE-A) communication channel, which is referred to as a 4G communication channel.

(20) The core network **106** provides, manages, and controls security services, user authentication, access authorization, tracking, Internet Protocol (IP) connectivity, and other access, routing, or mobility functions. The base stations **102** interface with the core network **106** through a first set of backhaul links (e.g., S1 interfaces) and can perform radio configuration and scheduling for communication with the wireless devices **104** or can operate under the control of a base station controller (not shown). In some examples, the base stations **102** can communicate with each other, either directly or indirectly (e.g., through the core network **106**), over a second set of backhaul links **110-1** through **110-3** (e.g., X1 interfaces), which can be wired or wireless communication links.

(21) The base stations **102** can wirelessly communicate with the wireless devices **104** via one or more base station antennas. The cell sites can provide communication coverage for geographic coverage areas **112-1** through **112-4** (also referred to individually as “coverage area **112**” or collectively as “coverage areas **112**”). The geographic coverage area **112** for a base station **102** can be divided into sectors making up only a portion of the coverage area (not shown). The network **100** can include base stations of different types (e.g., macro and/or small cell base stations). In some implementations, there can be overlapping geographic coverage areas **112** for different service environments (e.g., Internet-of-Things (IoT), mobile broadband (MBB), vehicle-to-everything (V2X), machine-to-machine (M2M), machine-to-everything (M2X), ultra-reliable low-latency communication (URLLC), machine-type communication (MTC), etc.).

(22) The network **100** can include a 5G network **100** and/or an LTE/LTE-A or other network. In an LTE/LTE-A network, the term eNB is used to describe the base stations **102**, and in 5G new radio (NR) networks, the term gNBs is used to describe the base stations **102** that can include mmW communications. The network **100** can thus form a heterogeneous network **100** in which different types of base stations provide coverage for various geographic regions. For example, each base

station **102** can provide communication coverage for a macro cell, a small cell, and/or other types of cells. As used herein, the term “cell” can relate to a base station, a carrier or component carrier associated with the base station, or a coverage area (e.g., sector) of a carrier or base station, depending on context.

(23) A macro cell generally covers a relatively large geographic area (e.g., several kilometers in radius) and can allow access by wireless devices that have service subscriptions with a wireless network **100** service provider. As indicated earlier, a small cell is a lower-powered base station, as compared to a macro cell, and can operate in the same or different (e.g., licensed, unlicensed) frequency bands as macro cells. Examples of small cells include pico cells, femto cells, and micro cells. In general, a pico cell can cover a relatively smaller geographic area and can allow unrestricted access by wireless devices that have service subscriptions with the network **100** provider. A femto cell covers a relatively smaller geographic area (e.g., a home) and can provide restricted access by wireless devices having an association with the femto unit (e.g., wireless devices in a closed subscriber group (CSG), wireless devices for users in the home). A base station can support one or multiple (e.g., two, three, four, and the like) cells (e.g., component carriers). All fixed transceivers noted herein that can provide access to the network **100** are NANs, including small cells.

(24) The communication networks that accommodate various disclosed examples can be packet-based networks that operate according to a layered protocol stack. In the user plane, communications at the bearer or Packet Data Convergence Protocol (PDCP) layer can be IP-based. A Radio Link Control (RLC) layer then performs packet segmentation and reassembly to communicate over logical channels. A Medium Access Control (MAC) layer can perform priority handling and multiplexing of logical channels into transport channels. The MAC layer can also use Hybrid ARQ (HARQ) to provide retransmission at the MAC layer, to improve link efficiency. In the control plane, the Radio Resource Control (RRC) protocol layer provides establishment, configuration, and maintenance of an RRC connection between a wireless device **104** and the base stations **102** or core network **106** supporting radio bearers for the user plane data. At the physical (PHY) layer, the transport channels are mapped to physical channels.

(25) Wireless devices can be integrated with or embedded in other devices. As illustrated, the wireless devices **104** are distributed throughout the system **100**, where each wireless device **104** can be stationary or mobile. For example, wireless devices can include handheld mobile devices **104-1** and **104-2** (e.g., smartphones, portable hotspots, tablets, etc.); laptops **104-3**; wearables **104-4**; drones **104-5**; vehicles with wireless connectivity **104-6**; head-mounted displays with wireless augmented reality/virtual reality (ARNR) connectivity **104-7**; portable gaming consoles; wireless routers, gateways, modems, and other fixed-wireless access devices; wirelessly connected sensors that provides data to a remote server over a network; IoT devices such as wirelessly connected smart home appliances, etc.

(26) A wireless device (e.g., wireless devices **104-1**, **104-2**, **104-3**, **104-4**, **104-5**, **104-6**, and **104-7**) can be referred to as user equipment (UE), customer premise equipment (CPE), a mobile station, a subscriber station, a mobile unit, a subscriber unit, a wireless unit, a remote unit, a handheld mobile device, a remote device, a mobile subscriber station, terminal equipment, an access terminal, a mobile terminal, a wireless terminal, a remote terminal, a handset, a mobile client, a client, or the like.

(27) A wireless device can communicate with various types of base stations and network **100** equipment at the edge of a network **100** including macro eNBs/gNBs, small cell eNBs/gNBs, relay base stations, and the like. A wireless device can also communicate with other wireless devices either within or outside the same coverage area of a base station via device-to-device (D2D) communications.

(28) The communication links **114-1** through **114-10** (also referred to individually as “communication link **114**” or collectively as “communication links **114**”) shown in network **100**

include uplink (UL) transmissions from a wireless device **104** to a base station **102**, and/or downlink (DL) transmissions from a base station **102** to a wireless device **104**. The downlink transmissions can also be called forward link transmissions while the uplink transmissions can also be called reverse link transmissions. Each communication link **114** includes one or more carriers, where each carrier can be a signal composed of multiple sub-carriers (e.g., waveform signals of different frequencies) modulated according to the various radio technologies. Each modulated signal can be sent on a different sub-carrier and carry control information (e.g., reference signals, control channels), overhead information, user data, etc. The communication links **114** can transmit bidirectional communications using frequency division duplex (FDD) (e.g., using paired spectrum resources) or time division duplex (TDD) operation (e.g., using unpaired spectrum resources). In some implementations, the communication links **114** include LTE and/or mmW communication links.

(29) In some implementations of the network **100**, the base stations **102** and/or the wireless devices **104** include multiple antennas for employing antenna diversity schemes to improve communication quality and reliability between base stations **102** and wireless devices **104**. Additionally or alternatively, the base stations **102** and/or the wireless devices **104** can employ multiple-input, multiple-output (MIMO) techniques that can take advantage of multi-path environments to transmit multiple spatial layers carrying the same or different coded data.

(30) In some examples, the network **100** implements 6G technologies including increased densification or diversification of network nodes. The network **100** can enable terrestrial and non-terrestrial transmissions. In this context, a Non-Terrestrial Network (NTN) is enabled by one or more satellites such as satellites **116-1** and **116-2** to deliver services anywhere and anytime and provide coverage in areas that are unreachable by any conventional Terrestrial Network (TN). A 6G implementation of the network **100** can support terahertz (THz) communications. This can support wireless applications that demand ultrahigh quality of service requirements and multi-terabits per second data transmission in the 6G and beyond era, such as terabit-per-second backhaul systems, ultrahigh-definition content streaming among mobile devices, AR/VR, and wireless high-bandwidth secure communications. In another example of 6G, the network **100** can implement a converged Radio Access Network (RAN) and Core architecture to achieve Control and User Plane Separation (CUPS) and achieve extremely low user plane latency. In yet another example of 6G, the network **100** can implement a converged Wi-Fi and Core architecture to increase and improve indoor coverage.

(31) 5G Core Network Functions

(32) FIG. 2 is a block diagram that illustrates an architecture **200** including 5G core network functions (NFs) that can implement aspects of the present technology. A wireless device **202** can access the 5G network through a NAN (e.g., gNB) of a RAN **204**. The NFs include an Authentication Server Function (AUSF) **206**, a Unified Data Management (UDM) **208**, an Access and Mobility management Function (AMF) **210**, a Policy Control Function (PCF) **212**, a Session Management Function (SMF) **214**, a User Plane Function (UPF) **216**, and a Charging Function (CHF) **218**.

(33) The interfaces N1 through N15 define communications and/or protocols between each NF as described in relevant standards. The UPF **216** is part of the user plane and the AMF **210**, SMF **214**, PCF **212**, AUSF **206**, and UDM **208** are part of the control plane. One or more UPFs can connect with one or more data networks (DNs) **220**. The UPF **216** can be deployed separately from control plane functions. The NFs of the control plane are modularized such that they can be scaled independently. As shown, each NF service exposes its functionality in a Service Based Architecture (SBA) through a Service Based Interface (SBI) **221** that uses HTTP/2. The SBA can include a Network Exposure Function (NEF) **222**, a NF Repository Function (NRF) **224**, a Network Slice Selection Function (NSSF) **226**, and other functions such as a Service Communication Proxy (SCP).

(34) The SBA can provide a complete service mesh with service discovery, load balancing, encryption, authentication, and authorization for interservice communications. The SBA employs a centralized discovery framework that leverages the NRF **224**, which maintains a record of available NF instances and supported services. The NRF **224** allows other NF instances to subscribe and be notified of registrations from NF instances of a given type. The NRF **224** supports service discovery by receipt of discovery requests from NF instances and, in response, details which NF instances support specific services.

(35) The NSSF **226** enables network slicing, which is a capability of 5G to bring a high degree of deployment flexibility and efficient resource utilization when deploying diverse network services and applications. A logical end-to-end (E2E) network slice has predetermined capabilities, traffic characteristics, service-level agreements, and includes the virtualized resources required to service the needs of a Mobile Virtual Network Operator (MVNO) or group of subscribers, including a dedicated UPF, SMF, and PCF. The wireless device **202** is associated with one or more network slices, which all use the same AMF. A Single Network Slice Selection Assistance Information (S-NSSAI) function operates to identify a network slice. Slice selection is triggered by the AMF, which receives a wireless device registration request. In response, the AMF retrieves permitted network slices from the UDM **208** and then requests an appropriate network slice of the NSSF **226**.

(36) The UDM **208** introduces a User Data Convergence (UDC) that separates a User Data Repository (UDR) for storing and managing subscriber information. As such, the UDM **208** can employ the UDC under 3GPP TS 22.101 to support a layered architecture that separates user data from application logic. The UDM **208** can include a stateful message store to hold information in local memory or can be stateless and store information externally in a database of the UDR. The stored data can include profile data for subscribers and/or other data that can be used for authentication purposes. Given a large number of wireless devices that can connect to a 5G network, the UDM **208** can contain voluminous amounts of data that is accessed for authentication. Thus, the UDM **208** is analogous to a Home Subscriber Server (HSS), to provide authentication credentials while being employed by the AMF **210** and SMF **214** to retrieve subscriber data and context.

(37) The PCF **212** can connect with one or more application functions (AFs) **228**. The PCF **212** supports a unified policy framework within the 5G infrastructure for governing network behavior. The PCF **212** accesses the subscription information required to make policy decisions from the UDM **208**, and then provides the appropriate policy rules to the control plane functions so that they can enforce them. The SCP (not shown) provides a highly distributed, multi-access edge compute cloud environment and a single point of entry for a cluster of network functions once they have been successfully discovered by the NRF **224**. This allows the SCP to become the delegated discovery point in a datacenter, offloading the NRF **224** from distributed service meshes that make-up a network operator's infrastructure. Together with the NRF **224**, the SCP forms the hierarchical 5G service mesh.

(38) The AMF **210** receives requests and handles connection and mobility management while forwarding session management requirements over the N11 interface to the SMF **214**. The AMF **210** determines that the SMF **214** is best suited to handle the connection request by querying the NRF **224**. That interface and the N11 interface between the AMF **210** and the SMF **214** assigned by the NRF **224**, use the SBI **221**. During session establishment or modification, the SMF **214** also interacts with the PCF **212** over the N7 interface and the subscriber profile information stored within the UDM **208**. Employing the SBI **221**, the PCF **212** provides the foundation of the policy framework which, along with the more typical Quality of Service (QoS) and charging rules, includes Network Slice selection, which is regulated by the NSSF **226**.

(39) Reducing Network Traffic Associated with a Throughput Intensive Communication Over a Wireless Telecommunication Network

(40) FIG. 3 shows different types of artificial realities. Virtual reality (VR) **310** is a rendered

version of a delivered visual and audio scene. The rendering is designed to mimic the visual and audio sensory stimuli of the real world as naturally as possible to users as they move within the limits defined by the application, typically in a pseudo-3D user experience.

(41) Augmented reality (AR) **300** provides the user with additional information or artificially generated items or content overlaid upon their current environment. The additional information or content is usually visual and/or audible. The user's observation of his or her current environment can be direct, with no intermediate sensing, processing, and rendering. Alternatively, the user's observation of the current environment can be indirect, where the user's perception of the environment is relayed via sensors and can be enhanced or processed.

(42) Mixed reality (MR) **320** is an advanced form of AR **300** where some virtual elements are inserted into the physical scene with the intent to provide the illusion that these elements are part of the real scene.

(43) Extended reality (XR) **330** refers to all real-and-virtual combined environments and human-machine interactions generated by computer technology and wearables. XR includes representative forms, such as AR **300**, VR **310**, and MR **320**, and the areas interpolated among them.

(44) The 5G network **100** in FIG. 1 can provide XR content to a UE **340**. The XR content can include 3D messaging, AR sharing, and real-time 3D communication etc., as defined by 3GPP 26.928. To support an XR application, the basic downlink (DL) throughput needs to be approximately 30 megabits per second (Mbps), while the uplink (UL) throughput needs to be 10 Mbps or less. The packet delay needs to be between 10 ms to 30 ms.

(45) In general, the 5G network **100** is designed to provide DL at approximately 2 Mbps at the edge of coverage areas **112-1** through **112-4** in FIG. 1, and approximately 200 kilobits per second URL at the edge of coverage areas **112-1** through **112-4**. Consequently, the network **100** cannot provide the needed throughput required by XR everywhere. While the UE **340** is close to the cell site **102-1-102-3** in FIG. 1, the UE **340** can receive XR service at the needed throughput, but in some other locations such as the edge of coverage areas **112-1** through **112-4**, the UE **340** may not. In addition, time of day can affect the XR service such as during peak hours when the network is congested. However, the UE **340** may not know that the XR service is not available or of low-quality due to location or time of day, and the UE may keep trying to access service which can result in excessive network **100** traffic and consequently bad user experience.

(46) FIG. 4 shows media streaming within the 5G network **100** in FIG. 1. 5G Media Service (5GMS) AF **400** is an application function similar to that defined in TS 23.501 clause 6.2.10, dedicated to 5G media streaming. 5GMS AS **410** is an application server dedicated to 5G media streaming. 5GMS client **420** is a UE internal function dedicated to 5G media streaming. The 5GMS client **420** is a logical function and its subfunctions may be distributed within the UE according to implementation choice.

(47) FIG. 5 shows extended reality communication within the 5G network **100** in FIG. 1. The 5GMS client **420** running on the UE **540** can include a media session handler **500** and a media stream handler **510**, which are constituent functions exposing APIs to one another in the same way that those APIs M6 and M7 are exposed to 5GMS-aware application **520**. The 5GMS client **420** does not have to expose APIs M6 and M7 within the 5GMS client. The 5GMS client **420** can be completely self-contained, such that all functionality to politically implementing in the 5GMS-aware application **520** is embedded in the UE **540**, and thus interfaces M6 and M7 are not exposed at all.

(48) The media session handler **500** is a module running on the UE **540** that communicates with the 5GMS AF **400** to establish control and support the delivery of a media session and can perform additional functions such as consumption and quality of experience (QoE) metrics collection and reporting. The media session handler **500** can expose APIs M6 and M7 that can be used by the 5GMS-aware application **520**.

(49) The media stream handler **510** is a module running on the UE **540** that communicates with the

5GMS AS **410** to stream the media content and can provide APIs to the 5GMS-aware application **520** for media playback and to the media session handler **500** for media session control.

(50) FIG. **6** shows communication between UE and the base station. A throughput intensive application **600**, such as an XR application, can be the 5GMS-aware application **520** in FIG. **5**. The throughput intensive application **600** can initiate a throughput intensive communication **610**, e.g., an XR communication, and send the indication **620** to the base station **630** associated with the network **100** in FIG. **1**, requesting XR content. The initiation of throughput intensive communication **610** can use a new user assistance information element or use an existing user assistance information spare bit to send the indication. The UE **650** can send indication **620** using the radio resource control (RRC) protocol **670** to the base station **630** associated with the network **100**. The UE **650** can send indication **620** along with regularly sent radio frequency (RF) measurements such as Reference Signals Received Power (RSRP).

(51) The base station (BS) **630** can determine whether it can provide the desired downlink throughput and the desired uplink throughput to the UE **650**, based on a location of the UE, RF associated with the UE such as RSRP level, number of UEs connected to the base station, available base station resources, buffer estimation, hybrid automatic repeat request (hybrid ARQ or HARQ) feedback, current base station load, etc. HARQ is a combination of high-rate forward error correction (FEC) and automatic repeat request (ARQ) error control. In standard ARQ, redundant bits are added to data to be transmitted using an error-detecting (ED) code such as a cyclic redundancy check (CRC). Receivers detecting a corrupted message will request a new message from the sender. In Hybrid ARQ, the original data is encoded with an FEC code, and the parity bits are either immediately sent along with the message or only transmitted upon request when a receiver detects an erroneous message.

(52) If the base station **630** determines that it can provide throughput intensive communication at the desired downlink and uplink throughput, the base station **630** can provide extended reality content to the UE **650**. However, if the base station **630** determines that it cannot provide throughput intensive communication at the desired downlink and uplink throughput, the base station can send a message **680** to the UE **650** indicating that throughput intensive communication **610** is not available or of low-quality.

(53) The UE **650** can provide a notice **690** indicating that the throughput intensive communication **610** is not available or of low-quality. The notice **690** can be an icon shown in a corner of the UE **650** to not obstruct view of other UE display. The user can select a button **640**, such as an “OK” button **640** or the notice **690** itself, and the notice **690** can disappear. By selecting the button **640**, the user indicates that the UE **650** should not keep requesting throughput intensive communication **610**. If the user is already engaged in throughput intensive communication **610**, by selecting the button **640**, the user indicates that the UE **650** should cease engaging in the throughput intensive communication **610**. The user not selecting the button **640** indicates to the UE **650** to continue requesting throughput intensive communication. If the UE **650** is already engaged in throughput intensive communication **610**, the user not selecting the button **640** indicates to the device to continue to receive the throughput intensive communication.

(54) If the user selects the button **640**, the UE **650** can also create a timer and, after a predetermined passage of time such as 5 minutes, the UE can remove the notice **690** and can send the indication **620** again, requesting throughput intensive communication **610**.

(55) In addition, the base station **630** can determine whether the location of the UE has changed, such as the UE has gotten closer to the base station, and can determine whether, based on the new location, the base station can provide the desired uplink throughput and the desired downlink throughput needed for throughput intensive communication **610**. If that is the case, the base station **630** can proactively notify the user that the throughput intensive communication **610** is available. Similarly, the base station **630** can monitor various indicators such as base station load, RF associated with the UE **650**, the time of day, etc. If any of these indicators improve and enable the

base station to provide throughput intensive communication **610**, the base station can proactively send a notice indicating so to the UE.

(56) The base station **630** can, based on the indication **620**, communicate to other base stations that UE **650** is seeking throughput intensive communication **610**. If the UE **650** changes location and is handed off to a different base station, the different base station can determine if it can offer throughput intensive communication **610** to the UE and, if so, can proactively send a notice to the UE indicating the XR communication availability.

(57) By waiting for a notification from the network **100**, or by waiting for the expiration of the predetermined passage of time before requesting throughput intensive communication **610**, as opposed to continuously requesting throughput intensive communication **610**, the UE reduces network **100** traffic. For example, the UE **650** can keep requesting the throughput intensive communication **610** every few seconds, e.g., three or four seconds, thus clogging the network **100**. After receiving the indication from the user to cease requesting throughput intensive communication **610** or to cease engaging throughput rate intensive communication, the UE **650** can re-request the throughput intensive communication at a longer time interval, such as five minutes, 30 minutes, or an hour, thus reducing the network load over 100 times.

(58) FIG. 7 shows a single stream download extended reality communication model. Extended reality communication can be single stream or multi-stream. In the single stream extended reality communication **700**, the extended reality DL traffic is modelled as a sequence of video frames arriving at the base station according to the predetermined video frame rates and random jitter. The size of each frame is also random according to a certain distribution.

(59) In multi-streams extended reality communication model, the stream can consist of: option 1 including I-Frames and P-Frame, option 2 including audio and video data, or option 3 including field of view and omnidirectional stream.

(60) In option 1, the extended reality communication can include a slice-based traffic model or a group of picture (GOP) base traffic model. In a slice-based traffic model, a single video frame is divided into N slices. Out of N, one slice is I slice and remaining N-1 slices are P slices. N packets (one I and N-1 P) packets correspond to one video frame arriving at the same time. In a GOP base traffic model, a single video frame is either I frame or P frame. I frame is transmitted every K frame, where K is the GOP size, i.e., every group of picture. One video frame arrives at a time as a packet.

(61) In option 2, the extended reality communication can include video and audio data communicated via two streams. The first stream can carry video, while the second stream can carry audio. In option 3, the extended reality communication can include a first stream indicating a field of view, and a second stream including an omnidirectional view stream. The omnidirectional view stream enables the user to interactively explore the environment because the environment is omnidirectionally represented, i.e., from every viewpoint.

(62) FIG. 8 is a flowchart of a method to reduce network traffic associated with throughput intensive communication over a 5G or higher generation wireless telecommunication network. In step **800**, a hardware or software processor executing instructions described in this application can determine that an application associated with user equipment (UE) is requesting a throughput intensive communication over a wireless telecommunication network. The throughput intensive communication can be an extended reality communication, virtual reality communication, an augmented reality communication, etc. The throughput intensive communication is associated with a downlink throughput and an uplink throughput, where the downlink throughput is higher than the uplink throughput. The downlink throughput associated with the throughput intensive communication can be approximately above 20 Mbps, where an uplink throughput associated with throughput intensive communication can be approximately up to 10 Mbps.

(63) In step **810**, the processor can send a first indication to the wireless telecommunication network, where the first indication specifies to a base station associated with the wireless

telecommunication network that the UE is requesting the throughput intensive communication. The base station can be configured to determine whether the base station can provide the downlink throughput and the uplink throughput to the UE. The base station can make the determination based on a location of the UE, RRC connected users, available base station resources, buffer estimation, HARQ feedback, etc. The base station can be configured to, upon determining that the base station cannot provide the downlink throughput and the uplink throughput to the UE, send a first message to the UE indicating that the throughput intensive communication is of low quality, e.g., not available.

(64) In step **820**, upon receiving the first message, the processor can wait for a predetermined criterion to be satisfied before attempting to engage in the throughput intensive communication, thereby reducing network traffic associated with the throughput intensive communication by eschewing sending repeated requests for the throughput intensive communication. The predetermined criterion can be receiving a second message from the wireless telecommunication network indicating that the throughput intensive communication is available. The predetermined criterion can be a predetermined passage of time at which point the UE can resend the request. The predetermined passage of time can be five minutes or longer. By contrast, by following the standard protocol, the UE can request to engage in the throughput intensive communication every few seconds. Consequently, by implementing the disclosed technology, the network traffic can reduce 50 RRC loads by over 50 times.

(65) The processor can display a notification to a user indicating that the throughput intensive communication is unavailable, e.g., that the throughput intensive communication is of low quality. The notification can be an icon located in a corner of the display, e.g., the right top corner of the device screen, thus not significantly impacting visibility of content displayed underneath the notification. The user can remove the icon from the display so that the notification does not block the user from doing anything. The processor can create a timer configured to measure a passage of time since the display of the notification to the user. The processor can obtain an expiration time, such as five minutes, 30 minutes, or an hour. The expiration time can be user-adjusted. The processor can determine whether the passage of time since the display of the notification to the user is greater than equal to the expiration time. Upon determining that the passage of time since the display of the notification to the user is greater than or equal to the expiration time, the processor can cease displaying the notification to the user. Upon determining the passage of time since the display of the notification to the user is greater than or equal to the expiration time, the processor can send a second indication to the wireless telecommunication network requesting the throughput intensive communication with the UE. In another embodiment, the processor can wait for an input from the user indicating that the UE chooses to cease engaging with the extended reality communication. Only after receiving the input from the user does the processor cease requesting throughput intensive communication and wait for the timer to expire. If the user does not provide the input, the processor continues to request the extended reality communication.

(66) The processor can determine whether the UE has changed location, where changing location includes the UE moving closer to the base station or connecting to a different base station. Upon determining that the UE has changed location, the processor can send a second indication to the wireless telecommunication network requesting the throughput intensive communication with the UE.

(67) The processor can determine whether the UE is in connected mode or in the idle mode. In the connected mode the UE keeps its transmitter and receiver on, i.e., the UE's radio is in the on state. In the connected mode, the UE constantly communicates with the network so the UE knows its location at the cell level. While the UE is in connected mode, the processor can store the first indication at the base station. If the UE is in idle mode, the processor can delete the first indication. Upon determining that the UE is in idle mode, the processor can remove the first indication from the base station. The processor can determine whether the base station is capable of providing the

throughput intensive communication based on the base station load, available base station resources, buffer estimation, HARQ feedback, etc. Upon determining that the base station is capable of providing the throughput intensive communication to the UE and that the UE is in connected mode, the processor can offer the throughput intensive communication to the UE.

(68) The processor can, at a predetermined frequency, report a radiofrequency indicator associated with the UE to the base station. The predetermined frequency is determined by report periodicity setting which can be set at 120 ms or 480 ms, or other value. The radiofrequency indicator can be RSRP, Reference Signal Received Quality (RSRQ), or Signal to Interference Plus Noise Ratio (SINR). For example, when the UE is in connected mode, the UE keeps reporting RSRP and/or RSRQ to the base station. The base station can be configured to determine whether the reported radiofrequency indicator enables the throughput intensive communication, and upon determining that the reported radiofrequency enables the throughput intensive communication the base station can send a notification to the UE. Upon receiving the notification, the processor can engage in the throughput intensive communication.

(69) The processor can cause the base station to send to a second base station a notification that the UE is requesting the throughput intensive communication. The processor can establish a connection between the UE and the second base station, after, for example, a handoff. The processor can cause the second base station to determine whether the second base station can provide the throughput intensive communication to the UE, without the UE requesting the throughput intensive communication. Upon causing the second base station to determine that the second base station can provide the throughput intensive communication to the UE, the processor can establish the throughput intensive communication between the UE and the second base station. In effect, when the UE connects to a different base station that can offer the throughput intensive communication, the UE is proactively notified.

(70) The processor can send a second indication to the wireless telecommunication network, where the second indication specifies to the base station associated with the wireless telecommunication network that the UE is triggering an IP Multimedia Subsystem (IMS) voice call. Currently, the base station does not know when UE is triggering IMS voice call (either voice over LTE or voice over new radio), because the session initiation protocol (SIP) channel inside message is transparent to the base station. Only when the core network asks the base station to set up IMS voice channel does the base station know there is an IMS voice call ongoing.

(71) The first indication and/or the second indication can include a user assistant information element new to 5G or higher generation communication protocol. Alternatively, the first and/or the second indication can use a spare bit associated with an existing user assistant information element. The processor can send the first indication to the base station along with a measurement associated with a radiofrequency of the UE, such as RSRP.

(72) FIG. 9 is a flowchart of steps performed by a system to reduce network traffic associated with throughput intensive communication over a wireless telecommunication network. In step 900, a throughput intensive application executing on a UE is configured to engage in a throughput intensive communication with a wireless telecommunication network. The throughput intensive communication can be associated with a desired downlink throughput and a desired uplink throughput, where the downlink throughput is higher than the uplink throughput. The throughput intensive application is configured to receive an indication from a base station of the wireless telecommunication network that the base station cannot provide the desired downlink throughput or the desired uplink throughput. The throughput intensive application can present the indication to a user associated with the UE.

(73) In step 910, an input module can be configured to receive an indication from the user specifying whether the UE should continue to engage in the throughput intensive communication or the UE should cease engaging in the throughput intensive communication.

(74) In step 920, upon receiving the indication specifying to cease engaging in the throughput

intensive communication, the throughput intensive application can cease the throughput intensive communication. Otherwise, the throughput intensive application can continue with the throughput intensive communication even if the quality of service is low.

(75) A connection module executing the network or the UE can be configured to determine whether the UE has changed location, where changing location includes the UE moving closer to the base station or connecting to a different base station. Upon determining that the UE has changed location, the connection module can send an indication to the wireless telecommunication network requesting the throughput intensive communication.

(76) The base station can store the UE's first indication as long as the UE keeps in connected mode. If the UE is released to idle mode, the base station can remove the first indication. When the base station determines that the load in the base station is getting low and that the base station can support the desired uplink and downlink throughput, the base station can proactively notify the UE that the throughput intensive communication is available, and the base station can remove the icon indicating contrary.

(77) A connection module running on the network can determine whether the UE is in connected mode. In the connected mode, the UE keeps its transmitter and receiver always “on,” i.e., the UE's radio is in the “on” state. In the connected mode, the UE constantly communicates with the network so the network knows the UE's location at the cell level. While the UE is in connected mode, the network can store the first indication at the base station. Upon determining that the UE is in idle mode, the network can remove the first indication from the base station. The connection module can determine whether the base station is capable of providing the throughput intensive communication based on RRC, connected users available, base station resources, buffer estimation, HARQ feedback, etc. Upon determining that the base station is capable of providing the throughput intensive communication to the UE and that the UE is in connected mode, the connection module can offer the throughput intensive communication to the UE.

(78) A connection module executing on the UE can, at a predetermined frequency, report a radiofrequency indicator associated with the UE to the base station. The base station can be configured to determine whether the reported radiofrequency indicator, such as RSRP or RSRQ, enables the throughput intensive communication. Upon determining that the reported radiofrequency indicator enables the throughput intensive communication, the base station can proactively send a notification to the UE indicating the availability of the throughput intensive communication. Upon receiving the notification, the connection module engages in the throughput intensive communication.

(79) Computer System

(80) FIG. 10 is a block diagram that illustrates an example of a computer system **1000** in which at least some operations described herein can be implemented. As shown, the computer system **1000** can include: one or more processors **1002**, main memory **1006**, non-volatile memory **1010**, a network interface device **1012**, video display device **1018**, an input/output device **1020**, a control device **1022** (e.g., keyboard and pointing device), a drive unit **1024** that includes a storage medium **1026**, and a signal generation device **1030** that are communicatively connected to a bus **1016**. The bus **1016** represents one or more physical buses and/or point-to-point connections that are connected by appropriate bridges, adapters, or controllers. Various common components (e.g., cache memory) are omitted from FIG. 10 for brevity. Instead, the computer system **1000** is intended to illustrate a hardware device on which components illustrated or described relative to the examples of the Figures and any other components described in this specification can be implemented.

(81) The computer system **1000** can take any suitable physical form. For example, the computing system **1000** can share a similar architecture as that of a server computer, personal computer (PC), tablet computer, mobile telephone, game console, music player, wearable electronic device, network-connected (“smart”) device (e.g., a television or home assistant device), AR/VR systems

(e.g., head-mounted display), or any electronic device capable of executing a set of instructions that specify action(s) to be taken by the computing system **1000**. In some implementations, the computer system **1000** can be an embedded computer system, a system-on-chip (SOC), a single-board computer system (SBC) or a distributed system such as a mesh of computer systems, or it can include one or more cloud components in one or more networks. Where appropriate, one or more computer systems **1000** can perform operations in real time, near real time, or in batch mode.

(82) The network interface device **1012** enables the computing system **1000** to mediate data in a network **1014** with an entity that is external to the computing system **1000** through any communication protocol supported by the computing system **1000** and the external entity.

Examples of the network interface device **1012** include a network adaptor card, a wireless network interface card, a router, an access point, a wireless router, a switch, a multilayer switch, a protocol converter, a gateway, a bridge, bridge router, a hub, a digital media receiver, and/or a repeater, as well as all wireless elements noted herein.

(83) The memory (e.g., main memory **1006**, non-volatile memory **1010**, machine-readable medium **1026**) can be local, remote, or distributed. Although shown as a single medium, the machine-readable medium **1026** can include multiple media (e.g., a centralized/distributed database and/or associated caches and servers) that store one or more sets of instructions **1028**. The machine-readable (storage) medium **1026** can include any medium that is capable of storing, encoding, or carrying a set of instructions for execution by the computing system **1000**. The machine-readable medium **1026** can be non-transitory or comprise a non-transitory device. In this context, a non-transitory storage medium can include a device that is tangible, meaning that the device has a concrete physical form, although the device can change its physical state. Thus, for example, non-transitory refers to a device remaining tangible despite this change in state.

(84) Although implementations have been described in the context of fully functioning computing devices, the various examples are capable of being distributed as a program product in a variety of forms. Examples of machine-readable storage media, machine-readable media, or computer-readable media include recordable-type media such as volatile and non-volatile memory devices **1010**, removable flash memory, hard disk drives, optical disks, and transmission-type media such as digital and analog communication links.

(85) In general, the routines executed to implement examples herein can be implemented as part of an operating system or a specific application, component, program, object, module, or sequence of instructions (collectively referred to as “computer programs”). The computer programs typically comprise one or more instructions (e.g., instructions **1004**, **1008**, **1028**) set at various times in various memory and storage devices in computing device(s). When read and executed by the processor **1002**, the instruction(s) cause the computing system **1000** to perform operations to execute elements involving the various aspects of the disclosure.

(86) Remarks

(87) The terms “example,” “embodiment,” and “implementation” are used interchangeably. For example, reference to “one example” or “an example” in the disclosure can be, but not necessarily are, references to the same implementation; and such references mean at least one of the implementations. The appearances of the phrase “in one example” are not necessarily all referring to the same example, nor are separate or alternative examples mutually exclusive of other examples. A feature, structure, or characteristic described in connection with an example can be included in another example of the disclosure. Moreover, various features are described which can be exhibited by some examples and not by others. Similarly, various requirements are described which can be requirements for some examples but not for other examples.

(88) The terminology used herein should be interpreted in its broadest reasonable manner, even though it is being used in conjunction with certain specific examples of the invention. The terms used in the disclosure generally have their ordinary meanings in the relevant technical art, within the context of the disclosure, and in the specific context where each term is used. A recital of

alternative language or synonyms does not exclude the use of other synonyms. Special significance should not be placed upon whether or not a term is elaborated or discussed herein. The use of highlighting has no influence on the scope and meaning of a term. Further, it will be appreciated that the same thing can be said in more than one way.

(89) Unless the context clearly requires otherwise, throughout the description and the claims, the words “comprise,” “comprising,” and the like are to be construed in an inclusive sense, as opposed to an exclusive or exhaustive sense; that is to say, in the sense of “including, but not limited to.” As used herein, the terms “connected,” “coupled,” or any variant thereof means any connection or coupling, either direct or indirect, between two or more elements; the coupling or connection between the elements can be physical, logical, or a combination thereof. Additionally, the words “herein,” “above,” “below,” and words of similar import can refer to this application as a whole and not to any particular portions of this application. Where context permits, words in the above Detailed Description using the singular or plural number may also include the plural or singular number respectively. The word “or” in reference to a list of two or more items covers all of the following interpretations of the word: any of the items in the list, all of the items in the list, and any combination of the items in the list. The term “module” refers broadly to software components, firmware components, and/or hardware components.

(90) While specific examples of technology are described above for illustrative purposes, various equivalent modifications are possible within the scope of the invention, as those skilled in the relevant art will recognize. For example, while processes or blocks are presented in a given order, alternative implementations can perform routines having steps, or employ systems having blocks, in a different order, and some processes or blocks may be deleted, moved, added, subdivided, combined, and/or modified to provide alternative or sub-combinations. Each of these processes or blocks can be implemented in a variety of different ways. Also, while processes or blocks are at times shown as being performed in series, these processes or blocks can instead be performed or implemented in parallel or can be performed at different times. Further, any specific numbers noted herein are only examples such that alternative implementations can employ differing values or ranges.

(91) Details of the disclosed implementations can vary considerably in specific implementations while still being encompassed by the disclosed teachings. As noted above, particular terminology used when describing features or aspects of the invention should not be taken to imply that the terminology is being redefined herein to be restricted to any specific characteristics, features, or aspects of the invention with which that terminology is associated. In general, the terms used in the following claims should not be construed to limit the invention to the specific examples disclosed herein, unless the above Detailed Description explicitly defines such terms. Accordingly, the actual scope of the invention encompasses not only the disclosed examples, but also all equivalent ways of practicing or implementing the invention under the claims. Some alternative implementations can include additional elements to those implementations described above or include fewer elements.

(92) Any patents and applications and other references noted above, and any that may be listed in accompanying filing papers, are incorporated herein by reference in their entireties, except for any subject matter disclaimers or disavowals, and except to the extent that the incorporated material is inconsistent with the express disclosure herein, in which case the language in this disclosure controls. Aspects of the invention can be modified to employ the systems, functions, and concepts of the various references described above to provide yet further implementations of the invention.

(93) To reduce the number of claims, certain implementations are presented below in certain claim forms, but the applicant contemplates various aspects of an invention in other forms. For example, aspects of a claim can be recited in a means-plus-function form or in other forms, such as being embodied in a computer-readable medium. A claim intended to be interpreted as a mean-plus-function claim will use the words “means for.” However, the use of the term “for” in any other

context is not intended to invoke a similar interpretation. The applicant reserves the right to pursue such additional claim forms in either this application or in a continuing application.

Claims

1. At least one non-transitory computer-readable storage medium storing instructions to reduce network traffic associated with an extended reality communication over a 5G or higher generation wireless telecommunication network which, when executed by at least one data processor of a system, causes the system to: determine that an application associated with a mobile device is requesting the extended reality communication over the 5G or higher generation wireless telecommunication network, wherein the extended reality communication includes real-and-virtual combined environments or human-machine interactions generated by computer technology and wearables, wherein a desired downlink throughput associated with the extended reality communication is approximately above 20 Mbps, and, wherein a desired uplink throughput associated with the extended reality communication is approximately up to 10 Mbps; send a first indication to the 5G or higher generation wireless telecommunication network, wherein the first indication specifies to a base station associated with the 5G or higher generation wireless telecommunication network that the mobile device is requesting the extended reality communication, wherein the base station is configured to determine whether the base station can provide the desired downlink throughput and the desired uplink throughput to the mobile device, and wherein the base station is configured to, upon determining that the base station cannot provide the desired downlink throughput or the desired uplink throughput to the mobile device, send a first message to the mobile device indicating that the extended reality communication is of low-quality; and upon receiving the first message, wait for a second message from the 5G or higher generation wireless telecommunication network indicating that the extended reality communication is available, thereby reducing network traffic associated with the extended reality communication by eschewing sending repeated requests for the extended reality communication.
2. The at least one non-transitory computer-readable storage medium of claim 1, comprising instructions to: display a notification to a user indicating that the extended reality communication is of a low quality; receive an input indicating that the mobile device chooses to cease engaging with the extended reality communication; create a timer configured to measure a passage of time since the display of the notification to the user; obtain an expiration time; determine whether the passage of time since the display of the notification to the user is greater than or equal to the expiration time; upon determining that the passage of time since the display of the notification to the user is greater than or equal to the expiration time, cease displaying the notification to the user; and upon determining that the passage of time since the display of the notification to the user is greater than or equal to the expiration time, send a second indication to the 5G or higher generation wireless telecommunication network requesting the extended reality communication with the mobile device.
3. The at least one non-transitory computer-readable storage medium of claim 1, comprising instructions to: determine whether the mobile device has changed location, wherein changing location includes the mobile device moving closer to the base station or connecting to a different base station; and upon determining that the mobile device has changed location, send a second indication to the 5G or higher generation wireless telecommunication network requesting the extended reality communication with the mobile device.
4. The at least one non-transitory computer-readable storage medium of claim 1, comprising instructions to: determine whether the mobile device is in connected mode; upon determining that the mobile device is in idle mode, remove the first indication from the base station; determine whether the base station is capable of providing the extended reality communication; and upon determining that the base station is capable of providing the extended reality communication to the mobile device and that the mobile device is in connected mode, offer the extended reality

communication to the mobile device.

5. The at least one non-transitory computer-readable storage medium of claim 1, comprising instructions to: at a predetermined frequency report a radio frequency indicator associated with the mobile device to the base station, wherein the base station is configured to determine whether the reported radio frequency indicator enables the extended reality communication, and upon determining that the reported radio frequency indicator enables the extended reality communication, send a notification to the mobile device; and upon receiving the notification, engage in the extended reality communication.

6. The at least one non-transitory computer-readable storage medium of claim 1, comprising instructions to: cause the base station to send to a second base station a notification that the mobile device is requesting the extended reality communication; establish a connection between the mobile device and the second base station; cause the second base station to determine whether the second base station can provide the extended reality communication to the mobile device, without the mobile device requesting the extended reality communication; and upon causing the second base station to determine that the second base station can provide the extended reality communication to the mobile device, establish the extended reality communication between the mobile device and the second base station.

7. The at least one non-transitory computer-readable storage medium of claim 1, comprising instructions to: send a second indication to the 5G or higher generation wireless telecommunication network, wherein the second indication specifies to the base station associated with the 5G or higher generation wireless telecommunication network that the mobile device is triggering an IP Multimedia Subsystem (IMS) voice call.

8. The at least one non-transitory computer-readable storage medium of claim 1, wherein the first indication includes a mobile device assistance information element new to 5G or higher generation communication protocol, or wherein the first indication uses a spare bit associated with an existing user assistant information element; and comprising instructions to: send the first indication to the base station along with a measurement associated with a radio frequency of the mobile device.

9. A system comprising: at least one hardware processor; and at least one non-transitory memory storing instructions, which, when executed by the at least one hardware processor, cause the system to: determine that an application associated with a user equipment (UE) is requesting a throughput intensive communication over a wireless telecommunication network, wherein the throughput intensive communication is associated with a downlink throughput and an uplink throughput, wherein the downlink throughput is higher than the uplink throughput; send a first indication to the wireless telecommunication network, wherein the first indication specifies to a base station associated with the wireless telecommunication network that the UE is requesting the throughput intensive communication, wherein the base station is configured to determine whether the base station can provide the downlink throughput and the uplink throughput to the UE, and wherein the base station is configured to, upon determining that the base station cannot provide the downlink throughput or the uplink throughput to the UE, send a first message to the UE indicating that the throughput intensive communication is of low quality; and upon receiving the first message, wait for a predetermined criterion to be satisfied before attempting to engage in the throughput intensive communication, thereby reducing network traffic associated with the throughput intensive communication by eschewing sending repeated requests for the throughput intensive communication.

10. The system of claim 9, comprising instructions to: display a notification to a user indicating that the throughput intensive communication is unavailable; create a timer configured to measure a passage of time since the display of the notification to the user; obtain an expiration time; determine whether the passage of time since the display of the notification to the user is greater than equal to the expiration time; upon determining that the passage of time since the display of the notification to the user is greater than or equal to the expiration time, cease displaying the

notification to the user; and upon determining the passage of time since the display of the notification to the user is greater than or equal to the expiration time, send a second indication to the wireless telecommunication network requesting the throughput intensive communication with the UE.

11. The system of claim 9, comprising instructions to: determine whether the UE has changed location, wherein changing location includes the UE moving closer to the base station or connecting to a different base station; and upon determining that the UE has changed location, send a second indication to the wireless telecommunication network requesting the throughput intensive communication with the UE.

12. The system of claim 9, comprising instructions to: determine whether the UE is in connected mode; upon determining that the UE is in idle mode, remove the first indication from the base station; determine whether the base station is capable of providing the throughput intensive communication; and upon determining that the base station is capable of providing the throughput intensive communication to the UE and that the UE is in connected mode, offer the throughput intensive communication to the UE.

13. The system of claim 9, comprising instructions to: at a predetermined frequency, report a radio frequency indicator associated with the UE to the base station, wherein the base station is configured to determine whether the reported radio frequency indicator enables the throughput intensive communication, and upon determining that the reported radio frequency indicator enables the throughput intensive communication, send a notification to the UE; and upon receiving the notification, engage in the throughput intensive communication.

14. The system of claim 9, comprising instructions to: cause the base station to send to a second base station a notification that the UE is requesting the throughput intensive communication; establish a connection between the UE and the second base station; cause the second base station to determine whether the second base station can provide the throughput intensive communication to the UE, without the UE requesting the throughput intensive communication; and upon causing the second base station to determine that the second base station can provide the throughput intensive communication to the UE, establish the throughput intensive communication between the UE and the second base station.

15. The system of claim 9, comprising instructions to: send a second indication to the wireless telecommunication network, wherein the second indication specifies to the base station associated with the wireless telecommunication network that the UE is triggering an IP Multimedia Subsystem (IMS) voice call.

16. The system of claim 9, wherein the first indication includes a user assistant information element new to 5G or higher generation communication protocol, or wherein the first indication uses a spare bit associated with an existing user assistant information element; and comprising instructions to: send the first indication to the base station along with a measurement associated with a radio frequency of the UE.

17. A system comprising: a throughput intensive application executing on a UE, wherein the throughput intensive application is configured to engage in a throughput intensive communication with a wireless telecommunication network, wherein the throughput intensive communication is associated with a desired downlink throughput and a desired uplink throughput, wherein the desired downlink throughput is higher than the desired uplink throughput, wherein the throughput intensive application is configured to receive a first indication from a base station of the wireless telecommunication network specifying that the base station cannot provide the desired downlink throughput or the desired uplink throughput, and wherein the throughput intensive application is configured to present the first indication to a user associated with the UE; an input module configured to receive a second indication from the user specifying whether the UE should continue to engage in the throughput intensive communication or the UE should cease engaging in the throughput intensive communication; and upon receiving the second indication, specifying to cease

engaging in the throughput intensive communication, wherein in response thereto, the throughput intensive application ceases the throughput intensive communication.

18. The system of claim 17, comprising a connection module configured to: determine whether the UE has changed location, wherein changing location includes the UE moving closer to the base station or connecting to a different base station; and upon determining that the UE has changed location, send a third indication to the wireless telecommunication network requesting the throughput intensive communication.

19. The system of claim 17, comprising a connection module configured to: determine whether the UE is in connected mode; upon determining that the UE is in idle mode, remove a third indication from the base station, wherein the third indication requests the throughput intensive communication; determine whether the base station is capable of providing the throughput intensive communication; and upon determining that the base station is capable of providing the throughput intensive communication to the UE and that the UE is in connected mode, offer the throughput intensive communication to the UE.

20. The system of claim 17, comprising a connection module configured to: at a predetermined frequency, report a radio frequency indicator associated with the UE to the base station, wherein the base station is configured to determine whether the reported radio frequency indicator enables the throughput intensive communication, and upon determining that the reported radio frequency indicator enables the throughput intensive communication, send a notification to the UE; and upon receiving the notification, engage in the throughput intensive communication.
