

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12408300
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Chang; Ren-Chun et al.

Cooling system

Abstract

The present disclosure provides a cooling system, including an air-cooling device and a water-cooling device. The air-cooling device includes a first fan, an evaporator, a first condenser, and a second fan. The first fan is arranged in a first cooling room and configured to blow a hot air inside a rack into a first cooling room. The evaporator is arranged in the first cooling room. The first condenser is arranged in a second cooling room. The second fan is arranged in the second cooling room and configured to blow an outside air into the second cooling room. The water-cooling device includes a radiator. The radiator is arranged in the second cooling room and configured to receive a hot liquid from an electronic device in the rack through a third pipeline and transmit a cold liquid to the electronic device through a fourth pipeline.

Inventors: Chang; Ren-Chun (Taoyuan, TW), Lai; Shao-Hsuan (Taoyuan, TW), You; Siang-Lin (Taoyuan, TW)

Applicant: DELTA ELECTRONICS, INC. (Taoyuan, TW)

Family ID: 90855236

Assignee: DELTA ELECTRONICS, INC. (Taoyuan, TW)

Appl. No.: 18/167078

Filed: February 10, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240138113 A1	Apr. 25, 2024
US 20240237287 A9	Jul. 11, 2024

Foreign Application Priority Data

CN	202211304824.9	Oct. 24, 2022
----	----------------	---------------

Publication Classification

Int. Cl.: H05K7/20 (20060101)

U.S. Cl.:

CPC H05K7/20318 (20130101); H05K7/20136 (20130101); H05K7/203 (20130101); H05K7/20309 (20130101); H05K7/20327 (20130101); H05K7/20818 (20130101);

Field of Classification Search

CPC: H05K (7/20318); H05K (7/20136); H05K (7/203); H05K (7/20309); H05K (7/20327); H05K (7/20818); H05K (7/20636); H05K (7/20609); H05K (7/20218); H05K (7/20272); H05K (7/2039)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
9445530	12/2015	Reytblat et al.	N/A	N/A
10117362	12/2017	Noteboom et al.	N/A	N/A
11202394	12/2020	Weems	N/A	H05K 7/20818
11656665	12/2022	Heydari	700/300	G06F 1/20
11991866	12/2023	Salim	N/A	H05K 7/20763
2013/0213071	12/2012	Takahashi	165/185	H05K 7/2079

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
101420839	12/2010	CN	N/A
104754924	12/2015	CN	N/A
205939837	12/2016	CN	N/A
105120637	12/2016	CN	N/A
109814690	12/2018	CN	N/A
115209686	12/2021	CN	N/A
I237174	12/2004	TW	N/A
I240607	12/2004	TW	N/A
I289245	12/2006	TW	N/A
2010123660	12/2009	WO	N/A

Primary Examiner: Schult; Allen R. B.

Attorney, Agent or Firm: CKC & Partners Co., LLC

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION

(1) This application claims priority to China application No. 202211304824.9, filed on Oct. 24, 2022, which are herein incorporated by reference in their entirety.

BACKGROUND

Field of Invention

(2) The present disclosure relates to a cooling system. More particularly, the present disclosure relates to a cooling system including an air-cooling device and a water-cooling device.

Description of Related Art

(3) Outdoor communication racks generally include equipment such as power systems and switching mode rectifiers (SMRs). Traditionally, the racks use air-cooling approaches to cool down the equipment and other electronic components. However, as the electronic components inside the chips have better performance, the chips generate more heat as well. Thus, the traditional air-cooling approaches cannot cool down the electronic components efficiently.

SUMMARY

(4) The present disclosure provides a cooling system, including an air-cooling device and a water-cooling device. The air-cooling device includes a first fan, an evaporator, a first condenser, and a second fan. The first fan is arranged in a first cooling room and configured to blow a hot air inside a rack into a first cooling room. The evaporator is arranged in the first cooling room. The first condenser is arranged in a second cooling room. The second fan is arranged in the second cooling room and configured to blow an outside air into the second cooling room. In response to the evaporator receiving the hot air through the first fan, the evaporator is configured to heat a refrigerant into a gaseous state and transmit the refrigerant to the first condenser through a first pipeline. In response to the first condenser receiving the outside air through the second fan, the first condenser is configured to condense the refrigerant into a liquid state and transmit the refrigerant to the evaporator through a second pipeline. The water-cooling device includes a radiator. The radiator is arranged in the second cooling room and configured to receive a hot liquid from an electronic device in the rack through a third pipeline and transmit a cold liquid to the electronic device through a fourth pipeline. In response to the radiator receiving the outside air through the second fan, the radiator is configured to cool down the hot liquid to the cold liquid.

(5) The present disclosure also provides a cooling system, including a plate heat exchanger, a first fan, a second fan, and a water-cooling device. The plate heat exchanger includes plates. The plates are configured to form at least one hot air channel and at least one cool air channel. The first fan is configured to blow a hot air inside a rack into the at least one hot air channel of the plate heat exchanger. The second fan is configured to blow an outside air into the at least one cool air channel of the plate heat exchanger. In response to the hot air flows through the at least one hot air channel and the outside air flows through the at least one cool air channel, the plates are configured to cool down the hot air. The water-cooling device includes a radiator. The radiator is configured to receive a hot liquid from an electronic device in the rack through a first pipeline and transmit a cold liquid to the electronic device through a second pipeline. In response to the radiator receiving the outside air through the second fan, the radiator is configured to cool down the hot liquid to the cold liquid.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The invention can be more fully understood by reading the following detailed description of the embodiment, with reference made to the accompanying drawings as follows:

(2) FIG. 1 is a diagram of a cooling system in accordance with some embodiments of the present disclosure.

(3) FIG. 2A is a diagram of a first condenser and an evaporator as shown in FIG. 1 in accordance with some embodiments of the present disclosure.

(4) FIG. 2B is a diagram of the first condenser and the evaporator as shown in FIG. 1 in accordance with some embodiments of the present disclosure.

- (5) FIG. 3 is a diagram of a radiator as shown in FIG. 1 in accordance with some embodiments of the present disclosure.
- (6) FIG. 4A is a diagram of a portion of the cooling system as shown in FIG. 1 in accordance with some embodiments of the present disclosure.
- (7) FIG. 4B is a diagram of a cooling plate as shown in FIG. 4A in accordance with some embodiments of the present disclosure.
- (8) FIG. 5 is a diagram of a portion of the cooling system as shown in FIG. 1 in accordance with some embodiments of the present disclosure.
- (9) FIG. 6A is a diagram of a portion of the cooling system as shown in FIG. 1 in accordance with some embodiments of the present disclosure.
- (10) FIG. 6B is a diagram of a second condenser as shown in FIG. 6A in accordance with some embodiments of the present disclosure.
- (11) FIG. 7A is a diagram of a cooling system in accordance with some embodiments of the present disclosure.
- (12) FIG. 7B is a diagram of a plate heat exchanger as shown in FIG. 7A in accordance with some embodiments of the present disclosure.
- (13) FIG. 7C is a diagram of the plate heat exchanger as shown in FIG. 7A in accordance with some embodiments of the present disclosure.

DETAILED DESCRIPTION

- (14) Reference will now be made in detail to embodiments of the present disclosure, examples of which are described herein and illustrated in the accompanying drawings. While the disclosure will be described in conjunction with embodiments, it will be understood that they are not intended to limit the disclosure to these embodiments. On the contrary, the disclosure is intended to cover alternatives, modifications and equivalents, which may be included within the spirit and scope of the disclosure as defined by the appended claims. It is noted that, in accordance with the standard practice in the industry, the drawings are only used for understanding and are not drawn to scale. Hence, the drawings are not meant to limit the actual embodiments of the present disclosure. In fact, the dimensions of the various features may be arbitrarily increased or reduced for clarity of discussion. Wherever possible, the same reference numbers are used in the drawings and the description to refer to the same or like parts for better understanding.
- (15) The terms used in this specification generally have their ordinary meanings in the art, within the context of the invention, and in the specific context where each term is used.
- (16) As used in the present disclosure, the terms “comprising,” “including,” “having,” “containing,” “involving,” and the like are to be understood to be open-ended, i.e., to mean including but not limiting to. In addition, as used in the present disclosure, the term “and/or” includes any and all combinations of one or more of the associated listed items. Moreover, it will be understood that, although the terms “first,” “second,” etc., may be used herein to describe various elements, these elements should not be limited by these terms. These terms are used to distinguish one element from another.
- (17) Some embodiments of the present disclosure provide a cooling system. Reference is now made to FIG. 1. FIG. 1 is a diagram of a cooling system **100** in accordance with some embodiments of the present disclosure. The cooling system **100** is configured to lower a temperature inside a rack RAK. In some embodiments, the rack RAK is arranged outdoor and is configured to accommodate communication equipment. A power module SMR is configured to convert alternative current (AC) to direct current (DC) and transmit the direct current to a power system POW. The power system POW is configured to provide power to electronic devices ED1-ED3. The power module SMR, the power system POW, and the electronic devices ED1-ED3 generate heat during operation, and thus a hot air is generated inside the rack RAK as shown in FIG. 1.
- (18) In some embodiments, the electronic devices ED1-ED3 are central processing units (CPUs), graphics processing units (GPUs), or other chips for computing and processing communication

data and information. In some embodiments, the electronic devices ED1-ED3 with higher computing power or performance generate more heat during operation.

(19) For illustration of FIG. 1, the cooling system **100** includes a first fan **110**, and a second fan **130**, an evaporator **120**, a first condenser **140**, and a radiator **160**. The first fan **110** and the evaporator **120** are arranged in a first cooling room R1, and the second fan **130**, the first condenser **140**, and the radiator **160** are arranged in a second cooling room R2. The evaporator **120** and the first condenser **140** are connected to each other through a first pipeline P1 and a second pipeline P2. The radiator **160** is connected to the electronic devices ED1-ED3 through a third pipeline P3 and a fourth pipeline P4.

(20) In some embodiments, as shown in FIG. 1, the first cooling room R1 and the second cooling room R2 are arranged at the same side with respect to the rack RAK, and the first cooling room R1 is arranged between the second cooling room R2 and the rack RAK.

(21) In some embodiments, the air inside the first cooling room R1 and the air inside the rack RAK communicate with each other through a hole (not shown in FIG. 1), and the air inside the second cooling room R2 and the outside air of the outdoor environment communicate with each other through another hole (not shown in FIG. 1).

(22) In some embodiments, the cooling system **100** further includes an isolation wall ISO. As shown in FIG. 1, the first cooling room R1 and the second cooling room R2 are separated from each other by the isolation wall ISO. Alternatively stated, the isolation wall ISO is arranged between the first cooling room R1 and the second cooling room R2. The isolation wall ISO is configured to prevent the hot air blown into the first cooling room R1 by the first fan **110** from flowing into the second cooling room R2 and to prevent the outside air blown into the second cooling room R2 by the second fan **130** from flowing into the first cooling room R1.

(23) In some embodiments, at least one hole (not shown in FIG. 1) is arranged at the isolation wall ISO, and the at least one hole is configured for the first pipeline P1, the second pipeline P2, the third pipeline P3, and the fourth pipeline P4 to pass through the isolation wall ISO. In some embodiments, four holes (not shown in FIG. 1) are arranged at the isolation wall ISO, and are configured for the first pipeline P1, the second pipeline P2, the third pipeline P3, and the fourth pipeline P4 to pass through the isolation wall ISO respectively.

(24) Accordingly, the isolation wall ISO is configured to prevent the air from flowing between the first cooling room R1 and the second cooling room R2, allow a refrigerant to be transmitted between the evaporator **120** and the first condenser **140** through the first pipeline P1 and the second pipeline P2, and allow a fluid to be transmitted between the electronic devices ED1-ED3 and the radiator **160** through the third pipeline P3 and the fourth pipeline P4.

(25) It is worth noting that the configuration of the embodiment in FIG. 1 is merely exemplary and does not intend to limit the embodiments of the present disclosure. In various embodiments, structures and relative positions of the first cooling room R1, the second cooling room R2, and the rack RAK are different from the embodiment of FIG. 1.

(26) In some embodiments, the cooling system **100** uses an air-cooling device and a water-cooling device to lower the temperature inside the rack RAK. Alternatively stated, the components of the cooling system **100** can be categorized and/or divided into the air-cooling device(s) and the water-cooling device(s). As the first fan **110**, the second fan **130**, the evaporator **120**, the first condenser **140**, the first pipeline P1, and the second pipeline P2 are configured to use air as media to bring heat outside the rack RAK, these components are referred to as the air-cooling device(s). As the radiator **160**, the third pipeline P3, and the fourth pipeline P4 are configured to use fluid as media to bring heat outside the rack RAK, these components are referred to as the water-cooling device(s). Paragraphs below describe details regarding the operations of these components in the cooling system **100**.

(27) In some embodiments, as shown in FIG. 1, the first fan **110** is arranged at a relatively high position, and the second fan **130** is arranged at a relatively low position. Alternatively stated, in the

direction perpendicular to the ground, the first fan **110** is higher, and the second fan **130** is lower.

(28) For illustration of FIG. **1**, when the power module SMR, the power system POW, and the electronic devices ED1-ED3 in the rack RAK generate the hot air, the first fan **110** is configured to blow the hot air inside the rack RAK into the first cooling room R1. In some embodiments, the first fan **110** is arranged in the first cooling room R1, and a hole (not shown in FIG. **1**) is arranged at a position adjacent to the first fan **110** between the first cooling room R1 and the rack RAK, so that the first fan **110** can blow the hot air from the rack RAK into the first cooling room R1 through the hole.

(29) For illustration of FIG. **1**, after the first fan **110** blows the hot air into the first cooling room R1, the isolation wall ISO is further configured for the hot air to flow along a side of the isolation wall ISO to the evaporator.

(30) For illustration of FIG. **1**, when the hot air coming from the rack RAK is blowed to the evaporator **120** by the first fan **110**, the evaporator **120** is configured to heat a refrigerant in the evaporator **120** into a gaseous state and transmit the refrigerant to the first condenser **140** through the first pipeline P1. In some embodiments, the evaporator **120** is configured to store a liquid-state refrigerant (refrigerant in the liquid state). When the evaporator **120** receives the hot air coming from the rack RAK through the first fan **110**, the liquid-state refrigerant in the evaporator **120** is heated to a certain temperature and is converted into the gaseous state. The gaseous-state refrigerant (refrigerant in the gaseous state) will rise in and along the first pipeline P1 and then be transmitted to the first condenser **140**.

(31) Reference is now made to FIGS. 2A-2B. FIGS. 2A-2B are diagrams of the first condenser **140** and the evaporator **120** as shown in FIG. **1** in accordance with some embodiments of the present disclosure. In some embodiments, the evaporator **120** in FIG. **1** has the configuration of the condenser/evaporator **200** as shown in FIGS. 2A-2B. As shown in FIGS. 2A-2B, the condenser/evaporator **200** includes parallel-flow flat tubes **220** that are arranged to be adjacent to each other. Each of the parallel-flow flat tubes **220** is connected to a refrigerant inlet and a refrigerant outlet and includes multiple micro channels **240**. The micro channels **240** are configured as paths for transmitting the refrigerant. Multiple cooling fins **260** are arranged between any two of the parallel-flow flat tubes **220**. The cooling fins **260** contact the adjacent parallel-flow flat tubes **220** and are configured for the liquid or the refrigerant in the micro tubes and the air passing through the cooling fins **260** to exchange heat.

(32) In some embodiments, when the refrigerant passes through the micro channels **240** in the parallel-flow flat tubes **220**, because the hot air coming from the rack RAK passes through the cooling fins **260** and transmits heat to the cooling fins **260**, the cooling fins **260** are configured to transmit the heat to the parallel-flow flat tubes **220**, and the parallel-flow flat tubes **220** are configured to transmit the heat to the refrigerant inside the micro channels **240**. Accordingly, the condenser/evaporator **200** is configured to absorb the heat of the hot air and then heat the refrigerant into the gaseous state.

(33) In some embodiments, when the liquid-state refrigerant is heated to a certain temperature, the liquid-state refrigerant converts into the gaseous-state refrigerant. In some embodiments, when the gaseous-state refrigerant is cooled down to a certain temperature, the gaseous-state refrigerant is converted into the liquid-state refrigerant.

(34) Reference is made to FIG. **1** again. The second fan **130** is configured to blow the outside air into the second cooling room R2. In some embodiments, the second fan **130** is arranged in the second cooling room R2, and the second cooling room R2 includes a hole (not shown in FIG. **1**) that is arranged at a position adjacent to the second fan **130**, so that the second fan **130** can blow the outside air from the outdoor environment into the second cooling room R2 through the hole.

(35) For illustration of FIG. **1**, after the second fan **130** blows the outside air into the second cooling room R2, the isolation wall ISO is further configured for the outside air to flow along the isolation wall ISO to the first condenser **140**.

(36) For illustration of FIG. 1, after the first condenser **140** receives the gaseous-state refrigerant through the first pipeline **P1**, when the first condenser **140** receives the outside air through the second fan **130**, the first condenser **140** is configured to condense the gaseous-state refrigerant into the liquid state and transmit the liquid-state refrigerant to the evaporator **120** through the second pipeline **P2**. Alternatively stated, when the gaseous-state refrigerant in the first condenser **140** is cooled down to a certain temperature, the gaseous-state refrigerant is converted into the liquid-state refrigerant. The liquid-state refrigerant will flow downward along the second pipeline **P2** due to gravity and then be transmitted to the evaporator **120**.

(37) In some embodiments, the second cooling room **R2** further includes a hole (not shown in FIG. 1) that is arranged at a position adjacent to the first condenser **140**, and the hole is connected to the outdoor environment. After the outside air flows through the first condenser **140** and absorbs the heat from the refrigerant in the first condenser **140**, the outside air will flow out of the second cooling room **R2** through this hole. Thus, the heat is transmitted out of the rack **RAK** and to the outdoor environment.

(38) In some embodiments, the first condenser **140** in FIG. 1 has the configuration of the condenser/evaporator **200** as shown in FIGS. 2A-2B. When the refrigerant passes through the micro channels **240** in the parallel-flow flat tubes **220** and the outside air flows through the air flow paths of the condenser/evaporator **200**, the cooling fins **260** are configured to transmit the heat coming from the gaseous-state refrigerant in the micro channels **240** to the outside air that flows through and contacts the cooling fins **260**. Accordingly, the condenser/evaporator **200** is configured to transmit the heat of the gaseous-state refrigerant to the outside air, allowing the gaseous-state refrigerant to be condensed into the liquid-state refrigerant.

(39) In some embodiments, as shown in FIG. 1, after the first condenser **140** transmits the liquid-state refrigerant to the evaporator **120** through the second pipeline **P2**, when the evaporator **120** receives the liquid-state refrigerant through the second pipeline **P2**, the first fan **110** is further configured to blow into the rack **RAK** the cool air that is cooled down by the liquid-state refrigerant in the evaporator **120**.

(40) In some embodiments, a hole (not shown in FIG. 1) is arranged at a position adjacent to the evaporator **120** between the first cooling room **R1** and the rack **RAK**. When the evaporator **120** receives the cooled liquid-state refrigerant, the air blown out by the first fan **110** passes through the evaporator **120** and then flows into the rack **RAK** through the hole mentioned above. Because the evaporator **120** includes the cooled liquid-state refrigerant, the air passing through the evaporator **120** will exchange heat with the refrigerant in the evaporator **120** and be cooled down, so the cool air will flow back into the rack **RAK**.

(41) Through the configuration of the first fan **110**, the second fan **130**, the evaporator **120**, the first condenser **140**, the first pipeline **P1**, and the second pipeline **P2**, the heat of the hot air inside the rack **RAK** is transmitted to the refrigerant, the heat of the refrigerant is then transmitted to the outside air, and the heat of the outside air is eventually transmitted to the outdoor environment. Accordingly, the cooling system **100** transmits a portion of the heat in the rack **RAK** out of the rack **RAK** through the air-cooling devices.

(42) As discussed above, in some embodiments, the electronic devices **ED1-ED3** will generate great heat during operation, and the cooling system **100** transmits the heat generated by the electronic devices **ED1-ED3** out of the rack **RAK** through the water-cooling devices. Paragraphs below describe the operations of the water-cooling devices in the cooling system **100**.

(43) For illustration of FIG. 1, the radiator **160** is arranged in the second cooling room **R2** and is configured to receive a hot liquid from the electronic devices **ED1-ED3** in the rack **RAK** through a third pipeline **P3**, and transmit a cold liquid to the electronic devices **ED1-ED3** through a fourth pipeline **P4**. Alternatively stated, the electronic devices **ED1-ED3** generate heat during operation, and the third pipeline **P3** and the fourth pipeline **P4** are configured to transmit liquid between the electronic devices **ED1-ED3** and the radiator **160**, in order to exhaust the heat out of the rack **RAK**.

through the liquid.

(44) In some embodiments, after the liquid receives the heat generated by the electronic devices ED1-ED3, the third pipeline P3 is configured to transmit the heat to the radiator 160. After the radiator 160 cools down the hot liquid to the cold liquid, the fourth pipeline P4 is configured to transmit the cold liquid back to the electronic devices ED1-ED3, and then the cold liquid can exchange heat with the electronic devices ED1-ED3.

(45) In some embodiments, as shown in FIG. 1, when the radiator 160 receives the outside air through the second fan 130, the radiator 160 is configured to cool down the hot liquid into the cold liquid. Alternatively stated, when the outside air passes through the radiator 160, the outside air exchanges heat with the hot liquid in the radiator 160, so that the hot liquid is cooled down into the cold liquid.

(46) In some embodiments, as shown in FIG. 1, through the configuration of the cooling system 100 as shown in FIG. 1, after the outside air is blown into the second cooling room R2 by the second fan 130, the outside air passes through the radiator 160 first, then the first condenser 140, and flows out to the outdoor environment through the hole adjacent to the first condenser 140. In various embodiments, the cooling system 100 has a configuration different from the one shown in FIG. 1. After the outside air is blown into the second cooling room R2 by the second fan 130, the outside air passes through the first condenser 140 first, then the radiator 160, and flows out to the outdoor environment through the hole.

(47) Reference is now made to FIG. 3. FIG. 3 is a diagram of the radiator 160 as shown in FIG. 1 in accordance with some embodiments of the present disclosure. In some embodiments, the radiator 160 includes openings 162 and 168, a pipe structure 164, and a fin structure 166. The opening 162 is configured for the radiator 160 to connect to the third pipeline P3 in FIG. 1 and receive the hot liquid from the electronic devices ED1-ED3. The opening 168 is configured for the radiator 160 to connect to the fourth pipeline P4 in FIG. 1 and transmit the cold liquid to the electronic devices ED1-ED3. The pipe structure 164 has a winding structure. The fin structure 166 is arranged around the pipe structure 164 and is configured for the liquid in the pipe structure 164 to exchange heat with the air passing through the fin structure 166. For example, when the outside air passes through the radiator 160 and makes contact with the fin structure 166 of the radiator 160, the outside air exchanges heat with the hot liquid in the pipe structure 164, so that the hot liquid is cooled down in the cold liquid.

(48) In some embodiments, as shown in FIG. 1, the cooling system 100 further includes a pump 150. The pump 150 is arranged at a portion of the fourth pipeline P4. When the cold liquid flows to the pump 150 through the fourth pipeline P4, the pump 150 is configured to apply pressure to the cold liquid to increase the velocity of the cold liquid, in order to transmit the cold liquid to the electronic devices ED1-ED3. In various embodiments, the pump 150 is arranged at a portion of the third pipeline P3. When the hot liquid flows to the pump 150 through the third pipeline P3, the pump 150 is configured to increase the velocity of the hot liquid.

(49) Through the configuration of the radiator 160, the pump 150, the third pipeline P3, and the fourth pipeline P4 mentioned above, the heat generated by the electronic devices ED1-ED3 is transmitted out of the rack RAK through the liquid. Accordingly, the cooling system 100 transmits the heat generated by the electronic devices ED1-ED3 in the rack RAK outside the rack RAK through the water-cooling devices.

(50) In some embodiments, the liquid transmitted by the third pipeline P3 and the fourth pipeline P4 exchanges heat with the electronic devices ED1-ED3 through a cooling plate. Reference is now made to FIG. 4A. FIG. 4A is a diagram of a portion of the cooling system 100 as shown in FIG. 1 in accordance with some embodiments of the present disclosure. FIG. 4A merely illustrates the water-cooling devices in the cooling system 100 that include the radiator 160, the pump 150, the third pipeline P3 and the fourth pipeline P4. The air-cooling devices are omitted in FIG. 4A.

(51) For illustration of FIG. 4A, in a tank CON, an electronic device ED is arranged on a circuit

board PCB, and a cooling plate **420** is arranged on the electronic device ED and contacts the electronic device ED. The cooling plate **420** is configured to transmit the hot liquid to the radiator **160** through the third pipeline P3, receive the cold liquid from the radiator **160** through the fourth pipeline P4, and allow the liquid to exchange heat with the electronic device ED by contacting the electronic device ED.

(52) Reference is now made to FIG. 4B. FIG. 4B is a diagram of the cooling plate **420** as shown in FIG. 4A in accordance with some embodiments of the present disclosure. In some embodiments, the cooling plate **420** includes a pipe structure **426** and a plate structure **424**. The pipe structure **426** includes openings **422** and **428**. The openings **422** and **428** are configured for the pipe structure **426** to connect to the third pipeline P3 and the fourth pipeline P4 respectively. The pipe structure **426** is arranged on the plate structure **424** and contacts the plate structure **424**. The plate structure **424** is configured to contact the electronic device ED. In some embodiments, the plate structure **424** includes materials with high thermal conductivity.

(53) For illustration of FIG. 4A, when the cold liquid is transmitted to the cooling plate **420** through the fourth pipeline P4, the cold liquid exchanges heat with the electronic device ED through the cooling plate **420**, and the cold liquid is heated into the hot liquid after receiving the heat generated by the electronic device ED. The hot liquid is transmitted to the radiator **160** through the third pipeline P3, and the radiator **160** cools down the hot liquid into the cold liquid as described in previous embodiments. In some embodiments, the cooling plate **420** is referred to as a water-cooling plate.

(54) Reference is now made to FIG. 5. FIG. 5 is a diagram of a portion of the cooling system **100** as shown in FIG. 1 in accordance with some embodiments of the present disclosure. FIG. 5 merely illustrates the water-cooling devices in the cooling system **100**, and the air-cooling devices in the cooling system **100** are omitted in FIG. 5. In some embodiments, as shown in FIG. 5, the tank CON is configured to store a dielectric fluid **520** and soak the electronic device ED into the dielectric fluid **520**. Alternatively stated, the electronic device ED is soaked into the dielectric fluid **520** and contacts the dielectric fluid **520** in order to exchange heat with the dielectric fluid **520**. After the dielectric fluid **520** absorbs the heat from the electronic device ED, the third pipeline P3 is configured to transmit the dielectric fluid **520** from the tank CON to the radiator **160**. After the radiator **160** cools down the dielectric fluid **520**, the fourth pipeline P4 is configured to transmit the cooled dielectric fluid **520** back to the tank CON.

(55) In some embodiments, the dielectric fluid **520** includes electrical insulating substances, such as oil, fluorides, and others alike.

(56) Reference is now made to FIG. 6A. FIG. 6A is a diagram of a portion of the cooling system **100** as shown in FIG. 1 in accordance with some embodiments of the present disclosure. FIG. 6A merely illustrates the water-cooling devices in the cooling system **100**, and the air-cooling devices in the cooling system **100** are omitted. In some embodiments, compared with the embodiment of FIG. 5, in the embodiment of FIG. 6A, the cooling system **100** further includes a second condenser **620**. The second condenser **620** is arranged in the tank CON and is connected to the third pipeline P3 and the fourth pipeline P4.

(57) In some embodiments, as shown in FIG. 6A, the boiling point of the dielectric fluid **520** is below 100° C. For example, the boiling point of the dielectric fluid **520** is between 50° C. and 65° C. When the dielectric fluid **520** is heated above its boiling point by the electronic device ED, the dielectric fluid **520** is converted from the liquid state into the gaseous state, and the second condenser **620** is configured to condense the dielectric fluid **520** into the liquid state. Alternatively stated, the liquid-state dielectric fluid **520** is converted into the gaseous-state dielectric fluid **520**, and the tank CON is filled with the gaseous-state dielectric fluid **520**. When the gaseous-state dielectric fluid **520** contacts the second condenser **620**, because the cold liquid coming from the fourth pipeline P4 flows through the second condenser **620**, the gaseous-state dielectric fluid **520** with a relatively high temperature will condense on the surface of the second condenser **620** that

has a relatively low temperature due to the cold liquid.

(58) When the gaseous-state dielectric fluid **520** condense on the second condenser **620**, the dielectric fluid **520** exchanges heat with the cold liquid in the second condenser **620**, so that the cold liquid in the second condenser **620** is heated into the hot liquid. The second condenser **620** then transmits the hot liquid to the radiator **160** through the radiator **160**. The dielectric fluid **520** condensed on the second condenser **620** is converted back into the liquid state and remains in the tank CON.

(59) Different from the embodiment of FIG. 5, in the embodiment of FIG. 6A, the liquid in the third pipeline P3, the fourth pipeline P4, the second condenser **620**, and the radiator **160** is separated from the dielectric fluid **520** in the tank CON. In the embodiment of FIG. 5, the dielectric fluid **520** flows in the third pipeline P3, the fourth pipeline P4, and the radiator **160**.

(60) Reference is now made to FIG. 6B. FIG. 6B is a diagram of the second condenser **620** as shown in FIG. 6A in accordance with some embodiments of the present disclosure. In some embodiments, the second condenser **620** includes openings **622** and **626** and a pipe structure **624**. The opening **626** is configured to connect the fourth pipeline P4, in order to receive the cold liquid from the radiator **160** and transmit the cold liquid to the pipe structure **624**. The opening **622** is configured to connect the third pipeline P3, in order to transmit the hot liquid to the radiator **160**. When the liquid flows in the pipe structure **624**, the pipe structure **624** is configured to condense the heated gaseous-state dielectric fluid **520** onto the surface of the pipe structure **624**, which allows the dielectric fluid **520** to exchange heat with the liquid in the pipe structure **624**.

(61) The water-cooling devices described in the embodiments of FIGS. 4A, 5, and 6A can be used in the cooling system **100** shown in FIG. 1 to exhaust the heat generated by the electronic devices ED1-ED3 as shown in FIG. 1.

(62) Some embodiments of the present disclosure provide another cooling system. Reference is now made to FIG. 7A. FIG. 7A is a diagram of a cooling system **700** in accordance with some embodiments of the present disclosure. The cooling system **700** includes a first fan **710**, a second fan **730**, a plate heat exchanger **720**, a radiator **740**, and a pump **750**.

(63) In some embodiments, as shown in FIG. 7A, the first fan **710**, the second fan **730**, the plate heat exchanger **720**, the radiator **740**, and the pump **750** are arranged in a cooling room R3.

(64) Reference is now made to FIGS. 7B-7C. FIGS. 7B-7C are diagrams of the plate heat exchanger **720** as shown in FIG. 7A in accordance with some embodiments of the present disclosure. The plate heat exchanger **720** includes multiple plates **722**. The plates **722** are arranged to be separate from each other and are configured to form hot air channels P5 and cool air channels P6.

(65) In some embodiments, as shown in FIG. 7C, the hot air coming from the rack RAK flows through the hot air channels P5, and the outside air coming from the outdoor environment flows through the cool air channels P6. When the hot air and the outside air flow along the two sides of the plates **722**, the hot air and the outside air exchange heat through the plates **722**. Thus, the hot air transmits heat to the outside air, and the hot air is cooled down.

(66) Reference is made to FIG. 7A again. When the power module SMR, the power system POW, and the electronic devices ED1-ED3 generate the hot air, the first fan **710** is configured to blow the hot air in the rack RAK into the cooling room R3. In some embodiments, the first fan **710** is arranged in the cooling room R3, a hole (not shown in FIG. 7A) is arranged at a position adjacent to the first fan **710** between the cooling room R3 and the rack RAK, so that the first fan **710** can blow the hot air from the rack RAK into the cooling room R3 through the hole.

(67) For illustration of FIG. 7A, the hot air coming from the rack RAK is blown into the hot air channel P5 in the plate heat exchanger **720**. For brevity of FIG. 7A, the hot air channel P5 and the cool air channel P6 illustrated in FIG. 7A are merely exemplary. In some embodiments, multiple hot air channels P5 and multiple cool air channels P6 are formed between the plates **722** of the plate heat exchanger **720** as shown in FIG. 7C.

(68) For illustration of FIG. 7A, the second fan **730** is configured to blow the outside air from the outdoor environment into the cooling room R3. The outside air passes through the radiator **740** first and then flows into the cool air channel P6 in the plate heat exchanger **720**. In some embodiments, the cooling room R3 includes a hole (not shown in FIG. 7A), and the outside air flows to the outdoor environment through the hole after passing through the cool air channel P6 in the plate heat exchanger **720**.

(69) In some embodiments, when the hot air flows into the hot air channels P5 in the plate heat exchanger **720** and the outside air flows into the cool air channel P6 in the plate heat exchanger **720**, the plates **722** of the plate heat exchanger **720** are configured to cool down the hot air. The hot air and the outside air exchange heat through the plates **722**, and the hot air transmits heat to the outside air.

(70) In some embodiments, the cooling room R3 includes a hole (not shown in FIG. 7A). After the hot air passes through the hot air channels P5 in the plate heat exchanger **720** and is cooled down to the cool air, the first fan **710** is configured to blow the cool air into the rack RAK through the hole.

(71) Through the configuration of the first fan **710**, the second fan **730**, and the plate heat exchanger **720**, the hot air coming from the rack RAK is cooled down by the plate heat exchanger **720** and then flows back into the rack RAK.

(72) For illustration of FIG. 7A, the radiator **740** is arranged in the cooling room R3 and is configured to receive a hot liquid from the electronic devices ED1-ED3 in the rack RAK through the first pipeline P7 and to transmit a cold liquid to the electronic devices ED1-ED3 through the second pipeline P8.

(73) In some embodiments, after the liquid absorbs the heat generated by the electronic devices ED1-ED3, the first pipeline P7 is configured to transmit the hot liquid to the radiator **740**. After the radiator **740** cools down the hot liquid to the cold liquid, the second pipeline P8 is configured to transmit the cold liquid back to the electronic devices ED1-ED3, and then the cold liquid exchanges heat with the electronic devices ED1-ED3 again.

(74) In some embodiments, as shown in FIG. 7A, when the radiator **740** receives the outside air through the second fan **730**, the radiator **740** is configured to cool down the hot liquid to the cold liquid. Alternatively stated, when the outside air passes through the radiator **740**, the outside air exchanges heat with the hot liquid in the radiator **740**, and the hot liquid is cooled down to the cold liquid.

(75) In some embodiments, through the configuration of the cooling system **700** as shown in FIG. 7A, after the outside air is blown into the cooling room R3 by the second fan **730**, the outside air flows through the radiator **740** first, then flows through the plate heat exchanger **720**, and flows to the outdoor environment through the hole of the cooling room R3 that is adjacent to the plate heat exchanger **720**. In various embodiments, the cooling system **700** has a configuration different from the one shown in FIG. 7A. After the outside air is blown into the cooling room R3 by the second fan **730**, the outside air passes through the plate heat exchanger **720** first, then the radiator **740**, and flows out to the outdoor environment through the hole of the cooling room R3.

(76) In some embodiments, as shown in FIG. 7A, the pump **750** is arranged at a portion of the second pipeline P8. When the cold liquid flows to the pump **750** through the second pipeline P8, the pump **750** is configured to apply pressure to the cold liquid to increase the velocity of the cold liquid, in order to transmit the cold liquid to the electronic devices ED1-ED3. In various embodiments, the pump **750** is arranged at a portion of the first pipeline P7. When the hot liquid flows to the pump **750** through the first pipeline P7, the pump **750** is configured to increase the velocity of the hot liquid.

(77) Compared with the cooling system **100** as shown in FIG. 1, the cooling system **700** adopts different air-cooling devices and uses the plate heat exchanger **720**, and uses the water-cooling devices that are similar to the ones used in the cooling system **100**. Alternatively stated, the cooling system **700** uses the configuration of the radiator **740**, the first pipeline P7, and the second pipeline

P8 to exhaust the heat generated by the electronic devices ED1-ED3 out of the rack RAK. In addition, the water-cooling devices described in the embodiments of FIGS. 4A, 5, and 6A can be used in the cooling system **700** shown in FIG. 7A.

(78) In conclusion, the present disclosure provides cooling systems having both the air-cooling devices and the water-cooling devices. The air-cooling devices use configuration of the evaporator and the condenser or the configuration of the plate heat exchanger. The water-cooling devices use configuration of the water-cooling plate or use the configuration that the electronic devices are soaked in the dielectric fluid. Accordingly, the heat generated by the devices inside the rack can be effectively transmitted out of the rack, and the performance of the devices inside the rack can be maintained.

(79) Although the present invention has been described in considerable detail with reference to certain embodiments thereof, other embodiments are possible. Therefore, the spirit and scope of the appended claims should not be limited to the description of the embodiments contained herein. It will be apparent to those skilled in the art that various modifications and variations can be made to the structure of the present invention without departing from the scope or spirit of the invention. In view of the foregoing, it is intended that the present invention cover modifications and variations of this invention provided they fall within the scope of the following claims.

Claims

1. A cooling system, comprising: an air-cooling device, comprising: a first fan, arranged in a first cooling room and configured to blow a hot air inside a rack into a first cooling room; an evaporator, arranged in the first cooling room; a first condenser, arranged in a second cooling room; and a second fan, arranged in the second cooling room and configured to blow an outside air into the second cooling room; wherein, in response to the evaporator receiving the hot air through the first fan, the evaporator is configured to heat a refrigerant into a gaseous state and transmit the refrigerant to the first condenser through a first pipeline; in response to the first condenser receiving the outside air through the second fan, the first condenser is configured to condense the refrigerant into a liquid state and transmit the refrigerant to the evaporator through a second pipeline; and a water-cooling device, comprising: a radiator, arranged in the second cooling room and configured to receive a hot liquid from an electronic device in the rack through a third pipeline and transmit a cold liquid to the electronic device through a fourth pipeline; wherein, in response to the radiator receiving the outside air through the second fan, the radiator is configured to cool down the hot liquid to the cold liquid.

2. The cooling system of claim 1, wherein the water-cooling device further comprises: a cooling plate, the cooling plate contacting the electronic device, the cooling plate being configured to transmit the hot liquid to the radiator through the third pipeline and receive the cold liquid from the radiator through the fourth pipeline.

3. The cooling system of claim 1, wherein the water-cooling device further comprises: a tank, configured to store a dielectric fluid and soak the electronic device into the dielectric fluid.

4. The cooling system of claim 3, wherein the water-cooling device further comprises: a second condenser, arranged in the tank and connected to the third pipeline and the fourth pipeline; wherein, in response to the dielectric fluid being heated into a gaseous state by the electronic device, the second condenser is configured to condense the dielectric fluid into a liquid state.

5. The cooling system of claim 1, further comprising: an isolation wall, arranged between the first cooling room and the second cooling room and configured to prevent the hot air that is blown into the first cooling room by the first fan from flowing into the second cooling room and to prevent the outside air that is blown into the second cooling room by the second fan from flowing into the first cooling room.

6. The cooling system of claim 5, wherein the isolation wall includes at least one hole, the at least

one hole is configured to allow the first pipeline, the second pipeline, the third pipeline, and the fourth pipeline to pass through the isolation wall.

7. The cooling system of claim 5, wherein after the first fan blows the hot air into the first cooling room, the isolation wall is further configured for the hot air to flow along the isolation wall to the evaporator.

8. The cooling system of claim 5, wherein after the second fan blows the outside air into the second cooling room, the isolation wall is further configured for the outside air to flow along the isolation wall to the first condenser.

9. The cooling system of claim 1, wherein the first fan is arranged at a relatively high position, and the second fan is arranged at a relatively low position.

10. The cooling system of claim 1, wherein in response to the evaporator receiving the refrigerant in the liquid state from the second pipeline, the first fan is further configured to blow into the rack a cool air that is cooled down by the refrigerant.

11. The cooling system of claim 1, further comprising: a pump, arranged at a portion of the fourth pipeline, wherein, in response to the cold liquid flowing to the pump through the fourth pipeline, the pump is configured to apply pressure to the cold liquid in order to transmit the cold liquid to the electronic device.

12. A cooling system, comprising: a plate heat exchanger, comprising a plurality of plates, the plurality of plates being configured to form at least one hot air channel and at least one cool air channel; a first fan, configured to blow a hot air inside a rack into the at least one hot air channel of the plate heat exchanger; a second fan, configured to blow an outside air into the at least one cool air channel of the plate heat exchanger; wherein, in response to the hot air flowing through the at least one hot air channel and the outside air flowing through the at least one cool air channel, the plurality of plates are configured to cool down the hot air; and a water-cooling device, comprising: a radiator, configured to receive a hot liquid from an electronic device in the rack through a first pipeline and transmit a cold liquid to the electronic device through a second pipeline; wherein, in response to the radiator receiving the outside air through the second fan, the radiator is configured to cool down the hot liquid to the cold liquid.

13. The cooling system of claim 12, wherein the water-cooling device further comprises: a cooling plate, the cooling plate contacting the electronic device, the cooling plate being configured to transmit the hot liquid to the radiator through the first pipeline and receive the cold liquid from the radiator through the second pipeline.

14. The cooling system of claim 12, wherein the water-cooling device further comprises: a tank, configured to store a dielectric fluid and soak the electronic device into the dielectric fluid.

15. The cooling system of claim 14, wherein the water-cooling device further comprises: a condenser, arranged in the tank and connected to the first pipeline and the second pipeline; wherein, in response to the dielectric fluid being heated into a gaseous state by the electronic device, the condenser is configured to condense the dielectric fluid into a liquid state.

16. The cooling system of claim 12, wherein after the hot air flows through the at least one hot air channel and is cooled down to a cool air, the first fan is further configured to blow the cool air into the rack.

17. The cooling system of claim 12, wherein the first fan is arranged at a relatively high position, and the second fan is arranged at a relatively low position.

18. The cooling system of claim 12, further comprising: a cooling room, abutting the rack, wherein the plate heat exchanger, the first fan, the second fan, and the radiator are arranged in the cooling room.

19. The cooling system of claim 18, wherein the second fan is further configured to blow the outside air into the cooling room, so that the outside air passes through the radiator first and then flows into the at least one cool air channel in the plate heat exchanger.

20. The cooling system of claim 12, further comprising: a pump, arranged at a portion of the

second pipeline, wherein, in response to the cold liquid flowing to the pump through the second pipeline, the pump is configured to apply pressure to the cold liquid in order to transmit the cold liquid to the electronic device.
