

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12403340
Kind Code	B1
Date of Patent	September 02, 2025
Inventor(s)	Yang; Ke et al.

Fire alarming and suppression system for electric vehicle charging station

Abstract

A fire alarming and suppression system for an electric vehicle charging station includes a supporting assembly, an image information acquisition unit, a local controller and a box, wherein the supporting assembly is vertically arranged in the charging station; the image information acquisition unit is arranged at a top end of the supporting assembly for acquiring image information of electric vehicles in the charging station; the local controller is arranged on the supporting assembly for receiving the image information, analyzing and processing the image information, determining whether there is a fire risk, and providing a fire alarm if it determines that there is a fire risk; a fire blanket is provided in the box so that the fire blanket can be taken out of the box and used to cover an electric vehicle when the electric vehicle is on fire.

Inventors:	Yang; Ke (Shanghai, CN), Li; Haifeng (Wuhu, CN)
Applicant:	Shanghai Tyrehub Automotive Technology Co., Ltd. (Shanghai, CN)
Family ID:	92188576
Assignee:	Shanghai Tyrehub Automotive Technology Co., Ltd. (Shanghai, CN)
Appl. No.:	18/660992
Filed:	May 10, 2024

Foreign Application Priority Data

CN	202410434198.8	Apr. 10, 2024
----	----------------	---------------

Publication Classification

Int. Cl.: A62C3/07 (20060101); A62C3/16 (20060101); B60L53/30 (20190101); A62C3/06 (20060101); G08B17/10 (20060101)

U.S. Cl.:

CPC **A62C3/07** (20130101); **A62C3/16** (20130101); **B60L53/305** (20190201); A62C3/06 (20130101); G08B17/10 (20130101)

Field of Classification Search

CPC: B60L (53/18); B60L (53/31); H02J (7/00); H02J (7/0042); A62C (3/00); A62C (3/0257); A62C (3/06); A62C (3/07); A62C (3/16)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2024/0001791	12/2023	Mowery	N/A	B60L 53/31
2024/0253485	12/2023	Cho	N/A	B60L 53/67
2024/0416162	12/2023	Lucarelli, III	N/A	A62C 3/16

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2652696	12/2022	KR	N/A
2654066	12/2022	KR	N/A

Primary Examiner: Trieu; Van T

Attorney, Agent or Firm: Calfee, Halter & Griswold LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

(1) The present application claims the priority of Chinese Patent Application No. 202410434198.8 filed on Apr. 10, 2024 and titled as “Fire Alarming and Suppression System for Electric Vehicle Charging Station”, which is specifically incorporated herein in entirety by reference.

FIELD

(2) The present disclosure relates to the technical field of fire safety, in particular to a fire alarming and suppression system for an electric vehicle charging station.

BACKGROUND

(3) Li-ion batteries are widely applied in the field of electric vehicles by virtue of their advantages such as high energy density, long cycle life, wide working temperature range and no memory effect. However, owing to their intrinsic characteristics and service environments, Li-ion batteries are prone to thermal runaway, which will cause thermal damages to Li-ion batteries and may lead to spontaneous combustion and even explosion of the electric vehicles. At present, the inducing factors of thermal runaway of Li-ion batteries may be categorized into three categories: mechanical abuses (needling, deformation caused by squeezing, and external impact), electrical abuses (overcharge, over-discharge, and short circuit), and thermal abuses (failure of thermal management system). In electrical abuses, the pressure inside a battery will be too high if the battery is charged with excessive charging current or at an excessive voltage for a long time, and the temperature inside the battery will rise when the pressure reaches a certain level, eventually leading to thermal

runaway. Therefore, it is of great practical significance to provide fire alarming for electric vehicle charging stations to prevent fires caused by electrical abuses.

(4) In related arts, since electric vehicle charging stations are usually located outdoor, the inventor of the present application has found that it is inconvenient to provide fire alarming in such large spaces, for example, it is necessary to consider how to arrange the fire alarming system in electric vehicle charging stations, how to conveniently install the fire alarming system and effectively obtain image information for fire alarming, how to integrate relevant components of the fire alarming system, and how to facilitate ongoing maintenance and service, etc. In addition, since electric vehicles are often parked together when they are charged, chained burning may occur and cause serious economic losses if one of the electric vehicles is on fire and burns. Therefore, it is of great practical significance to implement fire alarming and suppression for electric vehicle charging stations.

SUMMARY

(5) The object of the present disclosure is to solve at least one of the technical problems in related arts to some extent. To that end, the present disclosure provides a fire alarming and suppression system for an electric vehicle charging station.

(6) To attain the above object, the present disclosure provides a fire alarming and suppression system for an electric vehicle charging station, which includes: a supporting assembly vertically arranged in the charging station; an image information acquisition unit arranged at a top end of the supporting assembly for acquiring image information of electric vehicles in the charging station; a local controller arranged on the supporting assembly for receiving the image information, analyzing and processing the image information, determining whether there is a fire risk, and providing a fire alarm if it determines that there is a fire risk; and Optionally, the fire alarming and suppression system for electric vehicle charging station further includes an one-button alarm device arranged on the supporting assembly, wherein the one-button alarm device includes a 4G communication module in communication with an alarm platform via a network connection through a 4G mobile communication network, a button arranged to immediately send an alarm signal to the alarm platform when pressed, a microphone for voice calls with the staff of the alarm platform, and a power supply module electrically connected to the 4G communication module and the microphone respectively for power supply.

(7) Optionally, the fire alarming and suppression system for electric vehicle charging station further includes an audible and visual alarm device, wherein a control input end of the audible and visual alarm device is connected to a control output end of the local controller, so as to control the audible and visual alarm device to send audible and visual signals when the local controller confirms that there is a fire risk through analysis.

(8) Optionally, the audible and visual alarm device includes a loudspeaker and a light strip that extends in a height direction of the supporting assembly.

(9) Optionally, the fire alarming and suppression system for electric vehicle charging station further includes: a signal transmission module arranged in the local controller for receiving the image information acquired by the image information collection unit and transmitting the image information; and a back-end control center communicatively connected with the signal transmission module for receiving the image information from the signal transmission module, processing and analyzing the image information, determining whether there is a fire risk at the back end, and providing a fire alarm in real time if it determines that there is a fire risk.

(10) According to the above technical scheme, the image information acquisition unit for acquiring image information of the electric vehicles in the charging station is arranged at the top end of the supporting assembly, and the supporting assembly can be conveniently arranged at any position in the electric vehicle charging station as required, thereby any position in the electric vehicle charging station can be effectively monitored, any electric vehicle on fire can be found timely, and a problem that the fire is out of control due to untimely alarming can be avoided; furthermore, if an

electric vehicle on fire is found, a person near the box may take out the fire blanket stored in the box and use the fire blanket to cover the electric vehicle on fire, so as to avoid fire spreading.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a schematic structural diagram of a fire alarming and suppression system for an electric vehicle charging station provided by the present disclosure;
- (2) FIG. 2 is a schematic structural diagram of the fire alarming and suppression system for an electric vehicle charging station in FIG. 1 after a back panel of the box is removed.
- (3) FIG. 3 is a partial sectional view of the fire alarming and suppression system for an electric vehicle charging station in FIG. 1 in the width direction of the box;
- (4) FIG. 4 is a sectional view of the fire alarming and suppression system for an electric vehicle charging station in FIG. 1 in the length direction of the box;
- (5) FIG. 5 is a schematic enlarged view of the part at position A in FIG. 4;
- (6) FIG. 6 is a schematic structural diagram of a supporting assembly provided by the present disclosure;
- (7) FIG. 7 is a schematic structural diagram of a baffle plate provided by the present disclosure;
- (8) FIG. 8 is a sectional view of a supporting assembly provided by the present disclosure;
- (9) FIG. 9 is a schematic diagram of the connection between a supporting assembly and a mounting plate provided by the present disclosure.

REFERENCE NUMBERS

- (10) **10**—box; **11**—bottom plate; **111**—raised part; **112**—recessed part; **12**—box door; **121**—accommodating cavity; **122**—notched part; **13**—locking mechanism; **20**—supporting assembly; **21** upright post; **22**—supporting post; **221**—access opening; **23**—connecting pipe; **24**—baffle plate; **241**—clamping block; **2411**—clamping slot; **242**—connecting hole; **243**—folded part; **25**—flanged edge; **251**—mounting hole; **30**—bearing plate; **40**—reinforcing plate; **50**—connecting plate; **51**—angular connecting block; **60**—mounting plate; **61**—connecting part.

DETAILED DESCRIPTION

- (11) Some embodiments of the present disclosure will be detailed below with reference to the accompanying drawings. It may be understood that the embodiments described herein are only provided to describe and explain the present disclosure, but are not intended to constitute any limitation on the present disclosure.
- (12) As described above and shown in FIGS. 1-5, the present disclosure provides a fire alarming and suppression system for an electric vehicle charging station, which includes a supporting assembly **20**, an image information acquisition unit, a local controller and a box **10**, wherein the supporting assembly **20** is vertically arranged in the charging station; the image information acquisition unit is arranged at a top end of the supporting assembly **20** for acquiring image information of electric vehicles in the charging station; the local controller is arranged on the supporting assembly **20** for receiving the image information, analyzing and processing the image information, determining whether there is a fire risk, and providing a fire alarm if it determines that there is a fire risk; the box **10** is arranged beside the supporting assembly **20** and provided with a fire blanket therein, so that the fire blanket can be taken out of the box and used to cover an electric vehicle when the electric vehicle is on fire.
- (13) It can be understood: in the present disclosure, the image information acquisition unit for acquiring image information of the electric vehicles in the charging station is arranged at the top end of the supporting assembly **20**, and the supporting assembly **20** can be conveniently arranged at any position in the electric vehicle charging station as required, thereby any position in the electric vehicle charging station can be effectively monitored, any electric vehicle on fire can be found

timely, and a problem that the fire is out of control due to untimely alarming can be avoided; furthermore, if an electric vehicle on fire is found, a person near the box **10** may take out the fire blanket stored in the box **10** and use the fire blanket to cover the electric vehicle on fire, so as to avoid fire spreading.

(14) It may be noted: in the present disclosure, the image information of the electric vehicles parked in the charging station is acquired by the image information acquisition unit, and relevant image information is analyzed by the local controller to determine whether there is a fire risk and provide a fire alarm if a fire risk is detected. Compared with an existing smoke particle sensing system, the image information acquisition unit employed in the present disclosure can overcome a problem that the smoke particle sensing system is not applicable to a large space such as an outdoor charging station.

(15) In a specific embodiment of the present disclosure, the image information acquisition unit includes a thermal imaging camera and a color camera, the thermal imaging camera is configured to acquire temperature information of the electric vehicles in the charging station and form first image data according to the temperature information; the color camera is configured to acquire real-time images of the electric vehicles in the charging station to form second image data; and the local controller can receive the first image data and the second image data, analyze and process the first image data and the second image data, determine whether there is a fire risk, and provide a fire alarm if it determines that there is a fire risk.

(16) It can be understood: in the present disclosure, by using the image data acquired by the thermal imaging camera and the color camera in combination, the problems of missing report and false report in solely visual detection with a color camera are solved to a certain extent, thereby the fire alarming system for an electric vehicle charging station can detect fire situations more effectively and accurately.

(17) In some embodiments, as shown in FIGS. **2** and **4**, a side of the box **10** is fixedly connected to the supporting assembly **20**, so that the bottom of the box **10** is spaced above the ground; and a bottom plate **11** of the box **10** is bent toward the inside of the box **10** to form at least one raised part **111**, and a bearing plate **30** is fixed on the raised part **111** and laid flat on the bottom of the box **10** for bearing the fire blanket.

(18) In the present disclosure, the side of the box **10** is fixedly connected to the supporting assembly **20** to make the box **10** suspended above the ground, so as to avoid a problem that the bottom of the box **10** arranged outdoor is corroded and damaged due to long-term contact with the ground; the bottom plate **11** of the box **10** is bent toward the inside of the box **10** to form at least one raised part **111**, and the bearing plate **30** is fixed on the raised part **111** to bear the fire blanket, thus, the bearing capacity of the box **10** can be significantly improved when compared with a flat bottom structure.

(19) It can be understood that no improvement is made to the material or bottom thickness of the box **10** in the present disclosure; instead, only adjustments are made to the bottom structure. Thus, in the present disclosure, the bearing capacity of the box **10** suspended above the ground can be improved without significantly increasing the cost, so that the box **10** can meet the requirement for storing the fire blanket; besides, the bottom that the bottom of the box **10** is corroded and damaged due to long-term contact with the ground is avoided.

(20) It may be noted: in the present disclosure, the raised part **111** may be arranged to extend in any suitable direction, as long as the top of the raised part **111** is flush to facilitate the arrangement of the bearing plate **30**. For example, the raised part **111** may be arranged to extend in the width direction of the box **10**.

(21) In some embodiments, the raised part **111** extends in a length direction of the box **10**, an outer side of the bottom plate **11** corresponding to the raised part **111** is formed into a recessed part **112**, a reinforcing plate **40** is arranged in the recessed part **112**, and an end of the reinforcing plate **40** extends out of the recessed part **112** and fixedly connected to the supporting assembly **20**. By

arranging the raised part **111** to extend in the length direction of the box **10**, the space of the recessed part **112** formed in the outer side of the bottom plate **11** when the raised part **111** is formed on the bottom plate **11** can be utilized skillfully to arrange a reinforcing plate **40** in the recessed part **112**, and the reinforcing plate **40** is connected to the supporting assembly **20**, so that the box **10** can be supported by the reinforcing plate **40** to further improve the bearing capacity of the box **10**.

(22) In some embodiments, in order to further reduce the cost and reduce the dead weight, the reinforcing plate **40** is configured in a square tube shape. Especially, the square tube-shaped reinforcing plate **40** further has advantages of convenient fixation and reliable fixation.

(23) In some embodiments, as shown in FIGS. **2** and **4**, two boxes **10** are provided and respectively arranged at two sides of the supporting assembly **20**. By providing two boxes **10**, more fire blankets can be stored in the boxes **10**, and the boxes **10** can be symmetrically arranged at two sides of the supporting assembly **20** to improve stability and prevent a problem of instability caused by arranging a box **10** only at one side of the supporting assembly **20**.

(24) In some embodiments, a connecting plate **50** is arranged above the two boxes **10**, two ends of the connecting plate **50** are respectively fixedly connected to sides of the two boxes **10** that face away from each other, the connecting plate **50** is provided with a through-hole for the supporting assembly **20** to pass through, and the connecting plate **50** is connected with the supporting assembly **20** via angular connecting blocks **51**. By providing an integral connecting plate **50** to connect and fix the two boxes **10** together and using angular connecting blocks **51** to connecting and fixing the connecting plate **50** and the supporting assembly **20** together, the reliability of the overall structure is improved.

(25) In some embodiments, in the case that two boxes **10** are provided, the reinforcing plates **40** at the bottoms of the two boxes **10** extend out of respective recessed parts **112** and are respectively fixedly connected to the supporting assembly **20**. By fixing one end of the reinforcing plate **40** on the supporting assembly **20** to support the box **10** with the reinforcing plate **40**, the bearing capacity of the box **10** is further improved.

(26) In some embodiments, as shown in FIG. **9**, a bottom end of the supporting assembly **20** is provided with a mounting plate **60**, which is arranged to be close to the ground for fixing the supporting assembly **20** on the ground in a vertical direction. It may be noted that the area of the mounting plate **60** is greater than the cross-sectional area of the bottom end of the supporting assembly **20**. By arranging the mounting plate **60** at the bottom end of the supporting assembly **20**, the supporting assembly **20** is fixed in the vertical direction with the mounting plate **60**, and the reliability of the mounting and fixation of the supporting assembly **20** on the ground is ensured.

(27) It can be understood: in the present disclosure, the mounting plate **60** may be fixedly connected to the bottom end of the supporting assembly **20** in any suitable form; for example, the mounting plate **60** may be welded and fixed to the bottom end of the supporting assembly **20**.

(28) In some embodiments, the mounting plate **60** is provided with a connecting part **61** extending in the vertical direction for fixedly connecting to the bottom end of the supporting assembly **20**.

(29) More specifically, as shown in FIG. **9**, the connecting part **61** is configured to be inserted into the bottom end of the supporting assembly **20** and fixedly connected to the supporting assembly **20** by bolts; alternatively, the connecting part **61** is provided with a cavity for the supporting assembly **20** to be inserted from top to bottom, and the connecting part **61** is fixedly connected to the supporting assembly **20** by bolts. In the above structural arrangement, the connection between the mounting plate **60** and the supporting assembly **20** is simple and efficient.

(30) In some embodiments, a front side of the box **10** is provided with an opening, a box door **12** is rotatably connected to the box **10** for closing or opening the opening, a locking mechanism **13** is arranged between the box door **12** and the box **10** for locking or unlocking the box door **12** in a state of closing the opening; the box door **12** is provided with an accommodating cavity **121** for accommodating a key for opening the locking mechanism **13**, and an opening of the accommodating cavity **121** is closed by a piece of glass.

- (31) In case of a fire, the key placed in the accommodating cavity **121** can be obtained by breaking the glass, then the locking mechanism **13** can be opened with the key, and then the door **12** can be opened, the fire blanket stored in the box **10** can be taken out and used to cover the electric vehicle on fire, so as to prevent the fire from spreading while extinguishing the fire.
- (32) In some embodiments, the box door **12** is provided with a notched part **122** extending in a thickness direction of the box door **12** for mounting the locking mechanism **13**. In the structural arrangement described above, the locking mechanism **13** can be accommodated in the notched part **122** to achieve a certain protective effect, and the notched part **122** can be used as a force application point for opening the door **12**, so that the door **12** can be opened without a door handle.
- (33) In the present disclosure, on one hand, the supporting assembly **20** is provided to support the image information acquisition unit, so that the image information acquisition unit can obtain a better viewing field, thereby obtain image information that is more conducive to judging whether there is a fire risk; on the other hand, the supporting assembly enables the box **10** to be suspended above the ground, thereby avoids a problem that the bottom of the box **10** is corroded and damaged due to long-term contact with the ground.
- (34) In some embodiments, as shown in FIG. 6, the supporting assembly **20** includes an upright post **21** and a supporting post **22**, the upright post **21** and the supporting post **22** respectively extend in the vertical direction, and a bottom end of the supporting post **22** is detachably fixed to a top end of the upright post **21**; a side of the box **10** is fixedly connected to the upright post **21**, the image information acquisition unit is arranged at the top end of the supporting post **22**, and the top end of the upright post **21** is not higher than a top end of the box **10**.
- (35) The side of the box **10** is fixedly connected to the upright post **21**, so that the bottom of the box **10** is spaced from the ground, and the image information acquisition unit is arranged at the top end of the supporting post **22**, so that the image acquisition unit has a better viewing field, thereby image information that is more conducive to judging whether there is a fire risk can be obtained. In the present disclosure, the supporting assembly **20** is divided into two parts, namely, an upright post **21** and a supporting post **22**, and the image information acquisition unit is arranged at the top end of the supporting post **22**, so as to meet the requirement for the viewing field of the image information acquisition unit and facilitate transportation.
- (36) In the present disclosure, the upright post **21** and the supporting post **22** may be detachably connected in any suitable form. In a specific embodiment of the present disclosure, a connecting pipe **23** is arranged between the upright post **21** and the supporting post **22**, and two ends of the connecting pipe **23** are respectively inserted into the upright post **21** and the supporting post **22** and fixedly connected to the upright post **21** and the supporting post **22** by bolts.
- (37) In some embodiments, the upright post **21** and the supporting post **22** respectively have a hollow structure extending in the vertical direction. In particular, as shown in FIGS. 6 and 7, at least one side of the supporting post **22** is provided with an access opening **221** extending in the height direction of the supporting post **22**, and the supporting post **22** is provided with a detachable baffle plate **24** for closing the access opening **221**.
- (38) It can be understood: by configuring the upright post **21** and the supporting post **22** that constitute the supporting assembly **20** into hollow structures, a plurality of components and functional modules that constitute the fire alarming system can be conveniently integrated in the supporting assembly **20** while the dead weight is reduced; in addition, since at least one side of the supporting post **22** is provided with an access opening **221** extending in the height direction of the supporting post **22** and the supporting post **22** is provided with a baffle plate **24** for closing the access opening **221**, maintenance and service can be carried out conveniently during later use after the baffle plate **24** is removed.
- (39) In the present disclosure, the baffle plate **24** may be arranged on the supporting post **22** in any suitable form to close the access opening **221**. In some embodiments, the supporting post **22** has flanged edges **25** formed at two sides of the access opening **221** respectively, each of the flanged

edges 25 has a mounting surface parallel to the baffle plate 24, the mounting surface of the flanged edge 25 is provided with a mounting hole 251 extending in the vertical direction, and the baffle plate 24 is provided with clamping blocks 241 configured to be inserted into the mounting holes 251; when the baffle plate 24 is shifted, the clamping blocks 241 are clamped and fixed in the mounting holes 251; the baffle plate 24 is further provided with connecting holes 242 for bolts to penetrate there-through and fix to the flanged edges 25.

(40) It can be understood: in the present disclosure, by arranging flanged edges 25 with mounting surfaces at the two sides of the access opening 221 and configuring the baffle plate 24 into a flat plate, the mounting requirements can be met. In the mounting process, first, the clamping blocks 241 on the baffle plate 24 are aligned to and inserted into the mounting holes 251 in the flanged edges 25, then the baffle plate 24 is shifted so that the clamping blocks 241 are clamped and fixed in the mounting holes 251, and then the baffle plate 24 is secured and fixed to the flanged edges 25 by bolts, thus, the mounting is completed; to remove the baffle plate 24, first, the bolts between the baffle plate 24 and the flanged edges 25 are removed, and then the baffle plate 24 is shifted so that the clamping blocks 241 are aligned to the mounting holes 251 and can be moved out of the mounting holes 251. Compared with a method of directly connecting the baffle plate 24 to the flanged edges 25 by bolts, the above-mentioned connecting method provided by the present disclosure can ensure the safety in the mounting and removal process of the baffle plate 24.

(41) In some embodiments, each of the clamping blocks 241 is provided with a clamping slot 2411 with an upward opening. When the clamping blocks 241 are inserted into the mounting holes 251 and the baffle plate 24 is shifted, the clamping slots 2411 abut and fit with the upper edges of the mounting holes 251. It can be understood: by configuring each clamping block 241 to have a clamping groove 2411 with an upward opening, the self-weight of the baffle plate 24 can be partially utilized when the baffle plate 24 is to be removed, so that the baffle plate 24 can be conveniently removed from the flanged edges 25.

(42) In the present disclosure, in order to ensure the reliability of the connection and fixation of the baffle plate 24 to the supporting post 22, the flanged edges 25 at the two sides of the access opening 221 are provided with a plurality of mounting holes 251 respectively, and the plurality of mounting holes 251 are arranged at an interval in the vertical direction. It can be understood: in order to align the clamping blocks 241 on the baffle plate 24 to the mounting holes 251 in the flanged edges 25, the plurality of mounting holes 251 in the two flanged edges 25 at the two sides of the access opening 221 are at the same level respectively.

(43) In some embodiments, the flanged edges 25 are bent toward the inside of the supporting post 22 to form the mounting surfaces. When the baffle plate 24 is mounted in place, the side of the supporting post 22 where the baffle plate 24 is located is an overall flat surface.

(44) In some embodiments, in order to improve the connection strength, as shown in FIG. 8, two side portions of the baffle plate 24 are respectively bent to the side where the supporting post 22 is located to form folded parts 243, and both the clamping blocks 241 and the connecting holes 242 are arranged on the folded parts 243.

(45) In some embodiments, the fire alarming and suppression system for electric vehicle charging station further includes an one-button alarm device arranged on the supporting assembly 20, wherein the one-button alarm device includes a 4G communication module in communication with an alarm platform via a network connection through a 4G mobile communication network, a button arranged to immediately send an alarm signal to the alarm platform when pressed, a microphone for voice calls with the staff of the alarm platform, and a power supply module electrically connected to the 4G communication module and the microphone respectively for power supply.

(46) By providing a one-button alarm device, in case of a fire in the electric vehicle charging station, a person near the one-button alarm device can directly send an alarm signal to the alarm platform by pressing the button, and can talk with the staff of the alarm platform through the microphone at the same time to describe the situation, so as to facilitate the staff of the alarm

platform to dispatch personnel to deal with the fire timely.

(47) In the present disclosure, as a means for sending an alarm signal, the fire alarming and suppression system for electric vehicle charging station further includes an audible and visual alarm device, wherein a control input end of the audible and visual alarm device is connected to a control output end of the local controller, so as to control the audible and visual alarm device to send audible and visual signals when the local controller confirms that there is a fire risk through analysis.

(48) More specifically, the audible and visual alarm device includes a loudspeaker and a light strip that extends in a height direction of the supporting assembly **20**. By providing a light strip extending along the supporting assembly **20**, specifically, in the height direction of the supporting post **22**, the alarm signal is more eye-catching and easier to be noticed.

(49) In some embodiments, the fire alarming and suppression system for an electric vehicle charging station further includes a signal transmission module and a back-end control center, wherein the signal transmission module is arranged in the local controller and used for receiving the image information acquired by the image information collection unit and transmitting the image information; the back-end control center is communicatively connected with the signal transmission module for receiving the image information from the signal transmission module, processing and analyzing the image information, determining whether there is a fire risk at the back end, and providing a fire alarm in real time if it determines that there is a fire risk. With the above scheme, remote alarming can be realized, and an alarm signal can be sent timely once the back-end control center detects a fire situation in the electric vehicle charging station, to ensure the safe operation of the electric vehicle charging station.

(50) While some optional embodiments of the present disclosure are described above in detail with reference to the accompanying drawings, the present disclosure is not limited to those embodiments. Various simple variations may be made to the technical scheme of the present disclosure within the technical concept of the present disclosure. To avoid unnecessary repetitions, various possible combinations are not described specifically in the present disclosure. However, such simple variations and combinations shall also be deemed as having been disclosed herein and falling in the scope of protection of the present disclosure.

Claims

1. A fire alarming and suppression system for an electric vehicle charging station, comprising: a supporting assembly vertically arranged in the charging station; an image information acquisition unit arranged at a top end of the supporting assembly for acquiring image information of electric vehicles in the charging station; a local controller arranged on the supporting assembly for receiving the image information, analyzing and processing the image information, determining whether there is a fire risk in the charging station, and providing a fire alarm if it determines that there is a fire risk; and a box arranged beside the supporting assembly and provided with a fire blanket therein, so that the fire blanket can be taken out of the box and used to cover an electric vehicle in a case that the electric vehicle is on fire.
2. The fire alarming and suppression system for an electric vehicle charging station according to claim 1, wherein a side of the box is fixedly connected to the supporting assembly, so that the bottom of the box is spaced from the ground; and a bottom plate of the box is bent toward the inside of the box to form at least one raised part, and a bearing plate is fixed on the raised part and laid flat on the bottom of the box for bearing the fire blanket.
3. The fire alarming and suppression system for an electric vehicle charging station according to claim 2, wherein the raised part extends in a length direction of the box, an outer side of the bottom plate corresponding to the raised part is formed into a recessed part, a reinforcing plate is arranged in the recessed part, and an end of the reinforcing plate extends out of the recessed part and fixedly

connected to the supporting assembly.

4. The fire alarming and suppression system for an electric vehicle charging station according to claim 3, wherein the reinforcing plate is configured in a square tube shape.

5. The fire alarming and suppression system for an electric vehicle charging station according to claim 3, wherein two boxes are provided and respectively arranged at two sides of the supporting assembly.

6. The fire alarming and suppression system for an electric vehicle charging station according to claim 5, wherein a connecting plate is arranged above the two boxes, two ends of the connecting plate are respectively fixedly connected to sides of the two boxes that face away from each other, the connecting plate is provided with a through-hole for the supporting assembly to pass through, and the connecting plate is connected with the supporting assembly via angular connecting blocks.

7. The fire alarming and suppression system for an electric vehicle charging station according to claim 5, wherein the reinforcing plates at the bottoms of the two boxes respectively extend out of respective recessed parts and are respectively fixedly connected to the supporting assembly.

8. The fire alarming and suppression system for an electric vehicle charging station according to claim 1, wherein a bottom end of the supporting assembly is provided with a mounting plate, which is arranged to be close to the ground for fixing the supporting assembly on the ground in a vertical direction.

9. The fire alarming and suppression system for an electric vehicle charging station according to claim 8, wherein the mounting plate is provided with a connecting part extending in the vertical direction for fixedly connecting to the bottom end of the supporting assembly.

10. The fire alarming and suppression system for an electric vehicle charging station according to claim 1, wherein a front side of the box is provided with an opening, a box door is rotatably connected to the box for closing or opening the opening, a locking mechanism is arranged between the box door and the box for locking or unlocking the box door in a state of closing the opening; the box door is provided with an accommodating cavity for accommodating a key for opening the locking mechanism, and an opening of the accommodating cavity is closed by a piece of glass.

11. The fire alarming and suppression system for an electric vehicle charging station according to claim 10, wherein the box door is provided with a notched part extending in a thickness direction of the box door for mounting the locking mechanism.

12. The fire alarming and suppression system for an electric vehicle charging station according to claim 1, wherein the supporting assembly comprises an upright post and a supporting post, the upright post and the supporting post respectively extend in the vertical direction, and a bottom end of the supporting post is detachably fixed to a top end of the upright post; and the side of the box is fixedly connected to the upright post, the image information acquisition unit is arranged at the top end of the supporting post, and the top end of the upright post is not higher than a top end of the box.

13. The fire alarming and suppression system for an electric vehicle charging station according to claim 12, wherein a connecting pipe is arranged between the upright post and the supporting post, and two ends of the connecting pipe are respectively inserted into the upright post and the supporting post and respectively fixedly connected to the upright post and the supporting post by bolts.

14. The fire alarming and suppression system for an electric vehicle charging station according to claim 1, further comprising an one-button alarm device arranged on the supporting assembly, wherein the one-button alarm device comprises a 4G communication module in communication with an alarm platform via a network connection through a 4G mobile communication network, a button arranged to immediately send an alarm signal to the alarm platform when pressed, a microphone for voice calls with the staff of the alarm platform, and a power supply module electrically connected to the 4G communication module and the microphone respectively for power supply.

15. The fire alarming and suppression system for an electric vehicle charging station according to claim 1, further comprising an audible and visual alarm device, wherein a control input end of the audible and visual alarm device is connected to a control output end of the local controller, so as to control the audible and visual alarm device to send audible and visual signals when the local controller confirms that there is a fire risk through analysis.
16. The fire alarming and suppression system for an electric vehicle charging station according to claim 15, wherein the audible and visual alarm device comprises a loudspeaker and a light strip that extends in a height direction of the supporting assembly.
17. The fire alarming and suppression system for an electric vehicle charging station according to claim 1, further comprising: a signal transmission module arranged in the local controller for receiving the image information acquired by the image information collection unit and transmitting the image information; and a back-end control center communicatively connected with the signal transmission module for receiving the image information from the signal transmission module, processing and analyzing the image information, determining whether there is a fire risk, and providing a fire alarm in the back-end control center in real time if it determines that there is a fire risk.
-