

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12403409
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Meng; Zhiyan

Curly hair doll

Abstract

Systems and methods related to a curly hair doll are provided. A doll includes a head and a plurality of material strands coupled to the head to embody curls of hair. Each material strand may define a three-dimensional (3D) helix formed by a two-dimensional (2D) spiral cut into a flat piece of flexible material. Additional systems and associated methods are also provided.

Inventors:	Meng; Zhiyan (Guangdong, CN)
Applicant:	Meng; Zhiyan (Guangdong, CN)
Family ID:	92361646
Appl. No.:	18/345264
Filed:	June 30, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240416251 A1	Dec. 19, 2024

Foreign Application Priority Data

CN	202321569368.0	Jun. 19, 2023
----	----------------	---------------

Publication Classification

Int. Cl.: A63H3/44 (20060101); A63H3/02 (20060101); A63H9/00 (20060101)

U.S. Cl.:

CPC A63H3/44 (20130101); A63H3/02 (20130101); A63H9/00 (20130101);

Field of Classification Search

CPC: A63H (3/44); A63H (9/00); A63H (37/00)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5180325	12/1992	Eddins	446/385	A63H 3/44
5607338	12/1996	Landi	446/296	A63H 3/44
5807159	12/1997	Watkins	83/924	A63H 37/00
10786747	12/2019	Choi	N/A	A63H 3/44
2006/0141900	12/2005	Wesley	446/394	A63H 3/44
2017/0055616	12/2016	Swoope	N/A	A63H 3/44

Primary Examiner: Ricci; John A

Attorney, Agent or Firm: Dorsey & Whitney LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION

(1) This application claims priority under 35 U.S.C. § 119 (a)-(d) to Chinese Utility Model application No. 202321569368.0, filed on Jun. 19, 2023, which is hereby incorporated by reference for all purposes.

TECHNICAL FIELD

(2) The present disclosure relates generally to dolls, and, more particularly, to systems and methods related to curly hair dolls.

BACKGROUND

(3) Conventional dolls often include features to resemble real or lifelike features, such as curly hair. However, the hair curls of these dolls may not be robust and diminish over time. Therefore, a need exists for improved curly hair doll systems and methods.

BRIEF SUMMARY

(4) Various embodiments of the present disclosure include a doll. The doll includes a head and a plurality of material strands coupled to the head to embody curls of hair. Each material strand may define a three-dimensional (3D) helix formed by a two-dimensional (2D) spiral cut into a flat piece of flexible material.

(5) Various embodiments of the present disclosure include a method of making a doll. The method includes coupling a plurality of material strands to a head of the doll. Each material strand may define a 3D helix formed by a 2D spiral cut into a flat piece of flexible material.

(6) The scope of the invention is defined by the claims, which are incorporated into this section by reference. A more complete understanding of embodiments of the present invention will be afforded to those skilled in the art, as well as a realization of additional advantages thereof, by a consideration of the following detailed description of one or more embodiments. Reference will be made to the appended sheets of drawings that will first be described briefly.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1A is a perspective view of a doll, according to one or more embodiments of the disclosure.
- (2) FIG. 1B is a perspective view of an alternative configuration of the doll, according to one or more embodiments of the disclosure.
- (3) FIG. 2 is an enlarged, fragmentary view of the doll of FIG. 1 and taken along detail 2-2 of FIG. 1.
- (4) FIG. 3 is an end view of a die used in forming a material strand configured to embody a curl of hair, according to one or more embodiments of the disclosure.
- (5) FIG. 4A is a diagram illustrating the formed material strand within the die after stamping, according to one or more embodiments of the disclosure.
- (6) FIGS. 4B-4K are diagrams illustrating example cut configurations to form the material strand, according to one or more embodiments of the disclosure.
- (7) FIG. 5 is a perspective view of the formed material strand defining a 3D helix, according to one or more embodiments of the disclosure.
- (8) FIG. 6 is a flowchart of a method of making a doll, according to one or more embodiments of the disclosure.
- (9) Embodiments of the present disclosure and their advantages are best understood by referring to the detailed description that follows. It is noted that sizes of various components and distances between these components are not drawn to scale in the figures. It should be appreciated that like reference numerals are used to identify like elements illustrated in one or more of the figures.

DETAILED DESCRIPTION

- (10) Embodiments of the present disclosure are directed to systems and methods related to curly hair dolls. A flexible piece of material may be cut (e.g., die cut) into a two-dimensional (2D) spiral, such that once extended, the 2D spiral forms a three-dimensional (3D) helix-type shape. These material strands may be coupled to the head of a doll to embody curls of hair. The shape of the 2D spiral and/or the 3D helix may provide a desired curl and/or bounce-back level or characteristic, such as a desired curl shape when the material strands are extended under their own weight. The material strands may bounce-back to their original curl shapes after user manipulation, such as regardless of degree or time of user manipulation, thereby providing curls that remain constant or generally constant throughout the doll's useful life.
- (11) FIG. 1A is a perspective view of a doll, according to one or more embodiments of the disclosure. Referring to FIG. 1, a doll **100** (e.g., a toy doll) may include a head **106** and a body **108** of certain shapes and configurations to embody various human, animal, or other object characteristics. For instance, the doll **100** may be a human doll, an animal doll, or any other doll, such as to be used as a children's toy, although other configurations are contemplated.
- (12) As shown without intent to limit, the doll **100** embodies a human and includes human-like elements or features, such as hair, arm, and leg-like elements, among others. For example, the head **106** may include facial expressions **114** and a hair region **116**. The facial expressions **114** may be fixed or set, such as by stitching operations to define eyes, a nose, and a mouth, or any combination thereof. In addition or separately, the facial expressions **114** may be defined by one or more elements attached to the head **106**. In embodiments, the facial expressions **114** may be defined by movable, reconfigurable, or actuatable elements representing the eyes, nose, or mouth, or any combination thereof. The hair region **116** may be defined or set off by stitching, material, material color, or material texture, among other distinguishing elements. The body **108**, which is coupled to the head **106** such as by stitching, may include various combinations of arms **120** and/or legs **122** attached to a torso **124**. In embodiments, the body **108** may include fabric or other material

embodying clothing (e.g., a dress, skirt, shirt, pants, shorts, etc.). In embodiments, the clothing may be removable from the body **108**. In addition or separately, the clothing material may define at least portions of the body **108** itself.

(13) In embodiments, the doll **100** may be a soft or plush doll stuffed with flexible material, such as natural or synthetic fiber, batting, cotton, straw, wood wool, plastic pellets, etc. Depending on the application, the doll **100** may be realistic in relative dimensions/sizing or may include abnormal dimensions or sizing, such as having an enlarged head size compared to body size, among other variations. In embodiments, the doll **100** may include various accessories, such as one or more hair, shoe, or clothing accessories, etc. The doll **100** may include a clip **126** to couple the doll **100** to an object, such as a backpack, stand, lanyard, rope, etc.

(14) FIG. **1B** is a perspective view of an alternative configuration of the doll **100**, according to one or more embodiments of the disclosure. Except as otherwise noted below, the doll **100** illustrated in FIG. **1B** includes similar features as described above with reference to FIG. **1A**. Referring to FIG. **1B**, the doll **100**, or at least some features thereof, may include different proportions. For example, the legs **122** may be lengthened compared to the embodiment illustrated in FIG. **1A** to embody a larger or taller doll. In some embodiments, the legs **122** may include a length similar to the torso **124** or a length greater than the torso **124**. Additionally, or alternatively, the doll **100** illustrated in FIG. **1B** may be devoid of one or more features described above. For instance, the doll **100** of FIG. **1B** does not include the clip **126**.

(15) FIG. **2** is an enlarged, fragmentary view of the doll **100** of FIG. **1** and taken along detail 2-2 of FIG. **1**. Referring to FIGS. **1-2**, one or more, such as a plurality of, material strands **130** are coupled to the head **106** to embody curls of hair. For instance, as shown in FIG. **1**, a first plurality of material strands **132** may be coupled together to define a first pigtail or bunch **134**, and a second plurality of material strands **140** may be coupled together to define a second pigtail or bunch **142**, although other configurations are contemplated. The first and second pigtails **134**, **142** may be coupled to opposite sides of the head **106**, such as left and right sides of the head **106**, respectively.

(16) As best illustrated in FIG. **2**, each material strand **130** may include a first end **148** attached to the head **106**, and an unattached second end **150** including a rounded end **152**. In embodiments, the doll **100** includes a hair accessory **160** at each attachment of a pigtail to the head **106** (e.g., at the first ends **148** of the material strands **130**). Although a bow is illustrated, the hair accessory **160** may include a bow, a pin, a band, or a clamp, or any combination thereof. The hair accessory **160** may at least partially conceal the pigtail's attachment to the head **106** and/or otherwise add visual interest to the doll **100**.

(17) The material strands **130** may be formed from flexible material such that the material strands **130** can move and flow (e.g., similar to hair), such as during play of the doll **100**. Some example materials include velvet, crystal velvet, felt, linen, and cloth, without intent to limit. In embodiments, the material strands **130** may be formed of multiple layers of material. For instance, the material strands **130** may be formed of two layers of crystal velvet, although other materials and configurations are contemplated. The multiple layers of material may be laminated (e.g., with adhesive in high temperature) or connected in other manners.

(18) In embodiments, each material strand **130** may be shaped and configured to provide a desired level or characteristic of curl and/or bounce-back. For instance, each material strand **130** may define a curl shape when extended, such as in a natural extended state under its own weight as shown in FIGS. **1-2**. The material strand **130** may be configured to achieve a certain weight so that a 3D spiral of the material strand **130** can bounce back to a 2D shape. User manipulation (e.g., pulling, stretching, lifting, etc.) of the material strand **130** may temporarily alter the curl. However, the material strands **130** may bounce-back to their original curl shapes once released by the user. This bounce-back may occur regardless of degree or time of user manipulation. For example, the material strands **130** may bounce-back to their original curl shapes even after extended use or play of the doll **100**. In this manner, the shape of the material strands **130** in their natural extended states

may remain constant or generally constant throughout the doll's useful life.

(19) FIG. 3 is an end view of a die **300** used in forming the material strands **130**, according to one or more embodiments of the disclosure. FIG. 4A is a diagram illustrating a formed material strand **130** within the die **300** after stamping, according to one or more embodiments of the disclosure. Referring to FIG. 3, the die **300** includes a die body **304** having a cutting edge **306**. As shown, the cutting edge **306** defines a 2D spiral **312** (as shown in dashed lines in FIG. 3). The 2D spiral **312** may include many forms to define the curl shape of the material strands **130**. For example, the 2D spiral **312** may include an Archimedean spiral, an involute spiral, or an Atzema spiral, among other spiral shapes.

(20) Referring to FIG. 4A, the die **300** is used to stamp the 2D spiral **312** into a flat piece of flexible material, such as the materials listed above. As shown, the die **300** may define the first end **148** and the second end **150** with a spiral of material therebetween. The die **300** may form any suitable number of spiral revolutions in the material strand **130**, such as less than one revolution, one revolution, two revolutions, more than two revolutions, or multiples of revolutions (e.g., 1.5 revolutions, 1.75 revolutions, 2.25 revolutions, 2.75 revolutions, etc.). In embodiments, the 2D spiral **312** may curve spirally outward through a certain angle from its second end **150** to its first end **148** to define a desired number of revolutions and/or length of the material strand **130**. For instance, the 2D spiral **312** may spirally curve less than 720-degrees, greater than 720-degrees, between 810-degrees and 900-degrees (e.g., about 858.35-degrees), or any other angle to define the length of the material strand **130** between the first and second ends **148**, **150**. In some examples, the 2D spiral **312** may spirally curve less than 4π radian, greater than 4π radian, between 4.5π radian and 5π radian, about 4.75π radian, etc.

(21) The width of the material strand **130** may be generally uniform or vary along the length of the material strand **130**. For instance, as illustrated in FIG. 4A, the material strand **130** includes various widths along its length, such as a width **400A**, a width **400B**, a width **400C**, a width **400D**, a width **400E**, a width **400F**, and a width **400G** at the locations shown, among other widths and locations. In one embodiment, the widths **400A-400G** may be equal or substantially equal. In other embodiments, the widths **400A-400G** may vary. For instance, in one example, width **400A** may be about 1.4 cm, width **400B** may be about 1.4 cm, width **400C** may be about 1.4 cm, width **400D** may be about 1.4 cm, width **400E** may be about 1.5 cm, width **400F** may be about 1.6 cm, and width **400G** may be about 1.6 cm, although other configurations are contemplated.

(22) With continued reference to FIG. 4A, the material strand **130** may have a first total width **410** and a second total width **412** orthogonal to the first total width **410**. The first and second widths **410**, **412** may be equal or substantially equal, or the first total width **410** may be different than the second total width **412**. For example, the second total width **412** may be greater than the first total width **410**. In one example, the first total width **410** may be about 6 cm, and the second total width **412** may be about 6.8 cm, although other configurations are contemplated.

(23) FIGS. 4B-4K are diagrams illustrating example cut configurations to form the material strand **130**, according to one or more embodiments of the disclosure. Depending on the application, material may be cut (e.g., spirally cut, rotationally cut, etc.) about one or two rotation points to define the material strand **130**. For instance, referring to FIGS. 4B-4C, starting from the center of the 2D spiral **312**, first and second cuts **430**, **432** may be made about a first center **434** to at least partially define the second end **150** (e.g., the rounded end **152**). As shown, each of the first cut **430** and the second cut **432** may be a circular arc subtending 90-degrees about the first center **434**. The first and second cuts **430**, **432** may be defined by a first radius **436** such that the first and second cuts **430**, **432** together define a first semicircle about first center **434** with first radius **436**.

(24) Referring to FIGS. 4D-4E, third and fourth cuts **440**, **442** may be made about a second center **444**. As shown, the second center **444** may be defined at the start of the first cut **430**. As shown, each of the third cut **440** and the fourth cut **442** may be a circular arc subtending 90-degrees about the second center **444**. The third and fourth cuts **440**, **442** may be defined by a second radius **446**.

greater than the first radius **436**. In embodiments, the third and fourth cuts **440**, **442** may together define a first semicircle about second center **444** with second radius **446**.

(25) Referring to FIGS. **4F-4G**, fifth and sixth cuts **450**, **452** may be made about first center **434**. Each of the fifth cut **450** and the sixth cut **452** may be a circular arc subtending 90-degrees about first center **434**. The fifth and sixth cuts **450**, **452** may be defined by a third radius **456** greater than the first radius **436** and the second radius **446**. In embodiments, the fifth and sixth cuts **450**, **452** may together define a second semicircle about first center **434** with third radius **456**.

(26) Referring to FIGS. **4H-4I**, seventh and eighth cuts **460**, **462** may be made about second center **444**. Each of the seventh cut **460** and the eighth cut **462** may be a circular arc subtending 90-degrees about second center **444**. The seventh and eighth cuts **460**, **462** may be defined by a fourth radius **466** greater than the first radius **436**, the second radius **446**, and the third radius **456**. In embodiments, the seventh and eighth cuts **460**, **462** may together define a second semicircle about second center **444** with fourth radius **466**.

(27) Referring to FIGS. **4J-4K**, ninth and tenth cuts **470**, **472** may be made about first center **434**. The ninth cut **470** may be a circular arc subtending 90-degrees about first center **434**. As shown, the tenth cut **472** may be a circular arc subtending 48.35-degrees about first center **434**, although other configurations are contemplated, including greater than 48.35-degrees or less than 48.35-degrees. The ninth and tenth cuts **470**, **472** may be defined by a fifth radius **476** greater than the first radius **436**, the second radius **446**, the third radius **456**, and the fourth radius **466**.

(28) FIG. **5** is a perspective view of a single material strand **130**, according to one or more embodiments of the disclosure. When extended, such as in its natural extended state, each material strand **130** may define a 3D helix **500** formed by the 2D spiral **312** cut into a flat piece of flexible material. The 3D helix **500** may include various shapes defined by the material strand **130** twisting or wrapping (e.g., around a center axis) as the second end **150** of the material strand **130** extends away from the first end **148** to define the strand's curl. Depending on the application, the 3D helix **500** may be defined by a wide or narrow strand of material. A wide strand may define a shorter and/or wider curl, and a narrow strand may define a longer and/or narrower curl. In this manner, the shape of the doll's curls may be defined as desired.

(29) FIG. **6** is a flowchart of a method **600** of making a doll, according to one or more embodiments of the disclosure. For explanatory purposes, the method **600** is described herein with reference to FIGS. **1-5**, although the method **600** is not limited to the embodiments illustrated in FIGS. **1-5**. Note that one or more operations in FIG. **6** may be combined, omitted, and/or performed in a different order as desired.

(30) In block **610**, the method **600** includes forming a plurality of material strands. The material strands may be similar to the material strands **130** described above. For example, each material strand may define a 3D helix (e.g., 3D helix **500**) formed by a 2D spiral (e.g., 2D spiral **312**) cut into a flat piece of flexible material. The 2D spiral may include an Archimedean spiral, an involute spiral, or an Atzema spiral, among other spiral shapes, as described above. Each material strand may include a first end attached to the doll's head, and an unattached second end, as described above. In embodiments, block **610** may include stamping the 2D spiral into the flat piece of flexible material (e.g., using die **300**), such as in the manner and shapes described above.

(31) In block **620**, the method **600** includes coupling the plurality of material strands to a head of a doll (e.g., to the head **106** of doll **100**), such as in a manner as described above. For instance, block **620** may include coupling the first plurality of material strands **132** together to define the first pigtail **134**, and coupling the second plurality of material strands **140** together to define the second pigtail **142**. In such embodiments, block **620** may include coupling the first and second pigtails **134**, **142** to opposite sides of the doll's head. Although two pigtails are shown and described, any number of pigtails may be coupled to the doll, such as no pigtails, one pigtail, or more than two pigtails. In this manner, the term "pigtail" is to be construed broadly as bunches of hair extending from the doll's head, whether in a true pigtail fashion or otherwise.

(32) In block **630**, the method **600** includes coupling a hair accessory (e.g., hair accessory **160**) at each attachment of a pigtail to the doll's head. The hair accessory may include at least one of a bow, a pin, a band, or a clamp, as described above.

(33) In block **640**, the method **600** includes coupling a body (e.g., body **108**) to the head of the doll. As detailed above, the body may include various combinations of arms and/or legs attached to a torso, such as two or more legs, two arms, or fewer than two arms, or any combination thereof. In this manner, the doll may embody a human or an animal as desired.

(34) While certain exemplary embodiments of the invention have been described and shown in the accompanying drawings, it is to be understood that such embodiments are merely illustrative of and not restrictive on the broad invention, and that the embodiments of the invention not be limited to the specific constructions and arrangements shown and described, since various other modifications may occur to those ordinarily skilled in the art. The intention is to cover all modifications, equivalents and alternatives falling within the spirit and scope of the disclosure as defined by the claims.

(35) For example, the elements and teachings of the various embodiments may be combined in whole or in part in some or all of the embodiments. In addition, one or more of the elements and teachings of the various embodiments may be omitted, at least in part, and/or combined, at least in part, with one or more of the other elements and teachings of the various embodiments. In addition, while different steps, processes, and procedures are described as appearing as distinct acts, one or more of the steps, one or more of the processes, and/or one or more of the procedures may also be performed in different orders, simultaneously, and/or sequentially. In some embodiments, the steps, processes, and/or procedures may be merged into one or more steps, processes, and/or procedures. In some embodiments, one or more of the operational steps in each embodiment may be omitted.

Claims

1. A doll comprising: a head; and a plurality of material strands coupled to the head to embody curls of hair, wherein each material strand defines a three-dimensional (3D) helix formed by a two-dimensional (2D) spiral cut into a flat piece of flexible material.
2. The doll of claim 1, wherein the 2D spiral is stamped into the flat piece of flexible material.
3. The doll of claim 1, wherein the 2D spiral comprises an Archimedean spiral, an involute spiral, or an Atzema spiral.
4. The doll of claim 1, wherein each material strand comprises: a first end attached to the head; and an unattached second end comprising a rounded end.
5. The doll of claim 1, wherein the plurality of material strands comprises: a first plurality of material strands coupled together to define a first pigtail; and a second plurality of material strands coupled together to define a second pigtail.
6. The doll of claim 5, wherein the first and second pigtails are coupled to opposite sides of the head.
7. The doll of claim 5, further comprising a hair accessory at each attachment of a pigtail to the head.
8. The doll of claim 7, wherein the hair accessory comprises at least one of a bow, a pin, a band, or a clamp.
9. The doll of claim 1, further comprising a body coupled to the head.
10. The doll of claim 1, wherein the doll embodies a human.
11. A method of making a doll, the method comprising: coupling a plurality of material strands to a head of the doll, wherein each material strand defines a three-dimensional (3D) helix formed by a two-dimensional (2D) spiral cut into a flat piece of flexible material.
12. The method of claim 11, further comprising forming the plurality of material strands, wherein the forming comprises stamping the 2D spiral into the flat piece of flexible material.

13. The method of claim 11, wherein the 2D spiral comprises an Archimedean spiral, an involute spiral, or an Atzema spiral.
 14. The method of claim 11, wherein each material strand comprises: a first end attached to the head; and an unattached second end.
 15. The method of claim 11, wherein the coupling comprises: coupling a first plurality of material strands together to define a first pigtail; and coupling a second plurality of material strands together to define a second pigtail.
 16. The method of claim 15, wherein the coupling the plurality of material strands to the head of the doll comprises coupling the first and second pigtails to opposite sides of the head.
 17. The method of claim 15, further comprising coupling a hair accessory at each attachment of a pigtail to the head.
 18. The method of claim 17, wherein the hair accessory comprises at least one of a bow, a pin, a band, or a clamp.
 19. The method of claim 11, further comprising coupling a body to the head.
 20. The method of claim 11, wherein the doll embodies a human.
-