

# US Patent & Trademark Office

## Patent Public Search | Text View

---

|                      |                       |
|----------------------|-----------------------|
| United States Patent | 12404933              |
| Kind Code            | B2                    |
| Date of Patent       | September 02, 2025    |
| Inventor(s)          | Fujita; Wakana et al. |

---

### Sealing device

---

#### Abstract

A sealing device to seal an annular space formed by a fixed side member and a rotation side member, including a first seal member and a second seal member, and being provided between the two members in a state in which the first and the second seal members are combined. The sealing device includes a coating layer having an easily scraped property and being provided at least at one place in a gap between facing regions in which the first and the second seal members are provided so as to face each other in an initial state in which the first and the second seal members are combined. The coating layer slidably contacts a region to which the coating layer faces in a state in which the first and the second seal members rotate relative to each other from the initial state.

---

|                   |                                                                |
|-------------------|----------------------------------------------------------------|
| <b>Inventors:</b> | <b>Fujita; Wakana (Akaiwa, JP), Ohmori; Keita (Akaiwa, JP)</b> |
| <b>Applicant:</b> | <b>UCHIYAMA MANUFACTURING CORP. (Okayama, JP)</b>              |
| <b>Family ID:</b> | <b>92459753</b>                                                |
| <b>Assignee:</b>  | <b>UCHIYAMA MANUFACTURING CORP. (Okayama, JP)</b>              |
| <b>Appl. No.:</b> | <b>18/595000</b>                                               |
| <b>Filed:</b>     | <b>March 04, 2024</b>                                          |

#### Prior Publication Data

|                            |                         |
|----------------------------|-------------------------|
| <b>Document Identifier</b> | <b>Publication Date</b> |
| US 20240301917 A1          | Sep. 12, 2024           |

#### Foreign Application Priority Data

|    |             |               |
|----|-------------|---------------|
| JP | 2023-034552 | Mar. 07, 2023 |
|----|-------------|---------------|

---

#### Publication Classification

**Int. Cl.: F16J15/3256** (20160101); **F16C33/78** (20060101); **F16C33/80** (20060101); **F16J15/447** (20060101)

**U.S. Cl.:**

**CPC F16J15/3256** (20130101); **F16C33/7883** (20130101); **F16C33/805** (20130101); **F16J15/4472** (20130101); F16C33/7823 (20130101); F16C33/80 (20130101); F16J15/4474 (20130101); F16J15/4476 (20130101); F16J15/4478 (20130101)

## Field of Classification Search

**CPC:** F16C (33/7823); F16C (33/7826); F16C (33/7883); F16C (33/80); F16J (15/4472)

---

## References Cited

### U.S. PATENT DOCUMENTS

| Patent No.   | Issued Date | Patentee Name  | U.S. Cl. | CPC          |
|--------------|-------------|----------------|----------|--------------|
| 5186472      | 12/1992     | Romero         | 277/572  | F16J 15/3256 |
| 6702295      | 12/2003     | Kapcoe         | 277/572  | F16J 15/3252 |
| 8657296      | 12/2013     | Banowetz       | 277/412  | F16J 15/3256 |
| 9151391      | 12/2014     | Kern-Trautmann | N/A      | B23P 6/00    |
| 9523059      | 12/2015     | Kunishima      | N/A      | C08J 7/043   |
| 10294441     | 12/2018     | Sasaki         | N/A      | C10M 107/32  |
| 11428110     | 12/2021     | Jouy           | N/A      | F01D 11/127  |
| 11739654     | 12/2022     | Perez          | 277/412  | F16J 15/447  |
| 2002/0064325 | 12/2001     | Yeo            | 384/484  | F16C 33/6618 |
| 2011/0089642 | 12/2010     | Terasawa       | 277/562  | F16C 41/007  |
| 2011/0222805 | 12/2010     | Sasaki         | 384/477  | F16C 33/7823 |
| 2014/0333032 | 12/2013     | Kern-Trautmann | 277/412  | F16J 15/453  |
| 2016/0068779 | 12/2015     | Kunishima      | 508/106  | F16J 15/324  |
| 2017/0073605 | 12/2016     | Sasaki         | N/A      | F16D 69/025  |
| 2020/0400033 | 12/2019     | Jouy           | N/A      | F16J 15/447  |
| 2022/0120189 | 12/2021     | Perez          | N/A      | F01D 11/02   |

### FOREIGN PATENT DOCUMENTS

| Patent No.  | Application Date | Country | CPC |
|-------------|------------------|---------|-----|
| 2009-298367 | 12/2008          | JP      | N/A |
| 2011-012740 | 12/2010          | JP      | N/A |

---

*Primary Examiner:* Foster; Nicholas L

*Attorney, Agent or Firm:* MUNCY, GEISSLER, OLDS & LOWE, P.C.

---

## Background/Summary

### BACKGROUND OF THE INVENTION

#### Field of the Invention

(1) The present invention relates to a sealing device which seals an annular space formed by two

members, a fixed side member and a rotation side member, which includes a first seal member to be fitted to the rotation side member and a second seal member to be fitted to the fixed side member, and which is provided between the two members.

#### Description of the Related Art

(2) The following Patent Documents 1 and 2 disclose a sealing device which has the above-mentioned structure provided in a wheel bearing device. The following Patent Document 1 describes an example, etc., in which a water-repellent treated layer is each provided on contact parts of an inner member and an outer member with a sealing member and the water-repellent treated layer is provided on an entire surface of the sealing member. According to the above, it is said that an intrusion of muddy water or the like is suppressed by providing the water-repellent treated layer on a part into which muddy water or the like is likely to intrude. Further, the following Patent Document 2 describes a sealing device in which a lubrication film using hydrophilic resin as binder is formed on a surface of a lip made of rubber provided for the sealing device. According to the above, by forming the lubrication film on the lip, it is said that sliding resistance of the lip is suppressed and thereby an effect of reduction in rotational torque is achieved.

#### RELATED ART DOCUMENT

##### Patent Document

(3) Patent Document 1: Japanese Unexamined Patent Application Publication No. 2009-298367

Patent Document 2: Japanese Unexamined Patent Application Publication No. 2011-12740

#### SUMMARY OF THE INVENTION

##### Problems to be Solved by the Invention

(4) Meanwhile, the sealing device as described above has a problem to achieve both sealing performance and torque reduction. In one well-known solution to solve the problem, a labyrinth, i.e., a gap, is structured to suppress intrusion of muddy water or the like instead of arranging a seal lip at a region into which muddy water or the like intrudes. The smaller the gap constituting the labyrinth becomes, the more the sealing performance is improved and the torque reduction is achieved since the gap does not slidably contact a member which is arranged to face the gap. However, in the case of the sealing device which is constituted by two members and is provided between the two members, since a dimensional tolerance or the like of each member and each part needs to be considered, there is a limit to a dimension of the labyrinth which is possible to be designed.

(5) The present invention is proposed in view of the above-mentioned problems, and an object of the present invention is to provide a sealing device which achieves both sealing performance and torque reduction even without considering a dimensional tolerance of each member and each part which constitute the sealing device.

##### Means of Solving the Problems

(6) In order to achieve the above-mentioned object, a sealing device of one aspect of the present invention seals an annular space formed by two members, a fixed side member and a rotation side member which rotates coaxially relative to the fixed side member, includes a first seal member to be fitted to the rotation side member and a second seal member to be fitted to the fixed side member, and is provided between the two members in a state in which the first seal member and the second seal member are combined. The sealing device includes a coating layer having an easily scraped property and being provided at least at one place in a gap between facing regions in which the first seal member and the second seal member are provided so as to face each other in an initial state in which the first seal member and the second seal member are combined, the coating layer slidably contacts a region to which the coating layer faces in a state in which the first seal member and the second seal member rotate relative to each other from the initial state.

(7) In the sealing device of another aspect of the present invention, the first seal member includes a first fitting cylindrical portion to be fitted to the rotation side member, a first disk portion extending in outer diametrical direction from one end portion of the first fitting cylindrical portion, and an

extension cylindrical portion extending in axial direction from one end portion of the first disk portion on an outer diametrical side, the second seal member includes a second fitting cylindrical portion to be fitted to the fixed side member, the extension cylindrical portion of the first seal member and the second fitting cylindrical portion of the second seal member are provided so as to face each other in radial direction in a state in which the sealing device is provided between the fixed side member and the rotation side member, and the gap between the facing regions can be a gap between the extension cylindrical portion and the second fitting cylindrical portion.

(8) In the sealing device of another aspect of the present invention, the first seal member includes a first fitting cylindrical portion to be fitted to the rotation side member and a first disk portion extending in outer diametrical direction from the one end portion of the first fitting cylindrical portion, the second seal member includes a core body member having a second fitting cylindrical portion to be fitted to the fixed side member, and a seal lip portion fixed to the core body member, the seal lip portion is provided so as to slidably contact the first disk portion of the first seal member, the seal lip portion and the first disk portion face each other in axial direction, and the gap between the facing regions can be a gap between the first disk portion and the seal lip portion.

(9) Further, in the sealing device of another aspect of the present invention, an uneven portion or a roughed surface portion of which surface is rougher than other surfaces can be provided on at least either one of surfaces in which the extension cylindrical portion and the second fitting cylindrical portion face each other. Furthermore, in the sealing device of another aspect of the present invention, the coating layer can be composed of a solid lubricant into which a powdered additive to reduce a coefficient of friction is mixed, or can be composed of a liquid adhesive of a curing reaction type.

#### Effects of the Invention

(10) Constituted as above, the sealing device of the present invention achieves both sealing performance and torque reduction even without considering a dimensional tolerance of each member and each part which constitute the sealing device.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a schematic longitudinal cross-sectional view illustrating one example of the bearing device to which the sealing device according to one embodiment of the present invention is applied.

(2) FIGS. 2A and 2B are views illustrating the sealing device according to the first embodiment of the present invention. FIG. 2A is a schematic cross-sectional view illustrating the initial state in which the first seal member and the second seal member are combined. FIG. 2B is a schematic cross-sectional view illustrating a state in which a labyrinth is formed by relative rotation of the first seal member and the second seal member.

(3) FIGS. 3A-3C are partially enlarged views for illustrating a modified example of the sealing device according to the first embodiment. FIG. 3A is a schematic cross-sectional view illustrating only one member at which a projection portion is provided. FIG. 3B is a schematic cross-sectional view illustrating the initial state in which the first seal member and the second seal member are combined. FIG. 3C is a schematic cross-sectional view illustrating the state in which the labyrinth is formed by the relative rotation of the first seal member and the second seal member.

(4) FIGS. 4A and 4B are views illustrating the second embodiment according to the present invention, and is an enlarged view of the part Y in FIG. 1. FIG. 4A is a schematic cross-sectional view illustrating an initial assembled state in which the first seal member and the second seal member are combined. FIG. 4B is a schematic cross-sectional view illustrating the state in which the labyrinth is formed by the relative rotation of the first seal member and the second seal member.

(5) FIGS. 5A-5C are partially enlarged views for explaining a modified example of the sealing device according to the second embodiment. FIG. 5A is a schematic cross-sectional view illustrating only one member to which roughing surface treatment is performed. FIG. 5B is a schematic cross-sectional view illustrating the initial state in which the first seal member and the second seal member are combined. FIG. 5C is a schematic cross-sectional view illustrating the state in which the labyrinth is formed by the relative rotation of the first seal member and the second seal member.

(6) FIGS. 6A and 6B are views illustrating the third embodiment according to the present invention, and is an enlarged view of the part X in FIG. 1. FIG. 6A is a schematic cross-sectional view illustrating the initial state in which the first seal member and the second seal member are combined. FIG. 6B is a schematic cross-sectional view illustrating the state in which the labyrinth is formed by the relative rotation of the first seal member and the second seal member.

(7) FIG. 6C is a partially enlarged view of FIG. 6B.

(8) FIGS. 7A and 7B are views illustrating the fourth embodiment according to the present invention, and is an enlarged view of the Part X in FIG. 1. FIG. 7A is a schematic cross-sectional view illustrating an initial assembled state between the two members. FIG. 7B is a schematic cross-sectional view illustrating the state in which the labyrinth is formed by the relative rotation of the first seal member and the second seal member.

(9) FIGS. 8A and 8B are views for illustrating a modified example of the sealing device according to the fourth embodiment, and is an enlarged view of the part X in FIG. 1. FIG. 8A is a schematic cross-sectional view illustrating the initial assembled state between the two members.

(10) FIG. 8B is a schematic cross-sectional view illustrating the state in which the labyrinth is formed by the relative rotation of the first seal member and the second seal member.

#### DESCRIPTION OF THE EMBODIMENTS

(11) Each embodiment of the present invention is explained below based on the drawings. In some figures, part of detailed reference signs allotted to other figures are omitted. In addition, a side towards a wheel along a shaft L is hereinafter referred to as a wheel side, i.e., the left side of FIG. 1 and the like, and a side towards a vehicle body is referred to as a vehicle body side, i.e., the right side of FIG. 1 and the like.

(12) A sealing device according to the present embodiment seals an annular space S formed by two members, a fixed side member 2 and a rotation side member 5 which rotates coaxially relative to the fixed side member 2, includes a first seal member 10 to be fitted to the rotation side member 5 and a second seal member 20 to be fitted to the fixed side member 2, and is provided between the two members in a state in which the first seal member 10 and the second seal member 20 are combined. The sealing device is provided with a coating layer 40 having an easily scraped property and being provided at least at one place in a gap between facing regions of the first seal member 10 and the second seal member 20 provided so as to face each other in an initial state in which the first seal member 10 and the second seal member 20 are combined; the coating layer 40 is provided so as to slidably contact a facing region thereof in a state in which the first seal member 10 and the second seal member 20 rotate relative to each other in the initial state. Therefore, when the rotation side member 5 rotates, the coating layer 40 slidably contacts either of the first seal member 10 or the second seal member 20, and the coating layer 40 is scraped by such sliding contact, thereby forming a minute gap. Then, the gap acts as a labyrinth having a sealing function. The details are explained below.

#### First Embodiment

(13) First, a sealing device 8 according to the first embodiment is explained below with reference to FIG. 1 to FIG. 3. FIG. 1 illustrates a bearing device 1 on which the sealing device 8 is mounted. The bearing device 1 is constituted by including an outer ring 2 which supports a wheel of a vehicle, not illustrated, in an axially rotatable manner and generally corresponds to the above-described fixed side member, an inner ring 5 which corresponds to the above-described rotation

side member, and two rows of rolling elements **6 . . .** (balls) which are interposed between the outer ring **2** and the inner ring **5**. The inner ring **5** is constituted as the rotation side member by a hub wheel **3** and an inner ring member **4**, and the inner ring member **4** is integrally fitted to a vehicle body side of the hub wheel **3**. A drive shaft **7** is coaxially spline-fitted to the hub wheel **3**, and is connected to a drive source, i.e., a drive transmission portion, not illustrated, through a constant velocity joint **70**. The drive shaft **7** is integrated with the hub wheel **3** by a nut **71**, and thereby the hub wheel **3** is prevented from falling off from the drive shaft **7**. The inner ring **5**, i.e., the hub wheel **3** and the inner ring member **4**, is a rotation member which is rotatable around the shaft **L** relative to the outer ring **2**; the outer ring **2** and the inner ring **5** constitute two members which rotate relative to each other; and thereby the annular space **S** is formed. Inside the annular space **S**, two rows of rolling elements **6 . . .** retained by a retainer **6a** are rotatably interposed between a bearing ring **2a** of the outer ring **2** and a bearing ring **3a** of the hub wheel **3**, and between the bearing ring **2a** of the outer ring **2** and a bearing ring **4a** of the inner ring member **4**. The hub wheel **3** includes a hub wheel body **30** in a cylindrical shape, and a hub flange **32** which is formed so as to extend radially outward from the hub wheel body through a rising portion **31**; the wheel is attached and fixed to the hub flange **32** by a bolt **33** and a nut, not illustrated. The sealing device **8** is provided for sealing the annular space **S** between the outer ring **2** and the inner ring member **4**, and is attached to an end portion of the outer ring **2** on the vehicle body side.

(14) The sealing device **8** includes the first seal member **10** and the second seal member **20**. The first seal member **10** is formed by pressing a steel plate such as SPCC or SUS, and is formed in a cylindrical shape of which cross section on one side is approximately in a U shape. The first seal member **10** is provided with a first fitting cylindrical portion **12** in a cylindrical shape to be fitted onto an outer circumferential face **4b** of the inner ring member **4**, a first disk portion **13** extending in the outer diametrical direction from one end portion **12a** of the first fitting cylindrical portion **12**, and an extension cylindrical portion **11** extending in the axial direction from one end portion **13a** of the first disk portion **13** on the outer diametrical side. Although not illustrated in the example illustrated in FIG. 2, a configuration can also be adopted, in which a magnetic encoder in a disk shape in which a N pole and a S pole are alternatively magnetized in the circumferential direction is provided on an outer face **13b** of the first disk portion **13** on the vehicle body side and thereby rotational speed of the wheel or the like is detected by the magnetic encoder and a magnetic sensor, not illustrated, provided at the vehicle body.

(15) The second seal member **20** includes a core body member **21** and a seal lip portion **24**. The core body member **21** is formed by pressing a steel plate such as SPCC or SUS, and is formed in a cylindrical shape of which cross section on one side is approximately in an inverted L shape. The core body member **21** includes a second fitting cylindrical portion **22** in a cylindrical shape to be fitted to an inner circumferential face **2b** of the outer ring **2** and a second disk portion **23** extending in the inner diametrical direction from one end portion **22a** of the second fitting cylindrical portion **22**. The second disk portion **23** has a first flat portion **23c** on which the outer face **13b** of the first disk portion **13** is stacked when sealing devices **8, 8** are stacked to each other and transported before assembling the sealing device **8** to the bearing device **1**, a slope portion **23d** which is inclined, and a second flat portion **23e** extending in the inner diametrical direction. The seal lip portion **24** is made of an elastic body such as rubber, and includes a seal base portion **24a** fixed to the core body member **21**, a plurality of axial lips **24b, 24b** which are formed by extending in the axial direction from the seal base portion **24a**, a grease lip **24c** extending inward in the diametrical direction, i.e., a side of the annular space **S**, from the seal base portion **24a**, and an annular projection portion **24d** provided on an outer diametrical side of the other end portion **22b** of the second fitting cylindrical portion **22**.

(16) The seal base portion **24a** is arranged so as to entirely cover an inner face side of the core body member **21**, and one end portion of the seal base portion **24a** is provided so as to wrap around one end portion **23a** of the second disk portion **23** on an inner diametrical side. The other end of the

seal base portion **24a** is provided so as to wrap around the other end portion **22b** of the second fitting cylindrical portion **22**. The axial lips **24b**, **24b** are formed so as to be inclined obliquely in the outer diametrical direction toward a side of an inner face **13c** of the first disk portion **13**. A tip end portion **24ba** of the axial lip **24b** which is arranged on the inner diametrical side among the plurality of axial lips **24b**, **24b** is elastically deformed to slidably contact the inner face **13c** of the first disk portion **13**; and the axial lip **24b** which is arranged on an outer diametrical side is provided in a non-contact state. The tip end portion **24ba** of the axial lip **24b** which slidably contacts the inner face **13c** of the first disk portion **13** is filled with grease, not illustrated, for improving a sliding property. The grease lip **24c** is formed to be inclined in an annular space **S** direction from a part of the seal base portion **24a** on the inner diametrical side toward an inner face **12b** of the first fitting cylindrical portion **12** which is arranged so as to face each other; and a tip end portion **24ca** of the grease lip **24c** slidably contacts the inner face **12b** of the first fitting cylindrical portion **12** in an elastically deformed state. The tip end portion **24ca** of the grease lip **24c** which slidably contacts the inner face **12b** of the first fitting cylindrical portion **12** is also filled with grease, not illustrated, for improving the sliding property. The annular projection portion **24d** is formed to protrude toward the outer diametrical side; when the second seal member **20** is fitted to the inner circumferential face **2b** of the outer ring **2**, the annular projection portion **24d** is provided so as to be interposed in a compressed state between the inner circumferential face **2b** of the outer ring **2** and the seal base portion **24a**. By interposing the annular projection portion **24d** in the compressed state between the inner circumferential face **2b** of the outer ring **2** and the seal base portion **24a**, intrusion of muddy water or the like into a fitting region between the inner circumferential face **2b** of the outer ring **2** and the second fitting cylindrical portion **22** of the core body member **21** from an outer space is suppressed.

(17) The first seal member **10** and the second seal member **20** are combined so that the inner face **13c** of the first disk portion **13** and an inner face **23b** of the second disk portion **23** face each other in the axial direction. Further, the first seal member **10** and the second seal member **20** are arranged so that the extension cylindrical portion **11** and the second fitting cylindrical portion **22** face each other in the radial direction and so that the first disk portion **13** and the second disk portion **23** face each other in the axial direction. Furthermore, in the sealing device **8**, the coating layer **40** having the easily scraped property is provided in the gap in the facing regions in which the first seal member **10** and the second seal member **20** are provided so as to face each other, i.e., a gap between an outer diametrical face **11b** of the extension cylindrical portion **11** and an inner diametrical face **22c** of the second fitting cylindrical portion **22**, and a gap between one end portion **11a** of the extension cylindrical portion **11** and the inner face **23b** of the second disk portion **23**. The coating layer **40** is softer than the seal lip portion **24** in a solidified state, and has a characteristic of being easily worn away. Specifically, in the initial state in which the first seal member **10** and the second seal member **20** are combined, in the gap between the outer diametrical face **11b** of the extension cylindrical portion **11** and the inner diametrical face **22c** of the second fitting cylindrical portion **22**, the coating layer **40** is provided over an entire surface without any gaps. More specifically, the coating layer **40** is provided by applying a liquid coating agent to an inner diametrical fixed face **24aa** of the seal base portion **24a** fixed to the inner diametrical face **22c** of the second fitting cylindrical portion **22**. An initial application amount of the coating agent before solidifying is preferably executed so as to be slightly larger than an interval of the gap between the facing region, as illustrated by two-dot chain lines in FIG. 2A. Further, when the first seal member **10** and the second seal member **20** are combined in such a state, the coating agent is provided up to a side of an internal corner portion, i.e., a vicinity of the one end portion **22a** of the second fitting cylindrical portion **22**, which is constituted by the second fitting cylindrical portion **22** and the second disk portion **23**. Furthermore, when the coating agent is solidified, the coating layer is further provided up to a gap formed by the one end portion **11a** of the extension cylindrical portion **11**, an inner face side of the first flat portion **23c** of the second disk portion **23**, and an inner

face side of the slope portion **23d**. The coating layer **40** becomes fixed to the inner diametrical fixed face **24aa** and an outer diametrical fixed face **24ab** of the seal base portion **24a**, and also becomes in contact with the outer diametrical face **11b** and the one end portion **11a** of the extension cylindrical portion **11**, referring to FIG. 2A.

(18) The coating layer **40** used here is not particularly limited as long as the coating layer **40** has the easily scraped property, i.e., easiness to be scraped, in which the coating layer **40** is scraped by rotating the first seal member **10** and the second seal member **20** relative to each other, and thereby minute gaps **L1**, **L2**, referring to FIG. 2B, are constituted. After the minute gaps **L1**, **L2** are formed, the coating layer **40** also has viscosity and shape retention which are maintained with the minute gaps **L1**, **L2** ensured in the gap between the facing regions.

(19) As for the coating agent becoming the coating layer **40**, a solid lubricant, a liquid adhesive, or the like is exemplified. Although the solid lubricant is not particularly limited, molybdenum disulfide, graphite, PTFE (polytetrafluoroethylene), or the like can be adopted, for example; the solid lubricant having a coefficient of friction of 0.1 or less, for example, 0.04 to 0.1 etc., is adopted. Further, the solid lubricant can be mixed with a powdered additive which further reduces the coefficient of friction. According to the mentioned configuration, friction resistance until the gap is formed by scraping is suppressed. Furthermore, the solid lubricant can be mixed with a fluororesin agent having water repellency as binder. If a water-repellent material is used as the binder of the solid lubricant, since the fluororesin agent is not strong against friction, the easily scraped property of the coating layer **40** is not affected; a labyrinth passage is to be covered with the coating layer **40** having the water repellency after the gaps **L1**, **L2** are formed, thereby more effectively preventing intrusion of muddy water or the like from the outside. Furthermore, when the solid lubricant with such a low coefficient of friction is adopted, even if abrasion powder after being scraped mixes with the grease filled in the axial lip **24b** or the like, since the abrasion powder after being scraped also has a low coefficient of friction, an effect on grease of the lubricant is suppressed.

(20) A layer thickness of the coating layer **40** is set to be approximately 500  $\mu\text{m}$  to 2 mm since there is no gap between the facing regions in which the first seal member **10** and the second seal member **20** face each other. When the layer thickness becomes less than 500  $\mu\text{m}$ , there is a fear that the inner diametrical fixed face **24aa** of the seal base portion **24a** and the outer diametrical face **11b** of the extension cylindrical portion **11** contact each other at the time of rotation of the inner ring **5** or the like. Further, when the layer thickness exceeds 2 mm, design dimensions of the first seal member **10** and the second seal member **20** which constitute the sealing device **8** is affected.

(21) In the example illustrated in FIG. 2A, the coating agent is applied to the inner diametrical fixed face **24aa** of the second seal member **20**; by combining the first seal member **10** and the second seal member **20**, the coating agent is solidified in a state of being provided up to the internal corner portion, i.e., the vicinity of the one end portion **22a** of the second fitting cylindrical portion **22**, which is constituted by the second fitting cylindrical portion **22** and the second disk portion **23** as illustrated in FIG. 2A; and thereby the coating agent becomes the coating layer **40**. Then, when the first seal member **10** and the second seal member **20** rotate relative to each other from the above-mentioned initial state, the coating layer **40** slidably contacts the first seal member **10** and is scraped by such sliding contact, thereby constituting the minute gaps **L1**, **L2**. More specifically, when the first seal member **10** and the second seal member **20** rotate relative to each other, the coating layer **40** which contacts the outer diametrical face **11b** of the extension cylindrical portion **11** and the one end portion **11a** of the extension cylindrical portion **11** is scraped until the coating layer **40** becomes a non-contact state relative to the outer diametrical face **11b** of the extension cylindrical portion **11** and the one end portion **11a** of the extension cylindrical portion **11**, thereby forming the minute gaps **L1**, **L2** as illustrated in FIG. 2B. The gaps **L1**, **L2** formed as above are formed between the outer diametrical face **11b** of the extension cylindrical portion **11** of the first seal member **10** and the coating layer **40** and between the one end portion **11a** of the extension

cylindrical portion **11** and the coating layer **40**; in such a case, a side to be rotated can be either the first seal member **10** or the second seal member **20**.

(22) Herein, initial relative rotation of the first seal member **10** and the second seal member **20** for forming the gaps **L1**, **L2** can form the minute gaps **L1**, **L2** by rotating the inner ring member **4** as the rotation side member in such a manner that the sealing device **8** is attached between the outer ring **2** and the inner ring member **4** of the bearing device **1** illustrated in FIG. **1**. In such a case, in a state in which the sealing device **8** is provided between the outer ring **2** and the inner ring member **4**, the extension cylindrical portion **11** of the first seal member **10** and the second fitting cylindrical portion **22** of the second seal member **20** are provided so as to face each other in the radial direction; the one end portion **11a** of the extension cylindrical portion **11** of the first seal member **10** and the second disk portion **23** of the second seal member **20** are provided so as to face each other in the axial direction. Then, between the above-described facing regions in the radial direction and in the axial direction, the coating layer **40** provided without any gaps is scraped by rotation of the inner ring member **4**, thereby forming the minute gaps **L1**, **L2** between the facing regions in the sealing device **8**. The gaps **L1**, **L2** formed as above achieve extremely small gap dimensions which are difficult to be formed by processing or the like. Therefore, the gaps **L1**, **L2** act as the labyrinths having the sealing function, and a non-contact sealing structure is formed, thereby achieving torque reduction. Further, since the minute gaps **L1**, **L2** are formed by the initial relative rotation after the first seal member **10** and **10**) the second seal member **20** are combined, even if there is a dimensional tolerance between the first seal member **10** and the second seal member **20**, variation in size of the gaps due to an influence of the dimensional tolerance is suppressed.

#### MODIFIED EXAMPLE

(23) Next, a modified example of the sealing device **8** is described below with reference to FIG. **3A** to FIG. **3C**. Explanations for configurations and effects which are common to the first embodiment are omitted.

(24) The modified example illustrated in FIG. **3A** to FIG. **3C** is different from the above-described embodiments in that, when the first seal member **10** and the second seal member **20** rotate relative to each other, the coating layer **40** slidably contacts the second seal member **20** and is scraped by such sliding contact, thereby constituting the minute gap **L1**. Further, the present modified example is different from the above-described embodiments in that a convex portion **25a** which constitutes an uneven portion **25** at the inner diametrical fixed face **24aa** of the seal base portion **24a** is provided. A configuration of the uneven portion **25** is not limited to that in the figures; the number of the convex portion **25a** can be greater than that in the figures as long as unevenness promotes the easily scraped property of the coating layer **40**. Further, the convex portion **25a** and a concave portion **25b** illustrated in FIG. **3** each have a rectangular shape in a cross-sectional view, but can have a curved shape or a triangular shape. Furthermore, the uneven portion **25** can be provided over a whole circumference, can be provided intermittently at intervals even half the circumference, or can be arranged equally or randomly. As illustrated in FIG. **3A**, when the uneven portion **25** is constituted at the inner diametrical fixed face **24aa**, the coating agent is applied to approximately an entire surface of the outer diametrical face **11b** of the first seal member **10**, and thereby the coating layer **40** is provided on the outer diametrical face **11b** of the extension cylindrical portion **11** of the first seal member **10**. Thereafter, as illustrated in FIG. **3B**, the first seal member **10** and the second seal member **20** are combined. Then, in a state in which the first seal member **10** and the second seal member **20** rotate relative to each other in the initial state in which the first seal member **10** and the second seal member **20** are combined, the coating layer **40** is surely scraped by the uneven portion **25**, thereby forming the minute gaps **L1**, **L2** on a side of the inner diametrical fixed face **24aa** as illustrated in FIG. **3C**.

#### Second Embodiment

(25) Next, a sealing device **9** according to the second embodiment is explained below with

reference to FIG. 4. Explanations for configurations and effects which are common to the first embodiment are omitted. The sealing device **9** is provided for sealing the annular space **S** between the outer ring **2** and the hub wheel **3**, and is attached to the end portion of the outer ring **2** on the wheel side.

(26) The sealing device **9** includes the first seal member **10** and the second seal member **20**. The first seal member **10** is formed by pressing a steel plate such as SPCC or SUS, and is formed in a cylindrical shape of which cross section on one side is approximately in the U shape; the extension cylindrical portion **11** extending into the axial direction from the one end portion **13a** of the first disk portion **13** on the outer diametrical side is provided with a step portion **11c** which is formed in a stepped shape. The first disk portion **13** is provided up to a position approximately the same as an outer circumferential face **2c** of the outer ring **2**; in a state of being attached to the hub wheel **3**, the extension cylindrical portion **11** is provided on the outer diametrical side further than the outer circumferential face **2c** and is arranged so as to cover an end portion of the outer circumferential face **2c** of the outer ring **2**. The first fitting cylindrical portion **12** is fitted to the hub wheel body **30**, and the first disk portion **13** is mounted in an abutting state against the rising portion **31**.

(27) The second seal member **20** includes the core body member **21** and the seal lip portion **24**. The core body member **21** is formed by pressing a steel plate such as SPCC or SUS, and is formed in the cylindrical shape of which cross section on one side is approximately in the inverted L shape; the second fitting cylindrical portion **22** in the cylindrical shape is fitted to the outer circumferential face **2c** of the outer ring **2**. The axial lip **24b** which is provided on the outer diametrical side among the plurality of axial lips **24b**, **24b** is formed so as to be inclined toward the one end portion **13a** of the first disk portion **13** on the outer diametrical side. The axial lip **24b** which is provided on the inner diametrical side among the plurality of axial lips **10**) **24b**, **24b** is provided in contact with an inner diametrical side of the first disk portion **13**; a space between the axial lips **24b**, **24b** is ensured larger than that in the first embodiment.

(28) The first seal member **10** and the second seal member **20** are combined in such a manner that the inner face **13c** of the first disk portion **13** and the inner face **23b** of the second disk portion **23** face each other in the axial direction, are arranged in such a manner that the extension cylindrical portion **11** and the second fitting cylindrical portion **22** face each other in the radial direction, and are arranged in such a manner that the first disk portion **13** and the second disk portion **23** face each other in the axial direction, thereby constituting the sealing device **9**. Further, in the sealing device **9**, the coating layer **40** having the easily scraped property is provided without any gaps between an inner diametrical face **11d** of the extension cylindrical portion **11** and an outer diametrical face **22d** of the second fitting cylindrical portion **22** as illustrated in FIG. 4A. Specifically, in the initial state in which the first seal member **10** and the second seal member **20** are combined, the coating agent is applied to the outer diametrical fixed face **24ab** of the seal base portion **24a** fixed to the outer diametrical face **22d** so that the coating agent is provided over an entire surface without any gaps between the inner diametrical face **11d** of the extension cylindrical portion **11** and the outer diametrical face **22d** of the second fitting cylindrical portion **22**. That is, the coating layer **40** is fixed to the outer diametrical fixed face **24ab** of the second seal member **20**, and is provided so as to slidably contact the inner diametrical face **11d** of the extension cylindrical portion **11** which is the first seal member **10**. The initial application amount of the coating agent is slightly large such that the layer of the coating layer **40** becomes greater than the interval of the gap between the facing regions, as illustrated by two-dot chain lines in FIG. 4A. In such a state, when the first seal member **10** and the second seal member **20** are combined and rotate relative to each other from the initial state in which the first seal member **10** and the second seal member **20** are combined, the coating layer **40** is scraped by slidably contacting the inner diametrical face **11d** of the extension cylindrical portion **11** which constitutes the first seal member **10**. Then, the coating layer **40** is scraped until the coating layer **40** becomes in non-contact with the inner diametrical face **11d**, thereby forming the minute gap **L1** as illustrated in FIG. 4B. The minute gap **L1** formed as above is

formed between the inner diametrical face **11d** of the extension cylindrical portion **11** of the first seal member **10** and the coating layer **40**.

(29) Like the first embodiment, the rotation of the first seal member **10** and the second seal member for forming the gap **L1** can be formed by rotation of the hub wheel **3** as the rotation side member in such a manner that the sealing device **9** is mounted between the outer ring **2** and the hub wheel **3** of the bearing device **1** illustrated in FIG. **1**; or the sealing device **9** can be mounted on the bearing device **1** after the gap **L1** is formed by rotating the first seal member **10** and the second seal member **20** relative to each other at a stage before mounting.

(30) By the above-described configuration, when the first seal member **10** and the second seal member **20** rotate relative to each other, the coating layer **40** slidably contacts the first seal member **10** and is scraped by such sliding contact, thereby forming the minute gap **L1** between the facing regions in the sealing device **9**; the gap **L1** acts as the labyrinth having the sealing function and the non-contact sealing structure is constituted, thereby achieving torque reduction. Further, since the minute gap **L1** is formed by the initial rotation after the first seal member **10** and the second seal member **20** are combined, even if there is a dimensional tolerance between the first seal member **10** and the second seal member **20**, variation in size of the gap due to the influence of the dimensional tolerance is suppressed.

#### MODIFIED EXAMPLE

(31) Next, a modified example of the sealing device **9** is described below with reference to FIG. **5A** to FIG. **5C**. Explanations for configurations and effects which are common to the above-described embodiments and the above-described modified example are omitted.

(32) The modified example illustrated in FIG. **5A** to FIG. **5C** is different from the above-described embodiments in that a roughed surface portion **26** which is rougher than other surfaces is provided on the inner diametrical face **11d** of the extension cylindrical portion **11** of the first seal member **10**. Herein, the other surfaces refer to places other than the inner diametrical face **11d** of the extension cylindrical portion **11** such as the outer diametrical face **11b** of the extension cylindrical portion **11**, the outer diametrical face **22d** of the second fitting cylindrical portion **22**, or the outer diametrical fixed face **24ab**; and a surface of the inner diametrical face **11d** is formed rougher than those other places. A degree of roughness of the roughed surface portion **26** is not particularly limited, and a minute uneven surface which promotes the easily scraped property of the coating layer **40** is sufficient. Also, roughness is not particularly limited, and a method of forming the roughed surface portion **26** is not particularly limited or can be shot peening or the like. Further, in an enlarged view of the part **Z** in FIG. **5A**, the surface is almost uniformly uneven but can be randomly uneven. Furthermore, in the figures, an area in which the roughed surface portion **26** is provided is entirely provided over the inner diametrical face **11d**; however, a surface which the coating layer **40** contacts can be the roughed surface portion **26**. Moreover, the roughed surface portion **26** can be provided over the whole circumference or can be provided intermittently at intervals even half the circumference.

(33) As illustrated in FIG. **5A**, when the roughed surface portion **26** is provided on the inner diametrical face **11d** of the extension cylindrical portion **11** which is the first seal member **10**, the coating agent is applied to the outer diametrical fixed face **24ab** of the second seal member **20**, and thereafter the first seal member **10** and the second seal member **20** are combined as illustrated in FIG. **5B**. Then, when the first seal member **10** and the second seal member **20** rotate relative to each other from the initial state in which the first seal member **10** and the second seal member **20** are combined, the coating layer **40** is surely scraped by the roughed surface portion **26**, and thereby the minute gap **L1** is formed on a side of the inner diametrical face **11d** of the extension cylindrical portion **11** as illustrated in FIG. **5C**.

#### Third Embodiment

(34) Next, a sealing device **8A** according to the third embodiment is explained with reference to FIG. **6**. Explanations for configurations and effects which are common to the first embodiment are

omitted. Similar to the sealing device **8** according to the first embodiment, the sealing device **8A** is provided for sealing the annular space **S** between the outer ring **2** and the inner ring **4**, and is attached to the end portion of the outer ring **2** on the vehicle body side.

(35) In the sealing device **8A**, the configuration of the first seal member **10** is similar to that of the first seal member **10** in the first embodiment, but is different in that the coating layer **40** is provided not on the outer diametrical face **11b** of the extension cylindrical portion **11** but on the inner face **13c** of the first disk portion **13**. Further, the second seal member **20** includes the core body member **21** and the seal lip portion **24**, which is the same as the second seal member **20** of the first embodiment. However, the axial lip **24b** is not plural and a plurality of seal lip portions **24** which slidably contact the inner face **12b** of the first fitting cylindrical portion **12** are arranged, which is different from the second seal member **20** of the first embodiment. Specifically, the seal lip portion **24** includes the axial lip **24b** which is arranged so as to slidably contact the first disk portion **13** of the first seal member **10** in an axially facing manner, a radial lip **24e** which faces the first fitting cylindrical portion **12** in the radial direction and slidably contacts the first fitting cylindrical portion **12** so as to be obliquely inclined toward a direction of the one end portion **12a** of the first fitting cylindrical portion **12**, and the grease lip **24c** which faces the first fitting cylindrical portion **12** in the radial direction and slidably contacts the first fitting cylindrical portion **12** so as to be obliquely inclined on the side of the annular space **S**.

(36) In the sealing device **8A**, the coating layer **40** having the easily scraped property is provided without any gaps between the inner face **13c** of the first disk portion **13** and the tip end portion **24ba** of the axial lip **24b**, as illustrated in FIG. **6A**. Specifically, in the initial state in which the first seal member **10** and the second seal member **20** are combined, the coating agent is applied to the inner face **13c** of the first disk portion **13** in such a manner that the coating layer is provided over an entire surface without any gaps between the inner face **13c** of the first disk portion **13** and the tip end portion **24ba** of the axial lip **24b**. In such a case, a spot to which the coating agent is applied becomes the inner face **13c** of the first disk portion **13** of the first seal member **10** which corresponds to a bottom surface approximately in the U shape, thereby application becomes easier. In a state in which the coating agent is applied, the coating agent is fixed to the inner face **13c** of the first disk portion **13**, and the axial lip **24b** is provided so as to slidably contact the coating layer **40**.

(37) Also in the sealing device **8A**, when the first seal member **10** and the second seal member **20** rotate relative to each other from the initial state in which the first seal member **10** and the second seal member **20** are combined, the coating layer **40** slidably contacts the second seal member **20** and the coating layer **40** is scraped by such sliding contact, thereby constituting a minute gap **L3**. Specifically, the coating layer **40** is scraped by the tip end portion **24ba** of the axial lip **24b** which constitutes the second seal member **20** until the coating layer **40** becomes non-contact with the tip end portion **24ba**, thereby forming the minute gap **L3** as illustrated in FIG. **6B**. The minute gap **L3** formed as above is formed between the tip end portion **24ba** of the axial lip **24b** and the coating layer **40**. Initial rotation of the first seal member **10** and the second seal member **20** for forming the minute gaps **L3** can be executed by the initial rotation after being mounted on the bearing device **1** in the same manner as the first embodiment, or the first seal member **10** and the second seal member **20** can be mounted on the bearing device **1** after the gap **L3** is formed by rotating the first seal member **10** and the second seal member **20** relative to each other at a stage before being mounted on the bearing device **1**.

(38) By the above-mentioned configuration, when the first seal member **10** and the second seal member **20** rotate relative to each other, the coating layer **40** slidably contacts the tip end portion **24ba** of the axial lip **24b** constituting the second seal member **20** and is scraped by rotation due to such sliding contact, thereby constituting the minute gap **L3** between the facing regions in the sealing device **8A**. The gap **L3** acts as the labyrinth having the sealing function and constitutes the non-contact sealing structure, thereby achieving reduction in torque of the bearing device **1**.

Further, since such minute gap L3 is formed by the initial rotation after the first seal member **10** and the second seal member **20** are combined, even if there is a dimensional tolerance between the first seal member **10** and the second seal member **20**, variation in size of the gap due to the influence of the dimensional tolerance is suppressed.

#### Fourth Embodiment

(39) Next, a sealing device **8B** according to the fourth embodiment is explained with reference to FIG. 7 and FIG. 8. Explanations for configurations and effects which are common to the first embodiment are omitted.

(40) In the sealing device **8B**, configurations of the first seal member **10** and the second seal member are similar to those of the first seal member **10** and the second seal member **20** of the first embodiment, but are different in that the coating layer **40** is provided not only between the outer diametrical face **11b** of the extension cylindrical portion **11** and the inner diametrical face **22c** of the second fitting cylindrical portion **22** but also on the inner face **13c** of the first disk portion **13**.

(41) In the sealing device **8B**, the coating layer **40** having the easily scraped property is provided without any gaps between the outer diametrical face **11b** of the extension cylindrical portion **11** and the inner diametrical face **22c** of the second fitting cylindrical portion **22** and further between the inner face **13c** of the first disk portion **13** and the tip end portion **24ba** of the axial lip **24b**, as illustrated in FIG. 7A. Specifically, in the initial state in which the first seal member **10** and the second seal member **20** are combined, between the outer diametrical face **11b** of the extension cylindrical portion **11** and the inner diametrical face **22c** of the second fitting cylindrical portion **22**, the coating agent is applied to the inner diametrical fixed face **24aa** of the seal base portion **24a** fixed to the inner diametrical face **22c** so that the coating layer is provided over the entire surface without any gaps. Further, also between the inner face **13c** of the first disk portion **13** and the tip end portion **24ba** of the axial lip **24b**, the coating agent is applied to the inner face **13c** of the first disk portion **13** so that the coating layer **40** is provided over the entire surface without any gaps.

(42) Also in the sealing device **8B**, when the first seal member **10** and the second seal member **20** rotate relative to each other from the initial state in which the first seal member **10** and the second seal member **20** are combined, the coating layer **40** slidably contacts the first seal member **10** and the coating layer **40** is scraped by such sliding contact, thereby constituting the minute gaps L1, L2, L3 between the facing regions in the sealing device **8B**. Specifically, the coating layer **40** slidably contacts the outer diametrical face **11b** of the extension cylindrical portion **11** which constitutes the first seal member **10** and is scraped by such sliding contact until the coating layer **40** becomes non-contact relative to the inner diametrical face **22c**, thereby forming the minute gaps L1, L2 as illustrated in FIG. 7B. Similarly, the tip end portion **24ba** of the axial lip **24b** constituting the second seal member **20** slidably contacts the coating layer **40**, and the coating layer **40** is scraped until the tip end portion **24ba** becomes non-contact with the coating layer **40**, thereby forming the minute gap L3 as illustrated in FIG. 7B. The gap L3 formed as above is formed between the tip end portion **24ba** of the axial lip **24b** and the coating layer **40**. The initial rotation of the first seal member **10** and the second seal member **20** for forming the gaps L1, L2, L3 can be executed in the same manner as the first embodiment by the initial rotation after being mounted on the bearing device **1**, or the first seal member **10** and the second seal member **20** can be mounted on the bearing device **1** after the gaps L1, L2, L3 are formed by rotating the first seal member **10** and the second seal member **20** relative to each other at the stage before being mounted.

(43) By the above-mentioned configuration, when the first seal member **10** and the second seal member **20** rotate relative to each other, the coating layer **40** slidably contacts the second seal member **20** and is scraped by rotation due to such sliding contact, thereby constituting the minute gaps L1, L2, L3 in the gap between the facing regions in the sealing device **8B**. The gaps L1, L2, L3 act as the labyrinths having the sealing function and constitute the non-contact sealing structure, thereby achieving reduction in torque of the bearing device **1**. Further, since such minute gaps L1, L2, L3 are formed by the initial rotation after the first seal member **10** and the second seal member

**20** are combined, even if there is a dimensional tolerance between the first seal member **10** and the second seal member **20**, variation in size of the gaps due to the influence of the dimensional tolerance is suppressed.

#### MODIFIED EXAMPLE

(44) Next, a modified example of the above-described sealing device **8B** is explained below with reference to FIG. **8A** and FIG. **8B**. Explanations for configurations and effects which are common to the first embodiment are omitted. A sealing device **8B'** illustrated in FIG. **8A** and FIG. **8** is different from the sealing device **8B** in that the coating layer **40** having the easily scraped property is provided between the outer diametrical face **11b** of the extension cylindrical portion **11** and the inner diametrical face **22c** of the second fitting cylindrical portion **22** and is provided on the inner face **12b** of the first fitting cylindrical portion **12**.

(45) Specifically, in the initial state in which the first seal member **10** and the second seal member are combined, between the outer diametrical face **11b** of the extension cylindrical portion **11** and the inner diametrical face **22c** of the second fitting cylindrical portion **22**, the coating agent is applied to the inner diametrical fixed face **24aa** of the seal base portion **24a** fixed to the inner diametrical face **22c** so that the coating layer **40** is provided over the entire surface without any gaps. Further, also between the inner face **12b** of the first fitting cylindrical portion **12** and the tip end portion **24ca** of the grease lip **24c**, the coating agent is applied to the inner face **12b** of the first fitting cylindrical portion **12** so that the coating layer **40** is provided over the entire surface without any gaps.

(46) Also in the sealing device **8B'**, when the first seal member **10** and the second seal member **20** rotate relative to each other from the initial state in which the first seal member **10** and the second seal member **20** are combined, the coating layer **40** slidably contacts the first seal member **10** and is scraped by such sliding contact, thereby constituting minute gaps **L1**, **L2**, **L4** between the facing regions in the sealing device **8B'**. The coating layer **40** on a side of the outer diametrical face **11b** of the extension cylindrical portion **11** which contacts the inner diametrical face **22c** of the second fitting cylindrical portion **22** is scraped until the coating layer becomes non-contact relative to the inner diametrical face **22c**, thereby forming the minute gaps **L1**, **L2**, as illustrated in FIG. **8B**. Similarly, the tip end portion **24ca** of the grease lip **24c** which constitutes the second seal member **20** slidably contacts the coating layer **40** and the coating layer **40** is scraped until the tip end portion **24ca** does not contact the coating layer **40**, thereby forming the minute gap **L4**, as illustrated in FIG. **8B**. The minute gap **L4** formed as above is formed between the tip end portion **24ca** of the grease lip **24c** and the coating layer **40**. Initial rotation of the first seal member **10** and the second seal member **20** for forming the minute gaps **L1**, **L2**, **L4** can be executed by the initial rotation after being mounted on the bearing device **1** in the same manner as the first embodiment, or the first seal member **10** and the second seal member **20** can be mounted on the bearing device **1** after forming the gaps **L1**, **L2**, **L4** by rotating the first seal member **10** and the second seal member **20** relative to each other at the stage before the mounting.

(47) By the above-mentioned configuration, when the first seal member **10** and the second seal member **20** rotate relative to each other, the coating layer **40** slidably contacts the second seal member **20** and is scraped by such sliding contact, thereby forming the minute gaps **L1**, **L2**, **L4** between the facing regions in the sealing device **8B'**; the gaps **L1**, **L2**, **L4** act as the labyrinths having the sealing function and constitute the non-contact sealing structure, thereby achieving torque reduction. Further, since such minute gaps **L1**, **L2**, **L4** are formed by the initial rotation after the first seal member **10** and the second seal member **20** are combined, even if there is a dimensional tolerance between the first seal member **10** and the second seal member **20**, variation in size of the gaps due to the influence of the dimensional tolerance is suppressed.

(48) The sealing devices **8** to **8B'**, and **9** of the above-described embodiments are not limited to the shapes and structures in the figures. For example, the first seal member **10** and the core body member **21** are not limited to steel plates, but can be formed of a hard resin material or the like.

Further, the shape and number of the seal lip portion **24** are not limited to those illustrated in the figures, and can be made of a resin material or the like having elasticity other than a rubber material. Although not illustrated, the annular magnetic encoder in which the N pole and the S pole are alternatively magnetized in the circumferential direction can be provided on a side of the outer face of the first disk portion **13** not only in the sealing device **8** but also in the sealing devices **8A** to **8B'**. Further, in the above-mentioned embodiment, an example is explained in which the fixed side member is the outer ring **2** and the rotation side member is the inner ring **5**, but the present invention is not limited to such examples, and the fixed side member can be the inner ring and the rotation side member can be the outer ring.

(49) Since the uneven portion **25** and the roughed surface portion **26** are provided to promote scrap performance of the coating layer **40**, forming positions and configurations of the uneven portion and the roughed surface portion **26** are not limited to those in the figures. For example, in the case of the sealing device **8** illustrated in FIG. 2A and the sealing device **8B** illustrated in FIG. 7A, the uneven portion **25** and the roughed surface portion **26** can be provided on the outer diametrical face **11b** of the extension cylindrical portion **11**. Further, in place of the uneven portion **25** illustrated in FIG. 3A to FIG. 3C, the roughed surface portion **26** can be provided on the seal base portion **24a**; or in place of the roughed surface portion **26** illustrated in FIG. 5A to FIG. 5C, the uneven portion **25** can be provided on the inner diametrical face **11d** of the extension cylindrical portion **11**. Furthermore, the uneven portion **25** or the roughed surface portion **26** can be provided at the tip end portion **24ba** of the axial lip **24b** or the tip end portion **24ca** of the grease lip **24c**. Moreover, in the example of FIG. 7A, the uneven portion **25** and the roughed surface portion **26** can be combined according to the spot at which the gap is desirable to be formed, for example, in such a manner that the roughed surface portion **26** is provided at the tip end portion **24ba** of the axial lip **24b** while providing the uneven portion **25** on the outer diametrical face **11b** of the extension cylindrical portion **11**.

(50) As for the coating agent, the liquid adhesive can also be suitably used in addition to the above; although not especially limited, a liquid adhesive of a curing reaction type can also be used, for example. In such a case, the coating agent is liquid and therefore is easily applied to the gap in the facing regions at which the coating layer **40** is arranged. In other words, the coating layer **40** is provided in such a manner that the first seal member **10** and the second seal member are not restricted by the facing regions and the shape of the gap of the facing regions. As for the liquid adhesive, an epoxy resin adhesive of a two-liquid curing type can be used, for example. In such a case, although a main agent and a curing agent are generally mixed in the same amount, the epoxy resin adhesive of the two-liquid curing type is preferably used by reducing a blending quantity of the curing agent so as not to completely harden. Further, when using the liquid adhesive, the solid lubricant as described above can be added and mixed in order to reduce sliding resistance.

(51) Further, it is acceptable if the coating layer **40** is sufficient if provided at least at one spot in the gap of the facing regions in which the first seal member **10** and the second seal member **20** are provided so as to face each other, the coating layer **40** is not limited to those in the figures; for example, in the sealing device **8B** of FIG. 7A, the coating layer can also be provided between the inner face **12b** of the first fitting cylindrical portion **12** and the tip end portion **24ca** of the grease lip **24c**. Furthermore, the coating layer **40** which is provided at the gap between the facing regions is preferable to be arranged evenly without any gaps, but a slight gap including air bubbles or some places on which the coating layer **40** is not arranged is permitted.

(52) Further, the coating layer **40** is not limited to ones which slidably contact either the first seal member **10** or the second seal member **20**, and can be arranged in such a manner that the facing regions, for example, the coating layer which is provided on the first seal member **10** and the coating layer which is provided on the second seal member **20**, slidably contact each other. That is, for example, by combining the first seal member **10** and the second seal member **20** after the coating agent is applied to each of the outer diametrical face **11b** of the extension cylindrical

portion **11** and the inner diametrical fixed face **24aa** of the seal base portion **24a**, the coating layers comes to face each other and can be arranged so as to slidably contact each other. Furthermore, the coating layer can be provided between the extension cylindrical portion **11** and the seal base portion **24a** in such a manner that the coating agent is applied between the extension cylindrical portion **11** and the seal base portion **24a** after combining the first seal member **10** and the second seal member **20** and thereafter the coating agent is solidified. In such a case, when the first seal member **10** and the second seal member **20** rotate relative to each other from the initial state, the coating layer is divided and the coating layers become sliding contact with each other.

(53) Further, after the initial state in which the first seal member **10** and the second seal member **20** are combined, as long as either one of the first seal member **10** and the second seal member **20** contacts the coating layer **40** in such a manner that a space of the annular space **S** in the radial direction becomes narrow when the outer ring **2** and the inner ring **4** rotate relative to each other, there can be a slight gap within a dimensional tolerance, for example, between the coating layer and the first seal member **10** or between the coating layer **40** and the second seal member **20** when installing the first seal member **10** and the second seal member **20**.

(54) Furthermore, the first seal member **10** and the second seal member **20** do not necessarily need to be mounted on the bearing device **1** in the combined state. For example, the first seal member **10** and the second seal member **20** can be combined when the outer ring **2** and the inner ring **5** are assembled after the first seal member **10** is mounted on the inner ring **5** and the second seal member **20** is mounted on the outer ring **2**.

#### DESCRIPTION OF THE REFERENCE NUMERAL

(55) **1** bearing device **2** outer ring (fixed side member) **5** inner ring (rotation side member) **8**, **8A**, **8B**, **8B'**, **9** sealing device **S** annular space **10** first seal member **20** second seal member **25** uneven portion **26** roughed surface portion **40** coating layer **L1**, **L2**, **L3**, **L4** gap

## Claims

1. A sealing device to seal an annular space formed by two members, a fixed side member and a rotation side member which rotates coaxially relative to the fixed side member, the sealing device comprising: a first seal member to be fitted to the rotation side member and a second seal member to be fitted to the fixed side member, the sealing device capable of being provided between the two members in a state in which the first seal member and the second seal member are combined; and a coating layer having an easily scraped property, having shape retention when scraped, and being provided without any gaps at least at one place between facing regions in which the first seal member and the second seal member are provided so as to face each other in an initial state in which the first seal member and the second seal member are combined, wherein a gap is formed when the coating layer is scraped by slidably contacting a region of the first seal member or the second seal member to which the coating layer faces in a state in which the first seal member and the second seal member rotate relative to each other from the initial state, and the gap has a sealing function.

2. The sealing device according to claim 1, wherein: the first seal member comprises a first fitting cylindrical portion to be fitted to the rotation side member, a first disk portion extending in outer diametrical direction from one end portion of the first fitting cylindrical portion, and an extension cylindrical portion extending in axial direction from one end portion of the first disk portion on an outer diametrical side, the second seal member comprises a second fitting cylindrical portion to be fitted to the fixed side member, the extension cylindrical portion of the first seal member and the second fitting cylindrical portion of the second seal member are provided so as to face each other in radial direction in a state in which the sealing device is provided between the fixed side member and the rotation side member, and the gap between the facing regions is a gap between the extension cylindrical portion and the second fitting cylindrical portion.

3. The sealing device according to claim 1, wherein; the first seal member comprises a first fitting cylindrical portion to be fitted to the rotation side member and a first disk portion extending in outer diametrical direction from one end portion of the first fitting cylindrical portion, the second seal member comprises a core body member having a second fitting cylindrical portion to be fitted to the fixed side member, and a seal lip portion fixed to the core body member, the seal lip portion is provided so as to slidably contact the first disk portion of the first seal member, the seal lip portion and the first disk portion facing each other in axial direction, and the gap between the facing regions is a gap between the first disk portion and the seal lip portion.
  4. The sealing device according to claim 2, wherein an uneven portion or a roughed surface portion of which surface is rougher than other surfaces is provided on at least either one of surfaces in which the extension cylindrical portion and the second fitting cylindrical portion face each other.
  5. The sealing device according to claim 1, wherein the coating layer is composed of a solid lubricant into which a powdered additive to reduce a coefficient of friction is mixed.
  6. The sealing device according to claim 1, wherein the coating layer is composed of a liquid adhesive of a curing reaction type.
  7. The sealing device according to claim 2, wherein the coating layer is composed of a solid lubricant into which a powdered additive to reduce a coefficient of friction is mixed.
  8. The sealing device according to claim 2, wherein the coating layer is composed of a liquid adhesive of a curing reaction type.
  9. The sealing device according to claim 2, wherein: the second seal member further has a second disk portion extending into an inner diameter direction from one end of the second fitting cylindrical portion, and the gap between the facing regions is a gap between one end of an extension cylindrical portion and the second disk portion.
  10. The sealing device according to claim 2, wherein: the second seal member has a core body member having the second fitting cylindrical portion and a seal lip portion fixed to the core body member, the seal lip portion faces the first fitting cylindrical portion of the first seal member in a diametrical direction so as to have slidable contact, and the gap between facing regions is a gap between the first fitting cylindrical portion and the seal lip portion.
  11. The sealing device according to claim 4, wherein: the second seal member has a core body member having the second fitting cylindrical portion and a seal lip portion fixed to the core body member, the seal lip portion faces the first fitting cylindrical portion of the first seal member in a diametrical direction so as to have slidable contact, and the gap between facing regions is a gap between the first fitting cylindrical portion and the seal lip portion.
-