

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12406048
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Moran; Brendan James et al.

Distributed verification of attestation evidence

Abstract

A method to distribute verification of attestation evidence and a verifiable system are provided. Method includes receiving, at a secondary verifier operating in a verifiable system, a request from a relying party to perform a verification process with respect to attestation evidence of a device in communication with the relying party, communicating self-attestation evidence, by the secondary verifier, to a trusted verifier to generate an attestation report of the verifiable system, communicating the attestation report of the verifiable system or other indicator of trustworthiness to the relying party to indicate trustworthiness of the secondary verifier with respect to performing the verification process, and performing, by the secondary verifier, the verification process on the attestation evidence of the device in communication with the relying party. The verifiable system includes instructions of a secondary verifier stored and executed by the verifiable system to perform the method to distribute verification of attestation evidence.

Inventors: Moran; Brendan James (Coton, GB), Petri; Gustavo Federico (Cambridge, GB), Fossati; Thomas (Cambridge, GB)

Applicant: Arm Limited (Cambridge, GB)

Family ID: 92119587

Assignee: ARM LIMITED (Cambridge, GB)

Appl. No.: 18/106750

Filed: February 07, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240265083 A1	Aug. 08, 2024

Publication Classification

Int. Cl.: G06F21/44 (20130101)

U.S. Cl.:

CPC G06F21/44 (20130101);

Field of Classification Search

CPC: G06F (21/44); G06F (21/53); G06F (21/606)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
8880667	12/2013	Novak	709/224	G06F 21/64
11595213	12/2022	Moran	N/A	H04L 63/0281
2015/0113618	12/2014	Sinha	726/6	G06F 21/44
2016/0366180	12/2015	Smith	N/A	H04W 4/70
2019/0311123	12/2018	Lal	N/A	G06F 21/57
2020/0322380	12/2019	Sheth	N/A	H04L 63/162
2021/0105265	12/2020	Yang	N/A	H04W 12/047
2022/0131856	12/2021	Xia	N/A	H04L 63/0853

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
3648438	12/2020	EP	G06F 16/211
WO-2024227510	12/2023	WO	G06F 21/57
WO-2024260532	12/2023	WO	G06F 21/57

Primary Examiner: Revak; Christopher A

Attorney, Agent or Firm: Talem IP Law, LLP

Background/Summary

BACKGROUND

(1) Attestation allows a device to prove properties about itself such as what software it is running, its identity, security capabilities, etc. Remote attestation is used as part of a process to establish trust between devices so that information passed between the two devices can be expected to be authentic, intact, and trustworthy. The accuracy of the attestation mechanism is itself subject to trust in the verifying entity (a “verifier”).

(2) In secure communication between parties, a relying party, such as a bank, relies on a verifier to establish the integrity of an individual or device in communication with the relying party. In order to provide a high level of security, the verifier software executes its code in a secure computing system so that third parties cannot interfere. A device in communication with the relying party presents its credentials in a message to the relying party. These credentials are termed attestation evidence. For example, the attester, e.g., the device in this example, presents a set of data including endorsements and measurements. One measurement that can be included is the device's public key.

Another common measurement is the digest of the software that will be executed in the secure computing system environment.

(3) A verification of the device is done, and the verifier produces an attestation report for the relying party. The attestation report contains trust metrics of the device. The verification is useful in improving the level of trust and security in communication partners. To provide trustworthy verification capabilities for the attestation mechanism on behalf of a relying party, the verifier needs to be operated at the highest level of security and availability.

BRIEF SUMMARY

(4) Distributed verification of attestation evidence is presented. Through the processes described herein, it is possible to run a verifier of attestation evidence in a less stringent environment.

(5) A method includes receiving, at a secondary verifier operating in a verifiable system, a request from a relying party to perform a verification process with respect to attestation evidence of a device in communication with the relying party, communicating self-attestation evidence, by the secondary verifier, to a trusted verifier to generate an attestation report of the verifiable system, communicating an indicator of trustworthiness to the relying party of the secondary verifier to indicate trustworthiness of the secondary verifier with respect to performing the verification process, performing, by the secondary verifier, the verification process on the attestation evidence of the device in communication with the relying party, and communicating, by the secondary verifier, an attestation report of the device to the relying party.

(6) A verifiable system includes instructions of a secondary verifier stored and executed by the verifiable system, the secondary verifier, when executed by the verifiable system, receives a request from a relying party to perform a verification process with respect to attestation evidence of a device in communication with the relying party, communicates self-attestation evidence to a trusted verifier operating in a secure computing system environment to generate an attestation report of the verifiable system, communicates the attestation report of the verifiable system to the relying party to indicate trustworthiness of the secondary verifier with respect to performing the verification process, and performs the verification process on the attestation evidence of the device in communication with the relying party.

(7) A method includes forming a trusted network comprising multiple secondary verifiers by the multiple secondary verifiers performing a mutual attestation with one another protocol, receiving, at one secondary verifier of the multiple secondary verifiers, the one secondary verifier operating in a verifiable system, a request from a relying party to perform a verification process with respect to attestation evidence of a device in communication with the relying party, communicating self-attestation evidence, by the one secondary verifier of the multiple secondary verifiers, to a trusted verifier to generate an attestation report of the verifiable system, communicating the attestation report of the verifiable system to the relying party to indicate trustworthiness of the secondary verifier with respect to performing the verification process, and performing, by a further secondary verifier of the multiple secondary verifiers, the verification process on the attestation evidence of the device in communication with the relying party.

Description

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

(1) To easily identify the discussion of any particular element or act, the most significant digit or digits in a reference number refer to the figure number in which that element is first introduced.

(2) FIG. 1 illustrates a schematic diagram of a trusted verifier in communication with a

(3) relying party.

(4) FIG. 2 illustrates a schematic diagram of a relying party in communication with a plurality of verifiers in accordance with one embodiment.

(5) FIG. 3 illustrates a schematic diagram of an operating environment in a distributed verification system in accordance with one embodiment.

(6) FIG. 4 illustrates a schematic diagram of a trusted network of secondary verifiers in communication with a relying party in accordance with one embodiment.

(7) FIG. 5 illustrates a method in accordance with one embodiment.

DETAILED DESCRIPTION

(8) Distributed verification of attestation evidence is presented. Through the processes described herein, it is possible to run a verifier of attestation evidence in a less stringent environment.

(9) Because a verifier needs to be operated at the highest level of security and availability to provide trustworthy verification capabilities for the attestation mechanism on behalf of a relying party, it can be challenging to implement a verifier. Verifiers tend to be hosted in data centers and require specialized hardware and software that is subject to strict verification and security analysis for maintaining security against malicious activities. Loss of the verification service causes the attestation mechanism to break down. This is a high level of responsibility for the verifier and thus there is a need to distribute this responsibility between multiple verifiers to reduce the burden of security and availability on a single verifier.

(10) In order to reduce the load and responsibility of a single verifier, a trusted verifier can be used to assist in creating another or other verifier(s) in a potentially untrusted environment. A two-step verification process is thus presented in which a less secure device can run verification software to verify devices by first being verified by the trusted verifier.

(11) FIG. 1 illustrates a schematic diagram of a trusted verifier **104** in communication with a relying party **106**. The trusted verifier **104** includes primary verifier **108** hosted within a secure computing system environment **110**. The secure computing system environment **110** may be a data center such as a cloud data center and may include specialized hardware such as a hardware security module (HSM). In an embodiment, a trusted execution environment (TEE) can be executed by the secure computing system environment **110**. The trusted execution environment may include physical circuitry elements, hardware, comprising logical elements controlled by a central processing unit. As an example, a CCA Realm, a hardware-based trusted execution environment, can be utilized as the secure computing system environment **110**.

(12) The primary verifier **108** executes its code within the secure computing system environment **110** and can verify attestation evidence in a message presented to the primary verifier **108** for correctness. The secure computing system environment **110** includes a first interface **102** to communicate with other entities. The first interface **102** includes interface circuitry to provide communication between the secure computing system environment circuitry and circuitry of an entity that is communicatively coupled to the secure computing system environment **110**.

(13) A relying party **106** may be the entity that is communicatively coupled to the trusted verifier **104**. The relying party **106** sends attestation evidence, AE **112**, to the trusted verifier **104** to be verified. The primary verifier **108** verifies the attestation evidence for correctness and sends an attestation report, AR **114**, back to the relying party **106** with the results.

(14) FIG. 2 illustrates a schematic diagram of a relying party **106** in communication with a plurality of verifiers in accordance with an embodiment. Instead of a single verifier, an operating environment for a relying party **106** can include multiple verifiers. The relying party **106** can communicate with different types of verifiers depending on access (to a particular verifier) and type of device being verified. For example, the relying party **106** can communicate with trusted verifiers **104**, e.g., a verifier operating in a secure computing system environment **110**, such as described with reference to FIG. 1.

(15) Alternately, the relying party **106** can communicate with secondary verifiers **204**. A secondary verifier **204** is a verifier that is itself verifiable. The secondary verifier **204** may be operating in a secure data center or on-premise server and has the capability to evaluate policies and store private keys without compromising the private keys (with at least some level of security). The secondary

verifier **204** includes a second interface **202** comprising interface circuitry to communicate with other entities. However, in contrast to a trusted verifier **104**, the secondary verifier **204** does not operate in a secure computing system environment **110**. That is, the security measures applied to the secondary verifier **204** may be less stringent than a fully trusted verifier (e.g., the trusted verifier **104**) or even if as stringent as the fully trusted verifier, responsibilities with respect to warranties on the security can be shifted (or confirmed). In particular, the secondary verifier **204** operates in a verifiable system **206** so that the secondary verifier **204** can be verified by a trusted verifier **104** to be considered another trusted verifier to the relying party **106**. For example, the secondary verifier **204** may be a system under control of or operating on behalf of a silicon vendor (i.e., the vendor that produces the chip that is found in the device being verified by the relying party **106**).

(16) FIG. 3 illustrates a schematic diagram of an operating environment **300** for a distributed attestation system in accordance with one embodiment. Referring to FIG. 3, during certain communications between a device **302** and a relying party **106**, the relying party **106** relies on a verifier to establish the integrity of the device **302** so that those certain communications and associate operations can be considered secure. For example, use of a banking application executed on a device can be verified by a relying party through the described systems.

(17) In the illustrated scenario, the relying party **106** provides the AE **304** to a third party, a secondary verifier for verification. As explained with respect to FIG. 2, a secondary verifier **204** is a verifier that itself can be verified (operating on a verifiable system). The secondary verifier **204** can be any system performing verification processes for attestation evidence and may be specific to a particular device or be any appropriate system that is in communication with a relying party **106**.

(18) The secondary verifier **204** performs method **500** as described with respect to FIG. 5. In particular, secondary verifier **204** can receive requests from the relying party **106** to perform a verification process with respect to attestation evidence (AE **304**) of a device **302** in communication with the relying party **106** and can perform the verification process on the attestation evidence (AE **304**) of the device **302**. The secondary verifier **204** also can communicate self-attestation evidence (verifier attestation evidence VAE **306**) to a primary verifier **108** (which is a trusted verifier) to generate an attestation report (verifier attestation report VAR **308**) of the verifiable system on which the secondary verifier is executing and can communicate the attestation report (VAR **308**) of the verifiable system to the relying party **106** to indicate trustworthiness of the secondary verifier **204** with respect to performing the verification process.

(19) In some cases, before the relying party **106** sends the request to perform the verification process, the relying party **106** requests that the secondary verifier **204** provide a self-attestation report. In some cases, the request to perform the verification process of the device **302** inherently or explicitly includes the request to provide a self-attestation report.

(20) In some cases, the secondary verifier **204** ensures that it has a valid attestation report (VAR **308**) (e.g., by storing the report and checking that the report has not expired before requesting a new attestation report from the primary verifier **108**) so that the secondary verifier **204** can send the valid attestation report (VAR **308**) for itself before, with (in a joint attestation report, for example), or after sending the attestation report (AR **310**) for the device without having to request a valid attestation report (VAR **308**) from the primary verifier **108** for each request from a relying party **106**. This is also useful for scenarios where the secondary verifier **204** goes offline and cannot reach a primary verifier **108** for a period of time.

(21) In some cases, the secondary verifier **204** sends the valid attestation report VAR **308** along with a certificate signing request (CSR) to a certificate authority **314**. The certificate authority **314** audits the attestation report VAR **308** and issues a certificate **316** for the secondary verifier **204** entitling the secondary verifier **204** to perform verifications for a period of time. In this way, the burden of auditing the secondary verifier is offloaded to a certificate authority **314** and the relying party **106** is unaware that the verifier is a secondary verifier. The certificate **316** issued by the

certificate authority **314** is another indicator of trustworthiness to prove trustworthiness of the secondary verifier **204**.

(22) An example implementation of the process is as follows. In response to receiving a request from the relying party **106** to perform a verification process with respect to attestation evidence (AE **304**) of device **302** (and if the secondary verifier **204** does not have a stored valid attestation report (VAR **308**), the secondary verifier **204** presents self-attestation evidence (VAE **306**) to the trusted verifier **104** (for verification by the primary verifier **108**). The trusted verifier **104** (through the primary verifier **108**) generates an attestation report (VAR **308**) of the verifiable system **206** and sends the attestation report (VAR **308**) back to the secondary verifier **204**. The attestation report (VAR **308**) of the secondary verifier **204** is sent to the relying party **106** to prove its trustworthiness.

(23) As mentioned above, the attestation of the secondary verifier **204** may be done at the time the secondary verifier **204** has a verification to perform on the attestation evidence (AE **304**) of the device **302**, but just prior to performing the verification of the attestation evidence (AE **304**) of the device **302**. Alternately, the attestation of the secondary verifier **204** may be done in advance. For example, the secondary verifier **204** can proactively have a verification of itself performed by the trusted verifier **104** well before it needs to perform a verification of attestation evidence (AE **304**) of the device **302**. The secondary verifier **204** can store the attestation report (VAR **308**) from the verification of itself by the trusted verifier **104** in the verifiable system, such as in a cache or other memory location, until the report expires. For example, the attestation report (VAR **308**) may have an expiration period set to one day so that the stored report is valid for a day, which can simplify/speed up the verification process. Of course, less or more time may be assigned to the validity of the attestation report (VAR **308**).

(24) Once attested, the secondary verifier **204** is prepared to verify the attestation evidence (AE **304**) of the device **302**. In order to perform the verification of the device **302**, the secondary verifier **204** will need to be able to access device-specific data. The secondary verifier **204**, however, may not have adequate memory to store device-specific data, referred to as verification data, for the many devices it may be called upon to verify and/or may not have information of all the different devices it may be called upon to verify. In such cases, the secondary verifier **204** will can obtain the verification data from an external source. The external source may be another secondary verifier (e.g., shown in FIG. 2 or described with respect to FIG. 4) or an external storage device (which may be accessible by a plurality of systems providing verification processes). In an embodiment, the secondary verifier **204** receives the device-specific verification data from a secure attestation resource **312**. The verification data can only be accessed in the attestation resource **312**, however, from a verified instance. For example, the attestation resource **312** may require the attestation report (VAR **308**) of the secondary verifier **204**. Alternately, as described in more detail with respect to FIG. 4, the secondary verifier **204** can receive the device-specific data from a file sharing network. For example, the secondary verifier **204** may be one of multiple secondary verifiers, each secondary verifier having a portion of the verification data (device-specific data). These multiple secondary verifiers **204** make up a peer-to-peer file sharing network. The secondary verifier **204** reaches out within the file sharing network to find the verification data it needs to verify the device **302**.

(25) Once the secondary verifier **204** has the verification data for the device **302**, the secondary verifier **204** verifies the attestation evidence (AE **304**) of the device **302** by checking the verification data. If the attestation evidence (AE **304**) satisfies conditions with respect to the verification data, the secondary verifier **204** verifies the attestation evidence (AE **304**) and sends an attestation report (AR **308**) of the device to the relying party **106**.

(26) FIG. 4 illustrates a schematic diagram of a trusted network of secondary verifiers in communication with a relying party in accordance with one embodiment. As shown in FIG. 4, a relying party **106** is in communication with a secondary verifier **204** that is one of a trusted network

402 of secondary verifiers **204**. In order to form the trusted network **402**, the secondary verifiers **204** form trust relationships, such as by performing a mutual attestation with each other. The mutual attestation may be done by direct attestation with one another or by using a trusted gossip protocol. Direct attestation is performed when each pair of secondary verifiers performs an attestation of each other.

(27) A gossip protocol is a process of peer-to-peer communication that relies on each peer in the network to spread data to its neighbor. When there is a large number of secondary verifiers **204**, direct attestation of pairs of secondary verifiers **204** can be computationally challenging equating to numerous operations. Thus, by utilizing a trusted gossip protocol, a large peer-to-peer trusted network **402** can be formed. In this case, a trusted verifier **104** can be used as a back-up node in the trusted network **402**.

(28) In an embodiment of a trusted gossip protocol, a list of trusted secondary verifiers **204** is maintained, reducing the number of operations needed to be performed. The gossip protocol works by adding the trusted verifiers of each secondary verifier **204** in the trusted network **402** to the list of trusted secondary verifiers **204**. While this one example of a trusted gossip protocol, other peer to peer network protocols can also work for the proposed method.

(29) Once the secondary verifiers **204**, **404** are mutually attested and a trusted network **402** is formed, an attestation of a device (e.g., device **302**) can be performed by an already-verified secondary verifier **404** in the trusted network **402**. The relying party **106** forms a relationship with this originating secondary verifier **404** of the multiple secondary verifiers **204**, **404** in the trusted network **402**. FIG. 4 illustrates the relying party **106** forming a relationship with the originating secondary verifier **404** in the trusted network **402**. Attestation evidence is then sent to the originating secondary verifier **404** by the relying party **106** for verification.

(30) The originating secondary verifier **404** performs verification of the attestation evidence in view of the device-specific data. In an embodiment, each secondary verifier **204**, **404** in the trusted network **402** includes a portion of verification data. The portion of verification data refers to a subset of device-specific data of all possible device-specific data available for verification. Some verifiers may store a same subset of device-specific data with others storing different subsets of data. In some cases, a secure storage resource, such as attestation resource **312** described with respect to FIG. 3, can be used by the trusted network **402** to store the necessary device-specific data.

(31) When the originating secondary verifier **404** has the appropriate verification data in its subset of device-specific data, the originating secondary verifier **404** verifies the attestation evidence and sends an attestation report to the relying party **106**. However, if the originating secondary verifier **404** does not have the appropriate verification data to verify the attestation evidence of the device **302**, the originating secondary verifier **404** can check with the other secondary verifiers **204** in the trusted network **402** (and/or the secure attestation resource **312**) to find one that does have the appropriate verification data.

(32) In an embodiment, the originating secondary verifier **404** sends a request to the other secondary verifiers **204** in the trusted network **402** for the appropriate verification data to verify the device **302**. The request may be sent out over the trusted network **402** utilizing the trusted gossip protocol, for example. Each of the other secondary verifiers **204** checks their respective portion of verification data. When one of the secondary verifiers **204** has the appropriate verification data, the secondary verifier **204** sends the appropriate verification data to the originating secondary verifier **404**. The originating secondary verifier **404** verifies the attestation evidence utilizing the appropriate verification data and sends the attestation report of the verification back to the relying party **106**.

(33) In another embodiment, the originating secondary verifier **404** sends the attestation evidence over the trusted network **402** to the other secondary verifiers **204**. Each of the other secondary verifiers **204** checks their respective portion of verification data for the correct verification data. A

further secondary verifier **204**, having the correct verification data verifies the attestation evidence and sends the attestation report back via the trusted network **402** to the originating secondary verifier **404**. The originating secondary verifier **404** then returns the result to the relying party **106** in the attestation report.

(34) FIG. 5 illustrates a method **500** to verify attestation evidence, in accordance with one embodiment. Referring to FIG. 5, in block **502**, a secondary verifier operating in a verifiable system receives, a request from a relying party to perform a verification process with respect to attestation evidence of a device in communication with the relying party. In block **504**, the secondary verifier communicates self-attestation evidence to a trusted verifier to generate an attestation report of the verifiable system. In block **506**, the secondary verifier communicates an indicator of trustworthiness to the relying party of the secondary verifier to indicate trustworthiness of the secondary verifier with respect to performing the verification process. In block **508**, the secondary verifier performs the verification process on the attestation evidence of the device in communication with the relying party. In block **510**, the secondary verifier communicates an attestation report of the device to the relying party.

(35) In operation, the proposed method distributes the load/responsibility of an attestation evidence verifier, reducing maintenance overhead and improving security. The proposed method creates a verifier network of secondary verifiers that is robust to failure. For example, attestation of a device typically requires access to a trusted verifier. While this attestation process is secure, it is not robust to network failure. If internet access fails, then any operation that depends on an attestation will also fail. The proposed method allows a local infrastructure, e.g., using secondary verifiers, to securely operate a verifier for a local device. The attestation evidence for the attestation requests may then be locally stored. In addition, the created verifier network can withstand a temporary failure of the trusted verifier. The verifier network of secondary verifiers can be guarded against an attack from a malicious attacker as it only communicates with other verified devices, effectively operating within a trusted VPN (Virtual Private Network).

Claims

1. A method, comprising: receiving, at a secondary verifier operating in a verifiable system, a request from a relying party to perform a verification process with respect to attestation evidence of a device in communication with the relying party, wherein the secondary verifier is one of multiple secondary verifiers; communicating self-attestation evidence, by the secondary verifier, to a trusted verifier operating in a secure computing system environment to generate an attestation report of the verifiable system; communicating an indicator of trustworthiness to the relying party of the secondary verifier to indicate trustworthiness of the secondary verifier with respect to performing the verification process; performing, by the secondary verifier, the verification process on the attestation evidence of the device in communication with the relying party; performing, by the secondary verifier with a further secondary verifier of the multiple secondary verifiers, a mutual attestation to form a trusted network of secondary verifiers, wherein verification data used in the verification process is obtained from the further secondary verifier; and communicating, by the secondary verifier, an attestation report of the device to the relying party.
2. The method of claim 1, wherein the indicator of trustworthiness of the secondary verifier is the attestation report of the verifiable system.
3. The method of claim 1, further comprising: communicating, by the secondary verifier, the attestation report of the verifiable system and a certificate signing request to a certificate authority, receiving, by the certificate authority, the attestation report of the verifiable system and the certificate signing request, auditing, by the certificate authority, the attestation report of the verifiable system, issuing, by the certificate authority, a certificate as the indicator of trustworthiness of the secondary verifier, and communicating, by the certificate authority, the

certIFICATE to the secondary verifier.

4. The method of claim 2, wherein the communicating of the attestation report of the verifiable system to the relying party and the communicating of the attestation report of the device to the relying party are performed by sending the attestation report of the device and the attestation report of the verifiable system in a joint attestation report to the relying party.
5. The method of claim 1, further comprising storing, at the verifiable system of the secondary verifier, the attestation report of the verifiable system.
6. The method of claim 1, wherein the communicating of the self-attestation report by the secondary verifier is sent before receiving the request from the relying party to perform the verification process with respect to attestation evidence of the device.
7. The method of claim 1, wherein performing the verification process includes obtaining the verification data of the device from an external source.
8. The method of claim 7, wherein the verification data is obtained from a secure attestation resource.
9. The method of claim 1, wherein the mutual attestation is performed by direct attestation.
10. The method of claim 1, wherein the mutual attestation is performed using a trusted gossip protocol.
11. The method of claim 1, wherein the obtaining of the verification data from the further secondary verifier includes sending a request through the trusted network of secondary verifiers for correct verification data and receiving the correct verification data from the further secondary verifier.
12. A verifiable system, comprising: instructions of a secondary verifier stored and executed by hardware including physical circuitry elements of the verifiable system, the secondary verifier, when executed by the hardware of the verifiable system: receives a request from a relying party to perform a verification process with respect to attestation evidence of a device in communication with the relying party, wherein the secondary verifier is one of multiple secondary verifiers, communicates self-attestation evidence to a trusted verifier operating in a secure computing system environment to generate an attestation report of the verifiable system, communicates the attestation report of the verifiable system to the relying party to indicate trustworthiness of the secondary verifier with respect to performing the verification process, and performs the verification process on the attestation evidence of the device in communication with the relying party, performs, by the secondary verifier with a further secondary verifier of the multiple secondary verifiers, a mutual attestation to form a trusted network of secondary verifiers, wherein verification data used in the verification process is obtained from the further secondary verifier, and communicates, by the secondary verifier, an attestation report of the device to the relying party.
13. The verifiable system of claim 12, wherein the verification process utilizes verification data stored in an attestation resource.
14. The verifiable system of claim 12, wherein the trusted verifier is a primary verifier hosted in a cloud data center.
15. The verifiable system of claim 12, wherein the secondary verifier operates as a silicon vendor.
16. A method to distribute verification of attestation evidence between multiple secondary verifiers, comprising: forming a trusted network comprising multiple secondary verifiers by the multiple secondary verifiers performing a mutual attestation with one another; receiving, at one secondary verifier of the multiple secondary verifiers, the one secondary verifier operating in a verifiable system, a request from a relying party to perform a verification process with respect to attestation evidence of a device in communication with the relying party; communicating self-attestation evidence, by the one secondary verifier of the multiple secondary verifiers, to a trusted verifier to generate an attestation report of the verifiable system; communicating the attestation report of the verifiable system to the relying party to indicate trustworthiness of the secondary verifier with respect to performing the verification process; and performing, by a further secondary verifier of

the multiple secondary verifiers, the verification process on the attestation evidence of the device in communication with the relying party.

17. The method of claim 16, wherein the mutual attestation is performed by direct attestation.

18. The method of claim 16, wherein the mutual attestation is performed using a trusted gossip protocol.
