

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12407918
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Kumagai; Koichi et al.

Electronic device

Abstract

An electronic device performs control to display a guide indicating a current focus position in a focus range from a first end on a close side to a second end on an infinity side, wherein the guide includes a focus range portion which is long in a predetermined direction, and includes one end whose a position in the predetermined direction corresponds to the first end, and an other end whose a position in the predetermined direction corresponds to the second end, a length of the focus range portion is a length according to an operation range of a focus operation, and a position of the first end and a position of the second end at the focus range portion are positions according to a relationship between an operation direction of the focus operation and a change direction of a focus position.

Inventors:	Kumagai; Koichi (Saitama, JP), Komatsuzaki; Taira (Tokyo, JP)
Applicant:	CANON KABUSHIKI KAISHA (Tokyo, JP)
Family ID:	92460297
Assignee:	CANON KABUSHIKI KAISHA (Tokyo, JP)
Appl. No.:	18/527535
Filed:	December 04, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240292088 A1	Aug. 29, 2024

Foreign Application Priority Data

JP	2023-029349	Feb. 28, 2023
----	-------------	---------------

Publication Classification

Int. Cl.: H04N23/63 (20230101); H04N23/62 (20230101)

U.S. Cl.:

CPC H04N23/633 (20230101); H04N23/62 (20230101);

Field of Classification Search

CPC: H04N (23/62); H04N (23/633); H04N (23/675)

USPC: 348/333.02

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6937284	12/2004	Singh	348/346	H04N 23/635
7324151	12/2007	Onozawa	348/346	H04N 23/673
8711273	12/2013	Hamada	348/346	H04N 23/635
9459514	12/2015	Ichihara	N/A	G03B 13/16
9509913	12/2015	Kaneko	N/A	H04N 23/61
9667861	12/2016	Lee	N/A	H04N 23/64
9888182	12/2017	Sawa	N/A	H04N 23/675
11076086	12/2020	Matsumoto	N/A	H04N 23/663
11206354	12/2020	Matsumoto	N/A	G03B 13/34
11509829	12/2021	Sato	N/A	H04N 23/631
2006/0029381	12/2005	Onozawa	348/E5.045	H04N 23/673
2012/0057062	12/2011	Hamada	348/E5.045	H04N 23/673
2014/0267869	12/2013	Sawa	348/333.03	H04N 23/66
2014/0368719	12/2013	Kaneko	348/333.02	H04N 23/672
2015/0244929	12/2014	Lee	348/346	H04N 23/633

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2004-258086	12/2003	JP	N/A

Primary Examiner: Prabhakher; Pritham D

Attorney, Agent or Firm: Cowan, Liebowitz & Latman, P.C.

Background/Summary

BACKGROUND OF THE INVENTION

Field of the Invention

(1) The present invention relates to a function of assisting a focus operation of manual focus.

Description of the Related Art

(2) When video work is shot, focus adjustment to (focusing on) an object is performed by a manual operation. As an assist function of such an operation (focus operation), there is a focus position guide display function of displaying a guide which is called a focus position guide. A focus position

guide indicates a current focus position (focus position) (Japanese Patent Application Publication No. 2004-258086). A user (photographer) can perform a focus operation of moving a focus position to a desired focus position while looking at the focus position guide.

(3) However, a conventional focus position guide display function displays the same focus position guide irrespectively of a lens type. Therefore, a user's sense and display of the focus position guide during the focus operation do not match, and the user cannot easily (intuitively) perform a desired focus operation.

SUMMARY OF THE INVENTION

(4) The present invention provides a technique which enables a user to easily (intuitively without hesitation) a desired focus operation.

(5) The present invention in its first aspect provides an electronic device including at least one memory and at least one processor which function as: an acquisition unit configured to acquire operation member information which is information on an operation member for a focus operation; and a display control unit configured to perform control to display a guide indicating a current focus position in a focus range from a first end on a close side to a second end on an infinity side based on the operation member information, wherein the guide includes a focus range portion which is a portion which is long in a predetermined direction, and includes one end whose a position in the predetermined direction corresponds to the first end, and an other end whose a position in the predetermined direction corresponds to the second end, a length of the focus range portion is a length according to an operation range which is a range of an operation amount of the focus operation which a user is able to perform on the operation member, and a position of the first end and a position of the second end at the focus range portion are positions according to a relationship between an operation direction of the focus operation on the operation member and a change direction of a focus position.

(6) The present invention in its second aspect provides an electronic device including at least one memory and at least one processor which function as: a display control unit configured to perform control to display a guide indicating a current focus position in a focus range from a first end on a close side to a second end on an infinity side, wherein the focus position is able to be changed by rotating a focus ring provided to a lens, the guide includes an arc including one end whose position corresponds to the first end, and an other end whose position corresponds to the second end, a center angle of the arc substantially matches with a rotation angle of the focus ring for changing the focus position from the first end to the second end, movement of the guide in a same rotation direction as a rotation direction of the focus ring indicates a change of the focus position, and the guide is different in a case of a first lens and in a case of a second lens.

(7) The present invention in its third aspect provides a control method of an electronic device, including: acquiring operation member information which is information on an operation member for a focus operation; and performing control to display a guide indicating a current focus position in a focus range from a first end on a close side to a second end on an infinity side based on the operation member information, wherein the guide includes a focus range portion which is a portion which is long in a predetermined direction, and includes one end whose a position in the predetermined direction corresponds to the first end, and an other end whose a position in the predetermined direction corresponds to the second end, a length of the focus range portion is a length according to an operation range which is a range of an operation amount of the focus operation which a user is able to perform on the operation member, and a position of the first end and a position of the second end at the focus range portion are positions according to a relationship between an operation direction of the focus operation on the operation member and a change direction of a focus position.

(8) The present invention in its fourth aspect provides a non-transitory computer readable medium that stores a program, wherein the program causes a computer to execute a control method of an electronic device, the control method including: acquiring operation member information which is

information on an operation member for a focus operation; and performing control to display a guide indicating a current focus position in a focus range from a first end on a close side to a second end on an infinity side based on the operation member information, wherein the guide includes a focus range portion which is a portion which is long in a predetermined direction, and includes one end whose a position in the predetermined direction corresponds to the first end, and an other end whose a position in the predetermined direction corresponds to the second end, a length of the focus range portion is a length according to an operation range which is a range of an operation amount of the focus operation which a user is able to perform on the operation member, and a position of the first end and a position of the second end at the focus range portion are positions according to a relationship between an operation direction of the focus operation on the operation member and a change direction of a focus position.

(9) Further features of the present invention will become apparent from the following description of exemplary embodiments with reference to the attached drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a block diagram illustrating a configuration of an imaging device according to the present embodiment;
- (2) FIG. 2 is a flowchart illustrating focus control according to the present embodiment;
- (3) FIG. 3 is a flowchart illustrating focus detection processing according to the present embodiment;
- (4) FIG. 4 is a flowchart illustrating AF driving processing according to the present embodiment;
- (5) FIG. 5 is a flowchart illustrating AF reactivation determination processing according to the present embodiment;
- (6) FIG. 6 is a flowchart illustrating MF driving processing according to the present embodiment;
- (7) FIG. 7 is a flowchart illustrating registration processing according to the present embodiment;
- (8) FIG. 8 is a flowchart illustrating match determination processing according to the present embodiment;
- (9) FIG. 9 is a flowchart illustrating display processing according to a first embodiment;
- (10) FIG. 10 is a flowchart illustrating display processing according to a second embodiment;
- (11) FIG. 11 is a flowchart illustrating display processing according to a third embodiment;
- (12) FIG. 12 is a view illustrating a match range according to the present embodiment;
- (13) FIG. 13 is a view illustrating a focus position guide according to the first embodiment;
- (14) FIG. 14A is a view illustrating a match guide and the focus position guide according to the first embodiment;
- (15) FIG. 14B is a view illustrating an index value icon of the focus position guide according to the first embodiment;
- (16) FIG. 15 is a view illustrating a change of the guide at a time of a focus operation according to the first embodiment;
- (17) FIGS. 16A to 16F are views illustrating a focus position guide according to the second embodiment; and
- (18) FIGS. 17A and 17B are views illustrating a focus position guide according to the third embodiment.

DESCRIPTION OF THE EMBODIMENTS

(19) Hereinafter, embodiments of the present invention will be described in detail with reference to the accompanying drawings. Note that the following embodiments do not limit the invention according to the claims. The following embodiments describe a plurality of features. However, all of the plurality of these features are not indispensable for the present invention, and the plurality of

features may be combined arbitrarily. Furthermore, same or similar components will be assigned the same reference numerals, and overlapping description thereof will be omitted.

First Embodiment

(20) Configuration of Imaging Device

(21) FIG. 1 is a block diagram schematically illustrating a configuration example of an interchangeable-lens type digital camera for shooting still images and moving images as an example of an imaging device according to the first embodiment of the present invention. Note that the present invention is not limited to the digital camera, and is applicable to various imaging devices. Furthermore, the present invention is applicable to an electronic device which is separate from the imaging device such as an external monitor connected to the imaging device. The external monitor may be a dedicated display device, or may not be a dedicated display device. Various electronic devices such as smartphones and tablet terminals can be used as the external monitor, and the present invention is applicable to the various electronic devices.

(22) An imaging device **1** in FIG. 1 mainly includes a detachable lens **200** and a camera main body unit **100**, and the lens **200** is attached to the camera main body unit **100** to use.

(23) The lens **200** will be described. In the lens **200**, a zoom unit **101** includes a zoom lens which changes magnification, and a zoom driving control unit **102** controls driving of the zoom unit **101**. A diaphragm unit **103** has a diaphragm function, and a diaphragm driving control unit **104** controls driving of the diaphragm unit **103**. An image blur correction unit **105** includes an image blur correction lens (e.g., shift lens), and an optical image blur correction control unit **106** controls driving of the image blur correction unit **105**. A focus unit **107** includes a focus lens which changes a focus position (a focal point and a focus adjustment position), and a focus driving control unit **108** controls driving of the focus unit **107**.

(24) A lens operation unit **109** includes various operation members for changing zoom, diaphragm, and focus states of the lens **200**. For example, the lens operation unit **109** includes an operation member (a focus operation member such as a focus ring) for a focus operation (manual focus operation) of changing the focus position. A lens shake detection unit **110** detects a shake amount of the lens **200**, and outputs a signal indicating the detected shake amount to a lens system control unit **111**. Note that the various operation members for changing the zoom, diaphragm, and focus states of the lens **200** may not be the operation members included in the lens operation unit **109**. For example, part of the operation members such as the focus operation member may be an operation member connected to the lens **200**, may be an operation member included in the camera main body unit **100**, or may be an operation member connected to the camera main body unit **100**.

(25) The lens system control unit **111** includes a Central Processing Unit (CPU), and integrally controls the overall lens **200** (each driving control unit and each correction control unit). The lens system control unit **111** can communicate with a camera system control unit **124** of the camera main body unit **100** via a lens communication control unit **112** and a camera communication control unit **125** of the camera main body unit **100**. Furthermore, the lens system control unit **111** acquires information which is necessary for the above-described integral control from each unit included in the lens **200**. For example, the lens system control unit **111** acquires focus operation information related to a focus operation on the focus operation member from the lens operation unit **109**. The focus operation information includes, for example, a current focus position, a direction of the focus operation, and an operation amount of the focus operation. The lens system control unit **111** may acquire current position information of each lens. The lens system control unit **111** transmits at least part of the acquired information to the camera system control unit **124** via the lens communication control unit **112** and the camera communication control unit **125** periodically or in response to a request from the camera system control unit **124**. Furthermore, the camera system control unit **124** performs various processing using the information received from the lens system control unit **111**.

(26) Next, the camera main body unit **100** will be described. In the camera main body unit **100**, a

shutter unit **113** controls entry of light (object light or light from an object) having passed through the lens **200** into the camera main body unit **100**. A shutter driving control unit **114** controls driving of the shutter unit **113**. An imaging unit **115** includes an imaging unit (image sensor) such as a CCD or CMOS sensor, and photoelectrically converts the light having passed through the shutter unit **113** and outputs an electric signal which expresses an optical image of the object. Note that the first embodiment assumes that the imaging element can individually receive a plurality of beams of light having passed through a plurality of exit pupil areas of the lens **200**, and output a plurality of electric signals (a plurality of electric signals associated with a plurality of exit pupil areas) corresponding to the plurality of beams of light. Furthermore, the camera system control unit **124** can perform focus detection of a so-called image plane phase-difference system based on the plurality of electric signals output from the imaging element. The imaging element can output a synthesis signal obtained by synthesizing (adding) the plurality of electric signals.

(27) An imaging signal processing unit **116** converts the electric signals output from an imaging unit **115** into focus detection signals and/or imaging signals. The focus detection signal is a signal for focus detection, and the imaging signal is a signal for display and/or recording. The imaging signal processing unit **116** outputs the focus detection signal to the camera system control unit **124**, and outputs the imaging signal to a video signal processing unit **117**. The video signal processing unit **117** processes the imaging signal output from the imaging signal processing unit **116** according to usage. For example, the video signal processing unit **117** can reduce an image blur of a video signal (image blur correction) by changing a clipping position of the video signal (a position to clip the video signal from the imaging signal) according to a correction amount of an electronic image blur correction control unit **123**.

(28) A display unit **118** displays images based on the video signal output from the video signal processing unit **117**, and displays information of various control of the lens system control unit **111** as needed. A recording unit **119** (recording medium) stores various items of data including the video signal output from the video signal processing unit **117**.

(29) A power supply unit **120** supplies power to each unit of the imaging device **1** according to usage.

(30) A camera operation unit **121** includes various operation members for the user to operate the imaging device **1**. For example, the camera operation unit **121** includes a shutter release button for instructing shooting of still images, a movie recording switch for instructing recording of movies, and a selection switch for selecting a playback mode. The camera operation unit **121** includes a button for selecting whether to enable or disable a focus position guide display function described later, and a button for registering a focus position guide index value described later. The camera operation unit **121** may include a shift button for changing the focus and zoom states of the lens **200**. The camera operation unit **121** outputs a signal matching (according to) a user's operation (an operation performed by the user) to the camera system control unit **124**. Note that these buttons and switches may be hardware keys or may be software keys. For user operations on the imaging device **1**, only ones of the hardware keys and the software keys may be used, or both of the hardware keys and the software keys may be used.

(31) The shutter release button is configured such that a first switch (SW1) and a second switch (SW2) are turned on in order in response to push. When the user pushes the shutter release button approximately halfway, the first switch SW1 is turned on, and, when the user pushes the shutter release button to the end, the second switch SW2 is turned on. In response to turning on of SW1, the focus driving control unit **108** drives the focus unit **107** to control (adjust) the focal point (focus position), and the diaphragm driving control unit **104** drives the diaphragm unit **103** to set an appropriate exposure amount. In response to turning on of SW2, image data (the video signal output from the video signal processing unit **117**) obtained from the optical image exposed to the imaging unit **115** is recorded in the recording unit **119**.

(32) When the user pushes the movie recording switch, recording of a movie starts, and, when the

user pushes the movie recording switch again during recording of the movie, recording of the movie ends. Note that a switch for instructing to start recording a movie and a switch for instructing to end recording a movie may be separately provided.

(33) A camera shake detection unit **122** detects a shake amount of the camera main body unit **100**, and outputs a signal indicating the detected shake amount to the camera system control unit **124**.

(34) The camera system control unit **124** includes a CPU, and integrally controls the overall imaging device **1**. The camera system control unit **124** can communicate with the lens system control unit **111** of the lens **200** via the camera communication control unit **125** and the lens communication control unit **112** of the lens **200**. In a state where the lens **200** is attached to and electrically connected to the camera main body unit **100**, the lens system control unit **111** and the camera system control unit **124** can communicate with each other via the lens communication control unit **112** and the camera communication control unit **125**.

(35) Focus Control

(36) Next, focus control performed by the camera system control unit **124** will be described with reference to a flowchart in FIG. **2**. The focus control in FIG. **2** is repeatedly performed in, for example, a shooting standby state.

(37) In **S201**, the camera system control unit **124** sets the focus position guide display function to enable or disable according to a user operation on the camera operation unit **121**.

(38) A user usually repeatedly performs a focus operation while visually checking a focus adjustment degree to adjust the focus on an object by manual focus control (MF). When adjusting the focus on a first object and then adjusting the focus on a second object, a user repeatedly performs the focus operation while visually checking a focus adjustment degree. The focus position guide display function is an assist function for such a focus operation. The focus position guide display function displays the focus position guide on the display unit **118**, for example, under control (display control) of the camera system control unit **124**. The focus position guide indicates a current focus position in a focus range (a range in which the focus position can be changed) from an end on a close side to an end on an infinity side. The user can perform the focus operation while checking the current focus position looking at the focus position guide, so that it is possible to expect an effect of reduction of a user's burden and reduction of a time taken until the focus is adjusted.

(39) The focus range is the range from the close end to the infinity end determined according to a mechanical configuration of the lens **200** in the first embodiment, yet is not limited to this. For example, the focus range may be an arbitrary range designated (set) by the user.

(40) The current focus position may be registered as the focus position guide index value in response to the user's operation (an instruction from the user) under control (registration control) of the camera system control unit **124**. Furthermore, the focus position guide may indicate the current focus position and the focus position guide index value. The user can perform the focus operation while checking current and past focus positions looking at the focus position guide, so that it is possible to expect the above effect of reduction of the user's burden and reduction of the time taken until the focus is adjusted.

(41) For example, the user instructs registration of the focus position guide index value in a state where the focus is adjusted on the first object. As a result, the focus position guide indicating the current focus position and the focus position guide index value (the focus position at which the focus is adjusted on the first object) is displayed. After adjusting the focus on the second object, the user can bring the focus position close to the focus position guide index value while checking the current focus position and the focus position guide index value looking at the focus position guide, and adjust the focus on the first object again.

(42) In **S202**, the camera system control unit **124** determines whether current settings of focus control are settings for performing automatic focus control (AF) or settings for performing manual focus control (MF). In a case of the settings for performing AF, the processing proceeds to **S203**,

and in a case of the settings for performing MF, the processing proceeds to S207.

(43) In S203, the camera system control unit **124** performs focus detection processing. The first embodiment assumes that defocus information and the degree of reliability for performing image plane phase difference AF is acquired by the focus detection processing. Details of the focus detection processing will be described later with reference to FIG. 3.

(44) In S204, the camera system control unit **124** determines whether or not AF driving is stopping. AF driving stop is a state where driving of the focus lens is stopped. The first embodiment assumes that, when it is determined that a current state is a focus adjustment state, driving of the focus lens is stopped. In a case where AF driving is not stopping, the processing proceeds to S205, and, in a case where AF driving is stopping, the processing proceeds to S206. The first embodiment assumes that whether or not AF driving is stopping is determination on whether or not an AF driving stop flag is set to on. The AF driving stop flag is set to on (a state where AF driving stop is enabled) during processing in S205 described later, and is set to off (a state where AF driving stop is disabled) during processing in S206 described later.

(45) In S205, the camera system control unit **124** performs AF driving processing based on the information acquired in S203. Subsequently, the processing proceeds to S208. Details of the AF driving processing will be described later with reference to FIG. 4.

(46) In S206, the camera system control unit **124** performs AF reactivation determination processing. Subsequently, the processing proceeds to S208. The AF reactivation determination processing is processing of determining whether or not to resume driving the focus lens. When, for example, a main object changes while AF driving is stopping, it is determined to resume driving the focus lens. Details of the AF reactivation determination processing will be described later with reference to FIG. 5.

(47) In S207, the camera system control unit **124** performs MF driving processing. Subsequently, the processing proceeds to S208. Details of the MF driving processing will be described later with reference to FIG. 6.

(48) In S208, the camera system control unit **124** determines whether or not the focus position guide display function is set to enable. In a case where the focus position guide display function is set to enable, the processing proceeds to S209. Furthermore, a series of processing related to the focus position guide display function are performed. In a case where the focus position guide display function is set to disable, the focus control in FIG. 2 is finished.

(49) In S209, the camera system control unit **124** acquires the focus operation member information related to the focus operation member to be used. For example, the camera system control unit **124** acquires the focus operation member information from the lens **200** via the camera communication control unit **125** and the lens communication control unit **112**. In a case where the focus operation member information related to the focus operation member to be used is stored in the recording unit **119** of the camera main body unit **100**, the camera system control unit **124** may acquire the focus operation member information from the recording unit **119**.

(50) The focus operation member information includes, for example, operation range information which indicates an operation range of the focus operation, and operation direction information which indicates a relationship between an operation direction of the focus operation and a change direction of the focus position. The operation range of the focus operation is a range of the operation amount of the focus operation which the user can perform on the focus operation member. As described above, the first embodiment assumes that the focus range is a range from the close end to the infinity end determined according to the mechanical configuration of the lens **200**. Hence, the operation range of the focus operation corresponds to the operation amount (effective operation amount) of the focus operation member which is necessary to change the focus position from one of the close end and the infinity end to the other one thereof.

(51) Hereinafter, a case will be considered where the focus operation member is a ring-shaped rotation operation member (focus ring). In this case, the operation range of the focus operation

corresponds to the rotation angle (effective operation angle) of the focus operation member which is necessary to change the focus position from one of the close end and the infinity end to the other one thereof. The operation direction of the focus operation is the rotation direction of the focus operation member. The operation direction information indicates that, in a case where, for example, the focus operation member is rotated in a first direction, the focus position changes from the close end to the infinity side, and, in a case where the focus operation member is rotated in a second direction, the focus position changes from the infinity side to the close side.

(52) In **S210**, the camera system control unit **124** performs focus position guide index value registration processing. Details of the focus position guide index value registration processing will be described later with reference to FIG. 7.

(53) In **S211**, the camera system control unit **124** performs focus position guide display processing. The operation range of the focus operation and the relationship between the operation direction of the focus operation and the change direction of the focus operation depends on a lens type. Therefore, when the same focus position guide is displayed irrespectively of the lens type, a user's sense and display of the focus position guide during the focus operation do not match, and the user cannot easily (intuitively) perform a desired focus operation in some cases. Hence, in **S211**, the camera system control unit **124** performs focus position guide display processing using the focus operation member information acquired in **S209**. Details of the focus position guide display processing will be described later with reference to FIG. 9.

(54) In **S212**, the camera system control unit **124** performs current focus position match determination processing. According to this match determination processing, the camera system control unit **124** determines whether or not the current focus position matches with the focus position guide index value registered in **S210**. Details of the focus position match determination processing will be described later with reference to FIG. 8.

(55) The focus control performed by the camera system control unit **124** has been described above. By periodically performing the focus control, the focus position and the focus position guide are periodically updated.

(56) Note that, although the focus control is repeatedly performed in the shooting standby state, the present invention is not limited to this. For example, the MF driving processing (**S207**) may be repeatedly performed only while the user operation is performed on the lens operation unit **109**. That the focus position guide display function has been set to enable may trigger repetition of a series of processing (**S209** to **S212**) related to the focus position guide display function until the focus position guide display function is set to disable. In addition, various modifications and changes are possible.

(57) Focus Detection Processing

(58) Next, the focus detection processing performed in **S203** in FIG. 2 will be described with reference to a flowchart in FIG. 3. In **S301**, the camera system control unit **124** acquires a pair of image signals (image data) from an arbitrarily set distance measurement range. In **S302**, the camera system control unit **124** calculates a correlation amount of the pair of image signals acquired in **S301**. In **S303**, the camera system control unit **124** calculates a correlation change amount from the correlation amount calculated in **S302**. In **S304**, the camera system control unit **124** calculates an out-of-focus amount from the correlation change amount calculated in **S303**. In **S305**, the camera system control unit **124** calculates the degree of the out-of-focus amount calculated in **S304**. In **S306**, the camera system control unit **124** converts the out-of-focus amount calculated in **S304** into a defocus amount. The camera system control unit **124** performs the processing in **S301** to **S306** on each of one or more distance measurement areas which exist in a distance measurement range. In **S307**, the distance measurement areas used for AF are determined.

(59) AF Driving Processing

(60) Next, the AF driving processing performed in **S205** in FIG. 2 will be described with reference to the flowchart in FIG. 4. The AF driving processing is performed in a case where AF driving is

not stopping. According to the AF driving processing, whether or not to enable AF driving stop is determined, and, in a case where AF driving stop is not enabled, the focus lens is driven.

(61) In **S401**, the camera system control unit **124** determines for the distance measurement area determined in **S307** in FIG. 3 whether or not a condition that the defocus amount calculated in **S306** is within a predetermined depth, and the degree of reliability calculated in **S305** is higher than a predetermined value is satisfied. When this condition is satisfied, the processing proceeds to **S402**, and, in a case where this condition is not satisfied, the processing proceeds to **S403**. The predetermined depth is, for example, an object depth or is a predetermined multiple of the object depth.

(62) In **S402**, the camera system control unit **124** determines that the current state is the focus adjustment state, and sets the AF driving stop flag to on (the state where AF driving stop is enabled). Thus, when it is determined that the current state is the focus adjustment state, driving of the focus lens is stopped, and whether or not to resume driving the focus lens is determined by the AF reactivation determination processing in **S206**.

(63) In **S403**, the camera system control unit **124** determines a driving speed, a driving amount, and a driving direction of the focus lens.

(64) In **S404**, the camera system control unit **124** drives the focus lens according to the driving speed, the driving amount, and the driving direction determined in **S403**, and updates the focus position.

(65) AF Reactivation Determination Processing

(66) Next, the AF reactivation determination processing performed in **S206** in FIG. 2 will be described with reference to a flowchart in FIG. 5. AF reactivation determination is performed while AF driving is stopping. According to the AF reactivation determination processing, whether or not to disable AF driving stop (whether or not to resume driving the focus lens) is determined.

(67) In **S501**, the camera system control unit **124** determines for the distance measurement area determined in **S307** in FIG. 3 whether or not the defocus amount calculated in **S306** is within the predetermined depth. In a case where the defocus amount is within the predetermined depth, the processing proceeds to **S502**, and, in a case where the defocus amount is within the predetermined depth, the processing proceeds to **S504**. The predetermined depth is, for example, the object depth or is a predetermined multiple of the object depth.

(68) In **S502**, the camera system control unit **124** determines for the distance measurement area determined in **S307** in FIG. 3 whether or not the degree of reliability calculated in **S305** is higher than the predetermined value. In a case where the degree of reliability is higher than the predetermined value, the processing proceeds to **S503**, and, in a case where the degree of reliability is the predetermined value or less, the processing proceeds to **S504**.

(69) In **S503**, the camera system control unit **124** resets an AF reactivation count value to 0. Subsequently, the processing proceeds to **S505**.

(70) In **S504**, the camera system control unit **124** adds 1 to the AF reactivation count value. Subsequently, the processing proceeds to **S505**.

(71) In a case where the defocus amount is large or the degree of reliability is low, it is highly probable that a shooting target main object has changed. Hence, in such a case, the camera system control unit **124** adds 1 to the AF reactivation count value in **S504** to prepare for resumption of driving of the focus lens. In a case where the defocus amount is small or the degree of reliability is high, the camera system control unit **124** resets the AF reactivation count value in **S503** to continue stopping driving the focus lens.

(72) Note that thresholds (thresholds of the defocus amount and the degree of reliability) used in **S501** and **S502** may be the same as a threshold used in **S401** in FIG. 4, or may be different. Various thresholds may be changed as appropriate. In a case where, for example, a change of the main object needs to be changed with high sensitivity, a small threshold (e.g., depth of field) may be used in **S501**. In a case where erroneous detection of the change of the main object needs to be

suppressed, a large threshold (e.g., a predetermined multiple of the depth of field) may be used in **S501**. Similarly, in a case where the change of the main object needs to be detected with high sensitivity, a small threshold may be used in **S502**. In a case where erroneous detection of the change of the main object needs to be suppressed, a large threshold may be used in **S502**.

(73) In **S505**, the camera system control unit **124** determines whether or not the AF reactivation count value is a predetermined threshold or more. In a case where the AF reactivation count value is the predetermined threshold or more, the processing proceeds to **S506**, and, in a case where the AF reactivation count value is less than the predetermined threshold, the AF reactivation determination processing in FIG. 5 is finished.

(74) In **S506**, the camera system control unit **124** determines that the main object has changed, and sets the AF driving stop flag to off (the state where AF driving stop is disabled).

(75) MF Driving Processing

(76) Next, the MF driving processing performed in **S207** in FIG. 2 will be described with reference to a flowchart in FIG. 6.

(77) In **S601**, the camera system control unit **124** determines whether or not the focus operation (manual focus operation) has been performed. In a case where the focus operation has been performed, the processing proceeds to **S602**, and, in a case where the focus operation has not been performed, the MF driving processing in FIG. 6 is finished.

(78) In **S602**, the camera system control unit **124** determines whether the focus lens position is electronically changed or mechanically changed. This determination may be interpreted as determination on whether the focus operation member is a member which is mechanically connected to the focus unit **107** or the focus driving control unit **108**, or a member which electronically transmits the focus operation information to the focus driving control unit **108**. In a case where the focus lens position is electronically changed, the processing proceeds to **S606**, and, in a case where the focus lens position is mechanically changed, the processing proceeds to **S603**.

(79) In **S603**, the camera system control unit **124** acquires the focus operation information generated based on the focus operation. For example, the lens system control unit **111** receives the focus operation information matching the focus operation from the lens operation unit **109**, and detects the direction of the focus operation and the operation amount of the focus operation based on the focus operation information. The lens system control unit **111** converts the focus operation information into information indicating the direction of the focus operation and the operation amount of the focus operation. Furthermore, the lens system control unit **111** transmits the converted focus operation information to the camera system control unit **124** via the lens communication control unit **112** and the camera communication control unit **125**.

(80) In **S604**, the camera system control unit **124** determines the driving speed, the driving amount, and the driving direction of the focus lens based on the focus operation information acquired in **S603**.

(81) In **S605**, the camera system control unit **124** drives the focus lens according to the driving speed, the driving amount, and the driving direction determined in **S604**, and updates the focus position. For example, the camera system control unit **124** transmits information of the driving speed, the driving amount, and the driving direction of the focus lens to the lens system control unit **111** via the camera communication control unit **125** and the lens communication control unit **112**. The lens system control unit **111** transmits a driving command for the focus lens to the focus driving control unit **108** based on the received information (the driving speed, the driving amount, and the driving direction). Furthermore, the focus driving control unit **108** drives the focus lens (focus lens **107**) according to the received driving command.

(82) In **S606**, the focus lens (focus lens **107**) is driven in response to the focus operation. Note that, in the case where the focus lens position is mechanically changed, too, the focus operation information may be acquired.

(83) Focus Position Guide Index Value Registration Processing

(84) Next, the focus position guide index value registration processing performed in S210 in FIG. 2 will be described with reference to a flowchart in FIG. 7.

(85) In S701, the camera system control unit 124 determines whether or not to register the current focus position as the focus position guide index value. For example, a function of registering the focus position guide index value is assigned to an assign button included in the camera operation unit 121 in FIG. 1, and determines whether or not the user has pushed the assign button. In a case where the current focus position is registered as the focus position guide index value, the processing proceeds to S702, and, in a case where the current focus position is not registered as the focus position guide index value, the processing proceeds to S703.

(86) In S702, the camera system control unit 124 registers the current focus position as the focus position guide index value. Then, the processing proceeds to S703. For example, it is assumed that 216 positions (0 to 65535) aligned at equal intervals from the close end to the infinity end are focus position guide index value candidates, and three focus position guide index values can be registered at maximum for one lens ID. Note that the number of the focus position guide index values which can be registered, and the number of the focus position guide index value candidates are not limited.

(87) In S703, the camera system control unit 124 selects whether or not to change sensitivity of the focus position match determination processing performed in S212 in FIG. 2. For example, the camera system control unit 124 determines whether or not the user has instructed to change the sensitivity using the camera operation unit 121 in FIG. 1. In a case where the sensitivity is changed, the processing proceeds to S704, and, in a case where the sensitivity is not changed, the registration processing in FIG. 7 is finished.

(88) In S704, the camera system control unit 124 sets the sensitivity of the match determination processing performed in S212. For example, the sensitivity can be set at five levels, and, according to the set sensitivity, a match range for determining that the registered focus position guide index value and the current focus position match is set. A rate for a maximum value of the focus position guide index values may be set as the sensitivity, and a range centered around the focus position guide index value may be set as the match range according to the rate.

(89) Focus Position Match Determination Processing

(90) Next, the focus position match determination processing performed in S212 in FIG. 2 will be described with reference to a flowchart in FIG. 8.

(91) In S801, the camera system control unit 124 determines whether the focus position guide index value registered in S702 and the current focus position (a processing result in S404 or S605) match at the sensitivity set in S704 in FIG. 7.

(92) For example, the camera system control unit 124 sets the match range for determining that the registered focus position guide index value and the current focus position match using following equations 1 to 3. In equations 1 to 3, FocusPosMax represents the maximum value of the focus position guide index value, Sens1 represents the sensitivity, Th1 represents the size of the match range, and FocusPos1 represents the focus position guide index value. Furthermore, Th1_lo represents the end (close side) of the match range, and Th1_hi represents the end (infinity side) of the match range. FIG. 12 illustrates the match range at a time of FocusPosMax=65535, FocusPos1=32767, and Sens1=0.05% (=0.0005). Furthermore, the camera system control unit 124 determines whether or not there is the match range including the current focus position. In a case where there is the match range including the current focus position, it is determined that the current focus position matches with the focus position guide index value matching the match range. In a case where there is not the match range including the current focus position, it is determined that the current focus position does not match with the focus position guide index value.

(93) $Th1 = FocusPosMax \times Sens1$ (Equation1) $Th1_lo = FocusPos1 - Th1 / 2$ (Equation2)

$Th1_hi = FocusPos1 + Th1 / 2$ (Equation3)

(94) In **S802**, the camera system control unit **124** displays on the display unit **118** a determination result on whether or not the current focus position matches with the focus position guide index value. In a case where, for example, the current focus position matches with the focus position guide index value as illustrated in FIG. **14A**, a match guide **1401** is displayed (the outline of the screen is highlighted). FIG. **14A** illustrates an example of the screen (display screen) displayed on the display unit **118**). In a case where the current focus position does not match with the focus position guide index value, the match guide **1401** is not displayed. Consequently, it is possible to identify whether or not the current focus position matches with the focus position guide index value. The screen may be displayed on an entire display surface (a surface which displays various images and various screens) included in the display unit **118**, or may be displayed on part of the display surface. The match guide **1401** may be interpreted as part of the focus position guide.

(95) Focus Position Guide Display Processing

(96) Next, the focus position guide display processing performed in **S211** in FIG. **2** will be described with reference to a flowchart in FIG. **9**.

(97) In **S901**, the camera system control unit **124** displays the focus position guide on the display unit **118** based on the focus operation member information acquired in **S209** in FIG. **2**. The first embodiment assumes that the focus operation member is the focus ring (rotation operation member). Furthermore, as described above, the first embodiment assumes that the focus range is the range from the close end to the infinity end determined according to the mechanical configuration of the lens **200**. Hence, as the focus position guide, a guide is displayed which includes a portion (focus range portion) which is long in a circumferential direction (a predetermined direction which substantially matches with the circumferential direction), and includes one end whose position in the circumferential direction corresponds to the close end and an other end whose position in the circumferential direction corresponds to the infinity end.

(98) For example, the focus position guide illustrated in FIG. **13** is displayed. The focus position guide in FIG. **13** includes an item **1301** which includes a focus range portion **1302** (bold arc), and an item **1303** (icon) which indicates the current focus position according to (by) a positional relationship with the focus range portion **1302**. “Near” in FIG. **13** means that this position corresponds to the close end, and “Far” means that this position corresponds to the infinity end.

(99) Note that, instead of character strings such as “Near” and “Far”, icons may indicate the close end and the infinity end. The entire item **1301** may correspond to the focus range portion **1302**, and, for example, an arc-shaped item may be displayed as the item **1301**. As the item **1301**, a fan-shaped item whose entire arc portion is the focus range portion may be displayed. The focus range portion **1302** may include a plurality of portions which are aligned in the circumferential direction (predetermined direction) and have different colors from each other. For example, the focus range portion **1302** may be displayed as a gradation in the circumferential direction. Furthermore, the camera system control unit **124** may display the item **1303** with a color of a portion corresponding to the current focus position among the plurality of portions.

(100) The camera system control unit **124** sets the length of the focus range portion **1302** (arc) in the circumferential direction (predetermined direction) based on the operation range information (the operation range of the focus operation) included in the focus operation member information. For example, an angle (a center angle of the arc) matching (corresponding to) the length of the focus range portion **1302** substantially matches with the effective operation angle of the focus ring.

(101) Furthermore, the camera system control unit **124** sets the positions of the close end and the infinity end at the focus range portion **1302** (arc) based on the operation direction information (the relationship between the operation direction of the focus operation and the change direction of the focus position) included in the focus operation member information. For example, the position of the close end and the position of the infinity end at the focus range portion **1302** (arc) are set such that movement of the focus position guide in the same rotation direction as the rotation direction of the focus ring indicates the change of the focus position. The movement which indicates the change

of the focus position will be described later.

(102) Accordingly, the user's sense and display of the focus guide during the focus operation match, so that the user can easily (intuitively without hesitation) perform a desired focus operation.

(103) In the first embodiment, the focus position guide differs depending on the lens type. As, for example, the effective operation angle of the focus ring is larger, the length (center angle) of the focus range portion (arc) is longer. In a case where the focus position is changed from the close end to the infinity side when the focus ring is turned right, and the focus position is changed from the infinity side to the close side when the focus ring is turned left, the right end of the focus range portion (arc) corresponds to the close end, and the left end corresponds to the infinity end. In a case where the focus position is changed from the infinity end to the close side when the focus ring is turned right, and the focus position is changed from the close side to the infinity side when the focus ring is turned left, the right end of the focus range portion (arc) corresponds to the infinity end, and the left end corresponds to the close end.

(104) In **S902**, the camera system control unit **124** overlays the item indicating the focus position guide index value registered by the registration processing (focus position guide index value registration processing) in **S210** on the focus position guide displayed in **S901** to display. The item which indicates the focus position guide index value may be interpreted as part of the focus position guide.

(105) Examples of the item indicating the focus position guide index value are illustrated in FIGS. **14A** and **14B**. FIG. **14B** is an enlargement view of a focus position guide **1402** displayed on the screen illustrated in FIG. **14A**. Three index value icons **1411** to **1413** indicating three focus position guide index values are overlaid and displayed on the focus position guide **1402**. The focus position guide index value associated with the index value icon **1411** is a focus position at which the focus is adjusted on a person **1421**, and the focus position guide index value associated with the index value icon **1412** is a focus position at which the focus is adjusted on a person **1422**.

(106) The index value icons **1411** to **1413** are displayed in different display modes (e.g., colors). Furthermore, the match guide **1401** is displayed in the same display mode as the index value icon associated with the focus position guide index value which the current focus position has been determined match with. Consequently, even in a case where the focus position guide index values concentrate, the user can easily grasp the focus position guide index value which matches with the current focus position. In FIG. **14A**, the current focus position matches with the focus position guide index value associated with the index value icon **1411**.

(107) Note that, although the example has been described where the index value icons indicating the focus position guide indices are displayed, the focus position guide index values may be indicated by other methods. For example, the example has been described where the index value icon is overlaid on the focus range portion **1302** (arc). However, similar to the item **1303** indicating the current focus position, the index value icon may be displayed outside the focus range portion **1302**. Furthermore, the example has been described where the match guide **1401** which highlights the outline of the screen is displayed. However, match of the focus position and the focus position guide index value may be indicated by other methods. For example, the display mode of the item **1303** indicating the current focus position may be changed to the same display mode as the index value icon associated with the focus position guide index value which the current focus position has been determined to match with.

(108) In **S903**, the camera system control unit **124** controls display of the focus position guide to indicate the change of the focus position based on the driving speed, the driving amount, and the driving direction determined in **S205** in FIG. **2** or the focus operation information acquired in **S207**. For example, as illustrated in FIG. **15**, the item **1303** indicating the current focus position is fixed, and the item **1301** (focus range portion **1302**) is rotated. The present invention is not limited to this, and various movement such as movement performed by, for example, fixing the item **1301** (focus range portion **1302**) and moving the item **1303** may indicate a change of the focus position. Instead

of the focus operation information acquired in S207 (S603), the driving speed, the driving amount, and the driving direction determined in S604 may be used.

(109) Conclusion

(110) As described above, according to the first embodiment, the length of the focus range portion is set according to the operation range of the focus operation. Furthermore, the position of the close end and the position of the infinity end of the focus range portion are set according to the relationship between the operation direction of the focus operation and the change direction of the focus position. Consequently, the user's sense and display of the focus position guide during the focus operation match, so that the user can easily (intuitively without hesitation) perform a desired focus operation.

(111) Note that the camera system control unit 124 may hide the focus position guide in response to a lapse of a predetermined time in a state where the focus operation is not performed (e.g., a non-operation state where the user operation is not performed at all). The camera system control unit 124 may increase the degree of transparency of the focus position guide or change a display position of the focus position guide in response to the lapse of the predetermined time in the state where the focus operation is not performed. The camera system control unit 124 may control the degree of transparency of the focus position guide to the degree of transparency designated by the user. The camera system control unit 124 may move the focus position guide to a position designated by the user.

Second Embodiment

(112) The second embodiment will be described. The second embodiment will describe an example where the focus position guide is displayed in different display modes in a case where the operation range of the focus operation is wider than a predetermined range, and in a case where the operation range of the focus operation is narrower than the predetermined range. Note that the configuration of the imaging device is the same as that in the first embodiment, and therefore description thereof will be omitted. Processing (control) other than the focus position guide display processing is also the same as those in the first embodiment, and therefore description thereof will be omitted.

(113) Focus position guide display processing according to the second embodiment will be described with reference to a flowchart in FIG. 10. In S211 in FIG. 2, the display processing in FIG. 10 is performed in place of the display processing in FIG. 9.

(114) In S1001, the camera system control unit 124 determines whether or not the operation range of the focus operation is wider than the predetermined range based on the focus operation member information (operation range information) acquired in S209 in FIG. 2. For example, the camera system control unit 124 determines whether or not the effective operation angle of the focus ring is larger than 360°. In a case where the operation range of the focus operation is wider than the predetermined range (a case where the effective operation angle is larger than 360°, the processing proceeds to S1002, and, in a case where the operation range of the focus operation is not wider than the predetermined range (a case where the effective operation angle is 360° or less), the processing proceeds to S1003.

(115) In S1002, the camera system control unit 124 displays the focus position guide of a first display mode on the display unit 118. Subsequently, the processing proceeds to S1004. For example, the camera system control unit 124 displays the focus position guide including a spiral focus range portion on the display unit 118 as illustrated in FIG. 16A. FIG. 16A illustrates an example of a case where the effective operation angle is 540°.

(116) In S1003, the camera system control unit 124 displays the focus position guide of a second display mode on the display unit 118. Subsequently, the processing proceeds to S1004. In a case where, for example, the effective operation angle is smaller than 360°, the camera system control unit 124 displays the focus position guide including an arc-shaped focus range portion on the display unit 118 similar to FIG. 13. In a case where, for example, the effective operation angle is 360°, the camera system control unit 124 displays the focus position guide including a circular

focus range portion on the display unit **118** as illustrated in FIG. **16B**.

(117) Processing in **S1004** is the same as the processing in **S902** in FIG. **9**, and processing in **S1005** is the same as the processing in **S903**.

(118) In a case where, for example, the effective operation angle is large than 360° , the portion corresponding to the close end may be hidden, and the focus range portion may be displayed in a circular shape as illustrated in FIG. **16C** during the focus operation of changing the focus position from the close side to the infinity side. Similarly, the portion corresponding to the infinity end may be hidden, and the focus range portion may be displayed in a circular shape as illustrated in FIG. **16D** during the focus operation of changing the focus position from the infinity side to the close side.

(119) Furthermore, the display modes of the focus position guides are not limited in particular, and, in a case where, for example, the effective operation angle is 360° or less, the focus range portion may be displayed in a shape formed by making a spiral shape shorter. FIG. **16E** illustrates an example of a case where the effective operation angle is 360° . In the case where the effective operation angle is larger than 360° , the focus range portion may be displayed in a circular shape as illustrated in FIG. **16F**. FIG. **16F** illustrates that the focus range portion is longer than one lap by transparent display, and illustrates that the effective operation angle is larger than 360° . In a case of FIG. **16F**, during the focus operation of changing the focus position from the close side to the infinity side, the portion corresponding to the infinity end may be displayed in a layer higher than that of the portion corresponding to the close end. Similarly, during the focus operation of changing the focus position from the infinity side to the close side, the portion corresponding to the infinity end may be displayed in a layer higher than that of the portion corresponding to the close end.

(120) As described above, according to the second embodiment, the focus position guides are displayed in the different display modes in the case where the operation range of the focus operation is wider than the predetermined range, and in the case where the operation range of the focus operation is narrower than the predetermined range. Consequently, even when the effective operation angle exceeds 360° , the focus position guide can indicate the entire focus range. As a result, the user can easily grasp the operation range and the operation direction of the focus operation, and easily (intuitively without hesitation) a desired focus operation.

Third Embodiment

(121) The third embodiment will be described. The third embodiment will describe an example where the focus range portion is displayed along the outline of the screen. Note that the configuration of the imaging device is the same as that in the first embodiment, and therefore description thereof will be omitted. Processing (control) other than the focus position guide display processing is also the same as those in the first embodiment, and therefore description thereof will be omitted. In this regard, in **S604** in FIG. **6**, the driving speed, the driving amount, and the driving direction of the focus lens are determined based on the focus operation information and operation sensitivity arbitrarily set by the user.

(122) Focus position guide display processing according to the third embodiment will be described with reference to a flowchart in FIG. **11**. In **S211** in FIG. **2**, the display processing in FIG. **11** is performed in place of the display processing in FIG. **9**.

(123) In **S1101**, the camera system control unit **124** converts the operation range information (the operation range of the focus operation such as the effective operation amount or the effective operation angle) acquired in **S209** in FIG. **2** into the length of the focus range portion based on the operation sensitivity arbitrarily set by the user. In a case where, for example, the operation sensitivity is high, the focus range portion is made longer to increase movement of the focus position guide (the movement which indicates the change of the focus position) in response to a predetermined operation amount of the focus operation. In a case where, for example, the operation sensitivity is low, the focus range portion is made shorter to decrease the movement of the focus position guide (the movement which indicates the change of the focus position) in response to the

predetermined operation amount of the focus operation.

(124) In **S1102**, the camera system control unit **124** acquires the length of a predetermined side of the screen which displays the focus position guide. For example, the camera system control unit **124** acquires the length of the right side of the screen.

(125) In **S1103**, the camera system control unit **124** determines whether or not the length of the focus range portion acquired in **S1101** is longer than the length of the right side acquired in **S1102**. In a case where the length of the focus range portion is longer than the length of the right side of the screen, the processing proceeds to **S1104**, and, in a case where the length of the focus range portion is the length of the right side of the screen or less, the processing proceeds to **S1105**.

(126) Note that, in place of the processing in **S1101** to **S1103**, whether or not the effective operation angle is larger than a threshold may be determined. For example, a rotation angle which matches the length of the right side of the screen and which is smaller as the operation sensitivity is higher (the rotation angle is larger as the operation sensitivity is lower) is set as the threshold. In a case where the effective operation angle is larger than the threshold, the processing proceeds to **S1104**, and, in a case where the effective operation angle is the threshold or less, the processing proceeds to **S1105**. In **S1104**, the camera system control unit **124** displays the focus position guide of the first display mode on the display unit **118**. Subsequently, the processing proceeds to **S1106**. For example, a focus position guide illustrated in FIG. **17A** is displayed. The focus position guide in FIG. **17A** includes a focus range portion **1701**, and an item **1702** which indicates the current focus position according to a positional relationship with the focus range portion **1701**. In FIG. **17A**, the focus range portion **1701** is displayed along the right side and the upper side of the screen (from the right side to the upper side of the screen).

(127) In **S1105**, the camera system control unit **124** displays the focus position guide of the second display mode on the display unit **118**. Subsequently, the processing proceeds to **S1106**. For example, a focus position guide illustrated in FIG. **17B** is displayed. The focus position guide in FIG. **17B** also includes a focus range portion **1701** and the item **1702**. In FIG. **17B**, the focus range portion **1701** is displayed along only the right side of the screen. The focus range portion is displayed on the entire right side in FIG. **17B**. However, the focus range portion may be displayed on part of the right side. In a case where, for example, the rotation angle matching the length of the entire right side is 360° and the effective operation angle is 180° , the focus range portion is displayed from the lower end of the right side to the center of the right side.

(128) Processing in **S1106** is the same as the processing in **S902** in FIG. **9**, and processing in **S1107** is the same as the processing in **S903**. In this regard, in **S1107**, in a case where the focus operation information is used, the operation sensitivity arbitrarily set by the user is further used. In cases in FIGS. **17A** and **17B**, the item **1702** moves to indicate the change of the focus position.

(129) Note that the focus range portion may be displayed in the circular shape, the arc shape, or the spiral shape similar to the second embodiment. In this case, in **S1103**, whether or not the length of the focus range portion is longer than a predetermined circumferential length may be determined.

(130) As described above, according to the third embodiment, the focus position guides are displayed in the different display modes in the case where the length of the focus range portion is longer than the predetermined length, and in the case where the length of the focus range portion is shorter than the predetermined length. Consequently, even in a case where the effective operation amount (effective operation angle) is large, the focus position guide can indicate the entire focus range. As a result, the user can easily grasp the operation range and the operation direction of the focus operation, and easily (intuitively without hesitation) a desired focus operation.

Other Embodiments

(131) Embodiment(s) of the present invention can also be realized by a computer of a system or apparatus that reads out and executes computer executable instructions (e.g., one or more programs) recorded on a storage medium (which may also be referred to more fully as a 'non-transitory computer-readable storage medium') to perform the functions of one or more of the

above-described embodiment(s) and/or that includes one or more circuits (e.g., application specific integrated circuit (ASIC)) for performing the functions of one or more of the above-described embodiment(s), and by a method performed by the computer of the system or apparatus by, for example, reading out and executing the computer executable instructions from the storage medium to perform the functions of one or more of the above-described embodiment(s) and/or controlling the one or more circuits to perform the functions of one or more of the above-described embodiment(s). The computer may comprise one or more processors (e.g., central processing unit (CPU), micro processing unit (MPU)) and may include a network of separate computers or separate processors to read out and execute the computer executable instructions. The computer executable instructions may be provided to the computer, for example, from a network or the storage medium. The storage medium may include, for example, one or more of a hard disk, a random-access memory (RAM), a read only memory (ROM), a storage of distributed computing systems, an optical disk (such as a compact disc (CD), digital versatile disc (DVD), or Blu-ray Disc (BD)TM), a flash memory device, a memory card, and the like.

(132) While the present invention has been described with reference to exemplary embodiments, it is to be understood that the invention is not limited to the disclosed exemplary embodiments. The scope of the following claims is to be accorded the broadest interpretation so as to encompass all such modifications and equivalent structures and functions.

(133) This application claims the benefit of Japanese Patent Application No. 2023-029349, filed on Feb. 28, 2023, which is hereby incorporated by reference herein in its entirety.

Claims

1. An electronic device comprising at least one memory and at least one processor which function as: an acquisition unit configured to acquire operation member information which is information on an operation member for a focus operation; and a display control unit configured to perform control to display a guide indicating a current focus position in a focus range from a first end on a close side to a second end on an infinity side based on the operation member information, wherein the guide includes a focus range portion which is a portion which is long in a predetermined direction, and includes one end whose a position in the predetermined direction corresponds to the first end, and an other end whose a position in the predetermined direction corresponds to the second end, a length of the focus range portion is a length according to an operation range which is a range of an operation amount of the focus operation which a user is able to perform on the operation member, and a position of the first end and a position of the second end at the focus range portion are positions according to a relationship between an operation direction of the focus operation on the operation member and a change direction of a focus position.
2. The electronic device according to claim 1, wherein the focus range is a range designated by the user.
3. The electronic device according to claim 1, wherein the focus range is a range from a close end to an infinity end determined according to a mechanical configuration of a lens.
4. The electronic device according to claim 1, wherein the at least one memory and the at least one processor further function as a registration control unit configured to perform control to register the current focus position according to an instruction from the user, the guide further indicates the registered focus position.
5. The electronic device according to claim 4, wherein the display control unit performs control to display the guide to enable identification on whether or not the current focus position matches with the registered focus position.
6. The electronic device according to claim 1, wherein the operation member information includes information indicating the operation range of the focus operation, and information indicating the relationship between the operation direction of the focus operation and the change direction of the

focus position.

7. The electronic device according to claim 1, wherein the operation member is a rotation operation member, the predetermined direction substantially matches with a circumferential direction, and an angle corresponding the length of the focus range portion substantially matches with a rotation angle of the operation member corresponding to the operation range of the focus operation.

8. The electronic device according to claim 1, wherein the operation member is a rotation operation member, the predetermined direction substantially matches with a circumferential direction, and movement of the guide in a same rotation direction as a rotation direction of the operation member indicates a change of the focus position.

9. The electronic device according to claim 1, wherein the display control unit performs control to hide the guide in response to a lapse of a predetermined time in a state where the focus operation is not performed.

10. The electronic device according to claim 1, wherein the display control unit performs control to display the guide at a degree of transparency designated by the user.

11. The electronic device according to claim 1, wherein the operation range of the focus operation corresponds to an operation amount of the operation member which is necessary to change the focus position from one of the first end and the second end to other one of the first end and the second end.

12. The electronic device according to claim 1, wherein the guide includes a first item which includes the focus range portion, and a second item which indicates the current focus position by a positional relationship with the focus range portion.

13. The electronic device according to claim 1, wherein the display control unit performs control to display the guide in a different display mode in a case where the operation range of the focus operation is wider than a predetermined range, and in a case where the operation range is narrower than the predetermined range.

14. The electronic device according to claim 13, wherein the operation member is a rotation operation member, and the predetermined range is a range corresponding to 360° .

15. The electronic device according to claim 1, wherein the display control unit performs control to display the guide in a different display mode in a case where the length of the focus range portion is longer than a predetermined length, and in a case where the length of the focus range portion is shorter than the predetermined length.

16. The electronic device according to claim 15, wherein the predetermined length is a length of a predetermined side of a screen.

17. The electronic device according to claim 1, wherein the guide includes a first item which includes the focus range portion, and a second item which indicates the current focus position by a positional relationship with the focus range portion, the operation member is a rotation operation member, and the display control unit performs control to display the focus range portion in an arc shape in a case where a rotation angle of the operation member corresponding to the operation range of the focus operation is smaller than 360° , and performs control to display the focus range portion in a spiral shape in a case where the rotation angle is larger than 360° .

18. The electronic device according to claim 17, wherein, in the case where the rotation angle is larger than 360° , the display control unit performs control to hide a portion corresponding to the first end, and display the focus range portion in a circular shape during a focus operation of changing the focus position from a side of the first end to a side of the second end, and performs control to hide a portion corresponding to the second end, and display the focus range portion in a circular shape during a focus operation of changing the focus position from the side of the second end to the side of the first end.

19. The electronic device according to claim 1, wherein the guide includes a first item which includes the focus range portion, and a second item which indicates the current focus position by to a positional relationship with the focus range portion, and the display control unit performs control

to display the focus range portion along a first side of a screen in a case where the length of the focus range portion is shorter than a length of the first side, and performs control to display the focus range portion along the first side and a second side of the screen in contact with the first side in a case where the length of the focus range portion is longer than the length of the first side.

20. The electronic device according to claim 1, wherein the guide includes a first item which includes the focus range portion, and a second item which indicates the current focus position by a positional relationship with the focus range portion, the focus range portion includes a plurality of portions which are aligned in the predetermined direction and have colors different from each other, and the display control unit performs control to display the second item with a color of a portion corresponding to the current focus position among the plurality of portions.

21. An electronic device comprising at least one memory and at least one processor which function as: a display control unit configured to perform control to display a guide indicating a current focus position in a focus range from a first end on a close side to a second end on an infinity side, wherein the focus position is able to be changed by rotating a focus ring provided to a lens, the guide includes an arc including one end whose position corresponds to the first end, and an other end whose position corresponds to the second end, a center angle of the arc substantially matches with a rotation angle of the focus ring for changing the focus position from the first end to the second end, movement of the guide in a same rotation direction as a rotation direction of the focus ring indicates a change of the focus position, and the guide is different in a case of a first lens and in a case of a second lens.

22. A control method of an electronic device, comprising: acquiring operation member information which is information on an operation member for a focus operation; and performing control to display a guide indicating a current focus position in a focus range from a first end on a close side to a second end on an infinity side based on the operation member information, wherein the guide includes a focus range portion which is a portion which is long in a predetermined direction, and includes one end whose a position in the predetermined direction corresponds to the first end, and an other end whose a position in the predetermined direction corresponds to the second end, a length of the focus range portion is a length according to an operation range which is a range of an operation amount of the focus operation which a user is able to perform on the operation member, and a position of the first end and a position of the second end at the focus range portion are positions according to a relationship between an operation direction of the focus operation on the operation member and a change direction of a focus position.

23. A non-transitory computer readable medium that stores a program, wherein the program causes a computer to execute a control method of an electronic device, the control method comprising: acquiring operation member information which is information on an operation member for a focus operation; and performing control to display a guide indicating a current focus position in a focus range from a first end on a close side to a second end on an infinity side based on the operation member information, wherein the guide includes a focus range portion which is a portion which is long in a predetermined direction, and includes one end whose a position in the predetermined direction corresponds to the first end, and an other end whose a position in the predetermined direction corresponds to the second end, a length of the focus range portion is a length according to an operation range which is a range of an operation amount of the focus operation which a user is able to perform on the operation member, and a position of the first end and a position of the second end at the focus range portion are positions according to a relationship between an operation direction of the focus operation on the operation member and a change direction of a focus position.
