

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12396870
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Gorochow; Lacey

Stent with shaped wires

Abstract

Stents generally can include a tubular structure having circumferentially positioned undulating wires that extend over a majority of a length of the stent such that the undulations oscillate circumferentially to define a circumference of the stent. The undulations can wrap over and under adjacent undulations to form an interwoven structure. Additionally, or alternatively, adjacent wires can be joined. Wires forming the stent can be cut from elastic tubing such that each wire has a three-dimensional shape.

Inventors:	Gorochow; Lacey (Miami, FL)
Applicant:	DePuy Synthes Products, Inc. (Raynham, MA)
Family ID:	1000008777510
Assignee:	DEPUY SYNTHES PRODUCTS, INC. (Raynham, MA)
Appl. No.:	18/111164
Filed:	February 17, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230190498 A1	Jun. 22, 2023

Related U.S. Application Data

division parent-doc US 16577567 20190920 US 11590007 child-doc US 18111164
us-provisional-application US 62734128 20180920

Publication Classification

Int. Cl.: **A61F2/86** (20130101); **A61F2/82** (20130101); **A61F2/90** (20130101); **A61F2/91** (20130101); A61F2/88 (20060101); D03D1/00 (20060101); D03D9/00 (20060101)

U.S. Cl.:

CPC **A61F2/86** (20130101); **A61F2/82** (20130101); **A61F2/90** (20130101); **A61F2/91** (20130101); A61F2/885 (20130101); A61F2210/0014 (20130101); A61F2230/0013 (20130101); A61F2240/001 (20130101); A61F2250/0036 (20130101); D03D1/00 (20130101); D03D9/00 (20130101); D10B2509/06 (20130101)

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4800882	12/1988	Gianturco	N/A	N/A
4969458	12/1989	Wiktor	N/A	N/A
5370683	12/1993	Fontaine	N/A	N/A
5707387	12/1997	Wijay	N/A	N/A
5925061	12/1998	Ogi et al.	N/A	N/A
6027526	12/1999	Limon et al.	N/A	N/A
6391037	12/2001	Greenhalgh	N/A	N/A
6517570	12/2002	Lau et al.	N/A	N/A
6551351	12/2002	Smith et al.	N/A	N/A
8277500	12/2011	Schmid et al.	N/A	N/A
8454535	12/2012	Majercak et al.	N/A	N/A
8585643	12/2012	Vo et al.	N/A	N/A
8623070	12/2013	Bales et al.	N/A	N/A
8721676	12/2013	Janardhan et al.	N/A	N/A
9039755	12/2014	Richter	N/A	N/A
9066827	12/2014	Schmid et al.	N/A	N/A
9232992	12/2015	Heidner	N/A	N/A
9314354	12/2015	Morris et al.	N/A	N/A
9408732	12/2015	Weier et al.	N/A	N/A
9452068	12/2015	Schmid et al.	N/A	N/A
9486339	12/2015	Bales, Jr. et al.	N/A	N/A
9532792	12/2016	Galdonik et al.	N/A	N/A
9532873	12/2016	Kelley	N/A	N/A
9533344	12/2016	Monetti et al.	N/A	N/A
9539011	12/2016	Chen et al.	N/A	N/A
9539022	12/2016	Bowman	N/A	N/A
9539122	12/2016	Burke et al.	N/A	N/A
9539382	12/2016	Nelson	N/A	N/A
9549830	12/2016	Bruszewski et al.	N/A	N/A
9554805	12/2016	Tompkins et al.	N/A	N/A
9561125	12/2016	Bowman et al.	N/A	N/A

9572982	12/2016	Burnes et al.	N/A	N/A
9579484	12/2016	Barnell	N/A	N/A
9585642	12/2016	Dinsmoor et al.	N/A	N/A
9615832	12/2016	Bose et al.	N/A	N/A
9615951	12/2016	Bennett et al.	N/A	N/A
9622753	12/2016	Cox	N/A	N/A
9622888	12/2016	Armstrong et al.	N/A	N/A
9636115	12/2016	Henry et al.	N/A	N/A
9636439	12/2016	Chu et al.	N/A	N/A
9642675	12/2016	Werneth et al.	N/A	N/A
9655633	12/2016	Leynov et al.	N/A	N/A
9655645	12/2016	Staunton	N/A	N/A
9655989	12/2016	Cruise et al.	N/A	N/A
9662129	12/2016	Galdonik et al.	N/A	N/A
9662238	12/2016	Dwork et al.	N/A	N/A
9662425	12/2016	Lilja et al.	N/A	N/A
9668898	12/2016	Wong	N/A	N/A
9675477	12/2016	Thompson	N/A	N/A
9675782	12/2016	Connolly	N/A	N/A
9676022	12/2016	Ensign et al.	N/A	N/A
9692557	12/2016	Murphy	N/A	N/A
9693852	12/2016	Lam et al.	N/A	N/A
9700262	12/2016	Janik et al.	N/A	N/A
9700399	12/2016	Acosta-Acevedo	N/A	N/A
9717421	12/2016	Griswold et al.	N/A	N/A
9717500	12/2016	Tieu et al.	N/A	N/A
9717502	12/2016	Teoh et al.	N/A	N/A
9724103	12/2016	Cruise et al.	N/A	N/A
9724526	12/2016	Strother et al.	N/A	N/A
9750565	12/2016	Bloom et al.	N/A	N/A
9757260	12/2016	Greenan	N/A	N/A
9764111	12/2016	Gulachenski	N/A	N/A
9770251	12/2016	Bowman et al.	N/A	N/A
9770577	12/2016	Li et al.	N/A	N/A
9775621	12/2016	Tompkins et al.	N/A	N/A
9775706	12/2016	Peterson et al.	N/A	N/A
9775732	12/2016	Khenansho	N/A	N/A
9788800	12/2016	Mayoras, Jr.	N/A	N/A
9795391	12/2016	Saatchi et al.	N/A	N/A
9795496	12/2016	Armstrong et al.	N/A	N/A
9801980	12/2016	Karino et al.	N/A	N/A
9808599	12/2016	Bowman et al.	N/A	N/A
9833252	12/2016	Sepetka et al.	N/A	N/A
9833604	12/2016	Lam et al.	N/A	N/A
9833625	12/2016	Waldhauser et al.	N/A	N/A
11590007	12/2022	Gorochow	N/A	A61F 2/91
2001/0003801	12/2000	Strecker	N/A	N/A
2002/0022875	12/2001	Strecker	623/1.15	A61F 2/90
2002/0173839	12/2001	Leopold et al.	N/A	N/A
2003/0083735	12/2002	Denardo et al.	N/A	N/A

2003/0114920	12/2002	Caro et al.	N/A	N/A
2003/0171801	12/2002	Bates	N/A	N/A
2004/0039435	12/2003	Hancock	623/1.2	A61B 17/12022
2006/0064151	12/2005	Guterman	N/A	N/A
2006/0136041	12/2005	Schmid et al.	N/A	N/A
2007/0208409	12/2006	Quigley	N/A	N/A
2008/0281350	12/2007	Sepetka	N/A	N/A
2010/0324649	12/2009	Mattsson	N/A	N/A
2011/0054590	12/2010	Leopold et al.	N/A	N/A
2012/0283768	12/2011	Cox et al.	N/A	N/A
2013/0226282	12/2012	Ahn et al.	N/A	N/A
2014/0135812	12/2013	Divino et al.	N/A	N/A
2014/0200607	12/2013	Sepetka et al.	N/A	N/A
2014/0330367	12/2013	Thapliyal	623/2.11	A61F 2/2415
2017/0007264	12/2016	Cruise et al.	N/A	N/A
2017/0007265	12/2016	Guo et al.	N/A	N/A
2017/0020670	12/2016	Murray et al.	N/A	N/A
2017/0020700	12/2016	Bienvenu et al.	N/A	N/A
2017/0027640	12/2016	Kunis et al.	N/A	N/A
2017/0027692	12/2016	Bonhoeffer et al.	N/A	N/A
2017/0027725	12/2016	Argentine	N/A	N/A
2017/0035436	12/2016	Morita	N/A	N/A
2017/0035567	12/2016	Duffy	N/A	N/A
2017/0042548	12/2016	Lam	N/A	N/A
2017/0049596	12/2016	Schabert	N/A	N/A
2017/0071737	12/2016	Kelley	N/A	N/A
2017/0072452	12/2016	Monetti et al.	N/A	N/A
2017/0079671	12/2016	Morero et al.	N/A	N/A
2017/0079680	12/2016	Bowman	N/A	N/A
2017/0079766	12/2016	Wang et al.	N/A	N/A
2017/0079767	12/2016	Leon-Yip	N/A	N/A
2017/0079812	12/2016	Lam et al.	N/A	N/A
2017/0079817	12/2016	Sepetka et al.	N/A	N/A
2017/0079819	12/2016	Pung et al.	N/A	N/A
2017/0079820	12/2016	Lam et al.	N/A	N/A
2017/0086851	12/2016	Wallace et al.	N/A	N/A
2017/0086996	12/2016	Peterson et al.	N/A	N/A
2017/0095259	12/2016	Tompkins et al.	N/A	N/A
2017/0100126	12/2016	Bowman et al.	N/A	N/A
2017/0100141	12/2016	Morero et al.	N/A	N/A
2017/0100143	12/2016	Granfield	N/A	N/A
2017/0100183	12/2016	Iaizzo et al.	N/A	N/A
2017/0113023	12/2016	Steingisser et al.	N/A	N/A
2017/0147765	12/2016	Mehta	N/A	N/A
2017/0151032	12/2016	Loisel	N/A	N/A
2017/0165062	12/2016	Rothstein	N/A	N/A
2017/0165065	12/2016	Rothstein et al.	N/A	N/A
2017/0165454	12/2016	Tuohy et al.	N/A	N/A
2017/0172581	12/2016	Bose et al.	N/A	N/A

2017/0172766	12/2016	Vong et al.	N/A	N/A
2017/0172772	12/2016	Khenansho	N/A	N/A
2017/0189033	12/2016	Sepetka et al.	N/A	N/A
2017/0189035	12/2016	Porter	N/A	N/A
2017/0215902	12/2016	Leynov et al.	N/A	N/A
2017/0216484	12/2016	Cruise et al.	N/A	N/A
2017/0224350	12/2016	Shimizu et al.	N/A	N/A
2017/0224355	12/2016	Bowman et al.	N/A	N/A
2017/0224467	12/2016	Piccagli et al.	N/A	N/A
2017/0224511	12/2016	Dwork et al.	N/A	N/A
2017/0224953	12/2016	Tran et al.	N/A	N/A
2017/0231749	12/2016	Perkins et al.	N/A	N/A
2017/0252064	12/2016	Staunton	N/A	N/A
2017/0265983	12/2016	Lam et al.	N/A	N/A
2017/0281192	12/2016	Tieu et al.	N/A	N/A
2017/0281331	12/2016	Perkins et al.	N/A	N/A
2017/0281344	12/2016	Costello	N/A	N/A
2017/0281909	12/2016	Northrop et al.	N/A	N/A
2017/0281912	12/2016	Melder et al.	N/A	N/A
2017/0290593	12/2016	Cruise et al.	N/A	N/A
2017/0290654	12/2016	Sethna	N/A	N/A
2017/0296324	12/2016	Argentina	N/A	N/A
2017/0296325	12/2016	Marrocco et al.	N/A	N/A
2017/0303939	12/2016	Greenhalgh et al.	N/A	N/A
2017/0303942	12/2016	Greenhalgh et al.	N/A	N/A
2017/0303947	12/2016	Greenhalgh et al.	N/A	N/A
2017/0303948	12/2016	Wallace et al.	N/A	N/A
2017/0304041	12/2016	Argentina	N/A	N/A
2017/0304092	12/2016	Hong et al.	N/A	N/A
2017/0304097	12/2016	Corwin et al.	N/A	N/A
2017/0304595	12/2016	Nagasrinivasa et al.	N/A	N/A
2017/0312109	12/2016	Le	N/A	N/A
2017/0312484	12/2016	Shipley et al.	N/A	N/A
2017/0316561	12/2016	Helm et al.	N/A	N/A
2017/0319826	12/2016	Bowman et al.	N/A	N/A
2017/0333228	12/2016	Orth et al.	N/A	N/A
2017/0333236	12/2016	Greenan	N/A	N/A
2017/0333678	12/2016	Bowman et al.	N/A	N/A
2017/0340383	12/2016	Bloom et al.	N/A	N/A
2017/0348014	12/2016	Wallace et al.	N/A	N/A
2017/0348514	12/2016	Guyon et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
0 282 175	12/1987	EP	N/A
H09-313617	12/1996	JP	N/A
2016-517751	12/2015	JP	N/A
2016-129575	12/2015	JP	N/A

OTHER PUBLICATIONS

Text of First Office Action and Search Report issued in Chinese Patent Application No.

201910891829.8, Search Report dated Jul. 24, 2023. cited by applicant

Partial European Search Report issued in corresponding European Patent Application No. 19 19 8448 mailed Feb. 5, 2020. cited by applicant

Translation of Japanese Office Action in corresponding JP Appln. No. 2023-193007, dated Aug. 27, 2024, and submitted herewith. cited by applicant

Machine Translation of Japanese Office Action date drafted Aug. 4, 2023, in corresponding JP Appln. No. 2019-170161, and submitted herewith. cited by applicant

Primary Examiner: Preston; Rebecca S

Attorney, Agent or Firm: TROUTMAN PEPPER LOCKE LLP

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS (1) This application is a divisional of U.S. patent application Ser. No. 16/577,567 filed Sep. 20, 2019, which claims the benefit of U.S. Provisional Application No. 62/734,128 filed on Sep. 20, 2018, which prior applications are hereby incorporated by reference in their entirety herein into this application as if set forth in full.

FIELD OF INVENTION

(1) The present invention generally relates to implantable stent medical devices, methods for manufacturing the same, and more particularly, to novel stent structures.

BACKGROUND

(2) Medical stents are used for supporting, maintaining, or repairing a lumen, passageway or opening in a living body. Stent design is unique to location and objective of the treatment as the stent must be flexible enough in a collapsed state to navigate body lumen to arrive at a treatment site, structurally robust enough in an implanted state to provide the required structural support to repair the treatment site, and flexibly expandable to have high conformity in treatment sites having tapered, bent, or other non-linear or non-tubular shapes. Flexibility, structural integrity, and conformability are often competing design goals that will vary depending on the location of the treatment site, goal of the treatment, and geometry of the treatment site.

(3) Wire, or braided stents, are typically braided from flexible wires to form a tube of wires that wrap helically around a center axis of the stent, with roughly half of the wires wrapping clockwise, and the other half wrapping counterclockwise such that wires extending in opposite direction wrap over and under each other diagonally in an alternating fashion. Wire stents can be very flexible, can achieve high conformity within a body lumen containing a bend, and can resist kinking; however, the wire stents typically lack structural integrity to apply outward force radially against a lumen wall that is required in some treatments.

(4) A general strategy for stent design when structural integrity is desired involves laser cutting patterns from a length of elastic tubing, typically made of a memory shape metal such as Nitinol or a Nitinol alloy. In general, material is removed from the tubing to form a cell pattern. Generally speaking, enough material must remain so that the overall structural integrity of the laser cut stent is sufficient to apply the required outward force against a lumen wall once implanted. Material is strategically removed to increase the flexibility of the stent for delivery to a treatment site and conformity to lumen walls in treatment sites including a bend or other non-uniform wall structure.

In many stent designs, patterns are cut to form rings that are substantially circumferential connected longitudinally by bridge struts. In such designs, bridge struts are added to achieve greater structural integrity and taken away to achieve greater flexibility.

(5) Attempts have been made to design a stent having greater flexibility and kink resistance compared to stents cut from elastic tubing and greater structural integrity compared to wire stents. One such strategy involves cutting elastic tubing to form a single helical structure that wraps circumferentially around the body of the stent such that adjacent windings of the helix are longitudinally interconnected with bridge struts (e.g. U.S. Pat. No. 5,925,061). Another strategy involves cutting a sheet of material to form a lattice strand that can be wrapped as a single helix about a mandrel and adjacent windings are subsequently interconnected (e.g. U.S. Pat. No. 5,370,683). Although such designs typically can achieve greater flexibility compared to a laser cut tubular stent utilizing circumferential rings, it is at the cost of structural integrity; and although such designs can achieve greater structural integrity compared to wire stents, they cannot achieve the conformability and kink resistance of most wire stents.

(6) There therefore exists a need for alternative stent designs for achieving flexibility, structural integrity, and conformability to meet the needs of a variety of treatment goals at a variety of treatment sites having a variety of anatomical geometries.

SUMMARY

(7) Disclosed herein are various exemplary stents of the present invention that can address the above needs. The stents generally can include a tubular structure having circumferentially positioned undulating wires that extend over a majority of a length of the stent such that the undulations oscillate circumferentially, and the undulations of the wires collectively define a circumference of the stent. The undulations can wrap over and under adjacent undulations to form an interwoven structure. Additionally, or alternatively, adjacent wires can be joined.

(8) An example stent can include a stent length measured from a first open end to a second open end, two or more wires each having a three-dimensional oscillating portion that extends over most of the stent length and is movable independent of the oscillating portion of every other of the one or more wires. The oscillating portion for each wire can have an oscillating portion length measured parallel to a z-axis, a curvature extending circumferentially through an arc of less than 360° about the z-axis at a constant radius from the z-axis, and a waveform that oscillates over the length of the oscillating portion through the arc. The oscillating portion of each of the one or more wires can be movable independent of every other of the one or more wires.

(9) Another example stent having a circumference and a length can include two or more wires, each wire having a three-dimensional waveform that oscillates circumferentially within an arc about a z-axis parallel to the stent length, such that each waveform extends parallel to the z-axis through a majority of the stent length, maintaining a substantially constant radial distance from the z-axis. The wires of the stent can be positioned circumferentially adjacent each other about the circumference of the stent to define the circumference of the stent. Each wire can be movable along a majority of the length of the stent independently of every other wire in the stent.

(10) Another example stent having a tubular structure with a circumference and a length can include a plurality of wires positioned around the circumference of the stent. Each wire can be independently formed, can undulate circumferentially to form a wave pattern that extends over a majority of the length of the stent, can pass under and over an adjacent wire in a repeated fashion while maintaining an adjacent position to the adjacent wire over the majority of the length of the stent, and can intertwine circumferentially with other wires to form the tubular stent.

(11) Another example stent having tubular structure can include circumferentially positioned undulating wires that extend over a majority of a length of the stent. The wires can each have undulations that oscillate circumferentially. The undulations of each wire can recess circumferentially within undulations of an adjacent wire such that the circumferential positioning of the undulating wires can define a circumference of the stent, and the circumferential positioning

of the undulating wires can solely define the circumference of the stent absent any additional structures to define the circumference of the stent.

(12) In any of the example stents, each wire of the stent can be independently formed from every other wire of the stent. Each wire of the stent can be joined at one or more locations to a circumferentially adjacent wire. The stent can include a first joint affixing a first wire to a second wire near the first open end. The first joint can be the only affixed joint between the first wire and the second wire. Additionally, or alternatively, to affixing adjacent wires, the first wire can cross under and cross over the second wire within one period of oscillation of the waveform of the first wire.

(13) In any of the example stents, the stent can include a first end structure positioned adjacent the first open end, extending between the first open end and the oscillating portion of the stent, and the stent can include a second end structure positioned adjacent the second open end, extending between the second open end and the oscillating portion. One or both of the first and second end structures can have an atraumatic shape.

(14) In any of the example stents, a wire of the stent can have a width that varies along the length of the stent.

(15) In any of the example stents, one or more of the wires can include a memory shape material. At least one wire can have a pre-determined three-dimensional shape curved along an arc, the three-dimensional shape having a wave pattern that undulates within the arc.

(16) An example method for manufacturing a stent including any of the example stents described herein can include the steps of providing an elastic tubing, cutting the tubing to form a plurality of substantially similar wave patterns, separating each of the plurality of wave patterns from the tubing, positioning each wave pattern to extend across a majority of the length of the stent, and forming a majority of a tubular stent body from the plurality of wave patterns. Each wave pattern can have an amplitude extending circumferentially through an arc within a circumference of the tubing from which it is cut, an axis extending along at least a portion of a length of the tubing over which the wave pattern repeats, and a curved inner surface being the cut portion of the luminal surface of the tubing.

(17) Another example method for manufacturing a stent including any of the example stents described herein can include the steps of providing an elastic tubing having a circumference and a length, cutting individual wires from the tubing such that each wire has a wave pattern oscillating peak-to-peak across a portion of the circumference, and weaving the wires to form a tube shape.

(18) Any of the example methods can include any combination of the steps of cutting individual wires from the provided tubing such that each wire has a wave pattern that oscillates peak-to-peak across a portion of the circumference, separating the cut wires from the tubing such that the wires are disconnected from each other, joining a first wire to a second wire at one or more locations, joining a first wire to a second wire near an end of the stent body, and/or intertwining each wire with a clockwise adjacent wire and a counterclockwise adjacent wire.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) The above and further aspects of this invention are further discussed with reference to the following description in conjunction with the accompanying drawings, in which like numerals indicate like structural elements and features in various figures. The drawings are not necessarily to scale, emphasis instead being placed upon illustrating principles of the invention. The figures depict one or more implementations of the inventive devices, by way of example only, not by way of limitation.

(2) FIG. 1 is a three-dimensional perspective view of a stent according to the present invention;

- (3) FIG. 2A is a side view of a stent in an expanded state according to the present invention;
- (4) FIG. 2B is a side view of the stent of FIG. 2A in a collapsed state according to the present invention;
- (5) FIG. 3A is a two-dimensional depiction of a wire of a stent according to the present invention;
- (6) FIG. 3B is a three-dimensional depiction of the wire of FIG. 3A according to the present invention;
- (7) FIG. 3C is a schematic of a coordinate system for describing the three-dimension shape of a wire of a stent such as the wire depicted in FIG. 3B;
- (8) FIGS. 4 to 9 are two-dimensional depictions of wires of a stent illustrating example placements of wires around a circumference of the stent according to the present invention;
- (9) FIGS. 10A to 10E illustrate example waveform patterns or undulating patterns for a wire of a stent according to the present invention;
- (10) FIG. 11 illustrates an example wire weave pattern of a stent according to the present invention; and
- (11) FIGS. 12A to 12D illustrate example wire segments having a variable width according to the present invention.

DETAILED DESCRIPTION

- (12) Various exemplary stents are described herein that can address the above needs. In general, a stent can have a generally tubular structure with circumferentially positioned undulating wires extending over a majority of a length of the stent. Undulations of each wire can oscillate circumferentially, and the undulations of a wire can recess within undulations of adjacent wires, such that the recession of each wire into each other defines a circumference of the stent. Adjacent wires can be joined at few locations, such as at the ends, or not at all, such that individual wires are movable independent from every other wire. Additionally, or alternatively, the undulations can wrap over and under adjacent undulations to form an interwoven structure.
- (13) Generally, example stents described herein can be cut from a metal tube and can be prepared by cutting the tube into separate wires that retain a helical curvature from the tube wall from which they are cut. Wires can be cut from the tube to be substantially independent from one another, and these wires can be braided, woven, or otherwise intertwined to form a tubular shape. In some applications it may be desirable to utilize between eight and sixteen laser cut wires to form a stent with desired flexibility, structural integrity, and conformability. Wires in some example stents can move independently of each other to some extent; for example, the wires of an example stent can be movable like how wires in known braided or woven structures are generally movable independent of each other. Additionally, or alternatively, wires in some example stents can be welded or otherwise joined to each other at one or more locations along a length of each of the wires. Joined wires can form an interlocking structure and can increase structural integrity of the stent.
- (14) Because wires of some example stents can be made substantially movable to each other, some example stents can have improved flexibility and kink resistance compared to known laser cut tube designs and can achieve flexibility and kink resistance like known wire braid stent designs. Because the wires of some example stents can be cut from a metal tube, the wires of an example stent can provide greater radial force compared to wires of known wire braid stent designs, the wires of the stent can be designed to have an atraumatic end structure (which is typically not achievable by using cut wires in known wire braid stent designs), and the stent can have wires that vary in thickness and shape along the length of the stent (which is generally not possible in known wire braid stent designs that utilize constant diameter wires). A potential application of some example stents can be supporting embolic coils within an aneurysm at a treatment site that requires navigation of torturous anatomy to reach.
- (15) FIG. 1 is a three-dimensional perspective view of a stent **100** having four wires **200a**, **200b**, **200c**, **200d**. As will be appreciated and understood a stent **100** can include as few or as many wires

as required to achieve a desired flexibility, structural integrity, and conformability. A stent having a greater number of wires may be required, for example, when treating a body lumen having a larger diameter. A stent can also be designed to have a space between wires through which a microcatheter for delivering an embolic implant can passthrough; in which case, it may be desirable to create pores between wires that are small enough to provide enough structural support but large enough so a coiling microcatheter can fit through a pore. In some applications it may be desirable to utilize between eight and sixteen laser cut wires.

(16) FIG. 2A is a side view of a stent **100** in an expanded state like that of FIG. 1 having four wires **200a**, **200b**, **200c**, **200d**. The stent **100** can have a substantially tubular body shape with a first open end **112**, a second open end **114**, and a length **110** extending from the first open end **112** to the second open end **114** in a longitudinal direction **10**. The stent **100** can be designed to have a length to meet the needs of the treatment, for example, the length **110** can be sized larger than a neck of an aneurysm such that aneurysms having a larger neck opening could be treated with a longer stent. The tubular body shape of the stent **100** can have a substantially uniform circumference **20** along its length **110** in an expanded state. Alternatively, (not shown) a stent can have a tubular body shape having a large circumference at a first open end that tapers to a smaller circumference at a second open end. Such a tapered design can be advantageous for treating tapered body lumens, for example.

(17) FIG. 2B is a side view of the stent of FIG. 2A in a collapsed state. In the collapsed state, the stent **100** can be sized to be delivered through a microcatheter to a treatment site within a vasculature. Because the stent **100** can be made of a small number of wires, and each wire **200a**, **200b**, **200c**, **200d** can be stretched in the longitudinal direction **10** to occupy a small cross-sectional profile, an advantage of the stent **100** is that it can be collapsed to a thinner dimension than a laser cut tubular type stent. Laser cut tubular type stents typically have little ability to stretch lengthwise. The thinner collapsed dimension, in some applications, can allow the stent **100** to be delivered to a treatment site through a smaller catheter, therefore reaching treatment sites that may be challenging or impossible to reach with other stent designs.

(18) A wire **200** is illustrated in FIG. 3A in two dimensions and in FIG. 3B in three dimensions. The wire **200** has a three-dimensional shape as illustrated in FIG. 3B; the two-dimensional illustration of FIG. 3A is provided to aid visualization and discussion of the wire **200**. Referring collectively to FIGS. 3A and 3B, a wire **200** can have an oscillating portion **210** having an oscillating portion length **211** measured parallel to a z-axis **12**. The oscillating portion **210** can have a waveform that repeats over the length **211** of the oscillating portion **210**, repeating with a period of oscillation **212**. The waveform can be sinusoidal having a series of peaks **202**, troughs **204**, and intermediate segments **206** extending between the peaks **202** and troughs **204**. The oscillating portion **210** can extend over a majority of a length of the stent, and the wire **200** can also have end structures **220** at the ends of each wire **200**. Each end structure **220** can have an atraumatic shape.

(19) FIG. 3C is a schematic of a cylindrical coordinate system for describing the three-dimension shape of a wire **200** of a stent **100** such as the wire depicted in FIG. 3B. In the cylindrical coordinate system, the z-axis **12** is understood to be perpendicular to the page, positioned at the center of the circle illustrated in FIG. 3C. In general, a position of a point in the cylindrical coordinate system can be defined by the coordinates r , θ , and z , where the r coordinate defines a distance from the z-axis, the θ coordinate defines an angle from the r-axis, and the z coordinate defines a linear position along the z-axis. A tube would therefore include points where r is equal to a constant, R over given length in the z-axis, and an arc in said tube would be confined to an angle, or range of values for θ , the angle being less than 360° . The example wire **200** illustrated in FIG. 3B can therefore be described as having a curvature extending circumferentially through an arc **216** of approximately 180° that maintains a substantially constant radius **214** from the z-axis. The waveform can be described as oscillating circumferentially, confined within the arc of the curvature, extending in the z-direction over the length **211** of the oscillating portion **210**. Referring

to FIG. 3A, an amplitude of the waveform can be described as the distance between the peaks **202** and the troughs **204**. Referring to FIGS. 3B and 3C, the amplitude of the waveform can therefore be expressed as a function of the arc of the curvature **216** and the radius **214**. As will be appreciated and understood, the curvature could be wider or narrower to achieve desired properties of the stent. For example, a waveform having a larger amplitude can result in an overall stent design having greater flexibility while a waveform having a smaller amplitude can result in an overall stent design that is easier to deliver through a microcatheter.

(20) Referring to FIGS. 3B and 3C, the wire can be formed by cutting the wire from a portion of elastic tubing. The tubing can have a radius **214**, and the tubing can be cut so that the resulting wire **200** has an oscillating portion that maintains the radius **214** of the tubing. The wire **200** can be cut from an arc defined by at least a portion of the circumference of the tubing so that the resulting wire **200** oscillates within the arc **216**, and the resulting wire can have a wave pattern that oscillates peak-to-peak across the cut portion of the circumference of the tube.

(21) The tubing can have a lumen with an inner luminal surface. The wire **200** can be cut from the tubing to have an inner surface that is cut from the luminal surface of the tubing. The wire **200** can be cut from the tubing such that a majority of the oscillating portion **210** is movable independent of oscillating portions **210** of other wires. The wire **200**, once cut, can be separated from the tubing to form an independently formed wire **200**.

(22) FIGS. 4 to 9 are two-dimensional depictions of wires of a stent illustrating example placements of wires around a circumference of the stent. The illustrations are provided in two dimensions for discussion and visualization. Referring collectively to FIGS. 4 to 8, the illustrations depict the placement of four wires **200a**, **200b**, **200c**, **200d** circumferentially to form a stent. The bottom wire **200a** is redrawn as a dashed wire **200a'** above the top wire **200d**, and the top wire **200d** is redrawn as a dashed wire **200d'** below the bottom wire **200a** to illustrate the placement and connection of the wires shown as the top and bottom wires **200d**, **200a** in a three-dimensional stent.

(23) The wires **200a**, **200b**, **200c**, **200d** can be cut from tubing, and each wire can be positioned to define a circumference of a stent. Wires can be positioned such that each oscillating portion **210** extends across a length of the stent. Inner curved surface of each oscillating portion **210** of each wire **200a**, **200b**, **200c**, **200d** can be aligned to collectively form the circumference of the stent. Wires **200a**, **200b**, **200c**, **200d** can be joined and/or woven to form a tube shape.

(24) FIG. 4 is a two-dimensional illustration of four wires placed to define a circumference of a stent like the stents depicted in FIGS. 1 and 2A. Each wire can be recessed circumferentially within undulations of circumferentially adjacent wires such that the circumferential positioning of the undulating wires defines a circumference of the stent. Each wire can be independently formed and at least to some extent, movable compared to every other wire.

(25) FIG. 5 is a two-dimensional illustration of four wires placed to define a circumference of a stent like the pattern shown in FIG. 4. Each wire can be connected to each adjacent wire by a single joint **230a**, **230b**, **230c**, **230d**, **230d'**. As shown, a first joint **230c** can join a first wire **200c** to a second wire **200d** adjacent to the first wire **200c**, and the first joint **230c** can be the only affixed joint between the first wire **200c** and the second wire **200d**. The first wire **200c** can also be joined to a third wire **200b** with a second joint **230b**. As shown, each wire **200a**, **200b**, **200c**, **200d** can be joined to its two adjacent neighbors by a single joint for each neighbor. Minimal connections **230a**, **230b**, **230c**, **230d** can allow the wires to move independently of each other over a majority of the length of the stent.

(26) As will be appreciated and understood, each joint can be formed by any conventional means such as welding, brazing, soldering, gluing, tying, etc. Alternatively, or additionally, a stent can be cut from a single piece of tubing such that the joints **230a**, **230b**, **230c**, **230d** are uncut portions of the tubing. In one example, a wire **200a**, **200b**, **200c**, **200d** joined to a neighboring wire by an uncut tubing portion would not be completely separated from the neighbor during manufacturing. However, the uncut portion can be placed at a joint location **230a**, **230b**, **230c**, **230d** like those

shown in FIGS. 5 and 6 and described herein to allow the wire **200a**, **200b**, **200c**, **200d** to be movable independently of the neighbor wire and other wires over a majority of the length of the stent.

(27) FIG. 6 is a two-dimensional illustration of four wires placed to define a circumference of a stent having one joint **230a**, **230b**, **230c**, **230d**, **230d'** connecting each pair of adjacent wires. As will be appreciated and understood, the joints **230a**, **230b**, **230c**, **230d**, **230d'** can be positioned at any number of locations. FIG. 6 illustrates an alternative configuration of the four wires **200a**, **200b**, **200c**, **200d**, illustrated in FIG. 5 and the four joints **230a**, **230b**, **230c**, **230d**. As will be appreciated and understood, any number of joints can be used to connect any number of wires to achieve a desired flexibility, structural integrity, and conformability for the stent. Minimal connections **230a**, **230b**, **230c**, **230d** can allow the wires **200a**, **200b**, **200c**, **200d** to move independently of each other over a majority of the length of the stent.

(28) FIG. 7 is a two-dimensional illustration of four wires placed to define a circumference of a stent such that the wires are interwoven to define a circumference of the stent. Each wire can cross over and under each neighboring wire. As illustrated, a first wire **200a** can cross under **244** a first neighboring wire **200d'** and over **246** the same wire **200d'** within one period of oscillation of the first wire **200a**. The first wire **200a** can cross under **242** a second neighboring wire **200b** and over **248** the second neighboring wire **200b** within the same period of oscillation of the first wire **200a**. The interwoven structure of the wires **200a**, **200b**, **200c**, **200d** can be sufficient to maintain the structural integrity of the stent absent any joints to affix wires. The wires can therefore be independently formed and independently movable. As will be appreciated and understood wires **200a**, **200b**, **200c**, **200d** can be intertwined with other wave patterns in any number of patterns.

(29) FIG. 8 is a two-dimensional illustration of four wires placed to define a circumference of a stent such that the wires are interwoven to define a circumference of the stent like the one as illustrated in FIG. 7. A stent can have both interwoven wires **200a**, **200b**, **200c**, **200d**, and joints **230a**, **230b**, **230c**, **230d** to join neighboring wires. As illustrated, a joint **230b** can be placed to connect a first wire **200c** and a second wire **200b** at a cross-over point. The joints **230a**, **230b**, **230c**, **230d** can be placed near an end of the wire, and only one joint can be used to connect each wire to each adjacent wire. As will be appreciated and understood, any number of joints can be used to connect wires and various locations along the length of the stent. Minimal connections **230a**, **230b**, **230c**, **230d** can allow the wires **200a**, **200b**, **200c**, **200d** to move independently of each other over a majority of the length of the stent.

(30) FIG. 9 is a two-dimensional illustration of four wire segments **200a**, **200b**, **200c**, **200d** joined by three bends **230**, wherein the wire segments are placed to define a circumference of a stent and each wire segment **200a**, **200b**, **200c**, **200d** is joined to a neighboring segment by a bend **230**. As illustrated, each bend **230** can be positioned at either a first or second open end of the stent to connect a first wire **200a** and a second wire **200b**. Connected thusly, the wire segments **200a**, **200b**, **200c**, **200d** can be joined to form a contiguous wire characterized by longitudinal undulating segments **200a**, **200b**, **200c**, **200d** that are joined alternatively at bends **230** positioned at each end of the stent. The contiguous wire can include atraumatic ends **220** positioned at an end of a first wire segment **200a** and an end of a last wire segment **200d** in the chain of segments. Alternatively (not shown), the stent can be constructed with multiple independent wires consisting of wire segments joined at bends. Wires and wire segments can be otherwise joined or interwoven as described in other examples presented herein or as known in the art.

(31) FIGS. 10A to 10E illustrate example waveform patterns or undulating patterns for a wire of a stent that can be used in addition to or in place of other waveforms depicted and described herein. As will be appreciated and understood, and number of waveform patterns can be utilized to achieve a desired flexibility, structural integrity, and conformability for the stent, including those not shown, and as known in the art.

(32) FIG. 11 illustrates an example wire weave pattern that could be utilized to form a stent in

addition to or in place of other weave patterns depicted and described herein.

(33) FIGS. 12A to 12D illustrate example wire segments having a variable width that could be utilized to form a stent in addition to or in place of other wire features depicted and described herein. As illustrated in FIG. 12A, a wire can have an undulating pattern having thicker segments near each end of the wire and thinner segments positioned in the middle of the wire. Thinner central segments can allow the stent to pass more easily through a microcatheter while thicker end segments can improve structural integrity at the stent ends for anchoring within a body lumen. As illustrated in FIG. 12B, a wire can have thin segments near one end and thicker segments at the other end. As illustrated, the segments can become increasingly thicker or thinner from one end of the wire to the other. Stents formed from wire segments with progressively changing segment thickness can be formed to have a tapered structure that can be advantageous for achieving conformity to the walls of a body lumen when implanted in a body lumen that is tapered.

(34) The descriptions contained herein are examples of embodiments of the invention and are not intended in any way to limit the scope of the invention. As described herein, the invention contemplates many variations and modifications of the stent, including alternative shapes for oscillating portions of wires, alternate shapes for atraumatic end segments of wires, alternative means of joining or connecting wires, alternative patterns for interlacing wires to form the stent, forming stents with any number of wires, or utilizing any of numerous materials or manufacturing means for the stent, for example. These modifications would be apparent to those having ordinary skill in the art to which this invention relates and are intended to be within the scope of the claims which follow.

Claims

1. A stent comprising: a stent length measured from a first open end to a second open end; two or more wires each comprising a three-dimensional oscillating portion, the oscillating portion comprising: an oscillating portion length measured parallel to a z-axis; a curvature extending circumferentially through an arc of less than 360° about the z-axis, extending the length of the oscillating portion, and maintaining a substantially constant radius from the z-axis over the oscillating portion length; and a waveform oscillating circumferentially, confined within the arc of the curvature, and extending over the oscillating portion length; and a first joint affixing a first wire of the two or more wires to a second wire of the two or more wires approximate the first open end, the first joint being the only affixed joint between the first wire and the second wire, wherein the oscillating portion length extends a majority of the stent length; wherein the oscillating portion of each of the two or more wires is movable independent of the oscillating portion of every other of the two or more wires; wherein the stent is movable from a collapsed configuration that is stretched lengthwise and has a smaller diameter to an expanded configuration that is compressed lengthwise and has a larger diameter; and wherein the waveform of each of the two or more wires comprises undulations, the undulations of each wire recessing circumferentially within undulations of at least one of a circumferentially adjacent wire such that the circumferential positioning of the undulating wires defines a circumference of the stent.
2. The stent of claim 1, wherein each of the two or more wires crosses under and crosses over the at least one circumferentially adjacent wire at least once within one period of undulation of the waveform of the first wire.
3. The stent of claim 1, wherein each of the two or more wires is independently formed from every other of the two or more wires.
4. The stent of claim 1, further comprising: a first end structure positioned adjacent the first open end, extending between the first open end and the oscillating portion of each of the two or more wires; and a second end structure positioned adjacent the second open end, extending between the second open end and the oscillating portion of each of the two or more wires.

5. The stent of claim 4, wherein the first end structures and the second end structures each comprises an atraumatic shape.
 6. The stent of claim 1, wherein a wire of the two or more wires has a width that varies along the length of the stent.
 7. The stent of claim 1, wherein the stent comprises three or more wires.
 8. A stent comprising a tubular structure comprising: a plurality of wires each comprising an undulating wire segment and an atraumatic wire segment, wherein the plurality of wires are positioned circumferentially to form the tubular structure, wherein the undulating wire segments extend over a majority of a length of the stent, the undulating wire segments each comprising undulations oscillating circumferentially, the undulations of each of the undulating wire segments recessing circumferentially within undulations of at least one of the circumferentially adjacent undulating wire segments such that the circumferential positioning of the undulating wire segments defines a circumference of the stent, wherein the atraumatic wire segments are each positioned approximate a first end or a second end of the stent, and wherein each wire of the plurality of wires is joined to a first circumferentially adjacent wire at only one joint, and wherein each wire of the plurality of wires is joined to a second, oppositely circumferentially adjacent wire of the plurality of wires at only one joint.
 9. The stent of claim 8, wherein each of the plurality of wires comprises two of the atraumatic wire segments, one atraumatic wire segment at each end of the wire, and one of the undulating wire segments extending between the two atraumatic wire segments.
 10. The stent of claim 8, wherein each of the plurality of wires comprises a width that varies along a length of the respective wire.
 11. The stent of claim 8, wherein a first wire of the plurality of wires crosses under and crosses over the at least one circumferentially adjacent wire of the plurality of wires at least once within one period of undulation of the waveform of the first wire.
-