

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent
Kind Code
Date of Patent
Inventor(s)

12397851
B2
August 26, 2025
Doerner; Christian

Method for steering a vehicle, actuator for rear axle steering system of a vehicle and rear axle steering system having such an actuator

Abstract

The disclosure relates to a method for steering a vehicle via a rear axle steering system that includes an actuator having a steering linkage at least indirectly operable by a threaded drive and longitudinally displaceable within a chassis-fixed housing. The actuator includes a rotor position sensor for detecting a rotor position of a rotor of an electric motor designed for actuating the threaded drive and a linear sensor for detecting an axial position of a target arranged on the steering linkage. The two sensors are connected to a control and analysis unit configured to carry out a comparison between the rotor position and the axial position of the target when there is a defined zero point of an axial position of the steering linkage relative to the housing and, in consideration of a thermal expansion of at least the steering linkage, operating the actuator to adjust the steering angle.

Inventors:	Doerner; Christian (Sugenheim, DE)
Applicant:	Schaeffler Technologies AG & Co. KG (Herzogenaurach, DE)
Family ID:	1000008777429
Assignee:	Schaeffler Technologies AG & Co. KG (Herzogenaurach, DE)
Appl. No.:	17/802201
Filed (or PCT Filed):	February 08, 2021
PCT No.:	PCT/DE2021/100116
PCT Pub. No.:	WO2021/175361
PCT Pub. Date:	September 10, 2021

Prior Publication Data

Document Identifier

US 20230339536 A1

Publication Date

Oct. 26, 2023

Foreign Application Priority Data

DE

10 2020 105 797.0

Mar. 04, 2020

Publication Classification

Int. Cl.: B62D5/04 (20060101); B62D7/15 (20060101)

U.S. Cl.:

CPC B62D5/0481 (20130101); B62D5/0496 (20130101); B62D7/15 (20130101);

Field of Classification Search

CPC: B62D (5/0481); B62D (5/0496)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5086861	12/1991	Peterson	180/445	B62D 7/1581
6298940	12/2000	Bohner	N/A	N/A
8244433	12/2011	Mitsuhara	701/41	B62D 15/0215
11267509	12/2021	Buering	N/A	B62D 15/0225
2010/0030427	12/2009	Mitsuhara et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
1236717	12/1998	CN	N/A
102667099	12/2011	CN	N/A
105416389	12/2015	CN	N/A
107215385	12/2016	CN	N/A
108367771	12/2017	CN	N/A
109311506	12/2018	CN	N/A
110550091	12/2018	CN	N/A
110582441	12/2018	CN	N/A
10164580	12/2002	DE	N/A
10329293	12/2004	DE	N/A
102004042243	12/2007	DE	N/A
102011085607	12/2011	DE	N/A
WO-2012059511	12/2011	WO	B60G 7/006
2015114256	12/2014	WO	N/A
2018206295	12/2017	WO	N/A

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

(1) This application is the U.S. National Phase of PCT Application No. PCT/DE2021/100116 filed on Feb. 8, 2021, which claims priority to DE 10 2020 105 797.0 filed on Mar. 4, 2020, the entire disclosures of which are incorporated by reference herein.

TECHNICAL FIELD

(2) This disclosure relates to a method for steering a vehicle by means of a rear axle steering system, wherein the rear axle steering system comprises an actuator with a steering linkage which is at least indirectly operable by a threaded drive and which is longitudinally displaceable within a chassis-fixed housing. The steering linkage can be used to adjust a steering angle of wheels at least indirectly connected thereto. The disclosure further relates to a rear axle steering system having such an actuator and to a vehicle comprising such a rear axle steering system or such an actuator.

BACKGROUND

(3) WO 2018/206 295 A1 discloses a steering device for a vehicle with a steering rod and at least one drive unit, wherein the steering rod is displaceable in its longitudinal extension by means of the drive unit. Furthermore, at least one first sensor device is provided for determining a sliding position of the steering rod. Viewed in the longitudinal direction, the steering rod has at least one change in its cross section, in particular its diameter, wherein the first sensor device is designed to detect this change.

SUMMARY

(4) The object of the present disclosure is to further develop a method for steering a vehicle and an actuator for a rear axle steering system of a vehicle.

(5) This object is achieved by a method and an actuator described herein.

(6) In a method according to the disclosure for steering a vehicle by means of a rear axle steering system, in which the rear axle steering system comprises an actuator having a steering linkage which is at least indirectly operable by a threaded drive and which is longitudinally displaceable within a chassis-fixed housing, wherein a steering angle of wheels that are at least indirectly connected to the steering linkage is adjusted by said steering linkage, the actuator comprising a rotor position sensor for detecting a current rotor position of a rotor of an electric motor designed for actuating the threaded drive and a linear sensor for detecting a current axial position of a target arranged on the steering linkage, at least the two sensors each being connected to a control and analysis unit, the control and analysis unit always carries out a comparison between the current rotor position of the rotor and the current axial position of the target when there is a defined zero point of an axial position of the steering linkage relative to the housing and, in consideration of a thermal expansion of at least the steering linkage, operates the actuator in order to adjust the steering angle.

(7) The actuator is provided for adjusting a steering angle of vehicle wheels that are operatively connected to the actuator on a rear axle of the vehicle by axially displacing the steering linkage relative to the chassis-fixed housing. This, for example, initiates a cornering of the vehicle. The steering linkage consists of one or more thrust rods which are operatively connected to one another and which can have, at their free ends, a respective fork connection with a fork element, on which, at least indirectly, the respective vehicle wheel is accommodated. The steering linkage can thus be constructed in one or several parts and additionally has a threaded spindle which is connected to it

in one or several parts and is arranged concentrically therewith.

(8) The axially non-displaceable threaded nut is driven at least indirectly by the electric motor, with the threaded nut being operatively connected at least indirectly to the rotatably drivable rotor of the electric motor. The threaded nut is operatively connected to the threaded spindle and thus indirectly to the steering linkage. The threaded spindle, or the steering linkage, is set in a lengthwise displacement or in a longitudinal displacement relative to the housing or the threaded nut by a rotation of the threaded nut. The threaded spindle and the threaded nut thus form a threaded drive, wherein the rotary drive of the threaded nut causes a linear adjusting movement of the steering linkage for adjusting the steering angle of the vehicle wheels. Furthermore, the drive unit can comprise a transmission device which is designed, for example, as a belt transmission or as a planetary transmission and is operatively connected to the threaded nut. The threaded drive is designed in particular as a planetary roller threaded drive, in which a large number of planetary rollers are arranged spatially between the threaded nut and the threaded spindle, which transmit the forces between the threaded nut and the threaded spindle and vice versa and convert a rotational movement of the threaded nut into a longitudinal movement of the threaded spindle.

(9) When the rear axle steering is in operation, it is not the actual steering angle of the vehicle wheels that is detected, but rather the axial position of the steering linkage relative to the housing. This is done using the target in conjunction with the linear sensor. However, the actual length of the steering linkage changes over a temperature curve, so that the actual or current steering angle does not always correspond to the target specification of the analysis and control unit. The housing of the actuator, the chassis of the vehicle, the threaded drive with the threaded spindle and the threaded nut, and other components of the vehicle are also subject to temperature-related deformations.

(10) A material-specific coefficient of thermal expansion is known for each of these components, which can be determined separately and stored in a database of the analysis and control unit. Consequently, the analysis and control unit provides the known coefficients of thermal expansion of the components relevant to the steering of the vehicle, so that a temperature-related deformation behavior of the components can be derived for each current temperature. In addition, constraints within the components can be taken into account, for example due to tension caused by screwing the housing to the chassis of the vehicle.

(11) During assembly of the rear axle steering, a zero point is determined or defined for the rotor position sensor and for the linear sensor. The zero point can be set at any desired point, wherein such a zero point is advantageous in that it is passed through or driven through as often as possible during operation of the rear axle steering. That axial position of the steering linkage in which the vehicle wheels are aligned in the direction of travel, i.e., straight ahead, is particularly suitable as the zero point. In other words, the zero point serves as a reference point in order to take into account a thermal expansion of at least the steering linkage for adjusting the steering angle of the vehicle wheels.

(12) The rotor position sensor is independent of the thermal expansion of the steering linkage and can therefore determine the zero point of the system, regardless of temperature. The rotor position sensor is operatively arranged on the electric motor and is intended to determine an angle of rotation of the rotor of the electric motor. The rotor is arranged, for example, radially inside a stator of the electric motor, which is supplied with electrical energy to rotatably drive the rotor. A torque can be transmitted to the threaded nut by means of the rotor, which at least indirectly axially displaces the threaded spindle. The steering linkage is thus braced on the threaded drive, so that the expansion of the steering linkage on the threaded drive is equal to 0, wherein the steering linkage expands to the left and right when it heats up and thus lengthening it, and shortening it to the left and right when it cools down.

(13) When the rear axle steering system is in operation, whenever the zero point is present, i.e., when the wheels are aligned straight ahead, for example, at least one signal is transmitted from the

rotor position sensor about the current rotor position of the rotor, at least one signal is transmitted from the linear sensor about the current axial position of the steering linkage and at least one signal is transmitted about the current temperature to the analysis and control unit. Other signals can also be received by the analysis and control unit.

(14) The thermal expansion of at least the steering linkage is can be determined by detecting current temperature data by means of at least one temperature sensor. In other words, at least one temperature sensor is provided on the vehicle, which is used to determine the current temperature, based on which the thermal expansion of at least the steering linkage or additional components relevant to the adjustment of the steering angle is determined. Based on this data and the constant comparison of the zero point between the rotor position sensor and the linear sensor, since the dimensions of the steering linkage, the housing, the threaded drive and other components as well as the associated material-dependent thermal expansion coefficients are known, the thermal expansion of the steering linkage can be calculated and taken into account for the operation of the rear axle steering system. In other words, depending on the thermal expansion, an actuation of the threaded drive can be adjusted in such a way that the actual steering angle of the vehicle wheels corresponds to a steering angle target specification of the analysis and control unit.

(15) The respective temperature sensor can be integrated within the analysis and control unit. If, for example, the introduced power losses are determined by the control and analysis unit via a power integral, the control and analysis unit can use this to determine a current temperature, which in turn can be used to determine the thermal expansion of the steering linkage.

(16) Alternatively or additionally, a temperature sensor is arranged on the linear sensor. As a result, the thermal expansion of the steering linkage can be determined comparatively precisely. Furthermore, alternatively or in addition, the respective temperature sensor is an outside temperature sensor. In addition, current temperature data can be used based on thermal information from surrounding actuators, such as a roll stabilizer or an e-axle of the vehicle. Consequently, the control and analysis unit can receive and further process temperature data from temperature sensors already located in the vehicle, as a result of which the rear axle steering system can be produced particularly cost-effectively.

(17) According to one exemplary embodiment, the control and analysis unit carries out a comparison between the current rotor position of the rotor and the current axial position of the target per revolution of an electric motor at least indirectly driving the threaded nut and on the basis of which operates an actuator for adjusting the steering angle. This comparison is carried out in addition to the previously described zero point comparison, wherein the comparison per electric motor revolution takes place over the entire actuating path of the actuator, so that a temperature-dependent compensation of temperature-related differences in component dimensions can be carried out even more precisely by the analysis and control unit.

(18) An actuator according to the disclosure for a rear axle steering system of a vehicle has a steering linkage which is at least indirectly operable by a threaded drive and which is longitudinally displaceable within a chassis-fixed housing. The steering linkage is designed to adjust a steering angle of wheels that are at least indirectly connected thereto. The actuator includes a rotor position sensor for detecting a current rotor position of a rotor of an electric motor designed for actuating the threaded drive and a linear sensor for detecting a current axial position of a target arranged on the steering linkage, at least the two sensors each being connected to a control and analysis unit. The control and analysis unit always carries out a comparison between the current rotor position of the rotor and the current axial position of the target when there is a defined zero point of an axial position of the steering linkage relative to the housing and, in consideration of a thermal expansion of at least the steering linkage, operating the actuator in order to adjust the steering angle.

(19) The housing is connected to the chassis at two, or four or more points. As a result, constraints can arise within the housing when the temperature changes, which can be determined in advance by suitable simulations and are taken into account by the control and analysis unit.

- (20) Such an actuator can be used in a rear axle steering system of a vehicle according to the disclosure. The vehicle can have a plurality of rear axles, with one or more rear axles each having a respective rear axle steering system with a respective actuator. In addition, the vehicle can have at least one actuator according to the disclosure for adjusting a steering angle of the vehicle.
- (21) The above statements relating to the method apply equally to the actuator according to the disclosure and to the rear axle steering system and the vehicle.
-

Description

BRIEF DESCRIPTION OF THE DRAWING

(1) Further measures to improve the disclosure are further described below together with a description of example embodiments using a single FIGURE, whereby identical or similar components are marked with the same reference sign. The only FIGURE shows a longitudinal section through a rear axle steering system according to an example embodiment.

DETAILED DESCRIPTION

(2) The single FIGURE shows a rear axle steering system **12** for a vehicle—not shown here—comprising an actuator **1** with a housing **3** in which a steering linkage **2** is guided longitudinally, i.e., in a displacement direction **13**. The housing **3** is fixed at four fixed points **15** in relation to a chassis of the vehicle—not shown here. The steering linkage **2** is designed in several parts and comprises a threaded spindle **14**, which is part of a threaded drive **4**, wherein the threaded spindle **14** is operatively connected to a threaded nut **7** lying radially outside of it. The threaded nut **7** is supported axially relative to the housing **3** and can be rotatably driven by an electric motor **16**, wherein, depending on the direction of rotation, a rotation of the threaded nut **7** is converted into an axial or longitudinal displacement of the threaded spindle **14** or the steering linkage **2** relative to the housing **3**. By means of the axial displacement of the steering linkage **2**, adjustments can be made in a steering angle of respective vehicle wheels—also not shown here—which are at least indirectly arranged on fork elements **5a**, **5b** of the rear axle steering system **12**.

(3) The actuator **1** also comprises a rotor position sensor **6** for detecting a current rotor position of a rotor of an electric motor **16** that is set up to actuate the threaded drive **4**—not shown here—and a linear sensor **8** for detecting a current axial position of a target **11** arranged on the steering linkage **2**, wherein, in addition to the linear sensor **8**, a temperature sensor **9** for acquiring current temperature data is also arranged on the steering linkage **2**. Alternatively, the temperature sensor **9** can also be arranged on the electric motor **16**. The sensors **6**, **8**, **9** are each connected to a control and analysis unit **10**. In the present case, the target **11** is arranged in an anti-rotation means **17** of the actuator **1**, which prevents the steering linkage **2** from rotating about its own longitudinal axis, wherein the target **11** interacts with the linear sensor **8** to determine the axial position of the steering linkage **2** relative to the housing **3**.

(4) During assembly of the rear axle steering system **12**, a zero point of the rotor position sensor **6** and the linear sensor **8** is defined in advance. In this case, for example, the distances between the fork elements **5a**, **5b** and the housing **3** are averaged out. The zero point is present, for example, when the vehicle wheels are aligned straight ahead, that is to say when the steering linkage **2** is in a specific axial position relative to the housing **3**. This situation occurs comparatively frequently in the general operation of the rear axle steering system **12** and is therefore suitable as a reference point for adjusting a control and regulation of the steering angle adjustment using the analysis and control unit **10**.

(5) Whenever the previously defined zero point of an axial position of the steering linkage **2** relative to the housing **3** is present, a comparison is made between the current rotor position of the rotor of the electric motor **16** and the current axial position of the target **11**, wherein the measurement signals of the temperature sensor **9** are evaluated at the same time and a thermal

expansion of at least the steering linkage **2** can be determined on the basis of coefficients of thermal expansion stored in the analysis and control unit **10**. By determining the thermal expansion of other components relevant to adjusting the steering angle, such as for the threaded spindle **14**, the threaded nut **7**, the housing **3** or the fork elements **5a**, **5b**, the operating adjustment of the actuator **1** can be performed more precisely. Such an adaptation consists essentially in taking into account a temperature-related deformation of the components in such a way that a target specification for a steering angle is adjusted to an actually existing steering angle of the vehicle wheels. In other words, temperature-related differences in component dimensions are compensated for by the control and analysis unit **10**.

(6) The control and analysis unit **10** is also designed to perform a comparison between the current rotor position of the rotor and the current axial position of the target **11** per rotor revolution and uses this to operate an actuator **1** to adjust the steering angle. As a result, temperature-related differences in component dimensions can be compensated for more precisely by the control and analysis unit **10**.

(7) According to the present example embodiment, the zero point of the rotor position sensor **6** and the linear sensor **8** is defined at a temperature of 20° C., for example. In other words, a reference point is determined, namely at which a specific rotor position of the rotor and a specific distance of the target **11** to a bracing point **23** of the steering linkage **2** on the threaded drive **4**—shown here as a middle vertical line—are present. Since the component dimensions of all components of the rear axle steering system **12** and the actuator **1** are known, based on the respective material-specific coefficients of thermal expansion, at a temperature of 20° C. the following distances are known or are defined: a first distance **17** of a first point **22a** of the first fork element **5a** to the bracing point **23** of the steering linkage **2** on the threaded drive **4**; a second distance **18** of a second point **22b** of the second fork element **5b** to the bracing point **23** of the steering linkage **2** on the threaded drive **4**; a third distance **19** of the target **11** to the bracing point **23** of the steering linkage **2** on the threaded drive **4**; a fourth distance **20** of a central axis **24** of the housing **3** to the bracing point **23** of the steering linkage **2** on the threaded drive **4**; and a fifth distance **21** from the central axis **24** of the housing **3** to the target **11**. Other distances can also be defined or determined. The more components are monitored by the control and analysis unit **10**, the more precisely the vehicle can be steered or the actuation of the actuator **1** can be adapted more precisely. The central axis **24** of the housing **3** is arranged centrally between the fixed points **15** of the housing **3** and is shown as a vertical line.

(8) If the temperature drops below 20° C. to 0° C., for example, during operation of the rear axle steering system **12** or the actuator **1**, the steering linkage **2** and the other components of the actuator **1** contract. Since the steering linkage **2** is braced in the threaded drive **4**, the first point **22a** of the first fork element **5a** shifts to the right in the direction of the threaded drive **4**, so that the first distance **17** is reduced. The second point **22b** of the second fork element **5b** as well as the target **11** and the linear sensor **8** are also shifted to the left in the direction of the threaded drive **4**, so that the second or third distance **18**, **19** is also reduced. The linear sensor **8** thus detects a movement to the left, although the first fork element **5a** moves to the right. Due to the smaller distance of the target **11**, the temperature-related displacement of the target **11** in the direction of the threaded drive **4** is smaller than the displacement of the second point **22b** of the second fork element **5b**. Consequently, the displacement of the target **11** compensates for the displacement of the right-hand fork element **5b**. This is taken into account by the control and analysis unit **10**, wherein the control and analysis unit **10** controls the threaded drive **4** based on the thermal expansion of the respective components in such a way that the actual steering angle of the vehicle wheels corresponds to a target specification of the control and analysis unit **10**.

(9) If, during operation of the rear axle steering system **12** or the actuator **1**, a temperature rises above 20° C., for example to 40° C., the steering linkage **2** and the other components of the actuator **1** expand. The first point **22a** of the first fork element **5a** shifts to the left and the second

point **22b** of the second fork element **5b** as well as the target **11** and the linear sensor **8** shift in the opposite direction, to the right, so that the distances **17**, **18**, **19** increase, wherein the differences in length are dependent on the respective component dimensions.

(10) The housing **3** also expands, starting from its center of gravity **24**, and lengthens to the left and to the right. The expansion of the housing **3** depends on how the housing **3** is braced on the chassis of the vehicle or how many fixed points **15** are provided. As a result of the expansion of the housing **3** to the left, the threaded drive **4** fastened to the housing **3** and the linear sensor **8** are shifted to the left even before the thermal expansion of these components **4**, **8** is taken into account. As a result, the first fork element **5a** is also shifted to the left, so that the linear sensor **8** detects a quasi-movement of the steering linkage **2**. The control and analysis unit **10** is designed to determine and take these relationships and length differences into account, with the threaded drive **4** being controlled based on the thermal expansion of the respective components in such a way that the actual steering angle of the vehicle wheels corresponds to a target specification of the control and analysis unit **10**.

LIST OF REFERENCE SYMBOLS

(11) **1** Actuator **2** Steering linkage **3** Housing **4** Threaded drive **5a**, **5b** Fork element **6** Rotor position sensor **7** Threaded nut **8** Linear sensor **9** Temperature sensor **10** Control and analysis unit **11** Target **12** Rear axle steering system **13** Direction of displacement **14** Threaded spindle **15** Fixed point **16** Electric motor **17** First distance **18** Second distance **19** Third distance **20** Fourth distance **21** Fifth distance **22a**, **22b** Point **23** Bracing point of the steering linkage on the threaded drive **24** Central axis of the housing

Claims

1. A method for steering a vehicle, the method comprising: providing a rear axle steering system comprising: an actuator having: a steering linkage configured to be at least indirectly operable by a threaded drive, the steering linkage longitudinally displaceable within a chassis-fixed housing, and a rotor position sensor configured for detecting a rotor position of a rotor of an electric motor configured for actuating the threaded drive, and a linear sensor configured for detecting an axial position of a target arranged on the steering linkage, and at least the rotor position and linear sensors configured to be connected to a control and analysis unit, and a steering angle of wheels configured to be at least indirectly connected to the steering linkage is adjusted by the steering linkage, comparing a rotor position of the rotor and an axial position of the target when there is a defined zero point of an axial position of the steering linkage relative to the housing and, determining a thermal expansion of at least the steering linkage, and operating the actuator via the control and analysis unit to adjust the steering angle according to the thermal expansion.
2. The method according to claim 1, wherein the determining of the thermal expansion of the at least the steering linkage is determined by detecting current temperature data via at least one temperature sensor.
3. The method according to claim 1, wherein the comparing of the rotor position of the rotor of the electric motor and the axial position of the target is accomplished by the control and analysis unit.
4. An actuator for a rear axle steering system of a vehicle having a steering linkage which is at least indirectly operable by a threaded drive and is longitudinally displaceable within a chassis-fixed housing, the actuator comprising: a rotor position sensor for detecting a rotor position of a rotor of an electric motor configured for actuating the threaded drive, and a linear sensor for detecting an axial position of a target arranged on the steering linkage, and each of the rotor position and linear sensors connected to a control and analysis unit, and the control and analysis unit configured to: i) carry out a comparison between the rotor position of the rotor and the axial position of the target when there is a defined zero point of an axial position of the steering linkage relative to the housing and, ii) in consideration of a thermal expansion of at least the steering linkage, operate the actuator

to adjust a steering angle.

5. The actuator according to claim 4, wherein the thermal expansion of at least the steering linkage is determined by detecting temperature data via at least one temperature sensor.

6. The actuator according to claim 5, wherein the at least one temperature sensor is integrated within the analysis and control unit.

7. The actuator according to claim 5, wherein the at least one temperature sensor is arranged on the linear sensor.

8. The actuator according to claim 5, wherein the at least one temperature sensor is an outside temperature sensor.

9. A vehicle comprising a rear axle steering system according to claim 4.

10. A rear axle steering system of a vehicle, the rear axle steering system comprising: a steering linkage having a threaded spindle configured to move longitudinally via a threaded nut rotatably driven by an electric motor, a rotor position sensor configured for detecting a rotor position of a rotor of the electric motor, a linear sensor configured for detecting an axial position of a target arranged on the steering linkage, and a control and analysis unit electronically connected to each of the rotor position and linear sensors, the control and analysis unit configured to: i) store at least one coefficient of thermal expansion for the steering linkage, and ii) utilize the at least one coefficient of thermal expansion to adjust a position of the steering linkage based on thermal expansion of the steering linkage.

11. The rear axle steering system of claim 10, further comprising a temperature sensor electronically connected to the control and analysis unit.

12. The rear axle steering system of claim 11, wherein the temperature sensor is arranged on the linear sensor.

13. The rear axle steering system of claim 11, wherein the temperature sensor is arranged on the electric motor.

14. The rear axle steering system of claim 10, wherein the target is arranged within an anti-rotation mechanism arranged to prevent rotation of the steering linkage about a longitudinal axis of the steering linkage.

15. The rear axle steering system of claim 10, wherein, to adjust a position of the steering linkage, the control and analysis unit utilizes a comparison of a rotor position of the rotor and the axial position of the target when there is a defined zero point of an axial position of the steering linkage.

16. The rear axle steering system of claim 10, further comprising a housing, and the steering linkage is longitudinally guided by the housing.

17. The rear axle steering system of claim 16, wherein the housing comprises a plurality of fixing points configured to attach the housing to a chassis of the vehicle.

18. The rear axle steering system of claim 16, further comprising first and second fork elements arranged at respective first and second ends of the steering linkage.

19. The rear axle steering system of claim 18, wherein the first and second fork elements are arranged outside of the housing.
