



US012399042B2

(12) **United States Patent**
Pettersson-Falk

(10) **Patent No.:** **US 12,399,042 B2**

(45) **Date of Patent:** **Aug. 26, 2025**

(54) **DATA LOGGER UNIT, SENSOR UNIT,
ABSORBENT ARTICLE MANAGEMENT
SYSTEM AND IDENTIFICATION METHOD**

(56) **References Cited**

U.S. PATENT DOCUMENTS

(71) Applicant: **Essity Hygiene and Health**
Aktiebolag, Gothenburg (SE)

5,845,644 A 12/1998 Hughes et al.
7,667,608 B2 2/2010 Ales et al.
(Continued)

(72) Inventor: **Henrik Pettersson-Falk**, Harryda (SE)

FOREIGN PATENT DOCUMENTS

(73) Assignee: **ESSITY HYGIENE AND HEALTH**
AKTIEBOLAG, Gothenburg (SE)

CN 1402768 A 3/2003
CN 102481112 A 5/2012
(Continued)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 712 days.

OTHER PUBLICATIONS

(21) Appl. No.: **17/439,993**

Colombian Application No. NC2021/0013791; Office Action with
English translation dated Sep. 2, 2024; 38 pages.

(22) PCT Filed: **Apr. 15, 2019**

(Continued)

(86) PCT No.: **PCT/EP2019/059672**

§ 371 (c)(1),

(2) Date: **Sep. 16, 2021**

Primary Examiner — Daryl C Pope

(74) *Attorney, Agent, or Firm* — CANTOR COLBURN
LLP

(87) PCT Pub. No.: **WO2020/211922**

PCT Pub. Date: **Oct. 22, 2020**

(65) **Prior Publication Data**

US 2022/0170874 A1 Jun. 2, 2022

(51) **Int. Cl.**

G01D 9/00 (2006.01)

A61F 13/42 (2006.01)

G01N 27/22 (2006.01)

(52) **U.S. Cl.**

CPC **G01D 9/005** (2013.01); **A61F 13/42**
(2013.01); **G01N 27/221** (2013.01); **A61F**
2013/424 (2013.01)

(58) **Field of Classification Search**


CPC G01D 9/005; G01D 21/00; A61F 13/42;
A61F 2013/424; A61F 13/15; G01N
27/221; G01N 27/223

See application file for complete search history.

(57) **ABSTRACT**

The present invention relates to data logger units, sensor units, and in particular those which are suitable for sensing the hygienic state of an absorbent article. The present disclosure also relates to a method of identifying a sensor unit for an absorbent article performed by a data logger unit adapted to cooperate with the sensor unit, as well as an absorbent article management system. The data logger unit and the sensor have identification terminals. A characteristic property of the sensor unit is encoded in the potentials at each of the identification terminals. The data logger unit can decode the potentials at each of the identification terminals to determine the characteristic property of a connected sensor unit.

43 Claims, 15 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

8,663,106	B2 *	3/2014	Stivoric	G16H 40/63 600/301
8,816,149	B2	8/2014	Richardson et al.	
9,904,562	B2	2/2018	Bergström et al.	
11,173,073	B2	11/2021	Macnaughton et al.	
2004/0078219	A1	4/2004	Kaylor et al.	
2005/0156744	A1	7/2005	Pires	
2005/0245839	A1	11/2005	Stivoric et al.	
2007/0083174	A1	4/2007	Ales et al.	
2007/0252713	A1	11/2007	Rondoni et al.	
2008/0132859	A1	6/2008	Pires	
2008/0171920	A1	7/2008	Teller et al.	
2008/0269702	A1	10/2008	Ales et al.	
2010/0245114	A1	9/2010	Celik-Butler et al.	
2012/0149996	A1	6/2012	Stivoric et al.	
2012/0268278	A1	10/2012	Lewis et al.	
2013/0018340	A1	1/2013	Abraham et al.	
2013/0268231	A1	10/2013	Sato	
2013/0303867	A1	11/2013	Elfstrom et al.	
2013/0307570	A1	11/2013	Bosaeus et al.	
2014/0218057	A1	8/2014	White et al.	
2014/0350503	A1	11/2014	Bosaeus et al.	
2014/0371702	A1	12/2014	Bosaeus et al.	
2016/0080841	A1	3/2016	Bergström et al.	
2016/0361209	A1	12/2016	Mashin-Chi et al.	
2017/0307458	A1	10/2017	Landmann	
2018/0333306	A1	11/2018	Ahong et al.	
2019/0247650	A1	8/2019	Tran	
2020/0060899	A1	2/2020	Neeley et al.	
2020/0323285	A1	10/2020	Longinotti-Buitoni et al.	
2020/0352794	A1	11/2020	Curran et al.	
2021/0113130	A1	4/2021	Tran	
2022/0015956	A1	1/2022	Öberg et al.	
2022/0054326	A1	2/2022	Øberg et al.	

FOREIGN PATENT DOCUMENTS

CN	102573713	A	7/2012
CN	103269667	A	8/2013
CN	103269668	A	8/2013
CN	103327944	A	9/2013
CN	103561705	A	2/2014
CN	104066409	A	9/2014
CN	107530214	A	1/2018
CO	08070222		11/2008
EP	1995579	A2	11/2008
EP	3415130	A1	12/2018
JP	S48123527		10/1973
JP	S50069190	U	6/1975
JP	2000093448	A	4/2000
JP	2002082080	A	3/2002
JP	2009006180	A	1/2009
JP	2009031264	A	2/2009
JP	2013039158	A	2/2013
JP	2013218454	A	10/2013
JP	2018501864	A	1/2018
KR	101667120	B1	10/2016
WO	2006047815	A1	5/2006
WO	2007128038	A1	11/2007
WO	2010049827	A2	5/2010
WO	2010123425	A1	10/2010
WO	2011004165	A1	1/2011
WO	2011054045	A1	5/2011
WO	2012084924	A1	6/2012
WO	2012084987	A2	6/2012
WO	2012114208	A1	8/2012
WO	2012166765	A1	12/2012
WO	2015102084	A1	7/2015
WO	2016090492	A1	6/2016
WO	2017152687	A1	9/2017
WO	2019096413	A1	5/2019
WO	2020125999	A1	6/2020

WO	2020126000	A1	6/2020
WO	2021004598	A1	1/2021
WO	2024061465	A1	3/2024

OTHER PUBLICATIONS

Third Party Observation for European Application No. EP20180826035 dated Apr. 28, 2023 15:01; 9 pages.

Third Party Observation for European Application No. EP20180826035 dated Apr. 28, 2023 15:05; 6 pages.

Third Party Observation for European Application No. EP20180826035 dated Mar. 19, 2024 11:42; 9 pages.

Third Party Observation for European Application No. EP20180826035 dated Mar. 19, 2024 14:42; 2 pages.

Third Party Submission on European Application No. 3897496A1 filed on Apr. 28, 2023; 16 pages.

Third Party Submission on European Application No. EP3897496A1 dated Apr. 27, 2023; 22 pages.

Japanese Application No. 2021-531773; Office Action with English Translation dated Nov. 14, 2022; 9 pages.

Korean Application No. 10-2021-7018888; Korean Office Action with English Translation dated Dec. 12, 2022; 18 pages.

Canadian Application No. 3,119,685; Canadian Office Action dated May 5, 2023; 4 pages.

Chinese Application No. 201880100107.X; Office Action with English Translation dated Mar. 25, 2023; 19 pages.

Colombian Application No. NC2021/0006510; Colombian Office Action with English translation dated Mar. 15, 2023; 28 pages.

Colombian Application No. NC2021/0006510; Colombian Office Action with English translation dated Nov. 25, 2022; 18 pages.

European Application No. 18826035.0; Third Party Observation filed Apr. 27, 2023; 22 pages.

European Application No. 18826035.0; Third Party Observation filed Apr. 28, 2023; 6 pages.

European Application No. 18826035.0; Third Party Observation filed Apr. 28, 2023; 9 pages.

Japanese Application No. 2021-531773; Decision to Grant with English Translation dated Feb. 14, 2023; 6 pages.

Japanese Application No. 2021-535834; Japanese Office Action with English translation mailed Mar. 27, 2023; 11 pages.

Korean Application No. 10-2021-7018888; Korean Office Action with English Translation dated Jun. 20, 2023; 3 pages.

Korean Application No. 10-2021-7019765; Korean Office Action with English Translation dated May 19, 2023; 23 pages.

Colombian Office Action issued in Colombian Application No. NC/2021/0008642; dated Nov. 30, 2023; 14 pages.

Non-Final Office Action issued in U.S. Appl. No. 17/413,669 dated Mar. 13, 2024; 14 pages.

National Intellectual Property Administration (CNIPA) of the People's Republic of China, Notification of the First Office Action, Application No. 201880100107.X, dated Dec. 2, 2021 (15 pages).

European Application No. 18826354.5-1102; Communication pursuant to Article 94(3) EPC dated Oct. 20, 2023; 3 pages.

Japanese Application No. 2021-535834; Decision of Rejection dated Aug. 21, 2023; 4 pages.

Japanese Application No. 2021-535834; Decision to Reject the Amendments dated Aug. 21, 2023; 9 pages.

Japanese Application No. 2021-560984; Decision of Rejection dated May 29, 2023; 8 pages.

Final Office Action issued in U.S. Appl. No. 17/413,670 dated Jun. 27, 2024.

Chinese Office Action issued in Chinese Application No. 201980095471.6 dated Dec. 13, 2023; 31 pages.

Non-Final Office Action issued in U.S. Appl. No. 17/413,670 dated Feb. 16, 2024, 63 pages.

Brazilian Search Report issued in Brazilian Application No. BR112021018767-7 dated Mar. 20, 2024.

Colombia Office Action issued in Application No. NC2021/0013791 dated Mar. 1, 2024 with English translation.

Notification of Grounds for Refusal issued in Korean Application No. 10-2021-7036456 forwarding date Mar. 22, 2024 with English translation.

(56)

References Cited**OTHER PUBLICATIONS**

Second Office Action issued in Chinese Application No. 201980095471.6 dated May 15, 2024 with English translation.
European Patent Office, International Search Report and Written Opinion of the International Searching Authority, International Application No. PCT/EP2018/086217, mailed Mar. 20, 2019 (13 pages).

European Patent Office, International Search Report and Written Opinion of the International Searching Authority, International Application No. PCT/EP2018/086218, mailed Jun. 25, 2019 (13 pages).

European Patent Office, International Search Report and Written Opinion of the International Searching Authority, International Application No. PCT/EP2019/059672, mailed Jan. 27, 2020 (14 pages).

Australian Government, IP Australia, Examination report No. 1 for standard patent application, Application No. 2018454396, mailed Oct. 29, 2021 (4 pages).

Brazilian Application No. BR112021008140-2; Brazilian Search Report dated Sep. 7, 2022; 4 pages.

Brazilian Application No. BR112021011142-5; Brazilian Search Report dated Sep. 7, 2022; 4 pages.

Canadian Application No. 3, 123,929; Canadian Office Action dated Oct. 6, 2022; 4 pages.

Canadian Application No. 3,134, 131; Canadian Office Action dated Nov. 24, 2022; 4 pages.

European Application No. 18826035.0; Communication pursuant to Article 94(3) EPC dated Jan. 3, 2023; 3 pages.

International Searching Authority, Search Report and Written Opinion issued in PCT/EP2018/086217, mailed Mar. 20, 2019 (13 pages).

International Searching Authority, Search Report and Written Opinion issued in PCT/EP2018/086218, mailed Jun. 25, 2019 (13 pages).

Japanese Application No. 2021-535834; Japanese Office Action with English translation mailed Sep. 12, 2022; 12 pages.

Japanese Application No. 2021-560984; Japanese Office Action with English Translation dated Oct. 31, 2022; 14 pages.

Korean Application No. 10-2021-7019765; Korean Office Action with English Translation dated Dec. 13, 2022; 22 pages.

Chinese Application No. 201880100107.X; Chinese Office Action dated Oct. 26, 2022; 11 pages.

Canadian Application No. 3,119,685; Canadian Office Action dated Oct. 13, 2022; 6 pages.

Australian Government, IP Australia, Examination report No. 1 for standard patent application, Application No. 2018454245, mailed Oct. 22, 2021 (5 pages).

National Intellectual Property Administration (CNIPA) of the People's Republic of China, Notification of the First Office Action, Application No. 201880100095.0, dated Dec. 2, 2021 (26 pages).

Australian Application No. 2018454396; Office Action dated Mar. 15, 2022; 4 pages.

Australian Government, IP Australia, Examination report No. 1 for standard patent application, Application No. 2018454245, mailed Mar. 31, 2022 (5 pages).

Chinese Application No. 201880100107.X; Office Action dated Jun. 28, 2022; 12 pages.

National Intellectual Property Administration (CNIPA) of the People's Republic of China, Office Action, Application No. 201880100095.0, dated Aug. 10, 2022 (26 pages).

Japanese Application No. 2021-531773; Office Action with English Translation dated May 9, 2022; 11 pages.

U.S. Appl. No. 17/413,670; Non-Final Office Action dated Nov. 8, 2024; 22 pages.

Australian Application No. 2019440869; Examination Report 1 dated Dec. 18, 2024; 3 pages.

International Search Report & Written Opinion for International Application No. PCT/EP2022/076369; International Filing Date: Sep. 22, 2022; Date of Mailing: May 19, 2023; 15 pages.

Japanese Application No. 2023-138032; Office Action with English translation dated Dec. 2, 2024; 14 pages.

* cited by examiner




Figure 1




Figure 2




Figure 3




Figure 4




Figure 5




Figure 6




Figure 7

MEAS




Figure 8





Figure 9



9250




Figure 11




Figure 12




Figure 13




Figure 14




Figure 15




Figure 16

1

DATA LOGGER UNIT, SENSOR UNIT, ABSORBENT ARTICLE MANAGEMENT SYSTEM AND IDENTIFICATION METHOD

CROSS REFERENCE TO RELATED APPLICATION

The present application is a U.S. National Stage entry under 35 U.S.C. § 371 of, and claims priority to, International Application No. PCT/EP2019/059672, filed Apr. 15, 2019, the disclosure of which is hereby incorporated herein by reference in its entirety.

FIELD OF THE INVENTION

The present invention relates to data logger units, sensor units, and in particular those which are suitable for sensing the hygienic state of an absorbent article. The present disclosure also relates to a method of identifying a sensor unit for an absorbent article performed by a data logger unit adapted to cooperate with the sensor unit, as well as an absorbent article management system.

BACKGROUND OF THE INVENTION

Absorbent articles, such as diapers, absorbent underwear, sanitary products and incontinence shields require periodic replacement, in use, to ensure that the absorbency of the article is not compromised.

In many settings, including domestic settings, institutional settings, healthcare settings and the like, there is a need to monitor the state of an absorbent article provided to a user to ensure that the article contains satisfactory absorbent capacity to fulfil its function.

Conventionally, such monitoring may be performed as self-monitoring by the user, in which the user informs care staff that the capacity of the absorbent article to absorb has diminished, or by periodic checking of the absorbent article by the user or by care staff. However, such processes are labour intensive. Moreover, the information gathered about the personal needs of the user in respect of the needed frequency of replacement of the absorbent article or the needed capacity of the absorbent article is slow to aggregate, and is frequently and incompletely collected.

Accordingly, it has been proposed to provide absorbent articles with sensors, which are coupled to data logging electronics. The data logging electronics can determine the absorbent state of the absorbent article, and, for example, can notify a carer when the absorbent state of the absorbent article has reached a predetermined state.

Arrangements have been proposed which use sensing wires embedded in an absorbent core of the absorbent article, such that data logging electronics measure the resistance between the wires to determine the presence of liquid in the absorbent core, and hence the state of the absorbent article.

In some configurations, the data logger can notify the user or nearby care giver by means of appropriate visual or audible signals that liquid is present in the core and therefore that the absorbent article requires replacement.

It has also been proposed to use such logging electronics as part of an absorbent article management system. In such a system, the data logging electronics may communicate the absorbent state of the absorbent article to a remote terminal. The remote terminal can be used for monitoring the absorbent state of the absorbent article. Such management systems may be of particular utility where the users may have

2

difficulty communicating their needs to care staff, such as in early years child care settings or in hospital settings.

In some systems, the remote terminal may aggregate the information recorded from a large number of data loggers associated with respective users. By such management systems, the absorbent state of a large number of articles associated with a large number of respective users can be conveniently monitored with reduced staffing requirements.

However, providing such articles having sensors and data logging electronics, and therefore consequently providing such systems, can be resource-intensive, in that absorbent articles fitted with such sensors and data logging electronics have a significantly higher unit cost than manually-monitored absorbent articles. This higher cost is significant because absorbent articles typically require frequent replacement, to the extent of several replacements of the article per user per day.

To address this, it has been proposed to provide data logging electronics and corresponding sensors as discrete logging packages which may be removably provided to an appropriately-designed absorbent article in order to monitor that absorbent article. When the article is replaced, then the logging package can be removed and provided to the replacement article.

However, because such sensors are difficult to integrate into the absorbent core of an absorbent article, the sensing capability may be reduced in systems using replaceable logging packages. Moreover, since absorbent articles are often provided in a range of forms and sizes, a logging package which is appropriate for provision to one type or size of absorbent article may perform poorly when used in combination of another type or size of absorbent article.

Accordingly, there is need for a more flexible means of measuring and monitoring the absorbent status of absorbent articles which overcomes at least some of the drawbacks associated with prior arrangements.

SUMMARY OF THE INVENTION

According to a first aspect of the present invention, there is provided a method of identifying, by a data logger unit, a sensor unit for an absorbent article. The sensor unit comprises a sensor-side terminal portion. The sensor unit comprises at least one sense element. The at least one sense element is electrically connected to at least one measurement terminal of the sensor-side terminal portion. The data logger unit comprises a logger-side terminal portion. The data logger unit comprises a measurement module electrically connected to at least one sense terminal of the logger-side terminal portion. The sensor terminal portion engages the logger-side terminal portion. The engagement is such as to bring terminals of the sensor-side terminal portion into electrical connection with corresponding terminals of the logger-side sensor portion. The data logger unit is adapted to perform an electrical measurement of the at least one sense element. The measurement is performed via the at least one measurement terminal of the sensor-side terminal portion. The measurement is performed via the at least one measurement terminal of the logger-side terminal portion. The data logger unit has a plurality of identification terminals at the logger-side terminal portion. The plurality of identification terminals are electrically connected to the measurement module. The sensor terminal portion has a plurality of identification terminals at the sensor-side terminal portion. The measurement module performs an electrical measurement of the plurality of identification terminals of the logger-side terminal portion. The measurement is performed

to identify a characteristic property of the sensor unit. The characteristic property of the sensor unit is encoded in the electrical potentials of the identification terminals of the sensor-side terminal portion.

The sensor-side terminal portion may have a reference terminal. The logger-side terminal portion may have a reference terminal. The measurement module may provide a reference potential to the reference terminal of the logger-side terminal portion. At least one of the identification terminals of the sensor-side terminal portion may be electrically connected via a conductor of the sensor unit to the reference terminal of the sensor-side terminal portion. The characteristic property of the sensor unit may be encoded in the potential at each of the identification terminals of the sensor-side terminal portion as compared with the reference potential.

A resistor of the data logger unit may be electrically connected between each of the identification terminals of the sensor-side terminal portion and a conductor of the data logger unit maintained at a potential provided by the measurement module which is different from the reference potential.

One or more of the identification terminals of the sensor-side terminal portion may be electrically connected by a conductor of the sensor unit to the reference terminal of the sensor-side terminal portion. The remaining identification terminals of the sensor-side terminal portion may be not electrically connected to the sensor reference terminal.

The reference potential may be a ground potential of the measurement module.

The reference terminal of the sensor-side terminal portion may be a ground reference terminal. The reference terminal of the sensor-side terminal portion may be a ground reference terminal. The ground reference terminal of the logger-side terminal portion may be connected by a conductor of the data logger unit to a ground of the measurement module. One or more of the identification terminals of the sensor-side terminal portion may be electrically connected to the sensor ground reference terminal by a conductor of the sensor unit.

The reference potential may be a potential different from a ground potential of the measurement module.

The reference terminal of the sensor-side terminal portion may be a supply terminal. The reference terminal of the logger-side terminal portion may be a supply terminal. The supply terminal of the logger-side terminal portion may be electrically connected by a conductor of the data logger unit to a supply potential of the measurement module. One or more of the identification terminals of the sensor-side terminal portion may be electrically connected together and to the sensor supply terminal by a conductor of the sensor unit.

The sensor-side terminal portion may have a ground reference terminal. The logger-side terminal portion may have a ground terminal. The ground reference terminal of the logger-side terminal portion may be connected to a ground potential of the measurement module by a conductor of the data logger unit.

The characteristic property of the sensor unit may be determined by identification of a single terminal, among the identification terminals of the logger-side terminal portion, as having the reference potential. The identified terminal may correlate with the characteristic property.

The characteristic property of the sensor unit may be determined by identification of a set of terminals, among the identification terminals of the logger-side terminal portion, as having the reference potential. The set of identified terminals may correlate with the characteristic property.

The potentials of the identification terminals of the logger-side terminal portion may define a sequence of binary digits. The data logger unit may decode a value correlating with the characteristic property from the sequence of binary digits.

The sense elements may be provided to a flexible substrate of the sensor unit.

The flexible substrate may be elongate along an axis of elongation. The sense elements may comprise a plurality of conductive plates arranged along the axis of elongation of the flexible substrate.

The flexible substrate may be elongate along an axis of elongation. The sense elements may comprise one or more pairs of elongate conductive plates. Each pair of conductive plates may be arranged with one plate of the pair of conductive plates on one side of the axis of elongation and the other plate of the pair of conductive plates on the other side of the axis of elongation in a direction crossing the axis of elongation.

The sense elements may be arranged on one surface of the flexible substrate. A conductive region may be arranged on the other surface of the flexible substrate to the side on which the one or more pairs of conductive plates are arranged so as to underlie the sense elements.

The conductive plate may be connected, via a ground terminal of the sensor-side terminal portion, to a ground potential of the measurement module.

Prior to the measurement module performing the electrical measurement, the data logger unit may be removably attached to the sensor unit.

Subsequent to the measurement module performing the electrical measurement, the data logger unit may be detached from the sensor unit and attached to another sensor unit.

According to a second aspect of the present invention, there is provided a data logger unit for receiving data from a sensor unit provided to an absorbent article. The data logger unit comprises a logger-side terminal portion and a measurement module electrically connected to at least one measurement terminal of the logger-side terminal portion. The logger terminal portion is adapted for engagement with a sensor-side terminal portion of the sensor unit. The connection is to connect the sensor unit and the data logger unit together. The measurement module is arranged to perform an electrical measurement via the at least one measurement terminal of the logger-side terminal portion. The data logger unit has a plurality of identification terminals at the logger-side terminal portion. The plurality of identification terminals are electrically connected to the measurement module. The measurement module is configured to perform a measurement of the plurality of identification terminals. The measurement is performed to identify a characteristic property of the sensor unit. The characteristic property of the sensor unit is encoded in the electrical potentials of the identification terminals.

The logger-side terminal portion may have a reference terminal. The measurement module may be configured to provide a reference potential to the reference terminal of the logger-side terminal portion. The characteristic property of the sensor unit may be encoded in the potential at each of the identification terminals of the logger-side terminal portion as compared with the reference potential.

A resistor of the data logger unit may be electrically connected between each of the identification terminals of the logger-side terminal portion and a conductor of the data

5

logger unit maintained at a potential provided by the measurement module which is different from the reference potential.

The reference potential may be a ground potential of the measurement module.

The reference terminal of the logger-side terminal portion may be a ground reference terminal. The ground reference terminal may be connected by a conductor of the data logger unit to a ground of the measurement module.

The reference potential may be a potential different from a ground potential of the measurement module.

The reference terminal of the logger-side terminal portion may be a supply terminal. The supply terminal may be electrically connected by a conductor of the data logger unit to a supply potential of the measurement module.

The logger-side terminal portion may have a ground terminal. The ground terminal of the logger-side terminal portion may be connected to a ground potential of the measurement module by a conductor of the data logger unit.

The characteristic property of the sensor unit may be determined by identification of a single terminal, among the identification terminals of the logger-side terminal portion, as having the reference potential. The identified terminal may correlate with the characteristic property.

The measurement module may be configured to determine the characteristic property of the sensor unit by identification of a set of terminals, among the identification terminals of the logger-side terminal portion, as having the reference potential. The set of identified terminals may correlate with the characteristic property.

The potentials of the identification terminals may define a sequence of binary digits. The data logger unit may decode a value correlating with the characteristic property from the sequence of binary digits.

The data logger unit may be detachably attachable to the sensor unit.

The data logger unit may be detachably attachable to the absorbent article.

The measurement module may be adapted to repeat performing the electrical measurement after the data logger unit is detached from the sensor unit and attached to another sensor unit.

According to a third aspect of the present invention, there is provided a sensor unit for an absorbent article for connection to a data logger unit to determine a hygiene state of the absorbent article. The sensor unit comprises a sensor-side terminal portion. The sensor unit comprises at least one sense element electrically connected to at least one measurement terminal of the sensor-side terminal portion. The sensor-side terminal portion is adapted for engagement with a logger-side terminal portion of the data logger unit. The engagement is thereby to connect the sensor unit and the data logger unit. The sensor terminal portion has a plurality of identification terminals at the sensor-side terminal portion. The identification terminals of the sensor-side terminal portion are configured to provide, by electrical measurement of the plurality of identification terminals, a characteristic property of the sensor unit. The characteristic property of the sensor unit is encoded in the electrical potentials of the identification terminals of the sensor-side terminal portion when connected to the data logger unit.

The sensor terminal portion may have a reference terminal. At least one of the identification terminals of the sensor-side terminal portion may be electrically connected via a conductor of the sensor to the reference terminal of the sensor-side terminal portion. The characteristic property of the sensor unit may be encoded in the potential at each of the

6

identification terminals of the sensor-side terminal portion as compared with the reference potential.

One or more of the identification terminals of the sensor-side terminal portion may be electrically connected by a conductor of the sensor unit to the reference terminal of the sensor-side terminal portion. The remaining identification terminals of the sensor-side terminal portion may not be electrically connected to the sensor reference terminal.

The reference terminal of the sensor-side terminal portion may be a ground reference terminal. One or more of the identification terminals of the sensor-side terminal portion may be electrically connected together and to the ground reference terminal of the sensor-side terminal portion by a conductor of the sensor unit.

The reference terminal of the sensor-side terminal portion may be a supply terminal. One or more of the identification terminals of the sensor-side terminal portion may be electrically connected together and to the sensor supply terminal of the sensor-side terminal portion by a conductor of the sensor.

The sensor-side terminal portion may have a ground reference terminal.

The characteristic property of the sensor unit may be determined by identification of a single terminal, among the sensor identification terminals of the sensor-side terminal portion, as having the reference potential. The identified terminal may correlate with the characteristic property.

The characteristic property of the sensor unit may be determined by identification of a plurality of terminals of the sensor-side terminal portion, among the identification terminals of the sensor-side terminal portion, as having the reference potential. The set of identified terminals may correlate with the characteristic property.

The potentials of the identification terminals of the sensor-side terminal portion may define a sequence of binary digits. The sequence of binary digits may decode to a value correlating with the characteristic property.

The sense elements may be provided to a flexible substrate.

The flexible substrate may be elongate along an axis of elongation. The sense elements may comprise a plurality of conductive plates arranged along the axis of elongation of the flexible substrate.

The flexible substrate may be elongate along an axis of elongation. The sense elements may comprise one or more pairs of elongate conductive plates, each pair of conductive plates being arranged with one plate of the pair of conductive plates on one side of the axis of elongation, and the other plate of the pair of conductive plates on the other side of the axis of elongation in a direction crossing the axis of elongation.

The sense elements may be arranged on one surface of the flexible substrate. A conductive region may be arranged on the other surface of the flexible substrate to the side on which the one or more pairs of conductive plates are arranged so as to underlie the sense elements.

The conductive plate may be connected to a ground terminal of the sensor-side terminal portion.

The sensor unit may be detachably attachable to the data logger unit.

The sensor unit may be detachably attachable to the absorbent article.

The sensor unit may be configured to detect the presence of body fluids in an absorbent article in proximity to the sensor unit in a non-contact manner.

According to a fourth aspect of the present invention, there is provided a plurality of interchangeable sensor units

according to the third aspect. Each sensor unit of the plurality of interchangeable sensor units has a common configuration of sensor-side terminal portion. The sensor-side terminal portion is adapted for engagement with a logger-side terminal portion of a common data logger unit. The engagement is such that the sensor units may be exchanged in connection with the data logger unit. The characteristic property may be a characteristic property which differs among the interchangeable sensor units. The characteristic property may be uniquely specified by the electrical potentials of the identification terminals of the sensor-side terminal portion of each sensor unit when connected to the data logger unit.

The characteristic property may be a length in an elongate direction of the sensor unit.

The characteristic property may be an electrical property associated with the at least one sense element.

The at least one sense element may comprise two elongate sense elements arranged parallel to one another. The characteristic property may be a capacitance between the sense elements.

The characteristic property may be a dimension associated with the at least one sense element.

The plurality of interchangeable sensor units may be adapted for detachable attachment to the common data logger unit.

According to a fourth aspect of the present invention, there is provided an absorbent article management system. The absorbent article management system comprises a data logger unit according to the second aspect. The absorbent article management system comprises a sensor unit according to the third aspect. The sensor unit is provided to an absorbent article such that the at least one sense element is arranged to determine a hygienic state of the absorbent article. The data logger unit is adapted to perform the method of the first aspect in a state in which the data logger unit is connected to the sensor unit. The data logger unit periodically performs an electrical measurement of the at least one sense element via the at least one measurement terminal of the sensors-side terminal portion and the at least one measurement terminal of the logger-side terminal portion. The data logger unit may associate information about the result of the electrical measurement with information about the electrical potential of the identification terminals of the sensor-side terminal portion for identifying the characteristic property of the sensor unit.

The data logger unit may comprise a data storage unit. The data logger unit may be adapted to store information about the result of the electrical measurement in association with information for identifying the characteristic property of the sensor unit.

The absorbent article management system may further comprise a remote terminal. The data logger unit may comprise a communication unit adapted to transmit data to the remote terminal. The communication unit may be adapted to transmit information about the result of the electrical measurement to the communication unit in association with information for identifying the characteristic property of the sensor unit.

The remote terminal may comprise a database. The database may be adapted to store information about the result of the electrical measurement in association with information for identifying the characteristic property of the sensor unit.

The data logger unit may be adapted to decode the electrical potentials of the identification terminals of the logger-side terminal portion to provide information about the characteristic property.

The remote terminal may be adapted to decode the electrical potentials of the identification terminals of the logger-side terminal portion to provide information about the characteristic property.

BRIEF DESCRIPTION OF THE DRAWINGS

For a better understanding of the present invention, and to show how the same may be carried into effect, reference will now be made, by way of example, to the accompanying drawings, in which:

FIG. 1 shows an absorbent article to which a sensor unit being an embodiment of the present invention is provided;

FIG. 2 shows a sensor unit being an embodiment of the present invention;

FIG. 3 shows a combination of a sensor unit and a data logging unit which is an embodiment of the present invention;

FIG. 4 shows a data logging unit which is an embodiment of the present invention with a terminal region exposed;

FIG. 5 shows a data logging unit which is an embodiment of the present invention with a terminal region covered by a clamp bar;

FIG. 6 shows a combination of a sensor unit and a data logging unit which is an embodiment of the present invention with aligned terminal regions;

FIG. 7 shows a combination of a sensor unit and a data logging unit which is an embodiment of the present invention with terminal regions covered by a clamp bar;

FIG. 8 shows a schematic electrical diagram of a data logging unit being an embodiment of the present invention;

FIG. 9 shows a schematic electrical diagram of a sensor unit being an embodiment of the present invention;

FIG. 10 shows a schematic electrical diagram of a data logging unit being a variant embodiment of the present invention;

FIG. 11 shows a schematic electrical diagram of a data logging unit being another variant embodiment of the present invention;

FIG. 12 shows a schematic electrical diagram of a data logging unit being another variant embodiment of the present invention;

FIG. 13 shows a schematic electrical diagram of a data logging unit being another variant embodiment of the present invention;

FIG. 14 shows a schematic electrical diagram of a data logging unit being another variant embodiment of the present invention;

FIG. 15 shows a schematic electrical diagram of a data logging unit being another variant embodiment of the present invention; and

FIG. 16 shows a block diagram of a data logging unit and a remote terminal forming an absorbent article management system and being an embodiment of the present invention.

DETAILED DESCRIPTION OF THE INVENTION

FIG. 1 shows an exemplary configuration of an absorbent article 900, specifically a diaper. Diaper 900 has front port waist portion 920, rear waist portion 930, and crotch portion 940 connecting the front waist portion 920 to the rear waist portion 930. Diaper 900 has an outer surface which faces away from the user, when worn, and an inner surface, which faces toward the user, when worn.

In the configuration of diaper 900 shown in FIG. 1, front waist portion has tab portions 921 and 922 which are

adapted to engage with corresponding tab portions **924** and **925** provided to rear waist portion **930**. For example, tab portion **921** and **922** may be provided with adhesive regions, are arranged to adhere to adhesive regions provided to tab portion **924** and **925**. Thereby, a secure fit of the diaper **900** around the waist of the user may be assured.

Diaper **900** also has an absorbent core **910** which is configured to absorb liquid and/or solid insults to the diaper from the user when worn. The construction of such a core, and the construction of the remainder of the diaper, may be conventional as known in the art. For example, the core may contain, in an absorbent layer, an absorbent material such as super-absorbent polymer, alone or in combination with further constituents, such as cellulosic fibers, and may comprise one or more additional layers having functions such as liquid acquisition, liquid distribution, and leakage prevention.

Diaper **900** may have a liquid permeable top sheet on its inner surface which provides a soft covering to the core **910**. Diaper **900** may have a liquid impermeable backsheet on its outer surface to prevent leakage, and the absorbent core **910** disposed between the liquid permeable topsheet and the liquid impermeable backsheet. The construction of such diapers is well known in the art. It is noted that while the backsheet is typically liquid impermeable, it may, or may not, be vapour permeable, in other words breathable.

Diaper **900** is provided with sensor unit **100**, the function of which is, in cooperation with appropriate measurement electronics, to sense the absorbent state, for example a wetness state, of the absorbent core **910**. Sensor unit **100** is in the form of an elongate, flexible strip and is arranged to overly absorbent core **910**. Sensor unit **100** has therefore, when arranged in a flat state, a longitudinal axis in the direction of elongation and a transverse axis in a direction across the axis of elongation, but in the plane of the strip. Sensor unit **100** need not be rectangular as shown, but can be bow-tie shaped, provided with curvilinear edges, can be oval, or can be another elongate shape.

Absorbent articles such as article **900** which are to be worn by the user or otherwise to be placed or secured on or against the user's body are conventionally understood to have an inside and an outside, the inside being the part which is, in use, to be arranged against the user's body, and the outside being the part which is to face outwardly of the user's body. As shown in FIG. 1, absorbent core **910** is on the inside of the absorbent article, while sensor unit **100** is provided on the outside of the absorbent article, here specifically on the side of the backsheet facing away from the absorbent core **910**.

Sensor unit **100** may be fixed to the surface of absorbent article **900** by means of a layer of adhesive, by hook-and-loop fasteners, or by other methods of releasable or temporary attachment known in the art. Advantageously, sensor unit **100** is designed to be releasable from the absorbent article after it has been attached thereto, so that the same sensor unit may be reused with a number of different absorbent articles.

Sensor unit **100** is provided with sensing plates **111**, **112**, **113**, **114**, which act as the plates of a plane-parallel-plate capacitor. By measuring the impedance between pairs of plates **111**, **112**, **113**, **114**, the presence or absence of liquid in the absorbent core may be determined. Without wishing to be bound by theory, the presence of liquid in the absorbent core **910** modifies the dielectric constant of the region underlying sensor unit **100**, and thereby modifies the dielec-

tric constant of the space above, for example, plates **111** and **112**, thereby affecting the impedance of the capacitor formed by those plates.

Such a configuration allows the detection of liquid in the absorbent core in a non-contact manner, in the sense that there is no direct contact between the body fluids and the sensor unit. Accordingly, sensor unit **100** can sense the state of an absorbent core or region of an absorbent core even when separated from the absorbent core by a liquid impermeable layer such as a liquid impermeable back sheet. This is in contrast, for example, to resistive-type sensing arrangements which tend to require contact between the liquid in the absorbent core and conductors which act as sense elements.

A more detailed view of an exemplary configuration of a sensor unit **100** is shown in FIG. 2, viewed from a side of the sensor unit at such that plates **111**, **112**, **113**, **114** face the viewer. Sensor unit **100** has a flexible substrate **120** to which plates **111**, **112**, **113**, **114** are provided, for example by surface plating. Flexible substrate **120**, therefore, may be a flexible printed circuit board (flexible PCB).

On the side of flexible substrate **120** opposite to that having plates **111**, **112**, **113**, **114** is grounding plate **130** which underlies substantially all of the surface of flexible substrate **120**, but specifically that region which bears the plates **111**, **112**, **113**, **114**. Thereby, the influence on the impedances between the plates **111**, **112**, **113**, **114** may predominantly be controlled by the environment above the surface of the flexible surface **120** carrying plates **111**, **112**, **113**, **114**, rather than on the environment adjacent to the opposite side of flexible substrate **120**.

Each of plates **111**, **112**, **113**, **114** is connected by a respective conductive trace **161**, **162**, **163**, **164** to respective conductive pads **151**, **153**, **154** arranged in a terminal region **140** of the sensor unit.

Conductive traces **161**, **162**, **163**, **164**, as well as plates **111**, **112**, **113**, **114** may be covered by a layer of dielectric material such a thin film on polymer. In contrast, pads **151**, **152**, **153**, **154**, are exposed at the surface of flexible substrate **120** so as to act as terminals facilitating connection between plates **111**, **112**, **113**, **114** and measurement and data logging electronics, to be described later.

The configuration of plates may be varied. For example, more than two pairs of plates may be provided. The plates may be elongate as shown, but need not be. The plates may be rectangular as shown, but need not be. The plates may be provided in pairs arranged across the axis of elongation of the flexible substrate, but need not be. The plates may be parallel, or may be inclined one to another. A wide variation in the arrangement of plates and their respective positions on the flexible substrate may therefore be considered.

As can be appreciated from FIG. 1, it is advantageous if sensor unit **100** is adapted to the length of absorbent core **910** of diaper **900**. For example, if sensor unit **100** is too long, the plates **111**, **112**, **113**, **114** may overlie regions of the diaper **900** where liquid is not expected to be absorbed, and therefore the sensitivity may be reduced, or the influence of other components in diaper **900** may cause erroneous readings. In contrast, if sensor unit **100** is significantly shorter than absorbent core **910** in the longitudinal absorbent core **910** then liquid may accumulate in the absorbent core **910** at locations where sensor unit **100** cannot sense the presence of liquid.

Therefore, it is considered appropriate in some embodiments that sensor unit **100**, or at least the part of it carrying the plates **111**, **112**, **113**, **114**, is coextensive and of comparable length and/or width as the absorbent core, for example, between 20% and 100% the respective dimension of the

11

core, optionally between 30% and 80%, or further optionally between 40% and 60%. For example, a rectangle bounding the absorbent core **910** and a rectangle bounding the plates **111**, **112**, **113**, **114**, each in the flat state, may have comparable dimensions.

Moreover, with reference again to FIG. 1, the configuration of core **910** may be significantly more complex than that shown, and absorbent core **910** may comprise different regions having different absorbencies and/or difference widths. Accordingly, the layout of plates **111**, **112**, **113**, **114** on sensor unit **100** may be adapted to such a configuration of absorbent core **910**. In such embodiments, the plates may be arranged so as to be within the boundary of the absorbent core, but only to coextend with a particular location, such as a long-term storage region of the absorbent core.

Such adaption renders sensor unit **100** most effective only when used in conjunction with such absorbent cores. Sensor unit **100** may be ineffective when used in conjunction with absorbent cores of different configuration.

The most usual variation in absorbent core **910** results in a change in the size of diaper **900** to cope with different sizes of user, most commonly associated with different ages of user. Accordingly, a sensor unit **100** which is suitable for a use in conjunction with a diaper to be provided, for example, to a new-born infant is unlikely to be suitable for use in conjunction with a diaper to be provided, for example, to an adult male.

Accordingly, a proper selection of sensor unit **100** may depend closely on the absorbent article with which it is to be used. Therefore, if a plurality of different absorbent articles are to be provided in any particular situation, a corresponding plurality of corresponding sensor units **100** may also be provided. Each type of sensor unit **100** for use with a particular type of absorbent article **900** may differ in one of more characteristics from other sensor units of similar configuration. For example, the dimensions, particularly the length of the flexible substrate **120** may differ, and/or the positions and dimensions of the pads **111**, **112**, **113**, **114**. Also, the electrical properties of the sensor unit **100** may differ from other sensor units of similar configuration, for example, the capacitances or impedances between the plates measured in free space.

Importantly, the sensor unit **100** as shown in FIG. 2 is unable on its own to monitor the absorbent state of an absorbent article. To allow sensor unit **100** to monitor the absorbent state of an absorbent article, as shown in FIG. 3, sensor unit **100** is combined with a data logging unit **200** such that data logging unit **200** is able to supply electrical signals to sensor unit **100** and to measure changes in the electrical properties of the sensor unit **100**.

For example, in the configuration of FIG. 3, data logging unit may be configured to measure electric potentials between pairs of plates **111**, **112**, **113**, **114** by means of pads **151**, **152**, **153**, **154** provided in terminal region **140**. An exemplary configuration of data logging unit **200** is shown in FIG. 4.

Data logging unit **200** shown in FIG. 4 has an enclosure **210** containing data logging electronics, to be described later.

At a terminal region **220** of enclosure **210**, terminals **231**, **232**, **233**, **234** are provided to correspond to pads **151**, **152**, **153**, **154** of sensor unit **100** shown in FIG. 2. Terminals **231**, **232**, **233**, **234** may be provided as, for example, spring terminals. Such spring terminal may be formed as flexible conductor plates projecting upwardly from terminal region **220** of enclosure **210** so as to form a good electric contact

12

with a conductor pressed against the surface of enclosure **210** in which terminal region **220** is formed.

Such a terminal arrangement is here exemplary, and other terminal arrangements as known to those in the art will also be substitutable for the spring terminal according to their own suitability for a particular configuration. Such other terminal arrangements include, for example, mezzanine connectors, plug-and-socket connectors, registered jack or modular connectors, pogo-pin connectors, tip-ring-sleeve connectors, D-subminiature connectors, DIN connectors, or other terminal or connector types as known in the art. Where such connectors are gendered, either of the male part or the female part may be provided to data logging unit **200** and the other of the male part or the female part may be provided to sensor unit **100**. Such terminal arrangements may also have a function to retain data logging unit **200** and sensor unit **100** in physical engagement as well as electrical connection, especially when locking or otherwise secured variants of such connectors are provided.

Terminal region **220** corresponds to terminal region **140** formed on sensor unit **110**, in that the number and locations of terminals **231**, **232**, **233**, **234** formed in terminal region **220** of data log **200** corresponds to the number and locations of pads **151**, **152**, **153**, **154** of sensor unit **100**. Accordingly, when terminal region **140** of sensor unit **100** is placed against terminal region **220** of data logging unit **200**, data logging unit **200** may supply and measure electric signals associated with plates **111**, **112**, **113**, **114** by terminals **231**, **232**, **233**, **234** in order to perform measurements with sensor unit **100**.

In order to secure terminal region **140** of sensor unit **100** against terminal region **220** of data logging unit **200**, data logging unit **200** comprises an engagement element, here clamp plate **250**, which has projections, not shown, which press-fit into apertures **241**, **242**, formed in enclosure **210**. This configuration is shown in FIG. 5. By means of the press fit, clamp plate **250** applies force against terminal region **220**, enabling clamp plate **250** to secure an interposed sensor strip.

To secure terminal region **140** of sensor unit **100** against terminal region **220** of data logging unit **200**, and a configuration as shown in FIG. 6, may be adopted, wherein terminal region **140** of sensor unit **100** is placed against terminal region **220** such that terminals **231**, **232**, **233**, **234** of data logging unit **200** align with pads **151**, **152**, **153**, **154** of sensor unit **100**.

Then, clamp plate **250** is provided to enclosure **210** such that the projections of clamp plate **250** engage with apertures (**241**, **242**) of enclosure **210**. The final configuration is shown in FIG. 7, in which clamp plate **250** secures terminal region **140** of sensor unit **100** against terminal region **220** of enclosure **210** sensor unit **100** is thereby appropriately secured and connected to data logging unit **200**, such that data logging unit **200** can reliably send and obtain signals respectively to and from plates **111**, **112**, **113**, **114** of sensor unit **100**.

In order to correctly interpret the signals received from sensor unit **100**, it is necessary to have information about the sensor unit **100** which is connected to data logging unit **200**. In particular, different arrangements of plates and/or different dimensions of sensor unit **100** will give rise to different changes in impedance under different conditions in an absorbent article with which sensor unit **100** is provided.

However, the configuration of data logging unit **200** shown in FIG. 5, and particularly the configuration of terminal region **220** with associated terminals **231**, **232**, **233**, **234** allows for a variety of sensor units **100** with a similarly-

13

configured pads **151, 152, 153, 154** in terminal region **140**, but having different configurations of plates **111, 112, 113, 114** to be used in conjunction with data logging unit **200**.

It is possible for a user, a carer, or an operator of the system, to manually record which sensor **100** is associated with which a particular data logging unit **200**, so that this information can be used to interpret the results from the data logging unit. However, it is advantageous if data logging unit **200** is able to obtain information about the sensor unit **100** to which it is connected such that this information is intermediately available, for use in further automated data-processing operations, and to avoid errors.

Accordingly, data logging unit **200** implements a method of identifying sensor unit **100** as will be further described in relation to FIGS. **8** to **15** below.

Inside enclosure **210** of data logging unit **200** is provided a measurement unit MEAS which is schematically depicted in FIG. **8** as part of the overall data logging unit **200**.

Measurement unit MEAS comprises microcontroller MC which has a plurality of analog measurement terminals **A0** to **A15** and a plurality of digital sense terminals **D0** to **D7**. Microcontroller MC is supplied with power from power supply PWR, and has selected terminals of analog sense terminals **A0** to **A15** and digital terminals **D0** to **D7** connected, by means of conductive wiring, to a series of terminals **230** provided at terminal region **220** of enclosure **210**.

Of these terminals, a subset of terminals **230a** are connected to a subset of analog sense terminals **A0** to **A15**, a subset of terminals **230c** are connected to digital terminals **D0** to **D2**, and one of the terminals **230b** is connected to a ground GND of measurement unit MEAS.

In the configuration shown in FIG. **8**, the digital terminals **D0** to **D7** of microcontroller MC, which are connected to terminals **230c** of terminal region **220**, are also connected individually to the power supply PWR by means of respective pull-up resistors **R1, R2, R3**. Accordingly, in an open-circuit state, terminals **230c** are maintained at an elevated potential, corresponding to a logical HIGH or binary 1.

Terminals **230a**, which are connected to the analog sense terminals **A0** to **A15** of microcontroller MC, are capable of being driven with potentials, for example, static or oscillating potentials, and are capable of performing measurements of potentials so as to measure simple or complex impedances between any of terminals **230a**. Terminals **230a** are thus referred to as measurement terminals.

For cooperation with the measurement unit **100** as shown in FIG. **8** and description in relation thereto, FIG. **9** shows a schematic diagram of the sensor unit **100**. In the configuration shown in FIG. **9**, six sense pads are provided, being pads **111, 112, 113, 114, 115, 116**. As described above, the number and layout of the pads may be varied depending on the application.

Pads **111, 112, 113, 114, 115, 116** are connected by respective conductive traces to terminal region **140**. In particular, of the terminals present at terminal region **140**, a set of terminals **150a** are individually connected to the respective pads **111, 112, 113, 114, 115, 116**. These terminals **150a**, as well as terminals **230a**, are referred to as measurement terminals.

A terminal **150b** is provided and connected to the grounding plate **130**.

Finally, a set of terminals **150c** are provided, of which a first and a third terminal in sequential order are connected to ground, and a second terminal is left unconnected. In other words, it is provided as an open circuit.

14

Accordingly, when sensor unit **100** shown in FIG. **9** is connected to a data logging **200** having a measurement unit MEAS as shown in FIG. **8**, ground terminal **230b** connects to ground terminal **150b**, thereby to provide a reference ground from the sensor unit, sense terminals **230a** connect to sense terminals **150a**, thereby to allow measurement unit MEAS to measure impedances between selected pairs of pads **111, 112, 113, 114, 115, 116**, and terminals **230c** of data logging unit **200** connect to corresponding terminals **150c** of sensor unit **100** such that the sequential first and third terminals **1** and **3** which are connected together at the sensor-unit-side, and which are moreover together connected to ground, reach a potential associated with ground, in other words, a digital LOW or binary 0 potential. In contrast, the sequential second terminal of terminals **230c**, **150c** is maintained at the digital high potential associated with power supply PWR by means of the action of pull-up resistor **R2**.

Of terminals **150c**, the terminals which are connected to ground and the terminals which are left open determine the potentials, in terms of logical high or low potentials, which are detected at digital terminals **D0** to **D7** of microcontroller MC. These terminals may be used to identify a characteristic of the sensor strip **100** which is provided to data logging unit **200**. Terminals **150c**, as well as terminals **230c**, therefore are referred to as identification terminals.

As shown in more detail in FIG. **10**, for ease of comparison with later-described embodiments, the connection together or certain of identification terminals **150c** may encode a binary number, for example, a binary triplet. Any of digital terminals **D0** to **D7** may be used for this purpose.

To demonstrate this, FIG. **9** shows a variant configuration in which a subset of terminals **D5** to **D7**, instead of **D0** to **D2** are used for the identification of sensor **100**.

In the configuration shown in FIGS. **9** and **10**, the first and the third sequential identification terminals **150c** are connected together and to ground, while the second sequential terminal is left as an open circuit. This may correspond to a sequence of binary digits 010, or in decimal notation **2** (two). Of course, in an alternative configuration, each of the first and third terminals could simply have an independent connection to ground.

Connecting together different terminals of identification terminals **150c** and connecting these terminals to ground encodes different decimal numbers as a sequence of three binary digits. For example, the table below gives example possibilities for how a series of three binary digits presented on terminals **150c** by means of connecting together certain terminals to ground to represent a digital LOW (or a binary 0), and leaving of certain terminals open to represent a digital HIGH (or a binary 1) could correspond to different lengths of sensor strip **100** suitable for different sizes types of absorbent article.

TABLE 1

Binary Sequence	Decimal Equivalent	Size
000	0	Test
001	1	Small adult
010	2	Medium adult
011	3	Large adult
100	4	Small baby
101	5	Medium baby
110	6	Large baby
111	7	No strip connected

15

Accordingly, with only three terminals, eight states of the sensor strip can be identified, including the state in which no strip is connected. Moreover, no separate components are required on the sensor unit **100** side, and the identification encoding may be performed simply by connecting certain terminals **150c** together, for example by conductive traces on flexible substrate **120**.

Accordingly, the sensor strip is robust even under deformation, as compared with a situation where additional components may be provided on sensor strip on sensor unit **100** to provide identification signals.

A further variant configuration is shown in FIG. **111**, in which identification terminals **230c** of terminal region **220** of data logger **200** are each individually connected to ground GND through a respective resistors **R1**, **R2**, **R3** which therefore act as pull-down resistors. Also, selected identification terminals **150c** of terminal region **140** of sensor unit **100** are connected together and are connected to a further terminal **150d**, which corresponds with a terminal **230d** of terminal region **220** of data logging unit **200** which is connected to the power supply. Terminals **230d** and **150d** may therefore be regarded as power supply terminals.

As a result of pull-down resistors **R1**, **R2**, **R3**, identification terminals **230C**, when in the open-circuit state, are maintained as digital LOW (or a binary 0). However, when connected to identification terminals **150D** which are connected together and, via power supply terminal **150C** and power supply terminal **230D** to the power supply PWR of data logging unit **200**, the selected identification terminals **230C** will be set to a potential corresponding to a digital HIGH (or a binary 1).

Again, in a similar manner as with regard to the embodiment variant of FIG. **10**, the selection of which terminals are connected to the power supply potential, and which are left in the open-circuit state, may be used to encode a characteristic of sensor **100** which is connected to data logging unit **200**.

In a further variant shown in FIG. **12**, five digital terminals **D3** to **D7** are connected to five identification terminals **230c** on terminal region **220** of data logging unit **200**, and each of these terminals is individually connected to the power supply PWR via a respective resistor **R1**, **R2**, **R3**, **R4**, **R5**. Accordingly, **R1**, **R2**, **R3**, **R4**, **R5** operate in a pull-up configuration.

On the sensor unit **100** side, a selected one of corresponding identification terminals **150c** provided at terminal region **140** of sensor unit **100** is maintained in an unconnected state, while the remaining identification terminals **150c** are connected to ground **130**.

Rather than using a binary encoding, this configuration uses a numerical encoding, in which the sequential number of the terminal **150c** which is not connected to ground encodes the type of sensor **100** which is connected. The decoding of the sensor type is simpler than the configuration of FIG. **12**, but a greater number of identification terminals **230c** is required to allow identification between a predetermined number of types of sensor unit **100** as compared with the binary encoding variants of FIGS. **10** and **11**. For example, with eight terminals in the embodiment of FIG. **12**, eight types of sensor unit **100** may be encoded, whereas with the variant of FIG. **10** or FIG. **11**, 2⁸ (two to the power of eight), or in other words 256 different configurations can be encoded with eight identification terminals.

A further variant is shown in FIG. **13**, in which, rather than grounding all identification terminals **150c** of sensor unit **100** except one, which is used to indicate the type of sensor unit **100** as in FIG. **12**, in the embodiment of FIG. **13**

16

all terminals **150c** are left as open circuit, except one, which is grounded and thus used to indicate the characteristic of the sensor unit **100** which is attached.

A further configuration is shown in FIG. **14**, as in the configuration of FIG. **11**, a power connection to the power supply PWR of data logger **200** is provided at a power supply **230d** terminal of terminal region **220** of data logging unit **220**. Power supply terminal **230d** is connected to power supply terminal **150d** of terminal region **140** on sensor unit **100**.

On the data-logging-unit side, identification terminals **220c** are connected to ground via resistors **R1**, **R2**, **R3**, **R4**, **R5**, which function as pull-down resistors, while on the sensor-unit-side, a selected one of identification terminals **150c** is connected via a conductive trace to power supply terminal **150d**, while the other identification terminals are left as open circuit. Accordingly, the selected one of the identification terminals **150c** is set at potential corresponding to digital HIGH, while the remaining identification terminals **150c** are maintained at digital LOW. The selection of the terminal which is set as digital LOW encodes the characteristic of sensor **100** which is used.

A further variant is shown in FIG. **15**, which corresponds to the configuration shown in FIG. **14**, except that all identification terminals **150c** on the sensor-unit-side are connected together and to power supply terminal **150d** so as to correspond to a digital HIGH, except one, which is maintained at an open circuit. As a result, the selection of which terminal is maintained as an open circuit, corresponding to a digital LOW, encodes the type of sensor **100**, which is connected.

In the above, disclosure has been made about a power supply PWR of the data logger **200**. This may be a replaceable battery, a non-user replaceable battery, a rechargeable battery, a disposable battery, or any alternative power supply which would meet the needs of supplying a data logging unit as shown and described.

Enclosure **210** of data logging unit **200** may be, for example, a plastic enclosure, which may be sealed, or which may be openable to allow maintenance and adjustment, for example, replacement of the power supply.

In the above, description has been made about the identification of a sensor unit which measures the status of an absorbent article by means of sensing plates which act as plates of a capacitor, thereby to measure an inductance associated with the presence of liquid in the absorbent core of the absorbent article. However, the above disclosure is not limited to such a configuration, and may be used in connection with any type of sensor unit which may be used to measure the absorbent state of an absorbent article.

For example, it is envisaged that the disclosure set forth herein may be equivalently be applied in the sensors which may operate on a resistive basis, which may react to the presence of certain chemicals, or otherwise, and which may be applied to absorbent articles either by penetrating the absorbent core with sense elements or by other means of sensory association of sense elements with an absorbent core of an absorbent article.

Moreover, although the disclosure has been made in respect of diapers, the present disclosure is not so limited, and the techniques herein can be applied to sensors for the sensing of an absorbent state of another absorbent article, such as absorbent pads, pant-type diapers, belt-type diapers, incontinence shields, wound dressings, sanitary goods, such as sanitary napkins, without limitation.

In the above disclosure, the data logging unit may be a stand-alone data logging unit, which is equipped with the

17

memory MRY and to which periodic measurements are stored. These periodic amendments may be later downloaded from the data logger to a management console, for example a personal computer, to evaluate a pattern of the absorbent state of the absorbent article over time. The data logging unit may be provided with a data retrieval interface such as a USB port for downloading over a wired connection, or may be provided with a short-range wireless data retrieval interface such as a Bluetooth module for downloading over a wireless configuration.

Alternatively, the data logging unit may measure the state of the absorbent article and may temporarily retain information about the state of the absorbent article in order to provide a notification on a change in the state of the absorbent article, for example by providing an audible (for example by a buzzer) or visible (for example by a light emitting diode, or LED) output signal from the data logging unit.

In another configuration, the data logging unit may be provided in association with a remote terminal, which may be a portable computing device such as a laptop, smartphone, or which may be a server or virtual server. The data logging unit may be connected by a wireless link to the remote terminal in order to periodically, on demand, or on detection on the change of absorbent status, signal the remote terminal in order to provide the results of the measurement to the remote terminal.

Such a configuration may be understood with reference to FIG. 16, in which data logging unit is provided, in addition to measurement unit MES, memory controller MCO, memory MRY, and transmission controller TX.

In the configuration of FIG. 16, data logger 200 may periodically make a measurement of the absorbent state of the absorbent article via the sensor unit 100. The result of this measurement may be recorded in a memory MRY by memory controller MCO. Then, according to a predetermined schedule, or when a predetermined number of measurements have been made, memory controller MCO may send the information stored in memory MRY, through transmission controller TX, to be transmitted on wireless link LNK to a reception controller RX of remote terminal 300.

Remote terminal 300 is provided with central processing unit CPU coupled to database DB and user interface UI. The data received from wireless link LNK by reception controller RX may be stored by the central processing unit CPU in database DB, which information may be retrieved by means of user interface UI.

Remote terminal 300 may be associated with a single data logging unit 200, or may be associated with a plurality of data logging units 200. In the former case, user interface controller UI may allow a user to query database DB to assess historical data on the absorbent status of the absorbent article associated with data logger 200. In the latter case, user interface controller UI may allow a user to query database DB to compare and analyse the results from a plurality of data loggers 200 associated with remote terminal 200.

In FIG. 16, data logger 200 and remote terminal 300 make up management system 400. In management system 400, memory MRY may be provided with a look-up table which enables measurement controller MCO to determine a characteristic of sensor unit 100 using the methods disclosed herein, such that the characteristic of sensor unit 100 may be stored together with the result of the measurement in memory MRY and may be transmitted together with the result of measurement to remote terminal 300 over wireless link LNK.

18

Alternatively, measurement unit MEAS may simply store the measurements of identification terminals 230c into memory MRY, which may be transmitted together with the measurement values over wireless link LNK. In such a configuration, database DB of the remote terminal 300 may include a look-up table enabling decoding of the identification information provided in identification terminals 230c so as to identify the characteristic of sensor unit 100 which is associated with the measurement.

In each of the above configurations, the measurement unit MEAS can determine the characteristic of the sensor unit 100 with each measurement made of the hygienic state of the absorbent article using sensor unit 100. In an alternative configuration, the determination may be performed once after a sensor unit 100 is connected to the data logger unit 200, which can be detected by a change in state of one of the identification terminals 230c.

The above disclosure has been made to specific examples, but one skilled in the art will appreciate that substantial modification and variation may be made without deviating from the various concepts in an advantageous configurations, devices, methods and systems herein disclosed and described. Accordingly, the present invention is to be understood as not being limited to the embodiments herein shown and described, but to be determined with reference to the appended claims.

What is claimed is:

1. A data logger unit for receiving data from a sensor unit provided to an absorbent article, the data logger unit comprising a logger-side terminal portion and a measurement module electrically connected to at least one measurement terminal of the logger-side terminal portion, the logger terminal portion being adapted for engagement with a sensor-side terminal portion of the sensor unit thereby to connect the sensor unit and the data logger unit together; the measurement module being arranged to perform an electrical measurement via the at least one measurement terminal of the logger-side terminal portion; the data logger unit having a plurality of identification terminals at the logger-side terminal portion electrically connected to the measurement module; the measurement module being configured to perform a measurement of the plurality of identification terminals to identify a characteristic property of the sensor unit; and the characteristic property of the sensor unit being encoded in the electrical potentials of the identification terminals.
2. The data logger unit of claim 1, the logger-side terminal portion having a reference terminal; the measurement module being configured to provide a reference potential to the reference terminal of the logger-side terminal portion; and the characteristic property of the sensor unit being encoded in the potential at each of the identification terminals of the logger-side terminal portion as compared with the reference potential.
3. The data logger unit of claim 1, wherein a resistor of the data logger unit is electrically connected between each of the identification terminals of the logger-side terminal portion and a conductor of the data logger unit maintained at a potential provided by the measurement module which is different from the reference potential.
4. The data logger unit of claim 1, wherein the reference potential is a ground potential of the measurement module.

19

5. The data logger unit of claim 4, wherein the reference terminal of the logger-side terminal portion is a ground reference terminal; and the ground reference terminal is connected by a conductor of the data logger unit to a ground of the measurement module.
6. The data logger unit of claim 1, wherein the reference potential is a potential different from a ground potential of the measurement module.
7. The data logger unit of claim 1, wherein the reference terminal of the logger-side terminal portion is a supply terminal; and the supply terminal is electrically connected by a conductor of the data logger unit to a supply potential of the measurement module.
8. The data logger unit of claim 7, wherein the logger-side terminal portion has a ground terminal; and the ground terminal of the logger-side terminal portion is connected to a ground potential of the measurement module by a conductor of the data logger unit.
9. The data logger unit of claim 7, wherein the characteristic property of the sensor unit is determined by identification of a single terminal, among the identification terminals of the logger-side terminal portion, as having the reference potential, the identified terminal correlating with the characteristic property.
10. The data logger unit of claim 1, wherein the measurement module is configured to determine the characteristic property of the sensor unit by identification of a set of terminals, among the identification terminals of the logger-side terminal portion, as having the reference potential, the set of identified terminals correlating with the characteristic property.
11. The data logger unit of claim 2, wherein the potentials of the identification terminals define a sequence of binary digits, and wherein the data logger unit decodes a value correlating with the characteristic property from the sequence of binary digits.
12. The data logger unit of claim 1, wherein the data logger unit is detachably attachable to the sensor unit.
13. The data logger unit of claim 1, wherein the data logger unit is detachably attachable to the absorbent article.
14. The data logger unit of claim 1, wherein the measurement module is adapted to repeat performing the electrical measurement after the data logger unit is detached from the sensor unit and attached to another sensor unit.
15. A sensor unit for an absorbent article for connection to a data logger unit to determine a hygiene state of the absorbent article,
the sensor unit comprising a sensor-side terminal portion and at least one sense element electrically connected to at least one measurement terminal of the sensor-side terminal portion;
the sensor-side terminal portion being adapted for engagement with a logger-side terminal portion of the data logger unit thereby to connect the sensor unit and the data logger unit;
the sensor terminal portion having a plurality of identification terminals at the sensor-side terminal portion;
the identification terminals of the sensor-side terminal portion being configured to provide, by electrical measurement of the plurality of identification terminals, a characteristic property of the sensor unit; and
the characteristic property of the sensor unit being encoded in the electrical potentials of the identification

20

- terminals of the sensor-side terminal portion when connected to the data logger unit.
16. The sensor unit of claim 15, the sensor terminal portion having a reference terminal; at least one of the identification terminals of the sensor-side terminal portion being electrically connected via a conductor of the sensor to the reference terminal of the sensor-side terminal portion; and the characteristic property of the sensor unit being encoded in the potential at each of the identification terminals of the sensor-side terminal portion as compared with the reference potential.
17. The sensor unit of claim 16, wherein one or more of the identification terminals of the sensor-side terminal portion are electrically connected by a conductor of the sensor unit to the reference terminal of the sensor-side terminal portion, and the remaining identification terminals of the sensor-side terminal portion are not electrically connected to the sensor reference terminal.
18. The sensor unit of claim 16, wherein the reference terminal of the sensor-side terminal portion is a ground reference terminal; and one or more of the identification terminals of the sensor-side terminal portion are electrically connected together and to the ground reference terminal of the sensor-side terminal portion by a conductor of the sensor unit.
19. The sensor unit of claim 16, wherein the reference terminal of the sensor-side terminal portion is a supply terminal; and one or more of the identification terminals of the sensor-side terminal portion are electrically connected together and to the sensor supply terminal of the sensor-side terminal portion by a conductor of the sensor.
20. The sensor unit of claim 19, wherein the sensor-side terminal portion has a ground reference terminal.
21. The sensor unit of claim 15, wherein the characteristic property of the sensor unit is determined by identification of a single terminal, among the sensor identification terminals of the sensor-side terminal portion, as having the reference potential, the identified terminal correlating with the characteristic property.
22. The sensor unit of claim 15, wherein the characteristic property of the sensor unit is determined by identification of a plurality of terminals of the sensor-side terminal portion, among the identification terminals of the sensor-side terminal portion, as having the reference potential, the set of identified terminals correlating with the characteristic property.
23. The sensor unit of claim 15, wherein the potentials of the identification terminals of the sensor-side terminal portion define a sequence of binary digits, and wherein the sequence of binary digits decodes to a value correlating with the characteristic property.
24. The sensor unit of claim 15, wherein the sense elements are provided to a flexible substrate.
25. The sensor unit of claim 24, wherein the flexible substrate is elongate along an axis of elongation, and wherein the sense elements comprise a plurality of conductive plates arranged along the axis of elongation of the flexible substrate.
26. The sensor unit of claim 25, wherein the flexible substrate is elongate along an axis of elongation, and wherein the sense elements comprise one or more pairs of elongate conductive plates, each pair of conductive plates

21

being arranged with one plate of the pair of conductive plates on one side of the axis of elongation, and the other plate of the pair of conductive plates on the other side of the axis of elongation in a direction crossing the axis of elongation.

27. The sensor unit of claim 24, wherein the sense elements are arranged on one surface of the flexible substrate and a conductive region is arranged on the other surface of the flexible substrate to the side on which the one or more pairs of conductive plates are arranged so as to underlie the sense elements.

28. The sensor unit of claim 27, wherein the conductive plate is connected to a ground terminal of the sensor-side terminal portion.

29. The sensor unit of claim 15, wherein the sensor unit is detachably attachable to the data logger unit.

30. The sensor unit of claim 15, wherein the sensor unit is detachably attachable to the absorbent article.

31. The sensor unit of claim 15, wherein the sensor unit is configured to detect the presence of body fluids in an absorbent article in proximity to the sensor unit in a non-contact manner.

32. A plurality of interchangeable sensor units according to claim 15, each having a common configuration of sensor-side terminal portion being adapted for engagement with a logger-side terminal portion of a common data logger unit such that the sensor units may be exchanged in connection with the data logger unit, the characteristic property being a characteristic property which differs among the interchangeable sensor units, and which is uniquely specified by the electrical potentials of the identification terminals of the sensor-side terminal portion of each sensor unit when connected to the data logger unit.

33. The plurality of interchangeable sensor units according to claim 32, the characteristic property being a length in an elongate direction of the sensor unit.

34. The plurality of interchangeable sensor units according to claim 32, the characteristic property being an electrical property associated with the at least one sense element.

35. The plurality of interchangeable sensor units according to claim 34, the at least one sense element comprising two elongate sense elements arranged parallel to one another, the characteristic property being a capacitance between the sense elements.

36. The plurality of interchangeable sensor units according to claim 32, the characteristic property being a dimension associated with the at least one sense element.

37. The plurality of interchangeable sensor units according to claim 32, being adapted for detachable attachment to the common data logger unit.

38. An absorbent article management system comprising:
a data logger unit, comprising:

a logger-side terminal portion and a measurement module electrically connected to at least one measurement terminal of the logger-side terminal portion, the logger terminal portion being adapted for engagement with a sensor-side terminal portion of the sensor unit thereby to connect the sensor unit and the data logger unit together;

the measurement module being arranged to perform an electrical measurement via the at least one measurement terminal of the logger-side terminal portion;

the data logger unit having a plurality of identification terminals at the logger-side terminal portion electrically connected to the measurement module;

22

the measurement module being configured to perform a measurement of the plurality of identification terminals to identify a characteristic property of the sensor unit; and

the characteristic property of the sensor unit being encoded in the electrical potentials of the identification terminals;

a sensor unit comprising:

a sensor-side terminal portion and at least one sense element electrically connected to at least one measurement terminal of the sensor-side terminal portion;

the sensor-side terminal portion being adapted for engagement with a logger-side terminal portion of the data logger unit thereby to connect the sensor unit and the data logger unit;

the sensor terminal portion having a plurality of identification terminals at the sensor-side terminal portion;

the identification terminals of the sensor-side terminal portion being configured to provide, by electrical measurement of the plurality of identification terminals, a characteristic property of the sensor unit;

the characteristic property of the sensor unit being encoded in the electrical potentials of the identification terminals of the sensor-side terminal portion when connected to the data logger unit; and

the sensor unit being provided to an absorbent article such that the at least one sense element is arranged to determine a hygienic state of the absorbent article;

the data logger unit being adapted to perform the method of claim 1 in a state in which the data logger unit is connected to the sensor unit;

the data logger unit periodically performing an electrical measurement of the at least one sense element via the at least one measurement terminal of the sensor-side terminal portion and the at least one measurement terminal of the logger-side terminal portion and associating information about the result of the electrical measurement with information about the electrical potential of the identification terminals of the sensor-side terminal portion for identifying the characteristic property of the sensor unit.

39. The absorbent article management system according to claim 38, wherein the data logger unit comprises a data storage unit and wherein the data logger unit is adapted to store information about the result of the electrical measurement in association with information for identifying the characteristic property of the sensor unit.

40. The absorbent article management system according to claim 38, further comprising a remote terminal and wherein the data logger unit comprises a communication unit adapted to transmit data to the remote terminal, and wherein the communication unit is adapted to transmit information about the result of the electrical measurement to the communication unit in association with information for identifying the characteristic property of the sensor unit.

41. The absorbent article management system according to claim 40, wherein the remote terminal comprises a database and wherein the database is adapted to store information about the result of the electrical measurement in association with information for identifying the characteristic property of the sensor unit.

42. The absorbent article management system according to claim 38, wherein the data logger unit is adapted to decode the electrical potentials of the identification terminals of the logger-side terminal portion to provide information about the characteristic property.

23

43. The absorbent article management system according to claim 40, wherein the remote terminal is adapted to decode the electrical potentials of the identification terminals of the logger-side terminal portion to provide information about the characteristic property.

5

* * * * *

24