

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12399551
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Lee; Eunkyung et al.

Wearable device for executing application based on information obtained by tracking external object and method thereof

Abstract

A processor of a wearable device is provided. The processor may identify an external object included in a displaying area of a display by using a camera. The processor may display a first visual object representing an application corresponding to the external object based on the location of the external object in the displaying area. The processor may obtain at least one of first information associated with a path of the external object moved on the plane, or second information including at least one stroke drawn by the external object, while the first visual object is displayed. The processor may display a second visual object for executing the application by using information, selected among the first information or the second information, based on the location, according to the attribute assigned to the external object.

Inventors: Lee; Eunkyung (Suwon-si, KR), Moon; Harin (Suwon-si, KR), Park; Wanje (Suwon-si, KR), Kang; Jiyoung (Suwon-si, KR), Lee; Jaehan (Suwon-si, KR), Lee; Chaekyung (Suwon-si, KR)

Applicant: Samsung Electronics Co., Ltd. (Suwon-si, KR)

Family ID: 1000008777453

Assignee: Samsung Electronics Co., Ltd. (Suwon-si, KR)

Appl. No.: 18/455218

Filed: August 24, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240143067 A1	May. 02, 2024

Foreign Application Priority Data

KR	10-2022-0144088	Nov. 01, 2022
----	-----------------	---------------

Related U.S. Application Data

continuation parent-doc WO PCT/KR2023/011313 20230802 PENDING child-doc US 18455218

Publication Classification

Int. Cl.: **G06F3/01** (20060101); **G06F3/00** (20060101); **G06Q10/109** (20230101); **G06T7/20** (20170101); **G06T11/60** (20060101); **G06T19/00** (20110101)

U.S. Cl.:

CPC **G06F3/011** (20130101); **G06Q10/109** (20130101); **G06T7/20** (20130101); **G06T11/60** (20130101); **G06T19/006** (20130101); G06F3/005 (20130101)

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
8633946	12/2013	Cohen	345/631	A63F 13/323
10120437	12/2017	Lin	N/A	H04N 21/41407
10409443	12/2018	Wright et al.	N/A	N/A
10848745	12/2019	Linde et al.	N/A	N/A
11460988	12/2021	Lee et al.	N/A	N/A
11501504	12/2021	Rohan	N/A	G06F 3/011
11635805	12/2022	Lee et al.	N/A	N/A
11681409	12/2022	Edwards	715/852	G06F 3/011
2001/0024193	12/2000	Fahraeus	345/173	G06F 3/0321
2007/0273644	12/2006	Mondine Natucci	345/156	G06T 19/006
2010/0306649	12/2009	Russ	715/810	G06F 3/04883
2013/0051615	12/2012	Lim et al.	N/A	N/A
2013/0222381	12/2012	Di Censo	345/419	G06T 19/006
2014/0089855	12/2013	Kim et al.	N/A	N/A
2014/0267011	12/2013	Devries	345/156	G06F 3/017
2014/0267770	12/2013	Gervautz	709/219	H04N 23/69
2015/0022444	12/2014	Ooi	345/156	G06V 20/20
2015/0185825	12/2014	Mullins	345/633	G06F 3/0304
2015/0205351	12/2014	Osterhout	345/156	G06F 3/03545
2016/0034027	12/2015	Sheng	345/173	G06F 3/04886

2016/0085422	12/2015	Lee	715/810	G06T 11/60
2016/0139691	12/2015	Li	345/179	G06F 40/171
2016/0224657	12/2015	Mullins	N/A	G06F 16/951
2018/0261011	12/2017	Kollencheri Puthenveetil	N/A	G06F 16/435
2019/0318545	12/2018	Sholudko et al.	N/A	N/A
2019/0324528	12/2018	Williams	N/A	G06F 18/40
2019/0339840	12/2018	Park	N/A	G10L 15/00
2021/0382605	12/2020	Edwards	N/A	G06F 3/04815

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
10-0360477	12/2002	KR	N/A
10-1343609	12/2013	KR	N/A
10-2014-0043961	12/2013	KR	N/A
10-2015-0063699	12/2014	KR	N/A
10-2019-0134975	12/2018	KR	N/A
10-2020-0055010	12/2019	KR	N/A
10-2020-0070551	12/2019	KR	N/A
10-2020-0076325	12/2019	KR	N/A
10-2248474	12/2020	KR	N/A
10-2021-0123156	12/2020	KR	N/A
10-2022-0037837	12/2021	KR	N/A
10-2393295	12/2021	KR	N/A
10-2412307	12/2021	KR	N/A

OTHER PUBLICATIONS

https://www.youtube.com/watch?v=04v_v1gnyO8, Nov. 2005. cited by applicant
Peter Vandoren et al., FluidPaint: an Interactive Digital Painting System using Real Wet Brushes, Hasselt University—tUL—IBBT, Expertise Centre for Digital Media, 3590 Diepenbeek—Belgium, Nov. 2009. cited by applicant
International Search Report with English translation and Written Opinion dated Nov. 15, 2023; International Appln. No. PCT/KR2023/011313. cited by applicant

Primary Examiner: Harris; Dorothy

Attorney, Agent or Firm: Jefferson IP Law, LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION(S) (1) This application is a continuation application, claiming priority under § 365(c), of an International application No. PCT/KR2023/011313, filed on Aug. 2, 2023, which is based on and claims the benefit of a Korean patent application number 10-2022-0144088, filed on Nov. 1, 2022, in the Korean Intellectual Property Office, and of a Korean patent application number 10-2022-0170126, filed on Dec. 7, 2022, in the Korean Intellectual Property Office, the disclosure of each of which is incorporated by reference herein in its entirety.

BACKGROUND

Technical Field

(1) The disclosure relates to a wearable device for executing an application based on information obtained by tracking an external object and method thereof.

Description of Related Art

(2) In order to provide an enhanced user experience, an electronic device providing an augmented reality (AR) service displaying information generated by a computer in association with an external object in the real-world is being developed. The electronic device may be a wearable device that may be worn by a user. For example, the electronic device may be an AR glasses and/or a head-mounted device (HMD).

(3) The above information is presented as background information only to assist with an understanding of the disclosure. No determination has been made, and no assertion is made, as to whether any of the above might be applicable as prior art with regard to the disclosure.

SUMMARY

(4) Aspects of the disclosure are to address at least the above-mentioned problems and/or disadvantages and to provide at least the advantages described below. Accordingly, an aspect of the disclosure is to provide a wearable device for executing an application based on information obtained by tracking an external object and method thereof.

(5) Additional aspects will be set forth in part in the description which follows and, in part, will be apparent from the description, or may be learned by practice of the presented embodiments.

(6) In accordance with an aspect of the disclosure, a wearable device may be provided. The wearable device includes a display, a camera, and a processor. The processor may be configured to identify, by using the camera, an external object included in a displaying area of the display. The processor may be configured to display a first visual object representing an application corresponding to the external object based on a location of the external object in the displaying area. The processor may be configured to obtain, while displaying the first visual object, at least one of first information associated with a path of the external object moved on a plane, or second information including at least one stroke drawn by the external object. The processor may be configured to display, based on the location, a second visual object for executing the application by using information that is identified among the first information or the second information according to an attribute assigned to the external object.

(7) A method of a wearable device according to an embodiment may comprise identifying, by using a camera of the wearable device, an external object included in a displaying area of a display of the wearable device. The method may comprise displaying a first visual object representing an application corresponding to the external object based on a location of the external object in the displaying area. The method may comprise obtaining, while displaying the first visual object, at least one of first information associated with a path of the external object moved on a plane, or second information including at least one stroke drawn by the external object. The method may comprise displaying, based on the location, a second visual object for executing the application by using information that is identified among the first information or the second information according to an attribute assigned to the external object.

(8) According to an embodiment, a wearable device may comprise a display, a memory, and a processor. The processor may be configured to display, in a display of the wearable device, list of a plurality of applications stored in a memory of the wearable device. The processor may be configured to obtain, based on an input indicating overlapping a visual object representing a first application included in the list on an external object included in a displaying area of the display, an attribute for executing the first application by using the external object. The processor may be configured to obtain, after obtaining the attribute, at least one of first information associated with a path of the external object moved on a plane, or second information including at least one stroke

drawn by the external object. The processor may be configured to execute, the first application by using information identified by the attribute among the first information or the second information.

(9) A method of a wearable device according to an embodiment may comprise displaying, in a display of the wearable device, list of a plurality of applications stored in a memory of the wearable device. The method may comprise obtaining, based on an input indicating overlapping a visual object representing a first application included in the list on an external object included in a displaying area of the display, an attribute for executing the first application by using the external object. The method may comprise obtaining, after obtaining the attribute, at least one of first information associated with a path of the external object moved on a plane, or second information including at least one stroke drawn by the external object. The method may comprise executing, the first application by using information identified by the attribute among the first information or the second information.

(10) Other aspects, advantages, and salient features of the disclosure will become apparent to those skilled in the art from the following detailed description, which, taken in conjunction with the annexed drawings, discloses various embodiments of the disclosure.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The above and other aspects, features, and advantages of certain embodiments of the disclosure will be more apparent from the following description taken in conjunction with the accompanying drawings, in which:

(2) FIG. 1 illustrates an operation in which a wearable device obtains information associated with an external object, according to an embodiment of the disclosure;

(3) FIG. 2 illustrates a flowchart for a wearable device according to an embodiment of the disclosure;

(4) FIG. 3A illustrates a perspective view of a wearable device according to an embodiment of the disclosure;

(5) FIG. 3B illustrates one or more hardware disposed in a wearable device according to an embodiment of the disclosure;

(6) FIGS. 4A and 4B illustrate an exterior of a wearable device according to an embodiment of the disclosure;

(7) FIG. 5 is a block diagram of a wearable device according to an embodiment of the disclosure;

(8) FIGS. 6A, 6B, 6C, and 6D illustrate an operation of identifying an input indicating that a wearable device registers an external object according to an embodiment of the disclosure;

(9) FIG. 7 illustrates a flowchart for a wearable device according to an embodiment of the disclosure;

(10) FIGS. 8A and 8B illustrate a user interface (UI) displayed by a wearable device based on an external object according to an embodiment of the disclosure;

(11) FIGS. 9A, 9B, and 9C illustrate an operation in which a wearable device executes an application based on information obtained by tracking an external object according to an embodiment of the disclosure;

(12) FIG. 10 illustrates an operation in which a wearable device switches a camera for tracking an external object according to an embodiment of the disclosure;

(13) FIG. 11 illustrates a UI displayed by a wearable device based on information obtained by tracking an external object, according to an embodiment of the disclosure;

(14) FIGS. 12A and 12B illustrate an operation in which a wearable device executes an application based on information obtained by tracking an external object according to an embodiment of the disclosure;

- (15) FIG. 13 illustrates an operation in which a wearable device executes an application based on information obtained by tracking an external object according to an embodiment of the disclosure;
- (16) FIG. 14 illustrates an operation in which a wearable device executes an application based on information obtained by tracking an external object according to an embodiment of the disclosure;
- (17) FIGS. 15A and 15B illustrate an operation in which a wearable device executes a plurality of applications based on information obtained by tracking an external object according to an embodiment of the disclosure;
- (18) FIG. 16 illustrates a flowchart for a wearable device according to an embodiment of the disclosure;
- (19) FIG. 17 illustrates an operation in which a wearable device displays a UI for recommending at least one application based on information obtained by tracking an external object according to an embodiment of the disclosure;
- (20) FIG. 18 illustrates a flowchart for a wearable device according to an embodiment of the disclosure; and
- (21) FIG. 19 illustrates an operation in which a wearable device executes an application based on information obtained by an external electronic device, according to an embodiment of the disclosure.
- (22) Throughout the drawings, it should be noted that like reference numbers are used to depict the same or similar elements, features, and structures.

DETAILED DESCRIPTION

- (23) The following description with reference to the accompanying drawings is provided to assist in a comprehensive understanding of various embodiments of the disclosure as defined by the claims and their equivalents. It includes various specific details to assist in that understanding but these are to be regarded as merely exemplary. Accordingly, those of ordinary skill in the art will recognize that various changes and modifications of the various embodiments described herein can be made without departing from the scope of the disclosure. In addition, descriptions of well-known functions and constructions may be omitted for clarity and conciseness.
- (24) The terms and words used in the following description and claims are not limited to the bibliographical meanings, but, are merely used by the inventor to enable a clear and consistent understanding of the disclosure. Accordingly, it should be apparent to those skilled in the art that the following description of various embodiments of the disclosure is provided for illustration purpose only and not for the purpose of limiting the disclosure as defined by the appended claims and their equivalents.
- (25) It is to be understood that the singular forms “a,” “an,” and “the” include plural referents unless the context clearly dictates otherwise. Thus, for example, reference to “a component surface” includes reference to one or more of such surfaces.
- (26) It should be appreciated that various embodiments of the disclosure and the terms used therein are not intended to limit the technological features set forth herein to particular embodiments and include various changes, equivalents, or replacements for a corresponding embodiment. With regard to the description of the drawings, similar reference numerals may be used to refer to similar or related elements. It is to be understood that a singular form of a noun corresponding to an item may include one or more of the things, unless the relevant context clearly indicates otherwise. As used herein, each of such phrases as “A or B,” “at least one of A and B,” “at least one of A or B,” “A, B, or C,” “at least one of A, B, and C,” and “at least one of A, B, or C,” may include any one of, or all possible combinations of the items enumerated together in a corresponding one of the phrases. As used herein, such terms as “1st” and “2nd,” or “first” and “second” may be used to simply distinguish a corresponding component from another, and does not limit the components in other aspect (e.g., importance or order). It is to be understood that if an element (e.g., a first element) is referred to, with or without the term “operatively” or “communicatively”, as “coupled with,” “coupled to,” “connected with,” or “connected to” another element (e.g., a second element),

it means that the element may be coupled with the other element directly (e.g., wiredly), wirelessly, or via a third element.

(27) As used in connection with various embodiments of the disclosure, the term “module” may include a unit implemented in hardware, software, or firmware, and may interchangeably be used with other terms, for example, “logic,” “logic block,” “part,” or “circuitry”. A module may be a single integral component, or a minimum unit or part thereof, adapted to perform one or more functions. For example, according to an embodiment of the disclosure, the module may be implemented in a form of an application-specific integrated circuit (ASIC).

(28) FIG. 1 illustrates an operation in which a wearable device obtains information associated with an external object according to an embodiment of the disclosure.

(29) Referring to FIG. 1, a wearable device **101** according to an embodiment of the disclosure may include head-mounted display (HMD) that may be wearable on a head of a user **110**. Although an appearance of the wearable device **101** having the form of glasses is illustrated, the embodiment is not limited thereto. An example of the structure of the wearable device **101** wearable on the head of the user **110** will be described with reference to FIGS. 3A and 3B and/or 4A and 4B. One or more pieces of hardware included in the wearable device **101** are illustratively described with reference to FIG. 5.

(30) According to an embodiment of the disclosure, the wearable device **101** may execute a function associated with augmented reality (AR) and/or mixed reality (MR). Referring to FIG. 1, in a state in which the user **110** is wearing the wearable device **101**, the wearable device **101** may include at least one lens disposed adjacent to the eyes of the user **110**. The wearable device **101** may combine light emitted from the display of the wearable device **101** to ambient light passing through the lens. The displaying area of the display may be formed in a lens through which the ambient light passes. Since the wearable device **101** combines the ambient light and the light emitted from the display, the user **110** may see a mixed image of a real object recognized by the ambient light and a virtual object formed by the light emitted from the display.

(31) According to an embodiment of the disclosure, the wearable device **101** may execute a function associated with video see-through (VST) and/or virtual reality (VR). Referring to FIG. 1, in the state in which the user **110** is wearing the wearable device **101**, the wearable device **101** may include a housing covering the eyes of the user **110**. The wearable device **101** may include the display disposed on a first surface facing the eyes in the state. The wearable device **101** may include a camera disposed on a second surface opposite to the first surface. By using the camera, the wearable device **101** may obtain frames including the ambient light. The wearable device **101** may make the user **110** recognize the ambient light through the display, by outputting the frames in the display disposed on the first surface. The displaying area of the display disposed on the first surface may be formed by one or more pixels included in the display. The wearable device **101** may make the user **110** recognize the virtual object together with the real object recognized by ambient light, by synthesizing the virtual object in frames outputted through the display.

(32) Referring to FIG. 1, an example in which the wearable device **101** identifies the external object **130**, according to an embodiment of the disclosure, in the state worn by a user **110** is illustrated. In an example of FIG. 1, the wearable device **101** may make the user **110** recognize an external space based on the AR, the MR, or the VST. In the external space, the wearable device **101** may identify the external object **130**. Although the external object **130** having the shape of a pen is exemplarily illustrated, the embodiment is not limited thereto. The external object **130** may include an object registerable in the wearable device **101**. For example, the external object **130** may have a shape extended along a length direction, such as the pen and/or a stick, such as a tree branch. The embodiment is not limited thereto, and the external object **130** may have a shape of a polyhedron or may have a shape of a curved surface body. According to an embodiment of the disclosure, an example of an operation performed by the wearable device **101** to register the external object **130** will be described with reference to FIGS. 6A to 6D and/or 7.

(33) Referring to FIG. 1, an image shown by the user **110** wearing the wearable device **101** is illustrated. According to an embodiment of the disclosure, the wearable device **101** may identify the external object **130** mapped to the function of the application. The wearable device **101** may display the visual object **160** based on the location of the external object **130** in the displaying area of the display. The visual object **160** may have a shape of an icon of the application mapped to the external object **130**. The shape, size, and/or location of the visual object **160** displayed by the wearable device **101** is not limited to an embodiment of FIG. 1.

(34) According to an embodiment of the disclosure, the wearable device **101** may obtain information associated with the motion of the external object **130**. Referring to FIG. 1, a state in which the external object **130** is moved by a hand **140** is illustrated. For example, by using a camera (and/or a depth sensor) of the wearable device **101** disposed toward the external object **130**, the wearable device **101** may obtain first information associated with the path of the external object **130**. The first information may include a path of the external object **130** contacted on a plane **150** (e.g., a paper and/or a table). In case that the external object **130** is an object capable of generating a trace (e.g., at least one stroke) on the plane **150**, such as the pen and/or a pencil, the wearable device **101** may obtain second information including at least one stroke drawn by the external object **130** by using the camera. The wearable device **101** may obtain content (e.g., a handwriting and/or an image) generated by the motion of the external object **130** by performing optical character recognition (OCR) for the at least one stroke.

(35) According to an embodiment of the disclosure, the wearable device **101** may execute the application corresponding to the external object **130** based on the first information associated with the path of the external object **130** and/or the second information including at least one stroke drawn by the external object **130**. For example, the wearable device **101** may execute a function associated with the first information and/or the second information by executing the application registered in the external object **130**. The wearable device **101** may execute the application in response to an input indicating to select the visual object **160** including an icon representing the application. An operation in which the wearable device **101** executes the application registered to the external object **130** will be described with reference to FIGS. 8A, 8B, 9A to 9C, 10, 11, 12A, 12B, 13, 14, 15A, 15B, and 16. According to the application registered to the external object **130**, the wearable device **101** may execute various functions based on the stroke drawn by the external object **130** and/or the path of the external object **130**.

(36) Referring to FIG. 1, according to an embodiment of the disclosure, the wearable device **101** may be connected to an external electronic device, such as a terminal **120** and/or a server **122**. The terminal **120** may include, for example, a personal computer (PC), such as a laptop or a desktop, a smartphone, a smartpad, and/or a tablet PC. The server **122** may support a function (e.g., the OCR) for analyzing the path of the external object **130** and/or the stroke drawn by the external object **130**. The wearable device **101**, the terminal **120** and/or the server **122** may be connected to each other through a wired network and/or a wireless network. The wired network may include a network, such as the Internet, a local area network (LAN), a wide area network (WAN), Ethernet, or a combination thereof. The wireless network may include a network, such as long term evolution (LTE), new radio (fifth generation (5G) NR), wireless fidelity (Wi-Fi), Zigbee, near field communication (NFC), Bluetooth, Bluetooth low-energy (BLE), or a combination thereof. Although the wearable device **101**, the terminal **120**, and the server **122** are directly connected, the wearable device **101**, the terminal **120**, and the server **122** are illustrated as directly connected, the wearable device **101**, the terminal **120**, and the server **122** may be indirectly connected through an intermediate node (e.g., one or more routers and/or access points (APs)).

(37) As described above, according to an embodiment of the disclosure, the wearable device **101** may track the path of the external object **130** and/or the at least one stroke drawn by the external object **130**. Based on the tracked path and/or stroke, the wearable device **101** may execute at least

one application corresponding to the external object **130**. At least one application matched to the external object **130** may be set by an attribute assigned to the external object **130**. The wearable device **101** may execute the at least one application based on any one of the path or the stroke selected by the attribute. As the at least one application is executed, the wearable device **101** may support the user **110** to control the wearable device **101** by using the external object **130**. Although the external object **130** does not include circuitry for communicating with the wearable device **101**, such as the pen and/or the pencil, the wearable device **101** may visualize information indicated by the external object **130**.

(38) Hereinafter, an example of an operation of the wearable device **101** according to an embodiment will be described with reference to FIG. 2.

(39) FIG. 2 illustrates a flowchart for a wearable device according to an embodiment of the disclosure. The wearable device of FIG. 2 may include the wearable device **101** of FIG. 1.

(40) Referring to FIG. 2, in operation **210**, according to an embodiment of the disclosure, the wearable device may identify an external object and a function mapped to the external object. For example, a wearable device may identify the external object shown by a user (e.g., a user **110** of FIG. 1) wearing the wearable device, such as the external object **130** of FIG. 1. In order to identify the external object shown by the user wearing the wearable device, the wearable device may include at least one camera disposed toward a designated direction. The wearable device may identify the external object by using the camera. In case that the external object is an external object registered in the wearable device, the wearable device may identify the function mapped to the external object. That the external object is registered in the wearable device may mean that the attribute assigned to the external object is stored in the wearable device. Based on the attribute, the wearable device may identify the function.

(41) Referring to FIG. 2, in operation **220**, according to an embodiment of the disclosure, the wearable device may obtain information on a motion of the external object or at least one stroke generated by the external object, based on whether the external object is identified. The motion of the external object may include the motion of the external object contacted on a plane (e.g., a plane **150** of FIG. 1) of an external space including the external object. The at least one stroke may be generated as a material (e.g., ink and/or graphite) included in the external object is adhered on the plane. The wearable device may selectively track one of the motion or the at least one stroke based on the attribute assigned to the external object. In order to obtain the information, the wearable device may communicate with an external electronic device (e.g., a terminal **120** and/or a server **122** of FIG. 1).

(42) In an embodiment of the disclosure, in order to obtain information on the motion of the external object, the wearable device may track a path of a portion (e.g., an end of the external object, and/or a surface) of the external object. Based on whether the portion of the external object is in contact with the plane, the wearable device may obtain first information associated with the path of the external object contacted on the plane. In the state of obtaining the first information, the wearable device may display one or more lines having a shape of the path on the display of the wearable device. The portion of the external object tracked by the wearable device may be set by an attribute assigned to the external object.

(43) In an embodiment of the disclosure, in order to obtain information on at least one stroke drawn by the external object, the wearable device may control a camera disposed toward the external object, among different cameras. The wearable device may identify at least one stroke drawn by the external object by using the camera. The wearable device may identify handwriting drawn by an external object based on the letter indicated by the at least one stroke. The embodiment is not limited thereto, and the wearable device may identify at least one figure indicated by the at least one stroke. The wearable device may communicate with the external electronic device to obtain text data (e.g., data encoded by a binary code, such as Unicode) corresponding to the handwriting.

(44) Referring to FIG. 2, in operation **230**, according to an embodiment of the disclosure, the

wearable device may execute a function mapped to the external object based on the obtained information. The function may be identified by an attribute assigned by the external object. The function may be supported by at least one application installed in the wearable device. According to an embodiment of the disclosure, the wearable device may visualize the result of executing the function to the user. The wearable device may execute the function based on an input indicating to select a visual object (e.g., a visual object **160** of FIG. **1**) displayed in the display. The visual object may be identified by the attribute. The wearable device may display the visual object based on a location of the external object in the display.

(45) As described above, according to an embodiment of the disclosure, the wearable device may register an object that does not support the function of communicating with the wearable device and may support the control of the wearable device based on the registered object. The wearable device may obtain electrical information (e.g., digital content) from non-electrical information on the external object by recognizing the motion of the external object, such as a pen or by recognizing at least one stroke drawn by the external object. Based on the electrical information, the wearable device may recognize an external object that cannot be directly connected to the wearable device and may obtain digital content from the recognized external object.

(46) Hereinafter, a structure of the wearable device for recognizing the external object according to an embodiment will be described with reference to FIGS. **3A** and **3B** and/or **4A** and **4B**.

(47) FIG. **3A** illustrates a perspective view of a wearable device according to an embodiment of the disclosure. A wearable device **300** of FIGS. **3A** and **3B** may be an example of the wearable device **101** of FIG. **1** and/or the wearable device of FIG. **2**.

(48) Referring to FIG. **3A**, according to an embodiment of the disclosure, the wearable device **300** may include at least one display **350** and a frame supporting the at least one display **350**.

(49) According to an embodiment of the disclosure, the wearable device **300** may be worn on a portion of a body of a user. The wearable device **300** may provide augmented reality (AR), virtual reality (VR), or mixed reality (MR) that mixes augmented reality and virtual reality to the user wearing the wearable device **300**. For example, the wearable device **300** may output a virtual reality image to the user through the at least one display **350** in response to the designated gesture of the user obtained through a motion recognition camera **340-2** of FIG. **3B**.

(50) According to an embodiment of the disclosure, the at least one display **350** in the wearable device **300** may provide visual information to the user. For example, the at least one display **350** may include a transparent or translucent lens. The at least one display **350** may include a first display **350-1** and/or a second display **350-2** spaced apart from the first display **350-1**. For example, the first display **350-1** and the second display **350-2** may be disposed at locations corresponding to the user's left and right eyes, respectively.

(51) FIG. **3B** illustrates one or more hardware disposed in a wearable device according to an embodiment of the disclosure.

(52) Referring to FIG. **3B**, the at least one display **350** may provide a user wearing the wearable device **300**, with visual information included in ambient light passing through the lens along with other visual information that is distinct from the visual information, by forming a displaying area on the lens. The lens may be formed based on at least one of a Fresnel lens, a pancake lens, or a multi-channel lens. The displaying area formed by the at least one display **350** may be formed on the second surface **332** among the first surface **331** and the second surface **332** of the lens. When the user wears the wearable device **300**, the ambient light may be transmitted to the user by being incident to the first surface **331** and passing through the second surface **332**. For another example, the at least one display **350** may display a virtual reality image to be combined with a real screen transmitted through the ambient light. The virtual reality image outputted from the at least one display **350** may be transmitted to the eyes of the user through one or more hardware included in the wearable device **300** (e.g., optical devices **382** and **384**), and/or at least one waveguides **333** and **334**.

(53) According to an embodiment of the disclosure, the wearable device **300** may include the waveguides **333** and **334** that are transmitted from the at least one display **350**, diffract light relayed by the optical devices **382** and **384**, and transmit it to the user. The waveguides **333** and **334** may be formed based on at least one of glass, plastic, or polymer. A nano pattern may be formed on at least a portion of the outside or inside of the waveguides **333** and **334**. The nano pattern may be formed based on a grating structure having a polygonal or curved shape. Light incident on one end of the waveguides **333** and **334** may be propagated to the other end of the waveguides **333** and **334** by the nano pattern. The waveguides **333** and **334** may include at least one of at least one diffraction element (e.g., a diffractive optical element (DOE), a holographic optical element (HOE)), and a reflection element (e.g., a reflective mirror). For example, the waveguides **333** and **334** may be disposed in the wearable device **300** to guide a screen displayed by the at least one display **350** to the eyes of the user. For example, the screen may be transmitted to the eyes of the user based on total internal reflection (TIR) generated in waveguides **333** and **334**.

(54) According to an embodiment of the disclosure, the wearable device **300** may analyze an object included in a real image collected through a photographing camera **340-1**, combine a virtual object corresponding to objects subject to augmented reality provision among the analyzed object and display it on the at least one display **350**. The virtual object may include at least one of text and images for various information associated with the object included in the real image. The wearable device **300** may analyze the object based on a multi-camera, such as a stereo camera. For the object analysis, the wearable device **300** may execute time-of-flight (ToF) and/or simultaneous localization and mapping (SLAM) supported by the multi-camera. The user wearing the wearable device **300** may view an image displayed on the at least one display **350**.

(55) According to an embodiment of the disclosure, the frame may have a physical structure in which the wearable device **300** may be worn on the body of the user. According to an embodiment of the disclosure, the frame may be configured so that when the user wears the wearable device **300**, the first display **350-1** and the second display **350-2** may be located in location corresponding to the user's left and right eyes. The frame may support the at least one display **350**. For example, the frame may support the first display **350-1** and the second display **350-2** to be located in location corresponding to the user's left and right eyes.

(56) According to an embodiment of the disclosure, referring to FIG. 3A, in case that the user wears the wearable device **300**, at least a portion of the frame may include an area **320** in contact with a portion of the body of the user. For example, the area **320** in contact with a portion of the body of the user of the frame may include an area in contact with a portion of the nose of the user, a portion of the ear of the user, and a portion of the side of the face of the user, in which the wearable device **300** contacts. According to an embodiment of the disclosure, the frame may include a nose pad **310** which is contacted on the portion of the body of the user. When the wearable device **300** is worn by the user, the nose pad **310** may be contacted on the portion of the nose of the user. The frame may include a first temple **304** and a second temple **305** which are contacted on another portion of the body of the user, which is distinct from a portion of the body of the user.

(57) In an embodiment of the disclosure, the frame may include a first rim **301** surrounding at least a portion of the first display **350-1**, a second rim **302** surrounding at least a portion of the second display **350-2**, a bridge **303** disposed between the first rim **301** and the second rim **302**, a first pad **311** disposed along a portion of the edge of the first rim **301** from one end of the bridge **303**, a second pad **312** disposed along a portion of the edge of the second rim **302** from the other end of the bridge **303**, the first temple **304** extending from the first rim **301** and fixed to a portion of the ear of the wearer, and the second temple **305** extending from the second rim **302** and fixed to a portion of the ear opposite to the ear. The first pad **311** and the second pad **312** may be in contact with a portion of the nose of the user, and the first temple **304** and the second temple **305** may be in contact with a portion of the face of the user and a portion of the ear of the user. The temples **304** and **305** may be rotatably connected to the rim through the hinge units **306** and **307** of FIG. 3B.

The first temple **304** may be rotatably connected with respect to the first rim **301** through a first hinge unit **306** disposed between the first rim **301** and the first temple **304**. The second temple **305** may be rotatably connected with respect to the second rim **302** through a second hinge unit **307** disposed between the second rim **302** and the second temple **305**. According to an embodiment of the disclosure, the wearable device **300** may identify an external object (e.g., a fingertip of the user) touching the frame and/or a gesture performed by the external object by using a touch sensor, a grip sensor, and/or a proximity sensor formed on at least a portion of the surface of the frame.

(58) According to an embodiment of the disclosure, the wearable device **300** may include hardware (e.g., hardware described above based on the block diagram of FIGS. **6A** and **6B**) that performs various functions. For example, the hardware includes a battery module **370**, an antenna module **375**, optical devices **382** and **384**, speakers **392-1** and **392-2**, and microphones **394-1**, **394-2** and **394-3**), a light emitting module (not illustrated), and/or a printed circuit board **390**. Various hardware may be disposed in the frame.

(59) According to an embodiment of the disclosure, the microphones **394-1**, **394-2**, and **394-3** of the wearable device **300** may obtain a sound signal, by being disposed on at least a portion of the frame. The first microphone **394-1** disposed on the nose pad **310**, the second microphone **394-2** disposed on the second rim **302**, and the third microphone **394-3** disposed on the first rim **301** are illustrated in FIG. **3B**, but the number and disposition of microphones **394** are not limited to the embodiment of FIG. **3B**. In case that the number of microphones **394** included in the wearable device **300** is two or more, the wearable device **300** may identify the direction of the sound signal by using a plurality of microphones disposed on different portions of the frame.

(60) According to an embodiment of the disclosure, the optical devices **382** and **384** may transmit the virtual object transmitted from the at least one display **350** to the waveguides **333** and **334**. For example, the optical devices **382** and **384** may be projectors. The optical devices **382** and **384** may be disposed adjacent to the at least one display **350** or included in the at least one display **350** as a portion of the at least one display **350**. The first optical device **382** may correspond to the first display **350-1**, and the second optical device **384** may correspond to the second display **350-2**. The first optical device **382** may transmit light outputted from the first display **350-1** to the first waveguide **333**, and the second optical device **384** may transmit light outputted from the second display **350-2** to the second waveguide **334**.

(61) In an embodiment of the disclosure, the camera **340** may include an eye tracking camera (ET CAM) **340-1**, the motion recognition camera **340-2**, and/or a photographing camera **340-3**. The photographing camera **340-3**, the eye tracking camera **340-1**, and the motion recognition camera **340-2** may be disposed at different locations on the frame and may perform different functions. The eye tracking camera **340-1** may output data representing the gaze of the user wearing the wearable device **300**. For example, the wearable device **300** may detect the gaze from an image including the pupils of the user obtain through the eye tracking camera **340-1**. An example of eye tracking camera **340-1** being disposed toward the right eye of the user is illustrated in FIG. **3B**, but the embodiment is not limited thereto, and the eye tracking camera **340-1** may be disposed alone toward the left eye of the user or may be disposed toward both eyes.

(62) In an embodiment of the disclosure, the photographing camera **340-3** may photograph a real image or background to be matched with a virtual image in order to implement augmented reality or mixed reality content. The photographing camera may photograph an image of a specific object existing at a location viewed by the user and provide the image to the at least one display **350**. The at least one display **350** may display one image in which a virtual image provided through the optical devices **382** and **384** is overlapped with information on a real image or background including an image of the specific object obtained by using the photographing camera. In an embodiment of the disclosure, the photographing camera may be disposed on the bridge **303** disposed between the first rim **301** and the second rim **302**.

(63) In an embodiment of the disclosure, the eye tracking camera **340-1** may realize a more

realistic augmented reality by matching the gaze of the user with the visual information provided on the at least one display **350** by tracking the gaze of the user wearing the wearable device **300**. For example, when the user looks at the front, the wearable device **300** may naturally display environment information associated with the front of the user on the at least one display **350** at the location where the user is located. The eye tracking camera **340-1** may be configured to capture an image of the pupil of the user in order to determine the gaze of the user. For example, the eye tracking camera **340-1** may receive gaze detection light reflected from the pupil of the user and may track the gaze of the user based on the location and movement of the received gaze detection light. In an embodiment of the disclosure, the eye tracking camera **340-1** may be disposed at a location corresponding to the left and right eyes of the user. For example, the eye tracking camera **340-1** may be located in the first rim **301** and/or the second rim **302** to face the direction in which the user wearing the wearable device **300** is located.

(64) In an embodiment of the disclosure, the motion recognition camera **340-2** may provide a specific event to the screen provided on the at least one display **350** by recognizing the movement of the entire or portion of the body of the user, such as the torso of the user, the hand of the user, or the face of the user, and the like. The motion recognition camera **340-2** may obtain a signal corresponding to the gesture by recognize the gesture of the user, and may provide a display corresponding to the signal on the at least one display **350**. The processor may perform a designated function based on identifying the signal corresponding to the operation. In an embodiment of the disclosure, the motion recognition camera **340-2** may be disposed on the first rim **301** and/or the second rim **302**.

(65) In an embodiment of the disclosure, the camera **340** included in the wearable device **300** is not limited to the above-described eye tracking camera **340-1** and the motion recognition camera **340-2**. For example, the wearable device **300** may identify an external object included in the field-of-view (FoV) by using a photographing camera **340-3** located toward the FoV of the user. That the wearable device **300** identifies the external object may be performed based on a sensor for identifying a distance between the wearable device **300** and the external object, such as a depth sensor and/or a time of flight (ToF) sensor. The camera **340** disposed toward the FoV may support an autofocus function and/or an optical image stabilization (OIS) function. For example, the wearable device **300** may include the camera **340** (e.g., a face tracking (FT) camera) disposed toward the face in order to obtain an image including the face of the user wearing the wearable device **300**.

(66) Although not illustrated, the wearable device **300** according to an embodiment may further include a light source (e.g., light-emitting diode (LED)) that emits light toward a subject (e.g., user's eye, face, and/or an external object in the FoV) photographed by using the camera **340**. The light source may include an LED having an infrared wavelength. The light source may be disposed on at least one of the frame and the hinge units **306** and **307**.

(67) According to an embodiment of the disclosure, the battery module **370** may supply power to electronic components of the wearable device **300**. In an embodiment of the disclosure, the battery module **370** may be disposed in the first temple **304** and/or the second temple **305**. For example, the battery module **370** may be a plurality of battery modules **370**. A plurality of battery modules **370** may be disposed on each of the first temple **304** and the second temple **305**. In an embodiment of the disclosure, the battery module **370** may be disposed at an end of the first temple **304** and/or the second temple **305**.

(68) In an embodiment of the disclosure, the antenna module **375** may transmit the signal or power to the outside of the wearable device **300** or may receive the signal or power from the outside. The antenna module **375** may be electrically and/or operatively connected to a communication circuit (e.g., a communication circuit **650** described later with reference to FIG. **6B**) in the wearable device **300**. In an embodiment of the disclosure, the antenna module **375** may be disposed in the first temple **304** and/or the second temple **305**. For example, the antenna module **375** may be

disposed close to one surface of the first temple **304** and/or the second temple **305**.

(69) In an embodiment of the disclosure, the speakers **392-1** and **392-2** may output sound signals to the outside of the wearable device **300**. A sound output module may be referred to as a speaker. In an embodiment of the disclosure, the speakers **392-1** and **392-2** may be disposed in the first temple **304** and/or the second temple **305** in order to be disposed adjacent to the ear of the user wearing the wearable device **300**. For example, the wearable device **300** may include the second speaker **392-2** disposed adjacent to the left ear of the user by being disposed in the first temple **304**, and the first speaker **392-1** disposed adjacent to the right ear of the user by being disposed in the second temple **305**.

(70) In an embodiment of the disclosure, the light emitting module (not illustrated) may include at least one light emitting element. The light emitting module may emit light of a color corresponding to a specific state or may emit light through an operation corresponding to the specific state in order to visually provide information on a specific state of the wearable device **300** to the user. For example, in case that the wearable device **300** needs charging, it may repeatedly emit red light at a designated timing. In an embodiment of the disclosure, the light emitting module may be disposed on the first rim **301** and/or the second rim **302**.

(71) Referring to FIG. 3B, according to an embodiment of the disclosure, the wearable device **300** may include the printed circuit board (PCB) **390**. The PCB **390** may be included in at least one of the first temple **304** and the second temple **305**. The PCB **390** may include an interposer disposed between at least two sub PCBs. On the PCB **390**, one or more hardware (e.g., hardware illustrated by blocks described later with reference to FIG. 5) included in the wearable device **300** may be disposed. The wearable device **300** may include a flexible PCB (FPCB) for interconnecting the hardware.

(72) According to an embodiment of the disclosure, the wearable device **300** may include at least one of a gyro sensor, a gravity sensor, and/or an acceleration sensor for detecting the posture of the wearable device **300** and/or the posture of a body part (e.g., a head) of the user wearing the wearable device **300**. The wearable device **300** may measure gravity acceleration and acceleration based on designated three-dimensional axes (e.g., x-axis, y-axis, and z-axis) perpendicular to each other by using the gravity sensor and the acceleration sensor, respectively. The gyro sensor may measure angular velocity of each of designated three-dimensional axes (e.g., x-axis, y-axis, and z-axis). At least one of the gravity sensor, the acceleration sensor, and the gyro sensor may be referred to as an inertial measurement unit (IMU). According to an embodiment of the disclosure, the wearable device **300** may identify the motion and/or gesture of the user performed to execute or stop a specific function of the wearable device **300** based on the IMU.

(73) FIGS. 4A and 4B illustrate an exterior of a wearable device **400** according to an embodiment of the disclosure. The wearable device **400** of FIGS. 4A and 4B may be an example of a wearable device **101** of FIG. 1 and/or a wearable device of FIG. 2. According to an embodiment of the disclosure, an example of an exterior of a first surface **410** of the housing of the wearable device **400** may be illustrated in FIG. 4A, and an example of an exterior of a second surface **420** opposite to the first surface **410** may be illustrated in FIG. 4B.

(74) Referring to FIG. 4A, according to an embodiment of the disclosure, the first surface **410** of the wearable device **400** may have an attachable shape on a body part of the user (e.g., a face of the user). Although not illustrated, the wearable device **400** may further include a strap for being fixed on the body part of the user, and/or one or more temples (e.g., a first temple **304** and/or a second temple **305** of FIGS. 3A and 3B). A first display **350-1** for outputting an image to the left eye among both eyes of the user and a second display **350-2** for outputting an image to the right eye among the both eyes of the user may be disposed on the first surface **410**. The wearable device **400** may be formed on the first surface **410** and may further include rubber or silicon packing for preventing interference by light (e.g., ambient light) different from the light emitted from the first display **350-1** and the second display **350-2**.

(75) According to an embodiment of the disclosure, the wearable device **400** may include cameras **440-1** and **440-2** for photographing and/or tracking both eyes of the user adjacent to each of the first display **350-1** and the second display **350-2**. The cameras **440-1** and **440-2** may be referred to as ET cameras. The wearable device **400** according to an embodiment may include cameras **440-3** and **440-4** for photographing and/or recognizing the face of the user. The cameras **440-3** and **440-4** may be referred to as FT cameras.

(76) Referring to FIG. **4B**, a camera (e.g., cameras **440-5**, **440-6**, **440-7**, **440-8**, **440-9**, and **440-10**), and/or a sensor (e.g., a depth sensor **430**) for obtaining information associated with the external environment of the wearable device **400** may be disposed on the second surface **420** opposite to the first surface **410** of FIG. **4A**. For example, the cameras **440-5**, **440-6**, **440-7**, **440-8**, **440-9**, and **440-10** may be disposed on the second surface **420** in order to recognize an external object different from the wearable device **400**. For example, by using cameras **440-9** and **440-10**, the wearable device **400** may obtain images and/or media to be transmitted to both eyes of the user. The camera **440-9** may be disposed on the second surface **420** of the wearable device **400** to obtain an image to be displayed through the second display **350-2** corresponding to the right eye among the two eyes. The camera **440-10** may be disposed on the second surface **420** of the wearable device **400** to obtain an image to be displayed through the first display **350-1** corresponding to the left eye among the two eyes.

(77) According to an embodiment of the disclosure, the wearable device **400** may include the depth sensor **430** disposed on the second surface **420** in order to identify a distance between the wearable device **400** and the external object. By using the depth sensor **430**, the wearable device **400** may obtain spatial information (e.g., a depth map) of at least a portion of the FoV of the user wearing the wearable device **400**.

(78) Although not illustrated, a microphone for obtaining sound outputted from the external object may be disposed on the second surface **420** of the wearable device **400**. The number of microphones may be one or more depending on embodiments.

(79) As described above, the wearable device **400** according to an embodiment may have a form factor for being worn on a head of the user. The wearable device **400** may provide a user experience based on augmented reality, virtual reality, and/or mixed reality in the state worn on the head. The wearable device **400** may display a screen including the external object by using the first display **350-1** and the second display **350-2** for being disposed toward each of the two eyes of the user. In the screen, the wearable device **400** may register the external object or may display a result of executing a function assigned to the external object.

(80) Hereinafter, referring to FIG. **5**, a structure of one or more hardware included in a wearable device (e.g., the wearable device **101** of FIG. **1**) including a wearable device **300** of FIGS. **3A** and **3B** and/or the wearable device **400** of FIGS. **4A** and **4B** will be described.

(81) FIG. **5** is a block diagram of a wearable device according to an embodiment of the disclosure. The wearable device **101** of FIG. **5** may include the wearable device **101** of FIG. **1**, a wearable device of FIG. **2**, a wearable device **300** of FIGS. **3A** and **3B**, and/or a wearable device **400** of FIGS. **4A** and **4B**.

(82) Referring to FIG. **5**, the wearable device **101** may include at least one of a processor **510**, a memory **520**, a display **530**, a camera **540**, and a communication circuit **550**. The processor **510**, the memory **520**, the display **530**, the camera **540**, and the communication circuit **550** may be electronically and/or operably coupled with each other by an electrical component, such as a communication bus **502**. Hereinafter, that the hardware operably coupled with each other may mean that a direct connection or an indirect connection between hardware is established by wire or wirelessly so that the second hardware is controlled by the first hardware among the hardware. Although illustrated based on different blocks, the embodiment is not limited thereto, and some of the hardware of FIG. **5** (e.g., at least a portion of the processor **510**, the memory **520**, and the communication circuit **550**) may be included in a single integrated circuit, such as a system on a

chip (SoC). The types and/or numbers of hardware components included in the wearable device **101** are not limited to those illustrated in FIG. 5. For example, the wearable device **101** may include only some of the hardware components illustrated in FIG. 5.

(83) The processor **510** of the wearable device **101** according to an embodiment may include the hardware component for processing data based on one or more instructions. The hardware component for processing data may include, for example, an arithmetic and logic unit (ALU), a floating point unit (FPU), a field programmable gate array (FPGA), a central processing unit (CPU), and/or an application processor (AP). The number of processors **510** may be one or more. For example, the processor **510** may have a structure of a multi-core processor, such as a dual core, a quad core, or a hexa core.

(84) According to an embodiment of the disclosure, the memory **520** of the wearable device **101** may include the hardware component for storing data and/or instructions inputted and/or outputted to the processor **510**. The memory **520** may include, for example, volatile memory such as a random-access memory (RAM) and/or a non-volatile memory, such as a read-only memory (ROM). The volatile memory may include, for example, at least one of a dynamic RAM (DRAM), a static RAM (SRAM), a cache RAM, and a pseudo SRAM (PSRAM). The non-volatile memory may include, for example, at least one of a programmable ROM (PROM), an erasable PROM (EPROM), an electrically erasable PROM (EEPROM), a flash memory, a hard disk, a compact disk, a solid state drive (SSD), and an embedded multimedia card (eMMC).

(85) According to an embodiment of the disclosure, in the memory **520** of the wearable device **101**, one or more instructions (or commands) indicating operations and/or operations to be performed on data by the processor **510** may be stored. The set of the one or more instructions may be referred to as firmware, operating system, process, routine, sub-routine, and/or application. For example, the wearable device **101** and/or the processor **510** may perform at least one of the operations of FIGS. 2, 7, 16, and/or 18 when set of a plurality of instructions distributed in the form of the operating system, the firmware, the driver, and/or the application is executed. Hereinafter, that the application is installed in the wearable device **101** means that the one or more instructions provided in the form of the application are stored in the memory **520** of the wearable device **101**, and the one or more applications are stored in an executable format (e.g., a file having an extension designated by the operating system of the wearable device **101**) by the processor **510** of the wearable device **101**. For example, the wearable device **101** may obtain information (e.g., a path of a portion of the external object and/or at least one stroke drawn by the external object) associated with the motion of the external object (e.g., an external object **130** of FIG. 1), by executing the one or more instructions. The wearable device **101** may execute the one or more applications installed in the memory **520** based on the obtained information. The wearable device **101** may execute the one or more applications to execute a function matched to the external object based on the obtained information.

(86) According to an embodiment of the disclosure, the display **530** of the wearable device **101** may output visualized information to the user. The display **530** of FIG. 5 may include at least one display **350** of FIGS. 3A and 3B and/or a first display **350-1** to a second display **350-2** of FIGS. 4A and 4B. The display **530** may output the visualized information to the user by being controlled by a controller, such as a graphics processing unit (GPU). The display **530** may include a flat panel display (FPD) and/or an electronic paper. The FPD may include a liquid crystal display (LCD), a plasma display panel (PDP), and/or one or more light emitting diodes (LEDs). The LED may include an organic LED (OLED).

(87) According to an embodiment of the disclosure, the camera **540** of the wearable device **101** may include one or more optical sensors (e.g., a charged coupled device (CCD) sensor and a complementary metal oxide semiconductor (CMOS) sensor) that generate an electrical signal indicating the color and/or brightness of light. A plurality of optical sensors included in the camera **540** may be disposed in the form of a 2 dimensional array. The camera **540** may include a first camera **540-1** and a second camera **540-2**. The camera **540** may generate 2 dimensional frame data

corresponding to light reaching the light sensors of the 2 dimensional array, by substantially simultaneously obtaining electrical signals of a plurality of light sensors. For example, photo data captured by using the camera **540** may mean the one 2 dimensional frame data obtained from the camera **540**. For example, video data captured by using the camera **540** may mean a sequence of a plurality of images obtained from the camera **540** according to a designated frame rate.

(88) According to an embodiment of the disclosure, the wearable device **101** may include one or more cameras (e.g., the camera **540**). In case that the wearable device **101** includes a plurality of cameras, the plurality of cameras may be distinguished by information to be obtained through the cameras. For example, a camera for tracking the eyes of the user wearing the wearable device **101** may be referred to as an ET camera (e.g., an ET camera **340-1** of FIGS. **3A** and **3B**). For example, a camera for tracking the face of the user wearing the wearable device **101** may be referred to as an FT camera. For example, in the wearable device **101**, a camera for tracking the hand (e.g., a hand **140** of FIG. **1**) of the user may be referred to as a motion recognition camera (e.g., a motion recognition camera **340-2** of FIG. **3B**). Each of the plurality of cameras may be distinguished by a field-of-view (FoV) formed by a direction in which the camera faces and/or a view angle in a state in which the user wears the wearable device **101**. The external object may include an object included in the FoV of the camera **540** and distinguished from the wearable device **101**.

(89) According to an embodiment of the disclosure, the communication circuit **550** of the wearable device **101** may include hardware for supporting transmission and/or reception of an electrical signal between the wearable device **101** and an external electronic device (e.g., a terminal **120** and/or a server **122** of FIG. **1**). The communication circuit **550** may include, for example, at least one of a modem (MODEM), an antenna, and an optic/electronic (O/E) converter. The communication circuit **550** may support transmission and/or reception of the electrical signal based on various types of protocols, such as ethernet, local area network (LAN), wide area network (WAN), wireless fidelity (Wi-Fi), Bluetooth, Bluetooth low energy (BLE), ZigBee, long term evolution (LTE), and 5G new radio (NR).

(90) Although not illustrated, the wearable device **101** according to an embodiment may include an output means for outputting information in a form other than a visualized form. For example, the wearable device **101** may include a speaker for outputting an acoustic signal. For example, the wearable device **101** may include a motor for providing haptic feedback based on vibration.

(91) According to an embodiment of the disclosure, the wearable device **101** may identify the external object by using the camera **540**. An attribute assigned to the external object may be stored in the memory **520** of the wearable device **101**. Based on the attribute, the wearable device **101** may track at least one of a path of the external object and/or at least one stroke drawn by the external object. Based on the tracked path and/or the at least one stroke, the wearable device **101** may execute an application corresponding to the attribute. The wearable device **101** may obtain digital content from the tracked path and/or analog content indicated by the at least one stroke, by executing the application. The embodiment is not limited thereto, and the wearable device **101** may process the tracked path and/or information included in the at least one stroke based on the application.

(92) In an embodiment of the disclosure, the wearable device **101** may receive an input for registering the identified external object by using the camera **540**. Hereinafter, an example of an operation in which the wearable device **101** receives the input according to an embodiment will be described with reference to FIGS. **6A** to **6D** and/or **7**.

(93) FIGS. **6A**, **6B**, **6C**, and **6D** illustrate an operation of identifying an input indicating that a wearable device registers an external object according to an embodiment of the disclosure. The wearable device **101** of FIG. **5** may include the wearable device **101** of FIGS. **6A** to **6D**.

(94) Referring to FIGS. **6A** to **6D**, according to an embodiment of the disclosure, different states **601**, **602**, **603**, and **604** in which the wearable device **101** displays a user interface (UI) through a displaying area of a display (e.g., the display **530** of FIG. **5**) are illustrated. In a state in which a

user **110** wears the wearable device **101**, the UI may be viewed by the user **110**.

(95) Referring to FIG. **6A**, according to an embodiment of the disclosure, the state **601** in which the wearable device **101** displays a list **610** of a plurality of applications stored in the memory (e.g., the memory **520** of FIG. **5**) of the wearable device **101** in the displaying area formed by the display, is illustrated. The list **610** may be displayed in a portion of the displaying area and may have the form of an application tray. The wearable device **101** may display icons **611**, **612**, **613**, and **614** representing each of the plurality of applications in the list **610**. The number of icons **611**, **612**, **613**, and **614** displayed in the list **610** by the wearable device **101** is not limited to the embodiment of FIG. **6A**. In case that the number of applications installed on the wearable device **101** exceeds a designated upper limit that may be simultaneously displayable through the list **610**, the wearable device **101** may switch an icon displayed through the list **610** in response to an input indicating to scroll the list **610**.

(96) In state **601** of FIG. **6A**, according to an embodiment of the disclosure, the wearable device **101** may identify one or more external objects **621**, **622**, **623**, and **624** shown by the user **110**. In a state in which the user **110** is wearing the wearable device **101**, the wearable device **101** may identify external objects **621**, **622**, **623**, and **624** included in the displaying area of the display. Based on identifying external objects **621**, **622**, **623**, and **624**, the wearable device **101** may display bounding boxes **631**, **632**, **633**, and **634** for guiding that the external objects **621**, **622**, **623**, and **624** have been identified by the wearable device **101**, in the displaying area. Although bounding boxes **631**, **632**, **633**, and **634** having a rectangular line shape are illustrated, the embodiments are not limited thereto.

(97) According to an embodiment of the disclosure, the wearable device **101** may identify whether the external object is registered based on the shape, size, and/or color of the external object. That the external object is registered may mean that the attribute of the external object including the shape, size, and/or color are stored in the wearable device **101** and/or the external electronic device (e.g., a terminal **120** and/or a server **122** of FIG. **1**). Hereinafter, the operation of registering the external object in the wearable device **101** is not limited to the operation of storing the attributes of the external object in the wearable device **101**, and may include a case stored in the external electronic device connected to the wearable device **101**. In the case, according to an embodiment of the disclosure, the wearable device **101** may obtain attributes of the external object stored in the external electronic device by accessing the external electronic device. The attribute may include information (e.g., motion of the external object and/or material outputted from the external object) on the external object, which should be tracked by the wearable device **101**. The attribute may include an application matched to the external object and/or a function matched to the external object among a plurality of functions supported by the application. The embodiment is not limited thereto, and the attribute may include a plurality of applications matched to the external object.

(98) For example, in case that an external object **621** is registered in a wearable device **101**, the wearable device **101** may display a bounding box **631** having a designated color (e.g., yellow) for guiding registration of the external object **621** overlapping with the external object **621** included in the displaying area. Referring to FIG. **6A**, the wearable device **101** may display the name (e.g., “1 APP”) of an application matched to the external object **621** in the displaying area in association with the external object **621**. In case that the external objects **622**, **623**, and **624**, which are distinguished from the external object **621**, are not registered in the wearable device **101**, the wearable device **101** may display the colors of the bounding boxes **632**, **633**, and **634**, which overlap with the external objects **622**, **623**, and **624**, in a designated color (e.g., blue) different from the designated color of the bounding box **631**.

(99) According to an embodiment of the disclosure, the wearable device **101** may enter the state **601** of FIG. **6A** in response to an input indicating that the external object is registered with the wearable device **101**. For example, the wearable device **101** may enter the state **601** of FIG. **6A** in response to an input indicating that the list **610** is displayed. In the state **601**, the wearable device

101 may display a visual object having the form of a button **640** for returning to another state before entering the state **601** in the displaying area.

(100) According to an embodiment of the disclosure, the wearable device **101** may identify an input indicating mapping of the application in the list **610** to the external object included in the displaying area. The input may include a gesture overlapping the visual object (e.g., at least one of icons **611**, **612**, **613**, and **614**) representing a specific application included in the list **610**. Referring to FIG. **6B**, a state **602** in which the wearable device **101** identifies the input included in the list **610** is illustrated. In the state **602**, the wearable device **101** may display the icon **612** overlapping the external object **622** in response to the input. In the state **602**, the wearable device **101** may identify a gesture that moves the icon **612** along the path **650** based on the motion of the designated body part (e.g., a hand **140** and/or an eye of FIG. **1**) the user **110**. The gesture may include a drag-and-drop gesture for the icon **612**. The gesture may be identified based on a hand (or finger) that moves to a portion (e.g., an area visible to the user **110** wearing the wearable device **101**, a space in which the icon **612** is floating) corresponding to the icon **612** in the outer space. The gesture may be identified based on the hand approaching less than a specified distance from the portion. The gesture may be identified based on the hand that remains in excess of a specified period (e.g., about 1 to 1.5 seconds) in a portion corresponding to the icon **612** in the external space. Although the gesture is illustrated based on the hand, the embodiment is not limited thereto. For example, the wearable device **101** may identify the gesture based on a direction of the gaze of the user **110** toward the icon **612**, and/or a period in which the direction of the gaze of the user **110** faces the icon **612**. For example, the wearable device **101** may identify an input that maps a specific application to a specific external object based on the remarks (e.g., "Please map which application with which pencil") of the user **110** and the gestures of the user **110** in the time section in which the remarks are received. Based on the input, the wearable device **101** may assign an application corresponding to the icon **612** to the external object **622** included in the displaying area.

(101) Within the state **602** in which the input dragged along the path **650** of FIG. **6B** is identified, the wearable device **101** may obtain attributes for executing the application (e.g., an application corresponding to the icon **612**) by using the external object **622**. Although the input of moving the icon **612** to the external object **622** along the path **650** is exemplarily described, the embodiment is not limited thereto. For example, the wearable device **101** may obtain the attribute for executing an application corresponding to an icon moved by the other input based on another input for moving one of the icons **611**, **612**, **613**, and **614**, to one of the external objects **621**, **622**, **623**, and **624**. For example, the wearable device **101** may display a visual object having the form of a window **660** for obtaining the attribute in the displaying area. The window **660** may be referred to as a screen for receiving one or more attributes associated with the application. In the window **660**, the wearable device **101** may display information associated with the external object **622** selected by the input and/or the application. In the window **660**, the wearable device **101** may display information (e.g., "function: schedule transmission") indicating an executable function by using the external object **622**. The function may be supported by the application. In the window **660**, the wearable device **101** may receive the attribute required to execute the function. The attribute required to execute the function may be set by the application selected by the input.

(102) Referring to FIG. **6B**, the wearable device **101** according to an embodiment may receive an input for selecting information to be recognized by the wearable device **101** in the window **660**. For example, the wearable device **101** may display options for selecting which of a motion of a portion of the external object **622** or a stroke drawn by the external object **622** is tracked in the window **660**. For example, in case that the external object **622** is recognized as a pen including ink, the wearable device **101** may display the options in the window **660**. The wearable device **101** may display options for selecting a portion of the external object **622** to be tracked by the wearable device **101** in the window **660**. For example, in case that one option for tracking the motion of the external object **622** is selected among the options, the wearable device **101** may track an end of the

external object 622. The end of the external object 622 may be selected based on the location of the icon 612 dragged on the external object 622 along the path 650 among both ends of the external object 622. The embodiment is not limited thereto, and the wearable device 101 may additionally receive an input to select a portion of the external object 622 to be tracked by the wearable device 101.

(103) Referring to FIG. 6B, an example of the wearable device 101 displaying the window 660 including attributes associated with the schedule application is illustrated in the state 602 in which the icon 612 corresponds to the schedule application. In the state 602, the wearable device 101 may display text (e.g., “calendar: personal calendar”) for selecting the type of calendar to which information (e.g., a path of a portion of the external object 622 and/or handwriting drawn by the external object 622) obtained by tracking the external object 622 is added. In the state 602, the wearable device 101 may display options for selecting whether to track the end of the external object 622 or the stroke drawn by the external object 622. For example, in case that an option is selected to track the stroke drawn by the external object 622, the wearable device 101 may identify the handwriting input inputted through the material (e.g., ink and/or graphite) of the external object 622. The end of the external object 622 may be selected as an end adjacent to the point of the external object 622 where the icon 612 dragged along the path 650 overlaps, among both ends of the external object 622 extending along a length direction. The wearable device 101 may selectively display the window 660 according to the type of application selected in the list 610. In the state 602 of FIG. 6B, in response to an input indicating that a button (e.g., a button including a designated text, such as “OK”) included in the window 660 is selected, the wearable device 101 may register external object 622 based on the attributes included in window 660. In an embodiment of registering the external object 622, independent of Windows 660, the wearable device 101 may register the external object 622 based on an input indicating that the icon 612 is dragged along the path 650. Based on the registration of the external object 622, the wearable device 101 may match a function (e.g., a function executed based on the attributes included in the window 660) to be executed by tracking the external object 622 to the external object 622.

(104) Although an operation of obtaining at least one attribute set by a schedule application through the window 660 by the wearable device 101 has been described, the embodiment is not limited thereto. According to one embodiment of the disclosure, wearable device 101 may identify one or more attributes required to execute an application corresponding to the external object 622 in the state 602 for registration of the external object 622. The one or more attributes may be set by an application corresponding to an icon moved to external object 622. For example, the one or more attributes may be classified as shown in Table 1 based on applications installed in the wearable device 101.

(105) TABLE-US-00001 TABLE 1 Application Attribute Schedule application the type of calendar the event will be stored in, the number of repetitions, and the timing of the reminder Note application the digital note where the handwriting will be stored, the style of the stroke (e.g., color, thickness, transparency and/or pattern) Messenger application receiver Payment application currency, bank, receiver

(106) Referring to Table 1, in case of matching the note application and the external object 622, the wearable device 101 may obtain a digital note in which digital content including at least one stroke drawn by the external object 622 is to be stored and/or the attribute for the style of the at least one stroke. In case of matching the messenger application and the external object 622, the wearable device 101 may obtain the attribute for a counterpart to receive the identified text message by tracking the external object 622. In case of matching the payment application and the external object 622, the wearable device 101 may obtain the attribute for the currency for the amount identified by tracking the external object 622, the counterpart to which the amount is to be remitted, and/or the bank. Independently of the attribute included in Table 1, the wearable device 101 may obtain an attribute for whether to track the end of the external object 622 or the stroke drawn by the

external object **622**.

(107) Referring to FIG. **6C**, the state **603** in which the wearable device **101** registers the external object **622** is illustrated. The state **603** may be a state after the state **602**. In the state **603**, the wearable device **101** may display an icon **615** representing an application matched to the external object **622** in association with the external object **622** included in the displaying area. In an embodiment in which the external object **622** is registered based on an input that moves the icon **612** of FIG. **6B** to the external object **622** along the path **650**, the icon **615** of FIG. **6C** may match the icon **612** of FIGS. **6A** and **6B**. The embodiment is not limited thereto. As described with reference to the state **601** of FIG. **6A**, in the state **603** after the external object **621** is registered to the wearable device **101**, the wearable device **101** may display the bounding boxes **631** and **632** having shapes wrapping each of the external objects **621** and **622** in a color different from that of the bounding boxes **633** and **634**. The wearable device **101** may display the names (e.g., “1 APP” and “2 APP”) of applications matched to each of the external objects **621** and **622** on a portion of the displaying area adjacent to the bounding boxes **631** and **632**. In the state **603** of FIG. **6C**, the wearable device **101** may change analog content generated by the registered external object **622** into digital content by using an application matched to the icon **612**.

(108) An embodiment of registering the external object by using the list **610** of FIG. **6A** has been described, but the embodiment is not limited thereto. Referring to FIG. **6D**, a state **604** in which the wearable device **101** registers an external object **688** is illustrated by using a camera (e.g., a motion recognition camera **340-2** of FIG. **3B**, cameras **440-9** and **440-10** of FIG. **4B** and/or a camera **540** of FIG. **5**) having FoV that at least partially overlaps the displaying area of the wearable device **101**. The wearable device **101** may display lists of one or more external objects registered as the wearable device **101** in a visual object having the form of a window **670** overlapping at least a portion of the displaying area. In the window **670**, the wearable device **101** may display a visual object having the form of a button **672** including designated text (e.g., “add pen”) for registering the external object. In response to an input indicating to select the button **672**, the wearable device **101** may display a UI for registering the external object in the displaying area.

(109) In the state **604** of FIG. **6D**, the wearable device **101** may display the UI for identifying the selection of the user for the external object in the displaying area based on the input indicating to select the button **672**. For example, the wearable device **101** may display a visual object having the form of a window **682** including a designated text (e.g., “Please recognize the pen to be registered”) for guiding the selection of the external object in the displaying area. The wearable device **101** may display a bounding box **684** in association with the external object **688** included in the displaying area based on identifying the external object **688** in the displaying area. The wearable device **101** may display a shutter **686** for recognizing the external object **688** included in the displaying area. Based on an input indicating to select the shutter **686** and/or the bounding box **684**, the wearable device **101** may display a window **690** for registering the external object **688**.

(110) In the state **604** of FIG. **6D**, the wearable device **101** may display an image for the external object **688** in the window **690**. The image may include an image obtained by controlling the camera by the wearable device **101** that identifies a gesture for the shutter **686**. In the image, the wearable device **101** may display a portion of the external object **688** to be tracked by the wearable device **101**. In the window **690**, the wearable device **101** may display one or more attributes for the external object **688**. The one or more attributes for the external object **688** may include a name assigned to the external object **688**. The wearable device **101** may identify an input indicating that the name is assigned by using a text box **691** included in the window **690**. The one or more attributes for the external object **688** may include one or more applications matched to the external object **688**. The wearable device **101** may display a list **692** of applications installed in the wearable device **101** in the window **690**. Through the list **692**, the wearable device **101** may identify an input indicating to match the one or more applications to the external object **688**. The wearable device **101** may emphasize an icon of an application selected by the input in the list **692**. The wearable

device **101** may emphasize the icon based on the thickness, color and/or pattern of the outline of the icon.

(111) According to an embodiment of the disclosure, the wearable device **101** may display the attribute associated with at least one application selected through the list **692** in a portion **693** of the window **690**. In the state **604** of FIG. **6D**, the wearable device **101** may display the attribute associated with the drawing application in the portion **693**, in response to an input indicating to select the drawing application for drawing an image in the list **692**. For example, the wearable device **101** may display a visual object for adjusting a brush type corresponding to the external object **688** in the portion **693**. The wearable device **101** may identify a category of the external object **688** among designated categories associated with the pen by performing object recognition on the external object **688**. In the state **604** that the wearable device **101** has identified the external object **688** having the shape of a fountain pen, the wearable device **101** may display text indicating the brush type (e.g., “fountain pen”) corresponding to the category of the external object **688** in the portion **693** of the window **690**. The attribute displayed through the portion **693** is not limited thereto, and the wearable device **101** may display other attributes (e.g., stroke width, color, and pattern) associated with the drawing application in the portion **693**. The other attributes may also be adaptively changed based on the category of the external object **688**.

(112) As described above, the wearable device **101** according to an embodiment may register the external object based on object recognition using a camera in a state worn by the user **110**. The wearable device **101** may provide the user **110** with a user experience of changing the analog content into digital content, by registering the external object, such as a pen used by the user **110** to generate analog content. In the state **604** of registering the external object **688**, the wearable device **101** may change the attribute for the external object **688** based on characteristics of the external object **688**.

(113) Hereinafter, an operation of the wearable device **101** associated with the states **601**, **602**, **603**, and **604** of FIGS. **6A** to **6D** will be described with reference to FIG. **7**.

(114) FIG. **7** illustrates a flowchart for a wearable device according to an embodiment of the disclosure. A wearable device **101** of FIG. **5** may include the wearable device of FIG. **7**. For example, operations of FIG. **7** may be performed by the wearable device **101** and/or a processor **510** of FIG. **5**. The operations of FIG. **7** may be associated with at least one of the states **601**, **602**, **603**, and **604** of FIGS. **6A** to **6D**. The operations of FIG. **7** may be associated with at least one of the operations of FIG. **2** (e.g., an operation **210** of FIG. **2**).

(115) Referring to FIG. **7**, in operation **710**, according to an embodiment of the disclosure, the wearable device may display a list of one or more applications. In the state **601** of FIG. **6A**, the wearable device may display the list (e.g., a list **610** of FIG. **6A**) of one or more applications installed in the wearable device by performing operation **719**. In the list, the wearable device may display one or more icons representing the one or more applications.

(116) Referring to FIG. **7**, in operation **720**, according to an embodiment of the disclosure, the wearable device may identify an input indicating to assign an application included in the list to an external object shown through a display. For example, based on the icon included in the list and selected by a user (e.g., a user **110** in FIG. **1**), such as an input indicating dragging an icon **612** along a path **650** in FIG. **6B**, the wearable device may identify the input indicating to assign the application to the external object. Before identifying the input (720-NO), the wearable device may maintain displaying the list based on the operation **710**.

(117) Based on operation **730**, in the state of receiving the input indicating to assign the application to the external object (720-YES), according to an embodiment of the disclosure, the wearable device may identify at least one attribute required to execute an application corresponding to the input. As shown in Table 1, the at least one attribute may be set by the application assigned to the external object by the input of the operation **720**. The embodiment is not limited thereto, and the number of attributes set by the application may be zero. In case that the at least one attribute

required to execute the application does not exist (**730-NO**), the wearable device may bypass performing operation **740**. For example, in case that no attribute is required to execute the application, the wearable device may not obtain at least one attribute based on the operation **740**. (118) In the state of identifying the at least one attribute (e.g., an attribute distinguished by the application of Table 1) required to execute the application (**730-YES**), based on the operation **740**, the wearable device according to an embodiment may obtain the at least one attribute. The at least one attribute may be set by a category of the external object identified based on the shape of the external object and/or object recognition. The at least one attribute may be identified through a visual object having the form of a pop-up window displayed by the wearable device to receive attributes, such as a window **660** of FIG. **6B** and/or a window **690** of FIG. **6D**. For example, the wearable device may display the visual object to identify the at least one attribute, such as the window **660** of FIG. **6B** and/or a portion **693** of the window **690** of FIG. **6D**, based on the operation **740**.

(119) Referring to FIG. **7**, in operation **750**, the wearable device according to an embodiment may store information for executing the application by using the external object. The wearable device may store, in a memory (e.g., the memory **520** of FIG. **5**), the at least one attribute obtained based on the operation **740** together with information for recognizing the external object. After the operation **750**, in response to identifying motion of the external object (e.g., a path of a portion of the external object) and/or analog content (e.g., at least one stroke generated by a material included in the external object) generated by the external object, the wearable device may execute the application by using the stored information based on the operation **750**.

(120) As described above, according to an embodiment of the disclosure, the wearable device, such as a pen, may register the external object that does not support communication with the wearable device. Based on the registered external object, the wearable device may obtain digital content from the external object. Hereinafter, according to an embodiment of the disclosure, an example of a UI displayed by a wearable device within a state identifying different external objects registered as wearable devices will be described with reference to FIGS. **8A** and **8B**.

(121) FIGS. **8A** and **8B** illustrate a user interface (UI) displayed by a wearable device based on an external object according to an embodiment of the disclosure. The wearable device **101** of FIG. **5** may include the wearable device **101** of FIGS. **8A** and **8B**.

(122) Referring to FIGS. **8A** and **8B**, according to an embodiment of the disclosure, different states **801**, **802**, and **803** in which the wearable device **101** displays the UI based on different external objects **810** and **820** included in the displaying area of a display (e.g., the display **530** of FIG. **5**) are illustrated. It is assumed that each of the external objects **810** and **820** is registered as the wearable device **101** in response to an input indicating to register the external object described above with reference to FIGS. **6A** to **6D** and/or **7**.

(123) Referring to FIG. **8A**, in state **801**, according to one embodiment of the disclosure, the wearable device **101** may identify the external objects **810** and **820** by using a camera having FoV that overlaps at least partially with the displaying area (e.g., a motion recognition camera **340-2** of FIG. **3B**, cameras **440-9** and **440-10** of FIG. **4B**, and/or a camera **540** of FIG. **5**). The wearable device **101** may identify whether each of the external objects **810** and **820** is an external object registered in the wearable device **101** based on the shape and/or size of each of the external objects **810** and **820**. In the assumption, the wearable device **101** may identify attributes assigned to each of the external objects **810** and **820**. Based on the identified attribute, the wearable device **101** may display one or more visual objects based on the attribute, overlapping the external objects **810** and **820** in the displaying area.

(124) In the state **801** of FIG. **8A**, in case that a note application for generating a digital note is assigned to an external object **810**, the wearable device **101** may display an icon **832** that is associated with the external object **810** and represents the note application. Referring to FIG. **8A**, the wearable device **101** may display the icon **832** representing the note application overlapping the

external object **810**. The embodiment is not limited thereto, and the wearable device **101** may display the icon **832** on a portion adjacent to the external object **810** in the displaying area. The wearable device **101** may display a FIG. **830** for guiding the note application registered as an external object **810**. The wearable device **101** may display the quadrangle FIG. **830** having a location associated with the external object **810**. The color of the FIG. **830** may have a designated transparency or opacity and may at least partially include the color of the icon **832**. For example, the color of the FIG. **830** may be a gradation of the color of the icon **832** and the color of the external object **810**. Although the polygonal FIG. **830**, such as a quadrangle is exemplarily illustrated, the embodiment is not limited thereto, and the wearable device **101** may display the FIG. **830** having the form of a closed curve and/or a line. The wearable device **101** may display text indicating an attribute assigned to the external object **810** by overlapping with the external object **810**. In the state **801** in which the note application is assigned to the external object **810**, the wearable device **101** may display the name (e.g., “K-note”) of the digital note matched to the external object **810** by overlapping with the external object **810**.

(125) In the state **801** of FIG. **8A**, in case that a messenger application for exchanging messages is assigned to the external object **820**, the wearable device **101** may display an icon **842** representing the messenger application by overlapping with the external object **820**. The wearable device **101** may emphasize that the external object **820** is registered as the wearable device **101** by using a FIG. **840** overlapping the external object **820**. The wearable device **101** may display the color of the FIG. **840** based on at least one of the color of the icon **842** and/or the color of the external object **820**. The wearable device **101** may display attributes (e.g., receiver) assigned to the external object **820** based on the messenger application by overlapping with the external object **820**.

(126) According to an embodiment of the disclosure, the wearable device **101** may identify a designated body part that is moved in the displaying area to select external objects **810** and **820**, such as a hand **850**. Referring to FIG. **8B**, in response to identifying the external object **810**, and/or the hand **850** pointing to the visual object (e.g., the icon **832**) overlapping the external object **810**, the wearable device **101** may display a UI for changing the attribute assigned to the external object **810** as shown in the state **802**. The UI may be displayed overlapping with the external object **810** in the displaying area. In state **802**, the wearable device **101** may display the UI for changing the attribute assigned to the external object **810** based on the note application matched with the external object **810**. The UI may include a button **834** (e.g., the button **834** including designated text, such as “pen settings”) for adjusting the style of at least one stroke to be added to the note application by the external object **810**. The UI may include a button **836** (e.g., the button **836** including designated text, such as “note setting”) for selecting the digital note to which information obtained by tracking the external object **810** is added. In response to an input indicating to select any one of the buttons **834** and **836**, the wearable device **101** may display a window for changing the attribute corresponding to the button selected by the input in the displaying area.

(127) Referring to FIG. **8B**, in response to identifying the hand **850** pointing to the external object **820** among external objects **810** and **820**, the wearable device **101** may display the UI for changing the attribute assigned to the external object **820**, as shown in state **803**. A gesture for displaying the UI is not limited to the gesture of the hand **850** described above. For example, the wearable device **101** may display the UI based on identifying that the user stares at the external object **820** for more than a designated period of time by using data indicating the direction of the gaze of the user (e.g., a user **110** of FIG. **1**). The attribute changed through the UI may be set by the messenger application matched with the external object **820**. In the state **803**, the wearable device **101** may display a button **844** (e.g., the button **844** including designated text, such as “receiver change”) for changing the counterpart to receive a message including information obtained by tracking the external object **820**. The wearable device **101** may display the button **844** overlapping the external object **820**. In response to an input instructing selecting the button **844**, the wearable device **101** may display the UI for changing the counterpart, such as a contact list.

(128) As described above, according to an embodiment of the disclosure, the wearable device **101** may display the visual object based on one or more attributes assigned to the external object by overlapping with the external object (e.g., the external objects **810** and **820**) registered as the wearable device **101**. Based on identifying the external object registered as the wearable device **101**, such as the external objects **810** and **820**, the wearable device **101** may track the identified external object. The information obtained by tracking the external object may include information on a path of a portion of the external object selected by the attribute assigned to the external object, or at least one stroke drawn by the external object. Based on the information, the wearable device **101** may execute at least one application matched to the external object. Since the wearable device **101** executes the application based on the motion of the external object produced independently of the communication circuit, the wearable device **101** may enable the user to control the wearable device **101** by using more various tools.

(129) Hereinafter, cases in which the wearable device **101** according to an embodiment executes the at least one application matched to the external object based on information obtained by tracking the external object will be described. For example, an example in which the wearable device **101** executes the note application will be described with reference to FIGS. **9A** to **9C**, **10**, and **11**. For example, an example in which the wearable device **101** executes a calendar application will be described with reference to FIGS. **12A** and **12B**. For example, an example in which the wearable device **101** executes the messenger application will be described with reference to FIG. **13**. For example, an example in which the wearable device **101** executes a recording application will be described with reference to FIG. **14**. For example, an example in which the wearable device **101** executes a plurality of applications assigned as one external object will be described with reference to FIGS. **15A** and **15B**.

(130) FIGS. **9A**, **9B**, and **9C** illustrate an operation in which a wearable device executes an application based on information obtained by tracking an external object according to an embodiment of the disclosure. The wearable device **101** of FIG. **5** may include the wearable device **101** of FIGS. **9A** to **9C**. Hereinafter, it is assumed that a note application for generating digital content, such as a digital note in which text, image, and/or video are combined is matched with the external object **130**. The wearable device **101** may identify an input indicating to register the note application as the external object **130** based on the operations of FIGS. **6A** to **6D** and/or **7**.

(131) Referring to FIG. **9A**, in a state **901**, according to an embodiment of the disclosure, the wearable device **101** may track the external object **130**. That the wearable device **101** tracks the external object **130** may be performed based on an application executed by the wearable device **101** and/or a terminal **120**. The wearable devices **101** may identify and/or track the external object **130** by using a camera (e.g., a motion recognition camera **340-2** of FIG. **3B**, cameras **440-9** and **440-10** of FIG. **4B**, and/or a camera **540** of FIG. **5**) having FoV at least partially overlapping the displaying area. The operation of identifying the external object **130** may include an operation of identifying one or more applications assigned to the external object **130**. In the state **901** in which the external object **130** is identified, the wearable device **101** may display an icon **920** representing the note application matched to the external object **130** in a portion adjacent to the external object **130** in the displaying area.

(132) Referring to FIG. **9A**, in the state **901** of tracking the external object **130**, the wearable device **101** may display a visual object based on information obtained by tracking the external object **130** in the displaying area. In the state **901** in which the wearable device **101** tracks a path of a portion (e.g., a point P corresponding to a pen tip) of the external object **130**, the wearable device **101** may display a virtual object **930** representing the path in the displaying area. Based on the distance between the external object **130** and the wearable device **101**, the wearable device **101** may identify a path of the external object **130** that is contacted on one plane (e.g., a plane formed by a note **910**). For example, based on identifying the contact between the external object **130** and the plane, the wearable device **101** may track the path. The wearable device **101** may display the virtual object

930 representing the tracked path in the displaying area.

(133) Referring to FIG. 9A, the state **901** in which the virtual object **930** having the shape of a line and/or a stroke is displayed by the wearable device **101** is illustrated, but the embodiment is not limited thereto. For example, the wearable device **101** may change the thickness, color, and/or pattern of the stroke included in the virtual object **930** based on the shape of the external object **130** and/or the shape of a portion of the external object **130** selected by the user **110**. For example, the wearable device **101** may set at least one of the color, transparency, or thickness of the stroke included in the virtual object **930** based on an attribute (e.g., an attribute set through a portion **693** of FIG. 6D) assigned to the external object **130**. For example, the color of the stroke included in the virtual object **930** may be set to a specific color by the attribute assigned to the external object **130** or may be set to a second color (e.g., the second color in which the first color is inverted) based on a first color (e.g., a background color) adjacent to the external object **130** in the displaying area. According to an embodiment of the disclosure, the wearable device **101** may change the color of the stroke based on the color distribution in the displaying area. For example, the wearable device **101** may identify a representative color from the color distribution by applying weights assigned to each of the portions of the displaying area to the color distribution. The wearable device **101** may set the color of the stroke by inverting the representative color. The wearable device **101** may invert the color based on brightness, saturation, and/or distance between colors in a color space.

(134) Although an embodiment in which the wearable device **101** tracks the path of the point P of the external object **130** is described, the embodiment is not limited thereto. For example, the wearable device **101** may identify at least one stroke drawn by a material (e.g., ink and/or graphite) outputted from the external object **130**. The wearable device **101** may selectively track any one of the path of the point P or the material based on the attribute assigned to the external object **130**.

(135) Referring to FIG. 9A, in the state **901** tracking the external object **130**, the wearable device **101** may display a button **940** for executing the application (e.g., the note application corresponding to the icon **920**) by using information (e.g., information for displaying the virtual object **930**) obtained by tracking an external object **130**. The button **940** may include designated text (e.g., confirmation (“done”)) for executing the application. The button **940** may be displayed based on the location of the external object **130** in the displaying area. In response to an input indicating to select the button **940**, the wearable device **101** may execute the note application. The embodiment is not limited to this, and the wearable device **101** may execute the note application before (e.g., timing of identifying the external object **130**) the input and may execute the function of the note application based on the input associated with the button **940**. In an embodiment of the disclosure, the wearable device **101** may transmit a signal for executing the note application installed in the terminal **120** to the terminal **120** based on the information in response to the input.

(136) Referring to FIG. 9B, an embodiment in which the wearable device **101** executes the note application corresponding to the external object **130** based on the input associated with the button **940** is illustrated, but the embodiment is not limited thereto. For example, the wearable device **101** may track the path of the point P of the external object **130** independently of displaying the button **940**. The wearable device **101** may execute the note application independently of the button **940** based on information obtained by tracking the external object **130**.

(137) In the state in which the note application is executed, the wearable device **101** may execute at least one function matching the attribute among different functions supported by the note application based on the attributes (e.g., for the note application, the digital note where the handwriting drawn by the external object **130** will be stored) assigned to the external object **130**. For example, the wearable device **101** may add an image and/or at least one character represented by the virtual object **930** into the digital note stored in the wearable device **101** by the note application. For example, the image and/or the at least one character represented by the virtual object **930** may be displayed in the displaying area of the wearable device **101** and/or the terminal **120** based on the execution of the note application of the wearable device **101** and/or the terminal

120. The wearable device **101** may store information (e.g., digital content) generated by the external object **130**, such as the virtual object **930**, in the wearable device **101**, based on the execution of the note application corresponding to the external object **130**.

(138) According to an embodiment of the disclosure, the wearable device **101** may change at least one of the color, thickness, or transparency of a stroke added by information obtained by tracking the external object **130** based on a posture of a hand **140** holding the external object **130**. Referring to FIG. **9B**, according to an embodiment of the disclosure, states **901**, **902**, and **903** in which the wearable device **101** changes the attribute of the external object **130** based on the posture of the hand **140** are illustrated. Referring to FIG. **9B**, in the state **902** after the state **901**, the wearable device **101** may identify a posture in which the index finger included in the hand **140** is unfolding. The wearable device **101** may change the attribute assigned to the external object **130** based on the location and/or trajectory of the point F in the fingertip of the index finger.

(139) In the state **902** of FIG. **9B**, the wearable device **101** may change the color and/or pattern of the stroke extended by the path of the point P of the external object **130** based on the color of a portion adjacent to the point F in the displaying area. For example, a posture of unfolding the index finger may correspond to a tool (e.g., pipette) for selecting the color of the stroke drawn by the external object **130**. Based on identifying the posture of the hand **140** unfolding the index finger, the wearable device **101** may display an icon **922** (e.g., the icon **922** representing the pipette) for guiding the tool in the displaying area. The wearable device **101** may display the icon **922** on a portion of the displaying area adjacent to the hand **140**.

(140) According to an embodiment of the disclosure, the wearable device **101** may identify an input indicating to change the color of the stroke based on the point F of the fingertip. For example, the wearable device **101** may move the point F to a portion of the displaying area and then may repeatedly move the fingertip. Based on identifying the fingertip (e.g., the fingertip that is repeatedly moved along a path T1 between points F1 and F2) that is repeatedly moved, the wearable device **101** may select the color of a portion adjacent to the point F in the displaying area. The wearable device **101** may change the color (e.g., the color of the outline of the icon **922**) of the icon **922** based on the selected color. In the state **902**, after changing the color based on the gesture associated with the point F, the wearable device **101** may add a stroke having the changed color along the path of the external object **130**.

(141) In an embodiment of the disclosure, an operation performed by the wearable device **101** by using a gesture for the fingertip is not limited to the selection and/or change of the above-described color. Based on identifying the gesture of rotating the fingertip in a circular shape, the wearable device **101** may mix the color indicated by the attribute assigned to the external object **130** and another color adjacent to the point F in the fingertip. The wearable device **101** may add a stroke having in the shape of the path of the external object **130** and having the mixed color. For example, in case that the color (e.g., the color of the strokes included in the virtual object **930**) of the stroke drawn by the path of the point P of the external object **130** is yellow and the other color adjacent to the point F is white, the wearable device **101** may gradually change the color of the stroke to white based on the number of rotations of the fingertip in the circular shape. The wearable device **101** may perform color mixing differently based on the rotation direction of the fingertip. For example, in case of identifying the gesture of the fingertip rotating in a clockwise direction, the wearable device **101** may change the ratio of mixing the first color indicated by the attribute assigned to the external object **130** and the second color of the point F in the fingertip to increase the proportion of the second color. In the above example, in case of identifying the gesture of the fingertip rotating in a counterclockwise direction, the wearable device **101** may change the ratio so that the weight of the first color increases.

(142) In an embodiment of the disclosure, the posture of the index finger identified by the wearable device **101** is not limited to the posture of unfolding the index finger. For example, the wearable device **101** may identify whether the index finger is unfolded or bent by using an angle of joints

included in the index finger. Based on identifying the posture (e.g., the index finger bent toward a point F3) of the bent index finger, the wearable device **101** may execute a function of extracting a pattern of a portion adjacent to the point P of the external object **130** in the displaying area. For example, after identifying the posture, the wearable device **101** may display a visual object indicating that the function of extracting the pattern is executed. The wearable device **101** may identify a portion of the displaying area including the point P of the external object **130** in the state in which the function is executed. The wearable device **101** may add a stroke to the path of the point P of the external object **130** based on the identified portion.

(143) Referring to FIG. **9B**, in the state **903**, the wearable device **101** may display a stroke **932** representing the path of the point P of the external object **130** based on the attribute changed by the posture of the hand **140** identified in the state **902**. In case that the wearable device **101** identifies an input indicating to select a color based on the unfolded index finger, in the state **903**, the color of the stroke **932** may have the color selected by the input. In case that the wearable device **101** identifies an input indicating to mix colors based on the fingertip rotating in the circular shape, in the state **903**, the color of the stroke **932** may have a color mixed by the input. In case that the wearable device **101** identifies an input indicating to select the pattern based on the bent index finger, in the state **903**, the color of the stroke **932** may have the pattern selected by the input.

(144) In an embodiment of the disclosure, the wearable device **101** may identify a movement of the hand **140** touching the external object **130** in order to change the attribute assigned to the external object **130**. Referring to FIG. **9C**, according to an embodiment of the disclosure, a state **904** in which the wearable device **101** identifies a gesture (e.g., a drag gesture) rubbing the external object **130** along a direction **950** from a point Q on the surface of the external object **130** is shown. The gesture may be performed by a finger (e.g., the index finger) of the hand **140** holding the external object **130**. Based on identifying the gesture, the wearable device **101** may change at least one of attributes assigned to the external object **130**. For example, the wearable device **101** may increase saturation and/or transparency. Similarly, in case of identifying the finger rubbing the external object **130** in a different direction opposite to the direction **950** on the surface of the external object **130**, the wearable device **101** may reduce the saturation and/or transparency.

(145) In an embodiment of the disclosure, identifying the movement of the hand **140** in which the wearable device **101** touches the external object **130** is not limited to a drag gesture performed along a direction in which the external object **130** extends. For example, the wearable device **101** may display a visual object for changing at least one attribute assigned to the external object **130** based on identifying a gesture (e.g., a long tap gesture) that touches the point Q on the external object **130** for more than a designated period (e.g., 1.5 seconds). In the state **904** of FIG. **9C**, based on identifying the long tap gesture for the point Q, the wearable device **101** may display buttons **962**, **964**, and **966** for changing the at least one attribute in the displaying area. The button **962** may correspond to a function for stopping the display of buttons **964** and **966**. The button **964** may correspond to a function for changing the transparency of a stroke to be added along the path of the point P of the external object **130**. The wearable device **101** may display designated text (e.g., “opacity”) for guiding a change of transparency in the button **964**. The button **966** may change the saturation of a stroke to be added along the path of the point P of the external object **130**. The wearable device **101** may display designated text (e.g., “saturation”) for guiding the change of saturation in the button **966**.

(146) As described above, according to an embodiment of the disclosure, the wearable device **101** may track the path of the point P of the external object **130**. Based on the tracked path, the wearable device **101** may display the virtual object (e.g., the virtual object **930** and/or stroke **932**) representing the tracked path in the displaying area. The virtual object may be associated with the attribute (e.g., the stroke thickness, color, and/or pattern) assigned to the external object **130**. The wearable device **101** may at least partially change the attribute based on the posture of the hand **140** holding the external object **130**. The wearable device **101** may obtain digital content independently

of electrical communication between the external object **130** and the wearable device **101** by tracking the hand **140** holding the external object **130** and/or the external object **130**. In the state **903** of FIG. **9B**, in response to an input indicating to select the button **940**, the wearable device **101** may store the digital note including the virtual object **930** and the stroke **932** in the memory (e.g., the memory **520** of FIG. **5**) based on the execution of the note application.

(147) Referring to FIGS. **9A** to **9C**, an embodiment of tracking the motion for the external object **130** by using the camera having the FoV that at least partially overlaps with the displaying area of the wearable device **101** has been described, but the embodiment is not limited thereto. Hereinafter, an example of an operation of tracking the motion by the wearable device **101** by using another camera different from the camera according to an embodiment will be described with reference to FIG. **10**.

(148) FIG. **10** illustrates an operation in which a wearable device switches a camera for tracking an external object according to an embodiment of the disclosure. The wearable device **101** of FIG. **5** may include the wearable device **101** of FIG. **10**.

(149) Referring to FIG. **10**, according to an embodiment of the disclosure, the wearable device **101** may include a first camera **1012** having FoV overlapping a displaying area formed by the display (e.g., the display **530** of FIG. **5**) of the wearable device **101** and a second camera **1014** having a direction and/or FoV different from that of the first camera. The first camera **1012** and the second camera **1014** of FIG. **10** may be an example of a camera **540** of FIG. **5**.

(150) Referring to FIG. **10**, a state in which the wearable device **101** tracks the external object **130** by using the first camera **1012** and the second camera **1014** according to an embodiment is illustrated. For example, in timing **t1**, based on identifying the external object **130** registered as the wearable device **101** by using the first camera **1012** having the FoV overlapping the displaying area, the wearable device **101** may obtain information associated with the external object **130** by using an attribute assigned to the external object **130**. In the timing **t1**, the wearable device **101** may display a virtual object **1020** (e.g., a stroke) indicating the tracked path in a displaying area of the wearable device **101**, by tracking a path of a point **P** of the external object **130**.

(151) According to an embodiment of the disclosure, the wearable device **101** may select any one of the cameras based on identifying the external object **130** moving between FoVs of cameras in the wearable device **101**. In a state in which a user (e.g., a user **110** of FIG. **1**) wears the wearable device **101**, based on the motion of the head of the user, the external object **130** may be moved out of the FoV of the first camera **1012**. In timing **t2**, the external object **130** may be moved out of the FoV of the first camera **1012** and may be included in the FoV of the second camera **1014** different from the first camera **1012**. According to an embodiment of the disclosure, the wearable device **101** may identify that the external object **130** is moved out of the displaying area and/or the FoV of the first camera **1012** based on the frames obtained from the first camera **1012**. Based on identifying that the external object **130** is moved out of the displaying area, the wearable device **101** may track the path of the external object **130** by using the second camera **1014** facing the external object **130**.

(152) Referring to FIG. **10**, in the timing **t2** of tracking the external object **130** by using the second camera **1014**, the wearable device **101** may display information associated with the external object **130** tracked by the second camera **1014** in the displaying area. For example, the wearable device **101** may display a virtual object **1030** in which the path of the point **P** of the external object **130** is represented in the displaying area. The virtual object **1030** may include a line in which the path of the point **P** of the external object **130** tracked by the second camera **1014** and the path of the point **P** of the external object **130** tracked by the first camera **1012** different from the second camera **1014** before the timing **t2** are combined. A point at which the virtual object **1030** is displayed in the displaying area is not limited to an example of FIG. **10**.

(153) As described above, according to an embodiment of the disclosure, in a state in which the external object **130** is tracked by using the first camera **1012** overlapping the displaying area, the wearable device **101** may continuously track the external object **130** by using the second camera

1014, which is different from the first camera **1012** based on the external object **130** which is moved out of the displaying area. Since the external object **130** is tracked by using different cameras of the wearable device **101**, the wearable device **101** may track the external object **130** independently of the location relationship between the wearable device **101** and the external object **130**. In case that the external object **130** moves out of the displaying area, the wearable device **101** may display the virtual object **1030** in the displaying area in order to visualize information obtained by tracking the external object **130**. By using the virtual object **1030**, the wearable device **101** may inform the user of the motion of the external object **130** moved out of the FoV of the user.

(154) Hereinafter, an example of the operation of the wearable device **101** that displays the virtual object **1030** in the displaying area based on the motion of the external object **130** moved out of the FoV of the user will be described with reference to FIG. **11**.

(155) FIG. **11** illustrates a UI displayed by a wearable device based on information obtained by tracking an external object according to an embodiment of the disclosure. The wearable device **101** of FIG. **5** may include the wearable device **101** of FIG. **11**. The wearable device **101** of FIG. **11** may be an example of the wearable device **101** of FIG. **10**. For example, the first camera **1012** and the second camera **1014** of FIG. **11** may include the first camera **1012** and the second camera **1014** of FIG. **10**.

(156) Referring to FIG. **11**, a state of tracking the external object **130** by using a second camera **1014** having FoV different from that of the displaying area of the wearable device **101** is illustrated. In the state of FIG. **11**, the wearable device **101** may display information obtained by tracking the external object **130** in a portion **1120** of the displaying area. In the portion **1120**, the wearable device **101** may display one or more strokes representing a path of contacted external object **130** on a plane **1110**. According to an embodiment of the disclosure, the wearable device **101** may identify one or more characters from the path. For example, in the timing **t1**, the wearable device **101** may identify a plurality of characters arranged along one line, such as “hello”. That the wearable device **101** identifies the plurality of characters may be performed by the wearable device **101** and/or an external electronic device (e.g., a terminal **120** of FIG. **1**) connected to the wearable device **101**. The wearable device **101** may display a virtual object **1131** representing the plurality of characters in the portion **1120** of the displaying area based on identifying the plurality of characters. The virtual object **1131** may have a shape of a path of the external object **130** contacting the plane **1110**.

(157) Referring to FIG. **11**, the wearable device **101** may identify a gesture indicating to add a line in which the plurality of characters are arranged based on the motion of the external object **130**. In the state of FIG. **11** that identifies the alphabets, the wearable device **101** may identify the plurality characters recorded along the direction from left to right. In the above state, the wearable device **101** may recognize a new character represented by the path of the external object **130** by using a second line different from a first line in which the plurality of characters are arranged based on identifying the external object **130** moved from right to left. Referring to timing **t2**, the wearable device **101** may identify written characters (“WORLD”) along a direction from the left to the right of the plane **1110** in the plane **1110**. The wearable device **101** may display a virtual object **1132** on which characters “WORLD” are disposed in the portion **1120**, in a line different from the line in which the identified characters (“hello”) are disposed in the timing **t1**, in the timing **t2**. Similarly, between the timing **t2** and timing **t3**, based on identifying the external object **130** moving back to the left of the plane **1110**, the wearable device **101** may add the characters “glasses” obtained by tracking the point P of the external object **130**, in a line different from the first line where the characters (“hello”) are disposed, and the second line where the characters (“WORLD”) are disposed. In a virtual object **1133** displayed in the portion **1120** within the displaying area of the wearable device **101** in the timing **t3**, each of characters (“hello”, “WORLD”, and “glasses”) may be displayed through three different lines.

(158) As described above, the wearable device **101** may identify a gesture indicating to add a line in which the plurality of characters are arranged, by comparing the direction in which the

characters are arranged with the direction of the external object **130**. For example, in case of a language in which characters are arranged from the left to the right in the line, such as English, the wearable device **101** may identify the gesture based on detecting the external object **130** moving from the right to the left. For example, in case of a language in which characters are arranged from the right to the left, such as Arabic, the wearable device **101** may identify the gesture based on identifying the external object **130** moving from the left to the right. Since the wearable device **101** add a line in which characters drawn by the external object **130** are arranged by using the direction of the external object **130**, the wearable device **101** may support recognizing characters arranged along a plurality of lines based on the plane **1110** having the size of a single line.

(159) FIGS. **12A** and **12B** illustrates an operation in which a wearable device executes an application based on information obtained by tracking an external object according to an embodiment of the disclosure. The wearable device **101** of FIG. **5** may include the wearable device **101** of FIGS. **12A** and **12B**. Hereinafter, it is assumed that a calendar application for storing the schedule is matched with the external object **130**. The wearable device **101** may identify an input indicating that the calendar application is registered as the external object **130** based on the operations of FIGS. **6A** to **6D** and/or **7**.

(160) Referring to FIG. **12A**, in a state **1201** in which the external object **130** matched with the calendar application is identified, the wearable device **101** may display an icon **1210** representing the calendar application in the displaying area. Together with the icon **1210**, the wearable device **101** may display a visual object indicating an attribute assigned to the external object **130** overlapping the external object **130**. In the state **1201** of FIG. **12A**, the wearable device **101** may display text **1220** (e.g., “account A”) indicating an account matched with the external object **130** among accounts registered in the calendar application, overlapping with the external object **130**.

(161) In the state **1201** of FIG. **12A**, the wearable device **101** may track a path of a portion of the external object **130** or at least one stroke drawn by a material included in the external object **130** based on the attribute assigned to the external object **130**. For example, in the state **1201** identifying the attribute set to track ink extended from one end (e.g., a pen tip of the external object **130**) of the external object **130**, the wearable device **101** may identify at least one stroke drawn by the ink. The wearable device **101** may identify a character (in an example of FIG. **12A**, “11/1 vacation”) expressed by the at least one stroke. The wearable device **101** may obtain the result of recognizing characters from the at least one stroke by using a terminal **120** and/or a server **122** connected to the wearable device **101**. For example, in order to reduce the amount of computation of the wearable device **101**, the wearable device **101** may request the terminal **120** and/or the server **122** to recognize characters from the strokes drawn by the ink. The reduction in the amount of computation of the wearable device **101** may reduce heat emitted from the wearable device **101**.

(162) In the state **1201** of FIG. **12A**, in which a character drawn by ink output from the external object **130** is identified, the wearable device **101** may identify an input indicating to select a button **1230** for executing the calendar application matched with the external object **130**. In response to the input, the wearable device **101** may execute the calendar application based on the characters (e.g., “11/1 vacation”) drawn by the ink. In an embodiment of the disclosure, the wearable device **101** may execute a function based on the characters by using the calendar application executed before the input. The wearable device **101** may execute a function associated with the identified text by executing the calendar application before receiving the input associated with the button **1230** based on identifying the character drawn by the external object **130**. For example, the wearable device **101** may add schedule data based on information included in the text **1220** in the account indicated by the text **1220** in the state that the calendar application is executed.

(163) Referring to FIG. **12B**, a state **1202** in which the wearable device **101** displays a window **1240** for adding schedule data is illustrated based on an input indicating to select the button **1230** in the state **1201** of FIG. **12A**. In the state **1202**, the wearable device **101** may display the window **1240** for adding schedule data based on characters identified in the state **1201**. In the window **1240**,

the wearable device **101** may display parameters (e.g., schedule title, and time) required to generate the schedule data. The wearable device **101** may change the parameters based on information (e.g., the characters) obtained by tracking the external object **130** in the state **1201**. For example, the parameter (e.g., a parameter having a field name of “schedule title”) included in the window **1240** and indicating the name of the schedule data may include some (e.g., “vacation”) of the characters identified in the state **1201**. For example, the parameter (e.g., a parameter having a field name of “time”) included in the window **1240** and representing the time of schedule data may include the date and/or time represented by some (e.g., “11/1”) of the characters identified in the state **1201**. Matching the characters identified in the parameters and the state **1201** may be performed by an engine (e.g., a natural language engine (NLU)) executed by the wearable device **101** and/or the server **122** for natural language processing.

(164) Referring to FIG. **12B**, the wearable device **101** may display a button **1242** for adding schedule data based on parameters displayed through the window **1240** in the window **1240**. In the button **1242**, the wearable device **101** may display designated text (e.g., “store”) for guiding the addition and/or storing of schedule data. In the window **1240**, the wearable device **101** may display a button **1244** (e.g., a button **1244** including designated text, such as “cancel”) for stopping adding the schedule data.

(165) In the state **1202** of FIG. **12B**, in response to an input indicating to select the button **1242**, the wearable device **101** may store schedule data based on parameters displayed through the window **1240** by executing the calendar application. Referring to FIG. **12B**, the schedule data may be shared in different electronic devices (e.g., the wearable device **101**, and the terminal **120**) used by the user **110**. For example, the terminal **120** connected to the wearable device **101** may display a visual object **1252** based on the schedule data in the screen **1250** displayed through the display of the terminal **120**.

(166) As described above, according to an embodiment of the disclosure, the wearable device **101** may obtain information for adding schedule data from the path of a portion of the external object **130** and/or from at least one stroke drawn by the external object **130**. In the states **1201** and **1202** in which the external object **130** and the calendar application are matched, the wearable device **101** may obtain the information by recognizing characters drawn by the external object **130**. Since the wearable device **101** adds the schedule data by using the information, it may obtain the computer readable information independently of communication with the external object **130**.

(167) FIG. **13** illustrates an operation in which a wearable device executes an application based on information obtained by tracking an external object according to an embodiment of the disclosure. The wearable device **101** of FIG. **5** may include the wearable device **101** of FIG. **13**.

(168) Referring to FIG. **13**, states **1301**, **1302**, **1303**, and **1304** in which the wearable device **101** executes a messenger application by using information obtained by tracking the external object **1330** are illustrated, according to an embodiment. In state **1301**, the wearable device **101** may display a list **1310** of applications installed in the wearable device **101**, similar to states **601** and **602** of FIG. **6A**. The wearable device **101** may identify an input indicating that the messenger application matched with the icon **1311** is matched with the external object **1330**, based on the icon **1311** dragged to the external object **1330** along the path **1320**, among the icons **1311**, **1312**, and **1313** included in the list **1310**. Based on the input, the wearable device **101** may switch from the state **1301** to the state **1302**.

(169) In the state **1302** of FIG. **13**, the wearable device **101** may display a window **1340** for receiving at least one parameter required to execute the messenger application. In the window **1340**, the wearable device **101** may display a list for selecting a counterpart to receive a message corresponding to the information obtained by tracking the external object **1330**. The list may be associated with a contact list stored in a memory (e.g., the memory **520** of FIG. **5**) of the wearable device **101**. It is assumed that the wearable device **101** has received an input indicating to select a user A in the window **1340** in the state **1302** of FIG. **13**. In the assumption, the wearable device **101**

may store an attribute indicating that external object **1330** matches the function of the messenger application for transmitting a message to the user A.

(170) Referring to FIG. **13**, in the state **1303** after registering the external object **1330** based on the state **1302**, the wearable device **101** may track the external object **1330** included in the displaying area. In the state **1303**, the wearable device **101** may display the icon **1311** representing an application matched with the external object **1330** and a text **1350** indicating the attribute assigned to the external object **1330** by overlapping with the external object **1330**. In the assumption, the wearable device **101** may display the text **1350** (e.g., “user A”) indicating a counterpart to receive a message including information obtained by tracking the external object **1330**. The embodiment is not limited thereto, and the wearable device **101** displays a shape based on the color of the icon **1311** and/or the color of the external object **1330** by overlapping with the external object **1330**, such as shapes **832** and **834** of FIGS. **8A** and **8B**.

(171) In the state **1303** of FIG. **13**, the wearable device **101** may identify one or more strokes (e.g., handwriting expressing “message”) drawn by ink outputted from the point A. The wearable device **101** may identify text corresponding to the one or more strokes based on the OCR. In the state **1303**, the wearable device **101** may display a button **1355** for executing an application (e.g., a messenger application) by using information obtained by tracking external object **1330**. In response to an input indicating to select the button **1355**, the wearable device **101** may switch from the state **1303** to the state **1304**.

(172) Referring to FIG. **13**, in the state **1304**, the wearable device **101** may display the window **1360** provided from the messenger application corresponding to the external object **1330**. In the window **1360**, the wearable device **101** may display information obtained by tracking the external object **1330**. For example, the wearable device **101** may guide that text identified from the strokes drawn by the external object **1330** (e.g., “message”) will be transmitted to the counterpart (e.g., “user A”) indicated by the attribute assigned to the external object **1330** by using the window **1360**. The wearable device **101** may display a button **1372** for transmitting a message based on the information included in the window **1360** and a button **1375** for stopping transmission of the message in the displaying area, together with the window **1360**. In the button **1372**, the wearable device **101** may display designated text (e.g., “transmission”) for guiding the transmission of the message. In a button **1374**, the wearable device **101** may display designated text (e.g., “cancel”) for guiding the stop of message transmission. For example, in response to an input indicating to select the button **1372**, the wearable device **101** may execute a function for transmitting a message among the functions supported by the messenger application based on the information included in the window **1360**. The wearable device **101** may control a communication circuit (e.g., the communication circuit **550** of FIG. **5**) to transmit a message.

(173) As described above, according to an embodiment of the disclosure, the wearable device **101** may obtain information used to transmit a message by using the messenger application by tracking the external object **1330** matched with the messenger application. For example, the wearable device **101** may obtain text to be included in the message from at least one character drawn by the external object **1330**. The wearable device **101** may execute a function for transmitting a message including the text to the counterpart indicated by the attribute assigned to the external object **1330** by using the communication circuit of the wearable device **101**.

(174) FIG. **14** illustrates an operation in which a wearable device executes an application based on information obtained by tracking an external object according to an embodiment of the disclosure.

(175) Referring to FIG. **14**, the wearable device **101** of FIG. **5** may include the wearable device **101** of FIG. **14**. Hereinafter, it is assumed that a recording application for recording an audio signal is matched with the external object **1410**. The wearable device **101** may identify an input indicating to register the recording application as the external object **1410** based on the operations of FIGS. **6A** to **6D** and/or **7**.

(176) Referring to FIG. **14**, different states **1401** and **1402** in which the wearable device **101** tracks

the external object **1410** are illustrated. In the state **1401**, the wearable device **101** identifying the external object **1410** may display an icon **1412** representing the recording application matched with the external object **1410** and/or a button **1414** for recording the audio signal based on the execution of the recording application by overlapping with the external object **1410** in the displaying area. In the state **1401**, in response to an input indicating to select the button **1414**, the wearable device **101** may execute the recording application. Based on the execution of the recording application, the wearable device **101** may initiate recording of the audio signal. In order to record the audio signal, the wearable device **101** may include a microphone.

(177) Referring to FIG. **14**, in a state **1402** of recording the audio signal based on the execution of the recording application, the wearable device **101** may display text **1420** indicating the name of a file including the recorded audio signal, by overlapping with the external object **1410** included in the displaying area. In the state **1402**, the wearable device **101** may track the external object **1410** matched to the recording application. For example, the wearable device **101** may identify a handwriting (“bookmark”) drawn by the external object **1410**. Information obtained by tracking the external object **1410** by the wearable device **101** may include text corresponding to the handwriting. For example, the information may include a result of performing OCR on the handwriting.

(178) In the state **1402** of FIG. **14**, based on identifying handwriting drawn by the external object **1410**, the wearable device **101** may add the bookmark in the audio signal recorded by the execution of the recording application. For example, the wearable device **101** may add the bookmark to the section corresponding to the timing at which the handwriting is drawn in the audio signal recorded by the recording application. The bookmark may be stored in metadata corresponding to the audio signal. The name of the bookmark may include text corresponding to the handwriting.

(179) Referring to FIG. **14**, an example of a screen **1430** displayed while playing the audio signal obtained in the state **1402** is illustrated. The screen **1430** may be displayed by the wearable device **101** in response to an input instructing to play the audio signal. In an embodiment of the disclosure, the wearable device **101** may obtain text representing speech included in the audio signal by performing speech-to-text (STT) on the audio signal. In a portion **1432** of the screen **1430**, the wearable device **101** may display the obtained text. The wearable device **101** may display the text (e.g., “I’m going to write with an object”) included in the section corresponding to the timing at which the handwriting is drawn in the state **1402** among the text displayed in the screen **1430** together with a visual object **1434** indicating the bookmark added by the handwriting. For example, the visual object **1434** may have a shape of a bounding box for distinguishing text (e.g., “I’m going to write with an object”) recognized from a portion of the audio signal corresponding to the section from other text. Based on an input indicating to select the visual object **1434**, the wearable device **101** may display an attribute of the bookmark (e.g., a name of the bookmark) corresponding to the visual object **1434** in the displaying area.

(180) As described above, according to an embodiment of the disclosure, the wearable device **101** may execute different functions of the recording application by tracking the external object **1410** matched to the recording application. For example, the wearable device **101** may execute a recording function based on the recording application based on the button **1414** displayed by overlapping with the external object **1410**. For example, the wearable device **101** may execute a function for adding the bookmark to the audio signal recorded by the recording application based on information obtained by tracking the external object **1410**.

(181) FIGS. **15A** and **15B** illustrate an operation in which a wearable device executes a plurality of applications based on information obtained by tracking an external object according to an embodiment of the disclosure. The wearable device **101** of FIG. **5** may include the wearable device **101** of FIGS. **15A** and **15B**. Hereinafter, it is assumed that a plurality of applications (e.g., a note application and a recording application) are matched with the external object **1510**. The wearable device **101** may identify an input indicating that the plurality of applications are registered as the

external object **1510** based on the operations of FIGS. 6A to 6D and/or 7.

(182) Referring to FIG. 15A, different states **1501** and **1502** in which the wearable device **101** tracks the external object **1510** are illustrated. In the state **1501**, the wearable device **101** identifying the external object **1510** may display icons **1512** and **1514**, which represent each of a plurality of applications matched with the external object **1510** by overlapping with the external object **1510** included in the displaying area. For example, the wearable device **101** may display the icon **1512** representing the note application and the icon **1514** representing the recording application. In the state **1501**, the wearable device **101** may identify a curve drawn by the external object **1510** from a point P1 along a point P2. The curve may be a visualization of a path of a portion of the external object **1510** by the wearable device **101**. The curve may be drawn by ink in the external object **1510**.

(183) Referring to FIG. 15A, in the state **1501** in which a curve drawn by the external object **1510** is identified, the wearable device **101** may execute the plurality of applications matched with the external object **1510**. For example, the wearable device **101** may execute the note application and the recording application. Based on the execution of the recording application, the wearable device **101** may initiate recording of an audio signal. Based on the execution of the note application, the wearable device **101** may identify digital content based on the identified curve. For example, based on execution of the recording application, in the state **1501**, the wearable device **101** may obtain the audio signal including a speech **1521**.

(184) Referring to FIG. 15A, in the state **1502**, similar to the state **1501**, the wearable device **101** may maintain tracking the curve drawn by the external object **1510**. The wearable device **101** may maintain recording based on execution of the recording application in the state **1502**. The wearable device **101** may identify another curve drawn by the external object **1510** from the point P2 along a point P3 in the state **1502**. The wearable device **101** may obtain the audio signal including a speech **1522** based on the recording application in the state **1502**.

(185) According to an embodiment of the disclosure, the wearable device **101** may obtain first media content including curves moved along the points P1, P2, and P3 based on the states **1501** and **1502**. The first media content may be obtained based on execution of the note application among a plurality of applications matched with the external object **1510**. The wearable device **101** may obtain second media content in which the speeches **1521** and **1522** are recorded based on the states **1501** and **1502**. The second media content may be obtained based on execution of the recording application among a plurality of applications matched to the external object **1510**. The first media content and the second media content may be stored in a memory (e.g., the memory **520** of FIG. 5) of the wearable device **101**.

(186) According to an embodiment of the disclosure, the wearable device **101** may synchronize the first media content and the second media content obtained by executing each of a plurality of applications matched with the external object **1510**. Referring to FIG. 15A, after the states **1501** and **1502**, the wearable device **101** may display a screen **1530** for synchronizing the first media content and the second media content. The screen **1530** may be displayed through the displaying area formed by a display device (e.g., the display **530** of FIG. 5) of the wearable device **101**. The screen **1530** may be provided from at least one of the note application or the recording application matched with the external object **1510**.

(187) Referring to FIG. 15A, in the screen **1530**, the wearable device **101** may display a visual object **1540** corresponding to first media content obtained based on the execution of the note application. For example, the visual object **1540** may be a line representing a path of a portion of the external object **1510** moved along the points P1, P2, and P3 in the states **1501** and **1502**. Based on the screen **1530** on which the visual object **1540** corresponding to the first media content is displayed, the wearable device **101** may execute a function for synchronizing the first media content and the second media content. The function for synchronizing the first media content and the second media content may include an operation of simultaneously playing a line (e.g., a line

representing a path of the external object **1510**) included in the first media content and the audio signal included in the second media content.

(188) Referring to FIG. **15A**, in the screen **1530**, the wearable device **101** may display visual objects **1551** and **1552** corresponding to different sections of the second media content. The visual object **1551** may correspond to a first section in which the speech **1521** is recorded in the second media content. The visual object **1552** may correspond to a second section in which the speech **1522** is recorded in the second media content. The wearable device **101** may display the visual object **1551** corresponding to the first section in a line included in the visual object **1540**, adjacent to a portion of a line drawn in the first section. The wearable device **101** may display the visual object **1552** corresponding to the second section in a line included in the visual object **1540**, adjacent to a portion of a line drawn in the second section. As described above, according to an embodiment of the disclosure, the wearable device **101** may synchronize a line included in the first media content and an audio signal included in the second media content based on a section in the screen **1530**.

(189) According to an embodiment of the disclosure, the wearable device **101** may simultaneously play the first media content and the second media content. For example, while playing a first animation that draws a curve along the points **P1** and **P2** in the screen **1530**, the wearable device **101** may play an audio signal (e.g., an audio signal including the speech **1521**) corresponding to the visual object **1551**. After playing the first animation, while playing a second animation that draws a curve along the points **P2** and **P3** in the screen **1530**, the wearable device **101** may play an audio signal (e.g., an audio signal including the speech **1522**) corresponding to the visual object **1552**.

(190) As described above, the wearable device **101** may obtain a plurality of media contents by using each of the plurality of applications in a state in which a plurality of applications are matched with the external object **1510**. In the states **1501** and **1502** of FIG. **15A**, the wearable device **101** may obtain different types of media content (e.g., the first media content including the visualized stroke, and the second media content including the audio signal). The wearable device **101** may synchronize the plurality of media contents obtained substantially simultaneously.

(191) Referring to FIG. **15B**, a state **1503** in which the wearable device **101** simultaneously executes a plurality of applications matched with an external object **1510** is illustrated. The wearable device **101** may register the plurality of applications as the external object **1510** based on the operations of FIGS. **6A** to **6D** and/or **7**. Hereinafter, it is assumed that the plurality of applications include the note application corresponding to the icon **1512** and the recording application corresponding to the icon **1514**.

(192) Referring to FIG. **15B**, the wearable device **101** may execute a plurality of applications matched with the external object **1510** in the state **1503** in which a curve drawn by the external object **1510** is identified. For example, in the state **1503** identifying the path of a portion of external object **1510**, or the curve drawn by a material (e.g., ink and/or graphite) included in external object **1510**, the wearable device **101** may execute the plurality of applications in response to an input indicating selection of a visual object **1560**. Referring to FIG. **15B**, the visual object **1560** having the shape of a button including a designated text, such as “done” is exemplarily illustrated in the displaying area of the wearable device **101**, but the embodiment is not limited thereto.

(193) In the state **1503** of FIG. **15B**, the wearable device **101** may display a multi-window **1570** in which screens **1571** and **1572** provided from each of the plurality of applications assigned to the external object **1510** are arranged. The screens **1571** and **1572** may be displayed on at least a portion of the displaying area of the wearable device **101**. Referring to FIG. **15B**, a case in which the wearable device **101** displays the screens **1571** and **1572** coupled in parallel in a vertical direction is illustrated. The embodiment is not limited thereto, and the wearable device **101** may display the screens **1571** and **1572** along a direction (e.g., a horizontal direction **1573**) different from the vertical direction. The wearable device **101** may display the screens **1571** and **1572** on portions spaced apart from each other in the displaying area.

(194) Referring to FIG. 15B, based on the assumption, the wearable device **101** may display the screen **1571** corresponding to the recording application and the screen **1572** corresponding to the note application. The wearable device **101** may obtain an audio signal obtained while tracing the external object **1510** or a curve drawn by the external object **1510** in the screen **1571**. In a case in which the audio signal includes a speech **1523**, the wearable device **101** may display text for the speech **1523** on the screen **1571**. The wearable device **101** may display an image representing the curve in the screen **1572**.

(195) As described above, according to an embodiment of the disclosure, the wearable device **101** may execute a plurality of applications assigned to the external object **1510** substantially simultaneously based on multi-tasking. The wearable device **101** may display the multi-window in which the screens **1571** and **1572** provided from the plurality of applications are arranged. The wearable device **101** may execute one or more functions for obtaining digital content based on the external object **1510** that does not include a communication circuit, by using the multi-window.

(196) Hereinafter, referring to FIG. 16, an operation in which the wearable device **101** according to an embodiment executes applications matched with the external object by using the external object will be described.

(197) FIG. 16 illustrates a flowchart for a wearable device according to an embodiment of the disclosure. A wearable device **101** of FIG. 5 may include the wearable device of FIG. 16. For example, the operations of FIG. 16 may be performed by the wearable device **101** and/or the processor **510** of FIG. 5. The operations of FIG. 16 may be associated with the operations of the wearable device **101** described above with reference to FIGS. 8A, 8B, 9A to 9C, 10, 11, 12A, 12B, 13, 14, 15A, and 15B. The operations of FIG. 16 be associated with at least one (e.g., an operation **220** of FIG. 2) of the operations of FIG. 2 and/or the operations of FIG. 7.

(198) Referring to FIG. 16, in operation **1610**, according to an embodiment of the disclosure, the wearable device may identify an external object included in the displaying area. The wearable device may identify the external object registered as the wearable device based on information stored in a memory (e.g., the memory **520** of FIG. 5). The information may include data indicating the shape, color, and/or size of the external object registered as the wearable device. The wearable device may identify the external object based on frames obtained from the camera (e.g., a motion recognition camera **340-2** of FIG. 3B, cameras **440-9** and **440-10** of FIG. 4B, and/or a camera **540** of FIG. 5) that overlap at least partially with the displaying area of the wearable device. That the wearable device identify the external object may include identifying at least one attribute assigned to the external object.

(199) Referring to FIG. 16, in operation **1620**, according to an embodiment of the disclosure, the wearable device may display the first visual object representing the application corresponding to the external object based on the location of the external object in the displaying area. The first visual object may be displayed to emphasize the external object identified based on the operation **1610**. The first visual object may include, for example, FIGS. **830** and **840** of FIG. 8A and icons **832** and **842**. The first visual object may include text (e.g., a name assigned to the application) indicating the application.

(200) Referring to FIG. 16, in operation **1630**, according to an embodiment of the disclosure, the wearable device may obtain at least one of first information associated with the motion of the external object or second information including an image drawn by the external object. For example, the wearable device may obtain the first information including at least partially a path of a portion (e.g., a point **P** of FIG. 9A) of the external object indicated by the attribute assigned to the external object. The first information may include a path of a portion of the external object contacted on one plane (e.g., a plane formed by the note **910** of FIG. 9A). For example, the wearable device may obtain the second information including at least one stroke drawn by a material (e.g., ink and/or graphite) outputted from the external object based on the attribute assigned to the external object. For example, the at least one stroke may be referred to as at least

one stroke drawn by the external object.

(201) Referring to FIG. 16, in operation 1640, according to an embodiment of the disclosure, the wearable device may select any one of the first information or the second information based on the attribute assigned to the external object and may display a second visual object for executing an application by using the selected information. The second visual object may include a buttons 940 of FIGS. 9A to 9C. According to an embodiment of the disclosure, the wearable device may selectively obtain any one of the first information or the second information of the operation 1630 by using the attribute assigned to the external object. After the operation 1640, the wearable device may execute the application based on the selected information in response to an input indicating to select the second visual object. Based on execution of the application, the wearable device may execute a function of the application based on the selected information.

(202) As described above with reference to FIGS. 6A, 6B, 7, 8A, 8B, 9A to 9C, 10, 11, 12A, 12B, 13, 14, 15A, 15B, and 16, the wearable device according to an embodiment may require an input for registering the external object in order to execute the application based on the external object. However, the embodiment is not limited thereto. Hereinafter, referring to FIGS. 17 and 18, an example of an operation in which the wearable device according to an embodiment identifies the external object independently of the input and executes at least one application corresponding to the identified external object will be described.

(203) FIG. 17 illustrates an operation in which a wearable device displays a UI for recommending at least one application based on information obtained by tracking an external object according to an embodiment of the disclosure. The wearable device 101 of FIG. 5 may include the wearable device 101 of FIG. 17.

(204) Referring to FIG. 17, according to an embodiment of the disclosure, a state 1701 in which the wearable device 101 identifies an external object 1705 included in the displaying area is illustrated. Hereinafter, it is assumed that the state 1701 is a state before the wearable device 101 receives an input indicating to register the external object 1705 described above with reference to FIGS. 6A to 6D and/or 7. For example, in the state 1701, the wearable device 101 may not be able to identify information that matches the shape, color, and/or size of the external object 1705 included in the displaying area. In the state 1701 in which the external object 1705 is not registered as the wearable device 101, the wearable device 101 may identify a category of the external object 1705. In case that the external object 1705 is classified into a designated category corresponding to a pen including a material, such as ink and/or graphite, the wearable device 101 may identify at least one stroke drawn by the external object 1705. For example, the wearable device 101 may identify analog content drawn by the external object 1705 on a note 1710. For example, as the external object 1705 is moved on the note 1710 by a hand 140 holding the external object 1705, the wearable device 101 is attached on the note 1710 and may identify traces of ink outputted from the external object 1705.

(205) In the state 1701 of FIG. 17, the wearable device 101 may identify the text 1712 drawn on the note 1710 by the external object 1705. The wearable device 101 is obtained from a camera (e.g., a camera 540 of FIG. 5) and may identify the text 1712 based on an image including the note 1710. For example, the wearable device 101 may identify the text 1712 by performing OCR on the image. According to an embodiment of the disclosure, the wearable device 101 may recommend a user 110 to execute at least one of a plurality of applications installed in wearable device 101 based on the information included in the text 1712 generated by the external object 1705. For example, the wearable device 101 may select at least one application to be recommended to the user 110 based on whether the text 1712 includes characters arranged along the format included in Table 2. “#” in Table 2 may mean a number between 0 and 9.

(206) TABLE-US-00002 TABLE 2 Format Applications to be recommended #####-##-## Calendar application #month #date Date format, such as #####year #month #date and the like ## hour ## minute or ##:## Reminder (or alarm) application Formula including arithmetic Calculator

application operators Numbers including monetary units Payment application Non-textual information, including Note application pictures Textual information that does not Note application correspond to the above format

(207) Referring to Table 2, the wearable device **101** may recommend the execution of the calendar application based on identifying handwriting recorded according to notation of the related art for recording dates. The wearable device **101** may recommend the execution of the reminder application based on handwriting recorded according to the customary notation for recording time. Referring to FIG. 17, since the text **1712** has a format of formula including an addition operator (+), the wearable device **101** may recommend the calculator application based on the text **1712**.

(208) In the state **1701** of FIG. 17, the wearable device **101** may display an icon **1721** representing the calculator application by overlapping with the external object **1705** included in the displaying area. The wearable device **101** may display another icon representing another application installed in the wearable device **101** together with the icon **1721** corresponding to the calculator application. For example, the wearable device **101** may sequentially display one or more icons representing the application recently executed by the wearable device **101** together with the icon **1721** of the application selected based on the text **1712**.

(209) Referring to FIG. 17, the state **1701** in which the wearable device **101** sequentially displays a plurality of icons **1721**, **1722**, **1723**, and **1734** is illustrated. Among the icons **1721**, **1722**, **1723**, and **1724**, the wearable device **101** may dispose the icon **1721**, which corresponds to the calculator application recommended based on the text **1712**, closest to a portion (e.g., a portion where ink is outputted from the external object **1705**, such as a pen tip) of the external object **1705**.

(210) According to an embodiment of the disclosure, the order in which the wearable device **101** displays icons **1721**, **1722**, **1723**, and **1724** on the external object **1705** may be associated with the order executed by the wearable device **101**. For example, the order of icons **1722**, **1723**, and **1724** except for the icon **1721** corresponding to the calculator application recommended based on the text **1712** may correspond to the order of applications recently executed by the wearable device **101**. For example, in case that the wearable device **101** does not recommend any application, the wearable device **101** may display icons for a plurality of recently executed applications.

(211) Referring to FIG. 17, the wearable device **101** may arrange icons **1721**, **1722**, **1723**, and **1724** based on the shape of the external object **1705** shown through the displaying area. For example, the icons **1721**, **1722**, **1723**, and **1724** may be arranged along a direction in which the external object **1705** extends in the displaying area. The number of icons **1721**, **1722**, **1723**, and **1724**, which overlap on the external object **1705**, may be associated with the length of the external object **1705** shown through the displaying area and the size of each of the icons **1721**, **1722**, **1723**, and **1724**. The number of icons displayed together with the external object **1705** may have a designated upper limit or may be adaptively changed based on the length of the external object **1705** shown through the displaying area.

(212) Referring to FIG. 17, in the state **1701** in which applications are recommended by using the icons **1721**, **1722**, **1723**, and **1724**, the wearable device **101** may identify an input indicating to execute at least one of the recommended applications. For example, the wearable device **101** may execute the calculator application corresponding to the icon **1721**, in response to an input indicating to select the icon **1721**. The wearable device **101** may output a result of the formula, by executing the calculator application based on the formula included in the text **1712**. The result may be visually displayed in the displaying area of the wearable device **101** and/or may be outputted in the form of an audio signal through a speaker of the wearable device **101**.

(213) Referring to FIG. 17, in a state **1702** after executing the calculator application, the wearable device **101** may display a window **1740** for registering the external object **1705**. In the window **1740**, the wearable device **101** may display text (e.g., "Do you want to register a calculator with this pen?") for guiding whether to register the calculator application. In the window **1740**, the wearable device **101** may display a button **1742** for registering the calculator application and a

button **1746** for stopping the display of the window **1740**. In response to an input indicating to select the button **1742**, the wearable device **101** may register the external object **1705**. In the state of registering the external object **1705**, the wearable device **101** may store information for executing the calculator application based on the external object **1705**.

(214) As described above, according to an embodiment of the disclosure, the wearable device **101** may identify the analog content drawn by the external object **1705** in the state **1701** in which the external object **1705**, such as the pen is identified. In case that the external object **1705** is not registered, the wearable device **101** may recommend execution of at least one application based on the digital content converted from the analog content. The wearable device **101** may enhance user experience associated with the external object **1705**, such as the pen, by recommending the execution of the application.

(215) FIG. **18** illustrates a flowchart for a wearable device according to an embodiment of the disclosure. A wearable device **101** of FIG. **5** may include the wearable device of FIG. **18**. For example, the operations of FIG. **18** may be performed by the wearable device **101** and/or a processor **510** of FIG. **5**. The operations of FIG. **18** may be associated with the operations of the wearable device **101** described above with reference to FIG. **17**. The operations of FIG. **18** may be associated with the operations of FIGS. **2**, **7** and/or **16**.

(216) Referring to FIG. **18**, in operation **1810**, according to an embodiment of the disclosure, the wearable device may identify an external object for drawing one or more strokes. The external object may be another external object different from the external object registered in the wearable device, such as an external object **1705** of FIG. **17**. The wearable device may identify the external object by using a camera (e.g., a camera **540** of FIG. **5**) in the wearable device. For example, the wearable device may identify the external object including the pen.

(217) Referring to FIG. **18**, in operation **1820**, according to an embodiment of the disclosure, the wearable device may identify media content indicated by one or more strokes adjacent to the external object. The wearable device may identify the one or more strokes drawn on the external object by tracking the motion of the external object. The wearable device may obtain an image including the one or more strokes by using the camera in the wearable device. The wearable device may identify the media content by performing OCR on the obtained image. The media content identified by the wearable device may include text and/or images indicated by the one or more strokes.

(218) Referring to FIG. **18**, in operation **1830**, according to an embodiment of the disclosure, the wearable device may determine whether media content of a designated type is identified. For example, the wearable device may identify whether text arranged according to a designated format of Table 2 is included in the media content. The designated type of the operation **1830** may be associated with the designated format of Table 2. For example, the designated type may be set to identify at least one application corresponding to the media content identified by the wearable device.

(219) In case that the media content of the designated type is identified (in operation **1830-YES**), based on operation **1840**, the wearable device may display at least one icon including an icon representing an application corresponding to the designated type. For example, like an icon **1721** of FIG. **17**, the wearable device may display an icon for guiding the execution of the application corresponding to the designated type. The wearable device may display icons representing other applications recently executed by the wearable device together with an icon representing the application corresponding to the designated type. The icons displayed by the wearable device may be displayed by overlapping with the external object in the displaying area. Since the icons are displayed by overlapping with the external object, the wearable device may prevent the media content from being covered by the icons. For example, the wearable device may maintain the visibility of the media content by superimposing and displaying the icons on the external object.

(220) In case that the designated type of media content is not identified (in operation **1830-NO**), the

wearable device may display at least one icon based on the history in which the applications have been executed, by perform operation **1850**. For example, the wearable device may display icons representing a designated number of applications recently executed by the wearable device. In the displaying area, the wearable device may display the icons by overlapping with the external object. In case that the external object, such as the pen, has a shape extended along a length direction, the wearable device may arrange the icons along the length direction in the displaying area.

(221) As described above, according to an embodiment of the disclosure, the wearable device may recognize the external object independently of an operation of electrically communicating with the external object. Based on the recognition of the external object, the wearable device may execute a function of generating digital content based on the external object. The embodiment is not limited thereto, and the wearable device may obtain information used for execution of an application installed on the wearable device by communicating with the external object. Hereinafter, an example of an operation in which the wearable device communicates with the external object according to an embodiment will be described with reference to FIG. **19**.

(222) FIG. **19** illustrates an operation in which a wearable device executes an application based on information obtained by an external electronic device according to an embodiment of the disclosure. The wearable device **101** of FIG. **5** may include the wearable device **101** of FIG. **19**.

(223) Referring to FIG. **19**, states **1901**, **1902**, and **1903** after the wearable device **101** identifies the external electronic device **1920** according to an embodiment are illustrated. Hereinafter, the external electronic device **1920** having the form of a smart watch on a user's hand **1915** will be described as an example, but the embodiment is not limited thereto. For example, the wearable device **101** may be connected to the external electronic device **1920**, such as a smart ring or a stylus. The wearable device **101** may identify the external electronic device **1920** based on a wireless communication protocol, such as Bluetooth. The wearable device **101** may identify the external electronic device **1920** by using a camera (e.g., a camera **540** of FIG. **5**) having an FoV that at least partially overlaps with the displaying area.

(224) In state **1901** of FIG. **19**, the wearable device **101** may display a list **1910** of applications installed in the wearable device **101** similarly to states **601** and **602** of FIG. **6A**. Among the icons **1911**, **1912**, and **1913** included in the list **1910**, the wearable device **101** may identify the icon **1913** dragged on the external electronic device **1920** dragged along the path **1930**. Based on an input of dragging the icon **1913** along the path **1930**, the wearable device **101** may assign a note application corresponding to the icon **1913** to the external electronic device **1920**.

(225) Referring to FIG. **19**, a state **1902** after the wearable device **101** assigns the note application to the external electronic device **1920** is illustrated. In the state **1902**, the wearable device **101** may display the icon **1913** representing the note application assigned to the external electronic device **1920** in a portion of the displaying area adjacent to the external electronic device **1920**. In the state **1902**, the wearable device **101** may track the motion of the external electronic device **1920** by using the camera. For example, the wearable device **101** may identify the motion of the external electronic device **1920** moving along a path **1940**. The wearable device **101** may identify the two-dimensional motion of the external electronic device **1920** from the frames of the camera.

According to an embodiment of the disclosure, the wearable device **101** may identify the motion three-dimensionally by electrically communicating with the external electronic device **1920**. For example, in the state **1902**, the wearable device **101** may request information identified by a sensor (e.g., an inertial measurement unit (IMU)) in external electronic device **1920** to the external electronic device **1920**. The information may include a three-dimensional motion of the external electronic device **1920** moved along the path **1940**. Based on the information received from the external electronic device **1920**, the wearable device **101** may identify the three-dimensional motion of the external electronic device **1920**.

(226) Referring to FIG. **19**, the state **1903** after executing the note application based on the information obtained by tracking the external electronic device **1920** is illustrated. In the state

1902, the wearable device **101** may switch from the state **1902** to the state **1903** based on an input for selecting a button **1950** for executing the note application. In the state **1903**, the wearable device **101** may display a screen **1960** for storing digital content based on information obtained by tracking the external electronic device **1920**, by executing the note application. In the screen **1960**, the wearable device **101** may display a visual object **1962** representing the motion of the external electronic device **1920** moved along the path **1940**. Since the wearable device **101** identified the three-dimensional motion of the external electronic device **1920** moved along the path **1940** by using the sensor of the external electronic device **1920**, the wearable device **101** may three-dimensionally display the visual object **1962**.

(227) In the state **1903** of FIG. **19**, the wearable device **101** may display the screen **1960** for three-dimensionally browsing the visual object **1962** based on axes (x-axis, y-axis, and z-axis). For example, based on the axes, the wearable device **101** may identify an input for rotating the visual object **1962**. Based on the input, the wearable device **101** may provide a user experience of viewing the visual object **1962** in a three-dimensional spatial coordinate system by rotating or moving the visual object **1962**. The wearable device **101** may display a button **1964** for storing digital content corresponding to the visual object **1962** in the screen **1960**. Based on an input indicating to select the button **1964**, the wearable device **101** may store information for displaying the path **1940** in three dimensions, such as the visual object **1962**, in memory.

(228) As described above, the wearable device **101** according to an embodiment may support registering the external electronic device **1920**. By using the sensor included in the external electronic device **1920**, the wearable device **101** may enhance information obtained by tracking the external electronic device **1920**. For example, by using the sensor included in the external electronic device **1920**, the wearable device **101** may enhance information obtained by using a camera.

(229) In an embodiment of the disclosure, a method for a wearable device to execute an application installed in the wearable device, by recognizing the motion of an external object or analog content drawn by an external object may be required. As described above, a wearable device (e.g., a wearable device **101** of FIGS. **1** and/or **5**) according to an embodiment may comprise a display (e.g., a display **530** of FIG. **5**), a camera (e.g., a camera **540** of FIG. **5**), and a processor (e.g., a processor **510** of FIG. **5**). The processor may be configured to identify, by using the camera, an external object (e.g., an external object **130** of FIG. **1**) included in a displaying area of the display. The processor may be configured to display a first visual object (e.g., an icon **160** of FIG. **1**) representing an application corresponding to the external object based on a location of the external object in the displaying area. The processor may be configured to obtain, while displaying the first visual object, at least one of first information associated with a path of the external object moved on a plane, or second information including at least one stroke drawn by the external object. The processor may be configured to display, based on the location, a second visual object (e.g., a button **940** of FIG. **9A**) for executing the application by using information that is identified among the first information or the second information according to an attribute assigned to the external object. According to an embodiment of the disclosure, the wearable device may execute the application installed in the wearable device by using the information obtained by tracking the external object.

(230) For example, the processor may be configured to obtain the first information by tracking the path based on whether a portion of the external object indicated by the attribute is contact to the plane.

(231) For example, the processor may be configured to display one or more lines having a shape of the tracked path in the display.

(232) For example, the processor may be configured to identify, while tracking the path by using the camera which is a first camera, that the external object is moved outside of the displaying area by motion of the wearable device. The processor may be configured to track a path of the external object by using a second camera toward the external object moved outside of the displaying area.

The processor may be configured to display a line having a shape of the path tracked by the second camera, in the display.

(233) For example, the processor may be configured to display one or more lines having at least one of color, opacity or thickness set by the attribute, in the display.

(234) For example, the processor may be configured to obtain, based on the attribute set to tracking the at least one stroke drawn by an ink extended from an end of the external object, the second information among the first information or the second information.

(235) For example, the processor may be configured to execute, in response to an input indicating to select the second visual object, the application by using the information identified according to the attribute.

(236) For example, the processor may be configured to display, by executing the application based on the second visual object, a screen including an image indicated by the information identified according to the attribute in the display.

(237) For example, the electronic device may further comprise a communication circuit. The processor may be configured to transmit to an external electronic device indicated by the second visual object through the communication circuit, a message including text indicated by the information identified according to the attribute by executing the application based on the second visual object.

(238) For example, the processor configured to obtain, by executing the application based on the second visual object, schedule data based on text indicated by the information identified according to the attribute.

(239) As described above, a method of a wearable device according to an embodiment may comprise displaying, in a display of the wearable device, list of a plurality of applications stored in a memory of the wearable device. The method may comprise obtaining, based on an input indicating overlapping a visual object representing a first application included in the list on an external object included in a displaying area of the display, an attribute for executing the first application by using the external object. The method may comprise obtaining, after obtaining the attribute, at least one of first information associated with a path of the external object moved on a plane, or second information including at least one stroke drawn by the external object. The method may comprise executing, the first application by using information identified by the attribute among the first information or the second information.

(240) For example, the obtaining the attribute may comprise displaying, in response to the input, a screen for receiving one or more attributes associated with the first application, in the displaying area.

(241) For example, the obtaining the attribute may comprise identifying, among both ends of the external object extended along a length direction, an end adjacent to the first visual object overlapped to the external object by the input.

(242) For example, the obtaining at least one of the first information or the second information may comprise obtaining the first information associated with the path of the identified end.

(243) For example, the executing may comprise executing the application based on text recognized from the information identified by the attribute among the first information or the second information.

(244) For example, the method may comprise displaying one or more lines having at least one of color, opacity or thickness set by the attribute, in the display.

(245) For example, the method may comprise obtaining, based on the attribute set to tracking the at least one stroke drawn by an ink extended from an end of the external object, the second information among the first information or the second information.

(246) As described above, a method of a wearable device according to an embodiment may comprise identifying, by using a camera of the wearable device, an external object included in a displaying area of a display of the wearable device. The method may comprise displaying a first

visual object representing an application corresponding to the external object based on a location of the external object in the displaying area. The method may comprise obtaining, while displaying the first visual object, at least one of first information associated with a path of the external object moved on a plane, or second information including at least one stroke drawn by the external object. The method may comprise displaying, based on the location, a second visual object for executing the application by using information that is identified among the first information or the second information according to an attribute assigned to the external object.

(247) For example, the obtaining may comprise obtaining the first information by tracking the path based on whether a portion of the external object indicated by the attribute is contact to the plane.

(248) For example, the obtaining the first information may comprise displaying one or more lines having a shape of the tracked path in the display.

(249) For example, the displaying the one or more lines may comprise identifying, while tracking the path by using the camera which is a first camera, that the external object is moved outside of the displaying area by motion of the wearable device. The method may comprise tracking a path of the external object by using a second camera toward the external object moved outside of the displaying area. The method may comprise displaying a line having a shape of the path tracked by the second camera, in the display.

(250) For example, the method may comprise executing, in response to an input indicating to select the second visual object, the application by using the information identified according to the attribute.

(251) For example, the executing may comprise displaying a screen including an image indicated by the information identified according to the attribute in the display.

(252) For example, the executing may comprise transmitting a message including text indicated by the information identified according to the attribute to an external electronic device indicated by the second visual object through a communication circuit of the wearable device.

(253) For example, the executing may comprise obtaining schedule data based on the text indicated by the information identified according to the attribute.

(254) As described above, according to an embodiment of the disclosure, a wearable device (e.g., a wearable device **101** of FIGS. **1** and/or **5**) may comprise a display (e.g., a display **530** of FIG. **5**), a memory (e.g., the memory **520** of FIG. **5**), and a processor (e.g., a processor **510** of FIG. **5**). The processor may be configured to display, in a display of the wearable device, list (e.g., a list **610** of FIGS. **6A** and **6B**) of a plurality of applications stored in a memory of the wearable device. The processor may be configured to obtain, based on an input indicating overlapping a visual object representing a first application included in the list on an external object (e.g., an external object **130** of FIG. **1**) included in a displaying area of the display, an attribute for executing the first application by using the external object. The processor may be configured to obtain, after obtaining the attribute, at least one of first information associated with a path of the external object moved on a plane, or second information including at least one stroke drawn by the external object. The processor may be configured to execute, the first application by using information identified by the attribute among the first information or the second information.

(255) For example, the processor may be configured to display a screen for receiving one or more attributes associated with the first application in the displaying area in response to the input.

(256) For example, the processor may be configured to identify, among both ends of the external object extended along a length direction, an end adjacent to the first visual object overlapped to the external object by the input.

(257) For example, the processor may be configured to obtain the first information associated with the path of the identified end.

(258) For example, the processor may be configured to execute the application based on text recognized from the information identified by the attribute among the first information or the second information.

(259) The apparatus described above may be implemented as a combination of hardware components, software components, and/or hardware components and software components. For example, the devices and components described in the embodiments may be implemented using one or more general purpose computers or special purpose computers, such as processors, controllers, arithmetical logic unit (ALU), digital signal processor, microcomputers, field programmable gate array (FPGA), programmable logic unit (PLU), microprocessor, any other device capable of executing and responding to instructions. The processing device may perform an operating system OS and one or more software applications performed on the operating system. In addition, the processing device may access, store, manipulate, process, and generate data in response to execution of the software. For convenience of understanding, although one processing device may be described as being used, a person skilled in the art may see that the processing device may include a plurality of processing elements and/or a plurality of types of processing elements. For example, the processing device may include a plurality of processors or one processor and one controller. In addition, other processing configurations, such as a parallel processor, are also possible.

(260) The software may include a computer program, code, instruction, or a combination of one or more of them and configure the processing device to operate as desired or command the processing device independently or in combination. Software and/or data may be embodied in any type of machine, component, physical device, computer storage medium, or device to be interpreted by a processing device or to provide instructions or data to the processing device. The software may be distributed on a networked computer system and stored or executed in a distributed manner. Software and data may be stored in one or more computer-readable recording media.

(261) The method according to the embodiment may be implemented in the form of program instructions that may be performed through various computer means and recorded in a computer-readable medium. In this case, the medium may continuously store a computer-executable program or temporarily store the program for execution or download. In addition, the medium may be a variety of recording means or storage means in which a single or several hardware are combined and is not limited to media directly connected to any computer system and may be distributed on the network. Examples of media may include magnetic media, such as hard disks, floppy disks and magnetic tapes, optical recording media, such as compact disc (CD)-ROMs and digital versatile discs (DVDs), magneto-optical media, such as floppy disks, ROMs, RAMs, flash memories, and the like to store program instructions. Examples of other media include app stores that distribute applications, sites that supply or distribute various software, and recording media or storage media managed by servers.

(262) While the disclosure has been shown and described with reference to various embodiments thereof, it will be understood by those skilled in the art that various changes in form and details may be made therein without departing from the described method or are substituted or substituted by other components or equivalents, appropriate results may be achieved. Therefore, other implementations, other embodiments, and scope of the disclosure as defined by the appended claims and their equivalents.

Claims

1. A wearable device comprising: at least one display, when the wearable device is worn by a user, positioned toward an eye of the user; at least one camera; at least one processor comprising processing circuitry; and memory, comprising one or more storage mediums, storing instructions, wherein the instructions, when executed by the at least one processor individually or collectively, cause the wearable device to: display a first screen using images representing a field of view (FOV) of the at least one camera; identify a defined object using the images representing the FOV of the at least one camera; based on the defined object identified in the FOV; obtain information indicating

movement of the defined object; identify a software application which is associated with the defined object; and based on the software application identified as associated with the defined object, display, within the first screen, an executable object indicating the software application; and in response to a user input on the executable object, display a second screen by executing the software application using the information.

2. The wearable device of claim 1, wherein the instructions, when executed by the at least one processor individually or collectively, cause the wearable device to: based on the defined object being in contact with a plane, obtain the information indicating a movement path of an end of the defined object being in contact with the plane.
3. The wearable device of claim 2, wherein the instructions, when executed by the at least one processor individually or collectively, cause the wearable device to: while obtaining the information, display one or more lines having a shape of the movement path superimposed on the first screen.
4. The wearable device of claim 1, wherein the at least one camera include a first camera and a second camera, and wherein the instructions, when executed by the at least one processor individually or collectively, cause the wearable device to: based on the information indicating the movement of the defined object in the FOV of the first camera, identify whether the defined object is moved outside of the first camera: based on the defined object identified as being moved outside of the FOV of the first camera, identify the defined object in another FOV of the second camera; and based on the defined object identified in the other FOV, obtain the information indicating the movement of the defined object within the other FOV.
5. The wearable device of claim 4, wherein the instructions, when executed by the at least one processor individually or collectively, cause the wearable device to: based on the defined object identified as being moved outside of the FOV of the first camera, display a third screen including at least portion of images representing the other FOV of the second camera.
6. The wearable device of claim 5, wherein the instructions, when executed by the at least one processor individually or collectively, cause the wearable device to: display the third screen including a first line indicating a trajectory of the defined object identified in the FOV, and a second line, which is connected to an end of the first line, indicating a trajectory of the defined object identified in the other FOV.
7. The wearable device of claim 4, wherein the instructions, when executed by the at least one processor individually or collectively, cause the wearable device to: based on the defined object identified in the FOV, identify at least one stroke drawn by an ink extended from an end of the defined object using the images obtained via the first camera.
8. The wearable device of claim 4, wherein the instructions, when executed by the at least one processor individually or collectively, cause the wearable device to: perform object recognition using the images; based on the object recognition performed while displaying the first screen, identify an external object in the FOV of the first camera; and based on the external object identified in the FOV, determine whether the external object is the defined object using another information stored in the memory indicating a shape of the defined object, wherein the other information further indicate the software application that is set to be associated with the defined object.
9. The wearable device of claim 1, further comprising: at least one communication circuitry, wherein the instructions, when executed by the at least one processor individually or collectively, cause the wearable device to: transmit, to an external electronic device indicated by the executable object through the at least one communication circuitry, a message including text indicated by the information using the software application executed by the user input.
10. The wearable device of claim 1, wherein the instructions, when executed by the at least one processor individually or collectively, cause the wearable device to: obtain, by using the software application on executed by the user input, schedule data based on text indicated by the information.

11. A method of a wearable device, the method comprising: displaying, in a display of the wearable device, list of a plurality of software applications stored in a memory of the wearable device; obtaining, based on an input indicating overlapping a visual object representing a first software application included in the list on an external object included in a displaying area of the display, an attribute for executing the first software application by using the external object; storing the attribute to be used to identify the external object as a defined object associated with the first software application; and after storing the attribute, executing the first software application based on identifying the defined object using images obtained by at least one camera of the wearable device.

12. The method of claim 11, wherein the obtaining of the attribute comprises: displaying, in response to the input, a screen for receiving one or more attributes associated with the first software application, in the displaying area.

13. The method of claim 11, wherein the obtaining of the attribute comprises: identifying, among both ends of the external object extended along a length direction, an end adjacent to the visual object overlapped to the external object by the input.

14. The method of claim 11, wherein the executing of the first software application comprises: executing the first software application based on information indicating a movement of the defined object using the images.

15. A non-transitory computer readable storage medium storing instructions, wherein the instructions, when executed by a wearable device comprising at least one display, when the wearable device is worn by a user, positioned toward an eye of the user, and at least one camera, cause the wearable device to: display a first screen using images representing a field of view (FOV) of the at least one camera; identify a defined object using the images representing the FOV of the at least one camera; based on the defined object identified in the FOV: obtain information indicating movement of the defined object; identify a software application which is associated with the defined object; and based on the software application identified as associated with the defined object, display, within the first screen, an executable object indicating the software application; and in response to a user input on the executable object, display a second screen by executing the software application using the information.

16. The non-transitory computer readable storage medium of claim 15, wherein the instructions, when executed by the wearable device, cause the wearable device to: based the defined object being in contact with a plane, obtain the information indicating a movement path of an end of the defined object being in contact with the plane.

17. The non-transitory computer readable storage medium of claim 16, wherein the instructions, when executed by the wearable device, cause the wearable device to: while obtaining the information, display one or more lines having a shape of the movement path superimposed on the first screen.

18. The non-transitory computer readable storage medium of claim 15, wherein the at least one camera include a first camera and a second camera, and wherein the instructions, when executed by the wearable device, cause the wearable device to: based on the information indicating the movement of the defined object in the FOV of the first camera, identify whether the defined object is moved outside of the first camera; based on the defined object identified as being moved outside of the FOV of the first camera, identify the defined object in another FOV of the second camera; and based on the defined object identified in the other FOV, obtain the information indicating the movement of the defined object within the other FOV.

19. The non-transitory computer readable storage medium of claim 18, wherein the instructions, when executed by the wearable device, cause the wearable device to: based on the defined object identified as being moved outside of the FOV of the first camera, display a third screen including at least portion of image representing the other FOV of the second camera.
