

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12400427
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Kimura; Daichi et al.

Display device, display method, and display program for visualizing and monitoring plant equipment and devices

Abstract

A display device includes processing circuitry configured to acquire data of plural pieces of equipment installed in a facility, carry out image recognition of drawing data drawing the equipment disposed in the facility as a component and, based on a result of the image recognition, store, in a storage, a correspondence relation between each of the equipment installed in the facility and the component in the drawing data, and generate an image including the component corresponding to the equipment disposed on the drawing data by using the drawing data and the correspondence relation stored in the storage.

Inventors: Kimura; Daichi (Saitama, JP), Shimada; Kenichiro (Tokyo, JP), Izumitani; Tomonori (Tokyo, JP)

Applicant: NTT Communications Corporation (Tokyo, JP)

Family ID: 1000008777520

Assignee: NTT COMMUNICATIONS CORPORATION (Tokyo, JP)

Appl. No.: 17/863504

Filed: July 13, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20220343633 A1	Oct. 27, 2022

Foreign Application Priority Data

JP	2020-003970	Jan. 14, 2020
----	-------------	---------------

Related U.S. Application Data

Publication Classification

Int. Cl.: G06V10/764 (20220101); G06T7/00 (20170101); G06V30/10 (20220101)

U.S. Cl.:

CPC G06V10/764 (20220101); G06T7/0004 (20130101); G06V30/10 (20220101);

Field of Classification Search

CPC: G06V (10/764); G06V (30/10); G06T (7/0004); G05B (19/418)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
10540378	12/2019	Hsiao	N/A	G06F 18/24
2012/0179727	12/2011	Esser	707/802	G09B 29/106
2020/0193708	12/2019	Maggiore	N/A	H04W 4/029
2020/0384648	12/2019	Katsunuma	N/A	B25J 9/1674
2020/0401861	12/2019	Akechi	N/A	G06K 17/0022
2021/0003983	12/2020	Okamoto	N/A	G01N 21/3518
2021/0050107	12/2020	Sailer	N/A	G16H 30/20
2021/0365877	12/2020	Huie	N/A	G06V 30/41
2022/0032976	12/2021	Ando	N/A	G06T 11/203
2022/0070513	12/2021	Shirai	N/A	H04N 21/41407
2022/0172374	12/2021	Tsuji	N/A	H04N 7/18
2022/0318322	12/2021	Kamaraju	N/A	G06V 30/19147

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2002-342384	12/2001	JP	N/A

OTHER PUBLICATIONS

“Piping and Instrumentation Diagram”, Wikipedia, Available Online at:
https://en.wikipedia.org/wiki/Piping_and_instrumentation_diagram, Retrieved on: Jan. 6, 2020, pp. 1-7. cited by applicant

Primary Examiner: Hon; Ming Y

Attorney, Agent or Firm: XSENSUS LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation application of International Application No. PCT/JP2020/047571 filed on Dec. 18, 2020 which

claims the benefit of priority of the prior Japanese Patent Application No. 2020-003970, filed on Jan. 14, 2020, the entire contents of which are incorporated herein by reference.

FIELD

(1) The present invention relates to a display device, a display method, and a display program.

BACKGROUND

(2) In various process industries of chemical, steel, energy, etc., piping and instrumentation diagrams (for example, Piping and Instrumentation Diagram: P&ID) are widely used as diagrams which illustrate flows and control information of plants and correspondence relations of pieces of main equipment such as sensors. P&ID is requested for designing of plants and is capable of visualizing the correspondence relations between devices and facilitating understanding of flows.

(3) Based on this P&ID, operators carry out monitoring/maintenance operation of the state in the plant in real time. P&ID forms a basement of a live imitation diagram displayed by a graphical user interface of a large-scale industrial control system such as Supervisory Control And Data Acquisition (SCADA) or a decentralized control system.

(4) Non Patent Document 1: “Piping and instrumentation diagram”, [online], [searched on Jan. 6, 2020], the Internet <en.wikipedia.org/wiki/Piping_and_instrumentation_diagram>

(5) However, related methods have not been able to easily build a monitoring system of a target facility. More specifically, many facilities and pieces of control equipment are present in a real plant. Therefore, the related methods have not been able to easily build a monitoring system since, for example, disposing P&ID components determined by International Standardizing Association (ISA) standards by human hands to build the monitoring system costs a lot of labor.

SUMMARY

(6) It is an object of the present invention to at least partially solve the problems in the related technology.

(7) According to an aspect of the embodiments, a display device includes: processing circuitry configured to: acquire data of plural pieces of equipment installed in a facility; carry out image recognition of drawing data drawing the equipment disposed in the facility as a component and, based on a result of the image recognition, store, in a storage, a correspondence relation between each of the equipment installed in the facility and the component in the drawing data; and generate an image including the component corresponding to the equipment disposed on the drawing data by using the drawing data and the correspondence relation stored in the storage.

(8) The above and other objects, features, advantages and technical and industrial significance of this invention will be better understood by reading the following detailed description of presently preferred embodiments of the invention, when considered in connection with the accompanying drawings.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) FIG. 1 is a configuration diagram of a system including a display device according to a first embodiment;

(2) FIG. 2 is a block diagram illustrating a configuration example of the display device according to the first embodiment;

(3) FIG. 3 is a diagram illustrating an example of data stored in a sensor-data storage unit;

(4) FIG. 4 is a diagram illustrating an example of data stored in a drawing-data storage unit;

(5) FIG. 5 is a diagram illustrating an example of data stored in an associated-data storage unit;

(6) FIG. 6 is a diagram illustrating a processing example of an image generation process executed by a display device;

(7) FIG. 7 is a flow chart illustrating an example of a flow of a display device according to the first

embodiment; and

(8) FIG. 8 is a diagram illustrating a computer which executes a display program.

DESCRIPTION OF EMBODIMENT(S)

(9) Preferred embodiments will be explained with reference to accompanying drawings.

Hereinafter, embodiments of a display device, a display method, and a display program according to the present application will be described in detail based on drawings. Note that the display device, the display method, and the display program according to the present application are not limited by these embodiments.

First Embodiment

(10) In the following embodiment, a configuration example of a system including a display device **10** according to a first embodiment, a configuration example of the display device **10**, and a flow of a process of the display device **10** will be sequentially described, and effects of the first embodiment will be described in the end.

(11) Configuration of System

(12) First, a configuration of the system including the display device **10** will be described by using FIG. 1. FIG. 1 is a configuration diagram of the system including the display device according to the first embodiment. The system exemplified in FIG. 1 has the display device **10**, a distributed control system (DCS) device **20**, a database **30**, and a facility **40**. Note that the configuration illustrated in FIG. 1 is merely an example, and specific configurations and the number of devices are not particularly limited.

(13) The display device **10** is a terminal device such as a workstation which displays flow information of a process based on P&ID on a graphical user interface (GUI) application. For example, components are automatically disposed to generate image data by reading image data of P&ID and carrying out artificial intelligence (AI) or image processing. Note that a design of P&ID is image data created in a process of constructing a factory or a plant. Also, the display device **10**, for example, automatically correlates components with pieces of equipment, which are stored in the database **30**. Note that the components can be appropriately corrected.

(14) The DCS device **20** collects information from pieces of equipment (for example, controllers and sensors) in the facility **40** and stores the collected information in the database **30**. Also, the DCS device **20** controls the pieces of equipment in the facility **40** by carrying out communication and monitoring mutually between control devices of the equipment.

(15) The database **30** stores information about the pieces of equipment in the facility **40**. For example, the database **30** stores various sensor data in the facility **40**. The facility **40** is a factory, a plant, or the like, and pieces of equipment such as sensors and controllers are installed therein.

(16) Configuration of Display Device

(17) Next, a configuration of the display device **10** will be described by using FIG. 2. FIG. 2 is a block diagram illustrating a configuration example of the display device according to the first embodiment. As illustrated in FIG. 1, the display device **10** has a communication processing unit **11**, an input unit **12**, an output unit **13**, a control unit **14**, and a storage unit **15**. Hereinafter, processes of each of the units of the display device **10** will be described.

(18) The communication processing unit **11** carries out data communication with other devices via a network. For example, the communication processing unit **11** is a network interface card (NIC). The input unit **12** receives input of data from a user. The input unit **12** is an input device such as a mouse or a keyboard. The output unit **13** outputs data, for example, by display of a screen. The output unit **13** is, for example, a display device such as a display.

(19) Also, the storage unit **15** stores data and programs used for various processing, which is carried out by the control unit **14**, and has a sensor-data storage unit **15a**, a drawing-data storage unit **15b**, and associated-data storage unit **15c**. For example, the storage unit **15** is a storage device such as a semiconductor memory element such as a random access memory (RAM) or a flash memory.

(20) The sensor-data storage unit **15a** stores the sensor data acquired from the database **30** by an acquisition unit **14a** described later. For example, the sensor-data storage unit **15a** stores the values of the various sensor data correlated with sensor IDs and sensor names which identify the sensors.

(21) Herein, by using an example of FIG. 3, an example of the data stored in the sensor-data storage unit **15a** will be described. FIG. 3 is a diagram illustrating an example of the data stored in the sensor-data storage unit. As exemplified in FIG. 3, the sensor-data storage unit **15a** mutually correlates and stores “sensor ID”, “sensor names”, and “sensor data”. Note that, as the sensor data, the sensor-data storage unit **15a** stores, for example, the values of various sensor data such as acceleration (triaxial), light intensity, temperature, humidity, magnetic force, pressure, etc. and the time at which the sensor data is acquired. Note that, as the data of sensors, the sensor-data storage unit **15a** may store information such as the types of the sensors, the names of installed pieces of equipment, installation positions of the sensors, etc.

(22) The drawing-data storage unit **15b** stores drawing data in which the pieces of equipment disposed in the facility **40** are drawn as components. For example, the drawing-data storage unit **15b** stores data of piping and instrumentation diagrams such as P&ID. Also, the drawing-data storage unit **15b** stores the data of the components included in the drawing data.

(23) Herein, by using an example of FIG. 4, an example of the data stored in the drawing-data storage unit **15b** will be described. FIG. 4 is a diagram illustrating an example of the data stored in the drawing-data storage unit. As exemplified in FIG. 4, the drawing-data storage unit **15b** correlates and stores “component IDs” which identify the components, “component names” which are names of the components, and “positions” indicating coordinates on the drawings of the components. Note that the drawing data stored in the drawing-data storage unit **15b** is assumed to be stored in advance.

(24) The associated-data storage unit **15c** stores the data representing correspondence relations between the pieces of equipment installed in the facility **40** and the components of the drawing data. Herein, by using an example of FIG. 5, an example of the data stored in the associated-data storage unit **15c** will be described. FIG. 5 is a diagram illustrating an example of the data stored in the associated-data storage unit. As exemplified in FIG. 5, the associated-data storage unit **15c** correlates and stores “sensor IDs” and “component IDs”. For example, in the example of FIG. 5, the associated-data storage unit **15c** stores a sensor ID “1” and a component ID “A”. This means that the sensor of the sensor ID “1” is a component of the component ID “A” in the drawing data.

(25) The control unit **14** has an internal memory for storing a program(s) and requested data defining various processing procedure, etc. and executes various processing by the program and data. For example, the control unit **14** has an acquisition unit **14a**, a housing unit **14b**, and an image generation unit **14c**. Herein, the control unit **14** is, for example, an electronic circuit such as a central processing unit (CPU), a micro processing unit (MPU), or a graphical processing unit (GPU) or an integrated circuit such as an application specific integrated circuit (ASIC) or a field programmable gate array (FPGA).

(26) The acquisition unit **14a** acquires the data of plural pieces of equipment installed in the facility. For example, the acquisition unit **14a** acquires, from the database **30**, plural pieces of sensor data installed in the facility **40** such as a factory or a plant and stores the data in the sensor-data storage unit **15a**.

(27) Herein, the sensor data acquired by the acquisition unit **14a** is, for example, various data of temperatures, pressures, sound, vibrations, etc. about devices or reactor furnaces in a factory or a plant, which is a monitoring target facility. Note that the acquisition unit **14a** may acquire data in real time. For example, the acquisition unit **14a** may be configured to acquire numerical-value data of multivariate time series periodically (for example, every one minute) from the sensors installed in a monitoring target facility such as a factory or a plant.

(28) The housing unit **14b** carries out image recognition of the drawing data in which the pieces of equipment disposed in the facility **40** are drawn as components and, based on the results of the

image recognition, stores, in the associated-data storage unit **15c**, the correspondence relations between the pieces of equipment installed in the facility **40** and the components in the drawing data.

(29) For example, the housing unit **14b** carries out image recognition of the drawing data in which the pieces of equipment disposed in the facility **40** are drawn as components, gives component IDs and component names to the components included in the drawing data, and stores that in the drawing-data storage unit **15b** together with the positions thereof in the drawing data. About a method of giving the component names, for example, the housing unit **14b** specifies the types of the components from the shapes of symbols of the components in the drawing by image recognition and gives the names of the components corresponding to the specified types of the components.

(30) Also, the housing unit **14b** may be configured to input, as input data, the data of the pieces of equipment installed in the facility **40** and the drawing data to a learned model, which carries out the image recognition, acquire the correspondence relations between the pieces of equipment installed in the facility **40** and the components in the drawing data as output results, and store the correspondence relations in the associated-data storage unit **15c**.

(31) Moreover, the housing unit **14b** may be configured to carry out the image recognition of the drawing data, in addition, subject the characters included in the drawing data to character recognition, compare the recognized characters with the names of the pieces of equipment, specify the correspondence relations between the pieces of equipment installed in the facility **40** and the components in the drawing data, and store the correspondence relations in the associated-data storage unit **15c**. For example, the housing unit **14b** subjects the characters included in the drawing data to character recognition and compares the recognized characters with the names of the pieces of equipment. If the recognized characters are the same or similar to the names of the pieces of equipment, the housing unit connects the pieces of equipment with the components near the characters and stores that in the associated-data storage unit **15c**.

(32) The image generation unit **14c** generates an image, in which the components corresponding to the pieces of equipment are disposed on drawing data, by using the drawing data and the correspondence relations stored in the associated-data storage unit **15c**. Then, the image generation unit **14c** displays the generated image in response to a request of a user.

(33) For example, the image generation unit **14c** reads sensor data from the sensor-data storage unit **15a**, drawing data from the drawing-data storage unit **15b**, and associated data from the associated-data storage unit **15c**. Then, the image generation unit **14c** disposes only the components, which are stored in the associated-data storage unit **15c**, on the drawing data.

(34) Also, for example, if there are pieces of equipment which are not drawn as components in the drawing data, but are stored in the sensor-data storage unit **15a**, the image generation unit **14c** generates symbols of the components corresponding to the types of the sensors stored in the sensor-data storage unit **15a**, estimates the disposed positions of the components based on, for example, the names of the installed pieces of equipment and the installation positions of the sensors stored in the sensor-data storage unit **15a**, and disposes the components in a process flow on a GUI application. Note that the components disposed in the process flow on the GUI application can be arbitrarily subjected to disposition changes by operation made by the user.

(35) Also, for example, the image generation unit **14c** may input the drawing data and the correspondence relations, which are stored in the associated-data storage unit **15c**, to a learned model which generates an image, acquire the image in which the components corresponding to the pieces of equipment are disposed on the drawing data as an output result, and display the acquired image. Note that a learned method of the above described learned model may be carried out by any of existing methods.

(36) Herein, by using FIG. **6**, a processing example of an image generation process executed by the display device **10** will be described. FIG. **6** is a diagram describing the processing example of the

image generation process executed by the display device. As exemplified in FIG. 6, the display device **10** reads an image of a factory design of P&ID as an input image. Then, the display device **10** subjects the read image to image recognition and image processing and generates an image of a process flow on a GUI application.

(37) For example, in the example of FIG. 6, the display device **10** generates components for a sensor X, a sensor Y, and a compressor Z stored in the database **30** and generates and displays an image in which the components are disposed in a process flow. Also, the display device **10** automatically connects components with the pieces of equipment of the database **30** to carry out systematization. In this manner, the display device **10** automatically generates, from a factory design, a process flow diagram, which is displayed on the GUI application, by image recognition and/or image processing using AI. Therefore, the display device **10** can easily build a monitoring system based on P&ID.

(38) Processing Procedure of Display Device

(39) Next, an example of a processing procedure of the display device **10** according to the first embodiment will be described by using FIG. 7. FIG. 7 is a flow chart illustrating an example of a flow of a learning process of the display device according to the first embodiment.

(40) As exemplified in FIG. 7, when image data of a design is acquired (step S101, positive), the housing unit **14b** of the display device **10** inputs the image data to a learned model (step S102). Then, the housing unit **14b** recognizes the image data and correlates the information of pieces of equipment with components of the design (step S103).

(41) For example, the housing unit **14b** inputs, as input data, the data of the pieces of equipment installed in the facility **40** and the drawing data to the learned model, which carries out the image recognition, acquires the correspondence relations between the pieces of equipment installed in the facility **40** and the components in the drawing data as output results, and stores the correspondence relations in the associated-data storage unit **15c**.

(42) Subsequently, the image generation unit **14c** generates image data in which the components are disposed (step S104) and displays the generated image data (step S105). For example, the image generation unit **14c** inputs the drawing data and the correspondence relations, which are stored in the associated-data storage unit **15c**, to the learned model which generates an image, acquires the image in which the components corresponding to the pieces of equipment are disposed on the drawing data as an output result, and displays the acquired image.

(43) Effects of First Embodiment

(44) The display device **10** according to the first embodiment acquires the data of plural pieces of equipment installed in the facility **40**, carries out image recognition of the drawing data in which the pieces of equipment disposed in the facility **40** are drawn as components, and, based on the results of the image recognition, stores, in the associated-data storage unit **15c**, the correspondence relations between the pieces of equipment installed in the facility and the components in the drawing data. Then the display device **10** generates an image, in which the components corresponding to the pieces of equipment are disposed on drawing data, by using the drawing data and the correspondence relations stored in the associated-data storage unit **15c**. For example, the display device **10** automatically disposes P&ID components from a P&ID diagram created upon plant designing and connects the components with the information of real-time sensor data. Therefore, the display device **10** can easily build a monitoring system which can monitor the real-time sensor data of the pieces of equipment in the target facility.

(45) In other words, the display device **10** can automatically connect the components with the pieces of equipment and easily build a system in which the information of the components and the real-time sensor data is connected. Also, the display device **10** automatically generates, for example from a factory design of P&ID, a process flow diagram, which is displayed on the GUI application, by image recognition and/or image processing using AI. Therefore, the display device **10** can easily build a monitoring system based on P&ID.

(46) System Configuration, Etc.

(47) Illustrated constituent elements of the devices are functional ideas and are not necessarily required to be physically formed as the illustration. More specifically, specific modes of dispersion/integration of the devices are not limited to the illustrated ones, and all or part thereof can be functionally or physically dispersed/integrated in arbitrary units depending on various load, usage conditions, etc. Furthermore, all or arbitrary part of the processing functions implemented by the devices are realized by a CPU or a GPU and a program analyzed and executed by the CPU or the GPU or can be realized as hardware of wired logic.

(48) Moreover, among the processes described in the present embodiment, all or part of the processes described as automatically carried out processes may be also manually carried out, or all or part of the processes described as manually carried out processes can be also automatically carried out by a publicly known method. Furthermore, processing procedures, control procedures, specific names, and information including various data or parameters illustrated in above described document or drawings can be arbitrarily changed unless otherwise specified.

(49) Program

(50) Also, the processes executed by an information processing device described in the above described embodiment can be created by a program described in a computer-executable language. For example, the processes executed by the display device **10** according to the embodiment can be created by a program described in a computer-readable language. In such a case, effects similar to those of the above described embodiment can be obtained when a computer executes the program. Furthermore, processes similar to those of the above described embodiment may be realized by recording the program in a computer-readable recording medium and causing a computer to read and execute the program recorded in the recording medium.

(51) FIG. **8** is a diagram illustrating a computer which executes the display program. As exemplified in FIG. **8**, a computer **1000** has, for example, a memory **1010**, a CPU **1020**, a hard-disk-drive interface **1030**, a disk-drive interface **1040**, a serial port interface **1050**, a video adapter **1060**, and a network interface **1070**, and these units are connected by a bus **1080**.

(52) As exemplified in FIG. **8**, the memory **1010** includes a read only memory (ROM) **1011** and a RAM **1012**. The ROM **1011** stores, for example, a boot program such as Basic Input Output System (BIOS). As exemplified in FIG. **8**, the hard-disk-drive interface **1030** is connected to the hard disk drive **1090**. As exemplified in FIG. **8**, the disk-drive interface **1040** is connected to a disk drive **1100**. For example, a detachable medium such as a magnetic disk or an optical disk is inserted into the disk drive **1100**. As exemplified in FIG. **8**, the serial port interface **1050** is connected to, for example, a mouse **1110** and a keyboard **1120**. As exemplified in FIG. **8**, the video adapter **1060** is connected to, for example, a display **1130**.

(53) Herein, as exemplified in FIG. **8**, the hard disk drive **1090** stores, for example, an OS **1091**, an application program **1092**, a program module **1093**, and program data **1094**. In other words, the above described program is stored, for example, in the hard disk drive **1090** as a program module in which commands executed by the computer **1000** are described.

(54) Also, the various data described in the above described embodiment is stored, for example, in the memory **1010** or the hard disk drive **1090** as program data. Then, the CPU **1020** loads, to the RAM **1012**, the program module **1093** and/or the program data **1094** stored in the memory **1010** or the hard disk drive **1090** in accordance with needs and executes various processing procedures.

(55) Note that the program module **1093** and/or the program data **1094** related to the program is not limited to be stored in the hard disk drive **1090**, but may be, for example, stored in a detachable storage medium and loaded by the CPU **1020** via a disk drive or the like. Alternatively, the program module **1093** and/or the program data **1094** related to the program may be stored in another computer connected via a network (local area network (LAN), wide area network (WAN), or the like) and loaded by the CPU **1020** via the network interface **1070**.

(56) According to the present invention, an effect that a monitoring system of a target facility can

be easily build is exerted.

(57) Although the invention has been described with respect to specific embodiments for a complete and clear disclosure, the appended claims are not to be thus limited but are to be construed as embodying all modifications and alternative constructions that may occur to one skilled in the art that fairly fall within the basic teaching herein set forth.

Claims

1. A display device comprising: processing circuitry configured to: acquire in real-time data of plural pieces of equipment installed in a facility; carry out image recognition of drawing data drawing the equipment disposed in the facility as a component and, based on a result of the image recognition, store, in a storage, a correspondence relation between the real-time data of each of the equipment installed in the facility and the component in the drawing data, the drawing data including a piping and instrumentation diagram (P&ID); generate an image of process flow diagram including the component corresponding to the equipment disposed on the drawing data by using the drawing data and the correspondence relation stored in the storage; and display the image on a display.
2. The display device according to claim 1, wherein the processing circuitry is further configured to input, as input data, the data of the equipment installed in the facility and the drawing data to a learned model that carries out the image recognition, acquire a correspondence relation between the equipment installed in the facility and the component in the drawing data as an output result, and store the correspondence relation in the storage.
3. The display device according to claim 1, wherein the processing circuitry is further configured to carry out the image recognition of the drawing data and subject a character included in the drawing data to character recognition, compare the recognized character with a name of the equipment to specify the correspondence relation between the equipment installed in the facility and the component in the drawing data, and store the correspondence relation in the storage.
4. The display device according to claim 1, wherein the processing circuitry is further configured to input the drawing data and the correspondence relation stored in the storage to a learned model that generates the image and acquire, as an output result, the image including the component corresponding to the equipment disposed on the drawing data.
5. The display device according to claim 1, wherein when the storage stores data of equipment that has no corresponding component in the drawing data, the circuitry is further configured to include a component on the image of the process flow diagram corresponding to the equipment that has no corresponding component in the drawing data using a learned model.
6. The display device according to claim 1, wherein the data of the plural pieces of equipment include at least one of sensor data, temperature data, pressure data, vibration data, and sound data.
7. A display method comprising: acquiring in real-time data of plural pieces of equipment installed in a facility; carrying out image recognition of drawing data drawing the equipment disposed in the facility as a component and, based on a result of the image recognition, storing, in a storage, a correspondence relation between the real-time data each of the equipment installed in the facility and the component in the drawing data, the drawing data including a piping and instrumentation diagram (P&ID); generating an image of a process flow diagram including the component corresponding to the equipment disposed on the drawing data by using the drawing data and the correspondence relation stored in the storage, by processing circuitry; and displaying the image on a display.
8. The display method according to claim 7, wherein when the storage stores data of equipment that has no corresponding component in the drawing data, the method further comprises including a component on the image of the process flow diagram corresponding to the equipment that has no corresponding component in the drawing data using a learned model.

9. The display method according to claim 7, wherein the data of the plural pieces of equipment include at least one of sensor data, temperature data, pressure data, vibration data, and sound data.
10. A non-transitory computer-readable recording medium storing therein a display program that causes a computer to execute a process comprising: acquiring in real-time data of plural pieces of equipment installed in a facility; carrying out image recognition of drawing data drawing the equipment disposed in the facility as a component and, based on a result of the image recognition, storing, in a storage, a correspondence relation between the real-time data each of the equipment installed in the facility and the component in the drawing data; generating an image of a process flow diagram including the component corresponding to the equipment disposed on the drawing data by using the drawing data and the correspondence relation stored in the storage, the drawing data including a piping and instrumentation diagram (P&ID); and displaying the image on a display.
11. The non-transitory computer-readable recording medium according to claim 10, wherein when the storage stores data of equipment that has no corresponding component in the drawing data, the process further comprises including a component on the image of the process flow diagram corresponding to the equipment that has no corresponding component in the drawing data using a learned model.
12. The non-transitory computer-readable recording medium according to claim 10, wherein the data of the plural pieces of equipment include at least one of sensor data, temperature data, pressure data, vibration data, and sound data.
-