

# US Patent & Trademark Office

## Patent Public Search | Text View

---

|                      |                           |
|----------------------|---------------------------|
| United States Patent | 12401050                  |
| Kind Code            | B2                        |
| Date of Patent       | August 26, 2025           |
| Inventor(s)          | Maruyama; Takehiro et al. |

---

### Fuel cell ship

---

#### Abstract

A fuel cell ship includes a fuel cell compartment in which a fuel cell is installed, a tank compartment in which a fuel tank is installed, a fuel supply pipe through which fuel is supplied from the fuel tank to the fuel cell, and a control unit. The fuel supply pipe includes at least two shutoff valves. Fuel gas detectors that detect a fuel gas being in a gaseous state of the fuel are each installed in the compartments. If at least one of the fuel gas detectors detects that a concentration of the fuel gas is equal to or greater than a predetermined standard value, the control unit controls to close a shutoff valve in a compartment out of the tank compartment and the fuel cell compartment, where the fuel gas detector having detected the concentration equal to or greater than the standard value is installed.

---

**Inventors:** Maruyama; Takehiro (Osaka, JP), Yamaguchi; Yasuyoshi (Osaka, JP), Hiraiwa; Takuya (Osaka, JP), Shinagawa; Manabu (Osaka, JP), Kimura; Yukihiro (Kunisaki, JP)

**Applicant:** Yanmar Holdings Co., Ltd. (Osaka, JP)

**Family ID:** 1000008777465

**Assignee:** YANMAR HOLDINGS CO., LTD. (Osaka, JP)

**Appl. No.:** 17/830112

**Filed:** June 01, 2022

#### Prior Publication Data

| Document Identifier | Publication Date |
|---------------------|------------------|
| US 20220393198 A1   | Dec. 08, 2022    |

#### Foreign Application Priority Data

|    |             |               |
|----|-------------|---------------|
| JP | 2021-092708 | Jun. 02, 2021 |
|----|-------------|---------------|

---

## Publication Classification

**Int. Cl.:** **H01M8/04858** (20160101); **B63H21/00** (20060101); **B63H21/17** (20060101);  
**B63H21/38** (20060101); **H01M8/04082** (20160101)

**U.S. Cl.:**

**CPC** **H01M8/0494** (20130101); **B63H21/17** (20130101); **B63H21/38** (20130101);  
**H01M8/04201** (20130101); **B63H2021/003** (20130101); **H01M2250/20** (20130101)

## Field of Classification Search

**CPC:** B63H (21/00); B63H (21/17); B63H (2021/003); B63H (21/38); B63B (21/21); B63B (11/04); B63B (11/02); H01M (8/04947); H01M (8/04679); H01M (8/04753); H01M (8/04865); H01M (2250/20); H01M (8/249); H01M (8/0444); H01M (16/006); H01M (8/04932); H01M (8/04089); H01M (8/04201); H01M (8/04664); H01M (8/04955); H01M (50/35); H01M (2220/20); H01M (8/2475); H01M (8/04447); H01M (8/0494); H01M (8/04388); F17C (2201/0109); F17C (2201/035); F17C (2201/056); F17C (2205/0103); F17C (2205/0142); F17C (2205/0176); F17C (2205/0335); F17C (2221/012); F17C (2223/0123); F17C (2223/036); F17C (2250/0452); F17C (2260/038); F17C (2260/042); F17C (2270/0105); F17C (1/002); F17C (13/084); B60L (58/13); B60L (2240/54); B60L (50/71); B60L (2200/32); B60L (3/0053); B60L (50/70); B60L (58/30); B60R (25/042); Y02E (60/50); Y02T (90/40); Y02T (70/50)

**USPC:** 440/60; 440/1; 180/65.22

---

## References Cited

### U.S. PATENT DOCUMENTS

| Patent No.   | Issued Date | Patentee Name | U.S. Cl.  | CPC             |
|--------------|-------------|---------------|-----------|-----------------|
| 8123577      | 12/2011     | Riggs         | 440/6     | H01M 12/06      |
| 8683937      | 12/2013     | Sancoff       | 114/61.15 | B63G 8/36       |
| 10071650     | 12/2017     | Saito         | N/A       | N/A             |
| 10364009     | 12/2018     | Sako          | N/A       | H01M<br>8/04089 |
| 2006/0009092 | 12/2005     | Krietzman     | 440/6     | B63H 21/17      |
| 2006/0012248 | 12/2005     | Matsushita    | 307/10.1  | B60L 58/40      |
| 2007/0122667 | 12/2006     | Kelley        | 429/513   | C01B 3/382      |
| 2015/0280260 | 12/2014     | Lee           | 429/414   | H01M<br>8/04231 |

### FOREIGN PATENT DOCUMENTS

| Patent No.    | Application Date | Country | CPC |
|---------------|------------------|---------|-----|
| 110335438     | 12/2020          | CN      | N/A |
| 2018-092815   | 12/2017          | JP      | N/A |
| 1020160058012 | 12/2015          | KR      | N/A |

### OTHER PUBLICATIONS

European Search Report dated May 31, 2023 issued for EP Application No. 22175802.2. cited by applicant

---

*Primary Examiner:* Venne; Daniel V

*Attorney, Agent or Firm:* NORTON ROSE FULBRIGHT US LLP

---

## Background/Summary

### CROSS-REFERENCE TO RELATED APPLICATIONS

(1) This application is claims priority under 35 U.S.C. § 119 to JP Application No. 2021-092708 filed Jun. 2, 2021, the entire contents of which are hereby incorporated by reference.

### TECHNICAL FIELD

(2) The present invention relates to a fuel cell ship.

### BACKGROUND ART

(3) In the related art, a fuel cell ship in which a fuel gas (for example, hydrogen gas) is supplied from a fuel tank to a fuel cell and a propulsion device is driven by electric power generated by the fuel cell has been proposed (see, for example, Patent Document 1).

### PRIOR ART DOCUMENT

Patent Document

(4) Patent Document 1: Japanese Unexamined Patent Application Publication No. 2018-92815

### SUMMARY OF INVENTION

Technical Problem

(5) The fuel gas is a combustible gas. For this reason, in a fuel cell ship, it may be required to install a fuel tank that stores the fuel gas and a fuel cell supplied with the fuel gas, in independent

compartments. A compartment where the fuel tank is installed is also referred to as a “tank compartment” hereinafter. A compartment where the fuel cell is installed is also referred to as a “fuel cell compartment” hereinafter. In an unlikely event of a fuel gas leak in at least one of the tank compartment and the fuel cell compartment, it would be a hazardous state, and thus would be necessary to take some measures.

(6) The present invention has been made to solve the above problems, and an object of the present invention is to provide a fuel cell ship where electric power generation by a fuel cell can be stopped in an unlikely event of a fuel gas leak in at least one of a tank compartment and a fuel cell compartment.

#### Solution to Problem

(7) A fuel cell ship according to an aspect of the present invention includes a fuel cell that generates electric power by an electrochemical reaction of fuel, a propulsion device that generates a propulsive force in a hull by the electric power supplied from the fuel cell, a fuel cell compartment in which the fuel cell is installed, a tank compartment in which a fuel tank that stores the fuel is installed, and a fuel supply pipe through which the fuel is supplied from the fuel tank to the fuel cell. In the fuel cell ship, the fuel supply pipe includes two or more shutoff valves, and at least one of the two or more shutoff valves is installed in each of the tank compartment and the fuel cell compartment, the fuel cell ship further includes a control unit that controls opening and closing the shutoff valves, the tank compartment and the fuel cell compartment are each provided with fuel gas detectors that detect a fuel gas being in a gaseous state of the fuel, and if at least one of the fuel gas detectors detects that a concentration of the fuel gas is equal to or greater than a predetermined standard value, the control unit controls to close the shutoff valve in a compartment out of the tank compartment and the fuel cell compartment, in which the fuel gas detector that detects that the concentration is equal to or greater than the predetermined standard value is installed.

#### Advantageous Effects of Invention

(8) With the configuration described above, it is possible to stop electric power generation by a fuel cell in an unlikely event of a fuel gas leak in at least one of a tank compartment and a fuel cell compartment.

---

## Description

### BRIEF DESCRIPTION OF DRAWINGS

(1) FIG. 1 is an explanatory diagram illustrating a schematic configuration of a fuel cell ship according to an embodiment of the present invention.

(2) FIG. 2 is an explanatory diagram schematically illustrating an internal structure of the fuel cell ship.

(3) FIG. 3 is a flowchart illustrating a processing flow according to an example of control for opening and closing shutoff valves of the fuel cell ship.

(4) FIG. 4 is a flowchart illustrating a processing flow according to another example of control for opening and closing the shutoff valves.

(5) FIG. 5 is a flowchart illustrating a processing flow when control for opening and closing a release valve of the fuel cell ship is further performed.

(6) FIG. 6 is a flowchart illustrating a processing flow according to another example of control for opening and closing the release valve.

(7) FIG. 7 is a flowchart illustrating a processing flow according to yet another example of control for opening and closing the release valve.

(8) FIG. 8 is a flowchart illustrating a processing flow according to an example of control for opening and closing the shutoff valves and the release valve in consideration of also detecting a fuel gas in a duct compartment of the fuel cell ship.

(9) FIG. 9 is a flowchart illustrating a processing flow according to an example of control for opening and closing the shutoff valves and the release valve in consideration of also detecting a fuel gas by a vent pipe internal gas detector of the fuel cell ship.

## DESCRIPTION OF EMBODIMENTS

(10) An embodiment of the present invention will be described below based on the drawings. In this description, direction is defined as follows. First, a direction from the stern to the bow of the fuel cell ship is “front”, and a direction from the bow to the stern is “rear”. A horizontal direction perpendicular to a front-rear direction is defined as a left-right direction. At this time, when the fuel cell ship is moving forward, the left side is defined as “left” and the right side is defined as “right” when viewed from the operator. The upstream side in the gravity direction perpendicular to the front-back direction and the left-right direction is referred to as “up”, and the downstream side is referred to as “down”.

(11) [1. Schematic Configuration of Fuel Cell Ship]

(12) Firstly, a fuel cell ship SH according to the present embodiment will be described with reference to FIG. 1. FIG. 1 is an explanatory diagram illustrating a schematic configuration of the fuel cell ship SH. The fuel cell ship SH includes a hull 1 and a cabin 2. The cabin 2 is arranged on an upper surface of the hull 1.

(13) The fuel cell ship SH further includes a fuel cell system 3, a fuel gas storage unit 4, a storage battery system 5, a propulsion device 6, a plurality of pieces of peripheral equipment 11, and a control device 12. In FIG. 1, a control signal or a high voltage power supply line is indicated by a solid line, and a control signal or a low voltage power supply line is indicated by a dashed line.

(14) The fuel cell system 3 functions as a main power supply. The fuel cell system 3 consumes a fuel gas to generate electric power (specifically, DC electric power). The fuel gas is an example of a fuel, for example, a combustible gas. Typically, the fuel gas is hydrogen gas. The fuel cell system 3 supplies generated electric power to the propulsion device 6 and the peripheral equipment 11. The fuel cell system 3 can also supply electric power to the storage battery system 5 to charge the storage battery system 5.

(15) The fuel gas storage unit 4 stores the fuel gas to be supplied to the fuel cell system 3. The fuel gas is supplied from the fuel gas storage unit 4 to the fuel cell system 3 via a fuel gas supply pipe 32 described later (see FIG. 2).

(16) The storage battery system 5 includes a storage battery. The storage battery is, for example, a lithium secondary battery, but may also be a nickel-cadmium storage battery, a nickel-hydrogen storage battery, or the like. The storage battery system 5 functions as an auxiliary power source for supplying the stored electric power (specifically, DC electric power) to the propulsion device 6 and the peripheral equipment 11. Thus, the storage battery system 5 functions as an auxiliary power source, and thus, it is possible to compensate for a shortage of electric power supplied from the fuel cell system 3 to the propulsion device 6 or the like. The storage battery system 5 may supply electric power to the control device 12.

(17) The propulsion device 6 is driven by electric power supplied from a fuel cell 31 described later (see FIG. 2) of the fuel cell system 3, and generates a propulsive force on the hull 1. That is, the fuel cell ship SH includes the propulsion device 6 that generates a propulsive force on the hull 1 by the electric power supplied from the fuel cell 31.

(18) It is noted that the propulsion device 6 may be driven only by the electric power supplied from the storage battery included in the storage battery system 5, or may be driven by the electric power supplied from both the fuel cell 31 and the storage battery. That is, the propulsion device 6 may be driven by the electric power supplied from at least one of the fuel cell and the storage battery to generate the propulsive force on the hull 1.

(19) The propulsion device 6 includes an electric power conversion device 6a, a propulsion motor 6b, and a propeller 6c. The electric power conversion device 6a converts the electric power supplied from the fuel cell system 3 into electric power according to the specifications of the

propulsion motor **6b**. For example, the electric power conversion device **6a** converts DC electric power into AC electric power. In this case, the electric power conversion device **6a** has, for example, an inverter. The propulsion motor **6b** is driven by electric power (for example, AC electric power) supplied from the electric power conversion device **6a**. When the propulsion motor **6b** is driven, the rotational force of the propulsion motor **6b** is transmitted to the propeller **6c**. As a result, the propeller **6c** rotates, and a propulsive force is generated on the hull **1**. A configuration is also possible in which a marine gear is provided between the propulsion motor **6b** and the propeller **6c**.

(20) Examples of the peripheral equipment **11** include a compressor, a solenoid valve, and a pump. Examples of the peripheral equipment **11** also include electrical equipment such as lighting equipment and air conditioning equipment, but the types of peripheral equipment **11** are not particularly limited.

(21) The control device **12** controls the fuel cell system **3**, the fuel gas storage unit **4**, the storage battery system **5**, the propulsion device **6**, and a plurality of the peripheral equipment **11**. The control device **12** is composed of, for example, one or more computers. The computer is, for example, a Programmable Logic Controller (PLC), but may also be an Electronic Control Unit (ECU). The control device **12** is supplied with electric power from a battery (for example, a lead battery) not illustrated or from the storage battery of the storage battery system **5**.

(22) The control device **12** has a control unit **12a** and a storage unit **12b**. The control unit **12a** includes a processor such as a Central Processing Unit (CPU). The storage unit **12b** includes a storage device and stores data and computer programs. Specifically, the storage unit **12b** includes a main storage device such as a semiconductor memory and an auxiliary storage device such as a semiconductor memory, a solid state drive, and/or a hard disk drive. The storage unit **12b** may also include removable media. The storage unit **12b** corresponds to an example of a non-transitory computer-readable storage medium.

(23) The processor of the control unit **12a** executes a computer program stored in the storage device of the storage unit **12b**, to control the fuel cell system **3**, the fuel gas storage unit **4**, the storage battery system **5**, the propulsion device **6**, and the plurality of pieces of peripheral equipment **11**.

(24) [2. Internal Structure of Fuel Cell Ship]

(25) Next, an internal structure of the fuel cell ship SH will be described with reference to FIG. 2. FIG. 2 is an explanatory diagram schematically illustrating the internal structure of the fuel cell ship SH. In FIG. 2, the air flow is indicated by a dashed line arrow. In FIG. 2, the right side of the drawing is the bow side, the left side of the drawing is the stern side, and each member is illustrated; however, the position of the member is not limited to the position illustrated in FIG. 2 as long as the connection relationship of the member is maintained.

(26) The fuel cell ship SH includes an engine room **13** and a fuel room **14**. The engine room **13** and the fuel room **14** are arranged below a deck **1a** of the hull **1**. The engine room **13** is located on the bow side with respect to the fuel room **14**. Below the deck **1a**, partition walls W1, W2 and W3 are located in order from the bow side to the stern side. The engine room **13** is separated from other spaces by the partition walls W1 and W2. The fuel room **14** is separated from other spaces by the partition walls W2 and W3. The partition walls W1 to W3 are made of, for example, fiber reinforced plastics (FRP), but may be iron plates.

(27) (2-1. Configuration of Fuel Cell System)

(28) The fuel cell system **3** of the fuel cell ship SH is located in the engine room **13**. The fuel cell system **3** includes the fuel cell **31**, the fuel gas supply pipe **32**, and a fuel cell side shutoff valve **33**. The fuel cell side shutoff valve **33** is an example of the peripheral equipment **11** (see FIG. 1).

(29) The fuel cell **31** generates electric power (specifically, DC electric power) by an electrochemical reaction between the fuel gas being an example of fuel and an oxidant gas. Typically, the oxidant gas is air and the oxidant is oxygen. That is, the fuel cell ship SH includes the fuel cell **31** that generate electric power by the electrochemical reaction of fuel.

(30) The fuel cell **31** is a fuel cell stack composed of a plurality of stacked cells. For example, each cell of the fuel cell **31** has a solid polymer electrolyte membrane, an anode electrode, a cathode electrode, and a pair of separators. The solid polymer electrolyte membrane is sandwiched between the anode electrode and the cathode electrode. The anode electrode is a negative electrode (fuel electrode). The anode electrode includes an anode catalyst layer and a gas diffusion layer. The cathode electrode is a positive electrode (air electrode). The cathode electrode includes a cathode catalyst layer and a gas diffusion layer. The anode electrode, the solid polymer electrolyte membrane, and the cathode electrode form a Membrane-Electrode Assembly (MEA). The pair of separators sandwich the membrane-electrode assembly. Each separator has a plurality of grooves. Each groove of one separator forms a flow path for the fuel gas. Each groove of the other separator forms a flow path for the oxidant gas.

(31) In the configuration described above of the fuel cell **31**, hydrogen included in the fuel gas is decomposed into hydrogen ions and electrons by a catalyst on the anode electrode side. The hydrogen ions pass through the solid polymer electrolyte membrane and move to the cathode electrode side. On the other hand, the electrons move to the cathode electrode side through an external circuit. As a result, an electric current is generated (electricity is generated). On the cathode electrode side, oxygen included in the oxidant gas combines with the electrons flowing through the external circuit and the hydrogen ions passing through the solid polymer electrolyte membrane to generate water. The generated water is discharged outside the ship via a discharge pipe **31a**.

(32) The fuel cell **31** supplies generated electric power to the propulsion device **6** and the peripheral equipment **11** illustrated in FIG. **1**. The fuel cell **31** may indirectly supply generated electric power to the propulsion device **6** and the peripheral equipment **11** via a circuit such as a DC/DC converter or the like.

(33) The fuel gas supply pipe **32** is a fuel supply pipe for supplying, to the anode electrode of the fuel cell **31**, fuel (for example, a fuel gas) stored in a fuel tank **41** described later of the fuel gas storage unit **4**. That is, the fuel cell ship SH includes the fuel gas supply pipe **32** through which the fuel is supplied from the fuel tank **41** to the fuel cell **31**.

(34) The fuel cell side shutoff valve **33** is an example of a shutoff valve SV that opens or closes the flow path of the fuel gas supply pipe **32**. The opening and closing of the fuel cell side shutoff valve **33** is controlled by the control unit **12a** (see FIG. **1**). Specifically, the fuel cell side shutoff valve **33** switches between supplying the fuel gas from the fuel tank **41** to the fuel cells **31** and stopping the supply of fuel gas based on the control of the control unit **12a**. Although only one fuel cell side shutoff valve **33** is provided in the fuel gas supply pipe **32** in a fuel cell compartment **30** (described later), two or more may be provided.

(35) The fuel cell ship SH further includes the fuel cell compartment **30**. The fuel cell compartment **30** is a housing body that houses the fuel cell **31**, and is arranged in the engine room **13**. That is, the fuel cell ship SH includes the fuel cell compartment **30** in which the fuel cell **31** is installed.

(36) The fuel cell compartment **30** has a hollow shape. For example, the fuel cell compartment **30** has a hollow and substantially rectangular parallelepiped shape. In this case, the outer walls of the fuel cell compartment **30** include, for example, a top wall **30a**, a bottom wall **30b**, a front wall (not illustrated), a back wall (not illustrated), a side wall **30c**, and a side wall **30d**. However, the top surface, bottom surface, front surface, back surface, and side surfaces of the fuel cell compartment **30** can be arbitrarily determined. The shape of the fuel cell compartment **30** is not particularly limited as long as the fuel cell compartment **30** has a space that can house the fuel cell **31**. The fuel cell compartment **30** can also be considered as a container, chamber, or box for housing the fuel cell **31**. The material of the outer wall of the fuel cell compartment **30** is, for example, FRP, but may be an iron plate.

(37) A cell compartment air supply port **30e** with an opening is provided on the side wall **30d** of the fuel cell compartment **30**. The cell compartment air supply port **30e** is connected to a cell

compartment air supply pipe **35**, which will be described later. The cell compartment air supply port **30e** may be provided on an outer wall other than the side wall **30d** in the fuel cell compartment **30**.

(38) On the other hand, a cell compartment exhaust port **30f** with an opening is provided on the side wall **30c** of the fuel cell compartment **30**. The cell compartment exhaust port **30f** communicates with a duct compartment **90**, which will be described later. The cell compartment exhaust port **30f** may be provided on an outer wall other than the side wall **30c** in the fuel cell compartment **30**.

(39) The fuel cell compartment **30** has an interior that is a closed space, with the exception of the cell compartment air supply port **30e** and the cell compartment exhaust port **30f**.

(40) A part of the fuel gas supply pipe **32** described above and the fuel cell side shutoff valve **33** are housed in the fuel cell compartment **30**. The fuel cell compartment **30** further houses a cell compartment internal gas detector **34a** and a cell compartment internal fire detector **34b**.

(41) The cell compartment internal gas detector **34a** is a fuel gas detector arranged inside the fuel cell compartment **30**. For example, if the fuel gas is hydrogen gas, the cell compartment internal gas detector **34a** includes a hydrogen gas detection sensor.

(42) The cell compartment internal gas detector **34a** is arranged on an inner surface of the top wall **30a** located at an upper part of the fuel cell compartment **30**. Hydrogen gas as the fuel gas is lighter than air and rises. Therefore, by arranging the cell compartment internal gas detector **34a** on the top wall **30a** of the fuel cell compartment **30**, a leaked fuel gas can be reliably detected by the cell compartment internal gas detector **34a** even if the fuel gas leaks in the fuel cell compartment **30**. The installation position of the cell compartment internal gas detector **34a** may be located on the most downstream side of the flow path through which the fuel gas flows when the fuel gas leaks in the fuel cell compartment **30**.

(43) When the cell compartment internal gas detector **34a** detects a fuel gas in the fuel cell compartment **30**, a detection signal is sent from the cell compartment internal gas detector **34a** to the control unit **12a**. As a result, the control unit **12a** can control the fuel cell side shutoff valve **33** provided in the fuel gas supply pipe **32** to stop the supply of the fuel gas from the fuel tank **41** to the fuel cell **31**. The details of control for opening and closing the fuel cell side shutoff valve **33** will be described later.

(44) The cell compartment internal fire detector **34b** is a fire detector arranged inside the fuel cell compartment **30**. The cell compartment internal fire detector **34b** includes, for example, one or more sensors among a smoke sensor for detecting smoke, a heat sensor for detecting heat, and a flame sensor for detecting flame. The cell compartment internal fire detector **34b** may include a thermocouple type fire detector.

(45) The cell compartment internal fire detector **34b** is arranged on an inner surface of the top wall **30a** located at an upper part of the fuel cell compartment **30**. In an unlikely event of a fire inside the fuel cell compartment **30**, the cell compartment internal fire detector **34b** detects the fire and outputs, to the control unit **12a**, a detection signal indicating that the fire has occurred. In this case, the control unit **12a** can control the fuel cell side shutoff valve **33** to stop the supply of the fuel gas from the fuel tank **41** to the fuel cell **31**. As a result, in the fuel cell compartment **30**, the risk of explosion due to ignition of the fuel gas can be reduced as much as possible.

(46) The cell compartment air supply pipe **35** is connected to the fuel cell compartment **30**. The cell compartment air supply pipe **35** extends from the cell compartment air supply port **30e** of the fuel cell compartment **30**, to the deck **1a** and is exposed from the upper surface of the deck **1a**.

(47) A cell compartment air supply device **36** and a cell compartment external gas detector **37** are arranged at an end portion on the deck **1a** side of the cell compartment air supply pipe **35**. The cell compartment air supply device **36** and the cell compartment external gas detector **37** are located above the deck **1a**.

(48) The cell compartment air supply device **36** includes, for example, an inexpensive non-



explosion-proof air supply fan, but may include an explosion-proof air supply fan. The drive of the cell compartment air supply device **36** is controlled by the control unit **12a**. One or more filters (not illustrated) may be arranged in the cell compartment air supply device **36**. The filter removes, for example, dust or sea salt particles.

(49) The cell compartment air supply device **36** supplies air outside the fuel cell compartment **30** to the inside of the fuel cell compartment **30** via the cell compartment air supply pipe **35** and the cell compartment air supply port **30e**. The air inside the fuel cell compartment **30** is discharged to the duct compartment **90** via the cell compartment exhaust port **30f**. In this way, the inside of the fuel cell compartment **30** is ventilated. As a result, it is possible to prevent combustible gas (for example, the fuel gas leaking from the fuel cell **31**) from being retained in the fuel cell compartment **30**.

(50) The cell compartment external gas detector **37** detects combustible gas (for example, hydrogen gas floating around the hull **1**) flowing into the fuel cell compartment **30** from the outside. The cell compartment external gas detector **37** is, for example, a combustible gas sensor such as a hydrogen gas sensor. The cell compartment external gas detector **37** is arranged on a side opposite to the cell compartment air supply pipe **35** with respect to the cell compartment air supply device **36**, that is, on the upstream side of the air flow from the outside to the inside of the fuel cell compartment **30**. The cell compartment external gas detector **37** may include a gas sensor that detects a combustible gas other than hydrogen gas. Examples of combustible gases other than hydrogen gas include methane, ethane, propane, and carbon monoxide.

(51) The cell compartment external gas detector **37** outputs, for example, a detection signal indicating the concentration of combustible gas to the control unit **12a**. As a result, the control unit **12a** can determine, based on the detection signal, whether the concentration of the combustible gas is equal to or higher than a standard value. Then, if the concentration is equal to or higher than the standard value, the control unit **12a** can control the fuel cell side shutoff valve **33** to stop the supply of fuel gas from the fuel tank **41** to the fuel cell **31**. The above-mentioned standard value may be determined based on experiments and/or experience.

(52) The fuel cell ship SH further includes a cooling medium tank **38** and a cooling medium pipe **39**. The cooling medium tank **38** stores cooling medium for cooling the fuel cells **31**. The cooling medium is, for example, an antifreeze liquid having low electrical conductivity. The antifreeze liquid is, for example, a liquid obtained by mixing pure water and ethylene glycol in a predetermined ratio. The cooling medium tank **38** is sealed, but an upper portion may be open.

(53) The cooling medium pipe **39** is a pipe for circulating the cooling medium between the fuel cells **31** and a heat exchanger (not illustrated). A circulation pump (not illustrated) is also provided at a location along the cooling medium pipe **39**. The fuel cells **31** are cooled by driving the circulation pump to supply the cooling medium from the heat exchanger to the fuel cells **31** via the cooling medium pipe **39**. The cooling medium supplied for cooling the fuel cells **31** is also supplied, via the cooling medium pipe **39**, to the cooling medium tank **38**, at which a volume change due to a temperature change of the cooling medium is absorbed and the amount of the cooling medium liquid is monitored.

(54) A cooling tank internal gas detector **38a** is provided in an upper portion inside the cooling medium tank **38**. The cooling tank internal gas detector **38a** is a fuel gas detector that detects the fuel gas existing in the cooling medium tank **38**. As the fuel gas existing in the cooling medium tank **38**, for example, a fuel gas which is leaked in the fuel cell **31** and then enters into the cooling medium tank **38** via the cooling medium pipe **39** can be considered. The fuel gas detection result (for example, fuel gas concentration information) by the cooling tank internal gas detector **38a** is sent to the control unit **12a**. As a result, the control unit **12a** determines, based on the detection result of the cooling tank internal gas detector **38a**, whether there is a fuel gas leak in the fuel cells **31**, and if there is a leak, the control unit **12a** can, for example, perform control to stop electric power generation by the fuel cells **31**.

(55) (2-2. Configuration of Fuel Gas Storage Unit)

(56) The fuel gas storage unit **4** of the fuel cell ship SH includes the fuel tank **41**, a gas filling pipe **42**, and a tank side shutoff valve **43**. The tank side shutoff valve **43** is an example of the peripheral equipment **11**.

(57) The fuel tank **41** stores the fuel gas to be supplied to the fuel cells **31**. In FIG. 2, for convenience, only one fuel tank **41** is illustrated, but the number of fuel tanks **41** is not particularly limited and there may be a plurality of the fuel tanks **41**.

(58) The gas filling pipe **42** is a pipe for replenishing the fuel tank **41** with the fuel gas or filling the fuel tank **41** with an inert gas. One end side of the gas filling pipe **42** is connected to the fuel tank **41**. The other end side of the gas filling pipe **42** is branched into two, and these ends are connected to a fuel gas filling port **82** and an inert gas filling port **84**, respectively. The fuel gas filling port **82** and the inert gas filling port **84** are provided in the duct compartment **90** (particularly an upper duct compartment **80**) described later.

(59) The above-mentioned inert gas is, for example, nitrogen gas. For example, if the fuel gas remains in the fuel tank **41** when performing maintenance such as inspection or repair of the fuel cell ship SH in the dock (dry dock), there is a danger that an explosion may occur when the fuel gas ignites for some reason. Therefore, at the time of maintenance of the fuel cell ship SH, the fuel tank **41** is filled with the inert gas, and the fuel gas is removed from the fuel tank **41**. As a result, it is possible to avoid the danger of explosion.

(60) In the fuel gas supply pipe **32** described above, a side opposite to the connection side with the fuel cell **31** is connected to the fuel tank **41**. That is, the fuel tank **41** and the fuel cell **31** are connected via the fuel gas supply pipe **32**.

(61) The tank side shutoff valve **43** is an example of a shutoff valve SV that opens or closes the flow path of the fuel gas supply pipe **32**. The opening and closing of the tank side shutoff valve **43** is controlled by the control unit **12a**. More specifically, the tank side shutoff valve **43** switches between supplying the fuel gas from the fuel tank **41** to the fuel cells **31** and stopping the supply of fuel gas based on the control of the control unit **12a**. Although only one tank side shutoff valve **43** is provided in the fuel gas supply pipe **32** in a tank compartment **40** described later, two or more tank side shutoff valves **43** may be provided.

(62) That is, it can be said that the fuel gas supply pipe **32** connecting the fuel tank **41** and the fuel cell **31** has at least two shutoff valves SV. The at least two shutoff valves SV include the fuel cell side shutoff valve **33** and the tank side shutoff valve **43**.

(63) The fuel cell ship SH further includes the tank compartment **40**. The tank compartment **40** is a housing body that houses the fuel tank **41**. That is, the fuel cell ship SH includes the tank compartment **40** in which a fuel tank **41** that stores a fuel gas is installed. The tank compartment **40** is arranged in the fuel room **14**.

(64) The tank compartment **40** has a hollow shape. For example, the tank compartment **40** has a hollow and substantially rectangular parallelepiped shape. In this case, the outer walls of the tank compartment **40** include, for example, a top wall **40a**, a bottom wall **40b**, a front wall (not illustrated), a back wall (not illustrated), a side wall **40c**, and a side wall **40d**. However, the top surface, bottom surface, front surface, back surface, and side surfaces of the tank compartment **40** can be arbitrarily determined. The shape of the tank compartment **40** is not particularly limited as long as the tank compartment **40** has a space that can house at least one fuel tank **41**. The tank compartment **40** can also be considered as a container, chamber, or box for housing the fuel tank **41**. The material of the outer wall of the tank compartment **40** is, for example, FRP, but may be an iron plate.

(65) A tank compartment air supply port **40e** with an opening is provided on the side wall **40c** of the tank compartment **40**. The tank compartment air supply port **40e** is connected to a tank compartment air supply pipe **45** described later. The tank compartment air supply port **40e** may be provided on an outer wall other than the side wall **40c** in the tank compartment **40**.

- (66) On the other hand, a tank compartment exhaust port **40f** with an opening is provided on the top wall **40a** of the tank compartment **40**. The tank compartment exhaust port **40f** communicates with a vent pipe **10**. The vent pipe **10** is a pipe for guiding air inside the tank compartment **40** to the outside of the ship. The tank compartment exhaust port **40f** may be provided on an outer wall other than the top wall **40a** in the tank compartment **40**.
- (67) The tank compartment **40** has an interior that is a closed space except for the tank compartment air supply port **40e** and the tank compartment exhaust port **40f**.
- (68) A part of the fuel gas supply pipe **32** described above and the tank side shutoff valve **43** are housed in the tank compartment **40**. The tank compartment **40** further houses a tank compartment internal gas detector **44a** and a tank compartment internal fire detector **44b**.
- (69) The tank compartment internal gas detector **44a** is a fuel gas detector arranged inside the tank compartment **40**. For example, if the fuel gas is hydrogen gas, the tank compartment internal gas detector **44a** includes a hydrogen gas detection sensor.
- (70) The tank compartment internal gas detector **44a** is arranged on the top wall **40a** located at the upper part of the tank compartment **40** to be close to the tank compartment exhaust port **40f** or inside the tank compartment exhaust port **40f**. In the unlikely event that the fuel gas leaks from the fuel tank **41** in the tank compartment **40**, the leaked fuel gas goes toward the vent pipe **10** through the tank compartment exhaust port **40f**. That is, the tank compartment exhaust port **40f** is located on the most downstream side of the flow path through which the fuel gas flows when the fuel gas leaks inside the tank compartment **40**. Therefore, by arranging the tank compartment internal gas detector **44a** at a position near the tank compartment exhaust port **40f** or inside the tank compartment exhaust port **40f**, a fuel gas leaked in the tank compartment **40** can be reliably detected by the tank compartment internal gas detector **44a** located on the most downstream side of the flow path, regardless of where the fuel gas leaks.
- (71) When the tank compartment internal gas detector **44a** detects a fuel gas inside the tank compartment **40**, a detection signal is sent from the tank compartment internal gas detector **44a** to the control unit **12a**. As a result, the control unit **12a** can control the tank side shutoff valve **43** provided in the fuel gas supply pipe **32** to stop the supply of the fuel gas from the fuel tank **41** to the fuel cell **31**. The details of control for opening and closing the tank side shutoff valve **43** will be described later.
- (72) The tank compartment internal fire detector **44b** is a fire detector arranged inside the tank compartment **40**. The tank compartment internal fire detector **44b** includes, for example, one or more sensors among a smoke sensor for detecting smoke, a heat sensor for detecting heat, and a flame sensor for detecting flame. The tank compartment internal fire detector **44b** may include a thermocouple type fire detector.
- (73) The tank compartment internal fire detector **44b** is arranged on an inner surface of the top wall **40a** located at an upper part of the tank compartment **40**. In an unlikely event of a fire inside the tank compartment **40**, the tank compartment internal fire detector **44b** detects the fire and outputs, to the control unit **12a**, a detection signal indicating that the fire has occurred. In this case, the control unit **12a** can control the tank side shutoff valve **43** to stop the supply of the fuel gas from the fuel tank **41** to the fuel cell **31**. As a result, in the tank compartment **40**, the risk of explosion due to ignition of the fuel gas can be reduced as much as possible.
- (74) The tank compartment air supply pipe **45** is connected to the tank compartment **40**. The tank compartment air supply pipe **45** extends from the tank compartment air supply port **40e** of the tank compartment **40** to the deck **1a**, and is exposed from an upper surface of the deck **1a**.
- (75) A tank compartment air supply device **46** and a tank compartment external gas detector **47** are arranged at an end portion on the deck **1a** side of the tank compartment air supply pipe **45**. The tank compartment air supply device **46** and the tank compartment external gas detector **47** are located above the deck **1a**.
- (76) The tank compartment air supply device **46** includes, for example, an inexpensive non-

explosion-proof air supply fan, but may include an explosion-proof air supply fan. The drive of the tank compartment air supply device **46** is controlled by the control unit **12a**. One or more filters (not illustrated) may be arranged in the tank compartment air supply device **46**. The filter removes, for example, dust or sea salt particles.

(77) The tank compartment air supply device **46** supplies air outside the tank compartment **40** to the inside of the tank compartment **40** via the tank compartment air supply pipe **45** and the tank compartment air supply port **40e**. The air inside the tank compartment **40** is discharged to the vent pipe **10** via the tank compartment exhaust port **40f**. In this way, the inside of the tank compartment **40** is ventilated. As a result, even if the fuel gas leaks from the fuel tank **41** in the tank compartment **40**, the retention of the fuel gas can be suppressed.

(78) The tank compartment external gas detector **47** detects combustible gas (for example, hydrogen gas floating around the hull **1**) flowing into the tank compartment **40** from the outside. The tank compartment external gas detector **47** is, for example, a combustible gas sensor such as a hydrogen gas sensor. The tank compartment external gas detector **47** is arranged on a side opposite to the tank compartment air supply pipe **45** with respect to the tank compartment air supply device **46**, that is, on the upstream side of the air flow from the outside to the inside of the tank compartment **40**. The tank compartment external gas detector **47** may include a gas sensor that detects a combustible gas other than hydrogen gas.

(79) The tank compartment external gas detector **47** outputs, to the control unit **12a**, for example, a detection signal indicating the concentration of combustible gas. As a result, the control unit **12a** can determine, based on the detection signal, whether the concentration of the combustible gas is equal to or greater than a standard value. Then, if the concentration is equal to or greater than the standard value, the control unit **12a** can control the tank side shutoff valve **43** to stop the supply of the fuel gas from the fuel tank **41** to the fuel cell **31**. The above-mentioned standard value may be determined based on experiments and/or experience.

(80) (2-3. Duct Compartment)

(81) The fuel cell ship SH further includes a lower duct compartment **70** and an upper duct compartment **80**. Here, the lower duct compartment **70** and the upper duct compartment **80** are collectively referred to as a duct compartment **90**. The duct compartment **90** is a housing body that houses various types of pipes. For example, the duct compartment **90** houses a part of the fuel gas supply pipe **32**. That is, the fuel cell ship SH further includes the duct compartment **90** that houses a part of the fuel gas supply pipe **32**. The inside of the lower duct compartment **70** and the inside of the upper duct compartment **80** communicate with each other via a duct communication portion **91**. In the following, details of the lower duct compartment **70** and the upper duct compartment **80** will be described.

(82) <2-3-1. Lower Duct Compartment>

(83) The lower duct compartment **70** is arranged below the deck **1a**.

(84) More specifically, the lower duct compartment **70** is arranged in the engine room **13**. In the engine room **13**, the lower duct compartment **70** is located on the stern side with respect to the fuel cell compartment **30**. That is, below the deck **1a**, the lower duct compartment **70** is located between the fuel cell compartment **30** and the tank compartment **40**. The lower duct compartment **70** houses a part of the fuel gas supply pipe **32** and a part of the gas filling pipe **42**.

(85) Here, the “part of the fuel gas supply pipe **32**” housed in the lower duct compartment **70** refers to a portion of the fuel gas supply pipe **32** located between the fuel cell compartment **30** and the tank compartment **40**. The “part of the gas filling pipe **42**” housed in the lower duct compartment **70** refers to a portion of the gas filling pipe **42** located between the tank compartment **40** and the upper duct compartment **80**.

(86) The material of the lower duct compartment **70** is, for example, FRP, but may be an iron plate. The lower duct compartment **70** has a hollow shape. For example, the lower duct compartment **70** has a hollow and substantially rectangular parallelepiped shape. In this case, the outer walls of the

lower duct compartment **70** include, for example, a top wall **70a**, a bottom wall **70b**, a front wall (not illustrated), a back wall (not illustrated), a side wall **70c**, and a side wall **70d**. However, the top surface, bottom surface, front surface, back surface, and side surfaces of the lower duct compartment **70** can be arbitrarily determined. The shape of the lower duct compartment **70** is not particularly limited as long as the lower duct compartment **70** has a space that can house a part of the fuel gas supply pipe **32** and the like. The lower duct compartment **70** can also be regarded as a container, a chamber, or a box for housing a part of the fuel gas supply pipe **32** and the like.

(87) A lower duct compartment air supply port **70e** with an opening is provided in the side wall **70d** of the lower duct compartment **70**. The lower duct compartment air supply port **70e** is connected to a lower duct compartment air supply pipe **74** described later. The lower duct compartment air supply port **70e** may be provided on an outer wall other than the side wall **70d** in the lower duct compartment **70**.

(88) On the other hand, a lower duct compartment communication port **70f** with an opening is provided in the top wall **70a** of the lower duct compartment **70**. The lower duct compartment communication port **70f** communicates with the duct communication portion **91** described above. The lower duct compartment communication port **70f** may be provided on an outer wall other than the top wall **70a** in the lower duct compartment **70**.

(89) A cell compartment communication port **70g** with an opening is provided in the side wall **70d** of the lower duct compartment **70**. The cell compartment communication port **70g** is connected to the cell compartment exhaust port **30f** of the fuel cell compartment **30** described above via a communication pipe **92**. As a result, the air inside the fuel cell compartment **30** flows into the lower duct compartment **70** via the cell compartment exhaust port **30f**, the communication pipe **92**, and the cell compartment communication port **70g**. The cell compartment communication port **70g** may be provided on an outer wall other than the side wall **70d** in the lower duct compartment **70**.

(90) The communication pipe **92** includes, for example, a double pipe having an inner pipe and an outer pipe. Examples of the inner pipe include the fuel gas supply pipe **32**. The outer pipe is located on the outside of the inner pipe in the radial direction. The gas inside the fuel cell compartment **30** travels between the inner pipe and the outer pipe of the communication pipe **92**, from the cell compartment exhaust port **30f** to the cell compartment communication port **70g** of the lower duct compartment **70**.

(91) The lower duct compartment **70** has a closed space inside except for the lower duct compartment air supply port **70e**, the lower duct compartment communication port **70f**, and the cell compartment communication port **70g**.

(92) The lower duct compartment **70** houses a part of a fuel gas discharge pipe **71**. The fuel gas discharge pipe **71** is a fuel discharge pipe provided by branching from the fuel gas supply pipe **32** located in the lower duct compartment **70**. For example, the fuel gas discharge pipe **71** is provided by branching from the fuel gas supply pipe **32** between the two shutoff valves SV.

(93) More specifically, the fuel gas discharge pipe **71** is provided by branching from the fuel gas supply pipe **32** between the tank side shutoff valve **43** in the tank compartment **40** and the fuel cell side shutoff valve **33** in the fuel cell compartment **30**. The fuel gas discharge pipe **71** extends from the inside of the lower duct compartment **70** to the inside of the upper duct compartment **80** via the lower duct compartment communication port **70f** and the duct communication portion **91**, and further communicates with the inside of the vent pipe **10**. Therefore, the “part of the fuel gas discharge pipe **71**” housed in the lower duct compartment **70** refers to a portion of the fuel gas discharge pipe **71** located between the point of the branching from the fuel gas supply pipe **32** and the upper duct compartment **80**.

(94) The lower duct compartment **70** further houses the release valve **72**. The release valve **72** is an on-off valve installed in the fuel gas discharge pipe **71** to open or close the flow path of the fuel gas discharge pipe **71**. The release valve **72** is an example of peripheral equipment **11**. The opening and closing of the release valve **72** are controlled by the control unit **12a**.

(95) As described above, when the shutoff valve SV installed in the tank compartment **40** is the tank side shutoff valve **43** and the shutoff valve SV installed in the fuel cell compartment **30** is the fuel cell side shutoff valve **33**, the fuel cell ship SH further includes, between the tank side shutoff valve **43** and the fuel cell side shutoff valve **33**, the fuel gas discharge pipe **71** provided by branching from the fuel gas supply pipe **32** and a release valve **72** installed in the fuel gas discharge pipe **71**. The release valve **72** may be installed in the upper duct compartment **80**.

(96) The lower duct compartment **70** further houses a lower duct compartment internal gas detector **73**. The lower duct compartment internal gas detector **73** is a fuel gas detector arranged inside the lower duct compartment **70**. For example, if the fuel gas is hydrogen gas, the lower duct compartment internal gas detector **73** includes a hydrogen gas detection sensor.

(97) The lower duct compartment internal gas detector **73** is arranged on the top wall **70a** located at an upper portion of the lower duct compartment **70** to be close to the lower duct compartment communication port **70f** or inside the lower duct compartment communication port **70f**. In the unlikely event that the fuel gas leaks from the fuel gas supply pipe **32** in the lower duct compartment **70**, the leaked fuel gas goes toward the upper duct compartment **80** through the lower duct compartment communication port **70f**. That is, the lower duct compartment communication port **70f** is located on the most downstream side of the flow path through which the fuel gas flows when the fuel gas leaks in the lower duct compartment **70**. Therefore, by arranging the lower duct compartment internal gas detector **73** at a position close to the lower duct compartment communication port **70f** or inside the lower duct compartment communication port **70f**, a fuel gas leaked in the lower duct compartment **70** can be reliably detected by the lower duct compartment internal gas detector **73** located on the most downstream side of the flow path, regardless of where the fuel gas leaks.

(98) If the lower duct compartment internal gas detector **73** detects the fuel gas in the lower duct compartment **70**, a detection signal is sent from the lower duct compartment internal gas detector **73** to the control unit **12a**. As a result, the control unit **12a** can control the shutoff valves SV provided in the fuel gas supply pipe **32** to stop the supply of fuel gas from the fuel tank **41** to the fuel cell **31**.

(99) The lower duct compartment **70** may further house a fire detector that detects a fire inside the lower duct compartment **70**.

(100) The lower duct compartment air supply pipe **74** is connected to the lower duct compartment **70**. The lower duct compartment air supply pipe **74** extends from the lower duct compartment air supply port **70e** of the lower duct compartment **70** to the deck **1a** and is exposed from the upper surface of the deck **1a**.

(101) A lower duct compartment air supply device **75** and a lower duct compartment external gas detector **76** are arranged at an end portion on the deck **1a** side of the lower duct compartment air supply pipe **74**. The lower duct compartment air supply device **75** and the lower duct compartment external gas detector **76** are located above the deck **1a**.

(102) The lower duct compartment air supply device **75** includes, for example, an inexpensive non-explosion-proof air supply fan, but may include an explosion-proof air supply fan. The drive of the lower duct compartment air supply device **75** is controlled by the control unit **12a**. One or more filters (not illustrated) may be arranged in the lower duct compartment air supply device **75**. The filter removes, for example, dust or sea salt particles.

(103) The lower duct compartment air supply device **75** supplies the air outside the lower duct compartment **70** (duct compartment **90**) to the inside of the lower duct compartment **70** via the lower duct compartment air supply pipe **74** and the lower duct compartment air supply port **70e**. The air inside the lower duct compartment **70** is discharged to the upper duct compartment **80** through the lower duct compartment communication port **70f**. In this way, the inside of the lower duct compartment **70** is ventilated. As a result, even if the fuel gas leaks from the fuel gas supply pipe **32** in the lower duct compartment **70**, retention of the fuel gas can be suppressed.

(104) The lower duct compartment external gas detector **76** detects combustible gas (for example, hydrogen gas floating around the hull **1**) flowing into the duct compartment **90** from the outside. The lower duct compartment external gas detector **76** is, for example, a combustible gas sensor such as a hydrogen gas sensor. The lower duct compartment external gas detector **76** is arranged on a side opposite to the lower duct compartment air supply pipe **74** with respect to the lower duct compartment air supply device **75**, that is, on the upstream side of the air flow from the outside to the inside of the duct compartment **90**. The lower duct compartment external gas detector **76** may include a gas sensor that detects a combustible gas other than hydrogen gas.

(105) The lower duct compartment external gas detector **76** outputs, for example, a detection signal indicating the concentration of combustible gas to the control unit **12a**. As a result, the control unit **12a** can determine, based on the detection signal, whether the concentration of the combustible gas is equal to or higher than a standard value. Then, if the concentration is equal to or higher than the standard value, the control unit **12a** can control the shutoff valves **SV** to stop the supply of fuel gas from the fuel tank **41** to the fuel cell **31**. The above-mentioned standard value may be determined based on experiments and/or experience.

(106) <2-3-2. Upper Duct Compartment>

(107) The upper duct compartment **80** is arranged on the deck **1a**. More specifically, the upper duct compartment **80** is arranged on the deck **1a** to cover an area partially including the lower duct compartment **70** and the tank compartment **40**. The upper duct compartment **80** houses a part of the fuel gas discharge pipe **71** and a part of the gas filling pipe **42**.

(108) Here, the “part of the fuel gas discharge pipe **71**” housed in the upper duct compartment **80** refers to a portion of the fuel gas discharge pipe **71** that extends from the lower duct compartment **70** toward the vent pipe **10**. The “part of the gas filling pipe **42**” housed in the upper duct compartment **80** refers to a portion of the gas filling pipe **42** that extends from the lower duct compartment **70** to the fuel gas filling port **82** described later.

(109) The material of the upper duct compartment **80** is, for example, FRP, but may be an iron plate. The upper duct compartment **80** has a hollow shape. For example, the upper duct compartment **80** has a hollow and substantially rectangular parallelepiped shape. In this case, the outer walls of the upper duct compartment **80** include, for example, a top wall **80a**, a bottom wall **80b**, a front wall (not illustrated), a back wall (not illustrated), a side wall **80c**, and a side wall **80d**. However, the top surface, bottom surface, front surface, back surface, and side surfaces of the upper duct compartment **80** can be arbitrarily determined. The shape of the upper duct compartment **80** is not particularly limited as long as the upper duct compartment **80** has a space that can house a part of the fuel gas discharge pipe **71** and the like. The upper duct compartment **80** can also be regarded as a container, a chamber, or a box for housing the part of the fuel gas discharge pipe **71** and the like.

(110) The fuel gas discharge pipe **71**, as described above, communicates with the inside of the vent pipe **10**. Thus, when the release valve **72** is opened, the gas inside the fuel gas discharge pipe **71** (for example, the fuel gas) flows from an end portion **71a** of the fuel gas discharge pipe **71** into the vent pipe **10** and is released from the vent pipe **10** to outside the ship. Here, it is desirable that, in the vent pipe **10**, the end portion **71a** of the fuel gas discharge pipe **71** faces upward, that is, faces the open port side of the vent pipe **10**. In this case, the discharge direction of gas discharged from the end portion **71a** of the fuel gas discharge pipe **71** is upward.

(111) For example, if the fuel gas is discharged sideways from the end portion **71a** of the fuel gas discharge pipe **71**, the discharged fuel gas reaches the inner wall surface of the vent pipe **10** and then flows downward. This may result in unwanted detection by the tank compartment internal gas detector **44a** in the tank compartment **40**. By the end portion **71a** of the fuel gas discharge pipe **71** facing upward inside the vent pipe **10** as described above, it is possible to reduce unwanted detection by the tank compartment internal gas detector **44a** due to the fuel gas discharged from the end portion **71a**.

(112) An upper duct compartment air supply port **80e** with an opening is provided in the bottom wall **80b** of the upper duct compartment **80**. The upper duct compartment air supply port **80e** communicates with the duct communication portion **91**. Therefore, the upper duct compartment **80** communicates with the lower duct compartment **70** via the upper duct compartment air supply port **80e**, the duct communication portion **91**, and the lower duct compartment communication port **70f**. The upper duct compartment air supply port **80e** may be provided on an outer wall other than the bottom wall **80b** in the upper duct compartment **80**.

(113) The upper duct compartment **80** has a vent pipe communication portion **81**. The vent pipe communication portion **81** is a pipe communicating between the inside of the upper duct compartment **80** and the vent pipe **10**. In FIG. 2, the vent pipe communication portion **81** is illustrated as a portion having a shape bent upward from the horizontal direction, but the shape of the vent pipe communication portion **81** is not limited to the shape in FIG. 2. The reason why the vent pipe communication portion **81** is bent upward is similar to the reason why the end portion **71a** of the fuel gas discharge pipe **71** is bent upward. That is, the vent pipe communication portion **81** is bent upward to reduce unwanted detection by the tank compartment internal gas detector **44a** due to the fuel gas discharged from the vent pipe communication portion **81**, which will be described later.

(114) The vent pipe **10** extends upward from the tank compartment **40** and passes through the interior of the upper duct compartment **80**. More specifically, the vent pipe **10** passes through the bottom wall **80b** of the upper duct compartment **80**, enters the inside of the vent pipe **10**, and passes through the top wall **80a**. The vent pipe communication portion **81** is provided in the upper duct compartment **80** to penetrate through the side wall of the vent pipe **10**. As a result, the upper duct compartment **80** communicates with the vent pipe **10** via the vent pipe communication portion **81**.

(115) Therefore, the air inside the upper duct compartment **80** is discharged to the outside of the ship through the vent pipe communication portion **81** and the vent pipe **10**. In this way, it is possible to ventilate the inside of the upper duct compartment **80**. If the fuel gas leaks from the fuel gas discharge pipe **71** in the upper duct compartment **80**, the leaked fuel gas is discharged to the outside of the ship through the vent pipe communication portion **81** and the vent pipe **10**. In this way, it is possible to prevent the leaked fuel gas from being retained in the upper duct compartment **80**.

(116) The upper duct compartment **80** and the lower duct compartment **70** communicate with each other via the duct communication portion **91**. As a result, (1) air taken into the inside of the lower duct compartment **70** via the lower duct compartment air supply pipe **74**, (2) a fuel gas leaked from the fuel gas supply pipe **32** in the lower duct compartment **70** for some reason, and (3) air or a fuel gas discharged from the fuel cell compartment **30** to the lower duct compartment **70** via the communication pipe **92** can be discharged to the outside of the ship via the upper duct compartment **80** and the vent pipe **10**. In this way, it is possible to suppress the retention of the fuel gas inside the lower duct compartment **70** and inside the fuel cell compartment **30**.

(117) The fuel gas filling port **82** and a fuel gas check valve **83** are provided in the upper duct compartment **80**. The fuel gas filling port **82** is connected to the gas filling pipe **42**. The fuel gas check valve **83** is provided in the gas filling pipe **42**. More specifically, the fuel gas check valve **83** is located between the point where an inert gas pipe **87** (described later) branches from the gas filling pipe **42** and the fuel gas filling port **82**.

(118) The fuel gas supplied from the fuel gas filling port **82** travels through the fuel gas check valve **83** and the gas filling pipe **42**, and is supplied to the fuel tank **41** in the tank compartment **40**. As a result, the fuel gas is filled in the fuel tank **41** and stored. The fuel gas check valve **83** is provided to prevent backflow of the fuel gas from the fuel tank **41** side to the fuel gas filling port **82**.

(119) The upper duct compartment **80** is further provided with the inert gas filling port **84**, an on-off valve **85**, an inert gas check valve **86**, and the inert gas pipe **87**. The inert gas filling port **84** is connected to the inert gas pipe **87**. The inert gas pipe **87** is provided by branching from the gas



filling pipe **42** in the upper duct compartment **80**. The on-off valve **85** and the inert gas check valve **86** are provided in the inert gas pipe **87**. In the inert gas pipe **87**, the on-off valve **85** is located between the inert gas filling port **84** and the inert gas check valve **86**.

(120) The on-off valve **85** opens or closes the flow path of the inert gas pipe **87**. In a configuration in which the inert gas check valve **86** is provided in the inert gas pipe **87**, installation of the on-off valve **85** may be omitted.

(121) When inert gas is supplied to the inert gas filling port **84** and the on-off valve **85** opens the flow path of the inert gas pipe **87** in a state in which the fuel gas is not supplied to the fuel gas filling port **82**, the inert gas is supplied to the fuel tank **41** in the tank compartment **40** through the inert gas check valve **86**, and via the inert gas pipe **87** and the gas filling pipe **42**. In addition, the tank side shutoff valve **43** opens the flow path of the fuel gas supply pipe **32**, the fuel cell side shutoff valve **33** closes the flow path of the fuel gas supply pipe **32**, and the release valve **72** opens the flow path of the fuel gas discharge pipe **71**, whereby the fuel gas remaining in the fuel tank **41** is discharged to the vent pipe **10** via the fuel gas supply pipe **32** and the fuel gas discharge pipe **71**. As a result, the fuel gas can be removed from the fuel tank **41** (purge process).

(122) There may be a pipe from the gas filling pipe **42** that is directly connected to the fuel gas supply pipe **32** between the fuel tank **41** and the tank side shutoff valve **43** (tank method). In this configuration, when performing a purge process for the fuel tank **41** using the inert gas, it is necessary to fill the fuel tank **41** with the inert gas in a state in which the tank side shutoff valve **43** is closed, and after that, to open the tank side shutoff valve **43** for the purpose of facilitating the release of the inert gas from the fuel tank **41**.

(123) The fuel gas filling port **82** and the inert gas filling port **84** are provided in the upper duct compartment **80** as described above. More specifically, the fuel gas filling port **82** and the inert gas filling port **84** are located at a boundary surface between the inside and the outside of the upper duct compartment **80**. That is, “the fuel gas filling port **82** and the inert gas filling port **84** are provided in the upper duct compartment **80**” includes a case where the fuel gas filling port **82** and the inert gas filling port **84** are provided at the boundary surface of the upper duct compartment **80**.

(124) An upper duct compartment internal gas detector **88** is housed in the upper duct compartment **80**. The upper duct compartment internal gas detector **88** is a fuel gas detector arranged inside the upper duct compartment **80**. For example, if the fuel gas is hydrogen gas, the upper duct compartment internal gas detector **88** includes a hydrogen gas detection sensor.

(125) The upper duct compartment internal gas detector **88** is arranged on the top wall **80a** located in an upper portion of the upper duct compartment **80**. Hydrogen gas as the fuel gas is lighter than air and rises. Therefore, if the fuel gas leaks in the upper duct compartment **80**, the leaked fuel gas can be reliably detected by the upper duct compartment internal gas detector **88**. To more reliably detect the fuel gas leaked in the upper duct compartment **80**, the upper duct compartment internal gas detector **88** may be arranged at a position close to the vent pipe communication portion **81**.

(126) If the upper duct compartment internal gas detector **88** detects the fuel gas in the upper duct compartment **80**, a detection signal is sent from the upper duct compartment internal gas detector **88** to the control unit **12a**. As a result, the control unit **12a** can control the shutoff valves SV provided in the fuel gas supply pipe **32** to stop the supply of fuel gas from the fuel tank **41** to the fuel cell **31**.

(127) The upper duct compartment **80** may further house a fire detector that detects a fire inside the upper duct compartment **80**.

(128) (2-4. Supplementary Information about Vent Pipe)

(129) Inside the vent pipe **10**, a vent pipe internal gas detector **10a** is provided further on the downstream side than a discharge port **81a** of the vent pipe communication portion **81**. The downstream side refers to the downstream side in the air flow direction when the air inside the tank compartment **40** flows inside the vent pipe **10** and is discharged to the outside of the ship. For example, if the fuel gas is hydrogen gas, the vent pipe internal gas detector **10a** is configured by a

diffusion type or suction type hydrogen gas detection sensor. A detection signal from the vent pipe internal gas detector **10a** is sent to the control unit **12a**. The control of the control unit **12a** based on the detection result of the vent pipe internal gas detector **10a** will be described later.

(130) [3. Opening and Closing Control of Shutoff Valves]

(131) As described above, in the fuel gas supply pipe **32**, at least one tank side shutoff valve **43** is provided in the tank compartment **40**, and at least one fuel cell side shutoff valve **33** is provided in the fuel cell compartment **30**. That is, at least one shutoff valve SV (the tank side shutoff valve **43**, the fuel cell side shutoff valve **33**) is installed in each of the tank compartment **40** and the fuel cell compartment **30**.

(132) The tank compartment internal gas detector **44a** is installed in the tank compartment **40**, and the cell compartment internal gas detector **34a** is installed in the fuel cell compartment **30**. That is, in each of the tank compartment **40** and the fuel cell compartment **30**, a fuel gas detector (the tank compartment internal gas detector **44a**, the cell compartment internal gas detector **34a**) that detects a fuel gas being a gaseous state of the fuel, is each installed.

(133) In such a configuration, the control unit **12a** controls the opening and closing the shutoff valves SV as described below based on a detection signal (detection result) output from the fuel gas detectors. Hereinafter, a specific example of control for the opening and closing the shutoff valves SV will be described with reference to FIGS. **1** and **2** as necessary based on the flowcharts starting in FIG. **3**. Here, unless otherwise specified, it is presumed that the control unit **12a** issues a closing command (a control signal for closing) to the release valve **72**, whereby the release valve **72** is closed.

(134) (3-1. Specific Example 1 of Control for Opening and Closing Shutoff Valve)

(135) FIG. **3** is a flowchart illustrating a processing flow according to an example of control for opening and closing the shutoff valves SV in the present embodiment. If the tank compartment internal gas detector **44a** detects that the concentration of the fuel gas in the tank compartment **40** is equal to or greater than the standard value (Yes in **S1**), the control unit **12a** outputs a closing signal to both the tank side shutoff valve **43** and the fuel cell side shutoff valve **33** to close both the tank side shutoff valve **43** and the fuel cell side shutoff valve **33** (**S2**). As a result, the supply of the fuel gas from the fuel tank **41** to the fuel cell **31** via the fuel gas supply pipe **32** is stopped.

(136) For example, 40% LEL can be considered as the standard value, but as described above, the standard value may be appropriately determined based on experiments or experience (the same also applies to the standard values below).

(137) In **S1**, even if the tank compartment internal gas detector **44a** detects that the concentration of the fuel gas in the tank compartment **40** is less than the standard value (No in **S1**), when the cell compartment internal gas detector **34a** detects that the concentration of the fuel gas in the fuel cell compartment **30** is equal to or greater than the standard value (Yes in **S3**), the control unit **12a** outputs a closing signal to both the tank side shutoff valve **43** and the fuel cell side shutoff valve **33** to close both the tank side shutoff valve **43** and the fuel cell side shutoff valve **33** (**S2**). Therefore, in this case as well, the supply of the fuel gas from the fuel tank **41** to the fuel cell **31** via the fuel gas supply pipe **32** is stopped.

(138) On the other hand, in **S3** when the cell compartment internal gas detector **34a** detects that the concentration of the fuel gas in the fuel cell compartment **30** is less than the standard value (No in **S13**), the control unit **12a** outputs an opening signal to both the tank side shutoff valve **43** and the fuel cell side shutoff valve **33** to open both the tank side shutoff valve **43** and the fuel cell side shutoff valve **33** (**S4**). In this case, the fuel gas is supplied from the fuel tank **41** to the fuel cell **31** via the fuel gas supply pipe **32**. The order of **S1** and **S3** may be interchanged.

(139) (3-2. Specific Example 2 of Control for Opening and Closing Shutoff Valve)

(140) FIG. **4** is a flowchart illustrating a processing flow according to another example of control for opening and closing the shutoff valves SV. The control unit **12a** may control the opening and closing the shutoff valves SV as described below. That is, if the tank compartment internal gas

detector **44a** detects that the concentration of the fuel gas in the tank compartment **40** is equal to or greater than the standard value (Yes in **S11**), the control unit **12a** outputs a closing signal to the tank side shutoff valve **43** to close the tank side shutoff valve **43** (**S12**). Due to the closing of the tank side shutoff valve **43**, the supply of the fuel gas from the fuel tank **41** to the fuel cell **31** is stopped. (141) In **S11**, if the tank compartment internal gas detector **44a** detects that the concentration of the fuel gas in the tank compartment **40** is less than the standard value (No in **S11**), the control unit **12a** outputs an opening signal to the tank side shutoff valve **43** to open the tank side shutoff valve **43** (**S13**).

(142) If the cell compartment internal gas detector **34a** detects that the concentration of the fuel gas in the fuel cell compartment **30** is equal to or greater than the standard value (Yes in **S14**), the control unit **12a** outputs a closing signal to the fuel cell side shutoff valve **33** to close the fuel cell side shutoff valve **33** (**S15**). As a result, even in a state in which the tank side shutoff valve **43** is open, the fuel gas supply from the fuel tank **41** to the fuel cell **31** is stopped due to the closing of the fuel cell side shutoff valve **33**.

(143) In **S14**, if the cell compartment internal gas detector **34a** detects that the concentration of the fuel gas in the fuel cell compartment **30** is less than the standard value (No in **S14**), the control unit **12a** outputs an opening signal to the fuel cell side shutoff valve **33** to open the fuel cell side shutoff valve **33** (**S16**). Therefore, if the tank side shutoff valve **43** is opened in **S13**, the fuel gas is supplied from the fuel tank **41** to the fuel cell **31** by opening the fuel cell side shutoff valve **33** in **S16**.

(144) As described above, in the Specific Examples 1 and 2, if the concentration of the fuel gas is less than the standard value in both the tank compartment **40** and the fuel cell compartment **30**, the fuel gas is supplied from the fuel tank **41** to the fuel cell **31** via the fuel gas supply pipe **32**. If the concentration of the fuel gas is equal to or greater than the standard value in at least one of the tank compartment **40** and the fuel cell compartment **30**, the fuel gas supply from the fuel tank **41** to the fuel cell **31** via the fuel gas supply pipe **32** is stopped.

(145) Based on Specific Examples 1 and 2, the following can also be said. That is, if the tank compartment internal gas detector **44a** detects that the concentration of the fuel gas is equal to or greater than the standard value, the control unit **12a** closes the shutoff valve SV (tank side shutoff valve **43**) in the compartment (tank compartment **40**) in which the tank compartment internal gas detector **44a** is installed. if the cell compartment internal gas detector **34a** detects that the concentration of the fuel gas is equal to or greater than the standard value, the control unit **12a** closes the shutoff valve SV (fuel cell side shutoff valve **33**) in the compartment (fuel cell compartment **30**) in which the cell compartment internal gas detector **34a** is installed (see **S2**, **S12**, **S15**).

(146) As described above, the fuel cell ship SH according to the present embodiment includes the control unit **12a** that controls the opening and closing the shutoff valves SV. If at least one of the fuel gas detectors (at least one of the tank compartment internal gas detector **44a** and the cell compartment internal gas detector **34a**) (installed in the tank compartment **40** and the fuel cell compartment **30**) detects that the concentration of the fuel gas is equal to or greater than a predetermined standard value, the control unit **12a** closes the shutoff valve SV in the tank compartment **40** or the fuel cell compartment **30** in which the fuel gas detector that detects the concentration equal to or greater than the standard value is installed.

(147) If the shutoff valve SV in the compartment where the fuel gas detector (the tank compartment internal gas detector **44a** or the cell compartment internal gas detector **34a**) that detects that the concentration of the fuel gas is equal to or greater than the standard value is installed is closed, and the supply of the fuel gas from the fuel tank **41** to the fuel cell **31** is stopped, the fuel cell **31** cannot generate electric power by an electrochemical reaction with the fuel gas. That is, in the unlikely event of a fuel gas leak in the above compartment so that the concentration is equal to or greater than the standard value, the electric power generation of the fuel cell **31** can be stopped. Even if the

electric power generation of the fuel cell **31** is stopped, it is possible to continue the propulsion of the fuel cell ship SH by the propulsion device **6** by supplying electric power from the storage battery of the storage battery system **5**.

(148) Particularly, when at least one of the fuel gas detectors (at least one of the tank compartment internal gas detector **44a** and the cell compartment internal gas detector **34a**) detects that the concentration of the fuel gas is equal to or greater than the standard value, the control unit **12a** closes the shutoff valves SV (the tank side shutoff valve **43**, the fuel cell side shutoff valve **33**) in all the compartments (S2).

(149) If the concentration of the fuel gas is equal to or greater than the standard value, the shutoff valves SVs are closed in all the compartments: the tank compartment **40** and the fuel cell compartment **30**. As a result, the supply of the fuel gas from the fuel tank **41** to the fuel cells **31** is reliably stopped, and the electric power generation of the fuel cells **31** can be reliably stopped.

(150) [4. Combined Use with Control for Opening and Closing Release Valve]

(151) FIG. **5** is a flowchart illustrating a processing flow when control for the opening and closing the release valve **72** is also controlled in control for the opening and closing the shutoff valves SV in the above-described Specific Example 1. The flowchart in FIG. **5** is similar to that in FIG. **3** except that step S2-1 is added. When at least one of the fuel gas detectors (at least one of the tank compartment internal gas detector **44a** and the cell compartment internal gas detector **34a**) detects that the concentration of the fuel gas is equal to or greater than the standard value (Yes in S1, or Yes in S3), it is desirable that the control unit **12a** closes the tank side shutoff valve **43** and the fuel cell side shutoff valve **33** (S2) and opens the release valve **72** (S2-1).

(152) In S2, when the tank side shutoff valve **43** and the fuel cell side shutoff valve **33** are closed, the fuel gas remains in the fuel gas supply pipe **32** between the tank side shutoff valve **43** and the fuel cell side shutoff valve **33**. When the fuel gas with a high pressure is left remaining in the fuel gas supply pipe **32**, there is a risk of explosion due to ignition when the fuel gas leaks for some reason.

(153) In S2-1, if the control unit **12a** controls to open the release valve **72**, the fuel gas remaining in the fuel gas supply pipe **32** between the tank side shutoff valve **43** and the fuel cell side shutoff valve **33** may be released to the outside (for example, outside the ship) via the release valve **72**. As a result, it is possible to avoid a situation in which the fuel gas with a high pressure is left remaining in the fuel gas supply pipe **32**.

(154) FIG. **6** is a flowchart illustrating a processing flow according to another example of control for opening and closing the release valve **72**. The flowchart in FIG. **6** is similar to that in FIG. **5** except that steps S2-2 and S2-3 are added. When the pressure inside the fuel gas supply pipe **32** reaches a predetermined specified pressure after the release valve **72** is opened in S2-1, the control unit **12a** desirably closes the release valve **72** (S2-2, S2-3).

(155) The above-mentioned specified pressure refers to, for example, atmospheric pressure. Determining whether the pressure inside the fuel gas supply pipe **32** has reached the specified pressure may be performed by the control unit **12a** determining whether a specified time (for example, one second) has elapsed since the release valve **72** was opened. The pressure inside the fuel gas supply pipe **32** may be measured by a pressure gauge, and based on the measurement result, the control unit **12a** may determine whether the pressure inside the fuel gas supply pipe **32** has reached a specified pressure.

(156) When the release valve **72** is left open for a long time in the state of atmospheric pressure, air enters the fuel gas supply pipe **32** from the outside (for example, via the vent pipe **10**). In this case, when the release valve **72** is closed, the shutoff valve SV is opened, and the fuel gas is supplied from the fuel tank **41** to the fuel cell **31**, to restart the fuel cell ship SH, the air existing in the fuel gas supply pipe **32** is also supplied to the fuel cell **31**. The air may cause inconveniences such as oxidizing and corroding the electrodes of the fuel cell **31**.

(157) If the release valve **72** is closed after the release valve **72** is opened and then a pressure inside

the fuel gas supply pipe **32** reaches a specified pressure, it then is possible to prevent air from entering the fuel gas supply pipe **32** from the outside (via the vent pipe **10**) via the release valve **72**. As a result, it is possible to reduce the possibility that the air will cause inconveniences such as corrosion of the electrodes of the fuel cell **31**.

(158) FIG. **7** is a flowchart illustrating a processing flow according to yet another example of control for opening and closing the release valve **72**. The flowchart in FIG. **7** is similar to that in FIG. **6** except that step S2-2 is replaced with step S2-2'. The control unit **12a** may close the release valve **72** after a predetermined specified time has elapsed since opening the release valve **72** in S2-1 (S2-2', S2-3). Desirably the specified time is set to a time shorter than the time when the pressure in the fuel gas supply pipe **32** reaches the atmospheric pressure after the release valve **72** is opened. From this aspect, the specified time may be set to several seconds (for example, one second).

(159) If air (including oxygen) exists in the fuel gas supply pipe **32**, then, when the release valve **72** is closed, the shutoff valves SV are opened, and a fuel gas is supplied from the fuel tank **41** to the fuel cell **31** to restart an operation of the fuel cell ship SH, the above air may be also supplied to the fuel cell **31**, and inconveniences such as corrosion of the electrodes of the fuel cell **31** may occur as described above.

(160) If the release valve **72** is closed after a predetermined specified time has elapsed since the release valve **72** was opened, the amount of air entering the fuel gas supply pipe **32** from the outside via the release valve **72** can be reduced as much as possible. As a result, it is possible to reduce as much as possible the possibility of causing inconveniences such as corrosion of the electrodes of the fuel cell **31** described above.

(161) [5. Control for Opening and Closing Shutoff Valves and Release Valve in Consideration of the Duct Compartment]

(162) FIG. **8** is a flowchart illustrating a processing flow according to an example of control for opening and closing the shutoff valves SV and the release valve **72** in consideration of also detecting a fuel gas in the duct compartment. The flowchart in FIG. **8** is similar to that in FIG. **5** except that step S3-1 is added between steps S3 and S4. FIG. **8** does not illustrate steps (S2-2, S2-2', S2-3) of closing the release valve **72** after opening the release valve **72** as illustrated in FIGS. **6** and **7**, but needless to say, these steps may also be performed.

(163) In the present embodiment, as described above, a fuel gas detector is installed in the duct compartment **90** in addition to the tank compartment **40** and the fuel cell compartment **30**. For example, an upper duct compartment internal gas detector **88** is installed in the upper duct compartment **80**. In this configuration, when the fuel gas detector in the duct compartment **90** (for example, the upper duct compartment internal gas detector **88**) detects that the concentration of the fuel gas is equal to or greater than the standard value, the control unit **12a** may close the tank side shutoff valve **43** and the fuel cell side shutoff valve **33** (S3-1, S2). When the fuel gas detector in the lower duct compartment **70** (the lower duct compartment internal gas detector **73**) detects that the concentration of the fuel gas is equal to or greater than the standard value, the control unit **12a** may close the tank side shutoff valve **43** and fuel cell side shutoff valve **33**.

(164) In the duct compartment **90**, even if a fuel gas leak occurs so that the concentration of the fuel gas is equal to or greater than the standard value, the tank side shutoff valve **43** and the fuel cell side shutoff valve **33** are closed. As a result, the supply of the fuel gas from the fuel tank **41** to the fuel cell **31** is stopped. Therefore, even if a fuel gas leak occurs in the duct compartment **90**, the electric power generation of the fuel cell **31** can be stopped.

(165) [6. Failure Determination of Release Valve]

(166) In the present embodiment, as described above, the fuel gas discharge pipe **71** branching from the fuel gas supply pipe **32** extends from the inside the lower duct compartment **70** to the inside of the upper duct compartment **80** and further communicates with the inside of the vent pipe **10**. In this configuration, it is possible to guide the fuel gas discharged from the fuel gas discharge pipe **71** via the release valve **72** to the vent pipe **10** and then discharge the fuel gas to the outside

via the vent pipe **10**. The vent pipe internal gas detector **10a** is provided inside the vent pipe **10**. (167) Thus, in the configuration in which the fuel cell ship SH is provided with the vent pipe **10** that guides the fuel gas discharged from the fuel gas discharge pipe **71** to the outside through the release valve **72**, and the vent pipe internal gas detector **10a** that detects the fuel gas inside the vent pipe **10**, the control unit **12a** can determine whether the release valve **72** has failed by using the detection result of the vent pipe internal gas detector **10a**. This will be described in detail below. (168) FIG. **9** is a flowchart illustrating a processing flow according to an example of control for opening and closing the shutoff valves SV and the release valve **72** in consideration of also detecting the fuel gas by the vent pipe internal gas detector **10a**. The flowchart of FIG. **9** is similar to that of FIG. **8** except that steps S3-2, S5, and S6 are added. The control unit **12a** is in a state of issuing a closing command to the release valve **72**.

(169) When, in S1, the tank compartment internal gas detector **44a** detects that the concentration of the fuel gas in the tank compartment **40** is less than the standard value (No in S1), in S3, the cell compartment internal gas detector **34a** detects that the concentration of the fuel gas in the fuel cell compartment **30** is less than the standard value (No in S3), in S3-1, the upper duct compartment internal gas detector **88** detects that the concentration of the fuel gas in the duct section **90** is less than the standard value (No in S3-1), if the vent pipe internal gas detector **10a** detects that the fuel gas inside the vent pipe **10** is equal to or greater than the standard value (No in S3-2), the control unit **12a** determines that the release valve **72** has failed (S5). The reason why the control unit **12a** makes such a determination is as described below.

(170) The fuel gas detected by the vent pipe internal gas detector **10a** is one of: (A) a fuel gas that has leaked inside the tank compartment **40** and flowed into the vent pipe **10**, (B) a fuel gas that has leaked into the duct compartment **90** and flowed to the vent pipe **10** via the vent pipe communication portion **81**, (C) a fuel gas that has leaked into the fuel cell compartment **30** and then flowed into the vent pipe **10** via the duct compartment **90** and the vent pipe communication portion **81**, or (D) a fuel gas that has flowed to the vent pipe **10** through the fuel gas discharge pipe **71**. Of these, the fuel gas (A) is always detected by the tank compartment internal gas detector **44a**. The fuel gases (B) and (C) are always detected by the upper duct compartment internal gas detector **88**. Therefore, even though the fuel gas is not detected by the tank compartment internal gas detector **44a** and the upper duct compartment internal gas detector **88**, the fact that the vent pipe internal gas detector **10a** detects the fuel gas means that the fuel gas is not the fuel gases (A) to (C) but the fuel gas (D).

(171) Here, for example, in a state in which the control unit **12a** issues an opening command to the release valve **72** and the release valve **72** is opened, in the fuel gas discharge pipe **71**, the fuel gas flows in the fuel gas discharge pipe **71** to the vent pipe **10** via the discharge valve **72**. Therefore, it is natural that the vent pipe internal gas detector **10a** detects the fuel gas. However, in a state in which the control unit **12a** issues a closing command to the release valve **72**, if the vent pipe internal gas detector **10a** detects the fuel gas, the discharge valve **72** does not completely close the flow path of the fuel gas discharge pipe **71**. Therefore, in the case of No in S3-2, the control unit **12a** can determine that the release valve **72** has failed (S5).

(172) In S5, if the control unit **12a** determines that the release valve **72** has failed, the control unit **12a** notifies the outside (S6). The above notification includes a monitor display, output of an alarm sound, transmission of information to an external terminal (for example, transmission of e-mail), and the like.

(173) As described above, the control unit **12a**, based on the detection results of the fuel gas detectors (for example, the tank compartment internal gas detector **44a** and the upper duct compartment internal gas detector **88**) and the vent pipe internal gas detector **10a**, determines whether the release valve **72** has failed (S1, S3-1, S3-2), and if the release valve **72** has failed, notifies the outside (S5, S6).

(174) By notifying the outside if the release valve **72** has failed, it is possible to quickly prompt a

maintenance person to inspect, repair, or replace the release valve **72**.

(175) Particularly, when the vent pipe internal gas detector **10a** detects a fuel gas having a concentration equal to or greater than the standard value in a state in which none of the fuel gas detectors in the tank compartment **40** and in the duct compartment **90** (for example, the tank compartment internal gas detector **44a** and the upper duct compartment internal gas detector **88**) has detected a fuel gas having a concentration equal to or greater than the standard value, and a closing command has been issued to the release valve **72**, the control unit **12** determines that the release valve **72** has failed (S5).

(176) When the vent pipe internal gas detector **10a** detects a fuel gas having a concentration equal to or greater than the standard value even though a fuel gas leakage is not detected in the tank compartment **40** and in the duct compartment **90** and a command to close the release valve **72** has been issued, there is a high possibility that a fuel gas has leaked from the release valve **72** and flows into the vent pipe **10**. Therefore, it is possible to reliably determine whether the release valve **72** has failed by the above determination method.

(177) [7. Other]

(178) In the present embodiment, a fuel gas being gaseous is used as fuel supplied from the fuel tank **41** to the fuel cell **31**, but the fuel is not limited to a gas and may be a liquid. If a liquid fuel is used, when the liquid fuel leaks from a pipe, the leaked liquid fuel vaporizes and is a gas (fuel gas).

(179) In the present embodiment, the configuration in which the fuel cell ship SH has the duct compartment **90** has been described, but the duct compartment **90** may not be installed. For example, if vent pipes corresponding to each of the tank compartment **40** and the fuel cell compartment **30** are provided, the installation of the duct compartment **90** may be omitted (this is because it is not necessary to maintain a flow path from the fuel cell compartment **30** to the vent pipe **10**). In this case, for example, the control for opening and closing the shutoff valves SV and the release valve **72** illustrated in FIGS. **3** to **7** is effective.

(180) However, in the configuration in which the fuel cell ship SH has the duct compartment **90** as in the present embodiment, the air inside each compartment (the tank compartment **40**, the fuel cell compartment **30**, the duct compartment **90**) of the fuel cell ship SH or the fuel gas at the time of leakage can be collected in the vent pipe **10** communicating with the tank compartment **40** and the duct compartment **90** to be discharged to outside the ship. As a result, the fuel cell ship SH can be compactly configured because the number of parts is reduced compared to a configuration in which the vent pipe is separately provided in the fuel cell compartment **30** and dangerous places specified by ship safety regulations is reduced.

(181) Embodiments of the present invention have been described above; however, the scope of the present invention is not limited to these embodiments, and can be extended or modified without departing from the gist of the invention.

#### INDUSTRIAL APPLICABILITY

(182) The present invention can be used, for example, in a fuel cell ship.

#### REFERENCE SIGNS LIST

(183) **1** . . . Hull **6** . . . Propulsion device **10** . . . Vent pipe **10a** . . . Vent pipe internal gas detector **12a** . . . Control unit **30** . . . Fuel cell compartment **31** . . . Fuel cell **32** . . . Fuel gas supply pipe (fuel supply pipe) **33** . . . Fuel cell side shutoff valve **34a** . . . Cell compartment internal gas detector (fuel gas detector) **40** . . . Tank compartment **41** . . . Fuel tank **43** . . . Tank side shutoff valve **44a** . . . Tank compartment internal gas detector (fuel gas detector) **70** . . . Lower duct compartment (duct compartment) **71** . . . Fuel gas discharge pipe (fuel discharge pipe) **72** . . . Release valve **73** . . . Lower duct compartment internal gas detector (fuel gas detector) **80** . . . Upper duct compartment (duct compartment) **88** . . . Upper duct compartment internal gas detector (fuel gas detector) **90** . . . Duct compartment SH . . . Fuel cell ship SV . . . Shutoff valve

## Claims

1. A fuel cell ship comprising: a fuel cell configured to generate electric power by an electrochemical reaction of fuel; a propulsion device configured to generate a propulsive force in a hull by the electric power supplied from the fuel cell; a fuel cell compartment in which the fuel cell is installed; a tank compartment in which a fuel tank configured to store the fuel is installed; and a fuel supply pipe through which the fuel is configured to be supplied from the fuel tank to the fuel cell, wherein: the fuel supply pipe includes two or more shutoff valves, at least one of the two or more shutoff valves is installed in each of the tank compartment and the fuel cell compartment, the fuel cell ship further includes a control unit configured to control opening and closing of the two or more shutoff valves, the tank compartment and the fuel cell compartment are each provided with fuel gas detectors configured to detect a fuel gas being in a gaseous state of the fuel, and based on detection by at least one of the fuel gas detectors that a concentration of the fuel gas is equal to or greater than a predetermined standard value, the control unit is configured to close the shutoff valve in a compartment out of the tank compartment and the fuel cell compartment, in which the fuel gas detector that detects that the concentration is equal to or greater than the predetermined standard value is installed.
2. The fuel cell ship according to claim 1, wherein the control unit is configured to close the shutoff valves in all of the compartments based on detection by at least one of the fuel gas detectors that the concentration of the fuel gas is equal to or greater than the predetermined standard value.
3. The fuel cell ship according to claim 2, wherein: the shutoff valve installed in the tank compartment is a tank side shutoff valve and the shutoff valve installed in the fuel cell compartment is a fuel cell side shutoff valve, the fuel cell ship further comprises: a fuel discharge pipe branched from the fuel supply pipe and provided between the tank side shutoff valve and the fuel cell side shutoff valve; and a release valve installed in the fuel discharge pipe, and the control unit is configured to close the tank side shutoff valve and the fuel cell side shutoff valve and to open the release valve based on detection by at least one of the fuel gas detectors that the concentration of the fuel gas is equal to or greater than the predetermined standard value.
4. The fuel cell ship according to claim 3, wherein the control unit is configured to close the release valve based on a pressure in the fuel supply pipe being greater than or equal to a predetermined specified pressure after the release valve is opened.
5. The fuel cell ship according to claim 3, wherein the control unit is configured to close the release valve after a predetermined specified time elapses after the release valve is opened.
6. The fuel cell ship according claim 3, further comprising: a duct compartment that houses a part of the fuel supply pipe, wherein: the fuel gas detector is further installed in the duct compartment in addition to the tank compartment and the fuel cell compartment, and the control unit is configured to close the tank side shutoff valve and the fuel cell side shutoff valve based on detection by the fuel gas detector in the duct compartment that the concentration of the fuel gas is equal to or greater than the predetermined standard value.
7. The fuel cell ship according to claim 6 further comprising: a vent pipe configured to guide, to outside, the fuel gas discharged from the fuel discharge pipe via the release valve; and a vent pipe internal gas detector configured to detect the fuel gas inside the vent pipe, wherein the control unit is configured to: determine whether the release valve has failed based on detection results of the fuel gas detectors and the vent pipe internal gas detector, and provide a notification.
8. The fuel cell ship according to claim 7, wherein the control unit is configured to: based on detection by the vent pipe internal gas detector that the fuel gas has a concentration equal to or greater than the predetermined standard value in a state in which neither of the fuel gas detectors in the tank compartment and in the duct compartment detect the fuel gas having the concentration



equal to or greater than the predetermined standard value: determine that the release valve has failed, and issue a closing command to the release valve.

---