

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent
Kind Code
Date of Patent
Inventor(s)

12402020
B2
August 26, 2025
Soryal; Joseph

Using unmanned mobile surfaces to reflect a signal from access point equipment to signal receiving equipment

Abstract

The technologies described herein are generally directed to detecting reflective surfaces for use reflecting a signal from access point equipment to destination equipment in advanced networks, e.g., at least a fifth generation (5G) network. For example, a method described herein can include receiving a request, from access point equipment, to establish a communications session between the access point equipment and destination equipment. The method can further include identifying a mobile reflective surface to reflect a communications beam to facilitate a connection between the destination equipment and the access point equipment, resulting in reflected path information corresponding to a reflected path for the communications session. Further, the method can include, in response to the request, communicating to the access point equipment, the reflected path information.

Inventors: Soryal; Joseph (Glendale, NY)
Applicant: AT&T Intellectual Property I, L.P. (Atlanta, GA)
Family ID: 1000008777434
Assignee: AT&T Intellectual Property I, L.P. (Atlanta, GA)
Appl. No.: 17/809445
Filed: June 28, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230422051 A1	Dec. 28, 2023

Publication Classification

Int. Cl.: H04W16/26 (20090101); H04W84/00 (20090101)

U.S. Cl.:

CPC **H04W16/26** (20130101); H04W84/005 (20130101)

Field of Classification Search

CPC: H04W (40/22); H04W (24/02); H04W (40/20); H04W (16/28); H04W (40/00); H04W (64/00); H04W (28/0226); H04W (16/26); H04W (84/005); H04W (84/06); H04W (84/047); H04W (88/04); H04B (17/103)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
11750319	12/2022	Kong	455/1	H04K 3/80
2018/0319495	12/2017	Tu	N/A	H04B 7/18504
2021/0152240	12/2020	Buer	N/A	H04B 7/18517
2023/0134172	12/2022	Sun	370/331	H04L 5/0035
2023/0144085	12/2022	Dutta	342/350	H04B 7/04013
2023/0208479	12/2022	Wang	375/262	H04B 7/0617
2024/0107485	12/2023	Duan	N/A	H04B 7/155
2024/0129023	12/2023	Tashiro	N/A	H04B 7/0695
2024/0154646	12/2023	Wang	N/A	H01Q 1/241
2024/0365152	12/2023	Elshafie	N/A	H04B 17/25

Primary Examiner: Patidar; Sudesh M.

Attorney, Agent or Firm: Guntin & Gust, PLC

Background/Summary

TECHNICAL FIELD

(1) The subject application is related to different approaches to handling communication in networked computer systems and, for example, to using reflective surfaces to improve signal propagation.

BACKGROUND

(2) As demands for fast, high-quality wide area network connections have increased, wireless providers have implemented many new technologies, each having advantages and drawbacks over traditional approaches. New, shorter wavelength frequency bands can provide dramatically faster broadband connections to mobile devices, but because these bands can be blocked easier and have narrower beams, positioning transmitters to offer service to user devices in a variety of different locations has been challenging.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The technology described herein is illustrated by way of example and not limited in the

accompanying figures in which like reference numerals indicate similar elements and in which:

- (2) FIG. 1 is an architecture diagram of an example system that can facilitate detecting reflective surfaces for use reflecting a signal from access point equipment to destination equipment, in accordance with one or more embodiments.
- (3) FIG. 2 is a diagram of a non-limiting example system that can facilitate using unmanned mobile surfaces to reflect an access point signal to destination equipment, in accordance with one or more embodiments.
- (4) FIG. 3 is a diagram of a non-limiting example system that provides additional details regarding different approaches to using unmanned mobile surfaces to reflect an access point signal to destination equipment, in accordance with one or more embodiments.
- (5) FIG. 4 is a diagram of a non-limiting example system that can facilitate using unmanned mobile surfaces to reflect an access point signal to destination equipment, in accordance with one or more embodiments.
- (6) FIG. 5 illustrates an implementation of an example, non-limiting system that can utilize machine learning predictive models to use unmanned mobile surfaces to reflect an access point signal to destination equipment, by approaches including but not limited to, those described herein, in accordance with one or more embodiments.
- (7) FIG. 6 depicts a non-limiting example architecture diagram of an example system that can facilitate using unmanned mobile surfaces to reflect an access point signal to destination equipment, in accordance with one or more embodiments.
- (8) FIG. 7 depicts a non-limiting example architecture diagram of an example system that can facilitate using unmanned mobile surfaces to reflect an access point signal to destination equipment, in accordance with one or more embodiments.
- (9) FIG. 8 illustrates an example method that can facilitate using unmanned mobile surfaces to reflect an access point signal to destination equipment, in accordance with one or more embodiments.
- (10) FIG. 9 illustrates an example method **900** that can facilitate using unmanned mobile surfaces to reflect an access point signal to destination equipment, in accordance with one or more embodiments.
- (11) FIG. 10 depicts a system **1000** that can facilitate using unmanned mobile surfaces to reflect an access point signal to destination equipment, in accordance with one or more embodiments.
- (12) FIG. 11 depicts an example **1100** non-transitory machine-readable medium **1110** that can include executable instructions that, when executed by a processor of a system, facilitate using unmanned mobile surfaces to reflect an access point signal to destination equipment, in accordance with one or more embodiments described above.
- (13) FIG. 12 illustrates an example block diagram of an example mobile handset operable to engage in a system architecture that can facilitate processes described herein, in accordance with one or more embodiments.
- (14) FIG. 13 illustrates an example block diagram of an example computer operable to engage in a system architecture that can facilitate processes described herein, in accordance with one or more embodiments.

DETAILED DESCRIPTION

(15) Generally speaking, one or more embodiments of a system described herein can facilitate using unmanned mobile surfaces to reflect an access point signal to destination equipment. In addition, one or more embodiments described herein can be directed towards a multi-connectivity framework that supports the operation of new radio (NR, sometimes referred to as 5G). As will be understood, one or more embodiments can improve network connectivity, by supporting control and mobility functionality on cellular links (e.g., long term evolution (LTE) or NR). One or more embodiments can provide benefits including, system robustness, reduced overhead, and global resource management.

(16) It should be understood that any of the examples and terms used herein are non-limiting. For instance, while examples are generally directed to non-standalone operation where the NR backhaul links are operating on millimeter wave (mmWave) bands and the control plane links are operating on sub-6 GHz long term evolution (LTE) bands, it should be understood that it is straightforward to extend the technology described herein to scenarios in which the sub-6 GHz anchor carrier providing control plane functionality could also be based on NR. As such, any of the examples herein are non-limiting examples, any of the embodiments, aspects, concepts, structures, functionalities or examples described herein are non-limiting, and the technology may be used in various ways that provide benefits and advantages in radio communications in general.

(17) In some embodiments, understandable variations of the non-limiting terms “signal propagation source equipment” or simply “propagation equipment,” “radio network node” or simply “network node,” “radio network device,” “network device,” and access elements are used herein. These terms may be used interchangeably and refer to any type of network node that can serve user equipment and/or be connected to other network node or network element or any radio node from where user equipment can receive a signal. Examples of radio network node include, but are not limited to, base stations (BS), multi-standard radio (MSR) nodes such as MSR BS, gNode B (gNB), eNode B (eNB), network controllers, radio network controllers (RNC), base station controllers (BSC), relay, donor node controlling relay, base transceiver stations (BTS), access points (AP), transmission points, transmission nodes, remote radio units (RRU) (also termed radio units herein), remote radio heads (RRH), and nodes in distributed antenna system (DAS). Additional types of nodes are also discussed with embodiments below, e.g., donor node equipment and relay node equipment, an example use of these being in a network with an integrated access backhaul network topology.

(18) In some embodiments, understandable variations of the non-limiting term user equipment (UE) are used. This term can refer to any type of wireless device that can communicate with a radio network node in a cellular or mobile communication system. Examples of UEs include, but are not limited to, a target device, device to device (D2D) user equipment, machine type user equipment, user equipment capable of machine to machine (M2M) communication, PDAs, tablets, mobile terminals, smart phones, laptop embedded equipped (LEE), laptop mounted equipment (LME), USB dongles, and other equipment that can have similar connectivity. Example UEs are described further with FIGS. 10 and 11 below. Some embodiments are described in particular for 5G new radio (NR) systems. The embodiments are however applicable to any radio access technology (RAT) or multi-RAT system where the UEs operate using multiple carriers, e.g., LTE. Some embodiments are described in particular for 5G new radio systems. The embodiments are however applicable to any RAT or multi-RAT system where the UEs operate using multiple carriers, e.g., LTE.

(19) One having skill in the relevant art(s), given the disclosure herein, understands that the computer processing systems, computer-implemented methods, equipment (apparatus) and/or computer program products described herein employ hardware and/or software to solve problems that are highly technical in nature (e.g., rapidly and dynamically utilizing mapped reflective surfaces to direct communication beams), that are not abstract and cannot be performed as a set of mental acts by a human. For example, a human, or even a plurality of humans, cannot efficiently manage the complex reflected paths (which generally cannot be performed manually by a human) with the same level of accuracy and/or efficiency as the various embodiments described herein.

(20) Aspects of the subject disclosure will now be described more fully hereinafter with reference to the accompanying drawings in which example components, graphs and selected operations are shown. In the following description, for purposes of explanation, numerous specific details are set forth in order to provide a thorough understanding of the various embodiments. For example, some embodiments described can facilitate detecting reflective surfaces for use reflecting a signal from access point equipment to destination equipment. Different examples that describe these aspects are

included with the description of FIGS. 1-13 below. It should be noted that the subject disclosure may be embodied in many different forms and should not be construed as limited to this example or other examples set forth herein.

(21) FIG. 1 is an architecture diagram of an example system **100** that can facilitate detecting reflective surfaces for use reflecting a signal from access point equipment to destination equipment, in accordance with one or more embodiments. For purposes of brevity, description of like elements and/or processes employed in other embodiments is omitted. As depicted, system **100** includes routing controller equipment **150** communicatively coupled to access point equipment **170** via network **190**. Access point equipment **170** has a direct signal path **146** to destination device **175**, and also, in accordance with one or more embodiments, communicate indirect signal **148** to be reflected off of surface **185** to become reflected signal **149** received by destination device **175**.

(22) With respect to reflected signal **149** (as well as other reflected signals discussed herein), one having skill in the relevant art(s), given the description herein, understands that, as used to describe one or more embodiment herein, a reflected beam can be along a path according to which the beam is relayed by the surface to the user equipment at a first angle corresponding to a second angle at which the second signal strikes the surface. Further to this, it is noted that example signal paths shown in various drawings herewith are approximations meant to be used to illustrate different concepts described herein, and are not meant to show particular reflection angles, distances, and other path characteristics.

(23) Routing controller equipment **150** can include computer-executable components **120**, processor **160**, storage device **162** and memory **165**. Storage device **162** can include surface repository **125**. Computer-executable components **120** can include request receiving component **122**, surface controller component **124**, path providing component **126**, and other components described or suggested by different embodiments described herein, that can improve the operation of system **100**.

(24) Generally speaking, as described herein, access point equipment can be provided useful information regarding surface **185** that can facilitate routing a communications signal via reflection from surface **185** for reasons including routing around connection issues **197**. It is appreciated that connection issues **197** can include one or more conditions that affect the transmission of communication beams (e.g., radio waves, light beams, sound waves) along direct signal path **146** from access point equipment to destination device **175**.

(25) With respect to all signal receiving equipment described herein, it is appreciated that one or more embodiments can be used to provide replacement or additional signals for different types of communication (e.g., for control signals and/or customer communication signals). One having skill in the relevant art(s), given the description herein, understands how one or more embodiments can beneficially provide additional signal streams to destination devices with multiple input capabilities, e.g., as part of multiple input/multiple output (MIMO) capabilities.

(26) One having skill in the relevant art(s), given the descriptions herein, understands that connection issue **197** conditions can include signals congestion, interference, and blockages. In one or more embodiments, connection issues **197** can also broadly include conditions that can detract from signals being communicated to destination device **175** on a priority basis, e.g., when destination device **175** is designated as being used by first responders, additional communication beams can be used to improve one or more aspects of connections therewith. Further to this point, it should be appreciated that one or more embodiments can use reflected signal **149** as a supplement to otherwise unimpeded direct signal path **146**, e.g., providing additional communication signals to destination device **175** as a MIMO device.

(27) Thus, in an example, when quality of a communications session with destination device **175** (e.g., via direct signal path **146**) is identified as being below a threshold level of quality (e.g., resulting in a low-quality signal), one or more embodiments can request additional paths based on reflected signals from routing controller equipment **150** to provide alternative or additional (e.g.,

via MIMO capabilities of destination device **175**) signals to improve the quality of the communications session.

(28) With respect to the uplink communication capabilities of destination device **175**, based on the disclosure herein, it is appreciated that surface repository **125** and surface **185** can also, in one or more embodiments described herein, be used by destination device **175** to communicate uplink signals to access point equipment **170**, e.g., to avoid connection issues **197** or to supplement MIMO communications by utilizing both the reverse of direct signal path **146** and the reverse of reflected signal **149**. It should be noted that, to facilitate the use of surface **185** for reflection of signals from destination device **175** to access point equipment **170** can utilize capabilities of destination device **175** to transmit signals in a particular direction, e.g., these capabilities being now known or developed in the future.

(29) Continuing the discussion of routing controller equipment **150**, it should be appreciated that these components, as well as aspects of the embodiments of the subject disclosure depicted in this figure and various figures disclosed herein, are for illustration only, and as such, the architecture of such embodiments are not limited to the systems, devices, and/or components depicted therein. For example, in some embodiments, routing controller equipment **150** can further comprise various computer and/or computing-based elements described herein with reference to mobile handset **1200** of FIG. **12**, and operating environment **1300** of FIG. **13**. For example, one or more of the different functions of network equipment can be divided among various equipment, including, but not limited to, including equipment at a central node global control located on the core Network, e.g., mobile edge computing (MEC), self-organized networks (SON), or RAN intelligent controller (RIC) network equipment.

(30) In some embodiments, memory **165** can comprise volatile memory (e.g., random access memory (RAM), static RAM (SRAM), dynamic RAM (DRAM), etc.) and/or non-volatile memory (e.g., read only memory (ROM), programmable ROM (PROM), electrically programmable ROM (EPROM), electrically erasable programmable ROM (EEPROM), etc.) that can employ one or more memory architectures. Further examples of memory **165** are described below with reference to system memory **1306** and FIG. **13**. Such examples of memory **165** can be employed to implement any embodiments of the subject disclosure.

(31) According to multiple embodiments, storage device **162** can include, but is not limited to, RAM, ROM, EEPROM, flash memory or other memory technology, solid state drive (SSD) or other solid-state storage technology, Compact Disk Read Only Memory (CD ROM), digital video disk (DVD), blu-ray disk, or other optical disk storage, magnetic cassettes, magnetic tape, magnetic disk storage or other magnetic storage devices, or any other medium which can be used to store the desired information and which can be accessed by the computer.

(32) As described further herein, storage device **162** is provided as an example storage component for storage of surface information (e.g., for surface **185**) including but not limited to, one or more of, the geographic location of surface **185**, the absolute orientation (e.g., heading) of surface **185**, the relative location of surface **185** relative to access point equipment **170** and/or destination device **175**, the relative orientation of surface **185** to access point equipment **170** and/or destination device **175**, characteristics of surface **185** (e.g., reflective capability, times when surface is available, limitations on use of surface **185**), and whether surface **185** is moving or stationary. One having skill in the relevant art(s), given the description herein, understands additional characteristics that can be stored in surface repository **125** that can affect how surface **185** can provide the different functions described herein, e.g., directing reflected signal **149** to destination device **175**. It is also appreciated that storage device **162** is a non-limiting example location for surface repository **125**, with other beneficial locations of part or all of this repository being selected based on implementation specific factors, e.g., storage at access point equipment **170** and/or destination device **175**.

(33) According to multiple embodiments, processor **160** can comprise one or more processors

and/or electronic circuitry that can implement one or more computer and/or machine readable, writable, and/or executable components and/or instructions that can be stored on memory **165**. For example, processor **160** can perform various operations that can be specified by such computer and/or machine readable, writable, and/or executable components and/or instructions including, but not limited to, logic, control, input/output (I/O), arithmetic, and/or the like. In some embodiments, processor **160** can comprise one or more components including, but not limited to, a central processing unit, a multi-core processor, a microprocessor, dual microprocessors, a microcontroller, a system on a chip (SOC), an array processor, a vector processor, and other types of processors. Further examples of processor **160** are described below with reference to processing unit **1304** of FIG. **13**. Such examples of processor **160** can be employed to implement any embodiments of the subject disclosure.

(34) In one or more embodiments, computer-executable components **120** can be used in connection with implementing one or more of the systems, devices, components, and/or computer-implemented operations shown and described in connection with FIG. **1** or other figures disclosed herein. For example, in one or more embodiments, computer-executable components **120** can include instructions that, when executed by processor **160**, can facilitate performance of operations defining request receiving component **122**. As discussed with FIG. **3** below, request receiving component **122** can, in accordance with one or more embodiments, receive a request from access point equipment to establish a communications session between the access point equipment and a user equipment. For example, one or more embodiments of routing controller equipment **150** can receive a request from access point equipment **170** to establish a communications session between the access point equipment and user equipment, e.g., destination device **175**.

(35) Further, in another example, in one or more embodiments, computer-executable components **120** can include instructions that, when executed by processor **160**, can facilitate performance of operations defining surface controller component **124**. As further discussed with FIGS. **3-5** below, surface controller component **124** can, in accordance with one or more embodiments, identify a mobile reflective surface to reflect a communications beam to facilitate a connection between the destination equipment and the access point equipment, resulting in reflected path information corresponding to a reflected path for the communications session.

(36) For example, in different implementations, one or more embodiments can predict that reflective surface **185** will be usable to facilitate a connection between destination device **175** and access point equipment **170**, resulting in reflected path information corresponding to a reflected path for the communications session, e.g., indirect signal **148** reflected off of surface **185** resulting in reflected signal **149** to destination device **175**. FIG. **3** below describes an example surface **185** as a transient reflective surface, e.g., at a particular time, surface **185** can be moving, and can be predicted to be at particular geographic location by one or more embodiments. Additional examples of the transience of some surfaces are also discussed with FIG. **3** below, e.g., some surfaces **185** can be predicted to be reflective to different degrees because of different types of precipitation.

(37) In yet another example, computer-executable components **120** can include instructions that, when executed by processor **160**, can facilitate performance of operations defining path providing component **126**. As discussed herein, in one or more embodiments, path providing component **126** can in response to the request, communicate to the access point equipment, the reflected path information. For example, one or more embodiments can in response to the request from access point equipment **170**, routing controller can receive path information from surface controller component **124**, and provide the reflected path information to access point equipment **170** for use communicating with destination device **175**.

(38) In an example process whereby surface controller component **124** can use signal propagation principles to select surface **185** from surface repository **125**, one or more embodiments can, based on the request from access point equipment **170**, identify respective geographic locations of access point equipment **170** (e.g., based on a location reported by the access point equipment with the

request, or from network records of access point locations) and the user equipment (e.g., determined by location determining technology of destination device **175**, or estimated by access point equipment **170**). One having skill in the relevant art(s), given the description herein, appreciates that signal reflection paths can be estimated based on the signal transmission point (e.g., the location of access point equipment **170**), the location and orientation of a reflective surface (e.g., surface **185**) at the time of the reflection, and the destination of the signal, e.g., destination device **175**.

(39) Additional factors that can affect the propagation of signals described by some embodiments herein include, but are not limited to, the transmission strength of the signal, e.g., varying based on factors including the reflective capability of surface **185** and the distances of the elements the reflected signal path. Other factors include the time for the connection (e.g., some surfaces **185** vary in their availability based on different dates and times, and whether the reflective surface **185** that can facilitate the connection is a moving surface. One having skill in the relevant art(s), given the description herein, appreciates that modern processing power can enable the rapid (e.g., changes made in milliseconds) selection and modification of factors including the surfaces selected for reflection, signals to be aimed, transmission strengths to be selected.

(40) Additional approaches to identifying, selecting, and utilizing transient reflective surfaces that can be used by one or more embodiments are discussed with the descriptions of FIGS. 2-3 below.

(41) FIG. 2 is a diagram of a non-limiting example system **200** that can facilitate using unmanned mobile surfaces to reflect an access point signal to destination equipment, in accordance with one or more embodiments. For purposes of brevity, description of like elements and/or processes employed in other embodiments is omitted.

(42) As depicted, system **200** shows routing controller equipment **150** receiving information from access points **210A-B**, with access point **210A** communicating test signal **246** and communication signal **247** to surfaces **250A-B**, with these surfaces relaying reflective signals **248A** and **246B** to access point **210B** and user equipment **275B**, respectively. As depicted in FIG. 2, communication signal **247** is directed to user equipment **275A**, but surface **250B** results in blocked path **248**. To identify surfaces **250A-B** to access point **210A**, one or more embodiments can utilize beam mapping component **222** of routing controller equipment **150**.

(43) Generally speaking, FIG. 2 depicts, and this section describes, different approaches to generating and updating predictions based on surface repository **125**. Even given these approaches to building a frequently updated repository of reflective surface information, it should be noted that one or more embodiments can use different approaches to discover and use reflective surfaces as needed. It is envisioned that any of the preemptive approaches described below (e.g., test signals **246**) can be used in response to requirements for supplemental connectivity, e.g., based on interference or other connection issues **197**.

(44) In the example depicted in FIG. 2, routing controller equipment is building or updating information in surface repository **125**, e.g., locations, movement profiles, reflective orientations, and characteristics of reflective surfaces **250A-B**. In a first approach, beam mapping component can request that tasks be performed by access point **210A**, e.g., an example task being to transmit one or more test signals **246** in different, known directions. In different embodiments, test signal **246** is generated and aimed at surface **250A** (e.g., a building or other potentially reflective structure) to assess different, potentially useful characteristics of the surface.

(45) In this example, test signal **246** reflects off of surface **250A** and is received by another access point **210B** in the communications network. One having skill in the relevant art(s), given the description herein, appreciates that having the known locations of access points **210A-B** and either an estimated location (e.g., by signal strengths of transmitted and received signals) or a known location (e.g., by maps of buildings, etc.) of surface **250A**, can facilitate the determination or estimation of different characteristics of surface **250A**, e.g., reflective orientation and reflective capacity. This information can be used to update surface repository **125**. Alternative

implementations of this example can be based on the workload of access point **210A** (e.g., with test signal **246** being generated at a time of low utilization).

(46) After the information is collected by access points **210A-B**, routing controller equipment **150** can receive the information, e.g., including a unique code and a direction indication of test signal **246**. Based on this direction indication and a destination location of the signal (e.g., the geographic location of access point **210B**) beam mapping component **222** can map a geographic location of surface **250A** and this information can be stored in surface repository **125**. In an example, beam mapping component **222** can be implemented as a radio access network intelligent component (RANIC), discussed with FIGS. **6-8** below.

(47) In another example, surface **250B** can be detected and analyzed based on a communication signal **247** sent out under a standard communication session by access point **210A**. In the example depicted, communication signal can have been directed toward user equipment **275A**, but the path of this signal is blocked by surface **250B**, e.g., resulting in reflected signal **246B**. Similar to the first example discussed above, reflected signal is detected by an element of the communications network, e.g., user equipment **275B**. In this example, the received signal strength and other signal quality can be measured. In a variation of this signal measurement, user equipment **275B** can utilize a directional antenna to determine the direction from which reflected signal **246B** originated.

(48) FIG. **3** is a diagram of a non-limiting example system **300** that provides additional details regarding different approaches to using unmanned mobile surfaces to reflect an access point signal to destination equipment, in accordance with one or more embodiments. For purposes of brevity, description of like elements and/or processes employed in other embodiments is omitted. FIG. **3** depicts access point **310** communicating with moving user equipment **380** respectively via communications signals **349A-B** reflected from transient reflective surfaces **350A-B** of example unmanned mobile surfaces discussed below.

(49) In one or more embodiments, a system for providing reflective surfaces for reflection of communication signals can include unmanned mobile vehicles, e.g., unmanned aerial vehicle **355** and unmanned terrestrial vehicle **381**.

(50) In some implementations, unmanned aerial vehicle **355** (also termed a “drone” in some of the relevant art(s)) can fly over areas served to provide transient reflective surface **350A**, similar to the reflective surfaces discussed with FIGS. **1** and **2** above. In an example, unmanned mobile vehicles can operate as self-navigating, autonomous devices that can move to different locations based on one or more factors including, but not limited to, predictions (e.g., made by approaches that include the machine learning approaches of FIG. **5**) that supplemental coverage may be required in an area predicted to be congested, an indication that high-priority users (e.g., first responders) may require additional capacity in an area, and indications of actual or predicted types of other connection issues **197**, as discussed with FIG. **1** above.

(51) As described with FIGS. **1** and **2** above, in one or more embodiments, in response to the request from access point equipment to establish a communications session between access point equipment **310** and moving user equipment **380**, in the information retrieval from surface repository **125** can include information describing characteristics of transient reflective surface **350A**, e.g., location, orientation of transient reflective surface **350A**, reflectiveness of transient reflective surface **350A** and other similar criteria that can be used to direct reflected signal **348A**. Based on this location, transient reflective surface **350A** can be used to direct reflected signal **348A** to moving user equipment **380**.

(52) Alternatively or additionally, a circumstance can exist where unmanned aerial vehicle is not in a location where transient reflective surface **350A** can be used for reflection. In this circumstance, surface controller component **124** can instruct unmanned aerial vehicle **355** to move to a more advantageous location for extending coverage, e.g., based on tracking the locations and requirements of network devices, e.g., moving user equipment **380**. In addition, unmanned aerial vehicle **355** can have control over different reflective characteristics of the reflections that can be

provided. For example, in one or more embodiments, transient reflective surface **350A** can be adjusted independent of unmanned aerial vehicle **355**, with this capability facilitating in some circumstances the directing of reflected signal **348A** to be directed at moving user equipment **380** while the user equipment is also moving.

(53) In some implementations where multiple unmanned aerial vehicles **355** can be controlled to work together, these vehicles can be instructed to interwork (cluster) together as a cloud for service delivery, e.g., autonomously and temporarily forming a flying cloud to serve a purpose, task, mission, such as a self-contained and self-managed cluster/cloud, or a data center. In these circumstances different participating unmanned aerial vehicles **355** can be designated as commanding nodes for commanding other unmanned aerial vehicles **355** nearby. In an approach to selecting commanding nodes, these nodes can be selected based on the integrity and security of previous node operation, e.g., from records of operation stored in a blockchain.

(54) In one or more embodiments, commanding nodes can dictate the locations and positions of other nodes so as to address the goals of the current mission, e.g., a game, an emergency, or supplementary coverage in a congested area. In one or more embodiments commanding nodes can dictate the functionality of each node. Because each node can use a software defined platform, the commanding node can designate nodes to have different roles, e.g., an authenticator, a firewall, a mobility manager, a handoff functionality coordinator, public switched telephone network (PSTN) gateway, etc. In other examples of unmanned aerial vehicles **355** working in a coordinated fashion, vehicles can be arranged in formations with a purpose of saving power.

(55) In the examples depicted, unmanned aerial vehicle **355** can include a transient reflective surface **350A** that can be temporarily rendered reflective by reflective precipitation, e.g., rain, snow, hail, sleet, and ice can be reflective. Access point **310** communicates by transmitting communication signals **349A** transient reflective surface **350A**, e.g., based on predictions provided by surface controller component **124**, as discussed above.

(56) As is understood by one having skill in the relevant art(s), given the description herein, beam mapping component **222** can use a variety of different types of information to gather information for predicting the usability of transient reflective surfaces **350A-B** for signal reflection. Information sources can include, as discussed with FIG. 2 above, surface information gathered by network components (e.g., access points **210A-B** and user equipment **275A-B**) over time, e.g., checking locations for the occasional presence of reflective surfaces, e.g., a parking lot, a roadway, train tracks, bodies of water, windows and doors that open and close, etc., can all have moving reflective surfaces that can be detected, tracked, and modeled so as to facilitate predictions.

(57) Additional information that can be used to supplement the collected information include, but are not limited to, maps that include locations that can be determined to potentially have reflective surfaces available (e.g., roads, train tracks, parking lots, buildings, etc.), transportation schedules describing the movement of buses and trains, sports schedules describing when parking lots are predicted to be full.

(58) In addition, one or more embodiments can receive information from the moving surfaces as to their present and future locations, e.g., the bus operator of vehicle **378A** can be offered incentives to provide real time tracking information about the movement of vehicles **378B**, e.g., location, direction, and velocities on the roadway of both mobile user equipment **380** and vehicle **378A**. In addition, the velocities and other movement characteristics of traffic on the roadway generally can be used to predict the locations of the network elements discussed.

(59) It should be noted that, although mobile user equipment **380** and transient reflective surface are depicted as moving (e.g., with vehicle **379**), one having skill in the relevant art(s), given the description herein appreciates that any combination of the three network components can be mobile or stationary, e.g., access point **310** can also be mobile and, in some implementations, receiving surface and destination tracking information from both mobile user equipment **380** and vehicle **379**.

(60) In an additional or alternative embodiment, transient reflective surface **350B** can be a surface positioned on unmanned terrestrial vehicle **381**, e.g., a driverless vehicle that, instead of only being used for ground transportation is instructed to navigate to different locations to facilitate the reflective distribution of communication signals via a reflected signal **348B**, e.g., as discussed above. In one or more embodiments, while certain normal surfaces of different reflective objects can be naturally reflective (e.g., glass and shiny metal that are exposed on unmanned terrestrial vehicle **381**) additional incentives can be offered that can cause specially provided reflective surfaces to be added to vehicles, buildings, and other potentially reflective objects, e.g., reflective paint and other attachable surfaces.

(61) It should be noted that, in additional implementations, approaches similar to those discussed above that can be used to locate moving vehicles for use reflecting signals, can also be used to specifically avoid the use of certain vehicles for reflective purposes. For example, when a schedule, data feed, or other provided data source indicates that an aircraft is predicted to be in a particular space, one or more embodiments can use this information to avoid transmitting signals towards the aircraft. This can be useful for use in areas where reflective surfaces such as building windows are detected and designated for use above the altitude of potential aircraft in the area, e.g., one or more embodiments can distinguish between usable and unusable reflective surfaces.

(62) Another type of transient reflective surface that can be used by one or more embodiments includes surfaces that can temporarily be rendered reflective by reflective precipitation **341**, e.g., by rain or other precipitation adhered to the precipitation-holding material. For example, a weather forecast for, or real time weather observation of weather **342** can indicate that reflective precipitation **341** is predicted to change the reflective characteristics of transient reflective surface **350B**.

(63) FIG. 4 is a diagram of a non-limiting example system **400** that can facilitate using unmanned mobile surfaces to reflect an access point signal to destination equipment, in accordance with one or more embodiments. For purposes of brevity, description of like elements and/or processes employed in other embodiments is omitted. FIG. 4 depicts access point **310** using earth station **415** (e.g., based on connection issues **197**) to reflect communications beam **449** to destination device **474** via reflected communications beam **462** directed to reflective spaceborne vehicle **455**.

(64) One having skill in the relevant art(s), given the description herein, understands that the reflection of signals discussed herein can be used with both radio and optical signals. In the example depicted in FIG. 4 communications beam **449** can be a modulated beam of laser light generated by the earth station **415** based on a signal from access point **310**, e.g., modulated to encode information for a communications session with destination device **474**. Continuing this example, the mobile reflective surface comprises can laser reflecting surface comprised on reflective spaceborne vehicle **455** (e.g., an orbiting satellite) or unmanned aerial vehicle **355** (not shown). Similar to the aerial tracking approach discussed with FIGS. 1-3 above, identifying the mobile reflective surface of reflective spaceborne vehicle **455** can include identifying a spaceborne location of the orbiting satellite based on tracking information describing the spaceborne location.

(65) In one or more implementations of reflective spaceborne vehicle **455**, the surface of the satellite can include multiple independently adjustable reflective surfaces that can be directed towards different directions simultaneously via an on-board controller, e.g., directed by surface controller component **124**.

(66) FIG. 5 illustrates an implementation of an example, non-limiting system **500** that can utilize machine learning predictive models to predict the availability of dynamic and transient reflective surfaces, by employing artificial intelligence and machine learning in combination or individually, by approaches including but not limited to, those described below, in accordance with one or more embodiments. For purposes of brevity, description of like elements and/or processes employed in other embodiments is omitted.

(67) As depicted, system **500** can comprise surface controller component **124**, surface repository

125, training data **595**, and surface prediction model **510**. surface controller component **124**, in this example, can comprise artificial neural network (ANN) **575**, ANN training model **572**, and regression analysis component **590**.

(68) In certain embodiments, different functions of surface controller component **124** can be facilitated based on classifications, correlations, inferences and/or expressions associated with principles of artificial intelligence and machine learning. For example, surface controller component **124** can employ expert systems, fuzzy logic, SVMs, Hidden Markov Models (HMMs), greedy search algorithms, rule-based systems, Bayesian models (e.g., Bayesian networks), ANNs, other non-linear training techniques, data fusion, utility-based analytical systems, systems employing Bayesian models, and ensemble ML algorithms/methods, comprising deep neural networks (DNN), reinforcement learning (RL), Bayesian Statistics, long short-term memory (LSTM) networks. One or more of the above approaches can be specified in capacity prediction model **510** can be used by surface controller component **124** to analyze one or more sources of network usage information discussed above. In an approach that can be used by some embodiments described herein, the impact of different parameters on the overall working of the slice can be modeled, and specific conditions can be identified under which the slice performance can slow down or users can experience performance degradation.

(69) In an example embodiment, surface repository **125** can be used with training model **572** to train (also termed ‘optimize’) ANN **575**, e.g., by historical information collected by routing controller equipment **150**. In additional embodiments, initial and subsequent training of ANN **575** can be based on collected production data stored in surface repository **125** that has been divided into training data **595** in a first data portion and optimizing data (e.g., testing and validation data) in a second portion of data. In different approaches, these portions can be selected based on different approaches that comprise, but are not limited to, a random or pseudorandom selection process.

(70) As would be appreciated by one having skill in the relevant art(s), given the description herein, different aspects of network data records can be used to train ANN **575**. Example values that can be assessed comprise, bandwidth utilization, quality of service metrics such as key performance indicators (KPIs) and key quality indicators (KQI), performance and configuration data collected by UE/eNodeB, along with different scenarios of traffic utilization e.g., peak utilization, minimal utilization, and average utilization of network interfaces. As would be appreciated by one having skill in the relevant art(s), given the description herein, after training by the first portion of data, the second portion of data, analysis results for the data, can be used to validate and update ANN **575**, if needed. It should be noted that this description of employing an ANN is non-limiting, e.g., one or more embodiments can use other types of artificial intelligence and machine learning algorithms that receive input and perform capacity analysis as described above.

(71) In another approach, machine learning (supervised learning) based solutions to analyze the types of data described above to generate predicted need for capacity assigning modifications for network slices. As would be appreciated by one having skill in the relevant art(s), given the description herein, regression analysis component **590** can be used to apply a regression analysis approach to machine learning for embodiments, e.g., this approach being useful in some circumstances for analyzing data to generate different optimal solutions to a problem.

(72) FIGS. **6**, **7**, and **8** respectively depict an example signal diagram **600**, and architecture diagrams **700** and **800** that can facilitate using unmanned mobile surfaces to reflect an access point signal to destination equipment, in accordance with one or more embodiments. For purposes of brevity, description of like elements and/or processes employed in other embodiments is omitted. Signal diagram **600** illustrates a non-limiting example sequence of events that illustrates how existing 5G core virtual network functions (VNFs) and elements of the 5G RAN (e.g., gNB s) can be configured to facilitate handshaking for scanning expanded coverage areas enabled by reflective surfaces.

(73) Illustrative components of signal diagram **600** include UE **610**, radio access network

intelligent controller (RANIC) **612**, access management function (AMF) **614**, session management function (SMF) **616**, user plane function (UPF) **618**, policy control function (PCF) **620**, unified data management (UDM) **622**, and data network (DN) **624**. Non-limiting architecture diagram **700** of FIG. **7** includes some of the above noted components of FIG. **6**, as well as network slice selection function (NSSF) **712**, authentication server function (AUSF) **714**, gNB **792**, and application function (AF) **716**. Non-limiting architecture diagram **800** of FIG. **8** includes some of the above noted components of FIGS. **6** and **7**, as well as network exposure function (NEF) **812**, and network repository function (NRF) **814**.

(74) At **642**, a protocol data unit (PDU) session establishment request is communicated from UE **610** to SMF **616** via AN **612** and AMF **614**. At **644**, a get subscription data message is relayed from SMF **616** to UDM **622**, via UPF **618** and PCF **620**. At **646**, a get policy rules message is communicated from SMF **616** to PCF **620**, via UPF **618**. At **648**, SMF **616** establishes with UPF **618**, a session for the user plane.

(75) At **650**, based on a priority for the communication to UE **610**, SMF **616** can request radio resources from RANIC **612** via AMF **614**, e.g., additional resources can be dedicated for RANIC **612** to locate useful reflective surfaces for the connection. In one or more embodiments, resources allocated to RANIC **612** can be adjusted based on different system requirements, e.g., additional resources can be allocated to increase the frequency with which discoveries of useful reflective surfaces occur. One having skill in the relevant art(s), given the description herein appreciates different types of applications that can require improved performance, e.g., applications with holographic communications, e-gaming, tele-health applications for live diagnostics, etc.

(76) As depicted in FIG. **8**, earth station **810** can coordinate with AMF **614** for a specific call session, e.g., to minimize the signal transmitted and received for a certain user equipment. This interfacing with AMF **614** by earth station **810** can facilitate coordination between different reflective aerial vehicles **802** so as to reduce the repetition of processes, e.g., if a mobile user is authenticated in one cloud formation and moves to another cloud formation coverage, then full authentication again is not required because the two formations can communicate to reduce processes.

(77) At **652**, radio resources can be setup by communication between UE **610** and RANIC **612**. At **654**, RANIC **612** responds to the **650** request, e.g., an example response being a notification to core network resources regarding reflective surfaces are identified and can be potentially can be used during the call, even in a situation where UE **610** and/or reflective surface **250** are mobile. At **656**, SMF **616** updates UPF **618** to setup a tunnel to RANIC **612**. At **658**, a user session can be established between UE **610** and UPF **618** via AN **612**, AMF **614**, SMF **616**, and UPF **618**.

(78) In an example implementation, a user application can be installed on UE **610** to monitor the applications of UE **610** and, based on the workload and QoS and reliability requirements, the user application can notify a backend server to use UPF **618** to command RANIC **612** to dedicate additional system resources to finding reflective surfaces for better signal coverage. In a variation of this example, the user application can also monitor the communications of UE **610** for excessive packet loss or delay and can trigger the above noted resource allocations based on these conditions.

(79) In one or more embodiments, preemptive activity can be performed to facilitate potentially required supplementation of communications signals by reflective signal bandwidth, e.g., utilizing a reachability management module of AMF **614** to track the position of UE **610** in relation to known and potentially useful reflective surfaces if UE **610** requires additional resources. Based on this tracking, AMF **614** can provide additional feedback to RANIC **612** regarding locations where resources available for the supplementation of surface repository **125** can be utilized. Further to this end, in one or more embodiments, a security context management module of AMF **614** can conserve RANIC **612** resources by authenticating the service level allocated to UE **610**, e.g., whether UE **610** has a higher priority designation, such as for public safety customers.

(80) FIG. **9** illustrates an example method **900** that can facilitate using unmanned mobile surfaces

to reflect an access point signal to destination equipment, in accordance with one or more embodiments. For purposes of brevity, description of like elements and/or processes employed in other embodiments is omitted.

(81) At **902**, method **900** can include receiving a request, from access point equipment, to establish a communications session between the access point equipment and destination equipment. At **904**, method **900** can include identifying a mobile reflective surface to reflect a communications beam to facilitate a connection between the destination equipment and the access point equipment, resulting in reflected path information corresponding to a reflected path for the communications session. At **906**, method **900** can include communicating to the access point equipment, the reflected path information.

(82) FIG. **10** depicts a system **1000** that can facilitate using unmanned mobile surfaces to reflect an access point signal to destination equipment, in accordance with one or more embodiments. For purposes of brevity, description of like elements and/or processes employed in other embodiments is omitted. As depicted, system **1000** can include request receiving component **122**, surface controller component **124**, path providing component **126**, and other components described or suggested by different embodiments described herein, that can improve the operation of system **1000**.

(83) In a non-limiting example, component **1002** can include the functions of request receiving component **122**, supported by the other layers of system **1000**. For example, component **1002** can receive a request, from access point equipment, to establish a communications session between the access point equipment and destination equipment. In this and other examples, component **1004** can include the functions of surface controller component **124**, supported by the other layers of system **1000**. Continuing this example, in one or more embodiments, component **1004** can identify a mobile reflective surface to reflect a communications beam to facilitate a connection between the destination equipment and the access point equipment, resulting in reflected path information corresponding to a reflected path for the communications session. Continuing this example, component **1006** can include the functions of path providing component **126**, supported by the other layers of system **1000**. For example, component **1006** can in response to the request, communicate to the access point equipment, the reflected path information.

(84) FIG. **11** depicts an example **1100** non-transitory machine-readable medium **1110** that can include executable instructions that, when executed by a processor of a system, facilitate using unmanned mobile surfaces to reflect an access point signal to destination equipment, in accordance with one or more embodiments described above. For purposes of brevity, description of like elements and/or processes employed in other embodiments is omitted. As depicted, non-transitory machine-readable medium **1110** includes executable instructions that can facilitate performance of operations **1102-1106**.

(85) In one or more embodiments, the operations can include operation **1102** that can receive a request, from access point equipment, to establish a communications session between the access point equipment and destination equipment. Operations can further include operation **1104**, that can identify a mobile reflective surface to reflect a communications beam to facilitate a connection between the destination equipment and the access point equipment, resulting in reflected path information corresponding to a reflected path for the communications session. In one or more embodiments, the operations can further include operation **1106** that can, in one or more embodiments, in response to the request, communicate to the access point equipment, the reflected path information.

(86) FIG. **12** illustrates an example block diagram of an example mobile handset **1200** operable to engage in a system architecture that facilitates wireless communications according to one or more embodiments described herein. Although a mobile handset is illustrated herein, it will be understood that other devices can be a mobile device, and that the mobile handset is merely illustrated to provide context for the embodiments of the various embodiments described herein.

The following discussion is intended to provide a brief, general description of an example of a suitable environment in which the various embodiments can be implemented. While the description includes a general context of computer-executable instructions embodied on a machine-readable storage medium, those skilled in the art will recognize that the embodiments also can be implemented in combination with other program modules and/or as a combination of hardware and software.

(87) Generally, applications (e.g., program modules) can include routines, programs, components, data structures, etc., that perform particular tasks or implement particular abstract data types. Moreover, those skilled in the art will appreciate that the methods described herein can be practiced with other system configurations, including single-processor or multiprocessor systems, minicomputers, mainframe computers, as well as personal computers, hand-held computing devices, microprocessor-based or programmable consumer electronics, and the like, each of which can be operatively coupled to one or more associated devices

(88) A computing device can typically include a variety of machine-readable media. Machine-readable media can be any available media that can be accessed by the computer and includes both volatile and non-volatile media, removable and non-removable media. By way of example and not limitation, computer-readable media can comprise computer storage media and communication media. Computer storage media can include volatile and/or non-volatile media, removable and/or non-removable media implemented in any method or technology for storage of information, such as computer-readable instructions, data structures, program modules, or other data. Computer storage media can include, but is not limited to, RAM, ROM, EEPROM, flash memory or other memory technology, solid state drive (SSD) or other solid-state storage technology, Compact Disk Read Only Memory (CD ROM), digital video disk (DVD), Blu-ray disk, or other optical disk storage, magnetic cassettes, magnetic tape, magnetic disk storage or other magnetic storage devices, or any other medium which can be used to store the desired information and which can be accessed by the computer. In this regard, the terms “tangible” or “non-transitory” herein as applied to storage, memory or computer-readable media, are to be understood to exclude only propagating transitory signals per se as modifiers and do not relinquish rights to all standard storage, memory or computer-readable media that are not only propagating transitory signals per se.

(89) Communication media typically embodies computer-readable instructions, data structures, program modules, or other data in a modulated data signal such as a carrier wave or other transport mechanism, and includes any information delivery media. The term “modulated data signal” means a signal that has one or more of its characteristics set or changed in such a manner as to encode information in the signal. By way of example, and not limitation, communication media includes wired media such as a wired network or direct-wired connection, and wireless media such as acoustic, RF, infrared and other wireless media. Combinations of the any of the above should also be included within the scope of computer-readable media

(90) The handset includes a processor **1202** for controlling and processing all onboard operations and functions. A memory **1204** interfaces to the processor **1202** for storage of data and one or more applications **1206** (e.g., a video player software, user feedback component software, etc.). Other applications can include voice recognition of predetermined voice commands that facilitate initiation of the user feedback signals. The applications **1206** can be stored in the memory **1204** and/or in a firmware **1208**, and executed by the processor **1202** from either or both the memory **1204** or/and the firmware **1208**. The firmware **1208** can also store startup code for execution in initializing the handset **1200**. A communications component **1210** interfaces to the processor **1202** to facilitate wired/wireless communication with external systems, e.g., cellular networks, VoIP networks, and so on. Here, the communications component **1210** can also include a suitable cellular transceiver **1211** (e.g., a GSM transceiver) and/or an unlicensed transceiver **1213** (e.g., Wi-Fi, WiMax) for corresponding signal communications. The handset **1200** can be a device such as a cellular telephone, a PDA with mobile communications capabilities, and messaging-centric

devices. The communications component **1210** also facilitates communications reception from terrestrial radio networks (e.g., broadcast), digital satellite radio networks, and Internet-based radio services networks

(91) The handset **1200** includes a display **1212** for displaying text, images, video, telephony functions (e.g., a Caller ID function), setup functions, and for user input. For example, the display **1212** can also be referred to as a “screen” that can accommodate the presentation of multimedia content (e.g., music metadata, messages, wallpaper, graphics, etc.). The display **1212** can also display videos and can facilitate the generation, editing and sharing of video quotes. A serial I/O interface **1214** is provided in communication with the processor **1202** to facilitate wired and/or wireless serial communications (e.g., USB, and/or IEEE 1294) through a hardwire connection, and other serial input devices (e.g., a keyboard, keypad, and mouse). This supports updating and troubleshooting the handset **1200**, for example. Audio capabilities are provided with an audio I/O component **1216**, which can include a speaker for the output of audio signals related to, for example, indication that the user pressed the proper key or key combination to initiate the user feedback signal. The audio I/O component **1216** also facilitates the input of audio signals through a microphone to record data and/or telephony voice data, and for inputting voice signals for telephone conversations.

(92) The handset **1200** can include a slot interface **1218** for accommodating a SIC (Subscriber Identity Component) in the form factor of a card SIM or universal SIM **1220**, and interfacing the SIM card **1220** with the processor **1202**. However, it is to be appreciated that the SIM card **1220** can be manufactured into the handset **1200**, and updated by downloading data and software.

(93) The handset **1200** can process IP data traffic through the communications component **1210** to accommodate IP traffic from an IP network such as, for example, the Internet, a corporate intranet, a home network, a person area network, etc., through an ISP or broadband cable provider. Thus, VoIP traffic can be utilized by the handset **1200** and IP-based multimedia content can be received in either an encoded or a decoded format.

(94) A video processing component **1222** (e.g., a camera) can be provided for decoding encoded multimedia content. The video processing component **1222** can aid in facilitating the generation, editing, and sharing of video quotes. The handset **1200** also includes a power source **1224** in the form of batteries and/or an AC power subsystem, which power source **1224** can interface to an external power system or charging equipment (not shown) by a power I/O component **1226**.

(95) The handset **1200** can also include a video component **1230** for processing video content received and, for recording and transmitting video content. For example, the video component **1230** can facilitate the generation, editing and sharing of video quotes. A location tracking component **1232** facilitates geographically locating the handset **1200**. As described hereinabove, this can occur when the user initiates the feedback signal automatically or manually. A user input component **1234** facilitates the user initiating the quality feedback signal. The user input component **1234** can also facilitate the generation, editing and sharing of video quotes. The user input component **1234** can include such conventional input device technologies such as a keypad, keyboard, mouse, stylus pen, and/or touch screen, for example.

(96) Referring again to the applications **1206**, a hysteresis component **1236** facilitates the analysis and processing of hysteresis data, which is utilized to determine when to associate with the access point. A software trigger component **1238** can be provided that facilitates triggering of the hysteresis component **1236** when the Wi-Fi transceiver **1213** detects the beacon of the access point. A SIP client **1240** enables the handset **1200** to support SIP protocols and register the subscriber with the SIP registrar server. The applications **1206** can also include a client **1242** that provides at least the capability of discovery, play and store of multimedia content, for example, music.

(97) The handset **1200**, as indicated above related to the communications component **1210**, includes an indoor network radio transceiver **1213** (e.g., Wi-Fi transceiver). This function supports the indoor radio link, such as IEEE 802.11, for the dual-mode GSM handset **1200**. The handset

1200 can accommodate at least satellite radio services through a handset that can combine wireless voice and digital radio chipsets into a single handheld device.

(98) Network **190** can employ various cellular systems, technologies, and modulation schemes to facilitate wireless radio communications between devices. While example embodiments include use of 5G NR systems, one or more embodiments discussed herein can be applicable to any RAT or multi-RAT system, including where user equipment operate using multiple carriers, e.g., LTE FDD/TDD, GSM/GERAN, CDMA2000, etc. For example, wireless communication system **200** can operate in accordance with global system for mobile communications (GSM), universal mobile telecommunications service (UMTS), long term evolution (LTE), LTE frequency division duplexing (LTE FDD, LTE time division duplexing (TDD), high speed packet access (HSPA), code division multiple access (CDMA), wideband CDMA (WCDMA), CDMA2000, time division multiple access (TDMA), frequency division multiple access (FDMA), multi-carrier code division multiple access (MC-CDMA), single-carrier code division multiple access (SC-CDMA), single-carrier FDMA (SC-FDMA), orthogonal frequency division multiplexing (OFDM), discrete Fourier transform spread OFDM (DFT-spread OFDM) single carrier FDMA (SC-FDMA), Filter bank based multi-carrier (FBMC), zero tail DFT-spread-OFDM (ZT DFT-s-OFDM), generalized frequency division multiplexing (GFDM), fixed mobile convergence (FMC), universal fixed mobile convergence (UFMC), unique word OFDM (UW-OFDM), unique word DFT-spread OFDM (UW DFT-Spread-OFDM), cyclic prefix OFDM CP-OFDM, resource-block-filtered OFDM, Wi Fi, WLAN, WiMax, and the like. However, various features and functionalities of system **100** are particularly described wherein the devices of system **100** are configured to communicate wireless signals using one or more multi carrier modulation schemes, wherein data symbols can be transmitted simultaneously over multiple frequency subcarriers (e.g., OFDM, CP-OFDM, DFT-spread OFMD, UFMC, FMBC, etc.). The embodiments are applicable to single carrier as well as to multicarrier (MC) or carrier aggregation (CA) operation of the user equipment. The term carrier aggregation (CA) is also called (e.g., interchangeably called) “multi-carrier system”, “multi-cell operation”, “multi-carrier operation”, “multi-carrier” transmission and/or reception. Note that some embodiments are also applicable for Multi RAB (radio bearers) on some carriers (that is data plus speech is simultaneously scheduled).

(99) Various embodiments described herein can be configured to provide and employ wireless networking features and functionalities. With 5G networks that may use waveforms that split the bandwidth into several sub bands, different types of services can be accommodated in different sub bands with the most suitable waveform and numerology, leading to improved spectrum utilization for 5G networks. Notwithstanding, in the mmWave spectrum, the millimeter waves have shorter wavelengths relative to other communications waves, whereby mmWave signals can experience severe path loss, penetration loss, and fading. However, the shorter wavelength at mmWave frequencies also allows more antennas to be packed in the same physical dimension, which allows for large-scale spatial multiplexing and highly directional beamforming.

(100) FIG. **13** provides additional context for various embodiments described herein, intended to provide a brief, general description of a suitable operating environment **1300** in which the various embodiments of the embodiment described herein can be implemented. While the embodiments have been described above in the general context of computer-executable instructions that can run on one or more computers, those skilled in the art will recognize that the embodiments can be also implemented in combination with other program modules and/or as a combination of hardware and software.

(101) Generally, program modules include routines, programs, components, data structures, etc., that perform particular tasks or implement particular abstract data types. Moreover, those skilled in the art will appreciate that the various methods can be practiced with other computer system configurations, including single-processor or multiprocessor computer systems, minicomputers, mainframe computers, Internet of Things (IoT) devices, distributed computing systems, as well as

personal computers, hand-held computing devices, microprocessor-based or programmable consumer electronics, and the like, each of which can be operatively coupled to one or more associated devices.

(102) The illustrated embodiments of the embodiments herein can be also practiced in distributed computing environments where certain tasks are performed by remote processing devices that are linked through a communications network. In a distributed computing environment, program modules can be located in both local and remote memory storage devices.

(103) Computing devices typically include a variety of media, which can include computer-readable storage media, machine-readable storage media, and/or communications media, which two terms are used herein differently from one another as follows. Computer-readable storage media or machine-readable storage media can be any available storage media that can be accessed by the computer and includes both volatile and nonvolatile media, removable and non-removable media. By way of example, and not limitation, computer-readable storage media or machine-readable storage media can be implemented in connection with any method or technology for storage of information such as computer-readable or machine-readable instructions, program modules, structured data or unstructured data.

(104) Computer-readable storage media can include, but are not limited to, random access memory (RAM), read only memory (ROM), electrically erasable programmable read only memory (EEPROM), flash memory or other memory technology, compact disk read only memory (CD-ROM), digital versatile disk (DVD), Blu-ray disc (BD) or other optical disk storage, magnetic cassettes, magnetic tape, magnetic disk storage or other magnetic storage devices, solid state drives or other solid state storage devices, or other tangible and/or non-transitory media which can be used to store desired information. In this regard, the terms “tangible” or “non-transitory” herein as applied to storage, memory or computer-readable media, are to be understood to exclude only propagating transitory signals per se as modifiers and do not relinquish rights to all standard storage, memory or computer-readable media that are not only propagating transitory signals per se.

(105) Computer-readable storage media can be accessed by one or more local or remote computing devices, e.g., via access requests, queries or other data retrieval protocols, for a variety of operations with respect to the information stored by the medium.

(106) Communications media typically embody computer-readable instructions, data structures, program modules or other structured or unstructured data in a data signal such as a modulated data signal, e.g., a carrier wave or other transport mechanism, and includes any information delivery or transport media. The term “modulated data signal” or signals refers to a signal that has one or more of its characteristics set or changed in such a manner as to encode information in one or more signals. By way of example, and not limitation, communication media include wired media, such as a wired network or direct-wired connection, and wireless media such as acoustic, RF, infrared and other wireless media.

(107) With reference again to FIG. 13, the example operating environment **1300** for implementing various embodiments of the aspects described herein includes a computer **1302**, the computer **1302** including a processing unit **1304**, a system memory **1306** and a system bus **1308**. The system bus **1308** couples system components including, but not limited to, the system memory **1306** to the processing unit **1304**. The processing unit **1304** can be any of various commercially available processors. Dual microprocessors and other multi-processor architectures can also be employed as the processing unit **1304**.

(108) The system bus **1308** can be any of several types of bus structure that can further interconnect to a memory bus (with or without a memory controller), a peripheral bus, and a local bus using any of a variety of commercially available bus architectures. The system memory **1306** includes ROM **1310** and RAM **1312**. A basic input/output system (BIOS) can be stored in a non-volatile memory such as ROM, erasable programmable read only memory (EPROM), EEPROM,

which BIOS contains the basic routines that help to transfer information between elements within the computer **1302**, such as during startup. The RAM **1312** can also include a high-speed RAM such as static RAM for caching data.

(109) The computer **1302** further includes an internal hard disk drive (HDD) **1314** (e.g., EIDE, SATA), one or more external storage devices **1316** (e.g., a magnetic floppy disk drive (FDD) **1316**, a memory stick or flash drive reader, a memory card reader, etc.) and a drive **1320**, e.g., such as a solid-state drive, an optical disk drive, which can read or write from a disk **1322**, such as a CD-ROM disc, a DVD, a BD, etc. Alternatively, where a solid-state drive is involved, disk **1322** would not be included, unless separate. While the internal HDD **1314** is illustrated as located within the computer **1302**, the internal HDD **1314** can also be configured for external use in a suitable chassis (not shown). Additionally, while not shown in environment **1300**, a solid-state drive (SSD) could be used in addition to, or in place of, an HDD **1314**. The HDD **1314**, external storage device(s) **1316** and drive **1320** can be connected to the system bus **1308** by an HDD interface **1324**, an external storage interface **1326** and a drive interface **1328**, respectively. The interface **1324** for external drive implementations can include at least one or both of Universal Serial Bus (USB) and Institute of Electrical and Electronics Engineers (IEEE) 1394 interface technologies. Other external drive connection technologies are within contemplation of the embodiments described herein.

(110) The drives and their associated computer-readable storage media provide nonvolatile storage of data, data structures, computer-executable instructions, and so forth. For the computer **1302**, the drives and storage media accommodate the storage of any data in a suitable digital format. Although the description of computer-readable storage media above refers to respective types of storage devices, it should be appreciated by those skilled in the art that other types of storage media which are readable by a computer, whether presently existing or developed in the future, could also be used in the example operating environment, and further, that any such storage media can contain computer-executable instructions for performing the methods described herein.

(111) A number of program modules can be stored in the drives and RAM **1312**, including an operating system **1330**, one or more application programs **1332**, other program modules **1334** and program data **1336**. All or portions of the operating system, applications, modules, and/or data can also be cached in the RAM **1312**. The systems and methods described herein can be implemented utilizing various commercially available operating systems or combinations of operating systems.

(112) Computer **1302** can optionally comprise emulation technologies. For example, a hypervisor (not shown) or other intermediary can emulate a hardware environment for operating system **1330**, and the emulated hardware can optionally be different from the hardware illustrated in FIG. **13**. In such an embodiment, operating system **1330** can comprise one virtual machine (VM) of multiple VMs hosted at computer **1302**. Furthermore, operating system **1330** can provide runtime environments, such as the Java runtime environment or the .NET framework, for applications **1332**. Runtime environments are consistent execution environments that allow applications **1332** to run on any operating system that includes the runtime environment. Similarly, operating system **1330** can support containers, and applications **1332** can be in the form of containers, which are lightweight, standalone, executable packages of software that include, e.g., code, runtime, system tools, system libraries and settings for an application.

(113) Further, computer **1302** can be enable with a security module, such as a trusted processing module (TPM). For instance, with a TPM, boot components hash next in time boot components, and wait for a match of results to secured values, before loading a next boot component. This process can take place at any layer in the code execution stack of computer **1302**, e.g., applied at the application execution level or at the operating system (OS) kernel level, thereby enabling security at any level of code execution.

(114) A user can enter commands and information into the computer **1302** through one or more wired/wireless input devices, e.g., a keyboard **1338**, a touch screen **1340**, and a pointing device, such as a mouse **1342**. Other input devices (not shown) can include a microphone, an infrared (IR)

remote control, a radio frequency (RF) remote control, or other remote control, a joystick, a virtual reality controller and/or virtual reality headset, a game pad, a stylus pen, an image input device, e.g., camera(s), a gesture sensor input device, a vision movement sensor input device, an emotion or facial detection device, a biometric input device, e.g., fingerprint or iris scanner, or the like. These and other input devices are often connected to the processing unit **1304** through an input device interface **1344** that can be coupled to the system bus **1308**, but can be connected by other interfaces, such as a parallel port, an IEEE 1394 serial port, a game port, a USB port, an IR interface, a BLUETOOTH® interface, etc.

(115) A monitor **1346** or other type of display device can be also connected to the system bus **1308** via an interface, such as a video adapter **1348**. In addition to the monitor **1346**, a computer typically includes other peripheral output devices (not shown), such as speakers, printers, etc.

(116) The computer **1302** can operate in a networked environment using logical connections via wired and/or wireless communications to one or more remote computers, such as a remote computer(s) **1350**. The remote computer(s) **1350** can be a workstation, a server computer, a router, a personal computer, portable computer, microprocessor-based entertainment appliance, a peer device or other common network node, and typically includes many or all of the elements described relative to the computer **1302**, although, for purposes of brevity, only a memory/storage device **1352** is illustrated. The logical connections depicted include wired/wireless connectivity to a local area network (LAN) **1354** and/or larger networks, e.g., a wide area network (WAN) **1356**. Such LAN and WAN networking environments are commonplace in offices and companies, and facilitate enterprise-wide computer networks, such as intranets, all of which can connect to a global communications network, e.g., the Internet.

(117) When used in a LAN networking environment, the computer **1302** can be connected to the local network **1354** through a wired and/or wireless communication network interface or adapter **1358**. The adapter **1358** can facilitate wired or wireless communication to the LAN **1354**, which can also include a wireless access point (AP) disposed thereon for communicating with the adapter **1358** in a wireless mode.

(118) When used in a WAN networking environment, the computer **1302** can include a modem **1360** or can be connected to a communications server on the WAN **1356** via other means for establishing communications over the WAN **1356**, such as by way of the Internet. The modem **1360**, which can be internal or external and a wired or wireless device, can be connected to the system bus **1308** via the input device interface **1344**. In a networked environment, program modules depicted relative to the computer **1302** or portions thereof, can be stored in the remote memory/storage device **1352**. It will be appreciated that the network connections shown are example and other means of establishing a communications link between the computers can be used.

(119) When used in either a LAN or WAN networking environment, the computer **1302** can access cloud storage systems or other network-based storage systems in addition to, or in place of, external storage devices **1316** as described above, such as but not limited to a network virtual machine providing one or more aspects of storage or processing of information. Generally, a connection between the computer **1302** and a cloud storage system can be established over a LAN **1354** or WAN **1356** e.g., by the adapter **1358** or modem **1360**, respectively. Upon connecting the computer **1302** to an associated cloud storage system, the external storage interface **1326** can, with the aid of the adapter **1358** and/or modem **1360**, manage storage provided by the cloud storage system as it would other types of external storage. For instance, the external storage interface **1326** can be configured to provide access to cloud storage sources as if those sources were physically connected to the computer **1302**.

(120) The computer **1302** can be operable to communicate with any wireless devices or entities operatively disposed in wireless communication, e.g., a printer, scanner, desktop and/or portable computer, portable data assistant, communications satellite, any piece of equipment or location

associated with a wirelessly detectable tag (e.g., a kiosk, news stand, store shelf, etc.), and telephone. This can include Wireless Fidelity (Wi-Fi) and BLUETOOTH® wireless technologies. Thus, the communication can be a predefined structure as with a conventional network or simply an ad hoc communication between at least two devices.

(121) The above description of illustrated embodiments of the subject disclosure, including what is described in the Abstract, is not intended to be exhaustive or to limit the disclosed embodiments to the precise forms disclosed. While specific embodiments and examples are described herein for illustrative purposes, various modifications are possible that are considered within the scope of such embodiments and examples, as those skilled in the relevant art can recognize.

(122) In this regard, while the disclosed subject matter has been described in connection with various embodiments and corresponding Figures, where applicable, it is to be understood that other similar embodiments can be used or modifications and additions can be made to the described embodiments for performing the same, similar, alternative, or substitute function of the disclosed subject matter without deviating therefrom. Therefore, the disclosed subject matter should not be limited to any single embodiment described herein, but rather should be construed in breadth and scope in accordance with the appended claims below.

(123) Further to the description above, as it employed in the subject specification, the term “processor” can refer to substantially any computing processing unit or device comprising, but not limited to comprising, single-core processors; single-processors with software multithread execution capability; multi-core processors; multi-core processors with software multithread execution capability; multi-core processors with hardware multithread technology; parallel platforms; and parallel platforms with distributed shared memory. Additionally, a processor can refer to an integrated circuit, an application specific integrated circuit (ASIC), a digital signal processor (DSP), a field programmable gate array (FPGA), a programmable logic controller (PLC), a complex programmable logic device (CPLD), a discrete gate or transistor logic, discrete hardware components, or any combination thereof designed to perform the functions described herein. Processors can exploit nano-scale architectures such as, but not limited to, molecular and quantum-dot based transistors, switches and gates, in order to optimize space usage or enhance performance of user equipment. A processor may also be implemented as a combination of computing processing units.

(124) In the subject specification, terms such as “store,” “storage,” “data store,” data storage,” “database,” and substantially any other information storage component relevant to operation and functionality of a component, refer to “memory components,” or entities embodied in a “memory” or components comprising the memory. It will be appreciated that the memory components described herein can be either volatile memory or nonvolatile memory, or can include both volatile and nonvolatile memory.

(125) As used in this application, the terms “component,” “system,” “platform,” “layer,” “selector,” “interface,” and the like are intended to refer to a computer-related entity or an entity related to an operational apparatus with one or more specific functionalities, wherein the entity can be either hardware, a combination of hardware and software, software, or software in execution. As an example, a component may be, but is not limited to being, a process running on a processor, a processor, an object, an executable, a thread of execution, a program, and/or a computer. By way of illustration and not limitation, both an application running on a server and the server can be a component. One or more components may reside within a process and/or thread of execution and a component may be localized on one computer and/or distributed between two or more computers. In addition, these components can execute from various computer readable media, device readable storage devices, or machine-readable media having various data structures stored thereon. The components may communicate via local and/or remote processes such as in accordance with a signal having one or more data packets (e.g., data from one component interacting with another component in a local system, distributed system, and/or across a network such as the Internet with

other systems via the signal). As another example, a component can be an apparatus with specific functionality provided by mechanical parts operated by electric or electronic circuitry, which is operated by a software or firmware application executed by a processor, wherein the processor can be internal or external to the apparatus and executes at least a part of the software or firmware application. As yet another example, a component can be an apparatus that provides specific functionality through electronic components without mechanical parts, the electronic components can include a processor therein to execute software or firmware that confers at least in part the functionality of the electronic components.

(126) In addition, the term “or” is intended to mean an inclusive “or” rather than an exclusive “or.” That is, unless specified otherwise, or clear from context, “X employs A or B” is intended to mean any of the natural inclusive permutations. That is, if X employs A; X employs B; or X employs both A and B, then “X employs A or B” is satisfied under any of the foregoing instances. Moreover, articles “a” and “an” as used in the subject specification and annexed drawings should generally be construed to mean “one or more” unless specified otherwise or clear from context to be directed to a singular form.

(127) Additionally, the terms “core-network”, “core”, “core carrier network”, “carrier-side”, or similar terms can refer to components of a telecommunications network that typically provides some or all of aggregation, authentication, call control and switching, charging, service invocation, or gateways. Aggregation can refer to the highest level of aggregation in a service provider network wherein the next level in the hierarchy under the core nodes is the distribution networks and then the edge networks. User equipment do not normally connect directly to the core networks of a large service provider, but can be routed to the core by way of a switch or radio area network.

Authentication can refer to determinations regarding whether the user requesting a service from the telecom network is authorized to do so within this network or not. Call control and switching can refer determinations related to the future course of a call stream across carrier equipment based on the call signal processing. Charging can be related to the collation and processing of charging data generated by various network nodes. Two common types of charging mechanisms found in present day networks can be prepaid charging and postpaid charging. Service invocation can occur based on some explicit action (e.g., call transfer) or implicitly (e.g., call waiting). It is to be noted that service “execution” may or may not be a core network functionality as third-party network/nodes may take part in actual service execution. A gateway can be present in the core network to access other networks. Gateway functionality can be dependent on the type of the interface with another network.

(128) Furthermore, the terms “user,” “subscriber,” “customer,” “consumer,” “prosumer,” “agent,” and the like are employed interchangeably throughout the subject specification, unless context warrants particular distinction(s) among the terms. It should be appreciated that such terms can refer to human entities or automated components (e.g., supported through artificial intelligence, as through a capacity to make inferences based on complex mathematical formalisms), that can provide simulated vision, sound recognition and so forth.

(129) Aspects, features, or advantages of the subject matter can be exploited in substantially any, or any, wired, broadcast, wireless telecommunication, radio technology or network, or combinations thereof. Non-limiting examples of such technologies or networks include Geocast technology; broadcast technologies (e.g., sub-Hz, ELF, VLF, LF, MF, HF, VHF, UHF, SHF, THz broadcasts, etc.); Ethernet; X.25; powerline-type networking (e.g., PowerLine AV Ethernet, etc.); femto-cell technology; Wi-Fi; Worldwide Interoperability for Microwave Access (WiMAX); Enhanced General Packet Radio Service (Enhanced GPRS); Third Generation Partnership Project (3GPP or 3G) Long Term Evolution (LTE); 3GPP Universal Mobile Telecommunications System (UMTS) or 3GPP UMTS; Third Generation Partnership Project 2 (3GPP2) Ultra Mobile Broadband (UMB); High Speed Packet Access (HSPA); High Speed Downlink Packet Access (HSDPA); High Speed Uplink Packet Access (HSUPA); GSM Enhanced Data Rates for GSM Evolution (EDGE) Radio

Access Network (RAN) or GERAN; Terrestrial Radio Access Network (UTRAN); or LTE Advanced.

(130) What has been described above includes examples of systems and methods illustrative of the disclosed subject matter. It is, of course, not possible to describe every combination of components or methods herein. One of ordinary skill in the art may recognize that many further combinations and permutations of the disclosure are possible. Furthermore, to the extent that the terms “includes,” “has,” “possesses,” and the like are used in the detailed description, claims, appendices and drawings such terms are intended to be inclusive in a manner similar to the term “comprising” as “comprising” is interpreted when employed as a transitional word in a claim.

(131) While the various embodiments are susceptible to various modifications and alternative constructions, certain illustrated implementations thereof are shown in the drawings and have been described above in detail. It should be understood, however, that there is no intention to limit the various embodiments to the specific forms disclosed, but on the contrary, the intention is to cover all modifications, alternative constructions, and equivalents falling within the spirit and scope of the various embodiments.

(132) In addition to the various implementations described herein, it is to be understood that other similar implementations can be used, or modifications and additions can be made to the described implementation(s) for performing the same or equivalent function of the corresponding implementation(s) without deviating therefrom. Still further, multiple processing chips or multiple devices can share the performance of one or more functions described herein, and similarly, storage can be affected across a plurality of devices. Accordingly, the embodiments are not to be limited to any single implementation, but rather are to be construed in breadth, spirit and scope in accordance with the appended claims.

Claims

1. A method, comprising: transmitting, by routing controller equipment comprising a processor, a test signal via a first access point equipment, wherein the test signal is directed toward a first mobile reflective surface; receiving, by the routing controller equipment, a reflected version of the test signal via a second access point equipment, wherein the reflected version of the test signal is generated by the test signal interacting with the first mobile reflective surface; determining, by the routing controller equipment, characteristics of the first mobile reflective surface by analyzing the reflected version of the test signal, wherein the characteristics of the first mobile reflective surface include a reflective orientation and a reflective capacity; storing, by the routing controller equipment, the characteristics of the first mobile reflective surface in a surface repository including a plurality of characteristics of a plurality of mobile reflective surfaces; receiving, by the routing controller equipment, a request, from the first access point equipment, to establish a communications session between the first access point equipment and destination equipment; identifying, by the routing controller equipment, the first mobile reflective surface from the plurality of mobile reflective surfaces in the surface repository according to the characteristics of the first mobile reflective surface, wherein the first mobile reflective surface is operable to reflect a communications beam to facilitate a connection between the destination equipment and the first access point equipment, resulting in reflected path information corresponding to a reflected path for the communications session; and in response to the request, communicating, by the routing controller equipment, to the first access point equipment, the reflected path information.
2. The method of claim 1, wherein the first mobile reflective surface is on an unmanned aerial vehicle, and wherein identifying the first mobile reflective surface comprises identifying an airborne location of the unmanned aerial vehicle based on tracking information describing the airborne location.
3. The method of claim 2, further comprising, before receiving the request, based on a condition

associated with coverage by the first access point equipment, communicating, by the routing controller equipment, an instruction directing the unmanned aerial vehicle to move to the airborne location.

4. The method of claim 3, wherein the communications session comprises a supplementary communications session, wherein the condition comprises the condition that a current communications session with the destination equipment is below a threshold level of quality, resulting in a low-quality signal, and wherein the request to establish the supplementary communications session is based on an enhancing of the low-quality signal.

5. The method of claim 2, further comprising, before receiving the request, based on a condition associated with the destination equipment, communicating, by the routing controller equipment, an instruction directing the unmanned aerial vehicle to adjust an angle of the first mobile reflective surface.

6. The method of claim 1, wherein the communications beam comprises a beam of laser light generated by the first access point equipment and modulated to encode information for the communications session, and wherein the first mobile reflective surface comprises a laser reflecting surface.

7. The method of claim 6, wherein the first mobile reflective surface is on an orbiting satellite, and wherein identifying the first mobile reflective surface comprises identifying a spaceborne location of the orbiting satellite based on tracking information describing the spaceborne location.

8. The method of claim 7, wherein the reflected path from the first access point equipment to the destination equipment comprises a path via a satellite ground station.

9. A device, comprising: a processor; and a memory that stores executable instructions that, when executed by a processing system including a processor, facilitate performance of operations, comprising: transmitting a test signal via a first access point equipment, wherein the test signal is directed toward a first mobile reflective surface; receiving a reflected version of the test signal via a second access point equipment, wherein the reflected version of the test signal is generated by the test signal interacting with the first mobile reflective surface; determining characteristics of the first mobile reflective surface by analyzing the reflected version of the test signal, wherein the characteristics of the first mobile reflective surface include a reflective orientation and a reflective capacity; storing the characteristics of the first mobile reflective surface in a surface repository including a plurality of characteristics of a plurality of mobile reflective surfaces; receiving a request, from the first access point equipment, to establish a communications session between the first access point equipment and destination equipment; identifying the first mobile reflective surface from the plurality of mobile reflective surfaces in the surface repository according to the characteristics of the first mobile reflective surface, wherein the first mobile reflective surface is operable to reflect a communications beam to facilitate a connection between the destination equipment and the first access point equipment, resulting in reflected path information corresponding to a reflected path for the communications session; and in response to the request, communicating to the first access point equipment, the reflected path information.

10. The device of claim 9, wherein the first mobile reflective surface is on an unmanned aerial vehicle, and wherein identifying the first mobile reflective surface comprises identifying an airborne location of the unmanned aerial vehicle based on tracking information describing the airborne location.

11. The device of claim 10, wherein the operations further comprise, before receiving the request, based on a condition associated with coverage by the first access point equipment, communicating an instruction directing the unmanned aerial vehicle to move to the airborne location.

12. The device of claim 11, wherein the communications session comprises a supplementary communications session, wherein the condition comprises the condition that a current communications session with the destination equipment is below a threshold level of quality, resulting in a low-quality signal, and wherein the request to establish the supplementary

communications session is based on an enhancing of the low-quality signal.

13. The device of claim 10, wherein the operations further comprise, before receiving the request, based on a condition associated with the destination equipment, communicating an instruction directing the unmanned aerial vehicle to adjust an angle of the first mobile reflective surface.

14. The device of claim 9, wherein the communications beam comprises a beam of laser light generated by the first access point equipment and modulated to encode information for the communications session, and wherein the first mobile reflective surface comprises a laser reflecting surface.

15. The device of claim 14, wherein the first mobile reflective surface is on an orbiting satellite, and wherein identifying the first mobile reflective surface comprises identifying a spaceborne location of the orbiting satellite based on tracking information describing the spaceborne location.

16. The device of claim 15, wherein the reflected path from the first access point equipment to the destination equipment comprises a path via a satellite ground station.

17. A non-transitory machine-readable medium, comprising executable instructions that, when executed by a processing system of a first network device including a processor, facilitate performance of operations, comprising: transmitting a test signal via a first access point equipment, wherein the test signal is directed toward a first mobile reflective surface; receiving a reflected version of the test signal via a second access point equipment, wherein the reflected version of the test signal is generated by the test signal interacting with the first mobile reflective surface; determining characteristics of the first mobile reflective surface by analyzing the reflected version of the test signal, wherein the characteristics of the first mobile reflective surface include a reflective orientation and a reflective capacity; storing the characteristics of the first mobile reflective surface in a surface repository including a plurality of characteristics of a plurality of mobile reflective surfaces; receiving a request, from the first access point equipment, to establish a communications session between the first access point equipment and destination equipment; identifying the first mobile reflective surface from the plurality of mobile reflective surfaces in the surface repository according to the characteristics of the first mobile reflective surface, wherein the first mobile reflective surface is operable to reflect a communications beam to facilitate a connection between the destination equipment and the first access point equipment, resulting in reflected path information corresponding to a reflected path for the communications session; and in response to the request, communicating to the first access point equipment, the reflected path information.

18. The non-transitory machine-readable medium of claim 17, wherein the first mobile reflective surface is on an unmanned aerial vehicle, and wherein identifying the first mobile reflective surface comprises identifying an airborne location of the unmanned aerial vehicle based on tracking information describing the airborne location.

19. The non-transitory machine-readable medium of claim 18, wherein the operations further comprise, before receiving the request, based on a condition associated with coverage by the first access point equipment, communicating an instruction directing the unmanned aerial vehicle to move to the airborne location.

20. The non-transitory machine-readable medium of claim 17, wherein the communications beam comprises a beam of laser light generated by the first access point equipment and modulated to encode information for the communications session, and wherein the first mobile reflective surface comprises a laser reflecting surface.
