

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12402049
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Damnjanovic; Jelena et al.

Techniques for providing cell mobility information during handover

Abstract

Methods, systems, and devices for wireless communications are described to support inclusion of layer 1 (L1) or layer 2 (L2) cell mobility information within a layer 3 (L3) handover command. A base station may transmit, to the UE, signaling indicating for the UE to perform a measurement on a first set of cells. The UE may perform the measurement on the first set of cells and may transmit, to the base station, an indication associated with the measurement on the first set of cells. In response to the indication, the base station may transmit, to the UE, an L3 handover command, where the L3 handover command may include L1 or L2 cell mobility information, such as an indication of a second set of cells that the UE is to use for L1 or L2 cell mobility after completing the L3 handover command.

Inventors: Damnjanovic; Jelena (Del Mar, CA), Luo; Tao (San Diego, CA), Damnjanovic; Aleksandar (Del Mar, CA)

Applicant: QUALCOMM Incorporated (San Diego, CA)

Family ID: 1000008777418

Assignee: QUALCOMM Incorporated (San Diego, CA)

Appl. No.: 17/528773

Filed: November 17, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20230156541 A1	May. 18, 2023

Publication Classification

Int. Cl.: H04W36/00 (20090101); H04W36/08 (20090101)

U.S. Cl.:

CPC **H04W36/0085** (20180801); **H04W36/08** (20130101);

Field of Classification Search

CPC: H04W (74/0833); H04W (36/0055); H04W (56/0015); H04W (36/06); H04W (36/0085);
H04L (5/0048); H04L (5/001); H04L (69/323); H04L (69/324); H04B (7/022); H04B
(7/0695); H04B (7/0617)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2008/0013474	12/2007	Nagarajan	370/321	H04L 12/4633
2013/0223409	12/2012	Jung	370/331	H04W 36/0072
2015/0031366	12/2014	Lee	455/436	H04W 24/10
2018/0176710	12/2017	Jang	N/A	H04W 4/70
2018/0199328	12/2017	Sang	N/A	H04L 5/0048
2018/0279182	12/2017	Sang	N/A	H04W 74/0833
2021/0329515	12/2020	Sharma et al.	N/A	N/A
2022/0182894	12/2021	Damnjanovic et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
WO-2022091072	12/2021	WO	N/A

OTHER PUBLICATIONS

International Search Report and Written Opinion—PCT/US2022/078489—ISA/EPO—Feb. 14, 2023. cited by applicant

Primary Examiner: Liu; Jung

Attorney, Agent or Firm: Holland & Hart LLP / QUALCOMM Incorporated

Background/Summary

INTRODUCTION

(1) The following relates to wireless communications, including techniques for cell mobility management.

(2) Wireless communications systems are widely deployed to provide various types of communication content such as voice, video, packet data, messaging, broadcast, and so on. These systems may be capable of supporting communication with multiple users by sharing the available

system resources (e.g., time, frequency, and power). Examples of such multiple-access systems include fourth generation (4G) systems such as Long Term Evolution (LTE) systems, LTE-Advanced (LTE-A) systems, or LTE-A Pro systems, and fifth generation (5G) systems which may be referred to as New Radio (NR) systems. These systems may employ technologies such as code division multiple access (CDMA), time division multiple access (TDMA), frequency division multiple access (FDMA), orthogonal FDMA (OFDMA), or discrete Fourier transform spread orthogonal frequency division multiplexing (DFT-S-OFDM). A wireless multiple-access communications system may include one or more base stations or one or more network access nodes, each simultaneously supporting communication for multiple communication devices, which may be otherwise known as user equipment (UE).

SUMMARY

(3) A method for wireless communication at a UE is described. The method may include receiving, from a base station, signaling indicating the UE is to perform a measurement on a first set of cells. The method may further include transmitting, to the base station, a first indication associated with the measurement on the first set of cells. The method may also include and receiving, from the base station and in response to the first indication, a layer 3 (L3) handover command including a second indication of a second set of cells for layer 1 (L1) or layer 2 (L2) cell mobility that the UE is to use after completing the L3 handover command, the L1 or L2 cell mobility within the second set of cells managed using L1 signaling or L2 signaling.

(4) An apparatus for wireless communication at a UE is described. The apparatus may include a processor and memory coupled to the processor. The processor and memory may be configured to receive, from a base station, signaling indicating the UE is to perform a measurement on a first set of cells. The processor and memory may also be configured to transmit, to the base station, a first indication associated with the measurement on the first set of cells. The processor and memory may further be configured to receive, from the base station and in response to the first indication, a L3 handover command including a second indication of a second set of cells for L1 or L2 cell mobility that the UE is to use after completing the L3 handover command, the L1 or L2 cell mobility within the second set of cells managed using L1 signaling or L2 signaling.

(5) Another apparatus for wireless communication at a UE is described. The apparatus may include means for receiving, from a base station, signaling indicating the UE is to perform a measurement on a first set of cells. The apparatus may further include means for transmitting, to the base station, a first indication associated with the measurement on the first set of cells. The apparatus may also include means for receiving, from the base station and in response to the first indication, a L3 handover command including a second indication of a second set of cells for L1 or L2 cell mobility that the UE is to use after completing the L3 handover command, the L1 or L2 cell mobility within the second set of cells managed using L1 signaling or L2 signaling.

(6) A non-transitory computer-readable medium storing code for wireless communication at a UE is described. The code may include instructions executable by a processor to receive, from a base station, signaling indicating the UE is to perform a measurement on a first set of cells. The code may also include instructions executable by the processor to transmit, to the base station, a first indication associated with the measurement on the first set of cells. The code may further include instructions executable by the processor to receive, from the base station and in response to the first indication, a L3 handover command including a second indication of a second set of cells for L1 or L2 cell mobility that the UE is to use after completing the L3 handover command, the L1 or L2 cell mobility within the second set of cells managed using L1 signaling or L2 signaling.

(7) Some examples of the method, apparatuses, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for receiving, via the L3 handover command, a third indication of a communication configuration for the second set of cells.

(8) Some examples of the method, apparatuses, and non-transitory computer-readable medium

described herein may further include operations, features, means, or instructions for receiving, via the L3 handover command, a fourth indication of an activated subset of the second set of cells to be used for communications after completing the L3 handover command.

(9) In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, the L3 handover command may further include a fifth indication of quasi co-location (QCL) information indicative of a set of beams to use on the activated subset of the second set of cells.

(10) Some examples of the method, apparatuses, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for receiving, via the L3 handover command, a sixth indication of a subset of candidate primary cells (PCells) within the second set of cells, where the subset of candidate PCells includes at least one cell configured to be activated as a PCell via L1 signaling or L2 signaling.

(11) Some examples of the method, apparatuses, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for receiving, via the L3 handover command, a seventh indication of signaling to use for L1 measurements performed on the second set of cells for the L1 or L2 cell mobility.

(12) In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, each cell in the second set of cells may be associated with a same central unit (CU) as a target cell for the L3 handover command.

(13) Some examples of the method, apparatuses, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for performing joint beam reporting for the first set of cells, the first set of cells associated with a same base station as a target cell for the L3 handover command and transmitting signaling indicating a result of the measurement on the first set of cells based on performing the joint beam reporting.

(14) Some examples of the method, apparatuses, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for determining that the measurement on the first set of cells satisfies a threshold measurement value and performing a second measurement on a third set of cells associated with a same base station as the first set of cells based on determining that the measurement on the first set of cells satisfies the threshold measurement value.

(15) In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, the measurement on the first set of cells may include a beam measurement associated with L1 signaling and L3 signaling.

(16) Some examples of the method, apparatuses, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for transmitting, to the base station, an eighth indication to use the second set of cells for the L1 or L2 cell mobility, the receiving the L3 handover command including the second indication of the second set of cells based on transmitting the eighth indication to use the second set of cells.

(17) Some examples of the method, apparatuses, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for transmitting, to the base station, a ninth indication of an activated subset of the second set of cells for the L1 or L2 cell mobility, the receiving the L3 handover command including the second indication of the second set of cells based on transmitting the ninth indication of the activated subset of the second set of cells.

(18) A method for wireless communication at a base station is described. The method may include transmitting, to a UE, signaling indicating the UE is to perform a measurement on a first set of cells. The method may also include receiving, from the UE, a first indication associated with the measurement on the first set of cells. The method may further include transmitting, to the UE and in response to the first indication, a L3 handover command including a second indication of a second set of cells for L1 or L2 cell mobility that the UE is to use after completing the L3 handover

command, the L1 or L2 cell mobility within the second set of cells managed using L1 signaling or L2 signaling.

(19) An apparatus for wireless communication at a UE is described. The apparatus may include a processor and memory coupled to the processor. The processor and memory may be configured to transmit, to a UE, signaling indicating the UE is to perform a measurement on a first set of cells. The processor and memory may further be configured to receive, from the UE, a first indication associated with the measurement on the first set of cells. The processor and memory may also be configured to transmit, to the UE and in response to the first indication, a L3 handover command including a second indication of a second set of cells for L1 or L2 cell mobility that the UE is to use after completing the L3 handover command, the L1 or L2 cell mobility within the second set of cells managed using L1 signaling or L2 signaling.

(20) Another apparatus for wireless communication at a base station is described. The apparatus may include means for transmitting, to a UE, signaling indicating the UE is to perform a measurement on a first set of cells. The apparatus may also include means for receiving, from the UE, a first indication associated with the measurement on the first set of cells. The apparatus may further include means for transmitting, to the UE and in response to the first indication, a L3 handover command including a second indication of a second set of cells for L1 or L2 cell mobility that the UE is to use after completing the L3 handover command, the L1 or L2 cell mobility within the second set of cells managed using L1 signaling or L2 signaling.

(21) A non-transitory computer-readable medium storing code for wireless communication at a base station is described. The code may include instructions executable by a processor to transmit, to a UE, signaling indicating the UE is to perform a measurement on a first set of cells. The code may also include instructions executable by the processor to receive, from the UE, a first indication associated with the measurement on the first set of cells. The code may further include instructions executable by the processor to transmit, to the UE and in response to the first indication, a L3 handover command including a second indication of a second set of cells for L1 or L2 cell mobility that the UE is to use after completing the L3 handover command, the L1 or L2 cell mobility within the second set of cells managed using L1 signaling or L2 signaling.

(22) Some examples of the method, apparatuses, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for transmitting, via the L3 handover command, a third indication of a communication configuration for the second set of cells.

(23) Some examples of the method, apparatuses, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for transmitting, via the L3 handover command, a fourth indication of an activated subset of the second set of cells to be used for communications after completing the L3 handover command.

(24) In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, the L3 handover command may include a fifth indication of QCL information indicative of a set of beams to use on the activated subset of the second set of cells.

(25) Some examples of the method, apparatuses, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for transmitting, via the L3 handover command, a sixth indication of a subset of candidate PCells within the second set of cells, the subset of candidate PCells including at least one cell configured to be activated as a PCell via L1 signaling or L2 signaling.

(26) Some examples of the method, apparatuses, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for transmitting, via the L3 handover command, a seventh indication of signaling to use for L1 measurements performed on the second set of cells for the L1 or L2 cell mobility.

(27) In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, each cell in the second set of cells may be associated with a same CU as a target

cell for the L3 handover command.

(28) Some examples of the method, apparatuses, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for receiving signaling indicating a result of the measurement on the first set of cells associated with joint beam reporting for the first set of cells, the first set of cells associated with a same base station as a target cell for the L3 handover command.

(29) Some examples of the method, apparatuses, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for transmitting an indication for the UE to perform a second measurement on a third set of cells associated with a same base station as the first set of cells based on determining that the measurement on the first set of cells satisfies a threshold measurement value.

(30) In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, the measurement on the first set of cells includes a beam measurement associated with L1 signaling and L3 signaling.

(31) Some examples of the method, apparatuses, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for receiving, from the UE, an eighth indication to use the second set of cells for the L1 or L2 cell mobility, the transmitting the L3 handover command including the second indication of the second set of cells based on receiving the eighth indication to use the second set of cells.

(32) Some examples of the method, apparatuses, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for receiving, from the UE, a ninth indication of an activated subset of the second set of cells for the L1 or L2 cell mobility, the transmitting the L3 handover command including the second indication of the second set of cells based on receiving the ninth indication of the activated subset of the second set of cells.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 illustrates an example of a wireless communications system that supports techniques for providing cell mobility information during handover in accordance with one or more aspects of the present disclosure.

(2) FIG. 2 illustrates an example of a wireless communications system that supports techniques for providing cell mobility information during handover in accordance with one or more aspects of the present disclosure.

(3) FIG. 3 illustrates an example of a measurement scheme that supports techniques for providing cell mobility information during handover in accordance with one or more aspects of the present disclosure.

(4) FIG. 4 illustrates an example of a process flow that supports techniques for providing cell mobility information during handover in accordance with one or more aspects of the present disclosure.

(5) FIGS. 5 and 6 show block diagrams of devices that support techniques for providing cell mobility information during handover in accordance with one or more aspects of the present disclosure.

(6) FIG. 7 shows a block diagram of a communications manager that supports techniques for providing cell mobility information during handover in accordance with one or more aspects of the present disclosure.

(7) FIG. 8 shows a diagram of a system including a device that supports techniques for providing cell mobility information during handover in accordance with one or more aspects of the present disclosure.

(8) FIGS. 9 and 10 show block diagrams of devices that support techniques for providing cell mobility information during handover in accordance with one or more aspects of the present disclosure.

(9) FIG. 11 shows a block diagram of a communications manager that supports techniques for providing cell mobility information during handover in accordance with one or more aspects of the present disclosure.

(10) FIG. 12 shows a diagram of a system including a device that supports techniques for providing cell mobility information during handover in accordance with one or more aspects of the present disclosure.

(11) FIGS. 13 through 16 show flowcharts illustrating methods that support techniques for providing cell mobility information during handover in accordance with one or more aspects of the present disclosure.

DETAILED DESCRIPTION

(12) A base station may include multiple cells, of which one or more activated cells (e.g., an activated subset of cells) may be or represent cells used for data and/or control communications with a UE to support uplink and/or downlink communications. As described herein, a cell may refer to a logical communication entity used for communication between a UE and a base station. In some examples, a cell may also refer to a geographic area, or a portion thereof, over which the logical communication entity operates. At least one of the cells associated with the communications may be configured as a primary cell (PCell). A PCell may refer to a cell over which a UE performs an initial connection with the network, or a connection re-establishment with the network, and is the cell with which the UE performs a majority of communications with the network. In some cases (e.g., if the UE is mobile, if network conditions change), communication quality may be increased by changing the PCell to another PCell, or by changing one or more cells of the activated subset. Such techniques may be referred to as cell mobility, cell mobility management, or inter-cell mobility, among other examples.

(13) In some cases, the base station may provide higher-layer signaling (e.g., radio resource control (RRC) signaling, such as L3 signaling) to perform the inter-cell mobility (e.g., switch PCells or change the activated subset of cells, which may include a PCell and one or more other cells). Such signaling may be referred to as a handover, a handover command, an L3 handover, or an L3 handover command, among other examples. In some cases, an L3 handover command may be associated with an increased latency and/or increased delays, for example, in comparison with lower-layer signaling (e.g., L1 signaling, such as physical layer signaling, and L2 signaling, such as medium access control (MAC) signaling, radio link control (RLC) signaling, packet data convergence protocol (PDCP) signaling). In some cases, the base station and the UE may support cell mobility (e.g., switching PCells, changing the activated subset of cells) using L1 or L2 signaling, which may be referred to as L1/L2 inter-cell mobility, L1/L2 mobility, or L1/L2 cell mobility (e.g., L1 or L2 cell mobility), among other examples.

(14) The network (e.g., a base station) may configure a set of cells for L1/L2 cell mobility. The set of cells may include an activated subset of cells, which may represent a set of cells that is ready to be used for data and/or control communications (e.g., data and control transfer in the uplink and/or downlink). Within the set of cells, L1 and/or L2 signaling may be used to perform cell mobility. For example, L1 or L2 signaling may be used to activate and/or deactivate cells within the set of cells (e.g., to remove or add cells to the activated subset), to select communication beams, or to select a new PCell (e.g., within the set of cells). In some cases, the UE may use one or more other UEs that serve as relay UEs to communicate with a cell, which relay UEs may also be activated or deactivated as relay UEs via L1 or L2 signaling.

(15) A PCell (e.g., a target cell) for the UE may be changed using an L3 handover or L3 handover command. In such cases, after performing the handover procedure as indicated in the command, the UE may receive other signaling to update the set of cells used for L1/L2 cell mobility. However,

configuring L1/L2 cell mobility after performing the handover procedure may increase latency (e.g., based on performing new measurements and receiving a new L1/L2 cell mobility configuration based on the measurements). In some cases, the increased latency may result in decreased reliability, for example, in scenarios where a channel may be impaired or blocked relatively quickly, or where handovers may be more frequent (e.g., based on a smaller coverage area). For example, decreased reliability may occur if the handover is completed to a PCell with a lower signal quality than another available cell, if the handover is completed too early (e.g., when the UE is mobile), if signal blockage occurs after handover, or if radio link failure occurs on the new PCell.

(16) The present disclosure provides techniques for including information for L1/L2 cell mobility (e.g., L1/L2 cell mobility information, L1/L2 information, L1/L2 mobility information) within an L3 handover command, which may result in reduced latency and increased reliability. For example, the handover command may include L1/L2 cell mobility information (e.g., an L1/L2 cell mobility configuration), where the L1/L2 cell mobility information may include an indication of a new set of cells for L1/L2 cell mobility and an associated configuration for the new set of cells. The L1/L2 cell mobility information may, in some cases, also include an indication of a new activated subset of cells for L1/L2 cell mobility, a new subset of candidate PCells for L1/L2 cell mobility, or beam information for L1/L2 cell mobility (e.g., beam information for the new PCell, for the activated subset of cells), among other examples. Based on the L1/L2 cell mobility information, the UE may perform L1/L2 cell mobility (e.g., switch active cells, switch PCells) any time after performing the L3 handover command (e.g., rather than waiting for a reconfiguration), such that a PCell may be quickly changed in case of communication problems (e.g., handover is completed early, signal blockage, radio link failure).

(17) The base station may transmit, to the UE, signaling indicating the UE is to perform a measurement on a first set of cells (e.g., in preparation for performing the handover and to determine new L1/L2 mobility information). The measurement may include channel quality measurements, signal quality measurements, beam measurements, reference signal measurements, or any other signal measurement. The first set of cells may represent, for example, one or more sets of cells that may be used by the UE for L1/L2 cell mobility after the handover, as determined by the base station (e.g., based on previous signal measurements and/or reports).

(18) The UE may perform the measurement on the first set of cells and may transmit a first indication, to the base station, associated with the measurement on the first set of cells. The first indication may indicate, for cells in the first set of cells, a result of the measurement, a signal quality, a channel quality, a beam quality, or any other indication associated with the measurement on the first set of cells. In response to the first indication, the base station may transmit, to the UE, an L3 handover command, where the L3 handover command may include a second indication of a second set of cells (e.g., a new set of cells) that the UE is to use for L1/L2 cell mobility (e.g., for managing or changing active cells using L1/L2 signaling) after completing the L3 handover command (e.g., after transferring communications to a new PCell in accordance with the L3 handover command). As described herein, an L3 handover command (e.g., a handover command) may represent L3 signaling indicating for the UE to be transferred to a new PCell that is outside of a current set of cells used for L1/L2 cell mobility.

(19) The second set of cells indicated in the handover command may be included within the first set of cells and may be selected by the base station for use in L1/L2 cell mobility based on the first indication associated with the measurement, as reported by the UE. The L3 handover command may also include other L1/L2 cell mobility information, such as an indication of an activated subset of the second set of cells, an indication of one or more candidate PCells in the second set of cells, or beam information, among other examples.

(20) Aspects of the disclosure are initially described in the context of wireless communications systems. Aspects of the disclosure are further illustrated by and described with reference to a

process flow, apparatus diagrams, system diagrams and flowcharts that relate to techniques for providing cell mobility information during handover.

(21) FIG. 1 illustrates an example of a wireless communications system **100** that supports techniques for providing cell mobility information during handover in accordance with one or more aspects of the present disclosure. The wireless communications system **100** may include one or more base stations **105**, one or more UEs **115**, and a core network **130**. In some examples, the wireless communications system **100** may be a Long Term Evolution (LTE) network, an LTE-Advanced (LTE-A) network, an LTE-A Pro network, or a New Radio (NR) network. In some examples, the wireless communications system **100** may support enhanced broadband communications, ultra-reliable communications, low latency communications, communications with low-cost and low-complexity devices, or any combination thereof.

(22) The base stations **105** may be dispersed throughout a geographic area to form the wireless communications system **100** and may be devices in different forms or having different capabilities. The base stations **105** and the UEs **115** may wirelessly communicate via one or more communication links **125**. Each base station **105** may provide a coverage area **110** over which the UEs **115** and the base station **105** may establish one or more communication links **125**. The coverage area **110** may be an example of a geographic area over which a base station **105** and a UE **115** may support the communication of signals according to one or more radio access technologies.

(23) The UEs **115** may be dispersed throughout a coverage area **110** of the wireless communications system **100**, and each UE **115** may be stationary, or mobile, or both at different times. The UEs **115** may be devices in different forms or having different capabilities. Some example UEs **115** are illustrated in FIG. 1. The UEs **115** described herein may be able to communicate with various types of devices, such as other UEs **115**, the base stations **105**, or network equipment (e.g., core network nodes, relay devices, integrated access and backhaul (IAB) nodes, or other network equipment), as shown in FIG. 1.

(24) The base stations **105** may communicate with the core network **130**, or with one another, or both. For example, the base stations **105** may interface with the core network **130** through one or more backhaul links **120** (e.g., via an S1, N2, N3, or other interface). The base stations **105** may communicate with one another over the backhaul links **120** (e.g., via an X2, Xn, or other interface) either directly (e.g., directly between base stations **105**), or indirectly (e.g., via core network **130**), or both. In some examples, the backhaul links **120** may be or include one or more wireless links.

(25) One or more of the base stations **105** described herein may include or may be referred to by a person having ordinary skill in the art as a base transceiver station, a radio base station, an access point, a radio transceiver, a NodeB, an eNodeB (eNB), a next-generation NodeB or a giga-NodeB (either of which may be referred to as a gNB), a Home NodeB, a Home eNodeB, or other suitable terminology.

(26) A UE **115** may include or may be referred to as a mobile device, a wireless device, a remote device, a handheld device, or a subscriber device, or some other suitable terminology, where the “device” may also be referred to as a unit, a station, a terminal, or a client, among other examples. A UE **115** may also include or may be referred to as a personal electronic device such as a cellular phone, a personal digital assistant (PDA), a tablet computer, a laptop computer, or a personal computer. In some examples, a UE **115** may include or be referred to as a wireless local loop (WLL) station, an Internet of Things (IoT) device, an Internet of Everything (IoE) device, or a machine type communications (MTC) device, among other examples, which may be implemented in various objects such as appliances, or vehicles, meters, among other examples.

(27) The UEs **115** described herein may be able to communicate with various types of devices, such as other UEs **115** that may sometimes act as relays as well as the base stations **105** and the network equipment including macro eNBs or gNBs, small cell eNBs or gNBs, or relay base stations, among other examples, as shown in FIG. 1.

(28) The UEs **115** and the base stations **105** may wirelessly communicate with one another via one

or more communication links **125** over one or more carriers. The term “carrier” may refer to a set of radio frequency spectrum resources having a defined physical layer structure for supporting the communication links **125**. For example, a carrier used for a communication link **125** may include a portion of a radio frequency spectrum band (e.g., a bandwidth part (BWP)) that is operated according to one or more physical layer channels for a given radio access technology (e.g., LTE, LTE-A, LTE-A Pro, NR). Each physical layer channel may carry acquisition signaling (e.g., synchronization signals, system information), control signaling that coordinates operation for the carrier, user data, or other signaling. The wireless communications system **100** may support communication with a UE **115** using carrier aggregation or multi-carrier operation. A UE **115** may be configured with multiple downlink component carriers and one or more uplink component carriers according to a carrier aggregation configuration. Carrier aggregation may be used with both frequency division duplexing (FDD) and time division duplexing (TDD) component carriers. (29) In some examples (e.g., in a carrier aggregation configuration), a carrier may also have acquisition signaling or control signaling that coordinates operations for other carriers. A carrier may be associated with a frequency channel (e.g., an evolved universal mobile telecommunication system terrestrial radio access (E-UTRA) absolute radio frequency channel number (EARFCN)) and may be positioned according to a channel raster for discovery by the UEs **115**. A carrier may be operated in a standalone mode where initial acquisition and connection may be conducted by the UEs **115** via the carrier, or the carrier may be operated in a non-standalone mode where a connection is anchored using a different carrier (e.g., of the same or a different radio access technology).

(30) The communication links **125** shown in the wireless communications system **100** may include uplink transmissions from a UE **115** to a base station **105**, or downlink transmissions from a base station **105** to a UE **115**. Carriers may carry downlink or uplink communications (e.g., in an FDD mode) or may be configured to carry downlink and uplink communications (e.g., in a TDD mode).

(31) A carrier may be associated with a particular bandwidth of the radio frequency spectrum, and in some examples the carrier bandwidth may be referred to as a “system bandwidth” of the carrier or the wireless communications system **100**. For example, the carrier bandwidth may be one of a number of determined bandwidths for carriers of a particular radio access technology (e.g., 1.4, 3, 5, 10, 15, 20, 40, or 80 megahertz (MHz)). Devices of the wireless communications system **100** (e.g., the base stations **105**, the UEs **115**, or both) may have hardware configurations that support communications over a particular carrier bandwidth or may be configurable to support communications over one of a set of carrier bandwidths. In some examples, the wireless communications system **100** may include base stations **105** or UEs **115** that support simultaneous communications via carriers associated with multiple carrier bandwidths. In some examples, each served UE **115** may be configured for operating over portions (e.g., a sub-band, a BWP) or all of a carrier bandwidth.

(32) Signal waveforms transmitted over a carrier may be made up of multiple subcarriers (e.g., using multi-carrier modulation (MCM) techniques such as orthogonal frequency division multiplexing (OFDM) or discrete Fourier transform spread OFDM (DFT-S-OFDM)). In a system employing MCM techniques, a resource element may consist of one symbol period (e.g., a duration of one modulation symbol) and one subcarrier, where the symbol period and subcarrier spacing are inversely related. The number of bits carried by each resource element may depend on the modulation scheme (e.g., the order of the modulation scheme, the coding rate of the modulation scheme, or both). Thus, the more resource elements that a UE **115** receives and the higher the order of the modulation scheme, the higher the data rate may be for the UE **115**. A wireless communications resource may refer to a combination of a radio frequency spectrum resource, a time resource, and a spatial resource (e.g., spatial layers or beams), and the use of multiple spatial layers may further increase the data rate or data integrity for communications with a UE **115**.

(33) One or more numerologies for a carrier may be supported, where a numerology may include a

subcarrier spacing (Δf) and a cyclic prefix. A carrier may be divided into one or more BWPs having the same or different numerologies. In some examples, a UE **115** may be configured with multiple BWPs. In some examples, a single BWP for a carrier may be active at a given time and communications for the UE **115** may be restricted to one or more active BWPs.

(34) The time intervals for the base stations **105** or the UEs **115** may be expressed in multiples of a basic time unit which may, for example, refer to a sampling period of $T_{\text{sub.s}} = 1/(\Delta f_{\text{sub.max}} \cdot N_{\text{sub.f}})$ seconds, where $\Delta f_{\text{sub.max}}$ may represent the maximum supported subcarrier spacing, and $N_{\text{sub.f}}$ may represent the maximum supported discrete Fourier transform (DFT) size. Time intervals of a communications resource may be organized according to radio frames each having a specified duration (e.g., 10 milliseconds (ms)). Each radio frame may be identified by a system frame number (SFN) (e.g., ranging from 0 to 1023).

(35) Each frame may include multiple consecutively numbered subframes or slots, and each subframe or slot may have the same duration. In some examples, a frame may be divided (e.g., in the time domain) into subframes, and each subframe may be further divided into a number of slots. Alternatively, each frame may include a variable number of slots, and the number of slots may depend on subcarrier spacing. Each slot may include a number of symbol periods (e.g., depending on the length of the cyclic prefix prepended to each symbol period). In some wireless communications systems **100**, a slot may further be divided into multiple mini-slots containing one or more symbols. Excluding the cyclic prefix, each symbol period may contain one or more (e.g., $N_{\text{sub.f}}$) sampling periods. The duration of a symbol period may depend on the subcarrier spacing or frequency band of operation.

(36) A subframe, a slot, a mini-slot, or a symbol may be the smallest scheduling unit (e.g., in the time domain) of the wireless communications system **100** and may be referred to as a transmission time interval (TTI). In some examples, the TTI duration (e.g., the number of symbol periods in a TTI) may be variable. Additionally or alternatively, the smallest scheduling unit of the wireless communications system **100** may be dynamically selected (e.g., in bursts of shortened TTIs (sTTIs)).

(37) Physical channels may be multiplexed on a carrier according to various techniques. A physical control channel and a physical data channel may be multiplexed on a downlink carrier, for example, using one or more of time division multiplexing (TDM) techniques, frequency division multiplexing (FDM) techniques, or hybrid TDM-FDM techniques. A control region (e.g., a control resource set (CORESET)) for a physical control channel may be defined by a number of symbol periods and may extend across the system bandwidth or a subset of the system bandwidth of the carrier. One or more control regions (e.g., CORESETs) may be configured for a set of the UEs **115**. For example, one or more of the UEs **115** may monitor or search control regions for control information according to one or more search space sets, and each search space set may include one or multiple control channel candidates in one or more aggregation levels arranged in a cascaded manner. An aggregation level for a control channel candidate may refer to a number of control channel resources (e.g., control channel elements (CCEs)) associated with encoded information for a control information format having a given payload size. Search space sets may include common search space sets configured for sending control information to multiple UEs **115** and UE-specific search space sets for sending control information to a specific UE **115**.

(38) Each base station **105** may provide communication coverage via one or more cells, for example a macro cell, a small cell, a hot spot, or other types of cells, or any combination thereof. The term “cell” may refer to a logical communication entity used for communication with a base station **105** (e.g., over a carrier) and may be associated with an identifier for distinguishing neighboring cells (e.g., a physical cell identifier (PCID), a virtual cell identifier (VCID), or others). In some examples, a cell may also refer to a geographic coverage area **110** or a portion of a geographic coverage area **110** (e.g., a sector) over which the logical communication entity operates. Such cells may range from smaller areas (e.g., a structure, a subset of structure) to larger areas

depending on various factors such as the capabilities of the base station **105**. For example, a cell may be or include a building, a subset of a building, or exterior spaces between or overlapping with geographic coverage areas **110**, among other examples.

(39) A macro cell may cover a relatively large geographic area (e.g., several kilometers in radius) and may allow unrestricted access by the UEs **115** with service subscriptions with the network provider supporting the macro cell. A small cell may be associated with a lower-powered base station **105**, as compared with a macro cell, and a small cell may operate in the same or different (e.g., licensed, unlicensed) frequency bands as macro cells. Small cells may provide unrestricted access to the UEs **115** with service subscriptions with the network provider or may provide restricted access to the UEs **115** having an association with the small cell (e.g., the UEs **115** in a closed subscriber group (CSG), the UEs **115** associated with users in a home or office). A base station **105** may support one or multiple cells and may also support communications over the one or more cells using one or multiple component carriers.

(40) In some examples, a carrier may support multiple cells, and different cells may be configured according to different protocol types (e.g., MTC, narrowband IoT (NB-IoT), enhanced mobile broadband (eMBB)) that may provide access for different types of devices.

(41) In some examples, a base station **105** may be movable and therefore provide communication coverage for a moving geographic coverage area **110**. In some examples, different geographic coverage areas **110** associated with different technologies may overlap, but the different geographic coverage areas **110** may be supported by the same base station **105**. In other examples, the overlapping geographic coverage areas **110** associated with different technologies may be supported by different base stations **105**. The wireless communications system **100** may include, for example, a heterogeneous network in which different types of the base stations **105** provide coverage for various geographic coverage areas **110** using the same or different radio access technologies.

(42) The wireless communications system **100** may be configured to support ultra-reliable communications or low-latency communications, or various combinations thereof. For example, the wireless communications system **100** may be configured to support ultra-reliable low-latency communications (URLLC). The UEs **115** may be designed to support ultra-reliable, low-latency, or critical functions. Ultra-reliable communications may include private communication or group communication and may be supported by one or more services such as push-to-talk, video, or data. Support for ultra-reliable, low-latency functions may include prioritization of services, and such services may be used for public safety or general commercial applications. The terms ultra-reliable, low-latency, and ultra-reliable low-latency may be used interchangeably herein.

(43) In some examples, a UE **115** may also be able to communicate directly with other UEs **115** over a device-to-device (D2D) communication link **135** (e.g., using a peer-to-peer (P2P) or D2D protocol). One or more UEs **115** utilizing D2D communications may be within the geographic coverage area **110** of a base station **105**. Other UEs **115** in such a group may be outside the geographic coverage area **110** of a base station **105** or be otherwise unable to receive transmissions from a base station **105**. In some examples, groups of the UEs **115** communicating via D2D communications may utilize a one-to-many (1:M) system in which each UE **115** transmits to every other UE **115** in the group. In some examples, a base station **105** facilitates the scheduling of resources for D2D communications. In other cases, D2D communications are carried out between the UEs **115** without the involvement of a base station **105**.

(44) The core network **130** may provide user authentication, access authorization, tracking, Internet Protocol (IP) connectivity, and other access, routing, or mobility functions. The core network **130** may be an evolved packet core (EPC) or 5G core (5GC), which may include at least one control plane entity that manages access and mobility (e.g., a mobility management entity (MME), an access and mobility management function (AMF)) and at least one user plane entity that routes packets or interconnects to external networks (e.g., a serving gateway (S-GW), a Packet Data

Network (PDN) gateway (P-GW), or a user plane function (UPF)). The control plane entity may manage non-access stratum (NAS) functions such as mobility, authentication, and bearer management for the UEs **115** served by the base stations **105** associated with the core network **130**. User IP packets may be transferred through the user plane entity, which may provide IP address allocation as well as other functions. The user plane entity may be connected to IP services **150** for one or more network operators. The IP services **150** may include access to the Internet, Intranet(s), an IP Multimedia Subsystem (IMS), or a Packet-Switched Streaming Service. A UE **115** may communicate with the core network **130** through communication link **155**.

(45) Some of the network devices, such as a base station **105**, may include subcomponents such as an access network entity **140**, which may be an example of an access node controller (ANC). Each access network entity **140** may communicate with the UEs **115** through one or more other access network transmission entities **145**, which may be referred to as radio heads, smart radio heads, or transmission/reception points (TRPs). Each access network transmission entity **145** may include one or more antenna panels. In some configurations, various functions of each access network entity **140** or base station **105** may be distributed across various network devices (e.g., radio heads and ANCs) or consolidated into a single network device (e.g., a base station **105**).

(46) The wireless communications system **100** may operate using one or more frequency bands, such as in the range of 300 megahertz (MHz) to 300 gigahertz (GHz). The region from 300 MHz to 3 GHz may be known as the ultra-high frequency (UHF) region or decimeter band because the wavelengths range from approximately one decimeter to one meter in length. The UHF waves may be blocked or redirected by buildings and environmental features, but the waves may penetrate structures sufficiently for a macro cell to provide service to the UEs **115** located indoors. The transmission of UHF waves may be associated with smaller antennas and shorter ranges (e.g., less than 100 kilometers) compared to transmission using the smaller frequencies and longer waves of the high frequency (HF) or very high frequency (VHF) portion of the spectrum below 300 MHz.

(47) The wireless communications system **100** may also operate in a super high frequency (SHF) region using frequency bands from 3 GHz to 30 GHz, also known as the centimeter band, or in an extremely high frequency (EHF) region of the spectrum (e.g., from 30 GHz to 300 GHz), also known as the millimeter band. In some examples, the wireless communications system **100** may support millimeter wave (mmW) communications between the UEs **115** and the base stations **105**, and EHF antennas of the respective devices may be smaller and more closely spaced than UHF antennas. In some examples, this may facilitate use of antenna arrays within a device. The propagation of EHF transmissions, however, may be subject to even greater atmospheric attenuation and shorter range than SHF or UHF transmissions. The techniques disclosed herein may be employed across transmissions that use one or more different frequency regions, and designated use of bands across these frequency regions may differ by country or regulating body.

(48) The electromagnetic spectrum is often subdivided, based on frequency/wavelength, into various classes, bands, channels, etc. In 5G NR two initial operating bands have been identified as frequency range designations FR1 (410 MHz-7.125 GHz) and FR2 (24.25 GHz-52.6 GHz). It should be understood that although a portion of FR1 is greater than 6 GHz, FR1 is often referred to (interchangeably) as a “Sub-6 GHz” band in various documents and articles. A similar nomenclature issue sometimes occurs with regard to FR2, which is often referred to (interchangeably) as a “millimeter wave” band in documents and articles, despite being different from the extremely high frequency (EHF) band (30 GHz-300 GHz) which is identified by the International Telecommunications Union (ITU) as a “millimeter wave” band.

(49) The frequencies between FR1 and FR2 are often referred to as mid-band frequencies. Recent 5G NR studies have identified an operating band for these mid-band frequencies as frequency range designation FR3 (7.125 GHz-24.25 GHz). Frequency bands falling within FR3 may inherit FR1 characteristics and/or FR2 characteristics, and thus may effectively extend features of FR1 and/or FR2 into mid-band frequencies. In addition, higher frequency bands are currently being

explored to extend 5G NR operation beyond 52.6 GHz. For example, three higher operating bands have been identified as frequency range designations FR4a or FR4-1 (52.6 GHz-71 GHz), FR4 (52.6 GHz-114.25 GHz), and FR5 (114.25 GHz-300 GHz). Each of these higher frequency bands falls within the EHF band.

(50) With the above aspects in mind, unless specifically stated otherwise, it should be understood that the term “sub-6 GHz” or the like if used herein may broadly represent frequencies that may be less than 6 GHz, may be within FR1, or may include mid-band frequencies. Further, unless specifically stated otherwise, it should be understood that the term “millimeter wave” (e.g., mmW) or the like if used herein may broadly represent frequencies that may include mid-band frequencies, may be within FR2, FR4, FR4-a or FR4-1, and/or FR5, or may be within the EHF band.

(51) The wireless communications system **100** may utilize both licensed and unlicensed radio frequency spectrum bands. For example, the wireless communications system **100** may employ License Assisted Access (LAA), LTE-Unlicensed (LTE-U) radio access technology, or NR technology in an unlicensed band such as the 5 GHz industrial, scientific, and medical (ISM) band. When operating in unlicensed radio frequency spectrum bands, devices such as the base stations **105** and the UEs **115** may employ carrier sensing for collision detection and avoidance. In some examples, operations in unlicensed bands may be based on a carrier aggregation configuration in conjunction with component carriers operating in a licensed band (e.g., LAA). Operations in unlicensed spectrum may include downlink transmissions, uplink transmissions, P2P transmissions, or D2D transmissions, among other examples.

(52) A base station **105** or a UE **115** may be equipped with multiple antennas, which may be used to employ techniques such as transmit diversity, receive diversity, multiple-input multiple-output (MIMO) communications, or beamforming. The antennas of a base station **105** or a UE **115** may be located within one or more antenna arrays or antenna panels, which may support MIMO operations or transmit or receive beamforming. For example, one or more base station antennas or antenna arrays may be co-located at an antenna assembly, such as an antenna tower. In some examples, antennas or antenna arrays associated with a base station **105** may be located in diverse geographic locations. A base station **105** may have an antenna array with a number of rows and columns of antenna ports that the base station **105** may use to support beamforming of communications with a UE **115**. Likewise, a UE **115** may have one or more antenna arrays that may support various MIMO or beamforming operations. Additionally or alternatively, an antenna panel may support radio frequency beamforming for a signal transmitted via an antenna port.

(53) Beamforming, which may also be referred to as spatial filtering, directional transmission, or directional reception, is a signal processing technique that may be used at a transmitting device or a receiving device (e.g., a base station **105**, a UE **115**) to shape or steer an antenna beam (e.g., a transmit beam, a receive beam) along a spatial path between the transmitting device and the receiving device. Beamforming may be achieved by combining the signals communicated via antenna elements of an antenna array such that some signals propagating at particular orientations with respect to an antenna array experience constructive interference while others experience destructive interference. The adjustment of signals communicated via the antenna elements may include a transmitting device or a receiving device applying amplitude offsets, phase offsets, or both to signals carried via the antenna elements associated with the device. The adjustments associated with each of the antenna elements may be defined by a beamforming weight set associated with a particular orientation (e.g., with respect to the antenna array of the transmitting device or receiving device, or with respect to some other orientation).

(54) A base station **105** or a UE **115** may use beam sweeping techniques as part of beam forming operations. For example, a base station **105** may use multiple antennas or antenna arrays (e.g., antenna panels) to conduct beamforming operations for directional communications with a UE **115**. Some signals (e.g., synchronization signals, reference signals, beam selection signals, or other control signals) may be transmitted by a base station **105** multiple times in different directions. For

example, the base station **105** may transmit a signal according to different beamforming weight sets associated with different directions of transmission. Transmissions in different beam directions may be used to identify (e.g., by a transmitting device, such as a base station **105**, or by a receiving device, such as a UE **115**) a beam direction for later transmission or reception by the base station **105**.

(55) Some signals, such as data signals associated with a particular receiving device, may be transmitted by a base station **105** in a single beam direction (e.g., a direction associated with the receiving device, such as a UE **115**). In some examples, the beam direction associated with transmissions along a single beam direction may be determined based on a signal that was transmitted in one or more beam directions. For example, a UE **115** may receive one or more of the signals transmitted by the base station **105** in different directions and may report to the base station **105** an indication of the signal that the UE **115** received with a highest signal quality or an otherwise acceptable signal quality.

(56) In some examples, transmissions by a device (e.g., by a base station **105** or a UE **115**) may be performed using multiple beam directions, and the device may use a combination of digital precoding or radio frequency beamforming to generate a combined beam for transmission (e.g., from a base station **105** to a UE **115**). The UE **115** may report feedback that indicates precoding weights for one or more beam directions, and the feedback may correspond to a configured number of beams across a system bandwidth or one or more sub-bands. The base station **105** may transmit a reference signal (e.g., a cell-specific reference signal (CRS), a channel state information reference signal (CSI-RS)), which may be precoded or unprecoded. The UE **115** may provide feedback for beam selection, which may be a precoding matrix indicator (PMI) or codebook-based feedback (e.g., a multi-panel type codebook, a linear combination type codebook, a port selection type codebook). Although these techniques are described with reference to signals transmitted in one or more directions by a base station **105**, a UE **115** may employ similar techniques for transmitting signals multiple times in different directions (e.g., for identifying a beam direction for subsequent transmission or reception by the UE **115**) or for transmitting a signal in a single direction (e.g., for transmitting data to a receiving device).

(57) A receiving device (e.g., a UE **115**) may try multiple receive configurations (e.g., directional listening) when receiving various signals from the base station **105**, such as synchronization signals, reference signals, beam selection signals, or other control signals. For example, a receiving device may try multiple receive directions by receiving via different antenna subarrays, by processing received signals according to different antenna subarrays, by receiving according to different receive beamforming weight sets (e.g., different directional listening weight sets) applied to signals received at multiple antenna elements of an antenna array, or by processing received signals according to different receive beamforming weight sets applied to signals received at multiple antenna elements of an antenna array, any of which may be referred to as “listening” according to different receive configurations or receive directions. In some examples, a receiving device may use a single receive configuration to receive along a single beam direction (e.g., when receiving a data signal). The single receive configuration may be aligned in a beam direction determined based on listening according to different receive configuration directions (e.g., a beam direction determined to have a highest signal strength, highest signal-to-noise ratio (SNR), or otherwise acceptable signal quality based on listening according to multiple beam directions).

(58) The wireless communications system **100** may be a packet-based network that operates according to a layered protocol stack. In the user plane, communications at the bearer or PDCP layer may be IP-based. An RLC layer may perform packet segmentation and reassembly to communicate over logical channels. A MAC layer may perform priority handling and multiplexing of logical channels into transport channels. The MAC layer may also use error detection techniques, error correction techniques, or both to support retransmissions at the MAC layer to improve link efficiency. In the control plane, the RRC protocol layer may provide establishment,

configuration, and maintenance of an RRC connection between a UE **115** and a base station **105** or a core network **130** supporting radio bearers for user plane data. At the physical layer, transport channels may be mapped to physical channels.

(59) Techniques described herein, in addition to or as an alternative to be carried out between UEs **115** and base stations **105**, may be implemented via additional or alternative wireless devices, including IAB nodes **104**, distributed units (DUs) **165**, CUs **160**, radio units (RUs) **170**, and the like. For example, in some implementations, aspects described herein may be implemented in the context of a disaggregated radio access network (RAN) architecture (e.g., open RAN architecture). In a disaggregated architecture, the RAN may be split into three areas of functionality corresponding to the CU **160**, the DU **165**, and the RU **170**. The split of functionality between the CU **160**, DU **165**, and RU **170** is flexible and as such gives rise to numerous permutations of different functionalities depending upon which functions (e.g., MAC functions, baseband functions, radio frequency functions, and any combinations thereof) are performed at the CU **160**, DU **165**, and RU **170**. For example, a functional split of the protocol stack may be employed between a DU **165** and an RU **170** such that the DU **165** may support one or more layers of the protocol stack and the RU **170** may support one or more different layers of the protocol stack.

(60) Some wireless communications systems (e.g., wireless communications system **100**), infrastructure and spectral resources for NR access may additionally support wireless backhaul link capabilities in supplement to wireline backhaul connections, providing an IAB network architecture. One or more base stations **105** may include CUs **160**, DUs **165**, and RUs **170** and may be referred to as donor base stations **105** or IAB donors. One or more DUs **165** (e.g., and/or RUs **170**) associated with a donor base station **105** may be partially controlled by CUs **160** associated with the donor base station **105**. The one or more donor base stations **105** (e.g., IAB donors) may be in communication with one or more additional base stations **105** (e.g., IAB nodes **104**) via supported access and backhaul links. IAB nodes **104** may support mobile terminal (MT) functionality controlled and/or scheduled by DUs **165** of a coupled IAB donor. In addition, the IAB nodes **104** may include DUs **165** that support communication links with additional entities (e.g., IAB nodes **104**, UEs **115**, etc.) within the relay chain or configuration of the access network (e.g., downstream). In such cases, one or more components of the disaggregated RAN architecture (e.g., one or more IAB nodes **104** or components of IAB nodes **104**) may be configured to operate according to the techniques described herein.

(61) In some examples, the wireless communications system **100** may include a core network **130** (e.g., a next generation core network (NGC)), one or more IAB donors, IAB nodes **104**, and UEs **115**, where IAB nodes **104** may be partially controlled by each other and/or the IAB donor. The IAB donor and IAB nodes **104** may be examples of aspects of base stations **105**. IAB donor and one or more IAB nodes **104** may be configured as (e.g., or in communication according to) some relay chain.

(62) For instance, an access network (AN) or RAN may refer to communications between access nodes (e.g., IAB donor), IAB nodes **104**, and one or more UEs **115**. The IAB donor may facilitate connection between the core network **130** and the AN (e.g., via a wireline or wireless connection to the core network **130**). That is, an IAB donor may refer to a RAN node with a wireline or wireless connection to core network **130**. The IAB donor may include a CU **160** and at least one DU **165** (e.g., and RU **170**), where the CU **160** may communicate with the core network **130** over an NG interface (e.g., some backhaul link). The CU **160** may host layer 3 (L3) (e.g., RRC, service data adaptation protocol (SDAP), PDCP, etc.) functionality and signaling. The at least one DU **165** and/or RU **170** may host lower layer, such as layer 1 (L1) and layer 2 (L2) (e.g., RLC, MAC, physical (PHY), etc.) functionality and signaling, and may each be at least partially controlled by the CU **160**. The DU **165** may support one or multiple different cells. IAB donor and IAB nodes **104** may communicate over an F1 interface according to some protocol that defines signaling messages (e.g., F1 AP protocol). Additionally, CU **160** may communicate with the core network over an NG

interface (which may be an example of a portion of backhaul link), and may communicate with other CUs **160** (e.g., a CU **160** associated with an alternative IAB donor) over an Xn-C interface (which may be an example of a portion of a backhaul link).

(63) TAB nodes **104** may refer to a RAN node that provides IAB functionality (e.g., access for UEs **115**, wireless self-backhauling capabilities, etc.). IAB nodes **104** may include a DU **165** and an MT. A DU **165** may act as a distributed scheduling node towards child nodes associated with the IAB node **104**, and the MT may act as a scheduled node towards parent nodes associated with the IAB node **104**. That is, an IAB donor may be referred to as a parent node in communication with one or more child nodes (e.g., an IAB donor may relay transmissions for UEs through one or more other IAB nodes **104**). Additionally, an IAB node **104** may also be referred to as a parent node or a child node to other IAB nodes **104**, depending on the relay chain or configuration of the AN. Therefore, the MT entity of IAB nodes **104** (e.g., MTs) may provide a Uu interface for a child node to receive signaling from a parent IAB node **104**, and the DU interface (e.g., DUs **165**) may provide a Uu interface for a parent node to signal to a child IAB node **104** or UE **115**.

(64) For example, IAB node **104** may be referred to a parent node associated with IAB node, and a child node associated with IAB donor. The IAB donor may include a CU **160** with a wireline (e.g., optical fiber) or wireless connection to the core network and may act as parent node to IAB nodes **104**. For example, the DU **165** of IAB donor may relay transmissions to UEs **115** through IAB nodes **104**, and may directly signal transmissions to a UE **115**. The CU **160** of IAB donor may signal communication link establishment via an F1 interface to IAB nodes **104**, and the IAB nodes **104** may schedule transmissions (e.g., transmissions to the UEs **115** relayed from the IAB donor) through the DUs **165**. That is, data may be relayed to and from IAB nodes **104** via signaling over an NR Uu interface to MT of the IAB node **104**. Communications with IAB node **104** may be scheduled by DU **165** of IAB donor and communications with IAB node **104** may be scheduled by DU **165** of IAB node **104**.

(65) In the case of the techniques described herein applied in the context of a disaggregated RAN architecture, one or more components of the disaggregated RAN architecture (e.g., one or more IAB nodes **104** or components of IAB nodes **104**) may be configured to support techniques described herein. For example, some operations described as being performed by a UE **115** or a base station **105** may additionally or alternatively be performed by components of the disaggregated RAN architecture (e.g., IAB nodes, DUs, CUs, etc.).

(66) One or more of the operations performed by a UE **115** may be performed by a communications manager **101**, which may be an example of a communications manager **520**, **620**, **720**, or **820** as described with reference to FIGS. 5 through 8. In some cases, a transceiver may perform the receiving or transmitting operations and a processor may identify one or more aspects of L1/L2 mobility information for the UE **115**.

(67) One or more of the operations performed by a base station may be performed by a communications manager **102**, which may be an example of a communications manager **920**, **1020**, **1120**, or **1220** as described with reference to FIGS. 9 through 12. In some cases, a transceiver may perform the receiving or transmitting operations and a processor may identify one or more aspects of L1/L2 mobility information based on measurement information received from a UE **115**.

(68) FIG. 2 illustrates an example of a wireless communications system **200** that supports techniques for providing cell mobility information during handover in accordance with one or more aspects of the present disclosure. In some examples, wireless communications system **200** may implement or be implemented by one or more aspects of wireless communications system **100**. For example, wireless communications system **200** may include a base station **105-a** and a UE **115-a**, which may be examples of a base station **105** and a UE **115** described with reference to FIG. 1. Base station **105-a** may include one or more cells **205**, where each cell **205** may represent any one or more of the examples of a cell described with reference to FIG. 1. In some examples, base station **105-a** may include each of the cells **205** illustrated by FIG. 1, while in some other

examples, base station **105-a** may include at least a subset or a portion of the cells **205** illustrated by FIG. 1.

(69) One or more of the cells **205** may communicate with UE **115-a**, for example, to support uplink and/or downlink communications with base station **105-a**, or with another base station **105**. For example, UE **115-a** may communicate with an activated subset **235** of cells **205**, which may include cells **205-b**, **205-c**, and **205-d** (e.g., among other cells **205**). At least one of the cells **205** in the activated subset **235** may be configured as a PCell (e.g., cell **205-d** may be a PCell for UE **115-a**). In some cases (e.g., if UE **115-a** is mobile, if network conditions change), communication quality may be increased by changing the PCell to another cell, or by changing one or more cells of the activated subset **235** (e.g., by activating one or more cells **205** outside of the activated subset **235**, to be included in the activated subset **235**).

(70) Such techniques may be referred to as cell mobility, cell mobility management, or inter-cell mobility, among other examples. In some cases, base station **105-a** (e.g., or another base station **105**) may provide higher-layer signaling, or L3 signaling, to perform the inter-cell mobility (e.g., switch PCells, change the activated subset **235** of cells **205**). Such signaling may be referred to as a handover, an L3 handover, or a handover command, among other examples, and may be associated with an increased latency and/or delays, for example, in comparison with lower-layer signaling, such as L1 signaling **275** and L2 signaling **280**. Although some signal or links are shown as being associated with L1 signaling **275** or L2 signaling **280**, it is to be understood that any link or any signaling may be associated with any one or combination of L1 signaling **275**, L2 signaling **280**, or L3 signaling **255**. In some cases, base station **105-a** and UE **115-a** may support inter-cell mobility using L1 or L2 signaling, which may be referred to as L1/L2 inter-cell mobility, L1/L2 mobility, or L1/L2 cell mobility management, among other examples.

(71) In a first example (e.g., a first scheme) of L1/L2 inter-cell mobility, base station **105-a** and UE **115-a** may perform beam-based mobility (e.g., dynamic point selection based mobility) using L1 signaling **275** or L2 signaling **280**, where base station **105-a** may indicate for UE **115-a** to use a beam from a cell **205** outside of the activated subset **235** (e.g., from a non-serving cell) for communications with the network. In the first example, the network may refrain from changing a PCell for UE **115-a** using L1 signaling **275** or L2 signaling **280**. In a second example (e.g., a second scheme) of L1/L2 inter-cell mobility, base station **105-a** and UE **115-a** may perform serving cell based mobility using L1 signaling **275** or L2 signaling **280**, where a serving cell (e.g., cells **205** in the activated subset **235**) may be changed using L1 signaling **275** or L2 signaling **280**. In the second example, the PCell for UE **115-a** may be changed using L1 signaling **275** or L2 signaling **280** (e.g., without requiring an L3 handover). Such signaling may be used to provide L1/L2 mobility for a direct link between UE **115-a** and base station **105-a** (e.g., a Uu link) or for a sidelink link.

(72) Serving cell based L1/L2 mobility may be referred to herein as L1/L2 mobility, L1/L2 inter-cell mobility, or L1/L2 cell mobility management, among other examples. This L1/L2 mobility may be similar to carrier aggregation, but the cells **205** may be on one or more same carrier frequencies for the L1/L2 mobility. In some examples, the network may utilize existing mechanisms of carrier aggregation to support L1/L2 mobility. In order to support L1/L2 mobility, the network (e.g., base station **105-a** or another base station **105-a**) may configure (e.g., via RRC signaling) a set of cells **230** for L1/L2 mobility.

(73) The set of cells **230** may include an activated subset **235** of cells **205** and a deactivated subset of cells **205** (e.g., any cells **205** included in the set of cells **230**, but not included in the activated subset **235**). The activated subset **235** may include a group of cells **205**, within the set of cells **230**, that is activated and ready to be used for data and control communications (e.g., data and control transfer). For example, UE **115-a** may communicate with the cells **205** within the activated subset **235** (e.g., with cells **205-b**, **205-c**, and **205-d**), such as via a direct link or via a relayed link (e.g., a relayed sidelink). The deactivated subset of cells **205** may be a group of cells **205** in the set of cells

230 that is deactivated, where one or more cells **205** of the deactivated subset may be activated by L1/L2 signaling. The set of cells **230** may also include a subset **240** of candidate cells **205** (e.g., candidate PCells), where the subset **240** of candidate cells **205** may include one or more cells **205** that may be activated as a PCell via L1 signaling **275** or L2 signaling **280**.

(74) Within the set of cells **230**, L1 signaling **275** and/or L2 signaling **280** may be used to perform cell mobility management. For example, L1 signaling **275** or L2 signaling **280** may be used to activate and/or deactivate cells **205** within the set of cells **230** (e.g., to remove or add cells **205** to the activated subset **235**). L1 signaling **275** or L2 signaling **280** may additionally or alternatively be used to select one or more communication beams associated with cells **205** within the activated subset **235**. As such, the L1/L2 mobility within the set of cells **230** may support a relatively seamless mobility within activated cells **205** of the set of cells **230** (e.g., cells within the activated subset **235**).

(75) L1/L2 mobility may also support PCell management within the set of cells **230**. For example, L1 signaling **275** or L2 signaling **280** may be used to set or configure a PCell for UE **115-a** out of the activated subset **235** (e.g., by indicating a cell **205** that is configured as a possible PCell, such as within the subset **240** of candidate cells **205**).

(76) In some cases, UE **115-a** may additionally or alternatively use one or more other UEs **115**, that serve as relay UEs **115**, to communicate with a cell **205**. For example, UE **115-a** may (e.g., in addition or as an alternative to direct links with cells **205-b**, **205-c**, and **205-d**) communicate with cells **205-b** and **205-c** via UE **115-b**, which may serve as a relay UE **115**. For example, UE **115-a** may communicate with UE **115-b** via a sidelink, and UE **115-b** may communicate with cells **205-b** and **205-c** via a direct link, to relay communications (e.g., uplink and/or downlink communications) for UE **115-a**. In some cases, when UE **115-a** is served by one or more relay UEs **115** L1 signaling **275** or L2 signaling **280** may be used to select which UEs **115** to serve as relay UEs **115** for UE **115-a**, which may be referred to as UE relay with L1/L2 mobility. Being served by the one or more relay UEs **115** in L1/L2 mobility may support using an increased number of cells **205** for communications with UE **115-a**, as well as an increase in a coverage area within which L1/L2 mobility may be utilized.

(77) A set of relay UEs **115** that support L1/L2 mobility may be configured as a UE relay set for UE **115-a**. The UE relay set may include an activated subset **245** of activated (e.g., active) relay UEs **115** that is actively serving UE **115-a**. For example, the activated subset **245** may include UE **115-b**, or may include UE **115-b** and one or more other UEs **115**. The UE relay set may also include a deactivated subset **250** of deactivated relay UEs **115**, which may be activated to serve UE **115-a** (e.g., which are prepared to serve UE **115-a**). For example, the deactivated subset **250** may include UEs **115-c** and **115-d**.

(78) Base station **105-a** may configure a subset of the set of relay UEs **115** (e.g., a subset that includes UE **115-b** and UE **115-c**, or any other combination of UEs **115**) for L1/L2 mobility, such that UE **115-a** may autonomously activate the relay UEs **115** within the L1/L2 subset using L1 signaling **275** or L2 signaling **280** (e.g., may add one or more UEs **115** to the activated subset **245** using L1 signaling **275** or L2 signaling **280**). UE **115-a** may also indicate, to base station **105-a**, which relay UEs **115** have been activated by UE **115-a**. UE **115-a** may, for example, use L1 signaling **275** or L2 signaling **280** to directly inform base station **105-a** of the activated UE(s) **115**. Additionally or alternatively (e.g., when UE **115-a** is out of coverage of base station **105-a**), an activated relay UE **115** (e.g., UE **115-b**) may use L1 signaling **275** or L2 signaling **280** to inform base station **105-a** about an activation received from UE **115-a**.

(79) Performing L1/L2 mobility directly with one or more cells **205**, via a relay UE **115**, or both, may support cell mobility based on L1 signaling **275** or L2 signaling **280**, which may reduce latency. In a first example, UE **115-a** may be served by one cell **205** (e.g., the activated subset **235** may include one cell **205**), which may support backward compatibility of one serving cell **205** on one carrier frequency, as well as supporting increased cell mobility and decreased latency by using

L1 signaling **275** or L2 signaling **280** instead of L3 signaling. In such cases, UE **115-a** may be configured with one active transmission configuration indicator (TCI) state (e.g., UE **115-a** may support one TCI state). In a second example, UE **115-a** may be served by multiple cells **205** (e.g., the activated subset **235** may include multiple cells **205**) on a same carrier frequency, which may support increased transmission diversity, coverage, and throughput, while decreasing latency.

(80) If UE **115-a** is to be served by a new PCell (e.g., a target cell) that is not included within the set of cells **230** (e.g., based on channel or signal quality), L3 mobility (e.g., an L3 handover or handover command) may be used for changing the PCell serving UE **115-a**. In such cases, after performing the handover procedure, UE **115-a** may receive signaling (e.g., RRC signaling) to update the set of cells **230** used for L1/L2 mobility. However, such configuration after performing the handover procedure may take time (e.g., based on performing new measurements and receiving a new configuration based on the measurements), which may result in increased latency before UE **115-a** is configured for L1/L2 mobility procedures after performing a handover command.

(81) In some cases, the increased latency may result in decreased reliability, for example, in a mmW context in which a channel may be impaired or blocked relatively quickly and handovers may be more frequent (e.g., based on a smaller coverage area). For example, decreased reliability may occur if the handover is completed to a PCell with a lower signal quality than another available cell **205**, if the handover is completed too early (e.g., when UE **115-a** is mobile), if signal blockage occurs after handover (e.g., for mmW signaling), or if radio link failure occurs on the new PCell.

(82) The present disclosure provides techniques for including L1/L2 mobility information within an L3 handover command **225** (e.g., within L3 signaling **255**), which may result in reduced latency and increased reliability. For example, the handover command may include L1/L2 mobility information (e.g., an L1/L2 mobility configuration) such as an indication of a new set of cells **230** and an associated configuration (e.g., RRC configuration), among other information (e.g., an indication of a new activated subset **235** of cells **205**, a new subset **240** of candidate cells **205**). Based on the L1/L2 mobility information, UE **115-a** may perform L1/L2 mobility (e.g., switch active cells **205**, switch PCells) any time after performing the handover command (e.g., rather than waiting for a reconfiguration), such that a PCell may be quickly changed in case of communication problems (e.g., handover is completed early, signal blockage, radio link failure).

(83) In order to support including the L1/L2 information within the L3 handover command **225**, base station **105-a** may transmit, to UE **115-a**, signaling **210** indicating for UE **115-a** to perform a measurement **265** (e.g., one or more measurements) on a first set of cells **205**. The first set of cells **205** may represent, for example, a set of cells **205** that could be used by UE **115-a** after the handover and is described in more detail with reference to FIG. 3. In some cases, the signaling **210** may include a tenth indication **290**, which may indicate for UE **115-a** to perform a second measurement on a third set of cells associated with a same base station **105** as the first set of cells (e.g., if the measurement on the first set of cells satisfies a threshold value). UE **115-a** may perform the measurement **265** on the first set of cells and may transmit a first indication **215**, to base station **105-a**, associated with the measurement (e.g., may indicate of a result of the measurement **265**) on the first set of cells. For example, UE **115-a** may perform joint beam reporting **285**, and may indicate a result of the joint beam reporting **285** in the first indication **215**. In some cases, UE **115-a** may also transmit an eighth indication **220-a** of a requested set of cells **230** or a ninth indication **220-b** an activated subset **235** of cells **205** for the L1/L2 mobility.

(84) In response to the first indication **215** associated with the measurement **265**, base station **105-a** may transmit, to UE **115-a**, an L3 handover command **225**, where the L3 handover command **225** may include an identification of a second set of cells **205** (e.g., a new set of cells **230**) that UE **115-a** is to use for L1/L2 mobility after completing the handover command. For example, the L3 handover command **225** may include a second indicate **260-a** of a second set of cells **205** for L1/L2 mobility that UE **115-a** is to use after completing the L3 handover command **225**. In some cases,

the first set of cells **205** may include all or a portion of the second set of cells **205**. The second set of cells is also further described herein with reference to FIG. 3.

(85) As described herein, the L3 handover command **225** may further include one or more other indications. For example, the L3 handover command **225** may include a third indication **260-b** of a communication configuration for the second set of cells **205**. The L3 handover command **225** may also include a fourth indication **260-c** of an activated subset of the second set of cells **205** (e.g., to be used for communications after completing the L3 handover command **225**). The L3 handover command **225** may also include a fifth indication **260-d** of QCL information indicative of a set of beams **270** to use on the activated subset of the second set of cells **205**. The L3 handover command **225** may also include a sixth indication **260-e** of a subset of candidate PCells within the second set of cells **205**. The L3 handover command **225** may also include a seventh indication **260-f** of signaling to use for L1 measurements performed on the second set of cells **205** for L1/L2 cell mobility.

(86) FIG. 3 illustrates an example of a measurement scheme **300** that supports techniques for providing cell mobility information during handover in accordance with one or more aspects of the present disclosure. In some examples, measurement scheme **300** may implement or be implemented by one or more aspects of wireless communications system **100** or **200**. For example, measurement scheme **300** may be implemented when performing measurements on one or more respective cells **305** of base stations **105-b** and **105-c**, which may represent examples of cells and base stations **105** described with reference to FIGS. 1 and 2.

(87) As described with reference to FIG. 2, prior to performing a handover (e.g., an L3 handover) a base station **105** may indicate for a UE **115** to perform measurements on a first set of cells **315**, where the base station **105** may determine a second set of cells **320** for L1/L1 mobility (e.g., after the handover) based on the measurements. The indication for the UE **115** to perform the measurements may, in some cases, reduce a quantity of persistent measurements to support L1/L2 mobility, for example, because the measurements may be performed as indicated by the base station **105** (e.g., instead of being performed persistently or semi-persistently by the UE **115**). The measurements may include beam measurements, for example, to support L1/L2 mobility for one or more frequency ranges, such as a frequency range 2 (FR2), frequency range 3 (FR3), and frequency range 4 (FR4), among other examples. The measurements may include L3 measurements, or a combination of L1 and L3 measurements, on the first set of cells **315**.

(88) Based on one or more previous measurements (e.g., performed by the UE **115**, such as legacy measurements), the base station **105** may select or determine a group of candidate PCells for performing the handover procedure, which may be referred to as candidate target cells **305**. For example, the base station **105** may select one or more first candidate target cells **305** on base station **105-b** and one or more second candidate target cells **305** on base station **105-c** (e.g., among other candidate target cells **305** on one or more other base stations **105**). The base station **105** may request for the UE **115** to perform the measurements on the candidate target cells **305**, as well as perform measurements on one or more other cells **305** belonging to a same base station **105** as the candidate target cells **305**. The candidate target cells **305**, together with the one or more other cells **305**, may be referred to as the first set of cells **315** (e.g., for which the UE **115** is to perform the measurements).

(89) In some cases, the one or more candidate target cells **305** and the one or more other cells **305** may include all of the cells **305** on a base station **105**. Additionally or alternatively, the one or more candidate target cells **305** and the one or more other cells **305** may include a subset of the cells **305** on a base station **105**. According to one example, the base station **105** may indicate for the UE **115** to perform measurements on the first set of cells **315**, which may include all of the cells **305** on base station **105-b** (e.g., cells **305-a** through **305-e**), and which may also include a subset of cells **305** on base station **105-c** (e.g., cells **305-g**, **305-h**, and **305-i**). In some cases, after receiving an indication of the measurements from the UE **115**, the base station **105** may expand or update the

first set of cells **315** and may request for the UE **115** to perform measurements on the updated first set of cells **315**.

(90) In some cases, the measurements performed by the UE **115** may be based on a channel quality, for example, as indicated by a baseline measurement configuration. For example, based on a configuration of the UE **115** (e.g., as indicated by the base station **105**), the UE **115** may perform the measurements on the first set of cells **315**, which may be referred to as the baseline measurement configuration. The UE **115** may extend the measurements to a third set of cells **325** if a threshold measurement (e.g., threshold channel quality) is satisfied.

(91) For example, the UE **115** may perform measurements on cells **305-g**, **305-h**, and **305-i** of base station **105-c**, based on the cells **305** being included in the first set of cells **315** (e.g., the UE **115** may perform measurements on a set of cells **305** of a base station **105**). If one or more measurements from the cells **305-g**, **305-h**, and/or **305-i** satisfy a threshold, the UE **115** may also perform the measurements on the third set of cells **325**, which may include cells **305-f** and **305-j** on base station **105-c** (e.g., the UE **115** may extend the measurements to additional cells **305** of the same base station **105**). In some cases, the UE **115** may be configured (e.g., as defined at the UE **115** or as indicated by the base station **105**) to perform the additional measurements if the threshold is satisfied. In some cases, the base station **105** may determine whether the threshold is satisfied (e.g., based on reported measurements by the UE **115**) and may request for the UE **115** to perform the measurements on the third set of cells **325**.

(92) In some cases, the measurements may include performing joint beam reporting on a set of cells **305** (e.g., neighboring cells) that belong to a same base station **105**. For example, the UE **115** may perform joint beam reporting on a per-base station basis for the first set of cells **315**. As such, the UE **115** may perform joint beam reporting for cells **305-a** through **305-e**, and may also perform joint beam reporting for cells **305-g** through **305-i**. The set of cells **305** for joint beam reporting may have a same distributed unit (DU) or may have different DUs.

(93) Based on the measurements received from the UE **115**, the base station **105** may select the second set of cells **320** for L1/L2 mobility. The second set of cells **320** may belong to a same base station **105** (e.g., a target base station **105**), and may include a PCell (e.g., a target cell **305**) for communications with the UE **115**. The second set of cells **320** may represent a subset of cells **305** of the target base station **105**, or may represent all of the cells **305** of the target base station **105**. For example, the base station may select base station **105-c** as the target base station **105**, and the second set of cells **320** may include cells **305-g**, **305-h**, and a PCell **330** (e.g., a target cell **335**), or the second set of cells **320** may include cells **305-f** through **305-j** and PCell **330** (e.g., may include all of the cells **305** of base station **105-c**).

(94) Each cell **305** of the second set of cells **320** may belong to a same CU **310** as the target cell **305** (e.g., new PCell). For example, cells **305-h** and **305-j** may belong to the same CU **310**, or all of the cells **305** of base station **105-c** may belong to the same CU **310**. The second set of cells **320** may include cells **305** that belong to a same serving DU, or to different serving DUs.

(95) Based on the measurements requested by the base station **105**, and performed and reported by the UE **115**, the base station **105** may determine an L1/L2 mobility configuration (e.g., a second set of cells **320**, active cells **305** of the second set of cells **320**, candidate PCells **330** of the second set of cells **320**). The base station **105** may include at least some L1/L2 mobility information associated with the L1/L2 mobility configuration in a handover command for the UE **115**. For example, the base station **105** may include an indication of the second set of cells **320** in the handover command.

(96) FIG. 4 illustrates an example of a process flow **400** that supports techniques for providing cell mobility information during handover in accordance with one or more aspects of the present disclosure. In some examples, process flow **400** may implement or be implemented by one or more aspects of wireless communications system **100** or **200**, as well as measurement scheme **300**. For example, process flow **400** may be implemented by a UE **115-c** and a base station **105-d**, which

may be examples of a UE **115** and a base station **105** described with reference to FIGS. **1-3**.

(97) In the following description of process flow **400**, the operations may be performed in a different order than the order shown, or the operations performed by UE **115-e** and base station **105-d** may be performed in different orders or at different times. For example, some operations may also be left out of process flow **400**, or other operations may be added to process flow **400**. In one example, one or more of the indications described herein may be transmitted together, or may be transmitted separately. Although UE **115-e** and base station **105-d** are shown performing the operations of process flow **400**, some aspects of some operations may also be performed by one or more other wireless devices.

(98) At **505**, base station **105-d** may transmit, to UE **115-e**, signaling indicating UE **115-e** is to perform measurements on a first set of cells. For example, as described with reference to FIGS. **2** and **3**, prior to performing a handover (e.g., an L3 handover), base station **105-d** may request measurements on the first set of cells, which measurements may support determination of an L1/L2 mobility configuration that is to be used by UE **115-e** after the handover.

(99) At **510**, UE **115-e** may perform the measurements on the first set of cells. For example, as described with reference to FIG. **3**, UE **115-e** may perform the indicated measurements on the first set of cells. In some cases, if the measurements on the first set of cells satisfy a threshold measurement value, UE **115-e** may perform measurements on a third set of cells associated with a same base station **105** as at least a portion of the first set of cells. In some cases, UE **115-e** may perform joint beam reporting as described herein.

(100) At **515**, UE **115-e** may transmit, to base station **105-d**, an indication of a result of the measurements on the first set of cells. For example, as described with reference to FIGS. **2** and **3**, UE **115-e** may transmit an indication of the result of the measurements, which may be used by base station **105-d** to determine or select a second set of cells for L1/L2 mobility.

(101) At **520**, in some cases, UE **115-e** may transmit, to base station **105-d**, an indication to use a second set of cells for L1/L2 mobility. For example, UE **115-e** may provide a recommendation of cells and beams to use for L1/L2 mobility (e.g., within the first set of cells, based on the measurements). Based on such a recommendation, base station **105-d** may make a handover decision for UE **115-e** that may consider a channel quality of a target PCell, as well as a number of cells and an associated channel quality that may be used for L1/L2 mobility with the target PCell.

(102) At **525**, base station **105-d** may transmit, to UE **115-e**, a handover command that includes an identification of the second set of cells that the UE is to use after completing the handover command for managing active cells using L1 or L2 signaling (e.g., for performing L1/L2 mobility). The handover command may include, for example, a list of the second set of cells (e.g., a list of cells that belong to the cell set for L1/L2 mobility) and a configuration (e.g., RRC configuration) for the second set of cells. The handover command may also include an indication of an activated subset of the second set of cells (e.g., for L1/L2 mobility), to be used for communications with a target base station **105** after completing the handover command.

(103) In some cases, the handover command may include QCL information for beams (e.g., indicative of a set of beams) to be used on the subset of activated cells. In some cases, the handover command may include an indication of a subset of candidate PCells within the second set of cells. For example, the handover command may include a list and a configuration of the subset of candidate PCells in the second set of cells (e.g., set of cells for L1/L2 mobility), where each of the candidate PCells may be activated to be used as a PCell by L1 or L2 signaling. In some cases, the handover command may include an indication of signaling to use for L1 measurements performed on the second set of cells for managing active cells using L1 or L2 signaling (e.g., a measurement configuration for the L1/L2 mobility configuration). For example, the handover command may include an indication of one or more synchronization signal blocks (SSBs) or channel state information reference signals (CSI-RS) to be used for L1 measurements on the cells in the second set of cells.

(104) In some cases, after performing the handover, UE **115-e** may recommend, to the target base station **105**, cells to be activated for L1/L2 mobility, based on the measurements on the first set of cells (e.g., for L1/L2 mobility). In such cases, L1 or L2 signaling may be used to signal the request or recommendation of the cells to be activated, and the target base station **105** may signal an indication of the activation (e.g., an acknowledgement) to UE **115-e**. In some cases, after performing the handover, UE **115-e** may make a decision as to which cells are to be activated for L1/L2 mobility, and may notify the target base station **105** (e.g., via the target cell). Such a decision may be modified by the target base station **105** after receiving the notification from UE **115-e**.

(105) FIG. 5 shows a block diagram **500** of a device **505** that supports techniques for providing cell mobility information during handover in accordance with one or more aspects of the present disclosure. The device **505** may be an example of aspects of a UE **115** as described herein. The device **505** may include a receiver **510**, a transmitter **515**, and a communications manager **520**. The device **505** may also include a processor. Each of these components may be in communication with one another (e.g., via one or more buses).

(106) The receiver **510** may provide a means for receiving information such as packets, user data, control information, or any combination thereof associated with various information channels (e.g., control channels, data channels, information channels related to techniques for providing cell mobility information during handover). Information may be passed on to other components of the device **505**. The receiver **510** may utilize a single antenna or a set of multiple antennas.

(107) The transmitter **515** may provide a means for transmitting signals generated by other components of the device **505**. For example, the transmitter **515** may transmit information such as packets, user data, control information, or any combination thereof associated with various information channels (e.g., control channels, data channels, information channels related to techniques for providing cell mobility information during handover). In some examples, the transmitter **515** may be co-located with a receiver **510** in a transceiver module. The transmitter **515** may utilize a single antenna or a set of multiple antennas.

(108) The communications manager **520**, the receiver **510**, the transmitter **515**, or various combinations thereof or various components thereof may be examples of means for performing various aspects of techniques for providing cell mobility information during handover as described herein. For example, the communications manager **520**, the receiver **510**, the transmitter **515**, or various combinations or components thereof may support a method for performing one or more of the functions described herein.

(109) The communications manager **520** may be an example of means for performing various aspects of cell mobility management as described herein. The communications manager **520**, or its sub-components, may be implemented in hardware (e.g., in communications management circuitry). The circuitry may comprise of processor, digital signal processor (DSP), an application-specific integrated circuit (ASIC), a field programmable gate array (FPGA) or other programmable logic device, discrete gate or transistor logic, discrete hardware components, or any combination thereof designed to perform the functions described in the present disclosure. In some examples, a processor and memory coupled with the processor may be configured to perform one or more of the functions described herein (e.g., by executing, by the processor, instructions stored in the memory).

(110) In another implementation, the communications manager **520**, or its sub-components, may be implemented in code (e.g., as communications management software or firmware) executed by a processor, or any combination thereof. If implemented in code executed by a processor, the functions of the communications manager **520**, or its sub-components may be executed by a general-purpose processor, a DSP, an ASIC, an FPGA or other programmable logic device (e.g., configured as or otherwise supporting a means for performing the functions described in the present disclosure).

(111) In some examples, the communications manager **520** may be configured to perform various operations (e.g., receiving, transmitting) using or otherwise in cooperation with the receiver **510**, the transmitter **515**, or both. For example, the communications manager **520** may receive information from the receiver **510**, send information to the transmitter **515**, or be integrated in combination with the receiver **510**, the transmitter **515**, or both to receive information, transmit information, or perform various other operations as described herein.

(112) The communications manager **520** may support wireless communication at a UE in accordance with examples as disclosed herein. For example, the communications manager **520** may be configured as or otherwise support a means for receiving, from a base station, signaling indicating the UE is to perform a measurement on a first set of cells. The communications manager **520** may be configured as or otherwise support a means for transmitting, to the base station, a first indication associated with the measurement on the first set of cells. The communications manager **520** may be configured as or otherwise support a means for receiving, from the base station and in response to the first indication, an L3 handover command including a second indication of a second set of cells for layer 1 or layer 2 cell mobility that the UE is to use after completing the L3 handover command, the L1 or L2 cell mobility within the second set of cells managed using L1 signaling or L2 signaling.

(113) The communications manager **520** may increase available battery power and communication quality at a wireless device (e.g., a UE **115**) by supporting inclusion of L1/L2 mobility information in an L3 handover command, which may increase communication quality at the wireless device by decreasing latency and increasing reliability. The associated increase in communication quality may result in increased link performance and decreased overhead based on the L1/L2 mobility information. Accordingly, communications manager **520** may save power and increase battery life at a wireless device (e.g., a UE **115**) by strategically increasing a quality of communications at a wireless device (e.g., a UE **115**).

(114) FIG. **6** shows a block diagram **600** of a device **605** that supports techniques for providing cell mobility information during handover in accordance with one or more aspects of the present disclosure. The device **605** may be an example of aspects of a device **505** or a UE **115** as described herein. The device **605** may include a receiver **610**, a transmitter **615**, and a communications manager **620**. The device **605** may also include a processor. Each of these components may be in communication with one another (e.g., via one or more buses).

(115) The receiver **610** may provide a means for receiving information such as packets, user data, control information, or any combination thereof associated with various information channels (e.g., control channels, data channels, information channels related to techniques for providing cell mobility information during handover). Information may be passed on to other components of the device **605**. The receiver **610** may utilize a single antenna or a set of multiple antennas.

(116) The transmitter **615** may provide a means for transmitting signals generated by other components of the device **605**. For example, the transmitter **615** may transmit information such as packets, user data, control information, or any combination thereof associated with various information channels (e.g., control channels, data channels, information channels related to techniques for providing cell mobility information during handover). In some examples, the transmitter **615** may be co-located with a receiver **610** in a transceiver module. The transmitter **615** may utilize a single antenna or a set of multiple antennas.

(117) The device **605**, or various components thereof, may be an example of means for performing various aspects of techniques for providing cell mobility information during handover as described herein. For example, the communications manager **620** may include a cell measurement indication component **625**, a cell measurement reporting component **630**, an L3 handover command reception component **635**, or any combination thereof. The communications manager **620** may be an example of aspects of a communications manager **520** as described herein. In some examples, the communications manager **620**, or various components thereof, may be configured to perform

various operations (e.g., receiving, monitoring, signaling) using or otherwise in cooperation with the receiver **610**, the transmitter **615**, or both. For example, the communications manager **620** may receive information from the receiver **610**, send information to the transmitter **615**, or be integrated in combination with the receiver **610**, the transmitter **615**, or both to receive information, transmit information, or perform various other operations as described herein.

(118) The communications manager **620** may support wireless communication at a UE in accordance with examples as disclosed herein. The cell measurement indication component **625** may be configured as or otherwise support a means for receiving, from a base station, signaling indicating the UE is to perform a measurement on a first set of cells. The cell measurement reporting component **630** may be configured as or otherwise support a means for transmitting, to the base station, a first indication associated with the measurement on the first set of cells. The L3 handover command reception component **635** may be configured as or otherwise support a means for receiving, from the base station and in response to the first indication, an L3 handover command including a second indication of a second set of cells for layer 1 or layer 2 cell mobility that the UE is to use after completing the L3 handover command, the L1 or L2 cell mobility within the second set of cells managed using L1 signaling or L2 signaling.

(119) A processor of a wireless device (e.g., controlling the receiver **610**, the transmitter **615**, or the transceiver **815** as described with reference to FIG. **8**) may increase available battery power and communication quality. The increased communication quality may increase available battery power and throughput (e.g., via implementation of system components described with reference to FIG. **7**) compared to other systems and techniques, for example, that do not support inclusion of L1/L2 mobility information in an L3 handover command. Further, the processor of the wireless device may identify one or more aspects of the L1/L2 mobility information, which may result in increased communication quality, as well as save power and increase battery life at the wireless device (e.g., by strategically decreasing latency and increasing reliability), among other examples.

(120) FIG. **7** shows a block diagram **700** of a communications manager **720** that supports techniques for providing cell mobility information during handover in accordance with one or more aspects of the present disclosure. The communications manager **720** may be an example of aspects of a communications manager **520**, a communications manager **620**, or both, as described herein. The communications manager **720**, or various components thereof, may be an example of means for performing various aspects of techniques for providing cell mobility information during handover as described herein. For example, the communications manager **720** may include a cell measurement indication component **725**, a cell measurement reporting component **730**, an L3 handover command reception component **735**, a cell measurement component **740**, a cell request component **745**, or any combination thereof. Each of these components may communicate, directly or indirectly, with one another (e.g., via one or more buses).

(121) The communications manager **720** may support wireless communication at a UE in accordance with examples as disclosed herein. The cell measurement indication component **725** may be configured as or otherwise support a means for receiving, from a base station, signaling indicating the UE is to perform a measurement on a first set of cells. The cell measurement reporting component **730** may be configured as or otherwise support a means for transmitting, to the base station, a first indication associated with the measurement on the first set of cells. The L3 handover command reception component **735** may be configured as or otherwise support a means for receiving, from the base station and in response to the first indication, an L3 handover command including a second indication of a second set of cells for layer 1 or layer 2 cell mobility that the UE is to use after completing the L3 handover command, the L1 or L2 cell mobility within the second set of cells managed using L1 signaling or L2 signaling.

(122) In some examples, the L3 handover command reception component **735** may be configured as or otherwise support a means for receiving, via the L3 handover command, a third indication of a communication configuration for the second set of cells. In some examples, the L3 handover

command reception component **735** may be configured as or otherwise support a means for receiving, via the L3 handover command, a fourth indication of an activated subset of the second set of cells to be used for communications after completing the L3 handover command. In some examples, the L3 handover command may further include a fifth indication of QCL information indicative of a set of beams to use on the activated subset of the second set of cells.

(123) In some examples, the L3 handover command reception component **735** may be configured as or otherwise support a means for receiving, via the L3 handover command, a sixth indication of a subset of candidate PCells within the second set of cells, the subset of candidate PCells including at least one cell configured to be activated as a PCell via L1 signaling or L2 signaling. In some examples, the L3 handover command reception component **735** may be configured as or otherwise support a means for receiving, via the L3 handover command, a seventh indication of signaling to use for L1 measurements performed on the second set of cells for the L1 or L2 cell mobility. In some examples, each cell in the second set of cells is associated with a same CU as a target cell for the L3 handover command.

(124) In some examples, the cell measurement component **740** may be configured as or otherwise support a means for performing joint beam reporting for the first set of cells, the first set of cells associated with a same base station as a target cell for the L3 handover command. In some examples, the cell measurement reporting component **730** may be configured as or otherwise support a means for transmitting signaling indicating a result of the measurement on the first set of cells based on performing the joint beam reporting.

(125) In some examples, the cell measurement component **740** may be configured as or otherwise support a means for determining that the measurement on the first set of cells satisfies a threshold measurement value. In some examples, the cell measurement component **740** may be configured as or otherwise support a means for performing a second measurement on a third set of cells associated with a same base station as the first set of cells based on determining that the measurement on the first set of cells satisfies the threshold measurement value. In some examples, the measurement on the first set of cells may include a beam measurement associated with L1 signaling and L3 signaling.

(126) In some examples, the cell request component **745** may be configured as or otherwise support a means for transmitting, to the base station, an eighth indication to use the second set of cells for the L1 or L2 cell mobility, the receiving the L3 handover command including the second indication of the second set of cells based on transmitting the eighth indication to use the second set of cells. In some examples, the cell request component **745** may be configured as or otherwise support a means for transmitting, to the base station, a ninth indication of an activated subset of the second set of cells for the L1 or L2 cell mobility, the receiving the L3 handover command including the second indication of the second set of cells based on transmitting the ninth indication of the activated subset of the second set of cells.

(127) FIG. **8** shows a diagram of a system **800** including a device **805** that supports techniques for providing cell mobility information during handover in accordance with one or more aspects of the present disclosure. The device **805** may be an example of or include the components of a device **505**, a device **605**, or a UE **115** as described herein. The device **805** may communicate wirelessly with one or more base stations **105**, UEs **115**, or any combination thereof. The device **805** may include components for bi-directional voice and data communications including components for transmitting and receiving communications, such as a communications manager **820**, an input/output (I/O) controller **810**, a transceiver **815**, an antenna **825**, a memory **830**, code **835**, and a processor **840**. These components may be in electronic communication or otherwise coupled (e.g., operatively, communicatively, functionally, electronically, electrically) via one or more buses (e.g., a bus **845**).

(128) The I/O controller **810** may manage input and output signals for the device **805**. The I/O controller **810** may also manage peripherals not integrated into the device **805**. In some cases, the

I/O controller **810** may represent a physical connection or port to an external peripheral. In some cases, the I/O controller **810** may utilize an operating system such as iOS®, ANDROID®, MS-DOS®, MS-WINDOWS®, OS/2®, UNIX®, LINUX®, or another known operating system. Additionally or alternatively, the I/O controller **810** may represent or interact with a modem, a keyboard, a mouse, a touchscreen, or a similar device. In some cases, the I/O controller **810** may be implemented as part of a processor, such as the processor **840**. In some cases, a user may interact with the device **805** via the I/O controller **810** or via hardware components controlled by the I/O controller **810**.

(129) In some cases, the device **805** may include a single antenna **825**. However, in some other cases, the device **805** may have more than one antenna **825**, which may be capable of concurrently transmitting or receiving multiple wireless transmissions. The transceiver **815** may communicate bi-directionally, via the one or more antennas **825**, wired, or wireless links as described herein. For example, the transceiver **815** may represent a wireless transceiver and may communicate bi-directionally with another wireless transceiver. The transceiver **815** may also include a modem to modulate the packets, to provide the modulated packets to one or more antennas **825** for transmission, and to demodulate packets received from the one or more antennas **825**. The transceiver **815**, or the transceiver **815** and one or more antennas **825**, may be an example of a transmitter **515**, a transmitter **615**, a receiver **510**, a receiver **610**, or any combination thereof or component thereof, as described herein.

(130) The memory **830** may include random access memory (RAM) and read-only memory (ROM). The memory **830** may store computer-readable, computer-executable code **835** including instructions that, when executed by the processor **840**, cause the device **805** to perform various functions described herein. The code **835** may be stored in a non-transitory computer-readable medium such as system memory or another type of memory. In some cases, the code **835** may not be directly executable by the processor **840** but may cause a computer (e.g., when compiled and executed) to perform functions described herein. In some cases, the memory **830** may contain, among other things, a basic I/O system (BIOS) which may control basic hardware or software operation such as the interaction with peripheral components or devices.

(131) The processor **840** may include an intelligent hardware device (e.g., a general-purpose processor, a DSP, a CPU, a microcontroller, an ASIC, an FPGA, a programmable logic device, a discrete gate or transistor logic component, a discrete hardware component, or any combination thereof). In some cases, the processor **840** may be configured to operate a memory array using a memory controller. In some other cases, a memory controller may be integrated into the processor **840**. The processor **840** may be configured to execute computer-readable instructions stored in a memory (e.g., the memory **830**) to cause the device **805** to perform various functions (e.g., functions or tasks supporting techniques for providing cell mobility information during handover). For example, the device **805** or a component of the device **805** may include a processor **840** and memory **830** coupled to the processor **840**, the processor **840** and memory **830** configured to perform various functions described herein.

(132) The communications manager **820** may support wireless communication at a UE in accordance with examples as disclosed herein. For example, the communications manager **820** may be configured as or otherwise support a means for receiving, from a base station, signaling indicating the UE is to perform a measurement on a first set of cells. The communications manager **820** may be configured as or otherwise support a means for transmitting, to the base station, a first indication associated with the measurement on the first set of cells. The communications manager **820** may be configured as or otherwise support a means for receiving, from the base station and in response to the first indication, an L3 handover command including a second indication of a second set of cells for layer 1 or layer 2 cell mobility that the UE is to use after completing the L3 handover command, the L1 or L2 cell mobility within the second set of cells managed using L1 signaling or L2 signaling.

(133) In some examples, the communications manager **820** may be configured to perform various operations (e.g., receiving, monitoring, transmitting) using or otherwise in cooperation with the transceiver **815**, the one or more antennas **825**, or any combination thereof. Although the communications manager **820** is illustrated as a separate component, in some examples, one or more functions described with reference to the communications manager **820** may be supported by or performed by the processor **840**, the memory **830**, the code **835**, or any combination thereof. For example, the code **835** may include instructions executable by the processor **840** to cause the device **805** to perform various aspects of techniques for providing cell mobility information during handover as described herein, or the processor **840** and the memory **830** may be otherwise configured to perform or support such operations.

(134) FIG. **9** shows a block diagram **900** of a device **905** that supports techniques for providing cell mobility information during handover in accordance with one or more aspects of the present disclosure. The device **905** may be an example of aspects of a base station **105** as described herein. The device **905** may include a receiver **910**, a transmitter **915**, and a communications manager **920**. The device **905** may also include a processor. Each of these components may be in communication with one another (e.g., via one or more buses).

(135) The receiver **910** may provide a means for receiving information such as packets, user data, control information, or any combination thereof associated with various information channels (e.g., control channels, data channels, information channels related to techniques for providing cell mobility information during handover). Information may be passed on to other components of the device **905**. The receiver **910** may utilize a single antenna or a set of multiple antennas.

(136) The transmitter **915** may provide a means for transmitting signals generated by other components of the device **905**. For example, the transmitter **915** may transmit information such as packets, user data, control information, or any combination thereof associated with various information channels (e.g., control channels, data channels, information channels related to techniques for providing cell mobility information during handover). In some examples, the transmitter **915** may be co-located with a receiver **910** in a transceiver module. The transmitter **915** may utilize a single antenna or a set of multiple antennas.

(137) The communications manager **920**, the receiver **910**, the transmitter **915**, or various combinations thereof or various components thereof may be examples of means for performing various aspects of techniques for providing cell mobility information during handover as described herein. For example, the communications manager **920**, the receiver **910**, the transmitter **915**, or various combinations or components thereof may support a method for performing one or more of the functions described herein.

(138) The communications manager **920** may be an example of means for performing various aspects of cell mobility management as described herein. The communications manager **920**, or its sub-components, may be implemented in hardware (e.g., in communications management circuitry). The circuitry may comprise of processor, DSP, an ASIC, an FPGA or other programmable logic device, discrete gate or transistor logic, discrete hardware components, or any combination thereof designed to perform the functions described in the present disclosure. In some examples, a processor and memory coupled with the processor may be configured to perform one or more of the functions described herein (e.g., by executing, by the processor, instructions stored in the memory).

(139) In another implementation, the communications manager **920**, or its sub-components, may be implemented in code (e.g., as communications management software or firmware) executed by a processor, or any combination thereof. If implemented in code executed by a processor, the functions of the communications manager **920**, or its sub-components may be executed by a general-purpose processor, a DSP, an ASIC, an FPGA or other programmable logic device (e.g., configured as or otherwise supporting a means for performing the functions described in the present disclosure).

(140) In some examples, the communications manager **920** may be configured to perform various operations (e.g., receiving, monitoring, transmitting) using or otherwise in cooperation with the receiver **910**, the transmitter **915**, or both. For example, the communications manager **920** may receive information from the receiver **910**, send information to the transmitter **915**, or be integrated in combination with the receiver **910**, the transmitter **915**, or both to receive information, transmit information, or perform various other operations as described herein.

(141) The communications manager **920** may support wireless communication at a base station in accordance with examples as disclosed herein. For example, the communications manager **920** may be configured as or otherwise support a means for transmitting, to a UE, signaling indicating the UE is to perform a measurement on a first set of cells. The communications manager **920** may be configured as or otherwise support a means for receiving, from the UE, a first indication associated with the measurement on the first set of cells. The communications manager **920** may be configured as or otherwise support a means for transmitting, to the UE and in response to the first indication, an L3 handover command including a second indication of a second set of cells for layer 1 or layer 2 cell mobility that the UE is to use after completing the L3 handover command, the L1 or L2 cell mobility within the second set of cells managed using L1 signaling or L2 signaling.

(142) FIG. **10** shows a block diagram **1000** of a device **1005** that supports techniques for providing cell mobility information during handover in accordance with one or more aspects of the present disclosure. The device **1005** may be an example of aspects of a device **905** or a base station **105** as described herein. The device **1005** may include a receiver **1010**, a transmitter **1015**, and a communications manager **1020**. The device **1005** may also include a processor. Each of these components may be in communication with one another (e.g., via one or more buses).

(143) The receiver **1010** may provide a means for receiving information such as packets, user data, control information, or any combination thereof associated with various information channels (e.g., control channels, data channels, information channels related to techniques for providing cell mobility information during handover). Information may be passed on to other components of the device **1005**. The receiver **1010** may utilize a single antenna or a set of multiple antennas.

(144) The transmitter **1015** may provide a means for transmitting signals generated by other components of the device **1005**. For example, the transmitter **1015** may transmit information such as packets, user data, control information, or any combination thereof associated with various information channels (e.g., control channels, data channels, information channels related to techniques for providing cell mobility information during handover). In some examples, the transmitter **1015** may be co-located with a receiver **1010** in a transceiver module. The transmitter **1015** may utilize a single antenna or a set of multiple antennas.

(145) The device **1005**, or various components thereof, may be an example of means for performing various aspects of techniques for providing cell mobility information during handover as described herein. For example, the communications manager **1020** may include a cell measurement indication component **1025**, a cell measurement reception component **1030**, an L3 handover command transmission component **1035**, or any combination thereof. The communications manager **1020** may be an example of aspects of a communications manager **920** as described herein. In some examples, the communications manager **1020**, or various components thereof, may be configured to perform various operations (e.g., receiving, monitoring, transmitting) using or otherwise in cooperation with the receiver **1010**, the transmitter **1015**, or both. For example, the communications manager **1020** may receive information from the receiver **1010**, send information to the transmitter **1015**, or be integrated in combination with the receiver **1010**, the transmitter **1015**, or both to receive information, transmit information, or perform various other operations as described herein.

(146) The communications manager **1020** may support wireless communication at a base station in accordance with examples as disclosed herein. The cell measurement indication component **1025**

may be configured as or otherwise support a means for transmitting, to a UE, signaling indicating the UE is to perform a measurement on a first set of cells. The cell measurement reception component **1030** may be configured as or otherwise support a means for receiving, from the UE, a first indication associated with the measurement on the first set of cells. The L3 handover command transmission component **1035** may be configured as or otherwise support a means for transmitting, to the UE and in response to the first indication, an L3 handover command including a second indication of a second set of cells for layer 1 or layer 2 cell mobility that the UE is to use after completing the L3 handover command, the L1 or L2 cell mobility within the second set of cells managed using L1 signaling or L2 signaling.

(147) FIG. **11** shows a block diagram **1100** of a communications manager **1120** that supports techniques for providing cell mobility information during handover in accordance with one or more aspects of the present disclosure. The communications manager **1120** may be an example of aspects of a communications manager **920**, a communications manager **1020**, or both, as described herein. The communications manager **1120**, or various components thereof, may be an example of means for performing various aspects of techniques for providing cell mobility information during handover as described herein. For example, the communications manager **1120** may include a cell measurement indication component **1125**, a cell measurement reception component **1130**, an L3 handover command transmission component **1135**, a cell request reception component **1140**, or any combination thereof. Each of these components may communicate, directly or indirectly, with one another (e.g., via one or more buses).

(148) The communications manager **1120** may support wireless communication at a base station in accordance with examples as disclosed herein. The cell measurement indication component **1125** may be configured as or otherwise support a means for transmitting, to a UE, signaling indicating the UE is to perform a measurement on a first set of cells. The cell measurement reception component **1130** may be configured as or otherwise support a means for receiving, from the UE, a first indication associated with the measurement on the first set of cells. The L3 handover command transmission component **1135** may be configured as or otherwise support a means for transmitting, to the UE and in response to the first indication, an L3 handover command including a second indication of a second set of cells for layer 1 or layer 2 cell mobility that the UE is to use after completing the L3 handover command, the L1 or L2 cell mobility within the second set of cells managed using L1 signaling or L2 signaling.

(149) In some examples, the L3 handover command transmission component **1135** may be configured as or otherwise support a means for transmitting, via the L3 handover command, a third indication of a communication configuration for the second set of cells. In some examples, the L3 handover command transmission component **1135** may be configured as or otherwise support a means for transmitting, via the L3 handover command, a fourth indication of an activated subset of the second set of cells to be used for communications after completing the L3 handover command. In some examples, the L3 handover command further includes a fifth indication of QCL information indicative of a set of beams to use on the activated subset of the second set of cells.

(150) In some examples, the L3 handover command transmission component **1135** may be configured as or otherwise support a means for transmitting, via the L3 handover command, a sixth indication of a subset of candidate PCells within the second set of cells, the subset of candidate PCells including at least one cell configured to be activated as a PCell via L1 signaling or L2 signaling. In some examples, the L3 handover command transmission component **1135** may be configured as or otherwise support a means for transmitting, via the L3 handover command, a seventh indication of signaling to use for L1 measurements performed on the second set of cells for the L1 or L2 cell mobility. In some examples, each cell in the second set of cells is associated with a same CU as a target cell for the L3 handover command.

(151) In some examples, the cell measurement reception component **1130** may be configured as or otherwise support a means for receiving signaling indicating a result of the measurement on the

first set of cells associated with joint beam reporting for the first set of cells, the first set of cells associated with a same base station as a target cell for the L3 handover command.

(152) In some examples, the cell measurement indication component **1125** may be configured as or otherwise support a means for transmitting an indication for the UE to perform a second measurement on a third set of cells associated with a same base station as the first set of cells based on determining that the measurement on the first set of cells satisfies a threshold measurement value. In some examples, the measurement on the first set of cells includes a beam measurement associated with L1 signaling and L3 signaling.

(153) In some examples, the cell request reception component **1140** may be configured as or otherwise support a means for receiving, from the UE, an eighth indication to use the second set of cells for the L1 or L2 cell mobility, the transmitting the L3 handover command including the second indication of the second set of cells based on receiving the eighth indication to use the second set of cells. In some examples, the cell request reception component **1140** may be configured as or otherwise support a means for receiving, from the UE, a ninth indication of an activated subset of the second set of cells for the L1 or L2 cell mobility, the transmitting the L3 handover command including the second indication of the second set of cells based on receiving the ninth indication of the activated subset of the second set of cells.

(154) FIG. 12 shows a diagram of a system **1200** including a device **1205** that supports techniques for providing cell mobility information during handover in accordance with one or more aspects of the present disclosure. The device **1205** may be an example of or include the components of a device **905**, a device **1005**, or a base station **105** as described herein. The device **1205** may communicate wirelessly with one or more base stations **105**, UEs **115**, or any combination thereof. The device **1205** may include components for bi-directional voice and data communications including components for transmitting and receiving communications, such as a communications manager **1220**, a network communications manager **1210**, a transceiver **1215**, an antenna **1225**, a memory **1230**, code **1235**, a processor **1240**, and an inter-station communications manager **1245**. These components may be in electronic communication or otherwise coupled (e.g., operatively, communicatively, functionally, electronically, electrically) via one or more buses (e.g., a bus **1250**).

(155) The network communications manager **1210** may manage communications with a core network **130** (e.g., via one or more wired backhaul links). For example, the network communications manager **1210** may manage the transfer of data communications for client devices, such as one or more UEs **115**.

(156) In some cases, the device **1205** may include a single antenna **1225**. However, in some other cases the device **1205** may have more than one antenna **1225**, which may be capable of concurrently transmitting or receiving multiple wireless transmissions. The transceiver **1215** may communicate bi-directionally, via the one or more antennas **1225**, wired, or wireless links as described herein. For example, the transceiver **1215** may represent a wireless transceiver and may communicate bi-directionally with another wireless transceiver. The transceiver **1215** may also include a modem to modulate the packets, to provide the modulated packets to one or more antennas **1225** for transmission, and to demodulate packets received from the one or more antennas **1225**. The transceiver **1215**, or the transceiver **1215** and one or more antennas **1225**, may be an example of a transmitter **915**, a transmitter **1015**, a receiver **910**, a receiver **1010**, or any combination thereof or component thereof, as described herein.

(157) The memory **1230** may include RAM and ROM. The memory **1230** may store computer-readable, computer-executable code **1235** including instructions that, when executed by the processor **1240**, cause the device **1205** to perform various functions described herein. The code **1235** may be stored in a non-transitory computer-readable medium such as system memory or another type of memory. In some cases, the code **1235** may not be directly executable by the processor **1240** but may cause a computer (e.g., when compiled and executed) to perform functions described herein. In some cases, the memory **1230** may contain, among other things, a BIOS which

may control basic hardware or software operation such as the interaction with peripheral components or devices.

(158) The processor **1240** may include an intelligent hardware device (e.g., a general-purpose processor, a DSP, a CPU, a microcontroller, an ASIC, an FPGA, a programmable logic device, a discrete gate or transistor logic component, a discrete hardware component, or any combination thereof). In some cases, the processor **1240** may be configured to operate a memory array using a memory controller. In some other cases, a memory controller may be integrated into the processor **1240**. The processor **1240** may be configured to execute computer-readable instructions stored in a memory (e.g., the memory **1230**) to cause the device **1205** to perform various functions (e.g., functions or tasks supporting techniques for providing cell mobility information during handover). For example, the device **1205** or a component of the device **1205** may include a processor **1240** and memory **1230** coupled to the processor **1240**, the processor **1240** and memory **1230** configured to perform various functions described herein.

(159) The inter-station communications manager **1245** may manage communications with other base stations **105**, and may include a controller or scheduler for controlling communications with UEs **115** in cooperation with other base stations **105**. For example, the inter-station communications manager **1245** may coordinate scheduling for transmissions to UEs **115** for various interference mitigation techniques such as beamforming or joint transmission. In some examples, the inter-station communications manager **1245** may provide an X2 interface within an LTE/LTE-A wireless communications network technology to provide communication between base stations **105**.

(160) The communications manager **1220** may support wireless communication at a base station in accordance with examples as disclosed herein. For example, the communications manager **1220** may be configured as or otherwise support a means for transmitting, to a UE, signaling indicating the UE is to perform a measurement on a first set of cells. The communications manager **1220** may be configured as or otherwise support a means for receiving, from the UE, a first indication associated with the measurement on the first set of cells. The communications manager **1220** may be configured as or otherwise support a means for transmitting, to the UE and in response to the first indication, an L3 handover command including a second indication of a second set of cells for layer 1 or layer 2 cell mobility that the UE is to use after completing the L3 handover command, the L1 or L2 cell mobility within the second set of cells managed using L1 signaling or L2 signaling.

(161) In some examples, the communications manager **1220** may be configured to perform various operations (e.g., receiving, monitoring, transmitting) using or otherwise in cooperation with the transceiver **1215**, the one or more antennas **1225**, or any combination thereof. Although the communications manager **1220** is illustrated as a separate component, in some examples, one or more functions described with reference to the communications manager **1220** may be supported by or performed by the processor **1240**, the memory **1230**, the code **1235**, or any combination thereof. For example, the code **1235** may include instructions executable by the processor **1240** to cause the device **1205** to perform various aspects of techniques for providing cell mobility information during handover as described herein, or the processor **1240** and the memory **1230** may be otherwise configured to perform or support such operations.

(162) FIG. **13** shows a flowchart illustrating a method **1300** that supports techniques for providing cell mobility information during handover in accordance with one or more aspects of the present disclosure. The operations of the method **1300** may be implemented by a UE or its components as described herein. For example, the operations of the method **1300** may be performed by a UE **115** as described with reference to FIGS. **1** through **8**. In some examples, a UE may execute a set of instructions to control the functional elements of the UE to perform the described functions. Additionally or alternatively, the UE may perform aspects of the described functions using special-purpose hardware.

(163) At **1305**, the method may include receiving, from a base station, signaling indicating the UE is to perform a measurement on a first set of cells. The operations of **1305** may be performed in accordance with examples as disclosed herein. In some examples, aspects of the operations of **1305** may be performed by a cell measurement indication component **725** as described with reference to FIG. 7.

(164) At **1310**, the method may include transmitting, to the base station, a first indication associated with the measurement on the first set of cells. The operations of **1310** may be performed in accordance with examples as disclosed herein. In some examples, aspects of the operations of **1310** may be performed by a cell measurement reporting component **730** as described with reference to FIG. 7.

(165) At **1315**, the method may include receiving, from the base station and in response to the first indication, an L3 handover command including a second indication of a second set of cells for layer 1 or layer 2 cell mobility that the UE is to use after completing the L3 handover command, the L1 or L2 cell mobility within the second set of cells managed using L1 signaling or L2 signaling. The operations of **1315** may be performed in accordance with examples as disclosed herein. In some examples, aspects of the operations of **1315** may be performed by an L3 handover command reception component **735** as described with reference to FIG. 7.

(166) FIG. **14** shows a flowchart illustrating a method **1400** that supports techniques for providing cell mobility information during handover in accordance with one or more aspects of the present disclosure. The operations of the method **1400** may be implemented by a UE or its components as described herein. For example, the operations of the method **1400** may be performed by a UE **115** as described with reference to FIGS. **1** through **8**. In some examples, a UE may execute a set of instructions to control the functional elements of the UE to perform the described functions. Additionally or alternatively, the UE may perform aspects of the described functions using special-purpose hardware.

(167) At **1405**, the method may include receiving, from a base station, signaling indicating the UE is to perform a measurement on a first set of cells. The operations of **1405** may be performed in accordance with examples as disclosed herein. In some examples, aspects of the operations of **1405** may be performed by a cell measurement indication component **725** as described with reference to FIG. 7.

(168) At **1410**, the method may include transmitting, to the base station, a first indication associated with the measurement on the first set of cells. The operations of **1410** may be performed in accordance with examples as disclosed herein. In some examples, aspects of the operations of **1410** may be performed by a cell measurement reporting component **730** as described with reference to FIG. 7.

(169) At **1415**, the method may include receiving, from the base station and in response to the first indication, an L3 handover command including a second indication of a second set of cells for layer 1 or layer 2 cell mobility that the UE is to use after completing the L3 handover command, the L1 or L2 cell mobility within the second set of cells managed using L1 signaling or L2 signaling. The operations of **1415** may be performed in accordance with examples as disclosed herein. In some examples, aspects of the operations of **1415** may be performed by an L3 handover command reception component **735** as described with reference to FIG. 7.

(170) At **1420**, the method may include receiving, via the L3 handover command, a fourth indication of an activated subset of the second set of cells to be used for communications after completing the L3 handover command. The operations of **1420** may be performed in accordance with examples as disclosed herein. In some examples, aspects of the operations of **1420** may be performed by an L3 handover command reception component **735** as described with reference to FIG. 7.

(171) FIG. **15** shows a flowchart illustrating a method **1500** that supports techniques for providing cell mobility information during handover in accordance with one or more aspects of the present

disclosure. The operations of the method **1500** may be implemented by a base station or its components as described herein. For example, the operations of the method **1500** may be performed by a base station **105** as described with reference to FIGS. **1** through **4** and **9** through **12**. In some examples, a base station may execute a set of instructions to control the functional elements of the base station to perform the described functions. Additionally or alternatively, the base station may perform aspects of the described functions using special-purpose hardware.

(172) At **1505**, the method may include transmitting, to a UE, signaling indicating the UE is to perform a measurement on a first set of cells. The operations of **1505** may be performed in accordance with examples as disclosed herein. In some examples, aspects of the operations of **1505** may be performed by a cell measurement indication component **1125** as described with reference to FIG. **11**.

(173) At **1510**, the method may include receiving, from the UE, a first indication associated with the measurement on the first set of cells. The operations of **1510** may be performed in accordance with examples as disclosed herein. In some examples, aspects of the operations of **1510** may be performed by a cell measurement reception component **1130** as described with reference to FIG. **11**.

(174) At **1515**, the method may include transmitting, to the UE and in response to the first indication, an L3 handover command including a second indication of a second set of cells for layer 1 or layer 2 cell mobility that the UE is to use after completing the L3 handover command, the L1 or L2 cell mobility within the second set of cells managed using L1 signaling or L2 signaling. The operations of **1515** may be performed in accordance with examples as disclosed herein. In some examples, aspects of the operations of **1515** may be performed by an L3 handover command transmission component **1135** as described with reference to FIG. **11**.

(175) FIG. **16** shows a flowchart illustrating a method **1600** that supports techniques for providing cell mobility information during handover in accordance with one or more aspects of the present disclosure. The operations of the method **1600** may be implemented by a base station or its components as described herein. For example, the operations of the method **1600** may be performed by a base station **105** as described with reference to FIGS. **1** through **4** and **9** through **12**. In some examples, a base station may execute a set of instructions to control the functional elements of the base station to perform the described functions. Additionally or alternatively, the base station may perform aspects of the described functions using special-purpose hardware.

(176) At **1605**, the method may include transmitting, to a UE, signaling indicating the UE is to perform a measurement on a first set of cells. The operations of **1605** may be performed in accordance with examples as disclosed herein. In some examples, aspects of the operations of **1605** may be performed by a cell measurement indication component **1125** as described with reference to FIG. **11**.

(177) At **1610**, the method may include receiving, from the UE, a first indication associated with the measurement on the first set of cells. The operations of **1610** may be performed in accordance with examples as disclosed herein. In some examples, aspects of the operations of **1610** may be performed by a cell measurement reception component **1130** as described with reference to FIG. **11**.

(178) At **1615**, the method may include transmitting, to the UE and in response to the first indication, an L3 handover command including a second indication of a second set of cells for layer 1 or layer 2 cell mobility that the UE is to use after completing the L3 handover command, the L1 or L2 cell mobility within the second set of cells managed using L1 signaling or L2 signaling. The operations of **1615** may be performed in accordance with examples as disclosed herein. In some examples, aspects of the operations of **1615** may be performed by an L3 handover command transmission component **1135** as described with reference to FIG. **11**.

(179) At **1620**, the method may include transmitting, via the L3 handover command, a fourth indication of an activated subset of the second set of cells to be used for communications after

completing the L3 handover command. The operations of **1620** may be performed in accordance with examples as disclosed herein. In some examples, aspects of the operations of **1620** may be performed by an L3 handover command transmission component **1135** as described with reference to FIG. **11**.

(180) The following provides an overview of aspects of the present disclosure:

(181) Aspect 1: A method for wireless communication at a UE, comprising: receiving, from a base station, signaling indicating the UE is to perform a measurement on a first set of cells; transmitting, to the base station, a first indication associated with the measurement on the first set of cells; and receiving, from the base station and in response to the first indication, a L3 handover command including a second indication of a second set of cells for L1 or L2 cell mobility that the UE is to use after completing the L3 handover command, the L1 or L2 cell mobility within the second set of cells managed using L1 signaling or L2 signaling.

(182) Aspect 2: The method of aspect 1, the receiving the L3 handover command comprising: receiving, via the L3 handover command, a third indication of a communication configuration for the second set of cells.

(183) Aspect 3: The method of any of aspects 1 through 2, the receiving the L3 handover command comprising: receiving, via the L3 handover command, a fourth indication of an activated subset of the second set of cells to be used for communications after completing the L3 handover command.

(184) Aspect 4: The method of aspect 3, the L3 handover command further comprising a fifth indication of QCL information indicative of a set of beams to use on the activated subset of the second set of cells.

(185) Aspect 5: The method of any of aspects 1 through 4, the receiving the L3 handover command comprising: receiving, via the L3 handover command, a sixth indication of a subset of candidate PCells within the second set of cells, the subset of candidate PCells comprising at least one cell configured to be activated as a PCell via L1 signaling or L2 signaling.

(186) Aspect 6: The method of any of aspects 1 through 5, the receiving the L3 handover command comprising: receiving, via the L3 handover command, a seventh indication of signaling to use for L1 measurements performed on the second set of cells for the L1 or L2 cell mobility.

(187) Aspect 7: The method of any of aspects 1 through 6, wherein each cell in the second set of cells is associated with a same CU as a target cell for the L3 handover command.

(188) Aspect 8: The method of any of aspects 1 through 7, further comprising: performing joint beam reporting for the first set of cells, the first set of cells associated with a same base station as a target cell for the L3 handover command; and transmitting signaling indicating a result of the measurement on the first set of cells based at least in part on performing the joint beam reporting.

(189) Aspect 9: The method of any of aspects 1 through 8, further comprising: determining that the measurement on the first set of cells satisfies a threshold measurement value; and performing a second measurement on a third set of cells associated with a same base station as the first set of cells based at least in part on determining that the measurement on the first set of cells satisfies the threshold measurement value.

(190) Aspect 10: The method of any of aspects 1 through 9, the measurement on the first set of cells comprising a beam measurement associated with L1 signaling and L3 signaling.

(191) Aspect 11: The method of any of aspects 1 through 10, further comprising: transmitting, to the base station, an eighth indication to use the second set of cells for the L1 or L2 cell mobility, the receiving the L3 handover command comprising the second indication of the second set of cells based at least in part on transmitting the eighth indication to use the second set of cells.

(192) Aspect 12: The method of any of aspects 1 through 11, further comprising: transmitting, to the base station, a ninth indication of an activated subset of the second set of cells for the L1 or L2 cell mobility, the receiving the L3 handover command comprising the second indication of the second set of cells based at least in part on transmitting the ninth indication of the activated subset of the second set of cells.

(193) Aspect 13: A method for wireless communication at a base station, comprising: transmitting, to a UE, signaling indicating the UE is to perform a measurement on a first set of cells; receiving, from the UE, a first indication associated with the measurement on the first set of cells; and transmitting, to the UE and in response to the first indication, a L3 handover command including a second indication of a second set of cells for L1 or L2 cell mobility that the UE is to use after completing the L3 handover command, the L1 or L2 cell mobility within the second set of cells managed using L1 signaling or L2 signaling.

(194) Aspect 14: The method of aspect 13, the transmitting the L3 handover command comprising: transmitting, via the L3 handover command, a third indication of a communication configuration for the second set of cells.

(195) Aspect 15: The method of any of aspects 13 through 14, the transmitting the L3 handover command comprising: transmitting, via the L3 handover command, a fourth indication of an activated subset of the second set of cells to be used for communications after completing the L3 handover command.

(196) Aspect 16: The method of aspect 15, the L3 handover command further comprising a fifth indication of QCL information indicative of a set of beams to use on the activated subset of the second set of cells.

(197) Aspect 17: The method of any of aspects 13 through 16, the transmitting the L3 handover command comprising: transmitting, via the L3 handover command, a sixth indication of a subset of candidate PCells within the second set of cells, the subset of candidate PCells comprising at least one cell configured to be activated as a PCell via L1 signaling or L2 signaling.

(198) Aspect 18: The method of any of aspects 13 through 17, the transmitting the L3 handover command comprising: transmitting, via the L3 handover command, a seventh indication of signaling to use for L1 measurements performed on the second set of cells for the L1 or L2 cell mobility.

(199) Aspect 19: The method of any of aspects 13 through 18, wherein each cell in the second set of cells is associated with a same CU as a target cell for the L3 handover command.

(200) Aspect 20: The method of any of aspects 13 through 19, further comprising: receiving signaling indicating a result of the measurement on the first set of cells associated with joint beam reporting for the first set of cells, the first set of cells associated with a same base station as a target cell for the L3 handover command.

(201) Aspect 21: The method of any of aspects 13 through 20, the transmitting the signaling indicating the UE is to perform the measurement on the first set of cells comprising: transmitting an indication for the UE to perform a second measurement on a third set of cells associated with a same base station as the first set of cells based at least in part on determining that the measurement on the first set of cells satisfies a threshold measurement value.

(202) Aspect 22: The method of any of aspects 13 through 21, the measurement on the first set of cells comprising a beam measurement associated with L1 signaling and L3 signaling.

(203) Aspect 23: The method of any of aspects 13 through 22, further comprising: receiving, from the UE, an eighth indication to use the second set of cells for the L1 or L2 cell mobility, the transmitting the L3 handover command comprising the second indication of the second set of cells based at least in part on receiving the eighth indication to use the second set of cells.

(204) Aspect 24: The method of any of aspects 13 through 23, further comprising: receiving, from the UE, a ninth indication of an activated subset of the second set of cells for the L1 or L2 cell mobility, the transmitting the L3 handover command comprising the second indication of the second set of cells based at least in part on receiving the ninth indication of the activated subset of the second set of cells.

(205) Aspect 25: An apparatus for wireless communication at a UE, comprising a processor; and memory coupled to the processor, the processor and memory configured to cause the apparatus to perform a method of any of aspects 1 through 12.

(206) Aspect 26: An apparatus for wireless communication at a UE, comprising at least one means for performing a method of any of aspects 1 through 12.

(207) Aspect 27: A non-transitory computer-readable medium storing code for wireless communication at a UE, the code comprising instructions executable by a processor to perform a method of any of aspects 1 through 12.

(208) Aspect 28: An apparatus for wireless communication at a base station, comprising a processor; and memory coupled to the processor, the processor and memory configured to cause the apparatus to perform a method of any of aspects 13 through 24.

(209) Aspect 29: An apparatus for wireless communication at a base station, comprising at least one means for performing a method of any of aspects 13 through 24.

(210) Aspect 30: A non-transitory computer-readable medium storing code for wireless communication at a base station, the code comprising instructions executable by a processor to perform a method of any of aspects 13 through 24.

(211) It should be noted that the methods described herein describe possible implementations, and that the operations and the steps may be rearranged or otherwise modified and that other implementations are possible. Further, aspects from two or more of the methods may be combined.

(212) Although aspects of an LTE, LTE-A, LTE-A Pro, or NR system may be described for purposes of example, and LTE, LTE-A, LTE-A Pro, or NR terminology may be used in much of the description, the techniques described herein are applicable beyond LTE, LTE-A, LTE-A Pro, or NR networks. For example, the described techniques may be applicable to various other wireless communications systems such as Ultra Mobile Broadband (UMB), Institute of Electrical and Electronics Engineers (IEEE) 802.11 (Wi-Fi), IEEE 802.16 (WiMAX), IEEE 802.20, Flash-OFDM, as well as other systems and radio technologies not explicitly mentioned herein.

(213) Information and signals described herein may be represented using any of a variety of different technologies and techniques. For example, data, instructions, commands, information, signals, bits, symbols, and chips that may be referenced throughout the description may be represented by voltages, currents, electromagnetic waves, magnetic fields or particles, optical fields or particles, or any combination thereof.

(214) The various illustrative blocks and components described in connection with the disclosure herein may be implemented or performed with a general-purpose processor, a DSP, an ASIC, a CPU, an FPGA or other programmable logic device, discrete gate or transistor logic, discrete hardware components, or any combination thereof designed to perform the functions described herein. A general-purpose processor may be a microprocessor, but in the alternative, the processor may be any processor, controller, microcontroller, or state machine. A processor may also be implemented as a combination of computing devices (e.g., a combination of a DSP and a microprocessor, multiple microprocessors, one or more microprocessors in conjunction with a DSP core, or any other such configuration).

(215) The functions described herein may be implemented in hardware, software executed by a processor, firmware, or any combination thereof. If implemented in software executed by a processor, the functions may be stored on or transmitted over as one or more instructions or code on a computer-readable medium. Other examples and implementations are within the scope of the disclosure and appended claims. For example, due to the nature of software, functions described herein may be implemented using software executed by a processor, hardware, firmware, hardwiring, or combinations of any of these. Features implementing functions may also be physically located at various positions, including being distributed such that portions of functions are implemented at different physical locations.

(216) Computer-readable media includes both non-transitory computer storage media and communication media including any medium that facilitates transfer of a computer program from one place to another. A non-transitory storage medium may be any available medium that may be accessed by a general-purpose or special-purpose computer. By way of example, and not limitation,

non-transitory computer-readable media may include RAM, ROM, electrically erasable programmable ROM (EEPROM), flash memory, compact disk (CD) ROM or other optical disk storage, magnetic disk storage or other magnetic storage devices, or any other non-transitory medium that may be used to carry or store desired program code means in the form of instructions or data structures and that may be accessed by a general-purpose or special-purpose computer, or a general-purpose or special-purpose processor. Also, any connection is properly termed a computer-readable medium. For example, if the software is transmitted from a website, server, or other remote source using a coaxial cable, fiber optic cable, twisted pair, digital subscriber line (DSL), or wireless technologies such as infrared, radio, and microwave, then the coaxial cable, fiber optic cable, twisted pair, DSL, or wireless technologies such as infrared, radio, and microwave are included in the definition of computer-readable medium. Disk and disc, as used herein, include CD, laser disc, optical disc, digital versatile disc (DVD), floppy disk and Blu-ray disc where disks usually reproduce data magnetically, while discs reproduce data optically with lasers.

Combinations of the above are also included within the scope of computer-readable media.

(217) As used herein, including in the claims, “or” as used in a list of items (e.g., a list of items prefaced by a phrase such as “at least one of” or “one or more of”) indicates an inclusive list such that, for example, a list of at least one of A, B, or C means A or B or C or AB or AC or BC or ABC (i.e., A and B and C). Also, as used herein, the phrase “based on” shall not be construed as a reference to a closed set of conditions. For example, an example step that is described as “based on condition A” may be based on both a condition A and a condition B without departing from the scope of the present disclosure. In other words, as used herein, the phrase “based on” shall be construed in the same manner as the phrase “based at least in part on.”

(218) The term “determine” or “determining” encompasses a wide variety of actions and, therefore, “determining” can include calculating, computing, processing, deriving, investigating, looking up (such as via looking up in a table, a database or another data structure), ascertaining and the like. Also, “determining” can include receiving (such as receiving information), accessing (such as accessing data in a memory) and the like. Also, “determining” can include resolving, selecting, choosing, establishing and other such similar actions.

(219) In the appended figures, similar components or features may have the same reference label. Further, various components of the same type may be distinguished by following the reference label by a dash and a second label that distinguishes among the similar components. If just the first reference label is used in the specification, the description is applicable to any one of the similar components having the same first reference label irrespective of the second reference label, or other subsequent reference label.

(220) The description set forth herein, in connection with the appended drawings, describes example configurations and does not represent all the examples that may be implemented or that are within the scope of the claims. The term “example” used herein means “serving as an example, instance, or illustration,” and not “preferred” or “advantageous over other examples.” The detailed description includes specific details for the purpose of providing an understanding of the described techniques. These techniques, however, may be practiced without these specific details. In some instances, known structures and devices are shown in block diagram form in order to avoid obscuring the concepts of the described examples.

(221) The description herein is provided to enable a person having ordinary skill in the art to make or use the disclosure. Various modifications to the disclosure will be apparent to a person having ordinary skill in the art, and the generic principles defined herein may be applied to other variations without departing from the scope of the disclosure. Thus, the disclosure is not limited to the examples and designs described herein but is to be accorded the broadest scope consistent with the principles and novel features disclosed herein.

Claims

1. An apparatus for wireless communication at a user equipment (UE), comprising: one or more memories; and one or more processors coupled with the one or more memories and configured to cause the UE to: receive, from a network entity, signaling to indicate the UE is to perform a measurement on a first set of cells; transmit, to the network entity and in response to the signaling, a first indication associated with the measurement on the first set of cells; and receive, from the network entity and in response to the first indication, a layer 3 handover command for layer 1 or layer 2 cell mobility, wherein the layer 3 handover command includes a second indication of a second set of cells for layer 1 or layer 2 cell mobility, and wherein the layer 1 or layer 2 cell mobility within the second set of cells is managed via layer 1 signaling or layer 2 signaling.
2. The apparatus of claim 1, wherein the one or more processors are configured to cause the UE to: receive, via the layer 3 handover command, a third indication of a communication configuration for the second set of cells.
3. An apparatus for wireless communication at a network entity, comprising: one or more memories; and one or more processors coupled with the one or more memories and configured to cause the network entity to: transmit signaling to indicate a user equipment (UE) is to perform a measurement on a first set of cells; receive, in response to the signaling, a first indication associated with the measurement on the first set of cells; and transmit, in response to the first indication, a layer 3 handover command for layer 1 or layer 2 cell mobility, wherein the layer 3 handover command includes a second indication of a second set of cells for layer 1 or layer 2 cell mobility, and wherein the layer 1 or layer 2 cell mobility within the second set of cells is managed via layer 1 or layer 2 signaling.
4. The apparatus of claim 3, wherein the one or more processors are configured to cause the network entity to: transmit, via the layer 3 handover command, a third indication of a communication configuration for the second set of cells.
5. A method for wireless communication at a user equipment (UE), comprising: receiving, from a network entity, signaling to indicate the UE is to perform a measurement on a first set of cells; transmitting, to the network entity and in response to the signaling, a first indication associated with the measurement on the first set of cells; and receiving, from the network entity and in response to the first indication, a layer 3 handover command for layer 1 or layer 2 cell mobility, wherein the layer 3 handover command includes a second indication of a second set of cells for layer 1 or layer 2 cell mobility, and wherein the layer 1 or layer 2 cell mobility within the second set of cells is managed via layer 1 or layer 2 signaling.
6. The method of claim 5, wherein receiving the layer 3 handover command comprises: receiving, via the layer 3 handover command, a fourth indication of an activated subset of the second set of cells to be used for communications after a completion of the layer 3 handover command.
7. The method of claim 5, further comprising: receiving, via the layer 3 handover command, a third indication of a communication configuration for the second set of cells.
8. A method for wireless communication at a network entity, comprising: transmitting signaling to indicate a user equipment (UE) is to perform a measurement on a first set of cells; receiving, in response to the signaling, a first indication associated with the measurement on the first set of cells; and transmitting, in response to the first indication, a layer 3 handover command for layer 1 or layer 2 cell mobility, wherein the layer 3 handover command includes a second indication of a second set of cells for layer 1 or layer 2 cell mobility, and wherein the layer 1 or layer 2 cell mobility within the second set of cells is managed via layer 1 or layer 2 signaling.
9. The method of claim 8, wherein transmitting the layer 3 handover command comprises: transmitting, via the layer 3 handover command, a fourth indication of an activated subset of the second set of cells to be used for communications after a completion of the layer 3 handover

command.

10. The method of claim 8, further comprising: transmitting, via the layer 3 handover command, a third indication of a communication configuration for the second set of cells.

11. A non-transitory computer-readable medium storing code for wireless communication a user equipment (UE), the code comprising instructions executable by one or more processors to: receive, from a network entity, signaling to indicate the UE is to perform a measurement on a first set of cells; transmit, to the network entity and in response to the signaling, a first indication associated with the measurement on the first set of cells; and receive, from the network entity and in response to the first indication, a layer 3 handover command for layer 1 or layer 2 cell mobility, wherein the layer 3 handover command includes a second indication of a second set of cells for layer 1 or layer 2 cell mobility, and wherein the layer 1 or layer 2 cell mobility within the second set of cells is managed via layer 1 or layer 2 signaling.

12. A non-transitory computer-readable medium storing code for wireless communication, the code comprising instructions executable by one or more processors to: transmit signaling to indicate a user equipment (UE) is to perform a measurement on a first set of cells; receive, in response to the signaling, a first indication associated with the measurement on the first set of cells; and transmit, in response to the first indication, a layer 3 handover command for layer 1 or layer 2 cell mobility, wherein the layer 3 handover command includes a second indication of a second set of cells for layer 1 or layer 2 cell mobility, and wherein the layer 1 or layer 2 cell mobility within the second set of cells is managed via layer 1 or layer 2 signaling.

13. A user equipment (UE) for wireless communication, comprising: means for receiving, from a network entity, signaling to indicate the UE is to perform a measurement on a first set of cells; means for transmitting, to the network entity and in response to the signaling, a first indication associated with the measurement on the first set of cells; and means for receiving, from the network entity and in response to the first indication, a layer 3 handover command for layer 1 or layer 2 cell mobility, wherein the layer 3 handover command includes a second indication of a second set of cells for layer 1 or layer 2 cell mobility, and wherein the layer 1 or layer 2 cell mobility within the second set of cells is managed via layer 1 or layer 2 signaling.

14. A network entity for wireless communication, comprising: means for transmitting signaling to indicate a user equipment (UE) is to perform a measurement on a first set of cells; means for receiving, in response to the signaling, a first indication associated with the measurement on the first set of cells; and means for transmitting, in response to the first indication, a layer 3 handover command for layer 1 or layer 2 cell mobility, wherein the layer 3 handover command includes a second indication of a second set of cells for layer 1 or layer 2 cell mobility, and wherein the layer 1 or layer 2 cell mobility within the second set of cells is managed via layer 1 or layer 2 signaling.

15. An apparatus for wireless communication at a user equipment (UE), comprising: one or more memories; and one or more processors coupled with the one or more memories and configured to cause the UE to: receive, from a network entity, signaling to indicate the UE is to perform a measurement on a first set of cells; transmit, to the network entity and in response to the signaling, a first indication associated with the measurement on the first set of cells; and receive, from the network entity and in response to the first indication, a message that includes a layer 3 handover command and includes a layer 1 or layer 2 cell mobility configuration, wherein the message further includes a second indication of a second set of cells for layer 1 or layer 2 cell mobility, and wherein the layer 1 or layer 2 cell mobility within the second set of cells is managed via layer 1 signaling or layer 2 signaling.

16. The apparatus of claim 15, wherein the one or more processors are configured to cause the UE to: receive, via the layer 3 handover command, a third indication of a communication configuration for the second set of cells.

17. The apparatus of claim 15, wherein the one or more processors are configured to cause the UE to: receive, via the layer 3 handover command, a fourth indication of an activated subset of the

second set of cells to be used for communications after a completion of the layer 3 handover command.

18. The apparatus of claim 17, wherein the layer 3 handover command further comprises a fifth indication of quasi co-location information indicative of a set of beams to use on the activated subset of the second set of cells.

19. The apparatus of claim 15, wherein the one or more processors are configured to cause the UE to: receive, via the layer 3 handover command, a sixth indication of a subset of candidate primary cells within the second set of cells, wherein the subset of candidate primary cells comprises at least one cell configured to be activated as a primary cell via layer 1 signaling or layer 2 signaling.

20. The apparatus of claim 15, wherein the one or more processors are configured to cause the UE to: receive, via the layer 3 handover command, a seventh indication of signaling to use for layer 1 measurements performed on the second set of cells for the layer 1 or layer 2 cell mobility.

21. The apparatus of claim 15, wherein each cell in the second set of cells is associated with a same central unit as a target cell for the layer 3 handover command.

22. The apparatus of claim 15, wherein the one or more processors are configured to cause the UE to: perform joint beam reporting for the first set of cells, the first set of cells associated with a same network entity as a target cell for the layer 3 handover command; and transmit signaling that indicates a result of the measurement on the first set of cells based at least in part on a performance of the joint beam reporting.

23. The apparatus of claim 15, wherein the one or more processors are configured to cause the UE to: determine that the measurement on the first set of cells satisfies a threshold measurement value; and perform a second measurement on a third set of cells associated with a same network entity as the first set of cells based at least in part on a determination that the measurement on the first set of cells satisfies the threshold measurement value.

24. The apparatus of claim 15, wherein the measurement on the first set of cells comprises a beam measurement associated with layer 3 signaling or a combination of layer 1 signaling and layer 3 signaling.

25. The apparatus of claim 15, further comprising an antenna, wherein the one or more processors are configured to cause the UE to: transmit, to the network entity and via the antenna, an eighth indication to use the second set of cells for the layer 1 or layer 2 cell mobility, wherein the layer 3 handover command comprises the second indication of the second set of cells based at least in part on a reception of the eighth indication to use the second set of cells.

26. The apparatus of claim 15, further comprising an antenna, wherein the one or more processors are configured to cause the UE to: transmit, to the network entity and via the antenna, a ninth indication of an activated subset of the second set of cells for the layer 1 or layer 2 cell mobility, wherein the layer 3 handover command comprises the second indication of the second set of cells based at least in part on a transmission of the ninth indication of the activated subset of the second set of cells.

27. The apparatus of claim 15, wherein the layer 3 handover command comprises radio resource control (RRC) signaling.

28. The apparatus of claim 15, wherein the layer 1 signaling or layer 2 signaling comprises medium access control (MAC) signaling.

29. The apparatus of claim 15, wherein the layer 1 signaling or layer 2 signaling comprises physical layer signaling, medium access control (MAC) signaling, radio link control (RLC) signaling, packet data convergence protocol (PDCP) signaling, or a combination thereof, or wherein the measurement on the first set of cells includes a channel quality measurement, a signal quality measurement, a beam measurement, a reference signal measurement, or combinations thereof.

30. The apparatus of claim 15, wherein the layer 1 or layer 2 cell mobility within the second set of cells is managed via both layer 1 signaling and layer 2 signaling.

31. An apparatus for wireless communication at a network entity, comprising: one or more

memories; and one or more processors coupled with the one or more memories and configured to cause the network entity to: transmit signaling to indicate a user equipment (UE) is to perform a measurement on a first set of cells; receive, in response to the signaling, a first indication associated with the measurement on the first set of cells; and transmit, in response to the first indication, a message that includes a layer 3 handover command and includes a layer 1 or layer 2 cell mobility configuration, wherein the message further includes a second indication of a second set of cells for layer 1 or layer 2 cell mobility, and wherein the layer 1 or layer 2 cell mobility within the second set of cells is managed via layer 1 signaling or layer 2 signaling.

32. The apparatus of claim 31, wherein the one or more processors are configured to cause the network entity to: transmit, via the layer 3 handover command, a third indication of a communication configuration for the second set of cells.

33. The apparatus of claim 31, wherein the one or more processors are configured to cause the network entity to: transmit, via the layer 3 handover command, a fourth indication of an activated subset of the second set of cells to be used for communications after completion of the layer 3 handover command.

34. The apparatus of claim 33, wherein the layer 3 handover command further comprises a fifth indication of quasi co-location information indicative of a set of beams to use on the activated subset of the second set of cells.

35. The apparatus of claim 31, wherein the one or more processors are configured to cause the network entity to: transmit, via the layer 3 handover command, a sixth indication of a subset of candidate primary cells within the second set of cells, wherein the subset of candidate primary cells comprises at least one cell configured to be activated as a primary cell via layer 1 or layer 2 signaling.

36. The apparatus of claim 31, wherein the one or more processors are configured to cause the network entity to: transmit, via the layer 3 handover command, a seventh indication of signaling to use for layer 1 measurements performed on the second set of cells for the layer 1 or layer 2 cell mobility.

37. The apparatus of claim 31, wherein each cell in the second set of cells is associated with a same central unit as a target cell for the layer 3 handover command.

38. The apparatus of claim 31, wherein the one or more processors are configured to cause the network entity to: receive signaling that indicates a result of the measurement on the first set of cells associated with joint beam reporting for the first set of cells, the first set of cells associated with a same network entity as a target cell for the layer 3 handover command.

39. The apparatus of claim 31, wherein, to transmit the signaling that indicates the UE is to perform the measurement on the first set of cells, the one or more processors are configured to cause the network entity to: transmit a tenth indication for the UE to perform a second measurement on a third set of cells associated with a same network entity as the first set of cells based at least in part on a determination that the measurement on the first set of cells satisfies a threshold measurement value.

40. The apparatus of claim 31, wherein the measurement on the first set of cells comprises a beam measurement associated with layer 3 signaling or a combination of layer 1 signaling and layer 3 signaling.

41. The apparatus of claim 31, further comprising an antenna, wherein the one or more processors are configured to cause the network entity to: receive, via the antenna, an eighth indication to use the second set of cells for the layer 1 or layer 2 cell mobility, wherein the layer 3 handover command comprises the second indication of the second set of cells based at least in part on a reception of the eighth indication to use the second set of cells.

42. The apparatus of claim 31, further comprising an antenna, wherein the one or more processors are configured to cause the network entity to: receive, via the antenna, a ninth indication of an activated subset of the second set of cells for the layer 1 or layer 2 cell mobility, wherein the layer 3

handover command comprises the second indication of the second set of cells based at least in part on a reception of the ninth indication of the activated subset of the second set of cells.

43. The apparatus of claim 31, wherein the layer 3 handover command comprises radio resource control (RRC) signaling.

44. The apparatus of claim 31, wherein the layer 1 signaling or layer 2 signaling comprises medium access control (MAC) signaling.

45. The apparatus of claim 31, wherein the layer 1 signaling or layer 2 signaling comprises physical layer signaling, medium access control (MAC) signaling, radio link control (RLC) signaling, packet data convergence protocol (PDCP) signaling, or a combination thereof, or wherein the measurement on the first set of cells includes a channel quality measurement, a signal quality measurement, a beam measurement, a reference signal measurement, or combinations thereof.

46. The apparatus of claim 31, wherein the layer 1 or layer 2 cell mobility within the second set of cells is managed via both layer 1 signaling and layer 2 signaling.

47. A method at a user equipment (UE), comprising: receiving, from a network entity, signaling to indicate the UE is to perform a measurement on a first set of cells; transmitting, to the network entity and in response to the signaling, a first indication associated with the measurement on the first set of cells; and receiving, from the network entity and in response to the first indication, a message that includes a layer 3 handover command and includes a layer 1 or layer 2 cell mobility configuration, wherein the message further includes a second indication of a second set of cells for layer 1 or layer 2 cell mobility, and wherein the layer 1 or layer 2 cell mobility within the second set of cells is managed via layer 1 signaling or layer 2 signaling.

48. The method of claim 47, further comprising: receiving, via the layer 3 handover command, a third indication of a communication configuration for the second set of cells.

49. The method of claim 47, further comprising: receiving, via the layer 3 handover command, a fourth indication of an activated subset of the second set of cells to be used for communications after a completion of the layer 3 handover command.

50. The method of claim 47, further comprising: receiving, via the layer 3 handover command, a sixth indication of a subset of candidate primary cells within the second set of cells, wherein the subset of candidate primary cells comprises at least one cell configured to be activated as a primary cell via layer 1 signaling or layer 2 signaling.

51. The method of claim 47, further comprising: receiving, via the layer 3 handover command, a seventh indication of signaling to use for layer 1 measurements performed on the second set of cells for the layer 1 or layer 2 cell mobility.

52. The method of claim 47, wherein each cell in the second set of cells is associated with a same central unit as a target cell for the layer 3 handover command.

53. The method of claim 47, further comprising: performing joint beam reporting for the first set of cells, the first set of cells associated with a same network entity as a target cell for the layer 3 handover command; and transmitting signaling that indicates a result of the measurement on the first set of cells based at least in part on a performance of the joint beam reporting.

54. The method of claim 47, further comprising: determining that the measurement on the first set of cells satisfies a threshold measurement value; and performing a second measurement on a third set of cells associated with a same network entity as the first set of cells based at least in part on a determination that the measurement on the first set of cells satisfies the threshold measurement value.

55. The method of claim 47, wherein the measurement on the first set of cells comprises a beam measurement associated with layer 3 signaling or a combination of layer 1 signaling and layer 3 signaling.

56. The method of claim 47, wherein the layer 3 handover command comprises radio resource control (RRC) signaling.

57. The method of claim 47, wherein the layer 1 signaling or layer 2 signaling comprises medium

access control (MAC) signaling.

58. The method of claim 47, wherein the layer 1 signaling or layer 2 signaling comprises physical layer signaling, medium access control (MAC) signaling, radio link control (RLC) signaling, packet data convergence protocol (PDCP) signaling, or a combination thereof, or wherein the measurement on the first set of cells includes a channel quality measurement, a signal quality measurement, a beam measurement, a reference signal measurement, or combinations thereof.

59. The method of claim 47, wherein the layer 1 or layer 2 cell mobility within the second set of cells is managed via both layer 1 signaling and layer 2 signaling.

60. A method at a network entity, comprising: transmitting signaling to indicate a user equipment (UE) is to perform a measurement on a first set of cells; receiving, in response to the signaling, a first indication associated with the measurement on the first set of cells; and transmitting, in response to the first indication, a message that includes a layer 3 handover command and includes a layer 1 or layer 2 cell mobility configuration, wherein the message further includes a second indication of a second set of cells for layer 1 or layer 2 cell mobility, and wherein the layer 1 or layer 2 cell mobility within the second set of cells is managed via layer 1 signaling or layer 2 signaling.

61. The method of claim 60, further comprising: transmitting, via the layer 3 handover command, a third indication of a communication configuration for the second set of cells.

62. The method of claim 60, further comprising: transmitting, via the layer 3 handover command, a fourth indication of an activated subset of the second set of cells to be used for communications after completion of the layer 3 handover command.

63. The method of claim 60, further comprising: transmitting, via the layer 3 handover command, a sixth indication of a subset of candidate primary cells within the second set of cells, wherein the subset of candidate primary cells comprises at least one cell configured to be activated as a primary cell via layer 1 or layer 2 signaling.

64. The method of claim 60, further comprising: transmitting, via the layer 3 handover command, a seventh indication of signaling to use for layer 1 measurements performed on the second set of cells for the layer 1 or layer 2 cell mobility.

65. The method of claim 60, wherein each cell in the second set of cells is associated with a same central unit as a target cell for the layer 3 handover command.

66. The method of claim 60, further comprising: receiving signaling that indicates a result of the measurement on the first set of cells associated with joint beam reporting for the first set of cells, the first set of cells associated with a same network entity as a target cell for the layer 3 handover command.

67. The method of claim 60, wherein transmitting the signaling that indicates the UE is to perform the measurement on the first set of cells comprises: transmitting a tenth indication for the UE to perform a second measurement on a third set of cells associated with a same network entity as the first set of cells based at least in part on a determination that the measurement on the first set of cells satisfies a threshold measurement value.

68. The method of claim 60, wherein the measurement on the first set of cells comprises a beam measurement associated with layer 3 signaling or a combination of layer 1 signaling and layer 3 signaling.

69. The method of claim 60, wherein the layer 3 handover command comprises radio resource control (RRC) signaling.

70. The method of claim 60, wherein the layer 1 signaling or layer 2 signaling comprises medium access control (MAC) signaling.

71. The method of claim 60, wherein the layer 1 signaling or layer 2 signaling comprises physical layer signaling, medium access control (MAC) signaling, radio link control (RLC) signaling, packet data convergence protocol (PDCP) signaling, or a combination thereof, or wherein the measurement on the first set of cells includes a channel quality measurement, a signal quality

measurement, a beam measurement, a reference signal measurement, or combinations thereof.

72. The method of claim 60, wherein the layer 1 or layer 2 cell mobility within the second set of cells is managed via both layer 1 signaling and layer 2 signaling.

73. A non-transitory computer-readable medium storing code for wireless communication at a user equipment (UE), the code comprising instructions executable by one or more processors to: receive, from a network entity, signaling to indicate the UE is to perform a measurement on a first set of cells; transmit, to the network entity and in response to the signaling, a first indication associated with the measurement on the first set of cells; and receive, from the network entity and in response to the first indication, a message that includes a layer 3 handover command and includes a layer 1 or layer 2 cell mobility configuration, wherein the message further includes a second indication of a second set of cells for layer 1 or layer 2 cell mobility, and wherein the layer 1 or layer 2 cell mobility within the second set of cells is managed via layer 1 signaling or layer 2 signaling.

74. The non-transitory computer-readable medium of claim 73, wherein the instructions are further executable by the one or more processors to: receive, via the layer 3 handover command, a third indication of a communication configuration for the second set of cells.

75. A non-transitory computer-readable medium storing code for wireless communication at a network entity, the code comprising instructions executable by one or more processors to: transmit signaling to indicate a user equipment (UE) is to perform a measurement on a first set of cells; receive, in response to the signaling, a first indication associated with the measurement on the first set of cells; and transmit, in response to the first indication, a message that includes a layer 3 handover command and includes a layer 1 or layer 2 cell mobility configuration, wherein the message further includes a second indication of a second set of cells for layer 1 or layer 2 cell mobility, and wherein the layer 1 or layer 2 cell mobility within the second set of cells is managed via layer 1 signaling or layer 2 signaling.

76. The non-transitory computer-readable medium of claim 75, wherein the instructions are further executable by the one or more processors to: transmit, via the layer 3 handover command, a third indication of a communication configuration for the second set of cells.

77. A user equipment (UE), comprising: means for receiving, from a network entity, signaling to indicate the UE is to perform a measurement on a first set of cells; means for transmitting, to the network entity and in response to the signaling, a first indication associated with the measurement on the first set of cells; and means for receiving, from the network entity and in response to the first indication, a message that includes a layer 3 handover command and includes a layer 1 or layer 2 cell mobility configuration, wherein the message further includes a second indication of a second set of cells for layer 1 or layer 2 cell mobility, and wherein the layer 1 or layer 2 cell mobility within the second set of cells is managed via layer 1 signaling or layer 2 signaling.

78. The UE of claim 77, further comprising: means for receiving, via the layer 3 handover command, a third indication of a communication configuration for the second set of cells.

79. A network entity, comprising: means for transmitting signaling to indicate a user equipment (UE) is to perform a measurement on a first set of cells; means for receiving, in response to the signaling, a first indication associated with the measurement on the first set of cells; and means for transmitting, in response to the first indication, a message that includes a layer 3 handover command and includes a layer 1 or layer 2 cell mobility configuration, wherein the message further includes a second indication of a second set of cells for layer 1 or layer 2 cell mobility, and wherein the layer 1 or layer 2 cell mobility within the second set of cells is managed via layer 1 signaling or layer 2 signaling.

80. The network entity of claim 79, further comprising: means for transmitting, via the layer 3 handover command, a third indication of a communication configuration for the second set of cells.
