

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12411545
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Suzuki; Yasuyuki

Recording device, image-capturing apparatus, control method, and recording system

Abstract

In the case where a confirmation operation is performed by a user, a CPU 3 performs control to store information related to the confirmation operation in association with a still image or a moving image displayed on a display element 10.

Inventors:	Suzuki; Yasuyuki (Kanagawa, JP)
Applicant:	CANON KABUSHIKI KAISHA (Tokyo, JP)
Family ID:	83847200
Assignee:	Canon Kabushiki Kaisha (Tokyo, JP)
Appl. No.:	18/493408
Filed:	October 24, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240085979 A1	Mar. 14, 2024

Foreign Application Priority Data

JP	2021-076748	Apr. 28, 2021
----	-------------	---------------

Related U.S. Application Data

continuation parent-doc WO PCT/JP2022/018625 20220422 PENDING child-doc US 18493408

Publication Classification

Int. Cl.: G06F3/01 (20060101); H04N23/695 (20230101)

U.S. Cl.:

CPC G06F3/013 (20130101); H04N23/695 (20230101);

Field of Classification Search

CPC: G06F (3/013); H04N (23/695); H04N (23/611); H04N (5/92); H04N (23/60); G03B (17/00)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5689619	12/1996	Smyth	706/45	B60K 35/235
6426740	12/2001	Goto	345/157	A61F 4/00
6677969	12/2003	Hongo	715/863	G06F 3/017
7561143	12/2008	Milekic	345/32	G06F 3/013
9652034	12/2016	He	N/A	G06F 3/013
11868672	12/2023	Dehkordi	N/A	G06F 9/451
2011/0109880	12/2010	Nummela	351/210	G02B 27/0081
2013/0063340	12/2012	Mondragon	345/156	G09G 5/00
2015/0332091	12/2014	Kim	382/103	H04N 5/2621
2016/0246384	12/2015	Mullins	N/A	G06F 3/017
2019/0354171	12/2018	Dai	N/A	G06F 3/013
2022/0253146	12/2021	Erivantcev	N/A	G06F 3/016
2022/0261073	12/2021	Francis	N/A	G06F 3/017

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2001-36901	12/2000	JP	N/A
2004-181233	12/2003	JP	N/A
2018207415	12/2017	JP	N/A
2019/171522	12/2018	WO	N/A

Primary Examiner: Chen; Chiawei

Attorney, Agent or Firm: Canon U.S.A., Inc., IP Division

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a Continuation of International Patent Application No. PCT/JP2022/018625, filed Apr. 22, 2022, which claims the benefit of Japanese Patent Application No. 2021-076748, filed Apr. 28, 2021, both of which are hereby incorporated by reference herein in their entirety.

TECHNICAL FIELD

(1) The present invention relates to a device capable of detecting a line of sight.

BACKGROUND ART

(2) In recent years, cameras have become increasingly automated and intelligent, and a technique of obtaining and using position information of a line of sight of an image-capturing person (user) has been proposed.

(3) Japanese Patent Laid-Open No. 2018-207415 discloses a technique of adding position information of a line of sight of an image-capturing person during image-capturing to images and displaying a locus of an image-capturing position to be superimposed on the captured images after the image-capturing.

CITATION LIST

Patent Literature

(4) PTL 1: Japanese Patent Laid-Open No. 2018-207415

(5) Further improvement is desired in terms of information added to an image.

SUMMARY OF INVENTION

(6) Accordingly, it is an object of the present invention to provide a recording device, an image-capturing apparatus, a control method, and a recording system that enable an intention of an image-capturing person to be reflected.

(7) Accordingly, the present invention is configured to include an eyeball imaging element configured to obtain an eyeball image of a user; calculation means configured to calculate, from the eyeball image obtained from the eyeball imaging element, a point of gaze corresponding to a line of sight of the user onto display means on which a still image or a moving image is displayed; an operation member configured to receive an operation performed by the user to perform a confirmation operation for confirming a point of gaze; and storage means configured to store information related to the confirmation operation in association with the still image or the moving image displayed on the display means in a case where the confirmation operation is performed by the user.

(8) Further features of the present invention will become apparent from the following description of exemplary embodiments with reference to the attached drawings.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) FIG. 1 is a schematic configuration diagram of an image-capturing apparatus to which a first embodiment of the present invention is applied.

(2) FIG. 2A is a schematic external view of the image-capturing apparatus in the first embodiment of the present invention.

(3) FIG. 2B is a schematic external view of the image-capturing apparatus in the first embodiment of the present invention.

(4) FIG. 3 is a block diagram of the image-capturing apparatus to which the first embodiment of the present invention is applied.

(5) FIG. 4A is an explanatory diagram illustrating a field of vision within a viewfinder in the first embodiment of the present invention.

(6) FIG. 4B is an explanatory diagram illustrating the field of vision within the viewfinder in the first embodiment of the present invention.

(7) FIG. 5 is an explanatory diagram of the principle of a line-of-sight detection method in the first embodiment of the present invention.

(8) FIGS. 6A and 6B are schematic diagrams of an eyeball image projected onto an eyeball imaging element 17.

(9) FIG. 7 illustrates a schematic flow of a line-of-sight detection routine.

(10) FIG. 8 illustrates a schematic routine of recording confirmed point-of-gaze information and

line-of-sight detection information in the first embodiment of the present invention.

(11) FIG. 9 illustrates a schematic routine of recording confirmed point-of-gaze information and line-of-sight detection information in a second embodiment of the present invention.

(12) FIG. 10 illustrates a schematic routine of recording confirmed point-of-gaze information and line-of-sight detection information in a third embodiment of the present invention.

(13) FIG. 11 illustrates a schematic routine of recording confirmed point-of-gaze information and line-of-sight detection information in a fifth embodiment of the present invention.

(14) FIG. 12 illustrates a schematic routine of recording confirmed point-of-gaze information and line-of-sight detection information in a sixth embodiment of the present invention.

DESCRIPTION OF EMBODIMENTS

(15) Preferred embodiments of the present invention will be described in detail below with reference to the accompanying drawings.

First Exemplary Embodiment

(16) <Description of Configuration>

(17) FIGS. 1 to 3 are diagrams illustrating a configuration of a camera according to the present exemplary embodiment.

(18) FIGS. 2A and 2B illustrate an external appearance of a digital still camera 1 according to the present invention. FIG. 2A is a front perspective view, and FIG. 2B is a rear perspective view. In the present exemplary embodiment, as illustrated in the front perspective view of FIG. 2A, the digital still camera 1 includes an image-capturing lens 1A and a housing 1B of a camera body. The digital still camera 1 is also provided with a shutter-release button 5 which is an operation member for receiving an imaging operation from an image-capturing person (user).

(19) As illustrated in the rear perspective view of FIG. 2B, on a rear surface of the digital still camera 1, an eyepiece lens 12 is provided through which the image-capturing person looks into a display element (to be described below) included inside the camera. In addition, various operation members used for operating the camera, such as an operation member α (touch-panel liquid crystal display), an operation member β (lever-type operation member), and an operation member γ (button-type cross key) respectively denoted by 41 to 43 are provided.

(20) FIG. 1 is a sectional view of the camera housing taken along a YZ plane formed by a Y axis and a Z axis illustrated in FIG. 2A, and is an explanatory diagram illustrating a schematic configuration of the digital still camera 1 according to the present invention. In FIGS. 1, 2A, and 2B, corresponding portions are denoted by the same numeral.

(21) In FIG. 1, 1A denotes the image-capturing lens for interchangeable-lens cameras. In the present embodiment, the inside of the image-capturing lens 1A is depicted with two lenses 101 and 102 for the sake of convenience. However, as is well known, the image-capturing lens 1A is constituted by a larger number of lens in practice. 1B denotes the housing of the camera body, and configurations of units included therein are as follows. 2 denotes an imaging element, which is disposed on a plane on which the image-capturing lens 1A of the digital still camera 1 is expected to form an image. The digital still camera 1 includes therein a CPU 3 that controls the entire camera, and a memory unit 4 in which an image captured by the imaging element 2 is recorded. The digital still camera 1 is also provided with a display element 10 constituted by a liquid crystal display or the like for displaying a captured image, a display-element drive circuit 11 that drives the display element 10, and the eyepiece lens 12 through which a subject image displayed on the display element 10 is observed. The imaging element 2 and the display element 10 correspond to an imaging element and display means in claim 1, respectively.

(22) 13a and 13b denote light sources that illuminate an eyeball 14 of the image-capturing person to detect a line-of-sight direction on the basis of relationships between the pupil and reflection images, resulting from corneal reflection, of the light sources used in a single-lens reflex camera or the like in the related art. The light sources 13a and 13b are constituted by infrared-emitting diodes and are arranged around the eyepiece lens 12. An eyeball image of the illuminated eyeball and

images of the light sources **13a** and **13b** resulting from corneal reflection pass through the eyepiece lens **12**, are reflected by a light separator **15**, and are formed, by a light-receiving lens **16**, on the eyeball imaging element **17** such as a CCD in which lines of photoelectric elements are arranged two-dimensionally. The light-receiving lens **16** positions the pupil of the eyeball **14** of the image-capturing person and the eyeball imaging element **17** to have a conjugate image-forming relationship. On the basis of the positional relationships between the images of the light sources **13a** and **13b** resulting from corneal reflection and the eyeball image that are formed on the eyeball imaging element **17**, the line-of-sight direction is detected using a predetermined algorithm (to be described below). The eyeball imaging element **17** described above corresponds to an imaging element in claim **1**.

(23) **111** denotes a diaphragm provided in the image-capturing lens **1A**. **112** denotes a diaphragm drive device. **113** denotes a lens driving motor. **114** denotes a lens driving member including a driving gear and so on. **115** denotes a photocoupler, which detects rotation of a pulse board **116** that moves in conjunction with the lens driving member **114** and transmits information on the rotation to a focus adjusting circuit **118**. The focus adjusting circuit **118** drives the lens driving motor **113** by a predetermined amount on the basis of this information and information on a lens driving amount supplied from the camera to move the lens **101** to an in-focus position. **117** denotes a mount contact that serves as a publicly known interface between a camera and a lens. **6** denotes an acceleration sensor built in the camera. The acceleration sensor **6** detects panning of the camera. **119** denotes an acceleration sensor built in the lens. The acceleration sensor **119** detects panning of the lens. One or both of the acceleration sensor **6** built in the camera and the acceleration sensor **119** built in the lens are used in determination of panning (to be described below).

(24) FIG. **3** is a block diagram illustrating electrical components built in the digital still camera **1** having the foregoing configuration. The same component as that in FIG. **1** is denoted by the same numeral. The central processing unit **3** that is a microcomputer built in the camera body is hereinafter referred to as “CPU **3**”. A line-of-sight detection circuit **201**, a photometer circuit **202**, an auto-focus detection circuit **203**, a signal input circuit **204**, the display-element drive circuit **11**, an illumination-light-source drive circuit **205**, and the acceleration sensor **6** are connected to the CPU **3**. Signals are delivered to the focus adjusting circuit **118** disposed in the image-capturing lens **1A**, a diaphragm control circuit **206** included in the diaphragm drive device **112** described above, and the acceleration sensor **119** through the mount contact **117** illustrated in FIG. **1**. The memory unit **4** attached to the CPU **3** has a function of storing imaging signals supplied from the imaging element **2** and the eyeball imaging element **17**. The memory unit **4** is connected to a recording medium **7**. The CPU **3** converts an imaging signal from the imaging element **2** stored in the memory unit **4** into a captured image. The captured image is then transferred to the recording medium **7**.

(25) The line-of-sight detection circuit **201** performs A/D conversion on an output based on a formed eyeball image from the eyeball imaging element **17** (CCD-EYE), and sends this image information to the CPU **3**. The CPU **3** extracts feature points of the eyeball image necessary for line-of-sight detection in accordance with a predetermined algorithm (to be described below), and further calculates a line of sight of the image-capturing person on the basis of positions of the respective feature points.

(26) The photometer circuit **202** amplifies a luminance signal output corresponding to a brightness of a subject field on the basis of a signal obtained from the imaging element **2** that also serves as a photometer sensor, performs logarithmic compression and A/D conversion on the result, and sends the result as subject field luminance information to the CPU **3**.

(27) The auto-focus detection circuit **203** performs A/D conversion on signal voltages supplied from a plurality of pixels that are included in the CCD of the imaging element **2** and are used for phase-difference detection, and sends the resultant signals to the CPU **3**. The CPU **3** calculates a distance to the subject corresponding to each focus detection point on the basis of the signals of the

plurality of pixels. This is a well-known technique known as imaging-plane phase-difference AF. In the present exemplary embodiment, for example, suppose that there are 180 focus detection points at positions on an imaging plane which correspond to areas indicated in an image of a field of vision within a viewfinder in FIGS. 4A and 4B.

(28) A switch SW1 is connected to the signal input circuit 204. The switch SW1 is turned on in response to a first stroke of the shutter-release button 5 (not illustrated) to start a photometry operation, a distance measurement operation, a line-of-sight detection operation of the camera, an operation of determining a line-of-sight position of an image-capturing person, and the like. A switch SW2 is also connected to the signal input circuit 204. The switch SW2 is turned on in response to a second stroke of the shutter-release button 5 to start a shutter-release operation. The signal is input to the signal input circuit 204 and sent to the CPU 3.

(29) The operation member α (touch-panel liquid crystal display), the operation member β (lever-type operation member), and the operation member γ (button-type cross key) described above and respectively denoted by 41 to 43 are configured to transmit operation signals thereof to the CPU 3.

(30) FIGS. 4A and 4B are diagrams illustrating a field of vision within a viewfinder and illustrate a state in which the display element 10 is in operation.

(31) In FIGS. 4A and 4B, 300 denotes a field-of-vision mask, 400 denotes a focus detection region, and 4001 to 4180 denote 180 focus point indicators displayed over a through image displayed on the display element 10 to be superimposed at respective positions corresponding to the plurality of focus detection points on the imaging plane. An indicator corresponding to an estimated position of a current point of gaze among those indicators is displayed with a frame as indicated by an estimated point of gaze A in the figure. Displaying a frame at the estimated position of the point of gaze corresponds to displaying, on the display element, an indicator indicating a position of the point of gaze estimated by the point-of-gaze-position estimation means. The configuration in which the CPU 3 sends a signal to the display element 10 to display the frame at the estimated position of the point of gaze corresponds to point-of-gaze position display means.

(32) FIG. 5 is an explanatory diagram of the principle of a line-of-sight detection method and corresponds to a simplified diagram of an optical system for performing line-of-sight detection in FIG. 1 described above.

(33) In FIGS. 5, 13a and 13b denote light sources such as light-emitting diodes that emit infrared rays not to be sensed by an observer. The light sources 13a and 13b are disposed to be substantially symmetric about the optical axis of the light-receiving lens 16 and illuminate the eyeball 14 of the observer. Part of the illumination light reflected by the eyeball 14 is condensed onto the eyeball imaging element 17 by the light-receiving lens 16.

(34) A line-of-sight detection method will be described below with reference to FIGS. 5 to 7.

(35) <Description of Line-of-Sight Detection Operation>

(36) FIG. 7 illustrates a schematic flow of a line-of-sight detection routine. In FIG. 7, after the line-of-sight detection routine is started, the light sources 13a and 13b emit infrared rays toward the eyeball 14 of an observer in step S001. An eyeball image of the observer illuminated with the infrared rays is formed on the eyeball imaging element 17 through the light-receiving lens 16 and is photo-electrically converted by the eyeball imaging element 17, so that the eyeball image can be processed as an electric signal.

(37) In step S002, an eyeball image signal thus obtained from the eyeball imaging element 17 is sent to the CPU 3.

(38) In step S003, coordinates of points corresponding to a pupil center c and corneal reflection images Pd and Pe of the light sources 13a and 13b illustrated in FIG. 5 are calculated on the basis of information of the eyeball image signal obtained in S002. The infrared rays emitted from the light sources 13a and 13b illuminate a cornea 142 of the eyeball 14 of the observer. At this time, the corneal reflection images Pd and Pe formed of the infrared rays partially reflected by the surface of the cornea 142 are condensed by the light-receiving lens 16. Consequently, the corneal

reflection images Pd and Pe are formed on the eyeball imaging element **17** (points Pd' and Pe' illustrated in the figure). Likewise, light rays from end portions a and b of a pupil **141** form images on the eyeball imaging element **17**. In FIGS. **6A** and **6B**, FIG. **6A** illustrates an example image of a reflection image obtained from the eyeball imaging element **17** and FIG. **6B** illustrates example luminance information, in a region a in the example image, obtained from the eyeball imaging element **17**. As illustrated, the X axis denotes the horizontal direction and the Y axis denotes the vertical direction. In this case, let Xd and Xe denote coordinates, in the X-axis direction (horizontal direction), of the formed images Pd' and Pe' of the corneal reflection images of the light sources **13a** and **13b**, respectively. In addition, let Xa and Xb denote coordinates, in the X-axis direction, of formed images a' and b' of the light rays from the end portions a and b of the pupil **141**. In the example luminance information in FIG. **6B**, an extremely high luminance level is obtained at the positions Xd and Xe corresponding to the formed images Pd' and Pe' of the corneal reflection images of the light sources **13a** and **13b**. A region from the coordinate Xa to the coordinate Xb corresponds to the region of the pupil **141**. In this region, an extremely low luminance level is obtained except at the positions Xd and Xe described above. A region with X-coordinate values less than Xa and a region with X-coordinate values greater than Xb correspond to the region of an iris **143** located on the outer side of the pupil **141**. In these regions, intermediate values between the two aforementioned luminance levels are obtained. On the basis of information on the above-described change in the luminance level with respect to the X-coordinate position, the X coordinates Xd and Xe of the formed images Pd' and Pe' of the corneal reflection images of the light sources **13a** and **13b** and the X coordinates Xa and Xb of the images a' and b' of the pupil ends can be obtained. When a rotation angle θ_x of the optical axis of the eyeball **14** relative to the optical axis of the light-receiving lens **16** is small, a coordinate Xc of the location (referred to as c') corresponding to the pupil center c in the image formed on the eyeball imaging element **17** can be represented by $Xc \approx (Xa + Xb)/2$. Thus, the X coordinate of c' corresponding to the pupil center c in the image formed on the eyeball imaging element **17** and the X coordinates of the corneal reflection images Pd' and Pe' of the light sources **13a** and **13b** can be estimated.

(39) In step **S004**, an image formation magnification β of the eyeball image is calculated. β denotes a magnification determined in accordance with the position of the eyeball **14** relative to the light-receiving lens **16** and can be calculated as a function of an interval (Xd–Xe) between the corneal reflection images Pd' and Pe' in practice.

(40) The X coordinate of the middle point between the corneal reflection images Pd and Pe substantially coincides with the X coordinate of the curvature center O of the cornea **142**. Thus, when an average distance from the curvature center O of the cornea **142** to the center c of the pupil **141** is denoted by Oc, the rotation angle θ_x of the optical axis of the eyeball **14** in the Z-X plane can be calculated on the basis of a relational expression $\beta \cdot Oc \cdot \sin \theta_x \approx \{(Xd + Xe)/2\} - Xc$ in step **S005**. FIGS. **5** and **6** illustrate the example of calculating the rotation angle θ_x in the case where the eyeball **14** of the observer rotates in a plane perpendicular to the Y axis. However, a method of calculating a rotation angle θ_y in the case where the eyeball **14** of the observer rotates in a plane perpendicular to the X axis is substantially the same.

(41) After the rotation angles θ_x and θ_y of the optical axis of the eyeball **14** of the observer are calculated in the previous step, θ_x and θ_y are used to calculate the position of the line of sight of the observer on the display element **10** (the position of a point gazed at by the observer, hereinafter referred to as “point of gaze”) in step **S006**. Assuming that the position of the point of gaze is denoted by coordinates (Hx, Hy) corresponding to the center c of the pupil **141** on the display element **10**, Hx and Hy can be calculated as follows.

$$Hx = m \times (Ax \times \theta_x + Bx)$$

$$Hy = m \times (Ay \times \theta_y + By)$$

Here, a factor m is a constant determined in accordance with the configuration of a viewfinder optical system of the camera and is a conversion factor for converting the rotation angles θ_x and θ_y

into the coordinates of the position corresponding to the center **c** of the pupil **141** on the display element **10**. The factor **m** is determined in advance and stored in the memory unit **4**. In addition, **Ax**, **Bx**, **Ay**, and **By** are line-of-sight correction factors for correcting an individual difference in the line of sight of the observer, are obtained by performing a calibration operation, and are stored in the memory unit **4** before the line-of-sight detection routine is started.

(42) After the coordinates (**Hx**, **Hy**) of the center **c** of the pupil **141** on the display element **10** are calculated in the above-described manner, the above-described coordinates (hereinafter, referred to as “coordinates of the position of the point of gaze”) and the obtained time of the eyeball image signal (hereinafter, referred to as “line-of-sight detection time”) are stored in the memory unit **4** in step **S008**. Then, the line-of-sight detection routine ends.

(43) The method of obtaining the coordinates of the point of gaze on the display element by using the corneal reflection images of the light sources **13a** and **13b** has been described above. However, the method is not limited to this one, and any method of obtaining the eyeball rotation angles from a captured eyeball image is applicable to the present invention.

(44) The line-of-sight detection routine described above corresponds to point-of-gaze-position estimation means.

(45) <Description of Point-of-Gaze-Position Confirmation Operation>

(46) Two-step pressing operations can be performed on the shutter-release button **5**. In response to the first stroke, which is a half pressing operation (hereinafter, referred to as **SW1**), an instruction for an AF operation can be issued. In response to the second stroke, which is a fully pressing operation (hereinafter, referred to as **SW2**), shutter-releasing can be performed. The shutter-release button **5** includes a function of determining the position of the point of gaze in accordance with an intention of the image-capturing person (hereinafter, referred to as line-of-sight confirmation) before the AF operation is performed in response to the **SW1** operation. This allows AF operation to be performed at the determined position of the point of gaze. The point-of-gaze position information confirmed through the line-of-sight confirmation may be coordinates of the position of the point of gaze or the detection time of the determined position of the point of gaze. The point-of-gaze position information just needs to allow a timing at which the point-of-gaze coordinates are detected in the line-of-sight detection routine and a timing at which the point-of-gaze coordinates are determined in accordance with the intention of the image-capturing person to be distinguished from each other. The coordinates of the position of the point of gaze determined through the line-of-sight confirmation or the confirmation timing is stored in the memory unit **4**.

(47) In addition, the line-of-sight confirmation function similar to the **SW1** operation may be assigned to any of the above-described operation members α to γ respectively denoted by **41** to **43**. The line-of-sight confirmation function corresponds to point-of-gaze-position confirmation means.

(48) <Description of Association Operation to Still Image or Moving Image>

(49) Line-of-sight-detection-information recording means and confirmed-point-of-gaze-information recording means will be described next with reference to FIG. **8**.

(50) After line-of-sight detection-information recording is started, line-of-sight detection is performed in step **S101**. The line-of-sight detection in step **S101** corresponds to steps **S001** to **S007** described above. After the position of the point of gaze is calculated in step **S101**, the coordinates of the position of the point of gaze and the line-of-sight detection time are stored in the memory unit **4** in step **S102**. The process then proceeds to step **S103**. **S102** corresponds to **S008** described above and the line-of-sight-detection-information recording means.

(51) If the position of the point of gaze is determined by the **SW1** operation or an operation performed by the image-capturing person on any of the operation members α to γ respectively denoted by **41** to **43** in **S103**, coordinates of the point of gaze determined in accordance with the operation performed by the image-capturing person or the line-of-sight detection time is stored in the memory unit **4** in step **S104**. **S104** corresponds to the confirmed-point-of-gaze-information recording means. If the position of the point of gaze is not confirmed in step **S103**, the process

proceeds to step **S105**.

(52) In **S105**, it is determined whether the current mode is a still image capturing mode or a moving image capturing mode. The still image capturing mode and the moving image capturing mode can be switched between by using various operation members used for operating the camera. The various operation members used herein are, for example, the operation member α (touch-panel liquid crystal display), the operation member β (lever-type operation member), and the operation member γ (button-type cross key) respectively denoted by **41** to **43** in FIG. 2B.

(53) In the case of the still image capturing mode, the process proceeds to **S106**. In **S106**, it is determined whether the shutter is released in response to the SW2 operation. If the shutter is not released, the process returns to the **S101** and the line-of-sight detection is repeated. If the confirmation operation of the position of the point of gaze is performed multiple times in **S103** before the process reaches **S105**, the point-of-gaze coordinates or the line-of-sight detection time obtained at the latest confirmation of the point of gaze in the memory unit **4** is updated in **S104**.

(54) If the shutter-release button **5** is pressed in step **S106**, the process proceeds to step **S107**. In step **S107**, the CPU **3** records, in the recording medium **7** together with data of the captured still image, the coordinates of the position of the point of gaze and the line-of-sight detection time stored in **S102** and the point-of-gaze coordinates or the line-of-sight detection time obtained when the point of gaze is confirmed and stored in **S104**.

(55) If it is determined in **S105** that the current mode is the moving image capturing mode, the process proceeds to **S108**. In **S108**, it is determined whether capturing of a moving image is ended. If the capturing of the moving image is not ended, the process returns to **S101** and the line-of-sight detection is repeated. As in the still image mode, if the confirmation operation of the position of the point of gaze is performed multiple times in **S103** before the process reaches **S105**, the point-of-gaze coordinates or the line-of-sight detection time obtained at the latest confirmation of the point of gaze in the memory unit **4** is updated in **S104**.

(56) If it is determined in step **S108** that capturing of the moving image is ended, the process proceeds to step **S109**. In step **S109**, the CPU **3** records, in the recording medium **7** together with data of the captured moving image, the coordinates of the position of the point of gaze and the line-of-sight detection time stored in **S102** and the point-of-gaze coordinates or the line-of-sight detection time obtained when the point of gaze is confirmed and stored in **S104**.

(57) Since **S101** and the **S102** are repeated until the line-of-sight detection is ended, the coordinates of the position of the point of gaze and the line-of-sight detection time are accumulated as a plurality of pieces of past line-of-sight detection information in the memory unit **4**. Thus, when the shutter-release button **5** is pressed in **S106** or when capturing of the moving image is ended in **S108**, the plurality of past line-of-sight detection results are recorded in association with captured image data of the still image.

Second Exemplary Embodiment

(58) In a second exemplary embodiment that is a modification of the first exemplary embodiment, a method of recording, in the recording medium **7**, the plurality of pieces of past line-of-sight detection information recorded in step **S107** of FIG. 8 without any overlap will be described with reference to FIG. 9.

(59) In **S107** of FIG. 8 in the first exemplary embodiment described above, the plurality of pieces of past line-of-sight detection information are recorded in a fixed size since the size recordable in association with a still image is usually finite. In this case, the plurality of pieces of past line-of-sight detection information accumulated until the shutter is released in response to the SW2 operation are recorded a fixed number of times.

(60) However, if the plurality of pieces of past line-of-sight detection information are recorded the fixed number of times even during continuous image capturing, the plurality of pieces of past line-of-sight detection information added to the previous captured image data may have an overlap. For example, suppose that ten line-of-sight detection results can be added to one piece of captured

image data. In the case where the line-of-sight detection routine can be performed five times during continuous image capturing, the five pieces of line-of-sight detection information overlap between the previous one and the current one. The five pieces of past line-of-sight detection information for the current captured image data can be checked using the previous captured image. Thus, redundancy occurs in the recorded data. In view of a transfer time of the line-of-sight detection information from the memory unit **4** to the recording medium **7** and a recordable capacity of the recording medium **7**, the information to be associated with the captured image data is desirably minimized.

(61) FIG. **9** will be described below.

(62) Since steps **S201** to **S206** of FIG. **9** are equivalent to steps **S101** to **S104**, **S106**, and **S107** of FIG. **8**, a description thereof is omitted. After the line-of-sight detection information stored in step **S202** and the confirmed point-of-gaze information stored in step **204** are added to the captured image data in step **S206**, the process proceeds to step **S207**. In **S207**, the coordinates of the position of the point of gaze and the line-of-sight detection time obtained multiple times in the past and recorded in the memory unit **4** in **S202** are erased.

(63) According to FIG. **9**, in the case of continuous image capturing, the line-of-sight detection results detected in the next line-of-sight detection routine are recorded in the memory unit **4** that has been cleared. Thus, the plurality of past line-of-sight detection results added to a captured image when the shutter is released next time do not overlap with the plurality of past line-of-sight detection results recorded for the previous one.

(64) The second exemplary embodiment corresponds to an image-capturing apparatus.

Third Exemplary Embodiment

(65) In a third exemplary embodiment that is a modification of the first and second exemplary embodiments, a method of storing confirmed point-of-gaze information stored in the memory unit **4** in **S104** of FIG. **8** or **S204** of FIG. **9** will be described with reference to FIG. **10**.

(66) The point-of-gaze coordinates or the line-of-sight detection time (hereinafter, referred to as confirmed line-of-sight information) obtained when the point of gaze is confirmed and stored in the memory unit **4** in **S104** of FIG. **8** or **S204** of FIG. **9** may overlap a plurality of pieces of past line-of-sight detection information stored in **S102** of FIG. **8** or **S202** of FIG. **9**. As described in the second exemplary embodiment, in view of the transfer time of the line-of-sight detection information from the memory unit **4** to the recording medium **7** and the recordable capacity of the recording medium **7**, the line-of-sight detection information is desirably recorded in the recording medium **7** after eliminating the overlapping line-of-sight detection information as much as possible. Accordingly, it is conceived to reduce the confirmed line-of-sight information that overlaps any of the plurality of pieces of past line-of-sight detection information to a minimum amount and add, to captured image data, only data that can identify the confirmed line-of-sight information from among the plurality of pieces of past line-of-sight detection information.

(67) FIG. **10** is a diagram for describing a method of storing the confirmed line-of-sight information. Since steps **S301** to **S303** are substantially the same as steps **S101** to **S103** in the first exemplary embodiment, a description thereof is omitted.

(68) If the position of the point of gaze is determined in step **S303**, the process proceeds to step **S304**, in which it is determined whether there is point-of-gaze position information that matches any of the plurality of pieces of past line-of-sight detection information stored in **S302**. If there is point-of-gaze position information that matches any of the plurality of pieces of past line-of-sight detection information in **S304**, the process proceeds to step **S305**, in which only the line-of-sight detection time at the time of the line-of-sight confirmation is stored in the memory unit **4**. If the point-of-gaze position information does not match any of the plurality of pieces of past line-of-sight detection information in **S304**, the process proceeds to step **S306**, in which both the point-of-gaze coordinates and the line-of-sight detection time at the time of the line-of-sight confirmation are stored in the memory unit **4**. After each of steps **S305** and **S306** is performed, the process

proceeds to step **S307**. Since **S307** to **S311** are substantially the same as **S105** to **S109** in FIG. **8**, a description thereof is omitted. The third exemplary embodiment corresponds to an image-capturing apparatus.

Fourth Exemplary Embodiment

(69) In a fourth exemplary embodiment, information recorded by the confirmed-point-of-gaze-information recording means and the line-of-sight-detection-information recording means will be described.

(70) As described in the second exemplary embodiment, in view of the transfer time of the line-of-sight detection information from the memory unit **4** to the recording medium **7** and the recordable capacity of the recording medium **7**, a minimum amount of information is desirably stored in association with captured image data.

(71) However, since the confirmed point-of-gaze information desirably recorded by the confirmed-point-of-gaze-information recording means is point-of-gaze information at a timing determined in accordance with the intention of the image-capturing person, it is desired to record more detailed information of line-of-sight information at the confirmation timing and provide the information to a third party or use the information for analysis. Recording more detailed information of the confirmed line-of-sight information than the line-of-sight detection information achieves both addition of a minimum amount of information to captured image data and making information at the confirmation timing more detailed.

(72) Specifically, the confirmed point-of-gaze information and the line-of-sight detection information are, but not limited to, as follows.

(73) Confirmed point-of-gaze information: point-of-gaze coordinates, line-of-sight detection time, line-of-sight variation degree, blink information, line-of-sight angular velocity, and leap (great jump of the line of sight to another subject) determination information

(74) Line-of-sight detection information (plurality of pieces of past information are held): point-of-gaze coordinates, line-of-sight detection time

Fifth Exemplary Embodiment

(75) A fifth exemplary embodiment will be described with reference to FIG. **11**.

(76) As described in the first exemplary embodiment, the point-of-gaze-position confirmation means is a means used for determining the position gazed at by the image-capturing person. The confirmed-point-of-gaze-information recording means records the position of the point of gaze determined by the point-of-gaze-position confirmation means in the recording medium **7** together with captured image data.

(77) Since the timing of the operation performed by the point-of-gaze-position confirmation means is different from the shutter-release timing, the detection timing of the position of the point of gaze determined by the point-of-gaze-position confirmation means may greatly deviate from the generation timing of the captured image data. In this case, if the scene being captured is changed due to movement of the camera in a period from line-of-sight confirmation to shutter-releasing, the scene at the time of the line-of-sight confirmation is not left as captured image data. Thus, the confirmed line-of-sight information becomes useless. Therefore, in the case where the camera is panned, the coordinates and the detection time obtained at the line-of-sight confirmation are not recorded in the memory unit **4**.

(78) The flow will be described below with reference to FIG. **11**.

(79) Since steps **S401** to **S404** are substantially the same as steps **S101** to **S104** of FIG. **8** in the first exemplary embodiment, a description thereof is omitted.

(80) After step **S404** is performed, the process proceeds to step **S405**, in which an acceleration is obtained. The acceleration is obtained from the acceleration sensor **6** in the camera or the acceleration sensor **119** in the lens.

(81) If the position of the point of gaze is not confirmed yet, the process proceeds to step **S406**. Since **S406** and **S407** are substantially the same as **S105** and **S106** of FIG. **8** in the first exemplary

embodiment, a description thereof is omitted.

(82) In step **S408**, it is determined whether the camera is panned in a period from the line-of-sight confirmation to the present. Whether the camera is panned in the period from the line-of-sight confirmation to the present is determined in accordance with whether the acceleration is greater than a threshold by using the acceleration obtained in **S405**. If the acceleration is greater than the threshold, it is determined that the camera is panned in the period from confirmation of the point of gaze to the present, and the process proceeds to step **S409**.

(83) In **S409**, only the plurality of pieces of past line-of-sight detection information are recorded in the recording medium **7** in association with still image data.

(84) On the other hand, if it is determined in step **S408** that the acceleration is equal to or smaller than the threshold, it is determined that the camera is not panned in the period from confirmation of the point of gaze to the present. Thus, the process proceeds to step **S410**, in which both the plurality of pieces of past line-of-sight detection information and the confirmed point-of-gaze information are recorded in the recording medium **7** in association with the still image data.

(85) If it is determined in step **S406** that the current mode is the moving image capturing mode, the process proceeds to step **S411**, in which it is determined whether image capturing is ended. If image capturing is not ended in **S411**, the process returns to **S401** and the line-of-sight detection is repeated. If image capturing is ended in **S411**, the process proceeds to step **S412**.

(86) In step **S412**, it is determined whether the camera is panned in a period from the line-of-sight confirmation to the present. Whether the camera is panned in the period from the line-of-sight confirmation to the present is determined in accordance with whether the acceleration is greater than the threshold by using the acceleration obtained in **S405**. If the acceleration is greater than the threshold, it is determined that the camera is panned in the period from confirmation of the point of gaze to the present, and the process proceeds to step **S413**.

(87) In **S413**, only the plurality of pieces of past line-of-sight detection information are recorded in the recording medium **7** in association with moving image data.

(88) On the other hand, if it is determined in step **S412** that the acceleration is equal to or smaller than the threshold, it is determined that the camera is not panned in the period from confirmation of the point of gaze to the present. Thus, the process proceeds to step **S414**, in which both the plurality of pieces of past line-of-sight detection information and the confirmed point-of-gaze information are recorded in the recording medium **7** in association with the moving image data.

(89) As described above, according to the fifth exemplary embodiment, meaningful point-of-gaze position information can be recorded in association with captured image data.

Sixth Exemplary Embodiment

(90) A sixth embodiment is a modification of the fifth exemplary embodiment and corresponds to an image-capturing apparatus according to claim **7**. In the fifth exemplary embodiment, the description has been given of whether to associate the confirmed point-of-gaze information with captured image data in accordance with whether the camera is panned in a period from line-of-sight confirmation to shutter-releasing.

(91) On the other hand, in the case of an image capturing method in which a subject desirably captured is kept within an angle of view while the camera is being panned as in a panning shot mode, it is highly likely that a relative positional relationship between the subject and the position of the point of gaze at the time of the line-of-sight confirmation does not change although the camera is being panned. In this case, it is highly likely that the position of the point of gaze determined by the point-of-gaze-position confirmation means for captured image data is meaningful information. Thus, the position of the point of gaze needs to be associated with the captured image data.

(92) FIG. **12** is a flowchart illustrating association of the point-of-gaze position information at the time of confirmation of the position of the point of gaze with captured image data in the panning shot mode. The flow will be described below.

(93) Since steps S501 to S507 are substantially the same as S401 to S407 of FIG. 11 in the fifth exemplary embodiment and step 512 is substantially the same as S411 of FIG. 11, a description thereof is omitted.

(94) If it is determined in step S508 that the current mode is the panning shot mode, the process proceeds to step S511, in which both the plurality of pieces of past line-of-sight detection information and the confirmed line-of-sight information are recorded in the recording medium 7 in association with still image data.

(95) On the other hand, if it is not determined that the current mode is the panning shot mode, the process proceeds to step S509.

(96) A setting of the panning shot mode can be made by using various operation members used for operating the camera, such as the operation member α (touch-panel liquid crystal display), the operation member β (lever-type operation member), and the operation member γ (button-type cross key) respectively denoted by 41 to 43 in FIG. 2B.

(97) Since S509 to S511 are substantially the same as S408 to S410 described in the fifth exemplary embodiment, a description thereof is omitted.

(98) If it is determined in step S513 that the current mode is the panning shot mode, the process proceeds to step S516, in which both the plurality of pieces of past line-of-sight detection information and the confirmed line-of-sight information are recorded in the recording medium 7 in association with moving image data.

(99) On the other hand, if it is not determined that the current mode is the panning shot mode, the process proceeds to step S514.

(100) Since S514 to S516 are substantially the same as S412 to S414 described in the fifth exemplary embodiment, a description thereof is omitted.

(101) As described above, according to the sixth exemplary embodiment, meaningful point-of-gaze position information can be recorded in association with captured image data in the case of the panning shot mode.

Seventh Exemplary Embodiment

(102) In a seventh exemplary embodiment, detection information recorded in the memory unit 4 by the line-of-sight-detection-information recording means and the confirmed-point-of-gaze-information recording means is recorded in association with still image data or moving image data only when the point-of-gaze-position estimation means is enabled.

(103) The point-of-gaze-position estimation means can be switched between enabled and disabled by using various operation members used for operating the camera. The various operation members are, for example, the operation member α (touch-panel liquid crystal display), the operation member β (lever-type operation member), and the operation member γ (button-type cross key) respectively denoted by 41 to 43 in FIG. 2B.

(104) Note that although the configuration of the camera has been mainly described in the exemplary embodiments above, the processes described in the exemplary embodiments above can also be applied to other apparatuses. The apparatuses may be, for example, a head-mounted display, or may be a recording system in which a configuration for detecting a line of sight, a configuration for displaying an image, a configuration for confirming a point of gaze, and a configuration for recording an image and other information are implemented by separate apparatuses.

(105) Although the preferred embodiments of the present invention have been described above, the present invention is not limited to these embodiments, and various modifications and changes can be made within the scope of the gist of the present invention.

(106) The present invention is not limited to the embodiments described above, and various changes and modifications can be made without departing from the spirit and scope of the present invention. Accordingly, the following claims are appended to disclose the scope of the invention.

(107) According to the present invention, an intention of an image-capturing person can be reflected.

(108) While the present invention has been described with reference to exemplary embodiments, it is to be understood that the invention is not limited to the disclosed exemplary embodiments. The scope of the following claims is to be accorded the broadest interpretation so as to encompass all such modifications and equivalent structures and functions.

Claims

1. A control device comprising: an imaging element configured to obtain an eyeball image of a user; and at least one memory storing instructions; and at least one processor that, upon execution of the stored instructions, is configured to: calculate, from the eyeball image obtained from the imaging element, a point of gaze corresponding to a line of sight of the user onto a display on which a still image or a moving image is displayed; receive an operation performed by the user to perform a confirmation operation for confirming a point of gaze; and control, based on presence or absence of panning during capturing of the still image or the moving image, an operation of storing information related to the confirmation operation in association with the still image or the moving image displayed on the display in a case where the confirmation operation is performed by the user.
2. The control device according to claim 1, wherein the information related to the confirmation operation includes position information of the point of gaze of the user at a performed timing of the confirmation operation.
3. The control device according to claim 2, wherein the position information of the point of gaze is information of coordinates corresponding to the point of gaze.
4. The control device according to claim 1, wherein the information related to the confirmation operation includes information corresponding to a performed time of the confirmation operation.
5. The control device according to claim 1, wherein execution of the stored instructions further configures the at least one processor to record, in addition to the information related to the confirmation operation, a plurality of pieces of line-of-sight detection information in association with the still image or the moving image.
6. The control device according to claim 5, wherein each of the plurality of pieces of line-of-sight detection information includes position information of a point of gaze and information on an obtained time of the position information.
7. An image-capturing apparatus comprising the control device according to claim 1, wherein the information related to the confirmation operation is not recorded in a case where the image-capturing apparatus is panned at a performed timing of the confirmation operation.
8. The image-capturing apparatus according to claim 7, wherein the information related to the confirmation operation is recorded in association with the still image or the moving image in a case where the image-capturing apparatus is panned but a panning shot is performed by the user using the image-capturing apparatus.
9. A control method for a control device including an imaging element configured to obtain an eyeball image of a user, the control method comprising: a calculation step of calculating, from the eyeball image obtained from the imaging element, a point of gaze corresponding to a line of sight of the user onto display on which a still image or a moving image is displayed; an operation step of receiving an operation performed by the user to perform a confirmation operation for confirming a point of gaze; and a control step of controlling, based on presence or absence of panning during capturing of the still image or the moving image, an operation of storing information related to the confirmation operation in association with the still image or the moving image displayed on the display in a case where the confirmation operation is performed by the user.
10. A control system comprising: an imaging element configured to obtain an eyeball image of a user; at least one memory storing instructions; and at least one processor that, upon execution of the stored instructions, is configured to: calculate, from the eyeball image obtained from the imaging element, a point of gaze corresponding to a line of sight of the user onto display on which

a still image or a moving image is displayed; an operation member configured to receive an operation performed by the user to perform a confirmation operation for confirming a point of gaze; and control, based on presence or absence of panning during capturing of the still image or the moving image, an operation of storing information related to the confirmation operation in association with the still image or the moving image displayed on the display means in a case where the confirmation operation is performed by the user.
