

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12411593
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Kawano; Yusuke

Information processing system for providing file image information, information processing method, and non-transitory computer readable medium

Abstract

An information processing system includes a processor configured to: cause an enlarged image to be displayed if a file image is selected, the file image being an image which is displayed on a display and which corresponds to a file, and the enlarged image being an image which corresponds to a selected file image, that is, the file image that is selected, and which has a larger display size than the selected file image; and cause a file-corresponding image to be displayed on the display if the selected file image is positioned behind the enlarged image, the file-corresponding image being an image that corresponds to the selected file image.

Inventors:	Kawano; Yusuke (Yokohama, JP)
Applicant:	FUJIFILM Business Innovation Corp. (Tokyo, JP)
Family ID:	83438627
Assignee:	FUJIFILM Business Innovation Corp. (Tokyo, JP)
Appl. No.:	17/901631
Filed:	September 01, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230315268 A1	Oct. 05, 2023

Foreign Application Priority Data

JP	2022-053686	Mar. 29, 2022
----	-------------	---------------

Publication Classification

Int. Cl.: G06F3/04812 (20220101); G06F3/04845 (20220101); G06F3/0482 (20130101)

U.S. Cl.:

CPC G06F3/04845 (20130101); G06F3/04812 (20130101); G06F3/0482 (20130101); G06F2203/04804 (20130101)

Field of Classification Search

CPC: G06F (3/04845); G06F (3/04812); G06F (3/0482); G06F (2203/04804); G06F (3/04817); G06F (2203/04806)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2002/0089518	12/2001	Shigeta	715/790	G06F 3/14
2008/0282196	12/2007	Park	715/838	H04M 1/72445
2013/0104065	12/2012	Stecher	715/767	G06F 3/04842
2016/0313805	12/2015	Vroom	N/A	G06F 3/038
2017/0123596	12/2016	Kashima	N/A	N/A
2021/0243314	12/2020	Munetomo	N/A	G06F 3/04817

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2008-077210	12/2007	JP	N/A
2009-175935	12/2008	JP	N/A

OTHER PUBLICATIONS

May 25, 2023 extended Search Report issued in European Patent Application No. 22197153.4. cited by applicant

Primary Examiner: Yi; Rinna

Attorney, Agent or Firm: Oliff PLC

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

(1) This application is based on and claims priority under 35 USC 119 from Japanese Patent Application No. 2022-053686 filed Mar. 29, 2022.

BACKGROUND

(i) Technical Field

(2) The present disclosure relates to an information processing system, an information processing method, and a non-transitory computer readable medium.

(ii) Related Art

(3) Japanese Unexamined Patent Application Publication No. 2009-175935 relates to an image display device having, on a display screen, a preview image area in which a preview image is displayed and a thumbnail display area in which multiple thumbnail images smaller than the preview image are displayed, and discloses a configuration that enlarges the preview display area and reduces the thumbnail display area, or displays the thumbnail image to match the reduced thumbnail display area without changing the size of the thumbnail image, depending on the position of a pointer.

SUMMARY

(4) When a file image is selected, for example, if an image which corresponds to the selected file image and which has a larger display size than the file image is displayed, the user obtains information about the file image more easily. However, if the file image is positioned behind the image that is displayed when the file image is selected, information about the file image is hidden, making it difficult for the user to obtain information about the file image.

(5) Aspects of non-limiting embodiments of the present disclosure relate to providing information about a selected file image to the user in the case where the file image is positioned behind an image that is displayed in association with the selection of the file image.

(6) Aspects of certain non-limiting embodiments of the present disclosure address the above advantages and/or other advantages not described above. However, aspects of the non-limiting embodiments are not required to address the advantages described above, and aspects of the non-limiting embodiments of the present disclosure may not address advantages described above.

(7) According to an aspect of the present disclosure, there is provided an information processing system including a processor configured to: cause an enlarged image to be displayed if a file image is selected, the file image being an image which is displayed on a display and which corresponds to a file, and the enlarged image being an image which corresponds to a selected file image, that is, the file image that is selected, and which has a larger display size than the selected file image; and cause a file-corresponding image to be displayed on the display if the selected file image is positioned behind the enlarged image, the file-corresponding image being an image that corresponds to the selected file image.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) An exemplary embodiment of the present disclosure will be described in detail based on the following figures, wherein:

(2) FIG. 1 is a diagram illustrating an exemplary overall configuration of an information processing system;

(3) FIG. 2 is a block diagram illustrating an example of a hardware configuration of a server device;

(4) FIG. 3 is a block diagram illustrating an example of a hardware configuration of a terminal device;

(5) FIG. 4 is a diagram illustrating a display example on a display;

(6) FIG. 5 is a diagram illustrating the state of a display when a mouseover is performed on an enlarge button image of a first file icon;

(7) FIG. 6 is a diagram illustrating another display example on a display;

(8) FIG. 7 is a diagram illustrating the state of a display after a maintain button image of an enlarged image is clicked;

(9) FIG. 8 is a diagram illustrating another display example on a display;

(10) FIG. 9 is a diagram illustrating another display example on a display;

- (11) FIG. **10** is a diagram illustrating the state of a display when a cursor is moved off a corresponding image and positioned over an enlarged image;
- (12) FIG. **11** is a diagram illustrating another display example on a display;
- (13) FIG. **12** is a diagram illustrating the state of a display when a user operation is performed with respect to a menu image on a menu bar;
- (14) FIG. **13** is a diagram illustrating another display example on a display;
- (15) FIG. **14** is a diagram illustrating a display example on a display in the case where multiple corresponding images are displayed;
- (16) FIG. **15** is a diagram illustrating another display example on a display;
- (17) FIG. **16** is a diagram illustrating an example of information managed by an information processing system; and
- (18) FIG. **17** is a flowchart illustrating a flow of processes executed when displaying an enlarged image and a corresponding image to which an exemplary embodiment is applied.

DETAILED DESCRIPTION

(19) Hereinafter, an exemplary embodiment of the present disclosure will be described in detail and with reference to the attached drawings. FIG. **1** is a diagram illustrating an overall configuration example of an information processing system **1** to which the exemplary embodiment is applied. The information processing system **1** according to the exemplary embodiment is configured by connecting, over a communication network **80**, a server device **10** that manages files and terminal devices **20** (**20a**, **20b**, and so on) used by users for viewing files. The communication network **80** is a network such as the Internet, for example, and is used to communicate information between the server device **10** and the terminal devices **20**. In the information processing system **1** according to the exemplary embodiment, it is assumed that files uploaded to the server device **10** are viewed and edited on the terminal devices **20**.

(20) Note that in the exemplary embodiment, a “file” refers to an electronic file stored in the server device **10** or the like. A file may include an image in addition to text, or include an image only without text. Moreover, a file may not only include document data or image data, but also information to be used when converting document data into an image and attribute information such as the file modification date and time, a paper size, a number of pages, and keywords inside the file.

(21) The server device **10** is a device for managing files uploaded from the terminal devices **20**. The files managed by the server device **10** are shared by multiple users and may be edited by one or multiple users. The server device **10** is realized by a computer device, for example. The server device **10** may be configured as a single computer or may be realized through distributed processing performed by multiple computers.

(22) The terminal device **20** is a device for viewing and editing files managed in the server device **10**. The terminal device **20** includes a display that displays images corresponding to files. The terminal device **20** is provided with a computer device. Forms of the terminal device **20** include a desktop personal computer (PC), a laptop PC, a tablet information terminal, a smartphone, and a game console, for example.

(23) A hardware configuration of the server device **10** will be described. FIG. **2** is a block diagram illustrating an example of a hardware configuration of the server device **10** according to the exemplary embodiment. The server device **10** includes a computational processing unit **11** that executes digital computational processing according to a program for managing files, secondary storage **12** in which files and the like are recorded, and a communication unit **13** that transmits and receives information over the communication network **80** (see FIG. **1**). The secondary storage **12** is realized by an existing information storage device such as a hard disk drive (HDD), semiconductor memory, or magnetic tape, for example.

(24) The computational processing unit **11** is provided with a CPU **11a** as one example of a processor. The CPU **11a** controls the server device **10** as a whole. The computational processing

unit **11** is also provided with RAM **11b** used as a working memory of the CPU **11a** and ROM **11c** that stores data such as programs to be executed by the CPU **11a**. In addition, the computational processing unit **11** is provided with non-volatile memory **11d** which is rewritable and capable of retaining data even if the power supply is cut off, and an interface **11e** that controls each unit such as the communication unit **13** connected to the computational processing unit **11**.

(25) The non-volatile memory **11d** is configured using battery-backed SRAM or flash memory, for example, and the non-volatile memory **11d** stores data such as correspondence information that associates information about files and files to each other. Also, in addition to storing information related to files and the like, the secondary storage **12** also stores programs to be executed by the computational processing unit **11**. In the exemplary embodiment, the processes of the server device **10** are executed by causing the computational processing unit **11** to load a program stored in the secondary storage **12**. Note that the computational processing unit **11**, the secondary storage **12**, and the communication unit **13** are connected through a bus or signal lines.

(26) The server device **10** executes processes such as acquiring a new file, performing file extraction, associating files with each other, and applying the updated content of a file in response to requests and the like from the terminal devices **20**. Additionally, the server device **10** provides various information such as files, the results of search processes, and update information to the terminal devices **20** in response to requests and the like from the terminal devices **20**. In the exemplary embodiment, the secondary storage **12** stores information related to files and the like. Also, the communication unit **13** receives requests and the like from the terminal devices **20** and transmits requested files and the like.

(27) A program to be executed by the CPU **11a** provided in the server device **10** may be provided to the server device **10** in a recorded state on a computer-readable recording medium, such as a magnetic recording medium (such as magnetic tape or a magnetic disk), an optical recording medium (such as an optical disc), a magneto-optical recording medium, or semiconductor memory. A program to be executed by the CPU **11a** may also be provided to the server device **10** by using a means of communication such as the Internet.

(28) Next, a hardware configuration of the terminal device **20** will be described. FIG. **3** is a block diagram illustrating an example of a hardware configuration of the terminal device **20**. Each terminal device **20** according to the exemplary embodiment includes a computational processing unit **21** that executes processing for displaying images according to a program, secondary storage **22** in which information related to files and the like is recorded, and a communication unit **23** that transmits and receives information over the communication network **80** (see FIG. **1**).

(29) Also, each terminal device **20** includes an input unit **24** that receives input operations from a user and a display **25** that displays images, text information, and the like to a user. The display **25** may be a liquid crystal display (LCD) panel or an organic light-emitting diode (OLED) display panel, for example. The secondary storage **22** is realized by an existing information storage device such as a hard disk drive (HDD), semiconductor memory, or magnetic tape, for example.

(30) The computational processing unit **21** is provided with a CPU **21a** as one example of a processor. The CPU **21a** controls the terminal device **20** as a whole. The computational processing unit **21** is also provided with RAM **21b** used as a working memory of the CPU **21a** and ROM **21c** that stores data such as programs to be executed by the CPU **21a**. In addition, the computational processing unit **21** is provided with non-volatile memory **21d** which is rewritable and capable of retaining data even if the power supply is cut off, and an interface **21e** that controls each unit such as the communication unit **23** connected to the computational processing unit **21**.

(31) The non-volatile memory **21d** is configured using battery-backed SRAM or flash memory, for example, and stores data such as files and update information. Also, in addition to storing information related to files and the like, the secondary storage **22** also stores programs to be executed by the computational processing unit **21**. The processes of the terminal device **20** are executed by causing the computational processing unit **21** to load a program stored in the

secondary storage **22**. Note that the computational processing unit **21**, the secondary storage **22**, and the communication unit **23** are connected through a bus or signal lines.

(32) The input unit **24** is a pointing device or the like that the user operates when inputting information. For example, in the case where the input unit **24** is a mouse, the user performs operations for moving a cursor and click operations to thereby specify a position on display screen displayed on the display **25**, specify an image displayed on the display **25**, and move the specified image. Also, in the case where the input unit **24** is a touch panel, the user performs operations that involve touching the touch panel with a finger or the like and operations that involve moving the finger while touching the touch panel. With this arrangement, the user is able to specify a position on display screen displayed on the display **25**, specify an image displayed on the display **25**, and move the specified image.

(33) Note that a touch panel may be provided in the terminal device **20** in some cases, and in such cases, the input unit **24** and the display **25** are provided as a unified component. Additionally, besides the pointing device or the like described above, the input unit **24** may also be a keyboard used to perform input operations via keys.

(34) A program to be executed by the CPU **21a** provided in the terminal device **20** may be provided to the terminal device **20** in a recorded state on a computer-readable recording medium, such as a magnetic recording medium (such as magnetic tape or a magnetic disk), an optical recording medium (such as an optical disc), a magneto-optical recording medium, or semiconductor memory. A program to be executed by the CPU **21a** may also be provided to the terminal device **20** by using a means of communication such as the Internet.

(35) In the exemplary embodiment, the term “processor” refers to hardware in a broad sense. Examples of the processor include general processors (e.g., CPU: Central Processing Unit), dedicated processors (e.g., GPU: Graphics Processing Unit, ASIC: Application Specific Integrated Circuit, FPGA: Field Programmable Gate Array, and programmable logic device).

(36) Also, the term “processor” is broad enough to encompass one processor or plural processors in collaboration which are located physically apart from each other but may work cooperatively. The order of operations of the processor is not limited to one described in the exemplary embodiment, and may be changed.

(37) <Display on Display **25**>

(38) Next, the display on the display **25** provided in the terminal device **20** will be described using FIG. **4** (a diagram illustrating a display example on a display). In the exemplary embodiment, information to be used to control the display on the display **25** provided in the terminal device **20** is generated by the CPU **11a** (see FIG. **2**) provided as an example of a processor in the server device **10**. Thereafter, the terminal device **20** controls the display according to the information. With this arrangement, the various screens described hereinafter are displayed on the display **25** of the terminal device **20**. Note that the information to be used to control the display on the display **25** of the terminal device **20** may also be generated by the terminal device **20** rather than the server device **10**. Moreover, one portion of the information to be used for control may be generated by the server device **10** and another portion may be generated by the terminal device **20**.

(39) As illustrated in FIG. **4**, in the exemplary embodiment, a workspace **400** of what is called file handling software is displayed on the display **25** provided in the terminal device **20**. The file handling software is software that manages electronically converted files and has a function of facilitating integrated management of paper and electronic documents. Furthermore, the display **25** displays a cursor **200** that indicates the user operation location on the display **25**. The cursor **200**, which is given as one example of a pointer image, moves according to mouse operations performed by the user. The user moves the cursor **200** to a desired position on the display **25** and selects an element displayed on the display **25**.

(40) Also, in the exemplary embodiment, multiple icons **310** are displayed in the workspace **400** displayed on the display **25**. Furthermore, in the exemplary embodiment, an enlarge button image

311 for receiving an enlargement instruction from the user is displayed on some of the icons **310**.
(41) In the exemplary embodiment, if the user moves the cursor **200** onto an icon **310**, the enlarge button image **311** is displayed on the icon **310**. Also, in the exemplary embodiment, if the cursor **200** moves off the icon **310**, the enlarge button image **311** is hidden. Also, besides the icons **310**, a context menu **320** and a search box **330** are displayed on the display **25**.

(42) The context menu **320** is an image for receiving instructions from the user. In the exemplary embodiment, the context menu **320** is displayed if a right-click is performed after positioning the cursor **200** over an icon **310**, for example. Selectable options are displayed in the context menu **320**. In the exemplary embodiment, the user chooses an option from among the selectable options to thereby execute a process corresponding to the chosen option.

(43) The search box **330** is an image for receiving a search from the user. In the exemplary embodiment, a character string is inputted into the search box **330**. If a character string is inputted into the search box **330**, a search process using the inputted character string is executed with respect to the files in the workspace **400** displayed on the display **25**, for example. Note that the range of the search process is not limited to only the workspace **400** displayed on the display **25**, and other workspaces **400** or all files stored in the server device **10** and the terminal device **20** may also be included in the range of the search process.

(44) The icons **310** are images displayed on the display **25** in correspondence with each of user-selectable elements. A picture, symbol, character information, or the like is displayed in the icons **310**. Each of the icons **310** may also be considered to be a thumbnail image. In the display example illustrated in FIG. 4, a workspace A is displayed as the workspace **400**, and multiple icons **310** are displayed in the workspace A.

(45) In the exemplary embodiment, a first file icon **310a**, a second file icon **310e**, and a third file icon **310f** respectively corresponding to files with the file names “Sample1”, “Sample2”, and “Sample3” are displayed as the icons **310**. Also, tray icons **310b** respectively corresponding to trays with the tray names “Tray-01” and “Tray-02”, a folder icon **310c** corresponding to a folder, and a private box icon **310d** corresponding to a private box are displayed in the workspace A.

(46) Each of the first file icon **310a**, second file icon **310e**, and third file icon **310f** given as examples of file images is an image that corresponds to and represents a file. The first file icon **310a**, second file icon **310e**, and third file icon **310f** are configured as images that represent the content of a file using a picture, a symbol, or character information, for example. In the case where the files corresponding to the first file icon **310a**, second file icon **310e**, and third file icon **310f** contain image data, a reduced version of the image expressed by the image data is displayed as the file icon, for example.

(47) As another example, in the case where the files corresponding to the first file icon **310a**, second file icon **310e**, and third file icon **310f** contain multi-page documents, a reduced version of an image on a representative page, such as first page, is displayed as the file icon, for example. Additionally, the first file icon **310a**, second file icon **310e**, and third file icon **310f** function as icons for opening the corresponding files.

(48) The tray icons **310b** are icons corresponding to tray that contain files, and when selecting a tray, the user selects the corresponding tray icon. The folder icon **310c** is an icon corresponding to a folder that contains files, and when selecting a folder, the user selects the folder icon.

(49) The private box icon **310d** is an icon provided to every user who operates the terminal device **20**. In the exemplary embodiment, files provided by a third party to the user who operates the terminal device **20** are stored in an information storage area corresponding to the private box icon **310d**. When referencing a file stored in the information storage area, the user selects the private box icon **310d**.

(50) The enlarge button image **311**, which is one example of a button image, is an image for receiving, from the user, an instruction related to the display of an enlarged image **360** described later. In FIG. 4, the enlarge button image **311** is displayed in association with the first file icon

310a. The enlarge button image **311** displayed in FIG. 4 is an image for receiving, from the user, an instruction for displaying the enlarged image **360** (described later) corresponding to the first file icon **310a** with the file name “Sample1”.

(51) As described later, in the exemplary embodiment, if the enlarge button image **311** is selected by the user, the enlarged image **360** (see FIG. 5) which corresponds to the first file icon **310a** on which the enlarge button image **311** is displayed and which is an image having a larger display size than the first file icon **310a** is displayed.

(52) In the exemplary embodiment, an instruction for temporarily displaying the enlarged image **360** is received on the basis of a user operation performed on the enlarge button image **311**. In the exemplary embodiment, if a mouseover operation is performed on the enlarge button image **311**, the operation is received as an operation for temporarily displaying the enlarged image **360**. The enlarged image **360** is displayed while the mouseover operation continues, and the enlarged image **360** is hidden if the mouseover operation ends.

(53) In the exemplary embodiment, the enlarge button image **311** is displayed in the upper-right corner of the first file icon **310a**. Also, in the exemplary embodiment, the display size of the enlarge button image **311** is smaller than the display size of the first file icon **310a**.

(54) Note that besides the above, the enlarge button image **311** may also be semitransparent such that the portion of the first file icon **310a** that is positioned behind the enlarge button image **311** is visible through the enlarge button image **311**. In addition, the enlarge button image **311** may also be displayed in association with not only the first file icon **310a** but also other icons, such as the second file icon **310e**, the third file icon **310f**, the tray icons **310b**, the folder icon **310c**, and the private box icon **310d**. In this case, the enlarged image **360** may be displayed with respect to the other icons, too.

(55) FIG. 5 is a diagram illustrating the state of the display **25** when a mouseover is performed on the enlarge button image **311** of the first file icon **310a**. Here, in FIG. 5, the enlarged image **360** corresponding to the first file icon **310a** is displayed as described above.

(56) In the present exemplary embodiment, as illustrated in FIG. 5, if the first file icon **310a** corresponding to “Sample1” is selected, the enlarged image **360** which corresponds to the first file icon **310a** and which has a larger display size than the first file icon **310a** is displayed on the display **25**. More specifically, in the exemplary embodiment, if a mouseover or the like is performed on the enlarge button image **311** displayed in association with the first file icon **310a**, the enlarged image **360** having a larger display size than the first file icon **310a** is displayed on the display **25**.

(57) Here, a “having a larger display size” is synonymous with having a larger display area. Note that hereinafter in this specification, “having a larger display size” similarly refers to having a larger display area. Also, “having a smaller display size” refers to having a smaller display area.

(58) In the exemplary embodiment, the enlarged image **360** is displayed at a central position in the workspace **400** displayed on the display **25**, and also at a higher level (toward the user) than the display level of the first file icon **310a** from which the display of the enlarged image **360** originates. As another example, in the case where the icon **310** from which the display of the enlarged image **360** originates is displayed at a position close to the edge of the workspace **400** displayed on the display **25**, the enlarged image **360** may be displayed near the icon **310**. The enlarged image **360** may also be displayed in a location adjacent to the icon **310**. Also, with respect to the margins on each of the left and right sides of the icon **310**, the enlarged image **360** may be displayed on the side with the larger margin.

(59) In this way, in the exemplary embodiment, if a mouseover is performed on the enlarge button image **311** of the first file icon **310a**, the enlarged image **360** corresponding to the first file icon **310a** with the enlarge button image **311** displayed thereon is displayed.

(60) In the exemplary embodiment, the shape of the first file icon **310a** and the shape of the enlarged image **360** are similar to each other. Note that the configuration is not limited to an

appearance like the above, and content different from the display content of the first file icon **310a** may also be displayed in the enlarged image **360**. Moreover, the shape of the enlarged image **360** and the shape of the first file icon **310a** may be dissimilar to each other. In the exemplary embodiment, the “enlarged image **360**” refers to an image having a larger display size than the first file icon **310a** given as one example of a selected file image. Even if an image has a different shape from the first file icon **310a**, the image still corresponds to the enlarged image **360** if the image has a larger display size than the first file icon **310a**.

(61) Furthermore, in the exemplary embodiment, as illustrated in FIG. 5, if the first file icon **310a** from which the display of the enlarged image **360** originates is positioned behind the enlarged image **360**, a corresponding image **370** indicating information that corresponds to the first file icon **310a** selected by the user is displayed. At this point, “the first file icon **310a** . . . is positioned behind the enlarged image **360**” means that the area where the first file icon **310a** was displayed overlaps at least partially with the area where the enlarged image **360** is displayed. Specifically, in the exemplary embodiment, if the first file icon **310a** selected by the user is obscured due to the display of the enlarged image **360**, the corresponding image **370** is displayed to display information about the first file icon **310a** selected by the user.

(62) The corresponding image **370** given as one example of a file-corresponding image is an image that corresponds to the file represented by the first file icon **310a** from which the display of the enlarged image **360** originates. In the exemplary embodiment, a character image indicating the file name “Sample1” is displayed as a portion of the corresponding image **370**. Also, in the exemplary embodiment, the corresponding image **370** is displayed in the location where the first file icon **310a** selected by the user was displayed.

(63) The corresponding image **370** may be the same image as the first file icon **310a** or an image in which at least one of the shape, display size, color, or content is different from the first file icon **310a**. In the exemplary embodiment, the corresponding image **370** is an image obtained by applying transparency to the image of the first file icon **310a**.

(64) In the display example illustrated in FIG. 5, a maintain button image **312** for receiving, from the user, an instruction related to the display of the enlarged image **360** is additionally displayed. The maintain button image **312** given as one example of a button image is displayed when the enlarged image **360** is displayed. Also, the maintain button image **312** is displayed to receive, from the user, an instruction for maintaining the display of the enlarged image **360**. In FIG. 5, the maintain button image **312** is displayed in the location where the enlarge button image **311** (see FIG. 4) was displayed. Note that the maintain button image **312** may also be semitransparent such that the portion of the enlarged image **360** that is positioned behind the maintain button image **312** is visible through the maintain button image **312**.

(65) The maintain button image **312** is an image for receiving, from the user, an instruction for maintaining the display of the enlarged image **360** corresponding to the first file icon **310a** with the file name “Sample1”. Note that the maintain button image **312** may also be displayed in a different location from the location where the enlarge button image **311** was displayed, and the display position of the maintain button image **312** is not particularly limited. Moreover, the maintain button image **312** may also be added to the display without hiding the enlarge button image **311**.

(66) In the present exemplary embodiment, the display location of the maintain button image **312** is changed as illustrated in FIG. 6 from the location where the enlarge button image **311** was displayed (see FIG. 4), depending on the movement of the cursor **200**. In the present exemplary embodiment, the display location of the maintain button image **312** is changed such that the maintain button image **312** moves together with the cursor **200**, which is one example of a pointer image. If the maintain button image **312** moves together with the cursor **200** like in the present exemplary embodiment, usability is improved when the user selects the maintain button image **312**.

(67) Also, in the present exemplary embodiment, the display location of the maintain button image **312** satisfying a specific condition is changed such that the maintain button image **312** moves

together with the cursor **200**. On the other hand, the display location of the maintain button image **312** not satisfying the specific condition does not have to be changed. More specifically, the display location of the maintain button image **312** displayed in an overlapping state with the enlarged image **360** is changed such that the maintain button image **312** moves together with the cursor **200**. On the other hand, the display location of the maintain button image **312** displayed in a non-overlapping state with the enlarged image **360** does not have to be changed. If the maintain button image **312** moves together with the cursor **200** like in the present exemplary embodiment, the portion of the enlarged image **360** that was positioned behind the maintain button image **312** before the display location of the maintain button image **312** is changed may be displayed clearly. Note that instead of changing the display location, the maintain button image **312** may also be hidden temporarily or the transparency level may be changed.

(68) In the present exemplary embodiment, the user may click the maintain button image **312**, and if the maintain button image **312** is clicked, the display of the enlarged image **360** is maintained. Also, in the present exemplary embodiment, the maintain button image **312** may be clicked, and if the maintain button image **312** is clicked, the display of the enlarged image **360** is maintained even if the cursor **200** moves off the maintain button image **312**.

(69) FIG. 7 is a diagram illustrating the state of the display **25** after the maintain button image **312** of the enlarged image **360** is clicked. In the present exemplary embodiment, if the maintain button image **312** (see FIG. 6) of the enlarged image **360** is clicked, the cancel button image **313** is displayed. Also, in the present exemplary embodiment, if the maintain button image **312** is clicked, the display of the enlarged image **360** is maintained as described above. Accordingly, as illustrated in FIG. 7, even if the cursor **200** moves away from the location where the maintain button image **312** was displayed (see FIG. 6), the display of the enlarged image **360** is maintained.

(70) The cancel button image **313** given as an example of a button image is displayed to receive, from the user, an instruction for canceling the maintaining of the display of the enlarged image **360**. In FIG. 7, the cancel button image **313** is displayed in the location where the maintain button image **312** (see FIG. 6) was displayed. Note that the cancel button image **313** may also be semitransparent such that the portion of the enlarged image **360** that is positioned behind the cancel button image **313** is visible through the cancel button image **313**.

(71) The cancel button image **313** is an image for receiving, from the user, an instruction for canceling the maintaining of the display of the enlarged image **360** corresponding to the first file icon **310a** with the file name "Sample1". Note that the cancel button image **313** may also be displayed in a different location from the location where the maintain button image **312** (see FIG. 6) was displayed, and the display position of the cancel button image **313** is not particularly limited. Moreover, the cancel button image **313** may also be added to the display without hiding the maintain button image **312**. The cancel button image **313** may also move together with the cursor **200**.

(72) In the case of the present exemplary embodiment, if the user selects the cancel button image **313**, the maintain button image **312** (see FIG. 5) that was hidden is displayed again. Specifically, if the user selects the cancel button image **313** from the state illustrated in FIG. 7, the display on the display **25** returns to the display illustrated in FIG. 6.

(73) In the present exemplary embodiment, if the cursor **200** moves from the state illustrated in FIG. 7 to the state illustrated in FIG. 8, the cancel button image **313** is hidden. In the present exemplary embodiment, the cancel button image **313** is hidden if the display changes from the state illustrated in FIG. 7 in which the cursor **200** is positioned over the corresponding image **370**, to the state illustrated in FIG. 8 in which the cursor **200** is away from the corresponding image **370**. In other words, if the cancel button image **313** is not selected and the cursor **200** is away from the corresponding image **370**, the cancel button image **313** is hidden. On the other hand, if the cursor **200** has not moved off the corresponding image **370**, the display of the cancel button image **313** is maintained.

(74) Note that in the present exemplary embodiment, the cancel button image **313** is hidden in this way if the cursor **200** moves off the corresponding image **370**, but the display of the cancel button image **313** may also be maintained even if the cursor **200** moves off the corresponding image **370**. Additionally, for example, the display of the cancel button image **313** may be maintained if the cursor **200** is positioned in the display area of the enlarged image **360**, and hidden if the cursor **200** moves out of the display area of the enlarged image **360**.

(75) In the present exemplary embodiment, if the cursor **200** that has moved off the corresponding image **370** (see FIG. **8**) goes back over the corresponding image **370**, the cancel button image **313** that was hidden is displayed again, as illustrated in FIG. **9**. In the present exemplary embodiment, the cancel button image **313** that is displayed again when the cursor **200** goes back over the corresponding image **370** moves together with the cursor **200**. Note that the cancel button image **313** may also not move together with the cursor **200**, and may be displayed again at a predetermined location on the corresponding image **370**.

(76) FIG. **10** is a diagram illustrating the state of the display **25** when the cursor **200** is moved off the corresponding image **370** and positioned over the enlarged image **360**. In the display example in FIG. **10**, a menu bar **380** for receiving user operations with respect to the enlarged image **360** is displayed. In the present exemplary embodiment, the menu bar **380** is displayed if the cursor **200** moves off the corresponding image **370**. The menu bar **380**, which is one example of a reception image, is an image for receiving user operations on the file corresponding to the enlarged image **360**. In the present exemplary embodiment, the menu bar **380** is displayed if the cursor **200** is positioned in the portion of the enlarged image **360** that is not overlapping with the corresponding image **370**.

(77) In the case of the present exemplary embodiment, the menu bar **380** is displayed at a position that does not readily obstruct the user's view of the enlarged image **360**. The display size of the menu bar **380** is not particularly limited, but preferably is a size enabling the user to see individual menu images **383** corresponding to menu options, while also being a size that does not readily obstruct the display of the enlarged image **360**. Note that the display size and shape of the menu bar **380** does not have to be uniform and may also be changed to fit the display **25** and the display size and shape of the enlarged image **360**.

(78) On the menu bar **380**, a page display field **382** for displaying the number of pages in the file and menu images **383** corresponding to various menu options are displayed. Examples of the menu images **383**, which are examples of a reception image, include images for changing the displayed page and editing the file. In the present exemplary embodiment, file editing work may be carried out by performing operations on the menu images **383**. Specific examples of editing work include inputting text and adding label images or stamp images.

(79) Other examples of the menu images **383** include an image for causing a history of edits to the file to be displayed. Other examples of the menu images **383** include an image for receiving a user operation for enlarging the display area of the menu bar **380**. If additional images are made to be displayed as the display area of the menu bar **380** is enlarged, the user is able to perform other types of operations. Otherwise, images for receiving operations such as transmitting the file to another user or the like may also be displayed on the menu bar **380**.

(80) In the display example in FIG. **10**, the cursor **200** is positioned over the enlarged image **360**, but is not positioned over the menu bar **380**. In other words, the display example in FIG. **10** illustrates a state in which the menu bar **380** is not be specified by the user. In this state, in the present exemplary embodiment, the transparency level of the menu bar **380** is set to semitransparent such that the portion of the enlarged image **360** that overlaps with the menu bar **380** is visible through the menu bar **380**.

(81) On the other hand, in the state in which the cursor **200** is positioned over the menu bar **380**, as illustrated in FIG. **11**, a process for lowering the transparency level of the menu bar **380** is performed. In other words, in the state in which the cursor **200** exists over the enlarged image **360**

and the menu bar **380** is being specified by the user, as illustrated in FIG. **11**, a process for lowering the transparency level of the menu bar **380** is performed. With this arrangement, the menu images **383** on the menu bar **380** are displayed more clearly.

(82) FIG. **12** is a diagram illustrating the state of the display **25** when a user operation is performed with respect to the menu images **383** on the menu bar **380**. In FIG. **12**, the enlarged image **360** is displayed on the display **25** to reflect a process corresponding to the operated menu images **383**.

(83) The display example in FIG. **12** illustrates a case where one of the menu images **383** has been selected. In this display example, an area for receiving text input is displayed on the enlarged image **360** in association with the selection of one of the menu images **383**, as indicated by the sign **384**.

Also, in the display example in FIG. **12**, the display location of the corresponding image **370** is changed. Specifically, the display location of the corresponding image **370** is changed to a location away from the enlarged image **360**. With this arrangement, the portion of the enlarged image **360** that was positioned behind the corresponding image **370** is displayed clearly.

(84) In this process example, if the user selects the menu images **383**, the display location of the corresponding image **370** is changed to a location away from the enlarged image **360**. In this case, the portion of the enlarged image **360** that was difficult to see due to the corresponding image **370** is seen more easily. Note that the display location of the corresponding image **370** does not have to be changed, and if the user selects the menu images **383**, the corresponding image **370** may be hidden, as illustrated in FIG. **13**.

(85) In the present exemplary embodiment, the corresponding image **370** given as one example of a file-corresponding image is hidden if a predetermined condition is satisfied. As described above, one example of the predetermined condition is that the menu images **383** included on the menu bar **380** are selected by the user. Other examples of the predetermined condition include the case where the cursor **200** remains stopped for an elapsed time equal to or greater than a threshold value and the case where the user gives an instruction for hiding the corresponding image **370**.

(86) Otherwise, the display location of the corresponding image **370** may be changed or the corresponding image **370** may be hidden even if the user does not select the menu images **383** included on the menu bar **380**. For example, the display location of the corresponding image **370** may be changed or the corresponding image **370** may be hidden when the user performs a mouseover on the menu bar **380**. In other words, the display location of the corresponding image **370** may be changed or the corresponding image **370** may be hidden when the menu images **383** are not selected by the user, but the cursor **200** is positioned over the menu bar **380**.

(87) In the example described above, only the corresponding image **370** that corresponds to the first file icon **310a** from which the display of the enlarged image **360** originates is displayed, but a corresponding image **370** that corresponds to another icon **310** different from the first file icon **310a** may also be displayed. For example, if another icon **310** different from the first file icon **310a** selected by the user is positioned behind the enlarged image **360**, the corresponding image **370** that corresponds to the other icon **310** may also be displayed. In this case, multiple corresponding images **370** are displayed.

(88) FIG. **14** is a diagram illustrating a display example on the display **25** in the case where multiple corresponding images **370** are displayed. In FIG. **14**, the enlarged image **360** and corresponding images **370** (**370a**, **370e**) are displayed on the display **25**. In the display example in FIG. **14**, the first file icon **310a** selected by the user and a second file icon **310e** are positioned behind the enlarged image **360**. In this process example, corresponding images **370** are displayed for all icons **310** positioned behind the enlarged image **360**. In the display example in FIG. **14**, the corresponding image **370a** that corresponds to the first file icon **310a** selected by the user and the corresponding image **370e** that corresponds to the second file icon **310e** are displayed.

(89) Note that the appearance may also be differentiated between the corresponding image **370** that corresponds to the icon **310** selected by the user and the corresponding image **370** that corresponds to the icon **310** not selected by the user. In other words, the corresponding image **370** that

corresponds to the icon **310** from which the display of the enlarged image **360** originates may have a different appearance from the corresponding image **370** that corresponds to the icon **310** from which the display of the enlarged image **360** does not originate.

(90) Specifically, for example, if the first file icon **310a** is selected by the user and the enlarged image **360** is displayed, an image indicating the selection is applied to the corresponding image **370a** that corresponds to the first file icon **310a**. On the other hand, an image is not applied to the corresponding image **370e** that corresponds to the second file icon **310e**. More specifically, for example, a rectangular frame image which surrounds the corresponding image **370a** and which is colored light blue, yellow, or the like is applied to the corresponding image **370a** that corresponds to the first file icon **310a**. On the other hand, a colored image is not applied to the corresponding image **370e** that corresponds to the second file icon **310e**.

(91) Otherwise, for example, the corresponding image **370a** that corresponds to the first file icon **310a** selected by the user and the corresponding image **370e** that corresponds to the second file icon **310e** may be colored differently. More specifically, the corresponding image **370a** that corresponds to the first file icon **310a** selected by the user is colored light blue, and the corresponding image **370e** that corresponds to the second file icon **310e** is colored yellow.

(92) As another example, the corresponding image **370a** that corresponds to the first file icon **310a** selected by the user may be configured to blink, and the corresponding image **370e** that corresponds to the second file icon **310e** may be configured not to blink. As another example, the corresponding image **370a** that corresponds to the first file icon **310a** selected by the user and the corresponding image **370e** that corresponds to the second file icon **310e** may be configured to have different display sizes.

(93) In the display example illustrated in FIG. **14**, a portion of the second file icon **310e** is positioned behind the enlarged image **360**. In the case of the present exemplary embodiment, the corresponding image **370** is displayed for the portion of the icon **310** that is positioned behind the enlarged image **360**. In FIG. **14**, the corresponding image **370e** that corresponds to the portion of the second file icon **310e** that is positioned behind the enlarged image **360** is displayed. In FIG. **14**, by using the corresponding image **370e** to display the portion that is positioned behind the enlarged image **360**, information about the second file icon **310e** is displayed.

(94) Otherwise, in a state in which the icon **310** not selected by the user is positioned behind the enlarged image **360**, the corresponding image **370** that corresponds to the icon **310** may be displayed if the user performs a specific operation. Specifically, for example, in FIG. **14**, the corresponding image **370e** corresponds to the icon **310** not selected by the user, but the corresponding image **370e** may also be displayed according to a specific operation performed by the user after the enlarged image **360** is displayed. Examples of the specific operation include an operation for changing the position of the cursor **200**, an operation for positioning the cursor **200** in a specific location, and an operation for giving an instruction to display the corresponding image **370**.

(95) Otherwise, the corresponding image **370** that corresponds to the icon **310** not selected by the user may also be hidden in response to a specific operation performed by the user after the enlarged image **360** is displayed. Examples of the operation by the user include an operation causing the cursor **200** to stop for a predetermined time or more, an operation for selecting a specific location, and an operation for giving an instruction to hide the corresponding image **370**.

(96) FIG. **15** is a diagram illustrating another display example on the display **25**. In the display example illustrated in FIG. **15**, like the case described above, the first file icon **310a** (see FIG. **4**; hidden in FIG. **15**) from which the enlarged image **360** originates is positioned behind the enlarged image **360**. In the display example, a corresponding image **370A** indicating information that corresponds to the first file icon **310a** selected by the user is displayed in a location apart from the display area of the enlarged image **360**.

(97) The corresponding image **370A** given as one example of a file-corresponding image is an

image that corresponds to the file represented by the first file icon **310a** from which the display of the enlarged image **360** originates. In the present exemplary embodiment, an arrow is also displayed in addition to the corresponding image **370A**, the arrow being an example of an image indicating the location where the first file icon **310a** was displayed.

(98) <Information to be Managed by Information Processing System>

(99) FIG. **16** is a diagram illustrating an example of information managed by the information processing system **1**. FIG. **16** illustrates information to be recorded in the secondary storage **12**, **22** as the information to be managed by the information processing system **1**.

(100) In the example illustrated in FIG. **16**, for each file managed by the information processing system **1**, a file identifier that identifies the file, a file name, and the position of the icon **310** corresponding to the file to be displayed in the workspace **400** are recorded in the secondary storage **12**, **22**. Also, for each file managed by the information processing system **1**, the path to a thumbnail image to be used in the display of the icon **310**, the path to an enlarged image to be used in the display of the enlarged image **360**, and the path to a file to be used in the display of the actual file are recorded in the secondary storage **12**, **22**.

(101) The information processing system **1** acquires the above information recorded in the secondary storage **12**, **22** on the basis of a user operation, and information to be used to control the display on the display **25** provided in the terminal device **20** is generated. Thereafter, the terminal device **20** controls the display according to the generated information. With this arrangement, the various screens are displayed on the display **25** of the terminal device **20**.

(102) Also, in the exemplary embodiment, the information processing system **1** manages the path to a corresponding image to be used in the display of the corresponding image **370**. Specifically, the information processing system **1** manages paths to corresponding images in units of files. In the case of displaying the corresponding image **370**, the information processing system **1** specifies the file for which the corresponding image **370** is to be displayed on the basis of the managed path to the corresponding image, and the corresponding image **370** corresponding to the specified file is displayed on the display **25**.

(103) <Flow of Processes>

(104) Next, a sequential flow of the processes described above will be described with reference to FIG. **17**. Note that the following takes the example of a case where the user uses the input unit **24** such as a mouse to move the cursor **200**, which is one example of a pointer image, over the display screen. Also, FIG. **17** illustrates the flow of processes for the case where the icon **310** from which the display of the enlarged image **360** originates is positioned behind the enlarged image **360**.

(105) In the exemplary embodiment, first, the terminal device **20** displays the enlarge button image **311** (see FIG. **4**) on the basis of a user operation performed via the input unit **24** (step **101**). Specifically, the terminal device **20** determines whether the cursor **200** is positioned over the icon **310** (see FIG. **4**), and displays the enlarge button image **311** if the cursor **200** is positioned over the icon **310**.

(106) Next, the terminal device **20** receives an instruction for temporarily displaying the enlarged image **360** (see FIG. **5**) on the basis of a user operation performed via the input unit **24** (step **102**). Specifically, the terminal device **20** determines whether a user operation was performed on the enlarge button image **311**, and receives the instruction for temporarily displaying the enlarged image **360** if there was an operation.

(107) In response, the terminal device **20** temporarily displays the enlarged image **360** on the display **25** (step **103**). Specifically, the terminal device **20** temporarily displays the enlarged image **360** at a higher level than the display level of the icon **310** on which the enlarge button image **311** that was operated by the user was displayed. The icon **310** from which the display of the enlarged image **360** originates is positioned behind the enlarged image **360**.

(108) Also, the terminal device **20** displays the corresponding image **370** on the display **25** (step **104**). Specifically, the terminal device **20** displays the corresponding image **370** corresponding to

the icon **310** from which the display of the enlarged image **360** originates in the location where the icon **310** was displayed.

(109) Next, the terminal device **20** specifies whether the cursor **200** is positioned over the corresponding image **370** (step **105**). If the cursor **200** is not positioned over the corresponding image **370** (S**105**, NO), the terminal device **20** hides the temporarily displayed enlarged image **360** (step **106**).

(110) On the other hand, if the cursor **200** is positioned over the corresponding image **370** (S**105**, YES), the terminal device **20** displays the maintain button image **312** (see FIG. 5) on the display **25** (step **107**). Next, the terminal device **20** receives an instruction for maintaining the display of the enlarged image **360** (step **108**). Specifically, the terminal device **20** determines whether a user operation was performed on the maintain button image **312**, and receives the instruction for maintaining the display of the enlarged image **360** if there was an operation.

(111) In response, the terminal device **20** maintains the display of the enlarged image **360** displayed on the display **25** (step **109**). Specifically, the terminal device **20** maintains the display of the enlarged image **360** even if the cursor **200** moves off the corresponding image **370**.

(112) Next, the terminal device **20** specifies whether the cursor **200** is positioned over the corresponding image **370** (step **110**). If the cursor **200** is not positioned over the corresponding image **370** (S**110**, NO), the terminal device **20** stands by until the cursor **200** is positioned over the corresponding image **370**.

(113) On the other hand, if the cursor **200** is positioned over the corresponding image **370** (S**110**, YES), the terminal device **20** displays the cancel button image **313** (see FIG. 7) on the display **25** (step **111**). Next, in this process example, the terminal device **20** receives an instruction for canceling the maintaining of the display of the enlarged image **360** (step **112**). Specifically, the terminal device **20** receives a user operation performed on the cancel button image **313**.

(114) In response, the terminal device **20** cancels the maintaining of the display of the enlarged image **360** displayed on the display **25** (step **113**). Next, if the cursor **200** moves off the corresponding image **370**, the terminal device **20** hides the enlarged image **360** (step **114**).

(115) (Other)

(116) The maintain button image **312** and the cancel button image **313** do not have move uniformly with the cursor **200**, and may be configured to move together with the cursor **200** if the user gives an instruction. In other words, for example, if the user selects a mode for changing the display location of the maintain button image **312** and the cancel button image **313**, the display location of the maintain button image **312** and the cancel button image **313** may be changed to move together with the cursor **200**.

(117) Also, the movement of the maintain button image **312** and the cancel button image **313** is not limited to being dependent on the movement of the cursor **200**, and may also depend on another condition. For example, the maintain button image **312** and the cancel button image **313** may be moved if the enlarged image **360** has been displayed for an elapsed time equal to or greater than a threshold value, or if an instruction for changing the display location of the maintain button image **312** and the cancel button image **313** is given.

(118) The foregoing description of the exemplary embodiments of the present disclosure has been provided for the purposes of illustration and description. It is not intended to be exhaustive or to limit the disclosure to the precise forms disclosed. Obviously, many modifications and variations will be apparent to practitioners skilled in the art. The embodiments were chosen and described in order to best explain the principles of the disclosure and its practical applications, thereby enabling others skilled in the art to understand the disclosure for various embodiments and with the various modifications as are suited to the particular use contemplated. It is intended that the scope of the disclosure be defined by the following claims and their equivalents.

Claims

1. An information processing system comprising: a processor configured to: cause an enlarged image to be displayed when a file image is selected, the file image being an image which is displayed on a display and which corresponds to a file, and the enlarged image being an image which corresponds to a selected file image, that is, the file image that is selected, and which has a larger display size than the selected file image; and cause a file-corresponding image to be displayed on the display when the selected file image is positioned behind the enlarged image, the file-corresponding image being an image that corresponds to the selected file image; cause a button image for receiving, from a user, an instruction related to the display of the enlarged image to be displayed in a location where the file-corresponding image is displayed; change the display location of the button image when the button image overlaps with an image on the enlarged image; and cause the button image to move together with a pointer image that indicates a user operation location on the display.
2. The information processing system according to claim 1, wherein the processor is configured to cause the file-corresponding image to be displayed in a location where the selected file image was displayed.
3. The information processing system according to claim 2, wherein the processor is configured to cause an image obtained by applying transparency to the selected file image to be displayed as the file-corresponding image.
4. The information processing system according to claim 1, wherein the processor is configured to hide the file-corresponding image when a predetermined condition is satisfied.
5. The information processing system according to claim 4, wherein the processor is configured to: cause a reception image for receiving a user operation with respect to the enlarged image to be displayed; and hide the file-corresponding image when the reception image is selected.
6. The information processing system according to claim 1, wherein when another file image different from the selected file image is positioned behind the enlarged image, the processor is configured to cause information about the other file image to also be displayed on the display.
7. The information processing system according to claim 6, wherein the processor is configured to differentiate an appearance of the file-corresponding image from an appearance of the information about the other file image.
8. The information processing system according to claim 6, wherein when a user performs a specific operation in a state in which the other file image is positioned behind the enlarged image, the processor is configured to cause the information about the other file image to be displayed on the display.
9. An information processing method comprising: causing an enlarged image to be displayed when a file image is selected, the file image being an image which is displayed on a display and which corresponds to a file, and the enlarged image being an image which corresponds to a selected file image, that is, the file image that is selected, and which has a larger display size than the selected file image; and causing a file-corresponding image to be displayed on the display when the selected file image is positioned behind the enlarged image, the file-corresponding image being an image that corresponds to the selected file image; causing a button image for receiving, from a user, an instruction related to the display of the enlarged image to be displayed in a location where the file-corresponding image is displayed; changing the display location of the button image when the button image overlaps with an image on the enlarged image; and causing the button image to move together with a pointer image that indicates a user operation location on the display.
10. A non-transitory computer readable medium storing a program causing a computer to execute a process comprising: causing an enlarged image to be displayed when a file image is selected, the file image being an image which is displayed on a display and which corresponds to a file, and the

enlarged image being an image which corresponds to a selected file image, that is, the file image that is selected, and which has a larger display size than the selected file image; and causing a file-corresponding image to be displayed on the display when the selected file image is positioned behind the enlarged image, the file-corresponding image being an image that corresponds to the selected file image; causing a button image for receiving, from a user, an instruction related to the display of the enlarged image to be displayed in a location where the file-corresponding image is displayed; changing the display location of the button image when the button image overlaps with an image on the enlarged image; and causing the button image to move together with a pointer image that indicates a user operation location on the display.
