

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12413003
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Tsai; Yu Lun et al.

Electrical connector

Abstract

An electrical connector includes a plurality of terminal groups arranged along a front-rear direction. Each terminal group is formed by a first terminal and a second terminal provided in the front-rear direction. The first terminal includes a first base portion and two first elastic arms connected to the first base portion. Each first elastic arm has a first contact portion located in front of the first base portion. The second terminal includes a second base portion and two second elastic arms connected to the second base portion. The second elastic arms are formed by extending backward and then bending and extending forward relative to the second base portion. Each second elastic arm has a second contact portion. In a same terminal group, along the front-rear direction, a distance between the first and second base portions is less than a distance between the first and second contact portions.

Inventors:	Tsai; Yu Lun (Keelung, TW), Jin; Zuo Feng (Keelung, TW)
Applicant:	LOTES CO., LTD (Keelung, TW)
Family ID:	83486654
Assignee:	LOTES CO., LTD (Keelung, TW)
Appl. No.:	18/119384
Filed:	March 09, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230318217 A1	Oct. 05, 2023

Foreign Application Priority Data

CN	202210354452.4	Apr. 02, 2022
CN	202210728668.2	Jun. 24, 2022

Publication Classification

Int. Cl.: H01R13/24 (20060101); H01R12/58 (20110101); H01R13/6471 (20110101)

U.S. Cl.:

CPC H01R13/2407 (20130101); H01R12/58 (20130101); H01R13/6471 (20130101);

Field of Classification Search

CPC: H01R (13/2407); H01R (12/58); H01R (13/6471); H01R (12/714); H01R (12/73); H01R (12/7076); H01R (13/2435); H01R (12/7082); H01R (13/6461); H01R (13/24); H05K (7/1069)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6729890	12/2003	Shin	439/74	H01R 13/26
6793504	12/2003	Noda et al.	N/A	N/A
8439709	12/2012	Fan	439/660	H01R 12/716
8708716	12/2013	Ho	439/83	H01R 12/714
9172161	12/2014	Walden	N/A	H01R 13/2435
9350091	12/2015	Huang	N/A	H01R 12/57
9882296	12/2017	Ju	N/A	H01R 13/2435
10199756	12/2018	Ju	N/A	H01R 13/2464
10547130	12/2019	Ju	N/A	H01R 13/46
10797424	12/2019	Hsu	N/A	H01R 12/7076
10998662	12/2020	Chen	N/A	H01R 12/714
11251557	12/2021	Dai	N/A	H01R 43/16
11309646	12/2021	Ou	N/A	H01R 12/7082
11817644	12/2022	Tsai	N/A	H01R 13/405
2010/0291774	12/2009	Cheng	439/66	H05K 7/1069
2013/0267118	12/2012	Cai	439/607.01	H01R 13/6581
2021/0151916	12/2020	Li et al.	N/A	N/A
2021/0210885	12/2020	Dai	N/A	H01R 13/2435
2021/0305754	12/2020	Ho	N/A	H01R 12/7082
2023/0018797	12/2022	Jin	N/A	H01R 13/516
2023/0075216	12/2022	Jin	N/A	H01R 13/6315
2024/0047904	12/2023	Huang	N/A	H01R 12/712

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
104518317	12/2014	CN	N/A

Primary Examiner: Nguyen; Truc T

Attorney, Agent or Firm: Troutman Pepper Locke LLP

Background/Summary

CROSS-REFERENCE TO RELATED PATENT APPLICATION

(1) This non-provisional application claims priority to and the benefit of, pursuant to 35 U.S.C. § 119(a), patent application Serial No. CN202210354452.4 filed in China on Apr. 2, 2022, and patent application Serial No. CN202210728668.2 filed in China on Jun. 24, 2022. The disclosure of each of the above applications is incorporated herein in its entirety by reference.

(2) Some references, which may include patents, patent applications and various publications, are cited and discussed in the description of this disclosure. The citation and/or discussion of such references is provided merely to clarify the description of the present disclosure and is not an admission that any such reference is “prior art” to the disclosure described herein. All references cited and discussed in this specification are incorporated herein by reference in their entireties and to the same extent as if each reference were individually incorporated by reference.

FIELD

(3) The present invention relates to an electrical connector, and particularly to an electrical connector having elastic conductive terminals of two different structures.

BACKGROUND

(4) The background description provided herein is for the purpose of generally presenting the context of the disclosure. Work of the presently named inventors, to the extent it is described in this background section, as well as aspects of the description that may not otherwise qualify as prior art at the time of filing, are neither expressly nor impliedly admitted as prior art against the present disclosure.

(5) In the field of the existing electrical connector, particularly the electrical connector for transmitting high frequency signals, the requirement for the signal integrity becomes higher. In the electrical connector, to ensure the signal integrity, particular to resolve the crosstalk issue during the signal transmission, it is required to focus on the design of the specific structure of the conductive terminals.

(6) As shown in FIG. 10, an electrical connector **100'** generally used for supporting a central processing unit (CPU) has only conductive terminals **2'** having a single structure. These conductive terminals **2'** face an identical direction in a local region, and two conductive terminals **2'** adjacent to each other in a front-rear direction form a terminal group **C'**. Each conductive terminal **2'** includes a base portion **21'** and an elastic arm **22** bending and extending from the base portion **21'**. The elastic arm **22'** is provided with a contact portion **221'** to be in contact with the CPU. The base portion **21'** occupies a larger proportion relative to the whole conductive terminal **2'**, and the base portions **21'** and the contact portions **221'** are arranged at equal distances. When the signals being transmitted have a higher frequency, the conductive terminals **2'** being densely arranged, particularly at the base portions **21'** thereof, have a serious crosstalk issue.

(7) Therefore, a heretofore unaddressed need to design an electrical connector exists in the art to address the aforementioned deficiencies and inadequacies.

SUMMARY

(8) In view of the deficiencies in the background art, the present invention is directed to an electrical connector, which has conductive terminals of two different structures, thus adjusting the distance between the structures of the different conductive terminals having a larger proportion thereof, and reducing the crosstalk between the signal terminals during the signal transmission.

(9) To achieve the foregoing objective, the present invention adopts the following technical solutions.

(10) An electrical connector includes a body and a plurality of conductive terminals accommodated in the body. The conductive terminals comprise a plurality of terminal groups arranged along a

front-rear direction, and each of the terminal groups is formed by a first terminal and a second terminal adjacent to each other in the front-rear direction. The first terminal comprises a first base portion and two first elastic arms connected to an upper end and a lower end of the first base portion, the first base portion and the two first elastic arms altogether form a first opening facing forward, each of the two first elastic arms has a first contact portion, and the first contact portion is located in front of the first base portion. The second terminal comprises a second base portion and two second elastic arms connected to an upper end and a lower end of the second base portion, the second elastic arms are formed by extending backward and then bending and extending forward relative to the second base portion, and each of the two second elastic arms has a second contact portion. In a same terminal group of the terminal groups, the first base portion and the second base portion are provided face-to-face in the front-rear direction, and in the front-rear direction, a distance between the first base portion and the second base portion is less than a distance between the first contact portion and the second contact portion.

(11) In certain embodiments, in the front-rear direction, the distance between the first contact portion and the second contact portion in the same terminal group is equal to a distance between the first contact portion and the second contact portion in two adjacent ones of the terminal groups.

(12) In certain embodiments, the first base portion and the second base portion respectively extend vertically, and the second contact portion is located behind the second base portion.

(13) In certain embodiments, the first elastic arm connected to the upper end of the first base portion is defined as a first upper elastic arm, the first elastic arm connected to the lower end of the first base portion is defined as a first lower elastic arm, the second elastic arm connected to the upper end of the second base portion is defined as a second upper elastic arm, the second elastic arm connected to the lower end of the second base portion is defined as a second lower elastic arm, a location of the second upper elastic arm connected to the second base portion is lower than a location of the first upper elastic arm connected to the first base portion, and a location of the second lower elastic arm connected to the second base portion is higher than a location of the first lower elastic arm connected to the first base portion.

(14) In certain embodiments, each of the second elastic arms has a first extending arm, a second extending arm and a bending portion connecting the first extending arm and the second extending arm, the first extending arm is formed by bending and extending backward from the second base portion, the second extending arm is formed by extending forward from the bending portion, and the bending portion and a location of each of the first elastic arms connected to the first base portion are provided to be of equal height.

(15) In certain embodiments, the first terminals and the second terminals of the terminal groups are arranged alternately along the front-rear direction, and in the same terminal group, one of the first terminal and the second terminal functions as a single-ended signal terminal, and the other of the first terminal and the second terminal functions as a ground terminal.

(16) In certain embodiments, in three adjacent ones of the terminal groups in the front-rear direction, a front terminal group thereof and a rear terminal group thereof include signal terminals configured to transmit differential signals, and a middle terminal group thereof includes ground terminals.

(17) In certain embodiments, the conductive terminals further comprise at least one third terminal, the third terminal and the terminal groups are arranged along the front-rear direction, one of the at least one third terminal is arranged between two adjacent ones of the terminal groups, each of the terminal groups is configured to transmit differential signals, and the third terminal is a ground terminal.

(18) In certain embodiments, a structure of the third terminal is identical to a structure of one of the first terminal and the second terminal adjacent thereto in the front-rear direction.

(19) In certain embodiments, the third terminal comprises a third base portion and two third elastic arms connected to an upper end and a lower end of the third base portion, the third base portion and

the two third elastic arms altogether form a third opening facing forward, each of the two third elastic arms has a third contact portion, the third contact portion is located in front of the third base portion, and in the front-rear direction, a distance between the second base portion and the first base portion adjacent thereto at one side of the second base portion is less than a distance between the second base portion and the third base portion adjacent thereto at the other side of the second base portion.

(20) In certain embodiments, the third terminal comprises a third base portion and two third elastic arms connected to an upper end and a lower end of the third base portion, each of the two third elastic arms has a third contact portion, and in the front-rear direction, a distance between the third contact portion and the first contact portion or the second contact portion adjacent thereto is equal to the distance between the first contact portion and the second contact portion in each of the terminal groups.

(21) In certain embodiments, each of the terminal groups comprises an add-on member conductively connected to the second terminal, the add-on member has a fourth base portion, the fourth base portion and the second base portion are provided face-to-face in the front-rear direction, and the fourth base portion and the first base portion are located at two opposite sides of the second base portion.

(22) In certain embodiments, the fourth base portion extends upward and downward to the two second elastic arms, and when the two second elastic arms are pressed, the fourth base portion abuts the two second elastic arms to form electrical connections therebetween.

(23) In certain embodiments, each of the second elastic arms has a first extending arm, a second extending arm and a bending portion connecting the first extending arm and the second extending arm, the first extending arm is formed by bending and extending backward from the second base portion, the second extending arm is formed by extending forward from the bending portion, and when the two second elastic arms are pressed, the fourth base portion abuts the two bending portions of the two second elastic arms.

(24) In certain embodiments, the add-on member has a connecting portion, the connecting portion is integrally connected to the fourth base portion, and the connecting portion is fixedly connected to or abuts the second base portion.

(25) In certain embodiments, in the same terminal group, a distance between the fourth base portion and the second base portion in the front-rear direction is greater than the distance between the first base portion and the second base portion in the front-rear direction.

(26) An electrical connector includes a body and a plurality of conductive terminals accommodated in the body. The conductive terminals comprise a plurality of terminal groups arranged along a front-rear direction, and each of the terminal groups is formed by a first terminal and a second terminal adjacent to each other in the front-rear direction. The first terminal comprises a first base portion and a first elastic arm connected to an upper end of the first base portion, the first base portion is in a flat plate shape, the first elastic arm is formed by bending forward from the first base portion or by bending backward and then forward from the first base portion, the first elastic arm has a first contact portion, and the first contact portion is located in front of the first base portion. The second terminal comprises a second base portion and a second elastic arm connected to an upper end of the second base portion, the second base portion is in a flat plate shape, the second elastic arm is formed by extending backward and then bending and extending forward relative to the second base portion, and the second elastic arm has a second contact portion. In a same terminal group of the terminal groups, the first base portion and the second base portion are provided face-to-face in the front-rear direction, and in the front-rear direction, a distance between the first base portion and the second base portion is less than a distance between the first contact portion and the second contact portion.

(27) In certain embodiments, the first terminal and the second terminal in each of the terminal groups are both ground terminals or are both signal terminals, the terminal groups being arranged

in the front-rear direction are arranged in a ground-signal alternate manner, and the terminal groups including both the signal terminals are configured to transmit differential signals.

(28) In certain embodiments, each of the terminal groups comprises an add-on member, the add-on member has a fourth base portion extending vertically, and the fourth base portion and one of the first base portion and the second base portion are provided face-to-face in the front-rear direction.

(29) In certain embodiments, the fourth base portion and the first base portion are located at two opposite sides of the second base portion, the add-on member has a connecting portion, the connecting portion is integrally connected to the fourth base portion, the connecting portion and the second base portion are fixed by soldering, and the add-on member and the second terminal are altogether assembled to the body.

(30) Compared with the related art, in order to adjust the distance between the respective portions of the first terminal and the second terminal occupying a larger proportion thereof, on the premise of maintaining a consistent final extending direction of the first elastic arm and the second elastic arm in the same terminal group without increasing the distance between the first contact portion and the second contact portion adjacent to each other, the second base portion is closer to the first base portion, such that the second elastic arm extend backward and then forward. When one of the first terminal and the second terminal of each terminal group functions as a single-ended signal terminal, and the other thereof functions as the ground terminal, since the first base portion and the second base portion are located closer relative to the first contact portion and the second contact portion, and the first base portion and the second base portion generally occupy a larger proportion in the whole conductive terminal, it is easier for the ground terminal to absorb the electromagnetic radiation emitted by the signal terminal, thus reducing the crosstalk, and enhancing the shielding effect between the signal terminals inside the electrical connector. When the terminal group is used to transmit differential signals, that is, it functions as a differential signal pair, the distance between the structures of the adjacent differential signal pairs having a larger proportions thereof is increased, thus reducing the mutual capacitance and mutual inductance between the differential signal pairs, and further reducing the crosstalk between the adjacent differential signal pairs.

(31) These and other aspects of the present invention will become apparent from the following description of the preferred embodiment taken in conjunction with the following drawings, although variations and modifications therein may be effected without departing from the spirit and scope of the novel concepts of the disclosure.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The accompanying drawings illustrate one or more embodiments of the disclosure and together with the written description, serve to explain the principles of the disclosure. Wherever possible, the same reference numbers are used throughout the drawings to refer to the same or like elements of an embodiment, and wherein:

(2) FIG. 1 is a partial disassembled view of an electrical connector according to a first embodiment of the present invention.

(3) FIG. 2 is an assembled view of FIG. 1.

(4) FIG. 3 is a sectional view of FIG. 2.

(5) FIG. 4 is a perspective view of a first terminal in FIG. 1.

(6) FIG. 5 is a perspective view of a second terminal in FIG. 1.

(7) FIG. 6 is a sectional view of an electrical connector according to a second embodiment of the present invention.

(8) FIG. 7 is a perspective view of a second terminal and an add-on member in use according to a third embodiment of the present invention.

(9) FIG. **8** is a perspective disassembled view of FIG. **7**.

(10) FIG. **9** is a sectional view of the third embodiment of the present invention.

(11) FIG. **10** is a schematic view of related art.

DETAILED DESCRIPTION

(12) The present invention is more particularly described in the following examples that are intended as illustrative only since numerous modifications and variations therein will be apparent to those skilled in the art. Various embodiments of the invention are now described in detail. Referring to the drawings, like numbers indicate like components throughout the views. As used in the description herein and throughout the claims that follow, the meaning of “a”, “an”, and “the” includes plural reference unless the context clearly dictates otherwise. Also, as used in the description herein and throughout the claims that follow, the meaning of “in” includes “in” and “on” unless the context clearly dictates otherwise. Moreover, titles or subtitles may be used in the specification for the convenience of a reader, which shall have no influence on the scope of the present invention.

(13) It will be understood that when an element is referred to as being “on” another element, it can be directly on the other element or intervening elements may be present therebetween. In contrast, when an element is referred to as being “directly on” another element, there are no intervening elements present. As used herein, the term “and/or” includes any and all combinations of one or more of the associated listed items.

(14) Furthermore, relative terms, such as “lower” or “bottom” and “upper” or “top,” may be used herein to describe one element's relationship to another element as illustrated in the Figures. It will be understood that relative terms are intended to encompass different orientations of the device in addition to the orientation depicted in the Figures. For example, if the device in one of the figures is turned over, elements described as being on the “lower” side of other elements would then be oriented on “upper” sides of the other elements. The exemplary term “lower”, can therefore, encompass both an orientation of “lower” and “upper,” depending of the particular orientation of the figure. Similarly, if the device in one of the figures is turned over, elements described as “below” or “beneath” other elements would then be oriented “above” the other elements. The exemplary terms “below” or “beneath” can, therefore, encompass both an orientation of above and below.

(15) As used herein, “around”, “about” or “approximately” shall generally mean within 20 percent, preferably within 10 percent, and more preferably within 5 percent of a given value or range. Numerical quantities given herein are approximate, meaning that the term “around”, “about” or “approximately” can be inferred if not expressly stated.

(16) As used herein, the terms “comprising”, “including”, “carrying”, “having”, “containing”, “involving”, and the like are to be understood to be open-ended, i.e., to mean including but not limited to.

(17) The description will be made as to the embodiments of the present invention in conjunction with the accompanying drawings in FIGS. **1-10**. In accordance with the purposes of this invention, as embodied and broadly described herein, this invention, in one aspect, relates to an electrical connector.

(18) FIG. **1** is a schematic view of an electrical connector **100** according to a first embodiment of the present invention. The electrical connector **100** has a body **1** and a plurality of conductive terminals **2**, and is used to connect two electronic components (not shown), and the two electronic components are in contact with the conductive terminals **2** through a plurality of contact points (not shown). For example, one of the electronic components may be a chip, and the other thereof may be a circuit board. For convenience of description purposes, the X direction in the accompanying drawings functions as the “forward” direction in the description, the Y direction in the accompanying drawings functions as the “left” direction in the description, and the Z direction in the accompanying drawings functions as the “upward” direction in the description, but the actual

application of the present invention is not limited thereto.

(19) As shown in FIG. 1 to FIG. 3, the body **1** is formed by an insulating material, and has a plurality of accommodating holes **11**. The accommodating holes **11** run vertically through an upper surface and a lower surface of the body **1**, and are used to accommodate the conductive terminals **2**.

(20) As shown in FIG. 1 to FIG. 3, the conductive terminals **2** are provided in a plurality of rows in the left-right direction. The conductive terminals **2** in each row include a plurality of terminal groups **C** arranged along the front-rear direction. Each terminal group **C** is formed by a first terminal **21** and a second terminal **22** adjacent to each other in the front-rear direction, and the structures of the first terminal **21** and the second terminal **22** are different. In the present embodiment, the first terminal **21** and the second terminal **22** are formed by punching a metal plate.

(21) As shown in FIG. 4, the first terminal **21** includes a first base portion **211** extending vertically and two first elastic arms **212** connected to an upper end and a lower end of the first base portion **211**, where the first elastic arm **212** connected to the upper end of the first base portion **211** is defined as a first upper elastic arm **212a**, and the first elastic arm **212** connected to the lower end of the first base portion **211** is defined as a first lower elastic arm **212b**. Each first elastic arm **212** has a first contact portion **2121** used to be in contact with some of the contact points (not shown). The first elastic arms **212** extend forward relative to the first base portion **211**, and the first base portion **211** and the two first elastic arms **212** altogether form a first opening **213** facing forward. The first contact portion **2121** is located in front of the first base portion **211**. In the present embodiment, the first base portion **211** is in a flat plate shape. In other embodiments, the first elastic arms **212** may be formed by bending backward and then bending and extending forward, and the first terminal **21** may be provided with only one first elastic arm **212**, which is connected to the upper end of the first base portion **211**. The lower end of the first base portion **211** is connected to a first soldering portion (not shown), which is used to be soldered to the circuit board (not shown).

(22) As shown in FIG. 4, the first terminal **21** is further provided with a first through slot **214** at a location of the first base portion **211** connected to each first elastic arm **212**. The first through slot **214** runs through the first terminal **21**, and the first through slot **214** extends on the first base portion **211** and each first elastic arm **212**. The two first through slots **214** are not in communication with each other. In other embodiments, the two first through slots **214** may be in communication with each other.

(23) As shown in FIG. 5, the second terminal **22** includes a second base portion **221** extending vertically and two second elastic arms **222** connected to an upper end and a lower end of the second base portion **221**, where the second elastic arm **222** connected to the upper end of the second base portion **221** is defined as a second upper elastic arm **222a**, and the second elastic arm **222** connected to the lower end of the second base portion **221** is defined as a second lower elastic arm **222b**. Each second elastic arm **222** has a first extending arm **2221**, a second extending arm **2222** and a bending portion **2223** connecting the first extending arm **2221** and the second extending arm **2222**. The first extending arm **2221** is formed by bending and extending backward from the second base portion **221**, and the second extending arm **2222** is formed by extending forward from the bending portion **2223**. That is, the second extending arm **2222** is formed by bending and extending backward relative to the second base portion **221**, and then bending and extending forward. The second base portion **221** and the two first extending arms **2221** altogether form a second opening **223** facing backward. Each second extending arm **2222** has a second contact portion **2224**, and the second contact portion **2224** is used to be in contact with some other contact points (not shown). In the present embodiment, the second base portion **221** is in a flat plate shape, and the second contact portion **2224** does not pass forward beyond the second base portion **221** in the front-rear direction. That is, the second contact portion **2224** is located behind the second base portion **221**. In other embodiments, the second contact portion **2224** may be provided to pass forward beyond the second base portion **221** in the front-rear direction. In yet another embodiment, the second terminal **22** may be provided with only one second elastic arm **222**, which is connected to the upper end of the

second base portion **221**. The lower end of the second base portion **221** is connected to a second soldering portion (not shown), which is used to be soldered to the circuit board (not shown).

(24) As shown in FIG. 5, the second terminal **22** is further provided with a second through slot **224** at a location of the second base portion **221** connected to each second elastic arm **222**. The second through slot **224** runs through the second terminal **22**, and the second through slot **224** extends on the second base portion **221** and each second elastic arm **222**. The two second through slots **224** are not in communication with each other. In other embodiments, the two second through slots **224** may be in communication with each other.

(25) As shown in FIG. 3, in a same terminal group C, the first base portion **211** and the second base portion **221** are provided face-to-face in the front-rear direction, and in the front-rear direction, a distance **L1** between the first base portion **211** and the second base portion **221** is less than a distance **L2** between the first contact portion **2121** and the second contact portion **2224**.

(26) As shown in FIG. 3, in the conductive terminals **2** in a same row, the first terminals **21** and the second terminals **22** of the terminal groups C are arranged alternately along the front-rear direction, and in the front-rear direction, a distance **L1** between the second base portion **221** and the first base portion **211** adjacent at a front side thereof is less than a distance **L3** between the second base portion **221** and the first base portion **211** adjacent at a rear side thereof. In the same terminal group C, the distance **L2** between the first contact portion **2121** and the second contact portion **2224** is equal to a distance **L4** between the first contact portion **2121** and the second contact portion **2224** in two adjacent terminal groups C, such that without changing the arrangement of the contact points of the chip and the arrangement of the contact points of the circuit board, adjustment is correspondingly made merely to the location of the second base portion **221** of the second terminal **22**, thus satisfying the high frequency requirement of the electrical connector **100**.

(27) As shown in FIG. 3, a location of the second upper elastic arm **222a** connected to the second base portion **221** is lower than a location of the first upper elastic arm **212a** connected to the first base portion **211**, and a location of the second lower elastic arm **222b** connected to the second base portion **221** is higher than a location of the first lower elastic arm **212b** connected to the first base portion **211**. The bending portion **2223** and a location of each first elastic arm **212** connected to the first base portion **211** are provided to be of equal height, and the second contact portion **2224** and the first contact portion **2121** are provided to be of equal height.

(28) As shown in FIG. 2 and FIG. 3, the terminal groups C may function as differential signal terminals or ground terminals. Alternatively, in each terminal group C, one of the first terminal **21** and the second terminal **22** functions as a single-ended signal terminal, and the other thereof functions as a ground terminal.

(29) As shown in FIG. 3, when one terminal of each terminal group C functions to transmit single-ended signals, and the other thereof functions as a ground terminal, for example, the first terminal **21** functions as the signal terminal and the second terminal **22** functions as the ground terminal, or the first terminal **21** functions as the ground terminal and the second terminal **22** functions as the signal terminal, since the first base portion **211** and the second base portion **221** in the same terminal group C are located closer relative to the first contact portion **2121** and the second contact portion **2224**, and the first base portion **211** and the second base portion **221** generally occupy a larger proportion in the whole conductive terminal **2**, it is easier for the ground terminal to absorb the electromagnetic radiation emitted by the signal terminal, thus reducing the crosstalk, and enhancing the shielding effect between the signal terminals inside the electrical connector **100**.

(30) As shown in FIG. 3, when some of the terminal groups C in the same row are used to transmit differential signals, that is, they function as differential signal pairs, and the other terminal groups C are used for grounding, for example, in three adjacent terminal groups C in the front-rear direction, the first terminal **21** and the second terminal **22** in each of a front terminal group C and a rear terminal group C are signal terminals used to transmit differential signals, and the first terminal **21** and the second terminal **22** in a middle terminal group C are ground terminals. In the present

embodiment of the present invention, the distance L3 between the second base portion **221** of the front terminal group C used to transmit the differential signals and the first base portion **211** of the rear terminal group C used to transmit the differential signals is greater than the distance L0 between the base portions **21'** of different differential terminal groups C' in the related art (also referring to FIG. 7). That is, the configuration of the present invention, compared to the related art, increases the distance between the structures of the different terminal groups C used to transmit the differential signals occupying a larger proportion thereof (the first base portion **211** and the second base portion **221**), and further reducing the interference between the different terminal groups C used to transmit the differential signals.

(31) FIG. 6 is a schematic view of an electrical connector **100** according to a second embodiment of the present invention. In the second embodiment, the structures and functions of the first terminal **21** and the second terminal **22** of each terminal group C are identical to those in the first embodiment, and the difference between the second embodiment and the first embodiment exists in that: the electrical connector **100** further includes at least one third terminal **23**, and the conductive terminals **2** in one row is provided with at least one third terminal **23**. The third terminal **23** and the terminal groups C in one row are arranged along the front-rear direction, and one third terminal **23** is arranged between two adjacent terminal groups C.

(32) As shown in FIG. 6, a structure of the third terminal **23** is identical to a structure of one of the first terminal **21** and the second terminal **22** adjacent thereto in the front-rear direction. The third terminal **23** includes a third base portion **231** extending vertically and two third elastic arms **232** connected to an upper end and a lower end of the third base portion **231**. Each third elastic arm **232** has a third contact portion **2321**. In the front-rear direction, a distance L1 between the second base portion **221** and the first base portion **211** adjacent thereto at one side of the second base portion **221** is less than a distance L5 between the second base portion **221** and the third base portion **231** adjacent thereto at the other side of the second base portion **221**, and a distance L6 between the third contact portion **2321** and the first contact portion **2121** adjacent thereto or a distance L7 between the third contact portion **2321** and the second contact portion **2224** adjacent thereto is equal to the distance L2 between the first contact portion **2121** and the second contact portion **2224** in each terminal group C.

(33) As shown in FIG. 6, in the present embodiment, the third base portion **231** is in a flat plate shape. The third contact portion **2321** is located in front of the third base portion **231**, and the third base portion **231** and the two third elastic arms **232** altogether form a third opening **233** facing forward. The structure of the third terminal **23** is completely identical to that of the first terminal **21**. In other embodiments, the structure of the third terminal **23** may be identical to that of the second terminal **22**, or may adopt other structures different from those of the first terminal **21** and the second terminal **22**.

(34) As shown in FIG. 6, in the present embodiment, the terminal groups C may be used to transmit differential signals, and the third terminal **23** functions as the ground terminal. When the first terminal **21** or the second terminal **22** of each terminal group C is used to transmit the single-ended signals, and the other terminal functions as the ground terminal, the third terminal **23** may function as the ground terminal or the signal terminal.

(35) FIG. 7 to FIG. 9 are schematic views of an electrical connector **100** according to a third embodiment of the present invention, which is different from the first embodiment in that: each terminal group C additionally includes an add-on member **24**. The second terminal **22** and the first terminal **21** are identical to those in the first embodiment.

(36) As shown in FIG. 7 and FIG. 8, the add-on member **24** has a fourth base portion **241** extending vertically and a connecting portion **242** extending horizontally from the fourth base portion **241**. An upper end of the fourth base portion **241** extends to the bending portion **2223** of the second upper elastic arm **222a**, and a lower end of the fourth base portion **241** extends to the bending portion **2223** of the second lower elastic arm **222b**. In the present embodiment, regardless of whether the

second elastic arms **222** are pressed by the electronic components, the fourth base portion **241** abuts the two bending portions **2223** in the front-rear direction. When the two second elastic arms **222** are pressed, the bending portions **2223** may slide vertically along the surface of the fourth base portion **241**. In other embodiments, it may be configured that only after the second elastic arms **222** are pressed, the fourth base portion **241** abuts and is connected to the two bending portions **2223**, and the second elastic arms **222** maintain a gap from the fourth base portion **241** prior to being pressed.

(37) As shown in FIG. 7 and FIG. 8, the add-on member **24** and the second terminal **22** are conductively connected to each other, but the add-on member **24** and the second terminal **22** are separately formed, and are connected to each other through the connecting portion **242**. The connecting portion **242** extends from a middle portion of the fourth base portion **241**, and is integrally connected to a middle portion of the second base portion **221**. In the present embodiment, the connecting portion **242** is connected to a side edge of the fourth base portion **241**, and is provided with a bonding portion **242a** which is in a flat plate shape. The bonding portion **242a** and the second base portion **221**, which is also in the flat plate shape, are attached to each other, and are fixed to each other through a laser soldering process.

(38) In other embodiments, the bonding portion **242a** and the second base portion **221** may be fixed to each other through spraying a conductive adhesive, or the connecting portion **242** and the second base portion **221** may be provided to fix with each other by clamping. Alternatively, the add-on member **24** and the second terminal **22** may be designed to be formed by integrally punching a metal plate. Alternatively, the second base portion **221** and the bonding portion **242a** merely abut each other.

(39) As shown in FIG. 9, the add-on member **22** and the second terminal **22** are assembled altogether in the body **1**, and are configured in the same accommodating hole **11**. In the same terminal group C, the fourth base portion **241** and the second base portion **221** are provided face-to-face in the front-rear direction, and the fourth base portion **241** and the first base portion **211** are located at two opposite sides of the second base portion **221**. A distance between the fourth base portion **241** and the second base portion **221** in the front-rear direction is greater than the distance between the first base portion **211** and the second base portion **221** in the front-rear direction.

(40) As shown in FIG. 9, the second terminal **22** being configured with the add-on member **24** forms a plurality of conductive paths, where the current starts from the second elastic arms **222**, which flows only through the second base portion **221**, or flows only through the fourth base portion **241**, or flows through the second base portion **221** and through the fourth base portion **241** through the connecting portion **242**. When the second terminal **22** being configured with the add-on member **24** functions as a signal terminal, compared to the second terminal **22** in the first embodiment, it reduces the impedance, and is suited to application scenarios with lower characteristics impedances.

(41) As shown in FIG. 9, when the second terminal **22** being configured with the add-on member **24** functions as the ground terminal, on one hand, the second base portion **221** is closer to the first base portion **211** located in front thereof, which provides better shielding effect to the first terminal **21** located in front thereof compared to the related art. On the other hand, the fourth base portion **241** remedies the distance between the second base portion **221** and the first base portion **211** located therebehind, thus providing the shielding effect to a certain degree to the first terminal **21** located therebehind for transmitting the signals compared to the first embodiment.

(42) In other embodiments, the add-on member **24** may be conductively connected to the first terminal **21** of the terminal group C, which may be soldered together, or may be fixed together by clamping, or may abut together to form an electrical connection therebetween. The add-on member **24** may also be assembled with the first terminal **21** of the terminal group C together in the body **1**, and arranged in the same accommodating hole **11**. Alternatively, they may be assembled in two processes, and the two components are assembled in the body **1** in the front-rear direction.

(43) In other embodiments, the first base portion, the second base portion, the third base portion and the fourth base portion may be provided to be substantially extending vertically instead of being strictly extending vertically straight. Using the first base portion as an example, it can be provided to extend vertically as a whole, but one section thereof is a bending structure or an oblique structure, etc. Alternatively, the first base portion may be, as a whole, slightly oblique relative to the vertical direction.

(44) In sum, the electrical connector according to certain embodiments of the present invention has the following beneficial effects: (1) In order to adjust the distance between the respective portions of the first terminal **21** and the second terminal **22** occupying a larger proportion thereof, on the premise of maintaining a consistent final extending direction of the first elastic arm **212** and the second elastic arm **222** in the same terminal group C without increasing the distance between the first contact portion **2121** and the second contact portion **2224** adjacent to each other, the second base portion **221** is closer to the first base portion **211**, such that the second elastic arm **222** extend backward and then forward. When one of the first terminal **21** and the second terminal **22** of each terminal group C functions as a single-ended signal terminal, and the other thereof functions as the ground terminal, since the first base portion **211** and the second base portion **221** are located closer relative to the first contact portion **2121** and the second contact portion **2224**, and the first base portion **211** and the second base portion **221** generally occupy a larger proportion in the whole conductive terminal **2**, it is easier for the ground terminal to absorb the electromagnetic radiation emitted by the signal terminal, thus reducing the crosstalk, and enhancing the shielding effect between the signal terminals inside the electrical connector **100**. When the terminal group C is used to transmit differential signals, that is, it functions as a differential signal pair, the distance between the structures of the adjacent differential signal pairs having a larger proportions thereof is increased, thus reducing the mutual capacitance and mutual inductance between the differential signal pairs, and further reducing the crosstalk between the adjacent differential signal pairs. (2) The second contact portion **2224** does not pass forward beyond the second base portion **221**, such that the overall size of the second terminal **22** in the front-rear direction is not very large, and the size of the accommodating hole **11** in the front-rear direction may be further designed not to be excessively large, thus providing more accommodating holes **11** in the insulating body **1** with limited space, and accommodating more conductive terminals **2**. (3) The location of the second upper elastic arm **222a** connected to the second base portion **221** is lower than the location of the first upper elastic arm **212a** connected to the first base portion **211**, and the location of the second lower elastic arm **222b** connected to the second base portion **221** is higher than the location of the first lower elastic arm **212b** connected to the first base portion **211**, thus increasing an included angle between the second base portion **221** and the first extending arm **2221**, and preventing the stress at the bending location of the two components from being excessively large. Further, the bending portion **2223** and the location of each first elastic arm **212** connected to the first base portion **211** are provided to be of equal height, such that the second contact portion **2224** and the first contact portion **2121** are provided to be of equal height, thereby ensuring the first terminal **21** and the second terminal **22** with different structures may be in coplanar contact with the mated electronic component, and preventing some of the conductive terminals **2** from being in ill contact due to having different heights. (4) The structure of the third terminal **23** is identical to the structure of one of the first terminal **21** and the second terminal **22** adjacent thereto in the front-rear direction, thus preventing from providing a mold for forming the third terminal **23**, and saving the cost. (5) By providing the first through slot **214** at the location of the first base portion **211** connected to each first elastic arm **212**, the first elastic arms **212** may easily bend relative to the first base portion **211**. Meanwhile, the self-capacitance of the first terminal **21** is increased, and the impedance of the first terminal **21** is reduced, such that it complies with a standard impedance range. By providing the second through slot **224** at the location of the second base portion **221** connected to each second elastic arm **222**, the second elastic arms **222** may easily bend relative to

the second base portion **221**. Meanwhile, the self-capacitance of the second terminal **22** is increased, and the impedance of the second terminal **22** is reduced, such that it complies with a standard impedance range. (6) The second terminal **22** being configured with the add-on member **24** forms a plurality of conductive paths, where the current starts from the second elastic arms **222**, which flows only through the second base portion **221**, or flows only through the fourth base portion **241**, or flows through the second base portion **221** and through the fourth base portion **241** through the connecting portion **242**. When the second terminal **22** being configured with the add-on member **24** functions as a signal terminal, compared to the second terminal **22** in the first embodiment, it reduces the impedance, and is suited to application scenarios with lower characteristic impedances. (7) When the second terminal **22** being configured with the add-on member **24** functions as the ground terminal, on one hand, the second base portion **221** is closer to the first base portion **211** located in front thereof, which provides better shielding effect to the first terminal **21** located in front thereof compared to the related art. On the other hand, the fourth base portion **241** remedies the distance between the second base portion **221** and the first base portion **211** located therebehind, thus providing the shielding effect to a certain degree to the first terminal **21** located therebehind for transmitting the signals compared to the first embodiment.

(45) The foregoing description of the exemplary embodiments of the invention has been presented only for the purposes of illustration and description and is not intended to be exhaustive or to limit the invention to the precise forms disclosed. Many modifications and variations are possible in light of the above teaching.

(46) The embodiments were chosen and described in order to explain the principles of the invention and their practical application so as to activate others skilled in the art to utilize the invention and various embodiments and with various modifications as are suited to the particular use contemplated. Alternative embodiments will become apparent to those skilled in the art to which the present invention pertains without departing from its spirit and scope. Accordingly, the scope of the present invention is defined by the appended claims rather than the foregoing description and the exemplary embodiments described therein.

Claims

1. An electrical connector, comprising: a body; and a plurality of conductive terminals accommodated in the body, wherein the conductive terminals comprise a plurality of terminal groups arranged along a front-rear direction, and each of the terminal groups is formed by a first terminal and a second terminal adjacent to each other in the front-rear direction; wherein the first terminal comprises a first base portion and two first elastic arms connected to an upper end and a lower end of the first base portion, the first base portion and the two first elastic arms altogether form a first opening facing forward, each of the two first elastic arms has a first contact portion, and the first contact portion is located in front of the first base portion; wherein the second terminal comprises a second base portion and two second elastic arms connected to an upper end and a lower end of the second base portion, the second elastic arms are formed by extending backward and then bending and extending forward relative to the second base portion, and each of the two second elastic arms has a second contact portion; and wherein in a same terminal group of the terminal groups, the first base portion and the second base portion are provided face-to-face in the front-rear direction, and in the front-rear direction, a distance between the first base portion and the second base portion is less than a distance between the first contact portion and the second contact portion.

2. The electrical connector according to claim 1, wherein in the front-rear direction, the distance between the first contact portion and the second contact portion in the same terminal group is equal to a distance between the first contact portion and the second contact portion in two adjacent ones of the terminal groups.

3. The electrical connector according to claim 1, wherein the first base portion and the second base portion respectively extend vertically, and the second contact portion is located behind the second base portion.
4. The electrical connector according to claim 1, wherein the first elastic arm connected to the upper end of the first base portion is defined as a first upper elastic arm, the first elastic arm connected to the lower end of the first base portion is defined as a first lower elastic arm, the second elastic arm connected to the upper end of the second base portion is defined as a second upper elastic arm, the second elastic arm connected to the lower end of the second base portion is defined as a second lower elastic arm, a location of the second upper elastic arm connected to the second base portion is lower than a location of the first upper elastic arm connected to the first base portion, and a location of the second lower elastic arm connected to the second base portion is higher than a location of the first lower elastic arm connected to the first base portion.
5. The electrical connector according to claim 4, wherein each of the second elastic arms has a first extending arm, a second extending arm and a bending portion connecting the first extending arm and the second extending arm, the first extending arm is formed by bending and extending backward from the second base portion, the second extending arm is formed by extending forward from the bending portion, and the bending portion and a location of each of the first elastic arms connected to the first base portion are provided to be of equal height.
6. The electrical connector according to claim 1, wherein the first terminals and the second terminals of the terminal groups are arranged alternately along the front-rear direction, and in the same terminal group, one of the first terminal and the second terminal functions as a single-ended signal terminal, and the other of the first terminal and the second terminal functions as a ground terminal.
7. The electrical connector according to claim 1, wherein in three adjacent ones of the terminal groups in the front-rear direction, a front terminal group thereof and a rear terminal group thereof include signal terminals configured to transmit differential signals, and a middle terminal group thereof includes ground terminals.
8. The electrical connector according to claim 1, wherein the conductive terminals further comprise at least one third terminal, the third terminal and the terminal groups are arranged along the front-rear direction, one of the at least one third terminal is arranged between two adjacent ones of the terminal groups, each of the terminal groups is configured to transmit differential signals, and the third terminal is a ground terminal.
9. The electrical connector according to claim 8, wherein a structure of the third terminal is identical to a structure of one of the first terminal and the second terminal adjacent thereto in the front-rear direction.
10. The electrical connector according to claim 8, wherein the third terminal comprises a third base portion and two third elastic arms connected to an upper end and a lower end of the third base portion, the third base portion and the two third elastic arms altogether form a third opening facing forward, each of the two third elastic arms has a third contact portion, the third contact portion is located in front of the third base portion, and in the front-rear direction, a distance between the second base portion and the first base portion adjacent thereto at one side of the second base portion is less than a distance between the second base portion and the third base portion adjacent thereto at the other side of the second base portion.
11. The electrical connector according to claim 8, wherein the third terminal comprises a third base portion and two third elastic arms connected to an upper end and a lower end of the third base portion, each of the two third elastic arms has a third contact portion, and in the front-rear direction, a distance between the third contact portion and the first contact portion or the second contact portion adjacent thereto is equal to the distance between the first contact portion and the second contact portion in each of the terminal groups.
12. The electrical connector according to claim 1, wherein each of the terminal groups comprises

an add-on member conductively connected to the second terminal, the add-on member has a fourth base portion, the fourth base portion and the second base portion are provided face-to-face in the front-rear direction, and the fourth base portion and the first base portion are located at two opposite sides of the second base portion.

13. The electrical connector according to claim 12, wherein the fourth base portion extends upward and downward to the two second elastic arms, and when the two second elastic arms are pressed, the fourth base portion abuts the two second elastic arms to form electrical connections therebetween.

14. The electrical connector according to claim 13, wherein each of the second elastic arms has a first extending arm, a second extending arm and a bending portion connecting the first extending arm and the second extending arm, the first extending arm is formed by bending and extending backward from the second base portion, the second extending arm is formed by extending forward from the bending portion, and when the two second elastic arms are pressed, the fourth base portion abuts the two bending portions of the two second elastic arms.

15. The electrical connector according to claim 12, wherein the add-on member has a connecting portion, the connecting portion is integrally connected to the fourth base portion, and the connecting portion is fixedly connected to or abuts the second base portion.

16. The electrical connector according to claim 12, wherein in the same terminal group, a distance between the fourth base portion and the second base portion in the front-rear direction is greater than the distance between the first base portion and the second base portion in the front-rear direction.

17. An electrical connector, comprising: a body; and a plurality of conductive terminals accommodated in the body, wherein the conductive terminals comprise a plurality of terminal groups arranged along a front-rear direction, and each of the terminal groups is formed by a first terminal and a second terminal adjacent to each other in the front-rear direction; wherein the first terminal comprises a first base portion and a first elastic arm connected to an upper end of the first base portion, the first base portion is in a flat plate shape, the first elastic arm is formed by bending forward from the first base portion or by bending backward and then forward from the first base portion, the first elastic arm has a first contact portion, and the first contact portion is located in front of the first base portion; wherein the second terminal comprises a second base portion and a second elastic arm connected to an upper end of the second base portion, the second base portion is in a flat plate shape, the second elastic arm is formed by extending backward and then bending and extending forward relative to the second base portion, and the second elastic arm has a second contact portion; and wherein in a same terminal group of the terminal groups, the first base portion and the second base portion are provided face-to-face in the front-rear direction, and in the front-rear direction, a distance between the first base portion and the second base portion is less than a distance between the first contact portion and the second contact portion.

18. The electrical connector according to claim 17, wherein the first terminal and the second terminal in each of the terminal groups are both ground terminals or are both signal terminals, the terminal groups being arranged in the front-rear direction are arranged in a ground-signal alternate manner, and the terminal groups including both the signal terminals are configured to transmit differential signals.

19. The electrical connector according to claim 17, wherein each of the terminal groups comprises an add-on member, the add-on member has a fourth base portion extending vertically, and the fourth base portion and one of the first base portion and the second base portion are provided face-to-face in the front-rear direction.

20. The electrical connector according to claim 19, wherein the fourth base portion and the first base portion are located at two opposite sides of the second base portion, the add-on member has a connecting portion, the connecting portion is integrally connected to the fourth base portion, the

connecting portion and the second base portion are fixed by soldering, and the add-on member and the second terminal are altogether assembled to the body.
