

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12383437
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Weber; Ainas et al.

Smart absorbent articles

Abstract

An absorbent article for personal hygiene such as a diaper, or training pant, or incontinence insert, the absorbent article comprising: a liquid permeable topsheet; a liquid impermeable backsheet; an absorbent core positioned between said topsheet and backsheet, an indicator for indicating the presence of exudates and being positioned on a body-facing side of said backsheet, the indicator comprising an electrically conductive material, the article further comprising a detection device that can be removably attached to the absorbent article such to become in electrical communication with said indicator when attached to said article to measure a change in resistance or capacitance in response to a voiding event, wherein the absorbent core comprises a core wrap enclosing absorbent material therein and wherein a top layer of the core wrap is joined to a bottom layer of the core wrap to form one or more channels substantially free of absorbent material, and wherein the indicator comprises a pattern that extends inboard and/or outboard of said channel(s) such that it does not substantially overlap with said channel(s).

Inventors:	Weber; Ainas (Bad Neuenahr-Ahrweiler, DE), Hellmold; Jens (Beckum, DE), Heirman; Lisa (Waasmunster, BE), Idelson; Alissa (Rheinbach, DE)
Applicant:	ONTEX BV (Buggenhout, BE); ONTEX GROUP NV (Erembodegem, BE)
Family ID:	70189780
Assignee:	ONTEX BV (Buggenhout, BE); ONTEX GROUP NV (Erembodegem, BE)
Appl. No.:	17/915886
Filed (or PCT Filed):	April 01, 2021
PCT No.:	PCT/EP2021/058692
PCT Pub. No.:	WO2021/198460

PCT Pub. Date: October 07, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20230129630 A1	Apr. 27, 2023

Foreign Application Priority Data

EP	20168093	Apr. 03, 2020
----	----------	---------------

Publication Classification

Int. Cl.: A61F13/42 (20060101); A61F13/532 (20060101)

U.S. Cl.:

CPC A61F13/42 (20130101); A61F13/532 (20130101); A61F2013/422 (20130101)

Field of Classification Search

CPC: A61F (13/42); A61F (13/532); A61F (2013/422)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3860003	12/1974	Buell	N/A	N/A
4515595	12/1984	Kievit et al.	N/A	N/A
4681793	12/1986	Linman et al.	N/A	N/A
4710189	12/1986	Lash	N/A	N/A
5151092	12/1991	Buell et al.	N/A	N/A
5221274	12/1992	Buell et al.	N/A	N/A
5554145	12/1995	Roe et al.	N/A	N/A
5569234	12/1995	Buell et al.	N/A	N/A
5571096	12/1995	Dobrin et al.	N/A	N/A
5580411	12/1995	Nease et al.	N/A	N/A
5865823	12/1998	Curro	N/A	N/A
5938648	12/1998	Lavon et al.	N/A	N/A
6004306	12/1998	Robles et al.	N/A	N/A
6093869	12/1999	Roe	604/385.12	A61F 13/42
6583722	12/2002	Jeutter	340/941	A61F 13/42
6632504	12/2002	Gillespie et al.	N/A	N/A
6946585	12/2004	Brown	N/A	N/A
7352286	12/2007	Chan	340/603	A61F 13/505
7700821	12/2009	Ales, III	604/361	A61F 13/42
8421636	12/2012	Collette	340/573.5	A61F 13/42
8471715	12/2012	Solazzo	340/573.5	A61F 13/42
9675496	12/2016	Alkhamis	N/A	A61F 13/42

10624795	12/2019	Christiansen	N/A	A61F 13/42
11083636	12/2020	Potter	N/A	A61F 13/42
11173073	12/2020	MacNaughton	N/A	G08B 21/20
11173074	12/2020	Love	N/A	A61F 13/53
11229557	12/2021	Kurt	N/A	A61F 13/513
11278457	12/2021	Benz	N/A	A61F 13/42
11457848	12/2021	Harmeyer	N/A	A61B 5/369
11617689	12/2022	Kurt	340/539.11	A61F 13/53
11806219	12/2022	Kurt	N/A	A61F 13/513
12178689	12/2023	Kurt	N/A	A61F 13/42
12285320	12/2024	Love	N/A	A61G 7/05
2002/0021220	12/2001	Dreyer	340/573.1	G09B 19/0076
2002/0070864	12/2001	Jeutter	340/539.1	A61F 13/42
2004/0220538	12/2003	Panopoulos	604/361	A61F 13/42
2007/0049883	12/2006	Ales, III	604/361	A61F 13/42
2007/0083174	12/2006	Ales, III	604/361	A61F 13/42
2007/0270774	12/2006	Bergman	604/361	G16H 40/60
2008/0243099	12/2007	Tippey	604/361	A61F 13/15699
2008/0297325	12/2007	Torstensson	340/10.42	A61F 13/84
2010/0241094	12/2009	Sherron	604/361	A61F 13/42
2011/0319845	12/2010	Kuo	604/361	A61F 13/42
2013/0018231	12/2012	Hong	600/300	A61F 13/42
2013/0036802	12/2012	Johnson	73/74	A61F 13/42
2013/0076509	12/2012	Ahn	340/539.12	A61F 13/42
2013/0110063	12/2012	Abraham	604/361	G16H 40/67
2013/0123726	12/2012	Yu	235/492	H01Q 1/273
2014/0148772	12/2013	Hu	604/385.01	A61F 13/42
2014/0155850	12/2013	Shah	604/361	A61F 13/42
2014/0200538	12/2013	Euliano	604/361	A61F 13/42
2014/0324004	12/2013	Song	436/2	B32B 5/26
2015/0080819	12/2014	Charna	604/361	A61F 13/42
2015/0173968	12/2014	Joseph	604/361	A61F 13/5323
2016/0310329	12/2015	Patel	N/A	A61F 13/42
2017/0079858	12/2016	Willhaus	N/A	A61F 13/532
2017/0156594	12/2016	Stivoric	N/A	A61B 5/0008
2017/0252225	12/2016	Arizti	N/A	A61F 13/42
2018/0116878	12/2017	MacNaughton	N/A	G08B 21/20
2018/0263827	12/2017	Omori	N/A	G06K 19/0717
2018/0333306	12/2017	Ahong	N/A	A61B 5/6843
2019/0240078	12/2018	Li	N/A	G01B 7/02
2019/0262191	12/2018	Li	N/A	A61F 13/53
2019/0290501	12/2018	LaVon	N/A	A61F 13/51401
2020/0046573	12/2019	Douseki	N/A	G01N 27/416
2021/0093244	12/2020	Monson	N/A	A61B 5/0022
2021/0128368	12/2020	Chan	N/A	A61B 5/4318
2022/0168154	12/2021	Dean	N/A	A61B 5/202
2022/0192897	12/2021	Whitely	N/A	A61F 13/496

2023/0165728	12/2022	Dean	604/361	G16H 40/67
2023/0293335	12/2022	Hansen	604/344	A61B 5/0002

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2740450	12/2013	EP	N/A
2496197	12/2014	EP	N/A
2582341	12/2015	EP	N/A
2739254	12/2015	EP	N/A
3213727	12/2016	EP	H01Q 1/243
3415130	12/2017	EP	N/A
3451988	12/2019	EP	N/A
3747415	12/2019	EP	N/A
3461257	12/2020	EP	N/A
2012125452	12/2011	JP	N/A
1995016746	12/1994	WO	N/A
2008155699	12/2007	WO	N/A
2011163582	12/2010	WO	N/A
2012052172	12/2011	WO	N/A
2018228822	12/2017	WO	N/A
2018229017	12/2017	WO	N/A

OTHER PUBLICATIONS

International Search Report and Written Opinion for PCT/EP2021/058692, mailed Jun. 14, 2021.
cited by applicant

Primary Examiner: Townsend; Guy K

Attorney, Agent or Firm: VIVICAR Law, PLLC

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

(1) This application is the national stage application of corresponding international application number PCT/EP2021/058692, filed Apr. 1, 2021, which claims priority to and the benefit of European application no. 20168093.1 filed Apr. 3, 2020, which is hereby incorporated by reference in its entirety.

TECHNICAL FIELD

(2) The present disclosure is directed to an absorbent article for personal hygiene (such as baby or adult diapers, pants or incontinence briefs or pads) and a system for monitoring thereof.

BACKGROUND

(3) Absorbent articles for personal hygiene are designed to absorb and contain bodily exudates, such as a large quantity of urine. Non-limiting examples of disposable absorbent articles include diapers, pants, training pants, pADL, adult incontinence products, and feminine hygiene products (including, for example, sanitary napkins and tampons). Other examples of disposable absorbent articles include bandages and wound dressings. In some embodiments, for example, an absorbent article comprises several layers providing different functions, for example a topsheet, a backsheet and in-between an absorbent core, among other layers.

(4) The function of the absorbent core is to absorb and retain the exudates for a prolonged amount of time, for example overnight for a diaper, minimize re-wet to keep the wearer dry and avoid soiling of clothes or bed sheets. The majority of currently marketed absorbent articles comprise as absorbent material a blend of comminuted wood pulp with superabsorbent polymers (SAP) in particulate form, also called absorbent gelling materials (AGM), see for example U.S. Pat. No. 5,151,092 (Buell). Absorbent articles having a core consisting essentially of SAP as absorbent material (so called “airfelt-free” cores) have also been proposed but are less common than traditional mixed cores (see e.g. WO2008/155699 and WO2012/052172).

(5) A number of disclosures exist (see for example EP2496197B1, EP2739254B1, and EP2582341B1) directed to sensors to sense a condition such as temperature from body or moisture from incontinence. The sensor comprises a signal processing unit, a transmitter and a power supply, typically in form of a battery. These elements are arranged on a flexible substrate in low profile enabling disposition adjacent to the human body. A complex series of mathematical and statistical manipulations are then needed in order to determine wetness events and wetness levels.

(6) While such devices allow monitoring conditions of the human body and can also be used as a moisture sensor, it represents also relatively costly solution. It would not be seen appropriate to dispose of the sensor together with a (disposable) absorbent article. If the sensor, however, is to be reused, the sensing area has potentially been exposed to moisture. Therefore this concept does not allow for simple usage.

(7) Examples of articles that provide improvements to the above drawbacks are disclosed in EP3415130, WO/2018/228822, WO/2018/229017, EP3461257, and EP3451988. Moreover improved incontinence management systems are for example described on co-pending application EP19178665.6.

(8) A need nevertheless exists for improved monitoring devices especially those having fluid distribution enhancing features such as channels.

(9) A need also exists to provide an environmentally friendly solution for automatic voiding pattern detection preferably that can be further used to monitor the babies development or an adult's incontinence pattern and/or risk of leakage.

SUMMARY

(10) In a first aspect the disclosure relates to an absorbent article for personal hygiene such as a diaper, or training pant, or incontinence insert, the absorbent article comprising: a liquid permeable topsheet; a liquid impermeable backsheets; an absorbent core positioned between said topsheet and backsheets, an indicator for indicating the presence of exudates and being positioned on a body-facing side of said backsheets, the indicator comprising an electrically conductive material, the article further comprising a detection device that can be removably attached to the absorbent article such to become in electrical communication with said indicator when attached to said article to measure a change in resistance or capacitance in response to a voiding event, wherein the absorbent core comprises a core wrap enclosing absorbent material therein and wherein a top layer of the core wrap is joined to a bottom layer of the core wrap to form one or more channels substantially free of absorbent material, and wherein the indicator comprises a pattern that extends inboard and/or outboard of said channel(s) such that it does not substantially overlap with said channel(s).

(11) In a second aspect the disclosure relates to a kit comprising an absorbent article and a detection device, wherein the kit comprises a plurality of the absorbent articles and a detection device, wherein the detection device is removably attached to the absorbent articles, one after another as they are used, and wherein the detection device is arranged to stop working after a predetermined period of time, preferably wherein the predetermined period of time is more than 20 days and less than 50 days, more preferably from 30 days to 40 days.

Description

BRIEF DESCRIPTION OF THE FIGURES

- (1) FIG. 1 is a top view of an absorbent article according to an embodiment of the present disclosure in the form of a diaper with some layers partially removed.
- (2) FIG. 2 is a transversal cross-section of the embodiment of FIG. 1 at the crotch area.
- (3) FIG. 3 is a corresponding transversal cross-section of another embodiment of an absorbent article.
- (4) FIG. 4 is a further corresponding transversal cross-section of an embodiment of the present disclosure.
- (5) FIG. 5 shows a partial schematic view of an example embodiment of a reusable detector device that may be removably attached externally to a diaper, such as shown in FIG. 4
- (6) FIG. 6 shows a block diagram of an example implementation of a detector device adapted for removably coupling with one or more diapers.
- (7) FIG. 7 shows top, bottom and side views of an example embodiment of an exterior of a detector device, such as the one shown in FIG. 6.
- (8) FIG. 8 shows an example embodiment an attachment zone of a diaper exterior adapted for receiving a detector device, such as the detector device shown in FIGS. 6-7.
- (9) FIG. 9 shows a flow diagram of example operations that may be used to detect one or more bodily exudates within a diaper.
- (10) FIG. 10 shows example embodiments of spaced optical sensor and light element 604 pairs of example embodiments of one or more detector devices.
- (11) FIG. 11 shows another example embodiment of a detector device. In this embodiment, for example, an optical sensor and a light element are spaced from each other.
- (12) FIG. 12 shows another example embodiment of a detector device comprising a plurality of spaced optical sensor and light pairs.
- (13) FIG. 13 shows yet another example embodiment of a detector device comprising a plurality of spaced optical sensor and light pairs.
- (14) FIG. 14 shows still another example embodiment of a detector device comprising a plurality of spaced optical sensor and light pairs.
- (15) FIG. 15 shows an example embodiment of an absorbent article including a detector device coupled to the absorbent article.
- (16) FIG. 16 shows another example embodiment of an absorbent article including a plurality of property changing indicators disposed within the absorbent article.
- (17) FIG. 17 shows yet another example embodiment of an absorbent article including a plurality of property changing indicators disposed within the absorbent article.
- (18) FIG. 18 is a top view of an absorbent article according to an embodiment of the present disclosure in the form of a diaper with some layers partially removed.
- (19) FIG. 19 is a top view of an absorbent article according to an embodiment of the present disclosure in the form of a diaper with some layers partially removed.
- (20) FIG. 20 is a top view of an absorbent article according to an embodiment of the present disclosure in the form of a diaper with some layers partially removed.
- (21) FIG. 21 is a perspective view of the taped diaper according to embodiments herein as it may appear when worn before and after loading.
- (22) FIG. 22 is a schematic representation of part of a process flow according to embodiments herein.
- (23) FIG. 23 is a schematic representation of part of a process flow according to embodiments herein.
- (24) FIG. 24 is a schematic representation of a system according to embodiments herein.
- (25) FIG. 25 is a top view of an absorbent article according to an embodiment of the present disclosure in the form of a diaper with some layers partially removed.

DETAILED DESCRIPTION

(26) Unless otherwise defined, all terms used in disclosing characteristics of the disclosure, including technical and scientific terms, have the meaning as commonly understood by one of ordinary skill in the art to which this disclosure belongs. By means of further guidance, term definitions are included to better appreciate the teaching of the present disclosure.

(27) As used herein, the following terms have the following meanings:

(28) “A”, “an”, and “the” as used herein refers to both singular and plural referents unless the context clearly dictates otherwise. By way of example, “a compartment” refers to one or more than one compartment.

(29) “About” as used herein referring to a measurable value such as a parameter, an amount, a temporal duration, and the like, is meant to encompass variations of $\pm 20\%$ or less, preferably $\pm 10\%$ or less, more preferably $\pm 5\%$ or less, even more preferably $\pm 1\%$ or less, and still more preferably $\pm 0.1\%$ or less of and from the specified value, in so far such variations are appropriate to perform in the disclosed disclosure. However, it is to be understood that the value to which the modifier “about” refers is itself also specifically disclosed.

(30) The expression “% by weight” (weight percent), here and throughout the description unless otherwise defined, refers to the relative weight of the respective component based on the overall weight of the formulation.

(31) The recitation of numerical ranges by endpoints includes all numbers and fractions subsumed within that range, as well as the recited endpoints unless otherwise stated.

(32) As used herein, the “skin facing”, “body-facing” or “bodyside” surface means that surface of the article or component which is intended to be disposed toward or placed adjacent to the body of the wearer during ordinary use, while the “outward”, “outward-facing” or “garment-side” or “garment facing” surface is on the opposite side, and is intended to be disposed to face away from the wearer's body during ordinary use. Such outward surface may be arranged to face toward or placed adjacent to the wearer's garments or undergarments when the absorbent article is worn.

(33) As used herein “channels” are fluid distribution means within the absorbent core adapted to favour exudate flow therealong and are typically intended to exclude embossing patterns or ducts formed by compression and rather include structures that are substantially free of absorbent material instead of comprising compacted absorbent material. Channels herein can be formed by joining upper and lower layers of a core wrap as will be described in more detail hereinbelow or may be achieved by removing absorbent material such as by cutting.

(34) As used herein, the term “absorbent article” refers to disposable devices such as infant or adult diapers or pads, pants, training pants, and the like which are placed against or in proximity to the body of the wearer to absorb and contain the various exudates discharged from the body. Typically these articles comprise a topsheet, backsheet, an absorbent core and optionally an acquisition system (which may be comprised of one or several layers) and typically other components, with the absorbent core normally placed between the backsheet and the acquisition system or topsheet.

(35) The absorbent articles of the disclosure will be further illustrated in the below description and in the Figures in the form of a taped diaper, though all embodiments described herein may equally be applied onto absorbent articles in the form of pants (or even in the form of feminine hygiene or incontinence liners). Nothing in this description should be however considered limiting the scope of the claims unless explicitly indicated otherwise. Unless indicated otherwise, the description refers to the dry article, i.e. before use and conditioned at least 24 hours at $21^{\circ}\text{C.} \pm 2^{\circ}\text{C.}$ and $50 \pm 20\%$ Relative Humidity (RH).

(36) A “nonwoven web” as used herein means a manufactured sheet, web or batt of directionally or randomly orientated fibers, bonded by friction, and/or cohesion and/or adhesion, excluding paper and products which are woven, knitted, tufted, stitch-bonded incorporating binding yarns or filaments, or felted by wet-milling, whether or not additionally needled. The fibers may be of natural or man-made origin and may be staple or continuous filaments or be formed in situ.

Commercially available fibers have diameters ranging from less than about 0.001 mm to more than about 0.2 mm and they come in several different forms such as short fibers (known as staple, or chopped), continuous single fibers (filaments or monofilaments), untwisted bundles of continuous filaments (tow), and twisted bundles of continuous filaments (yarn). Nonwoven webs can be formed by many processes such as meltblowing, spunbonding, solvent spinning, electrospinning, carding and airlaying. The basis weight of nonwoven webs is usually expressed in grams per square meter (g/m² or gsm).

(37) The terms “joined” or “bonded” or “attached”, as used herein, encompasses configurations whereby an element is directly secured to another element by affixing the element directly to the other element, and configurations whereby an element is indirectly secured to another element by affixing the element to intermediate member(s) which in turn are affixed to the other element. The terms further include embodiments in which a pocket or other connector is formed in or attached to an area of the absorbent article. Further, these terms include configurations in which the elements are removably, or non-removably, joined, bonded, or attached. For example, wherein an element is described as “joined” within the configuration, it may be either removably joined or non-removably joined unless otherwise specified or evident from the context.

(38) The terms “comprise,” “comprising,” and “comprises” are open ended terms, each specifies the presence of what follows, e.g., a component, but does not preclude the presence of other features, e.g., elements, steps, components known in the art, or disclosed herein. These terms based on the verb “comprise” should be read as encompassing the narrower terms “consisting of” which excludes any element, step, or ingredient not specified and “consisting essentially of” which limits the scope of an element to the specified materials or steps and those that do not materially affect the way the element performs its function. Any preferred or exemplary embodiments described below are not limiting the scope of the claims, unless specifically indicated to do so. The words “typically”, “normally”, “advantageously” and the likes also qualify elements which are not intended to limit the scope of the claims unless specifically indicated to do so.

(39) By “absorbent material” it is meant a material which has some absorbency property or liquid retaining properties, such as SAP, cellulosic fibers as well as synthetic fibers, most preferably is selected from the group consisting of SAP, cellulose (or cellulosic) fibers, and mixtures thereof. Herein, absorbent materials in the form of fibrous absorbent materials have been found to be useful. These fibrous absorbent materials can comprise or consist of natural fibers, e.g. cellulosic fibers as well as synthetic fibers. Typically, glues used in making absorbent cores have no absorbency properties and are not considered as absorbent material.

(40) As used herein, the term “absorbent core” refers to the component or components of the article having the most absorbent capacity and comprising an absorbent material and optionally a core wrap enclosing the absorbent material. The term “absorbent core” does not include the acquisition-distribution system or layer or any other component of the article which is not either integral part of the core wrap or placed within the core wrap. The core may consist essentially of, or consist of, a core wrap, absorbent material as defined below and glue enclosed within the core wrap.

(41) The values indicated herein are measured according to the methods indicated herein below, unless specified otherwise. All measurements are performed at 21±2° C. and 50±20% RH, unless specified otherwise. All samples should be kept at least 24 hours in these conditions to equilibrate before conducting the tests, unless indicated otherwise. All measurements should be reproduced on at least 4 samples and the average value obtained indicated, unless otherwise indicated.

(42) The Absorbent Article

(43) Absorbent articles herein are for personal hygiene such as a diaper, or training pant, or incontinence insert, the absorbent article comprising: a liquid permeable topsheet **22**; a liquid impermeable backsheet **24**; an absorbent core **20** positioned between said topsheet **22** and backsheet **24**, an indicator **60** for indicating the presence of exudates and being positioned on a body-facing side of said backsheet **24**, the indicator **60** comprising an electrically conductive

material, the article further comprising a detection device **70** that can be removably attached to the absorbent article such to become in electrical communication with said indicator **60** when attached to said article to measure a change in resistance or capacitance in response to a voiding event, wherein the absorbent core **20** comprises a core wrap **66** enclosing absorbent material therein and wherein a top layer **66a** of the core wrap **66** is joined to a bottom layer **66b** of the core wrap **66** to form one or more channels **500** substantially free of absorbent material, and wherein the indicator **60** comprises a pattern that extends inboard and/or outboard of said channel(s) such that it does not substantially overlap with said channel(s). Typically wherein the channels(s) extend from 10% to 95% of a length of the core **20** such that said channel(s) are surrounded by absorbent material. Advantageously this arrangement allows for accurate exudate detection and position determination when liquid distributing channels are present in the core, indeed it has been found that in order to accurately determine position of soiling within the absorbent article, it is beneficial to ensure that the conductive layers of the indicator do not overlap the channels that are quickly immediately soiled with exudates in moments of time immediately following a voiding event.

(44) The absorbent article may comprises one or more indicator(s) adapted to indicate the presence and/or absence of bodily exudates and/or determine saturation level and when the article should be replaced with a new clean one. The indicator, in some embodiments, for example, may comprise an indicator that reacts to the presence and/or absence of bodily exudate(s) and/or one or more properties of those bodily exudate(s) within the absorbent article via one or more change in property of the indicator (e.g., a physical, chemical or biological property such as color, smell, sound, pH, or the like). One or more property or state of the indicator, in turn, may be detected by a detector device physically and/or communicatively coupled to the absorbent article. In one particular implementation, for example, the indicator comprises an optical property changing composition or device (e.g., a color-changing composition or device, such as a color changing indicator) that changes an optical property (e.g., color) in response to a variation of pH associated with the presence and/or absence of bodily exudates within the absorbent article). The indicator might also comprise one or more additional indicators of the same or different type that provide different types of indications and/or indications of bodily exudates (or properties of bodily exudates) detected in one or more different regions of the absorbent article. In one embodiment, for example, a second electrical indicator may comprise a resistance, capacitance, inductance or continuity sensitive indicator. Alternatively, such electrical indicators may be provided as an alternative or in conjunction with optical indicators. A resistance sensitive indicator can be provided, for example, by providing two or more electrical conductors disposed at a given spatial distance relative to each other. If bodily exudates, which typically comprise a liquid portion, come in contact with the two electrical conductors, the resistance between the two electrical conductors is reduced (examples of this arrangement are described in more detail in applicant's prior disclosures such as EP3415130, WO/2018/228822, WO/2018/229017, EP3461257, and EP3451988). Other indicators, as known in the field in the context for sensor for absorbent articles, can also be useful. In one particular embodiment, for example, the multiple property changing indicators may be provided in the same or different locations within the absorbent article. For example, an optical property changing indicator (e.g., color changing indicator) may be disposed in a first location of an absorbent article and a second property changing indicator that is the same or a different type of indicator (e.g., another optical property changing indicator such as a color changing indicator) may be disposed in a second location of the absorbent article.

(45) The absorbent article and the one or more indicators are provided to form an integral unit. For forming the integral unit, the indicator(s) can be directly or indirectly attached to the absorbent article. Direct or indirect attachment to the article is typically to one or more distinguishable element of the article. For example, it can be useful to attach the indicator(s) to the back sheet of the article, such that the indicator(s) and the back sheet of the article form one integral unit. For example if the indicator(s) are provided in sheet form, the respective sheet can be adhesively

attached to the back sheet of the article. The respective sheet could also be provided from one and the same material with the back sheet, this material however being treated in suitable ways as to provide an indicator in a pre-defined area (for example by printing an electrically conductive material on a skin or body facing side of the liquid impermeable backsheet layer).

(46) According to one particular embodiment, a detector device (herein also referred to a clip-on processing unit or clip-on unit) is also provided. The detector device, in this implementation, comprises a housing and is adapted to be physically coupled to the absorbent article such that the detector device is further communicatively coupled to one or more indicator integral with the absorbent article. The detector device and/or the absorbent article may comprise one or more connector for removably joining the detector device with the absorbent article. The connector(s) are provided such that the detector device can be attached to the absorbent article and can be detached from the absorbent article including the one or more indicator(s). The detector device can be attached to the integral unit and can be detached from the integral unit. In one particular embodiment, for example, the detector device can be attached to an area of the absorbent article juxtaposed the indicator integral to the absorbent article, and can be detached from that area of the absorbent article so as to be removably connectable thereto.

(47) The housing of the detector device, in one embodiment, has an outer extension in a first direction and an outer extension in a second direction, which is perpendicular to the first direction. The first direction, in this embodiment, may be chosen as characteristic directions, e.g. along a main axis and normally as that of largest extension of the housing. For safety and convenient handling of the device, it may be useful that the device has a length in the first direction of at least 3 cm, 4 cm or more (but normally less than 10 cm) and that the device has a length in the second direction of at least 2 cm, 3 cm or more (but normally less than 10 cm). In one particular embodiment, for example, the housing has a first dimension of at least about 4 cm and a second dimension of at least about 8 cm. In various embodiments, the housing can be rigid or at least partially or fully flexible. To be flexible the detector device can incorporate flexible electronic components (and boards).

(48) According to one embodiment, the detector device comprises one or more optical sensor, such as a color sensor. This optical sensor can generate an output which depends on an optical property (e.g., a color) observed by the optical sensor. Some examples of optical sensors across a range of wavelengths are: electron tube detectors, photosensors, photomultiplier tubes, phototubes, photodetectors, opto-semiconductor detectors, photodiodes, photomultipliers, image sensors, infrared detectors, thermal sensors, illuminance sensors, visible light sensors and color sensors. In one particular embodiment, for example, the optical sensor may comprise a photodiode such as a TCS 34725 color sensor commercially available from AMS-TAOS USA Inc.

(49) In other embodiments, for example, the detector device need not include a light source, such as where sufficient ambient light may be provided in an application, where light is provided elsewhere (e.g., associated with an absorbent article or clothing, or elsewhere in an environment) or where the property change of a property changing indicator may be detectable without light, such as resistance, impedance and/or capacitance measurements when the indicator comprises an electrically conductive material (such as a conductive ink).

(50) Often, the detector device will also comprise one or more light, such as a light emitting diode (LED), organic light emitting diode (OLED), an incandescent light bulb, thermionic light emission, luminescence (e.g., among others, fluorescence, chemilluminescence, electroluminescence (e.g., LED), for emitting light onto an area, the wavelength or spectrum of which is to be assessed by the optical sensor. The optical sensor in some color detecting embodiments can be optimized for assessing a color of a color-changing indicator. The optical sensor can be sensitive to visible and non-visible light, namely light in the near IR range. In various embodiments, UV, visible infrared and near infrared wavelengths may be used. A color changing indicator can change its color, for example, based on the presence and/or absence of bodily exudates and/or in response to some other

condition being monitored with respect to the absorbent article. In this embodiment, the color sensor can provide an output that varies depending on the presence or absence of bodily exudates. (51) In a preferred embodiment, an LED is used as light emitting source. Preferably, at least two light sources are emitted comprising a first color and a second color wherein the first color is different from the second color. Typically wherein the first color corresponds to a color that is most absorbed in a first state of the indicator and the second color corresponds to the color that is most absorbed by the indicator in a transition state. For example, the first color may be blue (this is particularly useful if the indicator is for example yellow in dry state) and the second color may be selected from red (this is particularly useful if the indicator is for example green in a transition state).

(52) In a particularly preferred embodiment, the indicator **60** is a color-changing indicator that changes color in response to a voiding event, such as an exudate wetness event, and wherein said indicator **60** has the following colors: substantially yellow in dry state, substantially blue in a fully saturated wet state, and is substantially green in a transition state between said dry state and said fully saturated wet state. These types of indicators, that will be described in further detail herein, have the advantage that when using Blue and Red LEDs a more accurate and energy efficient detection of wetness degree in the absorbent article can be determined. In fact, as discussed above when the indicator is yellow it will absorb mostly blue light and when the indicator is blue it will absorb mostly red light, but moreover when the indicator is in its green transition phase it will absorb both red and blue light, thus the specific selection of a Blue LED source and a Red LED source allows to accurately determine (by use of optical sensors as described herein) at least three conditions on the absorbent article: a dry state; a partly wet state; and a wet/saturated state. All this will be determined in a cost effective way and whilst limiting power usage by using color LEDs as described on more detail hereinbelow.

(53) In an embodiment, the light source may comprise a Blue LED, a Red LED, and a White LED. (54) In view of the above, in an embodiment, the LED source comprises a first color being green, a second color being red and a third color being blue. Advantageously, this combination of colors ensure to allow detection of any changes of any color change of the indicator thus allowing flexibility in choice of color changes by the indicator.

(55) In an embodiment, the light emitting source does not comprise a white color LED, indeed white LEDs have been found to consume more energy and thus significantly reduce the battery life of the clip-on units (or detection devices or detector devices) herein, advantageously color sources like Blue and Red LEDs use less energy and can thus increase the battery life without having to increase size of the battery and thus size of the overall detection device (herein also referred to as detector device).

(56) In a preferred embodiment, the optical sensor comprises an RGB (Red, Green and Blue) optical sensor and preferably further a Light Dependent Resistor (LDR). The former setup identifies colour variations while the latter detects intensity changes in the whole spectrum. The data acquisition may be realised by means of an Analog-to-Digital Converter (ADC) e.g. an Arduino, which sends the information to a processor via for example a continuous data link.

(57) In various embodiments, essentially any known color-changing indicator that responds to the absence or presence of bodily exudates or other conditions to be monitored with respect to the absorbent article can be useful. It may be useful to employ a color-changing indicator which comprises a chemical substance. Such a chemical substance can induce a color change when bodily exudates are present. One useful form of a color-changing indicator comprises a pH-sensitive indicator. Bodily exudates, for example, may influence the pH-value in their environment. Similarly, components within an absorbent article may alter a pH of the environment in response to contact with one or more bodily exudates. In one particular embodiment, for example, as AGM swells in the presence of urine or other liquids present in a bodily exudate, the AGM swelling changes the pH of the environment within the absorbent article. Thus, in this and other

embodiments, a pH-sensitive indicator can be used and detected by the detector device.

(58) Other useful indicators can comprise biological or physical sensor materials. The skilled person is aware of numerous useful biological sensor materials. Physical sensors can be provided by a material, which changes its color when the material is stretched. Stretching of a material can be induced by the swelling of the absorbent core. Biological sensors may include a bioreceptor that interacts with an analyte of interest, such as trypsin or urease. A bioreceptor, for example, may use reagent/analyte interactions that provide a property change (e.g., a color or other optical change) in the absorbent article upon detection of a particular analyte of interest. In one particular embodiment, for example, a bioreceptor may use an immobilised binding reagent also capable of binding to an analyte of interest. The immobilized reagent for example, may be disposed at a detection zone detectable by a sensor of a detector device.

(59) Additionally the indicator can comprise a material selected from the group comprising, consisting essentially of or consisting of: thermochromic inks, thermochromic dyes, thermochromic liquid crystalline materials, and combinations thereof. These indicators can, for example, serve to monitor other conditions associated with the absorbent article and/or wearer of the absorbent article, such as body temperature or fever indication.

(60) The present embodiments can usefully employ one or more connectors which allow for detachment and can also allow for refastening of an indication device to the absorbent article. Such connectors may comprise one or more adhesives or cohesives. Such connectors may further comprise one or more mechanical fasteners, including strap based fasteners or fasteners comprising at least one button or at least one magnet. Among the group of mechanical fasteners, a hook-end-loop fastener is useful. It can be useful to attach the hook-portion to the absorbent article or to attach the loop-portion to the absorbent article. The corresponding portion can then be attached to the detector device.

(61) In one useful embodiment, the loop portion of a hook-and-loop-fastener can be provided integral with the absorbent article. For example, if the outer side of the backsheet of the absorbent article is provided from a textile material, e.g. a non-woven material, loops provided in such a material can interact with the hooks of a hook-portion of a fastener.

(62) There are also alternative forms of mechanical fasteners (to be used as connectors), which can be used additionally or alternatively. For example, a pocket can be formed in an area of the absorbent article. For example, such a pocket can be formed between layers of the backsheet. A pocket can also be formed between other layers. For example, diapers can be provided as pant-diapers comprising a crotch-portion and a belt-portion. The crotch-portion and the belt-portion can be joined adhesively or mechanically, e.g. by crimping. In the area of adhesive joining, a certain portion can be free of adhesive and accessible from the outside. This portion can then serve as a pocket for receiving the detector device. A belt, strap or other device may be used to place and hold the detector device relative to the absorbent article. The detector device may similarly be joined or held to an article of clothing worn by the user wearing the absorbent article by mechanical means or otherwise.

(63) The detector device provides information which in one aspect will indicate the presence and/or absence of bodily exudates. Such a detector device can comprise a variety of output and/or display elements. A simple output element can comprise LED, OLED or similar lamps. For example a green light can be used as an indication for the absence of bodily exudates or presence only a low amount of bodily exudates whereas a red light can indicate the presence of a higher amount of bodily exudates and therefore will normally indicate the need to change the absorbent article. Information can be provided in more comprehensive forms and therefore a display element, for example in the form of a small monitor can be useful. Information to be displayed on such a monitor or similar display element could include information about the loading status of the absorbent article, the time at which a fresh absorbent article has been applied and so forth.

(64) The output element or display element can be provided within the housing or attached to the

detector device. The output element, for example, may include a visual output device (e.g., display, LED or the like), an audible output device (e.g., a speaker), a tactile output device and/or the like.

(65) The output or display element can also be provided in a separate unit. Such a separate unit can also have other functions. It can be useful to employ a mobile phone with a display or another personal digital assistant for use as a display element in the present context. The display element can also be a computer (including a laptop computer or a tablet computer). Information obtained from the detector device can also be displayed on several such units at the same time. This can be displayed there in the same format or in similar formats. For example a more detailed display of information on a computer can be combined with simplified display of information on a mobile phone. Additionally or alternatively the output element can also comprise acoustic indication device and can also rely on a computer generated voice. In some cases also, the information is not or not only displayed or provided, but directed to a data storage device for data aggregation.

(66) In one particular implementation, the separate unit may include any display or output device in the area surrounding the detector device (e.g., within a house, apartment or the like). The separate unit may further include a plurality of input/output nodes that may be communicatively coupled to the detector, such as an Amazon® Echo® device that may provide visual and/or audio outputs (e.g., “diaper needs changing”).

(67) For providing information to the separate unit the detector device can broadcast or otherwise send information to the unit comprising the display element. The skilled person is aware of useful standards for providing such broadcasting, for example Bluetooth, BTLE, mesh (e.g., IEEE 802.15.4), WiFi (e.g., IEEE 802.15.11), communication incorporating all or any portion of IEEE 802 or similar communication standards, RFID, 3G or 4G communication, Backscatter communication, light communication, audio/sound communication, harvesting protocol communication (e.g., a metadata harvesting protocol). Other communications protocols or combinations of communications protocols (e.g., a Bluetooth/Mesh combined protocol) can be employed. Additionally or alternatively an acoustic or optical broadcasting is useful.

(68) In a further embodiment, a kit comprising a multitude of absorbent articles and a detector device, which comprises a housing and a connector, such that the detector device can be connected to any one of the absorbent articles is also provided. The absorbent articles and the detector device may each comprise any of the further features described herein. Hence, the detector device can be used on a first absorbent article of the multitude, the absorbent article can be disposed of after use, and the detector device can be re-used on another (fresh) absorbent article.

(69) An exemplary absorbent article according to one embodiment in the form of an infant diaper **10** is represented in FIGS. **1** and **2**, although it is understood herein that equally adult diapers and pants may be suitable herein.

(70) FIG. **1** is a plan view of the exemplary diaper **10**, in a flattened state, with portions of the structure being cut-away to more clearly show the construction of the diaper **10**. This diaper **10** is shown for illustration purpose only as many embodiments may use a wide variety of diapers or other absorbent articles. The diaper extends from a front edge **12** to a longitudinally opposed rear edge **14**. It comprises left side edge **16** and transversally opposed right side edge **18**. The diaper **10** comprises an absorbent core which is positioned between topsheet **22**, which is at least partially liquid permeable and backsheet **24**, which is essentially impermeable to liquid.

(71) In FIG. **1** “X” denotes a transversal access through the geometrical center of the diaper, and axis “Y” denotes the longitudinal direction. The area A denotes the front area of the diaper as seen in the longitudinal direction and C denotes the rear area of the diaper as seen in the longitudinal direction, and B denotes the central area or crotch area positioned between area A and area B, in the longitudinal direction. L denotes the length of the diaper from the front edge **12** to rear edge **14** as measured in the longitudinal direction.

(72) The article comprises a crotch point P defined herein as the point placed on the longitudinal axis at a distance of two fifth ($\frac{2}{5}$) of L starting from the front edge **12** of the diaper **10**.

(73) The absorbent article comprises an indication means **60**, which can take the form of a small sheet of material or patch. As shown, a rectangular form is useful. The indication means **60** can be arranged in the front area A, the central area B or the rear area C of the diaper. It is often useful to arrange the indication means **60** in the central area B and in the front area A. As shown, it can be useful to provide the indication means **60** towards the front of the crotch point P and preferably on at least a portion of the central area B.

(74) The diaper **10** may further comprise gasketing cuffs **26** for maintaining a tight fit of the diaper **10** to the wearer, when the diaper **10** is worn. The gasketing cuffs **26** comprise elastics **28** for maintaining the tight fit, which helps to avoid leakage.

(75) The diaper **10** may further comprise barrier leg cuffs **30** on each side of the diaper. Barrier leg cuffs comprise proximal edges **32a** and **32b**, which are adjacent to topsheet **22**. Opposed to the respective proximal edges, the barrier leg cuffs **30** comprise distal edges **34a** and **34b**, respectively. In the area of the distal edges **34**, further elastics **36a** provided, while a portion of the distal edges **34** of the barrier leg cuffs **30** can be attached to components of the diaper **10**, such as the topsheet **22**, it is preferred that the barrier leg cuffs **30** also comprise unattached areas of the distal edges, herein referred to as free flaps **38**. The respective free flaps **38** are typically provided in the central zone of the diaper **10**.

(76) The diaper **10** may further comprise the fastening system, for fastening the diaper to the body of a wearer. This fastening system comprises two back ears **40**, which comprise adhesive tapes **42**. The adhesive tapes **42** can be attached to landing zone **44**. In the front area, the diaper comprises front ears **46**. As described below, for other embodiments other fastening systems can be useful, including mechanical fasteners and including fastening systems comprising more than two, for example for IS.

(77) In a preferred embodiment, the indicator **60** has a longest length parallel to the longitudinal axis Y and a shortest width perpendicular thereto, and wherein said indicator is positioned asymmetrically along the absorbent article (e.g. diaper **10**) length such that it overlaps the transverse centreline X of the diaper **10** and the distance between said transverse centreline X and a position of the indicator **60** closest to the back edge **14** is smaller than the distance between said transverse centreline X and a position of the indicator closest to the front edge **12**, as for example shown in FIG. 1. Advantageously, this allows the indicator to be easily viewed by a caregiver and to allow accurate detection of saturation as well as being functionally operable with a detection device as will be described in more detail hereinbelow, whilst at the same time limiting cost and unnecessary material waste.

(78) The core can optionally comprise areas, where there is a reduced amount of absorbent material or no absorbent material. These areas are referred to as channels. The channels are typically formed by joining together top and bottom core wrap layers, wherein the core wrap encloses the absorbent material therein except in the channel regions.

(79) As illustrated in exemplary FIG. 18, the core may comprise a plurality of channels **500**, preferably two channels **500**. Typically the channels **500** comprise at least one right channel and at least one left channel, the right channel being disposed between the right side edge **18** and the longitudinal centreline along axis Y, and the left channel being disposed between the left side edge **16** and the longitudinal centreline along axis Y. The right and left channels may be arcuate in shape such that the front and back ends of the left and right channels diverge towards the left side edge **16** and the transversely opposed right side edge **18** respectively and typically wherein the central portion of said channels converge towards the longitudinal centreline along axis Y.

(80) In an embodiment, the pattern of the indicator **60** comprises a plurality of sensing tracks **520** each track forming an open circuit corresponding to a different position of the backseat **24** and the absorbent core (**20**) such that voiding events in said different positions may be individually monitored. The different positions corresponding to at least two of: a front A, crotch B or back C portions of the article. Advantageously this allows for detection of exudates when a wearer is in

various positions such as standing, lying on the back or on the belly as exudates will flow generally in the direction of gravity such that accurate monitoring of risk of leakage and/or warnings to change wearer's position can be triggered.

(81) In an embodiment, each of the sensing tracks **520** comprises a connection end **521** arranged to couple to a respective terminal end of the detection device **70** to form an electrical connection between said detection device **70** and said sensing tracks **520** of the indicator.

(82) Preferably, the sensing tracks **520** are printed with a conductive ink.

(83) Preferably, wherein the conductive ink is a carbon-based ink and/or a conductive polymer-based ink.

(84) In an embodiment, the carbon-based ink comprises a conductive compound selected from the group consisting of graphene, graphite, nano-carbon-tubes and mixtures thereof.

(85) In an embodiment, the conductive polymer-based ink comprises a polymer selected from the group consisting of polyacetylene, polypyrrole, polyaniline and copolymers thereof, more preferably selected from the group consisting of poly(pyrrole)s (PPY), polyanilines (PANI), poly(thiophene)s (PT), poly(p-phenylene sulfide) (PPS), poly(p-phenylene) (PPP), Poly(acetylene)s (PAC), Poly(p-phenylene vinylene) (PPV), poly(3,4-ethylenedioxythiophene) (PEDOT), and mixtures thereof, most preferred conductive polymer-based ink comprising poly(3,4-ethylenedioxythiophene) polystyrene sulfonate (PEDOT:PSS).

(86) Preferably, the indicator (**60**) is free of metals.

(87) When channels are present, the indicator **60** may extend therebetween along the Y axis and is arranged such that it prolongs beyond the channels **500** at a first distance D1 towards front edge **12**. Preferably, the indicator **60** comprises a rear terminal edge (being the portion of said indicator **60** closest to the back or rear edge **14**) positioned between said channels **500** generally such that it does not prolong beyond the channels **500** towards the rear edge **14**. Advantageously, the detector device may thus be placed on the front of the article with limited risk of faulty or pre-mature warnings due to early saturation of regions of the core proximal to the channels that would otherwise cause the indicator to change color too soon prior to real saturation across the majority of the core.

(88) In a preferred embodiment, the channels **500** have a width $W_{sub.Ch}$ (typically in a dimension substantially parallel to the transverse axis X) and the indicator **60** has a width $W_{sub.I}$ (typically in a dimension substantially parallel to the transverse axis X), wherein $W_{sub.I}$ is greater than $W_{sub.Ch}$, preferably wherein $W_{sub.I}$ is from $1.1 W_{sub.Ch}$ to $4W_{sub.Ch}$, more preferably from $1.2W_{sub.Ch}$ to $3W_{sub.Ch}$, even more preferably from $1.3W_{sub.Ch}$ to $2.5W_{sub.Ch}$, even more preferably from $1.4W_{sub.Ch}$ to $2.2W_{sub.Ch}$, even more preferably from $1.5W_{sub.Ch}$ to $2.0W_{sub.Ch}$. Without wishing to be bound by theory, a larger width of the indicator is beneficial in order to ensure correct reading from the detector device and to limit any lateral light refractions on surfaces not covered by the indicator, however if the indicator width is too great it may negatively impact accuracy of the wetness determination as it approaches or even overlaps the channels that are designed to quickly transport liquid. A balance has therefore been determined between the channel width and indicator width that provides for stable detection and limit false warnings/alarms.

(89) The width $W_{sub.Ch}$ of channels herein may vary depending on the absorbent article (e.g. diaper) size, nevertheless typically is in the range of from 5 mm to 30 mm, preferably from 7 mm to 25 mm, even more preferably from 9 mm to 20 mm, even more preferably from 10 mm to 15 mm. Such measurements are typically taken from a dry-state diaper prior to it being wetted.

(90) In an embodiment, the distance between the indicator **60** and a position of a channel **500** closest thereto is less than indicator width $W_{sub.I}$ and is equal to or greater than the channel width $W_{sub.Ch}$. Typically the position where the one or more channels **500** are closest to the indicator **60** is proximal to the rear terminal edge of the indicator **60** and distal from a position where the detection device is to be coupled. It has been found that even in portions of the indicator distal from

where the detection device is to be connected, it is desirable to ensure a certain spacing between the indicator and the channels whilst at the same time being close enough to start triggering a change (e.g. of color) from positions proximal to the rear terminal edge towards the front edge of the indicator where the detection device is to be positioned.

(91) In an embodiment, the distance **D1** between a front-most edge of the one or more channels **500** and a front-most edge of the indicator **60** is more than $2.0W_{sub.Ch}$, preferably from $2.5W_{sub.Ch}$ to $10.0W_{sub.Ch}$, more preferably from $3.0W_{sub.Ch}$ to $8.0W_{sub.Ch}$, even more preferably from $3.5W_{sub.Ch}$ to $7.0W_{sub.Ch}$, even more preferably from $4.0W_{sub.Ch}$ to $6.0W_{sub.Ch}$, even more preferably from $4.5W_{sub.Ch}$ to $5.5W_{sub.Ch}$. The width of the channels has been found to affect the speed of liquid distribution along the core view of the absence of absorbent material therein, it is therefore beneficial for the indicator to extend further away from the apex of the channels to a position proximal to the front of the absorbent article where the detection device is to be connected (the detection device position DDP). Below the mentioned lower ratios, risk of premature warning before actual saturation of the diaper is very high, and above the mentioned upper ratios the risk of delayed warning is very high (e.g. too much time for the indicator at the detection device position DDP to change color).

(92) Although above embodiments have been described with reference to plural channels as illustrated in FIG. **18**, a person skilled in the art will understand that the same embodiments apply to different channel geometries. For example, as shown in FIG. **19**, the channel may be in the form of a single channel **500** that has two parallel and opposing longitudinally extending portions and one transversely extending portion connecting said longitudinally extending portions to form a substantially U-shaped channel **500**.

(93) In an embodiment, the detection device position DDP is at the front of the absorbent article and overlaps at least a portion of the indicator **60**, this is illustrated in FIG. **20**. The detection device position DDP may overlap the indicator **60** along an overlap length that is from 60% to 95% of distance **D1**, preferably from 70% to 90% of distance **D1**, even more preferably from 75% to 85% of distance **D1**, and preferably is positioned such that the front-most edge of the indicator **60** remains exposed. Advantageously, allowing the front-most edge of the indicator to remain exposed when the detection device is connected (i.e. 95% or less of **D1**) ensures limiting risk of interference/noise in the light color detection of the optical sensor (when used as described in embodiments herein below) that may cause false warnings at the same time ensuring sufficient distance from the channels (i.e. 60% or more of **D1**) allows for reduced risk of false saturation warnings when the diaper core is actually not yet saturated.

(94) FIG. **21** illustrates schematically the absorbent articles herein with channels **500**, indicator **60** and detection device position DDP as described herein in both dry and wet conditions.

(95) FIG. **2** is transversal cross-section of the embodiment of FIG. **1** and readily shows other structural elements of the diaper. As shown in this figure, the diaper may comprise an acquisition-distribution system **50**. This acquisition-distribution system comprises acquisition layer **52**, which first receives liquid, and distribution layer **54** underneath acquisition layer **52**.

(96) The absorbent core **20** may comprise a core layer **56**. This core layer can comprise particular material, such as super absorbent particles, herein also referred to SAP. Between the core layer **56** and the backsheet **24** the indication means **60** can be arranged. As shown in FIG. **2** the backsheet **24** can comprise an inner backsheet layer **62** (which is oriented towards the core **20**) and an outer backsheet layer **64**, which is generally oriented towards the garments of a wearer. As shown in FIG. **2**, in accordance with this particular embodiment, the indicator **60** can be provided above the inner backsheet layer and below the core wrap, more precisely, below the portion of the core wrap **66** which is oriented towards the backsheet **24**.

(97) FIG. **3** shows another example embodiment of an absorbent article. This embodiment resembles that shown in FIGS. **1** and **2**. However, the indicator **60** is arranged here between the inner backsheet layer **62** and the outer backsheet layer **64**.

(98) FIG. 4 shows another example embodiment of an absorbent article. For the embodiment shown in FIG. 2 the absorbent article is shown together with detector device 70. As shown, detector device 70 can take the form of a small pod which can have generally rectangular cross sections. The detector device 70 can be attached to the backsheet 24 of the diaper 10 by a mechanical fastener 68. In one embodiment, for example, the mechanical fastener comprises a first component and a second component. The first component can be attached to backsheet 24 and the second component can be attached to detector device 70. The two components interact with each other, for example hook and loop fasteners can be used. The respective component can be adhesively joined to the backsheet and to the detector device 70, respectively.

(99) Alternatively, the detector device may be inserted into or contained within a pocket formed between a garment facing surface of the backsheet and a covering layer, wherein the covering layer typically is a nonwoven comprising a spunbond layer that is joined to the garment facing surface of the backsheet by a joining means, such as adhesive, wherein the joining means is present outboard of the pocket and is absent inboard of the pocket such to form a containment volume for the detector device that may be advantageously retained therein and placed in direct contact with the indicator with no other layers therebetween. This has the advantage to limit light scattering or refraction in cases where a light source and optical sensor are used to measure a change in condition.

(100) The article may also comprise elasticized gasketing cuffs 26 joined to the chassis of the absorbent article, typically via the topsheet and/or backsheet, and substantially planar with the chassis of the diaper.

(101) The Figures also show typical taped diaper components such as a fastening system comprising adhesive tabs 42 attached towards the back edge of the article and cooperating with a landing zone 44 on the front of the article. The absorbent article may also comprise other typical elements, which are not represented, such as a back elastic waist feature, a front elastic waist feature, transverse barrier cuff(s), a lotion application, etc.

(102) The topsheet 22, the backsheet 24, the absorbent core 20 and the other article components may be assembled in a variety of well known configurations, in particular by gluing or heat embossing. Exemplary diaper configurations are described generally in U.S. Pat. Nos. 3,860,003, 5,221,274, 5,554,145, 5,569,234, 5,580,411, and 6,004,306. The absorbent article is preferably thin. The caliper at the crotch point P of the article may be for example from 4.0 mm to 12.0 mm, in particular from 6.0 mm to 10.0 mm, as measured with a suitable caliper test, for example the Absorbent Article Caliper Test disclosed in EP 2 740 450 A1 (Applicant: The Procter & Gamble Company).

(103) These and other components of the articles will now be discussed in more details.

(104) The topsheet 22 is the part of the absorbent article that is directly in contact with the wearer's skin. The topsheet 22 can be joined to the backsheet 24, the core 20 and/or any other layers as is known in the art. Usually, the topsheet 22 and the backsheet 24 are joined directly to each other in some locations (e.g. on or close to the periphery of the article) and are indirectly joined together in other locations by directly joining them to one or more other elements of the diaper 10.

(105) The topsheet 22 is preferably compliant, soft-feeling, and non-irritating to the wearer's skin. Further, at least a portion of the topsheet 22 is liquid permeable, permitting liquids to readily penetrate through its thickness. A suitable topsheet may be manufactured from a wide range of materials, such as porous foams, reticulated foams, apertured plastic films, or woven or nonwoven materials of natural fibers (e.g., wood or cotton fibers), synthetic fibers or filaments (e.g., polyester or polypropylene or bicomponent PE/PP fibers or mixtures thereof), or combinations thereof, e.g. a combination of natural and synthetic fibers. A combination of materials can be achieved by combining at least two materials by means of needle punching, ultra-sonic bonding, ring rolling, embossing, gluing or other types of mechanical entanglement. The resulting material may maintain a dual/multiple layer structure, but may also lose a structure of distinguishable layers after such

process steps. It can also be useful to provide a formed film patch underneath the topsheet. (106) If the topsheet **22** includes fibers, the fibers may be spunbond, carded, wet-laid, meltblown, hydroentangled, or otherwise processed as is known in the art, in particular spunbond PP nonwoven. A suitable topsheet comprising a web of staple-length polypropylene fibers is manufactured by Veratec, Inc., a Division of International Paper Company, of Walpole, Mass. under the designation P-8.

(107) The topsheet **22** may comprise one or more apertures to ease penetration of exudates therethrough, such as urine and/or feces (solid, semi-solid, or liquid). The size of at least the primary aperture is important in achieving the desired waste encapsulation performance. If the primary aperture is too small, the waste may not pass through the aperture, either due to poor alignment of the waste source and the aperture location or due to fecal masses having a diameter greater than the aperture. If the aperture is too large, the area of skin that may be contaminated by "rewet" from the article is increased. Typically, the total area of the apertures at the surface of a diaper may have an area of between about 10 mm² and about 50 mm², in particular between about 15 mm² and 35 mm². Examples of apertured topsheet are disclosed in U.S. Pat. No. 6,632,504, assigned to BBANONWOVENS SIMPSONVILLE. WO2011/163582 also discloses suitable colored topsheet having a basis weight of from 12 to 18 gsm and comprising a plurality of bonded points. Each of the bonded points has a surface area of from 2 mm² to 5 mm² and the cumulated surface area of the plurality of bonded points is from 10 to 25% of the total surface area of the topsheet. Typical diaper topsheets have a basis weight of from about 10 to about 21 gsm, in particular between from about 12 to about 18 gsm but other basis weights are possible.

(108) The backsheet **24** is generally that portion of the diaper **10** positioned adjacent the garment-facing surface of the absorbent core **20** and which prevents the exudates absorbed and contained therein from soiling articles such as bedsheets and undergarments. The backsheet **24** is typically impermeable to liquids (e.g. urine). The backsheet may for example be or comprise a thin plastic film such as a thermoplastic film having a thickness of about 0.012 mm to about 0.051 mm. Exemplary backsheet films include those manufactured by Tredegar Corporation, based in Richmond, Va., and sold under the trade name CPC2 film. Other suitable backsheet materials may include breathable materials which permit vapors to escape from the diaper **10** while still preventing exudates from passing through the backsheet **24**. Exemplary breathable materials may include materials such as woven webs, nonwoven webs, composite materials such as film-coated nonwoven webs, microporous films such as manufactured by Mitsui Toatsu Co., of Japan under the designation ESPOIR NO and by Tredegar Corporation of Richmond, Va., and sold under the designation EXAIRE, and monolithic films such as manufactured by Clopay Corporation, Cincinnati, Ohio under the name HYTREL blend P18-3097. Some breathable composite materials are described in greater detail in PCT Application No. WO 95/16746 published on Jun. 22, 1995 in the name of E. I. DuPont; U.S. Pat. No. 5,938,648 to LaVon et al., U.S. Pat. No. 4,681,793 to Linman et al., U.S. Pat. No. 5,865,823 to Curro; and U.S. Pat. No. 5,571,096 to Dobrin et al, U.S. Pat. No. 6,946,585B2 to London Brown.

(109) The backsheet **24** may be joined to the topsheet **22**, the absorbent core **20** or any other element of the diaper **10** by any attachment means known in the art. Suitable attachment means are described above with respect to means for joining the topsheet **22** to other elements of the diaper **10**. For example, the attachment means may include a uniform continuous layer of adhesive, a patterned layer of adhesive, or an array of separate lines, spirals, or spots of adhesive. Adhesives which have been found to be satisfactory are manufactured by H. B. Fuller Company of St. Paul, Minn. and marketed as HL-1620 and HL 1358-XZP. Alternatively, the attachment means may comprise heat bonds, pressure bonds, ultrasonic bonds, dynamic mechanical bonds, or any other suitable attachment means or combinations of these attachment means as are known in the art.

(110) The absorbent core **20** of the absorbent article may comprise a first core layer **56** and a second core layer **58**. As explained, the absorbent article might comprise and acquisition

distribution system, which will typically consist of one or more layers. Most typically, the layers are arranged above the core layer. Hence, a number of layers can be arranged between the topsheet and the backsheet. The skilled person will usually have no difficulty in distinguishing between these layers. In case of doubt, a core layer can be identified as being a layer which is generally less permeable than a layer forming part of the acquisition-/distribution-system.

(111) Permeability generally refers to the quality of a porous material that causes it to a lower liquid or gases to pass through it. Hence, the layers of the acquisition distribution system should generally be more permeable than the layers of the core system as these layers are meant to distribute liquid to the absorbent core, where the liquid is ultimately stored.

(112) The absorbent core can comprise absorbent material with a varying amount of superabsorbent polymers (herein abbreviated as “SAP”), often enclosed within a core wrap. The SAP content can represent from 0% to 80% by weight of the absorbent material contained in the core wrap. Often an SAP content of 20% to 50% by weight of the absorbent material contained in the core wrap is useful. The core wrap is not considered as absorbent material for the purpose of assessing the percentage of SAP in the absorbent core.

(113) The SAP content may be higher than 30%, for example at least 40%, at least 50%, at least 80% of the weight of the absorbent material contained within the core wrap. The absorbent material may in particular embodiments comprise from 10 to 70, for example 30 to 60 weight percent of natural or synthetic fibers.

(114) The absorbent core may comprise a generally planar top edge and a generally planar bottom edge. In some embodiments, the absorbent material will be advantageously distributed in higher amount towards the front edge than towards the rear edge as more absorbency is required at the front. In other embodiments, typically embodiments for other uses of an absorbent article, such as care of elderly incontinent people versus care of babies, the absorbent material will be advantageously distributed in higher amount towards the rear edge than towards the front edge as more absorbency is required at the rear area.

(115) The core wrap may be formed by two separate sheets of nonwoven material which may be at least partially sealed along the edges of the absorbent core. The core wrap may be at least partially sealed along its front edge, back edge and two longitudinal edges so that substantially no absorbent material leaks out of the absorbent core wrap.

(116) The absorbent core of the absorbent article may further comprise adhesive for example to help immobilizing the SAP within the core wrap and/or to ensure integrity of the core wrap, in particular when the core wrap is made of two or more substrates. Such an adhesive can be provided in the form of fibrous thermoplastic adhesive material.

(117) The fibrous thermoplastic adhesive material may be at least partially in contact with the superabsorbent material in the land areas and at least partially in contact with the substrate layer in the junction areas. This imparts an essentially three-dimensional structure to the fibrous layer of thermoplastic adhesive material, which in itself is essentially a two-dimensional structure of relatively small thickness, as compared to the dimension in length and width directions. Thereby, the fibrous thermoplastic adhesive material may provide cavities to cover the absorbent material in the land area, and thereby immobilizes this absorbent material.

(118) The thermoplastic adhesive material may comprise, in its entirety, a single thermoplastic polymer or a blend of thermoplastic polymers, having a softening point, as determined by the ASTM Method D-36-95 “Ring and Ball”, in the range between 50° C. and 300° C., and/or the thermoplastic adhesive material may be a hotmelt adhesive comprising at least one thermoplastic polymer in combination with other thermoplastic diluents such as tackifying resins, plasticizers and additives such as antioxidants.

(119) Superabsorbent material, herein also referred to as superabsorbent polymer material, superabsorbent polymers or SAP, refers to absorbent materials which are cross-linked polymeric materials that can absorb at least 10 times their weight of an aqueous 0.9% saline solution as

measured using the Centrifuge Retention Capacity (CRC) test (EDANA method WSP 241.2-05E). The SAP used may in particular have a CRC value of more than 20 g/g, or more than 24 g/g, or of from 20 to 50 g/g, or from 20 to 40 g/g, or 24 to 30 g/g. The SAP useful in example absorbent articles may include a variety of water-insoluble, but water-swellaable polymers capable of absorbing large quantities of fluids.

(120) The superabsorbent polymer can be in particulate form so as to be flowable in the dry state. Typical particulate absorbent polymer materials are made of poly(meth)acrylic acid polymers. However, e.g. starch-based particulate absorbent polymer material may also be used, as well polyacrylamide copolymer, ethylene maleic anhydride copolymer, cross-linked carboxymethylcellulose, polyvinyl alcohol copolymers, cross-linked polyethylene oxide, and starch grafted copolymer of polyacrylonitrile. The superabsorbent polymer may be polyacrylates and polyacrylic acid polymers that are internally and/or surface cross-linked.

(121) The SAP useful for example embodiments of absorbent articles may be of numerous shapes. The term “particles” refers to granules, fibers, flakes, spheres, powders, platelets and other shapes and forms known to persons skilled in the art of superabsorbent polymer particles. In some embodiments, the SAP particles can be in the shape of fibers, i.e. elongated, acicular superabsorbent polymer particles. In those embodiments, the superabsorbent polymer particles fibers have a minor dimension (i.e. diameter of the fiber) of less than about 1 mm, usually less than about 500 μm , and preferably less than 250 μm down to 50 μm . The length of the fibers is preferably about 3 mm to about 100 mm. The fibers can also be in the form of a long filament that can be woven.

(122) Typically, SAP are spherical-like particles. In contrast to fibers, “spherical-like particles” have a longest and a smallest dimension with a particulate ratio of longest to smallest particle dimension in the range of 1-5, where a value of 1 would equate a perfectly spherical particle and 5 would allow for some deviation from such a spherical particle. The superabsorbent polymer particles may have a particle size of less than 850 μm , or from 50 to 850 μm , preferably from 100 to 710 μm , more preferably from 150 to 650 μm , as measured according to EDANA method WSP 220.2-05. SAP having a relatively low particle size help to increase the surface area of the absorbent material which is in contact with liquid exudates and therefore support fast absorption of liquid exudates.

(123) The SAP may have a particle sizes in the range from 45 μm to 4000 μm , more specifically a particle size distribution within the range of from 45 μm to about 2000 μm , or from about 100 μm to about 1000, 850 or 600 μm . The particle size distribution of a material in particulate form can be determined as it is known in the art, for example by means of dry sieve analysis (EDANA 420.02 “Particle Size distribution”).

(124) The total amount of SAP present in the absorbent core may also vary according to expected usage. Diapers for newborns may require less SAP than infant or adult incontinence diapers. The amount of SAP in the core may be for example comprised from about 2 to 60 g, in particular from 5 to 50 g or 10 to 40 g. The average SAP basis weight within the (or “at least one”, if several are present) deposition area of the SAP may be for example of at least 50, 100, 200, 300, 400, 500 or more g/m². The areas of the channels present in the absorbent material deposition area, if any, are deduced from the absorbent material deposition area to calculate this average basis weight.

(125) The optional core wrap may be made of a single substrate folded around the absorbent material, or may advantageously comprise two (or more) substrates which are attached to another. Typical attachments are the so-called C-wrap and/or sandwich wrap. In a C-wrap, as exemplarily shown in FIG. 2, the longitudinal and/or transversal edges of one of the substrate are folded over the other substrate to form flaps. These flaps are then bonded to the external surface of the other substrate, typically by gluing.

(126) If the core wrap comprises a first substrate **66a** and a second substrate **66b** these may be made of the same type of material, or may be made of different materials or one of the substrate

may be treated differently than the other to provide it with different properties. As the polymers used for nonwoven production are inherently hydrophobic, they are preferably coated with hydrophilic coatings if placed on the fluid receiving side of the absorbent core. It is advantageous that the top side of the core wrap, i.e. the side placed closer to the wearer in the absorbent article, be more hydrophilic than the bottom side of the core wrap. A possible way to produce nonwovens with durably hydrophilic coatings is via applying a hydrophilic monomer and a radical polymerization initiator onto the nonwoven, and conducting a polymerization activated via UV light resulting in monomer chemically bound to the surface of the nonwoven. An alternative possible way to produce nonwovens with durably hydrophilic coatings is to coat the nonwoven with hydrophilic nanoparticles.

(127) The absorbent article may comprise a pair of barrier leg cuffs **30**. The barrier leg cuffs can be formed from a piece of material, typically a nonwoven, which is partially bonded to the rest of the article so that a portion of the material, the barrier leg cuffs, can be partially raised away and stand up from the plane defined by the topsheet when the article is pulled flat as shown e.g. in FIG. **1**. The barrier leg cuffs can provide improved containment of liquids and other bodily exudates approximately at the junction of the torso and legs of the wearer. The barrier leg cuffs extend at least partially between the front edge and the back edge of the diaper on opposite sides of the longitudinal axis and are at least present at the level of the crotch point (P). The barrier leg cuffs are delimited by a proximal edge **32** joined to the rest of the article, typically the topsheet and/or the backsheet, and a free terminal edge **66**, which is intended to contact and form a seal with the wearer's skin. The barrier leg cuffs are joined at the proximal edge **32** with the chassis of the article by a bond **33** which may be made for example by gluing, fusion bonding or combination of known bonding means. The bond **33** at the proximal edge **32** may be continuous or intermittent. The side of the bond **33** closest to the raised section of the leg cuffs delimits the proximal edge **32** of the standing up section of the leg cuffs. The distance between the inner sides of these bond **33** define the dry and wet width of the article at this level for the purpose of RCWR test (see below).

(128) The barrier leg cuffs can be integral with the topsheet or the backsheet, or more typically be formed from a separate material joined to the rest of the article. Typically the material of the barrier leg cuffs may extend through the whole length of the diapers but is “tack bonded” to the topsheet towards the front edge and back edge of the article so that in these sections the barrier leg cuff material remains flush with the topsheet. Each barrier leg cuff **30** may comprise one, two or more elastic **36** close to this free distal edge **34** to provide a better seal.

(129) In addition to the barrier leg cuffs **30**, the article may comprise gasketing cuffs **26**, which are joined to the chassis of the absorbent, article, in particular the topsheet and/or the backsheet and are placed transversely outwardly relative to the barrier leg cuffs. The gasketing cuffs can provide a better seal around the thighs of the wearer. Usually each gasketing leg cuff will comprise one or more elastic string or elastic element comprised in the chassis of the diaper for example between the topsheet and backsheet in the area of the leg openings.

(130) Embodiments of the absorbent articles may comprise an acquisition-distribution layer or system **50** (herein “ADL”) and may be a single layer (preferably a spunbond or carded thermobonded layer, or an air-layed nonwoven layer) or may be multilayer and comprising one or more of the following nonwoven layers: spunbond, carded thermobonded, meltblown, and combinations thereof. The function of the ADL is to quickly acquire the fluid and distribute it to the absorbent core in an efficient manner. The ADL may comprise one, two or more layers, which may form a unitary layer or remain discrete layers which may be attached to each other. In the examples below, the ADL can comprise two layers: a distribution layer **54** and an acquisition layer **52** disposed between the absorbent core and the topsheet, but embodiments of absorbent articles are not restricted to this example and rather multilayer or single-layer ADLs are equally contemplated herein.

(131) Typically, the ADL will not comprise SAP as this may slow the acquisition and distribution

of the fluid.

(132) The distribution layer **54** and the acquisition layer **52** may comprise the same or different layers.

(133) For example the distribution layer **54** may be a nonwoven selected from a spunbond, meltblown, carded (preferably thermobonded), and combinations thereof.

(134) The ADL may comprise an acquisition layer **52**. The acquisition layer may be disposed between the distribution layer **54** and topsheet **22**. The acquisition layer **52** may typically be or comprise a non-woven material, for example a SMS or SMMS material, comprising a spunbonded, a melt-blown and a further spunbonded layer or alternatively a carded chemical-bonded nonwoven.

(135) The absorbent article may include a fastening system. The fastening system can be used to provide lateral tensions about the circumference of the absorbent article to hold the absorbent article on the wearer as is typical for taped diapers. This fastening system is not necessary for training pant article since the waist region of these articles is already bonded. The fastening system usually comprises a fastener such as tape tabs (also referred to as adhesive tabs), hook and loop fastening components, interlocking fasteners such as tabs & slots, buckles, buttons, snaps, and/or hermaphroditic fastening components, although any other known fastening means are generally acceptable. A landing zone is normally provided on the front waist region for the fastener to be releasably attached.

(136) The absorbent article may comprise front ears **46** and back ears **40** as is known in the art. The ears can be integral part of the chassis, for example formed from the topsheet and/or backsheet as side panel. Alternatively, as represented on FIG. **1**, they may be separate elements attached by gluing and/or heat embossing or pressure bonding. The back ears **40** are advantageously stretchable to facilitate the attachment of the adhesive tabs **42** on the landing zone **44** and maintain the taped diapers in place around the wearer's waist. The back ears **40** may also be elastic or extensible to provide a more comfortable and contouring fit by initially conformably fitting the absorbent article to the wearer and sustaining this fit throughout the time of wear well past when absorbent article has been loaded with exudates since the elasticized ears allow the sides of the absorbent article to expand and contract.

(137) The absorbent article may also comprise at least one elastic waist feature that helps to provide improved fit and containment. The elastic waist feature is generally intended to elastically expand and contract to dynamically fit the wearer's waist. The elastic waist feature preferably extends at least longitudinally outwardly from at least one waist edge of the absorbent core **20** and generally forms at least a portion of the end edge of the absorbent article. Disposable diapers can be constructed so as to have two elastic waist features, one positioned in the front waist region and one positioned in the back waist region. The elastic waist feature may be constructed in a number of different configurations including those described in U.S. Pat. Nos. 4,515,595, 4,710,189, 5,151,092 and 5,221,274.

(138) Typically, adjacent layers and components will be joined together using conventional bonding method such as adhesive coating via slot coating or spraying on the whole or part of the surface of the layer, or thermo-bonding, or pressure bonding or combinations thereof. This bonding is not represented in the Figures (except for the bonding by bonds **33** between the raised elements of the barrier leg cuffs **30** with the topsheet **22**) for clarity and readability but bonding between the layers of the article should be considered to be present unless specifically excluded. Adhesives may be typically used to improve the adhesion of the different layers, for example between the backsheet and the core wrap. The glue may be any standard hotmelt glue as known in the art.

(139) FIGS. **5A** and **5B** show partial schematic views of an example embodiment of a reusable detector device **100** that may be removably attached externally to a diaper, such as shown in FIG. **4**. In this example embodiment, for example, all electronic components of the detector may be disposed outside the diaper. The detector device **100** is adapted to detect one or more color changes in an indicator **120**, such as a color change strip **122**, disposed within the diaper. In this particular

embodiment, the indicator **120** changes color directly or indirectly in response to presence and/or absence of a bodily exudate within the diaper.

(140) The color change strip **122**, for example, may be disposed in the diaper such as shown in FIG. **1** generally along a mid-line of the diaper and extend a predetermined distance in the cross-direction of the diaper. In one particular embodiment, for example, the color change strip **122** is between approximately 4 mm and 45 mm wide, preferably from 10 mm to 40 mm wide, even more preferably from 12 mm to 35 mm wide, even more preferably from 15 mm to 30 mm wide, such as approximately 20 mm wide, and between approximately 100 and 300 mm long, such as approximately 100 mm, 150 mm, 200 mm, 250 mm or 300 mm long. The dimensions of the color change strip, however, are merely exemplary and not limiting. The color change strip **122** (or other indicator **120**), for example, may include any number of form factors, such as but not limited to one or more stripes, circles, rectangles, dots, designs (e.g., a character or other drawing). The indicator **120** may also be disposed in other locations of the diaper than shown in FIG. **1**. Further, where the indicator **120** includes a material (e.g., adhesive, SAP/AGM) that migrates within the diaper or fades as the more bodily exudates are introduced into the diaper, a detection algorithm may maintain a state of wet/soiled once an initial detection has been made. For example, a ratchet or other feature in an algorithm may be used to maintain an indication that bodily exudates have been detected until the diaper has been changed or the detector **100** has been removed from the diaper.

(141) The detector device **100** includes one or more optical (e.g., color) sensors **102** and a light source **104** (e.g., an LED). The optical sensor **102** measures one or more light levels from the indicator **120**. In one particular embodiment, for example, the color sensor measures four light levels—clear, red, green and blue—with a sixteen (16) bit resolution. The clear level corresponds to a measure of an overall light intensity and the red, green and blue levels correspond to intensity in the relevant parts of the spectrum from the indicator **120**. In this embodiment, the detector device **100** takes multiple measurements with the optical sensor **102**. In a first operation, the optical sensor **102** is read without the light source **104** (e.g., the LED) illuminated to determine a background light level. Another reading of the color sensor is taken in another operation with the light source **104** illuminating the color change strip **122** of the indicator **120** to measure the clear, red, green and blue (RGB) light levels. A difference between the two measurements is obtained in a third operation and represents a color of the color change strip **122** of the indicator **120**. The clear color level may be used to normalize the RGB values. Fill levels corresponding to one or more intermediate states of the indicator **120** may also be determined, such as from the hue, saturation and brightness (HSB) values in combination with or instead of the RGB values.

(142) The optical sensor **102** may be spaced (or be positioned distal) from the light source **104** so that direct light from the light source **104** is reduced or eliminated at the optical sensor **102**. Similarly, too large a spacing between the optical sensor **102** and the light source **104** may reduce the signal strength at the optical sensor **102**. In one embodiment, for example, the optical sensor **102** may be spaced at least about 5 mm from the light source **104**. In another embodiment, the optical sensor may be spaced at least about 8 mm from the light source **104**, at least about 10 mm from the light source **104**, between approximately 5 and 20 mm from the light source **104**, and between approximately 10 to 15 mm from the light source **104**.

(143) In one embodiment, the optical sensor **102** may be positioned substantially between a plurality of light source **104**. For example, when two light sources are used, they are spaced apart along an axis and the optical sensor is positioned about mid-way along said axis. Alternatively, in case more than two light sources are used, they are preferably positioned along a circumference of an imaginary circle and the optical sensor is positioned at about the centre of said imaginary circle.

(144) In addition to spacing between the optical sensor **102** and the light source **104**, other factors may also affect light level measurements of the optical sensor **102**. For example, temperature, location of the detector device **100** on the diaper, the type, material and color of a connector (e.g., adhesive, tape, hook and loop, strap and other materials) disposed between the detector device **100**

and the indicator **120** disposed within the diaper, orientation of the detector device **100** relative to the indicator **120**, orientation of transmit and receive windows of the detector device **100** and the diaper, force of application of the detector device **100** against the diaper (e.g., may affect the distance between the optical sensor **102** and light source **104** of the detector device **100** and the indicator **120** of the diaper in use), ambient light, placement of an attachment zone on the diaper for coupling to the detector device **100** and placement of the detector device **100** relative to the indicator **120** of the diaper (e.g., in a cross-direction) such that the optical sensor **102** detects other components of the diaper disposed near the indicator **120**.

(145) In one embodiment, for example, the color change strip **122** changes color in response to a change in pH within the diaper. Swelling of Super Absorbent Polymers (SAP)/Absorbent Gelling Materials (AGM) within the diaper changes the pH of the environment within the diaper. In response to a change in pH, the color change strip **122** changes in color. The color change strip **122**, for example, may comprise a pH sensitive glue, such as H9588 glue that is commercially available from Bostik. While a human eye may only be able to distinguish general changes in color, such as a transition from yellow (dry) to blue (wet), an electronic color sensor such as a photodiode can detect intermediate colors as the indicator transitions from a first state to a second state.

(146) Although a pH sensitive color change strip **122** is discussed with respect to an example embodiment, the indicator **120** is not so limited. Rather, the indicator **120** may include any indicator that changes color or other appearance directly or indirectly related to the presence or absence of bodily exudates within the diaper. For example, color change materials that change from no color to one or more colors, from one or more colors to no colors, change colors in other color ranges than the pH sensitive adhesive described herein, materials that change color or appearance based on factors other than pH changes, such as but not limited to, temperature, wetness, odor, enzymes, organic components, inorganic components (e.g., salt level), colored SAP/AGM, mechanical forces (e.g., strain, stretch) or the like.

(147) Preferred however, are indicators that change from yellow (in dry state) to blue (in wet state), and green in a transition state from yellow to blue (or from dry to wet).

(148) As discussed with respect to FIG. **4** above, the detector device **100**, may include one or more user signal devices, which may include an audio and/or visual indicator such as but not limited to one or more LEDs, LCDs, display screens, lights, speakers or other indicators, that may be used to indicate the presence and/or absence of bodily exudates detected within the diaper.

(149) The detector device **100** may further include a communication module **106** adapted to transmit data from the detector device **100** to a remote device **130**, such as for storage and/or presentation to a user. The communication module **106**, for example, may include a Bluetooth communication module, a BTLE communication module, a mesh communication module (e.g., IEEE 802.15.4), a WiFi communication module (e.g., IEEE 802.15.11), a communication module incorporating all or any portion of IEEE 802 or similar communication standards, an RFID module, a 3G or 4G communication module, a Backscatter communication module, a light communication module, a sound communication module, a harvesting protocol communication module (e.g., a metadata harvesting protocol communication module). Other communications protocols or combinations of communications protocols (e.g., a Bluetooth/Mesh combined protocol) and mechanisms may also be used.

(150) In one embodiment, for example, a smartphone, tablet, computer or other remote device may be used to receive information from the detector device **100**, determine one or more state of the diaper (e.g., presence or absence of one or more bodily exudates) and display information related to the state of the diaper to a user. The remote device may be in direct communication with the detector device and/or be communicatively coupled with detector device (or via an intermediate device) via one or more computer networks, such as the Internet.

(151) FIG. **6** shows a block diagram of an example implementation of a detector device **200** adapted for removably coupling with one or more diapers. In this particular embodiment, the

detector device **200** includes a color sensor **202**, an LED light source **204**, a low energy Bluetooth (BTLE) communication module **206** and one or more batteries **208**. The batteries **208**, for example, may include one or more silver oxide batteries, nickel cadmium batteries, lithium batteries, alkaline batteries, capacitors or other energy storage devices. The batteries **208** may be disposable or rechargeable and provide power to the other components of the detector device **200**.

(152) In one embodiment, the detector device may further include one or more processors and memory storage for providing processing on the detector device **200**.

(153) The communications module **206**, for example, may be limited in power and/or duration of transmission to reduce electromagnetic (EM) energy transmitted in close proximity to a wearer of the diaper. The BTLE module **206**, for example, may be operated at approximately 2 mW for approximately 0.005% time of the time it is in operation (approximately one transmission per minute).

(154) FIG. 7 shows top, bottom and side views of an example embodiment of an exterior of a detector device **300**, such as the one shown in FIG. 8. In this embodiment, the top side **302** of the device **300** faces outwardly from a diaper in use and includes a decorative design. The bottom side **304** of the device includes a window **306** through which a light source, such as the LED light source **204** shown in FIG. 6, may transmit to an indicator disposed within the diaper and a color sensor may detect one or more colors of the indicator. In the particular embodiment shown in FIG. 7, for example, the a plurality of screws **308** or other connectors may secure the top and bottom components to each other. The side **310** includes a notch **312** or other opening to assist a user to separate the top and bottom sides **302**, **304** if the screws **308** are disengaged.

(155) The container of the detector device **300** maybe sized and shaped to prevent the device **300** from being a choking hazard. The container may further include materials such as silicone, Tecaform, Tecanat or other materials. The device container may also include one or more muted colors to minimize its attractiveness to children.

(156) FIG. 8 shows an example embodiment an attachment zone **400** of a diaper exterior adapted for receiving a detector device, such as the detector device shown in FIGS. 6 and 7. The attachment zone **400** includes a landing zone material **402** to improve attachment of the detector device to the diaper. The landing zone material **402**, for example, may include a brushknit or adhesive or cohesive tape material for mechanically or adhesively coupling the detector device to an outer surface of the diaper. The landing zone material **402** includes a window opening **404** that corresponds to the window of the detector device (e.g., window **306** shown in FIG. 7). In one particular implementation, the landing zone material **402** may be sized and shaped similarly to the detector device so as to facilitate placement of the detector device on the outer surface of the diaper. Other landing zone materials are also contemplated. For example, loop, hook, adhesive, strap, button, snap, pocket, magnet, or other materials may be used on the diaper and/or detector device.

(157) Alternatively, a pocket design such as described on paragraphs 0079-0084, 0128 and 0130-0131 of EP3451988 herein incorporated by reference. Advantageously, by being retained in such pocket the risk of accidentally decoupling the clip-on unit is limited.

(158) FIG. 9 shows a flow diagram of example operations that may be used to detect one or more bodily exudates within a diaper. In this embodiment, a detector device includes one or more color sensors for detecting one or more state of an indicator in a diaper. As described above, a color sensor of the detector device may determine one or more RGB light levels or HSB levels of the indicator. A communications device of the detector device may provide information based upon a detected color of the indicator to a remote computing device. The remote computing device then predicts presence, absence and/or amount of one or more bodily exudates based at least in part on the information received from the detector device. The remote computing device, for example, may determine a local saturation (e.g., exudate content quantity) level based upon the information received from the detector device.

(159) The remote computing device may further receive additional inputs, such as but not limited to, wear time, the time the absorbent article was attached to a wearer, the current time, absorbent article user information (e.g., baby demographic information such as sex, age, weight of wearer, whether the wearer is toilet training, degree of wearer incontinence), user input information, caregiver preference information, biometric information of the wearer, ambient sensor information and/or contextual information, and may use these additional inputs separately and/or in combination with the information received from the detector device.

(160) In the particular embodiment, shown in FIG. 9, for example, the remote computing device determines a predicted diaper fullness level (e.g., an exudate content quantity of the absorbent article such as a liquid and/or solid exudate content quantity) or state based at least in part upon the sensor information received from the detector device and contextual information (e.g., wear time of the diaper and baby demographic information). Contextual information, for example, may be input by consumers, retrieved via other sensors or information sources (e.g., thermostats). Sensor data, for example, may include property change indications (e.g., digital or analog such as an intensity of color change in a color changing indicator) and wear time. In one implementation, an analog detection may be based upon a calibration of an indicator (e.g., color) for different exudate load. Wear time, for example, may be described as the time determined between attachments of two fresh diapers.

(161) Further, in one example, exudate fullness may be determined by the following functions:
$$\text{Urine Fullness} = f(\text{Property Change Detection, wear time, wearer data and other data})$$
$$\text{Property Change Detection} = f(\text{color sensor data}).$$

(162) An exudate content quantity, for example, may be provided to a user to indicate a percent or other indication of diaper fullness or remaining capacity on the detector device, a remote display or a remote computing device. In one particular implementation, for example, the remote display or computing device may display a graphical or numerical representation of exudate content quantity or remaining capacity of the absorbent article.

(163) Calibration of the color of the indicator to a particular exudate load quantity, for example, can be determined in a number of manners. For example, in one embodiment, different load quantities of an absorbent article may be introduced and corresponding colors can then be measured. In another embodiment, for a given load quantity, a color change may be mapped versus time measured during loading to provide a kinetic curve that represents an exudate load quantity versus time.

(164) FIG. 10 shows example embodiments of spaced optical sensor **602** and light element **604** pairs of example embodiments of one or more detector devices. In these embodiments, various combinations of sensors (e.g., optical and/or color sensors) are spaced by a distance d from each other. For purposes of the present disclosure, the measurement d is a straight line measurement from the nearest points of the various optical sensors **602** and light elements **604**. In one example embodiment, for example, the optical sensor **602** and light element **604** are spaced at least about 5 mm from each other. In other embodiments, the optical sensor **602** and light element **604** are spaced at least about 8 mm, at least about 10 mm, between about 10 mm and about 15 mm and between about 10 mm and 20 mm.

(165) FIG. 11 shows another example embodiment of a detector device **620**. In this embodiment, for example, an optical sensor **622** and a light element **624** are spaced from each other a distance d . The detector device **620** further includes a communication module **606** and a pair of batteries **608**. Screw holes **630** are also provided to allow a cover to be securely fastened to enclose the components of the detector device. As described above, the detector device **620** may further include a window opposing the spaced optical sensor **622** and light element **624**.

(166) FIG. 12 shows another example embodiment of a detector device **640** comprising a plurality of spaced optical sensor and light pairs **642**. In this particular embodiment, three pairs of individual spaced optical sensor and light pairs **642** are disposed in different locations of the detector device

640 and adapted to detect a change in one or more optical properties at different locations of an absorbent article. The detector device **640** further comprises a communication module **646** and a battery **648** adapted to provide power to the sensors, lights and communication module **646**. (167) FIG. **13** shows yet another example embodiment of a detector device **660** comprising a plurality of spaced optical sensor and light pairs **662**. In this particular embodiment, five pairs of individual spaced optical sensor and light pairs **662** are disposed in different locations of the detector device **660** and adapted to detect a change in one or more optical properties at different locations of an absorbent article. The detector device **660** further comprises a communication module **646** and a battery **668** adapted to provide power to the sensors, lights and communication module **646**.

(168) FIG. **14** shows still another example embodiment of a detector device **680** comprising a plurality of spaced optical sensor and light pairs **682**. In this particular embodiment, two pairs of individual spaced optical sensor and light pairs **682** are disposed in different locations of the detector device **680** and adapted to detect a change in one or more optical properties at different locations of an absorbent article. The detector device **680** further comprises a communication module **686** and a battery **688** adapted to provide power to the sensors, lights and communication module **686**.

(169) FIG. **15** shows an example embodiment of an absorbent article **700** including a detector device **702** disposed adjacent to the absorbent article **700**. In this particular embodiment, the detector device comprises a plurality of sensors **704**. Each of the plurality of sensors **704** is spaced from each other and adapted to be disposed opposite different locations **706** of the absorbent article **700**. As shown in FIG. **15**, for example, a first sensor **708** is disposed opposite a front region of the absorbent article **700** and a second sensor **710** is disposed opposite a crotch region of the absorbent article **700**. The first and second sensors **708**, **710**, for example, may be spaced at least about 2 cm from each other, at least about 3 cm from each other, at least about 4 cm from each other, at least about 5 cm from each other, or at least about 10 cm from each other. This allows the sensors to detect property changes (e.g., optical/color property changes) in different regions of the absorbent article **700**. Further, the plurality of sensors **704** may comprise the same or different types of sensors.

(170) By measuring changes in multiple areas of the absorbent article, the detector device may be able to provide a better prediction of the presence and/or quantity of bodily exudates within the absorbent article given the broad distribution of urination patterns, urination loADL, dietary habits, wearer movement and activity during wear time, wearer body dimensions and the like, all of which may have an effect on exudate distribution within the absorbent article.

(171) FIG. **16** shows another example embodiment of an absorbent article **720** including a plurality of property changing indicators **722** disposed within the absorbent article **720**. In this embodiment, for example, the plurality of property changing indicators **722** comprises at least a first property changing indicator **724** of a first type and a second property changing indicator **726** of a second type that is different from the first type.

(172) FIG. **17** shows yet another example embodiment of an absorbent article **740** including a plurality of property changing indicators **742** disposed within the absorbent article **740**. In this embodiment, for example, the plurality of property changing indicators **742** comprises at least a first property changing indicator **724** and a second property changing indicator **726** of the same type of property changing indicator.

(173) In addition to the sensors described herein adapted to detect one or more property changes of an indicator, the detector devices may further include one or more additional sensors adapted to detect other conditions unrelated to the specific indicators of an absorbent article. For example, the detector device may further include one or more additional sensors such as, but not limited to, a temperature sensor, a humidity sensor, a relative humidity sensor, a chemical sensor, an audio sensor, a microphone, a strain gauge, a material expansion sensor and a vibration sensor.

(174) In an embodiment, a kit comprising an absorbent article and a detection device (70) such as described herein, may comprise a plurality of the absorbent articles and a detection device (70), wherein the detection device (70) is removably attached to the absorbent articles, one after another as they are used, and wherein the detection device (70) is arranged to stop working after a predetermined period of time, preferably wherein the predetermined period of time is more than 20 days and less than 50 days, more preferably from 30 days to 40 days. This allows for combining the sale of such kits with a subscription model to ensure continuity of absorbent article delivery.

(175) Preferably, the detection device comprises a battery and an internal clock, and wherein the life of the battery is greater than the predetermined time period, and wherein the predetermined time period is determined by said internal clock after the detection device (70) is first activated. Advantageously, the battery is still capable to operate the receiver such that as soon as a signal (e.g. relating to a confirmation trigger that a subscription has been activated or renewed) is received by the detection device is configured to reset the internal clock and continue operability and functionality.

(176) In an embodiment, the battery is re-chargeable, preferably by wireless means, and wherein the internal clock is in electrical communication with a switch that powers off the detection device once the predetermined time period has lapsed and typically further in electrical communication with a second switch that prevents the battery to be re-charged, preferably wherein the predetermined time period is remotely reset upon response to an incoming signal wherein said incoming signal is triggered by an event such as selected from the group consisting of a renewal of a non-existing or expired subscription, an automatic renewal of a subscription, a confirmation that a subscription is still active, and combinations thereof. Advantageously, this allows to promote continuity in the subscription in a more environmentally friendly way compared to for example limiting the predetermined period by battery life of a non-rechargeable or non-replaceable battery and force users to purchase a new detector device each time the battery depletes and/or receive a free one each time an active subscription is made.

(177) In any of the embodiments, the indicators herein may comprise an electrically conductive ink arranged in a pattern comprising a plurality of open circuits each corresponding to different positions of an absorbent core, said ink being printed on a skin-facing surface of the backsheet, wherein in response to a voiding event (or presence of exudates) a change in resistance is triggered within one or more of the circuits corresponding to the position of the voiding event. The pattern comprises a plurality of converging connection ends wherein each of said connection ends being adapted to come into electrical communication with corresponding connection terminals on the detection device when coupled to the absorbent article. The detection device typically comprising a battery, processor, a memory and a transmitter in order to process the triggered change in resistance and generate a signal to be sent to a further processing device (such as a computing device or a processing algorithm stored in the cloud).

(178) In a preferred embodiment, the indicator 60 is an electrically conductive sensor (typically said sensor comprising a plurality of conductive tracks as described hereinabove) adapted to change one or more of its electrical properties in response to a voiding event such as presence of exudates in the absorbent article. Preferably, wherein the one or more electrical properties are selected from the group consisting of resistance, capacitance, inductance, and combinations thereof.

(179) In an embodiment, the indicator 60 is adapted to detect each voiding event of a plurality of, typically sequential, voiding events throughout a wearing period of said absorbent article by a wearer. Advantageously, this allows for accurate monitoring of voiding pattern and behaviours with time to a degree that is not possible with standard color changing wetness indicators whereby once the color changes in response to a voiding event it fails to detect and differentiate any subsequent voiding events. Therefore, when the indicator comprises a color changing indicator it also comprises an electrically conductive sensor as described herein.

(180) Preferably, the detection device 70 is adapted to recognize and distinguish each voiding event

from each other voiding event immediately preceding and/or following the same, and preferably to cumulatively store a plurality of such events prior to transmitting a data set or data package to a processing device and/or computing means. Advantageously this allows to build a complete voiding pattern database that may be used to build a voiding pattern predictor and model.

(181) The Stock Management System

(182) Advantageously, the absorbent articles, kits and systems herein may allow for automatic inventory management in a household or even within institutional care.

(183) In an embodiment, the system for monitoring an absorbent article and providing stock management functionality comprises: an absorbent article comprising: a liquid permeable topsheet **22**, a liquid impermeable backsheet **24**, and an absorbent core **20** positioned between said topsheet **22** and backsheet **24**; an indicator **60** for indicating the presence of exudates, said indicator **60** being positioned on a body-facing side of said backsheet **24**, the indicator **60** comprising a color-changing indicator and/or an electrically conductive indicator (such as an electrically conductive ink); a detection device **70** that can be removably attached to the absorbent article and arranged to detect a change in condition of said indicator **60**; a computing means, such as a computing device or a computing algorithm typically stored on the cloud, arranged to deduct a one integer from a previous number n totaling the number of absorbent articles (typically in a stock or inventory of absorbent articles in a household or institution), including the one being used, (i.e. an inventory value) to generate a new number $n-1$ (i.e. an actual inventory value) representing the total number of absorbent articles left within an inventory (i.e. an inventory value), in response to at least one, preferably at least two, preferably only one, of the following: a signal from the detection device **70** triggered by a change in the state of the absorbent article such as from dry to wet; a signal from the detection device **70** triggered by a first-time connection to an absorbent article; and a signal from the detection device **70** triggered by disconnection of the detection device **70** from an absorbent article after a first-time connection to the absorbent article, and wherein the computing means is arranged to send a signal once the actual inventory value reaches a predefined threshold, wherein said signal triggers at least one of: a warning alarm (typically said alarm being triggered by the detection device or a mobile device as described in more detail hereinbelow); an automatic order of new stock comprising a plurality of new absorbent articles; and combinations thereof (by “new” it is meant herein an unused plurality of clean absorbent articles). Advantageously, this arrangement allows a user (or care giver) to be automatically notified when the stock of absorbent articles is running out well in advance to ensure replenishment without having to keep excessive stock within the household or institution and thus better manage supply chain based on needs and consumption. It is particularly advantageous to build an effective subscription model infrastructure where new deliveries of stock can be automated based on use rather than based on time period, hence providing a more flexible service to users and care givers based on the needs.

(184) In an embodiment, the detection device **70** has features as described in embodiments herein.

(185) In an embodiment, the detection device comprises a transmitter arranged to transmit signals to the computing means, preferably an algorithm or logic stored on a cloud-based server.

Advantageously, this allows to save battery power and processing power of the detection device in order to limit the size and cost thereof. Preferably the clip-on unit and the incontinence management system is arranged as described in co-pending application EP19178665.6, especially page 43 line 27 to page 57 line 28, herein incorporated by reference.

(186) As illustrated in exemplary FIG. **22**, following an optional pairing step, the detection device that is connected to the diaper begins to monitor for changes in status of the indicator (whether optical changes in case of a color changing indicator or electrical changes, such as resistance, in case of an electrically conductive indicator) and as soon as a wetness or voiding event is detected (such as exudates being present in the diaper) a signal is sent to the computing means to deduct an absorbent article from the total number of absorbent articles in an inventory or stock (such as an inventory or stock of absorbent articles in a household or institution).

(187) As illustrated in exemplary FIG. 23, following an optional pairing step, the detection device that is connected to the diaper begins to monitor for changes in status of the indicator and also the attachment state to the diaper (i.e. whether attached or not attached). The latter may be done by for example checking the presence of one of several, typically three, predetermined colors of the indicator (e.g. yellow, green or blue, in case a color changing indicator is used as described above that changes from yellow in dry state to blue in wet state) typically via the optical sensor; or a predetermined resistance when the indicator comprises one or more electrically conductive sensor tracks (such as a printed pattern with a conductive ink), and once a change is detected, such as a color different from the predetermined colors or the resistance increases to above said predetermined resistance, then a signal to the computing means is triggered to deduct an absorbent article from the total number of absorbent articles in an inventory or stock (such as an inventory or stock of absorbent articles in a household or institution).

(188) In an embodiment, the system for monitoring an absorbent article and providing stock management functionality comprises: an absorbent article comprising an optical property changing indicator adapted to change at least one optical property in response to the presence or absence of exudates, wherein the absorbent article and the indicator form one integral unit; a detection device comprising a housing, a battery, a transmitter and a receiver disposed within the housing, an optical sensor disposed within the housing, and at least two powered light sources disposed within the housing and spaced from the optical sensor, the optical sensor adapted to detect the change of the optical property of the indicator, wherein at least one of the absorbent article and the detection device is adapted to be associated together and disassociated from each other, wherein when the absorbent article and the detection device are associated together the light source emits light in a direction towards the absorbent article and the detection device is adapted to detect the change of optical property of the indicator in response to the presence or absence of exudates, wherein the at least two light sources comprise a first light source and a second light source being of different colors, preferably a Blue light source and a Red light source, and wherein each time the detection device detects a change in the state of the absorbent article such as from dry to wet, the detector device sends a signal to a computing device that is arranged, in response thereto, to deduct a one integer from a previous number n totaling the number of absorbent articles, including the one being used, to generate a new number $n-1$ representing the total number of absorbent articles left within an inventory, and preferably wherein the computing device sends a signal once the inventory value reaches a predefined threshold, wherein said signal is selected from the group consisting of (or triggers one or more of): a warning alarm, an automatic order of new stock comprising a plurality of new absorbent articles, and combinations thereof. Advantageously, this allows for a simple and effective way to manage an inventory without complex systems requiring recognizing of connection/decoupling of the detection device or other means to recognize when an absorbent article such as a diaper is being disposed of to track how many are left from a given stock. Indeed, the principle is that as soon as a voiding event happens, the diaper will at some point need to be replaced and for systems that are already designed to detect wetness events further linking an inventory management to specifically the voiding event leads to a reliable inventory tracking.

(189) In an embodiment, as exemplary shown in FIG. 24, the systems herein further comprise a mobile device such as a smartphone comprising an application with a user interface, and wherein at least an initial inventory value n is manually set by the user or caregiver such as when replenishing a stock comprising a plurality of absorbent articles in a household or institution via said mobile device, preferably wherein the mobile device is in wireless data communication with the computing means. Advantageously this allows users and caregivers to directly interact with the stock management system.

(190) In an embodiment, the inventory value n is automatically reset upon delivery of a new stock comprising a plurality of new absorbent articles, that are delivered within a subscription, typically following a respective signal sent from a subscription interface to the computing means.

Advantageously this allows for a usage based subscription model to be optimally implemented rather than classic time-based subscription models for a more individualized and user-focused experience.

(191) In an embodiment, once the actual inventory value reaches a predetermined threshold, such as a number from 10 to 40, the computing means is arranged to send a signal to a subscription interface to release the next shipment of absorbent articles to replenish the stock of a plurality of absorbent articles in a respective household or institution that is associated with said actual inventory value.

(192) Typically, one or more detection devices comprise a unique identifier that is associated to a household or institution, and typically wherein a plurality of metadata are associated with said unique identifier such as address and subscription status of the household or institution, and are typically retained in data transfer between the detection device(s) and the computing means. Preferably, wherein the computing means computes, updates and stores a plurality of inventory values for a plurality of households and/or institutions.

(193) In an embodiment, the predetermined threshold is pre-set manually by a user via a mobile device application, and typically wherein the subscription interface is adapted to send a signal to the computing means and/or mobile device application to trigger a warning and a suggested new predetermined threshold in response to a delivery-affecting event such as upcoming national holiday(s), strike of postal delivery providers, delays in supply chain production and the like. Advantageously this allows the user or caregiver to choose to increase the predetermined threshold value in order to have sufficient stock to cope with the event.

(194) Preferably, the mobile device application comprises a anticipated-delivery-request tab that when activated by a user or requestor (e.g. following such a warning as described above) triggers a signal to the subscription interface to deliver a new stock of absorbent articles even if the predetermined threshold is not reached.

(195) In an embodiment, the application stores historical data comprising voiding events and patterns such that it may be consulted by a user or caregiver or a predictive model be generated based thereon.

Claims

1. An absorbent article for personal hygiene, the absorbent article comprising: a liquid permeable topsheet (22); a liquid impermeable backsheet (24); an absorbent core (20) positioned between said topsheet (22) and backsheet (24), an indicator (60) for indicating the presence of exudates and being positioned on a body-facing side of said backsheet (24), the indicator (60) comprising an electrically conductive material, the article further comprising a detection device (70) that can be removably attached to the absorbent article such to become in electrical communication with said indicator (60) when attached to said article to measure a change in resistance or capacitance in response to a voiding event, characterized in that the absorbent core (20) comprises one or more channels (500) substantially free of absorbent material, and in that the indicator (60) comprises a pattern that extends inboard and/or outboard of said channel(s) such that it does not substantially overlap with said channel(s), wherein the pattern extends substantially parallel to at least a portion of said channel(s).

2. An absorbent article according to claim 1, wherein the absorbent core (20) comprises a core wrap (66) enclosing absorbent material therein and wherein a top layer (66a) of the core wrap (66) is joined to a bottom layer (66b) of the core wrap (66) to form one or more channels (500) substantially free of absorbent material.

3. An absorbent article according to claim 1, wherein the absorbent core (20) comprises a plurality of channels (500) comprising at least one right channel and at least one left channel, the right channel being disposed between the right side edge (18) and the longitudinal centreline along axis

(Y), and the left channel being disposed between the left side edge (16) and the longitudinal centreline along axis (Y), wherein the right and left channels are arcuate in shape such that the front and back ends of the left and right channels diverge towards the left side edge (16) and the transversely opposed right side edge (18) respectively and wherein the central portion of said channels converge towards the longitudinal centreline along axis (Y); or wherein the absorbent core (20) comprises a single channel (500) comprising two parallel and opposing longitudinally extending portions and one transversely extending portion connecting said longitudinally extending portions to form a substantially U-shaped channel (500).

4. An absorbent article according to claim 1, wherein the pattern of the indicator (60) comprises a plurality of sensing tracks (520) each track forming an open circuit corresponding to a different position of the backsheet (24) and the absorbent core (20) such that voiding events in said different positions may be individually monitored.

5. An absorbent article according to claim 4, wherein each of the sensing tracks (520) comprises a connection end (521) arranged to couple to a respective terminal end of the detection device (70) to form an electrical connection between said detection device (70) and said sensing tracks (520) of the indicator.

6. An absorbent article according to claim 4 wherein the sensing tracks (520) are printed with a conductive ink, wherein the conductive ink is a carbon-based ink and/or a conductive polymer-based ink.

7. An absorbent article according to claim 6 wherein the conductive polymer-based ink comprises a polymer selected from the group consisting of poly(pyrrole) s (PPY), polyanilines (PANI), poly(thiophene) s (PT), poly(p-phenylene sulfide) (PPS), poly(p-phenylene) (PPP), Poly(acetylene) s (PAC), Poly(p-phenylene vinylene) (PPV), poly(3,4-ethylenedioxythiophene) (PEDOT), and mixtures thereof.

8. An absorbent article according to claim 6 wherein the conductive polymer-based ink comprises poly(3,4-ethylenedioxythiophene) polystyrene sulfonate (PEDOT:PSS).

9. An absorbent article according to claim 6 wherein the carbon-based ink comprises a conductive compound selected from the group consisting of graphene, graphite, nano-carbon-tubes and mixtures thereof.

10. An absorbent article according to claim 6 wherein the conductive polymer-based ink comprises a polymer selected from the group consisting of polyacetylene, polypyrrole, polyaniline and copolymers thereof.

11. An absorbent article according to claim 1, wherein the indicator (60) is free of metals.

12. An absorbent article according to claim 1, wherein the indicator (60) further comprises a color-changing indicator.

13. An absorbent article according to claim 12 wherein the detection device (70) further comprises an optical sensor and one or more light sources.

14. An absorbent article according to claim 1, wherein the indicator (60) is an electrically conductive sensor adapted to change one or more of its electrical properties in response to a voiding event in the absorbent article.

15. An absorbent article according to claim 14 wherein the one or more electrical properties are selected from the group consisting of resistance, capacitance, inductance, and combinations thereof.

16. An absorbent article according to claim 14 wherein the indicator (60) is adapted to detect each voiding event of a plurality of voiding events throughout a wearing period of said absorbent article by a wearer.

17. An absorbent article according to claim 16 wherein the detection device (70) is adapted to recognize and distinguish each voiding event from each other voiding event immediately preceding and/or following the same, and to cumulatively store a plurality of voiding events prior to transmitting a data set or data package to a processing device and/or computing means.

