

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12384214
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Graus; Jonathon P. et al.

Vehicle having adjustable compression and rebound damping

Abstract

A damping control system for a vehicle having a suspension located between a plurality of ground engaging members and a vehicle frame are disclosed. The vehicle including at least one adjustable shock absorber having an adjustable damping characteristic.

Inventors: Graus; Jonathon P. (Stacy, MN), Helgeson; David D. (Vadnais Heights, MN), Scheuerell; Alex R. (Wyoming, MN)

Applicant: Polaris Industries Inc. (Medina, MN)

Family ID: 70728723

Assignee: POLARIS INDUSTRIES INC. (Medina, MN)

Appl. No.: 18/625274

Filed: April 03, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240262151 A1	Aug. 08, 2024

Related U.S. Application Data

continuation parent-doc US 17175888 20210215 US 11884117 20240130 child-doc US 17888938
division parent-doc US 17888938 20220816 US 11975584 child-doc US 18625274
division parent-doc US 16198280 20181121 US 10987987 20210427 child-doc US 17175888

Publication Classification

Int. Cl.: B60G17/016 (20060101); B60G17/0165 (20060101); B60G17/019 (20060101)

U.S. Cl.:

CPC B60G17/0162 (20130101); B60G17/0164 (20130101); B60G17/0165 (20130101);
B60G17/01908 (20130101); B60G2300/07 (20130101); B60G2400/1042 (20130101);

B60G2400/1062 (20130101); B60G2400/412 (20130101); B60G2400/44 (20130101);
B60G2400/82 (20130101); B60G2400/90 (20130101); B60G2500/10 (20130101);
B60G2800/016 (20130101); B60G2800/212 (20130101); B60G2800/22 (20130101);
B60G2800/24 (20130101)

Field of Classification Search

CPC: B60G (17/0162); B60G (17/0164); B60G (17/0165); B60G (17/01908); B60G (2300/07); B60G (2400/1042); B60G (2400/1062); B60G (2400/44); B60G (2400/82); B60G (2400/90); B60G (2500/10); B60G (2800/016); B60G (2800/212); B60G (2800/22); B60G (2800/24)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3013442	12/1960	Fox et al.	N/A	N/A
3400945	12/1967	Sampietro	N/A	N/A
3623565	12/1970	Ward et al.	N/A	N/A
3737001	12/1972	Rasenberger	N/A	N/A
3760246	12/1972	Wright et al.	N/A	N/A
3861229	12/1974	Domaas	N/A	N/A
3933213	12/1975	Trowbridge	N/A	N/A
3952829	12/1975	Gray	N/A	N/A
3982446	12/1975	Van Dyken	N/A	N/A
4075841	12/1977	Hamma et al.	N/A	N/A
4112885	12/1977	Iwata et al.	N/A	N/A
4116006	12/1977	Wallis	N/A	N/A
4319658	12/1981	Collonia et al.	N/A	N/A
4327948	12/1981	Beck et al.	N/A	N/A
4340126	12/1981	Larson	N/A	N/A
4453516	12/1983	Filsinger	N/A	N/A
4462480	12/1983	Yasui et al.	N/A	N/A
4508078	12/1984	Takeuchi et al.	N/A	N/A
4580537	12/1985	Uchiyama	N/A	N/A
4600215	12/1985	Kuroki et al.	N/A	N/A
4620602	12/1985	Capriotti	N/A	N/A
4658662	12/1986	Rundle	N/A	N/A
4671235	12/1986	Hosaka	N/A	N/A
4681292	12/1986	Thomas	N/A	N/A
4688533	12/1986	Otobe	N/A	N/A
4691676	12/1986	Kikuchi	N/A	N/A
4691677	12/1986	Hotate et al.	N/A	N/A
4722548	12/1987	Hamilton et al.	N/A	N/A
4741554	12/1987	Okamoto	N/A	N/A
4749210	12/1987	Sugasawa	N/A	N/A
4759329	12/1987	Nobuo et al.	N/A	N/A
4765296	12/1987	Ishikawa et al.	N/A	N/A
4770438	12/1987	Sugasawa et al.	N/A	N/A
4779895	12/1987	Rubel	N/A	N/A
4781162	12/1987	Ishikawa et al.	N/A	N/A
4785782	12/1987	Tanaka et al.	N/A	N/A
4787353	12/1987	Ishikawa et al.	N/A	N/A

4805923	12/1988	Soltis	N/A	N/A
4809179	12/1988	Klingler et al.	N/A	N/A
4809659	12/1988	Tamaki et al.	N/A	N/A
4817466	12/1988	Kawamura et al.	N/A	N/A
4819174	12/1988	Furuno et al.	N/A	N/A
4826205	12/1988	Kouda et al.	N/A	N/A
4827416	12/1988	Kawagoe et al.	N/A	N/A
4831533	12/1988	Skoldheden	N/A	N/A
4838780	12/1988	Yamagata et al.	N/A	N/A
4856477	12/1988	Hanaoka et al.	N/A	N/A
4860708	12/1988	Yamaguchi et al.	N/A	N/A
4862854	12/1988	Oda et al.	N/A	N/A
4867474	12/1988	Smith	N/A	N/A
4881428	12/1988	Ishikawa et al.	N/A	N/A
4893501	12/1989	Sogawa	N/A	N/A
4895343	12/1989	Sato	N/A	N/A
4898137	12/1989	Fujita et al.	N/A	N/A
4898138	12/1989	Nishimura et al.	N/A	N/A
4901695	12/1989	Kabasin et al.	N/A	N/A
4903983	12/1989	Fukushima et al.	N/A	N/A
4905783	12/1989	Bober	N/A	N/A
4913006	12/1989	Tsuyama et al.	N/A	N/A
4919097	12/1989	Mitui et al.	N/A	N/A
4926636	12/1989	Tadokoro et al.	N/A	N/A
4927170	12/1989	Wada	N/A	N/A
4930082	12/1989	Harara et al.	N/A	N/A
4934667	12/1989	Pees et al.	N/A	N/A
4949262	12/1989	Buma et al.	N/A	N/A
4949989	12/1989	Kakizaki et al.	N/A	N/A
4961146	12/1989	Kajiwara	N/A	N/A
4966247	12/1989	Masuda	N/A	N/A
4969695	12/1989	Maehata et al.	N/A	N/A
5000278	12/1990	Morishita	N/A	N/A
5002028	12/1990	Arai et al.	N/A	N/A
5002148	12/1990	Miyake et al.	N/A	N/A
5015009	12/1990	Ohyama et al.	N/A	N/A
5018408	12/1990	Bota et al.	N/A	N/A
5024460	12/1990	Hanson et al.	N/A	N/A
5029328	12/1990	Kamimura et al.	N/A	N/A
5033328	12/1990	Shimanaka	N/A	N/A
5036939	12/1990	Johnson et al.	N/A	N/A
5037128	12/1990	Okuyama et al.	N/A	N/A
5040114	12/1990	Ishikawa et al.	N/A	N/A
5054813	12/1990	Kakizaki	N/A	N/A
5060744	12/1990	Katoh et al.	N/A	N/A
5062657	12/1990	Majeed	N/A	N/A
5071157	12/1990	Majeed	N/A	N/A
5071158	12/1990	Yonekawa et al.	N/A	N/A
5076385	12/1990	Terazawa et al.	N/A	N/A
5078109	12/1991	Yoshida et al.	N/A	N/A
5080392	12/1991	Bazergui	N/A	N/A
5083811	12/1991	Sato et al.	N/A	N/A
5088464	12/1991	Meaney	N/A	N/A

5090728	12/1991	Yokoya et al.	N/A	N/A
5092298	12/1991	Suzuki et al.	N/A	N/A
5092624	12/1991	Fukuyama et al.	N/A	N/A
5096219	12/1991	Hanson et al.	N/A	N/A
5105923	12/1991	Iizuka	N/A	N/A
5113345	12/1991	Mine et al.	N/A	N/A
5113821	12/1991	Fukui et al.	N/A	N/A
5114177	12/1991	Fukunaga et al.	N/A	N/A
5129475	12/1991	Kawano et al.	N/A	N/A
5134566	12/1991	Yokoya et al.	N/A	N/A
5144559	12/1991	Kamimura et al.	N/A	N/A
5150635	12/1991	Minowa et al.	N/A	N/A
5161822	12/1991	Lund	N/A	N/A
5163538	12/1991	Derr et al.	N/A	N/A
5170343	12/1991	Matsuda	N/A	N/A
5174263	12/1991	Meaney	N/A	N/A
5189615	12/1992	Rubel et al.	N/A	N/A
5218540	12/1992	Ishikawa et al.	N/A	N/A
5233530	12/1992	Shimada et al.	N/A	N/A
5253728	12/1992	Matsuno et al.	N/A	N/A
5265693	12/1992	Rees et al.	N/A	N/A
5307777	12/1993	Sasajima et al.	N/A	N/A
5314362	12/1993	Nagahora	N/A	N/A
5315295	12/1993	Fujii	N/A	N/A
5337239	12/1993	Okuda	N/A	N/A
5342023	12/1993	Kuriki et al.	N/A	N/A
5343396	12/1993	Youngblood	N/A	N/A
5343780	12/1993	McDaniel et al.	N/A	N/A
5350187	12/1993	Shinozaki	N/A	N/A
5361209	12/1993	Tsutsumi	N/A	N/A
5361213	12/1993	Fujieda et al.	N/A	N/A
5362094	12/1993	Jensen	N/A	N/A
5366236	12/1993	Kuriki et al.	N/A	N/A
5375872	12/1993	Ohtagaki et al.	N/A	N/A
5377107	12/1993	Shimizu et al.	N/A	N/A
5383680	12/1994	Bock et al.	N/A	N/A
5384705	12/1994	Inagaki et al.	N/A	N/A
5390121	12/1994	Wolfe	N/A	N/A
5391127	12/1994	Nishimura	N/A	N/A
RE34906	12/1994	Tamaki et al.	N/A	N/A
5406920	12/1994	Murata et al.	N/A	N/A
5413540	12/1994	Streib et al.	N/A	N/A
5443558	12/1994	Ibaraki et al.	N/A	N/A
5444621	12/1994	Matsunaga et al.	N/A	N/A
5446663	12/1994	Sasaki et al.	N/A	N/A
5467751	12/1994	Kumagai	N/A	N/A
5475593	12/1994	Townend	N/A	N/A
5475596	12/1994	Henry et al.	N/A	N/A
5483448	12/1995	Liubakka et al.	N/A	N/A
5485161	12/1995	Vaughn	N/A	N/A
5487006	12/1995	Kakizaki et al.	N/A	N/A
5490487	12/1995	Kato et al.	N/A	N/A
5510985	12/1995	Yamaoka et al.	N/A	N/A

5514049	12/1995	Kamio et al.	N/A	N/A
5515273	12/1995	Sasaki et al.	N/A	N/A
5521825	12/1995	Unuvar et al.	N/A	N/A
5524724	12/1995	Nishigaki et al.	N/A	N/A
5550739	12/1995	Hoffmann et al.	N/A	N/A
5555499	12/1995	Yamashita et al.	N/A	N/A
5575737	12/1995	Weiss	N/A	N/A
5586032	12/1995	Kallenbach et al.	N/A	N/A
5611309	12/1996	Kumagai et al.	N/A	N/A
5630623	12/1996	Ganzel	N/A	N/A
5632503	12/1996	Raad et al.	N/A	N/A
5645033	12/1996	Person et al.	N/A	N/A
5678847	12/1996	Izawa et al.	N/A	N/A
5713428	12/1997	Linden et al.	N/A	N/A
5749596	12/1997	Jensen et al.	N/A	N/A
5774820	12/1997	Linden et al.	N/A	N/A
5832398	12/1997	Sasaki et al.	N/A	N/A
5845726	12/1997	Kikkawa et al.	N/A	N/A
5873802	12/1998	Tabata et al.	N/A	N/A
5880532	12/1998	Stopher	N/A	N/A
5890870	12/1998	Berger et al.	N/A	N/A
5897287	12/1998	Berger et al.	N/A	N/A
5921889	12/1998	Nozaki et al.	N/A	N/A
5922038	12/1998	Horiuchi et al.	N/A	N/A
5938556	12/1998	Lowell	N/A	N/A
5957992	12/1998	Kiyono	N/A	N/A
5992558	12/1998	Noro et al.	N/A	N/A
6000702	12/1998	Streiter	N/A	N/A
6002975	12/1998	Schiffmann et al.	N/A	N/A
6016795	12/1999	Ohki	N/A	N/A
6019085	12/1999	Sato et al.	N/A	N/A
6032752	12/1999	Karpik et al.	N/A	N/A
6038500	12/1999	Weiss	N/A	N/A
6070681	12/1999	Catanzarite et al.	N/A	N/A
6073072	12/1999	Ishii et al.	N/A	N/A
6073074	12/1999	Saito et al.	N/A	N/A
6076027	12/1999	Raad et al.	N/A	N/A
6078252	12/1999	Kulczycki et al.	N/A	N/A
6086510	12/1999	Kadota	N/A	N/A
6094614	12/1999	Hiwatashi	N/A	N/A
6112866	12/1999	Boichot et al.	N/A	N/A
6120399	12/1999	Okeson et al.	N/A	N/A
6122568	12/1999	Madau et al.	N/A	N/A
6124826	12/1999	Garthwaite et al.	N/A	N/A
6125326	12/1999	Ohmura et al.	N/A	N/A
6125782	12/1999	Takashima et al.	N/A	N/A
6134499	12/1999	Goode et al.	N/A	N/A
6138069	12/1999	Ellertson et al.	N/A	N/A
6148252	12/1999	Iwasaki et al.	N/A	N/A
6154703	12/1999	Nakai et al.	N/A	N/A
6155545	12/1999	Noro et al.	N/A	N/A
6157297	12/1999	Nakai	N/A	N/A
6157890	12/1999	Nakai et al.	N/A	N/A

6161908	12/1999	Takayama et al.	N/A	N/A
6167341	12/1999	Gourmelen et al.	N/A	N/A
6170923	12/2000	Iguchi et al.	N/A	N/A
6176796	12/2000	Lislegard	N/A	N/A
6178371	12/2000	Light et al.	N/A	N/A
6181997	12/2000	Badenoch et al.	N/A	N/A
6192305	12/2000	Schiffmann	N/A	N/A
6206124	12/2000	Mallette et al.	N/A	N/A
6217480	12/2000	Iwata et al.	N/A	N/A
6226389	12/2000	Lemelson et al.	N/A	N/A
6240365	12/2000	Bunn	N/A	N/A
6244398	12/2000	Girvin et al.	N/A	N/A
6244986	12/2000	Mori et al.	N/A	N/A
6249728	12/2000	Streiter	N/A	N/A
6249744	12/2000	Morita	N/A	N/A
6254108	12/2000	Germain et al.	N/A	N/A
6260650	12/2000	Gustavsson	N/A	N/A
6263858	12/2000	Pursifull et al.	N/A	N/A
6275763	12/2000	Lotito et al.	N/A	N/A
6276333	12/2000	Kazama et al.	N/A	N/A
6288534	12/2000	Starkweather et al.	N/A	N/A
6290034	12/2000	Ichimaru	N/A	N/A
6318337	12/2000	Pursifull	N/A	N/A
6318490	12/2000	Laning	N/A	N/A
6343248	12/2001	Rizzotto et al.	N/A	N/A
6351704	12/2001	Koerner	N/A	N/A
6352142	12/2001	Kim	N/A	N/A
6370458	12/2001	Shal et al.	N/A	N/A
6370472	12/2001	Fosseen	N/A	N/A
6371884	12/2001	Channing	N/A	N/A
6379114	12/2001	Schott et al.	N/A	N/A
6427115	12/2001	Sekiyama	N/A	N/A
6456908	12/2001	Kumar	N/A	N/A
6463385	12/2001	Fry	N/A	N/A
6470852	12/2001	Kanno	N/A	N/A
6476714	12/2001	Mizuta	N/A	N/A
6483201	12/2001	Klarer	N/A	N/A
6483467	12/2001	Kushida et al.	N/A	N/A
6485340	12/2001	Kolb et al.	N/A	N/A
6488609	12/2001	Morimoto et al.	N/A	N/A
6502025	12/2001	Kempen	N/A	N/A
6507778	12/2002	Koh	N/A	N/A
6513611	12/2002	Ito et al.	N/A	N/A
6526342	12/2002	Burdock et al.	N/A	N/A
6551153	12/2002	Hattori	N/A	N/A
6573827	12/2002	McKenzie	N/A	N/A
6581710	12/2002	Sprinkle et al.	N/A	N/A
6604034	12/2002	Speck et al.	N/A	N/A
6644318	12/2002	Adams et al.	N/A	N/A
6647328	12/2002	Walker	N/A	N/A
6655233	12/2002	Evans et al.	N/A	N/A
6657539	12/2002	Yamamoto et al.	N/A	N/A
6675577	12/2003	Evans	N/A	N/A

6684140	12/2003	Lu	N/A	N/A
6685174	12/2003	Behmenburg et al.	N/A	N/A
6699085	12/2003	Hattori	N/A	N/A
6704643	12/2003	Suhre et al.	N/A	N/A
6738705	12/2003	Kojima et al.	N/A	N/A
6738708	12/2003	Suzuki et al.	N/A	N/A
6752401	12/2003	Burdock	N/A	N/A
6757606	12/2003	Gonring	N/A	N/A
6761145	12/2003	Matsuda et al.	N/A	N/A
6772061	12/2003	Berthiaume et al.	N/A	N/A
6795764	12/2003	Schmitz et al.	N/A	N/A
6820712	12/2003	Nakamura	N/A	N/A
6834736	12/2003	Kramer et al.	N/A	N/A
6839630	12/2004	Sakamoto	N/A	N/A
6845314	12/2004	Fosseen	N/A	N/A
6845829	12/2004	Hafendorfer	N/A	N/A
6848420	12/2004	Ishiguro et al.	N/A	N/A
6848956	12/2004	Ozawa	N/A	N/A
6851495	12/2004	Sprinkle et al.	N/A	N/A
6851679	12/2004	Downey et al.	N/A	N/A
6860826	12/2004	Johnson	N/A	N/A
6874467	12/2004	Hunt et al.	N/A	N/A
6876924	12/2004	Morita et al.	N/A	N/A
6880532	12/2004	Kerns et al.	N/A	N/A
6886529	12/2004	Suzuki et al.	N/A	N/A
6887182	12/2004	Nakatani et al.	N/A	N/A
6889654	12/2004	Ito	N/A	N/A
6895318	12/2004	Barton et al.	N/A	N/A
6895518	12/2004	Wingen	N/A	N/A
6897629	12/2004	Wilton et al.	N/A	N/A
6938508	12/2004	Saagge	N/A	N/A
6941209	12/2004	Liu	N/A	N/A
6942050	12/2004	Honkala et al.	N/A	N/A
6945541	12/2004	Brown	N/A	N/A
6964259	12/2004	Raetzman	N/A	N/A
6964260	12/2004	Samoto et al.	N/A	N/A
6976689	12/2004	Hibbert	N/A	N/A
6990401	12/2005	Neiss et al.	N/A	N/A
7005976	12/2005	Hagenbuch	N/A	N/A
7011174	12/2005	James	N/A	N/A
7032895	12/2005	Folchert	N/A	N/A
7035836	12/2005	Caponetto et al.	N/A	N/A
7036485	12/2005	Koerner	N/A	N/A
7044260	12/2005	Schaedler et al.	N/A	N/A
7055454	12/2005	Whiting et al.	N/A	N/A
7055497	12/2005	Maehara et al.	N/A	N/A
7055545	12/2005	Mascari et al.	N/A	N/A
7058490	12/2005	Kim	N/A	N/A
7058506	12/2005	Kawase et al.	N/A	N/A
7066142	12/2005	Hanasato	N/A	N/A
7070012	12/2005	Fecteau	N/A	N/A
7076351	12/2005	Hamilton et al.	N/A	N/A
7077713	12/2005	Watabe et al.	N/A	N/A

7077784	12/2005	Banta et al.	N/A	N/A
7086379	12/2005	Blomenberg et al.	N/A	N/A
7092808	12/2005	Lu et al.	N/A	N/A
7096851	12/2005	Matsuda et al.	N/A	N/A
7097166	12/2005	Folchert	N/A	N/A
7104352	12/2005	Weinzierl	N/A	N/A
7123189	12/2005	Lalik et al.	N/A	N/A
7124865	12/2005	Turner et al.	N/A	N/A
7136729	12/2005	Salman et al.	N/A	N/A
7140619	12/2005	Hrovat et al.	N/A	N/A
7163000	12/2006	Ishida et al.	N/A	N/A
7168709	12/2006	Niwa et al.	N/A	N/A
7171945	12/2006	Matsuda et al.	N/A	N/A
7171947	12/2006	Fukushima et al.	N/A	N/A
7182063	12/2006	Keefover et al.	N/A	N/A
7184873	12/2006	Idsinga et al.	N/A	N/A
7185630	12/2006	Takahashi et al.	N/A	N/A
7220153	12/2006	Okuyama	N/A	N/A
7233846	12/2006	Kawauchi et al.	N/A	N/A
7234707	12/2006	Green et al.	N/A	N/A
7235963	12/2006	Wayama	N/A	N/A
7249986	12/2006	Otobe et al.	N/A	N/A
7259357	12/2006	Walker	N/A	N/A
7260319	12/2006	Watanabe et al.	N/A	N/A
7260471	12/2006	Matsuda et al.	N/A	N/A
7270335	12/2006	Hio et al.	N/A	N/A
7280904	12/2006	Kaji	N/A	N/A
7286919	12/2006	Nordgren et al.	N/A	N/A
7287511	12/2006	Matsuda	N/A	N/A
7287760	12/2006	Quick et al.	N/A	N/A
7305295	12/2006	Bauerle et al.	N/A	N/A
7311082	12/2006	Yokoi	N/A	N/A
7315779	12/2007	Rioux et al.	N/A	N/A
7316288	12/2007	Bennett et al.	N/A	N/A
7318410	12/2007	Yokoi	N/A	N/A
7318593	12/2007	Sterly et al.	N/A	N/A
7322435	12/2007	Lillbacka et al.	N/A	N/A
7325533	12/2007	Matsuda	N/A	N/A
7331326	12/2007	Arai et al.	N/A	N/A
7354321	12/2007	Takada et al.	N/A	N/A
7359787	12/2007	Ono et al.	N/A	N/A
7367247	12/2007	Horiuchi et al.	N/A	N/A
7367316	12/2007	Russell et al.	N/A	N/A
7367854	12/2007	Arvidsson	N/A	N/A
7380538	12/2007	Gagnon et al.	N/A	N/A
7386378	12/2007	Lauwerys et al.	N/A	N/A
7399210	12/2007	Yoshimasa	N/A	N/A
7401794	12/2007	Laurent et al.	N/A	N/A
7413196	12/2007	Borowski	N/A	N/A
7416458	12/2007	Suemori et al.	N/A	N/A
7421954	12/2007	Bose	N/A	N/A
7422495	12/2007	Kinoshita et al.	N/A	N/A
7427072	12/2007	Brown	N/A	N/A

7431013	12/2007	Hotta et al.	N/A	N/A
7433774	12/2007	Sen et al.	N/A	N/A
7441789	12/2007	Geiger et al.	N/A	N/A
7445071	12/2007	Yamazaki et al.	N/A	N/A
7454282	12/2007	Mizuguchi	N/A	N/A
7454284	12/2007	Fosseen	N/A	N/A
7458360	12/2007	Irihune et al.	N/A	N/A
7461630	12/2007	Maruo et al.	N/A	N/A
7475746	12/2008	Tsukada et al.	N/A	N/A
7478689	12/2008	Sugden et al.	N/A	N/A
7483775	12/2008	Karaba et al.	N/A	N/A
7486199	12/2008	Tengler et al.	N/A	N/A
7505836	12/2008	Okuyama et al.	N/A	N/A
7506633	12/2008	Cowan	N/A	N/A
7510060	12/2008	Izawa et al.	N/A	N/A
7523737	12/2008	Deguchi et al.	N/A	N/A
7526665	12/2008	Kim et al.	N/A	N/A
7529609	12/2008	Braunberger et al.	N/A	N/A
7530345	12/2008	Plante et al.	N/A	N/A
7533750	12/2008	Simmons et al.	N/A	N/A
7533890	12/2008	Chiao	N/A	N/A
7571039	12/2008	Chen et al.	N/A	N/A
7571073	12/2008	Gamberini et al.	N/A	N/A
7598849	12/2008	Gallant et al.	N/A	N/A
7600762	12/2008	Yasui et al.	N/A	N/A
7611154	12/2008	Delaney	N/A	N/A
7630807	12/2008	Yoshimura et al.	N/A	N/A
7641208	12/2009	Barron et al.	N/A	N/A
7644934	12/2009	Mizuta	N/A	N/A
7647143	12/2009	Ito et al.	N/A	N/A
7684911	12/2009	Seifert et al.	N/A	N/A
7707012	12/2009	Stephens	N/A	N/A
7711468	12/2009	Levy	N/A	N/A
7740256	12/2009	Davis	N/A	N/A
7751959	12/2009	Boon et al.	N/A	N/A
7771313	12/2009	Cullen et al.	N/A	N/A
7778741	12/2009	Rao et al.	N/A	N/A
7810818	12/2009	Bushko	N/A	N/A
7815205	12/2009	Barth et al.	N/A	N/A
7822514	12/2009	Erickson	N/A	N/A
7823106	12/2009	Baker et al.	N/A	N/A
7823891	12/2009	Bushko et al.	N/A	N/A
7826959	12/2009	Namari et al.	N/A	N/A
7862061	12/2010	Jung	N/A	N/A
7885750	12/2010	Lu	N/A	N/A
7899594	12/2010	Messih et al.	N/A	N/A
7912610	12/2010	Saito et al.	N/A	N/A
7926822	12/2010	Ohletz et al.	N/A	N/A
7940383	12/2010	Noguchi et al.	N/A	N/A
7942427	12/2010	Lloyd	N/A	N/A
7950486	12/2010	Van et al.	N/A	N/A
7959163	12/2010	Beno et al.	N/A	N/A
7962261	12/2010	Bushko et al.	N/A	N/A

7963529	12/2010	Oteman et al.	N/A	N/A
7970512	12/2010	Lu et al.	N/A	N/A
7975794	12/2010	Simmons	N/A	N/A
7984915	12/2010	Post et al.	N/A	N/A
8005596	12/2010	Lu et al.	N/A	N/A
8027775	12/2010	Takenaka et al.	N/A	N/A
8032281	12/2010	Bujak et al.	N/A	N/A
8050818	12/2010	Mizuta	N/A	N/A
8050857	12/2010	Lu et al.	N/A	N/A
8056392	12/2010	Ryan et al.	N/A	N/A
8065054	12/2010	Tarasinski et al.	N/A	N/A
8075002	12/2010	Pionke et al.	N/A	N/A
8086371	12/2010	Furuichi et al.	N/A	N/A
8087676	12/2011	McIntyre	N/A	N/A
8095268	12/2011	Parison et al.	N/A	N/A
8108104	12/2011	Hrovat et al.	N/A	N/A
8113521	12/2011	Lin et al.	N/A	N/A
8116938	12/2011	Itagaki et al.	N/A	N/A
8121757	12/2011	Song et al.	N/A	N/A
8170749	12/2011	Mizuta	N/A	N/A
8190327	12/2011	Poilbout	N/A	N/A
8195361	12/2011	Kajino et al.	N/A	N/A
8204666	12/2011	Takeuchi et al.	N/A	N/A
8209087	12/2011	Haegglund et al.	N/A	N/A
8214106	12/2011	Ghoneim et al.	N/A	N/A
8219262	12/2011	Stiller	N/A	N/A
8229642	12/2011	Post et al.	N/A	N/A
8260496	12/2011	Gagliano	N/A	N/A
8271175	12/2011	Takenaka et al.	N/A	N/A
8296010	12/2011	Hirao et al.	N/A	N/A
8308170	12/2011	Van et al.	N/A	N/A
8315764	12/2011	Chen et al.	N/A	N/A
8315769	12/2011	Braunberger et al.	N/A	N/A
8321088	12/2011	Brown et al.	N/A	N/A
8322497	12/2011	Marjoram et al.	N/A	N/A
8352143	12/2012	Lu et al.	N/A	N/A
8355840	12/2012	Ammon et al.	N/A	N/A
8359149	12/2012	Shin	N/A	N/A
8374748	12/2012	Jolly	N/A	N/A
8376373	12/2012	Conradie	N/A	N/A
8382130	12/2012	Nakamura	N/A	N/A
8396627	12/2012	Jung et al.	N/A	N/A
8417417	12/2012	Chen et al.	N/A	N/A
8424832	12/2012	Robbins et al.	N/A	N/A
8428839	12/2012	Braunberger et al.	N/A	N/A
8434774	12/2012	Leclerc et al.	N/A	N/A
8437935	12/2012	Braunberger et al.	N/A	N/A
8442720	12/2012	Lu et al.	N/A	N/A
8444161	12/2012	Leclerc et al.	N/A	N/A
8447489	12/2012	Murata et al.	N/A	N/A
8457841	12/2012	Knoll et al.	N/A	N/A
8473157	12/2012	Savaresi et al.	N/A	N/A
8517395	12/2012	Knox et al.	N/A	N/A

8532896	12/2012	Braunberger et al.	N/A	N/A
8534397	12/2012	Grajkowski et al.	N/A	N/A
8534413	12/2012	Nelson et al.	N/A	N/A
8548678	12/2012	Ummethala et al.	N/A	N/A
8550221	12/2012	Paulides et al.	N/A	N/A
8571776	12/2012	Braunberger et al.	N/A	N/A
8573605	12/2012	Di Maria	N/A	N/A
8626388	12/2013	Oikawa	N/A	N/A
8626389	12/2013	Sidlosky	N/A	N/A
8641052	12/2013	Kondo et al.	N/A	N/A
8645024	12/2013	Daniels	N/A	N/A
8651503	12/2013	Rhodig	N/A	N/A
8666596	12/2013	Arenz	N/A	N/A
8672106	12/2013	Laird et al.	N/A	N/A
8672337	12/2013	Van et al.	N/A	N/A
8676440	12/2013	Watson	N/A	N/A
8682530	12/2013	Nakamura	N/A	N/A
8682550	12/2013	Nelson et al.	N/A	N/A
8682558	12/2013	Braunberger et al.	N/A	N/A
8684887	12/2013	Krosschell	N/A	N/A
8700260	12/2013	Jolly et al.	N/A	N/A
8712599	12/2013	Westpfahl	N/A	N/A
8712639	12/2013	Lu et al.	N/A	N/A
8718872	12/2013	Hirao et al.	N/A	N/A
8725351	12/2013	Selden et al.	N/A	N/A
8725380	12/2013	Braunberger et al.	N/A	N/A
8731774	12/2013	Yang	N/A	N/A
8770594	12/2013	Tominaga et al.	N/A	N/A
8827019	12/2013	Deckard et al.	N/A	N/A
8903617	12/2013	Braunberger et al.	N/A	N/A
8954251	12/2014	Braunberger et al.	N/A	N/A
8972712	12/2014	Braunberger	N/A	N/A
8973930	12/2014	Rhodig	N/A	N/A
8994494	12/2014	Koenig et al.	N/A	N/A
8997952	12/2014	Götz et al.	N/A	N/A
9010768	12/2014	Kinsman et al.	N/A	N/A
9022156	12/2014	Bedard et al.	N/A	N/A
9027937	12/2014	Ryan et al.	N/A	N/A
9038791	12/2014	Marking	N/A	N/A
9050869	12/2014	Pelzer	N/A	N/A
9123249	12/2014	Braunberger et al.	N/A	N/A
9150070	12/2014	Luttinen et al.	N/A	N/A
9151384	12/2014	Kohler et al.	N/A	N/A
9162573	12/2014	Grajkowski et al.	N/A	N/A
9186952	12/2014	Yleva	N/A	N/A
9205717	12/2014	Brady et al.	N/A	N/A
9211924	12/2014	Safranski et al.	N/A	N/A
9327726	12/2015	Braunberger et al.	N/A	N/A
9327789	12/2015	Vezina et al.	N/A	N/A
9365251	12/2015	Safranski et al.	N/A	N/A
9371002	12/2015	Braunberger	N/A	N/A
9381810	12/2015	Nelson et al.	N/A	N/A
9381902	12/2015	Braunberger et al.	N/A	N/A

9428028	12/2015	Hawksworth et al.	N/A	N/A
9428242	12/2015	Ginther et al.	N/A	N/A
9429235	12/2015	Krosschell et al.	N/A	N/A
9527362	12/2015	Scheuerell et al.	N/A	N/A
9643538	12/2016	Braunberger et al.	N/A	N/A
9643616	12/2016	Lu	N/A	N/A
9662954	12/2016	Scheuerell et al.	N/A	N/A
9665418	12/2016	Arnott et al.	N/A	N/A
9695899	12/2016	Smith et al.	N/A	N/A
9771084	12/2016	Norstad	N/A	N/A
9802621	12/2016	Gillingham et al.	N/A	N/A
9809195	12/2016	Giese et al.	N/A	N/A
9830821	12/2016	Braunberger et al.	N/A	N/A
9834184	12/2016	Braunberger	N/A	N/A
9834215	12/2016	Braunberger et al.	N/A	N/A
9855986	12/2017	Braunberger et al.	N/A	N/A
9868385	12/2017	Braunberger	N/A	N/A
9878693	12/2017	Braunberger	N/A	N/A
9920810	12/2017	Smeljanskij et al.	N/A	N/A
9937762	12/2017	Sunahiro	N/A	N/A
9945298	12/2017	Braunberger et al.	N/A	N/A
10005335	12/2017	Brady et al.	N/A	N/A
10046694	12/2017	Braunberger et al.	N/A	N/A
10086698	12/2017	Grajkowski et al.	N/A	N/A
10137873	12/2017	Bowers et al.	N/A	N/A
10154377	12/2017	Post et al.	N/A	N/A
10189428	12/2018	Sellars et al.	N/A	N/A
10195989	12/2018	Braunberger et al.	N/A	N/A
10202159	12/2018	Braunberger et al.	N/A	N/A
10207554	12/2018	Schroeder et al.	N/A	N/A
10220765	12/2018	Braunberger	N/A	N/A
10227041	12/2018	Braunberger et al.	N/A	N/A
10266164	12/2018	Braunberger	N/A	N/A
10363941	12/2018	Norstad	N/A	N/A
10384682	12/2018	Braunberger et al.	N/A	N/A
10391989	12/2018	Braunberger	N/A	N/A
10406884	12/2018	Oakden-Graus et al.	N/A	N/A
10410520	12/2018	Braunberger et al.	N/A	N/A
10436125	12/2018	Braunberger et al.	N/A	N/A
10479408	12/2018	Upah et al.	N/A	N/A
10578184	12/2019	Gilbert et al.	N/A	N/A
10704640	12/2019	Galasso et al.	N/A	N/A
10723408	12/2019	Pelot	N/A	N/A
10731724	12/2019	Laird et al.	N/A	N/A
10774896	12/2019	Hamers et al.	N/A	N/A
10933710	12/2020	Tong	N/A	N/A
10975780	12/2020	Wishin et al.	N/A	N/A
10981429	12/2020	Tsiaras et al.	N/A	N/A
10987987	12/2020	Graus et al.	N/A	N/A
11001120	12/2020	Cox	N/A	N/A
11110913	12/2020	Krosschell et al.	N/A	N/A
11124036	12/2020	Brady et al.	N/A	N/A
11142033	12/2020	Yoshida et al.	N/A	N/A

11148748	12/2020	Galasso	N/A	N/A
11152555	12/2020	Hiller	N/A	N/A
11162555	12/2020	Haugen	N/A	N/A
11192414	12/2020	Berardi	N/A	N/A
11192424	12/2020	Tabata et al.	N/A	N/A
11235634	12/2021	Lavallee et al.	N/A	N/A
11279198	12/2021	Marking	N/A	N/A
11285964	12/2021	Norstad et al.	N/A	N/A
11306798	12/2021	Cox et al.	N/A	N/A
11351834	12/2021	Cox	N/A	N/A
11364762	12/2021	Hadi	N/A	N/A
11400784	12/2021	Brady et al.	N/A	N/A
11400785	12/2021	Brady et al.	N/A	N/A
11400786	12/2021	Brady et al.	N/A	N/A
11400787	12/2021	Brady et al.	N/A	N/A
11413924	12/2021	Cox et al.	N/A	N/A
11448283	12/2021	Strickland	N/A	N/A
11472252	12/2021	Tong	N/A	N/A
11479075	12/2021	Graus et al.	N/A	N/A
11884117	12/2023	Graus et al.	N/A	N/A
11975584	12/2023	Graus et al.	N/A	N/A
2001/0005803	12/2000	Cochofel et al.	N/A	N/A
2001/0021887	12/2000	Obradovich et al.	N/A	N/A
2001/0035166	12/2000	Kerns et al.	N/A	N/A
2001/0052756	12/2000	Noro et al.	N/A	N/A
2002/0045977	12/2001	Uchiyama et al.	N/A	N/A
2002/0082752	12/2001	Obradovich	N/A	N/A
2002/0113185	12/2001	Ziegler	N/A	N/A
2002/0113393	12/2001	Urbach	N/A	N/A
2002/0115357	12/2001	Hiki et al.	N/A	N/A
2002/0125675	12/2001	Clements et al.	N/A	N/A
2002/0177949	12/2001	Katayama et al.	N/A	N/A
2002/0193935	12/2001	Hashimoto et al.	N/A	N/A
2003/0014174	12/2002	Giers	N/A	N/A
2003/0036360	12/2002	Russell et al.	N/A	N/A
2003/0036823	12/2002	Mahvi	N/A	N/A
2003/0038411	12/2002	Sendrea	N/A	N/A
2003/0046000	12/2002	Morita et al.	N/A	N/A
2003/0047994	12/2002	Koh	N/A	N/A
2003/0054831	12/2002	Bardmesser	N/A	N/A
2003/0062025	12/2002	Samoto et al.	N/A	N/A
2003/0075882	12/2002	Delorenzis	280/5.508	B60G 17/056
2003/0125857	12/2002	Madau et al.	N/A	N/A
2003/0187555	12/2002	Lutz et al.	N/A	N/A
2003/0200016	12/2002	Spillane et al.	N/A	N/A
2003/0205867	12/2002	Coelingh et al.	N/A	N/A
2004/0010383	12/2003	Lu et al.	N/A	N/A
2004/0015275	12/2003	Herzog et al.	N/A	N/A
2004/0024515	12/2003	Troupe et al.	N/A	N/A
2004/0026880	12/2003	Bundy	N/A	N/A
2004/0034460	12/2003	Folkerts et al.	N/A	N/A
2004/0041358	12/2003	Hrovat et al.	N/A	N/A
2004/0090020	12/2003	Braswell	N/A	N/A

2004/0094912	12/2003	Niwa et al.	N/A	N/A
2004/0107591	12/2003	Cuddy	N/A	N/A
2004/0216550	12/2003	Fallak et al.	N/A	N/A
2004/0226538	12/2003	Cannone et al.	N/A	N/A
2004/0245034	12/2003	Miyamoto et al.	N/A	N/A
2005/0004736	12/2004	Belcher et al.	N/A	N/A
2005/0023789	12/2004	Suzuki et al.	N/A	N/A
2005/0027428	12/2004	Gloria et al.	N/A	N/A
2005/0045148	12/2004	Katsuragawa et al.	N/A	N/A
2005/0077696	12/2004	Ogawa	N/A	N/A
2005/0098964	12/2004	Brown	N/A	N/A
2005/0131604	12/2004	Lu	N/A	N/A
2005/0133006	12/2004	Frenz et al.	N/A	N/A
2005/0149246	12/2004	McLeod	N/A	N/A
2005/0155571	12/2004	Hanasato	N/A	N/A
2005/0178628	12/2004	Uchino et al.	N/A	N/A
2005/0217953	12/2004	Bossard	N/A	N/A
2005/0267663	12/2004	Naono et al.	N/A	N/A
2005/0279244	12/2004	Bose	N/A	N/A
2005/0280219	12/2004	Brown	N/A	N/A
2005/0284446	12/2004	Okuyama	N/A	N/A
2006/0014606	12/2005	Sporl et al.	N/A	N/A
2006/0017240	12/2005	Laurent et al.	N/A	N/A
2006/0018636	12/2005	Watanabe et al.	N/A	N/A
2006/0052909	12/2005	Cherouny	N/A	N/A
2006/0064223	12/2005	Voss	N/A	N/A
2006/0065239	12/2005	Tsukada et al.	N/A	N/A
2006/0112930	12/2005	Matsuda et al.	N/A	N/A
2006/0162681	12/2005	Kawasaki	N/A	N/A
2006/0191739	12/2005	Koga	N/A	N/A
2006/0224294	12/2005	Kawazoe et al.	N/A	N/A
2006/0226611	12/2005	Xiao et al.	N/A	N/A
2006/0229811	12/2005	Herman et al.	N/A	N/A
2006/0235602	12/2005	Ishida et al.	N/A	N/A
2006/0243246	12/2005	Yokoi	N/A	N/A
2006/0243247	12/2005	Yokoi	N/A	N/A
2006/0247840	12/2005	Matsuda et al.	N/A	N/A
2006/0270520	12/2005	Owens	N/A	N/A
2006/0278197	12/2005	Takamatsu et al.	N/A	N/A
2006/0284387	12/2005	Klees	N/A	N/A
2007/0007742	12/2006	Allen et al.	N/A	N/A
2007/0023566	12/2006	Howard	N/A	N/A
2007/0028888	12/2006	Jasem	N/A	N/A
2007/0039770	12/2006	Barrette et al.	N/A	N/A
2007/0045028	12/2006	Yamamoto et al.	N/A	N/A
2007/0050095	12/2006	Nelson et al.	N/A	N/A
2007/0050125	12/2006	Matsuda et al.	N/A	N/A
2007/0068490	12/2006	Matsuda	N/A	N/A
2007/0073461	12/2006	Fielder	N/A	N/A
2007/0096672	12/2006	Endo et al.	N/A	N/A
2007/0118268	12/2006	Inoue et al.	N/A	N/A
2007/0119419	12/2006	Matsuda	N/A	N/A
2007/0120332	12/2006	Bushko et al.	N/A	N/A

2007/0124051	12/2006	Fujita	701/70	B60G 17/0162
2007/0126628	12/2006	Lalik et al.	N/A	N/A
2007/0142167	12/2006	Kanafani et al.	N/A	N/A
2007/0151544	12/2006	Arai et al.	N/A	N/A
2007/0158920	12/2006	Delaney	N/A	N/A
2007/0168125	12/2006	Petrik	N/A	N/A
2007/0169744	12/2006	Maruo et al.	N/A	N/A
2007/0178779	12/2006	Takada et al.	N/A	N/A
2007/0192001	12/2006	Tatsumi et al.	N/A	N/A
2007/0213920	12/2006	Igarashi et al.	N/A	N/A
2007/0227796	12/2006	Simmons et al.	N/A	N/A
2007/0239331	12/2006	Kaplan	N/A	N/A
2007/0240917	12/2006	Duceppe	N/A	N/A
2007/0244619	12/2006	Peterson	N/A	N/A
2007/0246010	12/2006	Okuyama et al.	N/A	N/A
2007/0247291	12/2006	Masuda et al.	N/A	N/A
2007/0255462	12/2006	Masuda et al.	N/A	N/A
2007/0255466	12/2006	Chiao	N/A	N/A
2007/0260372	12/2006	Langer	N/A	N/A
2007/0271026	12/2006	Hijikata	N/A	N/A
2007/0294008	12/2006	Yasui et al.	N/A	N/A
2008/0004773	12/2007	Maeda	N/A	N/A
2008/0015767	12/2007	Masuda et al.	N/A	N/A
2008/0022969	12/2007	Frenz et al.	N/A	N/A
2008/0059034	12/2007	Lu	N/A	N/A
2008/0078355	12/2007	Maehara et al.	N/A	N/A
2008/0091309	12/2007	Walker	N/A	N/A
2008/0114521	12/2007	Doering	N/A	N/A
2008/0115761	12/2007	Deguchi et al.	N/A	N/A
2008/0119984	12/2007	Hrovat et al.	N/A	N/A
2008/0172155	12/2007	Takamatsu et al.	N/A	N/A
2008/0178838	12/2007	Ota	N/A	N/A
2008/0178839	12/2007	Oshima et al.	N/A	N/A
2008/0178840	12/2007	Oshima et al.	N/A	N/A
2008/0183353	12/2007	Post et al.	N/A	N/A
2008/0243334	12/2007	Bujak et al.	N/A	N/A
2008/0243336	12/2007	Fitzgibbons	N/A	N/A
2008/0269989	12/2007	Brenner et al.	N/A	N/A
2008/0275606	12/2007	Tarasinski et al.	N/A	N/A
2008/0287256	12/2007	Unno	N/A	N/A
2008/0300768	12/2007	Hijikata	N/A	N/A
2009/0008890	12/2008	Woodford	N/A	N/A
2009/0020966	12/2008	Germain	N/A	N/A
2009/0037051	12/2008	Shimizu et al.	N/A	N/A
2009/0071437	12/2008	Samoto et al.	N/A	N/A
2009/0076699	12/2008	Osaki et al.	N/A	N/A
2009/0093928	12/2008	Getman et al.	N/A	N/A
2009/0095252	12/2008	Yamada	N/A	N/A
2009/0095254	12/2008	Yamada	N/A	N/A
2009/0096598	12/2008	Tengler et al.	N/A	N/A
2009/0108546	12/2008	Ohletz et al.	N/A	N/A
2009/0132154	12/2008	Fuwa et al.	N/A	N/A
2009/0171546	12/2008	Tozuka et al.	N/A	N/A

2009/0173562	12/2008	Namari et al.	N/A	N/A
2009/0229568	12/2008	Nakagawa	N/A	N/A
2009/0234534	12/2008	Stempnik et al.	N/A	N/A
2009/0240427	12/2008	Siereveld et al.	N/A	N/A
2009/0243339	12/2008	Orr et al.	N/A	N/A
2009/0254249	12/2008	Ghoneim et al.	N/A	N/A
2009/0254259	12/2008	The	N/A	N/A
2009/0261542	12/2008	McIntyre	N/A	N/A
2009/0287392	12/2008	Thomas	N/A	N/A
2009/0301830	12/2008	Kinsman et al.	N/A	N/A
2009/0308682	12/2008	Ripley et al.	N/A	N/A
2009/0312147	12/2008	Oshima et al.	N/A	N/A
2009/0321167	12/2008	Simmons	N/A	N/A
2010/0012399	12/2009	Hansen	N/A	N/A
2010/0016120	12/2009	Dickinson et al.	N/A	N/A
2010/0017059	12/2009	Lu et al.	N/A	N/A
2010/0017070	12/2009	Doering et al.	N/A	N/A
2010/0023236	12/2009	Morgan et al.	N/A	N/A
2010/0057297	12/2009	Itagaki et al.	N/A	N/A
2010/0059964	12/2009	Morris	N/A	N/A
2010/0109277	12/2009	Furrer	N/A	N/A
2010/0113214	12/2009	Krueger et al.	N/A	N/A
2010/0121529	12/2009	Savaresi et al.	N/A	N/A
2010/0131131	12/2009	Kamio et al.	N/A	N/A
2010/0138142	12/2009	Pease	N/A	N/A
2010/0140009	12/2009	Kamen et al.	N/A	N/A
2010/0145579	12/2009	O'Brien	N/A	N/A
2010/0145581	12/2009	Hou	N/A	N/A
2010/0145595	12/2009	Bellistri et al.	N/A	N/A
2010/0152969	12/2009	Li et al.	N/A	N/A
2010/0181416	12/2009	Sakamoto et al.	N/A	N/A
2010/0191420	12/2009	Honma et al.	N/A	N/A
2010/0203933	12/2009	Eyzaguirre et al.	N/A	N/A
2010/0211261	12/2009	Sasaki et al.	N/A	N/A
2010/0219004	12/2009	Mackenzie	N/A	N/A
2010/0230876	12/2009	Inoue et al.	N/A	N/A
2010/0238129	12/2009	Nakanishi et al.	N/A	N/A
2010/0252972	12/2009	Cox et al.	N/A	N/A
2010/0253018	12/2009	Peterson	N/A	N/A
2010/0259018	12/2009	Honig et al.	N/A	N/A
2010/0276906	12/2009	Galasso et al.	N/A	N/A
2010/0282210	12/2009	Itagaki	N/A	N/A
2010/0301571	12/2009	Van et al.	N/A	N/A
2011/0022266	12/2010	Ippolito et al.	N/A	N/A
2011/0025012	12/2010	Nakamura	N/A	N/A
2011/0035089	12/2010	Hirao et al.	N/A	N/A
2011/0035105	12/2010	Jolly	N/A	N/A
2011/0036656	12/2010	Nicoson	N/A	N/A
2011/0074123	12/2010	Fought et al.	N/A	N/A
2011/0109060	12/2010	Earle et al.	N/A	N/A
2011/0121524	12/2010	Kamioka et al.	N/A	N/A
2011/0153158	12/2010	Acocella	N/A	N/A
2011/0153174	12/2010	Roberge et al.	N/A	N/A

2011/0166744	12/2010	Lu et al.	N/A	N/A
2011/0186360	12/2010	Brehob et al.	N/A	N/A
2011/0190972	12/2010	Timmons et al.	N/A	N/A
2011/0215544	12/2010	Rhodig	N/A	N/A
2011/0270509	12/2010	Whitney et al.	N/A	N/A
2011/0297462	12/2010	Grajkowski et al.	N/A	N/A
2011/0297463	12/2010	Grajkowski et al.	N/A	N/A
2011/0301824	12/2010	Nelson et al.	N/A	N/A
2011/0301825	12/2010	Grajkowski et al.	N/A	N/A
2011/0307155	12/2010	Simard	N/A	N/A
2012/0017871	12/2011	Matsuda	N/A	N/A
2012/0018263	12/2011	Marking	N/A	N/A
2012/0029770	12/2011	Hirao et al.	N/A	N/A
2012/0053790	12/2011	Oikawa	N/A	N/A
2012/0053791	12/2011	Harada	N/A	N/A
2012/0055745	12/2011	Buettner et al.	N/A	N/A
2012/0065860	12/2011	Isaji et al.	N/A	N/A
2012/0078470	12/2011	Hirao et al.	N/A	N/A
2012/0112424	12/2011	Cronquist et al.	N/A	N/A
2012/0119454	12/2011	Di Maria	N/A	N/A
2012/0136506	12/2011	Takeuchi et al.	N/A	N/A
2012/0139328	12/2011	Brown et al.	N/A	N/A
2012/0168268	12/2011	Bruno et al.	N/A	N/A
2012/0191301	12/2011	Benyo et al.	N/A	N/A
2012/0191302	12/2011	Sternecker et al.	N/A	N/A
2012/0222908	12/2011	Mangum	N/A	N/A
2012/0222927	12/2011	Marking	N/A	N/A
2012/0247852	12/2011	Fecteau et al.	N/A	N/A
2012/0247888	12/2011	Chikuma et al.	N/A	N/A
2012/0253601	12/2011	Ichida et al.	N/A	N/A
2012/0265402	12/2011	Post et al.	N/A	N/A
2012/0277953	12/2011	Savaresi et al.	N/A	N/A
2013/0009350	12/2012	Wolf-Monheim	N/A	N/A
2013/0018559	12/2012	Epple et al.	N/A	N/A
2013/0030650	12/2012	Norris et al.	N/A	N/A
2013/0041545	12/2012	Baer et al.	N/A	N/A
2013/0060423	12/2012	Jolly	N/A	N/A
2013/0060444	12/2012	Matsunaga et al.	N/A	N/A
2013/0074487	12/2012	Herold et al.	N/A	N/A
2013/0079988	12/2012	Hirao et al.	N/A	N/A
2013/0092468	12/2012	Nelson et al.	N/A	N/A
2013/0096784	12/2012	Kohler et al.	N/A	N/A
2013/0096785	12/2012	Kohler et al.	N/A	N/A
2013/0096793	12/2012	Krosschell	N/A	N/A
2013/0103259	12/2012	Eng et al.	N/A	N/A
2013/0124045	12/2012	Suzuki et al.	N/A	N/A
2013/0158799	12/2012	Kamimura	N/A	N/A
2013/0161921	12/2012	Cheng et al.	N/A	N/A
2013/0173119	12/2012	Izawa	N/A	N/A
2013/0190980	12/2012	Ramirez Ruiz	N/A	N/A
2013/0197732	12/2012	Pearlman et al.	N/A	N/A
2013/0197756	12/2012	Ramirez Ruiz	N/A	N/A
2013/0218414	12/2012	Meitinger et al.	N/A	N/A

2013/0226405	12/2012	Koumura et al.	N/A	N/A
2013/0253770	12/2012	Nishikawa et al.	N/A	N/A
2013/0261893	12/2012	Yang	N/A	N/A
2013/0270020	12/2012	Gagnon et al.	N/A	N/A
2013/0304319	12/2012	Daniels	N/A	N/A
2013/0328277	12/2012	Ryan et al.	N/A	N/A
2013/0334394	12/2012	Parison et al.	N/A	N/A
2013/0338869	12/2012	Tsumano	N/A	N/A
2013/0341143	12/2012	Brown	N/A	N/A
2013/0345933	12/2012	Norton et al.	N/A	N/A
2014/0001717	12/2013	Giovanardi et al.	N/A	N/A
2014/0005888	12/2013	Bose et al.	N/A	N/A
2014/0012467	12/2013	Knox et al.	N/A	N/A
2014/0038755	12/2013	Ijichi et al.	N/A	N/A
2014/0046539	12/2013	Wijffels et al.	N/A	N/A
2014/0058606	12/2013	Hilton	N/A	N/A
2014/0095022	12/2013	Cashman et al.	N/A	N/A
2014/0125018	12/2013	Brady	280/5.519	B60G 17/016
2014/0125027	12/2013	Rhodig	N/A	N/A
2014/0129083	12/2013	O'Connor et al.	N/A	N/A
2014/0131971	12/2013	Hou	N/A	N/A
2014/0136048	12/2013	Ummethala et al.	N/A	N/A
2014/0156143	12/2013	Evangelou et al.	N/A	N/A
2014/0167372	12/2013	Kim et al.	N/A	N/A
2014/0232082	12/2013	Oshita	280/124.161	B60G 17/0162
2014/0239602	12/2013	Blankenship et al.	N/A	N/A
2014/0316653	12/2013	Kikuchi et al.	N/A	N/A
2014/0353933	12/2013	Hawksworth et al.	N/A	N/A
2014/0353934	12/2013	Yabumoto	N/A	N/A
2014/0358373	12/2013	Kikuchi et al.	N/A	N/A
2015/0039199	12/2014	Kikuchi	N/A	N/A
2015/0046034	12/2014	Kikuchi	N/A	N/A
2015/0057885	12/2014	Brady et al.	N/A	N/A
2015/0081170	12/2014	Kikuchi	N/A	N/A
2015/0081171	12/2014	Ericksen et al.	N/A	N/A
2015/0084290	12/2014	Norton et al.	N/A	N/A
2015/0091269	12/2014	Yleva	N/A	N/A
2015/0108732	12/2014	Luttinen et al.	N/A	N/A
2015/0217778	12/2014	Fairgrieve et al.	N/A	N/A
2015/0329141	12/2014	Preijert	N/A	N/A
2015/0352920	12/2014	Lakehal-Ayat et al.	N/A	N/A
2016/0046170	12/2015	Lu	N/A	N/A
2016/0059660	12/2015	Brady et al.	N/A	N/A
2016/0082802	12/2015	Izak	N/A	N/A
2016/0107498	12/2015	Yamazaki	701/37	B60G 17/0162
2016/0121689	12/2015	Park et al.	N/A	N/A
2016/0121905	12/2015	Gillingham et al.	N/A	N/A
2016/0121924	12/2015	Norstad	N/A	N/A
2016/0153516	12/2015	Marking	N/A	N/A
2016/0200164	12/2015	Tabata	280/5.508	B60G 21/073
2016/0214455	12/2015	Reul et al.	N/A	N/A
2016/0236528	12/2015	Sunahiro	N/A	N/A
2016/0280331	12/2015	Mangum	N/A	N/A

2016/0347137	12/2015	Despres-Nadeau et al.	N/A	N/A
2016/0347142	12/2015	Seong et al.	N/A	N/A
2017/0008363	12/2016	Ericksen et al.	N/A	N/A
2017/0043778	12/2016	Kelly	N/A	N/A
2017/0087950	12/2016	Brady et al.	N/A	N/A
2017/0129298	12/2016	Lu et al.	N/A	N/A
2017/0129301	12/2016	Harvey	N/A	N/A
2017/0129390	12/2016	Akaza et al.	N/A	N/A
2017/0313152	12/2016	Kang	N/A	N/A
2017/0321729	12/2016	Melcher	N/A	N/A
2018/0001729	12/2017	Goffer et al.	N/A	N/A
2018/0009443	12/2017	Norstad	N/A	N/A
2018/0126817	12/2017	Russell et al.	N/A	N/A
2018/0141543	12/2017	Krosschell	N/A	B60G 17/0195
2018/0264902	12/2017	Schroeder et al.	N/A	N/A
2018/0265062	12/2017	Bowers et al.	N/A	N/A
2018/0297435	12/2017	Brady et al.	N/A	N/A
2018/0339566	12/2017	Ericksen et al.	N/A	N/A
2018/0354336	12/2017	Oakden-Graus	N/A	B60G 17/06
2018/0361853	12/2017	Grajkowski et al.	N/A	N/A
2019/0100071	12/2018	Tsiaras et al.	N/A	N/A
2019/0118604	12/2018	Suplin et al.	N/A	N/A
2019/0118898	12/2018	Ericksen et al.	N/A	N/A
2019/0217894	12/2018	Upah et al.	N/A	N/A
2019/0389478	12/2018	Norstad	N/A	N/A
2020/0016953	12/2019	Oakden-Graus et al.	N/A	N/A
2020/0096075	12/2019	Lindblad	N/A	N/A
2020/0156430	12/2019	Oakden-Graus et al.	N/A	N/A
2020/0223279	12/2019	McKeefery	N/A	N/A
2020/0238781	12/2019	Hadi	N/A	N/A
2020/0269648	12/2019	Halper	N/A	N/A
2020/0282786	12/2019	Lorenz et al.	N/A	N/A
2020/0377149	12/2019	Tagami	N/A	B60G 17/0162
2021/0031579	12/2020	Booth et al.	N/A	N/A
2021/0031713	12/2020	Kotrla et al.	N/A	N/A
2021/0070124	12/2020	Brady et al.	N/A	N/A
2021/0070125	12/2020	Brady et al.	N/A	N/A
2021/0070126	12/2020	Brady et al.	N/A	N/A
2021/0086578	12/2020	Brady et al.	N/A	N/A
2021/0088100	12/2020	Woelfel	N/A	N/A
2021/0102596	12/2020	Malmborg et al.	N/A	N/A
2021/0108696	12/2020	Radall	N/A	N/A
2021/0162830	12/2020	Graus et al.	N/A	N/A
2021/0162833	12/2020	Graus et al.	N/A	N/A
2021/0206263	12/2020	Grajkowski et al.	N/A	N/A
2021/0229519	12/2020	Tsiaras et al.	N/A	N/A
2021/0268860	12/2020	Randall	N/A	N/A
2021/0300140	12/2020	Ericksen et al.	N/A	N/A
2021/0300141	12/2020	De Grammont et al.	N/A	N/A
2021/0316716	12/2020	Krosschell et al.	N/A	N/A
2021/0362806	12/2020	Hedlund et al.	N/A	N/A
2021/0379957	12/2020	Tabata et al.	N/A	N/A

2021/0402837	12/2020	Azuma	N/A	N/A
2022/0009304	12/2021	Leclerc	N/A	N/A
2022/0016949	12/2021	Graus et al.	N/A	N/A
2022/0032708	12/2021	Tabata et al.	N/A	N/A
2022/0041029	12/2021	Randall et al.	N/A	N/A
2022/0056976	12/2021	Anderson	N/A	N/A
2022/0080796	12/2021	Dong et al.	N/A	N/A
2022/0088988	12/2021	Menden et al.	N/A	N/A
2022/0134830	12/2021	Voelkel et al.	N/A	N/A
2022/0227191	12/2021	Dong et al.	N/A	N/A
2022/0266844	12/2021	Norstad et al.	N/A	N/A
2022/0288990	12/2021	Smith	N/A	N/A
2022/0324282	12/2021	Brady et al.	N/A	N/A
2022/0332159	12/2021	Corsico	N/A	N/A
2022/0388362	12/2021	Graus et al.	N/A	N/A
2022/0397194	12/2021	Kohler et al.	N/A	N/A
2023/0013665	12/2022	Gagnon et al.	N/A	N/A
2023/0079941	12/2022	Graus et al.	N/A	N/A
2024/0123972	12/2023	Krosschell et al.	N/A	N/A
2024/0190448	12/2023	Norstad et al.	N/A	N/A
2024/0317009	12/2023	Brady et al.	N/A	N/A
2024/0317014	12/2023	Graus et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2012323853	12/2013	AU	N/A
2015328248	12/2016	AU	N/A
2260292	12/1999	CA	N/A
2851626	12/2012	CA	N/A
2963790	12/2015	CA	N/A
2965309	12/2015	CA	N/A
3018906	12/2018	CA	N/A
1129646	12/1995	CN	N/A
2255379	12/1996	CN	N/A
2544987	12/2002	CN	N/A
1660615	12/2004	CN	N/A
1664337	12/2004	CN	N/A
1746803	12/2005	CN	N/A
1749048	12/2005	CN	N/A
1810530	12/2005	CN	N/A
101088829	12/2006	CN	N/A
101417596	12/2008	CN	N/A
101522444	12/2008	CN	N/A
101549626	12/2008	CN	N/A
101868363	12/2009	CN	N/A
201723635	12/2010	CN	N/A
102069813	12/2010	CN	N/A
102168732	12/2010	CN	N/A
201914049	12/2010	CN	N/A
202040257	12/2010	CN	N/A
102069813	12/2011	CN	N/A
102616104	12/2011	CN	N/A
102627063	12/2011	CN	N/A
102678808	12/2011	CN	N/A

202449059	12/2011	CN	N/A
102729760	12/2011	CN	N/A
202468817	12/2011	CN	N/A
102168732	12/2011	CN	N/A
102840265	12/2011	CN	N/A
103079934	12/2012	CN	N/A
103303088	12/2012	CN	N/A
103318184	12/2012	CN	N/A
103507588	12/2013	CN	N/A
103507588	12/2013	CN	N/A
103857576	12/2013	CN	N/A
104755348	12/2014	CN	N/A
104755348	12/2014	CN	N/A
104768782	12/2014	CN	N/A
105564437	12/2015	CN	N/A
105564437	12/2015	CN	N/A
106183688	12/2015	CN	N/A
106183688	12/2015	CN	N/A
106218343	12/2015	CN	N/A
106794736	12/2016	CN	N/A
103857576	12/2016	CN	N/A
107406094	12/2016	CN	N/A
107521449	12/2016	CN	N/A
107521499	12/2016	CN	N/A
109203900	12/2018	CN	N/A
110121438	12/2018	CN	N/A
110691705	12/2019	CN	N/A
3705520	12/1987	DE	N/A
3811541	12/1987	DE	N/A
4017255	12/1989	DE	N/A
4323589	12/1993	DE	N/A
4328551	12/1993	DE	N/A
19508302	12/1995	DE	N/A
19922745	12/1999	DE	N/A
60029553	12/2006	DE	N/A
102010020544	12/2010	DE	N/A
102012101278	12/2012	DE	N/A
0361726	12/1989	EP	N/A
0398804	12/1989	EP	N/A
0403803	12/1989	EP	N/A
0403803	12/1991	EP	N/A
0398804	12/1992	EP	N/A
0544108	12/1992	EP	N/A
0546295	12/1992	EP	N/A
0405123	12/1992	EP	N/A
0473766	12/1993	EP	N/A
0691226	12/1995	EP	N/A
0546295	12/1995	EP	N/A
0544108	12/1995	EP	N/A
0745965	12/1995	EP	N/A
0829383	12/1997	EP	N/A
0829383	12/1997	EP	N/A
0691226	12/1997	EP	N/A

0953470	12/1998	EP	N/A
1005006	12/1999	EP	N/A
1022169	12/1999	EP	N/A
1022169	12/1999	EP	N/A
1172239	12/2001	EP	N/A
1219475	12/2001	EP	N/A
1238833	12/2001	EP	N/A
1238833	12/2001	EP	N/A
1258706	12/2001	EP	N/A
1355209	12/2002	EP	N/A
1449688	12/2003	EP	N/A
1481876	12/2003	EP	N/A
1164897	12/2004	EP	N/A
2123933	12/2008	EP	N/A
2216191	12/2009	EP	N/A
2268496	12/2010	EP	N/A
2397349	12/2010	EP	N/A
2517904	12/2011	EP	N/A
2517904	12/2012	EP	N/A
1449688	12/2013	EP	N/A
3150454	12/2016	EP	N/A
3204248	12/2016	EP	N/A
3461663	12/2018	EP	N/A
2935642	12/2009	FR	N/A
2233939	12/1990	GB	N/A
2234211	12/1990	GB	N/A
2259063	12/1992	GB	N/A
2262491	12/1992	GB	N/A
2329728	12/1998	GB	N/A
2377415	12/2002	GB	N/A
2377415	12/2002	GB	N/A
2412448	12/2004	GB	N/A
2441348	12/2007	GB	N/A
2445291	12/2007	GB	N/A
2552237	12/2017	GB	N/A
20130233813	12/2013	IN	N/A
01-208212	12/1988	JP	N/A
02-155815	12/1989	JP	N/A
03-137209	12/1990	JP	N/A
04-368211	12/1991	JP	N/A
05-178055	12/1992	JP	N/A
06-156036	12/1993	JP	N/A
07-117433	12/1994	JP	N/A
07-186668	12/1994	JP	N/A
08-332940	12/1995	JP	N/A
09-203640	12/1996	JP	N/A
2898949	12/1998	JP	N/A
2956221	12/1998	JP	N/A
11-321754	12/1998	JP	N/A
3087539	12/1999	JP	N/A
2001-018623	12/2000	JP	N/A
3137209	12/2000	JP	N/A
2001-121939	12/2000	JP	N/A

2001-233228	12/2000	JP	N/A
2001-278089	12/2000	JP	N/A
2002-219921	12/2001	JP	N/A
2003-328806	12/2002	JP	N/A
2008-273246	12/2007	JP	N/A
2009-035220	12/2008	JP	N/A
2009-160964	12/2008	JP	N/A
4584510	12/2009	JP	N/A
2011-126405	12/2010	JP	N/A
5149443	12/2012	JP	N/A
2013-173490	12/2012	JP	N/A
2013-189109	12/2012	JP	N/A
10-2008-0090833	12/2007	KR	N/A
M299089	12/2005	TW	N/A
M299089	12/2005	TW	N/A
92/10693	12/1991	WO	N/A
9210693	12/1991	WO	N/A
96/05975	12/1995	WO	N/A
9605975	12/1995	WO	N/A
97/27388	12/1996	WO	N/A
99/59860	12/1998	WO	N/A
9959860	12/1998	WO	N/A
00/53057	12/1999	WO	N/A
0053057	12/1999	WO	N/A
02/20318	12/2001	WO	N/A
0220318	12/2001	WO	N/A
2004/009433	12/2003	WO	N/A
2004/098941	12/2003	WO	N/A
2009/008816	12/2008	WO	N/A
2009/133000	12/2008	WO	N/A
2012/028923	12/2011	WO	N/A
2012028923	12/2011	WO	N/A
2015/004676	12/2014	WO	N/A
2015004676	12/2014	WO	N/A
2016/057555	12/2015	WO	N/A
2016057555	12/2015	WO	N/A
2016/069405	12/2015	WO	N/A
2016069405	12/2015	WO	N/A
2018/189712	12/2017	WO	N/A
2020/089837	12/2019	WO	N/A
2020089837	12/2019	WO	N/A

OTHER PUBLICATIONS

International Preliminary Report on Patentability issued by the International Bureau of WIPO, dated Dec. 10, 2019, for International Patent Application No. PCT/US2018/036383; 8 pages. cited by applicant
3Drive Compact Throttle Controller, Blitz Power USA, <http://pivotjp.com/product/thf_c/the.html>; earliest known archive via Internet Archive Wayback Machine Aug. 27, 2009;

<http://web.archive.org/web/20090827154111/http://pivotjp.com/product/thf_c/the.html>; see appended screenshot retrieved from the Internet Nov. 30, 2015; 2 pages. cited by applicant

Ackermann et al., “Robust steering control for active rollover avoidance of vehicles with elevated center of gravity”, Jul. 1998, pp. 1-6. cited by applicant

Article 34 Amendment, issued by the European Patent Office, dated Aug. 29, 2016, for related International patent application No. PCT/US2015/057132; 34 pages. cited by applicant

Bhattacharyya et al., “An Approach to Stability in Vehicles Using Suspension Relative Position Sensors And Lateral Acceleration Sensors”, Dec. 2005, 100 pages. cited by applicant

Compare: Three Selectable Terrain Management Systems, Independent Land Rover News Blog, retrieved from <https://web.archive.org/web/20120611082023/> . . . ; archive date Jun. 11, 2012; 4 pages. cited by applicant

EDFC Active Adjust Damping Force Instantly according to G-Force & Speed, TEIN, retrieved from <https://web.archive.org/web/20160515190809/> . . . ; archive date May 15, 2016; 22 pages. cited by applicant

English translation of Examination Report issued by the State Intellectual Property Office of People's Republic of China, dated Jun. 1, 2015, for Chinese Patent Application No. 201180037804.3; 13 pages. cited by applicant

European Search Report issued by the European Patent Office, dated Feb. 10, 2017, for corresponding European patent application No. 16193006; 7 pages. cited by applicant

Examination Report issued by the European Patent Office, dated Aug. 1, 2016, for European Patent Application No. 11724931.8; 5 pages. cited by applicant

Examination Report issued by the State Intellectual Property Office of People's Republic of China, dated Feb. 3, 2016, for Chinese Patent Application No. 201180037804.3; 14 pages. cited by applicant

Examination Report No. 1 issued by the Australian Government IP Australia, dated Apr. 15, 2014, for Australian Patent Application No. 2011261248; 5 pages. cited by applicant

Examination Report No. 1 issued by the Australian Government IP Australia, dated Aug. 10, 2018, for Australian Patent Application No. 2015328248; 2 pages. cited by applicant

Examination Report No. 1 issued by the Australian Government IP Australia, dated Jan. 12, 2017, for corresponding Australian patent application No. 2015271880; 6 pages. cited by applicant

Examination Report No. 2 issued by the Australian Government IP Australia, dated Jun. 29, 2017, for Australian Patent Application No. 2015271880; 8 pages. cited by applicant

Examination Report No. 2 issued by the Australian Government IP Australia, dated May 29, 2015, for Australian Patent Application No. 2011261248; 8 pages. cited by applicant

Examination Report No. 3 issued by the Australian Government IP Australia, dated Dec. 1, 2017, for Australian Patent Application No. 2015271880; 7 pages. cited by applicant

Extended European Search Report issued by the European Patent Office, dated Sep. 7, 2018, for European Patent Application No. 18183050.6; 7 pages. cited by applicant

First drive: Ferrari's easy-drive supercar, GoAuto.com.au, Feb. 16, 2010; 4 pages. cited by applicant

Gangadurai et al.; Development of control strategy for optimal control of a continuously variable transmission operating in combination with a throttle controlled engine; SAE International; Oct. 12, 2005. cited by applicant

Hac et al., “Improvements in vehicle handling through integrated control of chassis systems”, Int. J. of Vehicle Autonomous Systems(IJVAS), vol. 1, No. 1, 2002, pp. 83-110. cited by applicant

Huang et al., “Nonlinear Active Suspension Control Design Applied to a Half-Car Model”, Proceedings of the 2004 IEEE International Conference on Networking, March 21-23, 2004, pp. 719-724. cited by applicant

Ingalls, Jake; Facebook post <https://www.facebook.com/groups/877984048905836/permalink/110447996625624-2>; Sep. 11, 2016; 1 page. cited by applicant

International Preliminary Amendment issued by The International Bureau of WIPO, dated May 21, 2019, for International Patent Application No. PCT/US2017/062303; 22 pages. cited by applicant

International Preliminary Report on Patentability in PCT Application Serial No. PCT/US15/57132, issued Jan. 30, 2017 (6 pages). cited by applicant

International Preliminary Report on Patentability issued by the European Patent Office, dated Apr. 11, 2017, for International Patent Application No. PCT/US2015/054296; 7 pages. cited by applicant

International Preliminary Report on Patentability issued by The International Bureau of WIPO, Dec. 4, 2012, for International Application No. PCT/US2011/039165; 9 pages. cited by applicant

International Preliminary Report on Patentability received for PCT Patent Application No. PCT/IB2019/060089, mailed on Jun. 3, 2021, 22 pages. cited by applicant

International Preliminary Report on Patentability received for PCT Patent Application No. PCT/US2013/068937, mailed on May 21, 2015, 8 pages. cited by applicant

International Preliminary Report on Patentability received for PCT Patent Application No. PCT/US2021/033199, mailed on Dec. 1, 2022, 11 pages. cited by applicant

International Search Report and Written Opinion of the International Searching Authority for International

Application No. PCT/US2011/39165, dated Jan. 3, 2012; 15 pages. cited by applicant

International Search Report and Written Opinion of the International Searching Authority, dated Aug. 31, 2018, for International Patent Application No. PCT/US2018/036383; 12 pages. cited by applicant

International Search Report and Written Opinion received for PCT Patent Application No. PCT/IB2019/060089, mailed on May 29, 2020, 24 pages. cited by applicant

International Search Report and Written Opinion received for PCT Patent Application No. PCT/US2013/068937, mailed on Feb. 26, 2014, 10 pages. cited by applicant

International Search Report and Written Opinion received for PCT Patent Application No. PCT/US2015/054296, mailed on Dec. 18, 2015, 9 pages. cited by applicant

International Search Report and Written Opinion received for PCT Patent Application No. PCT/US2015/057132, mailed on May 13, 2016, 17 pages. cited by applicant

International Search Report and Written Opinion received for PCT Patent Application No. PCT/US2021/033199, mailed on Aug. 23, 2021, 14 pages. cited by applicant

International Search Report and Written Opinion received for PCT Patent Application No. PCT/US2021/042230, mailed on Dec. 17, 2021, 4 pages. cited by applicant

Machine translation of DE 3705520 A1 from espacenet.com November (Year: 2022). cited by applicant

McKay et al., Delphi Electronic Throttle Control Systems for Model Year 2000; Driver Features, System Security, and OEM Benefits. ETC for the Mass Market, Electronic Engine Controls 2000: Controls (SP-1500), SAE 2000 World Congress, Detroit, MI, Mar. 6-9, 2000, 13 pages. cited by applicant

Office Action issued by the Canadian Intellectual Property Office, dated Apr. 21, 2017, for corresponding Canadian patent application No. 2,801,334; 3 pages. cited by applicant

Office Action issued by the Canadian Intellectual Property Office, dated Jul. 26, 2019, for Canadian Patent Application No. 2,963,790; 3 pages. cited by applicant

Office Action issued by the Canadian Intellectual Property Office, dated Jun. 22, 2021, for Canadian Patent Application No. 3,043,481; 3 pages. cited by applicant

Office Action issued by the Canadian Intellectual Property Office, dated May 10, 2021, for Canadian Patent Application No. 2,890,996; 3 pages. cited by applicant

Office Action issued by the Canadian Intellectual Property Office, dated Oct. 1, 2019, for Canadian Patent Application No. 2,965,309; 8 pages. cited by applicant

Office Action issued by the Mexican Patent Office, dated Jun. 25, 2014, for corresponding Mexican patent application No. MX/a/2012/014069; 2 pages. cited by applicant

Scott Tsuneishi, "2005 Subaru WRX Sti—Blitz Throttle Controller," Oct. 1, 2008, Super Street Online, <<http://www.superstreetonline.com/how-to/engine/turp-0810-2005-subam-wrx-sti-blitz-throttle-controller>>; see appended screenshot retrieved from the Internet Nov. 30, 2015; 11 pages. cited by applicant

Throttle Controller, Blitz Power USA, <<http://www.blitzpowerusa.com/products/throcon/throcon.html>>; earliest known archive via Internet Archive Wayback Machine Sep. 14, 2009: <<http://web.archive.org/web/20090914102957/http://www.blitzpowerusa.com/products/throcon/throcon.html>>; see appended screenshot. cited by applicant

Trebi-Ollennu et al., Adaptive Fuzzy Throttle Control of an All Terrain Vehicle, 2001, Abstract. cited by applicant

Unno et al.; Development of Electronically Controlled DVT Focusing on Rider's Intention of Acceleration and Deceleration; SAE International; Oct. 30, 2007. cited by applicant

"International Application Serial No. PCT US20 15 054296, International Search Report mailed Dec. 18, 15", (02 26 19), 3 pgs. cited by applicant

"International Application Serial No. PCT US20 15 054296, Written Opinion mailed Dec. 18, 15", 6 pgs. cited by applicant

"International Application Serial No. PCT US20 15 054296, International Preliminary Report on Patentability mailed Apr. 20, 17", 8 pgs. cited by applicant

"U.S. Appl. No. 16/198,280, Restriction Requirement mailed Jun. 5, 2020", 7 pgs. cited by applicant

"U.S. Appl. No. 16/198,280, Response filed Jul. 28, 2020 to Restriction Requirement mailed Jun. 5, 2020", 18 pgs. cited by applicant

"U.S. Appl. No. 16/198,280, Notice of Allowance mailed Aug. 7, 2020", 11 pgs. cited by applicant

"U.S. Appl. 16/198,280, Notice of Allowance mailed Nov. 16, 2020", 11 pgs. cited by applicant

“U.S. Appl. 16/198,280, Notice of Allowance mailed Mar. 19, 2021”, 11 pgs. cited by applicant
“U.S. Appl. 17/175,888, Non Final Office Action mailed Nov. 16, 2022”, 18 pgs. cited by applicant
“U.S. Appl. 17/175,888, Response filed May 16, 2023 to Non Final Office Action mailed Nov. 16, 2022”, 7 pgs. cited by applicant
“U.S. Appl. 17/175,888, Final Office Action mailed Sep. 8, 2023”, 24 pgs. cited by applicant
“U.S. Appl. 17/175,888, Examiner Interview Summary mailed Oct. 30, 2023”, 2 pgs. cited by applicant
“U.S. Appl. 17/175,888, Response filed Oct. 31, 2023 to Final Office Action mailed Sep. 8, 2023”, 9 pgs. cited by applicant
“U.S. Appl. 17/175,888, Advisory Action mailed Nov. 6, 2023”, 3 pgs. cited by applicant
“U.S. Appl. 17/175,888, Notice of Allowance mailed Nov. 17, 2023”, 8 pgs. cited by applicant
“U.S. Appl. 17/175,888, Corrected Notice of Allowability mailed Dec. 4, 2023”, 2 pgs. cited by applicant
“Mexican Application Serial No. MX a 2021 005831, Office Action mailed Jan. 14, 2025”, With English Machine Translation, 55 pgs. cited by applicant
Jake, Ingalls, “Yamaha YXZ Addicts”, [Online]. Retrieved from the Internet: URL: <https://www.facebook.com/groups/877984048905836/permalink/1104479966256242/>, (Sep. 11, 2016), 3 pgs. cited by applicant
Vincent Bourque-Veilleux, “iACT: Arctic Cat redefines trail suspension standards”, sledmagazine.com; Feb. 27, 2018, <https://sledmagazine.com/iact-arctic-cat-redefines-trail-suspension-standards/>; 4 pages. cited by applicant

Primary Examiner: To; Toan C

Attorney, Agent or Firm: SCHWEGMAN LUNDBERG & WOESSNER, P.A.

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) The present application is a divisional of U.S. patent application Ser. No. 17/888,938, filed Aug. 16, 2022, which is a continuation of U.S. patent application Ser. No. 17/175,888, filed Feb. 15, 2021, titled “VEHICLE HAVING ADJUSTABLE COMPRESSION AND REBOUND DAMPING”, which is a divisional of U.S. patent application Ser. No. 16/198,280, filed Nov. 21, 2018, titled “VEHICLE HAVING ADJUSTABLE COMPRESSION AND REBOUND DAMPING”, the entire disclosures of which are expressly incorporated herein by reference.

FIELD OF DISCLOSURE

(1) The present disclosure relates to improved suspension characteristics for a vehicle and in particular to systems and methods of damping control, such as compression and/or rebound damping, for shock absorbers.

BACKGROUND OF THE DISCLOSURE

(2) Adjustable shock absorbers are known. Systems and methods for controlling one or more adjustable characteristics of adjustable shock absorbers are disclosed in US Published Patent Application No. 2016/0059660 (filed Nov. 6, 2015, titled VEHICLE HAVING SUSPENSION WITH CONTINUOUS DAMPING CONTROL) and US Published Application 2018/0141543 (filed Nov. 17, 2017, titled VEHICLE HAVING ADJUSTABLE SUSPENSION).

SUMMARY OF THE DISCLOSURE

(3) In an exemplary embodiment of the present disclosure, a recreational vehicle is provided. The recreational vehicle includes a plurality of ground engaging members, a frame supported by the plurality of ground engaging members, a plurality of suspensions, a plurality of adjustable shock absorbers, at least one sensor positioned on the recreational vehicle and configured to provide sensor information to a controller, and a controller operatively coupled to the sensor and the plurality of adjustable shock absorbers. Each of the suspensions couples a ground engaging member to the frame. The controller is configured to receive sensor information from the sensor, determine a cornering event related to the recreational vehicle executing a turn based on the sensor information, and provide, to at least one of the plurality of adjustable shock absorbers and based on the cornering event, one or more commands to result in a decrease of a damping characteristic of the at least one of the plurality of adjustable shock absorbers.

(4) In some instances, the controller is configured to determine, based on the sensor information, a direction of the turn corresponding to the cornering event, determine, based on the direction of the turn, at least one inner adjustable shock absorber of the plurality of adjustable shock absorbers, and provide, to the at least one inner adjustable shock absorber, one or more commands to result in a decrease of a compression damping characteristic and an increase of a rebound damping characteristic. In some examples, the at least one sensor comprises an inertial measurement unit (IMU), the sensor information comprises acceleration information indicating a lateral acceleration value, and the controller is configured to determine the cornering event by determining that the recreational vehicle is turning based on comparing the lateral acceleration value to a first threshold.

(5) In some variations, the sensor information further comprises yaw rate information indicating a yaw rate. The controller is further configured to determine the cornering event by determining that the recreational vehicle is turning based on comparing the yaw rate to a second threshold. In some instances, the at least one sensor further comprises a steering sensor and the sensor information further comprises steering information indicating a steering position or a steering rate corresponding to a steering wheel. Further, the controller is configured to determine the cornering event by determining that the recreational vehicle is turning based on comparing the steering position to a third threshold.

(6) In some variations, the sensor information comprises yaw rate information indicating a yaw rate and steering information indicating a steering position or a steering rate. The controller is further configured to prioritize the yaw rate information over the steering information such that the controller is configured to determine the vehicle is executing the turn in a first direction based on the yaw rate indicating the turn in the first direction and even if the steering position or the steering rate indicates the turn in a second direction or does not indicate the turn. In some instances, the sensor information comprises acceleration information indicating a lateral acceleration value and yaw rate information indicating a yaw rate. The controller is further configured to prioritize the acceleration information over the yaw rate information such that the controller is configured to determine the vehicle is executing the turn in a first direction based on the lateral acceleration value indicating the turn in the first direction and even if the yaw rate indicates the turn in a second direction or does not indicate the turn. In some examples, the sensor information comprises steering information indicating a steering position or a steering rate and acceleration information indicating a lateral acceleration value. The controller is further configured to prioritize the acceleration information over the steering information such that the controller is configured to determine the vehicle is executing the turn in a first direction based on the lateral acceleration value indicating the turn in the first direction and even if the steering position or the steering rate indicates the turn in a second direction or does not indicate the turn.

(7) In another exemplary embodiment of the present disclosure, a recreational vehicle is provided. The recreational vehicle includes a plurality of ground engaging members, a frame supported by the plurality of ground engaging members, a plurality of suspensions, a plurality of adjustable shock absorbers, a first sensor positioned on the recreational vehicle and configured to provide cornering information to a controller, a second sensor positioned on the recreational vehicle and configured to provide acceleration information to the controller and a controller operatively coupled to the sensor and the plurality of adjustable shock absorbers. Each of the suspensions couples a ground engaging member to the frame. The controller is configured to receive, from the first sensor, the cornering information, receive, from the second sensor, the acceleration information, determine, based on the cornering information, a cornering event corresponding to the recreational vehicle executing a turn, determine, based on the acceleration information, a position of the recreational vehicle during the turn, and provide, to the at least one of the plurality of adjustable shock absorbers and based on the cornering event and the position of the recreational vehicle during the turn, one or more commands to result in an adjustment of a damping characteristic of the at least one of the plurality of adjustable shock absorbers.

(8) In some instances, the second sensor is an accelerometer or an IMU. In some examples, the controller is configured to determine the position of the recreational vehicle during the turn by determining, based on the acceleration information indicating a longitudinal deceleration, that the vehicle is entering the turn. Also, the controller is further configured to determine, based on the cornering event, a plurality of damping characteristics for the plurality of adjustable shock absorbers, bias, based on the determining that the vehicle is entering the turn, the plurality of damping characteristics, and generate the one or more

commands based on the plurality of biased damping characteristics. In some instances, the controller is configured to bias the plurality of damping characteristics by additionally increasing the compression damping of a front adjustable shock absorber of the plurality of adjustable shock absorbers, and additionally decreasing the compression damping of a rear adjustable shock absorber of the plurality of adjustable shock absorbers. In some examples, the controller is configured to bias the plurality of damping characteristics by additionally increasing the rebound damping of a rear adjustable shock absorber of the plurality of adjustable shock absorbers and additionally decreasing the rebound damping of a front adjustable shock absorber of the plurality of adjustable shock absorbers.

(9) In some instances, the controller is configured to determine the position of the recreational vehicle during the turn by determining, based on the acceleration information indicating a longitudinal acceleration, that the vehicle is exiting the turn. Also, the controller is further configured to determine, based on the cornering event, a plurality of damping characteristics for the plurality of adjustable shock absorbers, bias, based on the determining that the vehicle is exiting the turn, the plurality of damping characteristics, and generate the one or more commands based on the plurality of biased damping characteristics. In some examples, the controller is configured to bias the plurality of damping characteristics by additionally increasing the compression damping of a rear adjustable shock absorber of the plurality of adjustable shock absorbers and additionally decreasing the compression damping of a front adjustable shock absorber of the plurality of adjustable shock absorbers. In some variations, the controller is configured to bias the plurality of damping characteristics by additionally increasing the rebound damping of a front adjustable shock absorber of the plurality of adjustable shock absorbers and additionally decreasing the rebound damping of a rear adjustable shock absorber of the plurality of adjustable shock absorbers.

(10) In another exemplary embodiment of the present disclosure, a recreational vehicle is provided. The recreational vehicle includes a plurality of ground engaging members, a frame supported by the plurality of ground engaging members, a plurality of suspensions, a plurality of adjustable shock absorbers, a sensor positioned on the recreational vehicle and configured to provide sensor information to a controller, and a controller operatively coupled to the sensor and the plurality of adjustable shock absorbers. Each of the suspensions couples a ground engaging member to the frame. The controller is configured to receive sensor information from the sensor, determine a braking event corresponding to the recreational vehicle based on the sensor information, and provide, to at least one of the plurality of adjustable shock absorbers and based on the braking event, one or more commands to decrease a damping characteristic of the at least one of the plurality of adjustable shock absorbers.

(11) In some instances, the controller is configured to provide one or more commands to decrease a rebound damping characteristic of the at least one of the plurality of adjustable shock absorbers. In some examples, the controller is configured to provide, one or more commands to decrease a compression damping characteristic of the at least one of the plurality of adjustable shock absorbers. In some variations, the sensor is a brake sensor, and the sensor information is information indicating actuation of a brake pedal. In some instances, the controller is configured to provide, to a front adjustable shock absorber of the plurality of adjustable shock absorbers, a command to increase a compression damping characteristic and to decrease a rebound damping characteristic. In some examples, the controller is configured to provide, to a rear adjustable shock absorber of the plurality of adjustable shock absorbers, a command to increase a rebound damping characteristic and to decrease a compression damping characteristic.

(12) In another exemplary embodiment of the present disclosure, a recreational vehicle is provided. The recreational vehicle includes a plurality of ground engaging members, a frame supported by the plurality of ground engaging members, a plurality of suspensions, a plurality of adjustable shock absorbers, a first sensor positioned on the recreational vehicle and configured to provide braking information to a controller, a second sensor positioned on the recreational vehicle and configured to provide acceleration information, and a controller operatively coupled to the sensor and the plurality of adjustable shock absorbers. Each of the suspensions couples a ground engaging member to the frame. The controller is configured to receive, from the first sensor, the braking information, receive, from the second sensor, the acceleration information, determine a braking event corresponding to the recreational vehicle based on the braking information, determine, based on the acceleration information, an amount to reduce a

damping characteristic of an adjustable shock absorber from the plurality of adjustable shock absorbers, and provide, to the adjustable shock absorber and based on the cornering event, one or more first commands to adjust the damping characteristics of the front adjustable shock absorber to the determined amount.

(13) In some instances, the second sensor is an accelerometer, and the acceleration information indicates a longitudinal deceleration of the recreational vehicle. In some examples, the second sensor is an inertial measurement unit (IMU), and the acceleration information indicates a longitudinal deceleration of the recreational vehicle. In some variations, the second sensor is a brake sensor, and the acceleration information indicates a longitudinal deceleration of the recreational vehicle. In some instances, the adjustable shock absorber is a shock absorber positioned at a rear portion of the recreational vehicle.

(14) In some variations, the controller is configured to determine, based on the acceleration information, a deceleration value, and in response to determining the deceleration value is below a first threshold, maintaining a compression damping of the adjustable shock absorber. In some examples, the controller is configured to determine, based on the acceleration information, a deceleration value, in response to determining the deceleration value is greater than a first threshold and below a second threshold, reducing a compression damping of the adjustable shock absorber to a first value, and in response to determining the deceleration value is greater than the first threshold and the second threshold, reducing the compression damping of the adjustable shock absorber to a second value, wherein the second value is below the first value.

(15) In another exemplary embodiment of the present disclosure, a recreational vehicle is provided. The recreational vehicle includes a plurality of ground engaging members, a frame supported by the plurality of ground engaging members, a plurality of suspensions, a plurality of adjustable shock absorbers, a sensor positioned on the recreational vehicle and configured to provide airborne information and landing information to a controller, and a controller operatively coupled to the sensor and the plurality of adjustable shock absorbers. Each of the suspensions couples a ground engaging member to the frame. The controller is configured to receive, from the sensor, the airborne information, determine, based on the airborne information, an airborne event indicating the recreational vehicle is airborne, provide, based on the airborne event, one or more first commands to result in decreasing a rebound damping characteristic for the plurality of adjustable shock absorbers from a pre-takeoff rebound value to a free-fall rebound value, receive, from the at least one sensor, landing information, determine, based on the landing information, a landing event indicating the recreational vehicle has landed subsequent to the airborne event, determine, based on the airborne event and the landing event, a time duration that the recreational vehicle is airborne, provide, based on the landing event and the time duration the recreational vehicle is airborne, one or more second commands to result in increasing the rebound damping characteristic for the plurality of adjustable shock absorbers from the free-fall rebound value to a post-landing rebound value to prevent a landing hop, and provide one or more third commands to result in decreasing the rebound damping characteristic for the plurality of adjustable shock absorbers from the post-landing rebound value to the pre-takeoff rebound value.

(16) In some instances, the sensor is an accelerometer or an IMU. In some examples, the sensor is an inertial measurement unit (IMU). In some variations, the one or more third commands cause the rebound damping characteristic for the plurality of adjustable shock absorbers to gradually decrease from the post-landing rebound value to the pre-takeoff rebound value. In some examples, the controller is further configured to increase the post-landing rebound value as the time duration that the recreational vehicle is airborne increases. In some variations, the controller is further configured to in response to determining the time duration is below a first threshold, set the post-landing rebound value to a same value as the pre-takeoff rebound value. In some instances, the controller is further configured to in response to determining the time duration is below a first threshold, bias the post-landing rebound value for a front shock absorber of the plurality of adjustable shock absorbers different from a rear shock absorber of the plurality of adjustable shock absorbers, and generate the one or more second commands based on the biasing the post-landing rebound value. In some instances, the controller is configured to bias the post-landing rebound value by additionally increasing the post-landing rebound value for the front shock absorber.

(17) In some examples, the controller is configured to provide, based on the airborne event, one or more

fourth commands to result in gradually increasing a compression damping characteristic for the plurality of adjustable shock absorbers from a pre-takeoff compression value to a post-landing compression value, provide, based on the landing event and the time duration, one or more fifth commands to result in maintaining the compression damping characteristic for the plurality of adjustable shock absorbers at the post-landing compression value, and provide one or more sixth commands to result in decreasing the compression damping characteristic for the plurality of adjustable shock absorbers from the post-landing compression value to the pre-takeoff compression value. In some instances, the controller is further configured to in response to determining the time duration is below a first threshold, set the post-landing compression value to a same value as the pre-takeoff compression value. In some examples, the controller is further configured to in response to determining the time duration is below a first threshold, bias the post-landing compression value for a front shock absorber of the plurality of adjustable shock absorbers different from a rear shock absorber of the plurality of adjustable shock absorbers, and generate the one or more fifth commands based on the biasing the post-landing compression value. In some variations, the controller is further configured to in response to determining the time duration is below a first threshold, bias the post-landing compression value for a front shock absorber of the plurality of adjustable shock absorbers different from a rear shock absorber of the plurality of adjustable shock absorbers, and generate the one or more fifth commands based on the biasing the post-landing compression value. In some examples, the free-fall rebound value is substantially zero.

(18) In another exemplary embodiment of the present disclosure, a recreational vehicle is provided. The recreational vehicle includes a plurality of ground engaging members, a frame supported by the plurality of ground engaging members, a plurality of suspensions, a plurality of adjustable shock absorbers, a sensor positioned on the recreational vehicle and configured to provide acceleration information to a controller, and a controller operatively coupled to the sensor and the plurality of adjustable shock absorbers. Each of the suspensions couples a ground engaging member to the frame. The controller is configured to receive, from the at least one sensor, the acceleration information, determine, based on the acceleration information, an orientation of the vehicle, and provide, to at least one of the plurality of adjustable shock absorbers and based on the orientation of the vehicle, one or more commands to result in an adjustment of a damping characteristic of the at least one of the plurality of adjustable shock absorbers.

(19) In some instances, the sensor is an accelerometer or an IMU. In some examples, the sensor is an IMU. In some variations, the recreational vehicle further includes an operator interface configured to provide one or more user inputs indicating mode selections to the controller. The controller is configured to provide the one or more commands to result in the adjustment of the damping characteristic based on receiving, from the operator interface, user input indicating a selection of a rock crawler mode. In some examples, the at least one sensor comprises a second sensor configured to provide vehicle speed information to the controller. The controller is further configured to receive, from the second sensor, vehicle speed information indicating a vehicle speed of the recreational vehicle, and in response to determining that the vehicle speed is greater than a threshold, transitioning the vehicle from the rock crawler mode to a different operating mode.

(20) In some variations, the controller is further configured to determine, based on the acceleration information, a longitudinal acceleration and a lateral acceleration of the recreational vehicle, determine, based on the longitudinal acceleration and the lateral acceleration, a pitch angle and a roll angle of the recreational vehicle, and the controller is configured to determine the orientation of the recreational vehicle based on the pitch angle and the roll angle. In some examples, the controller is configured to determine, based on the longitudinal acceleration and the lateral acceleration, that the orientation of the recreational vehicle is on flat ground, and provide, based on the determination that the recreational vehicle is on flat ground, one or more commands to result in an increase of a compression damping characteristic and a decrease of a rebound damping characteristic for the at least one of the plurality of adjustable shock absorbers.

(21) In some instances, the controller is configured to determine, based on the longitudinal acceleration and the lateral acceleration, at least one uphill adjustable shock absorber and at least one downhill adjustable shock absorber from the plurality of adjustable shock absorbers, and provide, to the at least one uphill adjustable shock absorber, one or more commands to result in an increase of a rebound damping characteristic and a decrease of a compression damping characteristic. In some examples, the controller is

further configured to determine, based on the longitudinal acceleration and the lateral acceleration, at least one uphill adjustable shock absorber and at least one downhill adjustable shock absorber from the plurality of adjustable shock absorbers, and provide, to the at least one downhill adjustable shock absorber, one or more commands to result in an increase of a compression damping characteristic.

(22) In another exemplary embodiment of the present disclosure, a recreational vehicle is provided. The recreational vehicle includes a plurality of ground engaging members, a frame supported by the plurality of ground engaging members, a plurality of suspensions, a plurality of adjustable shock absorbers, a sensor positioned on the recreational vehicle and configured to provide sensor information to a controller, and a controller operatively coupled to the sensor and the plurality of adjustable shock absorbers. Each of the suspensions couples a ground engaging member to the frame. The controller is configured to receive, from the at least one sensor, the sensor information, determine, based on the sensor information, a sliding event corresponding to the recreational vehicle sliding while traversing a slope, and provide, to at least one of the plurality of adjustable shock absorbers and based on the determining of the sliding event, one or more commands to result in adjusting a damping characteristic for the at least one of the plurality of adjustable shock absorbers.

(23) In some instances, the at least one sensor comprises an inertial measurement unit (IMU). Also, the sensor information comprises acceleration information indicating a lateral acceleration value. The controller is configured to determine the sliding event by determining that the recreational vehicle is sliding based on comparing the lateral acceleration value to a first threshold. In some examples, the sensor information further comprises yaw rate information indicating a yaw rate. The controller is further configured to determine the cornering based on the yaw rate. In some variations, the sensor information comprises acceleration information indicating a lateral acceleration value and yaw rate information indicating a yaw rate. The controller is further configured to prioritize the acceleration information over the yaw rate information such that the controller is configured to determine the vehicle is sliding while traversing the slope based on the lateral acceleration value exceeding a first threshold and even if the yaw rate does not exceed a second threshold.

(24) In some instances, the sensor information comprises steering information indicating a steering position or a steering rate and acceleration information indicating a lateral acceleration value. The controller is further configured to prioritizing the acceleration information over the steering information such that the controller is configured to determine the vehicle is sliding while traversing the slope based on the lateral acceleration value exceeding a first threshold and even if the steering position or the steering rate does not exceed a second threshold. In some variations, the sensor information indicates a lateral acceleration. The controller is further configured to determine, based on the lateral acceleration, a direction of a slide corresponding to the sliding event, determining, based on the direction of the slide, at least one leading adjustable shock absorber of the plurality of adjustable shock absorbers, and the controller is configured to provide the one or more commands by providing, to the at least one leading adjustable shock absorber, one or more commands to result in an increase of a compression damping characteristic and a decrease of a rebound damping characteristic.

(25) In some examples, the sensor information indicates a lateral acceleration. The controller is further configured to determine, based on the lateral acceleration, a direction of a slide corresponding to the sliding event, determining, based on the direction of the slide, at least one trailing adjustable shock absorber of the plurality of adjustable shock absorbers, and the controller is configured to provide the one or more commands by providing, to the at least one trailing adjustable shock absorber, one or more commands to result in a decrease of a compression damping characteristic and an increase of a rebound damping characteristic. In some variations, the sensor information indicates a longitudinal acceleration. The controller is further configured to determine, based on the longitudinal acceleration, an orientation of the vehicle, determine, based on the orientation of the vehicle, a plurality of damping characteristics for the plurality of adjustable shock absorbers, bias, based on the orientation of the vehicle, the plurality of damping characteristics, and generate the one or more commands based on the plurality of biased damping characteristics.

(26) In some instances, the controller is configured to bias the plurality of damping characteristics by additionally increasing a compression damping of a downhill adjustable shock absorber of the plurality of adjustable shock absorbers and additionally decreasing a compression damping of an uphill adjustable

shock absorber of the plurality of adjustable shock absorbers. In some examples, the controller is configured to bias the plurality of damping characteristics by additionally increasing the rebound damping of an uphill adjustable shock absorber of the plurality of adjustable shock absorbers.

(27) In another exemplary embodiment of the present disclosure, a method and vehicle of adjusting a plurality of adjustable shock absorbers of a recreational vehicle traveling over terrain including at least one dune is provided. For example, the method and vehicle determines an orientation of the recreational vehicle based on a longitudinal acceleration of the vehicle, determines a slide of the recreational vehicle based on a lateral acceleration of the vehicle, detects the recreational vehicle is sliding across the dune based on the orientation and the slide of the recreational vehicle, and adjusts at least one damping characteristic of the plurality of adjustable shock absorbers to turn the recreational vehicle into the dune as the recreational vehicle continues across the dune.

(28) In some instances, the method and vehicle determines, based on the slide, at least one leading adjustable shock absorber and at least one trailing adjustable shock absorber of the plurality of adjustable shock absorbers and provides, to the at least one leading adjustable shock absorber, one or more commands to result in an increase of a compression damping characteristic and a decrease in a rebound damping characteristic. In some examples, the method and vehicle determines, based on the slide, at least one leading adjustable shock absorber and at least one trailing adjustable shock absorber of the plurality of adjustable shock absorbers and provides, to the at least one trailing adjustable shock absorber, one or more commands to result in an increase of a rebound damping characteristic and a decrease of a compression damping characteristic.

(29) In some variations, the method and vehicle determines, based on the orientation, at least one uphill adjustable shock absorber and at least one downhill adjustable shock absorber of the plurality of adjustable shock absorbers and provides, to the at least one uphill adjustable shock absorber, one or more commands to result in an increase of a compression damping characteristic. In some instances, the method and vehicle determines, based on the orientation, at least one uphill adjustable shock absorber and at least one downhill adjustable shock absorber of the plurality of adjustable shock absorbers and provides, to the at least one downhill adjustable shock absorber, one or more commands to result in an increase of a rebound damping characteristic and a decrease of the compression damping characteristic.

(30) Additional features of the present disclosure will become apparent to those skilled in the art upon consideration of the following detailed description of illustrative embodiments exemplifying the best mode of carrying out the invention as presently perceived.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The foregoing aspects and many additional features of the present system and method will become more readily appreciated and become better understood by reference to the following detailed description when taken in conjunction with the accompanying drawings, where:
- (2) FIG. 1 shows a representative view of components of a vehicle of the present disclosure having a suspension with a plurality of continuous damping control shock absorbers and a plurality of sensors integrated with a controller of the vehicle;
- (3) FIG. 2 shows an adjustable damping shock absorber coupled to a vehicle suspension;
- (4) FIG. 3 shows an x-axis, a y-axis, and a z-axis for a vehicle, such as an ATV;
- (5) FIG. 4 shows a representative view of an exemplary power system for the vehicle of FIG. 1;
- (6) FIG. 5 shows a representative view of an exemplary controller of the vehicle of FIG. 1;
- (7) FIG. 6 shows a first, perspective view of an exemplary vehicle;
- (8) FIG. 7 shows a second, perspective view of the exemplary vehicle of FIG. 6;
- (9) FIG. 8 shows a side view of the exemplary vehicle of FIG. 6;
- (10) FIG. 9 shows a bottom view of the exemplary vehicle of FIG. 6;
- (11) FIG. 10 shows an exemplary control system for controlling the damping of one or more shock absorbers;
- (12) FIG. 11 shows an exemplary flowchart describing the operation of the suspension controller during a cornering event and/or a braking event;

- (13) FIG. **12** shows an example of the suspension controller adjusting the adjustable shock absorbers for the vehicle during a braking event;
- (14) FIG. **13** shows an example of the suspension controller adjusting the adjustable shock absorbers for the vehicle during a cornering event;
- (15) FIG. **14** shows an example flowchart describing the operation of the suspension controller **86** during an airborne event and a landing event;
- (16) FIG. **15** shows an example representation of the compression and rebound damping characteristics of a vehicle during a pre-takeoff period, a free-fall period, and a post-landing period;
- (17) FIG. **16** shows an exemplary flowchart describing the suspension controller performing in a rock crawl operation;
- (18) FIG. **17** shows an example of the suspension controller adjusting the adjustable shock absorbers for the vehicle performing in a rock crawl operation;
- (19) FIG. **18** shows another example of the suspension controller adjusting the adjustable shock absorbers for the vehicle performing in a rock crawl operation;
- (20) FIG. **19** shows another example of the suspension controller adjusting the adjustable shock absorbers for the vehicle performing in a rock crawl operation;
- (21) FIG. **20** shows another example of the suspension controller adjusting the adjustable shock absorbers for the vehicle performing in a rock crawl operation;
- (22) FIG. **21** shows an exemplary flowchart describing the operation of the suspension controller during a sliding event;
- (23) FIG. **22** shows another example of the suspension controller adjusting the adjustable shock absorbers during the sliding event;
- (24) FIG. **23** shows another example of the suspension controller adjusting the adjustable shock absorbers during the sliding event;
- (25) FIG. **24** shows an exemplary flowchart illustrating a method for performing real-time correction of the inertial measurement of a vehicle;
- (26) FIG. **25** shows an exemplary schematic block diagram illustrating an example of logic components in the suspension controller;
- (27) FIG. **26** shows an exemplary flowchart describing the operation of the suspension controller when switching between driver modes;
- (28) FIG. **27** shows an exemplary physical switch for adjusting driving modes;
- (29) FIG. **28** shows an exemplary graphical user interface for adjusting driver modes;
- (30) FIG. **29** shows an exemplary flowchart describing a method for implementing egress aid for a vehicle;
- (31) FIG. **30** illustrates a representative view of a sway bar of the vehicle of FIG. **1**; and
- (32) FIG. **31** illustrates a view of another exemplary vehicle.

DETAILED DESCRIPTION OF EMBODIMENTS

(33) For the purposes of promoting an understanding of the principles of the present disclosure, reference will now be made to the embodiments illustrated in the drawings, which are described below. The embodiments disclosed below are not intended to be exhaustive or limited to the precise form disclosed in the following detailed description. Rather, the embodiments are chosen and described so that others skilled in the art may utilize their teachings.

(34) Referring now to FIG. **1**, the present disclosure relates to a vehicle **10** having a suspension system **11** located between a plurality of ground engaging members **12** and a vehicle frame **14**. Exemplary ground engaging members **12** include wheels, skis, guide tracks, treads or other suitable devices for supporting the vehicle relative to the ground. The suspension typically includes springs **16** and shock absorbers **18** coupled between the ground engaging members **12** and the frame **14**. The springs **16** may include, for example, coil springs, leaf springs, air springs or other gas springs. The air or gas springs **16** may be adjustable. See, for example, U.S. Pat. No. 7,950,486, assigned to the current assignee, the entire disclosure of which is incorporated herein by reference.

(35) The adjustable shock absorbers **18** are often coupled between the vehicle frame **14** and the ground engaging members **12** through an A-arm linkage **70** (See FIG. **2**) or other type linkage. Springs **16** are also coupled between the ground engaging members **12** and the vehicle frame **14**. FIG. **2** illustrates an

adjustable shock absorber **18** mounted on an A-arm linkage **70** having a first end pivotably coupled to the vehicle frame **14** and a second end pivotably coupled to A-arm linkage **70** which moves with wheel **12**. A damping control activator **74** is coupled to controller **20** by one or more wires **76**. An exemplary damping control activator is an electronically controlled valve which is activated to increase or decrease the damping characteristics of adjustable shock absorber **18**.

(36) In one embodiment, the adjustable shock absorbers **18** include solenoid valves mounted at the base of the shock body or internal to a damper piston of the shock absorber **18**. The stiffness of the shock is increased or decreased by introducing additional fluid to the interior of the shock absorber, removing fluid from the interior of the shock absorber, and/or increasing or decreasing the ease with which fluid can pass from a first side of a damping piston of the shock absorber to a second side of the damping piston of the shock absorber. In another embodiment, the adjustable shock absorbers **18** include a magnetorheological fluid internal to the shock absorber **18**. The stiffness of the shock is increased or decreased by altering a magnetic field experienced by the magnetorheological fluid. Additional details on exemplary adjustable shocks are provided in US Published Patent Application No. 2016/0059660, filed Nov. 6, 2015, titled VEHICLE HAVING SUSPENSION WITH CONTINUOUS DAMPING CONTROL, assigned to the present assignee, the entire disclosure of which is expressly incorporated by reference herein.

(37) In one embodiment, a spring **16** and shock **18** are located adjacent each of the ground engaging members **12**. In an all-terrain vehicle (ATV), for example, a spring **16** and an adjustable shock **18** are provided adjacent each of the four wheels **12**. In a snowmobile, for example, one or more springs **16** and one or more adjustable shocks **18** are provided for each of the two front skis and the rear tread. Some manufacturers offer adjustable springs **16** in the form of either air springs or hydraulic preload rings. These adjustable springs **16** allow the operator to adjust the ride height on the go. However, a majority of ride comfort comes from the damping provided by shock absorbers **18**.

(38) In an illustrated embodiment, controller **20** provides signals and/or commands to adjust damping characteristics of the adjustable shocks **18**. For example, the controller **20** provides signals to adjust damping of the shocks **18** in a continuous or dynamic manner. In other words, adjustable shocks **18** may be adjusted to provide differing compression damping, rebound damping, or both. In one embodiment, adjustable shocks **18** include a first controllable valve to adjust compression damping and a second controllable valve to adjust rebound damping. In another embodiment, adjustable shocks include a combination valve which controls both compression damping and rebound damping.

(39) In an illustrated embodiment of the present disclosure, an operator interface **22** is provided in a location easily accessible to the driver operating the vehicle. For example, the operator interface **22** is either a separate user interface mounted adjacent the driver's seat on the dashboard or integrated onto a display within the vehicle. Operator interface **22** includes user input devices to allow the driver or a passenger to manually adjust shock absorber **18** damping during operation of the vehicle based on road conditions that are encountered or to select a preprogrammed active damping profile for shock absorbers **18** by selecting a ride mode. In one embodiment, a selected ride mode (e.g., a selected driver mode) alters characteristics of suspension system **11** alone, such as the damping profile for shock absorbers **18**. In one embodiment, a selected ride mode alters characteristics of suspension system **11** and other vehicle systems, such as a driveline torque management system **50** or a steering system **104**.

(40) Exemplary input devices for operator interface **22** include levers, buttons, switches, soft keys, and other suitable input devices. Operator interface **22** may also include output devices to communicate information to the operator. Exemplary output devices include lights, displays, audio devices, tactile devices, and other suitable output devices. In another illustrated embodiment, the user input devices are on a steering wheel, handle bar, or other steering control of the vehicle **10** to facilitate actuation of the damping adjustment. For example, referring to FIG. 27, a physical switch **820** may be located on the steering wheel, handle bar, or other steering control of the vehicle **10**. A display **24** is also provided on or next to the operator interface **22** or integrated into a dashboard display of vehicle **10** to display information related to the compression and/or rebound damping characteristics.

(41) As explained in further detail below, controller **20** receives user inputs from operator interface **22** and adjusts the damping characteristics of the adjustable shocks **18** accordingly. The operator may independently adjust front and rear shock absorbers **18** to adjust the ride characteristics of the vehicle **10**. In certain embodiments, each of the shocks **18** is independently adjustable so that the damping

characteristics of the shocks **18** are changed from one side of the vehicle **10** to another. Side-to-side adjustment is desirable during sharp turns or other maneuvers in which different damping profiles for shock absorbers **18** on opposite sides of the vehicle improves the handling characteristics of the vehicle. The damping response of the shock absorbers **18** can be changed in a matter of milliseconds to provide nearly instantaneous changes in damping for potholes, dips in the road, or other driving conditions. Additionally, and/or alternatively, controller **20** may independently adjust the damping characteristics of front and/or rear shocks **18**. An advantage, among others, of adjusting the damping characteristics of the front and/or rear shocks **18** is that the vehicle **10** may be able to operate more efficiently in rough terrain.

(42) The controller **20** communicates with (e.g., provides, transmits, receives, and/or obtains) multiple vehicle condition sensors **40**. For example, a wheel accelerometer **25** is coupled adjacent each ground engaging member **12**. The controller **20** communicates with each of the accelerometers **25**. For instance, the accelerometers **25** may provide information indicating movement of the ground engaging members and the suspension components **16** and **18** as the vehicle traverses different terrain. Further, the controller **20** may communicate with additional vehicle condition sensors **40**, such as a vehicle speed sensor **26**, a steering sensor **28**, a chassis supported accelerometer **30**, a chassis supported gyroscope **31**, an inertial measurement unit (IMU) **37** (shown on FIG. **10**), a physical switch **820** (shown on FIG. **10**), and other sensors which monitor one or more characteristics of vehicle **10**.

(43) Accelerometer **30** is illustratively a three-axis accelerometer supported on the chassis of the vehicle **10** to provide information indicating acceleration forces of the vehicle **10** during operation. In some instances, accelerometer **30** is located at or close to a center position (e.g., a center of gravity position) of vehicle **10**. In other instances, the accelerometer **30** is located at a position that is not near the center of gravity of the vehicle **10**. In the exemplary vehicle **200** illustrated in FIGS. **6-9**, the chassis accelerometer **30** is located along a longitudinal centerline plane **122** of vehicle **200**. The x-axis, y-axis, and z-axis for a vehicle **10**, illustratively an ATV, are shown in FIG. **3**.

(44) Gyroscope **31** is illustratively a three-axis gyroscope supported on the chassis to provide indications of inertial measurements, such as roll rates, pitch rates, and/or yaw rates, of the vehicle during operation. In one embodiment, accelerometer **30** is not located at a center of gravity of vehicle **10** and the readings of gyroscope **31** are used by controller **20** to determine the acceleration values of vehicle **10** at the center of gravity of vehicle **10**. In one embodiment, accelerometer **30** and gyroscope **31** are integrated into the controller **20**, such as a suspension controller **86**.

(45) In some examples and referring to FIG. **10**, an IMU, such as the IMU **37** is supported on the chassis to provide indications of the inertial measurements, including the angular rate and/or the acceleration forces, of the vehicle **10** during operation. The IMU **37** may include the functionalities of the accelerometer **30** and/or the gyroscope **31**. As such, in some instances, the accelerometer **30** and/or the gyroscope **31** are optional and might not be included in the vehicle **10**. In other instances, the vehicle **10** may include the gyroscope **31** and the accelerometer **30** instead of the IMU **37**.

(46) The controller **20** may also communicate with additional vehicle condition sensors **40**, such as a brake sensor **32**, a throttle position sensor **34**, a wheel speed sensor **36**, and/or a gear selection sensor **38**.

(47) Referring to FIG. **4**, one embodiment of a driveline torque management system **50** of vehicle **10** is illustrated. Driveline torque management system **50** controls the amount of torque exerted by each of ground engaging members **12**. Driveline torque management system **50** provides a positive torque to one or more of ground engaging members **12** to power the movement of vehicle **10** through a power system **60**. Driveline torque management system **50** further provides a negative torque to one or more of ground engaging members **12** to slow or stop a movement of vehicle **10** through a braking system **75**. In one example, each of ground engaging members **12** has an associated brake of braking system **75**.

(48) Power system **60** includes a prime mover **62**. Exemplary prime movers **62** include internal combustion engines, two stroke internal combustion engines, four stroke internal combustion engines, diesel engines, electric motors, hybrid engines, and other suitable sources of motive force. To start the prime mover **62**, a power supply system **64** is provided. The type of power supply system **64** depends on the type of prime mover **62** used. In one embodiment, prime mover **62** is an internal combustion engine and power supply system **64** is one of a pull start system and an electric start system. In one embodiment, prime mover **62** is an electric motor and power supply system **64** is a switch system which electrically couples one or more batteries to the electric motor.

(49) A transmission **66** is coupled to prime mover **62**. Transmission **66** converts a rotational speed of an output shaft **61** of prime mover **62** to one of a faster rotational speed or a slower rotational speed of an output shaft **63** of transmission **66**. It is contemplated that transmission **66** may additionally rotate output shaft **63** at the same speed as output shaft **61**.

(50) In the illustrated embodiment, transmission **66** includes a shiftable transmission **68** and a continuously variable transmission (“CVT”) **71**. In one example, an input member of CVT **71** is coupled to prime mover **62**. An input member of shiftable transmission **68** is in turn coupled to an output member of CVT **71**. In one embodiment, shiftable transmission **68** includes a forward high setting, a forward low setting, a neutral setting, a park setting, and a reverse setting. The power communicated from prime mover **62** to CVT **71** is provided to a drive member of CVT **71**. The drive member in turn provides power to a driven member through a belt. Exemplary CVTs are disclosed in U.S. Pat. Nos. 3,861,229; 6,176,796; 6,120,399; 6,860,826; and 6,938,508, the disclosures of which are expressly incorporated by reference herein. The driven member provides power to an input shaft of shiftable transmission **68**. Although transmission **66** is illustrated as including both shiftable transmission **68** and CVT **71**, transmission **66** may include only one of shiftable transmission **68** and CVT **71**. Further, transmission **66** may include one or more additional components.

(51) Transmission **66** is further coupled to at least one differential **73** which is in turn coupled to at least one ground engaging members **12**. Differential **73** may communicate the power from transmission **66** to one of ground engaging members **12** or multiple ground engaging members **12**. In an ATV embodiment, one or both of a front differential and a rear differential are provided. The front differential powering at least one of two front wheels of the ATV and the rear differential powering at least one of two rear wheels of the ATV. In a side-by-side vehicle embodiment having seating for at least an operator and a passenger in a side-by-side configuration, one or both of a front differential and a rear differential are provided. The front differential powering at least one of two front wheels of the side-by-side vehicle and the rear differential powering at least one of multiple rear wheels of the side-by-side vehicle. In one example, the side-by-side vehicle has three axles and a differential is provided for each axle. An exemplary side-by-side vehicle **200** is illustrated in FIGS. 6-9.

(52) In one embodiment, braking system **75** includes anti-lock brakes. In one embodiment, braking system **75** includes active descent control and/or engine braking. In one embodiment, braking system **75** includes a brake and in some embodiments a separate parking brake. Braking system **75** may be coupled to any of prime mover **62**, transmission **66**, differential **73**, and ground engaging members **12** or the connecting drive members therebetween. Brake sensor **32**, in one example, monitors when braking system **75** is applied. In one example, brake sensor **32** monitors when a user actuatable brake input, such as brake pedal **232** (see FIG. 7) in vehicle **200**, is applied.

(53) Referring to FIG. 5, controller **20** has at least one associated memory **76**. Controller **20** provides the electronic control of the various components of vehicle **10**. Further, controller **20** is operatively coupled to a plurality of vehicle condition sensors **40** as described above, which monitor various parameters of the vehicle **10** or the environment surrounding the vehicle **10**. Controller **20** performs certain operations (e.g., provides commands) to control one or more subsystems of other vehicle components. In certain embodiments, the controller **20** forms a portion of a processing subsystem including one or more computing devices having memory, processing, and communication hardware. Controller **20** may be a single device or a distributed device, and the functions of the controller **20** may be performed by hardware and/or as computer instructions on a non-transitory computer readable storage medium, such as memory **76**.

(54) As illustrated in the embodiment of FIG. 5, controller **20** is represented as including several controllers. These controllers may each be single devices or distributed devices or one or more of these controllers may together be part of a single device or distributed device. The functions of these controllers may be performed by hardware and/or as computer instructions on a non-transitory computer readable storage medium, such as memory **76**.

(55) In one embodiment, controller **20** includes at least two separate controllers which communicate over a network **78**. In one embodiment, network **78** is a CAN network. Details regarding an exemplary CAN network are disclosed in U.S. patent application Ser. No. 11/218,163, filed Sep. 1, 2005, the disclosure of which is expressly incorporated by reference herein. Of course any suitable type of network or data bus

may be used in place of the CAN network. In one embodiment, two wire serial communication is used for some connections.

(56) Referring to FIG. 5, controller **20** includes an operator interface controller **80** which controls communication with an operator through operator interface **22**. A prime mover controller **82** controls the operation of prime mover **62**. A transmission controller **84** controls the operation of transmission system **66**.

(57) A suspension controller **86** controls adjustable portions of suspension system **11**. Exemplary adjustable components include adjustable shocks **18**, adjustable springs **16**, and/or configurable stabilizer bars. Additional details regarding adjustable shocks, adjustable springs, and configurable stabilizer bars is provided in US Published Patent Application No. 2016/0059660, filed Nov. 6, 2015, titled VEHICLE HAVING SUSPENSION WITH CONTINUOUS DAMPING CONTROL, assigned to the present assignee, the entire disclosure of which is expressly incorporated by reference herein.

(58) Communication controller **88** controls communications between a communication system **90** of vehicle **10** and remote devices, such as other vehicles, personal computing devices, such as cellphones or tablets, a centralized computer system maintaining one or more databases, and other types of devices remote from vehicle **10** or carried by riders of vehicle **10**. In one embodiment, communication controller **88** of vehicle **10** communicates with paired devices over a wireless network. An exemplary wireless network is a radio frequency network utilizing a BLUETOOTH protocol. In this example, communication system **90** includes a radio frequency antenna. Communication controller **88** controls the pairing of devices to vehicle **10** and the communications between vehicle **10** and the remote device. In one embodiment, communication controller **88** of vehicle **10** communicates with remote devices over a cellular network. In this example, communication system **90** includes a cellular antenna and communication controller **88** receives and sends cellular messages from and to the cellular network. In one embodiment, communication controller **88** of vehicle **10** communicates with remote devices over a satellite network. In this example, communication system **90** includes a satellite antenna and communication controller **88** receives and sends messages from and to the satellite network. In one embodiment, vehicle **10** is able to communicate with other vehicles **10** over a Radio Frequency mesh network and communication controller **88** and communication system **90** are configured to enable communication over the mesh network. An exemplary vehicle communication system is disclosed in U.S. patent application Ser. No. 15/262,113, filed Sep. 12, 2016, titled VEHICLE TO VEHICLE COMMUNICATIONS DEVICE AND METHODS FOR RECREATIONAL VEHICLES, the entire disclosure of which is expressly incorporated by reference herein.

(59) A steering controller **102** controls portions of a steering system **104**. In one embodiment, steering system **104** is a power steering system and includes one or more steering sensors **28** (shown in FIG. 1). Exemplary sensors and electronic power steering units are provided in U.S. patent application Ser. No. 12/135,107, assigned to the assignee of the present application, titled VEHICLE, docket PLR-06-22542.02P, the disclosure of which is expressly incorporated by reference herein. A vehicle controller **92** controls lights, loads, accessories, chassis level functions, and other vehicle functions. A ride height controller **96** controls the preload and operational height of the vehicle. In one embodiment, ride height controller controls springs **16** to adjust a ride height of vehicle **10**, either directly or through suspension controller **86**. In one example, ride height controller **96** provides more ground clearance in a comfort ride mode compared to a sport ride mode.

(60) An agility controller **100** controls a braking system of vehicle **10** and the stability of vehicle **10**. Control methods of agility controller **100** may include integration into braking circuits (ABS) such that a stability control system can improve dynamic response (vehicle handling and stability) by modifying the shock damping in conjunction with electronic braking control.

(61) In one embodiment, controller **20** either includes a location determiner **110** and/or communicates via network **78** to a location determiner **110**. The location determiner **110** determines a current geographical location of vehicle **10**. An exemplary location determiner **110** is a GPS unit which determines the position of vehicle **10** based on interaction with a global satellite system.

(62) Referring to FIGS. 6-9, an exemplary side-by-side vehicle **200** is illustrated. Vehicle **200**, as illustrated, includes a plurality of ground engaging members **12**. Illustratively, ground engaging members **12** are wheels **204** and associated tires **206**. As mentioned herein, one or more of ground engaging

members **12** are operatively coupled to power system **60** (see FIG. **4**) to power the movement of vehicle **200** and braking system **75** to slow movement of vehicle **200**.

(63) Referring to the illustrated embodiment in FIG. **6**, a first set of wheels, one on each side of vehicle **200**, generally correspond to a front axle **208**. A second set of wheels, one on each side of vehicle **200**, generally correspond to a rear axle **210**. Although each of front axle **208** and rear axle **210** are shown having a single ground engaging member **12** on each side, multiple ground engaging members **12** may be included on each side of the respective front axle **208** and rear axle **210**. As configured in FIG. **6**, vehicle **200** is a four wheel, two axle vehicle.

(64) Referring to FIG. **9**, wheels **204** of front axle **208** are coupled to a frame **212** of vehicle **200** through front independent suspensions **214**. Front independent suspensions **214** in the illustrated embodiment are double A-arm suspensions. Other types of suspensions systems may be used for front independent suspensions **214**. The wheels **204** of rear axle **210** are coupled to frame **212** of vehicle **200** through rear independent suspensions **216**. Other types of suspensions systems may be used for rear independent suspensions **216**.

(65) Returning to FIG. **6**, vehicle **200** includes a cargo carrying portion **250**. Cargo carrying portion **250** is positioned rearward of an operator area **222**. Operator area **222** includes seating **224** and a plurality of operator controls. In the illustrated embodiment, seating **224** includes a pair of bucket seats. In one embodiment, seating **224** is a bench seat. In one embodiment, seating **224** includes multiple rows of seats, either bucket seats or bench seats or a combination thereof. Exemplary operator controls include a steering wheel **226**, a gear selector **228**, an accelerator pedal **230** (see FIG. **7**), and a brake pedal **232** (see FIG. **7**). Steering wheel **226** is operatively coupled to the wheels of front axle **208** to control the orientation of the wheels relative to frame **212**. Gear selector **228** is operatively coupled to the shiftable transmission **68** to select a gear of the shiftable transmission **68**. Exemplary gears include one or more forward gears, one or more reverse gears, and a park setting. Accelerator pedal **230** is operatively coupled to prime mover **62** to control the speed of vehicle **200**. Brake pedal **232** is operatively coupled to brake units associated with one or more of wheels **204** to slow the speed of vehicle **200**.

(66) Operator area **222** is protected with a roll cage **240**. Referring to FIG. **6**, side protection members **242** are provided on both the operator side of vehicle **200** and the passenger side of vehicle **200**. In the illustrated embodiment, side protection members **262** are each a unitary tubular member.

(67) In the illustrated embodiment, cargo carrying portion **250** includes a cargo bed **234** having a floor **256** and a plurality of upstanding walls. Floor **256** may be flat, contoured, and/or comprised of several sections. Portions of cargo carrying portion **250** also include mounts **258** which receive an expansion retainer (not shown). The expansion retainers which may couple various accessories to cargo carrying portion **250**. Additional details of such mounts and expansion retainers are provided in U.S. Pat. No. 7,055,454, to Whiting et al., filed Jul. 13, 2004, titled "Vehicle Expansion Retainers," the entire disclosure of which is expressly incorporated by reference herein.

(68) Front suspensions **214A** and **214B** each include a shock absorber **260**, respectively. Similarly, rear suspensions **216A** and **216B** each include a shock absorber **262**. In one embodiment each of shock absorbers **260** and shock absorbers **262** are electronically adjustable shocks **18** which are controlled by a controller **20** of vehicle **200**.

(69) Additional details regarding vehicle **200** are provided in U.S. Pat. Nos. 8,827,019 and 9,211,924, assigned to the present assignee, the entire disclosures of which are expressly incorporated by reference herein. Other exemplary recreational vehicles include ATVs, utility vehicles, snowmobiles, other recreational vehicles designed for off-road use, on-road motorcycles, and other suitable vehicles (e.g., FIG. **31**).

(70) FIG. **10** shows an exemplary control system **300** for controlling the damping of shock absorbers **18**. In some instances, the control system **300** may be included in the vehicle **10** and/or the vehicle **200** described above. For example, the suspension controller **86** may communicate with (e.g., receive and/or provide) one or more entities (e.g., sensors, devices, controllers, and/or subsystems) from the vehicle **10** and/or **200** described above. Additionally, and/or alternatively, the vehicle **10** and **200** may be the same vehicle (e.g., the vehicle **200** may include entities from vehicle **10**, such as the suspension controller **86**).

(71) Additionally, the controller **20** may include a suspension controller **86** as described above in FIG. **5**. The suspension controller **86** may communicate with the plurality of vehicle condition sensors **40** as

described above. Further, the suspension controller **86** may provide information (e.g., one or more commands) to each of the adjustable shock absorbers **18a**, **18b**, **18c**, and **18d**. For example, the suspension controller **86** may provide commands to adjust the compression damping characteristic and/or the rebound damping characteristic for the adjustable shock absorbers **18a**, **18b**, **18c**, and **18d**.

(72) While exemplary sensors, devices, controllers, and/or subsystems are provided in FIG. **10**, additional exemplary sensors, devices, controllers, and/or subsystems used by the suspension controller **86** to adjust shock absorbers **18** are provided in US Published Patent Application No. 2016/0059660 (filed Nov. 6, 2015, titled VEHICLE HAVING SUSPENSION WITH CONTINUOUS DAMPING CONTROL) and US Published Application 2018/0141543 (filed Nov. 17, 2017, titled VEHICLE HAVING ADJUSTABLE SUSPENSION), both assigned to the present assignee and the entire disclosures of each expressly incorporated by reference herein.

(73) The illustrative control system **300** is not intended to suggest any limitation as to the scope of use or functionality of embodiments of the present disclosure. Neither should the illustrative control system **300** be interpreted as having any dependency or requirement related to any single entity or combination of entities illustrated therein. Additionally, various entities depicted in FIG. **10**, in embodiments, may be integrated with various ones of the other entities depicted therein (and/or entities not illustrated). For example, the suspension controller **86** may be included within the controller **20**, and may communicate with one or more vehicle condition sensors **40** as described above. The functionalities of the suspension controller **86** and/or other entities in control system **300** will be described below.

(74) Cornering Event and Braking Event

(75) FIG. **11** shows an example flowchart describing the operation of the suspension controller **86** during a cornering event and/or a braking event. FIGS. **12** and **13** show examples of the suspension controller **86** adjusting the shock absorbers **18** for the vehicle **10** during a cornering event and/or braking event. As will be described in more detail below, for better performance during a braking and/or cornering event, a vehicle, such as vehicle **10**, may use a controller **20** (e.g., the suspension controller **86**) to adjust the rebound and/or compression damping. For instance, during a cornering event, the suspension controller **86** may reduce (e.g., decrease) the compression damping of the inner adjustable shock absorbers **18**, which may cause the vehicle **10** to ride lower during cornering and/or to be less upset when the inner ground engaging members **12** encounter bumps. Further, the suspension controller **86** may reduce the rebound damping of the outside adjustable shock absorbers **18**, which may promote shock extensions to flatten the vehicle **10** and/or cause the wheels of the vehicle **10** to follow the ground better to provide better traction. Additionally, and/or alternatively, the suspension controller **86** may increase the compression damping of the outside adjustable shocks **18** and/or increase the rebound damping of the inside adjustable shock absorbers **18**.

(76) During a braking event, the suspension controller **86** may reduce the compression damping for the rear adjustable shock absorbers **18** based on a deceleration rate (e.g., deceleration value), which may cause increased stability of the vehicle **10** during bumps and/or rough trails. Further, by reducing the compression damping for the rear adjustable shock absorbers **18**, the suspension controller **86** may cause the rear ground engaging members **12** to absorb events, such as bumps, better. Also, the suspension controller **86** may also reduce the rebound damping for the front adjustable shock absorbers **18**, which may promote shock extensions to flatten the vehicle **10** and/or cause the wheels of the vehicle **10** to follow the ground better to provide better traction. Additionally, and/or alternatively, the suspension controller **86** may increase the compression damping of the front adjustable shocks **18** and/or increase the rebound damping of the rear adjustable shock absorbers **18**. By increasing the rebound damping of the rear adjustable shock absorbers **18**, the vehicle **10** may be better able to control the pitch body movement and/or weight transfer during a braking event. Further, the suspension controller **86** may hold the vehicle **10** flatter and/or more stable when the vehicle **10** encounters bumps while braking.

(77) In operation, at step **402**, the suspension controller **86** may receive steering information from one or more sensors, such as the steering sensor **28**. The steering information may indicate a steering position, steering angle, and/or steering rate of a steering wheel, such as steering wheel **226**. The steering position and/or angle may indicate a position and/or an angle of the steering wheel for the vehicle **10**. The steering rate may indicate a change of the position and/or angle of the steering wheel over a period of time.

(78) At step **404**, the suspension controller **86** may receive yaw rate information from one or more

sensors, such as the gyroscope **31** and/or the IMU **37**. The yaw information indicates the yaw rate of the vehicle **10**.

(79) At step **406**, the suspension controller **86** may receive acceleration information indicating an acceleration rate or deceleration rate of the vehicle **10** from one or more sensors, such as the IMU **37** and/or the chassis accelerometer **30**. The acceleration information may indicate multi-axis acceleration values of the vehicle, such as a longitudinal acceleration and/or a lateral acceleration. In some examples, the suspension controller **86** may receive information from another sensor, such as the throttle position sensor **34** and/or the accelerator pedal sensor **33**. The suspension controller **86** use the information to determine the acceleration rate. For example, the suspension controller **86** may use the throttle position from the throttle position sensor and/or the position of the accelerator pedal **230** from the acceleration pedal sensor **33** to determine whether the vehicle **10** is accelerating and/or decelerating.

(80) At step **408**, the suspension controller **86** may receive brake information from a sensor, such as the brake sensor **32**. The brake information may indicate a position (e.g., braking and/or not braking) of the brake pedal **232**. Additionally, and/or alternatively, the brake information may indicate an amount of brake pressure on the brake pedal **232**.

(81) At step **410**, the suspension controller **86** may receive an operating mode of the vehicle **10** from the operator interface **22** and/or one or more other controllers (e.g., controller **20**). Each mode may include a different setting for the rebound and/or compression damping. An operator (e.g., user) may input a mode of operation on the operator interface **22**. The operator interface **22** may provide the user input indicating the mode of operation to the controller **20** and/or the suspension controller **86**. The suspension controller **86** may use the user input to determine the mode of operation for the vehicle **10**.

(82) At step **412**, the suspension controller **86** may determine whether a cornering event (e.g., a turn) is occurring. Further, the suspension controller **86** may determine a direction of the turn (e.g., a left turn or a right turn). For example, the suspension controller **86** may determine the cornering event and/or direction of the turn based on the steering information indicating a steering rate, angle, and/or position, yaw rate information indicating a yaw rate, and/or the acceleration information indicating a lateral acceleration. The suspension controller **86** may compare the steering rate, steering angle, steering position, yaw rate, and/or lateral acceleration with one or more corresponding thresholds (e.g., pre-determined, pre-programmed, and/or user-defined) to determine the cornering event. The suspension controller **86** may use the positive and/or negative values of the steering rate, angle, position, yaw rate, and/or lateral acceleration to determine the direction of the turn.

(83) In some examples, the suspension controller **86** may determine the cornering event based on the steering rate, angle, and/or position being greater than a threshold. In such examples, the method **400** may move to step **414**. Otherwise, if the suspension controller **86** determines that the steering rate, angle and/or position is below the threshold, the method **400** may move to step **418**. In some variations, the suspension controller **86** may determine the cornering event based on the yaw rate. For example, based on the yaw rate being greater than a threshold, the suspension controller **86** may determine a cornering event is occurring. In some instances, the suspension controller **86** may determine the cornering event based on a lateral acceleration. For example, based on the lateral acceleration being greater than a threshold, the suspension controller **86** may determine that a cornering event is occurring.

(84) In some variations, the suspension controller **86** may prioritize the steering information, the yaw rate information, and/or the acceleration information, and determine the cornering event based on the priorities. For instance, in some examples, the steering position and/or angle, steering rate, yaw rate, and lateral acceleration may all indicate a turn. In other examples, the steering position and/or angle, steering rate, yaw rate, and/or lateral acceleration may conflict (e.g., the steering position might not indicate a turn and the yaw rate may indicate a turn; the yaw rate might not indicate a turn and the lateral acceleration may indicate a turn). For example, in a counter steer or a slide, the vehicle **10** may be turning in one direction, such as a left turn (e.g., indicated by a yaw rate and/or lateral acceleration); however, the steering position may indicate a turn in the opposite direction, such as a right turn, or might not indicate a turn. In such examples, the suspension controller **86** may prioritize the lateral acceleration and/or the yaw rate over the steering rate, angle, and/or position. For example, the suspension controller **86** may determine the vehicle **10** is turning and the turn is a left turn.

(85) In some variations, the suspension controller **86** may prioritize the lateral acceleration over the yaw

rate and the yaw rate over the steering rate, angle, and/or position. In other words, the suspension controller **86** may determine the cornering event is occurring and/or a direction of turn based on the lateral acceleration indicating a turn even if the yaw rate, steering rate, angle, and/or position do not indicate a turn. Further, the suspension controller **86** may determine the cornering event is occurring and/or a direction of turn based on the yaw rate indicating a turn even if the steering rate, angle, and/or position do not indicate a turn.

(86) At step **414**, the suspension controller **86** may determine a cornering state of the vehicle **10**. The cornering state may indicate whether the vehicle **10** is entering, in the middle of, and/or exiting a corner event. Additionally, and/or alternatively, the cornering state may indicate whether the vehicle **10** is braking, accelerating, and/or decelerating through the cornering event. For example, the suspension controller **86** may determine the cornering state based on the acceleration information (e.g., the longitudinal acceleration) and/or the brake information (e.g., the position of the brake pedal **232** and/or amount of pressure on the brake pedal **232**). As will be explained below, the suspension controller **86** may adjust and/or bias the adjustable shock absorbers **18** based on the cornering event, the braking of the vehicle **10**, and/or the acceleration/deceleration of the vehicle **10**.

(87) At step **416**, the suspension controller **86** may execute a corner condition modifier for one or more of the adjustable shock absorbers **18**. For example, the suspension controller **86** may adjust (e.g., increase and/or decrease) the rebound and/or compression damping for one or more of the adjustable shock absorbers **18** based on detecting a cornering event (e.g., from step **412** indicating that the vehicle **10** is turning). FIG. **13** shows the suspension of the vehicle **10** during a cornering event. For example, in response to detecting the cornering event, the suspension controller **86** may provide information (e.g., one or more commands) to the adjustable shock absorbers **18**. For instance, the suspension controller **86** may determine that the vehicle **10** is turning left (e.g., based on the steering position or rate, yaw rate, and/or lateral acceleration). In response, the suspension controller **86** may provide information **302** and/or **306** to the inner adjustable shock absorbers **18a** and/or **18c** to decrease the compression damping (CD) and/or increase the rebound damping (RD). By decreasing the compression damping of the inner adjustable shock absorbers **18a** and/or **18c**, the vehicle **10** may absorb bumps on that side better and/or be more stable when cornering in rough terrain. Further, the vehicle **10** may sit lower when cornering because the inside will move through the compression stroke easier when the vehicle is “on the sway bar” torsion. Additionally, by increasing the rebound on the inside adjustable shock absorbers **18a** and/or **18c**, the vehicle **10** may control the roll gradient and/or rate during the cornering event. Also, the suspension controller **86** may provide information **304** and/or **308** to the outer adjustable shock absorbers **18b** and/or **18d** to increase the compression damping (CD) and/or decrease the rebound damping (RD). After the suspension controller **86** determines and/or executes a corner condition modifier, the method **400** may move back to step **402** and repeat continuously.

(88) In some variations, during the cornering event, the suspension controller **86** may adjust (e.g., increase and/or decrease) the rebound and/or compression damping for one or more of the adjustable shock absorbers **18** based on the cornering state (e.g., the braking of the vehicle **10** and/or the acceleration/deceleration of the vehicle **10**). For example, during a cornering event, the suspension controller **86** may adjust the compression and/or rebound damping for the inner and/or outer adjustable shock absorbers **18** as described above. Additionally, and/or alternatively, based on the braking, acceleration, and/or deceleration rate, the suspension controller **86** may further bias (e.g., further increase by a value or percentage and/or further decrease by a value or percentage) the compression damping and/or rebound damping for the front and rear adjustable shock absorbers **18**. By biasing the compression and/or rebound damping, the vehicle **10** may improve weight transfer on a corner entry and exit and may also improve the vehicle yaw response.

(89) In other words, in response to detecting the cornering event, the suspension controller **86** may adjust the inner/outer adjustable shock absorbers **18** as described above. Then, based on the vehicle **10** slowing down, the suspension controller **86** may detect and/or determine a longitudinal deceleration (e.g., negative longitudinal acceleration) of the vehicle. Based on detecting the longitudinal deceleration, the suspension controller **86** may further bias (e.g., change and/or determine) the compression and/or rebound damping for the front/rear shock absorbers **18**. For example, based on the longitudinal deceleration, the suspension controller **86** may additionally increase (e.g., increase by a percentage or a value) the compression

damping of the front adjustable shock absorbers **18a** and **18b** and/or additionally decrease (e.g., decrease by a percentage or a value) the compression damping of rear adjustable shock absorbers **18c** and **18d**. Further, the suspension controller **86** may additionally increase the rebound damping of the rear shock absorbers **18c** and **18d** and/or additionally decrease the rebound damping of the front shock absorbers **18a** and **18b**.

(90) For instance, the suspension controller **86** may adjust the compression and/or rebound damping for a shock absorber **18** based on whether the shock absorber is an inner or outer shock absorber as described above (e.g., set the compression damping at a value of 73). Then, based on the cornering state (e.g., a positive/negative longitudinal acceleration), the suspension controller **86** may further bias the compression and/or rebound damping. For example, the suspension controller **86** may decrease the front compression damping (e.g., set the compression damping from 73 to 62) if the suspension controller **86** detects a positive acceleration and increase the front compression damping (e.g., set the compression damping from 73 to 80) if the suspension controller **86** detects a negative acceleration. The suspension controller **86** may operate similarly for rebound damping.

(91) Additionally, and/or alternatively, the suspension controller **86** may bias the compression and/or rebound damping differently based on the positive/negative longitudinal acceleration being greater than or less than one or more thresholds. For example, if acceleration is greater than a first threshold, then the suspension controller **86** may set the compression damping from a first value (e.g., 73) to a second value (e.g., 62). If acceleration is greater than a second threshold, then the suspension controller **86** may set the compression damping from the first value (e.g., 73) to a third value (e.g., 59). Additionally, and/or alternatively, if acceleration is greater than a third threshold, then the suspension controller **86** may set the compression damping from the first value (e.g., 73) to a fourth value (**44**). The suspension controller **86** may operate similarly for negative accelerations and/or braking as well.

(92) At the end of the cornering event (e.g., a turn exit), the vehicle **10** may speed up (e.g., an operator may actuate the accelerator pedal **230**). Based on detecting a positive acceleration (e.g., a longitudinal acceleration), the suspension controller **86** may further bias the front/rear shock absorbers **18**. For example, based on the positive longitudinal acceleration, the suspension controller **86** may additionally increase the compression damping of rear adjustable shock absorbers **18c** and **18d** and/or additionally decrease the compression damping of the front adjustable shock absorbers **18a** and **18b**. Further, the suspension controller **86** may additionally increase the rebound damping of the front shock absorbers **18a** and **18b** and/or additionally decrease rebound damping of the rear shock absorbers **18c** and **18d**. After the executing the corner condition modifier, the method **400** may move back to step **402**.

(93) If the suspension controller **86** does not detect a cornering event, the method **400** may move to step **418**. At step **418**, the suspension controller **86** may determine whether a braking event is occurring. For example, the suspension controller **86** may determine whether the brake pedal **232** is actuated. In other words, the suspension controller **86** may determine or detect a braking event (e.g., whether the vehicle **10** is braking). If the suspension controller **86** determines that the brake pedal **232** is not actuated, the method **400** moves back to **402** and then repeats. If the suspension controller **86** determines that the brake pedal **232** is actuated, the method **400** moves to step **410**.

(94) At step **420**, the suspension controller **86** may determine the deceleration rate of the vehicle **10** (e.g., two tenths of a gravitational constant (G) or half of a G). For example, the suspension controller **86** may determine the deceleration rate of the vehicle **10** from the chassis accelerometer **30** and/or the IMU **37**. Additionally, and/or alternatively, the suspension controller **86** may determine and/or predict the deceleration rate of the vehicle **10** based on the amount of brake pressure on the brake pedal **232**. As mentioned above, the brake sensor **32** may provide the amount of brake pressure on the brake pedal **232** to the suspension controller **86**. Additionally, and/or alternatively, the suspension controller **86** may determine and/or predict the deceleration rate of the vehicle **10** based on an engine torque reduction from an engine torque sensor.

(95) At step **422**, the suspension controller **86** may execute a brake condition modifier for one or more of the adjustable shock absorbers **18**. For example, the suspension controller **86** may adjust (e.g., increase and/or decrease) the rebound and/or compression damping for one or more of the adjustable shock absorbers **18** based on detecting a braking event (e.g., from step **408** indicating that the brake pedal has been actuated). FIG. **12** shows the suspension of the vehicle **10** during a braking event. For example, in

response to detecting the braking event, the suspension controller **86** may provide information (e.g., one or more commands) to the adjustable shock absorbers **18** during the braking event. For instance, the suspension controller **86** may provide information **302** and/or **304** to the front adjustable shock absorbers **18a** and/or **18b** to increase the compression damping (CD) and decrease the rebound damping (RD). Further, the suspension controller **86** may provide information **306** and/or **308** to the rear adjustable shock absorbers **18c** and/or **18d** to increase the rebound damping (RD) and decrease the compression damping (CD). After the suspension controller **86** determines and/or executes a brake condition modifier, the method **400** may move back to step **402** and repeat continuously.

(96) In some examples, in response to detecting the braking event, the suspension controller **86** may adjust the rebound and/or compression damping for the one or more adjustable shock absorbers **18** using the deceleration rate from step **410**. For example, based on comparing the deceleration rate with a threshold, the suspension controller **86** may adjust the rebound and/or compression damping. For instance, if the deceleration rate is above a first threshold (e.g., above two tenths of a G), then the suspension controller **86** may reduce the compression damping of the rear adjustable shock absorbers **18c** and/or **18d**. If the deceleration is below the first threshold, then the suspension controller **86** might not reduce the compression damping (e.g., maintain the current compression damping) of the rear adjustable shock absorbers **18c** and/or **18d**. Additionally, and/or alternatively, if the deceleration rate is above the first threshold (e.g., above two tenths of a G), but below a second threshold (e.g., half of a G), then the suspension controller **86** may reduce the compression damping to a first value. If the deceleration is above the second threshold, then the suspension controller **86** may reduce to a second value that is below the first value (e.g., a softer compression damping value).

(97) In some instances, the suspension controller **86** may separate operation of the braking event and/or cornering event. For example, step **412**, **414**, and **416** may be optional, and the method **400** may move directly to step **418**.

(98) Landing Hop Prevention

(99) FIG. **14** shows an example flowchart describing the operation of the suspension controller **86** during an airborne event and a landing event. FIG. **14** will be described with reference to FIG. **15**. FIG. **15** shows an example graph **525** illustrating the compression and rebound damping characteristics of a vehicle, such as vehicle **10** and/or **200**, during a pre-takeoff period **530**, a free-fall period **535**, and a post-landing period **540**. As will be described in more detail below, by adjusting the compression damping and/or rebound damping of one or more adjustable shock absorbers **18** during a free-fall and/or post-landing event, the suspension controller **86** may increase the stability of vehicle **10** post-landing by preventing the vehicle **10** from hopping, unloading, and/or decreasing the weight on the ground engaging members **12**.

Additionally, and/or alternatively, this may also provide a faster vehicle **10** in a race environment since after a landing event, the throttle may be applied quicker without tire (e.g., ground engaging members **12**) spin. Additionally, and/or alternatively, this may also provide a more stable vehicle because the vehicle **10** will have better traction, and thus better user control.

(100) In operation, at step **502**, the suspension controller **86** may receive information (e.g., inputs) from one or more entities (e.g., sensors, devices, and/or subsystems) of vehicle **10**. For example, the suspension controller **86** may receive (e.g., retrieve and/or obtain) information (e.g., data packets and/or signals indicating sensor readings) from the one or more sensors, devices, and/or subsystems. In some instances, the suspension controller **86** may receive information indicating the x, y, and/or z-axis acceleration from the chassis accelerometer **30** and/or IMU **37**. For example, referring back to FIG. **3**, the chassis accelerometer **30** and/or IMU **37** may measure the x, y, and/or z-axis acceleration values for the vehicle **10**, and may provide the acceleration values to the suspension controller **86**.

(101) At step **506**, the suspension controller **86** may determine whether an airborne event is occurring. For example, the suspension controller **86** may determine whether an airborne event is occurring based on the magnitude of the x-axis acceleration value, the y-axis acceleration value, and/or the z-axis acceleration value. For instance, the suspension controller **86** may compare the x, y, and/or z-axis acceleration values with one or more thresholds (e.g., one or more pre-defined, pre-programmed, and/or user-defined thresholds) to determine whether the vehicle **10** is in free-fall. If the x, y, and/or z-axis acceleration values are less than the one or more thresholds, the method **500** may move to step **508**. If the x, y, and/or z-axis acceleration values are greater than the thresholds, the method **500** may move back to step **502** and repeat.

(102) In some examples, the suspension controller **86** may use two or three different thresholds. For example, the suspension controller **86** may compare the magnitudes for each of the x, y, and/or z-axis acceleration with a different threshold. Additionally, and/or alternatively, the suspension controller **86** may compare the magnitudes for the x and y-axis acceleration with a same threshold. For example, in free-fall, the chassis accelerometer **30** and/or IMU **37** may measure the vehicle **10** to have zero or substantially zero acceleration (e.g., wind, air resistance, and/or other factors may account for substantially zero acceleration) for the x and y-axis, and 1 G or substantially 1 G on the z-axis. As such, the suspension controller **86** may use a first threshold for the x-axis and y-axis acceleration values and a second threshold for the z-axis acceleration value. In some variations, the first threshold for the x-axis and the y-axis may be 0.3 Gs. In some instances, the suspension controller **86** may combine (e.g., calculate) a magnitude of acceleration for the x, y, and z-axis acceleration, and compare the combined magnitude with a threshold to determine whether the vehicle **10** is in free-fall.

(103) Exemplary detection of an airborne event is described in US Published Patent Application No. 2016/0059660 (filed Nov. 6, 2015, titled VEHICLE HAVING SUSPENSION WITH CONTINUOUS DAMPING CONTROL) and US Published Application 2018/0141543 (filed Nov. 17, 2017, titled VEHICLE HAVING ADJUSTABLE SUSPENSION), both assigned to the present assignee and the entire disclosures of each expressly incorporated by reference herein.

(104) At step **508**, the suspension controller **86** may determine an airborne condition modifier for one or more of the adjustable shock absorbers **18**. For example, the suspension controller **86** may provide information (e.g., one or more commands) to the adjustable shock absorbers **18** to increase and/or gradually increase the compression damping. By increasing the adjustable shock absorbers **18**, the vehicle **10** may increase the energy absorption upon landing. Further, the suspension controller **86** may provide information (e.g., one or more commands) to decrease the rebound damping for the adjustable shock absorbers **18**. By decreasing the rebound damping, the adjustable shock absorbers **18** may achieve full shock extension faster, increase energy absorption upon landing, and/or increase the travel of the shocks **18** available for landing. For example, the suspension controller **86** may reduce the rebound damping for the adjustable shock absorbers **18** to zero or substantially zero.

(105) FIG. **15** shows an example of a graph **525** indicating compression and rebound damping characteristics for a vehicle, such as vehicle **10**. The graph **525** is merely one example of a possible compression and rebound damping characteristics set by the suspension controller **86** over different periods of time. Graph **525** shows three periods, a pre-takeoff (e.g., pre-airborne) period **530**, a free-fall period **535**, and a post-landing period **540**. Initially, during the pre-takeoff period, the rebound damping **550** and the compression damping **555** for the adjustable shock absorbers **18** are steady. When an airborne event occurs, the suspension controller **86** gradually increases the compression damping **55** over the free-fall period **535** and decreases the rebound damping **550** to substantially zero. The post-landing period **540** will be discussed below.

(106) Referring back to FIG. **14**, at step **510**, the suspension controller **86** may determine whether a landing event has occurred. For example, similar to step **506**, the suspension controller **86** may determine whether a landing event is occurring based on the magnitude of the x-axis acceleration value, the y-axis acceleration value, and/or the z-axis acceleration value. For instance, the suspension controller **86** may compare the x, y, and/or z-axis acceleration values with one or more thresholds (e.g., one or more pre-defined, pre-programmed, and/or user-defined thresholds) to determine whether the vehicle **10** has landed. If the x, y, and/or z-axis acceleration values are greater than the one or more thresholds, the method **500** may move to step **508**. If the x, y, and/or z-axis acceleration values are less than the thresholds, then step **510** may repeat.

(107) In some examples, the suspension controller **86** may use the same thresholds as in step **506**. For example, as mentioned above, in free-fall, the chassis accelerometer **30** and/or IMU **37** may measure the vehicle **10** to have zero or substantially zero acceleration for the x and y-axis, and 1 G or substantially 1 G on the z-axis. As such, the suspension controller **86** may determine whether a landing event is occurring based on determining whether the acceleration values for the x and/or y-axis is greater than the first threshold (e.g., 0.3 Gs) and/or whether the acceleration values for the z-axis is greater than a second threshold. In some instances, the suspension controller **86** may combine (e.g., calculate) a magnitude of acceleration for the x, y, and z-axis acceleration, and compare the combined magnitude with a threshold

to determine whether the vehicle **10** has landed.

(108) At step **512**, the suspension controller **86** may determine a duration for the airborne event (e.g., a duration that the vehicle **10** is in free-fall). For example, the suspension controller **86** may include a timer, and may use the timer to determine the duration between detecting the airborne event at step **506** and detecting the landing event at step **510**.

(109) At step **514**, the suspension controller **86** may execute a landing condition modifier for one or more of the adjustable shock absorbers **18**. For example, the suspension controller **86** may provide information (e.g., one or more commands) to the adjustable shock absorbers **18** to adjust the compression damping and/or the rebound damping to a post-landing set-point for a period of time. For instance, the suspension controller **86** may increase the rebound damping for a period of time. Also, the suspension controller **86** may maintain the compression damping at the post-landing setting for a period of time. By maintaining the compression damping, the vehicle **10** may be easier able to get through the landing compression stroke of the shock.

(110) At step **516**, the suspension controller **86** may execute a normal condition modifier. For example, the suspension controller **86** may adjust the compression damping and/or rebound damping back to normal (e.g., back to the pre-takeoff position). For example, the suspension controller may decrease and/or gradually decrease the rebound damping back to the normal (e.g., the pre-takeoff rebound damping setting). Further, the suspension controller **86** may decrease the compression damping back to normal (e.g., the pre-takeoff compression damping setting).

(111) In some variations, the suspension controller **86** may adjust the post-landing compression damping settings and/or rebound damping settings based on the duration of the airborne event. Referring back to FIG. **15**, the compression damping **555** is gradually increasing, and increase as the duration of the airborne event increases. As such, during the post-landing period **540**, the suspension controller **86** may maintain an increased compression damping **555** based on the airborne event. Additionally, and/or alternatively, the suspension controller **86** may change the duration to maintain the increased compression damping **555** based on the duration of the airborne event. For example, the vehicle **10** may encounter a small bump (e.g., the airborne event is less than three hundred milliseconds). In such instances, the suspension controller **86** may compare the duration of the airborne event with a threshold (e.g., pre-programmed, pre-defined, and/or user-defined). If the duration of the airborne event is less than the threshold, the suspension controller **86** might not maintain the increased compression damping **555**. Instead, the suspension controller **86** may reduce and/or gradually reduce the compression damping back to the pre-takeoff **530** compression damping **555** in response to detecting the landing event.

(112) In some examples, if the duration of the airborne event is greater than the threshold, the suspension controller **86** may maintain the increased compression damping **555** for a period of time. In some instances, the suspension controller **86** may determine the period of time to maintain the increased compression damping **555** based on the duration of the airborne event (e.g., the longer the duration for the airborne event, the longer the period of time to maintain the increased compression damping **555**).

(113) In response to detecting the landing event (e.g., the start of the post-landing period **540**), the suspension controller **86** may increase the rebound damping **550** based on the duration of the airborne event. For example, traditionally, the vehicle **10** tends to unload the tires (e.g., wheels are light) and/or perform a hop upon landing. To prevent the hop or unloading of the tires, the suspension controller **86** increases the rebound damping **550** for the adjustable shock absorbers **18** based on the duration of the airborne event (e.g., as the duration of the airborne event increases, the rebound damping **550** after landing increases). After a set period of time (e.g., after the vehicle **10** has completed its first shock compression and rebound cycle), the suspension controller **86** decreases and/or gradually decreases the rebound damping **550** back to the pre-takeoff period's **530** rebound damping setting. By increasing the rebound damping **550**, the suspension controller **86** reduces the hop/unloading of the vehicle **10** causing increases in the stability and/or traction on the landing events.

(114) In some examples, the vehicle **10** may encounter a small bump or hill, the vehicle **10** might not perform a hop upon landing or performs a small hop upon landing. In such examples, the suspension controller **86** may adjust the compression and/or rebound damping characteristics based on comparing the duration of the airborne event with a threshold. For example, the suspension controller **86** might not increase the rebound damping **550**, and instead set the rebound damping **550** to the pre-takeoff period's

530 rebound damping setting in response to detecting the landing event.

(115) Additionally, and/or alternatively, based on the duration of the airborne event, the suspension controller **86** may bias the compression damping and/or rebound damping for the front and/or rear adjustable shock absorbers **18**. For example, based on detecting the duration of the airborne event is below a threshold (e.g., the vehicle **10** is encountering a small bump or hill), the suspension controller **86** may additionally increase the rebound damping for the post-landing rebound value for the rear adjustable shock absorbers **18c** and **18d**. Biasing the front/rear shock absorbers **18** in response to detecting the airborne event may increase stability of the vehicle **10** and/or assist the vehicle **10** when traveling through rough terrain.

(116) Rock Crawler Operation

(117) FIG. **16** shows an example flowchart describing the operation of the suspension controller **86** during a rock crawler operation. FIGS. **17-20** show examples of the suspension controller **86** adjusting the adjustable shock absorbers **18** for the vehicle **10** during the rock crawler operation.

(118) By adjusting the compression damping and/or rebound damping of one or more adjustable shock absorbers **18** during the rock crawl operation, the suspension controller **86** may increase vehicle **10** stability when encountering rocks. For example, based on received information (e.g., longitudinal acceleration, lateral acceleration vehicle speed, engine speed, and/or roll angle), the suspension controller **86** may determine the orientation of the vehicle **10** (e.g., whether the vehicle **10** is on flat ground, facing uphill, facing downhill, passenger side facing downhill, and/or driver side facing downhill). Based on the orientation of the vehicle **10**, the suspension controller **86** may adjust the compression and/or rebound damping to lean the vehicle **10** into the hill, and/or rock, causing the vehicle **10** to reduce the overall pitch/roll angle when traversing an obstacle. Further, by adjusting the compression and/or rebound damping when the vehicle **10** is on flat ground, the vehicle **10** has increased ground clearance.

(119) In operation, at step **602**, the suspension controller **86** may receive information (e.g., inputs) from one or more entities (e.g., sensors, devices, and/or subsystems) of vehicle **10**. For example, the suspension controller **86** may receive (e.g., retrieve and/or obtain) information (e.g., data packets and/or signals indicating sensor readings) from the one or more sensors, devices, and/or subsystems. In some instances, the suspension controller **86** may receive longitudinal and/or lateral acceleration rates from a sensor, such as the IMU **37** and/or the chassis accelerometer **30**. In some examples, the suspension controller **86** may receive pitch rate, roll rate, pitch angles, roll angles, and/or yaw rates from a sensor, such as the gyroscope **31**. In some instances, the suspension controller **86** may receive a vehicle speed from a sensor, such as the vehicle speed sensor **26**.

(120) In some examples, the suspension controller **86** may receive information indicating a mode of operation for the vehicle **10**. For example, the suspension controller **86** may receive information indicating the mode of operation from an operator interface **22** and/or another controller (e.g., controller **20**). For instance, the operator interface **22** may receive user input indicating a selection of the rock crawler mode. The operator interface **22** may provide the user input to the suspension controller **86**. The suspension controller **86** may be configured to operate in a rock crawler mode based on the user input.

(121) At step **604**, the suspension controller **86** may determine whether the vehicle **10** is in a rock crawler mode. For example, based on information indicating the mode of operation, the suspension controller **86** may determine whether the vehicle **10** is in the rock crawler mode. If the vehicle **10** is in the rock crawling mode, the method **600** may move to step **606**. If not, the method **600** may move back to step **602**.

(122) At step **606**, the suspension controller **86** may determine whether the vehicle speed is below a threshold. For example, the suspension controller **86** may compare the vehicle speed with a threshold. If the vehicle speed is less than the threshold, then the method **600** may move to step **608**. If not, then the method **600** may move back to step **602**. In other words, the suspension controller **86** may operate in the rock crawler mode and provide rock crawler condition modifiers at low vehicle speeds. At higher vehicle speeds, the suspension controller **86** might not operate in the rocker crawler mode. Instead, at higher vehicle speeds, the suspension controller **86** may operate in a different mode of operation, such as a normal or comfort mode. In some instances, the suspension controller **86** may use the engine speed rather than the vehicle speed to determine whether to operate in the rock crawler mode and/or provide rock crawler condition modifiers.

(123) At step **608**, the suspension controller **86** may determine an orientation of the vehicle **10**. For example, based on the magnitude of the x-axis acceleration value, the y-axis acceleration value, and/or the z-axis acceleration value, the suspension controller **86** may determine a longitudinal acceleration and/or a lateral acceleration of the vehicle **10**. Using the longitudinal and/or lateral acceleration, the suspension controller **86** may determine a roll and/or pitch angle of the vehicle **10**. Then, based on the roll and/or pitch angle of the vehicle, the suspension controller **86** may determine whether the vehicle **10** is on a flat surface, the front of the vehicle **10** facing uphill, the front of the vehicle **10** is facing downhill, the passenger side of the vehicle **10** is facing downhill, and/or the driver side of the vehicle **10** is facing downhill. Additionally, and/or alternatively, the suspension controller **86** may determine the orientation, such as whether the passenger side of the vehicle **10** is facing downhill and/or the driver side of the vehicle **10** is facing downhill, based on the roll rates from the gyroscope **31** and/or the IMU **37**.

(124) At step **610**, the suspension controller **86** may execute a rock crawler condition modifier. For example, based on the orientation of the vehicle **10**, the suspension controller **86** may provide information (e.g., one or more commands) to adjust the compression damping and/or the rebound damping for one or more of the adjustable shock absorbers **18**. In some examples, the suspension controller **86** may increase the compression damping for the downhill adjustable shock absorbers **18**. Additionally, and/or alternatively, the suspension controller **86** may increase the rebound damping and/or decrease the compression damping for the uphill adjustable shock absorbers **18**.

(125) FIGS. **17-20** show examples of the rebound and compression damping characteristics of the adjustable shock absorbers **18** using method **600**. FIG. **17** shows the compression damping and/or rebound damping characteristics of the vehicle **10** on flat ground. For example, at step **608**, the suspension controller **86** may determine the vehicle **10** is on flat ground (e.g., based on the longitudinal acceleration value and/or the lateral acceleration value). Based on the orientation of the vehicle **10**, the suspension controller **86** may provide information (e.g., one or more commands) to adjust the damping characteristics of the vehicle **10**. For instance, the suspension controller **86** may provide information **302**, **304**, **306**, **308** to increase the compression damping and to decrease the rebound damping for the adjustable shock absorber **18a**, **18b**, **18c**, and **18d**. By adjusting the compression damping and rebound damping, the suspension controller **86** may maximize the ground clearance for obstacle avoidance, may avoid full stiff compression when on flat ground to remove unnecessary harshness, and may allow the ground engaging members **12** to fall into holes in the ground more quickly, thus not upsetting the vehicle **10**.

(126) FIG. **18** shows the compression damping and/or rebound damping characteristics of the vehicle **10** when the front of the vehicle **10** is facing downhill. For example, at step **608**, the suspension controller **86** may determine the vehicle **10** is facing downhill (e.g., based on the longitudinal acceleration value and/or lateral acceleration value). Based on the orientation of the vehicle **10**, the suspension controller **86** may provide information (e.g., one or more commands) to adjust the damping characteristics of the vehicle **10**. For instance, the suspension controller **86** may provide information **302** and **304** to increase the compression damping for the adjustable shock absorbers **18a** and **18b** (e.g., the downhill facing shock absorbers). Further, the suspension controller **86** may provide information **306** and **308** to increase the rebound damping and/or decrease the compression damping for the adjustable shock absorber **18c** and **18d** (e.g., the uphill facing shock absorbers).

(127) FIG. **19** shows the compression damping and/or rebound damping characteristics of the vehicle **10** when the front of the vehicle **10** is facing uphill. For example, at step **608**, the suspension controller **86** may determine the vehicle **10** is facing uphill (e.g., based on the longitudinal acceleration value and/or lateral acceleration value). Based on the orientation of the vehicle **10**, the suspension controller **86** may provide information (e.g., one or more commands) to adjust the damping characteristics of the vehicle **10**. For instance, the suspension controller **86** may provide information **302** and **304** to increase the rebound damping and/or decrease the compression damping for the adjustable shock absorbers **18a** and **18b** (e.g., the uphill facing shock absorbers). Further, the suspension controller **86** may provide information **306** and **308** to increase the compression damping for the adjustable shock absorber **18c** and **18d** (e.g., the downhill facing shock absorbers).

(128) FIG. **20** shows the compression damping and/or rebound damping characteristics of the vehicle **10** when the passenger side of the vehicle **10** is facing downhill. For example, at step **608**, the suspension

controller **86** may determine the passenger side of the vehicle **10** is facing downhill (e.g., based on the lateral acceleration value and/or longitudinal acceleration value). Based on the orientation of the vehicle **10**, the suspension controller **86** may provide information (e.g., one or more commands) to adjust the damping characteristics of the vehicle **10**. For instance, the suspension controller **86** may provide information **304** and **308** to increase the compression damping for the adjustable shock absorbers **18b** and **18d** (e.g., the downhill facing shock absorbers). Further, the suspension controller **86** may provide information **302** and **306** to increase the rebound damping and/or decrease the compression damping for the adjustable shock absorber **18a** and **18c** (e.g., the uphill facing shock absorbers).

(129) In some variations, a portion of the vehicle **10**, such as the passenger side of the front of the vehicle **10**, is facing downhill. In other words, the vehicle **10** may be angled so one wheel (e.g., the front right ground engaging member **12b**) is facing downhill and one wheel (e.g., the rear left ground engaging member **12c**) is facing uphill. In such instances, at step **608**, the suspension controller **86** may determine a pitch and roll angle based on the longitudinal and/or lateral acceleration values. Based on the pitch and roll angles, the suspension controller **86** may determine the orientation of the vehicle (e.g., that the front right ground engaging member **12b** is facing). Based on the orientation of the vehicle **10**, the suspension controller **86** may provide information **304** to increase the compression damping for the adjustable shock absorbers **18b** (e.g., the downhill facing shock absorber). Further, the suspension controller **86** may provide information **306** to increase the rebound damping and/or decrease the compression damping for the adjustable shock absorber **18c** (e.g., the uphill facing shock absorber). Additionally, and/or alternatively, based on the angle of the orientation, the suspension controller **86** may provide information **302** to maintain and/or decrease the rebound damping and/or maintain and/or increase the compression damping for the adjustable shock absorber **18a** (e.g., a shock absorber that is neither uphill or downhill). Additionally, and/or alternatively, based on the angle of the orientation, the suspension controller **86** may provide information **308** to decrease the rebound damping and/or maintain the compression damping for the adjustable shock absorber **18d** (e.g., a shock absorber that is neither uphill or downhill).

(130) In some instances, when the vehicle **10** is in the rock crawler mode, the suspension controller **86** may increase, decrease, and/or maintain the compression and/or rebound damping as shown in FIG. **17**. Further, in response to determining the orientation of the vehicle **10** (e.g., step **608**), the suspension controller **86** may additionally increase and/or decrease the compression and/or rebound damping as shown in FIGS. **18-20**. In other words, in such instances, the increasing, decreasing, and/or maintain of the compression/rebound damping as shown in FIGS. **18-20** are based off of the compression/rebound damping from FIG. **17**.

(131) Hill (Dune) Sliding Operation

(132) FIG. **21** shows an example flowchart describing the operation of the suspension controller **86** during a hill sliding event. FIGS. **22** and **23** show examples of the suspension controller **86** adjusting the adjustable shock absorbers **18** for the vehicle **10** during the hill sliding event. By adjusting the damping during an front uphill sliding event, the vehicle **10** may lean better into the hill or dune, hold onto a steeper slope better, and/or provide a smoother ride (e.g., less chop) to the user when traversing the hill or dune. By adjusting the damping during a front downhill sliding event, the vehicle **10** may lean better into the hill or dune, increase vehicle stability, and/or make it easier to traverse back uphill. A hill sliding event is any event where the vehicle **10** is traversing a slope (e.g., hill, dune, ramp) and begins to slide in at least one direction.

(133) In operation, at step **652**, the suspension controller **86** may receive steering information from one or more sensors, such as the steering sensor **28**. The steering information may indicate a steering position (e.g., steering angle) of a steering wheel, such as steering wheel **226**. The steering position and/or angle may indicate a position and/or an angle of the steering wheel for the vehicle **10**. The steering rate may indicate a change of the position and/or angle of the steering wheel over a period of time.

(134) At step **654**, the suspension controller **86** may receive yaw rate information from one or more sensors, such as the gyroscope **31** and/or the IMU **37**. The yaw information indicates the yaw rate of the vehicle **10**.

(135) At step **656**, the suspension controller **86** may receive acceleration information indicating an acceleration rate or deceleration rate of the vehicle **10** from one or more sensors, such as the IMU **37** and/or the chassis accelerometer **30**. The acceleration information may indicate multi-axis acceleration

values of the vehicle, such as a longitudinal acceleration and/or a lateral acceleration. In some examples, the suspension controller **86** may receive information from another sensor, such as the throttle position sensor **34** and/or the accelerator pedal sensor **33**. The suspension controller **86** use the information to determine the acceleration rate. For example, the suspension controller **86** may use the throttle position from the throttle position sensor and/or the position of the accelerator pedal **230** from the acceleration pedal sensor to determine whether the vehicle **10** is accelerating and/or decelerating.

(136) At step **658**, the suspension controller **86** may receive an operating mode of the vehicle **10** from the operator interface **22** and/or one or more other controllers (e.g., controller **20**). Each mode may include a different setting for the rebound and/or compression damping. An operator (e.g., user) may input a mode of operation on the operator interface **22**. The operator interface **22** may provide the user input indicating the mode of operation to the controller **20** and/or the suspension controller **86**. The suspension controller **86** may use the user input to determine the mode of operation for the vehicle **10**.

(137) At step **660**, the suspension controller **86** may determine whether a hill sliding event (e.g., whether the vehicle **10** is sliding while traversing a slope) is occurring. For example, the suspension controller **86** may determine the hill sliding event based on the steering information indicating a steering rate, angle, and/or position, yaw rate information indicating a yaw rate, the acceleration information indicating a lateral and/or longitudinal acceleration, and/or other information (e.g., a pitch angle or rate). The suspension controller **86** may compare the steering rate, steering angle, steering position, yaw rate, lateral acceleration, and/or longitudinal acceleration with one or more thresholds (e.g., pre-determined, pre-programmed, and/or user-defined) to determine the hill sliding event. If the suspension controller **86** determines the vehicle **10** is in a hill sliding event, the method **650** may move to step **662**. If not, the method may move to step **652**.

(138) In some instances, the detection of the hill sliding event may be similar to the detection of the cornering event. Further, the commands to adjust the damping of the shock absorbers **18** based on the detection of the hill sliding event may be similar to the cornering event. For example, the suspension controller **86** may prioritize the steering information, the yaw rate information, and/or the acceleration information to determine the hill sliding event. In other words, the steering position and/or angle, steering rate, yaw rate, and/or lateral acceleration may conflict, and the suspension controller **86** may prioritize the lateral acceleration over the steering position, angle, rate and/or the yaw rate. For example, the suspension controller **86** may determine the hill sliding event is occurring based on the lateral acceleration value exceeding (e.g., above or below) a lateral acceleration threshold even if the yaw rate, steering rate, angle, and/or position do not exceed their corresponding thresholds.

(139) In some examples, the suspension controller **86** may use a vehicle speed and/or an engine speed to determine whether the vehicle **10** is in a hill sliding event. For example, the suspension controller **86** may compare the vehicle speed and/or the engine speed with a threshold. If the suspension controller **86** determines the vehicle speed and/or engine speed is greater than a threshold (e.g., the vehicle **10** is traveling at a high vehicle speed), then the method **650** may move to **662**. Otherwise, the method **650** may move back to **652**. In other words, the suspension controller **86** may execute the hill sliding condition modifier when the vehicle is moving at a high vehicle speed.

(140) At step **662**, the suspension controller **86** may determine a direction of the slide. For example, based on the lateral acceleration, the suspension controller **86** may determine whether the vehicle **10** is hill sliding to the left side or the right side.

(141) At step **664**, the suspension controller **86** may determine an orientation of the vehicle **10**. For example, similar to step **608**, based on the longitudinal and/or lateral acceleration, the suspension controller **86** may determine whether the front of the vehicle **10** is facing uphill, the front of the vehicle **10** is facing downhill, the passenger side of the vehicle **10** is facing downhill, and/or the driver side of the vehicle **10** is facing downhill.

(142) At step **666**, the suspension controller **86** may execute a hill sliding condition modifier. For example, based on the direction of the slide and/or the orientation of the vehicle **10**, the suspension controller **86** may provide information (e.g., one or more commands) to adjust the compression damping and/or the rebound damping for the one or more shock absorbers **18**. For example, based on the direction of the slide, the suspension controller **86** may increase the compression damping and/or decrease the rebound damping on the leading adjustable shock absorbers **18**. Additionally, and/or alternatively, the

suspension controller **86** may decrease the compression damping and/or increase the rebound damping on the trailing adjustable shock absorbers **18**. Also, based on the orientation (e.g., the front of the vehicle **10** facing uphill and/or downhill), the suspension controller **86** may further bias the compression damping and/or rebound damping for the front and rear shock absorbers **18**. In other words, the suspension controller **86** may additionally increase the compression damping on the downhill adjustable shock absorbers **18**. Additionally, and/or alternatively, the suspension controller **86** may additionally decrease the compression damping and/or additionally increase the rebound damping of the uphill shock absorbers **18**. Afterwards, the method **650** may move back to step **652**. FIGS. **22** and **23** will describe the hill condition modifier in further detail.

(143) FIG. **22** shows the vehicle **10** traveling uphill and in a left pointed slide. For example, the suspension controller **86** may determine that the vehicle **10** is traveling uphill **670** and sliding left **672** based on the lateral and/or longitudinal acceleration. The suspension controller **86** may adjust the compression and/or rebound damping characteristics for a left pointed slide **672** similar to a right turn during a cornering event. In other words, the suspension controller **86** may increase the compression damping and/or decrease the rebound damping for the leading shock absorbers **18a** and **18c** (e.g., the outside shock absorbers). Further, the suspension controller **86** may decrease the compression damping and/or increase the rebound damping for the leading shock absorbers **18b** and **18d** (e.g., the inside shock absorbers). For a right pointed slide, the suspension controller **86** may reverse the compression damping and/or rebound damping for the shock absorbers (e.g., decrease the compression damping and/or increase the rebound damping for the shock absorbers **18a** and **18c**; increase the compression damping and/or decrease the rebound damping for shock absorbers **18b** and **18d**).

(144) Additionally, and/or alternatively, the suspension controller **86** may bias the front and/or rear adjustable shock absorbers **18** for the uphill orientation **670** similar to detecting an acceleration during a cornering event. For example, based on the uphill orientation of the vehicle **10**, the suspension controller **86** may additionally increase (e.g., by a value or percentage) the compression damping and/or additionally decrease (e.g., by a value or a percentage) the rebound damping of rear adjustable shock absorbers **18c** and **18d** (e.g., the downhill shock absorbers). Further, the suspension controller **86** may additionally decrease the compression damping and/or additionally increase the rebound damping of the front adjustable shock absorbers **18a** and **18b** (e.g., the uphill shock absorbers).

(145) After determining the slide **672** and the orientation **670** of the vehicle, the suspension controller **86** may provide information (e.g., one or more commands) to adjust the shock absorbers **18**. For example, in an uphill **670** and left pointed slide **672**, the suspension controller **86** may provide information **302** to maintain or decrease the rebound damping and/or maintain or increase the compression damping for the adjustable shock absorber **18a**. Further, the suspension controller **86** may provide information **304** to increase the rebound damping and/or decrease the compression damping for the adjustable shock absorber **18b**. Also, the suspension controller **86** may provide information **306** to increase the compression damping and/or to decrease the rebound damping for the adjustable shock absorber **18c**. Additionally, the suspension controller **86** may provide information **308** to maintain or decrease the compression damping and/or increase the rebound damping for the adjustable shock absorber **18d**.

(146) FIG. **23** shows the vehicle **10** traveling downhill and in a right pointed slide. For example, the suspension controller **86** may determine that the vehicle **10** is traveling downhill **674** and sliding right **676** based on the lateral and/or longitudinal acceleration. The suspension controller **86** may adjust the compression and/or rebound damping characteristics for a right pointed slide **676** similar to a left turn during a cornering event. In other words, the suspension controller **86** may increase the compression damping and/or decrease the rebound damping for the leading shock absorbers **18b** and **18d** (e.g., the outside shock absorbers). Further, the suspension controller **86** may decrease the compression damping and/or increase the rebound damping for the trailing shock absorbers **18a** and **18c** (e.g., the inside shock absorbers). The left pointed slide **672** is described above.

(147) Additionally, and/or alternatively, the suspension controller **86** may bias the front and/or rear adjustable shock absorbers **18** for the downhill orientation **674** similar to detecting a deceleration (e.g., braking) during a cornering event. For example, based on the downhill orientation of the vehicle **10**, the suspension controller **86** may additionally increase (e.g., by a value or percentage) the compression damping and/or additionally decrease (e.g., by a value or a percentage) the rebound damping of front

adjustable shock absorbers **18a** and **18b** (e.g., the downhill shock absorbers). Further, the suspension controller **86** may additionally decrease the compression damping and/or additionally increase the rebound damping of the rear adjustable shock absorbers **18c** and **18d** (e.g., the uphill shock absorbers). (148) After determining the slide and the orientation of the vehicle **10**, the suspension controller **86** may provide information (e.g., one or more commands) to adjust the shock absorbers **18**. For example, in a downhill orientation **674** and right pointed slide **676**, the suspension controller **86** may provide information **302** to decrease or maintain the compression damping and/or increase or maintain the rebound damping for the adjustable shock absorber **18a**. Further, the suspension controller **86** may provide information **304** to increase the compression damping and/or decrease the rebound damping for the adjustable shock absorber **18b**. Also, the suspension controller **86** may provide information **306** to decrease the compression damping and/or to increase the rebound damping for the adjustable shock absorber **18c**. Additionally, the suspension controller **86** may provide information **308** to maintain or increase the compression damping and/or decrease or maintain the rebound damping for the adjustable shock absorber **18d**.

(149) Realtime Correction of Inertial measurement at a Center of Gravity of a Vehicle

(150) FIG. **24** shows an exemplary flowchart illustrating a method for performing real-time correction of the inertial measurement of a vehicle. For example, the IMU **37**, the gyroscope **31**, and/or the chassis accelerometer **30** may measure the inertial measurements of the vehicle **10** (e.g., the acceleration and/or angular velocity or rate of the vehicle **10**). In some examples, these sensors might not be at the center of gravity (CG) of the vehicle **10**, and a kinematic transformation may be used to account for the sensors not being at the CG. For example, a controller, such as the suspension controller **86**, may use a distance between a sensor (e.g., the IMU **37**, the gyroscope **31**, and/or the chassis accelerometer **30**) and the CG of the vehicle **10** to determine offset correction information. Using the offset correction information, the suspension controller **86** may transform (e.g., determine and/or calculate) the measured acceleration values to CG acceleration values (e.g., an estimated CG acceleration). Additionally, and/or alternatively, the CG of the vehicle **10** may also be affected by the number of users and/or the cargo. For example, a driver and a passenger may change the CG of the vehicle **10**. As such, the suspension controller **86** may receive user and/or cargo information, and use the user and/or cargo information to determine second offset correction information. The suspension controller **86** may use the first and/or second offset corrections to determine the CG acceleration values.

(151) By providing real-time correction of the inertial measurement of the vehicle **10**, the suspension controller **86** may allow for the IMU **37** and/or other sensors to reside at a location other than the CG of the vehicle **10** while still providing an accurate vehicle inertial measurement estimation for controls. Additionally, and/or alternatively, the suspension controller **86** may allow for a more accurate estimation given the additional information regarding the weight (e.g., riders) and/or location of the weight (e.g., location of the riders) of the vehicle **10**. FIG. **24** will be described below with reference to FIG. **25**.

(152) FIG. **25** shows a schematic block diagram illustrating an example of logic components in the suspension controller **86**. For example, the suspension controller **86** includes one or more logic components, such as an acceleration and/or velocity measurement logic **720**, angular acceleration logic **722**, angular acceleration calculation logic **724**, kinematics function logic **726**, estimated acceleration at center of gravity (CG) logic **728**, offset correction based on user or cargo information logic **730**, and/or offset correction based on sensor information logic **732**. The logic **720**, **722**, **724**, **726**, **728**, **730**, and/or **732** is any suitable logic configuration including, but not limited to, one or more state machines, processors that execute kernels, and/or other suitable structure as desired.

(153) Further, in some examples, the suspension controller **86** and/or the controller **20** may include memory and one or more processors. The memory may store computer-executable instructions that when executed by the one or more processors cause the processors to implement the method and procedures discussed herein, including the method **700**. Additionally, various components (e.g., logic) depicted in FIG. **25** are, in embodiments, integrated with various ones of the other components depicted therein (and/or components not illustrated), all of which are considered to be within the ambit of the present disclosure.

(154) In operation, at step **702**, the suspension controller **86** (e.g., logic **720**) may receive vehicle movement information from one or more entities (e.g., sensors, devices, and/or subsystems) of vehicle **10**.

For example, the suspension controller **86** may receive vehicle movement information indicating the acceleration and/or velocity of the vehicle **10** from one or more sensors. For instance, the logic **720** may receive x, y, and/or z acceleration values (e.g., linear acceleration values) from a sensor, such as the IMU **37** and/or the chassis accelerometer **30**. The logic **720** may also receive x, y, and/or z angular velocity values from a sensor, such as the IMU **37** and/or the gyroscope **31**.

(155) At step **704**, the suspension controller **86** (e.g., logic **730**) may receive user or cargo information from one or more entities (e.g., sensors, devices, and/or subsystems) of vehicle **10**. In some instances, the suspension controller **86** may receive user or cargo information from the operator interface **22**. For example, the operator interface **22** may provide, to the suspension controller **86**, user information indicating a number of riders in the vehicle **10** and/or a weight or mass corresponding to the riders in the vehicle **10**. Additionally, and/or alternatively, the operator interface **22** may provide, to the suspension controller **86**, cargo information indicating a weight or mass of cargo that the vehicle **10** is carrying.

(156) In some examples, the suspension controller **86** may receive the user or cargo information from one or more sensors. For example, one or more sensors, such as seat belt sensors, may provide, to the suspension controller **86**, information indicating the number of riders in the vehicle **10** (e.g., when a user puts on their seat belt, the seat belt sensor may provide information indicating the seat belt is engaged to the suspension controller **86**).

(157) At step **706**, the suspension controller **86** (e.g., the logic **722** and/or **724**) may determine the angular acceleration for the vehicle **10**. For example, the logic **722** may filter the angular velocity and/or rates received from a sensor, such as the IMU **37** and/or gyroscope **31**. The logic **724** may differentiate the angular rates to determine the angular acceleration.

(158) At step **708**, the suspension controller **86** (e.g., the logic **732**) may determine a first offset correction based on a distance between a sensor (e.g., the IMU **37**, the chassis accelerometer **30**, and/or the gyroscope **31**) and the CG of the vehicle **10**. The CG of the vehicle **10** may be pre-programmed and/or pre-defined. Additionally, and/or alternatively, the suspension controller **86** (e.g., the logic **732**) may determine the first offset correction based on a distance between a sensor (e.g., the IMU **37**, the chassis accelerometer **30**, and/or the gyroscope **31**) and the suspension controller **86**.

(159) At step **710**, the suspension controller **86** (e.g., the logic **730**) may determine a second offset correction based on the user and/or cargo information received at step **704**. For example, based on the number of users, weight/mass of users, and/or weight/mass of the cargo, the logic **730** may determine a second offset correction.

(160) At step **712**, the suspension controller **86** (e.g., the logic **726** and/or **728**) may determine an estimated acceleration at the CG of the vehicle **10**. For example, the logic **726** may receive information from the logic **720** (e.g., the linear acceleration values), the logic **724** (e.g., the determined angular acceleration values), the logic **730** (e.g., the second offset based on the user or cargo information), and/or the logic **732** (e.g., the first offset based on the sensor information). The logic **726** may use a kinematics function to determine the 3-axis estimated acceleration at the CG of the vehicle **10**. The logic **726** may provide the 3-axis estimated acceleration at the CG of the vehicle **10** to the logic **728**. Then, the method **700** may return to step **702**, and may repeat continuously.

(161) In some examples, the logic **726** may receive and/or store the 3-axis (e.g., x, y, and/or z-axis) estimated acceleration values at the CG of the vehicle **10**. Additionally, and/or alternatively, the methods **400**, **500**, and/or **700** may use the determined estimated acceleration values at the CG of the vehicle **10** to execute corner condition modifiers (e.g., step **418**), brake condition modifiers (e.g., step **412**), landing condition modifiers (e.g., step **415**), and/or sand dune condition modifiers (e.g., step **608**). For example, the suspension controller **86** may use the estimated acceleration values at the CG of the vehicle **10** to determine and/or detect events (e.g., cornering events, braking events, landing events, airborne events). Additionally, and/or alternatively, the suspension controller **86** may use the estimated acceleration values at the CG of the vehicle **10** to adjust the compression damping and/or rebound damping of the adjustable shock absorbers **18**.

(162) Changing Drive Modes, Active Vehicle Events, and Suspension Controller Architecture

(163) FIG. **26** shows an exemplary flowchart describing the operation of the suspension controller **86** when switching between driver modes. For example, an operator may use the operator interface **22** (e.g., a touch screen) and/or a physical switch to adjust the driving modes. For instance, each driving mode may

indicate a different compression and/or rebound damping setting. As will be explained below, the suspension controller **86** may receive one or more user inputs, and based on the user inputs may change the driving modes. In response to changing the driving modes, the suspension controller **86** may provide one or more commands to adjust the compression and/or rebound damping for the adjustable shock absorbers **18**. FIG. **26** will be described with reference to FIGS. **27** and **28** below.

(164) FIG. **27** shows an exemplary physical switch **820** for adjusting driving modes. In some examples, the physical switch **820** may be located on a steering wheel, such as the steering wheel **226**. The physical switch **820** may be operatively coupled to and/or communicate with the suspension controller **86**. For example, the suspension controller **86** may receive user input from the physical switch **820**. The switch **820** may include an increase mode (+) button **822** (e.g., a first mode changing input device), a decrease mode (−) button **824** (e.g., a second mode changing input device), and/or an instant compression switch **826**. When actuated and/or pressed by a user, the instant compression switch **826** may provide information to the suspension controller **86**. Based on the information from the instant compression switch **826**, the suspension controller **86** may provide momentary stiffness to the adjustable shock absorbers **18**. In other words, the suspension controller **86** may increase and/or significantly increase the compression damping of the adjustable shock absorbers **18** for a brief time duration.

(165) FIG. **28** shows an exemplary graphical user interface **830**. The graphical user interface **830** may be displayed on an interface, such as the operator interface **22**. For example, the suspension controller **86** may cause display of the graphical user interface **830** on the operator interface **22**. The graphical user interface **830** may include one or more modes, such as a first driver mode **832**, a second driver mode **834**, a third driver mode **836**, and/or a fourth driver mode **838**. The graphical user interface **830** is merely exemplary, and the suspension controller **86** may include multiple driver modes, including more or less than four driver modes. As will be explained below, the suspension controller **86** may receive multiple user inputs, and may adjust the compression and/or rebound damping characteristics based on the number of received user inputs. Exemplarily driving modes may include, but are not limited to, a comfort mode, a rough trial mode, a handling mode, and/or a rock crawl mode.

(166) In operation, at step **802**, the suspension controller **86** may determine whether it has received a first user input from the physical switch **820**. For example, a user may press (e.g., actuate) the increase mode (+) button **822** and/or the decrease mode (−) button **824**. The physical switch **820** may provide information indicating the actuation of the increase mode (+) button **822** and/or the decrease mode (−) button **824**. If the suspension controller **86** has received a first user input, then the method **800** may move to step **804**. If not, then the method **800** may remain at step **802**.

(167) At step **804**, the suspension controller **86** may cause display of the driving modes on an operator interface, such as operator interface **22**. For example, based on receiving the first user input from the physical switch **820**, the suspension controller **86** may cause display of the graphical user interface **830** on the operator interface **22**. Additionally, and/or alternatively, the graphical user interface **830** may indicate a current selected driver mode.

(168) At step **806**, the suspension controller **86** may determine whether it has received a new user input. For example, initially, when the suspension controller **86** receives the first user input, the suspension controller **86** might not change the current driving mode, such as the second driver mode **834**. Instead, the suspension controller **86** may change the current driving mode if it receives two or more user inputs (e.g., the first user input and one or more new user inputs). For example, at step **802**, the suspension controller **86** may receive a first user input indicating an actuation of the increase mode (+) button **822** and/or the decrease mode (−) button **824**. At step **806**, the suspension controller **86** may receive a new user input indicating a second actuation of the increase mode (+) button **822** and/or the decrease mode (−) button **824**.

(169) At step **808**, based on the new user input, the suspension controller **86** may change the requested driving mode. For example, after receiving the new user input (e.g., a second actuation of button **822** and/or button **824**), the suspension controller **86** may change the requested driving mode to a higher or lower driving mode. For instance, if the current driving mode is the second driver mode **834** and the suspension controller **86** receives an activation of button **822** at step **806**, the suspension controller **86** may change the requested driving mode to the third driver mode **836**. If the suspension controller **86** receives an activation of button **824**, the suspension controller **86** may change the requested driving mode

The first driver mode **832**. The method **800** may move back to step **806**, and repeat. In the next iteration, the suspension controller **86** may receive another new user input (e.g., a third actuation of the button **822** and/or button **824**). At step **808**, the suspension controller **86** may change the requested driving mode again based on whether button **822** or button **824** was actuated.

(170) In some instances, prior to changing the driving modes and/or adjusting the adjustable shock absorbers **18**, the suspension controller **86** may determine whether an event described above, such as a cornering event, a braking event, an airborne event, and/or a landing event, is occurring. If the suspension controller **86** determines an event is occurring, the suspension controller **86** may delay and/or not change the active driving mode until the event has ended. For example, if the requested driving mode is the second driver mode **834** and an event occurs, the suspension controller **86** may delay and/or not change to the active driver mode (e.g., the second driver mode **834**) until the event ends.

(171) Referring back to step **806**, if the suspension controller **86** does not receive a new input, the method **800** may move to step **810**. At step **810**, the suspension controller **86** may determine whether the amount of time that it has not received a new user input exceeds a timer, such as three seconds. If it has not exceeded the timer, then the method **800** may move back to **806**. If it has exceeded the timer, then the method may move to step **802**, and repeat. In other words, after a period of time (e.g., 3 seconds), the change driving mode feature may time out, and the user may need to provide another first input to begin the process again of switching driver modes.

(172) In some examples, the suspension controller **86** may include a wall for the highest and lowest driving modes (e.g., the first driver mode **832** and fourth driver mode **838**). For example, if the current driving mode is the second driver mode **834** and the suspension controller **86** receives more than two user inputs, the suspension controller **86** may change the requested driving mode to the highest driving mode, such as the fourth driver mode **838**, and remain at the highest driving mode regardless of additional user inputs. In other words, even if a user actuates the increase mode (+) button **822** ten times, the suspension controller **86** may continue to select the highest driving mode (e.g., the further driver mode **838**).

(173) In some examples, the controller **20** may include a steering controller **102** (e.g., a power steering controller). The steering controller **102** may include a plurality of power steering modes for the vehicle **10**. Based on the method **800**, the suspension controller **86** may determine a driving mode (e.g., a suspension mode and/or a power steering mode) as described above. The suspension controller **86** may adjust the adjustable shock absorbers **18** based on the driving mode. Additionally, and/or alternatively, the suspension controller **86** may provide the driving mode (e.g., the power steering mode) to the steering controller **102**. The steering controller **102** may change the power steering characteristics based on the received driving mode from the suspension controller **86**. In some instances, each suspension mode corresponds to one or more power steering modes. As such, by the operator selecting a suspension mode (e.g., using method **800**), the operator may also select a corresponding power steering mode. Thus, the suspension controller **86** may provide the selected driving mode to the steering controller **102**, and the steering controller **102** may implement the power steering mode characteristics.

(174) Push and Pull Instant Compression Button Activation

(175) The vehicle **10** may include a sensor on the steering shaft (e.g., a shaft connecting the steering wheel, such as steering wheel **226**, to the vehicle frame). The sensor, such as a strain gauge or a spring-loaded contact sensor, may detect a force (e.g., a push or pull) on the steering wheel **226**. The sensor may be operatively coupled to and/or communicate with the suspension controller **86**, and may provide information indicating the push or pull on the steering wheel **226** to the suspension controller **86**.

(176) The suspension controller **86** may receive the information indicating the push or pull (e.g., the force exerted on the steering wheel **226**), and compare the force exerted on the steering with a threshold. Based on the comparison, the suspension controller **86** may provide one or more commands to momentarily increase the compression damping (e.g., set the compression damping to a stiff damping level) for the adjustable shock absorbers **18**. In other words, instead of using a button, such as the instant compression switch **826** shown on FIG. 27, an operator may push or pull the steering wheel **226** to cause a momentary stiff compression damping for the adjustable shock absorbers **18**.

(177) Egress Aid

(178) FIG. 29 shows an exemplary flowchart describing a method for implementing egress aid for a vehicle. For example, an operator may seek to exit the vehicle, such as vehicle **10**. In such examples, the

suspension controller **86** may reduce the damping (e.g., the compression damping) for the adjustable shock absorbers **18**, causing the vehicle **10** to lower in height. By lowering the vehicle height, the operator may more easily exit the vehicle **10**.

(179) In operation, at step **902**, the suspension controller **86** may receive information (e.g., inputs) from one or more entities (e.g., sensors, devices, and/or subsystems) of vehicle **10**. For example, the suspension controller **86** may receive (e.g., retrieve and/or obtain) information (e.g., data packets and/or signals indicating sensor readings) from the one or more sensors, devices, and/or subsystems.

(180) At step **904**, the suspension controller **86** may determine whether the operator is going to (e.g., intending to) exit the vehicle **10**. For example, the suspension controller **86** may receive, from the gear selection sensor **38**, information indicating the vehicle has shifted to park. Based on the information, the suspension controller **86** may determine the operator is intending to exit the vehicle **10** and the method **900** may move to step **906**. If not, the method **900** may move to step **902**.

(181) In some instances, the suspension controller **86** may determine the operator is intending to exit the vehicle based on the engine speed. For example, the suspension controller **86** may receive information indicating the engine speed is zero or substantially zero. As such, the suspension controller **86** may determine the operator is intending to exit the vehicle. In some examples, the suspension controller **86** may determine the operator is intending to exit the vehicle based on information indicating a vehicle key in the off position and/or a vehicle speed (e.g., from the vehicle speed sensor **26**).

(182) In some variations, the suspension controller **86** may receive information indicating the vehicle **10** is operating in the rock crawling mode described above. In the rock crawling mode, the vehicle speed may be low and/or substantially zero and/or may be over a rock. As such, based on the vehicle **10** operating in the rock crawling mode, the suspension controller **86** may determine to deactivate the egress aid (e.g., to not cause the vehicle **10** to become stuck), and the method **900** may move back to step **902**.

(183) At step **906**, the suspension controller **86** may adjust the compression damping of the adjustable shock absorbers **18**. For example, the suspension controller **86** may reduce the compression damping of the adjustable shock absorbers **18**. By reducing the compression damping, the vehicle **10** may provide egress aid to the operator (e.g., based on lowering the height of the vehicle **10**).

(184) Sway Bar

(185) FIG. **30** illustrates a representative view of a sway bar of a vehicle, such as vehicle **10**. For example, the vehicle **10** may include a sway bar **1005**. Further, the sway bar **1005** may include one or more sway bar adjustable shock absorbers **1010**. The sway bar adjustable shock absorber **1010** may be coupled to the sway bar **1005** and a steering bar **1015**. The sway bar **1005** may be in the rear of the vehicle, and located close to a rear adjustable shock absorber, such as shock absorber **18c**. Further, the vehicle **10** may include more than one sway bar **1005** and/or sway bar adjustable shock absorber **1010**. For example, on the other side of the vehicle **10** (e.g., the side with the adjustable shock absorber **18d**), the vehicle **10** may include a second sway bar **1005** and/or a second sway bar adjustable shock absorber **1010**.

(186) Also, similar to the adjustable shock absorbers **18**, the suspension controller **86** may provide one or more commands to adjust the damping characteristics of the sway bar adjustable shock absorbers **1010**. For example, referring to FIG. **11**, in response to detecting a cornering event, the suspension controller **86** may provide one or more commands to increase and/or engage the compression damping for the sway bar adjustable shock absorbers **1010**. Additionally, and/or alternatively, the suspension controller **86** may provide different damping characteristics based on the driving modes. For instance, in some driving modes, the suspension controller **86** may increase and/or engage the compression damping for the sway bar adjustable shock absorbers **1010** in response to detecting events. In other driving modes, the suspension controller **86** might not increase nor engage the compression damping for the sway bar adjustable shock absorbers **1010** in response to detecting events. For example, referring to FIG. **26**, based on changing the driving modes, the suspension controller **86** may provide one or more commands to adjust the compression and/or rebound damping for the sway bar adjustable shock absorbers **1010**.

(187) Exemplary sway bars are described in U.S. Pat. No. 9,365,251 (filed Jun. 14, 2016, titled Side-by-side vehicle), which is assigned to the present assignee and the entire disclosure is expressly incorporated by reference herein.

(188) FIG. **31** illustrates a view of an exemplary vehicle **1100**, such as a snowmobile. Vehicle **1100**, as illustrated, includes a plurality of ground engaging members **12**. Illustratively, the ground engaging

members **12** are the endless track assembly **1108** and a pair of front skis **1112a** and **1112b**. The endless track assembly **1108** is operatively coupled to power system **60** (see FIG. **4**) to power the movement of vehicle **1100**. The vehicle may also include a seat **1102** and a seat surface **1104**. Also, the vehicle may include handlebars **1106**.

(189) Further, the suspensions **1114** and **1116** are coupled to the frame of the vehicle **1100** and the pair of front skis **1112a** and **1112b**. The suspensions **1114** and **1116** may include adjustable shock absorbers, such as the adjustable shock absorber **1110**. Also, the endless track assembly **1108** may also be coupled to one or more suspensions and/or adjustable shock absorbers.

(190) The vehicle **1100** may be the same and/or include components of vehicle **10**. For example, the vehicle **1100** may include the plurality of vehicle condition sensors **40** described above, and may also include one or more controllers, such as the suspension controller **86**. The suspension controller **86** may receive information from the plurality of vehicle condition sensors **40**. Using the received information, the suspension controller **86** may adjust the compression and/or rebound damping of the adjustable shock absorbers, such as adjustable shock absorber **1110** as described above. Additional details regarding vehicle **1100** are provided in U.S. Pat. Nos. 9,809,195 and 8,994,494, assigned to the present assignee, the entire disclosures of which are expressly incorporated by reference herein.

(191) In embodiments, substantially zero is any value which is effectively zero. For example, a substantially zero value does not provide an appreciable difference in the operation compared to when the value is zero.

(192) The above detailed description of the present disclosure and the examples described therein have been presented for the purposes of illustration and description only and not by limitation. It is therefore contemplated that the present disclosure covers any and all modifications, variations or equivalents that fall within the scope of the basic underlying principles disclosed above and claimed herein.

Claims

1. A recreational vehicle, comprising: a plurality of ground engaging members; a frame supported by the plurality of ground engaging members; a plurality of suspensions, wherein each of the plurality of suspensions couples a ground engaging member, from the plurality of ground engaging members, to the frame, wherein the plurality of suspensions includes a plurality of adjustable shock absorbers; at least one sensor positioned on the recreational vehicle and configured to provide sensor information to a controller, the at least one sensor comprises an acceleration sensor and the sensor information comprises acceleration information indicating a lateral acceleration value; and the controller operatively coupled to the at least one sensor and the plurality of adjustable shock absorbers, wherein the controller is configured to: receive, from the at least one sensor, the sensor information; determine, based on a comparison of the lateral acceleration value to a first threshold, a cornering event corresponding to the recreational vehicle executing a turn; and provide, to at least one of the plurality of adjustable shock absorbers and based on the determining of the cornering event, one or more commands to result in a decrease of a damping characteristic of the at least one of the plurality of adjustable shock absorbers.
2. The recreational vehicle of claim 1, wherein the controller is further configured to: determine, based on the sensor information, a direction of the turn corresponding to the cornering event; determining, based on the direction of the turn, at least one inner adjustable shock absorber of the plurality of adjustable shock absorbers, and wherein the controller is configured to provide the one or more commands by providing, to the at least one inner adjustable shock absorber, one or more commands to result in a decrease of a compression damping characteristic and an increase of a rebound damping characteristic.
3. The recreational vehicle of claim 2, wherein the controller is further configured to: determine, based on the direction of the turn, at least one outer adjustable shock absorber of the plurality of adjustable shock absorbers, and wherein the controller is configured to provide the one or more commands by providing, to the at least one outer adjustable shock absorber one or more commands to result in a decrease of a rebound damping characteristic and an increase of a compression damping characteristic.
4. The recreational vehicle of claim 1, wherein: the sensor information further comprises yaw rate information indicating a yaw rate; and the controller is further configured to determine the cornering event by determining that the recreational vehicle is turning based on comparing the yaw rate to a second

threshold.

5. The recreational vehicle of claim 4, wherein: the at least one sensor further comprises a steering sensor; the sensor information further comprises steering information indicating a steering position or a steering rate corresponding to a steering wheel; and the controller is configured to determine the cornering event by determining that the recreational vehicle is turning based on comparing the steering position to a third threshold.

6. The recreational vehicle of claim 1, wherein the sensor information comprises yaw rate information indicating a yaw rate and steering information indicating a steering position or a steering rate, and wherein the controller is further configured to: prioritize the yaw rate information over the steering information such that the controller is configured to determine the vehicle is executing the turn in a first direction based on the yaw rate indicating the turn in the first direction and even if the steering position or the steering rate indicates the turn in a second direction or does not indicate the turn.

7. The recreational vehicle of claim 1, wherein the sensor information comprises acceleration information indicating a lateral acceleration value and yaw rate information indicating a yaw rate, and wherein the controller is further configured to: prioritize the acceleration information over the yaw rate information such that the controller is configured to determine the vehicle is executing the turn in a first direction based on the lateral acceleration value indicating the turn in the first direction and even if the yaw rate indicates the turn in a second direction or does not indicate the turn.

8. The recreational vehicle of claim 1, wherein the sensor information comprises steering information indicating a steering position or a steering rate and acceleration information indicating a lateral acceleration value, and wherein the controller is further configured to: prioritizing the acceleration information over the steering information such that the controller is configured to determine the vehicle is executing the turn in a first direction based on the lateral acceleration value indicating the turn in the first direction and even if the steering position or the steering rate indicates the turn in a second direction or does not indicate the turn.

9. The recreational vehicle of claim 1, wherein the acceleration sensor is an inertial measurement unit (IMU).

10. A recreational vehicle comprising: a plurality of ground engaging members; a frame supported by the plurality of ground engaging members; a plurality of suspensions, wherein each of the plurality of suspensions couples a ground engaging member, from the plurality of ground engaging members, to the frame, wherein the plurality of suspensions includes a plurality of adjustable shock absorbers; a first sensor positioned on the recreational vehicle and configured to provide cornering information to a controller; and a second sensor positioned on the recreational vehicle and configured to provide acceleration information to the controller; the controller operatively coupled to the first sensor, the second sensor, and the plurality of adjustable shock absorbers, wherein the controller is configured to: receive, from the first sensor, the cornering information; receive, from the second sensor, the acceleration information; determine, based on the cornering information, a cornering event corresponding to the recreational vehicle executing a turn; determine, based on the acceleration information indicating a longitudinal deceleration, that the recreational vehicle is entering the turn; provide, to the at least one of the plurality of adjustable shock absorbers and based on the cornering event and the position of the recreational vehicle during the turn, one or more commands to result in an adjustment of a damping characteristic of the at least one of the plurality of adjustable shock absorbers; determine, based on the cornering event, a plurality of damping characteristics for the plurality of adjustable shock absorbers; bias, based on the determining that the vehicle is entering the turn, the plurality of damping characteristics; and generate the one or more commands based on the plurality of biased damping characteristics.

11. The recreational vehicle of claim 10, wherein the second sensor is an accelerometer or an inertial measurement unit (IMU).

12. The recreational vehicle of claim 10, wherein the controller is configured to bias the plurality of damping characteristics by: additionally increasing the compression damping of a front adjustable shock absorber of the plurality of adjustable shock absorbers; and additionally decreasing the compression damping of a rear adjustable shock absorber of the plurality of adjustable shock absorbers.

13. The recreational vehicle of claim 10, wherein the controller is configured to bias the plurality of

damping characteristics by: additionally increasing the rebound damping of a rear adjustable shock absorber of the plurality of adjustable shock absorbers; and additionally decreasing the rebound damping of a front adjustable shock absorber of the plurality of adjustable shock absorbers.

14. The recreational vehicle of claim 10, wherein the controller is configured to determine the position of the recreational vehicle during the turn by determining, based on the acceleration information indicating a longitudinal acceleration, that the vehicle is exiting the turn, and wherein the controller is further configured to: determine, based on the cornering event, a plurality of damping characteristics for the plurality of adjustable shock absorbers; bias, based on the determining that the vehicle is exiting the turn, the plurality of damping characteristics; and generate the one or more commands based on the plurality of biased damping characteristics.

15. The recreational vehicle of claim 14, wherein the controller is configured to bias the plurality of damping characteristics by: additionally increasing the compression damping of a rear adjustable shock absorber of the plurality of adjustable shock absorbers; and additionally decreasing the compression damping of a front adjustable shock absorber of the plurality of adjustable shock absorbers.

16. The recreational vehicle of claim 14, wherein the controller is configured to bias the plurality of damping characteristics by: additionally increasing the rebound damping of a front adjustable shock absorber of the plurality of adjustable shock absorbers; and additionally decreasing the rebound damping of a rear adjustable shock absorber of the plurality of adjustable shock absorbers.

17. A recreational vehicle, comprising: a plurality of ground engaging members; a frame supported by the plurality of ground engaging members; a plurality of suspensions, wherein each of the plurality of suspensions couples a ground engaging member, from the plurality of ground engaging members, to the frame, wherein the plurality of suspensions includes a plurality of adjustable shock absorbers; at least one sensor positioned on the recreational vehicle and configured to provide sensor information to a controller, and the sensor information comprises yaw rate information indicate a yaw rate and steering information indicating a steering position or a steering rate; and the controller operatively coupled to the at least one sensor and the plurality of adjustable shock absorbers, wherein the controller is configured to: receive, from the at least one sensor, the sensor information; determine, based on the sensor information, a cornering event corresponding to the recreational vehicle executing a turn; provide, to at least one of the plurality of adjustable shock absorbers and based on the determining of the cornering event, one or more commands to result in a decrease of a damping characteristic of the at least one of the plurality of adjustable shock absorbers; and prioritize the yaw rate information over the steering information such that the controller is configured to determine the vehicle is executing the turn in a first direction based on the yaw rate indicating the turn in the first direction and even if the steering position or the steering rate indicates the turn in a second direction or does not indicate the turn.

18. The recreational vehicle of claim 17, wherein the controller is further configured to: determine, based on the sensor information, a direction of the turn corresponding to the cornering event; determining, based on the direction of the turn, at least one inner adjustable shock absorber of the plurality of adjustable shock absorbers, and wherein the controller is configured to provide the one or more commands by providing, to the at least one inner adjustable shock absorber, one or more commands to result in a decrease of a compression damping characteristic and an increase of a rebound damping characteristic.

19. The recreational vehicle of claim 18, wherein the controller is further configured to: determine, based on the direction of the turn, at least one outer adjustable shock absorber of the plurality of adjustable shock absorbers, and wherein the controller is configured to provide the one or more commands by providing, to the least one outer adjustable shock absorber one or more commands to result in a decrease of a rebound damping characteristic and an increase of a compression damping characteristic.

20. The recreational vehicle of claim 17, wherein the at least one sensor is an acceleration sensor.

21. The recreational vehicle of claim 17, wherein the one or more commands results in an increase of a first damping characteristic and a decrease of a second damping characteristic of the at least one of the plurality of adjustable shock absorbers.

22. A recreational vehicle, comprising: a plurality of ground engaging members; a frame supported by the plurality of ground engaging members; a plurality of suspensions, wherein each of the plurality of suspensions couples a ground engaging member, from the plurality of ground engaging members, to the frame, wherein the plurality of suspensions includes a plurality of adjustable shock absorbers; at least one

sensor positioned on the recreational vehicle and configured to provide sensor information to a controller, and the sensor information comprises acceleration information indicating a lateral acceleration value and yaw rate information indicating a yaw rate; and the controller operatively coupled to the at least one sensor and the plurality of adjustable shock absorbers, wherein the controller is configured to: receive, from the at least one sensor, the sensor information; determine, based on the sensor information, a cornering event corresponding to the recreational vehicle executing a turn; provide, to at least one of the plurality of adjustable shock absorbers and based on the determining of the cornering event, one or more commands to result in a decrease of a damping characteristic of the at least one of the plurality of adjustable shock absorbers; and prioritize the acceleration information over the yaw rate information such that the controller is configured to determine the vehicle is executing the turn in a first direction based on the lateral acceleration value indicating the turn in the first direction and even if the yaw rate indicates the turn in a second direction or does not indicate the turn.

23. The recreational vehicle of claim 22, wherein the controller is further configured to: determine, based on the sensor information, a direction of the turn corresponding to the cornering event; determining, based on the direction of the turn, at least one inner adjustable shock absorber of the plurality of adjustable shock absorbers, and wherein the controller is configured to provide the one or more commands by providing, to the at least one inner adjustable shock absorber, one or more commands to result in a decrease of a compression damping characteristic and an increase of a rebound damping characteristic.

24. The recreational vehicle of claim 22, wherein the controller is further configured to: determine, based on the direction of the turn, at least one outer adjustable shock absorber of the plurality of adjustable shock absorbers, and wherein the controller is configured to provide the one or more commands by providing, to the least one outer adjustable shock absorber one or more commands to result in a decrease of a rebound damping characteristic and an increase of a compression damping characteristic.

25. The recreational vehicle of claim 22, wherein the at least one sensor is an acceleration sensor.

26. The recreational vehicle of claim 22, wherein the one or more commands results in an increase of a first damping characteristic and a decrease of a second damping characteristic of the at least one of the plurality of adjustable shock absorbers.

27. A recreational vehicle, comprising: a plurality of ground engaging members; a frame supported by the plurality of ground engaging members; a plurality of suspensions, wherein each of the plurality of suspensions couples a ground engaging member, from the plurality of ground engaging members, to the frame, wherein the plurality of suspensions includes a plurality of adjustable shock absorbers; at least one sensor positioned on the recreational vehicle and configured to provide sensor information to a controller, and the sensor information comprises steering information indicating a steering position or a steering rate and acceleration information indicating a lateral acceleration value; and the controller operatively coupled to the at least one sensor and the plurality of adjustable shock absorbers, wherein the controller is configured to: receive, from the at least one sensor, the sensor information; determine, based on the sensor information, a cornering event corresponding to the recreational vehicle executing a turn; provide, to at least one of the plurality of adjustable shock absorbers and based on the determining of the cornering event, one or more commands to result in a decrease of a damping characteristic of the at least one of the plurality of adjustable shock absorbers, and prioritize the acceleration information over the steering information such that the controller is configured to determine the vehicle is executing the turn in a first direction based on the lateral acceleration value indicating the turn in the first direction and even if the steering position or the steering rate indicates the turn in a second direction or does not indicate the turn.

28. The recreational vehicle of claim 27, wherein the controller is further configured to: determine, based on the sensor information, a direction of the turn corresponding to the cornering event; determining, based on the direction of the turn, at least one inner adjustable shock absorber of the plurality of adjustable shock absorbers, and wherein the controller is configured to provide the one or more commands by providing, to the at least one inner adjustable shock absorber, one or more commands to result in a decrease of a compression damping characteristic and an increase of a rebound damping characteristic.

29. The recreational vehicle of claim 27, wherein the controller is further configured to: determine, based on the direction of the turn, at least one outer adjustable shock absorber of the plurality of adjustable shock absorbers, and wherein the controller is configured to provide the one or more commands by providing, to the least one outer adjustable shock absorber one or more commands to result in a decrease

of a rebound damping characteristic and an increase of a compression damping characteristic.

30. The recreational vehicle of claim 27, wherein the at least one sensor is an acceleration sensor.

31. The recreational vehicle of claim 27, wherein the one or more commands results in an increase of a first damping characteristic and a decrease of a second damping characteristic of the at least one of the plurality of adjustable shock absorbers.

32. A recreational vehicle comprising: a plurality of ground engaging members; a frame supported by the plurality of ground engaging members; a plurality of suspensions, wherein each of the plurality of suspensions couples a ground engaging member, from the plurality of ground engaging members, to the frame, wherein the plurality of suspensions includes a plurality of adjustable shock absorbers; a first sensor positioned on the recreational vehicle and configured to provide cornering information to a controller; and a second sensor positioned on the recreational vehicle and configured to provide acceleration information to the controller; the controller operatively coupled to the first sensor, the second sensor, and the plurality of adjustable shock absorbers, wherein the controller is configured to: receive, from the first sensor, the cornering information; receive, from the second sensor, the acceleration information; determine, based on the cornering information, a cornering event corresponding to the recreational vehicle executing a turn; determine, based on the acceleration information indicating a longitudinal acceleration, that the recreational vehicle is exiting the turn; provide, to the at least one of the plurality of adjustable shock absorbers and based on the cornering event and the position of the recreational vehicle during the turn, one or more commands to result in an adjustment of a damping characteristic of the at least one of the plurality of adjustable shock absorbers; determine, based on the cornering event, a plurality of damping characteristics for the plurality of adjustable shock absorbers; bias, based on the determining that the vehicle is exiting the turn, the plurality of damping characteristics; and generate the one or more commands based on the plurality of biased damping characteristics.

33. The recreational vehicle of claim 32, wherein the controller is further configured to: determine, based on the sensor information, a direction of the turn corresponding to the cornering event; determining, based on the direction of the turn, at least one inner adjustable shock absorber of the plurality of adjustable shock absorbers, and wherein the controller is configured to provide the one or more commands by providing, to the at least one inner adjustable shock absorber, one or more commands to result in a decrease of a compression damping characteristic and an increase of a rebound damping characteristic.

34. The recreational vehicle of claim 32, wherein the controller is further configured to: determine, based on the direction of the turn, at least one outer adjustable shock absorber of the plurality of adjustable shock absorbers, and wherein the controller is configured to provide the one or more commands by providing, to the at least one outer adjustable shock absorber one or more commands to result in a decrease of a rebound damping characteristic and an increase of a compression damping characteristic.

35. The recreational vehicle of claim 32, wherein the at least one sensor is an acceleration sensor.

36. The recreational vehicle of claim 32, wherein the one or more commands results in an increase of a first damping characteristic and a decrease of a second damping characteristic of the at least one of the plurality of adjustable shock absorbers.
