

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent
Kind Code
Date of Patent
Inventor(s)

12385336
B2
August 12, 2025
Fischer; John et al.

Parameter monitoring and control for an electric driven hydraulic fracking system

Abstract

An electric driven hydraulic fracking system is disclosed. A pump configuration includes the single VFD, the single shaft electric motor, and the single hydraulic pump mounted on the single pump trailer. A controller associated with the single VFD and is mounted on the single pump trailer. The controller monitors operation parameters associated with an operation of the electric driven hydraulic fracking system as each component of the electric driven hydraulic fracking system operates to determine whether the operation parameters deviate beyond a corresponding operation parameter threshold. Each of the operation parameters provides an indicator as to an operation status of a corresponding component of the electric driven hydraulic fracking system. The controller initiates corrected actions when each operation parameter deviates beyond the corresponding operation threshold. Initiating the corrected actions when each operation parameter deviates beyond the corresponding operation threshold maintains the operation of the electric driven hydraulic fracking system.

Inventors: Fischer; John (Hempstead, TX), Crosetto; John J. (Oak Forest, IL), Kubricht; David (Cypress, TX), Cheatham; Richard (Houston, TX), Pollack; Jeffrey (Joliet, IL), Lawman; Chad (Joliet, IL), Todd; David (Houston, TX), Nolen; Tyler (Houston, TX)

Applicant: Halliburton Energy Services, Inc. (Houston, TX)

Family ID: 70728579

Assignee: Halliburton Energy Services, Inc. (Houston, TX)

Appl. No.: 18/625554

Filed: April 03, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240247556 A1	Jul. 25, 2024

Related U.S. Application Data

continuation parent-doc US 18226002 20230725 US 11976524 child-doc US 18625554
continuation parent-doc US 17968055 20221018 US 11708733 20230725 child-doc US 18226002
continuation parent-doc US 17707840 20220329 US 11473381 20221018 child-doc US 17968055
continuation parent-doc US 17511078 20211026 US 11286736 20220329 child-doc US 17707840
continuation parent-doc US 17234689 20210419 US 11156044 20211026 child-doc US 17511078
continuation parent-doc US 17129719 20201221 US 10982498 20210420 child-doc US 17234689
continuation parent-doc US 16927487 20200713 US 10871045 20201222 child-doc US 17129719
continuation parent-doc US 16791256 20200214 US 10753165 20200825 child-doc US 16927487
us-provisional-application US 62805521 20190214

Publication Classification

Int. Cl.: H02K7/18 (20060101); E21B4/04 (20060101); E21B7/02 (20060101); E21B21/08 (20060101); E21B43/26 (20060101); F04B17/03 (20060101); F04B17/06 (20060101); F04D13/06 (20060101); H02B1/52 (20060101); H02B5/00 (20060101); H02J13/00 (20060101); H02P27/04 (20160101); E21B4/02 (20060101)

U.S. Cl.:

CPC E21B21/08 (20130101); E21B4/04 (20130101); E21B7/022 (20130101); E21B43/2605 (20200501); E21B43/2607 (20200501); F04B17/03 (20130101); F04B17/06 (20130101); F04D13/0686 (20130101); H02B1/52 (20130101); H02B5/00 (20130101); H02J13/00036 (20200101); H02K7/18 (20130101); H02P27/04 (20130101); E21B4/02 (20130101); F05B2220/706 (20130101); F05B2240/941 (20130101)

Field of Classification Search

CPC: H02B (1/52); H02B (5/00); H02J (13/00036); H02K (7/18); H02P (27/04)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3075136	12/1962	Jones	N/A	N/A
3262036	12/1965	Clarke	N/A	N/A
3911677	12/1974	Collins	N/A	N/A
4011702	12/1976	Matyas	N/A	N/A
4031702	12/1976	Burnett	N/A	N/A
5712802	12/1997	Kumar	N/A	N/A
5795135	12/1997	Nyilas	N/A	N/A
5865247	12/1998	Paterson	N/A	N/A

6109372	12/1999	Dorel	N/A	N/A
6116040	12/1999	Stark	N/A	N/A
6129529	12/1999	Young	N/A	N/A
6167965	12/2000	Bearden	N/A	N/A
6271637	12/2000	Kushion	N/A	N/A
7051568	12/2005	Ciotti	N/A	N/A
7053568	12/2005	Rudinec	N/A	N/A
7092771	12/2005	Retlich	N/A	N/A
7109835	12/2005	Cern	N/A	N/A
7170262	12/2006	Pettigrew	N/A	N/A
7309835	12/2006	Morrison	N/A	N/A
7312593	12/2006	Streicher	N/A	N/A
7494263	12/2008	Dykstra	N/A	N/A
7539549	12/2008	Discenzo	N/A	N/A
7717193	12/2009	Egilsson	N/A	N/A
7836949	12/2009	Dykstra	N/A	N/A
7841394	12/2009	McNeel	N/A	N/A
7949483	12/2010	Discenzo	N/A	N/A
8056635	12/2010	Shampine	N/A	N/A
8106527	12/2011	Carr	N/A	N/A
8155922	12/2011	Loucks	N/A	N/A
8174853	12/2011	Kane	N/A	N/A
8379424	12/2012	Grbovic	N/A	N/A
8400093	12/2012	Knox	N/A	N/A
8503180	12/2012	Nojima	N/A	N/A
8789601	12/2013	Broussard	N/A	N/A
8874383	12/2013	Gambier	N/A	N/A
8997604	12/2014	Gimeno Grane	N/A	N/A
8997904	12/2014	Cryer	N/A	N/A
9140110	12/2014	Coli	N/A	N/A
9366114	12/2015	Coli	N/A	N/A
9410410	12/2015	Broussard	N/A	N/A
9450385	12/2015	Kristensen	N/A	N/A
9475020	12/2015	Coli	N/A	N/A
9534473	12/2016	Morris	N/A	N/A
9556721	12/2016	Jang	N/A	N/A
9611728	12/2016	Oehring	N/A	N/A
9650871	12/2016	Oehring	N/A	N/A
9650879	12/2016	Broussard	N/A	N/A
9745840	12/2016	Oehring	N/A	N/A
9777723	12/2016	Wiegman	N/A	N/A
9840901	12/2016	Oehring	N/A	N/A
9893500	12/2017	Oehring	N/A	N/A
9970278	12/2017	Broussard	N/A	N/A
10020711	12/2017	Oehring	N/A	N/A
10119381	12/2017	Oehring	N/A	N/A
10227854	12/2018	Glass	N/A	N/A
10254732	12/2018	Oehring	N/A	N/A
10280724	12/2018	Hinderliter	N/A	N/A
10337308	12/2018	Broussard	N/A	N/A

10408031	12/2018	Oehring	N/A	N/A
10519730	12/2018	Morris	N/A	N/A
10526882	12/2019	Oehring	N/A	N/A
10550665	12/2019	Golden	N/A	N/A
10648311	12/2019	Oehring	N/A	N/A
10738580	12/2019	Fischer	N/A	N/A
10753153	12/2019	Fischer	N/A	N/A
10753165	12/2019	Fischer	N/A	N/A
10794165	12/2019	Fischer	N/A	N/A
10851635	12/2019	Fischer	N/A	N/A
10871045	12/2019	Fischer	N/A	N/A
10876358	12/2019	Fischer	N/A	N/A
10934824	12/2020	Oehring	N/A	N/A
10975641	12/2020	Fischer	N/A	N/A
10982498	12/2020	Fischer	N/A	N/A
10988998	12/2020	Fischer	N/A	N/A
10989031	12/2020	Fischer	N/A	N/A
11053758	12/2020	Fischer	N/A	N/A
11091992	12/2020	Broussard	N/A	N/A
11125034	12/2020	Fischer	N/A	N/A
11136870	12/2020	Broussard	N/A	N/A
11142972	12/2020	Fischer	N/A	N/A
11156044	12/2020	Fischer	N/A	N/A
11168556	12/2020	Fischer	N/A	N/A
11220896	12/2021	Fischer	N/A	N/A
11274512	12/2021	Fischer	N/A	N/A
11286736	12/2021	Fischer	N/A	N/A
11319762	12/2021	Fischer	N/A	N/A
11434709	12/2021	Fischer	N/A	N/A
11466550	12/2021	Fischer	N/A	N/A
11473381	12/2021	Fischer	N/A	N/A
11492860	12/2021	Fischer	N/A	N/A
11560764	12/2022	Fischer	N/A	N/A
11668144	12/2022	Fischer	N/A	N/A
11708733	12/2022	Fischer	N/A	N/A
11739602	12/2022	Fischer	N/A	N/A
11773664	12/2022	Fischer	N/A	N/A
11788396	12/2022	Fischer	N/A	N/A
11795800	12/2022	Fischer	N/A	N/A
11939828	12/2023	Fischer	N/A	N/A
11976524	12/2023	Fischer	N/A	N/A
11976525	12/2023	Fischer	N/A	N/A
12000256	12/2023	Fischer	N/A	N/A
12006807	12/2023	Fischer	N/A	N/A
2003/0057704	12/2002	Baten	N/A	N/A
2005/0116541	12/2004	Seiver	N/A	N/A
2006/0260331	12/2005	Andreychuk	N/A	N/A
2007/0125544	12/2006	Robinson	N/A	N/A
2007/0201305	12/2006	Heilman	N/A	N/A
2008/0029267	12/2007	Shampine	N/A	N/A

2008/0083222	12/2007	Hubert	N/A	N/A
2008/0137266	12/2007	Jensen	N/A	N/A
2008/0264625	12/2007	Ochoa	N/A	N/A
2008/0266758	12/2007	Hurt	N/A	N/A
2008/0288115	12/2007	Rusnak	N/A	N/A
2009/0122578	12/2008	Beltran	N/A	N/A
2010/0248605	12/2009	Sharma	N/A	N/A
2010/0310384	12/2009	Stephenson	N/A	N/A
2010/0312415	12/2009	Loucks	N/A	N/A
2011/0061855	12/2010	Case	N/A	N/A
2011/0063942	12/2010	Hagan	N/A	N/A
2011/0079682	12/2010	Raybell	N/A	N/A
2011/0194256	12/2010	De Rijck	N/A	N/A
2011/0241590	12/2010	Horikoshi	N/A	N/A
2012/0085541	12/2011	Love	N/A	N/A
2012/0112757	12/2011	Vrankovic	N/A	N/A
2012/0217067	12/2011	Mebane, III	N/A	N/A
2012/0223524	12/2011	Williams	290/50	H02J 5/00
2012/0224977	12/2011	Sotz	N/A	N/A
2012/0255734	12/2011	Coli	N/A	N/A
2013/0030438	12/2012	Fox	N/A	N/A
2013/0306267	12/2012	Feldman	N/A	N/A
2013/0306322	12/2012	Sanborn	N/A	N/A
2014/0010671	12/2013	Cryer	N/A	N/A
2014/0012416	12/2013	Negishi	N/A	N/A
2014/0062088	12/2013	Carr	N/A	N/A
2014/0077607	12/2013	Clarke	N/A	N/A
2014/0138079	12/2013	Broussard et al.	N/A	N/A
2015/0001161	12/2014	Wiemers	N/A	N/A
2015/0003185	12/2014	Woodle	N/A	N/A
2015/0027712	12/2014	Vicknair	N/A	N/A
2015/0114652	12/2014	Lestz	N/A	N/A
2015/0144336	12/2014	Hardin	N/A	N/A
2015/0211524	12/2014	Broussard	N/A	N/A
2015/0252661	12/2014	Glass	N/A	N/A
2015/0369351	12/2014	Hermann	N/A	N/A
2016/0006222	12/2015	Warren	N/A	N/A
2016/0025826	12/2015	Taicher	N/A	N/A
2016/0032703	12/2015	Broussard	N/A	N/A
2016/0053542	12/2015	Stafford	N/A	N/A
2016/0076351	12/2015	Stehle	N/A	N/A
2016/0177675	12/2015	Morris	N/A	N/A
2016/0195082	12/2015	Wiegman	N/A	N/A
2016/0258267	12/2015	Payne	N/A	N/A
2016/0290114	12/2015	Oehring	N/A	N/A
2016/0326854	12/2015	Broussard	N/A	N/A
2016/0326855	12/2015	Coli	N/A	N/A
2016/0369609	12/2015	Morris	N/A	N/A
2017/0022788	12/2016	Oehring	N/A	N/A
2017/0051732	12/2016	Hernandez	N/A	F04B 17/06

2017/0093298	12/2016	Simms	N/A	N/A
2017/0222409	12/2016	Oehring	N/A	N/A
2017/0226842	12/2016	Omont	N/A	N/A
2018/0073344	12/2017	Patterson	N/A	N/A
2018/0101502	12/2017	Nassif	N/A	N/A
2018/0112468	12/2017	Savage	N/A	N/A
2018/0156210	12/2017	Oehring	N/A	N/A
2018/0223831	12/2017	Zhang	N/A	F04B 51/00
2018/0258746	12/2017	Broussard	N/A	N/A
2018/0363438	12/2017	Coli	N/A	N/A
2019/0003329	12/2018	Morris	N/A	N/A
2019/0071951	12/2018	Spencer	N/A	N/A
2019/0169971	12/2018	Oehring	N/A	N/A
2019/0245348	12/2018	Hinderliter et al.	N/A	N/A
2019/0293063	12/2018	Scott	N/A	N/A
2019/0368332	12/2018	Sun	N/A	N/A
2020/0003205	12/2019	Stokkevag	N/A	N/A
2020/0109617	12/2019	Oehring et al.	N/A	N/A
2020/0263527	12/2019	Fischer	N/A	N/A
2020/0263528	12/2019	Fischer	N/A	N/A
2020/0300073	12/2019	Hinderliter	N/A	N/A
2020/0340313	12/2019	Fischer	N/A	N/A
2020/0406496	12/2019	Howard	N/A	N/A
2024/0003208	12/2023	Fischer	N/A	N/A
2024/0247556	12/2023	Fischer	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2773843	12/2015	CA	N/A
2707269	12/2017	CA	N/A
3072670	12/2019	CA	N/A
3228052	12/2019	CA	N/A
3072660	12/2019	CA	N/A
3072663	12/2019	CA	N/A
3072788	12/2019	CA	N/A
3226507	12/2019	CA	N/A
2964593	12/2020	CA	N/A
3072669	12/2023	CA	N/A
202463670	12/2011	CN	N/A
2014116761	12/2013	WO	N/A
2014177346	12/2013	WO	N/A
2016148715	12/2015	WO	N/A

OTHER PUBLICATIONS

First Office Action dated Feb. 26, 2025 (36 pages), U.S. Appl. No. 18/663,929, filed May 14, 2024. cited by applicant

Dewinter, Frank A., et al. "The application of a 3500 HP variable frequency drive for pipeline pump control." IEEE Transactions on Industry Applications 25.6 (1989): 1019-1024. cited by applicant

Discenzo, Fred M., et al. "Next generation pump systems enable new opportunities for asset

management and economic optimization.” Proceedings of the 19th International Pump Users Symposium. Texas A&M University. Turbomachinery Laboratories, 2002. cited by applicant

Hefner, Allen R. “A dynamic electro-thermal model for the IGBT.” IEEE Transactions on Industry Applications 30.2 (1994): 394-405. cited by applicant

Hickok, Herbert N. “Adjustable speed—A tool for saving energy losses in pumps, fans, blowers, and compressors.” IEEE Transactions on Industry Applications 1 (1985): 124-136. cited by applicant

Irvine, Geoff, et al. “The use of variable frequency drives as a final control element in the petroleum industry.” Conference Record of the 2000 IEEE Industry Applications Conference. Thirty-Fifth IAS Annual Meeting and World Conference on Industrial Applications of Electrical Energy (Cat. No. 00CH37129). vol. 4. IEEE, 2000. cited by applicant

Iversen, Arthur H., et al. “A uniform temperature, ultra-high heat flux liquid-cooled, power semiconductor package.” IEEE transactions on industry applications 27.1 (1991): 85-92. cited by applicant

Lockley, Bill, et al. “IEEE Std 1566—The Need for a Large Adjustable Speed Drive Standard.” 2006 Record of Conference Papers. IEEE Industry Applications Society 53rd Annual Petroleum and Chemical Industry Conference. IEEE, 2006. cited by applicant

Hanna, Robert A., et al. “Medium-voltage adjustable speed drives-users' and manufacturers' experiences.” IEEE transactions on industry applications 33.6 (1997): 1407-1415. cited by applicant

Roethemeyer, D., et al. “Evolution of motor and variable frequency drive technology.” ACEEE Summer Study Proceedings on Energy Efficiency in Industry. 1995. cited by applicant

Perrin, Martin, et al. “Induction motors, reciprocating compressors and variable frequency drives.” Record of Conference Papers. IEEE Industry Applications Society 44th Annual Petroleum and Chemical Industry Conference. IEEE, 1997. cited by applicant

Shepherd, William, et al. “Unbalanced voltage control of 3-phase loads by the triggering of silicon controlled rectifiers.” IEEE Transactions on Industry and General Applications 3 (1965): 206-216. cited by applicant

Saidur, Rahman, et al. “Applications of variable speed drive (VSD) in electrical motors energy savings.” Renewable and sustainable energy reviews 16.1 (2012): 543-550. cited by applicant

“Drive Systems: Power on Demand.” Comprehensive Power, Drive Systems, Comprehensive Power Inc., web.archive.org/web/20081205001529/http://www.comprehensivepower.com/drive_systems. htrn. Accessed Dec. 5, 2008. cited by applicant

TMEIC Corporation “TMEIC Industrial Motors” Product Brochure M-1201 B 2015, <https://www.trneic.com/Repository/Others/Industrial%20Motor%20Brochure-rev%20Sep2015-10%20res.pdf> Accessed Nov. 10, 2023. cited by applicant

Integrated Power Services “Toshiba Drives.” Industrial Electronic Sales, www.ipsrpd.com/toshiba-drives.html. Accessed Nov. 10, 2023. cited by applicant

Asea Brown Boveri “ABB drives in power generation” 2011 <https://search.abb.com/library/Download.aspx?DocumentID=3BHT%20490%20510%20ROOOI&LanguageCode=en&DocumentPartId=&Action=Launch> Accessed Nov. 10, 2023. cited by applicant

Toshiba Motors & Drives “G9 Adjustable Speed Drives” Toshiba International Corporation 2020, 6 pages, https://www.toshiba.com/tic/datafiles/brochures/G9_6pg_ESSENCE_I|0419_nocrop.pdf. Accessed Nov. 10, 2023. cited by applicant

Toshiba Motors & Drives “H9 Adjustable Speed Drive” Toshiba International Corporation 2011 287 pages, https://pim.galco.com/Manufacturer/Toshiba/TechDocument/Operation%20Manual/driv_ac_h9_opm.pdf. Accessed Nov. 10, 2023. cited by applicant

Toshiba Motors & Drives “2011 Industrial Catalog” Toshiba International Corporation 2011 272 pages, https://esrmotors.com/Literature/Toshiba/VFDs/Catalogs/2011%20Industrial%20ASD%20PAC%20Pricebook_Apr-25-2011-small.pdf. Accessed Nov. 10, 2023. cited by applicant

National Electrical Manufacturers Association “Adjustable Speed Electrical Power Drive Systems: Part 4: General Requirement·· Rating Specifications for A.C. Power Drive Systems Above 1000 V A.C. and not Exceeding 35 kV” <https://web.archive.org/web/20060114093828/http://www.nema.org/stds/61800-4.cfm> . Accessed Nov. 10, 2023. cited by applicant

Perkon, Dave, “Peter Hammond Recalls the Birth of the Medium Voltage Drive.” Control Design.com, <https://www.controldesign.com/motion/drives/article/11323728/peter-hammond-recalls-the-birth-of-the-medium-voltage-drive> accessed Aug. 6, 2024. cited by applicant

Filing Receipt, Specification and Drawings for U.S. Appl. No. 18/628,179, entitled, “Slurry Proportioner System,” filed Apr. 5, 2024, 111 pages. cited by applicant

Filing Receipt, Specification and Drawings for U.S. Appl. No. 18/585,425, entitled, “Variable Frequency Drive Configuration for Electric Driven Hydraulic Fracking System,” filed Feb. 23, 2024, 98 pages. cited by applicant

Filing Receipt, Specification and Drawings for U.S. Appl. No. 18/664,000, entitled, “Electric Driven Hydraulic Fracking System,” filed May 14, 2024, 57 pages. cited by applicant

Filing Receipt, Specification and Drawings for U.S. Appl. No. 18/663,929, entitled, “Power Distribution Trailer for an Electric Driven Hydraulic Fracking System,” filed May 14, 2024, 73 pages. cited by applicant

Primary Examiner: Islam; Muhammad S

Attorney, Agent or Firm: Conley Rose, P.C.

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) The present application is a continuation of and claims priority to U.S. patent application Ser. No. 18/226,002 filed Jul. 25, 2023 and published as U.S. patent Application Publication No. 2023/0366280 A1, which is a continuation of and claims priority to U.S. patent application Ser. No. 17/968,055 filed Oct. 18, 2022, now U.S. Pat. No. 11,708,733, which is a continuation of and claims priority to U.S. patent application Ser. No. 17/707,840 filed Mar. 29, 2022, now U.S. Pat. No. 11,473,381, which is a continuation of and claims priority to U.S. patent application Ser. No. 17/511,078 filed Oct. 26, 2021, now U.S. Pat. No. 11,286,736, which is a continuation of and claims priority to U.S. patent application Ser. No. 17/234,689, filed Apr. 19, 2021, now U.S. Pat. No. 11,156,044, which is a continuation of and claims priority to U.S. patent application Ser. No. 17/129,719, filed Dec. 21, 2020, now U.S. Pat. No. 10,982,498, which is a continuation of and claims priority to U.S. patent application Ser. No. 16/927,487, filed Jul. 13, 2020, now U.S. Pat. No. 10,871,045, which is a continuation of and claims priority to U.S. patent application Ser. No. 16/791,256, filed Feb. 14, 2020, now U.S. Pat. No. 10,753,165, which claims priority to U.S. Provisional Patent Application No. 62/805,521 filed Feb. 14, 2019, each of which is hereby incorporated by reference in its entirety.

BACKGROUND

Field of Disclosure

(1) The present disclosure generally relates to electric driven hydraulic fracking systems and specifically to a single Variable Frequency Drive (VFD), a single shaft electric motor, and a single

hydraulic pump positioned on a single pump trailer.

Related Art

(2) Conventional hydraulic fracking systems are diesel powered in that several different diesel engines apply the power to the hydraulic pumps as well as several types of auxiliary systems that assist the hydraulic pumps to execute the fracking, such as hydraulic coolers and lube pumps. Conventional diesel powered hydraulic fracking systems require a diesel engine and a transmission to be connected to a hydraulic pump to drive the hydraulic pump. However, typically several hydraulic pumps are required at a single fracking site to prepare the well for the later extraction of the fluid, such as hydrocarbons, from the existing well. Thus, each of the several hydraulic pumps positioned at a single fracking site require a single diesel engine and single transmission to adequately drive the corresponding hydraulic pump requiring several diesel engines and transmissions to also be positioned at the single fracking site in addition to the several hydraulic pumps.

(3) Typically, the diesel engines limit the horsepower (HP) that the hydraulic pumps may operate thereby requiring an increased quantity of hydraulic pumps to attain the required HP necessary prepare the well for the later extraction of fluid, such as hydrocarbons, from the existing well. Any increase in the power rating of hydraulic pumps also results in an increase in the power rating of diesel engines and transmissions required at the fracking site as each hydraulic pump requires a sufficiently rated diesel engine and transmission. As the diesel engines, transmissions, and hydraulic pumps for a single fracking site increase, so does quantity of trailers required to transport and position configurations at the fracking site.

(4) The numerous diesel engines, transmissions, and hydraulic pumps required at a fracking site significantly drives up the cost of the fracking operation. Each of the numerous trailers required to transport and position configurations require CDL drivers to operate as well as increased manpower to rig the increased assets positioned at the fracking site and may be classified as loads in need of permits, thus adding expense and possible delays. The amount of diesel fuel required to power the numerous diesel engines to drive the numerous hydraulic pumps required to prepare the well for the later extraction of the fluid, such as hydrocarbons, from the existing well also significantly drives up the cost of the fracking operation. Further, the parasitic losses typically occur as the diesel engines drive the hydraulic pumps as well as drive the auxiliary systems. Such parasitic losses actually decrease the amount of HP that is available for the hydraulic pumps operate thereby significantly decreasing the productivity of hydraulic pumps. In doing so, the duration of the fracking operation is extended resulting in significant increases in the cost of the fracking operation. The diesel engines also significantly increase the noise levels of the fracking operation and may have difficulty operating within required air quality limits.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) Embodiments of the present disclosure are described with reference to the accompanying drawings. In the drawings, like reference numerals indicate identical or functionally similar elements. Additionally, the left most digit(s) of a reference number typically identifies the drawing in which the reference number first appears.

(2) FIG. 1 illustrates a top-elevational view of a hydraulic fracking operation such that the hydraulic pumps may pump a fracking media into a well to execute a fracking operation to extract a fluid from the well;

(3) FIG. 2 illustrates a top-elevational view of a single pump configuration that includes a single VFD, a single shaft electric motor, and a single hydraulic pump that are each mounted on a single pump trailer;

- (4) FIG. 3 illustrates a block diagram of an electric driven hydraulic fracking system that provides an electric driven system to execute a fracking operation in that the electric power is produced by a power generation system and then distributed such that each component in the electric driven hydraulic fracking system is electrically powered;
- (5) FIG. 4 illustrates a block diagram of an electric driven fracking system where the VFD controller, the fracking control center, and/or the power distribution trailer controller monitors various operation parameters associated with the operation of the electric driven fracking system;
- (6) FIG. 5 illustrates a block diagram of an electric driven hydraulic fracking system that further describes the interaction between the power distribution trailer and the VFD controllers; and
- (7) FIG. 6 illustrates a top-elevation view of a connector configuration for each of the components of the electric driven hydraulic fracking system that may couple to a medium voltage cable, a low voltage cable, and a communication cable.

DETAILED DESCRIPTION

(8) The following Detailed Description refers to accompanying drawings to illustrate exemplary embodiments consistent with the present disclosure. References in the Detailed Description to “one exemplary embodiment,” an “exemplary embodiment,” an “example exemplary embodiment,” etc., indicate the exemplary embodiment described may include a particular feature, structure, or characteristic, but every exemplary embodiment may not necessarily include the particular feature, structure, or characteristic. Moreover, such phrases are not necessarily referring to the same exemplary embodiment. Further, when a particular feature, structure, or characteristic may be described in connection with an exemplary embodiment, it is within the knowledge of those skilled in the art(s) to effect such feature, structure, or characteristic in connection with other exemplary embodiments whether or not explicitly described.

(9) The exemplary embodiments described herein are provided for illustrative purposes, and are not limiting. Other exemplary embodiments are possible, and modifications may be made to the exemplary embodiments within the spirit and scope of the present disclosure. Therefore, the Detailed Description is not meant to limit the present disclosure. Rather, the scope of the present disclosure is defined only in accordance with the following claims and their equivalents.

(10) Embodiments of the present disclosure may be implemented in hardware, firmware, software, or any combination thereof. Embodiments of the present disclosure may also be implemented as instructions applied by a machine-readable medium, which may be read and executed by one or more processors. A machine-readable medium may include any mechanism for storing or transmitting information in a form readable by a machine (e.g., a computing device). For example, a machine-readable medium may include read only memory (“ROM”), random access memory (“RAM”), magnetic disk storage media, optical storage media, flash memory devices, electrical optical, acoustical or other forms of propagated signals (e.g., carrier waves, infrared signals, digital signals, etc.), and others. Further firmware, software routines, and instructions may be described herein as performing certain actions. However, it should be appreciated that such descriptions are merely for convenience and that such actions in fact result from computing devices, processors, controllers, or other devices executing the firmware, software, routines, instructions, etc.

(11) For purposes of this discussion, each of the various components discussed may be considered a module, and the term “module” shall be understood to include at least one software, firmware, and hardware (such as one or more circuit, microchip, or device, or any combination thereof), and any combination thereof. In addition, it will be understood that each module may include one, or more than one, component within an actual device, and each component that forms a part of the described module may function either cooperatively or independently from any other component forming a part of the module. Conversely, multiple modules described herein may represent a single component within an actual device. Further, components within a module may be in a single device or distributed among multiple devices in a wired or wireless manner.

(12) The following Detailed Description of the exemplary embodiments will so fully reveal the

general nature of the present disclosure that others can, by applying knowledge of those skilled in the relevant art(s), readily modify and/or adapt for various applications such exemplary embodiments, without undue experimentation, without departing from the spirit and scope of the present disclosure. Therefore, such adaptations and modifications are intended to be within the meaning and plurality of equivalents of the exemplary embodiments based upon the teaching and guidance presented herein. It is to be understood that the phraseology or terminology herein for the purpose of description and not of limitation, such that the terminology or phraseology of the present specification is to be interpreted by those skilled in the relevant art(s) in light of the teachings herein.

(13) System Overview

(14) FIG. 1 illustrates a top-elevation view of a hydraulic fracking operation such that the hydraulic pumps may pump a fracking media into a well to execute a fracking operation to extract a fluid from the well. A hydraulic fracking operation **100** includes a fracking trailer **170** that a fracking configuration may be deployed. The fracking configuration may be the fracking equipment that executes the actual fracking to prepare the well for the later extraction of the fluid from the well. For example, the fracking trailer **170** may include the fracking equipment that implements the missile as well as the well heads that are affixed onto the well and distribute the fracking media into the well to prepare the well for later extraction of the fluid from the well. The fluid extracted from the well may include a liquid, such as crude oil, and so on, or a gas, such as such as hydrocarbons, natural gas and so on, that is extracted from the well that is then stored and distributed.

(15) The power that is generated to provide power to each of the numerous components included in the hydraulic fracking operation **100** is positioned on a power generation system **110**. Often times, the fracking site is a remote site where it has been determined that sufficient fluid has been located underground to justify temporarily establishing the hydraulic fracking operation **100** for a period of time to drill the well and extract the fluid from the well. Such fracking sites are often times positioned in remote locations such as uninhabited areas in mountainous regions with limited road access to the fracking sites such that the hydraulic fracking operation **100** is often times a mobile operation where each of the components are positioned on trailers that are then hauled to the fracking site via semi-trucks and/or tractors. For example, the fracking trailer **170** includes the fracking equipment which is hauled in via a semi-truck and is positioned closest to the well as compared to the other components in order to execute the fracking operation.

(16) In another example, the power generation system **110** may also be a mobile operation such that the power generation equipment may be mounted on a power generation trailer and transported to the fracking site via a semi-truck and/or tractor. The power generation system **110** may be positioned on the fracking site such that any component of the hydraulic fracking operation **100** may be powered by the power generation system **110**. In doing so, the power required for the hydraulic fracking operation **100** may be consolidated to the power generation system **110** such that the power generation system **110** provides the necessary power required for the hydraulic fracking operation **100**. Thus, the power generation system **110** may be positioned at the fracking site in a manner such that each component of the hydraulic fracking operation **100** may have power distributed from the power generation system **110** to each respective component of the hydraulic fracking operation **100**.

(17) The power generation system **110** may include power generation systems that generate electric power such that the hydraulic fracking operation **100** is powered via electric power generated by the power generation system **110** and does not require subsidiary power generation systems such as subsidiary power generation systems that include diesel engines. In doing so, the power generation system **110** may provide electric power to each component of the hydraulic fracking operation **100** such that the hydraulic fracking operation **100** is solely powered by electric power generated by the power generation system **110**. The power generation system **110** may consolidate the electric power

that is generated for the electric driven hydraulic fracking system **100** such that the quantity and size of power sources included in the power generation system **110** is decreased.

(18) The power sources are included in the power generation system **110** and output electric power such that the electric power outputted from each power source included in the power generation system **110** is collectively accumulated to be electric power at a power generation voltage level as will be discussed in detail below. For example, the power output for each of the power sources included in the power generation system **110** may be paralleled to generate the electric power at the power generation voltage level. The power generation system **110** may include numerous power sources as well as different power sources and any combination thereof. For example, the power generation system may include power sources that include a quantity of gas turbine engines. In another example, the power generation system **110** may include a power source that includes an electric power plant that independently generates electric power for an electric utility grid. In another example, the power generation system **110** may include a combination of gas turbine engines and an electric power plant. The power generation system **110** may generate the electric power at a power level and a voltage level.

(19) The power generation system **110** may generate electric power at a power generation voltage level in which the power generation voltage level is the voltage level that the power generation system is capable of generating the electric power. For example, the power generation system **110** when the power sources of the power generation system **110** include a quantity of gas turbine engines may generate the electric power at the power generation voltage level of 13.8 kV which is a typical voltage level for electric power generated by gas turbine engines. In another example, the power generation system **110** when the power sources of the power generation system include an electric power plant may generate the electric power at the power generation voltage level of 12.47 kV which is a typical voltage level for electric power generated by an electric power plant.

(20) In another example, the power generation system **110** may generate electric power that is already at a VFD voltage level to power the single shaft electric motor **150(a-n)** as discussed in detail below. In such an example, the power generation system **110** may generate the electric power that is already at the VFD voltage level of 4160V. In another example, the power generation system **110** may generate the electric power at the power generation voltage level at a range of 4160V to 15 kV. In another example, the power generation system **110** may generate electric power at the power generation voltage level of up to 38 kV. The power generation system **110** may generate the electric power at any power generation voltage level that is provided by the power sources included in the power generation system **110** that will be apparent to those skilled in the relevant art(s) without departing from the spirit and scope of the disclosure. The power generation system **110** may then provide the electric power at the power generation voltage level to the power distribution trailer **120** via a medium voltage cable.

(21) In an embodiment, the power generation system **110** may generate electric power at a power level of at least 24 Mega Watts (MW) that is generated at a power generation voltage level of at least 13.8 kV. In another embodiment, the power generation system **110** may generate electric power at a power level of at least 24 MW that is generated at a power generation voltage level of at least 12.47 kV. The power generation system **110** may generate electric power at a power level such that there is sufficient electric power to adequately power each of the components of the hydraulic fracking operation **100** while having gas turbine engines in quantity and in size that enable the gas turbine engines to be transported to the fracking site and set up remotely via a trailer. In doing so, the power distribution trailer **110** may include gas turbine engines that generate sufficient electric power to adequately power each of the components of the hydraulic fracking operation **100** while not requiring a large quantity of gas turbine engines and gas turbine engines of significant size that may significantly increase the difficulty and the cost to transport the gas turbine engines to the fracking site.

(22) In order to provide sufficient electric power to adequately power each of the components of

the hydraulic fracking operation **100** while not requiring large quantities of gas turbine engines and/or gas turbine engines of significant size, the power distribution trailer **110** may include single or multiple gas turbine engines that generate electric power at power levels of 5 MW, 12 MW, 16 MW, 20-25 MW, 30 MW and/or any other wattage level that may not require large quantities of gas turbine engines and/or gas turbine engines of significant size that will be apparent to those skilled in the relevant art(s) without departing from the spirit and scope of the disclosure. In another example, the power generation system **110** may be the electric utility power plant that is local to the location of the fracking operation such that the power distribution trailer **120** may receive the electric power at the power level of 24 MW and the power generation voltage level of 12.47 kV directly from the electric utility power plant.

(23) In an embodiment, the power generation system **110** may include a first gas turbine engine that generates electric power at a first power level in range of 12 MW to 16 MW and a second gas turbine engine that generates electric power at a second power level in a range of 12 MW to 16 MW. The first gas turbine engine and the second gas turbine engine generate the same voltage level of at least 13.8 kV that is provided to a power distribution trailer **120** when the first power level is in the range of 12 MW to 16 MW generated by the first gas turbine engine is combined with the second power level in the range of 12 MW to 16 MW. In order to provide sufficient electric power to adequately power each component of the hydraulic fracking operation **100** as well as limit the quantity of gas turbine engines as well as the size of the gas turbine engines such that the gas turbine engines may be positioned on a single trailer and transported to the fracking site, the power generation system **110** may include two electric gas turbine engines that generate electric power at power levels in the range of 12 MW to 16 MW such that the electric powers at the power levels in the range of 12 MW to 16 MW may be paralleled together to generate the total electric power that is available to power each of the components of the hydraulic fracking operation **100** is in the range of 24 MW to 32 MW.

(24) Further, the power generation system **110** including more than one gas turbine engine to generate the electric power provides redundancy in the power generation for the hydraulic fracking operation **100**. In doing so, the power generation system **110** provides a redundancy to the electric driven hydraulic fracking system in that the first gas turbine engine continues to provide the first power level to the power distribution trailer **120** when the second gas turbine engine suffers a short circuit and/or other shutdown condition and the second gas turbine engine continues to provide the second power level to the power distribution trailer **120** when the first gas turbine engine suffers the short circuit and/or other shutdown condition. The power generation system **110** may then maintain a reduced quantity of hydraulic pump(s) **160(a-n)** to continuously operate in the continuous duty cycle without interruption in continuously pumping the fracking media due to the redundancy provided by the first gas turbine engine and the second gas turbine engine.

(25) By incorporating two gas turbine engines that generate electric power at power levels in the range of 12 MW to 16 MW redundancy may be provided in that the electric power that is provided to the components of the hydraulic fracking operation **100** such that the fracking media is continuously pumped into the well to execute the fracking operation to prepare the well for the later extraction of the fluid from the well despite one of the gas turbine engines suffering a short circuit condition. In doing so, the incident energy at the point where the short circuit occurs may be reduced due to the reduced short circuit availability of the power generation system **110**. However, if one of the gas turbine engines were to fail due to a short circuit condition, the remaining gas turbine engine may continue to provide sufficient power to ensure the fracking media is continuously pumped into the well. A failure to continuously pump the fracking media into the well may result in the sand, which is a major component of the fracking media coming out of the suspension and creating a plug at the bottom of the well which typically results in a significant expense to remove the sand in the well so that the fracking can continue. The power generation system **110** may include any combination of gas turbine engines and/or single gas turbine engine at

any power level to sufficiently generate electric power to adequately power each of the components of the hydraulic fracking operation **100** that will be apparent to those skilled in the relevant art(s) without departing from the spirit and scope of the disclosure.

(26) The power generation system **110** may generate the electric power at a power generation voltage level that is in the medium voltage range of 1.0 kilo Volts (kV) to 72.0 kV. However, in an embodiment, the power generation system **110** may generate the electric power at the power generation voltage level of 13.8 kV. In another embodiment, the power generation system **110** may generate the electric power at the power generation voltage level of 13.8 kV. The generation of the electric power at the voltage level in the medium voltage range enables medium voltage cables to be used to connect the power generation system **110** to the power distribution trailer **120** to propagate the electric power from the power generation system **110** to the power distribution trailer **120** as well as enabling the use of medium voltage cables to propagate the electric voltage level to any of the components powered by the electric power in the medium voltage range. The use of medium voltage cables rather than the use of low voltage cables decreases the size of the cable required in that medium voltage cables require less copper than low voltage cables thereby reducing the size and/or quantity of the cables required for the distribution of power throughout the hydraulic fracking operation **100**.

(27) Further, the consolidation of gas turbine engines to decrease the quantity of gas turbine engines required to power the components of the hydraulic fracking operation **100** and/or the incorporation of the electric utility power plant also consolidates the quantity of medium voltage cables that are required to connect each of the gas turbine engines to the power distribution trailer **120** thereby further reducing the cost of the cables required for the hydraulic fracking operation **100**. Further, the power generation system **110** generated the electric power at the power generation voltage level of 13.8 kV and/or 12.47 kV enables the hydraulic fracking operation **100** to be more easily integrated with any electric utility grid anywhere in the world such that the electric utility grid may be more easily substituted into the power generation system **110** in replacement of the gas turbine engines since it is more common that the electric utility grid has transformers available to deliver the electric power at the power generation voltage level of 13.8 kV and/or 12.47 kV.

(28) The power distribution trailer **120** may distribute the electric power at the power level generated by the power generation system **110** to each variable frequency drive (VFD) **140(a-n)** positioned on each pump trailer **130(a-n)**. As noted above, the power generation system **110** may include at least one gas turbine engine, the electric utility grid, and/or a combination thereof, to generate the electric power. In doing so, a medium voltage power cable may be connected from each component of the power generation system **110** to the power distribution trailer **120**. For example, the power generation system **110** may include two gas turbine engines with each of the gas turbine engines generating electric power at the power level of 12 MW to 16 MW at the voltage level of 13.8 kV. In such an example, two medium voltage cables may then connect each of the two gas turbine engines to the power distribution trailer **120** such that the electric power at the power level of 12 MW to 16 MW at the voltage level of 13.8 kV may propagate from the gas turbine engines to the power distribution trailer **120**.

(29) The power distribution trailer **120** may then distribute the electric power to each of the VFDs **140(a-n)** positioned on each of the pump trailers **130(a-n)**. As will be discussed in detail below, several different hydraulic pumps **160(a-n)** may be required to continuously pump the fracking media into the well to execute the fracking operation to prepare the well for the later extraction of the fluid from the well. In doing so, each of the different hydraulic pumps **160(a-n)** may be driven by a corresponding VFD **140(a-n)** also positioned on the corresponding pump trailer **130(a-n)** with the hydraulic pump **160(a-n)**. Each of the VFDs **140(a-n)** may then provide the appropriate power to drive each of the single shaft electric motors **150(a-n)** that then drive each of the hydraulic pumps **160(a-n)** to continuously pump the fracking media into the well to execute the fracking operation to prepare the well for the later extraction of the fluid from the well. Thus, the power

distribution trailer **120** may distribute the electric power generated by the power distribution trailer **110** which is consolidated to reduce the quantity of the gas turbine engines to the several different VFDs **140(a-n)** positioned on each of the pump trailers **130(a-n)**. The components of the power distribution trailer **120** may be transported to the fracking site.

(30) For example, the power distribution trailer **120** is configured to distribute the electric power at the power level of at least 24 MW generated by the at least one gas turbine engine from the voltage level of at least 13.8 kV to the single VFD **140a** positioned on the single pump trailer **130a**. In such an example, the power generation system **110** includes two different gas turbine engines that generate the electric power at the power level of 12 MW to 16 MW and at the voltage level of 13.8 kV. Two different medium voltage cables may then propagate the electric power generated by each of the two gas turbine engines at the power level of 12 MW to 16 MW and at the voltage level of 13.8 kV to the power distribution trailer **120**. The power distribution trailer **120** may then combine the power levels of 12 MW to 16 MW generated by each of the two gas turbine engines to generate a power level of 24 MW to 32 MW at the voltage level of 13.8 kV. The power distribution trailer **120** may then distribute the electric power at the voltage level of 13.8 kV to each of eight different VFDs **140(a-n)** via eight different medium voltage cables that propagate the electric power at the voltage level of 13.8 kV from the power distribution trailer **120** to each of the eight different VFDs **140(a-n)**. The power distribution trailer **120** may distribute the power generated by any quantity of gas turbine engines to any quantity of VFDs that will be apparent to those skilled in the relevant art(s) without departing from the spirit and scope of the disclosure.

(31) In an embodiment, the power distribution trailer **120** may include a plurality of switch gear modules in that each switch gear module switches the electric power generated by each of the components of the power generation system **110** and received by the corresponding medium voltage cable to the medium voltage cable on and off to each of the corresponding VFDs **140(a-n)**. For example, the power distribution trailer **120** may include eight different switch gear modules to independently switch the electric power generated by the two gas turbine engines at the medium voltage level of 13.8 kV as received by the two different medium voltage cables on and off to the eight different medium voltage cables for each of the eight corresponding VFDs **140(a-n)** to distribute the electric power at the medium voltage level of 13.8 kV to each of the eight corresponding VFDs **140(a-n)**.

(32) In such an embodiment, the switch gear modules may include a solid state insulated switch gear (2SIS) that is manufactured by ABB and/or Schneider Electric. Such medium voltage switch gears may be sealed and/or shielded such that there is no exposure to live medium voltage components. Often times the fracking site generates an immense amount of dust and debris so removing any environmental exposure to live medium voltage components as provided by the 2SIS gear may decrease the maintenance required for the 2SIS. Further, the 2SIS may be permanently set to distribute the electric power from each of the gas turbine engines to each of the different VFDs **140(a-n)** with little maintenance. The power distribution trailer **120** may incorporate any type of switch gear and/or switch gear configuration to adequately distribute the electric power from the power generation system **110** to each of the different VFDs **140(a-n)** that will be apparent to those skilled in the relevant art(s) without departing from the spirit and scope of the disclosure.

(33) As noted above, the power distribution trailer **120** may distribute the electric power at the power generation voltage level generated by the power generation system **110** to each of the different VFDs **140(a-n)** positioned on the corresponding pump trailer **130(a-n)**. FIG. 2 illustrates a top-elevational view of a single pump configuration **200** that includes a single VFD **240**, a single shaft electric motor **250** and a single hydraulic pump **260** that are each mounted on a single pump trailer **230**. The single pump configuration **200** shares many similar features with each pump trailer **130(a-n)** that includes each corresponding VFD **140(a-n)**, single shaft electric motor **150(a-n)**, and single hydraulic pump **160(a-n)** depicted in the hydraulic fracking operation **100**; therefore, only the differences between the single pump configuration **200** and the hydraulic fracking operation

100 are to be discussed in further details.

(34) The power distribution trailer **120** may distribute the electric power at the voltage level generated by the power generation system **110** to the single VFD **240** that is positioned on the single pump trailer **130(a-n)**. The single VFD **240** may then drive the single shaft electric motor **250** and the single hydraulic pump **260** as well as control the operation of the single shaft electric motor **250** and the single hydraulic pump **260** as the single shaft electric motor **250** continuously drives the single hydraulic pump **260** as the single hydraulic pump **260** continuously pumps the fracking media into the well to execute the fracking operation to prepare the well for the later extraction of the fluid from the well. In doing so, the VFD **240** may convert the electric power distributed by the power distribution trailer **120** at the power generation voltage level generated by the power generation system **110** to a VFD voltage level that is a voltage level that is adequate to drive the single shaft electric motor **250**. Often times, the power generation voltage level of the electric power distributed by the power distribution trailer **120** as generated by the power generation system **110** may be at a voltage level that is significantly higher than a voltage level that is adequate to drive the single shaft electric motor **250**. Thus, the single VFD **240** may convert the power generation voltage level of the electric power as distributed by the power distribution trailer **120** to significantly lower (or higher) the voltage level to the VFD voltage level that is needed to drive the single shaft electric motor **250**. In an embodiment, the single VFD **240** may convert the power generation voltage level of the electric power as distributed by the power distribution trailer **120** to the VFD voltage level of at least 4160V. In another embodiment, the single VFD **240** may convert the power generation voltage level of the electric power as distributed by the power distribution trailer **120** to the VFD voltage level that ranges from 4160V to 6600V. In another embodiment, the single VFD **240** may convert the power generation level of the electric power as distributed by the power distribution trailer **120** to the VFD voltage level that ranges from 0V to 4160V.

(35) For example, the power generation system **110** generates the electric power at a power generation voltage level of 13.8 kV. The power distribution trailer **120** then distributes the electric power at the power generation voltage level of 13.8 kV to the single VFD **240**. However, the single shaft electric motor **250** operates at a rated voltage level of at least 4160V in order to drive the single hydraulic pump **260** in which the rated voltage level of at least 4160V for the single shaft electric motor **250** to operate is significantly less than the power generation voltage level of 13.8 kV of the electric power that is distributed by the power distribution trailer **120** to the single VFD **240**. The single VFD **240** may then convert the electric power at the power generation voltage level of at least 13.8 kV distributed from the power distribution trailer **120** to a VFD rated voltage level of at least 4160V and drive the single shaft electric motor **250** that is positioned on the single pump trailer **230** at the VFD rated voltage level of at least 4160V to control the operation of the single shaft electric motor **250** and the single hydraulic pump **260**. The single VFD **240** may convert any voltage level of the electric power distributed by the power distribution trailer **120** to any VFD voltage level that is adequate to drive the single shaft electric motor that will be apparent to those skilled in the relevant art(s) without departing from the spirit and scope of the disclosure.

(36) The single VFD **240** may also control the operation of the single shaft electric motor **250** and the single hydraulic pump **260**. The single VFD **240** may include a sophisticated control system that may control in real-time the operation of the single shaft electric motor **250** and the single hydraulic pump **260** in order for the single shaft electric motor **250** and the single hydraulic pump **260** to adequately operate to continuously pump the fracking media into the well to execute the fracking operation to prepare the well for the later extraction of the fluid from the well. Although, the single shaft electric motor **250** and the single hydraulic pump **260** may operate continuously to continuously pump the fracking media into the well, such continuous operation may not be continuously executed with the same parameters throughout the continuous operation. The parameters in which the single shaft electric motor **250** and the single hydraulic pump **260** may

continuously operate may actually vary based on the current state of the fracking operation. The single VFD **240** may automatically adjust the parameters in which the single shaft electric motor **250** and the single hydraulic pump continuously operate to adequately respond to the current state of the fracking operation.

(37) As noted above, the single VFD **240** may convert the electric power at the power generation voltage level distributed by the power distribution trailer **120** to the VFD voltage level that is adequate to drive the single shaft electric motor **250**. The single shaft electric motor **250** may be a single shaft electric motor in that the single shaft of the electric motor is coupled to the single hydraulic pump **260** such that the single shaft electric motor **250** drives a single hydraulic pump in the single hydraulic pump **260**. The single shaft electric motor **250** may continuously drive the single hydraulic pump **260** at an operating frequency to enable the single hydraulic pump **260** to continuously pump the fracking media into the well to execute the fracking operation to prepare the well for the later extraction of the fluid from the well. The single shaft electric motor **250** may operate at the VFD voltage levels and at the operating frequencies below or above the rated levels in order to rotate at a RPM level that is appropriate to continuously drive the single hydraulic pump **260** at the maximum horsepower (HP) level that the single hydraulic pump **260** is rated to pump. In an embodiment, the single shaft electric motor **250** may operate at a VFD voltage level of at least 4160V. In an embodiment, the single shaft electric motor **250** may operate at a VFD voltage level in a range of 4160V to 6600V. In an embodiment, the single shaft electric motor **250** may operate at a VFD voltage level in arrange of 0V to 4160V. The single shaft electric motor **250** may operate any VFD voltage level that is adequate to continuously drive the single hydraulic pump **260** that will be apparent to those skilled in the relevant art(s) without departing from the spirit and scope of the disclosure.

(38) For example, the power distribution trailer **120** may distribute the electric power to the single VFD **240** at the power generation voltage level of 13.8 kV. The single VFD **240** may then convert the electric power at the power generation voltage level of 13.8 kV to the VFD voltage level of 4160V to adequately drive the single shaft electric motor **250**. The single shaft electric motor **250** may operate at an operating frequency of 60 Hz and when the VFD voltage level of 4160V to adequately drive the single shaft electric motor at the operating frequency of 60 Hz, the single shaft electric motor **250** may then rotate at a RPM level of at least 750 RPM. The single shaft electric motor **250** may rotate at a RPM level of at least 750 RPM based on the VFD voltage level of at least 4160V as provided by the single VFD **240** and to drive the single hydraulic pump **260** that is positioned on the single pump trailer **230** with the single VFD **240** and the single shaft electric motor **250** with the rotation at the RPM level of at least 750 RPM.

(39) In an embodiment, the single shaft electric motor **250** may rotate at a RPM level of at least 750 RPM. In an embodiment, the single shaft electric motor **250** may rotate at a RPM level of 750 RPM to 1400 RPM. The single shaft electric motor **250** may operate at any RPM level to continuously drive the single hydraulic pump **260** that will be apparent to those skilled in the relevant art(s) without departing from the spirit and scope of the disclosure. The single shaft electric motor may operate at any operating frequency to continuously drive the single hydraulic pump **260** that will be apparent to those skilled in the relevant art(s) without departing from the spirit and scope of the disclosure.

(40) The single shaft electric motor **250** may be an induction motor that rotates at the RPM level needed to obtain required pump speed based on the input gear box ratio of the single hydraulic pump **260**. Based on the operating frequency of the single shaft motor **250** and the VFD voltage level applied to the single shaft electric motor **250**, the single shaft electric motor **250** may then rotate at the required RPM level and produce sufficient torque to cause the pump to produce the required flow rate of fracking media at the required output pressure level. However, the VFD voltage level applied to the single shaft electric motor **250** may be determined based on the input gear box ratio of the single hydraulic pump **260** as the single shaft electric motor **250** cannot be

allowed to rotate at the RPM level that exceeds the maximum speed rating of the input gear box of the single hydraulic pump **260** or the maximum speed of the single hydraulic pump **260**. The single shaft electric motor **250** may be an induction motor, a traction motor, a permanent magnet motor and/or any other electric motor that continuously drives the single hydraulic pump **260** that will be apparent to those skilled in the relevant art(s) without departing from the spirit and scope of the disclosure.

(41) As noted above, the single shaft electric motor **250** may be coupled to a single hydraulic pump in the single hydraulic pump **260** and drive the single hydraulic pump **260** such that the single hydraulic pump **260** continuously pumps the fracking media into the well to execute the fracking operation to prepare the well for the later extraction of the fluid from the existing well. The single hydraulic pump **260** may operate on a continuous duty cycle such that the single hydraulic pump **260** continuously pumps the fracking media into the well. Rather than operating on an intermittent duty cycle that causes conventional hydraulic pumps to temporarily stall in the pumping of the fracking media into the well, the single hydraulic pump **260** in operating on a continuous duty cycle may continuously pump the fracking media into the well without any intermittent stalling in the pumping. In doing so, the efficiency in the fracking operation to prepare the well for the later extraction of the fluid from the well may significantly increase as any intermittent stalling in pumping the fracking media into the well may result in setbacks in the fracking operation and may increase the risk of sand plugging the existing well. Thus, the single hydraulic pump **260** in operating on the continuous duty cycle may prevent any setbacks in the fracking operation due to the continuous pumping of the fracking media into the well.

(42) The single hydraulic pump **260** may continuously pump the fracking media into the well at the HP level that the single hydraulic pump **260** is rated. The increase in the HP level that the single hydraulic pump **260** may continuously pump the fracking media into the well may result in the increase in the efficiency in the fracking operation to prepare the well for later extraction of the fluid from the well. For example, the single hydraulic pump **260** may continuously pump the fracking media into the well at the HP level of at least 5000 HP as driven by the single shaft motor **250** at the RPM level of at least 750 RPM. The single hydraulic pump **260** operates on a continuous duty cycle to continuously pump the fracking media at the HP level of at least 5000 HP. In an embodiment, the single hydraulic pump **260** may operate at continuous duty with a HP level of 5000 HP and may be a Weir QEM5000 Pump. However, the single hydraulic pump **260** may any type of hydraulic pump that operates on a continuous duty cycle and at any HP level that adequately continuously pumps the pumping fracking media into the well to execute the fracking operation to prepare the well for the later extraction of the fluid from the well that will be apparent to those skilled in the relevant art(s) without departing from the spirit and scope of the disclosure.

(43) The single pump trailer **230** discussed in detail above may then be incorporated into the hydraulic fracking operation **100** depicted in FIG. 1. Each of the several pumps trailers **130(a-n)**, where n is an integer equal to or greater than one, may be incorporated into the hydraulic fracking operation **100** to increase the overall HP level that is applied to the fracking equipment positioned on the fracking trailer **170** by each of the single hydraulic pumps **160(a-n)** positioned on each of the pump trailers **130(a-n)**. In doing so, the overall HP level that is applied to the fracking equipment positioned on the fracking trailer **170** to continuously pump the fracking media into the well may be significantly increased as the HP level that is applied to the fracking equipment is scaled with each single hydraulic pump **160(a-n)** that is added to the hydraulic fracking operation **100**.

(44) The positioning of each single VFD **140(a-n)**, single shaft electric motor **150(a-n)**, and each single hydraulic pump **160(a-n)** positioned on each corresponding pump trailer **130(a-n)** enables the power distribution trailer **120** to distribute the electric power at the power generation voltage level to each single VFD **140(a-n)** from a single power distribution source rather than having a corresponding single power distribution source for each single VFD **140(a-n)**, single shaft electric

motor **150(a-n)**, and each single hydraulic pump **160(a-n)**. In doing so, the electric power at the power generation voltage level may be distributed to each single VFD **140(a-n)**, where n is an integer equal to or greater than one and corresponds to the number of pump trailers **130(a-n)**, then each single VFD **140(a-n)** may individually convert the power generation voltage level to the appropriate VFD voltage for the single shaft electric motor **150(a-n)** and the single hydraulic pump **160(a-n)** that is positioned on the corresponding pump trailer **130(a-n)** with the single VFD **140(a-n)**. The single VFD **140(a-n)** may then also control the corresponding single shaft electric motor **150(a-n)** and the single hydraulic pump **160(a-n)** that is positioned on the corresponding pump trailer **130(a-n)** with the single VFD **140(a-n)**.

(45) In isolating the single VFD **140(a-n)** to convert the electric power at the power generation voltage level to the appropriate VFD voltage level for the single shaft electric motor **150(a-n)** and the single hydraulic pump **160(a-n)** positioned on the corresponding single pump trailer **130(a-n)** as the single VFD **140(a-n)**, the capabilities of the single pump trailer **130(a-n)** may then be easily scaled by replicating the single pump trailer **130(a-n)** into several different pump trailers **130(a-n)**. In scaling the single pump trailer **130(a-n)** into several different pump trailers **130(a-n)**, the parameters for the single VFD **140(a-n)**, the single shaft electric motor **150(a-n)**, and the single hydraulic pump **160(a-n)** may be replicated to generate the several different pump trailers **130(a-n)** and in doing so scaling the hydraulic fracking operation **100**.

(46) In doing so, each single VFD **140(a-n)** may convert the electric power at the power generation voltage level as distributed by the power distribution trailer **120** to the VFD voltage level to drive each single shaft electric motor **150(a-n)**, where n is an integer equal to or greater than one and corresponds to the quantity of single VFDs **140(a-n)** and pump trailers **130(a-n)**, such that each single shaft electric motor **150(a-n)** rotates at the RPM level sufficient to continuously drive the single hydraulic pump **160(a-n)** at the HP level of the single hydraulic pump **160(a-n)**. Rather than simply having a single hydraulic pump **260** as depicted in FIG. 2 and discussed in detail above to continuously pump at the HP level of the single hydraulic pump **260**, several different hydraulic pumps **160(a-n)**, where n is an integer equal to or greater than one and corresponds to the quantity of single VFDs **140(a-n)**, single shaft electric motors **150(a-n)** and pump trailers **130(a-n)**, as positioned on different pump trailers **160** may be scaled together to scale the overall HP level that is provided to the fracking equipment as positioned on the fracking trailer **170**. In doing so, the overall HP level that is provided to the fracking equipment to continuously pump the fracking media into the well to execute the fracking operation to prepare the well for the later extraction of the fluid from the well may be easily scaled by incorporating each of the individual pump trailers **130(a-n)** each with single hydraulic pumps **160(a-n)** operating at the HP levels to scale the HP levels of the single hydraulic pumps **160(a-n)** to generate the overall HP level for the hydraulic fracking operation **100**.

(47) For example, each of the single hydraulic pumps **160(a-n)** positioned on each corresponding pump trailer **130(a-n)** may be operating on a continuous duty cycle at a HP level of at least 5000 HP. A total of eight pump trailers **130(a-n)** each with a single hydraulic pump **160(a-n)** positioned on the corresponding pump trailer **130(a-n)** results in a total of eight hydraulic pumps **160(a-n)** operating on a continuous duty cycle at a HP level of at least 5000 HP. In doing so, each of the eight hydraulic pumps **160(a-n)** continuously pump the fracking media into the well at a HP level of at least 40,000 HP and do so continuously with each of the eight hydraulic pumps **160(a-n)** operating on a continuous duty cycle. Thus, the fracking media may be continuously pumped into the well at a HP level of at least 40,000 HP to execute the fracking operation to prepare the well for the later extraction of the fluid from the well. The hydraulic pumps **160(a-n)** positioned on each corresponding pump trailer **130(a-n)** may operate on a continuous duty at any HP level and the quantity of pump trailers may be scaled to any quantity obtain an overall HP level for the hydraulic fracking operation **100** that will be apparent to those skilled in the relevant art(s) without departing from the spirit and scope of the disclosure.

(48) Further, conventional hydraulic fracking operations that incorporate diesel engines require a diesel engine to drive each conventional hydraulic pump rather than being able to consolidate the power generation to a power generation system **110** that consolidates the quantity and size of the gas turbine engines to generate the electric power. Such an increase in diesel engines significantly increases the cost of the fracking operation in that significantly more trailers and/or significantly over size/weight trailers are required to transport the diesel engines resulting in significantly more and/or specialized semi-trucks and/or trailers required to transport the diesel engines which requires significantly more CDL drivers. As the overall asset count increases at the fracking site, the overall cost increases due to the increased amount of manpower required, the costs and delays related to permitted loads, as well as an increase in the amount of rigging that is required to rig each of the diesel engines to the conventional hydraulic pumps and so on. Rather, the electric driven hydraulic fracking operation **100** decreases the asset count by consolidating the power generation to the gas turbine engines of decreased size and quantity that are consolidated into the power generation system **110**. The power distribution trailer **120** then further decreases the cost by consolidating the medium voltage cabling that is required to power each of the assets thereby decreasing the amount of rigging required.

(49) Further, conventional hydraulic fracking operations that incorporate diesel engines suffer significant parasitic losses throughout the different components included in the fracking operation. Diesel engines that generate at a power level equal to the rated power level of the conventional fracking pumps may not result in delivering the full rated power to the pump due to parasitic losses throughout the conventional diesel fracking trailer configuration. For example, the diesel engines may suffer parasitic losses when driving the hydraulic coolers and the lube pumps that are associated with the conventional hydraulic pump in addition to the parasitic losses suffered from driving the conventional hydraulic pump itself. In such an example, the diesel engine may be driving the conventional hydraulic pump that is rated at 2500 HP at the HP level of 2500 HP but due to parasitic losses, the diesel engine is actually only driving the conventional hydraulic pump at 85% of the HP level of 2500 HP due to the parasitic losses. However, the electric driven hydraulic fracking operation **100** may have the single hydraulic pump **160(a-n)** that is rated at the HP level of 5000 HP, however, the parasitic loads are controlled by equipment running in parallel with the single hydraulic pump **160(a-n)**, thus the single VFD **140(a-n)** associated with each corresponding single hydraulic pump **160(a-n)** provides all of its output electric power to the single hydraulic pump **160(a-n)**, the single hydraulic pump **160(a-n)** actually continuously pumps the fracking media into the well at 5000 HP. Thus, the asset count required for the electric driven hydraulic fracking operation **100** is significantly reduced as compared to the hydraulic fracking operations that incorporate diesel engines due to the lack of parasitic losses for the electric driven hydraulic fracking operation **100**.

(50) Further, the conventional hydraulic fracking operations that incorporate diesel engines generate significantly more noise than the electric driven hydraulic fracking operation **100**. The numerous diesel engines required in the conventional hydraulic fracking operations generate increased noise levels in that the diesel engines generate noise levels at 110 Dba. However, the gas turbine engines incorporated into the power generation system **110** of the electric driven hydraulic fracking operation **100** generate noise levels that are less than 85 Dba. Often times, the fracking site has noise regulations associated with the fracking site in that the noise levels of the fracking operation cannot exceed 85 Dba. In such situations, an increased cost is associated with the conventional hydraulic fracking operations that incorporate diesel engines in attempts to lower the noise levels generated by the diesel engines to below 85 Dba or having to build sound walls to redirect the noise in order to achieve noise levels below 85 Dba. The electric driven fracking operation **100** does not have the increased cost as the noise levels of the oilfield gas turbine engines include silencers and stacks, thus they already fall below 85 Dba.

(51) Further, the increase in the quantity of conventional hydraulic pumps further increases the

asset count which increases the cost as well as the cost of operation of the increase in quantity of conventional hydraulic pumps. Rather than having eight single hydraulic pumps **160(a-n)** rated at the HP level of 5000 HP to obtain a total HP level of 40000 HP for the fracking site, the conventional hydraulic fracking systems require sixteen conventional hydraulic pumps rated at the HP level of 2500 HP to obtain the total HP level of 40000 HP. In doing so, a significant cost is associated with the increased quantity of conventional hydraulic pumps. Further, conventional hydraulic pumps that fail to incorporate a single VFD **140(a-n)**, a single shaft electric motor **150(a-n)**, and a single hydraulic pump **160(a-n)** onto a single pump trailer **130(a-n)** further increase the cost by increasing additional trailers and rigging required to set up the numerous different components at the fracking site. Rather, the electric driven hydraulic fracking operation **100** incorporates the power distribution trailer **120** to consolidate the power generated by the power generation system **110** and then limit the distribution and the cabling required to distribute the electric power to each of the single pump trailers **130(a-n)**.

(52) In addition to the fracking equipment positioned on the fracking trailer **170** that is electrically driven by the electric power generated by the power generation system **110** and each of the VFDs **140(a-n)**, single shaft electric motors **150(a-n)**, and the single hydraulic pumps **160(a-n)** that are also electrically driven by the electric power generated by the power generation system **110**, a plurality of auxiliary systems **190** may be positioned at the fracking site may also be electrically driven by the electric power generated by power generation system **110**. The auxiliary systems **190** may assist each of the single hydraulic pumps **160(a-n)** as well as the fracking equipment positioned on the fracking trailer **170** as each of the hydraulic pumps **160(a-n)** operate to execute the fracking operation to prepare the well for the later extraction of the fluid from the well. In doing so, the auxiliary systems **190** may be systems in addition to the fracking equipment positioned on the fracking trailer **170** and the single hydraulic pumps **160(a-n)** that are required to prepare the well for the later execution of the fluid from the well.

(53) For example, the auxiliary systems **190**, such as a hydration system that provides adequate hydration to fracking media as the single hydraulic pumps **160(a-n)** continuously pump the fracking media into the well. Thus, auxiliary systems **190** may include but are not limited to hydration systems, chemical additive systems, blending systems, sand storage and transporting systems, mixing systems and/or any other type of system that is required at the fracking site that is addition to the fracking equipment positioned on the fracking trailer **170** and the single hydraulic pumps **160(a-n)** that may be electrically driven by the electric power generated by the power generation system **110** that will be apparent to those skilled in the relevant art(s) without departing from the spirit and scope of the disclosure.

(54) The electric power generated by the power generation system **110** may thus be distributed by the power distribution trailer **120** such that the electric power generated by the power generation system **110** may also be incorporated to power the auxiliary systems **190**. In doing so, the electric power generated by the power generation system **110** may be incorporated to not only drive the pump trailers **130(a-n)** via the single VFDs **140(a-n)** positioned on each pump trailer **130(a-n)** but to also power the auxiliary systems **190**. Thus, the hydraulic fracking operation **100** may be completely electric driven in that each of the required systems positioned on the fracking site may be powered by the electric power generated by the electric power that is consolidated to the power generation system **110**.

(55) As noted above, each of the single VFDs **140(a-n)** may include a sophisticated control system that may control in real-time the operation of the single shaft electric motors **150(a-n)** and the single hydraulic pumps **160(a-n)** in order for the single shaft electric motors **150(a-n)** and the single hydraulic pumps **160(a-n)** to optimally operate to continuously pump the fracking media into the well to execute the fracking operation to prepare the well for the later extraction of the fluid from the well. However, the fracking control center **180** that may be positioned at the fracking site and/or remote from the fracking site may also control the single VFDs **140(a-n)** and in doing so

control the real-time operation of the single shaft electric motors **150(a-n)** and the single hydraulic pumps **160(a-n)** in order for the single shaft electric motors **150(a-n)** and the single hydraulic pumps **160(a-n)** to optimally operate to continuously pump the fracking media into the well to execute the fracking operation to extract the fluid from the well. In doing so, the fracking control center **180** may intervene to control the single VFDs **140(a-n)** when necessary. The fracking control center **180** may also control the fracking equipment positioned on the fracking trailer **170** as well as the auxiliary systems **190** in order to ensure that the fracking operation is optimally executed to prepare the well for the later extraction of the fluid from the well.

(56) Communication between the fracking control center **180** and the single VFDs **140(a-n)**, the fracking equipment positioned on the fracking trailer **170**, and/or the auxiliary systems **190** may occur via wireless and/or wired connection communication. Wireless communication may occur via one or more networks **105** such as the internet or Wi-Fi wireless access points (WAP). In some embodiments, the network **105** may include one or more wide area networks (WAN) or local area networks (LAN). The network may utilize one or more network technologies such as Ethernet, Fast Ethernet, Gigabit Ethernet, virtual private network (VPN), remote VPN access, a variant of IEEE 802.11 standard such as Wi-Fi, and the like. Communication over the network **105** takes place using one or more network communication protocols including reliable streaming protocols such as transmission control protocol (TCP), Ethernet, Modbus, CanBus, EtherCAT, ProfiNET, and/or any other type of network communication protocol that will be apparent from those skilled in the relevant art(s) without departing from the spirit and scope of the present disclosure. Wired connection communication may occur but is not limited to a fiber optic connection, a coaxial cable connection, a copper cable connection, and/or any other type of direct wired connection that will be apparent from those skilled in the relevant art(s) without departing from the spirit and scope of the present disclosure. These examples are illustrative and not intended to limit the present disclosure.

(57) Electric Power Distribution and Control

(58) FIG. 3 illustrates a block diagram of an electric driven hydraulic fracking system that provides an electric driven system to execute a fracking operation in that the electric power is consolidated in a power generation system and then distributed such that each component in the electric driven hydraulic fracking system is electrically powered. An electric driven hydraulic fracking system **300** includes a power generation system **310**, a power distribution trailer **320**, a plurality of pump trailers **330(a-n)**, a plurality of single VFDs **340(a-n)**, a switchgear configuration **305**, a plurality of trailer auxiliary systems **315(a-n)**, a plurality of switchgears **325(a-n)**, a switchgear transformer configuration **335**, and fracking equipment **370**. The electric power is consolidated in the power generation system **310** and then distributed at the appropriate voltage levels by the power distribution trailer **320** to decrease the medium voltage cabling required to distribute the electric power. The single VFDs **340(a-n)** and the trailer auxiliary systems **315(a-n)** positioned on the pump trailers **330(a-n)** as well as the fracking control center **380** and auxiliary systems **390** are electrically powered by the electric power that is consolidated and generated by the power generation system **310**. The electric driven hydraulic fracking system **300** shares many similar features with the hydraulic fracking operation **100** and the single pump configuration **200**; therefore, only the differences between the electric driven hydraulic fracking system **300** and the hydraulic fracking operation **100** and single pump configuration **200** are to be discussed in further detail.

(59) As noted above, the power generation system **310** may consolidate the electric power **350** that is generated for the electric driven hydraulic fracking system **300** such that the quantity and size of the power sources included in the power generation system **310** is decreased. As discussed above, the power generating system **310** may include numerous power sources as well as different power sources and any combination thereof. For example, the power generating system **310** may include power sources that include a quantity of gas turbine engines. In another example, the power generation system **310** may include a power source that includes an electric power plant that

independently generates electric power for an electric utility grid. In another example, the power generation system **310** may include a combination of gas turbine engines and an electric power plant. The power generation system **310** may generate the electric power **350** at a power level and a voltage level.

(60) The power generation system **310** may generate electric power at a power generation voltage level in which the power generation voltage level is the voltage level that the power generation system is capable of generating the electric power **350**. For example, the power generation system **310** when the power sources of the power generation system **310** include a quantity of gas turbine engines may generate the electric power **350** at the voltage level of 13.8 kV which is a typical voltage level for electric power **350** generated by gas turbine engines. In another example, the power generation system **310** when the power sources of the power generation system include an electric power plant may generate the electric power **350** at the voltage level of 12.47 kV which is a typical voltage level for electric power **350** generated by an electric power plant.

(61) In another example, the power generation system **310** may generate electric power **350** that is already at the VFD voltage level to power the single shaft electric motor **150(a-n)** as discussed in detail below. In such an example, the power generation system **310** may generate the electric power **350** that is already at the VFD voltage level of 4160V. In another example, the power generation system **310** may generate the electric power **350** at the power generation voltage level in range of 4160V to 15 kV. In another example, the power generation system **310** may generate electric power **350** at the power generation voltage level of up to 38 kV. The power generation system **310** may generate the electric power **350** at any power generation voltage level that is provided by the power sources included in the power generation system **310** that will be apparent to those skilled in the relevant art(s) without departing from the spirit and scope of the disclosure. The power generation system **310** may then provide the electric power **350** at the power generation voltage level to the power distribution trailer **320** via a medium voltage cable.

(62) In continuing for purposes of discussion, the power distribution trailer **320** may then distribute the electric power **350** at the power generation voltage level to a plurality of single VFDs **340(a-n)**, where n is an integer equal to or greater than two, with each single VFD **340(a-n)** positioned on a corresponding single trailer **330(a-n)** from a plurality of single trailers, where n is an integer equal to or greater than two. The power distribution trailer **320** may include a switchgear configuration **305** that includes a plurality of switchgears **325(a-n)**, where n is an integer equal to or greater than two, to distribute the electric power **350** generated by the at least one power source included in the power distribution trailer **310** at the power generation voltage level **360** to each corresponding single VFD **340(a-n)** positioned on each corresponding trailer **330(a-n)**.

(63) Since the electric power **350** is consolidated to the power generation system **310**, the switch gear configuration **305** of the power distribution trailer **320** may distribute the electric power **350** at the power generation voltage level as generated by the power generation system **310** to each of the single VFDs **340(a-n)** as electric power **360** at the power generation voltage level such that the each of the single VFDs **340(a-n)** may then drive the single shaft electric motors and the single hydraulic pumps as discussed in detail below. For example, the switch gear configuration **305** of the power distribution trailer **320** may distribute the electric power **350** at the power generation voltage level of 13.8 kV to each of the single VFDs **340(a-n)** as electric power **360** at the power generation voltage level of 13.8 kV when the power distribution system **310** has power sources that include gas turbine engines. In another example, the switch gear configuration **305** of the power distribution trailer **320** may distribute the electric power **350** at the power generation level of 12.47 kV to each of the single VFDs **340(a-n)** as electric power **360** at the power generation level of 12.47 kV when the power distribution **310** has power sources that include an electric power plant.

(64) In order for the electric power to be consolidated to the power generation system **310** as well as to provide an electric driven system in which each of the components of the electric driven hydraulic fracking system **300** is driven by the electric power generated by the power generation

system **310**, the power distribution trailer **320** provides the flexibility to distribute the electric power **350** generated by the power generation system **310** at different voltage levels. In adjusting the voltage levels that the electric power **350** generated by the power generation system **310** is distributed, the power distribution trailer **320** may then distribute the appropriate voltage levels to several different components included in the electric driven hydraulic fracking system **300** to accommodate the electric power requirements of the several different components included in the electric driven hydraulic fracking system **300**. For example, the power distribution trailer **320** may distribute the electric power **360** generated by the power generation system **310** at the voltage level of 13.8 kV as generated by the power generation system **310** via the switch gears **325(a-n)** to each of the single VFDs **340(a-n)** for the each of the single VFDs **340(a-n)** to drive the single shaft electric motors and the single hydraulic pumps. In another example, the power distribution trailer **320** may distribute the electric power **360** generated by the power generation system **310** at the voltage level of 12.47 kV as generated by the power generation system **310** via the switch gears **325(a-n)** to each of the single VFDs **340(a-n)** for each of the single VFDs **340(a-n)** to drive the single shaft electric motors and the single hydraulic pumps.

(65) However, the electric power distribution trailer **320** may also distribute the electric power **350** generated by the power generation system **310** at a decreased voltage level from the voltage level of the electric power **350** originally generated by the power generation system **310**. Several different components of the electric driven hydraulic fracking system **300** may have power requirements that require electric power at a significantly lower voltage level than the electric power **350** originally generated by the power generation system **310**. In doing so, the power distribution trailer **320** may include a switchgear transformer configuration **335** that may step-down the voltage level of the electric power **350** as originally generated by the power distribution trailer **310** to a lower voltage level that satisfies the power requirements of those components that may not be able to handle the increased voltage level of the electric power **350** originally generated by the power distribution trailer **310**. In doing so, the electric power distribution trailer **320** may provide the necessary flexibility to continue to consolidate the electric power **350** to the power generation system **310** while still enabling each of the several components to be powered by the electric power generated by the power generation system **310**.

(66) For example, the switchgear transformer configuration **335** may convert the electric power **350** generated by the at least one power source of the power generation system **310** at the power generation voltage level to at an auxiliary voltage level that is less than the power generation voltage level. The switchgear transformer configuration **335** may then distribute the electric power **355** at the auxiliary voltage level to each single VFD **340(a-n)** on each corresponding single trailer **330(a-n)** to enable each single VFD **340(a-n)** from the plurality of single VFDs **340(a-n)** to communicate with the fracking control center **380**. The switchgear transformer configuration **335** may also distribute the electric power **355** at the auxiliary voltage level to a plurality of auxiliary systems **390**. The plurality of auxiliary systems **390** assists each single hydraulic pump as each hydraulic pump from the plurality of single hydraulic pumps operate to prepare the well for the later extraction of the fluid from the well.

(67) In such an example, the switchgear transformer configuration **335** may convert the electric power **350** generated by the power generation system **310** with power sources include gas turbine engines at the power generation voltage level of 13.8 kV to an auxiliary voltage level of 480V that is less than the power generation voltage level of 13.8 kV. The switchgear transformer configuration **335** may then distribute the electric power **355** at the auxiliary voltage level of 480V to each single VFD **340(a-n)** on each corresponding single trailer **330(a-n)** to enable each single VFD **340(a-n)** from the plurality of single VFDs **340(a-n)** to communicate with the fracking control center **380**. The switchgear transformer configuration **335** may also distribute the electric power **355** at the auxiliary voltage level of 480V to a plurality of auxiliary systems **390**.

(68) In another example, the switchgear transformer configuration **335** may convert the electric

power **350** generated by the power generation system **310** with power sources that include an electric power plant at the power generation voltage level of 12.47 kV to an auxiliary voltage level of 480V that is less than the power generation voltage level of 12.47 kV. In another example, the switchgear transformer configuration **33** may convert the electric power **350** at the power generation voltage level generated by the power generation system **310** to the auxiliary voltage level of 480V, 120V, 24V and/or any other auxiliary voltage level that is less than the power generation voltage level. The switchgear transformer configuration **335** may convert the electric power **350** at the power generation voltage level generated by the power generation system **310** to any auxiliary voltage level that is less than the power generation voltage level to assist each single VFD **340(a-n)** in executing operations that do not require the electric power **360** at the power generation voltage level that will be apparent to those skilled in the relevant art(s) without departing from the spirit and scope of the disclosure.

(69) Unlike each of the single VFDs **340(a-n)** that may convert the electric power **360** at the power generation voltage level to drive the single shaft electric motors and the single hydraulic pumps, the fracking control center **380**, the auxiliary systems **390**, the trailer auxiliary systems **315(a-n)** as well as the operation of features of the single VFDS **340(a-n)** that are unrelated to the driving of the single shaft electric motors and the single hydraulic pumps require the electric power to be stepped down to the electric power **355** at the auxiliary voltage level. The switchgear transformer configuration **335** may provide the necessary flexibility to step-down the electric power **360** at the power generation voltage level to the generate the electric power **355** at the auxiliary voltage level such that the remaining components of the electric driven hydraulic fracking system **300** may also be electrically driven by the electric power consolidated to the power generation system **310**.

(70) In stepping down the electric power **350** generated by the power generation system **310** at the power generation voltage level, the switchgear transformer configuration **335** may provide the electric power **355** at the auxiliary voltage level to the auxiliary systems **390**. In doing so, the auxiliary systems **390** may be electrically driven by the electric power **355** at the auxiliary voltage level such that the electric power consolidated by the power generation system **310** may drive the auxiliary systems **390**. The auxiliary systems **390** may include but are not limited hydration systems, chemical additive systems, fracturing systems, blending systems, mixing systems and so on such that each of the auxiliary systems **390** required to execute the fracking operation may be electrically driven by the electric power consolidated by the power generation system **310**. Further, the power distribution trailer **320** may also route a communication link **365** to each of the auxiliary systems **390** such that the fracking control center **380** may intervene and control each of the auxiliary systems **390** via the communication link **365** if necessary.

(71) The switchgear transformer configuration **335** may also provide the electric power **355** at the auxiliary voltage level to the fracking control center **380**. In providing the auxiliary voltage level to the fracking control center **380**, the fracking control center **380** may remotely control the auxiliary systems **390**, the single VFDs **340(a-n)**, as well as the trailer auxiliary systems **315(a-n)** as requested by the fracking control center **380**. The power distribution trailer **320** may route the communication link **365** to the auxiliary systems **390**, the single VFDs **340(a-n)**, and the trailer auxiliary systems **315(a-n)** such that the fracking control center **380** may communicate with each of the auxiliary systems **390**, the single VFDs **340(a-n)**, and the trailer auxiliary systems **315(a-n)** and thereby control via the communication link **365**. As discussed above, the communication link **365** may be a wireline and/or wireless communication link.

(72) The switchgear transformer configuration **335** may also provide the electric power **355** at the auxiliary voltage level to each of the single VFDs **340(a-n)**. As discussed above and below, the single VFDs **340(a-n)** convert the electric power **360** generated by the power generation system **310** at the power generation voltage level to drive the single shaft electric motors and the single hydraulic pumps. However, the single VFD **340(a-n)** may also operate with different functionality without having to drive the single shaft electric motors and the single hydraulic pumps. For

example, the auxiliary systems **315(a-n)** positioned on the pump trailers **330(a-n)** and/or included in the single VFDs **340(a-n)** may operate as controlled by a corresponding VFD controller **345(a-n)** that is positioned on the corresponding single trailer **330(a-n)** and associated with the corresponding single VFD **340(a-n)**.

(73) In doing so, the single VFD controllers **345(a-n)** may operate the auxiliary systems **315(a-n)** when the single VFD **340(a-n)** is simply provided the electric power **355** at the auxiliary voltage level rather than having to operate with the electric power **360** at the power generation voltage level. In doing so, the fracking control center **380** may also communicate with the VFD controllers **345(a-n)** and the single VFDs **340(a-n)** as well as the trailer auxiliary systems **315(a-n)** via the communication link **365** when the stepped-down electric power **355** at the auxiliary voltage level is provided to each of the single VFDs **340(a-n)**. In addition to operating auxiliary systems **315(a-n)** when the corresponding single VFD **340(a-n)** is provided the electric power **355** at the auxiliary voltage level, the VFD controller **345(a-n)** may also operate the trailer auxiliary systems **315(a-n)** as well as control the corresponding single shaft electric motor **150(a-n)** that then drives each of the corresponding hydraulic pumps **160(a-n)** to continuously pump the fracking media into the well to execute the fracking operation to extract the fluid from the well when the electric power **360** at the power generation voltage level is provided to the single VFDs **340(a-n)**.

(74) For example, the single VFDs **340(a-n)** may operate at a reduced capacity when the switchgear transformer configuration **335** provides the electric power **355** at the auxiliary voltage level. In doing so, the single VFDs **340(a-n)** may operate in a maintenance mode in which the electric power **355** at the auxiliary voltage level is sufficient for the single VFDs **340(a-n)** to spin the single shaft electric motors but not sufficient to drive the single shaft electric motors at the RPM levels that the single shaft electric motors are rated. In operating the single VFDs **340(a-n)** in the maintenance mode with the electric power **355** at the auxiliary voltage level, the hydraulic pumps as well as the fracking equipment **370** may be examined and maintenance may be performed on the hydraulic pumps and the fracking equipment **370** to ensure the hydraulic pumps **160(a-n)** and the fracking equipment **370** are operating adequately. The VFD controllers **345(a-n)** of the single VFDs **340(a-n)** may execute the functionality of the single VFDs **340(a-n)** when operating in the maintenance mode. The fracking control center **380** may also remotely control the single VFDs **340(a-n)** via the communication link **365** to execute the functionality of the single VFDs **340(a-n)** when operating in the maintenance mode.

(75) In another example, the trailer auxiliary systems **315(a-n)** may be operated when the single VFDs **340(a-n)** are operating at the reduced capacity when the switchgear transformer configuration **335** provides the electric power **355** at the auxiliary voltage level. The trailer auxiliary systems **315(a-n)** may be auxiliary systems positioned on the pump trailers **330(a-n)** and/or included in the single VFDs **340(a-n)** such that auxiliary operations may be performed on the single VFDs **340(a-n)**, the single shaft electric motors, and/or the single hydraulic pumps to assist in the maintenance and/or operation of the single VFDs **340(a-n)** the single shaft electric motors and/or single hydraulic pumps when the electric power **355** at the auxiliary voltage level is provided to the single VFDs **340(a-n)**. For example, the trailer auxiliary systems **315(a-n)** may include but are not limited to motor blower systems, the lube oil controls, oil heaters, VFD fans, and/or any other type of auxiliary system that is positioned on the pump trailers **330(a-n)** and/or included in the single VFDs **340(a-n)** to assist in the maintenance and/or operation of the single VFDs **340(a-n)**, single shaft electric motors, and/or single hydraulic pumps that will be apparent to those skilled in the relevant art(s) without departing from the spirit and scope of the disclosure.

(76) In an embodiment, each of the single VFDs **340(a-n)** may include a transformer (not shown) also positioned on the single trailers **330(a-n)** that may generate the electric power **355** at the auxiliary voltage level. Rather than have the switchgear transformer configuration **335** distribute the electric power **355** at the auxiliary voltage level to each of the single VFDs **340(a-n)**, each of the transformers may be able to generate the electric power **355** at the auxiliary voltage level such

that each of the features discussed in detail above that are operated due to the electric power **355** at the auxiliary voltage level may be performed by the electric power **355** at the auxiliary voltage level as generated by each of the transformers. As a result, cabling between the power distribution trailer **320** and each of the single VFDs **340(a-n)** may be reduced due to no longer requiring the cabling to propagate the electric power **355** at the auxiliary voltage level from the switchgear transformer configuration **335** to each of the single VFDs **340(a-n)**.

(77) Parameter Monitoring and Control

(78) In an embodiment, the controls for each of the trailer auxiliary systems **315(a-n)** may be embedded in the single VFDs **340(a-n)** such that the VFD controllers **345(a-n)** may control each of the trailer auxiliary systems **315(a-n)** with the sophisticated control system included in each of the single VFDs **340(a-n)**. However, the fracking control center **380** may also control each of the trailer auxiliary systems **315(a-n)** based on the communication link **365** in that the fracking control center **380** may hook into the controls for each of the trailer auxiliary systems **315(a-n)** that may be embedded in the single VFDs **340(a-n)** and control each of the trailer auxiliary systems **315(a-n)** remotely. In doing so, the data map of the fracking control center **380** may be mapped to the controls for each of the trailer auxiliary systems **315(a-n)** embedded in the single VFDs **340(a-n)** providing the single VFDs **340(a-n)** with the modularity to be easily externally controlled by any fracking control center **380** positioned at the fracking site and/or positioned remote from the fracking site.

(79) For example, the fracking control center **380** may request to activate the lubrication pumps included in the trailer auxiliary systems **315(a-n)** positioned on the pump trailers **330(a-n)**. The fracking control center **380** may simply activate the lube bit at the fracking control center **380** to activate the lubrication pumps to lube the single hydraulic pumps positioned on the pump trailers **330(a-n)**. The command then cascades down from the fracking control center **380** to the VFD controls **345(a-n)** for the lubrication pumps embedded in the single VFDs **340(a-n)** via the communication link **365** and enables the fracking control center **380** to remotely activate the lubrication pumps to initiate circulating oil throughout the single hydraulic pumps.

(80) The VFD controllers **345(a-n)** associated with each single VFD **340(a-n)** may automatically adjust the trailer auxiliary systems **315(a-n)** based on parameters monitored by the VFD controllers **345(a-n)** in real-time as the single hydraulic pumps are continuously pumping the fracking media into the well to execute the fracking operation to prepare the well for the later extraction of the fluid from the well. Real-time is the state of the parameters monitored by the VFD controllers **345(a-n)** as triggered by the operation of the electric driven hydraulic fracking system **100** as the hydraulic pumps **160(a-n)** continuously pump the fracking media into the well to execute the fracking operation. As the single hydraulic pumps **160(a-n)** are continuously pumping the fracking media into the well to execute the fracking operation to prepare the well for the later extraction of the fluid from the well, several different parameters may be continuously monitored by the single VFDs **340(a-n)** to determine whether the different parameters exceed and/or decrease below thresholds that may be indicative that the single VFDs **340(a-n)** may have to execute a corrective action to restore the different parameters to an adequate level. The single VFDs **340(a-n)** may then automatically execute the corrective actions to restore the different parameters to an adequate level and in doing so may prevent damage to any of the components of the electric driven fracking system **300** and/or a halt in the fracking operation.

(81) For example, the VFD controllers **345(a-n)** may monitor the temperature of the single VFDs **340(a-n)**, the single hydraulic pumps, and the single shaft electric motors to determine whether the temperature exceeds a temperature threshold in real-time. The temperature threshold may be indicative that the temperature of the single VFDs **340(a-n)**, the single shaft electric motors, and/or the single hydraulic pumps may be increasing and indicative that a corrective action in cooling the temperature of the single VFDs **340(a-n)**, the single shaft electric motors, and/or the single hydraulic pumps may be required to ensure that damage is not inflicted onto the single VFDs

340(a-n), the single shaft electric motors, and/or the single hydraulic pumps resulting in a halting of the fracking operation. Thus, the VFD controllers **345(a-n)** may then in real-time activate the fans positioned on the pump trailers **330(a-n)** to decrease the temperature of the single VFDs **340(a-n)**, the single shaft electric motors, and/or the single hydraulic pumps. In doing so, the VFD controllers **345(a-n)** may prevent damage to the single VFDs **340(a-n)**, the single shaft electric motors, and/or the single hydraulic pumps by cooling each appropriately by activating the fans when the temperature increased above the temperature threshold.

(82) In another example, the VFD controllers **345(a-n)** may monitor the pressure at the well head of the well as the fracking media is continuously injected into the well to determine whether the pressure of the fracking media exceeds a pressure threshold. The pressure threshold may be a regulatory threshold in that when the pressure of the fracking media at the well head in the well exceeds the pressure threshold, such as 15000 PSI, then the iron is required to be pulled out of the well based on regulation requirements such that the iron may be replaced and/or examined for any cracks and recertified. Such a halt in the fracking operation may significantly delay the fracking operation as well as significantly increase the cost. Thus, the VFD controllers **345(a-n)** may monitor the pressure at the well head of the well in real-time to determine whether the pressure exceeds the pressure threshold. The VFD controllers **345(a-n)** may then execute a corrective action when the pressure exceeds the pressure threshold.

(83) In an embodiment, the single VFDs **340(a-n)** may execute a dual frequency injection into the single shaft electric motors to produce a moderate braking effect on the single shaft electric motors when an unloaded motor needs to be stopped as quickly as possible. In another embodiment, a contactor may connect to a resistor such that the flux on the single shaft electric motor is maintained. The single VFDs **340(a-n)** may then transition the resistor across the line to facilitate a rapid decrease the RPM level of the single shaft electric motor when an unloaded motor needs to be stopped as quickly as possible. In another embodiment, the fracking control center **380** may remotely activate a clutch that may be installed between the single shaft electric motor and single hydraulic pump such that the fracking control center **380** may release the clutch to disengage the single shaft electric motor from the single hydraulic pump to enable the single hydraulic pump to decrease the HP level to disconnect the inertial forces an unloaded motor from continuing to drive the single hydraulic pump **160(a-n)** when the single hydraulic pump **160(a-n)** needs to be stopped as quickly as possible.

(84) The single VFDs **340(a-n)** may monitor any type of operation parameter such as but not limited to pressure change of the fluid flowing through the single hydraulic pump, flow rate, volume, temperature, pump efficiency, viscosity, thermal properties, Reynolds number, and/or any other type of parameter that may be indicative as to whether a corrective action should be executed to prevent damage to any component of the electric driven hydraulic fracking system **300** and/or to halt to fracking operation that will be apparent to those skilled in the relevant art(s) without departing from the spirit and scope of the disclosure.

(85) FIG. 4 illustrates a block diagram of an electric driven fracking system **400** where the VFD controller, the fracking control center **380**, and/or the power distribution trailer controller **430** monitors various operation parameters associated with the operation of the electric driven fracking system **400**. The VFD controller **405**, the fracking control center **380**, and/or the power distribution trailer controller **430** may then automatically execute corrective actions in response to the monitored operation parameters. In doing so, the VFD controller **405**, the fracking control center **380**, and/or power distribution trailer controller **430** may continuously monitor the operation parameters and execute corrective actions in real-time when necessary to maintain the operation parameters within their corresponding operation parameter thresholds to maintain the operation of the electric driven fracking system **400**. The electric driven fracking system **400** shares many similar features with the hydraulic fracking operation **100**, the single pump configuration **200**, and the electric driven hydraulic fracking system **300**; therefore, only the differences between the

electric driven hydraulic fracking system **400** and the hydraulic fracking operation **100**, the single pump configuration **200**, and the electric driven hydraulic fracking system **300** are to be discussed in further detail.

(86) In one embodiment of the present disclosure, the VFD controller **405**, the fracking control center **380**, and/or the power distribution trailer controller **430** may connect and/or communicate with via communication link **365** and/or wireless communication to one or more modules that when commands are received by the VFD controller **405**, the fracking control center **380**, and/or the power distribution trailer controller **430**, a corrective action is initiated based on the monitoring of operation parameters by each of the modules to maintain the operation parameters within the corresponding operation thresholds to maintain the operation of the electric driven hydraulic fracking system **400**. The one or more modules motor temperature sensor **425**, the enclosure temperature sensor **410**, the humidity sensor **420**, the VFD temperature sensor **430**, the percent load operation sensor **440**, the auxiliary system sensor **450**, the pressure sensor **460**, the torque sensor **470**, the pump speed sensor **480**, the electrical characteristic sensor **415**, the ground current sensor **435**, and the power consumption sensor **445** and/or any other module that may monitor operation parameters of the electric driven hydraulic fracking system to maintain the operation of the electric driven hydraulic fracking system that will be apparent to those skilled in the relevant art(s) without departing from the spirit and scope of the disclosure.

(87) The VFD controller **405** includes a microprocessor **480** and a memory **495** and may be referred to as a computing device or simply “computer”. For example, the VFD controller **405** may be workstation, mobile device, computer, cluster of computers, remote cloud service, set-top box, or other computing device. In one embodiment of the present invention, multiple modules may be implemented on the same computing device. Such a computing device may include software, firmware, hardware, or a combination thereof. Software may include one or more applications on an operating system. Hardware can include, but is not to be limited to, the microprocessor **290** and/or the memory **295**.

(88) The fracking control center **380** also includes a microprocessor (not shown) and a memory (not shown) and may be referred to as a computing device or simply “computer”. For example, the fracking control center **380** may be workstation, mobile device, computer, cluster of computers, remote cloud service, set-top box, or other computing device. In one embodiment of the present invention, multiple modules may be implemented on the same computing device. Such a computing device may include software, firmware, hardware, or a combination thereof. Software may include one or more applications on an operating system. Hardware can include, but is not to be limited to, the microprocessor and/or the memory.

(89) The power distribution trailer controller **430** also includes a microprocessor (not shown) and a memory (not shown) and may be referred to as a computing device or simply “computer”. For example, the power distribution trailer controller **430** may be a workstation, mobile device, computer, cluster of computers, remote cloud service, set-top box, or other computing device. In one embodiment of the present invention, multiple modules may be implemented on the same computing device. Such a computing device may include software, firmware, hardware, or a combination thereof. Software may include one or more applications on an operating system. Hardware can include, but is not to be limited to, the microprocessor and/or the memory.

(90) The VFD controller **405**, the fracking control center **380**, and/or the power distribution trailer controller **430** may communication with each of the motor temperature sensor **425**, the enclosure temperature sensor **410**, the humidity sensor **420**, the VFD temperature sensor **430**, the percent load operation sensor **440**, the auxiliary system sensor **450**, the pressure sensor **460**, the torque sensor **470**, the pump speed sensor **480**, the electrical characteristic sensor **415**, the ground current sensor **435**, and the power consumption sensor **445**. The communication between the VFD controller, the fracking control center **380**, and/or the power distribution trailer controller **430** occurs via the communication link **365**.

(91) As noted above, the communication between all components included in the electric driven hydraulic fracking system **400** may occur via the VFD controller **405**, the fracking control center **380**, and/or the power distribution trailer controller **430** based on the communication link **365** between the VFD controller **405**, the fracking control center **380**, and/or the power distribution trailer controller **430** and each corresponding component. The communication link **365** may be embodied via wireless and/or wired connection communication. For example, wireless communication via the communication link **365** may occur via one or more networks **105** such as the internet or Wi-Fi wireless access points (WAP). In some embodiments, the network **105** may include one or more wide area networks (WAN) or local area networks (LAN). The network may utilize one or more network technologies such as Ethernet, Fast Ethernet, Gigabit Ethernet, virtual private network (VPN), remote VPN access, a variant of IEEE 802.11 standard such as Wi-Fi, and the like. Communication over the network **105** takes place using one or more network communication protocols including reliable streaming protocols such as transmission control protocol (TCP), Ethernet, Modbus, CanBus, EtherCAT, ProfiNET, and/or any other type of network communication protocol that will be apparent from those skilled in the relevant art(s) without departing from the spirit and scope of the present disclosure. Wired connection communication via the communication link **365** may occur but is not limited to a fiber optic connection, a coaxial cable connection, a copper cable connection, and/or any other type of direct wired connection that will be apparent from those skilled in the relevant art(s) without departing from the spirit and scope of the present disclosure. These examples are illustrative and not intended to limit the present disclosure.

(92) For simplicity of discussion, the following discussion regarding the monitoring of operation parameters and the subsequent execution of corrective action to maintain the operation parameters within the operation threshold to maintain the operation of the electric driven hydraulic fracking system **400** is to be discussed with regard to the VFD controller **405**. However, any of the below discussion may be substituted via the fracking control center **380**, and/or the power distribution trailer controller **430**. The VFD controller **405**, the fracking control center **380**, and the power distribution trailer controller **430** provide a conduit of data associated with the monitoring of operation parameters with each other via communication link **365** such that any data obtained and/or monitored by the VFD controller **405**, the fracking control center **380** and/or the power distribution trailer controller **430** may then be automatically provided to each of the VFD controller **405**, the fracking control center **380**, and/or the power distribution trailer controller **430** via the communication link **365**. In doing so any of the VFD controller **405**, the fracking control center **380**, and/or the power distribution controller **430** may executed the necessary corrective action to maintain each operation parameter within the corresponding operation threshold to maintain the operation of the electric driven hydraulic fracking system **400**.

(93) The VFD controller **405** may monitor a plurality of operation parameters associated with an operation of the electric driven hydraulic fracking system **400** as each component of the electric driven fracking system **400** operates to determine whether at least one operation parameter deviates beyond at least one corresponding operation parameter threshold. Each of the operation parameters provides an indicator as to an operation status of a corresponding component of the electric driven hydraulic fracking system **400**. Each operation parameter provides insight to the VFD controller **405** as to the how the corresponding component that the operation parameter is monitoring is operating. The electric driven hydraulic fracking system **400** may include numerous components with each component operating and contributing to the operation of the electric driven hydraulic fracking system **400**. With such numerous components operating and contributing to the operation of the electric driven hydraulic fracking system **400**, any operation of such component that begins to deviate beyond the corresponding operation threshold may result in a significant increase in disturbance in the operation and/or damage to the electric hydraulic fracking system **400**. Any such disturbance in the operation and and/or damage to the electric hydraulic fracking system **400** may result in the significant amounts of money lost by the operating entity of the electric hydraulic

fracking system **400** if the electric hydraulic fracking system is required to shut down.

(94) The operation threshold is the operation threshold for each component included in the electric hydraulic fracking system **400** that when deviated from may result in a significant increase in risk that the operation of the component may result in a disturbance in the operation and/or cause damage to the electric hydraulic fracking system **400** thereby jeopardizing the operation of the electric hydraulic fracking system **400**. The VFD controller **405** may initiate at least one corrective action when each operating parameter deviates beyond the at least one corresponding operation threshold. Initiating the corrective action when each operation parameter deviates beyond the at least one corresponding operation threshold maintains the operation of the electric driven hydraulic fracking system **400**.

(95) The corrective action may be an action launched by the VFD controller **405** in response to the operation parameter deviating from the corresponding operation threshold to maintain the operation of the electric driven hydraulic fracking system **400** without any disruption and/or any damage to the electric driven hydraulic fracking system **400**. In doing so, the corrective action launched by the VFD controller **405** in response to the operation parameter deviating from the corresponding operation threshold may neutralize any potential impact to the disruption of the operation and/or damage to the electric driven hydraulic fracking system **400** to maintain the operation of the electric driven hydraulic fracking system **400** such that the electric driven hydraulic fracking system **400** is not required to be shut down.

(96) For example, a motor temperature sensor **425** may be positioned on the single pump trailer and may monitor the operation parameter of motor temperature of the component of the single shaft electric motor that is positioned on the single pump trailer. The VFD controller **405** may monitor the motor temperature of the single shaft electric motor as the single shaft electric motor operates to determine if the motor temperature increases beyond the operation threshold. An increase of the motor temperature beyond the operation threshold is indicative that the operation of the single shaft electric motor is becoming significantly hot and that the performance of the single shaft electric motor may be negatively impacted and/or damaged such as shutting down. Such a significant negative impact to the single shaft electric motor may have significant disruption in the electric driven hydraulic fracking system **400** with the single shaft electric motor failing to adequately operate. In an embodiment, the VFD controller **405** may execute the corrective action to automatically shut the single shaft electric motor when the motor temperature measured by the motor temperature sensor **425** increases beyond the operation threshold to thereby prevent the negatively impacted single shaft electric motor from damaging other components included in the electric driven hydraulic fracking system **400**.

(97) However, automatically shutting down the single shaft electric motor when the single motor temperature sensor **425** measures the motor temperature that exceeds the operation threshold may also result the shutting down of the complete electric driven hydraulic fracking system **400**. Such a complete shutdown of the electric driven hydraulic fracking system **400** may result in a significant amount of money lost by the operating entity during the complete shutdown of the electric driven hydraulic fracking system **400**. Further, the increased motor temperature that exceeds the operation threshold by the motor temperature sensor **425** may be due to the motor temperature sensor **425** failing to operate correctly. In such an example, the increase in the motor temperature beyond the operation threshold is not due to the negative operation of the single shaft electric motor but the motor temperature sensor **425**.

(98) Rather than automatically shutting down the single shaft electric motor by the VFD controller **405** when the motor temperature measured by the motor temperature sensor **425** exceeds the operation threshold, in an embodiment, the VFD controller **405** may execute the corrective action to funnel that data to the fracking control center **380**. The fracking control center **380** may determine that the motor temperature of the single shaft electric motor measured by the motor temperature sensor **425** is 200° C. However, the motor temperature measured by other motor

temperature sensors positioned on the single pump trailer of the single shaft electric motor may be 50° C. The fracking control center **380** may determine that the motor temperature sensor **425** is negatively operating and not the single shaft electric motor. As a result, the fracking control center **380** may execute the corrective action to override the motor temperature sensor **425** and maintain full operation of the single shaft electric motor thereby maintaining full operation of the electric driven hydraulic fracking system **400** rather than shut down the electric driven hydraulic fracking system **400** simply due to the negative operation of the motor temperature sensor **425**.

(99) The components of the electric driven hydraulic fracking system **400** that the VFD controller **405**, fracking control center **380**, and/or power distribution trailer controller **430** may monitor may include but is not limited to the fracking control center, auxiliary systems, the power generation system, the power distribution trailer controller, switchgears, the auxiliary system transformer, the additional system transformer, the additional systems, the black start generator, the single VFDs, VFD controllers, trailer auxiliary systems, the fracking equipment and/or any other component included in the electric driven hydraulic fracking system **400** that will be apparent to those skilled in the relevant art(s) without departing from the spirit and scope of the disclosure.

(100) The enclosure temperature sensor **410** may include one or more sensors positioned inside the enclosure of the single pump trailer. The enclosure temperature sensor **410** may monitor the operation parameter of the temperature inside the enclosure to ensure that temperature is within the operation temperature threshold to enable the components also positioned in the enclosure to operate correctly. The enclosure temperature sensor **410** may measure the temperature to ensure that the temperature of different components positioned in the enclosure does not exceed the operation threshold. For example, enclosure temperature sensor **410** may monitor the temperature of a bearing and the may increase in temperature beyond the temperature threshold. The VFD controller **405** may determine that such an increase in the temperature of the bearing may cause damage to the single shaft electric motor and thus the VFD controller **405** may execute the corrective action to deactivate the bearing.

(101) In another example, the enclosure temperature sensor **410** may measure the temperature of the enclosure such that the VFD controller **405** may ensure that the enclosure temperature does not decrease below the operation threshold of 32 degrees F. The single VFD may not be activated when the temperature of the enclosure is below 32 degrees F. The VFD controller **405** may then execute the corrective action of activating the trailer auxiliary heaters as well as the trailer auxiliary fans circulate the heated air to increase the temperature of the enclosure back into the operation threshold of above 32 degrees F. In another example, the humidity sensor **420** may measure the operation parameter of the moisture present in the enclosure. The activation of the electric power **360** at the power generation voltage level to the single VFD may negative impact the operation of the single VFD when the moisture present in the enclosure exceeds the operation threshold. The VFD controller **405** may execute the corrective action to activate the trailer auxiliary fans to dry the moisture present in the enclosure to decrease the moisture below the operation threshold.

(102) In another example, the VFD temperature sensor **430** may monitor the temperature of the single VFD such that the VFD controller **405** may ensure that the temperature of the single VFD remains below the operation threshold. As the temperature of the single VFD increases above the operation threshold, the VFD controller **405** may execute the corrective action to deactivate the single VFD to prevent damage to the single VFD. In another example, the VFD controller **405** may execute the corrective action to phase back the operation of the single VFD to a phase back threshold such that the phasing back the operation of the single VFD decreases the temperature of the single VFD to below the operation threshold. In such an example, the VFD controller **405** may phase back the operation of the single VFD to 75% to allow the single VFD to cool to below the operation threshold for the VFD temperature.

(103) The VFD controller **405** may also execute the corrective action with regard to dynamically adjusting the speed of the trailer auxiliary fans such that the trailer auxiliary fans may be

dynamically adjusted by the VFD controller **405** based on the temperature of the enclosure as well as the percentage of load that the electric driven hydraulic fracking system **400** is operating. In doing so, the VFD controller **405** may dynamically account for the current temperature of the enclosure as well as the percentage of load that the electric driven hydraulic fracking system **400** is operating to avoid unnecessarily running the trailer auxiliary fans at increased speeds when such cooling is not necessary and thereby running the trailer auxiliary fans at increased speeds results in an unnecessary consumption of energy. However, the VFD controller **405** may also dynamically increase the speed of the trailer auxiliary fans when the temperature of the enclosure and the percentage of load the electric driven hydraulic fracking system **400** is operating results in an increase in the temperature of the components of the single pump trailer thereby requiring a dynamic increase in the speed of the trailer auxiliary fans to cool the components to prevent damage to the components.

(104) The percentage of load of operation of the electric driven hydraulic fracking system **400** may drastically increase and/or decrease throughout operation. Often times, the electric driven hydraulic fracking system **400** may not operate continuously at the full percentage of operation for two weeks. Rather, the percentage of load operation may increase to 100% for an operation of two hours and then decrease to an operation of 15% for two hours. Rather than have the VFD temperature cycle drastically with the drastic cycling of the percentage of load of operation of the electric driven hydraulic fracking system **400** which negatively impacts the single VFD, the VFD controller **405** may dynamically monitor the temperature of the enclosure as well as the percentage of load operation to dynamically adjust the trailer auxiliary fans to maintain the VFD temperature within the VFD threshold. For example, the VFD controller **405** may determine that the outside temperature of 32 degrees F. and the decrease in the percentage of load operation of the electric driven hydraulic fracking system **400** requires that the enclosure heaters be activated and the speed of the trailer auxiliary fans be increased to maintain the temperature of the VFD at the operation threshold of 85 degrees to prevent the VFD temperature from decreasing due the temperature outside and the significant decrease in the load of operation of the electric driven hydraulic fracking system **400**.

(105) The VFD controller **405** may execute the corrective action of activating the trailer auxiliary heater when the enclosure temperature sensor **410** measures the decrease in the enclosure temperature below the operation threshold. In doing so, components positioned in the enclosure may increase in temperature to the operation threshold and the moisture of the enclosure may be decreased to the operation threshold.

(106) The VFD controller **405** may also monitor the numerous different auxiliary systems that are included in the electric driven hydraulic fracking system **400**. The VFD controller **405** may monitor numerous different operation parameters associated with the numerous different auxiliary systems. The VFD controller **405** may then execute numerous different corrective actions when any of the numerous different operation parameters deviate from the corresponding operation thresholds to maintain the operation of the numerous different auxiliary systems within the corresponding operation thresholds. For example, the VFD controller **405** may execute the corrective action of heating the different auxiliary systems when the operation parameter of temperature of the different auxiliary systems decreases below the operation threshold. The VFD controller **405** may execute the corrective action of cooling the different auxiliary systems when the operation parameter of temperature of the different auxiliary systems increases above the operation threshold. The VFD controller **405** may monitor the operation parameters of pressure and/or flow control of the different auxiliary systems. The VFD controller **405** may dynamically adjust the speed of the different auxiliary systems based on the operation parameters.

(107) FIG. 5 illustrates a block diagram of an electric driven hydraulic fracking system **500** that further describes the interaction between the power distribution trailer **320** and the VFD controllers **505(a-n)**, n is an integer that equals the quantity of single VFDs **340(a-n)**. The power distribution

trailer **320** includes the switchgear configuration **310**, a plurality of feeders, where n is an integer that equals the quantity of VFD connections **550(a-n)**, the power distribution trailer controller **430**, and the auxiliary system transformer **510**. Each single hydraulic trailer **330(a-n)** includes a single VFD **340(a-n)** and a VFD controller **505(a-n)** positioned on the single hydraulic trailer **330(a-n)** and each single VFD **340(a-n)** includes a VFD connection **550(a-n)**, where n is an integer that equals the quantity of feeders **530(a-n)**. The electric driven hydraulic fracking system **500** shares many similar features with the hydraulic fracking operation **100**, the single pump configuration **200**, the electric driven hydraulic fracking system **300**, and the electric driven hydraulic fracking system **400**; therefore, on the differences between the electric driven hydraulic fracking system **500** and the hydraulic fracking operation **100**, the single pump configuration **200**, the electric driven hydraulic fracking system **300**, and the electric driven hydraulic fracking system **400** are to be discussed in further detail.

(108) The VFD controller **505(a-n)** may monitor the operation parameters associated with the operation of the components associated with single pump trailer **330(a-n)** based on polling a corresponding switchgear **325(a-n)** included in the switchgear configuration **305** positioned on the power distribution trailer **320** that is electrically connected to the VFD connection **550(a-n)** of the single VFD **340(a-n)** positioned on the single pump trailer **330(a-n)**. The VFD controller **505(a-n)** may initiate at least one corrective action when each operation parameter associated with the operation of components associated with the single pump trailer **330(a-n)** deviates beyond the at least one corresponding operation threshold. The VFD controller **505(a-n)** initiates the at least one corrective action when each operation parameter deviates beyond the at least one corresponding operation threshold maintains the operation of the electric driven hydraulic fracking system **500**.

(109) The VFD controller **505(a-n)** may continuously poll the corresponding switchgear **325(a-n)** included in the switchgear configuration **305** via the communication link **365**. In doing so, the VFD controller **505(a-n)** may monitor numerous operation parameters associated with the corresponding switchgear **325(a-n)**. For example, the VFD controller **505(a-n)** may know the amount of electric power that is currently propagating out to the single shaft electric motor associated with VFD controller **505(a-n)** and the single hydraulic trailer **330(a-n)**. The VFD controller **505(a-n)** may know the amount of current that is currently propagating to the single shaft electric motor. The VFD controller **505(a-n)** may know the voltage level of the electric power that is currently propagating to the single shaft electric motor. The VFD controller **505(a-n)** may know the power factor of the electric power currently propagating to the single shaft electric motor. The VFD controller **505(a-n)** may then execute a corrective action when any of the operation parameters deviate from the operation threshold.

(110) Returning to FIG. 4, the VFD controller **405** may instruct the single VFD **340(a-n)** to increase pressure to a pump pressure threshold based on the operating parameter of pressure measured by the pressure sensor **460** and maintain the pressure applied to the single hydraulic pump at the pump pressure threshold before the electric driven hydraulic fracking system **400** executes a fracking operation to determine whether leaks are present in the pump. The pressure applied to the single hydraulic pump at the pump pressure threshold identifies whether leaks are present in the pump. The VFD controller **405** may instruct the single VFD **340(a-n)** to apply the operating parameter of torque to the single hydraulic pump at a torque threshold based on the operating parameter of torque measured by the torque sensor **470**. The torque applied at the torque threshold to the single hydraulic pump prevents the pressure applied to the single hydraulic pump from reaching a pressure damage threshold when reached damages the single hydraulic pump. The VFD controller **405** may monitor the pressure applied to the single hydraulic pump to determine if the pressure gradually increases towards the pressure damage threshold. The VFD controller **405** may execute the corrective action of deactivating the single hydraulic pump when the pressure gradually increases towards the pressure damage threshold that is indicative of leaks present in the pump.

(111) The operating entity of the electric driven hydraulic fracking system **400** may request to test whether leaks are present in the single hydraulic pump. Pressure may be applied to the single hydraulic pump and then the water may bleed down into the well should leaks exist in the single hydraulic pump. In order to test the single hydraulic pump as to whether the single hydraulic pump includes leaks before single hydraulic pump engages in the operation of the electric driven hydraulic fracking system **400**, the VFD controller **405** may increase the pressure on the single hydraulic pump to the pump pressure threshold. The VFD controller **405** may then instruct the single hydraulic pump to execute a positive displacement. The VFD controller **405** may then monitor the pressure to determine if the pressure spikes. Based on the positive displacement of the single hydraulic pump, water may be incompressible if the single hydraulic pump does not include any leaks as the water may have no outlet from the single hydraulic pump if the single hydraulic pump does not include any leaks resulting in a significant increase in pressure. However, if the single hydraulic pump does include leaks, then the water may be released into the well and the pressure of the single hydraulic pump may not significantly increase.

(112) However, the significant increase in pressure to the pressure damage threshold may significantly damage the single hydraulic pump when such an increase in pressure is the result of testing the single hydraulic pump for leaks and the single hydraulic pump passes with the increase in pressure. In order to prevent damage to the single hydraulic pump due to the increase in pressure, the VFD controller **405** may apply torque to the single hydraulic pump at the torque threshold. In applying by the VFD controller **405** the torque to the single hydraulic pump at the torque threshold may prevent the pressure of the single hydraulic pump from spiking quickly to the pressure damage threshold that when exceeded may significantly damage the single hydraulic pump. Rather the VFD controller **405** may monitor the pressure to determine the current status of the pressure relative to the pressure damage threshold and then may execute the corrective action of adjusting the torque applied to the single hydraulic pump to control the increase in the pressure as a linear reaction towards the pressure damage threshold rather than a spike beyond the pressure damage threshold. In doing so, the single hydraulic pump may be tested for leaks without damaging the single hydraulic pump.

(113) Often times, the electric driven hydraulic fracking system **400** may initiate the fracking operation without having all of the single hydraulic pumps operation at the start. However, during the operation of the electric driven hydraulic fracking system **400**, the remaining single hydraulic pumps that were initially inactive may require to be activated such that the electric driven hydraulic fracking system **400** may continue the fracking operation with each of the single hydraulic pumps operating at full capacity. Often times each of the single hydraulic pumps may be connected to a single pipe and the single hydraulic pumps in operation may be working at similar pressure and flow rates. However, to then activate a single hydraulic pump and increase the single hydraulic pump to full capacity may negatively impact the operation of the already active single hydraulic pumps.

(114) Rather the inactive single hydraulic pump is to be initially generated at a constant torque and at a decreased speed and then ramped up to then be synchronized with the already active single hydraulic pumps. In doing so, the VFD controller **405** may apply constant torque to the newly activated single hydraulic pump and then may initially start the single hydraulic pump at a decreased speed. The VFD controller **405** may monitor the operation parameter of the pump speed of the single hydraulic pump based on the pump speed measured by the pump speed sensor **480**. The VFD controller **405** may then continue to monitor the pump speed measured by the pump speed sensor **480** and gradually ramp up the pump speed of the single hydraulic pump until each of the single hydraulic pumps are operating in-line and synchronized.

(115) The VFD controller **405** may generate a grounding current that measures a plurality of electrical characteristics associated with a grounding system for a plurality of electrical connections that are included with the components that are associated with the single pump trailer **330(a-n)**. The

VFD controller **405** may determine whether at least one electrical characteristic deviates from when the electrical characteristics were initially measured by the ground current. The VFD controller **405** may generate an alert when at least one electrical characteristic deviates from when the electrical characteristics were initially measured by the ground current. The deviation from the at least one electrical characteristic is indicative that the ground system for the electrical connections that are included with the components that are associated with the single pump trailer is changed.

(116) Each of the numerous components that are electrically connected to the VFD controller **405**, such as the single VFD **340(a-n)**, the trailer auxiliary systems **315(a-n)**, the single shaft electric motor, the single hydraulic pump and so on may also be electrically grounded. Each of the numerous components may include electrical connections in which each electrical connection is electrically connected to ground. The single VFD **340(a-n)** may generate a grounding current such that the grounding current propagates throughout the electrical ground configuration and in doing so propagates through each of the electrical connections for each of the corresponding components that are electrically grounded to the electrical ground configuration. The single VFD **340(a-n)** may identify the electrical characteristics associated with the grounding current before the single VFD **340(a-n)** initially propagates the grounding current into the electrical ground configuration.

(117) The single VFD **340(a-n)** may then monitor the operation parameter of the electrical characteristics associated with the grounding current via the ground current sensor **435**. As the VFD controller **340(a-n)** continues to monitor the electrical characteristics associated with the grounding current via the ground current sensor **435**, the VFD controller **340(a-n)** may determine that the electrical ground configuration continues to maintain each of the numerous components grounded to the electrical ground configuration when the electrical characteristics associated with the grounding current as measured by the ground current sensor **435** are continue to be maintained as when the VFD controller **340(a-n)** initially propagated the grounding current into the electrical ground configuration. The VFD controller **340(a-n)** may determine that there is an issue with the electrical ground configuration when the electrical characteristics initially associated with the grounding current before the VFD controller **340(a-n)** initially propagates the grounding current into the electrical ground configuration then deviates which is indicative that the electrical ground configuration has changed.

(118) Returning to FIG. 5, the communication link **365** as included in the cables **540(a-n)** may provide communication from the VFD connection **550(a-n)** to the corresponding feeder **530(a-n)** and then to the power distribution trailer controller **430**. The communication link **365** may enable the power distribution trailer controller **430** to determine whether the appropriate electric power **360** at the power generation voltage level of 13.8 kV and the appropriate electric power **355** at the auxiliary voltage level of 480V is connected from the appropriate feeder **530(a-n)** to the appropriate VFD connection **550(a-n)**. Often times, installers of the electrical electric driven hydraulic fracking system **500** may incorrectly connect cables **540(a-n)** such that the incorrect VFD connection **550(a-n)** is connected to the incorrect feeder **530(a-n)**. In doing so, the incorrect electric power **360** at the power generation voltage level and/or the incorrect electric power **355** at the auxiliary voltage level may be connected to the incorrect single VFD **340(a-n)**.

(119) For example, the installer in the confusion of installing the electric driven hydraulic fracking system **500** may incorrectly connect cable **540a** from feeder **530a** to VFD connection **550n**. In doing so, the installer connected the incorrect electric power **360** at the power generation voltage level of 13.8 kV and/or the incorrect electric power **355** at the auxiliary voltage level of 480V to the incorrect single VFD **340n** via VFD connection **550n**. Rather than relying on manual policy and procedure for the installers to verify whether each cable **540(a-n)** correctly connects each VFD connection **550(a-n)** to each corresponding feeder **530(a-n)**, the power distribution trailer controller **430** may poll each feeder **530(a-n)** and to thereby determine whether each feeder **530(a-n)** is connected to the appropriate VFD connection **550(a-n)** via the appropriate cable **540(a-n)** via the

communication link **365** included in each cable **540(a-n)**. In doing so, the power distribution trailer controller **430** may verify whether each feeder **530(a-n)** is connected to the appropriate VFD connection **550(a-n)** based on the polling via the communication link **365** included in each cable **540(a-n)**. The power distribution trailer controller **430** may then confirm that each feeder **530(a-n)** is connected to each appropriate VFD connection **550(a-n)** when each communication link **365** confirms based on the polling of the power distribution trailer controller **430**. The power distribution trailer controller may then generate an alert and identify each feeder **530(a-n)** that is connected to the incorrect VFD connection **550(a-n)** when the communication link **365** identifies the incorrect connection based on the polling of the power distribution trailer controller **430**.

(120) In an embodiment, the VFD controller **505(a-n)** may transmit a plug-in signal that originates at a VFD connection **550(a-n)** that the VFD controller **505(a-n)** is positioned on the single pump trailer with the single VFD **340(a-n)** and propagates to a plurality of feeders **530(a-n)** associated with a power distribution trailer **320** that is distributing the electric power to the single VFD **540(a-n)**. The VFD controller **505(a-n)** may identify whether a return plug-in signal is received after the plug-in signal is transmitted. The VFD controller **505(a-n)** may determine that a cable **540(a-n)** is connected to the VFD connection **550(a-n)** associated with the corresponding single VFD **340(a-n)** and a feeder **530(a-n)** associated with the power distribution trailer **320** when the VFD controller **505(a-n)** receives the return plug-in signal and that the cable **540(a-n)** is not connected to the VFD connection **550(a-n)** and the feeder **530(a-n)** when the VFD controller **505(a-n)** fails to receive the return plug-in signal.

(121) In another embodiment, the VFD controller **505(a-n)** may identify a pulse train that is included in the plug-in signal that is received by the VFD controller **505(a-n)** when the cable **540(a-n)** is connected to the feeder **530(a-n)**. The VFD controller **505(a-n)** may determine the feeder **530(a-n)** that the cable **540(a-n)** is connected to via the VFD connection **550(a-n)** based on the pulse train that is included in the plug-in signal that is received by the VFD controller **505(a-n)** and differs from other pulse trains that are associated with other feeders **530(a-n)**. The VFD controller **505(a-n)** may verify the pulse train included in the plug-in signal that is associated with the feeder **530(a-n)** that the cable **540(a-n)** is correctly connected to via the VFD connection **550(a-n)**. The VFD controller **505(a-n)** may generate an alert when the pulse train included in the plug-in signal is associated with the feeder **530(a-n)** that the cable **540(a-n)** is incorrectly connected to via the VFD connection **550(a-n)**.

(122) Each of the VFD connections **550(a-n)** may include an electrical connection for the electric power **360** at the power generation voltage level, an electrical connection for the electric power **355** at the auxiliary power voltage level, and an electrical connection for the communication link **365**. Each of the feeders **530(a-n)** may also include a corresponding electrical connection for the electric power **360** at the power generation voltage level, an electrical connection for the electric power **355** at the auxiliary power voltage level, and an electrical connection for the communication link **365**. Each of the electrical connections at the feeder **530a** may generate a first pulse train, each of the electrical connections at the feeder **530b** may generate a second pulse train, and each of the electrical connections at the feeder **530n** may generate a third pulse train.

(123) The VFD controller **505a** understands that the cable for the electrical power **360** at the power generation voltage level, the cable for the electrical power **355** at the auxiliary voltage level, and the cable for the communication link **365** with regard to the VFD connection **550a** are to be electrically connected to the feeder **530a**. The VFD controller **505a** may then poll the feeder **530a** for the cable for the electrical power **360** at the power generation voltage level, the cable for the electrical power **355** at the auxiliary voltage level **355**, and the communication link **365** as electrically connected to the VFD connection **550a** are each also electrically connected to the feeder **530(a-n)**. In polling the feeder **530a**, the VFD controller **505a** determines whether the first pulse train associated with the feeder **530a** is received at the VFD connection **550a** for the cable for the electrical power **360** at the power generation voltage level, the cable for the electrical power

355 at the auxiliary voltage level, and the cable for the communication link **365**. If the VFD controller **505a** identifies the first pulse train for each of the cable for the electrical power at the power generation voltage level, the cable for the electrical power **355** at the auxiliary voltage level, and the cable for the communication link, the VFD controller **505** may verify that each are correctly electrically connected to the VFD connection **550a** and the feeder **530a**.

(124) However, if the VFD controller **505a** receives a different pulse train than the first pulse train for the electric power **360** at the power generation voltage level, the electric power **355** at the auxiliary voltage level, and/or the communication link, then the VFD controller **505a** may determine that whichever cable receives a different pulse train, then that particular cable is not electrically connected to the feeder **530a**. For example, the VFD controller **505a** may poll the cable for the electric power **360** at the power generation voltage level, the electric power **355** at the auxiliary voltage level, and the communication link **365** for the first pulse train from the feeder **530a**. The VFD controller **505a** may then receive the first pulse train for the electric power **360** at the power generation voltage level and the first pulse train for the electric power **355** at the auxiliary voltage level but the second pulse train for the communication cable **365**. The VFD controller **505a** may then generate an alert identifying that the communication link **365** for the VFD connection **550a** is incorrectly electrically connected to the feeder **530b** based on the second pulse train received by the VFD controller **505a** for the communication link **365**.

(125) The VFD controller **505(a-n)** may monitor a communication pin included in the VFD connection **550(a-n)** to determine if a communication cable **365** included in the cable **540(a-n)** is electrically connected to the communication pin included in the VFD connection **550(a-n)** and a plurality of electric power pins included in the VFD connection **550(a-n)** to determine if the power cable for the electric power **360** at the power generation voltage level and the electric power **355** at the auxiliary voltage level is electrically connected to the power pins in the VFD connection **550(a-n)**. The VFD controller **505(a-n)** may instruct a breaker associated with single VFD **340(a-n)** to transfer from a closed position to an open position when the VFD controller **505(a-n)** determines that the communication pin included in the VFD connection **550(a-n)** is not electrically to the communication cable **365** and the power pins are electrically connected to the power cables for the electric power **360** at the power generation voltage level and the electric power **355** at the auxiliary voltage level. A disconnection of the communication cable **365** from the communication pin is indicative that the power cables for the electric power **360** at the power generation voltage level and the electric power **355** at the auxiliary voltage level are being disconnected from the VFD connection **550(a-n)** with the communication cable **365**.

(126) The VFD connection **550(a-n)** may have a safety feature in that if a user begins to electrically disconnect the cable **540(a-n)** from the VFD connection **550(a-n)**, the communication cable **365** may lose contact with the communication pin included in the VFD connection **550(a-n)** before the power cables for the electric power **360** at the power generation voltage level and the electric power **355** at the auxiliary voltage level disconnect from the power pins included in the VFD connection **550(a-n)**. The VFD controller **505(a-n)** may then have a threshold of time in identifying that the communication cable **365** has lost contact with the communication pin before the power cables lose contact with the power pins. The VFD controller **505(a-n)** may then instruct a breaker to transfer from a closed position to an open position to deactivate the single VFD **340(a-n)** before the power cables lose contact with the power pins.

(127) Returning to FIG. 4, the VFD controller **405** may monitor an overall power consumption of the electrical driven hydraulic fracking system **400** as the electrical driven hydraulic fracking system **400** operates to determine if the overall power consumption of the electrical hydraulic fracking system **400** exceeds an overall power threshold. The overall power consumption of the electrical hydraulic fracking system **400** when exceeding the overall power consumption threshold is indicative that the electric power provided to the electrical driven hydraulic fracking system **400** is insufficient to maintain the electrical driven hydraulic fracking system **400** operating at a current

state.

(128) In an embodiment, the VFD controller **405** may phase back an operation of the single VFD **340(a-n)** in driving the single shaft electric motor and the single hydraulic pump to decrease power consumption of the single VFD **340(a-n)**, the single shaft electric motor, and the single hydraulic pump to a phase back threshold. The decreasing of the power consumption of the single VFD, the single shaft electric motor, and the single hydraulic pump to the phase back threshold decreases the overall power consumption of the electrical driven hydraulic fracking system **400** below the overall consumption power threshold. In an embodiment, VFD controller **405** may shutdown the operation of the single VFD **340(a-n)** in driving the single shaft electric motor and the single shaft hydraulic pump to decrease the power consumption of the single VFD, the single shaft electric motor, and the single hydraulic pump to the phase back threshold to maintain the overall power consumption of the electrical driven hydraulic fracking system **400** below the overall power consumption threshold.

(129) The VFD controller **405** may monitor the operation parameter of the overall power consumption of the single electric driven hydraulic fracking system **400** as the single electric driven hydraulic fracking system **400** conducts the fracking operation based on the overall power consumed as measured by the power consumption sensor **445**. If the overall power consumption consumed by the single electric driven hydraulic fracking system **400** exceeds the overall power consumption threshold, then single electric driven hydraulic fracking system **400** may brown out and in doing so may be deactivated from conducting the fracking operation. The amount of time that the single electric driven hydraulic fracking system **400** is in a brown out as well as the time required for the single electric driven hydraulic fracking system **400** to then reboot and ramp back up to conducting the fracking operation may be a significant amount of time resulting in a significant loss in money due to the down time of the electric driven hydraulic fracking system **400** due to the overall power consumed by the electric driven hydraulic fracking system **400** exceeding the overall power consumption threshold.

(130) Rather than brown out, the VFD controller **405** may conduct the corrective action to automatically phase back the operation of the electric driven hydraulic fracking system **400** from full capacity to a partial capacity that then decreases the overall power consumption of the electric driven hydraulic fracking system to below the overall power consumption threshold. For example, the VFD controller **405** may automatically phase back the operation of the electric driven hydraulic fracking system **400** by 25% to decrease the overall power consumption to below the overall power consumption threshold to avoid a brown out. The VFD controller **405** may also conduct the corrective action of identifying components of the electric driven hydraulic fracking system **400** to deactivate while maintaining the remaining components to operate at full capacity to reduce the overall power consumption to below the overall power consumption threshold.

(131) The VFD controller **405** may phase incrementally to determine the appropriate phase back to decrease the overall power consumption below the overall power consumption threshold. For example, the VFD controller **405** may first phase back the operation of the electric driven hydraulic system **400** to 97% of full capacity. The VFD controller **405** may then determine whether the overall power consumption has decreased below the overall power consumption threshold with the phase back to 97% of full capacity. The VFD controller **405** may then phase back the operation of the electric driven hydraulic system **400** to 96% of full capacity and so on until the phase back of the electric driven hydraulic system **400** decreases the overall power consumption to below the overall power consumption threshold

(132) In an embodiment, the VFD controller **405** may evaluate a priority table of components should the VFD controller **405** determine that the overall power consumption is increasing above the overall power consumption threshold. The priority table may list each of the components in priority as to the components that the VFD controller **405** is to first deactivate to reduce the overall power consumption to below the overall power consumption threshold. For example, the VFD controller **405** may first deactivate the component listed as the first component to deactivate when

the overall power consumption exceeds the overall power consumption threshold. The VFD controller **405** may then determine the overall power threshold as measured power consumption sensor **445** to determine whether the overall power consumption has decreased below the overall power consumption threshold after deactivating the component listed as the first component to be deactivated when the overall power consumption exceeds the overall power consumption threshold. The VFD controller **405** may then deactivate the second component listed in the priority table should the overall power consumption continue to exceed the overall power consumption threshold after deactivating the first component. The VFD controller **405** may then continue to do so until the overall power consumption has decreased below the overall power consumption threshold.

(133) In an embodiment, the VFD controller **405** may evaluate whether there are redundant components operating in that the redundancy in components is not necessary for the electric driven hydraulic fracking system **400** to continue to operate if one of the redundant components is deactivated. In doing so, the VFD controller **405** may recognize that the redundancy in components and may then automatically deactivate one of the redundant components when the overall power consumption increases beyond the overall consumption threshold due the redundant component unnecessarily consuming overall power and is not necessary to the electric driven hydraulic fracking system **400** to continue to operate. For example, the VFD controller **405** may identify that two blenders are operating but only a single blender is required to continue the operation of the electric driven hydraulic fracking system **400**. The VFD controller **405** may then automatically deactivate one of the redundant blenders to decrease the overall power consumption to below the overall power consumption threshold.

(134) In an embodiment, the VFD controller **405** may evaluate the capacity of operation for each of the components. The VFD controller **405** may then automatically deactivate the components that are operating at lesser capacity of the similar components to decrease the overall power consumption to below the overall power consumption threshold. For example, the VFD controller **405** may identify that seven single hydraulic pumps are operation and the overall power consumption is increasing above the overall power threshold. The VFD controller **405** may then identify that two of the single hydraulic pumps are running at 40% of capacity and the remaining five single hydraulic pumps are running at 80%. The VFD controller **405** may then automatically deactivate the two single hydraulic pumps that are operating at 40% to decrease the overall power consumption below the overall power consumption threshold.

(135) As noted above, medium voltage cables may propagate the AC voltage signal **360** at the voltage level of 13.8 kV from the power distribution trailer **320** to each of the VFDs **340(a-n)**. Low voltage cables may propagate the auxiliary voltage signal **355** at the auxiliary voltage level of 480V from the power distribution trailer **320** to each of the VFDs **340(a-n)**. Communication cables may propagate communication signals **365** from the power distribution trailer **320** to each of the VFDs **340(a-n)**. FIG. 5 illustrates a top-elevational view of connector configuration for each of the VFDs **340(a-n)** that may couple to a medium voltage cable, a low voltage cable, and a communication cable.

(136) The connector configuration **500** includes medium voltage connectors **510(a-b)** with each including a medium voltage plug and receptacle to eliminate the need of skilled personnel to connect the medium voltage cables to the VFDs **340(a-n)**. Rather than using a termination kit with non-shielded cable, the medium voltage connections **510(a-b)** enable medium voltage cables to be easily connected to the VFDs **340(a-n)** to propagate the AC voltage signal **360** at the voltage level of 13.8 kV without any risk of shorts and/or nicks in the non-shielded cable. The medium voltage connections **510(a-b)** include lockable handles that securely connect the medium voltage cables to the medium voltage connections **510(a-b)** and provide lock out tag out. The low voltage connections **520(a-b)** provide connections to the low voltage cables that propagate the auxiliary voltage signal **355** at the auxiliary voltage level of 480V to the VFDs **340(a-n)**. The communication connection **530** provides a connection to the communication cable to propagate communication

signals 365 to the VFDs 340(a-n).

CONCLUSION

(137) It is to be appreciated that the Detailed Description section, and not the Abstract section, is intended to be used to interpret the claims. The Abstract section may set forth one or more, but not all exemplary embodiments, of the present disclosure, and thus, is not intended to limit the present disclosure and the appended claims in any way.

(138) The present disclosure has been described above with the aid of functional building blocks illustrating the implementation of specified functions and relationships thereof. The boundaries of these functional building blocks have been arbitrarily defined herein for the convenience of the description. Alternate boundaries may be defined so long as the specified functions and relationships thereof are appropriately performed.

(139) It will be apparent to those skilled in the relevant art(s) the various changes in form and detail can be made without departing from the spirit and scope of the present disclosure. Thus the present disclosure should not be limited by any of the above-described exemplary embodiments, but should be defined only in accordance with the following claims and their equivalents.

Claims

1. An electric driven hydraulic fracking system for pumping a fracking media into a well, comprising: a variable frequency drive (VFD) configured to drive an electric motor to control the electric motor to drive a hydraulic pump; and a controller associated with the VFD and configured to: monitor a pump speed parameter associated with an operation of the electric driven hydraulic fracking system as the electric driven hydraulic fracking system operates to determine whether the pump speed parameter deviates beyond a pump speed parameter threshold, and initiate a corrective action, in response to the pump speed parameter deviating beyond the pump speed parameter threshold, to maintain the operation of the electric driven hydraulic fracking system.
2. The system of claim 1, wherein the pump speed parameter is detected using a pump speed sensor configured to detect pump speed of the hydraulic pump.
3. The system of claim 2, wherein a pump pressure output by the hydraulic pump is based on the pump speed, and wherein the system further comprises a pressure sensor configured to detect the pump pressure.
4. The system of claim 3, wherein the controller is further configured to determine a pump pressure parameter based on the pump pressure detected by the pressure sensor.
5. The system of claim 4, wherein the controller is further configured to monitor the pump pressure parameter which is generated from a leak pressure that is applied by the hydraulic pump as the leak pressure is increased to a pump pressure threshold, and determine whether a leak is present based on the pump pressure parameter.
6. The system of claim 5, wherein the controller is further configured to monitor the pump pressure parameter generated from the leak pressure that is applied by the hydraulic pump as the leak pressure is increased to the pump pressure threshold as the hydraulic pump executes positive displacement, and automatically apply torque to the hydraulic pump to a torque threshold as the hydraulic pump executes the positive displacement.
7. A method for pumping a fracking media into a well, comprising: driving, by a variable frequency drive (VFD), an electric motor associated with the VFD to control the electric motor to drive a hydraulic pump in an operation of hydraulic fracturing; monitoring, by a controller, a pump speed parameter associated with the operation of hydraulic fracturing to determine whether the pump speed parameter deviates beyond a pump speed parameter threshold; and initiating, by the controller, a corrective action, in response to the pump speed parameter deviating beyond the pump speed parameter threshold, to maintain the operation of hydraulic fracturing.
8. An electric driven hydraulic fracking system for pumping a fracking media into a well,

comprising: a variable frequency drive (VFD) for driving an electric motor at a VFD voltage level to control operation of the electric motor to drive a hydraulic pump; and a controller associated with the VFD and configured to determine whether a cable connecting a feeder of a power distribution system to a connection associated with the VFD is correctly plugged in based on a pulse train sent from the feeder, and generate an alert, in response to determining that the VFD is not correctly plugged in.

9. The system of claim 8, wherein the pulse train is sent from the feeder to the controller via the cable.

10. The system of claim 8, wherein the controller is further configured to verify that another cable connecting another feeder to the connection is correctly plugged in, in response to determining that another pulse train sent from the other feeder is associated with the other feeder.

11. The system of claim 8, wherein the controller is further configured to determine that the cable is not correctly plugged in, in response to determining that the pulse train is from the feeder which is intended to be connected to another VFD by the cable.

12. The system of claim 8, wherein the controller is further configured to determine whether another cable connecting the feeder to the connector is correctly plugged in based on another pulse train sent from the feeder.

13. The system of claim 12, wherein the other pulse train is sent from the feeder to the controller via the other cable.

14. The system of claim 13, wherein the pulse train corresponds to the other pulse train.

15. The system of claim 12, wherein the cable is a cable for transmitting electrical power at a power generation voltage level.

16. The system of claim 15, wherein the other cable is a cable for transmitting electrical power at an auxiliary voltage level.

17. The system of claim 8, wherein the cable is a cable for transmitting an electrical signal for a communication link.

18. A method for pumping a fracking media into a well, comprising: providing a variable frequency drive (VFD) for driving an electric motor at a VFD voltage level to control operation of the electric motor to drive a hydraulic pump; and determining, by a controller, whether a cable connecting a feeder of a power distribution system to a connection associated with the VFD is correctly plugged in based on a pulse train sent from the feeder; and generating, by the controller, an alert, in response to determining that the VFD is not correctly plugged in.
